

# ADAICK Utility Error Messages

## Overview of Messages

ERROR-121	ERROR-122	ERROR-123	ERROR-124	ERROR-125	ERROR-126
ERROR-127	ERROR-128	ERROR-129	ERROR-130	ERROR-131	ERROR-132
ERROR-133	ERROR-134	ERROR-135	ERROR-136	ERROR-137	ERROR-138
ERROR-139	ERROR-140	ERROR-141	ERROR-142	ERROR-143	ERROR-144
ERROR-145	ERROR-146	ERROR-147	ERROR-148	ERROR-149	ERROR-150
ERROR-151	ERROR-152	ERROR-153	ERROR-154	ERROR-155	ERROR-156
ERROR-157	ERROR-158	ERROR-159	ERROR-160	ERROR-161	ERROR-162
WARNING-163	ERROR-164	ERROR-165	ERROR-166	ERROR-167	ERROR-168
	ERROR-169	ERROR-170	ERROR-172	ERROR-173	ERROR-174
	ERROR-177				

---

### **ERROR-121** *block-number* block contains invalid packed value

**Explanation** The format indicator in the U3 element is "U" or "P", and the value in the "block-number" block is not a valid packed decimal number.

### **ERROR-122** *value1 value2* values do not agree

**Explanation** Each U3 element contains a value and an MI RABN. The first MI element (in the MI block pointed to by the U3 element) should contain the same value as the U3 element. If not, this message occurs.

This message also occurs if an MI element contains a value that does not agree with the value in the first NI element (in the NI block pointed to by the MI element).

### **ERROR-123** *block-number* block contains incorrect block/value length

**Explanation** The two-byte inclusive length at the beginning of each index block defines the logical end of that block. Each block contains variable length elements. The length of each element depends on the length of the value within the element (for NI blocks, it also depends on the ISN count).

In processing an index block (left to right), the end of each element is compared to the logical end of the block (as defined by the logical block length). If the end of the element is less than the logical end of the block, what follows is taken as the next element, and processing continues. If the block and element ends are equal, the block is considered to be correct. If the element end is greater than the block end, this message occurs.

**ERROR-124 MI ISN should be zero**

**Explanation** Each MI element points to an NI block. If the first ISN in the ISN list for the first NI element in that NI block is the lowest ISN for that value, then the "MI ISN" (in the MI element) should be zero. If the MI element is not zero, this message occurs.

**ERROR-125 MI/NI ISNS do not agree**

**Explanation** Each MI element points to an NI block. If the first ISN in the ISN list for the first NI element (in that NI block) is not the lowest ISN for that value, then that NI element should agree with the "MI ISN". If it does not agree, this message occurs.

**ERROR-126 NI/MI/UI values not increasing**

**Explanation** In processing the index for one descriptor (in an L9 sequence), the NI block values should be in ascending sequence. This message occurs if either of the following occurs:

- The values within one block are not strictly increasing (equal values are considered an error);
- The first value in an NI, MI, or UI block is less than the last value in the previous block (equal values are allowed).

**ERROR-127 NI block contains zero ISN count**

**Explanation** The ISN count in an NI element should not be zero.

**ERROR-128 NI block contains invalid ISN**

**Explanation** The ISN list for one value in an NI block must be in strict ascending sequence. If not, this message occurs. This message also occurs if an ISN is not less than the "first unused ISN" specified in the file control block (FCB).

**ERROR-129** *block-number* block contains incorrect level indicator

**Explanation** The third byte in the "block-number" block should contain the following value:

Block Type	Value
U13	0D
U12	0C
U11	0B
U10	0A
U9	09
U8	08
U7	07
U6	06
U5	05
U4	04
U3	03
M1	02
N1	01

If the third byte does not contain the correct value, this message occurs.

**ERROR-130** RABN outside ASSO extents

**Explanation** An attempt was made to read a block outside the RABN limits specified by the Associator extents for the general control blocks (GCBs).

**ERROR-131** *block-number* RABN outside extents

**Explanation** A "block-number" RABN is outside the RABN limits defined by the file control block (FCB) UI extents, or an NI RABN is outside the limits defined by the NI extents.

**ERROR-132** [AC2] DS RABN *rabn* outside extents

**Explanation** The Data Storage (DS) RABN given in the message (*rabn*) appears in an address converter (DS RABN) or secondary address converter (AC2 DS RABN) block and is outside the limits defined by the file control block (FCB) DS extents.

**ERROR-133** {AC|AC2} MAX ISN should be *value*

**Explanation** This message occurs if the top ISN value in the file control block (FCB) is incorrect.

The FCB contains the top ISN for each address converter (AC) or secondary address converter (AC2) extent. This is the ISN that corresponds to the last RABN in the last block for that extent. This ISN depends on the top ISN of the previous extent, on the number of blocks in the extent, and on the number of ISNs per block.

**ERROR-134** ISN *isn-number* not LT FCB+44 *value* (1ST unused ISN)  
or  
AC2 ISN *isn-number* not LT FCB+38 *value* (1ST unused AC2 ISN)

**Explanation** Address converter or secondary address converter (AC2) elements which correspond to ISNs greater than or equal to the first unused ISN (specified in the FCB) must all contain 00000000 or FFFFFFFE. Otherwise, this message occurs. The ISN (*isn-number*) and its value (*value*) are given in the message.

**ERROR-135** FCB file number incorrect

**Explanation** The requested file number, plus the RABN specified in file 1 FCB's GCB minus one, is assumed to be the FCB RABN for the requested file. The file number specified in that block does not agree with the requested file number.

**ERROR-136** FCB highest index level not 3 through 15

**Explanation** The highest index level specified in the file control block (FCB) must range 3 through 15, inclusively.

**ERROR-137** FCB highest index RABN outside UI extents

**Explanation** The highest index RABN specified in the file control block (FCB) must be within the upper index extents (also specified in the FCB).

**ERROR-138** First RABN greater than last RABN

**Explanation** The extent just printed is invalid because the first RABN is greater than the last RABN.

**ERROR-139** *block-number* extent overlaps FST extent *value1* through *value2*

**Explanation** The extent specified in the file control block (FCB) overlaps a free extent specified in the free space table (FST).

**ERROR-140** ADAIOR return code *rc reason*

**Explanation** The hexadecimal return code and reason code (*rc* and *reason*) was returned from ADAIOR after ADAICK attempted to either open the Associator or read the specified Associator block.

**ERROR-141** FCB {MAXISN|MAX AC2 ISN} expected should be *allocated-maxisn*

**Explanation** The file's MAXISN setting does not correspond to the MAXISN determined by the MAXISN value (*allocated-maxisn*) based on the allocated address converter (MAXISN) or secondary address converter (MAX AC2 ISN) extents.

**ERROR-142** NR *ix-block-number* blocks processed greater than NR blocks used

**Explanation** In performing the index check, a count is taken of the UI blocks read. The "number of blocks used" is the sum of the number of blocks used in each UI extent, which depends on the first RABN and first unused RABN for each extent. If the number of blocks processed exceeds the number used, at least one "ix-block-number" RABN occurs in more than one of that block type, because each "ix-block-number" RABN processed is checked to be sure it is within the used portion of some extent of the same index block type.

**ERROR-143** Field names not in ascending sequence - *field-name*

**Explanation** Each U3 element contains the field name for the descriptor. Field names must be in ascending sequence. "field-name" is the name of the field that is out of sequence.

**ERROR-144** *block-number* field names do not agree

**Explanation** Each upper-level index element contains the field name for the descriptor, and also points to a lower-level block. The field name in the first element in the lower-level block must agree with the field name in the higher-level element.

**ERROR-145** RABN is outside used ranges

**Explanation** The forward pointer in an element of the empty NI/UI block chain contains an invalid RABN. This forward pointer should contain a RABN of another empty NI/UI block, or should contain a zero to indicate the end of the chain.

**ERROR-146** Logical block length should be 0006

**Explanation** Every empty NI/UI block chained in the empty block chain must have a logical block size of X'0006'. This includes the length field itself (two bytes) and the logical forward pointer to the next block in the chain (four bytes).

**ERROR-147 Empty block chain loops back on itself**

**Explanation** The forward pointer in an element of the empty NI/UI block chain contains an invalid RABN. This forward pointer should contain either a RABN of another empty NI/UI block, or a zero to indicate the end of the chain. However, there is an invalid forward pointer value causing the chain to return into itself.

**ERROR-148 Descriptor *desc-name* not found in FDT**

**Explanation** A descriptor was found in a U3 block that is not in the field definition table (FDT). Every field in the index must be a descriptor, a sub-/super-/hyper- or phonetic descriptor, or a coupling descriptor if the file is coupled.

**ERROR-149 Descriptor *desc-name* found in FDT but not in U3**

**Explanation** Every descriptor, sub-/super-/hyper- or phonetic descriptor, or coupling descriptor must have at least one entry in a U3 block. If there are no values for this descriptor, an empty element is stored (value length=0, ISN=0, RABN=0).

**ERROR-150 {ISN|AC2 ISN} not found in DS block specified by {AC|AC2} element**

**Explanation** An ISN discrepancy was found between the address converter (AC) or secondary address converter (AC2) and Data Storage. For better analysis of the problem, run the ADAACK utility.

**ERROR-151 {ISN|AC2 ISN} *isn-number* is invalid**

**Explanation** The physical ISN found in a Data Storage record is either zero or is greater than the permitted maximum for the file, based on the ISNs listed in the address converter (ISN) or secondary address converter (AC2 ISN).

**ERROR-152 FDT end reached before record end**

**Explanation** While decompressing a Data Storage record, ADAICK reached the end of the field definition table (FDT) before finding the end-of-record. This indicates that the compressed record has an incorrect structure.

**ERROR-153 Record length is incorrect**

**Explanation** Either the block length of a Data Storage block is wrong, or the length of a record stored within this block is wrong. The sum of all record lengths, plus 4, should equal the logical block size of the Data Storage block.

**ERROR-154 Invalid PE count**

**Explanation** A periodic group count in a compressed Data Storage record is either 0 or greater than the allowed maximum.

**ERROR-155 Invalid MU count**

**Explanation** A multiple-value field count in a compressed Data Storage record is either 0 or greater than the allowed maximum.

**ERROR-156 Invalid CX byte**

**Explanation** The value for an empty field counter in a compressed Data Storage record that contains X'C0'. Any value from X'C1' through X'FF' is permitted.

**ERROR-157 Invalid value length**

**Explanation** The length of a value in a compressed Data Storage record is wrong. A valid length value is either X'01' through X'7F' or X'8001' through X'80FF'.

**ERROR-158 Invalid packed decimal number**

**Explanation** A packed value within a compressed Data Storage record contains invalid digits.

**ERROR-159 ISN/RABN not zero for empty descriptor**

**Explanation** If a descriptor has no values/ISNs, a value of X'00' is stored in the U3 block to indicate an empty descriptor. The following values for MIRABN and ISN must be zero.

**ERROR-160 Invalid value for rotating ISN in FCB**

**Explanation** The value for the rotating ISN must be less than or equal to the highest ISN, plus 1.

**ERROR-161 Duplicate element for empty descriptor**

**Explanation** There are at least two U3 entries for an empty descriptor. Each descriptor has at least one entry on the U3 level. There may be several entries for one descriptor when the descriptor spans several MI blocks, because each MI block has an entry on the U3 level. Although there are no MI blocks for an empty descriptor, there must be one (and only one) U3 entry.

**ERROR-162 Wrong pointer to last parent of super/hyperdescriptor**

**Explanation** The field descriptor table (FDT) contains an entry pointing to the last parent field of a super- or hyperdescriptor. The pointer contains the wrong value.

**WARNING-163 Unreachable index blocks**

**Explanation** An index block exists that is neither used nor in the unused RABN chain.

**Action** No immediate action is needed; however, the RABN block cannot be used until either the Associator is reordered or an UNLOAD/LOAD sequence is performed.

**ERROR-164 Error initializing collating user exit - return code=*return-code***

**Explanation** An error occurred while the collation descriptor user exit was being initialized.

**Action** Investigate the cause of the error; correct it; and rerun the job.

**ERROR-165 Collating user exit not loaded**

**Explanation** The collation descriptor user exit requested is not loaded.

**Action** Load the exit and rerun the job.

**ERROR-166 Invalid value for number of ISN per {AC|AC2} block in FCB**

**Explanation** The value for number of ISNs per address converter (AC) or secondary address converter (AC2) block must be the block size of the corresponding address converter, in bytes, divided by the size of the ISN (either 3 or 4 bytes).

**Action** Correct the value provided in the file control block (FCB).

**ERROR-167 First element without FE bit**

**Explanation** The upper index blocks contain index entries for one or more descriptors. The first element for a given descriptor contains the *first element bit* or *FE BIT*. A missing FE bit can result in incorrect index positioning or Adabas response codes.

**Action** Document the error. Try to fix the error as soon as possible, for example by reinverting the descriptor where the error occurred.



**ERROR-168 FDT and index control byte mismatch, DE = *dd***

**Explanation** An FDT and index control byte mismatch occurred for the description (*dd*) listed in the message. The comparison of the two compares the control byte IXUCTL of the index with the control byte FDTF of the FDT.

**Action** When this error occurs, dump and print the FDT using the ADAICK FDTPRINT utility. Then contact your Software AG support representative for assistance.

**ERROR-169 FDT length in FCB does not match with the FDT, FNR=*nnnnn***

**Explanation** The length fields found in FDTHLL and YFDTL are not equal. The file number is given in the message.

**Action** When this error occurs, dump and print the FCB using the ADAICK FCBPRINT utility for the file listed in the message. Then contact your Software AG support representative for assistance.

**ERROR-170 RABN-errormsgtext**

**Explanation** This error can have two different messages, as described in the following table:

Message Text	Description
RABN <i>rabn</i> not in extent	The RABN named in the message does not exist in the extent description of the GCBs.
RABN <i>rabn</i> not in extent, file <i>file</i>	The RABN named in the message does not exist in the extent description of the file.

These messages may occur after an ADAICK DATAPRINT or ADAICK DSCHECK run.

**Action** For either error message, run ADAICK GCBPRINT. If you receive the second message (RABN *rabn* NOT IN EXTENT, FILE *file*), also run ADAICK FCBPRINT for the file named in the message.

Then contact and send the output from these runs (as appropriate) to your Software AG support representative for assistance.

**ERROR-172 Invalid segment count for spanned DS record**

**Explanation** The number of spanned record segments has exceeded the maximum of 5.

**Action** Rebuild the file. Contact your Software AG technical support representative for assistance.

**ERROR-173 Next ISN is zero for master ISN**

**Explanation** The header of a primary spanned record lists zeros as the ISN for the next secondary record in the spanned record.

**Action** Contact your Software AG technical support representative for assistance.

**ERROR-174 Offset bigger than ASSO block size**

**Explanation** During the formatted print of an ASSO block, ADAICK tried to print out data behind the ASSO block.

**Action** Check the concerning ASSO block. This error may occur if the number of extents is erroneously too big.

**ERROR-176 Last formatted ISN exceeds MAX ISN  
Last formatted AC2 ISN exceeds AC2 MAX ISN**

**Explanation** This error occurs when one of the following invalid conditions occurs:

- The last formatted ISN is higher than the MAXISN.
- The last formatted AC2 ISN is higher than the AC2 MAXISN.

**Action** Contact your Software AG technical support representative for assistance.

**ERROR-177 Top ISN exceeds last formatted ISN  
Top AC2 ISN exceeds last formatted AC2 ISN**

**Explanation** This error occurs when one of the following invalid conditions occurs:

- The top ISN is higher than the last formatted ISN.
- The top AC2 ISN is higher than the last formatted AC2 ISN.

**Action** Contact your Software AG technical support representative for assistance.