

REVH* - Adabas Review Hub Messages

Overview of Messages

REVH03	REVH06	REVH07	REVH10	REVH11	REVH12	REVH13	REVH14
REVH15	REVH16	REVH17	REVH21	REVH22	REVH24	REVH25	REVH26
REVH27	REVH29	REVH30	REVH31				

REVH03 *hub-id* CLIENT MONITORING *jobname* HAS REGISTERED IN

Explanation When a client nucleus initializes, the nucleus sends a call to the hub specified on the ADARUN parameter REVIEW to determine whether an Adabas Review hub is active. When it receives the call, the Adabas Review hub displays this message identifying the job name of the client nucleus.

Action No action is required for this informational message.

REVH06 *hub-id* CLIENT *dbid* [- *nuc-id*] HAS CHECKED OUT

Explanation When a client nucleus is closing, the nucleus calls the hub identified on the ADARUN REVIEW parameter. When it receives the call, the hub displays this message identifying the DBID of the client nucleus. If the client nucleus is a member of an ADASMP or Adabas sysplex cluster, then the corresponding nucleus ID also displayed.

Action No action is required for this informational message.

REVH07 *hub-id* CLIENT *dbid* WAS DELETED

Explanation The specified client nucleus was deleted from the hub's registered client list.

Action None required. This is for your information only.

REVH10 *hub-id* CLIENT *dbid* WAS SENT A MESSAGE

Explanation When there is a change in the monitoring or reporting status of a client nucleus by Adabas Review, the hub sends a notification to the client nucleus. This message is displayed when the notification is sent to the client nucleus.

Action No action is required for this informational message.

RE VH11 *hub-id* { NO | *count* } REVIEW REPORT(S) STARTED.
hub-id { NO | *count* } REPORT(S) REQUIRING BUFFERS.

Explanation These messages are displayed in conjunction with the REVH10 message and indicate the status of information transmitted to the client nucleus by the hub.

count indicates the number of started reports and/or the number of reports requiring buffers.

Action None required. This message is for your information only.

RE VH12 *hub-id* OUTBOUND MESSAGE TO CLIENT *dbid* RECEIVED A RSP *rsp*

Explanation This message is displayed at the completion of a notification call to a client nucleus identified by *dbid*. A response code of zero indicates that the message was successfully received.

Action No action is required for this informational message.

RE VH13 *hub-id dbid nucid last-act-time globrpts/dbrpts buffers log-recs*
hubid CL.jobname last-act-time clientrpts/dbrpts ----- log-recs

Explanation This message is displayed in response to the DCLIENT operator command. A title that reads " *hubid Dbid Nucid Last-act Rpts Buffers Log-records*" appears as the first REVH13 message. Thereafter, the following information is supplied under the corresponding column titles for each client nucleus registered with the hub:

<i>buffers</i>	<p>The buffers requested for this client:</p> <ul style="list-style-type: none"> ● "F": format buffer requested ● "R": record buffer requested ● "S": search buffer requested ● "V": value buffer requested ● "I": ISN buffer requested ● "M": multifetch buffer requested ● "-": no buffer of the type requested <p>Note: In the case of the client report line in this message, there are no buffers, so dashes will appear in this section.</p>
<i>clientrpts</i>	The number of client reports running.
<i>dbid</i>	The database ID of the client nucleus.
<i>dbrpts</i>	The number of database-specific reports running for this client.
<i>globrpts</i>	The number of DBID=ALL reports running for this client.
<i>hubid</i>	The Adabas Review hub ID.
<i>jobname</i>	The job name of the client.
<i>last-act-time</i>	The time of last activity or the time when the last command log record was received from the client nucleus, in <i>hh:mm:ss</i> format.
<i>log-recs</i>	The number of command log records received from the client nucleus. For client report entries, this is the number of all command log records received from all client address spaces where client monitoring is or was switched on.
<i>nucid</i>	If the client nucleus represents an Adabas Parallel Services or Adabas Cluster Services database, the number of the nucleus within the cluster is also displayed.

The last line of the message lists the number of client reports running in the hub.

Action No action is required for this informational message.

REVH14 *hub-id* **CLIENT dbid IS NOT REGISTERED**

Explanation This message is displayed in response to an operator command that requested a service for a nonexistent client nucleus. The requested client nucleus could not be found in the hub's registered client list.

Action Ensure that the correct client nucleus ID is properly specified and reenter the operator command.

REVH15 *hub-id* **NO CLIENTS REGISTERED**

Explanation An operator command requested a service or status and there are no client nuclei presently listed in the hub's registration list.

Action None required. This is for your information only.

REVH16 *hub-id* **THE REVIEW HUB IS NOT RUNNING APF AUTHORIZED**

Explanation To use the Transport feature of the Adabas Review hub under z/OS, the load library needs to be APF-authorized.

Action APF-authorize the load library if you want to use the Transport feature.

REVH17 *hub-id* **TRANSPORT IS DISABLED**

Explanation The reason is provided in the previous message.

Action The Transport feature is not available in z/VSE environments. To use the Transport feature in other supported operating environments, refer to the previous message.

REVH21 *hub-id* **A CLIENT ATTEMPTED TO REGISTER WITHOUT A DBID**

Explanation The hub received a call from an unknown client. The hub ignores the request.

Action None required. This is for your information only.

REVH22 *hub-id* CLIENT *dbid* UNABLE TO ALLOCATE LIST SPACE

Explanation The hub was unable to insert a new client into its registration list. The client is given a non-zero response to prevent further communication. The hub continues processing and the registration of the new client is ignored.

Action Enter a DCLIENT=ALL operator command and review the list of clients. If there is a possibility of deleting a non-active client, then enter the STOPCLIENT=*dbid* operator command to stop the client from sending data, followed by a DELCLIENT=*dbid* to release the space in the registration list. To initiate the registration of the previously rejected client, start an Adabas Review report for that client.

REVH24 *hub-id* REVIEW NUCLEUS TERMINATED, REVIEW HUB ABORTING

Explanation The Adabas Review nucleus terminated abnormally. The hub can no longer process Adabas Review data and will terminate.

Action Check all messages from Adabas Review to determine the cause of the abnormal termination of the Adabas Review nucleus. Correct the problem and restart Adabas Review.

REVH25 *hub-id* REVIEW BUFFER SHORTAGE, INCREASE VALUE FOR BUFFER-SEGMENTS

Explanation The hub incurred a shortage of REVIEW buffers. The value for the available storage can be determined by the BUFFER-SEGMENTS parameter of the INPUT statement

Action See the *Adabas Review User* documentation.

REVH26 *hubid* HAND SHAKE COMMAND FOR DATA BASE *dbid* ISSUED
UBRSP=*ubrsp*

Explanation For diagnostic purposes, a handshake trace from the Adabas Review hub to the databases is activated. The Adabas Review hub issues a handshake command to a database because a report for this database is started, changed, or stopped. When the Adabas Review hub is brought down via ADAEND, the handshake command for the databases is also issued. UBRSP=8 indicates that the command is immediately complete and a 16-call is not required. UBRSP=4 indicates that the call is not complete and a 16-call is required.

Action No action is required for this informational message.

REVH27 *hubid* HAND SHAKE COMMAND FOR DATA BASE *dbid* HAS COMPLETED
hubid RSP=*acbrsp/acbsubcode*, ACBRSP=*acbrsp*

Explanation For diagnostic purposes, a handshake trace from the Adabas Review hub to the databases is activated. An Adabas X'1C' call with UB was sent to a database by the Adabas Review hub and message REVH26 was issued. A 16-call was issued (if required) and the command completed with the indicated response code and subcode.

Note:

ACBRSP=148 most likely means the database was not active.

Action No action is required for this informational message.

REVH29 *hubid* NO UB AVAILABLE FOR COMMAND TO CLIENT *dbid*

Explanation The hub attempted to send a command to the indicated client but found that its internal pool of UBs was exhausted.

Action This may be a transient condition if the hub is servicing many clients in a very busy system. Issue the STARTCLIENT operator command to reinitiate handshaking. If this does not resolve the error, contact your Software AG technical support representative.

REVH30 *hubid* LOGIC ERROR COMPLETING COMMAND TO CLIENT *dbid*

Explanation A command sent from the hub to a client was thought to be complete, but the 16-call did not mark it as complete. This is normally a logic error, but it might also occur during hub termination if the client was unresponsive..

Action Contact your Software AG technical support representative if this does not relate to an unresponsive client during hub termination.

REVH31 *hubid* INVALID STORAGE KEY *x*

Explanation The Adabas Review hub can only run in storage key 0 or 8.

Action Start the Adabas Review hub again under storage key 0 or storage key 8.