BREADCRUMB

The BREADCRUMB control represents a horizontal list of links. The number of links and the name of each link is dynamically controlled by the application.

The control always occupies 100% of the given width.

The following topics are covered below:

- Example
- Adapter Interface
- Built-in Events
- Properties

Example

Bread Crumbs...

Books ▷ Computers ▷ Ajax

The XML layout definition is:

```
<rowarea name="Bread Crumbs...">
<breadcrumb breadcrumbprop="items">
</breadcrumb>
</rowarea>
```

Adapter Interface

```
DEFINE DATA PARAMETER

1 ITEMS (1:*)

2 STYLE (U) DYNAMIC

2 TEXT (U) DYNAMIC

2 TOOLTIP (U) DYNAMIC

1 ITEMSINFO

2 SELECTEDITEM (I4)

END-DEFINE
```

Built-in Events

value-of-breadcrumbprop.onSelect

Properties

Basic			
breadcrumbprop	Name of the adapter parameter that represents the control in the adapter.	Obligatory	
breadcrumbstyle	CSS style definition that is directly passed into this control.	Optional	background-color: #FF0000
	With the style you can individually influence the rendering of the control. You can specify any style sheet expressions. Examples are:		color: #0000FF font-weight: bold
	border: 1px solid #FF0000		
	background-color: #808080		
	You can combine expressions by appending and separating them with a semicolon.		
	Sometimes it is useful to have a look into the generated HTML code in order to know where direct style definitions are applied. Press right mouse-button in your browser and select the "View source" or "View frame's source" function.		
pixeldistance	Pixel distance between the links that are rendered.	Optional	1
			2
			3
			int-value
comment	Comment without any effect on rendering and behaviour. The comment is shown in the layout editor's tree view.	Optional	