

WEBIO - Web I/O Interface Screen Rendering

This Natural profile parameter allows you to individually enable or disable the rendering of certain features of the Natural Web I/O Interface display on the basis of a style sheet. It corresponds to the NTWEBIO macro in the parameter module NATPARM.

For further information, see the corresponding sections in *Using Style Sheets* in the *Natural Web I/O Interface* documentation.

Possible settings	See <i>Keyword Subparameters</i> , below.	Possible subparameter keywords: ML KEYS WIN
Default setting	ML=OFF , KEYS=OFF , WIN=OFF	By default, the style sheet based rendering of the message line, PF key buttons and Natural window objects is disabled.
Dynamic specification	yes	The parameter WEBIO can only be specified dynamically. In NATPARM, use the macro NTWEBIO.
Specification within session	no	

The following topics are covered below:

- WEBIO Parameter Syntax
- NTWEBIO Macro Syntax
- Keyword Subparameters

WEBIO Parameter Syntax

The WEBIO parameter is specified as follows:

```
WEBIO=({ML=[ON|OFF],}{KEYS=[ON|OFF],}{WIN=[ON|OFF]})
```

For names and values of keyword subparameters, see *Keyword Subparameters* below.

NTWEBIO Macro Syntax

The NTWEBIO macro is specified as follows:

```
NTWEBIO {ML=[ON|OFF],}{KEYS=[ON|OFF],}{WIN=[ON|OFF]}
```

Keyword Subparameters

ML | KEYS | WIN

ML - Message Line

Enables/disables the style sheet based rendering of the message line. See also *Modifying the Message Line* in the *Natural Web I/O Interface* documentation. Possible values are:

ON	The style sheet based rendering of the message line is enabled.
OFF	The style sheet based rendering of the message line is disabled.

KEYS - PF Keys

Enables/disables the style sheet based rendering of the PF key buttons. See also *Modifying the Style of the PF Key Buttons* in the *Natural Web I/O Interface* documentation. Possible values are:

ON	The style sheet based rendering of the PF key buttons is enabled.
OFF	The style sheet based rendering of the PF key buttons is disabled.

WIN - Window Objects

Enables/disables the style sheet based rendering of Natural window objects. See also *Modifying the Natural Windows* in the *Natural Web I/O Interface* documentation. Possible values are:

ON	The style sheet based rendering of Natural window objects is enabled.
OFF	The style sheet based rendering of Natural window objects is disabled.