

Adabas for Linux, UNIX and Windows

Adabas Services on Windows

Version 6.7.1

October 2019

This document applies to Adabas for Linux, UNIX and Windows Version 6.7.1 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 1987-2019 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG.

Document ID: ADAOS-SERV-671-20211012

Table of Contents

Adabas Services on Windows	v
1 About this Documentation	1
Document Conventions	2
Online Information and Support	2
Data Protection	3
2 Adabas Services on Windows	5
Adabas Database Service	6
Adabas Shared Memory Service	8

Adabas Services on Windows

This document contains information about Adabas Services on Windows.

The following topic is covered:

- *Adabas Services on Windows*

1 About this Documentation

▪ Document Conventions	2
▪ Online Information and Support	2
▪ Data Protection	3

Document Conventions

Convention	Description
Bold	Identifies elements on a screen.
Monospace font	Identifies service names and locations in the format <i>folder.subfolder.service</i> , APIs, Java classes, methods, properties.
<i>Italic</i>	Identifies: Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources.
Monospace font	Identifies: Text you must type in. Messages displayed by the system. Program code.
{ }	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.
	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the symbol.
[]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [] symbols.
...	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...).

Online Information and Support

Software AG Documentation Website

You can find documentation on the Software AG Documentation website at <https://documentation.softwareag.com>.

Software AG Empower Product Support Website

If you do not yet have an account for Empower, send an email to empower@softwareag.com with your name, company, and company email address and request an account.

Once you have an account, you can open Support Incidents online via the eService section of Empower at <https://empower.softwareag.com/>.

You can find product information on the Software AG Empower Product Support website at <https://empower.softwareag.com>.

To submit feature/enhancement requests, get information about product availability, and download products, go to [Products](#).

To get information about fixes and to read early warnings, technical papers, and knowledge base articles, go to the [Knowledge Center](#).

If you have any questions, you can find a local or toll-free number for your country in our Global Support Contact Directory at https://empower.softwareag.com/public_directory.aspx and give us a call.

Software AG Tech Community

You can find documentation and other technical information on the Software AG Tech Community website at <https://techcommunity.softwareag.com>. You can:

- Access product documentation, if you have Tech Community credentials. If you do not, you will need to register and specify "Documentation" as an area of interest.
- Access articles, code samples, demos, and tutorials.
- Use the online discussion forums, moderated by Software AG professionals, to ask questions, discuss best practices, and learn how other customers are using Software AG technology.
- Link to external websites that discuss open standards and web technology.

Data Protection

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

2 Adabas Services on Windows

- Adabas Database Service 6
- Adabas Shared Memory Service 8

There are two services for Adabas on Windows:

- The Adabas Database Service is required to automatically start and stop databases at system start and shutdown.
- The Adabas Shared Memory Service is required to create shared memory, since this requires additional privileges.



Notes:

1. You must have administrator rights on the machine in question in order to install, start and stop the Adabas services.
2. If you want to administrate the Adabas services from the command line, start the Adabas Command Prompt with the option *Run as Administrator*. To do this, navigate via the **Start** menu : **All Programs -> Software AG -> Administration -> Adabas Server 6.x -> Start Command Prompt**, then right click on **Start Command Prompt** and select the option *Run as Administrator*.

Adabas Database Service

If you start an Adabas nucleus session under Windows, the session will be terminated normally when you log off, however, in many cases, this behaviour is not desired.

In order to prevent this happening, you must start the database with the Adabas Database Service. The Adabas Database Service is also able to start databases automatically when Windows is booted. You can administrate the Adabas Database Service via a command line interface.

Administration of the Adabas Database Service from the Command Line

➤ To install the Adabas Database Service

- Enter `ADASRV INSTALL` at the Command Prompt.

➤ To start the Adabas Database Service

- Enter `ADASRV START` at the Command Prompt.

Or:

Choose Services (depending on the operating system, these may be contained in either the Control Panel in the Main program group, or in Administrative Tools in the Control Panel) and then choose the Adabas Database Service from the Services list. Choose **Start** to start the service.

➤ **To stop the Adabas Database Service**

- Enter `ADASRV STOP` at the Command Prompt.

Or:

Choose Services (depending on the operating system, these may be contained in either the Control Panel in the Main program group, or in Administrative Tools in the Control Panel) and then choose the Adabas Database Service from the Services list. Choose **Stop** to stop the service.



Note: Stopping the Adabas Database Service also automatically stops any Adabas databases that were started by the service.

➤ **To remove (uninstall) the Adabas Database Service**

- Enter `ADASRV REMOVE` at the Command Prompt.

➤ **To set the startup mode of the Adabas Database Service**

- 1 Choose Services (depending on the operating system, these may be contained in either the Control Panel in the Main program group, or in Administrative Tools in the Control Panel) and then choose the Adabas Database Service from the Services list.
- 2 Select the required startup type (automatic, manual or disabled) from the **Startup type** drop-down list box.
- 3 Choose OK to set the startup mode.

➤ **To set and show the startup mode of a database**

- If you want a database to be started automatically when the Adabas Database Service starts, enter `ADASRV Set <dbid> AUTOSTART=Vnnnnn` where *nnnnn* is the Adabas version:

- 1st digit = major version
- 2nd digit = minor version
- 3rd digit = service pack
- 4th - 5th digit = fix number

Example:

`AUTOSTART=V67100` means:

- Major version = 6
- Minor version = 7

- Service pack = 1
- Fix = fix 00

If you want to display the value of `AUTOSTART` for a single/each database, enter `ADASRV SHOW [<dbid>]` at the Command Prompt.



Notes:

1. The value of the `AUTOSTART` parameter is stored in the configuration file `%ADADATADIR%\etc\ADABAS.INI` under the subtopic `[DBID_<dbid>]` in the section `[DB_LIST]`.
2. The `AUTOSTART` parameter is not case sensitive, both `AUTOSTART` and `autostart` are acceptable.

> **To display the status of a database**

- If you want to display which databases are currently started by the Adabas Database Service, enter `ADASRV STATUS` at the Command Prompt.

> **To start and stop single databases**

- If the Adabas Database Service is already running, you can start a single database by entering `ADASRV START <dbid>` at the Command Prompt.

If you want to stop a single database that has been started by the Adabas Database Service, enter `ADASRV STOP <dbid>` at the Command Prompt.



Note: You can use the Adabas Database Service to start and stop only those databases for which the value of `AUTOSTART` has previously been set.

Adabas Shared Memory Service

A standard user should be able to start the Adabas nucleus or utilities, but a standard user is not allowed to create shared memories. For this reason, the Adabas Shared Memory Service has been introduced. The Adabas installation installs this service as an automatic service, and therefore the service should always have the status Started.

However, it is possible to stop, start, remove and install the service from the command line, for example when a fix for the service is provided:

- To install the service, enter `adashm install [auto]` at the command prompt. If you specify `auto`, the startup type is automatic, otherwise it is manual.

- To start the service, enter `adashm start` at the command prompt.
- To stop the service, enter `adashm stop` at the command prompt.
- To remove the service, enter `adashm remove` at the command prompt.

