

# PL6nnna and PL6ann-PRILOG6 Print Program Messages

The following message groups are described:

- Messages from the Independent Components
  - Messages from the System-Dependent Component
- 

## Messages from the Independent Components

### Overview of Messages

PL6000I | PL6001E | PL6002E

**PL6000I**      **CARD READ =>control-card**

**Explanation:** Displays the PRILOG6 input control card that was read.

**PL6001E**      **UNRECOGNIZED INPUT CARD**

**Explanation:** One of the control cards read was not recognized by PRILOG6.

**Action:**        Ensure that all cards either being with PRILOG6 or an asterisk (\*) for a comment line.

**PL6002E**      **INVALID PARM: parameter**

**Explanation:** The specified input parameter or value in the PRILOG6 control cards is invalid.

**Action:**        Correct the identified parameter and rerun the program.

## Messages from the System-Dependent Component

### Overview of Messages

PL6D01 | PL6D02

**PL6D01        DDCARD FILE FAILED TO OPEN, USING DEFAULTS**

**Explanation:** The input card file could not be opened.

**Action:** If the defaults are used, there are no input cards and this file is not required. The message can be ignored. The default values are CLOGLAYOUT=5 and FIELDS=(LIST).

If values other than the defaults are required, ensure that the file is available and rerun the job.

**PL6D02        DDCLOGIN FILE FAILED TO OPEN - NO REPORTS**

**Explanation:** The file containing the CLOG records did not open. No reports are printed.

**Action:** Ensure that the file is properly allocated and rerun the job.