

Commands

This commands described in this section may be used within Adabas Review. Some may be entered on the command line of any Adabas Review screen; others are specific to a particular function. Refer to the description of the particular command for more information.

Terms enclosed in (square) brackets (e.g., [report-name]) are optional. "Curly" brackets called braces ({ }) enclose possible (mutually exclusive) options. Unless qualified by (square) brackets ([]), one of the terms listed within the braces must be chosen.

Command Overview

Please note that some of the commands listed in the following table may be used through Adabas Review; they are:

COLOR
EXIT
FIN
HELP
LOGO
MENU
MSG
QUIT

These commands are also described in section *Using Review Commands* in Getting Started.

Command	Action
AA	list target objects for a particular SVC
ACCPT	accept (temporarily save) selections or changes to selections
AOS or AO	access Adabas Online System
CD	change DBID
CH	compress history data
CL	close (suspend) report
COLOR {[ON]/OFF}	display color attributes or turn color off
CP [report-name]	change display program
CR	copy report definition
DBID=dbid	change the database
DD	display report information
DL [report-name]	download report output or history data
EB	access and edit Buffer Pool Report
EP [report-name]	access and edit display program
ER [report-name]	access and edit report definition

Command	Action
ET [<i>target-number</i>]	access and edit target object definitions
EU [{ <i>DEFAULT</i> <i>userid</i> }]	access and edit user profile
EX	expand list of history reports
EXIT	return to previous screen
FIELD [<i>field-type1</i> <i>field-type2 ...</i>]	list database fields
FIN	terminate Adabas Review session
FLDS [<i>field-type1</i> <i>field-type2 ...</i>]	list database fields
GENAUTO or GA	force regeneration of control statements for all autostarted reports
GENCARD or GC	generate report parameter cards for user-specified reports
HC [<i>report-name</i>]	print report output or history data (hard copy)
HELP	display help for screen or field
HUB= <i>hubid</i>	change the hub database
IN	display storage and processing information for active reports
LF [<i>field-type1 field-type2</i> <i>...]</i>	list database fields
LH	list history reports
LOG	in local mode only, reset selected parameters dynamically
LOGO	display Adabas Review logo screen
LOGON <i>library-name</i>	logon to the specified library
LR	list report definitions
LS	list started reports
LT	list target object definitions
LU	list user profiles
MENU	access the Adabas Review main menu
MSG [<i>message-number</i>]	display detailed explanation of the specified Adabas Review message
NAT	exit Adabas Review and return to Natural
NUCID and NUC LIST	monitor specific nucleus IDs separately when running in local mode
OPTNS	access and edit report options
PH	purge history data from expanded list
PR	purge report definition
PRINT [<i>report-name</i>]	print report output or history data
PS	purge (started) report output

Command	Action
PT	purge target object definition
PU	purge user profile
QUIT	terminate Adabas Review session
RA <i>[report-name]</i>	reactivate suspended report
REFRESH <i>[report-name]</i>	refresh report
REGEN <i>[report-name]</i>	regenerate display program
RESET HISTORY FILE	unlock history file locked as a result of the abnormal termination of the history compression program
RF <i>[report-name]</i>	refresh report
RG <i>[report-name]</i>	regenerate display program
RULES	access and edit report processing rules
SAVE	save report definition; write to Adabas Review repository
SETFILE or SET	access different Adabas Review repositories
SORT	dynamically change sort options from view (VW) of started report results
ST <i>[report-name]</i>	start report
START <i>[report-name]</i>	start report
SU <i>[report-name]</i>	suspend a started report
SW <i>[report-name]</i>	switch CLOG datasets
SWITCH <i>[report-name]</i>	switch CLOG datasets
TECH	displays environmental and maintenance information about the installed Adabas Review system
VIEW <i>[report-name]</i>	view started report, report output, or history data
VW <i>[report-name]</i>	view started report, report output, or history data
?	display help for a field

AA Command

Target objects are databases that may be monitored by Adabas Review. The AA (available Adabas nuclei) command is used to list the Adabas target objects for a particular supervisor call number (SVC) and provides a "snapshot" of processing activity as seen through Adabas Review.

For more information, see the section *Using the Adabas Availability Function in Displaying Statistics*.

ACCPT Command

The ACCPT command is used within the Edit Report (ER) function to save changes temporarily while you are working on another portion of the report. The ACCPT command does not save changes to disk.

Enter the ACCPT command on the command line of the Report Options screen in the Edit Report function.

For more information, see various subsections of the section *Using the Edit Report (ER) Function in Maintaining Report Definitions*.

AOS or AO Command

Adabas Online System (AOS) is a selectable unit of Adabas that enables database administrators to monitor and change aspects of an Adabas database interactively. For more information, refer to the *Adabas DBA Reference Documentation*.

If Adabas Online System is installed on your system and you have access privileges to it, you can access it by entering the AOS command on the command line of any Adabas Review screen. For more information, see the section *Accessing Adabas Online System in Displaying Statistics*.

CD Command

Each report collects data from a particular database. The CD command is used within the List Report Definitions (LR) function to change that database; that is, to change the DBID. The CD command is issued from the Report Definitions screen.

For more information, see the section *Changing the DBID in Maintaining Report Definitions*.

CH Command

The CH (compress history) command summarizes all history report occurrences within a date range into a single report occurrence. The original report occurrences are then purged. Although this command can dramatically reduce the number of records used to represent the report, it also denies you the possibility of thereafter viewing the data by different data ranges.

If the CH command terminates abnormally for any reason, the original history data could be lost; therefore, Software AG recommends backing up your data before executing this command. If an abnormal termination occurs, the history file is locked against further compression attempts for any report by any user. See the RESET HISTORY FILE command for information about unlocking the history file.

For more information, see the section *Compressing Accumulated History Report Data in Managing History Data*.

CL Command

The CL command is used within the List Started Reports (LS) function to close a report. Closing a report means that the report is suspended, and the accumulated data is written to the output locations defined to the report. Data accumulated by the report before the command was issued may not be viewed online after the command completes.

If the report option RESTART=Y is specified, the report is restarted automatically after the CL command has been issued.

On the Started Reports screen, enter the CL command on the selection line preceding the name of the report you are closing.

For more information, refer to the section *Closing Reports in Saved and Started Reports*.

COLOR Command

```
COLOR {ON | OFF }
```

If you use a color terminal, the COLOR command may be used throughout Adabas Review to change the display from color to monochrome. COLOR OFF turns off the color display, and COLOR ON (the default) turns on the color display.

CP Command

```
CP [report-name]
```

The CP command is used within the List Report Definitions (LR) function to change the display program used by the report.

The CP command is entered on the selection line preceding the report name on the Report Definitions screen. The cursor is automatically placed on the display program name so that you may enter the name of the new display program.

The CP command may also be entered on the command line of any Adabas Review screen as follows:

```
CP report-name
```

A window appears giving the report name, the name of the current display program, and an input line for the name of the new display program.

For more information, see the section *Changing to a Different Display Program in Maintaining Display Programs*.

CR Command

One way to create new reports is to use the Copy Report Definition (CR) command within the List Report Definitions (LR) function. The CR command is issued from the Report Definitions screen.

The CR command allows you to copy a report definition either to another Adabas Review repository, or to the current Adabas Review repository under a new name.

For more information, see the section *Copying a Report Definition in Maintaining Report Definitions*.

DBID Command

```
DBID = dbid
```

The DBID command is used to change to another local Adabas Review or to another Adabas Review hub database. DBID functions as a synonym for the HUB command. The command may be entered on the command line of any screen . Specify the database ID number of the new local Adabas Review or the new hub database for *dbid*.

The message "DBID has been changed" indicates that the connection between the Review Natural code and the indicated Review hub has been successfully established.

If Adabas Review is unable to change to the database specified, or if the database specified is running an earlier version of Review, an error message is displayed describing the condition.

DD Command

The DD command is used to display selected information about a report including the identity of the user who saved it, its format (summary or detail), whether history data is collected for it; what control breaks are specified; what totals and what averages are specified.

For more information, see the section *Displaying Report Information in Maintaining Report Definitions*.

DL Command

```
DL [report-name]
```

Note:

To use this command, Entire Connection is required.

The DL command is used to download to a personal computer the data accumulated by a started report. It may also be used to download history data.

The DL command may be issued from either the Started Reports (LS function) screen or the History Reports (LH function) screen by entering the command on the selection line preceding the report name.

The DL command may also be entered on the command line of any screen within Adabas Review as follows:

```
DL report-name
```

If the DL command is entered on the command line without a report name, the command applies to the report you last accessed.

After the command has been issued, Entire Connection prompts you for file and directory information. Entire Connection proceeds to download the report output to the file and directory specified.

For more information, see the section *Downloading Report Output* in *Managing Report Output*.

EB Command

A sample report called "Buffer Pool Report" is created when Adabas Review is installed. The EB command is used to create, edit, and start buffer pool reports for specific databases being monitored based on the provided sample report.

For more information, see the section *Editing the Buffer Pool Report* in *Maintaining Report Definitions*.

EP Command



```
EP [report-name]
```

The EP command is used to edit the Natural program that displays the report results online when the VIEW command is issued.

The EP command may be issued from any of the three list report function screens (Report Definitions, Started Reports, and Adabas History Reports) by entering the command on the selection line preceding the report name.

The command may also be issued on the command line of any screen in Adabas Review as follows:



```
EP report-name
```

For more information, refer to the section *Editing the Display Program* in *Maintaining Display Programs*.

ER Command



```
ER [report-name]
```

The ER command is used to create and modify reports. It may be issued from any of the list report function screens (Report Definitions, Started Reports, and Adabas History Reports) on the selection line preceding the report name.

The ER command may also be issued on the command line of any screen within Adabas Review. To edit an existing report, or to create a new report, enter the command as follows:



```
ER report-name
```

For more information, see the section *Using the Edit Report (ER) Function in Maintaining Report Definitions*.

ET Command



ET [target-number]

The ET command is used by Adabas Review administrators to edit target definitions. This command is issued by from the Target Definitions screen (LT function) by entering the command on the selection line preceding the target's DBID.

The ET command may also be issued on the command line of any screen within Adabas Review. To edit an existing target, or to add a new target, enter the command as follows:



ET target-number

For more information, see the sections *Accessing the Edit Target Screen*, *Defining a Target Object* and *Editing an Existing Target* in *Administrative Functions*.

EU Command



EU { DEFAULT | userid }

The EU command is used by Adabas Review administrators to create and edit user profiles, either the DEFAULT profile or the profile for a particular user ID.

For more information, see the sections *Customizing the Default Profile*, *Creating a User Profile*, *Editing a User Profile* or *Copying a User Profile* in *Administrative Functions*.

EX Command

The EX command is used within the List History Reports (LH) function. It "expands" the Adabas History Reports screen to list the dates when history data was accumulated by the report. For more information, see the section *Expanding the List of History Reports* in *Managing History Data*.

The command is issued by entering the EX code on the selection line preceding the report name.

The EX command must be issued before attempting to purge history data.

EXIT Command



EXIT

The EXIT command is used to terminate a function and return to the menu from which the function was called. This command is not to be confused with the MENU command, which terminates the function and returns to the Adabas Review main menu.

The EXIT command may be issued from any screen within Adabas Review. The command may be issued either by entering EXIT on the command line or by pressing PF3.

FIELD, FLDS or LF Command

{FIELD | FLDS | LF} [field-type1 field-type2 ...]

The FIELD, FLDS, or LF command is used within the Edit Report (ER) function to display the data fields that may be used in reports:

- The list of field categories is displayed by entering the FIELD, FLDS, or LF on the command line of any screen within the Edit Report (ER) function.
- The list of fields for a particular category is displayed by entering the FIELD, FLDS, or LF command followed by one or more of the following category codes:

AC	Adabas control block fields
BU	Adabas buffer fields
IN	Interval and time fields
IO	Adabas I/O fields
NA	Natural fields
NU	Adabas nucleus fields
OP	Operating system fields
TP	Fields used to monitor transaction processing

For more information, refer to the section *Entering the Field Names in Maintaining Report Definitions*.

FIN or QUIT Command

{FIN | QUIT}

The FIN or QUIT command is used to exit from Adabas Review. It may be issued from any screen in Adabas Review. If exiting from the Adabas Review main menu, you may also press PF12 or PF3 .

GENAUTO or GA Command

{GENAUTO | GA}

Note:

This command is not available to users of Adabas Review under z/VM.

The GENAUTO command is used to regenerate the control statements used by Adabas Review for autostarted reports. See the section *Autostarted Reports* in the *Introduction*.

Ordinarily, Adabas Review maintenance procedures eliminate the need for users to regenerate these statements. In exceptional circumstances (e.g., the PDS becomes too full and requires compressing), you may either use the GENAUTO command or code the parameters manually.

You can issue the command by entering GENAUTO or GA on the command line of any screen within Adabas Review. A message confirms that the parameter statements have been regenerated.

GENCARD or GC Command

```
{GENCARD | GC}
```

Note:

This command is not available to users of Adabas Review under z/VM.

The GENCARD command is used to generate batch parameter statements from Adabas Review online reports. The GENCARD command obtains target database information from the List Target Definitions (LT) function.

You can enter either GENCARD or GC on the command line of any screen within Adabas Review. A window appears, prompting you for the DD name of the output file and the report name. See the section *Generating Batch Report Parameters* in *Using Batch Facilities*. The batch report parameters generated by GENCARD can be copied to the RVUPARM dataset and used as input to a Review batch job.

HC or PRINT Command

```
{HC | PRINT} [report-name]
```

Note:

The hard copy facility of Natural must be installed for this command.

The HC or PRINT command is used to send report results to a hard copy printer. The command may be issued from the list of history reports or the list of started reports (LH or LS functions) by entering the command HC on the selection line preceding the report name.

The command may also be entered on the command line of any Adabas Review screen as:

```
HC report-name
```

If the HC or PRINT command is entered on the command line without a report name, the command is applied to the report you last accessed.

For more information, see the section *Printing Report Results* in *Managing Report Output*.

HELP Command and ? Command




The HELP command may be issued from any screen within Adabas Review to obtain online help for that screen. The command provides general information regarding systems and/or functions within Adabas Review.

You can obtain help for a particular screen by either entering the HELP command on the command line or pressing PF1.

You can obtain help for a particular input field on a screen by entering a ? on that field. If specific help for that field is not available, the general information supplied for the screen is displayed.

Refer to the section *Using the Online Help System* in *Getting Started*.

HUB Command



The HUB command is used to change the hub database for Adabas Review. It may be entered on the command line of any screen. Specify the database identification number of the new hub database for *hubid*.

The message "HUB has been changed" indicates that the connection between the Review Natural code and the indicated Review hub has been successfully established.

If Adabas Review is unable to change to the hub database specified, or if the hub database specified has a version of Review prior to the current version installed, an error message is displayed describing the condition.

IN Command

The IN command is used to display storage and processing information for active Adabas Review reports. It is not available in batch mode.

For more information, see the section *Displaying Active Report Information* in *Saved and Started Reports*.

LH Command

The LH command is used to list reports that have written history data to the Adabas Review repository. From this list, you can use commands to view, download to a PC, print, or purge history data. In addition, you can edit a report definition and its corresponding display program.

For more information, see the section *Listing History Reports* in *Managing History Data*.

LF Command

See the FIELD command.

LOG Command

The LOG command is used in local mode only to dynamically determine (that is, without cycling the system) whether

- Review commands are processed in Review; that is, whether the Review command processor includes commands issued by the Review online system in its reports.
- Adabas commands are processed by Review; that is, whether the Review command processor includes commands issued by Adabas in its reports.

Note:

Changes made by the LOG command are only valid as long as Adabas is running, and are not stored in a file; therefore, the changes remain in effect until Adabas and Review are restarted.

▶ To switch the value of one or more of these parameters dynamically

1. After the Review DB menu, type the LOG command on the command line and press ENTER.

The following window appears:

```

+-----+
|                                     |
|           Review Dynamic Params     |
|                                     |
|   Process Review Commands.. Y      |
|   Process Adabas Commands.. Y      |
|                                     |
| Enter-PF1---PF2---PF3---PF4---PF5---|
|                                     |
|                               Exit    Updat |
|                                     |
+-----+

```

2. Overtyping the current value of one or both parameters with the opposite value.
3. Press PF5 to implement the change; press PF3 to close the window. The change remains in effect until Adabas and Review are restarted.

LOGO Command



The LOGO command displays the Adabas Review Logo screen. The LOGO command may be issued on the command line of any Adabas Review screen.

LOGON Command



The LOGON command is used to exit Adabas Review and log on to the Natural library specified. Note that under Natural Security, your user ID must be defined to the library specified in order to log on to that library. It is not available in batch mode.

LR Command

The LR command is used to list all report definitions. From the list, you can use commands to maintain a report. Such commands are entered on the selection line preceding the name of the report in the list.

For more information, see the section *Listing Report Definitions in Maintaining Report Definitions*.

LS Command

The LS command is used to list all reports that have been started. From the list, you can use commands to suspend, reactivate, close, and refresh a report. You can view, download to a PC, print, or purge report output. Additionally, you can edit a report definition or its corresponding display program.

For more information, see the section *Listing Started Reports in Saved and Started Reports*.

LT Command

The LT command is used to list the existing target definitions. From the resulting list, the Adabas Review administrator can use commands to edit or purge a target definition.

For more information, see the section *Listing Target Definitions (LT) in Displaying Statistics* for non-administrators or *Listing Target Definitions in Administrative Functions* for Adabas Review administrators.

LU Command

The LU command is used by Adabas Review administrators to list the user profiles that have been defined. For more information, see the section *Listing User Profiles in Administrative Functions*.

MENU Command

A blue rectangular button with the word "MENU" in white, bold, uppercase letters.

The MENU command returns you to the Adabas Review main menu. It may be issued either by entering the command on the command line of any Adabas Review screen, or by pressing PF12.

MSG Command

A blue rectangular button with the text "MSG [message-number]" in white, bold, uppercase letters.

The MSG command displays detailed explanations of Adabas Review messages. It may be issued on the command line of any Adabas Review screen.

The MSG command may be entered with or without specifying a message number. If a message number is not specified, Adabas Review provides information about the last message displayed.

NAT Command

The NAT command is used to exit Adabas Review and return the user to the Natural NEXT prompt, or the Natural main menu, depending on how the system is configured. The NAT command is not available in batch mode.

NUCID and NUC LIST Commands

A white rectangular button with a thin border, containing the text "NUCID [nucid]" in blue, bold, uppercase letters.A white rectangular button with a thin border, containing the text "NUC LIST" in blue, bold, uppercase letters.

Adabas Review can monitor specific nucleus IDs separately when running in local mode through the NUCID command. The monitored Adabas nucleus must be a cluster nucleus (for example, you are running Adabas Cluster Services 7.4 or Adabas Parallel Services 7.4).

You can start the same report on each nucleus and then view them separately. To combine the data from a report that runs on multiple nuclei, you must create the report as a history report. The data from each nucleus will be combined only when viewing the history report.

NUCID Command

To access a specific nucleus, you must set the target NUCID in a similar manner as setting the target DBID. The target DBID is shown at the top right of each Review screen and the NUCID is shown at the top left of each screen. If you work in local mode on a cluster database without specifying a NUCID, you access one NUCID at random.

To set a specific NUCID, you may choose the NUCID from a list of available NUCIDs or enter it directly. To enter a NUCID directly, enter NUCID *nnnnn* in the Review command line, where *nnnnn* is the nucleus ID.

You can also set the NUCID to zero by entering NUCID in the Review command line. In this case, the NUCID indicator will be removed from the top left portion of the screen and all Review transactions will be to the NUCID selected by the Adabas command dispatcher.

NUC LIST Command

To set the NUCID by choosing one from a list of active NUCIDs, enter NUC LIST on the Review command line. Select a NUCID from the list by placing an X in the Sel column next the NUCID and press PF5 to accept the selection.

OPTNS Command

Report options describe additional processing aspects of the report such as whether it is a detail or summary report; whether it will perform physical command logging; or whether the data it collects will be written to the Adabas Review repository and stored as history data.

The OPTNS command is used within the Edit Report Definitions (ER) function to set these report options, logging options, and history options.

For more information, see the section *Using the Report Options Screen* in *Maintaining Report Definitions*.

PH Command

The PH command is used within the List History Report (LH) function to purge accumulated history data. This command is issued from the "expanded" Adabas History Reports screen; the EX command must be issued first.

The PH command is entered on the selection line preceding the report name on the expanded History Reports screen.

For more information, see the section *Purging Accumulated History Data* in *Managing History Data*.

PR Command

The PR command is used within the List Report Definitions (LR) function to purge reports. It is entered from the Report Definitions screen on the selection line preceding the report name.

For more information, see the section *Purging a Report Definition* in *Maintaining Report Definitions*.

PS Command

The PS command is used within the List Started Reports (LS) function to purge the data accumulated by a started report. The command is entered from the Started Reports screen on the selection line preceding the report name.

For more information, see the section *Purging Accumulated Data* in *Managing Report Output*.

PT Command

The PT command is used by Adabas Review administrators within the List Target Definitions (LT) function to purge target definitions. The command is issued from the Target Definitions screen on the selection line preceding the target's DBID.

For more information, refer to the section *Deleting a Target* in *Administrative Functions*.

PU Command

The PU command is used by the Adabas Review administrator to delete a user profile. The command is issued from the list of user profiles on the selection line preceding the profile name.

For more information, refer to the section *Purging a User Profile* in *Administrative Functions*.

RA Command



```
RA [report-name]
```

When you reactivate a suspended report, it resumes collecting data. The RA command is used to reactivate a suspended report. The command may be issued from the Started Reports (LS function) screen, and is entered on the selection line preceding the report name.

The command may also be entered on the command line of any screen within Adabas Review. If it is entered on the command line without a report name, Adabas Review attempts to reactivate the report you last accessed.

For more information, refer to the section *Reactivating Reports* in *Saved and Started Reports*.

REFRESH or RF Command



```
{REFRESH | RF} [report-name]
```

The REFRESH or RF command is used to refresh a started report. The REFRESH command purges the accumulated data and restarts the report.

When making changes to a started report, you are prompted to refresh the report when you attempt to start the report again. This is because the name of a report currently accumulating data matches the name of the report you are attempting to start; Adabas Review does not permit reports with duplicate names.

The RF command may be issued from the Started Reports (LS function) screen, and is entered on the selection line preceding the report name.

The RF or REFRESH command may also be entered on the command line of any screen within Adabas Review. If it is entered on the command line without a report name, the command is applied to the report you last accessed.

Because the REFRESH command executes a purge of the accumulated data, a window is displayed, prompting you to confirm the purge request.

For more information refer to the section *Refreshing Reports in Saved and Started Reports*.

REGEN or RG Command

```
{REGEN | RG} [ report-name ]
```

The REGEN or RG command is used to regenerate the display program that Adabas Review creates when a report is saved.

The RG command may be issued from the Report Definitions (LR function) screen, and is entered on the selection line preceding the report name.

The REGEN or RG command may also be entered on the command line of any screen in Adabas Review. If it is entered on the command line without a report name, the command is applied to the report you last accessed.

For more information, refer to the section *Regenerating a Display Program in Maintaining Display Programs*.

RESET HISTORY FILE Command

If you have used the CH command to compress accumulated history report data and the command processing terminates abnormally for any reason, the history file will be locked against further compression attempts for any report by any user.

To remove this lock, and to clean up any unusable compressed data, enter the following on the command line of the Adabas Review main menu:

```
RESET HISTORY FILE
```

If history records were lost as a result of the abnormal termination, the reset program will inform you of this. For more information, see the section *Compressing Accumulated History Report Data in Managing History Data*.

RULES Command

Report processing rules determine how field values are selected for your report. These rules restrict the accumulated data to certain values or conditions.

The RULES command is used within the Edit Report Definitions (ER) function to specify and modify processing rules for a report.

For more information, see the section *Using the Report Processing Rules Screen in Maintaining Report Definitions*.

SAVE Command

When a report definition is saved, it is written to the Adabas Review repository and a Natural display program is generated.

The SAVE command is used within the Edit Report Definitions (ER) function to write the report to the Adabas Review repository. To save a report, either enter the SAVE command on the command line of the Edit Report screen or press PF5.

For more information, see the section *Saved and Started Reports*.

SETFILE or SET Command



{SETFILE | SET}

The SETFILE or SET command allows you to access a Adabas Review repository that is different from the one you are currently accessing.

The Adabas Review repository contains user profiles, report definitions, and history data. Depending on how Adabas Review is configured, you may have more than one Adabas Review repository.

The SETFILE or SET command may be issued from any Adabas Review screen, by entering the command on the command line.

A window is displayed, showing the DBID and FNR of the Adabas Review repository you are currently accessing. To change Adabas Review repositories, type the new DBID and FNR over the existing information and press ENTER.

If you enter the information correctly, you receive a message that the Adabas Review file was set successfully.

If you enter an incorrect DBID or FNR, you receive a message indicating the error, and the change is not made.

SORT Command

The SORT command is used after the VIEW command is issued to dynamically change the setting of the "Display By" report option. The following settings are available within the SORT command:

Setting	Sorts the data in . . .	Equivalent to "Display by ..."
Account (Ascend)	ascending order by control break;	SORTED
Number of commands	descending order by the "Number of Commands" column;	USAGE
First summary field	descending order by the first summary field in the report;	SUMFIELD
Account (Descend)	descending order by control break;	SORTEDDE
Date and Time	ascending order by the start date and time of the control break interval;	DATETIME
Physical Sequence	the physical sequence in which it was collected.	LINEAR

You may issue the SORT command by first issuing the VIEW or VW command to display the results of a started report.

On the command line, enter the SORT command or press PF2. A window is displayed, listing the settings. The current setting is indicated by an arrow (>).

You may change the sort setting by placing the cursor on the setting you want to use and pressing ENTER. The display of the report results changes according to the sort setting you select.

For more information, refer to the section *Using the SORT Command in Managing Report Output*.

START or ST Command

```
{START | ST} [report-name]
```

A report must be started so that it can accumulate data. The ST or START command is used to start a report. It first executes the SAVE command to save the report definition and generate the display program. A started report can be suspended, reactivated, closed, or refreshed from the Started Reports screen (LS function).

The ST command may be issued from the Report Definitions (LR function) screen, by entering the command on the selection line preceding the report name.

The ST or START command may also be issued from any screen of Adabas Review. If it is issued without a report name, Adabas Review attempts to start the report you last accessed.

For more information, refer to the section *Saved and Started Reports*.

Note:

If you are trying to start a report in hub mode using batch Natural , you must issued the MENU HUB=*hubid* command prior to issuing the START command for the report.

SU Command

```
SU [report-name]
```

By suspending a started report, you stop it from accumulating any further data; however, the data already accumulated is retained. The RA (reactivate) command is used to reactivate a suspended report.

The SU command is used to suspend a started report. It may be issued from the Started Reports screen (LS function) by entering the command on the selection line preceding the report name.

The SU command may also be issued from any screen within Adabas Review. If it is issued without a report name, Adabas Review attempts to suspend the report you last accessed.

For more information, refer to the section *Suspending Reports* in *Saved and Started Reports*.

SWITCH or SW Command

```
{ SWITCH | SW } [report-name]
```

The SW or SWITCH command is used to switch to the next command log file defined for a specific report *before* the current log file is filled. This command is only valid for reports that have Adabas Review command logging turned on.

If the maximum number of command log files designated for that report is exceeded by this request, Adabas Review will begin writing over the file that contains the oldest data.

Note:

This command does not negate normal command file switching, nor does it switch the command log file for any report other than the one selected.

The SW command may be issued from the Started Reports (LS function) screen by entering the command on the selection line preceding the report name.

The SW or SWITCH command may also be issued from any screen of Adabas Review. If it is issued without a report name, Adabas Review attempts to switch to the next command log file for the report you accessed last.

For more information, see the section *Switching Command Log Files* in *Saved and Started Reports*.

TECH Command

The TECH command is used to display Adabas Review environmental and maintenance information. This function is useful in determining the environment in which Adabas Review is executing, and in determining which ZAPs have been applied.

For more information, see the section *Accessing Technical System Information* in *Getting Started*.

VIEW or VW Command

```
{ VIEW | VW } [report-name]
```

The VIEW or VW command allows you to view results of a started report or the data accumulated by a history report. The VW command may be issued from any list function screen (Report Definitions, Started Reports, or Adabas History Reports) on the selection line preceding the report name.

The VW or VIEW command may also be issued from any screen within Adabas Review. If it is issued without a report name, the command is applied to the report you last accessed.

For more information, refer to the section *Viewing Report Results* in *Managing Report Output*.