

NETInn - ADAIOR Messages

These Entire Net-Work system messages are identical to the corresponding ADAInn messages documented in *Adabas Messages and Codes* documentation.

Overview of Messages

NETI02 | NETI22 | NETI23 | NETI24 | NETI29 | NETI32

NETI02 GETMAIN mmmmmmmm (ssssss)

Explanation The first form of the message is written whenever memory is dynamically acquired and the requested memory is available. The second form of the message is written whenever memory is dynamically acquired and less than the requested memory is available. In the messages, 'mmmmmmm' is the amount of memory requested; 'aaaaaaa' is the amount of memory available; and 'ssssss' (printed only under z/VSE), is the source of the memory (GETVIS, COMREG, ADABUF).

NETI22 ADAIOR TRACE TABLE: --> IS CURRENT ENTRY

Explanation This is an informational message that occurs when the ADAIOR TRACE TABLE is made active and printed.

NETI23 node-id jobname ABEND CODE code

Explanation z/VSE or BS2000/OSD: This message indicates that Entire Net-Work requested cancellation. A dump is normally also provided. The value code corresponds to the user abend code. For more information, see the section *Entire Net-Work Abend Codes*. The value *jobname* is the z/VSE job name or BS2000/OSD program name.

NETI24 node-id READY FOR OPERATOR COMMUNICATION

Explanation SYSLOG displays this message once operator communications has been requested by the operator with the z/VSE 'MSG' command. The value 'node-id' is the target ID of the node.

User Action Enter a valid Entire Net-Work command.

NETI29 OPER CMD: command

Explanation z/VSE and BS2000/OSD: This message occurs in SYSLST as part of the session statistics during Adabas session termination. The value 'command' is the operator command last entered from SYSLOG.

NETI32 **node-id INTERNAL ERROR - FUNCTION funcname ERROR error**

Explanation An internal error has occurred in ADAIOR.

User Action Make a note of all recent messages, and contact your Software AG technical support representative.