

About ADARUN Parameters for Cluster Nuclei

Software AG recommends that you use your existing values (or the default settings) of the Adabas ADARUN parameters for each Adabas nucleus in a cluster, and then tune the values after analyzing the performance of the cluster. For more information about expected differences, read *Performance and Tuning*.

Session statistics can be used to determine the best settings for each parameter. The statistics are printed automatically at the end of a session, but can also be displayed using nucleus or ADACOM operator commands during the session.

For your convenience, ADARUN parameters that are most significant to Adabas Cluster Services usage are described in *Useful ADARUN Parameters*.

This chapter covers the following topics:

- Global ADARUN Parameters
 - ADARUN Parameter Usage in Cluster Environments
-

Global ADARUN Parameters

ADARUN parameters that must be the same for all nuclei in the cluster are called *global*.

Some global parameters are set at nucleus startup and cannot be changed during the ensuing session; other global parameters can be changed during a session:

- When you set a value for a global parameter that cannot be changed after the first nucleus in an Adabas cluster has started, intracluster messages are used to communicate the ADARUN parameter settings of the first nucleus to all subsequent cluster nuclei. Each subsequent nucleus receives this information during initialization and determines whether its global nonchangeable parameters are equal to those of the first nucleus.

If they are not equal, the nucleus fails with a parameter error. The nonequal global changeable parameters are reset to the value retrieved from the intracluster messages and a corresponding message is printed.

- If you change the value of a global parameter that can be changed during a running session, the nucleus on which you make the change acquires a "parameter change lock", makes the changes in its local parameter area, and communicates the changes to the other cluster nuclei using intracluster messages.

All other nuclei in the cluster receive the intracluster messages containing the global parameters that have changed, change the parameters in their local parameter area, and send an "acknowledge" message.

ADARUN Parameter Usage in Cluster Environments

A cluster nucleus makes use of:

- *global* parameters, whose values are enforced by Adabas Cluster Services to be equal for all nuclei in a cluster. Some of these parameters can be modified (globally modifiable) during a session using an operator command or the Adabas Online System (NISNHQ, NONDES, and AOSLOG are only modifiable using AOS); others are fixed (globally fixed) and cannot be modified while the nuclei in the cluster are running.
- *local* parameters, which can be different for each nucleus. Some of these parameters are modifiable (locally modifiable) using an operator command or the Adabas Online System; others are fixed (locally fixed) and cannot be modified.

A few Adabas ADARUN parameters are not available to a cluster nuclei (No).

In the following table, the "No" column indicates which ADARUN parameters are not available to a cluster nucleus, the "LF" column indicates whether the parameter is a locally fixed parameter, the "LM" column indicates whether the parameter is a locally modifiable parameter, the "GF" column indicates whether the parameter is a globally fixed parameter, and the "GM" column indicates whether the parameter is a globally modifiable parameter.

Parameter	Usage	No	LF	LM	GF	GM
<u>AOSLOG</u>	Log to DDPRINT commands issued by AOS or ADADBS OPERCOM that modify the active nucleus			X		
<u>AREXCLUDE</u>	Exclude file(s) from autorestart		X			
<u>ARMNAME</u>	Name used to activate ARM		X			
<u>ASSOCACHE</u>	Controller caching control for the Associator component		X			
<u>ASYTVS</u>	Asynchronous buffer flush based on volser			X		
CACHE	Load ADACSH (Adabas Caching Facility)		X			
CACTIVATE	RABN range activation (Adabas Caching Facility)			X		
CASSODSP	Associator RABNs cached for data space (Adabas Caching Facility)			X		
CASSOEXT	Associator RABNs cached for extended memory (Adabas Caching Facility)			X		
CASSOHSP	Associator RABNs cached for hiperspace (Adabas Caching Facility)			X		
CASSOV64	Associator RABNs cached for virtual 64 (Adabas Caching Facility)			X		
CASSOMAXS	Associator cache space unit size (Adabas Caching Facility)			X		

Parameter	Usage	No	LF	LM	GF	GM
CBUFNO	Read buffer count for concurrent I/O (Adabas Caching Facility)			X		
CCTIMEOUT	Cache space area inactivity time (Adabas Caching Facility)			X		
CDATADSP	Data Storage RABNs cached for data space (Adabas Caching Facility)			X		
CDATAEXT	Data Storage RABNs cached for extended memory (Adabas Caching Facility)			X		
CDATAHSP	Data Storage RABNs cached for hiperspace (Adabas Caching Facility)			X		
CDATAV64	Data Storage RABNs cached for virtual 64 (Adabas Caching Facility)			X		
CDATAMAXS	Data Storage cache space unit size (Adabas Caching Facility)			X		
CDEMAND	Lowest acceptable Adabas buffer efficiency level (Adabas Caching Facility)			X		
CDISPSTAT	RABN range statistic display location (Adabas Caching Facility)			X		
CDXnn	Collation descriptor user exit(s)				X	
CEXCLUDE	Excluded command types (Adabas Caching Facility)			X		
CFILE	File or file range to be cached (Adabas Caching Facility)			X		
<u>CLOGDEV</u>	Multiple command log device		X			
<u>CLOGLAYOUT</u>	Define command log format		X			
<u>CLOGMRG</u>	Automatic command log merge control in a cluster environment					X
<u>CLOGSIZE</u>	Multiple command log size (blocks)		X			
<u>CLUCACHENAME</u>	Cluster cache structure name (Adabas Cluster Services only)				X	
<u>CLUCACHESIZE</u>	Cluster cache area size (Parallel Services only)				X	
<u>CLUGROUPNAME</u>	Cluster group name (Adabas Cluster Services only)				X	
<u>CLULOCKNAME</u>	Cluster lock structure name (Adabas Cluster Services only)				X	
<u>CLULOCKSIZE</u>	Cluster lock area size (Parallel Services only)				X	
<u>CLUSTER</u>	Adabas cluster session control				X	

Parameter	Usage	No	LF	LM	GF	GM
CMAXCSPS	Storage area count for ADACSH (Adabas Caching Facility)			X		
CRETRY	Cache space retry interval (Adabas Caching Facility)			X		
CSTORAGE	RABN caching activation (Adabas Caching Facility)			X		
CT	Command time limit (seconds)					X
CWORKSTORAGE	Cache space type (Adabas Caching Facility)			X		
CWORK2FAC	Percentage of Work part 2 cached (Adabas Caching Facility)			X		
CWOFK3FAC	Percentage of Work part 3 cached (Adabas Caching Facility)			X		
CXFILE	Excluded files (Adabas Caching Facility)			X		
<u>DATA</u> CACHE	Controller caching control for the Data Storage component		X			
DIRRATIO/ELEMENTRATIO	Ratio of directory entries to data elements in a cluster cache structure/area				X	
<u>DB</u> ID	Database ID (physical)				X	
<u>DE</u> VICE	Device type of the first ASSO extent				X	
DSF	Delta Save Facility control				X	
DSFEX1	Delta Save Facility user exit				X	
<u>DTP</u> *	Distributed transaction processing control	*			X	
DUALCLD	Dual command log device		X			
DUALCLS	Dual command log size (blocks)		X			
DUALPLD	Dual protection log device		X			
DUALPLS	Dual protection log size (blocks)		X			
<u>FA</u> STPATH	Adabas Fastpath control				X	
<u>FM</u> XIO	Limit parallel I/O operations by LFIOP flush processing			X		
<u>FO</u> RCE	Overwrite IDTE		X			
HEXnn	Hyperdescriptor exit(s)				X	
<u>IGN</u> DIB	Ignore DIB entry		X			
<u>IGN</u> DTP	Ignore distributed transaction processing area (Work part 4)		X			
<u>INT</u> NAS	Interval between nucleus statistic checkpoints (SYNS 60)				X	

Parameter	Usage	No	LF	LM	GF	GM
<u>L</u> BP	Length of buffer pool		X			
<u>L</u> CP	Length of security pool		X			
<u>L</u> DEUQP	Length of unique (UQ) descriptor pool		X			
<u>L</u> DTP	Length of distributed transaction processing area (Work part 4)		X			
<u>L</u> FIOP	Length of asynchronous flush pool		X			
LFP	Length of internal format buffer pool		X			
LI	Length of ISN list table (TBI)		X			
<u>LOCAL</u>	Nucleus (cluster) unknown to the network				X	
LOGCB	Log control block			X		
<u>LOGC</u> LEX	Log command log extension (CLEX)			X		
<u>LOGF</u> B	Log format buffer			X		
<u>LOGG</u> ING	Logging of Adabas commands			X		
LOGIB	Log ISN buffer			X		
LOGIO	Log I/O activity			X		
<u>LOGR</u> B	Log record buffer			X		
LOGSB	Log search buffer			X		
<u>LOGS</u> IZE	Maximum command log size		X			
<u>LOGU</u> X	Log user exit B data			X		
<u>LOGV</u> B	Log value buffer			X		
LP	Length of data protection area (Work part 1)		X			
LQ	Length of sequential command table		X			
<u>LR</u> DP	Length of the redo pool in cluster environments.		X			
LS	Length of sort area		X			
LU	Length of intermediate user buffer				X	
<u>LW</u> KP2	Length of ISN list processing area (Work part 2)		X			
LWP	Length of Adabas work pool		X			
<u>MODE</u>	Mode of operation	X				
<u>MSG</u> BUF	Size of the message buffer		X			
MXCANCEL	Timeout threshold for a cancel request between cluster nuclei(Adabas Cluster Services and Adabas Parallel Services)			X		

Parameter	Usage	No	LF	LM	GF	GM
MXCANCELWARN	Timeout threshold for a cancel request warning between cluster nuclei (Adabas Cluster Services and Adabas Parallel Services)			X		
<u>MXMSG</u>	Maximum message reply time between cluster nuclei (Adabas Cluster Services and Adabas Parallel Services)			X		
MXMSGWARN	Timeout threshold for a message reply warning between cluster nuclei (Adabas Cluster Services and Adabas Parallel Services)			X		
MXSTATUS	XCF status monitoring heartbeat interval (Adabas Cluster Services)			X		
<u>MXTNA</u>	Maximum inactivity time limit override for a user				X	
<u>MXTSX</u>	Maximum Sx execution time limit override for a user				X	
MXTT	Maximum transaction time limit override for a user				X	
MXWTOR	Self-termination query operator response interval (Adabas Cluster Services and Adabas Parallel Services)			X		
<u>NAB</u>	Number of attached buffers		X			
NC	Number of command queue elements		X			
<u>NCLOG</u>	Number of command logs		X			
NH	Number of hold queue elements		X			
<u>NISNHQ</u>	Number of ISNs in hold queue for user					X
<u>NPLOG</u>	Number of protection logs		X			
<u>NONDES</u>	Non-descriptor searches					X
<u>NQCID</u>	Number of active command IDs per user					X
<u>NSISN</u>	Number of ISNs per ISN table element		X			
NT	Number of threads		X			
NU	Number of user queue elements		X			
<u>NUCID</u>	Custer nucleus ID		X			
<u>OPENRQ</u>	Open command required				X	
<u>PLOGDEV</u>	Multiple protection log device		X			
<u>PLOGRQ</u>	Protection log required				X	
<u>PLOGSIZE</u>	Multiple protection log size (blocks)		X			

Parameter	Usage	No	LF	LM	GF	GM
<u>PREFETCH</u> **	Prefetch/multifetch feature control (see note below)	X				
<u>PREFICMD</u> **	Include command from prefetch/multifetch (see note below)	X				
<u>PREFIFIL</u> **	Include file from prefetch/multifetch (see note below)	X				
<u>PREFNREC</u> **	Multifetch record count (see note below)	X				
<u>PREFSBL</u> **	Prefetch single buffer length (see note below)	X				
<u>PREFTBL</u> **	Prefetch total buffer length (see note below)	X				
<u>PREFXCMD</u> **	Exclude command from prefetch/multifetch (see note below)	X				
<u>PREFXFIL</u> **	Exclude file from prefetch/multifetch (see note below)	X				
<u>QBLKSIZE</u>	Sequential data set block size (optimized by ADAIOR)		X			
<u>READONLY</u>	Read-only session control	X				
<u>REVIEW</u>	Adabas Review control			X		
<u>SMGT</u>	Error handling (PIN) facility control		X			
<u>SORTCACHE</u>	Controller caching control for the Adabas sort area component		X			
<u>SPT</u>	Adabas triggers and stored procedures control				X	
<u>SVC</u>	SVC number		X			
<u>TCPIP</u>	TCP/IP access control			X		
<u>TCPURL</u>	TCP/IP universal resource locator (URL)			X		
<u>TEMPCACHE</u>	Controller caching for the Adabas temp area component		X			
<u>TFLUSH</u>	Synchronous buffer flush time	X				
<u>TLSCMD</u>	Time limit for S1, S2, and S4 complex searches (seconds)				X	
TNAA	Non-activity time limit (access-only users)					X
TNAE	Non-activity time limit (ET logic users)					X
TNAX	Non-activity time limit (exclusive update users)					X
TT	Transaction time limit					X
UExn	User exits: 1, 3, 4, 5, 8		X			
UExn	User exits: 2, 12				X	

Parameter	Usage	No	LF	LM	GF	GM
UEXn	User exits: 6, 9 (for utilities)	X				
UTIONLY	Utilities-only session				X	
VISTA	Adabas Vista control				X	
WORKCACHE	Controller caching for the Adabas work area component		X			

Notes:

1. * Adabas Cluster Services 8.1 does not support DTP=TM, but it does support DTP=RM.
2. ** The PREFxxx parameters are used with application programs (PROGRAM=USER) making Adabas calls. They have no effect when specified for an Adabas nucleus.