

Allocate or Deallocate File Space

▶ To allocate or deallocate space for a file

1. Select option "S" (allocate/deallocate file space).
2. Specify the file to be modified.
3. If the file is protected, supply the password.
4. Press ENTER.

The resulting Allocate/Deallocate File Space screen is used to create or remove extents for the address converter, normal index, upper index, and Data Storage of a file. You can specify the allocation in blocks or in cylinders, a starting relative Adabas block number (STARTRABN), and the device where allocated space is to be located.

10:45:12	*****	A D A B A S	BASIC SERVICES	*****	2006-07-20
DBID 105		-	Allocate/Deallocate File Space	-	PFLS002
File Number 200					
File Name TEST-FILE					
Enter Parameters :			Possible values:		
Allocate/Deallocate ... _			(A/D)		
Table Type _			(AC/DS/NI/UI)		
Size					
Blocks or Cylinders ... B			(B/C)		
Start RABN _____					
Device Type _____					
File Password					

This function corresponds to the utility functions ADADBS ALLOCATE and ADADBS DEALLOCATE.

Note:

If an attempt is made to allocate AC beyond MAXISN, Adabas will detect this and only allocate up to MAXISN.

The equivalent direct commands are

ALLOCATE SPACE file-number

DEALLOCATE SPACE file-number