

Configuring Directory Server for Windows XP Personal Firewall

If you have the default Microsoft Windows XP personal firewall enabled on a PC and you would like to install and run the Directory Server on that PC, you will need to allow communications through the firewall on certain ports. You can do this in one of two ways, as described in this chapter:

- Allow Ports for a Specific Executable Program
 - Open a Specific Port
-

Allow Ports for a Specific Executable Program

You can allow a specific executable program to open a port. To do so, issue the following commands:

```
C:\>netsh firewall add allowedprogram program="C:\Program Files\Software AG\Directory Server\xtsdssvcadi.exe"
name="Software AG Directory Server" profile=ALL
```

Program *xtsdssvcadi.exe* is the Windows service file for Directory Server.

To remove the Directory Server as an allowed program, issue the following command:

```
C:\>netsh firewall delete allowedprogram program="C:\Program Files\Software AG\Directory Server\xtsdssvcadi.exe"
profile=ALL
```

Open a Specific Port

To open a specific port for use by the Directory Server in the firewall, issue the following command:

```
C:\>netsh firewall add portopening protocol=TCP port=nnnn
name="Software AG Directory Server" profile=ALL
```

where *nnnn* is the port number you want to open. The default port for the Directory Server is 12731. For more information about Directory Server ports, read *The Directory Server Port Number*.

To close a specific port in the firewall, issue the following command:

```
C:\>netsh firewall delete portopening protocol=TCP port=nnnn profile=ALL
```

where *nnnn* is the port number you want to close.