

# ARXM\* - Event Replicator for Adabas Messages for Event Replicator Target Adapter

## Overview of Messages

ARXML001I | ARXML002I | ARXML003I | ARXML004I | ARXML005S | ARXML006I

---

### **ARXML001I XML TA Exit Startup for *dest-name* - Version *n.n.n.n* Built: *yyyymmdd***

**Explanation** Event Replicator Target Adapter initialization processing for destination *dest-name* has been started. The Event Replicator Target Adapter version (*n.n.n.n*) and the date (*yyyymmdd*) the Event Replicator Target Adapter code was built are also given in the message.

**Action** No action is required for this informational message.

### **ARXML002I XML TA Exit *dest-name* Terminating**

**Explanation** Event Replicator Target Adapter termination processing for destination *dest-name* has been started.

**Action** No action is required for this informational message.

### **ARXML003I Destination *dest-name* now active for *jobname***

**Explanation** Event Replicator Target Adapter processing for destination *dest-name* has been activated. The job name (*jobname*) of the Event Replicator Server is also given in the message.

**Action** No action is required for this informational message.

### **ARXML004I Received *code* event for *dest-name***

**Explanation** Event Replicator Target Adapter processing received the internal event code (*code*) listed in the message for destination *dest-name*.

**Action** No action is required for this informational message.

**ARXML005S Required field table information missing for subscription *subs-name***

**Explanation** Required field table information was missing for subscription *subs-name* during Event Replicator Target Adapter processing. This information is required for building the XML messages used in Event Replicator Target Adapter processing.

**Action** Verify that you have *generated* a global format buffer (GFB) for the subscription. If you do not *generate* a global format buffer using the tools provided in the Adabas Event Replicator Subsystem or in Event Replicator Administration, or if you elect to code a GFB by hand, the required field table information is not constructed for use by the Event Replicator Target Adapter. For more information, read one of the following sections:

- *Generating a GFB using the Adabas Event Replicator Subsystem*
- *Generating a GFB using Event Replicator Administration.*

For more information about correctly activating Event Replicator Target Adapter processing, read *Activating Event Replicator Target Adapter Processing*.

If the problem persists, contact your Software AG support representative.

**ARXML006I Schema generation for *subs-name* triggered**

**Explanation** An internal schema is being generated by Event Replicator Target Adapter, based on the field information provided in subscription *subs-name*. This internal schema maps the replicated data that the Event Replicator Target Adapter then transforms and applies to your relational database.

**Action** No action is required for this informational message.