

Adabas Review

Administration

Version 4.5.1

June 2014

This document applies to Adabas Review Version 4.5.1.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2014 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors..

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://documentation.softwareag.com/legal/>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices and license terms, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". This document is part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

Document ID: REV-ADMIN-451-20140626

Table of Contents

Administrative Functions	v
1 Maintaining User Profiles	1
Accessing the User Profile System	2
Customizing the Default Profile	3
Modifying Access Rules	5
Creating a User Profile	5
Listing User Profiles	6
Editing a User Profile	7
Copying a User Profile	8
Purging a User Profile	8
2 Displaying SVC Lists and Target Objects	9
Using the Adabas Availability Function	10
Creating a Target Definition	14
Listing Target Definitions	17
Editing an Existing Target Definition	18
Deleting a Target Definition	18
3 Defining Adabas Review User Fields	19
Step 1. Setting Parameters	20
Step 2. Modify the REVIEW-ADABAS-Vvrs -CLOG DDM	22
Example of Defining Adabas Review User Fields	23
Index	25

Administrative Functions

This document describes administration tasks for Adabas Review.

This documentation is organized in the following topics:

- | | |
|--|--|
| <i>Maintaining User Profiles</i> | Describes how to maintain user profiles and access the user profile system. |
| <i>Displaying SVC Lists and Target Objects</i> | Describes how maintain the list of SVCs and the target object definitions for Adabas Review. |
| <i>Defining Adabas Review User Fields</i> | Describes how to define custom reporting fields (user fields) in Adabas Review. |

1 Maintaining User Profiles

▪ Accessing the User Profile System	2
▪ Customizing the Default Profile	3
▪ Modifying Access Rules	5
▪ Creating a User Profile	5
▪ Listing User Profiles	6
▪ Editing a User Profile	7
▪ Copying a User Profile	8
▪ Purging a User Profile	8

The user profile system provides a series of menus to help you generate profiles that define access rules for Adabas Review users. You may create profiles for new users, change access rules for existing users, and purge user profiles that are no longer required.

Adabas Review provides a default profile to allow access for users who do not have a profile defined for them. When a user logs on, Adabas Review checks for the user's profile. If one is not found, the default profile is used.

The default profile is also used as a basis for creating user profiles. When a profile for a new user is generated, the default profile is copied. The new profile may then be customized to suit the needs of the user.



Note: The default profile provides unrestricted access to Adabas Review functions. Software AG recommends that you first create a user profile for the system administrator and other privileged users; then modify the default profile so that it conforms to the needs of the majority of users.

Accessing the User Profile System

▶ To access the user profile system

- Enter UP on the command line of the Adabas Review main menu and press ENTER.

The User Profile System menu appears as shown below:

```
22:54:17                A D A B A S - R E V I E W                2009-05-04
                        User Profile System

                        Code                Description
                        ----                -
                        EU                Edit User Profile
                        LU                List User Profiles
                        ----                -

Command: _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
                        Help                Exit                                Menu
```


Code	Description
EU	Edits a profile for a new or existing user.
LU	Displays a list of existing user profiles, including the default profile.

From the list of existing user profiles, you can select a particular profile to be edited or purged.

Customizing the Default Profile

You do not need to create a user profile for each user of Adabas Review. By customizing the default profile so that the access rules meet the needs of the majority of Adabas Review users, you eliminate the need for individual user profiles.

► To customize (edit) the default user profile

- From any screen within Adabas Review, type `UP EU DEFAULT` on the command line and press `ENTER`.

Or:

From any screen within the user profile system, type `EU DEFAULT` on the command line and press `ENTER`.

The following Edit User screen is displayed:

```

22:58:08                A D A B A S - R E V I E W                2009-05-04
                        Edit User

                        User Profile: DEFAULT_
+-----+-----+-----+-----+
! Name ..... DEFAULT PROFILE_____ Default DBID/Hub ..... 15690 !
!                                     Edit Report Definitions ..... Y   !
! Access Adabas Review ..... Y       Edit Target Definitions ..... Y   !
! Access User Profile System .... Y   Purge Historical Data ..... Y   !
! Confirm Purge/Save Requests ... Y   Purge Report Definitions .... Y   !
!                                     Purge Started Reports ..... Y   !
!                                     Purge Target Definitions .... Y   !
!                                     Start Reports ..... Y           !
!                                     Use AOS ..... Y                 !
!                                     View Reports ..... Y           !
+-----+-----+-----+-----+

Command: _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help           Exit           Save                               Menu

```

The User Profile field usually refers to the user ID corresponding to the profile; in this case it contains the word "DEFAULT".

The Name Field

The Name field may be used for the user's name or any other appropriate identifier.

Displaying General Access Rules

The fields in the left column of the Edit User screen are general access rules, which are described as follows (the default value is Y(es) for all fields):

General Access Rule	Value	Whether the user is . . .
Access Adabas Review	<u>Y</u> N	allowed to access Adabas Review.
Access User Profile System	<u>Y</u> N	allowed to access the User Profile System. Before setting this access rule to "N" in the default profile, you must first create a user profile that allows you to access the User Profile System. Otherwise, you will not be able to maintain user profiles.
Confirm Purge/Save Requests	<u>Y</u> N	prompted to confirm a purge or save request before it is executed.

Displaying Database Access Rules

The fields in the right column of the Edit User screen are database access rules. The DBID/Hub field is used to specify the default Adabas Review database for a user:

Database Access Rule	Value	Description
Default DBID/Hub	<i>nnnnn</i> <u>0</u>	Identifies the user's default Adabas Review database. The default value 0 indicates that the file corresponding to LFILE 241 is used.

The remaining fields identify the Adabas Review functions available to a user (the default value is Y(es) for all fields):

Database Access Rule	Value	Whether the user is allowed to . . .
Edit Report Definitions	<u>Y</u> N	use the Edit Report (ER) function.
Edit Target Definitions	<u>Y</u> N	create or edit target definitions.
Purge Historical Data	<u>Y</u> N	delete historical data from the Adabas Review repository.
Purge Report Definitions	<u>Y</u> N	delete report definitions.
Purge Started Reports	<u>Y</u> N	delete data collected by started reports.
Purge Target Definitions	<u>Y</u> N	delete target definitions.
Start Reports	<u>Y</u> N	initiate data accumulation by starting a report.
Use Adabas Online System (AOS)	<u>Y</u> N	use Adabas Online System.
View Reports	<u>Y</u> N	view the results of started reports online.

Modifying Access Rules

▶ **To modify access rules**

- 1 Type over the settings displayed on the screen.
- 2 When you have made all of the changes to a particular group of access rules, do one of the following:

Press PF3 to exit without saving the changes.

Or:

Press PF5 or enter the SAVE command to save the changes.

Creating a User Profile

▶ **To create a user profile**

- 1 From any screen in Adabas Review, type the following string on the command line and press ENTER:

```
UP EU userid
```

Or:

From any screen in the User Profile System, type the following string on the command line and press ENTER:

```
EU userid
```

Adabas Review creates a profile for the user by copying the default profile. It then displays the user profile for editing, and the following message appears at the bottom of the screen:

```
REV00101 - NEW USER PROFILE
```

- 2 Customize the user's profile, as required.

Refer to the section *Customizing the Default Profile* (earlier in this section) for information about access rules.

- 3 When the profile provides appropriate access privileges for the user, press PF5 to save the profile.


```

02:48:34          A D A B A S  -  R E V I E W          2009-06-20
                    User Profiles

  Sel  Userid  Name                               Sel  Userid  Name
+-----+-----+-----+-----+-----+-----+
! ?_   DE  +-----+-----+-----+-----+
!      !   Available Functions  !
!      !   !
!      !   EU  Edit User Profile  !
!      !   PU  Purge User Profile !
!      !   .   Exit                !
!      !   !
!      !   __  Enter Function      !
!      !   !
!      +-----+-----+-----+-----+
!
!
!
!
+-----+-----+-----+-----+

Command: _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help      Exit                +                Menu  ←
←

```

Editing a User Profile

▶ To edit an existing user profile

- Enter the command `EU` on the selection line preceding the profile name and press `ENTER`.

The profile is displayed and may be edited. Refer to the section [Customizing the Default Profile](#) (elsewhere in this section) for additional information.

If you are editing your own user profile, the changes you make take effect as soon as you save your profile. If you are editing a profile other than your own, the changes do not take effect until the next time the user logs on to Adabas Review.

You may also use this command to copy an existing profile for the purpose of creating a profile for a new user. If you have several users who require access privileges that are different from those specified in your default profile, you may use an existing profile as a model for the other profiles.

Copying a User Profile

▶ **To copy a user profile**

- 1 Enter the command EU on the selection line preceding the profile name to be copied.
- 2 Type the new user ID on the line labeled "User Profile".
- 3 Press PF5 to save the new user profile.

Purging a User Profile

▶ **To delete a user profile**

- Enter the command PU on the selection line preceding the profile name and press ENTER.

Depending on the setting in your profile, you may or may not be prompted to confirm the purge request as shown in the following screen:

```

02:50:50                A D A B A S  -  R E V I E W                2009-06-20
                        User Profiles

  Sel  Userid  Name                               Sel  Userid  Name
-----
!  ___  DEFAULT  DEFAULT PROFILE                          !
!  ___  USER1   REVIEW ADMIN                             !
!  ___  USER2   SMITH                               !
!  pu  USER3   JONES                               !
!  ___  USER4   ADAMS                               !
!  ___  USER5   GREENE                               !
!                                     +-----+
!                                     !           !
!                                     ! Please confirm PURGE request for:  !
!                                     !           !
!                                     !           USER3                       !
!                                     !           !
!                                     !           (Y or N) Y                       !
!                                     !           !
!                                     +-----+
!
+-----+

Command: _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help      Exit                               +                               Menu  ←
←
    
```

2 Displaying SVC Lists and Target Objects

▪ Using the Adabas Availability Function	10
▪ Creating a Target Definition	14
▪ Listing Target Definitions	17
▪ Editing an Existing Target Definition	18
▪ Deleting a Target Definition	18

The databases monitored by Adabas Review are considered to be target objects. The monitored databases and the hub are running on an Adabas SVC.

A target object is defined to Adabas Review in a *target definition* using the ET command. A target definition provides Adabas Review with the essential characteristics of the object to be monitored.

Adabas Review uses the target definition of Adabas targets to generate INPUT cards for Adabas Review reports that are autostarted (that is, started automatically when the database is initialized) or run in batch mode.

- If a target definition cannot be found, the INPUT cards are generated using the definition of the default target (that is, target ID 00000).
- If the default target cannot be found, Adabas Review generates the INPUT cards using internal defaults.

Adabas Review provides three commands for SVCs and target objects:

Code	Function	Action
AA	Adabas Availability	Lists target objects for a particular SVC.
ET	Edit Target Definitions	Used to create target definitions.
LT	List Target Definitions	Lists existing target definitions.

Using the Adabas Availability Function

The Adabas Availability (AA) subsystem displays available targets associated with an Adabas supervisor call (SVC). Adabas Review maintains a list of possible SVC numbers as part of its target definition subsystem.



Note: For BS2000 operating systems, this function is not yet available.

This section covers the following topics:

- [Accessing the SVC List](#)
- [Displaying Targets Associated with an SVC](#)

- [Displaying Adabas Nucleus Session Statistics](#)

Accessing the SVC List

▶ To access a list of all the active Adabas SVCs known to Adabas Review:

- Enter the AA code on any command line.

```

02:51:48          A D A B A S - R E V I E W          2009-06-20
                  Available SVCs                    HUB=15690
                  Mark One SVC to be queried with 'X'

   SVC Targs      SVC Targs      SVC Targs      SVC Targs      SVC Targs
+-----+-----+-----+-----+-----+
! _ 201  1        _ 239  0
! _ 203  1        _ 240  0
! _ 205  0        _ 241  0
! _ 214  0        _ 242  0
! _ 220  0        _ 243  1
! _ 227  6        _ 244  0
! _ 229  0        _ 246  0
! _ 232  0        _ 247  0
! _ 233  0        _ 248  1
! _ 235  3        _ 249  7
! _ 236 12        _ 252  1
! _ 237  6        _ 254  0
+-----+-----+-----+-----+

Command: _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help      Exit                                     Menu  ←
↵
    
```

The **Active Adabas SVCs** screen appears, where, for z/OS and z/VSE, the SVC is the supervisor call (SVC) number used for communications with the target object. The number of target objects assigned to that SVC is listed in the associated **Num Targs** field.

Displaying Targets Associated with an SVC

▶ To display a list of all targets known to a particular SVC number:

- Mark an SVC on the **Active Adabas SVCs** screen with an "X", and press ENTER.

The **Available Targets** screen appears, listing targets using the selected SVC for communication. Scroll keys are provided. If more than one screen of objects exists, PF8 (+) scrolls the list forward and PF7 (-) scrolls the list backward.



Note: The list of targets on this screen is the result of a direct query to the SVC and includes inactive targets and non-Adabas databases using that SVC.

```

02:52:52          A D A B A S - R E V I E W          2009-06-20
                  Available Targets                 HUB=15690
                  SVC 227

  DBID   NUCID   Prod   Class   Job Name   Job ID   Date       Time
+-----+-----+-----+-----+-----+-----+-----+-----+
! _  11231   N/A    ADA     I         SCASUPDB  JOB24605  2009-06-16  15:51:55 !
! _  19999   N/A    ADA     I         ATEXXMPM  JOB36900  2009-06-17  20:13:34 !
! _  15640   N/A    ADA     I         SSWSUPDB  JOB57199  2009-06-19  20:15:20 !
! _  7771    N/A    ADA     I         WT1ATA    JOB57290  2009-06-19  20:36:35 !
! _  15690   N/A    REV     I         SSWATAH   JOB57233  2009-06-19  20:18:21 !
! _  15650   N/A    ADA     I         SSWATAN1  JOB57235  2009-06-19  20:18:26 !
!
!
!
!
!
+-----+-----+-----+-----+-----+-----+-----+-----+
Command: _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help      Exit      -      +      Menu  ←
↵
    
```

The following table describes each field on this screen:

Screen Field	Description
Class	The class of the target object. "I" represents an isolated target and "IC" represents an isolated cluster target. For all other targets, the value is blank.
Date	The date on which the target was started.
DBID	The ID of the target object.
Job ID	The ID of the job used to start the target.
Job Name	The name of the startup job for the target.
NUCID	The nucleus ID associated with the target.
Prod	The three-character product code of the target assigned to the SVC.
Time	The time at which the target was started.

Displaying Adabas Nucleus Session Statistics

► To display statistics regarding an Adabas nucleus session:

- 1 Mark an SVC on the **Available SVCs** screen with an "X", and press ENTER.

The **Available Targets** screen appears, listing targets using the SVC for communication. Scroll keys are provided. If more than one screen of objects exists, PF8 (+) scrolls the list forward and PF7 (-) scrolls the list backward.



Note: The list of targets on this screen is the result of a direct query to the SVC and includes inactive targets and non-Adabas databases using that SVC.

- 2 Mark an Adabas database target on the **Available Targets** screen with an "X", and press ENTER.

If a non-Adabas target is selected, an error message appears.

If an Adabas target is selected, the **Adabas Availability** screen appears displaying statistics about the Adabas nucleus session.

```

02:53:49                A D A B A S  -  R E V I E W                2009-06-20
                        ADABAS Availability

  Pool / Queue          Length   MaxUsed   MaxPct          Various Statistics
+-----+-----+-----+-----+-----+-----+-----+-----+
! NAB (Attch Bffr)     65536    31232     47.6 ! ! Dbname          SSW-NATDB !
! NC (Cmd Queue)      38400      192       0.5 ! ! Dbid            15640 !
! LFP (Fmat Pool)     12000    11680     97.3 ! ! SVC              227 !
! NH (HoldQueue)     1400056   2380       0.1 ! ! Commands        147019 !
! LI (ISN Table)      10000       0         0.0 ! ! IOs              105375 !
! LQ (Seq Cmds)       5242880   448        0.0 ! ! Threads           5 !
! NU (UserQueue)      35112     5544     15.7 ! ! Bffr Eff          52.5 !
! LWP (WorkPool)     1048576   67912      6.4 ! ! Bffr Flushes     1291 !
+-----+-----+-----+-----+-----+-----+
! Fmat Overwrites      33 !
  Component    Reads    Writes    ! Fmat Trans       73 !
+-----+-----+-----+-----+-----+
! Asso           1120     7894 ! Thread Sw        293244 !
! Data          17683    45039 ! Threadbacks      0 !
! Work              3     33636 !
+-----+-----+-----+-----+-----+

Command: _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help      Exit                                     Menu ←
  
```

The following table describes the statistics shown on this screen:

Screen Field	Displays
Pool/Queue	The names of the Adabas pools and queues.
Length	The length of the associated Adabas pool or queue.
MaxUsed	The maximum amount used of the associated Adabas pool or queue.
MaxPct	The percentage used of the associated Adabas pool or queue.
Dbname	The name of the database.
Dbid	The number of the database.
SVC	The SVC used to communicate with the database.
Commands	The number of commands processed against the database.
IOs	The number of I/O operations processed against the database.
Threads	The number of threads in use by the database.
Bffr Eff	The buffer efficiency of the database.
Bffr Flushes	The number of buffer flushes performed by the database.
Fmat Overwrites	The number of format overwrites performed by the database.
Fmat Trans	The number of format translations performed by the database.
Thread Sw	The number of thread switches performed by the database.
Throwbacks	The number of throwbacks performed by the database.
Component	The database component: Asso (Associator), Data (Data Storage), Work (Work area)
Reads	The number of reads performed by the associated database component.
Writes	The number of writes performed by the associated database component.

Creating a Target Definition

Target definitions are usually edited by the Adabas Review administrator because changes to database targets affect all users of Adabas Review.

Target definitions can be created, edited, listed, and purged.



Note: When using the online interface to maintain target definitions, only one target entry can be specified for each DBID, even if there are multiple SVCs with the same DBID.

▶ To access the Edit Target screen:

- Enter the ET command on the command line and press ENTER.

The Edit Target screen appears as shown below:

```

02:54:32          A D A B A S - R E V I E W          2009-06-20
                  Edit Target                          HUB=15690

      Database Parameters          Numeric Delimiters
+-----+          +-----+
! Target DBID ....          !      ! Buffers-4K ..... 00200      !
! Target SVC   .... 000      !      ! Buffers-32K ..... 00030      !
! Target Version . 000      !      ! Files (VSE only) . 001      !
+-----+          +-----+

                  Logging Options
+-----+
! Target Name .....                          !
! REVIEW Commands ..... Y          (Y or N)      !
+-----+

Command: _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help      Exit      Save                               Menu ←
←
    
```

The Edit Target screen displays three categories of input fields:

- Database Parameters to describe characteristics of the database;
- Numeric Delimiters to control record and buffer segment sizes; and
- Logging Options.

The Adabas Review intermediate buffer is used as a staging area to pass the command log records between the Adabas Review subtask and the attached Adabas Review processor in local mode, or between the Adabas Review client and server in hub mode. The parameters BUFFERS-4K and BUFFERS-32K in the Adabas Review INPUT statement control the size allocation. The value for these parameters are obtained from the database target definition.

The following table provides more detailed information about the input fields on the Edit Target screen. Default values are underlined.

Database Parameters

Field	Value	Description
Target DBID (required)	<i>nnnn</i>	The database ID of the target object. There is no default value.
Target SVC (required)	<i>nnn</i> <u>000</u>	The number of the SVC used to communicate with the target.
Target Version	<i>nnn</i> <u>000</u>	The version, release, and system maintenance level of the target. For example, for Adabas version 7.4.1, this field would contain the value 741.

Numeric Delimiters

Field	Value	Description
Buffers-4K	<i>nnnn</i>	Defines the number of buffer pool entries that have a length of 4096 or less. This parameter is usually specified along with the BUFFERS-32K parameter. The minimum value is 124.
Buffers-32K	<i>nnnn</i>	Defines the number of buffer pool entries that have a length of 4097 or greater. This parameter is usually specified along with the BUFFERS-4K parameter. The minimum value is 15.
Files (z/VSE only)	<i>nnn</i> <u>001</u>	Specifies the number of command log files to be processed (used for GENCARD).

Logging Options

Field	Value	Description
Target Name	<i>name</i>	The name you use to identify the target database.
Review Commands	<u>Y</u> N	Indicates whether commands issued by Adabas Review should be included in the command processing for all reports. REVIEW-COMMANDS=NO indicates that special Adabas commands for Adabas Review (for example V4 commands) are not used for accounting and monitoring. To suppress RC commands issued from the SYSREVDDB application as well, set the Natural profile ADAPRM parameter ON (ADAPRM=ON). REVIEW-COMMANDS=YES indicates that these commands are used for accounting and monitoring.

Listing Target Definitions

The `List Target Definitions (LT)` command displays the existing target definitions that were created using the `Edit Target (ET)` command.

▶ **To display a list of target definitions**

- Enter the code `LT` on the command line and press `ENTER`.

The Target Definitions screen appears, similar to the one shown below:

```

02:55:24                A D A B A S - R E V I E W                2009-06-20
                        Target Definitions                        HUB=15690

      Sel  DBID      Target Name                Ver      SVC      Review
      ----  ----      -
      +-----+-----+-----+-----+-----+-----+-----+
      !  ___  00000  DEFAULT TARGET                813      227      Y      !
      !  ___  15650  DATABASE-15650                813      227      Y      !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      !                                           !
      +-----+-----+-----+-----+-----+-----+-----+

Command: _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help      Exit      -      +      Menu  ←
      ↵
  
```

The fields on the Target Definitions screen describe the targets as they are defined to the system. The following table describes the fields:

Field	Description
DBID	The database ID of the target object.
Target Name	The name assigned to the target by the user.
Ver	The version, revision, and system maintenance level of the target.
SVC	The number of the SVC used to communicate with the target.
Review Commands	Local mode only. Indicates whether the Adabas Review command processor includes commands issued by the Adabas Review online system in its reports. Used if the Adabas Review processor is running as an Adabas subtask; that is, not in batch.

You may edit or purge target definitions from the Target Definitions screen.

▶ **To display the commands available for use from this screen**

- Enter a ? on the selection line preceding a target definition and press ENTER.

Editing an Existing Target Definition

▶ **To edit an existing target definition:**

- 1 Enter the ET command on the selection line preceding the target definition and press ENTER.
The Edit Target screen for that particular target is displayed.
- 2 Modify the definition by typing over the existing information.
- 3 Either press PF5 or enter SAVE on the command line and press ENTER.

Deleting a Target Definition

Target definitions may be deleted by using the PURGE command.

▶ **To delete a target definition**

- 1 Enter the PT command on the selection line preceding the target definition and press ENTER.
- 2 Depending on your user profile, you may or may not be prompted to confirm the purge request.

3 Defining Adabas Review User Fields

- Step 1. Setting Parameters 20
- Step 2. Modify the REVIEW-ADABAS-Vvrs -CLOG DDM 22
- Example of Defining Adabas Review User Fields 23

The Adabas Review administrator can create up to five custom reporting fields. Portions of the command log and command log extension can be remapped using parameters to specify offsets and data types for these new fields.

▶ **To define custom reporting fields**

- 1 Set parameters to be read at Adabas Review startup.
- 2 Modify the REVIEW-ADABAS-*Vrs*-CLOG DDM to reflect the data types and lengths.

Step 1. Setting Parameters

Field definition parameters are read from the RVUFLD data set.

Sample parameters are provided in member USRPARM in the Adabas Review source library.

Rules of Syntax

```

NAME = USERFLD n
  LEN = length
  INTYPE= { C | B | T }
  OUTTYPE= { C | N | H | T | G }
  OFFSET = offset-into-clog
  DISPLEN = output-data-length
  HEADER = output-field-name
  CALC = { YES | NO }

```

- Each field is defined by a NAME statement followed by field description statements.
- Possible values for the NAME statement are USERFLD1 through USERFLD5.
- NAMES must be coded in ascending order with no gaps; for example, USERFLD2 must be followed by USERFLD3, not USERFLD 4.

Keywords

Parameter	Values	Description
NAME	USERFLD1 through USERFLD5	Field name
LEN	numeric	Length of the field in the Adabas Review internal command log record, LORECR.
INTYPE	C (character) B (binary) T (time)	Format of the data in CLOG or CLEX.
OUTTYPE	C (character) N (numeric) H (hexadecimal) T (time) G (Gregorian date)	Format of the data when printed or displayed.
OFFSET	numeric in decimal, not hex	Offset into the Adabas Review internal command log record, LORECR.
DISPLEN	numeric	Length of the data when printed or displayed.
HEADER	alphanumeric, 8-byte maximum	Name of the field when printed or displayed.
CALC	YES NO	Whether the field can be used for SUM, AVG, PCT, RATE.

Step 2. Modify the REVIEW-ADABAS-Vvrs -CLOG DDM

Each user field definition must be reflected in the DDM.

▶ To modify the DDM

- 1 Enter the Natural SYSDDM facility.
- 2 Edit the DDM

```
REVIEW-ADABAS-Vvrs -CLOG
```

Be sure to place "Y" in the REPLACE field.

- 3 Scan for user fields by entering on the command line

```
SC USER-FIELD
```

- 4 Modify the length and type of the fields

```
USER-FIELDn
```

- 5 Press PF11 to catalog the DDM.

The user fields you have defined are now ready to be used.

▶ To access the new fields either online or in batch

- Use the field names USERFLD1 through USERFLD5 as you would any other Adabas Review reporting field.



Important: Before changing user-defined fields, carefully consider the impact on existing reports and data. For example, if you were to create history data for a particular report that uses USERFLD1 and then you change USERFLD1 to represent different data, incorrect data would be added to the history report the next time the report stored history data.

Example of Defining Adabas Review User Fields

Suppose you wanted to display the last eight characters of the 28-byte communication ID in a user field. You would first determine that communication ID is stored in LORECR field LOX1CMID at offset X'44' or a decimal offset of 68. So the offset of the last eight characters of the communication ID is at decimal offset 88.

The specification for the user field, USERFLD1, would look like this:

```

NAME=USERFLD1
LEN=8
INTYPE=C
OUTTYPE=C
OFFSET=88
*-----*
*      OFFSET=X'58' = last 8 bytes of the communication ID in LORECR *
*-----*
DISPLEN=8
HEADER=LOX1CMID
CALC=NO
    
```

The specification for a report using the user field might look like this:

```

11:50:48                A D A B A S  -  R E V I E W                2009-05-26
                        Edit Report                                LOCL=00204
Detail/Summary: S
Report Name: RVUFLD45 - TEST OF LOX1CMID_____ DBID to Monitor: __204

+-----+
! Field      Order  Sum  Min  Max  Avg  Pct  Rate  Round !
!-----!
! SEQUENCE   _10    -    -    -    -    -    -    _____ !
! DATE_____ _20    -    -    -    -    -    -    _____ !
! TIME_____ _30    -    -    -    -    -    -    _____ !
! CMD_____  _40    -    -    -    -    -    -    _____ !
! USERFLD1  _50    -    -    -    -    -    -    _____ !
    
```

The specification for the DDM might look like this:

```

11:43:22                ***** Edit DDM (ADA) *****                2009-05-26
DDM Name REVIEW-ADABAS-V451-CLOG                               Def.Seq.          DBID  255 FNR  241
Command
I T L DB Name                                     F          Leng S D Remark
-----
S   3 EH USER-FIELD1                               A              8    (1:7)
    
```

The report might look like this:

Defining Adabas Review User Fields

11:49:23 RVUFLD45 - TEST OF LOX1CMID 2009-05-26
11:49:16 2009-05-26 Thru 11:49:23 2009-05-26 LOCL=00204
Page: 1

Sequence	Date	Time	Cmd	LOX1CMID	
4756	2009-05-26	11:49:16	V4	TSU23242	
4757	2009-05-26	11:49:16	V4	TSU23242	
4758	2009-05-26	11:49:16	S1	TSU23242	←

Index

Symbols

? command, 18

A

access rules

- display database, 4
- display general, 4
- modifying, 5

Adabas Availability function, 10

Adabas Review

- administration,
- administration,
 - customizing the default profile, 3
 - maintaining user profiles, 1
- autostarted reports, 10

B

Buffers-32K parameter, 16

Buffers-4K parameter, 16

C

creating target definitions, 14

customizing the default profile, 3

D

default profile, 2, 5

- customizing, 3

E

Edit Target screen, 14

Edit User Profile (EU) option, 3

Entire Net-Work

- as a target object, 10

Entire System Server

- as a target object, 10

ET command, 14, 18

EU command, 3

F

Files parameter, 16

L

List User Profiles (LU) option, 3

listing target definitions, 17

LT command, 17

LU command, 3, 6

M

maintaining user profiles, 1

N

Natural Process

- as a target object, 10

nucleus

- session statistics, 13

P

PT command, 18

R

reports

- autostarted, 10

Review Commands option, 16

S

session statistics, 13

SVCs

- accessing list, 11
- displaying active, 9
- displaying associated target objects, 11

T

Target DBID parameter, 16

target definitions

- creating, 14
- deleting, 18
- editing, 18
- listing, 17

Target Definitions screen, 17

Target Name option, 16

target objects

- creating definitions, 14

- database parameters, 16
 - defined, 10
 - definitions for, 14
 - deleting, 18
 - displaying, 9
 - editing, 18
 - listing, 11, 17
 - logging options, 16
 - numeric delimiters, 16
- Target SVC parameter, 16
- Target Version parameter, 16

U

- UP command, 2
- user fields
 - defining, 19
 - example definition, 23
 - keywords, 21
 - modifying the DDM, 22
 - rules of syntax, 21
 - setting parameters, 20
- user profile system, 2
- user profiles
 - accessing the user profile system, 2
 - available functions, 6
 - copying, 8
 - creating, 5
 - customizing the default, 3
 - editing, 7
 - listing, 6
 - listing commands, 6
 - maintaining, 1
 - modifying access rules, 5
 - purging, 8