

JCL/JCS Requirements and Examples

This section describes the job control information required to run ADAULD with BS2000, z/OS, and z/VSE systems and shows examples of each of the job streams.

This chapter covers the following topics:

- BS2000
- z/OS
- z/VSE

BS2000

Data Set	Link Name	Storage	More Information
Unloaded data	DDOUT1	tape/ disk	Output by ADAULD (see note)
Unloaded data	DDOUT2	tape/ disk	Output by ADAULD (see note)
Unloaded ISNs	DDISN	tape/ disk	Required with DDISN
Save tape	DDSAVE	tape/ disk	Required with SAVETAPE
Sequential PLOG	DDPLOG	tape/ disk	Required for online save tapes
Temp area	DDTEMPR1	disk	Required for online save tapes
Recovery log (RLOG)	DDRLOGR1	disk	Required for ADARAI
ADARUN parameters	SYSDTA/ DDCARD		<i>Operations</i>
ADAULD parameters	SYSDTA/ DDKARTE		
ADARUN messages	SYSOUT/ DDPRINT		<i>Messages and Codes</i>
ADAULD messages	SYSLST/ DDDRUCK		<i>Messages and Codes</i>

Note:

DDOUT1 and DDOUT2 must have the same block size; otherwise, an ADAULD error will occur. DDOUT2 is required only if NUMOUT=2 is specified.

ADAULD JCL Examples (BS2000)

Unload from Database

In SDF Format:

```

/.ADAULD LOGON
/MODIFY-TEST-OPTIONS DUMP=YES
/REMARK *
/REMARK * A D A U L D NON-SAVETAPE FUNCTIONS
/REMARK *
/DELETE-FILE ADAyyyyy.OUT1
/SET-JOB-STEP
/CREATE-FILE ADAyyyyy.OUT1 ,PUB(SPACE=( 480 ,48 ))
/SET-JOB-STEP
/ASS-SYSLST L.ULD
/ASS-SYSDTA *SYSCMD
/SET-FILE-LINK DDLIB,ADAvrs.MOD
/SET-FILE-LINK DDOUT1,ADAyyyyy.OUT1
/START-PROGRAM *M(ADA.MOD,ADARUN) ,PR-MO=ANY
ADARUN PROG=ADAULD,DB=yyyyyy, IDTNAME=ADABAS5B
ADAULD FILE=1, SORTSEQ=AA
/LOGOFF SYS-OUTPUT=DEL

```

In ISP Format:

```

/.ADAULD LOGON
/OPTION MSG=FH,DUMP=YES
/REMARK *
/REMARK * A D A U L D NON-SAVETAPE FUNCTIONS
/REMARK *
/SYSFILE SYSLST=L.ULD
/FILE ADA.MOD ,LINK=DDLIB
/FILE ADAyyyyy.OUT1 ,LINK=DDOUT1 ,SPACE=(480,48)
/EXEC (ADARUN,ADA.MOD)
ADARUN PROG=ADAULD,DB=yyyyyy, IDTNAME=ADABAS5B
ADAULD FILE=1, SORTSEQ=AA
/LOGOFF NOSPOOL

```

Unload from Offline Save Tape

In SDF Format:

```

/.ADAULD LOGON
/MODIFY-TEST-OPTIONS DUMP=YES
/REMARK *
/REMARK * A D A U L D SAVETAPE FUNCTION
/REMARK *
/DELETE-FILE ADAyyyyy.OUT1
/SET-JOB-STEP
/CREATE-FILE ADAyyyyy.OUT1 ,PUB(SPACE=( 480 ,48 ))
/SET-JOB-STEP
/ASS-SYSLST L.ULD
/ASS-SYSDTA *SYSCMD
/SET-FILE-LINK DDLIB,ADAvrs.MOD
/SET-FILE-LINK DDOUT1,ADAyyyyy.OUT1
/SET-FILE-LINK DDSAVE,ADAyyyyy.SAVE
/START-PROGRAM *M(ADA.MOD,ADARUN) ,PR-MO=ANY
ADARUN PROG=ADAULD,DB=yyyyyy, IDTNAME=ADABAS5B
ADAULD FILE=1, SAVETAPE
/LOGOFF SYS-OUTPUT=DEL

```

In ISP Format:

```

/ .ADAULD LOGON
/ OPTION MSG=FH,DUMP=YES
/ REMARK *
/ REMARK * A D A U L D SAVETAPE FUNCTION
/ REMARK *
/ SYSFILE SYSLST=L.ULD
/ FILE ADA.MOD ,LINK=DDLIB
/ FILE ADAyyyy.OUTPUT1 ,LINK=DDOUT1 ,SPACE=(480,48)
/ FILE ADAyyyy.SAVE ,LINK=DDSAVE
/ EXEC (ADARUN,ADA.MOD)
ADARUN PROG=ADAULD,DB=yyyy,IDTNAME=ADABAS5B
ADAULD FILE=1,SAVETAPE
/ LOGOFF NOSPOOL

```

z/OS

Data Set	DD Name	Storage	More Information
Unloaded data	DDOUT1	tape/ disk	Output by ADAULD (see note)
Unloaded data	DDOUT2	tape/ disk	Output by ADAULD (see note)
Unloaded ISNs	DDISN	tape/ disk	Required with DDISN
Save tape	DDSAVE	tape/ disk	Required with SAVETAPE
Sequential PLOG	DDPLOG	tape/ disk	Required for online save tapes
Temp area	DDTEMPR1	disk	Required for online save tapes
Recovery log (RLOG)	DDRLOGR1	disk	Required for ADARAI
ADAULD messages	DDDRUCK	printer	<i>Messages and Codes</i>
ADARUN messages	DDPRINT	printer	<i>Messages and Codes</i>
ADARUN parameters	DDCARD	reader	<i>Operations</i>
ADAULD parameters	DDKARTE	reader	

Note:

DDOUT1 and DDOUT2 must have the same block size; otherwise, an ADAULD error will occur. DDOUT2 is required only if NUMOUT=2 is specified.

ADAULD JCL Examples (z/OS)

Unload a File

```
//ADAULD    JOB
//*
//*    ADAULD:
//*        UNLOAD A FILE
//*
//ULD       EXEC PGM=ADARUN
//STEPLIB  DD   DISP=SHR,DSN=ADABAS.ADAvrs.LOAD          <=== ADABAS LOAD
//*
//DDASSOR1 DD   DISP=SHR,DSN=EXAMPLE.DByyyyy.ASSOR1 <=== ASSO
//DDDATAR1 DD   DISP=SHR,DSN=EXAMPLE.DByyyyy.DATAR1 <=== DATA
//DDWORKR1 DD   DISP=SHR,DSN=EXAMPLE.DByyyyy.WORKR1 <=== WORK
//DDDRUCK  DD   SYSOUT=X
//DDPRINT  DD   SYSOUT=X
//SYSUDUMP DD   SYSOUT=X

//DDOUT1   DD
DISP=(,CATLG),DSN=EXAMPLE.DByyyyy.OUT1,UNIT=DISK, <===
//          VOL=SER=DISK01,SPACE=(TRK,(200,10),RLSE)
//DDCARD   DD   *
ADARUN PROG=ADAULD,MODE=MULTI,SVC=xxx,DEVICE=dddd,DBID=yyyyy
/*
//DDKARTE  DD   *
ADAULD FILE=1, SORTSEQ=AA

00000100
/*
```

Refer to ADAULD in the JOBS data set for this example.

Unload a File from Save Tape Created Offline

```
//ADAULDS   JOB
//*
//*    ADAULD:
//*        UNLOAD A FILE FROM AN OFFLINE SAVE TAPE
//*
//ULD       EXEC PGM=ADARUN
//STEPLIB  DD   DISP=SHR,DSN=ADABAS.ADAvrs.LOAD          <=== ADABAS LOAD
//*
//DDASSOR1 DD   DISP=SHR,DSN=EXAMPLE.DByyyyy.ASSOR1 <=== ASSO
//DDDATAR1 DD   DISP=SHR,DSN=EXAMPLE.DByyyyy.DATAR1 <=== DATA
//DDWORKR1 DD   DISP=SHR,DSN=EXAMPLE.DByyyyy.WORKR1 <=== WORK
//DDSAVE   DD   DISP=SHR,DSN=EXAMPLE.DByyyyy.SAVE        <=== SAVE DATASET
//DDDRUCK  DD   SYSOUT=X
//DDPRINT  DD   SYSOUT=X
//SYSUDUMP DD   SYSOUT=X
//DDOUT1   DD   DISP=(,CATLG),DSN=EXAMPLE.DByyyyy.OUT1,UNIT=DISK, <===
//          VOL=SER=DISK01,SPACE=(TRK,(200,10),RLSE)
//DDCARD   DD   *
ADARUN PROG=ADAULD,MODE=MULTI,SVC=xxx,DEVICE=dddd,DBID=yyyyy
/*
//DDKARTE  DD   *
ADAULD FILE=1,SAVETAPE

00000100
/*
```

Refer to ADAULDS in the JOBS data set for this example.

z/VSE

File	Symbolic Name	Storage	Logical Unit	More Information
Unloaded data	OUT1	tape disk	SYS010 see note 1	Output by ADAULD (see note 2)
Unloaded data	OUT2	tape disk	SYS011 see note 1	Output by ADAULD (see note 2)
Unloaded ISNs	ISN	tape disk	SYS012 see note 1	Required with DDISN
Save tape	SAVE	tape disk	SYS013 see note 1	Required with SAVETAPE
Sequential PLOG	PLOG	tape disk	SYS014 see note 1	Required for online save tapes
Temp area	TEMPR1	disk	see note 1	Required for online save tapes
Recovery log (RLOG)	RLOGR1	disk	see note 1	Required for ADARAI
Messages	SYSLST	printer		<i>Messages and Codes</i>
ADARUN parameters	SYSRDR CRD	reader/ tape/ disk		<i>Operations</i>
ADAULD parameters	SYSIPT	reader		

Notes:

1. Any programmer logical unit can be used.
2. OUT1 and OUT2 must have the same block size; otherwise, an ADAULD error will occur. OUT2 is required only if NUMOUT=2 is specified.

ADAULD JCS Examples (z/VSE)

See *Library and File Procedures for z/VSE Examples* for descriptions of the z/VSE procedures (PROCs).

Unload a File from a Database

```
* $$ JOB JNM=ADAULD,CLASS=A,DISP=D
* $$ LST CLASS=A,DISP=D
```

```
// JOB ADAULD
*          UNLOAD A FILE
```

```

// EXEC PROC=ADAVvLIB
// EXEC PROC=ADAVvFIL
// ASSGN SYS004,DISK,VOL=vvvvvv,SHR
// DLBL OUT1,'EXAMPLE.ADA99.OUT1'
// EXTENT SYS004,,,,ssss,nnnn
// EXEC ADARUN,SIZE=ADARUN
ADARUN PROG=ADAULD,MODE=MULTI,SVC=xxx,DEVICE=dddd,DBID=yyyyy
/*
ADAULD FILE=1, SORTSEQ=AA
/*
/&
* $$ EOJ

```

Refer to member ADAULD.X for this example.

Unload a File from Save Tape Created Offline

```

* $$ JOB JNM=ADAULDS,CLASS=A,DISP=D
* $$ LST CLASS=A,DISP=D
// JOB ADAULDS
*          UNLOAD A FILE FROM AN OFFLINE SAVE TAPE
// EXEC PROC=ADAVvLIB
// EXEC PROC=ADAVvFIL
// ASSGN SYS004,DISK,VOL=vvvvvv,SHR
// DLBL OUT1,'EXAMPLE.ADA99.OUT1'
// EXTENT SYS004,,,,ssss,nnnn
// ASSGN SYS013,TAPE
// PAUSE MOUNT LOAD SAVE FILE ON TAPE cuu
// TLBL SAVE,'EXAMPLE.DByyyyy.SAVE'
// EXEC ADARUN,SIZE=ADARUN
ADARUN PROG=ADAULD,MODE=MULTI,SVC=xxx,DEVICE=dddd,DBID=yyyyy
/*
ADAULD FILE=1,SAVETAPE
/*
/&
* $$ EOJ

```

Refer to member ADAULDS.X for this example.