

Nucleus Startup Error Messages

This section describes error messages and response codes issued by the Adabas nucleus. These errors may occur during nucleus startup, usually as the result of an ADARUN parameter error. The nucleus prints an error message and then terminates with an abnormal end (abend) code of 20 (see the abend code descriptions).

Refer to the Adabas Operations documentation for a description of the ADARUN parameters.

These error messages have the following format:

```
PARM-ERROR nnn [detected during system open]
```

-where "nnn" is one of the startup errors and has the corresponding meaning described here. The error message may be followed by a brief error description.

Overview of Messages

PARM-ERROR 1	PARM-ERROR 2	PARM-ERROR 3	PARM-ERROR 4
PARM-ERROR 5	PARM-ERROR 6	PARM-ERROR 7	PARM-ERROR 8
PARM-ERROR 9	PARM-ERROR 10	PARM-ERROR 11	PARM-ERROR 12
PARM-ERROR 13	PARM-ERROR 14	PARM-ERROR 15	PARM-ERROR 16
PARM-ERROR 17	PARM-ERROR 18	PARM-ERROR 19	PARM-ERROR 20
PARM-ERROR 21	PARM-ERROR 22	PARM-ERROR 23	PARM-ERROR 24
PARM-ERROR 25	PARM-ERROR 26	PARM-ERROR 27	PARM-ERROR 28
PARM-ERROR 29	PARM-ERROR 30	PARM-ERROR 31	PARM-ERROR 32
PARM-ERROR 33	PARM-ERROR 34	PARM-ERROR 35	PARM-ERROR 36
PARM-ERROR 37	PARM-ERROR 38	PARM-ERROR 39	PARM-ERROR 40
PARM-ERROR 41	PARM-ERROR 42	PARM-ERROR 43	PARM-ERROR 44
PARM-ERROR 45	PARM-ERROR 46	PARM-ERROR 47	PARM-ERROR 48
PARM-ERROR 49	PARM-ERROR 50	PARM-ERROR 51	PARM-ERROR 52
PARM-ERROR 53	PARM-ERROR 54	PARM-ERROR 55	PARM-ERROR 56
PARM-ERROR 57	PARM-ERROR 58	PARM-ERROR 59	PARM-ERROR 60
PARM-ERROR 61	PARM-ERROR 62	PARM-ERROR 63	PARM-ERROR 64
PARM-ERROR 65	PARM-ERROR 66	PARM-ERROR 67	PARM-ERROR 68
PARM-ERROR 69	PARM-ERROR 70	PARM-ERROR 71	PARM-ERROR 72
PARM-ERROR 73	PARM-ERROR 74	PARM-ERROR 75	PARM-ERROR 76
PARM-ERROR 77	PARM-ERROR 78	PARM-ERROR 79	PARM-ERROR 80
PARM-ERROR 81	PARM-ERROR 82	PARM-ERROR 83	PARM-ERROR 84
PARM-ERROR 85	PARM-ERROR 86	PARM-ERROR 87	PARM-ERROR 88
PARM-ERROR 90	PARM-ERROR 91	PARM-ERROR 92	PARM-ERROR 93
PARM-ERROR 94	PARM-ERROR 95	PARM-ERROR 96	PARM-ERROR 97
PARM-ERROR 98	PARM-ERROR 99	PARM-ERROR 100	PARM-ERROR 101
PARM-ERROR 102	PARM-ERROR 103	PARM-ERROR 104	PARM-ERROR 105
PARM-ERROR 106	PARM-ERROR 107	PARM-ERROR 109	PARM-ERROR 110
PARM-ERROR 111			

PARM-ERROR**1**

Explanation The Associator data set(s) could not be opened or an error occurred during processing of the GCBs:

- invalid or incorrect DEVICE parameter;
- missing or invalid JCL or data sets for ASSO;
- mismatching database ID; or
- missing checkpoint file.

This error may result from a data set not located on a cylinder boundary.

Action For single-user mode, the appropriate Adabas job control statements must be specified.

PARM-ERROR**2**

Explanation Data Storage data set(s) could not be opened. This probably indicates missing or invalid JCL or data sets for DATA.

Action For single-user mode, the appropriate Adabas job control statements must be specified.

PARM-ERROR**3**

Explanation The Work data set could not be opened, or the last Work block was not readable. This probably indicates invalid DD/WORKR1 JCL or data set, or a data set not located on a cylinder boundary.

Action For single-user mode, the appropriate Adabas job control statements must be specified.

PARM-ERROR**4**

Explanation The value of the ADARUN statement's number of threads (NT) parameter is invalid. The allowed range is from 4 to 250.

PARM-ERROR**5**

Explanation The value of the ADARUN statement's number of hold queue elements (NH) parameter is invalid. The allowed range is from 20 to 16,777,215.

PARM-ERROR**6**

Explanation The value of the ADARUN statement's user queue element count (NU) parameter is invalid. The allowed range is from 20 to 16,777,215.

PARM-ERROR**7**

Explanation The value of the ADARUN statement's user ISN hold queue count (NISNHQ) is invalid. The allowed maximum is either the NH ADARUN parameter setting or 16,777,215 (whichever is smaller).

PARM-ERROR**8**

Explanation The value of the ADARUN statement's command queue element count (NC) parameter is invalid. The allowed range is from 20 to 32,767.

PARM-ERROR**9**

Explanation The value of the ADARUN statement's Adabas cluster nucleus ID (NUCID) is invalid. The maximum value is 65000.

PARM-ERROR**10**

Explanation The value of the ADARUN statement's ISN list table length (LI) parameter is invalid. The minimum value is 2000.

PARM-ERROR**11**

Explanation The value of the ADARUN statement's sequential command table (LQ) parameter is invalid. The minimum value is 2000.

**PARM-ERROR
12**

Explanation The value of the ADARUN statement's buffer pool length (LBP) parameter is invalid. The minimum value is 80,000.

**PARM-ERROR
13**

Explanation The value of the ADARUN statement's internal format pool (LFP) parameter is invalid. the minimum value is 6000.

**PARM-ERROR
14**

Explanation The value of the ADARUN statement's work pool length (LWP) parameter is invalid. The minimum value is 80,000.

**PARM-ERROR
15**

Explanation The value of the ADARUN statement's sort area length size (LS) parameter is invalid. The allowed range is from 19,968 to (LWP/2) -19,968.

**PARM-ERROR
16**

Explanation The value of the ADARUN statement's security pool length (LCP) parameter is invalid. The allowed range is from 2000 to 16,777,215.

**PARM-ERROR
17**

Explanation If you have Adabas Transaction Manager version 7.4 or earlier installed, the size of Work part 1 (the value of the ADARUN statement's LP parameter) is less than 200 blocks or greater than the Work data set size minus the space required for Work part 2 (the LWKP2 parameter), Work part 3 (minimum of 50 blocks), and, if used, Work part 4 (the LDTP parameter).

If you have Adabas Transaction Manager version 7.5 or later installed, the size of Work part 1 (the value of the ADARUN statement's LP parameter) is less than 200 blocks or greater than the Work data set size minus the space required for Work part 2 (the LWKP2 parameter), and Work part 3 (minimum of 50 blocks).

**PARM-ERROR
18**

Explanation Fewer than 50 blocks are available for Work part 3. Autorestart has been executed.

**PARM-ERROR
19**

Explanation The DBID of the general control blocks (GCBs) and DBID stored on the Work data set do not match. The Work data set contains autorestart information for a different database (DBID).

PARM-ERROR 20

Explanation GETMAIN below the 16MB line failed.

**PARM-ERROR
21**

Explanation The general control blocks (GCBs) contain an invalid device type. The GCBs may have been overwritten, damaged, or otherwise destroyed.

**PARM-ERROR
22**

Explanation An I/O error occurred when writing ASSO. The region is too small. The RABN that was to be written is printed.

PARM-ERROR**23****Explanation**

A nucleus entry already exists in the data integrity block (DIB) for one of the following reasons:

- An attempt was made to start a nucleus while another update nucleus was still active; or
- The previous nucleus session terminated abnormally but the "nucleus" DIB entry was not removed.

Action

If a DIB entry remained after an abnormal termination, rerun the job with the ADARUN IGNDIB=YES parameter. If the FORCE=YES parameter had been applied, then the nucleus must be started with FORCE=YES and IGNDIB=YES. Here the DIB entry will only be removed once the ID Table initialization had been successful. Running with IGNDIB=YES alone will result in a PARM-ERROR 26.

PARM-ERROR**24****Explanation**

An I/O error occurred when reading ASSO. The RABN that was to be read is printed.

PARM-ERROR**25****Explanation**

The Adabas nucleus cannot be started because a conflicting utility DIB entry was found. Either a utility with exclusive database control or an ADASAV (SAVE FILE or SAVE database) job is running.

Action

If an ADASAV SAVE FILE or ADASAV SAVE (database) ended abnormally, the nucleus can be restarted with the ADARUN IGNDIB=YES parameter; however, the save tape cannot be used for future RESTORE operations.

PARM-ERROR**26**

Explanation Interregion communication could not be established.

Action This message should be preceded by message ADAM98. If the ADAM98 error reason is “DUPLICATE ID (LOCAL)” and a previous nucleus ended such that it was not able to clean up, you may wish to restart specifying FORCE=YES. Refer to ADAM98 message documentation for information about other possible errors.

If IGNDIB=YES was specified, then the nucleus must be started with FORCE=YES and IGNDIB=YES. Here the DIB entry will only be removed once the ID Table initialization had been successful. Running with FORCE=YES alone will result in a PARM-ERROR 23.

Note:

Specifying FORCE=YES with the DBID of a currently active nucleus can disrupt operations on that nucleus. In addition, users of the old database whose ID is overwritten by the FORCE=YES option lose access to the database. Therefore, FORCE=YES should only be specified if absolutely necessary. For more information, refer to the FORCE parameter description in the Adabas Operations documentation.

PARM-ERROR**27**

Explanation The ADARUN statement's PLOGRQ parameter is specified as or defaults to YES, FORCE, or SEL, but a protection log and related parameters have not been provided.

PARM-ERROR**28**

Explanation The protection log (PLOG) data set(s) could not be opened, or the last dual or multiple PLOG block was not readable. This is probably due to incorrect PLOG data set definition, specification, or job control statements.

PARM-ERROR 29

Explanation Invalid command log (CLOG) device definition.

PARM-ERROR 30

Explanation FREEMAIN error.

PARM-ERROR 31

Explanation System autorestart error (see the nucleus response code).

PARM-ERROR 32

Explanation Error during buffer flush.

PARM-ERROR 33

Explanation Error during Work initialization.

**PARM-ERROR
34**

Explanation The nucleus is not allowed to start with READONLY=YES when an autorestart is pending.

**PARM-ERROR
35**

Explanation File control block (FCB) check failed. The FCB may have been overwritten or otherwise destroyed.

PARM-ERROR 36

Explanation Timer initialization failed, or operator communication could not be established.

**PARM-ERROR
37**

Explanation GETMAIN in common storage (CSA) failed; interregion communication could not be established. The specific reason is given in a detailed ADAM nn message.

PARM-ERROR 38

Explanation DIB overflow.

**PARM-ERROR
39**

Explanation Work pool is too small for the number of threads.

Action Increase the LWP parameter value to at least 25 kilobytes times the number of threads.

PARM-ERROR 40

Explanation Database version mismatch: the database is not version *version revision-level*.

Action Run the ADACNV utility to bring the database to the correct version.

**PARM-ERROR
41**

Explanation Parallel participant table (PPT) initialization error:

- an I/O error occurred reading or writing a PPT block (RABN); or
- a PPT length error occurred when a bad PPT block was encountered.

1	An error occurred reading the PPT block (RABN) to determine the PLOG entries from the last database session.
2	An error occurred trying to obtain the constant set for the PPT.
3	An error occurred in the PPT verification routine.
4	The PPT area is full; that is, there are already 32 active PPT entries.
5	An error occurred attempting to check for any active PPT blocks.
6	An error occurred while reading the PPT block prior to updating it.
7	A bad file name was detected in the PPT for the Work data set.
8	An error occurred trying to obtain the constant set for the PPT in order to log the Work data set in the PPT for the first time (no previous entry was found in the PPT for the Work data set).
9	A bad file name was detected in the PPT for the Work data set when logging the PPT entry for the first time (no previous entry was found for the Work data set).
10	An error occurred trying to obtain the constant set for the PPT entry in order to override a previous PPT entry.
11	A bad file name was found when attempting to log the PLOGR1 data set in the PPT.
12	A bad file length was found when attempting to compare the new PLOGR1 data set against the old one.
13	A bad file name was found when attempting to log the PLOGR2 data set in the PPT.
14	A bad file length was found when attempting to compare the new PLOGR2 data set against the old one.
15	An error occurred trying to obtain the constant set for the PPT prior to updating the PPT. Either a different PLOG data set was detected or no PLOGs are being used.
16	An error occurred when trying to obtain the constant set for the PPT prior to writing the PPT.
15	An error occurred when attempting to read the PPT block to ensure that no other nucleus is currently using the same PLOG.
18	An error was detected in the PLOG data set name when attempting to compare the current entry against other active entries in the cluster.
20	An internal error occurred attempting to initialize the PPT. Please contact your Adabas support representative supplying the DDPRINT and dump from the current session, a PPTPRINT, and the DDPRINT from the previous session.

PARM-ERROR 42**Explanation**

Error detected during system open:

- error writing PPT RABN; or
- a Work data set was already in use by another nucleus.

**PARM-ERROR
43****Explanation**

Error detected during system open:

- either a PLOG was supplied that was different from the one used in the previous session, or no PLOG was supplied. The PLOG from the previous session has not yet been copied.
- PLOGRQ=FORCE was specified and either the PLOG from the previous session has not yet been copied or a UEX2 or UEX12 has not been specified.

**PARM-ERROR
44****Explanation**

A noncluster nucleus attempted to start after a cluster failure; or, the first cluster nucleus is starting but there are already active blocks in the PPT. The nucleus is not allowed to start. Switching from single-nucleus mode to multi-nucleus cluster mode or from multi-nucleus cluster mode to single-nucleus mode is not allowed after an abnormal session termination.

**PARM-ERROR
45****Explanation**

GETMAIN above the 16MB line failed; memory-related parameters probably too big.

PARM-ERROR 46**Explanation**

UQE could not be generated.

Action

Increase NU parameter.

PARM-ERROR**47**

Explanation An I/O error occurred when reading or writing to the Work data set for one of the following reasons:

- The GCB doesn't match the actual size of the Work data set
- ADARUN LP is larger than the Work data set,
- ADADEF NEWWORK was not run after allocating a new Work data set

The RABN that was to be read or written is printed.

PARM-ERROR 48

Explanation An error occurred during checkpoint generation:

- the takeover of checkpoints generated by offline utilities failed; or
- creation of the session start checkpoint failed.

PARM-ERROR**49**

Explanation An I/O error occurred while reading or writing dual or multiple PLOGs. The RABN that was to be read or written is printed.

PARM-ERROR 50

Explanation Dual or multiple PLOG contains data from another database.

PARM-ERROR 51

Explanation Parameter conflict: READONLY=YES is not permitted with UTIONLY=YES.

PARM-ERROR**52**

Explanation No dual or multiple PLOG available for protection logging. All PLOGs are due to be copied.

**PARM-ERROR
53**

Explanation At least one of the specified PLOG data sets is already in use by another nucleus in the cluster.

**PARM-ERROR
54**

Explanation IGNDIB=YES was specified but the DIB does not contain a conflicting nucleus or utility entry.

Action Remove the IGNDIB parameter.

**PARM-ERROR
55**

Explanation Error while attempting to lock or unlock a global resource. An ADAN54 message preceding this parameter error indicates the specific global resource that could not be locked/unlocked.

**PARM-ERROR
56**

Explanation A DIB entry was found with an inconsistent group name. The associated nucleus may still be active. The DIB entry can be removed only by a nucleus of the same type (single, cluster) and the same CLUGROUPNAME as the DIB entry's owner.

**PARM-ERROR
57**

Explanation DIB entry missing. Another cluster nucleus is already active on this database, but its DIB entry is not present.

**PARM-ERROR
58**

Explanation The Work block size is too small to store the maximum compressed data record permitted in this database according to MAXRECL definition.

Action Increase the Work block length.

PARM-ERROR**59**

Explanation The Work block size is too small for the largest Associator block size present in this database.

PARM-ERROR**60**

Explanation The PLOG block size is too small to store the maximum compressed data record permitted in this database according to MAXRECL definition.

PARM-ERROR**61**

Explanation Important fields in the GCBs changed while this nucleus was starting. The nucleus is not able to handle this situation.

Action Restart the nucleus.

PARM-ERROR 62

Explanation CPU timer initialization failed.

PARM-ERROR**63**

Explanation RRDF=YES is not allowed. Note that the RRDF/ENET option for maintaining shadow databases is currently unavailable for cluster nuclei.

PARM-ERROR**64**

Explanation An attempt was made to start a version 7.2 or above nucleus without first formatting the protection logs (PLOGs). PLOGs must be formatted when converting to version 7.2 or above.

PARM-ERROR**65**

Explanation The ADARUN statement's NSISN parameter value is greater than the allowed maximum of $(\text{Work block size} - 6) / 4$.

PARM-ERROR**66**

Explanation The ADARUN statement's LU parameter specifies a value greater than the byte count implied by the NAB (number of attached buffers) parameter. The error was detected during open operation.

PARM-ERROR**67**

Explanation Initialization failed for DTP=RM or DTP=TM either because of conflicts in the DTP (distributed transaction processing) ADARUN parameter settings (perhaps with the MODE, READONLY, or LOCAL parameter settings as well) or because of problems with the DDWORKR4/WORKR4 data set used in transaction management. For more information, read about the DTP ADARUN parameter in the *Adabas Operations Manual* and the DDWORKR4/WORKR4 data set in *Adabas DBA Tasks*.

Action Review the message(s) that precede this parameter error to determine the cause and resolution of the problem.

PARM-ERROR**68**

Explanation If you have Adabas Transaction Manager version 7.4 or earlier installed, an invalid parameter was specified with DTP=TM:

- single user mode (MODE=SINGLE) is not allowed.
- LOCAL=YES is not allowed.
- READONLY=YES is not allowed.
- LDTP (Work part 4) specified with a nonzero value is not allowed.

If it is necessary for some reason to hold data about incomplete transactions in the TM, LDTP with a nonzero value can be specified but IGNDTP=YES must also be specified. The IGNDTP parameter is for emergency use only and should only be used in consultation with your Software AG technical support representative.

**Warning:**

Whenever the data on Work part 4 is ignored, the integrity of the incomplete global transactions that are related to that data cannot be guaranteed.

If you have Adabas Transaction Manager version 7.5 or later installed, an invalid parameter was specified with DTP=TM:

- single user mode (MODE=SINGLE) is not allowed.
- LOCAL=YES is not allowed.
- READONLY=YES is not allowed.

PARM-ERROR 69

Explanation The value specified for the DTP parameter is invalid.

Action Specify "RM" or "TM" or "NO".

PARM-ERROR 70

Explanation Error during generation of predefined formats:

- Reading system-file FCB or FDT failed;
- Translating internal format failed; or
- Pool for system-internal formats is too small.

**PARM-ERROR
71****Explanation**

If you have Adabas Transaction Manager version 7.4 or earlier installed, an invalid parameter was specified with NUCID:

- MODE=SINGLE is not allowed.
- READONLY=YES is not allowed.
- LFIOP must be nonzero.
- If protection logs are used, dual or multiple PLOGs must be specified.
- MXMSG must be between 1 and 32767.
- NUCID must not equal UBID.

If you have Adabas Transaction Manager version 7.5 or later installed, an invalid parameter was specified with NUCID:

- MODE=SINGLE is not allowed.
- READONLY=YES is not allowed.
- LFIOP must be nonzero.
- If protection logs are used, dual or multiple PLOGs must be specified.
- MXMSG must be between 1 and 32767.
- NUCID must not equal UBID.

PARM-ERROR 72**Explanation**

Initialization of recovery logging failed.

**PARM-ERROR
73****Explanation**

Response code 75 (ADARSP075) or 77 (ADARSP077) was received because the checkpoint file is full. Checkpoints from offline utilities may have been lost.

Action

Start the nucleus with UTIONLY=YES and reorder/increase the checkpoint file.

PARM-ERROR**74**

Explanation The database will not start until the PLOG data sets have been copied or reformatted. Most likely, the database was restored and the PLOG data sets had not yet been copied. They still may be needed for the regenerate function.

Action If the contents of the PLOG data sets are needed for a possible future regenerate function, run ADARES PLCOPY to copy them off. If the PLOGs are not needed, reformat them using the ADAFRM PLOGFRM function. In either case, start the nucleus after freeing the PLOG data sets.

PARM-ERROR**75**

Explanation The nucleus cannot run with the recovery log (RLOG) feature if it runs without PLOG or if PLOGRQ=SEL is specified. The protection log (PLOG) data set is not available; that is, PLOGRQ=SEL or PLOGRQ=NO is specified.

PARM-ERROR**76**

Explanation The nucleus was started with DTP=TM or DTP=NO, but Work Part 4 contains data about in-doubt transactions.

Action Start the nucleus with DTP=RM.

PARM-ERROR**77**

Explanation Machine clock (STCK) problem. The system was IPLed with the clock not set and running or set to an invalid date.

Action Correct the date (timestamp) and restart the nucleus.

PARM-ERROR**78**

Explanation Work part 2 has become too small because Work part 4 contains two-phase commit data that must be retained.

PARM-ERROR 79

Explanation The ENET user exit 10 is missing.

**PARM-ERROR
80**

Explanation ADACLU initialization failed and the nucleus terminated. A preceding PLX nnn message from ADACLU provided more detailed information.

Action Refer to the explanation and action of the preceding PLX nnn message.

**PARM-ERROR
81**

Explanation A read-only (READONLY=YES) or single-user (MODE=SINGLE) nucleus cannot start if DTP=RM is specified.

**PARM-ERROR
82**

Explanation During session open, the system detected that a Delta Save logging (DLOG) area was installed but parameter DSF was not set to YES. DSF=YES must be specified to run with the Delta Save Facility.

Action Restart the nucleus with parameter DSF=YES.

Alternatively, restart the nucleus with parameter DSF=NO; the nucleus then removes the DLOG area and runs in non-Delta Save mode.

**Warning:**

After switching to non-Delta Save mode, it is not longer possible to perform delta save operations.

**PARM-ERROR
83**

Explanation Initialization of the Delta Save Facility failed. A preceding Delta Save operator message indicates the cause of the failure.

Action Check messages from ADADSF.

**PARM-ERROR
84**

Explanation The DSF logging area could not be removed. Another Adabas cluster nucleus is already running with Delta Save Facility active.

Action Start the nucleus with DSF=YES.

**PARM-ERROR
85**

Explanation The previous nucleus session terminated with Work overflow. The nucleus has no free space on Work part 1 for protection information that will be produced during session autorestart.

Action In a cluster environment (Adabas Cluster Services or Parallel Services), start a different cluster nucleus (possibly a new one) with sufficient free space on Work part 1. In a non-cluster environment (base Adabas), restore and regenerate the database.

PARM-ERROR 86

Explanation VOL-SER table could not be established.

PARM-ERROR 87

Explanation Entire Conversion Services (ECS) initialization failed.

**PARM-ERROR
88**

Explanation A database that uses Universal Encoding Support (UES) needs a version 7 or above Adabas router. If the database uses UES features, it cannot work with an Adabas router (ADASVC) version 6.2 or below.

Action Install a version 7.1 or above router (ADASVC).

**PARM-ERROR
90**

Explanation Invalid ADATCP configuration or UES=NO. Running with TCPIP=YES requires universal encoding support.

Action Check and correct, if necessary, the TCPURL parameter. Install UES and specify UES=YES.

**PARM-ERROR
91**

Explanation Adabas cluster initialization failed. Either the program was not running authorized or the GETMAIN failed.

Action Ensure that the program is APF-authorized. Review the space requirements for your system. If you are unable to determine the problem, contact your Software AG technical support representative.

**PARM-ERROR
92**

Explanation During session open, an attempt to join the Adabas cluster communication group failed. This error initializing the Adabas cluster messaging service is preceded by other messages explaining the specific error.

**PARM-ERROR
93**

Explanation Connect to lock structure failed.

Action Review the lock structure definition requirements. If you are unable to determine the problem, contact your Software AG technical support representative.

**PARM-ERROR
94**

Explanation Connect to cache structure failed.

Action Review the cache structure definition requirements. If you are unable to determine the problem, contact your Software AG technical support representative.

**PARM-ERROR
95**

Explanation Communication with other active Adabas cluster nuclei failed.

Action Review the requirements for communication between cluster nuclei running on the same operating system image and between operating system images running members of the cluster. If you are unable to determine the problem, contact your Software AG technical support representative.

**PARM-ERROR
96**

Explanation Inconsistent structure name. Another Adabas cluster nucleus is already running with a different CLUCACHENAME or CLULOCKNAME parameter.

Action Ensure that all nuclei in a sysplex cluster use the same coupling facility cache and lock structure names.

**PARM-ERROR
97**

Explanation Incompatible global parameters. Another Adabas cluster nucleus is already running with incompatible global parameters that cannot be modified online.

Action Reset nonmodifiable global ADARUN parameters the same for all cluster nuclei. You may be required to stop nuclei, change the parameter settings, and restart.

PARM-ERROR 98

Explanation Locking/unlocking an Adabas cluster resource failed.

Action Contact your Software AG technical support representative.

PARM-ERROR 99

Explanation Internal error.

Action Contact your Software AG technical support representative.

PARM-ERROR 100 –

Explanation There are more than 31 nuclei in an Adabas Parallel Services cluster; this is not allowed.

Action Reconfigure your Adabas Parallel Services cluster so that you have 31 or fewer participating Adabas nuclei.

PARM-ERROR 101 –

Explanation Invalid parameters specified with CLOGMRG=YES; LOGGING=YES is required; dual or multiple CLOGs are required.

Action Specify the correct ADARUN parameters and restart the session.

PARM-ERROR 102 –

Explanation A cluster nucleus was started after abnormal termination with a different WORK data set. The PPT indicates that the previously used WORK data set still contains data, but this Cluster Service or Parallel Service nucleus was started with a different WORK data set.

Action Restart the cluster nucleus with the previously used WORK data set. Change the WORK data set only after normal termination.

PARM-ERROR 103 –

Explanation Incompatible usage of dual PLOG data sets.

If the first active nucleus uses PLOG data sets, all subsequent nuclei *must* use PLOG data sets. If the first active nucleus does not use PLOG data sets, all subsequent nuclei *must not* use PLOG data sets.

PARM-ERROR 104 –

Explanation Incompatible usage of UEX2 or UEX12.

If the first active nucleus uses either UEX2 or UEX12, all subsequent nuclei *must* use either UEX2 or UEX12. If the first active nucleus does not use UEX2 or UEX12, all subsequent nuclei *must not* use UEX2 or UEX12.

PARM-ERROR 105 –

Explanation Improper configuration of Global Resource Serialization (GRS). A resource lock acquired by this nucleus was ineffective against a peer nucleus.

Action Contact your system programmer to ensure that GRS is configured in a way that GRS resource locks are mutually effective against one another on all systems on which you intend to run Cluster Services nuclei.

PARM-ERROR 106 –

Explanation When LOCAL=YES is specified, all cluster nuclei for a database must start on the same system.

Action If LOCAL=YES is the intended parameter setting, start all cluster nuclei for the database on the same system. Otherwise, change the parameter setting to LOCAL=NO.

PARM-ERROR 107 – Replication initialization error

Explanation An error occurred during initialization of replication. Refer to the messages preceding Parm-Error 107 to determine what action to take.

Action Correct the condition specified in the message(s) displayed before Parm-Error 107 and restart initialization of replication.

If the replication definitions are stored on the Replicator system file and a change must be made to the Event Replicator Server definitions, complete the following steps:

1. Temporarily set the ADARUN parameter RPLPARMS to NONE.
2. Start the Event Replicator Server.
3. Make the related changes to the replication definitions in the Replicator system file.
4. Shut down the Event Replicator Server.
5. Change the ADARUN parameter RPLPARMS back to its original value.
6. Start the Event Replicator Server.

PARM-ERROR 109 –

Explanation The Adabas nucleus tried to load a valid license module (load module ADALIC), but errors occurred. Other error messages providing more information about the error accompany this nucleus startup error

Action Verify that you have received a valid Adabas license (via the installation media) and that it was installed correctly, according to the Adabas database installation steps specific to your operating environment. If problems persist, contact your Software AG technical support representative for assistance.

PARM-ERROR 110 –

Explanation An error occurred when the Adabas nucleus called a hyperdescriptor exit for initialization.

Action Investigate the response code and subcode to determine the reason for the error.

PARM-ERROR 111 –

Explanation A parameter value for cluster nuclei is invalid:

- MXCANCEL must be between 15 and 2,147,483,647 seconds.
- MXCANCELWARN must be zero (0) or between 4 and (MXCANCEL–1) seconds.
- MXMSG must be between 15 and 32,767 seconds.
- MXMSGWARN must be zero (0) or between 4 and (MXMSG–1) seconds.
- MXSTATUS must be zero (0) or between 15 and 21,474,836 seconds.
- MXWTOR must be zero (0) or between 15 and 64,800 seconds.

Action Correct the invalid parameter value to one of the valid values listed above.