## Adding a Managed Node

Using the System Management Hub (SMH), add appropriate managed nodes for your installation. You can only add managed nodes for Entire Net-Work 7 Kernels or for Entire Net-Work 5 nodes with the Simple Connection Line Driver installed. Managing classic Entire Net-Work installations (Entire Net-Work Versions 2 and 3, or mainframe Version 5 without the Simple Connection Line Driver) is not possible using the System Management Hub.

## Note:

Only limited functionality is provided in SMH for Entire Net-Work 5 managed nodes. You can only display information about such nodes at this time.

## **b** To add a managed node:

Make sure you have accessed the System Management Hub.

1. Select Entire Net-Work from the list of managed hosts.

The list of currently managed nodes appears.

2. Click on the Add Managed Net-Work Node command in the command frame of SMH.

The Add Managed Net-Work Node panel appears in the detail-view frame.

📥 Managed Hosts ⊡ 🗊 host.address.1	Add Managed Net-Work Node
🗉 🕱 Administrators	Select type of node:
🗉 🜻 Directory Server	• Version 5 mainframe node
🗉 🗗 Entire Net-Work	C ∨ersion 7 node
🗄 😽 System Management Hub	
	Enter Entire Net-Work node name, case sensitive for ∨7 node:
Add Managed Net-Work Node	
Help	
Refresh	Enter Entire Net-Work host name or TCP/IP address:
	Enter port number:
	8010
	OK Cancel Help

3. Select the type of Entire Net-Work node you want to add. Click either the Version 5 mainframe node or the Version 7 node selections.

4. Specify the Entire Net-Work node name, as described in the following table.

Entire Net-Work Node Version	Description
Version 5	This is the node name specified on the Entire Net-Work NODE statement.
Version 7	By default, this is the host name of the Windows workstation machine. Remember that node names for Entire Net-Work Version 7 nodes are case-sensitive.

5. Specify the Entire Net-Work host name or TCP/IP address. This is the host name or TCP/IP address of the machine where Entire Net-Work runs. (For Entire Net-Work 7, the host name and the node name should be the same.)

If you specify a host name, the machine on which SMH is running must be able to resolve the host name to a TCP/IP address. The name may also include a fully qualified domain name.

6. Enter the port number of the port where the Entire Net-Work node listens for SMH requests,. This value must be an unused port number between 1 and 65535; it defaults to **8010**.

Entire Net-Work Node Version	Description
Version 5	This is the same as the value of the SERVERID parameter on the SMH DRIVER statement.
Version 7	This is the same as the Central Administration port specified during the Entire Net-Work installation procedure.

## 7. Click OK.

The new managed node is added to the list of Entire Net-Work nodes.