

ADARUN Statement/Parameter Messages

The Adabas ADARUN statements and parameters define the nucleus operating environment. The error messages that can result from ADARUN statements and parameters are described in this section. These messages have the following format:

```
ADARUN error-nn,message-text
```

where *nn* is the message number and *message-text* describes the error. All ADARUN error messages are accompanied by a user abend 35 (abnormal end without a dump) code.

For information regarding ADARUN parameter syntax, refer to the Adabas operations documentation.

Overview of Messages

```
error-1 | error-2 | error-3 | error-5 | error-6 | error-7 | error-8 |
error-9 | error-10 | error-12 | error-13 | error-20 | error-21 |
error-22 | error-23 | error-24 | error-25 | error-26 | error-31 |
error-32 | error-33 | error-34 | error-98 | error-99 | error-140 |
WARNING 26 | WARNING 27 | WARNING 28
```

error-1 **I/O-error DDCARD**

Explanation A job control (JCL/JCS) error occurred.

Action Correct the error and rerun the job.

error-2 **Unknown module**

Explanation Either the ADARUN PROG parameter or the library allocation JCL is incorrect.

Action Correct the error and rerun the job.

error-3 **Invalid parmcard**

Explanation An ADARUN parameter statement is missing the literal "ADARUN" at the beginning of the ADARUN statement.

Action Correct the error and rerun the job.

error-5 Invalid parm

Explanation One of the following has occurred:

- The starting position of a keyword is either lower than "A" or higher than "Z".
- Positions 1-72 contain no valid parameters.

Action Correct the error and rerun the job.

error-6 Syntax error

Explanation ADARUN detected invalid parameter syntax.

Action Correct the error and rerun the job.

error-7 Unknown keyword

Explanation ADARUN detected an invalid keyword parameter.

Action Correct the error and rerun the job.

error-8 Error from load

Action ADARUN detected a nonzero return code from the operating system's load function.

Action Refer to any related ADAInn or other messages for the specific return code value, then refer to the appropriate operating system information for the action to take.

error-9 No user program

Explanation ADARUN was not called by a user program, or required ADARUN parameters were missing.

Action Correct the JCL or control statements and rerun the job.

error-10 Module = non-XS

Explanation BS2000 only. ADARUN was loaded from the XS library. During the loading procedure, the specified non-XS module was deleted.

Action Do not mix XS and non-XS libraries.

- error-12** **Invalid CMDQMODE = operand (above, below)**
- Explanation** BS2000 only. The CMDQMODE parameter specified an incorrect syntax option.
- Action** Job terminates. Set the correct parameter value.
-
- error-13** **Invalid TAPEREL = operand (NO, RELEASE, KEEP, UNLOAD, KEEPUNL)**
- Explanation** BS2000 only. The TAPEREL parameter specified an incorrect syntax option.
- Action** Job terminates. Set the correct parameter value.
-
- error-20** **RMODE error**
- Explanation** ADARUN detected one or more loaded modules linked with RMODE={ANY | 31} while it runs in AMODE=24.
- Action** Check the load library and either relink modules linked with AMODE=24 to AMODE={ANY | 31}, or relink modules linked with RMODE=ANY to RMODE=24.
-
- error-21** **CLU parm error**
- Explanation** ADARUN detected inconsistent CLUSTER parameter:
- CLUSTER=SYSPLEX or CLUSTER=LOCAL and NUCID=0; or
 - CLUSTER=NO (default) but NUCID is nonzero.
- Action** Correct the error and rerun the job.
-
- error-22** **NXLOG error**
- Explanation** ADARUN detected inconsistent parameter:
- Both NPLOG/NCLOG and DUALPLD/DUALCLD are specified; or
 - PPLOGDEV/CLOGDEV and PLOGSIZE/CLOGSIZE are specified but NPLOG/NCLOG is not specified; or
 - UEX2 together with NPLOG/NCLOG instead of UEX12 was found in the ADARUN parameters.
 - The CLOGMAX or CLOGBMAX parameter setting is smaller than 368 bytes.
- Action** Correct the error and rerun the job.

error-23 RPL PARM error

Explanation ADARUN detected an inconsistent replication parameter.

- RPLPARMS was not "PARMS", "FILE", "BOTH", or "NONE".
- RPWARNPERCENT was not in the range 0 to 99.
- RPWARNINCREMENT was not in the range 0 to 99.
- RPLSORT was not "YES", "NO", or "LAST".

Action Correct the error and rerun the job.

error-24 CLOG PARM error

Explanation ADARUN detected an inconsistent command logging parameter:

- CLOGLAYOUT was not 5 nor 8.
- LOGABDX was not YES nor NO.
- LOGUB was not YES nor NO.
- LOGMB was not YES nor NO.

Action Correct the error and rerun the job.

error-25 REV PARM error

Explanation ADARUN detected an inconsistent Adabas Review parameter:

- REVFILTER was not YES nor NO.
- REVLOGMAX was not in the range 2000 through 32768.
- REVLOGBMAX exceeded 32768.

Action Correct the error and rerun the job.

error-26 Parameter V64BIT is invalid

Explanation One or more of the following errors occurred when the V64BIT ADARUN parameter was specified:

- The ADARUN V64BIT parameter setting is not YES or NO.
- The machine does not have 64-bit address capability.
- The machine is not a z/OS machine.
- The ADARUN PROGRAM parameter is not set to ADANUC.

Action Correct the error and rerun the job.

error-31 IDTNAME does not start "ADA"

Explanation This is a BS2000 only error. The user has defined the IDTNAME or the ENVNAME in the SSFB2C parameter module which does not begin with "ADA". This will lead to a failure in communication between Client applications and nucleus.

Action Correct the IDTNAME in the ADARUN parameter list so that it begins with "ADA" and restart the nucleus.

error-32 SWITCHNR out of range 0 - 31

Explanation ADARUN detected an inconsistent Adabas BS2000 parameter. The job switch number to be set when a non-zero return code occurs is out of the range of 1 to 31.

Action Correct the error and rerun the job.

error-33 SUBMPSZ needs to be higher than x100000

Explanation ADARUN detected an inconsistent Adabas BS2000 parameter. The size of the declared subtask memory pool is too small.

Action Correct the error and rerun the job.

error-34 PAMREQS must be a value > 0

Explanation ADARUN detected an inconsistent Adabas BS2000 parameter. The maximum number of PAM blocks sent in one PAM macro must be greater than zero.

Action Correct the error and rerun the job.

error-98 Adabas v.v cannot run on NXS hardware**Explanation** BS2000 only. Adabas 6.2 and above require 31-bit processors.**error-99 Adabas v.v cannot run under BS2000 version lower than (<) 10****Explanation** BS2000 only. Adabas 6.2 and above require BS2000 version 10 or above.**error-140 PPT-Area allocation failed****Explanation** The allocation of the PPT area failed. An attempt was made to allocate 32 ASSO blocks.**Action** Increase the ASSO size of database and rerun the job.**WARNING Parameter AMODE out of service
26****Explanation** BS2000 only. ADARUN statement AMODE=31 detected. This parameter has been removed from Adabas. Targets that use SSF must run in AMODE 31.**Action** The job continues. Remove AMODE= from your ADARUN statements.**WARNING Parameter IDTMODE out of service
27****Explanation** BS2000 only. IDTMODE=ABOVE statement detected. This parameter has been removed from Adabas. IDTs created by SSF are allocated above the 16-megabyte line.**Action** The job continues. Remove IDTMODE= from your ADARUN statements.**WARNING Parameter NECB out of service
28****Explanation** BS2000 only. NECB= statement detected. This parameter has been removed from Adabas. The posted ECB queue can no longer overflow.**Action** Job continues. Remove NECB= from your ADARUN statements.