ADARPL Utility Error Messages

Overview of Messages

ERROR-121	ERROR-122	ERROR-123	ERROR-124	ERROR-125	ERROR-126
ERROR-127	ERROR-128	ERROR-129	ERROR-130	ERROR-131	ERROR-132
ERROR-133	ERROR-134	ERROR-135	ERROR-136	ERROR-137	ERROR-138
ERROR-139	ERROR-140	ERROR-141	ERROR-142	ERROR-143	ERROR-144
ERROR-145	ERROR-146	ERROR-147	ERROR-148	ERROR-149	ERROR-150
ERROR-151	ERROR-152	ERROR-153	ERROR-154	ERROR-156	ERROR-157

ERROR-121 Date and time must be reasonable. Time is invalid without a Date. Date must be entered in the form YYYYMMDD. Time must be entered in the form HHMMSSTH.

Explanation One or more of the specified date and time fields appear invalid.

Action Correct the date and time entries and try again.

ERROR-122 At least 1 file-number must be supplied using the FILES= parameter.

Explanation The FILES parameter has been specified incorrectly. When the FILES parameter is

specified, it must be in the format of FILES=nnnnn, where nnnnn is a valid file

number.

Action Correct the FILES parameter and try again.

ERROR-123 RPLDSBI must be a string of Y, N or Placeholders in single quotes.

Explanation The RPLDSBI parameter has been specified incorrectly. The RPLDSBI parameter

must be specified in single quotes and one Y or N value must be specified for each file

specified for the ADARPL run (for example RPLDSBI='Y,N,N,Y,Y,N,Y'.

Action Correct the RPLDSBI parameter and try again.

ERROR-124 TOTIME, FROMTIME and RESENDTIME require their respective DATE

value.

Explanation A TOTIME, FROMTIME, or RESENDTIME parameter was specified without the

corresponding *DATE parameter.

Action Specify the corresponding TODATE, TOTIME, or RESENDDATE parameter with the

appropriate *TIME parameter and try again.

ERROR-125 Invalid RPLTARGETID or RPLTARGETS. The value supplied must be a positive integer less than or equal to 65535.

Explanation An invalid value was specified for the RPLTARGETID or RPLTARGETS parameters.

Valid values for these parameters range from "1" to "65535"; values higher than

"65535" are invalid.

Action Correct the target IDs and try again.

ERROR-126 No. of RPLTARGETS, RPLKEY, and RPLDSBI must be equal to No. of FILES.

Explanation An incorrect number of values was specified for the RPLTARGETS, RPLKEY, or

RPLDSBI parameters. The number of values must match the number of files specified

by the FILES parameter for the ADARPL run.

Action Correct the parameter values and try again.

ERROR-127 RPLTARGETID and RPLTARGETS parameters are mutually exclusive.

Explanation An attempt was made to specify both the RPLTARGETID and RPLTARGETS

parameters in the same ADARPL run. This is invalid.

Action Specify one or the other parameter and try again.

ERROR-128 Event Replicator Server id, no active subscription or destination for file number.

Explanation No active destination or subscription could be found for the file listed in the message

on the Event Replicator Server named in the message.

Action First verify and correct (as necessary) the file number or the Event Replicator Server

target ID for the ADARPL run. If they are correct, modify the Replicator system file

subscription and destination definitions. Then try the ADARPL run again.

ERROR-129 Database dbid not defined to Event Replicator Server id.

Explanation The database with the database ID listed in the message is not defined to the Event

Replicator Server listed in the message.

Action Verify and correct the JCL or input parameters for the ADARPL run. If they are

correct, modify the Replicator system file definitions. Then try again.

ERROR-130 Event Replicator Server *id* replication pool overflow.

Explanation The replication pool for the Event Replicator Server listed in the message has an

overflow condition, which is a critical error.

Action Refer to the Event Replicator Server job's system log for error messages, which may

provide possible actions to take.

ERROR-131 RPLKEY and RPLDSBI are only valid with RPLTARGETID or RPLTARGETS.

Explanation An attempt to specify the RPLKEY or RPLDSBI parameters was made without also

specifying either a RPLTARGETID or RPLTARGETS parameter. When specifying the RPLKEY and RPLDSBI parameters, a corresponding RPLTARGETID or

RPLTARGETS parameter must be specified.

Action Correct the input parameters and try again.

ERROR-132 Dates and times must conform to the following general rule: FROMDATE/TIME <= RESENDDATE/TIME <= TODATE/TIME

Explanation The date and time values specified for the ADARPL run violate one or more of the following rules:

- FROMDATE and FROMTIME parameter values must specify dates and times earlier than those specified for the RESENDDATE and RESENDTIME parameters
- RESENDDATE and RESENDTIME parameter values must specify dates and times earlier than those specified for the TODATE and TOTIME parameters.

Action Correct the date and time parameters and rerun the ADARPL job.

ERROR-133 The file number cannot exceed 65535.

Explanation The file number specified on the FILES parameter was greater than "65535", which is

invalid. Valid values for the FILES parameter range from "1" through "65535".

Action Correct the file number and rerun the job.

ERROR-134 REPLAY is a required input parameter.

Explanation An attempt to run the ADARPL utility without specifying the REPLAY parameter.

You cannot run the ADARPL utility without specifying the REPLAY parameter.

Action Add the REPLAY parameter and rerun the ADARPL job.

ERROR-135 The Adabas nucleus is currently NOT active.

Explanation An attempt was made to run the ADARPL utility was made when the Adabas nucleus

was not active. The Adabas nucleus must be active to run ADARPL.

Action Activate the Adabas nucleus and try again.

ERROR-136 A resp 50 has been received during the Adabas open, probable invalid file number

specified.

Explanation An error occurred trying to open one of the file numbers specified for the ADARPL

run.

Action Verify and correct the file numbers specified for the ADARPL run and then rerun the

job.

ERROR-137 Invalid block number found.

The blocks of the current PLOG are not supplied in the correct order. The block

counts must be ascending by 1.

Current block count = count

Protection Log Number = number

Supply the correct sequence of protection logs and rerun the job.

Explanation ADARPL has detected an incorrect protection log. The current block count is shown,

as well as the protection log number to assist diagnosis.

Action Verify and check the PLOG data sets specified in the ADARPL job.

ERROR-138 DBID mismatch.

DBID on PLOG does not match DBID-parameter Supply the correct PLOG tapes and rerun the job.

Explanation ADARPL has detected a DBID mismatch.

Action Verify and check the PLOG data sets and the DBID parameter specified in the

ADARPL job.

ERROR-139 ADARPL replication pool overflow.

Increase LRPL parameter and rerun the job.

Explanation ADARPL has exceeded the replication pool size allocated via the LRPL parameter.

Action Verify and check the input parameter LRPL specified in the ADARPL job, and

increase it, as necessary, for successful job execution.

ERROR-140 Unexpected Event Replicator Server response rsp.

Explanation ADARPL has received a non-zero response code from the Event Replicator Server.

Action Use the response code in the error message to analyze and correct the problem.

ERROR-141 RPLCLEANUP was issued for this ADARPL token

Explanation An operator command of RPLCLEANUP was issued and the ADARPL token was

removed. Further execution is not possible.

Action Verify and determine why the RPLCLEANUP operator command was issued.

ERROR-142 Duplicate ADARPL jobs for the same FNR are not allowed

Explanation ADARPL has detected a concurrent execution of another ADARPL against the same

file number on this DBID.

Action Verify the execution of ADARPL jobs or check that the input parameters to ADARPL

are correct.

ERROR-143 Parameter RPLSORT must be set to YES or NO

Explanation ADARPL has detected that the setting for the RPLSORT parameter is incorrect.

Action Verify that the input parameter RPLSORT is set to "YES" or "NO".

ERROR-144 RPLTARGETID or RPLTARGETS must be specified if FILES are not specified

Explanation ADARPL has detected that the parameters RPLTARGETID or RPLTARGETS is

required because the FILES parameter is not specified.

Action Verify and check the input parameters to the ADARPL job for correct information,

specifying RPLTARGETID or RPLTARGETS if required.

ERROR-145 Invalid TOKEN or PLOGDBID or ORIGINDBID

The value supplied must be a positive integer less than or equal to 65535.

Explanation ADARPL had detected a TOKEN, PLOGDBID, or ORIGINDBID value which is not a

valid number.

Action Review and change, if necessary, the number listed in the ADARPL parameters. Then

run the ADARPL job again.

ERROR-146 RPLTARGETID must be specified if TOKEN is specified

Explanation ADARPL has detected a TOKEN parameter in the same run in which an

RPLTARGETID parameter was not specified. When you specify the TOKEN

parameter, you must also specify the RPLTARGETID parameter.

Action Review and change the ADARPL parameters, as necessary. Then run the ADARPL job

again.

ERROR-147 When parameter TOKEN is specified, only the following additional parameters

are valid: LRPL, NU, and RPLTARGETID

Explanation ADARPL has detected a TOKEN parameter in the same run as another ADARPL

parameter that is not allowed when the TOKEN parameter is specified. Only the LRPL,

NU, and RPLTARGETID parameters can be specified in an ADARPL run using

TOKEN.

Action Review and change the ADARPL parameters, as necessary. Then run the ADARPL job

again.

ERROR-148 TOKEN token not found in Event Replicator Server

Explanation There are no replay processes active with the token number listed in the message.

Action Review and change the ADARPL RPLTARGETID and TOKEN parameters, as

necessary. Then run the ADARPL job again.

ERROR-149 TOKEN token was not an ADARPL token.

Explanation The token listed in the message is a valid token number, but is not for a replay process.

Action Review and change the ADARPL TOKEN parameter, as necessary. Then run the

ADARPL job again.

ERROR-150 RPLSORT missing, possibly the Adabas is not connected to the Event Replicator

Server

Explanation ADARPL has detected that the Event Replicator Server does not have information

about RPLSORT, which is provided during an initialization handshake between an

Adabas database and an Event Replicator Server.

Action Verify that the Adabas database and the Event Replicator Server have established

communication.

ERROR-151 File *number* is not the anchor file in the expanded file chain

Explanation The file listed in the message is not the anchor file in the Adabas expanded file chain.

Only the anchor file can be specified in the FILES parameter.

Action Specify the file number of the anchor file in the expanded file chain and try again.

ERROR-152 Incomplete transaction found on PLOG

Explanation A transaction started before the input PLOG data set specified for replay processing

and ended after the FROMDATE and FROMTIME replay specifications.

Action Add the preceding PLOG data set in sequence to the input PLOG data sets for replay

processing and try again.

ERROR-153 Incomplete transaction found on PLOG

Explanation The ET record was not found for a transaction that was to be included in replay

processing.

Action Add the next PLOG data set in sequence to the input PLOG data sets for replay

processing and try again.

ERROR-154 File *num* not loaded in database *dbid*

Explanation An attempt to run the ADARPL utility failed because the file specified for the run does

not exist in the specified database. The file number and database ID are given in the

message.

Action Verify that the correct file number is specified and that the file does exist in the

database. Then try again.

ERROR-156 The source database Adabas version is not compatible with the Reptor Adabas

version

Explanation The version of Adabas or the Event Replicator used by the Adabas database is not the

same as the version of Adabas or Event Replicator used by the Event Replicator

Server.

Action Resolve the discrepancy in Adabas or Event Replicator versions before you try again.

ERROR-157 Either PLOGFILES specified for the master file only, or not all files of expanded file chain specified

Explanation A file number specified in PLOGFILES parameter is a component of an expanded file chain. At this time, the PLOGFILES parameter cannot specify files in an expanded chain and cannot be specified if any of the files listed in the FILES parameter is for a

file in an expanded chain.

Action Correct the ADARPL parameters and try again.