

JCL/JCS Requirements and Examples

This section describes the job control information required to run ADADCK with BS2000, z/OS, and z/VSE systems and shows examples of each of the job streams.

This chapter covers the following topics:

- BS2000
 - z/OS
 - z/VSE
-

BS2000

Data Set	Link Name	Storage	More Information
Associator	DDASSOR n or DDASSO nn	disk	
Data Storage	DDDATAR n or DDDATA nn	disk	
ADARUN parameters	SYSDTA/ DDCARD		<i>Operations</i>
ADADCK parameters	SYSDTA/ DDKARTE		
ADARUN messages	SYSOUT DDPRINT		<i>Messages and Codes</i>
ADADCK messages	SYSLST DDDRUCK		<i>Messages and Codes</i>

ADADCK JCL Example (BS2000)

In SDF Format:

```
/ .ADADCK LOGON
/MODIFY-TEST-OPTIONS DUMP=YES
/REMARK *
/REMARK *A D A D C K DATA STORAGE CHECK
/REMARK *
/REMARK *
/ASS-SYSLST L.DCK.DATA
/ASS-SYSDTA *SYSCMD
/SET-FILE-LINK DDLIB,ADAvrs.MOD
/SET-FILE-LINK DDASSOR1,ADAYYYYY.ASSO,SHARE-UPD=YES
/SET-FILE-LINK DDDATAR1,ADAYYYYY.DATA,SHARE-UPD=YES
/START-PROGRAM *M(ADA.MOD,ADARUN),PR-MO=ANY
ADARUN PROG=ADADCK,DB=YYYYYY,IDLNAME=ADABAS5B
ADADCK DSCHECK FILE=27
/LOGOFF SYS-OUTPUT=DEL
```

In ISP Format:

```

/.ADADCK LOGON
/OPTION MSG=FH,DUMP=YES
/REMARK *
/REMARK *A D A D C K DATA STORAGE CHECK
/REMARK *
/REMARK *
/SYSFILE SYSLST=L.DCK.DATA
/FILE ADA.MOD,LINK=DDLIB

/FILE ADAYYYYY.ASSO ,LINK=DDASSOR1,SHARUPD=YES
/FILE ADAYYYYY.DATA ,LINK=DDDATAR1,SHARUPD=YES
/EXEC (ADARUN,ADA.MOD)
ADARUN PROG=ADADCK,DB=YYYYYY,IDLNAME=ADABAS5B
ADADCK DSCHECK FILE=27
/LOGOFF NOSPOOL

```

z/OS

Data Set	DD Name	Storage	More Information
Associator	DDASSOR n or DDASSO n	disk	
Data Storage	DDDATAR n or DDDATA n	disk	
ADARUN parameters	DDCARD	reader	<i>Operations</i>
ADADCK parameters	DDKARTE	reader	
ADARUN messages	DDPRINT	printer	<i>Messages and Codes</i>
ADADCK messages	DDDRUCK	printer	<i>Messages and Codes</i>

ADADCK JCL Example (z/OS)

Refer to ADADCK in the JOBS data set for this example.

```

//ADADCK      JOB
//*
//*      ADADCK:
//*          DATA STORAGE CHECK
//*
//DCK      EXEC PGM=ADARUN
//STEPLIB  DD   DISP=SHR,DSN=ADABAS.ADAvrs.LOAD      <== ADABAS LOAD
//*
//DDASSOR1 DD   DISP=SHR,DSN=EXAMPLE.DBYYYYYY.ASSOR1 <== ASSO
//DDDATAR1 DD   DISP=SHR,DSN=EXAMPLE.DBYYYYYY.DATAR1 <== DATA
//DDDRUCK  DD   SYSOUT=X
//DDPRINT   DD   SYSOUT=X
//SYSUDUMP  DD   SYSOUT=X
//DDCARD    DD   *
ADARUN PROG=ADADCK,SVC=xxx,DEVICE=dddd,DBID=YYYYYY
/*
//DDKARTE  DD   *
ADADCK DSCHECK FILE=27
/*

```

z/VSE

File	Symbolic Name	Storage	Logical Unit	More Information
Associator	ASSORn or ASSOnn	disk	*	
Data Storage	DATARn or DATAAnn	disk	*	
ADARUN parameters	- CARD CARD	reader tape disk	SYSRDR SYS000 *	
ADADCK parameters		reader	SYSIPT	
ADARUN messages		printer	SYSLST	<i>Messages and Codes</i>
ADADCK messages		printer	SYS009	<i>Messages and Codes</i>

* Any programmer logical unit may be used.

ADADCK JCS Example (z/VSE)

See *Library and File Procedures for z/VSE Examples* for descriptions of the z/VSE procedures (PROCs).

Refer to member ADADCK.X for this example.

```
* $$ JOB JNM=ADADCK,CLASS=A,DISP=D
* $$ LST CLASS=A,DISP=D
// JOB ADADCK
*      DATA STORAGE CHECK
// EXEC PROC=ADAVvLIB
// EXEC PROC=ADAVvFIL
// EXEC ADARUN,SIZE=ADARUN
ADARUN PROG=ADADCK,MODE=MULTI,SVC=xxx,DEVICE=dddd,DBID=yyyyyy
/*
ADADCK DSCHECK FILE=27
/*
/&
* $$ EOJ
```