

RVCALL* - Adabas Review RVCALL API Messages

Overview of Messages

RVCALL00	RVCALL04	RVCALL05	RVCALL06	RVCALL07	RVCALL08
RVCALL09	RVCALL10	RVCALL11	RVCALL12	RVCALL13	RVCALL14
RVCALL15	RVCALL16	RVCALL17	RVCALL18	RVCALL19	RVCALL20
RVCALL22	RVCALL23	RVCALL24	RVCALL25	RVCALL27	RVCALL35
RVCALL98	RVCALL99	RVCALL420	RVCALL421	RVCALL499	

RVCALL00 **Function completed successfully**

Explanation The RVCALL function completed successfully.

Action No action is required for this informational message.

RVCALL04 **Invalid RVC-FUNCTION specified**

Explanation An invalid value was specified for the RVCALL parameter RVC-FUNCTION. Valid values are START, DELETE, CLOSE, SUSPEND, REACT, LIST, GETHUBID, GETDBID, EZSTART, VIEWON, or VIEWOFF.

Action Specify a valid value and try again.

RVCALL05 <msg-text>

Explanation The message text for this message varies. The following message texts may appear:

Message Text	Explanation
RVC-DBID must be specified	A value for the RVC-DBID parameter is required, but no value was specified.
RVC-DBID must not be greater than 65535	An invalid value was specified for RVC-DBID.
RVC-REVIEW-TARGET must be specified	A value for RVC-REVIEW-TARGET is required, but no value was specified.
RVC-REVIEW-TARGET must not be greater than 65535	An invalid value was specified for RVC-REVIEW-TARGET.

Action Correct the value of the RVC-DBID or RVC-REVIEW-TARGET parameter and try again.

RVCALL06 **RVC-REPORT-NAME must be specified**

Explanation A value for the RVC-REPORT-NAME parameter is required, but no value was specified.

Action Specify an valid value for RVC-REPORT-NAME and try again.

RVCALL07 **RVC-ACCOUNT-FIELDS required for summary reports**

Explanation A value for the RVC-ACCOUNT-FIELDS parameter is required, but no value was specified.

Action Specify the order in which fields should appear for summary reports in the RVC-ACCOUNT-FIELDS parameter. Then try again.

RVCALL08 **RVC-WRAP = "Y" valid for sequence reports only**

Explanation RVC-WRAP is specified, but the SEQUENCE field is not specified in the RVC-ACCOUNT-FIELDS parameter.

Action Examine the problem. Correct either the RVC-WRAP parameter setting or add SEQUENCE to the RVC-ACCOUNT-FIELDS parameter setting. Then try again.

RVCALL09 RVC-HISTORY-DBID must be specified for history reports

Explanation History data was requested, but no value was specified for the RVC-HISTORY-DBID parameter.

Action In the RVC-HISTORY-DBID parameter, specify the valid database ID (DBID) of the Adabas Review repository used to store history data. Then try again.

RVCALL10 RVC-HISTORY-FNR must be specified for history reports

Explanation History data was requested, but no value was specified for the RVC-HISTORY-FNR parameter.

Action In the RVC-HISTORY-FNR parameter, specify the valid file number of the Adabas Review repository used to store history data. Then try again.

RVCALL11 RVC-HISTORY-SVC must be specified for history reports

Explanation History data was requested, but no value was specified for the RVC-HISTORY-SVC parameter.

Action In the RVC-HISTORY-SVC parameter, specify the valid Adabas SVC number used to communicate with the Adabas Review repository to which history data should be written. Then try again.

RVCALL12 RVC-REPORT-NAME already active

Explanation The report specified in the RVC-REPORT-NAME parameter using the EZSTART function is already active.

Action Specify a different report in the RVC-REPORT-NAME parameter and try again. Alternatively, you could stop the running report and start it again using RVCALL, but if the report was started online using SYSREVDDB, it will need to be stopped online (not using RVCALL).

RVCALL13 UCMD area storage allocation failed

Explanation The storage available for Adabas Review reports is inadequate. This was determined during an attempt to run the EZSTART function.

Action Increase the storage available for Adabas Review reports and try again. If the problem persists, contact your Software AG technical support representative.

RVCALL14 Not enough storage to start report

Explanation There is not enough storage to start a report using the EZSTART function.

Action Increase the storage available for Adabas Review reports and try again. If the problem persists, contact your Software AG technical support representative.

RVCALL15 Invalid field definition in report

Explanation An invalid field definition was found in an Adabas Review report while running the RVCALL EZSTART function.

Action Using SYSREVDDB, correct the field definition online. Then try the RVCALL EZSTART function again.

RVCALL16 Invalid summary field specified in report

Explanation An invalid summary field was specified for an Adabas Review report while running the RVCALL EZSTART function.

Action Using SYSREVDDB, correct the summary field value online. Then try the RVCALL EZSTART function again.

RVCALL17 Field length error in report

Explanation An invalid field length was specified for an Adabas Review report while running the RVCALL EZSTART function.

Action Using SYSREVDDB, correct the field length value online. Then try the RVCALL EZSTART function again.

RVCALL18 Field format error in report

Explanation An invalid field format was specified for an Adabas Review report while running the RVCALL EZSTART function.

Action Using SYSREVDDB, correct the field format value online. Then try the RVCALL EZSTART function again.

RVCALL19 Error in report processing, resp = *rsp*

Explanation An unknown error occurred in the RVCALL EZSTART processing of an online report. The response code is given in the message (*rsp*).

Action Review the response code and use SYSREVDB to examine the report definition online. Make appropriate corrections and retry. If the problem persists, contact your Software AG technical support representative.

RVCALL20 RVC-REPORT-NAME is not active

Explanation The report name specified in the RVC-REPORT-NAME parameter is not active, but must be active for the RVCALL function identified in the RVC-FUNCTION parameter.

Action Either specify an active report name in the RVC-REPORT-NAME parameter or change the RVCALL function specified in the RVC-FUNCTION parameter.

RVCALL22 No active reports to be listed

Explanation During RVCALL LIST function processing (RVC-FUNCTION='LIST'), RVCALL found no active reports to list.

Action Determine whether this is really a problem. No action is required if there are no active reports. However, if there are active reports, verify that the other LIST function input parameters are specified correctly. Then try again.

RVCALL23 Error accessing DBID for L-FILE

Explanation An error occurred while processing an RVCALL GETDBID function.

Action Contact your Software AG technical support representative for assistance.

RVCALL24 Found zero HUBIDs on selected SVC

Explanation No hub IDs were found during RVCALL GETHUBID function processing for the SVC specified in the RVC-SVC parameter.

Action Verify that the SVC specified in the RVC-SVC parameter is valid and try again. If the problem persists, contact your Software AG technical support representative.

RVCALL25 RVC-SVC is invalid

Explanation The SVC specified in the RVC-SVC parameter for RVCALL GETHUBID function processing was invalid.

Action Specify a valid SVC in the RVC-SVC parameter for the run and try again.

RVCALL27 <msg-text>

Explanation One of the following errors occurred using ADATMZ during RVCALL processing.

Message Text	Explanation
ADATMZ: No Adabas SVCs found	No Adabas SVCs were found by ADATMZ.
ADATMZ: No Active targets for an SVC	No active targets were found for the SVC by ADATMZ.

Action Examine the message and take appropriate action. If the problem persists, contact your Software AG technical support representative for assistance.

RVCALL35 BUFFER POOL reports cannot have DBID=ALL

Explanation During RVCALL EZSTART processing, you specified "BUFFER POOL DISPLAY" for the report name and set the RVC-ALL parameter to "ALL". This is not allowed. You cannot produce the buffer pool display for all DBIDs.

Action Specify a single database ID in the RVC-DBID parameter for the RVCALL EZSTART run and remove the RVC-ALL='ALL' specification. Then try again.

RVCALL98 Adabas error, resp = rsp

Explanation An error occurred while the RVCALL API was calling Adabas. The response code from the call is given in the message (*rsp*).

Action Review the response code explanation in the Adabas Response Code documentation and try to resolve the problem. If the problem persists, contact your Software AG technical support representative.

RVCALL99 Adabas error, resp = *rsp*

Explanation An error occurred while the RVCALL API was calling Adabas. The response code from the call is given in the message (*rsp*).

Action Review the response code explanation in the Adabas Response Code documentation and try to resolve the problem. If the problem persists, contact your Software AG technical support representative.

RVCALL420 Unable to open command log file for output

Explanation The report requested during an RVCALL EZSTART run required a command log file that was not available.

Action Make the command log file available and try again.

RVCALL421 Command log dataset already in use

Explanation The report requested during an RVCALL EZSTART run required a command log data set that was not available.

Action Make the command log data set available and try again.

RVCALL499 Detail printer not available

Explanation The report requested during an RVCALL EZSTART run required a printer, but no printer was available.

Action Make the printer available and try again.