

Adabas

Messages and Codes

Version 8.5.3

April 2020

This document applies to Adabas Version 8.5.3 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 1971-2020 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG.

Document ID: ADAMF-MESSAGES-853-20230316

Table of Contents

Preface	vii
1 List of Abbreviations	1
2 About this Documentation	3
Document Conventions	4
Online Information and Support	4
Data Protection	5
I Message Prefix Reference	7
3 Message Prefix Reference	9
II Message Prefix Reference by Product	13
4 Message Prefix Reference by Product	15
III	21
5 ADARUN Statement/Parameter Messages	23
IV Adabas Checkpoints	29
6 Adabas Checkpoints	31
V	37
7 Adabas Console Messages (ADAN* & ADACM*)	39
ADATCP messages ADACM* messages ADATCP Messages (Prefix ADACM)	116
VI DCAM Feedback Codes	119
8 DCAM Feedback Codes	121
VII	123
9 Nucleus Startup Error Messages	125
10 Adabas Response Codes	147
VIII SNA Sense Codes	313
11 SNA Sense Codes	315
IX	317
12 Software AG Licensing Messages	319
X Universal Encoding System (UES) Component Error Codes	327
13 Universal Encoding System (UES) Component Error Codes	329
Entire Conversion Service (ECS) Errors	330
Open Virtual Operating System Interface (OVO) Errors	332
COX* Universal Encoding System Conversion (UES) Errors	333
XI User Abend Codes	335
14 User Abend Codes	337
XII	349
15 AAF* - Adabas SAF Security Messages	351
16 SAF Return Codes	357
17 SAF Internal Function Codes	359
18 AAS* - Adabas Administration Services Messages	361
19 AAUD* - AUDITLOG Messages	409
20 ACLX* - Adabas Review Interface Messages	411
21 ADAA* Adabas Auditing Messages	413
22 ADACM* - ADATCP Messages	419

23 ADAD*	Abend Code Messages	425
24 ADAE*	Adabas SAF Security (ADASAF) Messages	427
25 ADAF*	- Event Replicator for Adabas Messages	431
26 ADAH*	- Dump Formatter Status Messages	543
27 ADAI*	- ADAIOR System Messages	545
28 ADAJ*	System Messages	565
29 ADAK*	System Messages	567
30 ADAL*	- Command Log (CLOG) System Messages	579
31 ADAM*	-- ADAMPM System Messages	583
32 ADAQ*	- Adabas Review Hub Messages	601
33 ADAR*	System Messages	605
34 ADAS*	(Adabas SVC) System Messages	611
35 ADASIP*	(Adabas z/VSE SVC) System Messages	619
36 ADASM*	Adabas SMF Processing Messages	629
37 ADAU*	Utility Status Messages	631
38 ADAX*	- Adabas Cluster Nucleus Messages	649
39 ADAZ*	- ADAZIP System Messages	697
40 AFP*	- Adabas Fastpath Messages	701
41 APSPSX*	- ADAECS or ADATCP Messages	711
42 AREV*	- Adabas Review Hub Messages	713
43 ARF*	- Adabas Event Replicator Subsystem Messages	719
44 ARMT*	- Adabas Review Interface Messages	759
45 ARST*	- Adabas Review Interface Messages	761
46 ART*	- Event Replicator Target Adapter Messages	763
47 ARVU*	- Adabas Review Interface Messages	799
48 ARXM*	- Event Replicator for Adabas Messages for Event Replicator Target Adapter	811
49 ATM*	- Adabas Transaction Manager Messages	815
50	Adabas Transaction Manager Error Codes	845
51 AVInnn	- Adabas Vista Database Processing Messages	861
52 AVI-xxxx-xx	- Adabas Vista Processing Messages	863
53 CAS*	- Adabas System Coordinator Cluster Application Service Messages	865
54 COR*	- Adabas System Coordinator Kernel Messages	871
55 CORD*	- Adabas System Coordinator Daemon Messages	883
56 CWARN*	- Caching Facility Error Messages	897
57 DSF*	- Delta Save Facility Messages	901
	Nucleus-Related Console Messages (DSF001 - DSF029, DSF02A-D)	902
	Utility-Related Job Protocol Messages for ADARES and ADASAV (DSF030 - DSF099)	907
58 DSP*	- Cluster Data Space (ADADSP) Messages	927
59 LNKRVX*	Adabas Review Link Routine Messages	933
60 PLI*	- ADACOM Initialization Messages	935
61 PLX*	- ADACLU Messages	951
62 PL6*	- PRILOG6 Print Program Messages	963
	Messages from the System-Dependent Component	965

63 POP* - Adabas System Coordinator Server Component Messages	967
64 Adabas Review 00xxx Messages	971
65 Adabas Review 20xxx Messages	1037
66 REVH* - Adabas Review Hub Messages	1069
67 RTP* - Adabas Review Trans- port Messages	1075
68 RVCL* - Adabas Review Batch Client Reporting (REVCLRP) Messages	1077
69 SAF* - SAF Daemon Messages	1081
70 SAGE* - z/VSE Batch Job Exit Utility Messages	1085
71 SAGI* - Batch Initialization Messages (z/VSE Only)	1087
72 SEFM* - ADASAF SAF Interface and SAF Security Kernel Messages	1091
Operator Command Messages (SEFM900+ Series) Adabas SAF	
Securityoperator command messages SAF Security Kerneloperator command	
messages	1096
73 SM-PIN* - PIN Routine Messages	1103
74 XTS* - Software AG Internal Transport Subsystem Messages	1105
Warnings	1106
Errors	1108
Generic TCP/IP Messages	1122
XIII Utility Messages and Codes	1135
75 Errors Common to All Utilities	1147
76 ADAACK Utility Messages	1165
77 ADACDC Utility Messages	1169
78 ADACHK Utility CHK* Messages	1177
79 ADACHK Utility CRV* Decompression Messages	1229
80 ADACHK Utility SRT* Sort Messages	1237
81 ADACMP Utility Messages	1243
82 ADACNV Utility Messages	1251
83 ADADBS Utility Messages	1257
84 ADADCK Utility Messages	1277
85 ADADEF Utility Messages	1281
86 ADADRU Utility Messages	1285
87 ADAFRM Utility Messages	1297
88 ADAICK Utility Messages	1299
89 ADAINV Utility Messages	1309
90 ADALOD Utility Messages	1313
91 ADAMER Utility Messages	1329
92 ADAMTR Utility Messages	1331
93 ADAMTS Utility Messages	1335
94 ADAORD Utility Messages	1339
95 ADAPLP Utility Messages	1347
96 ADAPRI Utility Messages	1349
97 ADARAI Utility Messages	1351
ADARAI Error Messages Written to the Output Recovery Job (ERROR-160	
- ERROR-169)	1356
98 ADAREP Utility Messages	1361

99 ADARES Utility Messages	1365
100 ADARPE Utility Messages	1375
101 ADARPL Utility Messages	1379
102 ADARPP Utility Messages	1387
103 ADASAV Utility Messages	1391
104 ADASEL Utility Messages	1407
105 ADAULD Utility Messages	1425
106 ADAVAL Utility Messages	1431
107 ADAWRK Utility Messages	1433
108 ADAZAP Utility Messages	1443
109 ADAZIN Utility Messages	1445
Index	1449

Preface

This documentation contains a description of error messages and response codes for the basic Adabas database management system and the following options or add-on products:



Notes:

1. Data set names starting with DD are referred to in Adabas manuals with a slash separating the DD from the remainder of the data set name to accommodate z/VSE data set names that do not contain the DD prefix. The slash is not part of the data set name.
2. Notation *vrs*, *vr*, or *v*: When used in this documentation, the notation *vrs* or *vr* stands for the relevant version of a product. For further information on product versions, see *version* in the *Glossary*.
3. Information about Adabas operator commands, which are often issued in response to a message or code, can be found in the Adabas Operations documentation.

The description of messages and codes is organized in the following parts:

<i>Alphabetical Message Prefix Reference</i>	Lists all of the message prefixes used in Adabas messages alphabetically and identifies the Adabas components and products that use them. The messages themselves are provided elsewhere in this guide.
<i>Message Prefix Reference by Product</i>	Lists the message prefixes by Adabas component and product. The messages themselves are provided elsewhere in this guide.
<i>ADARUN Statement/Parameter Messages</i>	Describes the error messages that can result from ADARUN statements and parameters that define the nucleus operating environment.
<i>Adabas Checkpoints</i>	Describes Adabas nucleus and utility checkpoints.
<i>Adabas Console Messages (ADAN* & ADACM*)</i>	Describes messages that may be displayed on the operator console during an Adabas session.
<i>DCAM Feedback Codes</i>	Describes DCAM feedback codes (the first non-zero bytes) used with Entire Net-Work DCAM Communication.
<i>Nucleus Startup Messages</i>	Describes error messages issued by the Adabas nucleus during startup.
<i>Nucleus Response Codes</i>	Describes response codes issued by the Adabas nucleus during processing of nucleus commands.

<i>Software AG Mainframe Licensing Error Messages</i>	Describes error messages issued by Software AG's mainframe licensing software and the license utility (LICUTIL).
<i>SNA Sense Codes</i>	Describes the popular SNA sense codes used in conjunction with a DCAM/VTAM link and TRANSIT/CD in Entire Net-Work DCAM Communication.
<i>Universal Encoding System (UES) Component Error Codes</i>	Describes error codes issued by Adabas UES components and listed in other Adabas error messages.
<i>User Abend Codes</i>	Describes user abnormal end (abend) codes.
<i>AAF* - Adabas SAF Security Messages</i>	Describes Adabas SAF Security messages.
<i>AAS* - Adabas Administration Service Messages</i>	Describes Adabas Administration Service messages.
<i>SAF Return Codes</i>	Describes Adabas SAF Security and SAF Security Kernel return codes.
<i>SAF Internal Function Codes</i>	Describes Adabas SAF Security and SAF Security Kernel internal function codes.
<i>AAUD* - AUDITLOG Messages</i>	Describes the AUDITLOG auditing data message for the function issued.
<i>ACLX* - Adabas Review ADALNK Messages</i>	Describes Adabas Review ADALNK messages.
<i>ADAA* - Adabas Analytics Messages</i>	Describes Adabas Analytics messages.
<i>ADACM* - ADATCP Messages</i>	Describes the ADATCP messages used with Entire Net-Work.
<i>ADAD* Abend Code Messages</i>	Describes the abend code messages.
<i>ADAE* Adabas SAF Security (ADASAF) Messages</i>	Describes Adabas SAF Security (ADASAF) messages.
<i>ADAF* - Event Replicator for Adabas Messages</i>	Describes Event Replicator for Adabas messages.
<i>ADAH* - Dump Formatter Status Messages</i>	Describes dump formatter status messages.
<i>ADAI* - ADAIOR System Messages</i>	Describes ADAIOR system messages.
<i>ADAJ* System Messages</i>	Describes Adabas system messages with an ADAJ prefix.
<i>ADAK* System Messages</i>	Describes Adabas system messages with an ADAL prefix.
<i>ADAL* - Command Log (CLOG) System Messages</i>	Describes command log (CLOG) system messages.
<i>ADAM* -- ADAMPM System Messages</i>	Describes ADAMPM system messages.
<i>ADAQ* - Adabas Review Hub Messages</i>	Describes Adabas Review hub system messages beginning with the prefix ADAQ*.
<i>ADAR* System Messages</i>	Describes Adabas system messages.
<i>ADAS* (Adabas SVC) System Messages</i>	Describes Adabas SVC system messages.

<i>ADASM* Adabas SMF Processing Messages</i>	Describes messages produced by Adabas SMF record processing.
<i>ADASIP* (Adabas z/VSE SVC) System Messages</i>	Describes Adabas z/VSE SVC system messages.
<i>ADAU* Utility Status Messages</i>	Describes Adabas utility status messages.
<i>ADAX* - Adabas Cluster Nucleus Messages</i>	Describes Adabas cluster nucleus messages.
<i>ADAZ* - ADAZIP System Messages</i>	Describes Adabas system messages generated by module ADAZIP.
<i>AFP* - Adabas Fastpath Messages</i>	Describes the Adabas Fastpath (AFP*) messages.
<i>APSPSX* - ADAECS or ADATCP Messages</i>	Describes the APSPSX*, ADAECS, and ADATCP messages related to conversion.
<i>AREV* - Adabas Review Hub Messages</i>	Describes Adabas Review hub system messages beginning with the prefix AREV*.
<i>ARF* - Adabas Event Replicator Subsystem Messages</i>	Describes Adabas Event Replicator Subsystem messages.
<i>ARMT* - Adabas Review Hub Messages</i>	Describes Adabas Review hub system messages beginning with the prefix ARMT*.
<i>ARST* - Adabas Review Hub Messages</i>	Describes Adabas Review hub system messages beginning with the prefix ARST*.
<i>ARVU* - Adabas Review Hub Messages</i>	Describes Adabas Review hub system messages beginning with the prefix ARVU*.
<i>ARXM* - Event Replicator for Adabas Messages for Event Replicator Target Adapter</i>	Describes Event Replicator Target Adapter messages.
<i>ATM* - Adabas Transaction Manager Messages</i>	Describes the Adabas Transaction Manager (ATM*) messages.
<i>Adabas Transaction Manager Error Codes</i>	Describes the Adabas Transaction Manager error codes.
<i>AVInnn - Adabas Vista Database Processing Messages</i>	Describes Adabas Vista database processing messages
<i>AVI-xxxx-xx - Adabas Vista Processing Messages</i>	Describes Adabas Vista processing messages
<i>CAS* - Adabas System Coordinator Cluster Application Service Messages</i>	Messages issued from the clustered application service (CAS) operating in the Adabas System Coordinator daemon.
<i>CHK* - ADACHK Utility Messages</i>	Describes messages issued by Adabas ADACHK utility processing.
<i>COR* - Adabas System Coordinator Kernel Messages</i>	Messages issued by the Adabas System Coordinator kernel.
<i>CORD* - Adabas System Coordinator Daemon Messages</i>	Messages issued by the Adabas System Coordinator daemon.
<i>CRV* - ADACHK Utility Decompression Messages</i>	Describes messages issued by Adabas ADACHK utility decompression processing.
<i>CWARN* - Caching Facility Error Messages</i>	Describes Adabas Cache Facility error messages.

<i>DSF* - Delta Save Facility Messages</i>	Describes Adabas Delta Save messages.
<i>DSP* - Cluster Data Space (ADADSP) Messages</i>	Describes Adabas Parallel Services cluster data space (ADADSP) messages.
<i>DRU* - ADADRU Utility Messages</i>	Describes messages issued by Adabas ADADRU utility processing.
<i>LNKRVX* Adabas Review Link Routine Messages</i>	Describes Adabas Review link routine messages.
<i>MLC* - Software AG Mainframe Licensing Error Messages</i>	Describes error messages issued by Software AG's mainframe licensing software and the license utility (LICUTIL)
<i>PLI* - ADACOM Initialization Messages</i>	Describes ADACOM initialization messages.
<i>PLX* - ADACLU Messages</i>	Describes Adabas nucleus cluster environment (ADACLU) messages.
<i>PL6* - PRILOG6 Print Program Messages</i>	Describes Adabas PRILOG6 print program messages.
<i>POP* - Adabas System Coordinator Server Component Messages</i>	Describes messages issued from the Adabas System Coordinator Adabas server component.
<i>REV00* - Adabas Review 00xxx Messages</i>	Describes Adabas Review messages of the format REV00*.
<i>REV20* - Adabas Review 20xxx Messages</i>	Describes Adabas Review messages of the format REV20*.
<i>REXH* - Adabas Review Hub Messages</i>	Describes Adabas Review hub system messages beginning with the prefix REXH*.
<i>RTP* - Adabas Review Trans-<i>port</i> Messages</i>	Describes Adabas Review Trans- <i>port</i> messages beginning with the prefix RTP*.
<i>RVCL* - Adabas Review Batch Client Reporting (REVCLRP) Messages</i>	Describes Adabas Review batch client reporting (REVCLRP module) messages.
<i>SAF* - SAF Daemon Messages</i>	Describes SAF Security Kernel messages
<i>SAGE* - z/VSE Batch Job Exit Utility Messages</i>	Describes Software AG job exit utility (batch) messages for z/VSE systems.
<i>SAGI* - Batch Initialization Messages (z/VSE Only)</i>	Describes batch initialization messages for z/VSE systems.
<i>SEFM* - ADASAF SAF Interface and SAF Security Kernel Messages</i>	Describes Adabas SAF Security (ADASAF) and SAF Security Kernel operator console and command messages.
<i>SM-PIN* - PIN Routine Messages</i>	Describes Adabas messages for the plug-in (PIN) modules of the error handling and message buffering facility.
<i>SRT* - ADACHK Utility Sort Messages</i>	Describes messages issued by Adabas ADACHK utility sort processing.
Utility Messages and Codes	<i>Utility Return Codes</i> Describes return codes issued by Adabas utilities.

<i>Errors Common to All Utilities (ERROR-001 through ERROR-120)</i>	Describes common Adabas utility error messages.
<i>ADAACK Error Messages</i>	Describes ADAACK utility messages.
<i>ADACDC Utility Messages</i>	Describes ADACDC utility messages.
<i>ADACHK Utility CHK* Messages</i>	Describes ADACHK utility messages.
<i>ADACHK Utility CRV* Decompression Messages</i>	Describes ADACHK utility decompression messages.
<i>ADACHK Utility SRT* Sort Messages</i>	Describes ADACHK sort messages.
<i>ADACMP Utility Messages</i>	Describes ADACMP utility messages.
<i>ADACNV Utility Messages</i>	Describes ADACNV utility messages
<i>ADADBS Utility Messages</i>	Describes ADADBS utility messages
<i>ADADCK Error Messages</i>	Describes ADADCK utility messages
<i>ADADEF Utility Messages</i>	Describes ADADEF utility messages
<i>ADADRU Utility Messages</i>	Describes ADADRU utility messages
<i>ADAFRM Utility Messages</i>	Describes ADAFRM utility messages
<i>ADAICK Error Messages</i>	Describes ADAICK utility messages
<i>ADAINV Utility Messages</i>	Describes ADAINV utility messages
<i>ADALOD Utility Messages</i>	Describes ADALOD utility messages
<i>ADAMER Utility Messages</i>	Describes ADAMER utility messages
<i>ADAMTR Utility Messages</i>	Describes ADAMTR utility messages
<i>ADAMTS Utility Messages</i>	Describes ADAMTS utility messages
<i>ADAORD Utility Messages</i>	Describes ADAORD utility messages
<i>ADAPLP Utility Messages</i>	Describes ADAPLP utility messages
<i>ADAPRI Error Messages</i>	Describes ADAPRI utility messages
<i>ADARAI Utility Messages</i>	Describes ADARAI utility messages
<i>ADAREP Utility Messages</i>	Describes ADAREP utility messages
<i>ADARES Utility Messages</i>	Describes ADARES utility messages
<i>ADARPE Utility Messages</i>	Describes ADARPE utility messages
<i>ADARPL Utility Messages</i>	Describes ADARPL utility messages
<i>ADARPP Utility Messages</i>	Describes ADARPP utility messages
<i>ADASAV Utility Messages</i>	Describes ADASAV utility messages
<i>ADASEL Utility Messages</i>	Describes ADASEL utility messages
<i>ADAULD Utility Messages</i>	Describes ADAULD utility messages
<i>ADAVAL Error Messages</i>	Describes ADAVAL utility messages
<i>ADAWRK Utility Messages</i>	Describes ADAWRK utility messages

	<i>ADAZAP Utility Messages</i>	Describes ADAZAP utility messages
	<i>ADAZIN Utility Messages</i>	Describes ADAZIN utility messages



Note: Proprietary functions of Adabas may also return response codes and subcodes, some of which are not described in this manual. If using such Adabas functions and messages or codes occur that are not explained in this manual, refer to the documentation for those functions for additional information.

1 List of Abbreviations

Abbreviation	Meaning
AB	attached buffers
AC	address converter
ADACB	Adabas control block
ASSO	Associator
BP	buffer pool
CID	command ID
CLOG	command log
CQ	command queue
CQE	command queue element
DATA	Data Storage
DBID	database ID
DIB	data integrity block
DSST	Data Storage space table
DVT	descriptor value table
FB	format buffer
FCB	file control block
FDT	field definition table
FID	format ID
FNR	file number
FST	free space table
GCB	general control block
GFID	global format ID
HQ	hold queue
IB	ISN buffer

List of Abbreviations

Abbreviation	Meaning
ISN	internal sequence number
MU	multiple-value field
NI	normal index
PE	periodic group
PLOG	protection log
PPT	parallel participant table (nucleus cluster environments)
RABN	relative Adabas block number
RB	record buffer
SB	search buffer
SIBA	sequential data protection data set
TBI	table of ISNs
TBQ	
TBS	table of sequential ISNs
UI	upper index
UQ	user queue
UQE	user queue element
URL	universal resource locator
VB	value buffer
WORK	Work data set
WP	work pool

2 About this Documentation

- Document Conventions 4
- Online Information and Support 4
- Data Protection 5

Document Conventions

Convention	Description
Bold	Identifies elements on a screen.
Monospace font	Identifies service names and locations in the format <code>folder.subfolder.service</code> , APIs, Java classes, methods, properties.
<i>Italic</i>	Identifies: Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources.
Monospace font	Identifies: Text you must type in. Messages displayed by the system. Program code.
{ }	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.
	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the symbol.
[]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [] symbols.
...	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...).

Online Information and Support

Product Documentation

You can find the product documentation on our documentation website at <https://documentation.softwareag.com>.

In addition, you can also access the cloud product documentation via <https://www.software-ag.cloud>. Navigate to the desired product and then, depending on your solution, go to “Developer Center”, “User Center” or “Documentation”.

Product Training

You can find helpful product training material on our Learning Portal at <https://knowledge.softwareag.com>.

Tech Community

You can collaborate with Software AG experts on our Tech Community website at <https://tech-community.softwareag.com>. From here you can, for example:

- Browse through our vast knowledge base.
- Ask questions and find answers in our discussion forums.
- Get the latest Software AG news and announcements.
- Explore our communities.
- Go to our public GitHub and Docker repositories at <https://github.com/softwareag> and <https://hub.docker.com/publishers/softwareag> and discover additional Software AG resources.

Product Support

Support for Software AG products is provided to licensed customers via our Empower Portal at <https://empower.softwareag.com>. Many services on this portal require that you have an account. If you do not yet have one, you can request it at <https://empower.softwareag.com/register>. Once you have an account, you can, for example:

- Download products, updates and fixes.
- Search the Knowledge Center for technical information and tips.
- Subscribe to early warnings and critical alerts.
- Open and update support incidents.
- Add product feature requests.

Data Protection

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

I Message Prefix Reference

3 Message Prefix Reference

 **Note:** Adabas checkpoints, user abend codes, nucleus response codes, utility return codes, and UES component error codes are described in *Adabas Checkpoints*, *User Abend Codes*, *Nucleus Response Codes*, *Utility Return Codes*, and *Universal Encoding System (UES) Component Error Codes*, respectively. Entire Net-Work DCAM feedback codes and SNA sense codes are described in *DCAM Feedback Codes* and *SNA Sense Codes* respectively.

Prefix	Description	Read
AAF*	Adabas SAF Security messages	<i>AAF* - Adabas SAF Security Messages</i>
AAS*	Adabas Administration Service messages	<i>AAS* - Adabas Administration Service Messages</i>
AAUD*	AUDITLOG messages	<i>AAUD* - AUDITLOG Messages</i>
ACLX*	Adabas Review ADALNK messages	<i>ACLX* - Adabas Review ADALNK Messages</i>
ADAA*	Adabas Analytics messages	<i>ADAA* - Adabas Analytics Messages</i>
ADACM*	ADATCP console messages	<i>ADATCP Messages (Prefix ADACM)</i>
ADAD*	Abend code messages	<i>ADAD* Abend Code Messages</i>
ADAE*	Adabas SAF Security (ADASAF) messages	<i>ADAE* Adabas SAF Security (ADASAF) Messages</i>
ADAF*	Event Replicator for Adabas messages	<i>ADAF* - Event Replicator for Adabas Messages</i>
ADAH*	Dump formatter status messages	<i>ADAH* Dump Formatter Status Messages</i>
ADAI*	ADAIOR system messages	<i>ADAI* - ADAIOR System Messages</i>
ADAJ*	Adabas system messages	<i>ADAJ* System Messages</i>
ADAK*	Adabas system messages	<i>ADAK* System Messages</i>
ADAL*	Command log (CLOG) system messages	<i>ADAL* - Command Log (CLOG) System Messages</i>
ADAM*	ADAMPM system messages	<i>ADAM* -- ADAMPM System Messages</i>
ADAN*	General console messages	<i>ADANnn Console Messages</i>

Message Prefix Reference

Prefix	Description	Read
ADAQ*	Adabas Review Hub system messages	<i>ADAQ* - Adabas Review Hub Messages</i>
ADAR*	Adabas system messages	<i>ADAR* System Messages</i>
ADAS*	Adabas SVC system messages	<i>ADAS* (Adabas SVC) System Messages</i>
ADASIP*	Adabas z/VSE SVC system messages	<i>ADASIP* (Adabas z/VSE SVC) System Messages</i>
ADASM*	Adabas SMF record processing messages	<i>ADASM* Adabas SMF Processing Messages</i>
ADAU*	Adabas utility status messages	<i>ADAU* Utility Status Messages</i>
ADAX*	Adabas cluster nucleus messages	<i>ADAX* - Adabas Cluster Nucleus Messages</i>
ADAZ*	ADAZIP system messages	<i>ADAZ* - ADAZIP System Messages</i>
AFP*	Adabas Fastpath messages	<i>AFP* - Adabas Fastpath Messages</i>
APSPSX*	ADA ECS or ADATCP messages	<i>APSPSX* - ADA ECS or ADATCP Messages</i>
AREV*	Adabas Review hub system messages beginning with the prefix AREV*.	<i>AREV* - Adabas Review Hub Messages</i>
ARF*	Adabas Event Replicator Subsystem messages	<i>Adabas Event Replicator Subsystem Messages</i>
ARMT*	Adabas Review hub system messages beginning with the prefix ARMT*.	<i>ARMT* - Adabas Review Hub Messages</i>
ARST*	Adabas Review hub system messages beginning with the prefix ARST*.	<i>ARST* - Adabas Review Hub Messages</i>
ARVU*	Adabas Review hub system messages beginning with the prefix ARVU*.	<i>ARVU - Adabas Review Hub Messages</i>
ARXM*	Event Replicator Target Adapter messages	<i>ARXM* - Event Replicator for Adabas Messages for Event Replicator Target Adapter</i>
ATM*	Adabas Transaction Manager messages	<i>ATM* - Adabas Transaction Manager Messages</i>
AVI*	Adabas Vista database processing messages	<i>AVInnn - Adabas Vista Database Processing Messages</i>
AVI-*	Adabas Vista processing messages	<i>AVI-xxxx-xx - Adabas Vista Processing Messages</i>
CAS*	Adabas System Coordinator cluster application service (CAS) messages	<i>CAS* - Adabas System Coordinator Cluster Application Service Messages</i>
CHK*	Adabas ADACHK utility messages	<i>ADACHK Utility CHK* Messages</i>
COR*	Adabas System Coordinator kernel messages	<i>COR* - Adabas System Coordinator Kernel Messages</i>
CORD*	Adabas System Coordinator daemon messages	<i>CORD* - Adabas System Coordinator Daemon Messages</i>
CRV*	Adabas ADACHK utility decompression messages	<i>ADACHK Utility CRV* Decompression Messages</i>
CWARN*	Adabas Cache Facility error messages	<i>CWARN* - Caching Facility Error Messages</i>

Prefix	Description	Read
COX*	Universal Encoding Support (UES) Conversion Messages	<i>COX* Universal Encoding System Conversion (UES) Errors</i>
DRU*	Adabas ADADRU utility messages	<i>ADADRU Utility Messages</i>
DSF*	Adabas Delta Save messages	<i>DSF* - Delta Save Facility Messages</i>
DSP*	Adabas Parallel Services cluster data space (ADADSP) messages.	<i>DSP* - Cluster Data Space (ADADSP) Messages</i>
error-*	ADARUN parameter error messages	<i>ADARUN Statement/Parameter Messages</i>
	Adabas Transaction Manager error codes	<i>Adabas Transaction Manager Error Codes</i>
ERROR-001 through ERROR-120	Common Adabas utility error messages	<i>Errors Common to All Utilities</i>
ERROR-121 through ERROR-*	ADAACK utility messages	<i>ADAACK Error Messages</i>
	ADACDC utility messages	<i>ADACDC Utility Messages</i>
	ADACMP utility messages	<i>ADACMP Utility Messages</i>
	ADACNV utility messages	<i>ADACNV Utility Messages</i>
	ADADBS utility messages	<i>ADADBS Utility Messages</i>
	ADADCK utility messages	<i>ADADCK Error Messages</i>
	ADADEF utility messages	<i>ADADEF Utility Messages</i>
	ADAFRM utility messages	<i>ADAFRM Utility Messages</i>
	ADAICK utility messages	<i>ADAICK Error Messages</i>
	ADAINV utility messages	<i>ADAINV Utility Messages</i>
	ADALOD utility messages	<i>ADALOD Utility Messages</i>
	ADAMER utility messages	<i>ADAMER Utility Messages</i>
	ADAMTR utility messages	<i>ADAMTR Utility Messages</i>
	ADAMTS utility messages	<i>ADAMTS Utility Messages</i>
	ADAORD utility messages	<i>ADAORD Utility Messages</i>
	ADAPLP utility messages	<i>ADAPLP Utility Messages</i>
	ADAPRI utility messages	<i>ADAPRI Error Messages</i>
	ADARAI utility messages	<i>ADARAI Utility Messages</i>
	ADAREP utility messages	<i>ADAREP Utility Messages</i>
	ADARES utility messages	<i>ADARES Utility Messages</i>
	ADARPE utility messages	<i>ADARPE Utility Messages</i>
	ADARPL utility messages	<i>ADARPL Utility Messages</i>
	ADARPP utility messages	<i>ADARPP Utility Messages</i>
	ADASAV utility messages	<i>ADASAV Utility Messages</i>
ADAULD utility messages	<i>ADAULD Utility Messages</i>	
ADAVAL utility messages	<i>ADAVAL Error Messages</i>	

Message Prefix Reference

Prefix	Description	Read
	ADAWRK utility messages	<i>ADAWRK Utility Messages</i>
	ADAZAP utility messages	<i>ADAZAP Utility Messages</i>
	ADAZIN utility messages	<i>ADAZIN Utility Messages</i>
LNKR VX*	Adabas Review link routine messages	<i>LNKR VX* Adabas Review Link Routine Messages</i>
MLC*	Software AG mainframe license processing or license utility (LICUTIL) error messages	<i>Software AG Licensing Messages</i>
PARM-ERROR*	Adabas nucleus startup error messages	<i>Nucleus Startup Error Messages</i>
PLI*	ADACOM initialization messages	<i>PLI* - ADACOM Initialization Messages</i>
PLX*	Adabas nucleus cluster environment (ADACLU) messages	<i>PLX* - ADACLU Messages</i>
PL6*	Adabas PRILOG6 print program messages	<i>PL6* - PRILOG6 Print Program Messages</i>
POP*	Adabas System Coordinator server component messages	<i>POP* - Adabas System Coordinator Server Component Messages</i>
REV00*	Adabas Review messages of the format REV00*.	<i>Adabas Review 00xxx Messages</i>
REV20*	Adabas Review messages of the format REV20*.	<i>Adabas Review 20xxx Messages</i>
RE VH*	Adabas Review hub system messages.	<i>RE VH* - Adabas Review Hub Messages</i>
RTP*	Adabas Review Trans- <i>port</i> messages.	<i>RTP* - Adabas Review Trans-<i>port</i> Messages</i>
RVCL*	Adabas Review Batch Client Reporting (REVCLRP) Messages	<i>RVCL* - Adabas Review Batch Client Reporting (REVCLRP) Messages</i>
SAF*	Adabas SAF Security Kernel messages	<i>SAF* - SAF Daemon Messages</i>
SAGE*	Software AG job exit utility (batch) messages for z/VSE systems	<i>SAGE* - z/VSE Batch Job Exit Utility Messages</i>
SAGI*	Batch initialization messages for z/VSE systems	<i>SAGI* - Batch Initialization Messages (z/VSE Only)</i>
SEFM*	Adabas SAF Security (ADASAF) and SAF Security Kernel operator console and command messages.	<i>SEFM* - ADASAF SAF Interface and SAF Security Kernel Messages</i>
SEL*	ADASEL utility messages	<i>ADASEL Utility Messages</i>
SM-PIN*	Adabas messages for the plug-in (PIN) modules of the error handling and message buffering facility	<i>SM-PIN* - PIN Routine Messages</i>
SRT*	Adabas ADACHK utility sort processing.	<i>ADACHK Utility SRT* Sort Messages</i>
WARNING-*	ADARUN parameter warning messages	<i>ADARUN Statement/Parameter Messages</i>

II Message Prefix Reference by Product

4 Message Prefix Reference by Product

The following table groups messages by Adabas product. Bear in mind that messages produced by Adabas components may appear during the processing of its add-ons and companion products, such as Entire Net-Work.

Product	Prefix	Read
Adabas	AAUD*	<i>AAUD* - AUDITLOG Messages</i>
	ADACM*	<i>ADATCP Messages (Prefix ADACM)</i>
	ADAD*	<i>ADAD* Abend Code Messages</i>
	ADAH*	<i>ADAH* Dump Formatter Status Messages</i>
	ADAI*	<i>ADAI* - ADAIOR System Messages</i>
	ADAJ*	<i>ADAJ* System Messages</i>
	ADAK*	<i>ADAK* System Messages</i>
	ADAL*	<i>ADAL* - Command Log (CLOG) System Messages</i>
	ADAM*	<i>ADAM* -- ADAMPM System Messages</i>
	ADAN*	<i>ADANm Console Messages</i>
	ADAR*	<i>ADAR* System Messages</i>
	ADAS*	<i>ADAS* (Adabas SVC) System Messages</i>
	ADASIP*	<i>ADASIP* (Adabas z/VSE SVC) System Messages</i>
	ADASM*	<i>ADASM* Adabas SMF Processing Messages</i>
	ADAU*	<i>ADAU* Utility Status Messages</i>
	APSPSX*	<i>APSPSX* - ADAECS or ADATCP Messages</i>
	CHK*	<i>ADACHK Utility CHK* Messages</i>
	COX*	<i>COX* Universal Encoding System Conversion (UES) Errors</i>

Message Prefix Reference by Product

Product	Prefix	Read
	CRV*	<i>ADACHK Utility CRV* Decompression Messages</i>
	DRU*	<i>ADADRU Utility Messages</i>
	error-*	<i>ADARUN Statement/Parameter Messages</i>
	ERROR-001 through ERROR-120	<i>Errors Common to All Utilities</i>
	ERROR-121 through ERROR-*	<i>ADAACK Error Messages</i>
	ERROR-121 through ERROR-*	<i>ADACDC Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADACMP Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADACNV Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADADBS Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADADCK Error Messages</i>
	ERROR-121 through ERROR-*	<i>ADADEF Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAFRM Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAICK Error Messages</i>
	ERROR-121 through ERROR-*	<i>ADAINV Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADALOD Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAMER Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAMTR Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAMTS Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAORD Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAPLP Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAPRI Error Messages</i>

Product	Prefix	Read
	ERROR-121 through ERROR-*	<i>ADARAI Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAREP Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADARES Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADARPE Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADARPL Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADARPP Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADASAV Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAULD Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAVAL Error Messages</i>
	ERROR-121 through ERROR-*	<i>ADAWRK Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAZAP Utility Messages</i>
	ERROR-121 through ERROR-*	<i>ADAZIN Utility Messages</i>
	MLC*	<i>Software AG Licensing Messages</i>
	PARM-ERROR*	<i>Nucleus Startup Error Messages</i>
	PLI*	<i>PLI* - ADACOM Initialization Messages</i>
	PLX*	<i>PLX* - ADACLU Messages</i>
	PL6*	<i>PL6* - PRILOG6 Print Program Messages</i>
	SAGE*	<i>SAGE* - z/VSE Batch Job Exit Utility Messages</i>
	SAGI*	<i>SAGI* - Batch Initialization Messages (z/VSE Only)</i>
	SEL*	<i>ADASEL Utility Messages</i>
	SM-PIN*	<i>SM-PIN* - PIN Routine Messages</i>
	SRT*	<i>ADACHK Utility SRT* Sort Messages</i>
	WARNING-*	<i>ADARUN Statement/Parameter Messages</i>
	—	<i>Adabas Checkpoints</i>
	—	<i>User Abend Codes</i>
	—	<i>Nucleus Response Codes</i>

Message Prefix Reference by Product

Product	Prefix	Read	
	—	<i>Utility Return Codes</i>	
	—	<i>Universal Encoding System (UES) Component Error Codes</i>	
	Adabas Administration Service	AAS*	<i>AAS* - Adabas Administration Service Messages</i>
Adabas Analytics	ADAA*	<i>ADAA* - Adabas Analytics Messages</i>	
Adabas Cache Facility	CWARN*	<i>CWARN* - Caching Facility Error Messages</i>	
Adabas Cluster Services	ADAX	<i>ADAX* - Adabas Cluster Nucleus Messages</i>	
Adabas Delta Save	DSF*	<i>DSF* - Delta Save Facility Messages</i>	
Adabas Fastpath	AFP*	<i>AFP* - Adabas Fastpath Messages</i>	
Adabas Parallel Services	DSP*	<i>DSP* - Cluster Data Space (ADADSP) Messages</i>	
	ADAX*	<i>ADAX* - Adabas Cluster Nucleus Messages</i>	
Adabas Review	ACLX*	<i>ACLX* - Adabas Review ADALNK Messages</i>	
	ADAQ*	<i>ADAQ* - Adabas Review Hub Messages</i>	
	AREV*	<i>AREV* - Adabas Review Hub Messages</i>	
	ARMT*	<i>ARMT* - Adabas Review Hub Messages</i>	
	ARST*	<i>ARST* - Adabas Review Hub Messages</i>	
	ARVU*	<i>ARVU - Adabas Review Hub Messages</i>	
	LNKR VX*	<i>LNKR VX* Adabas Review Link Routine Messages</i>	
	REV00*	<i>Adabas Review 00xxx Messages</i>	
	REV20*	<i>Adabas Review 20xxx Messages</i>	
	RE VH*	<i>RE VH* - Adabas Review Hub Messages</i>	
	RTP*	<i>RTP* - Adabas Review Trans- port Messages</i>	
	RVCL*	<i>RVCL* - Adabas Review Batch Client Reporting (REVCLRP) Messages</i>	
Adabas SAF Security	AAF*	<i>AAF* - Adabas SAF Security Messages</i>	
	ADAE*	<i>ADAE* Adabas SAF Security (ADASAF) Messages</i>	

Product	Prefix	Read
	SEFM*	<i>SEFM* - ADASAF SAF Interface and SAF Security Kernel Messages</i>
	—	<i>SAF Return Codes</i>
	—	<i>SAF Internal Function Codes</i>
Adabas SAF Security Kernel	SAF*	<i>SAF* - SAF Daemon Messages</i>
	SEFM*	<i>SEFM* - ADASAF SAF Interface and SAF Security Kernel Messages</i>
	—	<i>SAF Return Codes</i>
	—	<i>SAF Internal Function Codes</i>
Adabas System Coordinator	CAS*	<i>CAS* - Adabas System Coordinator Cluster Application Service Messages</i>
	COR*	<i>COR* - Adabas System Coordinator Kernel Messages</i>
	CORD*	<i>CORD* - Adabas System Coordinator Daemon Messages</i>
	POP*	<i>POP* - Adabas System Coordinator Server Component Messages</i>
Adabas Transaction Manager	ATM*	<i>ATM* - Adabas Transaction Manager Messages</i>
	error-*	<i>Adabas Transaction Manager Error Codes</i>
Adabas Vista	AVI*	<i>AVInnn - Adabas Vista Database Processing Messages</i>
	AVI-*	<i>AVI-xxxx-xx - Adabas Vista Processing Messages</i>
Adabas for zIIP	ADAZ*	<i>ADAZ* - ADAZIP System Messages</i>
Event Replicator for Adabas	ADAF*	<i>ADAF* - Event Replicator for Adabas Messages</i>
	ARF*	<i>Adabas Event Replicator Subsystem Messages</i>
	ARXM*	<i>ARXM* - Event Replicator for Adabas Messages for Event Replicator Target Adapter</i>

III

5

ADARUN Statement/Parameter Messages

The Adabas ADARUN statements and parameters define the nucleus operating environment. The error messages that can result from ADARUN statements and parameters are described in this section. These messages have the following format:

```
ADARUN error-nn,message-text
```

where *nn* is the message number and *message-text* describes the error. All ADARUN error messages are accompanied by a user abend 35 (abnormal end without a dump) code.

For information regarding ADARUN parameter syntax, refer to the *Adabas Operations Manual*.

Error-1	I/O error Reading DDCARD
Explanation	A job control (JCL/JCS) error occurred.
Action	Correct the error and rerun the job.
Error-2	Unknown module
Explanation	The library allocation JCL is incorrect.
Action	Correct the error and rerun the job.
Error-3	Keyword ADARUN missing
Explanation	The ADARUN parameter statement is missing the literal "ADARUN" at the beginning of the statement.
Action	Add the ADARUN keyword and rerun the job.

Error-5	Invalid parameter syntax
Explanation	One of the following errors has occurred: <ul style="list-style-type: none">■ An ADARUN input line was encountered without a valid parameter.■ A delimiter is missing between ADARUN parameters.■ A parameter value is missing.■ A parameter value is too long.■ The numeric value specified for the ADARUN parameter is too large.■ An invalid unit indicator has been specified for a numeric parameter.■ An invalid hexadecimal string has been specified.■ Too many values have been specified in a list of values.■ A parameter keyword is missing.
Action	Correct the error and rerun the job.
Error-6	Ambiguous keyword {ambkey}
Explanation	ADARUN detected an ambiguous keyword (<i>ambkey</i>) in its specifications.
Action	Correct the error and rerun the job.
Error-7	Unknown keyword {keyword}
Explanation	ADARUN detected the invalid keyword shown in the message (<i>keyword</i>).
Action	Correct the error and rerun the job.
Error-8	Error loading module {modname}
Action	ADARUN detected a nonzero return code from the operating system's load function.
Action	Refer to any related ADAI <i>nn</i> or other messages for the specific return code value, then refer to the appropriate operating system information to determine what action to take.
Error-9	ADARUN not called from USER program
Explanation	ADARUN was <i>not</i> called by a user program but the ADARUN PROGRAM parameter was specified with a value of "USER" or "RENTUSER".
Action	Correct the JCL or control statements and rerun the job.

Error-12	Invalid CMDQMODE = operand (above, below)
Explanation	BS2000 only. The CMDQMODE parameter specified an incorrect syntax option.
Action	Job terminates. Set the correct parameter value.
Error-13	Invalid TAPEREL = operand (NO, RELEASE, KEEP, UNLOAD, KEEPUNL)
Explanation	BS2000 only. The TAPEREL parameter specified an incorrect syntax option.
Action	Job terminates. Set the correct parameter value.
Error-20	Wrong AMODE-24 for RMODE-31
Explanation	ADARUN detected one or more loaded modules linked with RMODE={ANY 31} while it runs in AMODE=24.
Action	Check the load library and either relink modules linked with AMODE=24 to AMODE={ANY 31}, or relink modules linked with RMODE=ANY to RMODE=24.
Error-21	Inconsistent CLUSTER parameter
Explanation	ADARUN detected an inconsistent CLUSTER parameter setting: <ul style="list-style-type: none"> ■ CLUSTER=SYSPLEX or CLUSTER=LOCAL and NUCID=0; or ■ CLUSTER=NO (default) but NUCID is nonzero.
Action	Correct the error and rerun the job.
Error-22	Inconsistent NPLOG or NCLOG parameter
Explanation	ADARUN detected an inconsistent parameter: <ul style="list-style-type: none"> ■ Both NPLOG/NCLOG and DUALPLD/DUALCLD are specified; or ■ PPLOGDEV/CLOGDEV and PLOGSIZE/CLOGSIZE are specified but NPLOG/NCLOG is not specified; or ■ UEX2 together with NPLOG/NCLOG instead of UEX12 was found in the ADARUN parameters. ■ The CLOGMAX or CLOGBMAX parameter setting is smaller than 368 bytes.
Action	Correct the error and rerun the job.

Error-23	Invalid value for parameter {parmname}
Explanation	ADARUN detected an invalid or inconsistent value for the parameter listed in the message (<i>parmname</i>).
Action	Correct the error and rerun the job.
Error-25	Version mismatch in one or more modules
Explanation	One or more Adabas modules loaded by ADARUN have different version/release/patch-level indicators (or in some cases, version/release indicators) than ADARUN itself. The mismatching modules are listed in preceding "ADARUN Warning: Mismatching version indicators in module <i>xxxxxx</i> " messages, where <i>xxxxxx</i> is the load module name.
	ADARUN terminates with the Error-25 only if the Adabas SAF Security add-on product is installed.
Action	Provide a load library (or concatenation of load libraries) where all Adabas modules belong to the same Adabas version, release and patch-level, or for add-on products, the same version and release level.
Error-29	Loaded modules do not support ENCRYPTION
Explanation	The Adabas load library is not correct and does not fully support Adabas Encryption, Adabas Auditing or Adabas SAF Security 8.3. Either the ADAIOR/IOS modules do not support Adabas Encryption or some of the required maintenance in the nucleus and utilities is missing.
Action	Review and correct the JOBLIB/STEPLIB concatenation or combined load library, as per the installation instructions for Adabas Encryption. Ensure that all zaps required for Adabas Encryption, Adabas Auditing or Adabas SAF Security 8.3 have been applied.
Error-31	IDTNAME does not start "ADA"
Explanation	This is a BS2000 only error. The user has defined the IDTNAME or the ENVNAME in the SSFB2C parameter module which does not begin with "ADA". This will lead to a failure in communication between Client applications and nucleus.
Action	Correct the IDTNAME in the ADARUN parameter list so that it begins with "ADA" and restart the nucleus.
Error-32	SWITCHNR out of range 0 - 31
Explanation	ADARUN detected an inconsistent Adabas BS2000 parameter. The job switch number to be set when a non-zero return code occurs is out of the range of 1 to 31.
Action	Correct the error and rerun the job.

Error-33	SUBMPSZ needs to be higher than x100000
Explanation	ADARUN detected an inconsistent Adabas BS2000 parameter. The size of the declared subtask memory pool is too small.
Action	Correct the error and rerun the job.
Error-34	PAMREQS must be a value > 0
Explanation	ADARUN detected an inconsistent Adabas BS2000 parameter. The maximum number of PAM blocks sent in one PAM macro must be greater than zero.
Action	Correct the error and rerun the job.
WARNING 26	Parameter AMODE out of service
Explanation	BS2000 only. ADARUN statement AMODE=31 detected. This parameter has been removed from Adabas. Targets that use SSF must run in AMODE 31.
Action	The job continues. Remove AMODE= from your ADARUN statements.
WARNING 27	Parameter IDTMODE out of service
Explanation	BS2000 only. IDTMODE=ABOVE statement detected. This parameter has been removed from Adabas. IDTs created by SSF are allocated above the 16-megabyte line.
Action	The job continues. Remove IDTMODE= from your ADARUN statements.
WARNING 28	Parameter NECB out of service
Explanation	BS2000 only. NECB= statement detected. This parameter has been removed from Adabas. The posted ECB queue can no longer overflow.
Action	Job continues. Remove NECB= from your ADARUN statements.

IV

Adabas Checkpoints

6 Adabas Checkpoints

Checkpoint names starting with "SYN" are reserved for the Adabas nucleus and utilities, as described in:

- SYNC -- A synchronized checkpoint made during nucleus initialization, including the status of the ADARUN IGNDIB and FORCE parameters.
- SYN F -- A checkpoint taken by a user program or utility that requires exclusive (EXF) control of one or more files.
- SYN P -- A checkpoint from a utility that requires privileged control. Such a utility can perform updating without using the Adabas nucleus.
- SYN S (mainframe only) -- A checkpoint from Adabas Online System (SYSAOS), ADADBS, or the nucleus. The table below identifies the source. The function identified by this checkpoint is implemented without user intervention during regeneration.

Exceptions include a second SYN S 5B recorded at the end of a nucleus session, SYN S 60 recorded at an interval specified by the ADARUN INTNAS parameter, and SYN S 61 recorded when more space is allocated for a file.

- SYN V (mainframe only) -- Indicates that a volume ID changed during sequential write to a data set is being closed.
- SYN X -- A checkpoint from a utility requiring exclusive control (EXU) of one or more files.
- SYN 1 (mainframe only) -- A checkpoint made at the beginning of online ADASAV execution (SAVE database function).
- SYN 2 (mainframe only) -- A checkpoint made at the end of online ADASAV execution (SAVE database function).
- SYN 4 (mainframe only) -- A checkpoint made at the beginning of online ADASAV execution (SAVE files operation).
- SYN 5 (mainframe only) -- A checkpoint made at the end of online ADASAV execution (SAVE files operation).

The following table describes the checkpoints written by the Adabas nucleus or utilities:

Type	Name	Originator	Description
01	SYNC	ADANUC	Written by nucleus at start of nucleus session.
01	SYNF	User/Utility	User/utility session OPEN with files used in EXF (exclusive use) mode.
01	SYNS	ADANUC	Written by the starting of a second or subsequent Parallel Services or Cluster Services nucleus.
01	SYNX	EXU user	EXU user open.
02	SYNV	ADANUC	VOLSER entry. Written at volume switch on DD/SIBA and at the end of the session if sequential logging is used.
03	SYNF	User/Utility	Close checkpoint for an EXF user.
03	SYNX	EXU	Close checkpoint for an EXU user.
05	SYN4	ADASAV	SAVE file(s)-start of operation with nucleus active.
05	SYN5	ADASAV	SAVE file(s)-end of operation with nucleus active.
05	SYNP	ADASAV	SAVE file(s)-start of operation
06	SYN1	ADASAV	SAVE database-start of operation with nucleus active.
06	SYN2	ADASAV	SAVE database-end of operation with nucleus active.
06	SYNP	ADASAV	SAVE database-start of operation
07	SYNP	ADASAV	RESTORE file(s)-end of operation
08	SYNP	ADASAV	RESTPLOG-end of operation
09	SYNV	ADASAV	SAVE file(s), VOLSER entry. Written at volume change on DD/SAVE and at SAVE-operation end.
0A	SYNV	ADASAV	SAVE database, VOLSER entry. Written at volume switch on DD/SAVE and at SAVE-operation end.
0B	SYN1	ADASAV	SAVE DELTA-start of operation with nucleus active
0B	SYN2	ADASAV	SAVE DELTA-end of operation with nucleus active
0B	SYNP	ADASAV	SAVE DELTA-end of operation
0C	SYNP	ADASAV	RESTORE DELTA-end of operation
0D	SYNP	ADASAV	MERGE-end of operation
0E	SYNV	ADASAV	SAVE DELTA, VOLSER entry
0F	SYNV	ADASAV	MERGE, VOLSER entry
10	SYNP	ADAINV	COUPLE files
11	SYNP	ADAINV	INVERT field(s)
15	SYNP	ADAORD	REORDER Associator database
16	SYNP	ADAORD	REORDER Data Storage database
17	SYNP	ADAORD	REORDER database
18	SYNP	ADAORD	REORDER Associator file
19	SYNP	ADAORD	REORDER Data Storage file

Type	Name	Originator	Description
1A	SYNP	ADAORD	REORDER file
1B	SYNP	ADAORD	STORE
1C	SYNP	ADAORD	RESTRUCTURE
1D	SYNP	ADADEF	DEFINE NEWWORK
1E	SYNP	ADADEF	MODIFY (default character encodings, timezone)
22	SYNX	ADARES	REGENERATE file
23	SYNX	ADARES	BACKOUT file
24	SYNX	ADARES	REGENERATE all; CPEXLIST lists excluded files
25	SYNX	ADARES	BACKOUT all; CPEXLIST lists excluded files
26	SYNP	ADARES	REPAIR Data Storage
27	SYNP	ADARES	COPY function sucessfully completed
27	SYNV	ADARES	COPY sequential protection log
28	SYNP	ADARES	PLCOPY function successfully completed
28	SYNV	ADARES	PLCOPY dual or multiple protection log
29	SYNP	ADARES	ADARES CLCOPY function successfully completed.
29	SYNV	ADARES	CLCOPY dual or multiple command log
2A	SYNP	ADARES	PLCOPY MERGE function successfully completed
2A	SYNV	ADARES	PLCOPY MERGE dual or multiple protection log
2B	SYNP	ADARES	CLOG MERGE function successfully completed
2B	SYNV	ADARES	CLOG MERGE dual or multiple command log
30	SYNP	ADALOD	LOAD file
31	SYNP	ADALOD	Mass update
35	SYNX	ADAULD	Unload file
3F	SYNP	ADAZAP	Successful VERIFY - REPLACE
40	SYNS	SYSAOS	Add extent
41	SYNS	SYSAOS	CHANGE default field length
42	SYNS	SYSAOS	DECREASE database size
44	SYNS	SYSAOS	Delete file
45	SYNS	SYSAOS	INCREASE database size
47	SYNS	SYSAOS	RECOVER space
48	SYNS	SYSAOS	Refresh file
49	SYNS	SYSAOS	Remove component file from expanded-file chain
4A	SYNS	SYSAOS	Release descriptor
4B	SYNS	SYSAOS	RENAME file
4C	SYNS	SYSAOS	RENUMBER file
4D	SYNS	SYSAOS	RESET DIB

Type	Name	Originator	Description
4E	SYNS	SYSAOS	Reuse ISN
4F	SYNS	SYSAOS	Reuse Data Storage
50	SYNS	SYSAOS	UNCOUPLE files
51	SYNS	SYSAOS	ALLOCATE file extent
52	SYNS	SYSAOS	DEALLOCATE file extent
53	SYNS	SYSAOS	Delete checkpoint
54	SYNS	SYSAOS	Set user priority
55	SYNS	SYSAOS	Modify FCB
57	SYNS	SYSAOS	DEFINE file
58	SYNS	SYSAOS	Write FDT
59	SYNS	SYSAOS	DEFINE new field
5B	SYNS	ADADBS	Write refreshed statistics (some or all per user request)
5B	SYNS	ADANUC	Write (all) statistics at end of nucleus session
5C	SYNS	SYSAOS	CHANGE default field format
5D	SYNS	SYSAOS	Change file encoding
5E	SYNS	ADADBS	ADADBS REPTOR function (refer to your Event Replicator for Adabas documentation)
60	SYNS	ADANUC	Nucleus statistic checkpoint
61	SYNS	ADANUC	Allocate file space
64	SYNS	ADASCR	Protect files
65	SYNS	ADASCR	Protect fields
66	SYNS	SYSAOS	Link component file into expanded-file chain
67	SYNS	NUCLEUS	Session start with IGNDIB=YES
68	SYNS	SYSAOS	Set USERISN on/off
69	SYNS	SYSAOS	Set MIXDSDEV on/off
6A	SYNS	SYSAOS	Install Delta Save DLOG area
6B	SYNS	SYSAOS	Change Delta Save DLOG area
6C	SYNS	SYSAOS	Remove Delta Save DLOG area
6D	SYNS	ADANUC	NUC-ZAP was used
6E	SYNS	ADADBS	ADADBS REPLICATION function (refer to your Event Replicator for Adabas documentation)
6F	SYNS	SYSAOS	Online process initiated
70	SYNS	SYSAOS	Online invert process
71	SYNS	SYSAOS	Online reorder process
73	SYNC	ADANUC	Nucleus (nuclei) successfully quiesced.
74	SYNC	ADANUC	Nucleus (nuclei) have resumed normal processing.
75	SYNS	ADANUC	Delete heuri-user-entry after Response 72 was detected during nucleus startup.

Type	Name	Originator	Description
76	SYNS	ADANUC	Delete heuri-user-entry after Response 72 was detected during nucleus session.
77	SYNS	ADADBS	Enable spanned record support.
78	SYNS	ADADBS	Enable or disable extended MU or PE fields
7A	SYNS	ADADBS	Delete field from the FDT
7B	SYNS	ADANUC	Logically delete a descriptor
7C	SYNS	SYSAOS	Set file status: READONLY mode
7D	SYNS	ADADBS	Add or delete CLOG
7E	SYNS	ADADBS	Add or delete PLOG
7F	SYNS	ADANUC	Change fields
81	SYNS	ADANUC	Modify FCB
82	SYNS	ADANUC	Online add or increase of an ASSO or DATA data set
83	SYNS	ADANUC	Autoincrease of an ASSO or DATA data set
84	SYNS	SYSAOS	AOSLOG information with user ID

V

7 Adabas Console Messages (ADAN* & ADACM*)

- ADATCP messages ADACM* messages ADATCP Messages (Prefix ADACM) 116

The following messages may be displayed on the operator console during an Adabas session. Each message number is followed first by either:

- "ADAB" for Adabas SVC module messages; or
- the database identification (DBID) of the physical database for which the message applies.

Then follows the error date and time and finally the message text. The console messages have the same general format:

```
ADANnn dbid yyyy-mm-dd hh:mm:ss message text
```

Because of space restrictions, the message descriptions are shown here without the database ID and date/time portion of the message.



Note: Some message numbers have been assigned to more than one message text.

ADAN01	Adabas ({vv . r . s}) is active Mode = {single multi} Running {with without} recovery-log
Explanation	The Adabas nucleus at release level <i>v . r . s</i> has been initiated successfully. Multi- or single-user mode is indicated, and whether the nucleus is running with or without the Adabas Recovery Aid (ADARAI) log.
ADAN02	Nucleus-run {with without} protection log
Explanation	The Adabas nucleus session has been initiated and database protection logging either has or has not been specified. The subsequent execution of the REGENERATE and BACKOUT functions of the ADARES utility for any updates applied during the session is only possible when protection logging has been specified. However, transaction recovery for ET logic users is not affected by PLOG specification since data protection information for such users is still maintained on the Adabas Work file.
ADAN03	Adabas coming up
Explanation	Adabas session initialization is in progress.
ADAN03	Initializing NUCID={nnnnn} INTNUCID={xx}
Explanation	Initialization is in progress for the specified external nucleus ID (<i>nnnnn</i>) with the specified internal nucleus ID (<i>xx</i>). This message is useful for determining the internal system-assigned nucleus ID associated with the external user-assigned NUCID.

ADAN04	Abnormal end due to Work overflow
Explanation	The Adabas nucleus detected an overflow condition on the Work data set that could not be rectified by normal Adabas backout processing. The Adabas session was therefore terminated abnormally.
Action	<p>In a non-cluster environment:</p> <p>When running in a non-cluster environment, the quickest way to recover the database is to run an ADARES REGENERATE from the last protection log data sets at the time of the abend. The regenerate should start at the checkpoint created by the last ADASAV SAVE operation or the last nucleus start (SYN2 or SYNC checkpoint). This way of recovery is valid if no ADADBS (or AOS) DELETE FILE, RENUMBER FILE, ADAORD STORE OVERWRITE, or ADASAV RESTORE/RESTONL OVERWRITE functions were performed after the start checkpoint of the ADARES REGENERATE run.</p> <p>An alternative way to recover the database that is always valid is to run an ADASAV RESTORE/RESTONL from the last database save, followed by an ADARES REGENERATE starting at the checkpoint created by that SAVE operation.</p> <p>In a cluster environment (Adabas Cluster Services or Adabas Parallel Services):</p> <p>When running in a cluster environment, the remaining active nuclei will perform an online recovery process. The failed nucleus can simply be restarted to continue processing after the online recovery.</p> <p>If the online recovery process also gets a Work overflow, all remaining active nuclei will go down, too. In this case, any of the cluster nuclei that have not yet gotten a Work overflow can be started in an attempt to recover the database. Alternatively, or if this fails, a new nucleus can be added to the cluster. Its Work data set needs to be the same size as those of the other nuclei in the cluster and its LP parameter should be set as high as possible within that size. The failed nuclei can be restarted after the recovery has succeeded.</p> <p>If all else fails, the database can be recovered as described above for the non-cluster environment.</p>
ADAN05	<p>Warning. Now it is too late to copy DDPLOGR{n} FROMBLK={blk1}, FROMTIME={timestamp1} TOBLK = {blk2}, TOTIME={timestamp2} ERROR obtaining timestamp information IOR function = X'{nn}', response = X'{nn}'</p>
Explanation	Adabas has begun to write data protection log data to the data set identified by DD/PLOGR n . This means that the data set can no longer be copied to tape for subsequent use as input to the REGENERATE or BACKOUT functions of the ADARES utility. A user exit 2 (dual log processing) or a user exit 12 (multiple log processing) call either was not made or did not successfully copy the DD/PLOGR n data set with the ADARES utility.

Normally, the from and to blocks and the from and to timestamps being overwritten are given in the message. The last two lines are printed only if an error occurs when the nucleus determines the contents of the PLOG that is about to be overwritten.

- ADAN05** **I/O error on PLOGR{n}**
Explanation An I/O error occurred on the dual or multiple protection log data sets. The Adabas nucleus terminates abnormally with user abend 21.
- ADAN06** **Number of HQEs = {nnn}**
Explanation This message is displayed in response to the operator command DNH. The number of ISNs currently in the Adabas hold queue is represented by "nnn".
- ADAN06** **I/O error on SIBA**
Explanation An I/O error occurred on sequential protection log SIBA. If the nucleus runs with PLOGRQ=YES or FORCE, the nucleus terminate with user abend 22; otherwise, the SIBA is set to DUMMY and processing continues without protection logging.
- ADAN07** **SIBA is set to DUMMY**
Explanation This message may follow an ADAN06 message.
- ADAN08** **Current HQ is empty**
Current HQ
File={file}, ISN={isn}, {Secondary}, {shared}
User={user}, SecUID='{secuid}' | ' '
Job='{jobname}', TID='{tid}'
...{num} more users
{n} out of {m} HQEs displayed
Explanation This message is produced in response to DHQ and DHQA operator commands. The response consists of a header line followed by one or more file/ISN detail sections. Each file/ISN detail section is followed by information about the user who holds the ISN. When there are no active hold queue elements, the response is the single "Current HQ is empty" line.
- The following table describes the possible substitutions provided in the message for each hold queue element.

Message Substitutions	Description
<i>file</i>	The file number.
<i>isn</i>	The record's Internal Sequence Number (ISN).
<i>jobname</i>	The name of the job from which the user issued Adabas calls.
<i>m</i>	The total number of active hold queue elements.
<i>n</i>	The number of hold queue elements displayed.
<i>num</i>	If all users were not displayed, this shows the number remaining.
<i>secuid</i>	The user's system security user ID (or logon ID). If none is available, the value ' ' (a blank space between two single quotes) displays.
<i>shared</i>	The term "Shared" is displayed if this file/ISN is not exclusive to a single user.
<i>Secondary</i>	The term "Secondary" is displayed if this file/ISN is a secondary ISN of a spanned record.
<i>tid</i>	The last eight bytes of the communication ID. If the user is hosted by a TP monitor, often a terminal ID or user ID is shown here. For a batch user, an STCK timestamp is shown. If this ID is comprised of printable hexadecimal characters it will appear in quotes, otherwise it will appear in alphanumeric characters.
<i>user</i>	The Adabas-assigned internal user ID. This is unique within a single Adabas nucleus.

ADAN09 **Number of UQEs = {nnn}**

Explanation This message is displayed in response to the operator command DNU. "nnn" indicates the number of user queue elements currently active.

ADAN11 **Current UQ**
User={user},SecUID={ {secuid}' | ' }
Comm-ID={communication-id}
Job='{jobname}',TID='{tid}'
ETID='{etid}',Type={type},Status={status}
Session={session-min}, Inactive={inactive-sec }
File list has {count} files [(restricted)]:
{file}({acctype}),...
No UQEs selected for display
-- {n} out of {m} UQEs displayed
Current UQ is empty

Explanation This message is displayed in response to the DUQ, DAUQ, DUQA, DUQE, and DUUQE operator commands. Not every line of this message will appear; the actual text of the message is determined by the actual command that is issued.

- The "Current UQ is empty" line appears when there are no active user queue elements.
- The "Current UQ" header line appears only in responses to the DUQ, DAUQ, and DUQA commands.
- The optional "(restricted)" text is displayed if you issued an OP command with Command Option 1 set to "R" and is restricted to using only the listed files.
- The "No UQEs selected for display" line appears in DUQA, DUQE and DDUQE command responses when no UQEs satisfy the filter criterion.

The following table describes the possible substitutions provided in the message for each user queue element.

Message Substitutions	Description
<i>acctype</i>	The file access type: <ul style="list-style-type: none"> ■ A: ET user reading the file or access-only user (ACC) ■ F: Exclusive file control (EXF) ■ P: Privileged (utilities and Adabas Online System) ■ S: Online file save ■ U: ET user updating the file (UPD) ■ X: Exclusive-update file control (EXU)
<i>communication-id</i>	The 28-byte communication ID in hexadecimal. This appears only in DUQE responses.
<i>count</i>	The quantity of file numbers in the following file list. The file list appears only in DUQE responses.
<i>etid</i>	The user's ETID (specified in the Additions-1 field of the OP command) or "None" if no ETID is present.
<i>file</i>	The file number. Repeated for each file in the user's file list.
<i>inactive-sec</i>	The time in seconds (rounded down) since the user's last command was selected for processing.
<i>jobname</i>	The name of the job from which the user issued Adabas calls.
<i>m</i>	The total number of active UQEs.
<i>n</i>	The number of UQEs displayed. This trailer line appears only in DUQ, DAUQ, DUQA and DUUQE responses.
<i>secuid</i>	The user's system security user ID (or logon ID). If none is available, the value ' ' (a blank space between two single quotes) displays.
<i>session-min</i>	The time in minutes (rounded down) since the user session started.

Message Substitutions	Description
<i>status</i>	<p>The user status:</p> <ul style="list-style-type: none"> ■ ET: ET logic user at ET status ■ Heur: Two-phase commit transaction heuristically terminated ■ HR-BT: Two-phase commit transaction heuristically backed out ■ HR-ET: Two-phase commit transaction heuristically committed ■ OK: None of the above ■ PET: Two-phase commit transaction with preliminary ET done, waiting for final ET. ■ T-Out: User timed out, response code 9 pending ■ Trans: ET logic user in a transaction (holding ISNs) ■ WK4: Two-phase commit transaction in PET status, copied to Work part 4
<i>tid</i>	<p>The last eight bytes of the communication ID. If the user is hosted by a TP monitor, often a terminal ID or user ID is shown here. For a batch user, an STCK timestamp is shown. If this ID is comprised of printable hexadecimal characters it will appear in quotes, otherwise it will appear in alphanumeric characters.</p>
<i>type</i>	<p>The user type:</p> <ul style="list-style-type: none"> ■ 2PC: ET logic user during two-phase commit ■ ACC: Access-only user ■ ET: ET logic user ■ EXF: Exclusive file control user ■ EXU: Exclusive-update file control user ■ UTI: Utility or Adabas Online System (AOS) user
<i>user</i>	<p>The Adabas-assigned internal user ID. This is unique within a single Adabas nucleus.</p>

ADAN13

Explanation

Number of posted CQEs = {nnn}

This message is displayed in response to the DNC operator command. "nnn" indicates the number of posted command queue elements.

ADAN14 **Current CQ is empty**
Cmd={command}, File={file}, Len={len}
Seq-Nr={seqnr}, Status={status}
Time={num} sec ago, SecUID={'{secuid}'| ' '}
Job='{jobname}', TID='{tid}'
-- {cqecount} CQEs displayed

Explanation This message is displayed in response to DCQ operator commands. The response consists of a header line followed by one or more detail sections describing active CQEs and a trailer line. When there are no active command queue elements, the response is the single "Current CQ is empty" line.

The following table describes the possible substitutions provided in the message for each command queue element.

Message Substitutions	Description
<i>command</i>	The two-character Adabas command code.
<i>cqecount</i>	The number of command queue elements displayed.
<i>file</i>	The file number.
<i>jobname</i>	The name of the job from which the user issued Adabas calls.
<i>len</i>	The total length of the user's buffers and control structures passed to the nucleus through the attached buffer pool.
<i>num</i>	The time in seconds (rounded down) since this command was added to the command queue.
<i>secuid</i>	The user's system security user ID (or logon ID). If none is available, the value ' ' (a blank space between two single quotes) displays.
<i>seqnr</i>	The command sequence number
<i>status</i>	The command status. The following values are possible: <ul style="list-style-type: none"> ■ Done: The command is complete and waiting for the user to retrieve the results. ■ Commit: An ET command is waiting for protection data to be written to the Work data set and the PLOG. ■ Wait-I: The command is waiting for an ISN held by another user. ■ Wait-S: The command is waiting for space in the workpool. ■ Wait-C: The command is waiting for other commands. ■ Trig: A precommand triggered procedure is running. ■ Ready: The command is ready to be selected. ■ Active: The command is being processed. ■ None: The command status cannot be determined. This may occur when the CQE is being built or released.

Message Substitutions	Description
<i>tid</i>	The last eight bytes of the communication ID. If the user is hosted by a TP monitor, often a terminal ID or user ID is shown here. For a batch user, an STCK timestamp is shown. If this ID is comprised of printable hexadecimal characters it will appear in quotes, otherwise it will appear in alphanumeric characters.

ADAN15 **LBP-size too small for the number of threads**

Explanation The specified or available buffer pool space may not be large enough for the number of threads specified by the ADARUN NT parameter. This message is a warning. Adabas allocates 50 kilobytes per thread and processing continues.

Action Either increase the buffer pool size (specified by the ADARUN LBP parameter) or decrease the thread count (with the ADARUN NT parameter). Restart Adabas. If the error occurs again, allocate more address space for the Adabas nucleus and check the session I/O statistics for buffer efficiency.

ADAN16 **{ADARUN-parameter-settings}**

Explanation This message is displayed on the console in response to the operator command DPARM. The current setting for each ADARUN parameter specified for an Adabas nucleus is given using this message number.

Action No action is required for this informational message.

ADAN17 **{dbid} {yyyymmdd} {hh:mm:ss} {adabas-statistic}**

Explanation This message is displayed in response to the operator command DSTAT. Various Adabas statistics appear for *adabas-statistic*, including statistics such as the number of Associator, Data Storage, and Work read and write I/Os and buffer flush statistics.

ADAN18 **THN={nnn}, ST={status}, USE={ccc}**

Explanation In response to the operator command DTH, shows the following information for each thread:

<i>nnn</i>	thread number	
<i>status</i>	thread status:	
	AA	Active
	RR	Ready to run
	UU	Unused
	WAP	Waiting for asynchronous post

WE	Waiting for event
WHQ	Waiting for hold queue space
WI	Waiting for I/O
WSP	Waiting for workpool space
WLF	Waiting for logical buffer flush
WPF	Waiting for physical buffer flush
WP2	Waiting for PLOG write I/O
WQE	Waiting for queued event
WRB	Waiting for RABN
WSE	Waiting for simple event
WTI	Waiting for time elapse
WW2	Waiting for WORK write I/O
W*	Waiting for other event
CCC	count of commands processed by the thread

ADAN19

Buffer flush is asynchronous

Explanation

This message and the asynchronous buffer flush occur when the ADARUN LFIOP parameter specifies a nonzero value.

ADAN1A

ASSO:
VOLSER High RABN
{volser high-rabn}
Reads {rrrr}
Writes {wwww}
ASSO total:
Reads {rrrr}
Writes {wwww}
DATA:
VOLSER High RABN
{volser high-rabn}
Reads {rrrr}
Writes {wwww}
DATA total:
Reads {rrrr}
Writes {wwww}
Total:
Reads
Writes {wwww}

Explanation

This message is used to display statistics about the number of ASSO and DATA I/Os by volume serial (VOLSER) number. The number of reads and writes to each volume is displayed. This message is printed as output for the operator command DVOLIO.

Action	No action is required for this informational message.
ADAN1B	File Commands {{file cmd count}}... Total {totalcount}
Explanation	This message is used to display statistics about the number of commands by file. This message is printed as output for the operator command DFILESTAT.
Action	No action is required for this informational message.
ADAN1C	Type Commands {{command count}}... Total {totalcount}
Explanation	This message is used to display statistics about the distribution of commands by type.
Action	No action is required for this informational message.
ADAN1D	Error {operation file rc system code}
Explanation	An error occurred using file <i>file</i> . The <i>operation</i> may be either opening, closing or writing. The ADAIOR return code is <i>rc</i> and <i>system code</i> is any operating system return code.
Action	If you are unable to resolve the error, contact your Software AG technical support representative.
ADAN1U	{cccc} license check failed: setting {pppp}=NO
Explanation	When product license check did not pass, the product <i>ppppp</i> with product code <i>cccc</i> was disabled in a utility or nucleus session.
Action	In order to activate the product, provide a valid license from the start or - provided that the product supports this - during a nucleus session by replacing the old license file or load module and issue a LICREFRESH operator command.
ADAN1V	Adabas is now executing in TCB mode
Explanation	In response to the operator command ZIIP=NO, this message indicates the Adabas nucleus is now executing in TCB mode (disabling the use of System z Integrated Information Processors). The ZIIP parameter value was changed to NO, from YES.
Action	No action is required for this informational message.

ADAN1W	Adabas is already executing in TCB mode
Explanation	In response to the operator command ZIIP=NO, this message indicates the Adabas nucleus was already executing in TCB mode (disabling the use of System z Integrated Information Processors). The ZIIP parameter value was not changed; it had already been NO.
Action	No action is required for this informational message.
ADAN1X	Adabas is now executing in SRB mode
Explanation	In response to the operator command ZIIP=YES, this message indicates the Adabas nucleus is now executing in SRB mode (enabling the use of System z Integrated Information Processors). The ZIIP parameter value was changed to YES, from NO.
Action	No action is required for this informational message.
ADAN1Y	Adabas is already executing in SRB mode
Explanation	In response to the operator command ZIIP=YES, this message indicates the Adabas nucleus was already executing in SRB mode (enabling the use of System z Integrated Information Processors). The ZIIP parameter value was not changed; it had already been YES.
Action	No action is required for this informational message.
ADAN1Z	zIIP-related statistics: Adabas is executing in {SRB TCB} mode ... (CPU consumption statistics for Adabas address space) (CPU consumption statistics for Adabas enclave) (SRB/TCB use statistics) (extended pause/release statistics) (type-of-work statistics) (processor-related statistics) ...
Explanation	In response to the operator command DZSTAT, these messages display the zIIP-related statistics of Adabas. The first line shows the current execution mode: "SRB" (execution on zIIP enabled) or "TCB" (execution on zIIP disabled). The following statistics correspond and are equivalent to the zIIP-related statistics at the end of the nucleus session statistics. See <i>Understanding the zIIP-Related Statistics</i> in the <i>Adabas for zIIP</i> documentation for detailed information about the various statistical figures.
Action	No action is required for this informational message.

- ADAN20** **ONLINE-DB-SAVE started**
PLOG-NR={session-number}, BLK-NR={block-number}
VOLSER-NR={volume}
- Explanation** Online execution of the ADASAV utility's SAVE database function has started. The message shown above occurs for both database and file SAVES and specifies the following:
- | | |
|-----------------------|--|
| <i>session-number</i> | the number of the session with which SAVE begins. |
| <i>block-number</i> | the RABN block that specifies the SYN1 starting point of the SAVE. |
| <i>volume</i> | the current SIBA volume/serial number. |
- Action** Save this session/RABN information and the related PLOG and other SAVE output for later ADASAV restore activity.
-
- ADAN21** **Protection log DD/PLOGRN started**
- Explanation** Adabas is now ready to begin writing data protection information to the dual or multiple data protection log identified by DD/PLOGRn.
- Action** Execute the PLCOPY function of the ADARES utility at this time.
-
- ADAN22** **File dump online started**
DATASET-NR={session-number}, BLK-NR={block-number}
VOLSER_NR={volser}
- Explanation** The online ADASAV SAVE FILE execution has begun. The SAVE operation begins with session *session-number*, using the SYN4 start point indicated by RABN *block-number*.
- Action** Save this session/RABN information and the related PLOG and SAVE output for later ADASAV RESTORE activity.
-
- ADAN23** **{online process} {started | partially done | done | stopped | terminated with error}**
{process-type}, FNR={fnr}, DE={aa}
- Explanation** An online process has started, is ongoing or has completed, terminated due to an error, or was stopped. The type of process is displayed, as well as the file number and details about the process as appropriate.

ADAN24 **DISPLAY PPT RABNs {nnnn} TO {mmmm}**

Explanation In response to operator command DPPT (Display PPT), this and subsequent messages show the contents of the Participating Plex-ID Table (PPT).

ADAN25 **DIB block is currently empty**
JOBNAME={jobname}, STARTTIME={hh:mm:ss} , LID={userid}

Explanation In response to operator command DDIB (display DIB block), this message either indicates an empty DIB block or provides the following DIB information:

<i>jobname</i>	job name
<i>hh:mm:ss</i>	job start time
<i>userid</i>	user ID assigned in the OP command

ADAN26 **Files locked={file-number}, ...**

Explanation In response to the DDIB operator command, this message displays the *file-number* of a file that is locked because it is being used by an Adabas utility.

ADAN27 **message**

Message	Explanation
release DE Release done, FNR= <i>fnr</i> DE= <i>de</i>	The Release Descriptor function at the end of an aborted online invert process has released the descriptor shown for the file shown.
Release DE terminated due to error File will be locked completely FNR= <i>fnr</i> DE= <i>de</i> RESPONSE= <i>rsp</i>	The Release Descriptor function at the end of an aborted online invert process has failed with the response code shown. The file is locked.
release DE Function terminated	The Release Descriptor function at the end of an aborted online invert process has finished. If the online invert was processing an expanded file, the Release Descriptor function has been executed on all component files of the expanded file.

ADAN28**Resource Size Current Highwater****Explanation**

In response to the DRES operator command, the first line of the message is a text header line. The second and subsequent lines of the message will display the resource name, allocated size or value, current usage value, and the highest usage value reached ("high water mark") in the current session for the following resources:

Resource Name	Description	Associated Parameter
AB - Pool	Attached buffer table.	NAB
CQ - Pool	Command queue.	NC
DUQ - Pool	Unique descriptor pool.	LDEUQP
FI - Pool	Internal format buffer pool.	LFP
HQ - Pool	Hold queue.	NH
Plog-IO B	PLOG I/O buffers.	NPLOGBUFFERS
Redo - Pool	Cluster redo pool. This is only displayed for Adabas cluster environments.	LRDP
RPL - Pool	Replication pool. This is only displayed for Event Replicator for Adabas environments.	LRPL
Sec - Pool	Security pool.	LCP
TBI - Pool	Table of ISNs.	LI
TBS - Pool	Table of sequential commands.	LQ
UQ - Pool	User queue.	NU
UQF - Pool	UQ file list pool.	NU
Wrk1 - IO B	Work I/O buffers.	NWORK1BUFFERS
WORK - Pool	Work pool.	LWP
Work Part1	Work Part 1. Note: The maximum pool value of Work part 1 is derived from the LP parameter. It corresponds to the maximum number of blocks a transaction can spend on Work Part 1 before Adabas decides to back it out.	LP
Work Pt 1b	Work Part 1 extension. This is only displayed for Adabas cluster environments.	CLUWORK1CACHE
Work Part2	Work Part 2.	LWKP2
Work Part3	Work Part 3.	
XID -Pool	XID -Pool.	NU

Resource Name	Description	Associated Parameter
	This is only displayed for Adabas Transaction Manager environments.	

The following is an example of the messages produced. The database ID and actual values shown in the example are variable, depending on the database and situation.

Time	DBID	InstID	Date	Time	Resource	Size	↔
17:32:07	ADAN28	00035	2016-11-29	17:32:05	Resource	Size	↔
					Current	Highwater	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	AB -Pool	1228800	↔
		N/A				1536	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	CQ -Pool	96000	↔
		0				192	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	DUQ -Pool	7000	↔
		0				0	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	FI -Pool	100000	↔
		0				160	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	HQ -Pool	416000	↔
		0				5200	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	Redo-Pool	10485760	↔
		0				176	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	Sec -Pool	10000	↔
		0				0	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	TBI -Pool	4000	↔
		0				0	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	TBS -Pool	30000	↔
		0				0	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	UQ -Pool	183456	↔
		1092				1456	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	UQF -Pool	48384	↔
		72				144	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	Wrk1-I0 B	50	↔
		0				5	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	WORK-Pool	5242880	↔
		128				34584	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	Work Part1	1200	↔
		0				7	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	Work Pt 1b	4	↔
		4				4	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	Work Part2	20	↔
		0				0	
17:32:07	ADAN28	00035	2016-11-29	17:32:05	Work Part3	270	↔
		0				0	↔

ADAN29	(No) users stopped
Explanation	In response to the STOPI operator command, this message displays either as "users stopped" or "no users stopped", depending on the action performed by the STOPI command.
ADAN2A	Overwriting PPT entry for NUCID={nnnnn}
Explanation	There are already 32 entries in the parallel participant table. The nucleus ID entry specified was inactive and is being overwritten.
ADAN2B	Different work data set was detected
Explanation	A Work data set was specified that is different from the one used in the previous session. This message is displayed only when the previously used Work data set contains a pending autorestart.
ADAN2C	Unable to open or read previous work data set
Explanation	A Work data set was specified that is different from the one used in the previous session. An attempt to read the Work data set used in the previous session to search for a pending autorestart failed.
ADAN2D	Caution - pending autorestart detected
Explanation	A Work data set was specified that is different from the one used in the previous session. The previously used Work data set was read and contains a pending autorestart. The ADAI63 message identifies the previous Work data set.
ADAN2E	Warning - PLOG datasets have changed. PPT overwritten. Use ADARES PLCOPY NOPPT to copy previous PLOG datasets.
Explanation	The protection log (PLOG) data sets have changed from the previous session and the previous PLOG data sets have not been copied. Because FORCE=YES was not specified, the parallel participant table (PPT) entry for these data sets has been overwritten.
Action	Software AG recommends that you use the ADARES PLCOPY NOPPT function to copy the PLOGs from the previous session.
ADAN2F	Warning: FST overflow - run ADAORD REORDB {ASSO DATA} element deleted: RABNs {x,xxx,xxx,xxx} -{ x,xxx,xxx,xxx}
Explanation	An attempt to add an extent to the Free Space Table (FST) was unsuccessful because the free space has become highly fragmented. Some free space could not be added and is therefore unavailable.
Action	The ADAORD REORDER DB utility function will compress free space and reconstruct the FST.

ADAN30 **FILES={nn}({type})[,{nn}({type})] ...**
A-Files={nn}
No files locked

Explanation In response to the operator command DLOCKF, this message displays the files that have been locked by LOCKF, LOCKU, LOCKX, or ALOCKF (if any). Different versions of this message appear, depending on the results. For file locked by LOCKF, LOCKU, or LOCKX, the type of lock (*type*) is displayed after the file number (*nn*). Possible types are:

Type	Description
F	The file was locked by LOCKF.
U	The file was locked by LOCKU.
X	The file was locked by LOCKX.

Files locked by ALOCKF (advanced file locks) are identified with the "A-Files=*nn*" version of this console message. Finally, if no files are locked, the "No files locked" message appears.

Action No action is necessary for this informational message.

ADAN31 **Current file usage by user**
File={file},{usage-counters }
User={user},SecUID={'{secuid}'| ' }
Job='{jobname}',TID='{tid }'
{... n} more users

Explanation This message is produced in response to DFILES operator commands. The response consists of a header line followed by one or more detail sections describing active files and any active users of the files. Up to five users of each file are displayed. The following table describes the possible substitutions provided in the message for each file.

Message Substitutions	Description
<i>file</i>	The file number.
<i>jobname</i>	The name of the job from which the user issued Adabas calls.
<i>n</i>	This line will appear only if there are more than five users of a file. Only the first five users are displayed
<i>secuid</i>	The user's system security user ID (or logon ID). If none is available, the value ' ' (a blank space between two single quotes) displays.
<i>tid</i>	The last eight bytes of the communication ID. If the user is hosted by a TP monitor, often a terminal ID or user ID is shown here. For a batch user, an STCK timestamp is shown. If this ID is comprised of printable hexadecimal characters it will appear in quotes, otherwise it will appear in alphanumeric characters.

Message Substitutions	Description
<i>usage counters</i>	Counts of the number of users using the file in each access mode. If there are no users, the phrase "is not being used" is displayed. Note that a single user may be using multiple access modes for a given file. <ul style="list-style-type: none"> ■ ACC=<i>u</i>: Number of users reading the file. ■ UPD=<i>u</i>: Number of users updating the file. ■ EXU=<i>u</i>: Number of users with exclusive update access to the file. ■ UTI=<i>u</i>: Number of utilities working with the file.
<i>user</i>	The Adabas-assigned internal user ID. This is unique within a single Adabas nucleus.

Action No action is necessary for this informational message.

ADAN33 **FILE={n}, USAGE={n}**
FILE={n} is not used

Explanation In response to the operator command DFILUSE, this message displays the number of active commands (USAGE=*n*) for the specified file (FILE=*n*), or that the specified file does not exist in the database.

ADAN34 **No users stopped**

Explanation In response to operator command STOPF, this message indicates that no users were active when the command was issued.

ADAN35 **online processes:**
{process-type} SORTSEQ={file=fnr}, CUR-RABN={rabn-nr}, CUR-ISN={isn}
ID={x'nnnnnnnn}', {active | suspended}

Explanation In response to the operator command DONLSTAT, this message lists all online processes present in the nucleus session, the kind of process, the file number, the current RABN or ISN (depending on the function), the ID of the process, and whether the process is active or suspended.

ADAN36	Dataset={dsn} {n}LOG number {x} has been {{deleted} {added}}
Explanation	A CLOG or PLOG data set has been dynamically added or deleted by an ADADBS utility function or using the Adabas Online System (AOS). The CLOG or PLOG data set name (<i>dsn</i>) and number (<i>x</i>) are given in the message.
ADAN41	Function completed
Explanation	The command or function issued was completed successfully.
ADAN42	Function accepted
Explanation	The command issued was accepted by Adabas.
ADAN43	Invalid type-in: {request}
Explanation	Either the request <i>request</i> was invalid or it was not correctly entered.
Action	Check the request/command syntax and validity, then retry the request. <ul style="list-style-type: none"> ■ A request to end a nucleus session with DUMP is invalid, and should not be retried. ■ An operator command to change the cache space parameters for a file (CFILE) that has an existing cache space is invalid. It is necessary to first delete the existing cache space and then add a new one with different parameters.
ADAN44	Function not executed
Explanation	Adabas could not perform the function because of <ul style="list-style-type: none"> ■ space restrictions; ■ a conflict between the requested command/function and the system status.
Action	Check for other related messages, correct any previously indicated errors, then retry the operation. Otherwise, contact your DBA, system support personnel, or Software AG technical support.
ADAN45	{various}
Explanation	Various message texts are provided with message ADAN45:

ADAN45 Message Text	Explanation	Action
Online process not found	The process specified in the request or command is either not active or not known to the system.	Verify that the specified process is valid.
Suspe.by I-STATE waiting for post	The requested process is currently suspended.	Verify that the specified process is valid.
Transaction Manager not active	The Adabas Transaction Manager must be active for the specified function.	Verify that the Adabas Transaction Manager is active.
User does not exist	The user specified in the request or command is either not active or not known to the system.	Verify that the specified user ID is valid.

ADAN46

Function not executable

Explanation

The requested function/command was valid but could not be executed. This message occurs preceded by one of the following ADAN46 messages, which provide reasons why the current nucleus status does not allow the requested function:

ADAN46 Message Text	Explanation	Action
ADASAV is running (DIB-entry found)	The READONLY=NO request was rejected because an ADASAV SAVE is running.	Wait until the ADASAV utility is finished, then retry the command.
AUTOINCxxxxSIZE is less than one track	The autoincrease size for xxxx (ASSO or DATA) was specified in blocks, but the size was smaller than the number of blocks per track. In z/OS environments, the minimum extent size is one track.	Specify a size that is either zero (to disable autoincrease for the component) or the minimum number of blocks for one full track.
AUTOINCxxxxTOTAL=nnnn is invalid current xxxxSIZE=zzzz	The value specified for the AUTOINCxxxxTOTAL operator command is invalid because it is less than the current allocated space in component xxxx. (The value of xxxx is either "ASSO" or "DATA".) The AUTOINCxxxxTOTAL value should be greater than the size currently allocated.	Specify a valid value for AUTOINCxxxxTOTAL and try again.

ADAN46 Message Text	Explanation	Action
AUTOINCxxxxTOTAL=nnnn is too big	The value specified for the AUTOINCxxxxTOTAL operator command is invalid because it is too large. The value exceeds 2,147,483,647 blocks or 16,777,215 blocks (3-byte RABNs). (The value of xxxx is either "ASSO" or "DATA".)	Specify a valid value for AUTOINCxxxxTOTAL and try again.
Command supported only on z/OS	AUTOINC* operator commands are currently only supported in z/OS environments.	No action is required for this informational message.
Command permitted only for cluster nuclei	The requested function was rejected because this function is only supported by a nucleus running in cluster mode.	No action is required for this informational message.
DSF is set to NO	The DDSF request was rejected because the nucleus is started with DSF=NO parameter.	Restart the nucleus with DSF=YES.
ET-Synchronization is already running	The SYNCC request was rejected because ET-Synchronization process is already running.	
Failed to acquire global parameter lock	An error occurred when a nucleus running in Adabas cluster mode attempted to acquire the global parameter lock in order to change a global Adabas parameter. The parameter was not changed.	Contact your Software AG technical support representative.
File is already locked	The ALOCKF request was rejected because the requested file is already locked.	No action is required for this informational message.
File is not locked	The RALOCKF request was rejected because the requested file is not locked.	No action is required for this informational message.
Function not executable	The requested function could not be run because is	Make sure you are trying to perform the

ADAN46 Message Text	Explanation	Action
	only supported in z/OS environments.	function in a z/OS environment.
Internal command pending for the user	The STOPU request was rejected because an internal command is running for this user (user is not selectable).	
LOGGING is set to NO	The requested function was rejected because the LOGGING parameter is set to NO.	Set LOGGING to YES before executing the command.
No free CLOGs	The FEOFCL request was rejected because no free CLOGs are available.	Run ADARES CLCOPY and then retry the command.
No free PLOGs	The FEOFPL request was rejected because no free PLOGs are available.	Run ADARES PLCOPY and then retry the command.
No online save is running	The RFDUMPST or RDUMPST request was rejected because no online save is running.	No action is required for this informational message.
Not yet supported by Cluster Services	The version of Cluster Services you are running does not support the requested function. The function is supported only by a nucleus running in noncluster mode.	No action is required for this informational message.
NUCID in PPT changed (Internal Error)	The READONLY=NO request was rejected because of an unexpected change in the PPT.	Contact your Software AG technical support representative for assistance.
Nucleus is a Resource Manager (RM)	The READONLY request was rejected because the nucleus is a resource manager.	A resource manager cannot be switched to READONLY status.
Nucleus is in READONLY status	The ALOCKF or RALOCKF request was rejected because the nucleus is in READONLY status.	First switch READONLY status to NO, then retry the command.
Nucleus is a Transaction Manager (TM)	The READONLY request was rejected because the nucleus is a transaction manager.	A transaction manager cannot be switched to READONLY status.

ADAN46 Message Text	Explanation	Action
Nucleus is in UTIONLY status	The READONLY request was rejected because the nucleus is in UTIONLY status.	First switch UTIONLY status to NO, then retry the command.
Online process running	The ADAEND request was rejected because an online reorder or online invert process is running.	Request ADAEND again after the online process finishes. Consider using HALT to stop the online process and shut down the nucleus.
Online recovery is running	The ADAEND or HALT request was rejected because an online recovery process is running.	Wait until recovery process is finished, then retry the command.
PLOGRQ is set to SEL	The FEOFPL request was rejected because PLOGRQ parameter is set to SEL.	
Read-Only preparation is running	The UTYONLY=YES or READONLY=NO request was rejected because a readonly preparation is running.	Wait until read-only preparation process is finished, then retry the command.
SMGT is set to NO	The SMGT... request was rejected because the nucleus is started with SMGT=NO parameter.	Restart the nucleus with SMGT=YES.
TCPIP is set to NO	The TCPIP request was rejected because the nucleus is started with TCPIP=NO parameter.	Restart the nucleus with TCPIP=YES.
TRANSACTIONS SUSPEND in progress	The requested function was rejected because the ADADBS TRANSACTION SUSPEND is in process.	Wait until the SUSPEND process is finished, then retry the command.
User is Online Process, use ONLSTOP	The STOPU request was rejected because the user is an online invert or online reorder process.	Use the ONLSTOP command to stop this user instead of STOPU.
Utility is running	The READONLY request was rejected because a utility is running.	Wait until the utility is finished, then retry the command.
User is waiting for command from ATM	The STOPU request was rejected because the user is waiting for the Adabas	

ADAN46 Message Text	Explanation	Action
	Transaction Manager. (ATM)	
Utility with exclusive DB control running	The requested function was rejected because a utility with exclusive DB control is running.	Wait until the utility is finished, then retry the command.
Work pool currently full	Work pool space for DFILES command could not be acquired.	Wait a minute or two, then retry the command.

ADAN47 Online DUMP-DB is running, function not executed
Explanation A SYNCC, ADAEND, HALT, or CANCEL operator command was issued, but is not permitted during the current online save operation.
Action Wait until the online save has ended, then retry the command.

ADAN47 Net-work termination target-node due to conflict
Explanation In Entire Net-Work, target node IDs must be unique across all connected systems. If an attempt is made to connect to a target node ID that is not unique, the system terminates abnormally (ADAEND).
Action Identify the conflicting node IDs and determine which one is to be active under the specified ID number.

ADAN48 File currently in use - function not executed
Explanation A LOCKF, LOCKU, or LOCKX operator command was issued but the file specified is currently in use.
Action Wait until the file is no longer in use, then retry the command.

ADAN48 File not loaded
Explanation The file specified in the ALOCKF function is not loaded.

ADAN49 {{userid} | {jobname}} backed out {during system open | by ADARES } UID={communication-id}
Explanation The last, incomplete transaction of the specified user (or job, if the user is not displayable) has been backed out during Adabas session autorestart or at the end of REGENERATE processing. The user ID (or job name) and communication ID are shown.
 The user ID is the user's ET-ID. For users without an ET-ID, "ADAEND" is displayed as their user ID.

The field following UID= is the last 8 bytes of the 28-byte communication ID of the user in hexadecimal format; that is, the terminal ID for an online user or a STCK time stamp for a batch or TSO user.

Action	None required. This is an information message only. The transaction status of the specified users may need to be checked.
ADAN4A	TRANS ET-SYNC point
Explanation	ET-SYNC has occurred for the TRANSACTIONS SUSPEND process. This message is followed by the ADAN4E message.
ADAN4B	TRANS SUSPEND started TT={time-limit}
Explanation	All verifications in the nucleus are complete and the SUSPEND process has started. TT indicates when the transactions will time out. The TT value is derived either from the TTSYN parameter in the ADADBS TRANSACTIONS SUSPEND TTSYN=nn job or the nucleus default ADARUN TT setting.
ADAN4C	Transactions TT rejected
Explanation	TPC is in effect and there are transactions on PET status. This is followed by the ADAN4B message displaying the original TT value.
ADAN4D	TRANS TIMER elapsed
Explanation	The timer specified by TRESUME in the ADADBS TRANSACTIONS SUSPEND process has been exceeded. The database returns to normal processing. This message is followed by the ADAN4F message.
ADAN4E	Updates stopped. TRESUME={time-limit}
Explanation	ET-SYNC has occurred for the SUSPEND function and updates are discontinued until either the RESUME function is issued or the timer specified by TRESUME expires.
ADAN4F	Normal processing resumes
Explanation	The database once again accepts and processes update commands as a result of either the RESUME function or a timeout.

ADAN50	Excluded files: {file1} ...
Explanation	This message documents the files that were excluded from autorestart due to the ADARUN AREXCLUDE parameter. These files remain unavailable for normal users and must be recovered (restore - regenerate).
ADAN51	{{operator} {aos-user}} typein: {command}
Explanation	Adabas repeats the operator command "command" before continuing. The second message is written for an operator command issued by an Adabas Online System user.
ADAN52	Partially inverted descriptor {present released descriptor={descriptor}, file={fnr}
Explanation	During session start, the nucleus detected the specified descriptor of the file <i>fnr</i> left over from an incomplete online invert operation. If the previous session terminated abnormally, the nucleus automatically releases the incomplete descriptor.
Action	If the nucleus did not release the descriptor and no regenerate on the file in question is to follow, release the incomplete descriptor using the AOS or ADADBS RELEASE function.
ADAN53	DBID waiting to serialize ({rrrddddd})
Explanation	The nucleus is trying to perform an action that only one nucleus or utility can do at a time. Another nucleus or utility is performing a similar action at the moment, so this nucleus must wait. <i>rrrddddd</i> identifies the logical resource used for serialization. The resource name comprises three letters followed by five digits representing the database ID. Possible resource names include: <ul style="list-style-type: none"> ■ SSE<i>dddd</i> for serializing nucleus session start and end. ■ DIB<i>dddd</i> for serializing DIB updates. ■ FST<i>dddd</i> for serializing FST updates.
Action	None required. This message is for information only. <p>If the nucleus hangs after displaying this message, another nucleus or utility is blocking the logical resource specified in the message. Identify the other job and either allow it to continue or terminate it.</p>
ADAN54	DBID global serialization error ({rrrrrrrr}) DBID IOR FUNCTION = {x'ff'}, RESPONSE = {x'cc'}
Explanation	An attempt to lock or unlock a logical resource failed. The ADAIOR function number was <i>ff</i> (in hexadecimal), its response code <i>cc</i> (in hexadecimal). Depending on the circumstances, the nucleus terminates abnormally or ignores the error.
Action	This is an unexpected error. Contact your Software AG technical support representative.

ADAN55 Recovery data found on work data set(s)

Explanation During session start (or, with Adabas nucleus clusters, during online recovery), the Adabas nucleus found recovery data on the Work data set (or Work data sets, in the case of nucleus clusters) that is needed to recover the database from a previous failure. The nucleus performs session autorestart logic.

**ADAN56 Backward repair done
Forward repair done
Autobackout done**

Explanation These message lines are printed when the Adabas nucleus finishes a phase of session autorestart (backward repair, forward repair, autobackout). The statistics (block counts and time durations) indicate how much repair and recovery work has already been done and how much remains to be done.

Session autorestart repairs physical inconsistencies in the database, redoing updates belonging to completed transactions and backing out updates belonging to incomplete transactions.

The following is an example of the messages produced. The database ID and actual values shown in the example are variable, depending on the database and situation.

```
ADAN56 dbid backward repair done
ADAN56 dbid work blocks processed        =            887
ADAN56 dbid work blocks remaining       =            1,269
ADAN56 dbid time used so far            =        00000:00:03

ADAN56 dbid forward repair done
ADAN56 dbid work blocks processed       =            1,774
ADAN56 dbid work blocks remaining       =            382
ADAN56 dbid time used so far            =        00000:00:05

ADAN56 dbid Autobackout done
ADAN56 dbid time used so far            =        00000:00:06
```

ADAN57 {various}

Explanation Various message texts can appear for this message number. The explanation and action for each is given in the following table.

Message Text	Explanation	Action
WK4 (DTP) GETMAIN failed	A nucleus with support for distributed transaction processing (DTP=RM) was performing the session autorestart after an abnormal termination. The nucleus was trying to allocate virtual storage for the processing of transactions for which the preliminary ET (PET) but not the final ET (FET) had been given. The storage allocation request failed, probably due to insufficient virtual storage being available to the nucleus address space.	Increase the region size, or decrease the size of a large pool (such as the buffer pool -- LBP), and restart the nucleus.
WK4-area (DTP) too small	A nucleus with support for distributed transaction processing (DTP=RM) was performing the session autorestart after an abnormal termination. The nucleus was trying to copy transactions to Work part 4 for which the preliminary ET (PET) but not the final ET (FET) had been given. Work part 4 was too small to keep the protection data for all these transactions.	Increase the LDTP parameter and restart the nucleus.
WORK4-index too small Increase the LDTP-parm and rerun DTP=RM nucleus: GETMAIN failed Increase the region size and rerun	An error occurred during nucleus startup at the time of DDWORKR4 interpretation. Note: DDWORKR4 must be interpreted before the system autorestart is done.	Adjust the startup JCL as requested in the message so DDWORKR4 is interpreted before the system autorestart and rerun the job.

ADAN58

Buffer-flush start record detected during autorestart. The nucleus will terminate after autorestart. In case of power failure, the database might be inconsistent because of partially written blocks. Only in this case, repair the database by restore and regenerate; Otherwise restart the nucleus.

Explanation

An autorestart operation found that a buffer flush was being performed when the action that caused the autorestart occurred; the buffer flush was therefore incomplete. The nucleus completes autorestart processing before terminating.

- If the cause of the autorestart was a power failure, the database may be inconsistent in a way that cannot be repaired by autorestart.
- If the cause of the autorestart was not a power failure, the database has already been made consistent and needs only to be restarted.

Action If a power failure caused the autorestart and your storage subsystem does not guarantee that no block is partially written, perform the following utility operations to ensure database consistency:

- ADASAV RESTORE (database)
- ADARES REGENERATE

If your storage subsystem technology does guarantee that no block is partially written, even in the case of power failure, there is no need to restore/regenerate after this message is received: simply restart the nucleus.

You may restrict the RESTORE - REGENERATE to the files modified by autorestart (see the ADAN5A message) but be sure to run the REGENERATE FILE with transaction logic (autobackout at the end of the regenerate) by specifying the ADARES parameter CONTINUE.

If the autorestart operation was not caused by a power failure, do not perform the utility operations described above. Simply restart the nucleus.

ADAN59 **Abend UCODE at address [= module+offset]**
r{register-00 register-01 register-02 register-03 (r0-r3)}
{register-04 register-05 register-06 register-07 (r4-r7)}
{register-08 register-09 register-10 register-11 (r8-rb)}
{register-12 register-13 register-14 register-15 (rc-rf)}

Explanation An internal error occurred that caused the nucleus to terminate abnormally. The message shows the abend code and the address, if possible also the module and offset, where the error was detected, as well as the contents of the general registers at that time.

Action Contact your Software AG technical support representative.

ADAN5A **Files modified during autorestart: {none | {file-list} }**

Explanation During nucleus startup, an autorestart was performed that modified the files listed in the message text.

ADAN60 **ARM element {element-name} successfully registered/deregistered**

Explanation The ARM ELEMENTNAME parameter has been specified and the nucleus has successfully registered or deregistered this element with the Automatic Restart Manager (ARM).

ADAN61	ARM registering /deregistering failed ARM reason code=X"{xxxx}"
Explanation	<p>The ARMELEMENTNAME parameter has been specified, but registering or deregistering with the Automatic Restart Manager (ARM) has failed. ARM has returned the reason code shown. The possible reason codes are described in the IBM manual <i>MVS Programming Sysplex Services Reference</i>. Common reason codes include:</p> <ul style="list-style-type: none"> ■ X`002C' The ARMELEMENTNAME parameter value is invalid. ■ X`013C' The Adabas nucleus has improper SAF authorization to register with ARM. ■ X`0150' ARMELEMENTNAME is not unique across the sysplex. ■ X`0004' The system does not support ARM. <p>The nucleus ignores the error and continues processing.</p>
Action	Look up the meaning of the reason code. If this explains the error, correct it. Otherwise, contact your systems programmer or your Software AG technical support representative.
ADAN62	FNR={fnr} A= U= ID= CA= CU=
Explanation	<p>This message is displayed in response to the DNFV operator command.</p> <ul style="list-style-type: none"> ■ FNR supplies the file number ■ A is set to either "Y", indicating that the file is being used by access-only users, or blank, indicating that it is not being used by access-only users. ■ U is used in the same way as A, but indicates usage by update users. ■ ID shows the ID of the database which has exclusive control over the file ■ CA provides the count of how many access-only users are using the file. ■ CU is the count of how many update users are using the file.
ADAN69	BASE AND LOB FILE ARE OUT-OF-SYNC BASE FNR={base-fnr,} UPDATE STATUS={upd-status1} LOB FNR={lob-fnr}, UPDATE STATUS={upd-status2}
Explanation	<p>A LOB file group consisting of a file with LB fields (base file) and a file containing the associated LB field values (LOB file) has become inconsistent. An illogical sequence of utility operations has exported (saved, restructured, unloaded) the files from, and subsequently reimported (restored, stored, loaded, defined) them into the database in a way that the two files no longer reflect the same point in time during processing.</p> <p>The base and LOB file have gotten out-of-sync. It is possible that the base file contains references to LB field values that should be, but are not, stored in the LOB file. Also, the LOB file may contain LB field values that should be, but are not, referenced by records in the base file.</p>

Action Investigate the cause of the base and LOB file getting out-of-sync. Take corrective action, such as reloading or restoring both files, depending on the findings. If necessary, you can use the following function to just mark the two files as being back in sync:

```
ADADBS MODFCB FILE=base-fnr,LOBFILE=lob-fnr
```

ADAN70 **Retry to switch PLOG/CLOG**

Explanation The nucleus is retrying the attempt to switch PLOGs or CLOGs. The retry is performed when the FEOFPL/CL attempt is made and there is currently no free PLOG or CLOG.

Action Submit an ADARES PLCOPY or CLCOPY to copy the appropriate data sets.

ADAN71 ***** Security error *****
Security system user ID is unknown
Job='{jobname}',TID='{tid}'
This user's calls are being rejected

Explanation A user's attempt to submit database calls has failed because the user's security system user ID is unknown. The following table describes the possible substitutions provided in the message.

Message Substitutions	Description
<i>jobname</i>	The name of the job from which the user issued Adabas calls.
<i>tid</i>	The last eight bytes of the communication ID. If the user is hosted by a TP monitor, often a terminal ID or user ID is shown here. For a batch user, an STCK timestamp is shown. If this ID is comprised of printable hexadecimal characters it will appear in quotes, otherwise it will appear in alphanumeric characters.

This message occurs when the ADARUN SECUID parameter is set to "REQUIRE".

Action Determine why the user's security system user ID is not known to Adabas and resolve the problem. Changing the ADARUN SECUID setting to WARN or ALLOW is one possible solution. For additional assistance, contact your Software AG technical support representative.

ADAN72 ***** Security error *****
Security system user ID has changed
Previous SECUID='{secuid1}' | ' ',Current SECUID='{secuid2}' | ' '
Job='{jobname}',TID='{tid}'
This user's calls are being rejected

Explanation A security error occurred because the security system user ID changed. Adabas calls by this user are being rejected. The following table describes the possible substitutions provided in the message.

Message Substitutions	Description
<i>jobname</i>	The name of the job from which the user issued Adabas calls.
<i>secuid1</i>	The user's previous system security user ID (or logon ID). If none is available, the value ' ' (a blank space between two single quotes) displays.
<i>secuid2</i>	The user's current system security user ID (or logon ID). If none is available, the value ' ' (a blank space between two single quotes) displays.
<i>tid</i>	The last eight bytes of the communication ID. If the user is hosted by a TP monitor, often a terminal ID or user ID is shown here. For a batch user, an STCK timestamp is shown. If this ID is comprised of printable hexadecimal characters it will appear in quotes, otherwise it will appear in alphanumeric characters.

This message occurs when the ADARUN SECUID parameter is set to "REQUIRE".

Action

Determine why the user's security system user ID has changed and resolve the problem. For additional assistance, contact your Software AG technical support representative.

ADAN73

**-- Security warning --
Security system user ID is unknown
Job='{jobname}',TID='{tid}'
This user's calls are being allowed**

Explanation

The security system user ID is unknown, but calls made by the user are being allowed. The following table describes the possible substitutions provided in the message.

Message Substitutions	Description
<i>jobname</i>	The name of the job from which the user issued Adabas calls.
<i>tid</i>	The last eight bytes of the communication ID. If the user is hosted by a TP monitor, often a terminal ID or user ID is shown here. For a batch user, an STCK timestamp is shown. If this ID is comprised of printable hexadecimal characters it will appear in quotes, otherwise it will appear in alphanumeric characters.

This message occurs when the ADARUN SECUID parameter is set to "WARN".

Action

Determine why the user's security system user ID is not known to Adabas and resolve the problem. Changing the ADARUN SECUID setting is one possible solution to controlling the display of this message. For additional assistance, contact your Software AG technical support representative.

ADAN74 **-- Security warning --**
Security system user ID has changed
Previous SECUID={secuid1}' | ' },Current SECUID={secuid2}' | ' }
Job={jobname}',TID={tid}'
This user's calls are being allowed

Explanation A security error occurred because the security system user ID changed. Adabas calls by this user are being allowed. The following table describes the possible substitutions provided in the message.

Message Substitutions	Description
<i>jobname</i>	The name of the job from which the user issued Adabas calls.
<i>secuid1</i>	The user's previous system security user ID (or logon ID). If none is available, the value ' ' (a blank space between two single quotes) displays.
<i>secuid2</i>	The user's current system security user ID (or logon ID). If none is available, the value ' ' (a blank space between two single quotes) displays.
<i>tid</i>	The last eight bytes of the communication ID. If the user is hosted by a TP monitor, often a terminal ID or user ID is shown here. For a batch user, an STCK timestamp is shown. If this ID is comprised of printable hexadecimal characters it will appear in quotes, otherwise it will appear in alphanumeric characters.

This message occurs when the ADARUN SECUID parameter is set to "WARN".

Action Determine why the user's security system user ID has changed and resolve the problem. For additional assistance, contact your Software AG technical support representative.

ADAN75 **Rsp={rep-code}, Fnr={fnr}, ISN={isn}**
Cmd={cc}, Op={cop1}', DE={de-name}, Val=x'{descriptor-value}'
NI-RABN={index-rabn}, USER=x'{userid}',SECUID=x'{secuid}'

Explanation The nucleus prints this message to the operator console and DD/PRINT when certain response codes are set. This message is used to inform your database administrator of a potential problem. The nucleus will print the message and then continue processing as it did before.

Within the message, the following information is supplied:

Message Value	Description
<i>rsp-code</i>	The Adabas response code being set.
<i>fnr</i>	The number of the Adabas file on which the error condition occurred.
<i>isn</i>	The ISN of the data record on which the error occurred.
<i>cc</i>	The Adabas command code of the command that encountered the error condition.
<i>cop1</i>	The Command Option 1 value of the command.
<i>de-name</i>	The name of the descriptor being processed when the error condition occurred.
<i>descriptor-value</i>	The related descriptor value (in hexadecimal, if it is not printable).
<i>index-rabn</i>	The RABN of the Normal Index block in which the descriptor value was sought or found.
<i>secuid</i>	The security ID of the user who issued the command (in hexadecimal format , if it is not printable).
<i>userid</i>	The last eight bytes of the communication ID of the user who issued the command (in hexadecimal, if it is not printable).

Action No action is required for this informational message.

ADAN76 **I/O-error { ASSO | DATA | WORK } RABN={rabn-number}**
Explanation The Adabas nucleus detected an internal I/O error.
Action Contact your Software AG technical support representative.

ADAN77 ***** Security violation *****
JOB='{jobname}',TID='{tid}'
ETID='{etid}',SECUID='{secuid}' | ' '
Command code='{cc}',File number={fnr}
Response code {rsp} is given for this call

Explanation A security violation occurred.
 The following table describes the possible substitutions provided in the message.

Message Substitutions	Description
<i>jobname</i>	The name of the job from which the user issued Adabas calls.

Message Substitutions	Description
<i>tid</i>	The last eight bytes of the communication ID. If the user is hosted by a TP monitor, often a terminal ID or user ID is shown here. For a batch user, an STCK timestamp is shown. If this ID is comprised of printable hexadecimal characters it will appear in quotes, otherwise it will appear in alphanumeric characters.
<i>etid</i>	The user's ETID (specified in the Additions-1 field of the OP command) or "None" if no ETID is present.
<i>secuid</i>	The user's system security user ID or ' ' (a blank space between two single quotes) if none is available.
<i>cc</i>	The Adabas command code of the command that encountered the error condition.
<i>fnr</i>	The number of the Adabas file on which the error condition occurred.
<i>rsp</i>	An appropriate Adabas response code. For more information about the response code, read the Adabas nucleus response code documentation , elsewhere in this guide.

Action Review the Adabas response code documentation to determine the cause of the security violation.

ADAN78 **Function extent**
Nucleus terminated after { ASSO | DATA } function

Explanation The function INCREASE or ADD for an Associator or Data Storage extent has been performed by the nucleus. The nucleus terminates and permits the newly added part of the Associator to be allocated and formatted, which is necessary before another Adabas session can be started and the new extent can be used.

Action Perform the necessary allocation/reformatting utility operations, and then restart the nucleus.

ADAN79 **I/O - error during asynchronous buffer flush ADAIOR-RESP = {hex-resp} the nucleus terminates with dump**

Explanation An I/O error occurred during asynchronous buffer flush operation. The nucleus ends operation.

Action Correct the cause of the I/O error.

ADAN7A**ECS error {error-code} in function {ecs-function}****Explanation**

ECS is the Entire Conversion Services, a subsystem of the Adabas universal encoding support (UES) system. This message is written after a function of the subsystem has failed.

Error codes produced by the ECS component are described in [Universal Encoding System \(UES\) Component Error Codes](#), elsewhere in this guide.

The following ECS functions may return errors:

ECS Function	Description
ECS LOAD	An error loading ECS. Check that the ECS load module is in the Adabas load library.
COX LOAD	An error loading ADACOX, which is loaded if the database is UES-enabled. ADACOX is the Adabas conversion exit for special conversions.
APS INIT	An error occurred during APS (POSIX Services) initialization. Verify that the APS library is in the load library concatenation and/or that the APS parameters are specified in SYSPARM.
SLIBLOAD	An error loading SAGECS, SAGOVO, or SAGSMP2. Check that these modules from the Software AG base technology library can be found in the load library concatenation.
DDECSOJ	An error occurred during initialization while reading ECS standard conversion objects. Check that the nonexecutable binary ECS conversion object library is specified in the DDECSOJ DD statement of the JCL.
GETHANDLE <i>nnnn</i>	An error occurred reading the ECS encoding descriptor object EDDnnnn. Check that the nonexecutable binary ECS conversion object library is specified in the DDECSOJ DD statement of the JCL. Check that EDDnnnn is contained in the library. If it is not, then either an invalid number was specified or the object is missing and must be added.
GETHANDLE <i>mmmm/nnnn</i>	See the GETHANDLE <i>nnnn</i> explanation. In this case, an ECS plane table object (PTO) is missing Txxx2yyy where xxx or yyy are the hexadecimal value of the decimal <i>mmmm</i> or <i>nnnn</i> , respectively. For some conversion combinations, it may be necessary to request additional PTOs from your Software AG support representative.

Action

Resolve the problem and try again.

ADAN7C **Entire conversion services {v.r.s }initialized**
Explanation The specified version of Entire Conversion Services was successfully initialized.

ADAN7D **Collation exit {nn} initialized**
Explanation The specified collation descriptor user exit was successfully initialized.

ADAN7E **Logic.-deleted-DE referenced**
DBID={dbid}, NUCID={nucid}, FNR={fnr}
DE-NAME={name}, JOBNAME={jobname}
Explanation The nucleus prints this message to the console and DD/PRINT when a command tries to reference a logically-deleted descriptor. The command will receive response code 39. This message is used to inform your database administrator that the logically-deleted descriptor is still used. The nucleus will print the message and then continue processing as it did before.

Within the message, the following information is supplied:

Message Value	Description
<i>dbid</i>	The database ID of the nucleus.
<i>fnr</i>	The number of the Adabas file on which the descriptor is referenced.
<i>jobname</i>	The job name of the program issuing the command.
<i>name</i>	The name of the referenced descriptor.
<i>nucid</i>	The nucleus ID in the cluster.

Action No action is required for this informational message.

ADAN7F **Security error messages suppressed**
Explanation To avoid flooding the event log and the console with redundant events and messages, Software AG has set limits on the number of security error messages created. This message occurs when that security error message limit has been exceeded.

Note: When message suppression takes place, the messages are no longer written to the console, but will continue to be written to DDPRINT.

Action No action is necessary for this informational message. Use other security error messages that have been sent to determine the cause (and solution) for the problem.

ADAN7G	Security warning messages suppressed
Explanation	To avoid flooding the event log and the console with redundant events and messages, Software AG has set limits on the number of security warning messages created. This message occurs when that security warning message limit has been exceeded.
	Note: When message suppression takes place, the messages are no longer written to the console, but will continue to be written to DDPRINT.
Action	No action is necessary for this informational message. Use other security warning messages that have been sent to determine the cause (and solution) for the problem.
ADAN80	Adabas dynamic caching environment established
Explanation	Adabas Caching Facility was successfully initialized.
Action	No action is required for this informational message.
ADAN80	Adabas dynamic caching 1M large page support available
Explanation	Adabas Caching Facility determined that 64-bit virtual storage that can be backed by non-pageable, 1M large pages is available for use.
Action	No action is required for this informational message.
ADAN80	Adabas dynamic caching 2GB large page support available
Explanation	Adabas Caching Facility determined that 64-bit virtual storage that can be backed by non-pageable, 2G large pages is available for use.
Action	No action is required for this informational message.
ADAN80	Adabas dynamic caching virtual 64 environment available
Explanation	Adabas Caching Facility determined that 64-bit virtual storage is available for use.
Action	No action is required for this informational message.
ADAN80	ADACSH active for work part 2 and work part 3 only
Explanation	In an Adabas nucleus cluster environment prior to version 7.2, caching is available only for Work parts 2 and 3.
Action	No action is required for this informational message.

ADAN81 **Warning: not all blocks of the DB are allocated and formatted - run ADAREP to check the DB's size**

Explanation The highest RABN of an ASSO or DATA extent, as defined in the GCBs, is not readable. Most likely, an Adabas Online System or ADADBS INCREASE function was performed without allocating and formatting the new database area. The nucleus continues. Any attempt to access an unallocated area of the database causes an I/O error.

Action Ensure that the defined extents are completely allocated and formatted.

ADAN81 **No statistics available for file {file-number} file not used**

Explanation An attempt was made to change cache space parameters for a file without first deleting its existing cache space.

Action Delete the existing cache space for the file; then add a new cache space with the changed parameters.

ADAN81 **(see explanation below)**

Explanation This message displays the output of the CSTAT, CFSTAT, and CSUM operator commands of the Adabas Caching Facility. See the Adabas Caching Facility documentation for more information.

The CSTAT command is used to display the current cache space statistics. A sample report display is shown below:

```
+-----+
+ 005 DATA SPACE, DATA, RABNS 81 THRU 135      +
+-----+
+ ALLOCATED, LA=17:04:26                          +
+-----+
+      253 CACHE WRITES  +          47 BLKS IN CACHE +
+      47 READ EXCPS    +          172,032 DATA SPC SIZE +
+      408 CACHE READS  +           55 BLKS/DATA SPC +
+      455 TOTAL READS  +          1320 INDXSPCE SIZE +
+      89.6 DSP EFFICIENCY+       167,936 MAX DSP USED  +
+ 0.071810 MAX NIOT (SEC)+       0.698682 MAX EXCPT(SEC)+
+ 0.000080 MIN NIOT (SEC)+       0.009600 MIN EXCPT(SEC)+
+ 0.000245 AVE NIOT (SEC)+       0.167286 AVE EXCPT(SEC)+
+-----+
```

The CFSTAT command is used for file-level caching to display the current cache space statistics for one or more files. When file-level caching is active, a report is produced for each RABN range associated with the file request. A sample report display is shown below:

```

+-----+
+ FNR 00001 AC CL1 EXT RABNS 91 THRU 93
+-----+
+   ALLOCATED, LA=09:55:36
+-----+
+           60 CACHE WRITES +           0 BLKS IN CACHE +
+           2 READ EXCPS   + 32,767,404 EXTM SIZE   +
+           52 CACHE READS +           16,351 BLKS/EXTM +
+           54 TOTAL READS +           28 RABN TAB SIZE +
+           96.2 ESP EFFICIENCY+           4,008 MAX ESP USED +
+ 0.001503 MAX NIOT (SEC)+ 0.092800 MAX EXCPT(SEC)+
+ 0.000018 MIN NIOT (SEC)+ 0.092071 MIN EXCPT(SEC)+
+ 0.000062 AVE NIOT (SEC)+ 0.092435 AVE EXCPT(SEC)+
+-----+

```

The CSUM command is used to display, for a session, the accumulated cache summary for all active and inactive cache spaces, including statistics from previously deleted cache spaces. A sample report display is shown below:

```

+-----+
+ A D A B A S DYNAMIC CACHING SESSION SUMMARY
+           52.5 CURRENT ADABAS BUFFER EFFICIENCY
+           7.2 PROJECTED NON-CACHE BUFFER EFFICIENCY
+           3 ACTIVE CACHE SPACES
+           4 CACHE SPACES DEFINED
+ -----ASSO----- DATA----- WORK----- +
+ CACHE WRITES           27,367           6,674           212 +
+ READ EXCPS              78             444             0 +
+ CACHE READS            27,288           6,203           4,865 +
+ TOTAL READS            27,366           6,647           4,865 +
+ EFFICIENCY              99.7            93.3            100.0 +
+-----+

```

ADAN82

Status switch
readonly = {yes | no}

Explanation

The READONLY status of the nucleus has been switched. This message occurs as a response to the operator command or Adabas Online System function READONLY.

ADAN83

status switch
utionly = {yes | no}

Explanation

The "utility use only" (UTIONLY) status of the nucleus has been switched. This message occurs as a response to the operator command or Adabas Online System function UTIONLY.

ADAN84 LP parameter has been increased, additional Protection area blocks are being formatted.

Explanation The ADARUN LP parameter was increased in the current Adabas session. Therefore, additional Work part 1 RABNs had to be formatted.

Action None required. Consider increasing the Work data set to ensure that sufficient Work part 3 space is available.

ADAN85 {various}

Explanation Various message texts can appear for this message number. The explanation and action for each is given in the following table.

Message Text	Explanation
DTP = RM INITIALIZATION PROBLEMS:	A problem was detected during DDWORKR4 interpretation.
Work part 4 problem detected during startup	During system startup and Work part 4 interpretation of a nucleus defined with DTP=RM, a problem was detected with Work part 4. This message is following by ADAN86.

Action Examine error ADAN86 for the cause of the error.

ADAN86 {various}

Explanation Various message texts can appear for this message number. The explanation and action for each is given in the following table.

Message Text	Explanation	Action
WK4 I/O error was detected { rabn=__ ior-resp=__ resp-code=__ subcode=__ }	During system startup and Work part 4 interpretation of a nucleus defined with DTP=RM, a Work part 4 I/O error was detected. This message follows ADAN85 and indicates either the RABN location and ADAIOR response code of the error or the nucleus response code and subcode of the error.	Determine the cause of the error, correct it, and rerun the job.
<i>dbid</i> GETMAIN (TBWK4) failed	If DTP=RM is specified, an additional GETMAIN is needed to allocate the tables used by a DTM=RM nucleus.	Increase the GETMAIN and rerun the job.
<i>dbid</i> File-list pool too small	The UQEFLIST_POOL, an extension of the user queue, is too	Increase the number of user queue elements using the ADARUN NU

Message Text	Explanation	Action
	small to receive all file definitions found on DDWORKR4.	parameter and rerun the job.
<i>dbid</i> User-queue too small	The user queue is too small to receive all user queue elements found on DDWORKR4.	Increase the number of user queue elements using the ADARUN NU parameter and rerun the job.
<i>dbid</i> name unequal in the cluster	The DDWORKR4 data set is a container file. All nuclei in a cluster must use the same DDWORKR4 data set. A subsequently started nucleus used an invalid DD statement. The nucleus will not come up.	Correct the DD statement and rerun the job.
<i>dbid</i> nucleus response code detected: RESP-CODE= <i>rc</i> , SUBCODE= <i>sc</i>	A nucleus response code was detected. The nucleus will go down.	Determine the cause of the error, correct it, and rerun the job.
<i>dbid</i> WORK4 size is diff. to last session BUT/AND IGNDTP not defined	The DDWORKR4 data set size is unequal to the size of the last session, but the data set is not empty.	Correct the DDWORKR4 DD statement and rerun the job.
<i>dbid</i> WORK4 I/O-error: RABN= <i>rabn</i> IOR-RESP= <i>resp</i>	The nucleus will go down.	Determine the cause of the error, correct it, and rerun the job.
<i>dbid</i> GCB contains WORK4 definition but: DTP=NO, IGNDTP=NO	The nucleus will not come up.	Determine the cause of the error, correct it, and rerun the job.
<i>dbid</i> Parameter conflict - MODE=SINGLE but last session run with DTP=RM - DTP=NO but WORKR4 defined	A parameter conflict exists, as described in the message text.	Correct the parameter conflict and rerun the job.

Action User actions are given in the explanation.

ADAN87 {various}

Explanation Various message texts can appear for this message number. The explanation and action for each is given in the following table.

Message Text	Explanation	Action
DDWORK4 too small The nucleus will terminate. Rerun with a bigger data set size.	A utility with exclusive database control is running. The nucleus will terminate with this message, followed by the U019 abend dump.	Increase the size of DDWORKR4 and rerun the job.
WK4 area too small The nucleus will terminate Increase LDTP parm and rerun	During startup of a nucleus defined with DTP=RM when it is necessary to copy partially completed transactions or during an ADARES REGENERATE for all files, insufficient space was available in Work part 4 to reestablish the previous environment. Because the nucleus cannot reestablish the previous environment and cannot terminate the incomplete transaction(s) heuristically, it terminates.	Increase the size of the Work part 4 area using the ADARUN LDTP parameter and rerun the job.

Action User actions are given in the explanation.

ADAN88 (rm=yes) abend
(DTP=RM) ABEND

Explanation During initialization of a nucleus defined with DTP=RM, a logic error was detected while executing DTP functions.

The nucleus terminates abnormally with abend 19. The registers at entry to the abend and the load addresses of ADANC0-ADANCB are printed.

Action Contact your local Software AG technical support representative.

ADAN89 {various}

Explanation Various message texts can appear for this message number. The explanation and action for each is given in the following table.

Message Text	Explanation	Action
DTP support WORKR4 open error WORKR4 I/O-error: RABN= <i>rabn</i> WORKR4 close-error	An I/O error occurred for the DDWORKR4 data set.	Check the DDWORKR4 data set or the nucleus JCL definition for DDWORKR4 to identify the problem. Then fix the problem and rerun the job.
DTP-database: Heuri. terminated user is moved: <i>userid secuid</i>	After a local ADAEND or HALT request was issued against a cluster nucleus, the terminating nucleus has heuristically terminated a prepared transaction (for which the preliminary ET was issued but the final ET still outstanding) and is now moving the affected user to another nucleus in the cluster, in order to allow that nucleus to inform the Adabas Transaction Manager about the heuristic transaction termination. The last 8 bytes of the 28-byte communication ID of the affected user are printed in hexadecimal format. The security ID of the affected user is printed	No action is required for this informational message.

Message Text	Explanation	Action
	in hexadecimal format.	
DTP-database: HEURISTIC termination occurred due to ET-SYNC request for user or (GLOBAL) ADAEND request	A <i>prepared</i> transaction, for which the <i>preliminary ET</i> has been issued but the <i>final ET</i> is still outstanding, is being heuristically committed, in order to allow an ET-sync process (e.g., at the end of an online save operation) or ADAEND process to complete. The last 8 bytes of the 28-byte communication ID of the affected user are printed in hexadecimal format. The security ID of the affected user is printed in hexadecimal format.	Use Adabas Transaction Manager Online Services to determine what happened to the transaction in the other resource managers involved with it and to correct any logical inconsistencies that may have arisen. For more information, refer to the Adabas Transaction Manager documentation available within Software AG's Empower site (https://empower.softwareag.com/default.asp).
DTP-database: 2PH-ADAEND : ADAEND is forced	After ADAEND had been requested, one or more <i>prepared</i> transactions have been waiting longer than one minute for the <i>final ET</i> . Adabas will heuristically commit these	Use Adabas Transaction Manager Online Services to determine what happened to the transaction in the other resource managers involved with it and to correct any logical inconsistencies that may have arisen. For more information, refer to the Adabas Transaction Manager documentation available within Software AG's Empower site (https://empower.softwareag.com/default.asp).

Message Text	Explanation	Action
	transactions and then shut down.	
User heuristically terminated G-TID= <i>communication-id</i> SECUID= <i>secuid</i> XID = <i>transaction-id</i> Held ISNs are (FNR/ISN): <i>fnr/isn-list</i>	A <i>prepared</i> transaction, for which the <i>preliminary ET</i> has been issued but the <i>final ET</i> is still outstanding, is being heuristically committed or rolled back. The 28-byte communication ID, security ID, and the internal transaction ID are printed in hexadecimal format. Furthermore, the data records exclusively locked by the transaction, identified by their file number/ISN pairs, are listed.	Use Adabas Transaction Manager Online Services to determine what happened to the transaction in the other resource managers involved with it and to correct any logical inconsistencies that may have arisen. For more information, refer to the Adabas Transaction Manager documentation available within Software AG's Empower site (https://empower.softwareag.com/default.asp).

Action User actions are given in the explanation.

ADAN8A file already being cached

Explanation The file specified for caching is already being cached by Adabas Caching Facility. This error can occur if you use operator or Adabas Online System commands in an attempt to define different types of memory to cache Associator and Data Storage RABNs of the same file.

Action It is possible at startup using ADARUN CFILE parameters to specify different types of memory to cache Associator and Data Storage RABNs of the same file. However, once a memory type is set for caching any RABNs of a file, Adabas Online System and operator commands do not allow you to specify any other memory type for the

same file. If you want to change the memory type for the file, you must delete the existing cache space and then add a new one with different parameters.

ADAN8B **Device constants could not be acquired.**
Explanation ADACSH (Adabas Caching Facility) could not acquire the Constant Set during initialization..
Action Contact your local Software AG technical support representative.

ADAN8C **Memory allocation failure or insufficient space available**
Explanation ADACSH could not acquire space for its working areas. Adabas Caching Facility is not started and the associated message ADAN8H is displayed.
Action Increase the region, partition, or address space size.

ADAN8D **{zzz} ({aaaa}) cache active**
Explanation A RABN range has been activated. This generally occurs when Adabas writes a RABN from its buffer pool to cache storage.

Message Variable	Description
<i>zzz</i>	The type of RABN range ("DSP" for data space; "ESP" for extended memory; "HSP" for hiperspace; "V64" for virtual 64; or "FNR" for file-related)
<i>aaaa</i>	The type of RABN range storage ("ASSO", "DATA" or "WORK")

ADAN8E **{track | hiperspace} I/O buffer allocation failure**
CSP (ASSO) RABNINDX allocation failure
Explanation Adabas Caching Facility could not allocate storage for the track or hiperspace I/O buffer, or for RABNINDX blocks. When the track I/O buffer is not available, a RABN I/O request being considered for read-ahead caching is issued normally. When the hiperspace I/O buffer is not available, caching using hiperspaces is not possible. When the RABNINDEXes for a cache space area are not available, the attempt to allocate the associated cache space area fails and is not attempted again until at least CRETRY seconds have elapsed.
Action Increase the region, partition, or address space size.

ADAN8F
Explanation

{various}

The Adabas Caching Facility detected an error while processing a console operator command.

Various message texts can appear for this message number. Possible error messages are listed in the following table.

Possible Error Messages
ADAN8F XXXXX File Caching mode required.
ADAN8F XXXXX Global caching mode required.
ADAN8F XXXXX SMP/PLEX nucleus prohibited.
ADAN8F XXXXX Cache type invalid.
ADAN8F XXXXX memory type not supported.
ADAN8F XXXXX from RABN missing.
ADAN8F XXXXX inconsistent RABN range.
ADAN8F XXXXX invalid RABN range ID.
ADAN8F XXXXX Service Class invalid.
ADAN8F XXXXX invalid File range (start>end).
ADAN8F XXXXX invalid File number (>max).
ADAN8F XXXXX invalid value "BUFNO" (> NT).
ADAN8F XXXXX invalid "CDISPSTAT" value.
ADAN8F XXXXX Parameter error INCLUDE/EXCLUDE.
ADAN8F XXXXX Invalid "ASSO/DATA" size.
ADAN8F XXXXX CWORKSTORAGE parameter missing.

ADAN8G
Explanation

{xxx} bytes [L64 | G64] storage [NOT] backed by [1M | 2G] large pages

The Adabas Caching Facility attempted to allocate 64-bit virtual storage backed by non-pageable large pages. The storage was allocated either for an L64 cache space backed by 1M large pages or for a G64 cache space backed by 2G large pages.

The original target size of the allocation request is given in the message (xxx). For an L64 cache space to be backed by 1M large pages, this was then rounded up to the next integral multiple of one megabyte. For a G64 cache space to be backed by 2G large pages, this was then rounded up to the next integral multiple of two gigabytes.

If the word "NOT" is omitted from the message, the storage allocation request was successful and the storage was backed by non-pageable large pages of the specified size. If the word "NOT" occurs in the message, insufficient large pages of the type requested were available. Instead, storage was allocated and backed by pageable 4 kilobyte pages.

This message is written to the operator console only.

Action If the message indicates that the storage is *not* backed by large pages, consider whether the number of fixed large pages specified for the operation system using the LFAREA parameter in SYS1.PARMLIB member IEASYSxx should be increased. If the message indicates that the storage *is* backed by large pages, no action is required for this informational message.

ADAN8H **ADABAS dynamic caching is -not- in service**

Explanation Adabas Caching Facility was not activated due to a previous parameter specification or error condition.

ADAN8J **CSP {nnn} ({aaaa}) released due to parallel utility operation
{xxx} BLKS released due to parallel utility on FNR {y}**

Explanation Depending on the utility, Adabas Caching Facility acted to maintain database integrity by releasing an entire cache space or a number of cache blocks because of a parallel utility operation.

Message Variable	Description
nnn	The cache space number
aaaa	The type of RABN storage: "ASSO", "DATA" or "WORK"
xxx	The number of blocks released
y	The file that owned the released blocks

ADAN8K **{zzz} ({aaaa}) released after exceeding non-activity time limit**

Explanation A cache storage area was released after it was inactive for a continuous elapsed time period of CCTIMEOUT seconds.

Message Variable	Description
zzz	The type of cache space area ("DSP" for data space; "ESP" for extended memory; "HSP" for hiperspace; "V64" for virtual 64)
aaaa	The type of RABN storage: "ASSO", "DATA" or "WORK".

ADAN8L **{zzz} {nnnnn} ({aaaa}) active, RABNS {xxx} thru {yyy}**

Explanation This message is displayed whenever a RABN range is activated. This generally occurs when Adabas writes a RABN from its buffer pool to cache storage.

Message Variable	Description
zzz	The type of RABN range ("DSP" for data space; "ESP" for extended memory; "HSP" for hiperspace; "V64" for virtual 64; or "FNR" for file-related)
nnnnn	The file number when zzz is "FNR"; otherwise, the RABN range ID
aaaa	The type of RABN range storage ("ASSO", "DATA" or "WORK")
xxx,yyy	The RABN range, with xxx representing the starting value and yyy representing the ending (and inclusive) value.

ADAN8M

**{zzz} ({aaaa}) size extended to {yyy} bytes
{zzz} ({aaaa}) extension failed**

Explanation

An attempt was made to add an additional cache storage area for a cache space.

Message Variable	Description
zzz	The type of cache space area ("DSP" for data space; "ESP" for extended memory; "HSP" for hiperspace; "V64" for virtual 64)
aaaa	The type of cache space area storage ("ASSO", "DATA" or "WORK")
yyy	The size of new area, in bytes

When the request is successful, the additional storage is available for the cache space and "yyy" reflects the size of the new area which is equal to the current CASSOMAXS or CDATAMAXS setting.

If unsuccessful, the system simply uses the storage areas already allocated for the cache space until CRETRY seconds pass. Then another attempt is made to add a new storage area for the cache space if this is still required.

Action

Check with the system programmer; the extension failure may be due to insufficient ESA capabilities (memory or page data sets), or too many data spaces or hiperspaces allocated at one time.

ADAN8O

AOS operator command: {xxxxx}

Explanation

An Adabas Online System (AOS) operator issued a command to change one of the Adabas Caching Facility system parameters.

Message Variable	Description
xxxxxx	Change as follows: CASSOMAXS=new size CDATAMAXS=new size CCTIMEOUT=new value CDISPSTAT=YES/NO CRETRY=new value CBUFNO=new value CEXCLUDE=exclude list CINCLUDE=include list

ADAN8P {zzz} {nnnnn} ({aaaa}) disabled after exceeding non-activity time limit

Explanation Demand caching is in effect and a RABN range or file has been inactive for a period longer than the CCTIMEOUT specification.

Message Variable	Description
zzz	The type of RABN range ("DSP" for data space, "ESP" for extended memory, "HSP" for hiperspace; "V64" for virtual 64; or "FNR" for file-related)
nnnnn	The file number when zzz is "FNR"; otherwise, the RABN range ID
aaaa	The type of RABN range storage ("ASSO" only, "DATA" only, "WORK", or "BOTH" if both ASSO and DATA are cached for the file)

ADAN8Q Hiperspace READ/WRITE error. RETCODE = {nn}

Explanation An error occurred during the processing of a hiperspace cache request. The system return code from the request (nn) is given in the message.

Generally speaking, this error causes a request to write to or read from a hiperspace cache to fail. In most cases, the system can continue by reading the RABN from disk or writing, ignoring the request from the nucleus.

However, where Work parts 1 or 2 are being cached 100%, the failure of a request to return a cached RABN may have more serious consequences because there is no copy of the RABN on disk and therefore the I/O cannot be satisfied.

Action Determine if the error was caused by some event or problem in the system that could impact on hiperspaces used by Adabas Caching Facility. If there is nothing evident, report the error and the circumstances surrounding the error to your Software AG technical support representative.

ADAN8R Insufficient storage for {xxxx}

Explanation An attempt to allocate dynamic storage in extended memory failed due to a shortage of space in extended memory.

Message Variable	One of the following for which the storage was intended:	
xxxxx	File table	Table of file control block entries
	File control block	Required for file caching
	RABN extent block	Required to define one RABN extent
	RABN table	Required to described RABNs cached
	RABN table expansion	Required when file becomes larger

Action Review your storage estimates to insure that there is sufficient storage available for the parameters specified.

ADAN8R **Hiperspace WRITE error. RETCODE = nn**
Explanation The write to hiperspace operation returned a nonzero condition code. The requested RABN is not written to hiperspace and is flagged as unused.
Action No operator intervention is required.

ADAN8S **{zzz} ({aaaa}) allocate failed. RETCODE = {nn}**
Explanation An attempt to allocate the first storage block for a cache area failed.

Message Variable	Description
<i>zzz</i>	The type of cache space area ("DSP" for data space; "ESP" for extended memory; "HSP" for hiperspace; "V64" for virtual 64)
<i>aaaa</i>	The type of cache space area storage ("ASSO", "DATA", or "WORK")
<i>nn</i>	The return code from the system function used to allocate the storage.

No storage is available for caching the RABNs for which the cache storage allocation was attempted. The situation continues at least until CRETRY seconds have elapsed and another attempt to allocate the storage is made, if required.

Action Check with the system programmer; the allocation failure may be due to insufficient memory or page data sets or too many data spaces and/or hiperspaces allocated at one time.

ADAN8T **{zzz} {nnnnn} ({aaaa}) {xxxx} by {yyyy} command**
{zzz} {nnnnn} ({aaaa}) not {xxxx} due to conflicts
Explanation An operator command was received and was either successfully completed or not.

Message Variable	Description										
<i>zzz</i>	The type of RABN range ("DSP" for data space, "ESP" for extended memory, "HSP" for hiperspace; "V64" for virtual 64; or "FNR" for file-related)										
<i>nnnnn</i>	The file number when <i>zzz</i> is "FNR"; otherwise, the RABN range ID										
<i>aaaa</i>	The type of RABN range storage ("ASSO" only, "DATA" only, "WORK", or "BOTH" if both ASSO and DATA are cached for the file)										
<i>xxxx</i>	The operation requested by the command. Valid values are: <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>ADDED</td> <td>CASSOxxx, CDATAxxx, or CFILE command</td> </tr> <tr> <td>CHANGED</td> <td>CCHANGE command</td> </tr> <tr> <td>DELETED</td> <td>CDELETE command</td> </tr> <tr> <td>DISABLED</td> <td>CDISABLE command</td> </tr> <tr> <td>ENABLED</td> <td>CENABLE command</td> </tr> </table>	ADDED	CASSOxxx, CDATAxxx, or CFILE command	CHANGED	CCHANGE command	DELETED	CDELETE command	DISABLED	CDISABLE command	ENABLED	CENABLE command
ADDED	CASSOxxx, CDATAxxx, or CFILE command										
CHANGED	CCHANGE command										
DELETED	CDELETE command										
DISABLED	CDISABLE command										
ENABLED	CENABLE command										

Message Variable	Description	
yyyy	The command requesting operation <i>xxxx</i> was issued by either:	
	AOS OPER	An Adabas Online System user; or
	OPERATOR	The operator.

Action If the command was unsuccessful, check DDPRINT for warning messages to determine why the command failed. Alternately, insure that the syntax used for the command is correct.

ADAN8U {zzz} {nnnnn} ({aaaa}) enabled on demand

Explanation This message is displayed for each inactive RABN range or file that is enabled when the Adabas buffer efficiency drops below the specified CDEMAND threshold level.

Message Variable	Description
zzz	The type of RABN range ("DSP" for data space; "ESP" for extended memory; "HSP" for hiperspace; "V64" for virtual 64; or "FNR" for file-related)
nnnnn	The file number when zzz is "FNR"; otherwise, the RABN range ID
aaaa	The type of RABN range storage ("ASSO" only, "DATA" only, "WORK", or "BOTH" if both ASSO and DATA are cached for the file)

ADAN8V {parameter list}

Explanation This message is displayed in response to the CPARM operator command. The parameters displayed are:

Parameter	Description
CASSOMAXS	maximum ASSO cache space size
CDATAMAXS	maximum DATA cache space size
CDISPSTAT	display to console option
CDEMAND	Adabas buffer efficiency threshold
CMAXCSPS	maximum number of cache spaces
CRETRY	retry time interval
CCTIMEOUT	non-activity time limit
CWORKSTORAGE	Work parts 2 and 3 cache type
CWORK2FAC	Work part 2 cache space factor
CWORK3FAC	Work part 3 cache space factor

ADAN8W **FNR nnnnn (aaaa) synchronized**
Explanation When Adabas Caching Facility first accesses a RABN belonging to a file to be cached, it learns about the extents and RABNs associated with the file and synchronizes its view of the file with the file's FCB.

If ADASCR detects that the structure of the file has changed (e.g., a new extent is added), ADASCR resynchronizes its view of the file at the next possible opportunity and issues this message.

nnnnn	file number
aaaa	what is being cached for the file (ASSO only, DATA only, or BOTH if both ASSO and DATA are being cached)

ADAN8Y **File-level caching initialized**
Explanation File-level caching is active for the current nucleus.

ADAN8Z **Logic error in ADACSH+{xxxxxxxx}**
Explanation A logic error occurred during Adabas Caching Facility processing.
Action Report the error and the hexadecimal offset to your Software AG technical support representative.

ADAN90 **TSP GETMAIN failed**
Explanation The Adabas trigger driver was unable to obtain enough storage within the region or address space to set up its I/O buffers.
Action Determine the source of the problem and correct it. Try increasing the region size for the MPM.

ADAN91 **TSP GETMAIN failed. Increase REG. size**
Explanation The Adabas trigger driver was unable to obtain enough storage within the region or address space to set up its I/O buffers.
Action Increase the region size for the MPM.

ADAN92 **TSP initialization completed**
Explanation The triggers and stored procedures facility was initialized successfully. Commands for detecting triggers are now processed.

ADAN92	TSP trigger refresh requested
Explanation	A request to refresh the trigger table buffer was made.
Action	No action is required.
ADAN92	TSP trigger refresh completed
Explanation	The trigger table buffer was refreshed. The triggers have been reloaded and the Adabas nucleus will continue to run normally.
ADAN93	TSP has been deactivated via AOS (SYSTRG)
Explanation	The ADARUN parameter SPT=YES was specified; however, because the database administrator has overridden this using the Adabas triggers subsystem, triggers will not be activated.
Action	To reactivate triggers, access the Adabas triggers subsystem function "modify profile information" (located on the Miscellaneous Functions Menu), and change the triggers status field in the profile to "active".
ADAN93	TSP cannot be run in single user mode
Explanation	The Adabas nucleus has been started with SPT=YES and MODE=SINGLE. This is not allowed.
Action	Start the nucleus with MODE=MULTI in the ADARUN parameters (DDCARD), or specify SPT=NO.
ADAN93	TSP incurred an internal error with cluster
Explanation	During the startup of the Adabas trigger driver, certain communication must occur with Adabas Parallel Services if it is active. The Adabas trigger driver was unable to complete the communication.
Action	After obtaining a dump, contact your Software AG technical support representative and report the error.
ADAN93	TSP trigger refresh incurred an error
Explanation	During the refresh of the trigger table buffer, an error occurred. This error was identified by a previous console message. The error causes an inconsistent state in the triggers subsystem that necessitates a shut-down as indicated in the error action option setting in the profile.
Action	Review previous console messages to determine the error. Correct it and, if necessary, restart the nucleus to restart the triggers subsystem.

ADAN94	TSP unable to read the trigger file FDT
Explanation	During the triggers initialization process, Adabas needs to read the trigger file FDT; however, the FDT could not be found. As a result, triggers will not be activated.
Action	Determine the reason why the FDT could not be found and correct the problem. Ensure that the file was correctly loaded as a system file.
ADAN95	TSP unable to read the trigger file FCB
Explanation	During the triggers initialization process, Adabas needs to read the trigger file FCB; however, the FCB could not be found. As a result, triggers will not be activated.
Action	Determine the reason why the FCB could not be found and correct the problem. Ensure that the file was correctly loaded as a system file.
ADAN96	TSP incurred resp xxx reading triggers
Explanation	During the triggers initialization process, Adabas needs to read the entries from the trigger file; however, a nonzero response code was received. As a result, triggers will not be activated.
Action	Determine the source of the problem; that is, analyze the response code and take the necessary action to resolve the problem.
ADAN97	nucleus will terminate with U021 dump due to internal autorestart failure; CMD={command}, FILE-NR={file-number}, RSP=rsrcode
Explanation	The nucleus terminates with a dump due to failure of the internal autorestart.
ADAN98	TSP unable to find any trigger entries
Explanation	During the triggers initialization process, Adabas needs to read the entries from the trigger file; however, no valid trigger entries were found in the file. As a result, triggers will not be activated.
Action	Verify that there are triggers defined on the trigger file and that the trigger file is set up correctly; that is, the file is loaded on the database where the error occurred.
ADAN99	TSP unable to load all trigger entries
Explanation	During the triggers initialization process, Adabas needs to load the entries from the trigger file into its buffer; however, the size calculated for the buffer is incorrect. The cause could be one of the following: <ul style="list-style-type: none"> ■ triggers were added by some means other than the Adabas triggers subsystem, or ■ the buffer size was not calculated or was specified incorrectly. As a result, triggers will not be activated.
Action	Recalculate the size required for the buffer. Issue the NUMBER or CHECK command from the Modify Profile screen to verify that the number is recorded correctly by

Adabas Online System. Also check the buffer size specified in the "trigger table size" field in the Adabas triggers and stored procedures profile.

ADAN99 TSP has ignored triggers gt file {nnnnn}

Explanation An attempt was made to process triggers that are assigned to file numbers greater than the maximum acceptable file number; that is, the highest loaded file plus 10.

Action This message is a warning. Triggers should not be assigned to file numbers greater than the maximum file number allowed.

ADAN9A TSP CNTL data missing on TRIG file ({nnnnn})

Explanation During the triggers initialization process, Adabas needs to read the profile definition from the trigger file; however, the profile definition could not be found. As a result, triggers will not be activated.

Action Using the Adabas triggers subsystem, add a profile for the subsystem.

ADAN9B TSP unable to read trigger control data

Explanation During the triggers initialization process, Adabas needs to read the profile definition from the trigger file. However, an internal error occurred during the read. As a result, triggers will not be activated.

Action Determine the cause of the error and correct it using the Adabas triggers subsystem. Possibly modify the profile again to ensure that it is correct.

ADAN9C TSP could not get work area. Check LWP

Explanation During the triggers initialization process, Adabas needs to acquire space for its buffer, but insufficient space was found. This can occur if the value specified for the LWP ADARUN parameter is too small. As a result, triggers will not be activated.

Action Check the value specified for the LWP ADARUN parameter and increase it as appropriate.

ADAN9D TSP no trigger file defined

Explanation The Adabas nucleus started with SPT=YES; however, no trigger file exists for this database. As a result, triggers will not be activated.

Action Either set SPT=NO or load a trigger file that contains at least one trigger definition onto the database.

ADAN9E	TSP missing module for subsystem
Explanation	During the triggers initialization process, Adabas needs to start the subsystems for the execution of procedures; however, the name specified was invalid. As a result, triggers has been deactivated.
Action	Check the batch Natural name setting in the Adabas triggers and stored procedures profile. Also ensure that the Natural nucleus module is concatenated in the JCS/JCL startup and is a loadable module.
ADAN9F	TSP has terminated the nucleus due to errors
Explanation	A serious or fatal error occurred that created an inconsistent state in the system. The nucleus has been shut down.
Action	Review previous console messages to determine the error. Correct it and restart the nucleus to restart the triggers subsystem.
ADAN9F	TSP has been deactivated due to errors
Explanation	Triggers incurred one or more errors and has been deactivated. The error action taken depends on the error action setting in the Adabas triggers and stored procedures profile.
Action	Review previous console messages to determine the cause of the errors and correct the problem.
ADAN9H	TSP subsystem ({nn}) {name} initialized / restarted
Explanation	<i>nn</i> is the unique number and <i>name</i> is the name of the Natural nucleus subsystem. During the triggers initialization process, a specified number of Natural subsystems will be started for the execution of procedures. When a subsystem has aborted it will be restarted. This message informs the user of the successful initialization/restart of each subsystem.
Action	No action is required. The subsystem will wait for work.
ADAN9I	TSP subsystem ({nn}) {name} has abended / SSF error / return code {code}
Explanation	<i>nn</i> is the unique number and <i>name</i> is the name of the Natural nucleus subsystem. The specified subsystem incurred an error and terminated abnormally. The Adabas trigger driver will try three times to restart it. A subsequent message will inform the user of the type of abend.
Action	Determine the cause and resolve the problem. The return code <i>code</i> given should provide additional information.

ADAN9I	TSP Status changed to Reject / Ignore mode
Explanation	The action to be taken by Adabas Triggers and Stored Procedures after a processing error from which the system cannot recover is changed to reject/ignore.
Action	No action is required.
ADAN9J	TSP subsystem ({nn}) {name} shut down
Explanation	<i>nn</i> is the unique number and <i>name</i> is the name of the Natural nucleus subsystem. Either a request was made to shut down the specified subsystem or three consecutive abends have occurred and the Adabas trigger driver has decided to deactivate the subsystem.
Action	Determine the cause and resolve the problem. The return code given should provide additional information.
ADAN9J	TSP unable to update Trigger table
Explanation	It was not possible to get an exclusive lock of the trigger table.
Action	Retry the command.
ADAN9J	TSP subsystem ({nn}) {name} shut down
Explanation	<i>nn</i> is the unique number and <i>name</i> is the name of the Natural nucleus subsystem. The shut-down of triggers has completed successfully. This message is shown for each subsystem.
ADAN9K	TSP subsystem ({nn}) {name} canceled / timed out
Explanation	<i>nn</i> is the unique number and <i>name</i> is the name of the Natural nucleus subsystem. During the processing of a trigger, it was detected that the originating command had timed out or was canceled by AOS request. The trigger will not be processed successfully.
Action	Retry the command.
ADAN9K	TSP subsystem ({nn}) {name} canceled
Explanation	<i>nn</i> is the unique number and <i>name</i> is the name of the Natural nucleus subsystem. The specified subsystem was canceled when a timeout occurred for a procedure that was executing in the subsystem. The subsystem will be restarted. A previous message gives specifics about the cancellation.
Action	Determine the cause and resolve the problem. The reason code given should provide additional information.

ADAN9K	TSP requested: {Halt} at {YYYY-MM-DD HH:MM:SS}
Explanation	The Error Action field in the Adabas triggers and stored procedures profile is set to <i>halt</i> , and either a fatal error occurred or Adabas Online System requested a shut-down of the Adabas triggers subsystem.
Action	Review previous messages to determine whether a problem occurred and, if so, correct the problem.
ADAN9L	TSP Timeout / Cancel: PROC {proc-name} JOB {jobname} CMD {yy} FNR {nnnnn} FIELD-UID {xxxxxxxxxxxxxxxx} SECUID {secuid}
Explanation	The Adabas trigger driver determined that a triggered procedure exceeded the specified time limit. The procedure was canceled so that processing can continue with another procedure and queuing can be prevented. FIELD-UID is the last 8 bytes of the user ID in hexadecimal, as specified in the UQE. SECUID is the security ID of the user ID.
Action	Check the procedure. Determine if it was looping, is doing too much work, or if the time-out parameter is too low. Correct the problem for the next time.
ADAN9L	TSP Timeout / Cancel: PROC {proc-name} JOB {jobname} *stored procedure req ** UID {xxxxxxxxxxxxxxxx} SECUID={secuid}
Explanation	The Adabas trigger driver determined that a particular stored procedure exceeded the specified time limit. The procedure has been canceled so that processing may continue with another procedure and queuing may be prevented. UID is the last 8 bytes of the user ID in hexadecimal, as specified in the UQE. SECUID is the security ID of the user ID.
Action	Check the procedure. Determine if it was looping, is doing too much work, or if the time-out parameter is too low. Correct the problem for the next time.
ADAN9M	TSP waiting on UID {userid} SECUID {secuid}
Explanation	Triggers is shutting down and must queue the subsystems. However, a procedure is still running. The user ID (UID) and security ID (SECUID) are provided to help the database administrator investigate a potential problem.
Action	No action is necessary. However, the database administrator may not want the Adabas trigger driver to wait; therefore, the user's procedure may be stopped.
ADAN9N	TSP subsystem ({nn}) {name} canceled TSP Subsystem({xx}) Triggers:{count}
Explanation	<i>nn</i> is the unique number and <i>name</i> is the name of the Natural nucleus subsystem. Subsequent to ADAN9N, the Adabas trigger driver decided not to wait for the specified subsystem to complete processing; therefore, the subsystem was canceled. The second line of this message appears during shutdown of TSP databases. It shows the number of triggers used during that nucleus session (<i>count</i>).

Action	No action is required for this informational message.
ADAN90	TSP subsystem shutdown in progress
Explanation	Either the nucleus is terminating (ADAEND or HALT) or the triggers and stored procedures facility has requested a halt, probably due to an error, and the Adabas trigger driver has also been requested to shut down.
Action	No action is required. The user is informed that this is in progress.
ADANA1	SMGT display active DUMP={on off}
Explanation	A display command is about to be processed with (ON) or without (OFF) a formatted dump.
ADANA2	SMGT {active not active}
Explanation	Indicates whether the error handling and message buffering facility is active in the nucleus.
ADANA3	Abnormal termination handler {active not active}
Explanation	Indicates whether the error handling and message buffering facility's abnormal termination handler is active.
ADANA5	No error conditions handled
Explanation	The error handling and message buffering facility has not encountered any of the errors it is looking for.
ADANA6	Last error occurred at: {date time}
Explanation	Indicates the <i>date</i> (yyyy-mm-dd) and <i>time</i> (hh:mm:ss) of the most recent error handled by the error handling and message buffering facility.
ADANA7	Condition: {{mvs-abend-code} rsp: {rsp-code}} location: {location}
Explanation	Identifies the abnormal termination that has occurred or the response code that has been received and indicates the location (if any) of the most recent error handled by the error handling and message buffering facility. Explanations of z/OS abnormal termination codes can be accessed in the <i>System Codes Manual</i> from IBM.

ADANA8	Count executions of abnormal termination handler
Explanation	Indicates the number of times an error or abend code is trapped and actually handled by the error handling and message buffering facility.
ADANA8	Count executions of response code handler
Explanation	Indicates the number of times a response code is actually handled (that is, a PIN routine is invoked) by the error handling and message buffering facility.
ADANA8	Count executions of total error recovery calls
Explanation	Indicates the total number of times the error handling and message buffering facility is invoked to handle a condition (response code or abend code).
ADANA9	Last error handled by pin pin-number
Explanation	Indicates the PIN routine invoked by the error handling and message buffering facility to handle the most recent error encountered.
ADANAA	{xxx} condition PIN routines recovered {yyy} errors
Explanation	Indicates the number of condition-handling PIN routines invoked and the number of errors they recovered.
ADANAB	{xxx} location PIN routines recovered {yyy} errors
Explanation	Indicates the number of location-only PIN routines invoked and the number of errors they recovered.
ADANAC	{xxx} response PIN routines recovered {yyy} errors
Explanation	Indicates the number of response-code PIN routines invoked and the number of errors they recovered.
ADANAD	{xxx} total PIN routines recovered {yyy} errors
Explanation	Indicates the total number of PIN routines invoked and the number of errors they recovered.

ADANAE	Message buffering is {active not active}
Explanation	Indicates whether message buffering in the error handling and message buffering facility is active.
ADANAF	{nnn} messages in buffer from {date} {time}
Explanation	Indicates the number of messages currently in the message buffer and the <i>date</i> (yyyy-mm-dd) and <i>time</i> (hh:mm:ss) of the oldest message.
ADANAG	PIN {nnnn} uses: {nnnn} condition: {{mvs-abend-code} rsp:{rsp-code}} {this pin valid for all locations {routine-name} location: {hexno hexno (routine-name)}}
Explanation	Provides information about an active (PIN) or inactive (*PIN) routine: the number of times used, the condition it handles (the abnormal termination that occurred or the response code that was returned), and the location(s) for which it is valid. Explanations of z/OS abnormal termination codes can be accessed in the <i>System Codes Manual</i> from IBM.
ADANAI	AUTOINC{xxxx}TOTAL={nnnn} is invalid, current {xxxx}SIZE={yyyy}
Explanation	An invalid autoincrease AUTOINCxxxxTOTAL operator command was specified. The specification for the AUTOINCASSOTOTAL or AUTOINCDATATOTAL operator command is smaller than the currently allocated size for the ASSO or DATA data set or exceeds 2,147,483,647 blocks or 16,777,215 blocks (3-byte RABNs).
ADANAL	There are currently no exits in use
Explanation	The DISPLAY=EXITS command was issued but no exits are currently in use.
ADANAX	Exit: {exit-code} modname: {exit-module-name} status: {ACTIVE ACTIVE CRT ENACT}
Explanation	Indicates whether the specified exit is active, active and critical, or inactive.
ADANC1	{dbid yyyy-mm-dd hh:mm:ss} Caution: DDCLOGR{n} dataset not yet copied
Explanation	The nucleus detected that there is one or more CLOG data set that needs to be copied and the LOGWARN timer has expired. One message will occur for each data set that needs to be copied.
Action	Check the status of the CLCOPY jobs affecting the oldest CLOG to be copied to determine why the copy has not worked correctly or in a timely fashion. If necessary, make corrections and resubmit the job. If all CLOG data sets become full, your nucleus may stall waiting for a free CLOG.

ADANC2	{dbid yyyy-mm-dd hh:mm:ss} CLOG warning no longer in effect
Explanation	All CLOG data sets have now been copied.
Action	No action is required for this informational message.
ADANC3	{dbid yyyy-mm-dd hh:mm:ss} Command logging has stalled
Explanation	There are no free command log data sets. The nucleus is unable to write command log data. This also prevents Adabas from executing commands and the environment may appear to be completely stalled.
Action	Check the status of the latest CLCOPY jobs, concentrating on the jobs affecting the oldest CLOG to be copied. If necessary, make corrections and resubmit the jobs.
ADANC4	{dbid yyyy-mm-dd hh:mm:ss} Command logging has resumed
Explanation	Command logging has resumed after a stalled situation. An ADANC3 stalled message should have appeared sometime before this message.
Action	No action is required for this informational message. The crisis of stalled command logging has been resolved.
ADANI2	SMGT abend handler active
Explanation	Indicates that the abnormal termination handler of the error handling and message buffering facility is active.
ADANI4	GETMAIN failed for exit table
Explanation	Not enough memory is available to run the error handling and message buffering facility. Adabas runs without the facility.
Action	Increase the region size available to the Adabas nucleus.
ADANI5	GETMAIN failed for initial PIN area
Explanation	Not enough memory is available to run the error handling and message buffering facility. Adabas runs without the facility.
Action	Increase the region size available to the Adabas nucleus.
ADANL0	Error opening license file DD:{ddname}
Explanation	An error occurred loading the license load module and then opening the license file specified by the DD/link statement. Where <i>ddname</i> is the DD/link name for the license sequential file. The name is concatenated from the string DDL and the product code <i>cccc</i> .
Action	Provide the license as load module or assign the license file to the <i>ddname</i> in the JCL.

ADANL1	License file size exceeds limit
Explanation	The license being read is larger than expected (8000 bytes).
Action	Verify that you are using the original license file obtained from Software AG.
ADANL2	Error reading license file DD:{ddname}
Explanation	An empty file or invalid record structure was detected. Where <i>ddname</i> is the DD/link name for the license sequential file. The name is concatenated from the string DDL and the product code <i>cccccc</i> .
Action	Verify that the license file has been copied correctly to the license data set. The file should not be empty and the data should not have been converted to EBCDIC (it should be in ASCII format).
ADANL3	Error license function {fx} subfunction {sfx} returned {err}
Explanation	An unexpected error occurred while performing the Adabas license check.. The license function (<i>fx</i>), subfunction (<i>sfx</i>) and return code (<i>err</i>) are given in the message.
Action	Examine the Adabas nucleus JCL and verify that the Adabas license is available as load module ADALIC or is assigned with the link (DD) name DDLIC.
ADANL4	License module could not be loaded
Explanation	The license processor module could not be loaded.
Action	Verify that the modules from the MLC <i>vrs</i> load library can be loaded by the Adabas nucleus.
ADANL6	License check failed for {cccc}
Explanation	The license file is physically correct, but some license property was found that did not match your Adabas nucleus execution environment. Where <i>cccccc</i> is the product code where the license was checked. This is a final message, accompanied by another message specifying details of the failure.
Action	Contact your Software AG sales representative to resolve the discrepancy between your license file and your execution environment.
ADANL7	License check completed for {cccc}
Explanation	The license check completed successfully. Where <i>cccccc</i> is the product code where the license was checked.
Action	No action is required for this informational message.

ADANL9	{cccc}LIC license could not be loaded
Explanation	The license module <code>ccccLIC</code> for Adabas or an add-on identified by product code <code>cccc</code> could not be loaded.
Action	Verify that the installation of the license file occurred correctly. For more information, read about the Adabas database installation steps for your operating environment. If problems persist, contact your Software AG technical support representative for assistance.
ADANLA	Error using MLC version older than {vvvv}
Explanation	The product license check works with the separate component Mainframe License Check (MLC). For a correct interaction with MLC a minimum version <code>vvvv</code> is required.
Action	Update the MLC component and rerun the job.
ADANN1	NWCONNECT RSP/ {rsp} // {subcode} // {node}*
Explanation	The NWCONNECT operator command received an unexpected response when attempting to define the DBID target to Entire Net-Work. The response and subcodes given in the message are from Entire Net-Work. Depending on the error, the Entire Net-Work node name may also appear. The most common response codes are 148 (ADARSP148 - Entire Net-Work not available) and 145 (ADARSP145 - target already defined on another Entire Net-Work node).
Action	Resolve the Entire Net-Work problem. If the problem persists, contact your Software AG technical support representative for assistance.
ADANO1	Invalid SMGT cmd: {command}
Explanation	The operands on an SMGT command were invalid.
Action	Correct the operands and reissue the command.
ADANO2	SMGT command processed
Explanation	The error handling and message buffering facility finished processing a command.
ADANO5	SMGT not currently active
Explanation	The error handling facility must be active (SMGT=ON) before the command can be issued. The command issued can be found in the ADANO1 message immediately following the ADANO5 message.
Action	Activate the error handling facility and reissue the command.

ADANP1	{dbid yyyy-mm-dd hh:mm:ss} Caution: DDPLOGR{n} dataset not yet copied
Explanation	The nucleus detected that there is one or more PLOG data set that needs to be copied and the LOGWARN timer has expired. One message will occur for each data set that needs to be copied.
Action	Check the status of the PLCOPY jobs affecting the oldest PLOG to be copied to determine why the copy has not worked correctly or in a timely fashion. If necessary, make corrections and resubmit the job. If all PLOG data sets become full, your nucleus may stall waiting for a free PLOG.
ADANP2	{dbid yyyy-mm-dd hh:mm:ss} PLOG warning no longer in effect
Explanation	All PLOG data sets have now been copied.
Action	No action is required for this informational message.
ADANP3	{dbid yyyy-mm-dd hh:mm:ss} Protection logging has stalled
Explanation	There are no free protection log data sets. The nucleus is unable to write protection log data. This also prevents Adabas from executing update commands which could eventually lead to a complete stall of the environment.
Action	Check the status of the PLCOPY jobs, concentrating on the jobs affecting the oldest PLOG to be copied. If necessary, make corrections and resubmit the jobs.
ADANP4	{dbid yyyy-mm-dd hh:mm:ss} Protection logging has resumed
Explanation	Protection logging has resumed after a stalled situation. An ADANP3 stalled message should have appeared sometime before this message.
Action	No action is required for this informational message. The situation of stalled protection logging has been resolved.
ADANR1	SMGT handling condition: {{mvs-abend-code} rsp: {rsp-code} }
Explanation	The error handling facility has been invoked for the specified condition. Note that explanations of z/OS abnormal termination codes can be accessed in the <i>System Codes Manual</i> from IBM.
ADANR2	Error is in {user hyper} exit {xx}, exit disabled
Explanation	An error occurred in the specified, noncritical exit. The exit is not invoked until the error is corrected.
Action	Consult diagnostic messages; correct the exit; reload the exit using the SGMT,XLOAD command; then reactivate the exit using the SGMT,XACT command.

ADANRP	PSW: {hexno hexno hexno hexno}
Explanation	Displays the PSW when the error was encountered.
ADANRR	{ry-ry} {hexno hexno hexno hexno}
Explanation	Displays the registers when the error was encountered.
ADANRS	Response {rspc/subc} when posting commands in cluster
Explanation	An unexpected response / subcode occurred when trying to post commands waiting for advance-locks in a cluster environment.
Action	Ensure that the communication between the cluster nodes works.
ADANRT	Condition is a {error-type} error
Explanation	The error handling facility is handling an error of the specified type.
ADANS1	SNAP file unavailable
Explanation	The nucleus startup JCL did not define a data set to hold a formatted hexadecimal dump of an area in memory, either an address space or a data space.
	To use the error handling and message buffering facility's SMGT,DUMP={ON OFF } or SMGT,SNAP[=(start,end)] command successfully, the data set ADASNAP must be defined in the Adabas startup JCL.
Action	Stop the Adabas session; add the required statement to the startup JCL, and start a new session.
ADANS5	{dbid} Database {ASSO DATA} usage is {xx}% {xxuu} of {yyuu} in use {bb} of {byy} blocks in use {cc} of {cyy} cylinders in use
Explanation	This space usage message is printed during nucleus startup when the ASSOSPACEWARN or DATASPACEWARN ADARUN parameters are specified with a nonzero threshold percentage and the ASSO or DATA space use is greater than or equal to the threshold specification. Similarly, if autoincrease ADARUN parameters have been specified with nonzero parameters, this message appears when either of the AUTOINCASSOTHRESHOLD or AUTOINCDATATHRESHOLD settings are exceeded. Only the first line of the message (percentage) appears in these cases.
	The message also appears in response to a DSPACE operator command. In this case, all four lines appear for both ASSO and DATA for a total of 8 lines.
	The second detail line expresses the statistics in <i>uu</i> units, which may be "KB" (2 ¹⁰ bytes), "MB" (2 ²⁰ bytes), "GB" (2 ³⁰ bytes) or "TB" (2 ⁴⁰ bytes).

When more than one container is configured for a component (ASSO or DATA) the statistics represent the sum of all the component's containers. If different device types are used for individual containers, the block size and the number of blocks per cylinder may be different for each container.

Action No action is necessary for this informational message. However, if the percentage is excessively high, determine the reason for the excessive ASSO or DATA space use. If necessary, adjust the ASSO or DATA space. For more information, read *Dynamically Increasing Associator and Data Storage Space*, in the *Adabas DBA Tasks Manual*.

ADANS6 {dbid} Database {ASSO|DATA} usage increased to {xx}%

Explanation This space usage message is printed when the amount of ASSO or DATA space used in the database increases by the increment set by the ADARUN ASSOSPACEWARN or DATASPACEWARN parameters or by the ASSOSPACEWARN or DATASPACEWARN operator commands.

Action No action is necessary for this informational message. However, if the percentage is excessively high, determine the reason for the excessive ASSO or DATA space use. If necessary, adjust the ASSO or DATA space. For more information, read *Dynamically Increasing Associator and Data Storage Space*, in the *Adabas DBA Tasks Manual*.

ADANS7 {dbid} Database {ASSO|DATA} usage increased to {xx}% in nucleus {zzzz}

Explanation This space usage message is printed when the amount of ASSO or DATA space used in the database increases by the increment set by the ADARUN ASSOSPACEWARN or DATASPACEWARN parameters or by the ASSOSPACEWARN or DATASPACEWARN operator commands. The increase in space usage in the database is being reported by nucleus zzzz in a cluster environment.

Action No action is necessary for this informational message. However, if the percentage is excessively high, determine the reason for the excessive ASSO or DATA space use. If necessary, adjust the ASSO or DATA space. For more information, read *Dynamically Increasing Associator and Data Storage Space*, in the *Adabas DBA Tasks Manual*.

ADANS8 {dbid} Database {ASSO|DATA} usage decreased to {xx}%

Explanation This space usage message is printed when the amount of ASSO or DATA space used in the database decreases by the increment set by the ADARUN ASSOSPACEWARN or DATASPACEWARN parameters or by the ASSOSPACEWARN or DATASPACEWARN operator commands.

Action No action is required for this informational message.

ADANS9	{dbid} Database {ASSO DATA} usage decreased to {xx}% in nucleus {zzzz}
Explanation	This space usage message is printed when the amount of ASSO or DATA space used in the database decreases by the increment set by the ADARUN ASSOSPACEWARN or DATASPACEWARN parameters or by the ASSOSPACEWARN or DATASPACEWARN operator commands. The decrease in space usage in the database is being reported by nucleus <i>zzzz</i> in a cluster environment.
Action	No action is required for this informational message.
ADANSA	{dbid} Autoincrease threshold exceeded for {ASSO DATA}
Explanation	This message is printed if the ASSO or DATA autoincrease ADARUN parameters have been specified with nonzero parameters and the AUTOINCASSOTHRESHOLD or AUTOINCDATATHRESHOLD settings have been exceeded.
Action	No action is required for this informational message.
ADANSB	{dbid} Autoincrease started for {ASSO DATA}
Explanation	This message is printed if the ASSO or DATA autoincrease ADARUN parameters have been specified with nonzero parameters, the AUTOINCASSOTHRESHOLD or AUTOINCDATATHRESHOLD settings have been exceeded and the nucleus has started the autoincrease process.
Action	No action is required for this informational message.
ADANSC	{dbid} Autoincrease added {nn} blocks to {ASSO DATA}
Explanation	This message is printed as a result of an autoincrease process after the database extents block (GCB2) has been updated. It indicates the number of blocks (<i>nn</i>) that have been added to the Associator or Data Storage data set.
Action	No action is required for this informational message.
ADANSD	{dbid} Autoincrease completed for {ASSO DATA}
Explanation	This message indicates that the autoincrease process has completed and the new space was added to the free space table (FST).
Action	No action is required for this informational message.
ADANSE	{dbid} Unable to autoincrease {ASSO DATA} Autoincrease {ASSO DATA} aborted because {reason}
Explanation	An error has occurred while attempting an autoincrease process for the ASSO or DATA container. The AUTOINCASSOTHRESHOLD or AUTOINCDATATHRESHOLD setting (as appropriate) has been set to zero to prevent another attempt. The reason for the failure is given in the message (<i>reason</i>). Possible reasons include: <ul style="list-style-type: none"> ■ Autoincrease total already reached ■ Container change already in progress

- Container change already in progress in peer nucleus
- Error in calculation of used space
- FST update failed
- GCB lock unavailable
- Get VOLSER table failed
- Getmain VOLSER extent failed
- HALT pending
- Invalid message index *idx* autoincrease {ASSO|DATA}
- IOR-3D open extended failure
- IOR-3E extend ASSO/DATA failure
- IOR-3E extend did not get any space
- IOR-3E extend failure on peer nucleus
- IOR-5B format track failure
- No room in FST for additional extent
- Online recovery in progress
- Other ONLINCREASE in progress
- Too many ASSO, DATA and DSST extents
- VOLSER table inconsistent
- VOLSER table mismatch

Action Contact your Software AG technical support representative if you are unable to resolve the failure.

ADANSF {dbid} Autoincrease formatted {mmm} of {nnn} {ASSO|DATA} blocks
Formatting {xx}% complete, {ss} seconds estimated to complete

Explanation These status messages are produced at intervals during the execution of an autoincrease process. They are issued while the autoincrease process is active or when one of the following operating commands is run: ADAEND, DSTAT, or HALT. They provide you with information about the progress of the autoincrease process.

Action No action is required for this informational message.

ADANSg {dbid} AUTOINC{xxxx}TOTAL smaller than existing [ASSO|DATA] size
Autoincrease for [ASSO|DATA] is being disabled

Explanation The AUTOINCxxxxTOTAL parameter for the ASSO or DATA container specifies a value smaller than the current size of the container. The parameter is set to zero, which disables autoincrease processing for the container.

Action To reenale autoincrease processes, reset the AUTOINCASSOTOTAL or AUTOINCDATATOTAL parameter to a nonzero value greater than the current size of the ASSO or DATA container.

ADANSH	{dbid} Autoincrease for [ASSO DATA] will not be performed at this time {reason}
Explanation	<p>An attempt was made to initiate an autoincrease process for the ASSO or DATA container, but the current environment does not allow autoincrease processes. A reason (<i>reason</i>) is given in the message. Possible reasons include:</p> <ul style="list-style-type: none"> ■ ADAEND/HALT pending ■ Autoincrease is not currently enabled ■ Conflicting utility running ■ Error reading FST ■ FST allocation failure ■ GCB2 overflow ■ Global container change lock unavailable ■ Highest possible RABN already reached ■ Invalid device type (internal error) ■ Invalid autoincrease size: too large/small ■ Local container change lock unavailable ■ No room in FST for additional extent ■ Nucleus in read-only mode ■ Nucleus in single-user mode ■ Online recovery in progress ■ ONLINEINCREASE in progress ■ Threshold no longer exceeded ■ Unable to calculate used percentage ■ Unable to create ICQE <p>Conflicting utilities are those that require exclusive database control, for example the ADAORD function REORGDB.</p> <p>The global lock is used only in cluster configurations.</p>
Action	Contact your Software AG technical support representative for assistance if you are unable to resolve the conflict.
ADANSJ	{dbid} Remaining cluster nuclei will check autoincrease thresholds
Explanation	This message is issued when a terminating cluster nucleus causes a threshold to be exceeded and there is at least one other active nucleus. Because autoincrease processes cannot be initiated during nucleus termination, a check of thresholds will occur on another nucleus.
Action	No action is required for this informational message.

ADANSK	{dbid} Error writing SYNS-83 checkpoint for [ASSO DATA] autoincrease Response/Subcode {rrr}/{sssss }
Explanation	The SYNS-83 checkpoint contains data relating to an autoincrease attempt. The checkpoint could not be created.
Action	Contact your Software AG technical support representative for assistance.
ADANSL	{dbid} Autoincrease formatting {ASSO DATA} started
Explanation	This message is printed as a result of an autoincrease process. It indicates that the formatting process of the increased space has started.
Action	No action is required for this informational message.
ADANSM	{dbid} Autoincrease formatting {ASSO DATA} finished
Explanation	This message is printed as a result of an autoincrease process. It indicates that the formatting process of the increased space has finished.
Action	No action is required for this informational message.
ADANSN	{dbid} AUTOINC{xxxx}THRESHOLD set to 0 to disable autoincrease
Explanation	An error described in a previous ADANSE or ADANSH message caused the nucleus to disable autoincrease processes for the specified component.
Action	To re-enable autoincrease processes, reset the ASSO or DATA threshold parameter AUTOINCxxxxTHRESHOLD to a nonzero value. Contact your Software AG technical support representative if you are unable to resolve the earlier failure.
ADANSP	{dbid} Extended {ddname} by {nnnnn} {cylinders blocks}
Explanation	This message indicates that the first step of an autoincrease process has successfully completed. It shows the size of the allocated extent for the ASSO or DATA data set. This size might be smaller than the size requested (see message ADAI79). For example, in z/OS environments, when the size specified in blocks is not a multiple of the blocks-per-track for the device, the size is rounded down to the last multiple.
Action	No action is required for this informational message.
ADANSQ	{dbid} Unable to allocate memory for autorestart WORK buffers Memory requested = {xxx,xxx} Memory acquired = {yyy,yyy} Autorestart will run with one WORK buffer
Explanation	This message indicates that a problem occurred allocating memory for the number of work buffers requested for autorestart processing in the ADARUN ARNWORKBUFFERS parameter. The amount of memory requested (xxx, xxx) and actually amount of memory acquired (yyy, yyy) are provided in the message. Because of this problem, autorestart processing will run with only one work buffer.

Action	No action is required for this informational message. However, you might consider adjusting your ADARUN ARNWORKBUFFERS parameter setting.
ADANT1	SMGT {activated deactivated}
Explanation	Indicates a change of status in the error handling and message buffering facility.
ADANT2	Message buffering {activated deactivated}
Explanation	Indicates a change of status in message buffering.
ADANT4	Abnormal termination handler {activated deactivated}
Explanation	Indicates a change of status in the abnormal termination handling or the error handling and message buffering facility.
ADANT5	GETMAIN failed for PIN descriptors
Explanation	Not enough memory was available to add new PINs. Adabas runs without the PIN module.
Action	Increase the size of the region available to the Adabas nucleus.
ADANT6	Module {module-name} load failed
Explanation	Unable to load the specified module. The error handling and message buffering facility runs without the module.
Action	Ensure that the module is available to the error handling facility by placing it in the Adabas program library.
ADANT7	Invalid exit {exit-code}
Explanation	The exit-code indicated in the message is not a valid code, or is not in the correct state for the command requested. Adabas rejects the command.
Action	Ensure that the exit-code is correct. If it is, ensure that the exit is in a state that allows the requested command.
ADANT8	Exit {exit-code} in use module({module-name})
Explanation	The exit-code specified in the message indicates an active exit. Adabas rejects the command.
Action	Ensure that the exit-code is correct. If it is, ensure that the exit is in a state that allows the requested command.

ADANT9	No module name for exit load
Explanation	Adabas cannot load the exit without the name of the module. Adabas rejects the command.
Action	Retype the SGMT,XLOAD command and include a member name for the exit.
ADANTA	Exit {exit-code} not loaded
Explanation	A command that requires an exit cannot be processed because the exit is not loaded. Adabas rejects the command.
Action	Ensure that the exit-code is correct. If it is, load the exit.
ADANTB	exit {exit-code} module {exit-module-name} status: {active inact loaded crit notcrt}
Explanation	The status (active, not active, loaded, critical, or not critical) of an exit changed as a result of an operator command, and this messages provides the details.
ADANTC	Invalid SNAP parameters
Explanation	The parameters provided for a SNAP command are invalid. Adabas rejects the command.
Action	Ensure that the addresses provided to the SNAP command are correct.
ADANTD	PIN routine {pin-number} disabled
Explanation	The specified PIN routine has been disabled.
ADANTE	PIN routine {pin-number} not found
Explanation	The PIN routine for the previous command was not found. Adabas rejects the command.
Action	Ensure that the PIN routine is correct and reissue the command.
ADANTF	PIN routine {pin-number} enabled
Explanation	The specified PIN routine has been enabled.
ADANTG	PIN module {module-name} loaded
Explanation	The specified PIN module has been loaded.

ADANTH	PIN module {module-name} deleted
Explanation	The specified PIN module has been removed from memory.
ADANTI	PIN module {module-name} not {found valid}
Explanation	The PIN module for the previous command is not available. Adabas rejects the command.
Action	Ensure that the PIN module name is correct, and that the PIN module is in the Adabas library; then reissue the command.
ADANTJ	{ FULL SNAP } dumps taken for events
Explanation	Indicates whether a full dump or a snap dump is taken.
ADANTM	Message buffering unable to activate
Explanation	Message buffering cannot be activated.
Action	Add the MSGBUF= parameter to the initial ADARUN parameters.
ADANX1	Command {cmd} Command-ID {hex-cid} FNR {file-number} Response {rsp-code} Subcode {rsp-subcode} FLD {field-name} TID {hex-internal-userid} UID {open-userid} JOB {jobname} SECUID {security-id}
Explanation	Format of the diagnostic information produced by the Adabas PINRSP or PINUES routine. The PINRSP routine will produce only the cmd, hex-cid, rsp-code, and rsp-subcode information.
ADANY1	Adabas must be run from an authorized environment
Explanation	The PIN ADAMXY detected a S047 abend.
Action	Run Adabas from an authorized load library.
ADANY4	Error occurred in routine: {routine-name}
Explanation	The PIN ADAMXY determined that the particular error is in the identified routine.
Action	Refer to the appropriate operating system documentation for a description of the system abend that occurred.

ADANZ1	Adabas SMGT terminated
Explanation	Adabas is in the process of termination, and the error handling and message buffer facility functions have been terminated.
ADEN1	Invalid control string: {string}
Explanation	Adabas Online System internal error.
Action	Contact your Software AG technical support representative.
ADONIS1	Load failed on SMGT module {module-name}
Explanation	A load module for the error handling and message buffering facility could not be loaded. Adabas runs without the facility.
Action	Ensure that all modules for the error handling and message buffering facility installed with Adabas are still in the distributed library. If modules are missing, restore a copy of the module from a backup and apply any maintenance.

ADATCP messages ADACM* messages ADATCP Messages (Prefix ADACM)

The ADATCP component displays several information or error messages on the system console. The functionality for which ATACM* ADATCP messages might be displayed is now largely provided by Entire Net-Work components.

ADACM007E	Parm error
Explanation	One of the parameters passed within the URL was incorrect.
Action	Ensure that the URL includes valid values for all required elements: the API name (protocol), stack ID, and port number. Correct the URL and try again.
ADACM008E	Invalid value in PORT= parameter
Explanation	The port that was specified in the URL was not valid.
Action	The port number can be 1-5 bytes; it cannot be zero (0) or greater than 65535.
ADACM009E	URL={url} already {active closed}
Explanation	Either the URL is already opened (ACTIVE) or already closed (CLOSED).
Action	Ensure that the URL includes valid values for all required elements: the API name (protocol), stack ID, and port number. Correct the URL and try again.

ADACM010E	URL={url} not found
Explanation	The URL itself was not found.
Action	Ensure that the URL includes valid values for all required elements: the API name (protocol), stack ID, and port number. Correct the URL and try again.
ADACM011I	URL={url} has been {closed opened}
Explanation	The URL was successfully closed or opened.

VI DCAM Feedback Codes

8

DCAM Feedback Codes

Code	Explanation
0C04	Application not connected with partner. LOSCON contingency processing is probably pending.
0C40	Connection was refused by partner without reason. With TRANSIT-CD (Entire Net-Work VTAM): Line was deactivated (INACT); e.g., /DADM PX25,vr,RESET,vr11r7.
0C48	Time-out for connection request. With TRANSIT-CD (Entire Net-Work VTAM): Cross-domain session did not notice IPL on IBM side; e.g., /DADM PNET,vr,ACT,siehost,siegate.
0C4C	DCAM partner application not active.
0C5CXX	OPNCON was rejected by partner: <ul style="list-style-type: none"> ■ 00: ■ 18: Application not active on SISNIX (via HDLC). ISO=Y on X.25 link. ■ 2: Partner rejects connection; partner has different information (NAME) for this application; or ISO application wanted to connect to a non-ISO application. ■ 5C: Application not active via X.25; or an X.25 "call-user-data" was probably required.
0C78	Immediately after connection installation, the partner or system disconnected. ISO parameter missing.
1840	Invalid processor name: <ul style="list-style-type: none"> ■ Check that the processor name is in RDDF; ■ Issue a /BCIN command.
100408	BDCAM buffer shortage. DCAM driver waits for 5 seconds and retries operation. When GO signal is not used. retry is scheduled after DCAM has given the GO signal.
10040C	BDCAM buffer shortage. Wait for GO signal.

VII

■ 9 Nucleus Startup Error Messages	125
■ 10 Adabas Response Codes	147

9 Nucleus Startup Error Messages

This section describes error messages and response codes issued by the Adabas nucleus. These errors may occur during nucleus startup, usually as the result of an ADARUN parameter error. The nucleus prints an error message and then terminates with an abnormal end (abend) code of 20 (see the [abend code descriptions](#)).

Refer to the Adabas Operations documentation for a description of the ADARUN parameters.

These error messages have the following format:

```
PARM-ERROR nnn [detected during system open]
```

-where "nnn" is one of the startup errors and has the corresponding meaning described here. The error message may be followed by a brief error description.

PARM-ERROR 1

Explanation	The Associator data set(s) could not be opened or an error occurred during processing of the GCBs: <ul style="list-style-type: none">■ invalid or incorrect DEVICE parameter;■ missing or invalid JCL or data sets for ASSO;■ mismatching database ID; or■ missing checkpoint file.
Action	This error may result from a data set not located on a cylinder boundary. For single-user mode, the appropriate Adabas job control statements must be specified.

PARM-ERROR 2

Explanation Data Storage data set(s) could not be opened. This probably indicates missing or invalid JCL or data sets for DATA.

Action For single-user mode, the appropriate Adabas job control statements must be specified.

PARM-ERROR 3

Explanation The Work data set could not be opened, or the last Work block was not readable. This probably indicates invalid DD/WORKR1 JCL or data set, or a data set not located on a cylinder boundary.

Action For single-user mode, the appropriate Adabas job control statements must be specified.

PARM-ERROR 4

Explanation The value of the ADARUN statement's number of threads (NT) parameter is invalid. The allowed range is from 4 to 250.

PARM-ERROR 5

Explanation The value of the ADARUN statement's number of hold queue elements (NH) parameter is invalid. The allowed range is from 20 to 16,777,215.

PARM-ERROR 6

Explanation The value of the ADARUN statement's user queue element count (NU) parameter is invalid. The allowed range is from 20 to 16,777,215.

PARM-ERROR 7

Explanation The value of the ADARUN statement's user ISN hold queue count (NISNHQ) is invalid. The allowed maximum is either the NH ADARUN parameter setting or 16,777,215 (whichever is smaller).

PARM-ERROR 8

Explanation The value of the ADARUN statement's command queue element count (NC) parameter is invalid. The allowed range is from 20 to 32,767.

PARM-ERROR 9

Explanation The value of the ADARUN statement's Adabas cluster nucleus ID (NUCID) is invalid. The maximum value is 65000.

PARM-ERROR 10

Explanation The value of the ADARUN statement's ISN list table length (LI) parameter is invalid. The minimum value is 2000.

PARM-ERROR 11

Explanation The value of the ADARUN statement's sequential command table (LQ) parameter is invalid. The minimum value is 2000.

PARM-ERROR 12

Explanation The value of the ADARUN statement's buffer pool length (LBP) parameter is invalid. The minimum value is 80,000.

PARM-ERROR 13

Explanation The value of the ADARUN statement's internal format pool (LFP) parameter is invalid. the minimum value is 6000.

PARM-ERROR 14

Explanation The value of the ADARUN statement's work pool length (LWP) parameter is invalid. The minimum value is 80,000.

PARM-ERROR 15

Explanation The value of the ADARUN statement's sort area length size (LS) parameter is invalid. The allowed range is from 19,968 to (LWP/2) -19,968.

PARM-ERROR 16

Explanation The value of the ADARUN statement's security pool length (LCP) parameter is invalid. The allowed range is from 2000 to 16,777,215.

PARM-ERROR 17

Explanation If you have Adabas Transaction Manager version 7.4 or earlier installed, the size of Work part 1 (the value of the ADARUN statement's LP parameter) is less than 200 blocks or greater than the Work data set size minus the space required for Work part 2 (the LWKP2 parameter), Work part 3 (minimum of 50 blocks), and, if used, Work part 4 (the LDTP parameter).

If you have Adabas Transaction Manager version 7.5 or later installed, the size of Work part 1 (the value of the ADARUN statement's LP parameter) is less than 200 blocks or greater than the Work data set size minus the space required for Work part 2 (the LWKP2 parameter), and Work part 3 (minimum of 50 blocks).

PARM-ERROR 18

Explanation Fewer than 50 blocks are available for Work part 3. Autorestart has been executed.

PARM-ERROR 19

Explanation The Work data set contains autorestart information for a different DBID or from a different Adabas version.

Action Provide the correct Work data set and restart the nucleus.

PARM-ERROR 20

Explanation GETMAIN below the 16MB line failed.

PARM-ERROR 21

Explanation The general control blocks (GCBs) contain an invalid device type. The GCBs may have been overwritten, damaged, or otherwise destroyed.

PARM-ERROR 22

Explanation An I/O error occurred when writing ASSO. The region is too small. The RABN that was to be written is printed.

PARM-ERROR 23

Explanation A nucleus entry already exists in the data integrity block (DIB) for one of the following reasons:

- An attempt was made to start a nucleus while another update nucleus was still active; or
- The previous nucleus session terminated abnormally but the "nucleus" DIB entry was not removed.

Action If a DIB entry remained after an abnormal termination, rerun the job with the ADARUN IGNDIB=YES parameter. If the FORCE=YES parameter had been applied, then the nucleus must be started with FORCE=YES and IGNDIB=YES. Here the DIB entry will only be removed once the ID Table initialization had been successful. Running with IGNDIB=YES alone will result in a PARM-ERROR 26.

PARM-ERROR 24

Explanation An I/O error occurred when reading ASSO. The RABN that was to be read is printed.

PARM-ERROR 25

Explanation The Adabas nucleus cannot be started because a conflicting utility DIB entry was found. Either a utility with exclusive database control or an ADASAV (SAVE FILE or SAVE database) job is running.

Action If an ADASAV SAVE FILE or ADASAV SAVE (database) ended abnormally, the nucleus can be restarted with the ADARUN IGNDIB=YES parameter; however, the save tape cannot be used for future RESTORE operations.

PARM-ERROR 26

Explanation Interregion communication could not be established.

Action This message should be preceded by message ADAM98. If the ADAM98 error reason is "DUPLICATE ID (LOCAL)" and a previous nucleus ended such that it was not able to clean up, you may wish to restart specifying FORCE=YES. Refer to ADAM98 message documentation for information about other possible errors.

If IGNDIB=YES was specified, then the nucleus must be started with FORCE=YES and IGNDIB=YES. Here the DIB entry will only be removed once the ID Table initialization had been successful. Running with FORCE=YES alone will result in a PARM-ERROR 23.

Note: Specifying FORCE=YES with the DBID of a currently active nucleus can disrupt operations on that nucleus. In addition, users of the old database whose ID is overwritten by the FORCE=YES option lose access to the database. Therefore, FORCE=YES should only be specified if absolutely necessary. For more information, refer to the FORCE parameter description in the Adabas Operations documentation.

PARM-ERROR 27

Explanation The ADARUN statement's PLOGRQ parameter is specified as or defaults to YES, FORCE, or SEL, but a protection log and related parameters have not been provided.

PARM-ERROR 28

Explanation The protection log (PLOG) data set(s) could not be opened, or the last dual or multiple PLOG block was not readable. This is probably due to incorrect PLOG data set definition, specification, or job control statements.

PARM-ERROR 29

Explanation Invalid command log (CLOG) device definition.

PARM-ERROR 30

Explanation FREEMAIN error.

PARM-ERROR 31

Explanation System autorestart error (see the nucleus response code).

PARM-ERROR 32

Explanation Error during buffer flush.

PARM-ERROR 33

Explanation Error during Work initialization.

PARM-ERROR 34

Explanation The nucleus is not allowed to start with READONLY=YES when an autorestart is pending.

PARM-ERROR 35

Explanation File control block (FCB) check failed. The FCB may have been overwritten or otherwise destroyed.

PARM-ERROR 36

Explanation Timer initialization failed, or operator communication could not be established.

PARM-ERROR 37

Explanation GETMAIN in common storage (CSA) failed; interregion communication could not be established. The specific reason is given in a detailed ADAM nn message.

PARM-ERROR 38

Explanation DIB overflow.

PARM-ERROR 39

Explanation Work pool is too small for the number of threads.

Action Increase the LWP parameter value to at least 25 kilobytes times the number of threads.

PARM-ERROR 40

Explanation Database version mismatch: the database is not version *version revision-level*.

Action Run the ADACNV utility to bring the database to the correct version.

PARM-ERROR 41

Explanation Parallel participant table (PPT) initialization error:

- an I/O error occurred reading or writing a PPT block (RABN); or
- a PPT length error occurred when a bad PPT block was encountered.

1	An error occurred reading the PPT block (RABN) to determine the PLOG entries from the last database session.
2	An error occurred trying to obtain the constant set for the PPT.
3	An error occurred in the PPT verification routine.
4	The PPT area is full and already contains 32 PPT entries that may be from cluster or non-cluster nuclei. To prevent losing data the nucleus is not permitted to start. Please make sure all relevant PLOG data sets are copied. An ADACHK PPTPRINT will help identify all the PLOG data sets.
5	An error occurred attempting to check for any active PPT blocks.
6	An error occurred while reading the PPT block prior to updating it.
7	A bad file name was detected in the PPT for the Work data set.
8	An error occurred trying to obtain the constant set for the PPT in order to log the Work data set in the PPT for the first time (no previous entry was found in the PPT for the Work data set).
9	A bad file name was detected in the PPT for the Work data set when logging the PPT entry for the first time (no previous entry was found for the Work data set).

10	An error occurred trying to obtain the constant set for the PPT entry in order to override a previous PPT entry.
11	A bad file name was found when attempting to log the PLOGR1 data set in the PPT.
12	A bad file length was found when attempting to compare the new PLOGR1 data set against the old one.
13	A bad file name was found when attempting to log the PLOGR2 data set in the PPT.
14	A bad file length was found when attempting to compare the new PLOGR2 data set against the old one.
15	An error occurred trying to obtain the constant set for the PPT prior to updating the PPT. Either a different PLOG data set was detected or no PLOGs are being used.
16	An error occurred when trying to obtain the constant set for the PPT prior to writing the PPT.
15	An error occurred when attempting to read the PPT block to ensure that no other nucleus is currently using the same PLOG.
18	An error was detected in the PLOG data set name when attempting to compare the current entry against other active entries in the cluster.
20	An internal error occurred attempting to initialize the PPT. Please contact your Adabas support representative supplying the DDPRINT and dump from the current session, a PPTPRINT, and the DDPRINT from the previous session.

PARM-ERROR 42

Explanation Error detected during system open:

- error writing PPT RABN; or
- a Work data set was already in use by another nucleus.

PARM-ERROR 43

Explanation Error detected during system open:

- either a PLOG was supplied that was different from the one used in the previous session, or no PLOG was supplied. The PLOG from the previous session has not yet been copied.
- PLOGRQ=FORCE was specified and either the PLOG from the previous session has not yet been copied or a UEX2 or UEX12 has not been specified.

PARM-ERROR 44

Explanation A noncluster nucleus attempted to start after a cluster failure; or, the first cluster nucleus is starting but there are already active blocks in the PPT. The nucleus is not allowed to start. Switching from single-nucleus mode to multi-nucleus cluster mode or from multi-nucleus cluster mode to single-nucleus mode is not allowed after an abnormal session termination.

PARM-ERROR 45

Explanation GETMAIN above the 16MB line failed; memory-related parameters probably too big.

PARM-ERROR 46

Explanation UQE could not be generated.

Action Increase NU parameter.

PARM-ERROR 47

Explanation An I/O error occurred when reading or writing to the Work data set for one of the following reasons:

- The GCB doesn't match the actual size of the Work data set
- ADARUN LP is larger than the Work data set,
- ADADEF NEWWORK was not run after allocating a new Work data set

The RABN that was to be read or written is printed.

PARM-ERROR 48

Explanation An error occurred during checkpoint generation:

- the takeover of checkpoints generated by offline utilities failed; or
- creation of the session start checkpoint failed.

PARM-ERROR 49

Explanation An I/O error occurred while reading or writing dual or multiple PLOGs. The RABN that was to be read or written is printed.

PARM-ERROR 50

Explanation Dual or multiple PLOG contains data from another database.

PARM-ERROR 51

Explanation Parameter conflict: READONLY=YES is not permitted with UTIONLY=YES.

PARM-ERROR 52

Explanation No dual or multiple PLOG available for protection logging. All PLOGs are due to be copied.

PARM-ERROR 53

Explanation At least one of the specified PLOG data sets is already in use by another nucleus in the cluster.

PARM-ERROR 54

Explanation IGNDIB=YES was specified but the DIB does not contain a conflicting nucleus or utility entry.

Action Remove the IGNDIB parameter.

PARM-ERROR 55

Explanation Error while attempting to lock or unlock a global resource. An ADAN54 message preceding this parameter error indicates the specific global resource that could not be locked/unlocked.

PARM-ERROR 56

Explanation A DIB entry was found with an inconsistent group name. The associated nucleus may still be active. The DIB entry can be removed only by a nucleus of the same type (single, cluster) and the same CLUGROUPNAME as the DIB entry's owner.

PARM-ERROR 57

Explanation DIB entry missing. Another cluster nucleus is already active on this database, but its DIB entry is not present.

PARM-ERROR 58

Explanation The Work block size is too small to store the maximum compressed data record permitted in this database according to MAXRECL definition.

Action Increase the Work block length.

PARM-ERROR 59

Explanation The Work block size is too small for the largest Associator block size present in this database.

PARM-ERROR 60

Explanation The PLOG block size is too small to store the maximum compressed data record permitted in this database according to MAXRECL definition.

PARM-ERROR 61

Explanation Important fields in the GCBs changed while this nucleus was starting. The nucleus is not able to handle this situation.

Action Restart the nucleus.

PARM-ERROR 62

Explanation CPU timer initialization failed.

PARM-ERROR 63

Explanation RRDF=YES is not allowed. Note that the RRDF/ENET option for maintaining shadow databases is currently unavailable for cluster nuclei.

PARM-ERROR 64

Explanation An attempt was made to start a version 7.2 or above nucleus without first formatting the protection logs (PLOGs). PLOGs must be formatted when converting to version 7.2 or above.

PARM-ERROR 65

Explanation The ADARUN statement's NSISN parameter value is greater than the allowed maximum of $(\text{Work block size} - 6) / 4$.

PARM-ERROR 66

Explanation The ADARUN statement's LU parameter specifies a value greater than the byte count implied by the NAB (number of attached buffers) parameter. The error was detected during open operation.

PARM-ERROR 67

Explanation Initialization failed for DTP=RM or DTP=TM either because of conflicts in the DTP (distributed transaction processing) ADARUN parameter settings (perhaps with the MODE, READONLY, or LOCAL parameter settings as well) or because of problems with the DDWORKR4/WORKR4 data set used in transaction management. For more information, read about the DTP ADARUN parameter in the *Adabas Operations Manual* and the DDWORKR4/WORKR4 data set in *Adabas DBA Tasks*.

Action Review the message(s) that precede this parameter error to determine the cause and resolution of the problem.

PARM-ERROR 68

Explanation If you have Adabas Transaction Manager version 7.4 or earlier installed, an invalid parameter was specified with DTP=TM:

- single user mode (MODE=SINGLE) is not allowed.
- LOCAL=YES is not allowed.
- READONLY=YES is not allowed.
- LDTP (Work part 4) specified with a nonzero value is not allowed.

If it is necessary for some reason to hold data about incomplete transactions in the TM, LDTP with a nonzero value can be specified but IGNDTP=YES must also be specified. The IGNDTP parameter is for emergency use only and should only be used in consultation with your Software AG technical support representative.

Caution: Whenever the data on Work part 4 is ignored, the integrity of the incomplete global transactions that are related to that data cannot be guaranteed.

If you have Adabas Transaction Manager version 7.5 or later installed, an invalid parameter was specified with DTP=TM:

- single user mode (MODE=SINGLE) is not allowed.
- LOCAL=YES is not allowed.
- READONLY=YES is not allowed.

PARM-ERROR 69

Explanation The value specified for the DTP parameter is invalid.
Action Specify "RM" or "TM" or "NO".

PARM-ERROR 70

Explanation Error during generation of predefined formats:

- Reading system-file FCB or FDT failed;
- Translating internal format failed; or
- Pool for system-internal formats is too small.

PARM-ERROR 71

Explanation If you have Adabas Transaction Manager version 7.4 or earlier installed, an invalid parameter was specified with NUCID:

- MODE=SINGLE is not allowed.
- READONLY=YES is not allowed.
- LFIOP must be nonzero.
- If protection logs are used, dual or multiple PLOGs must be specified.
- MXMSG must be between 1 and 32767.
- NUCID must not equal UBID.

If you have Adabas Transaction Manager version 7.5 or later installed, an invalid parameter was specified with NUCID:

- MODE=SINGLE is not allowed.
- READONLY=YES is not allowed.
- LFIOP must be nonzero.
- If protection logs are used, dual or multiple PLOGs must be specified.
- MXMSG must be between 1 and 32767.
- NUCID must not equal UBID.

PARM-ERROR 72

Explanation Initialization of recovery logging failed.

PARM-ERROR 73

Explanation Response code 75 (ADARSP075) or 77 (ADARSP077) was received because the checkpoint file is full. Checkpoints from offline utilities may have been lost.

Action Start the nucleus with UTIONLY=YES and reorder/increase the checkpoint file.

PARM-ERROR 74

Explanation The database will not start until the PLOG data sets have been copied or reformatted. Most likely, the database was restored and the PLOG data sets had not yet been copied. They still may be needed for the regenerate function.

Action If the contents of the PLOG data sets are needed for a possible future regenerate function, run ADARES PLCOPY to copy them off. If the PLOGs are not needed, reformat them using the ADAFRM PLOGFRM function. In either case, start the nucleus after freeing the PLOG data sets.

PARM-ERROR 75

Explanation The nucleus cannot run with the recovery log (RLOG) feature if it runs without PLOG or if PLOGRQ=SEL is specified. The protection log (PLOG) data set is not available; that is, PLOGRQ=SEL or PLOGRQ=NO is specified.

PARM-ERROR 76

Explanation The nucleus was started with DTP=TM or DTP=NO, but Work Part 4 contains data about in-doubt transactions.

Action Start the nucleus with DTP=RM.

PARM-ERROR 77

Explanation Machine clock (STCK) problem. The system was IPLed with the clock not set and running or set to an invalid date.

Action Correct the date (timestamp) and restart the nucleus.

PARM-ERROR 78

Explanation Work part 2 has become too small because Work part 4 contains two-phase commit data that must be retained.

PARM-ERROR 79

Explanation The ENET user exit 10 is missing.

PARM-ERROR 80

Explanation ADACLU initialization failed and the nucleus terminated. A preceding PLX*nnn* message from ADACLU provided more detailed information.

Action Refer to the explanation and action of the preceding PLX*nnn* message.

PARM-ERROR 81

Explanation A read-only (READONLY=YES) or single-user (MODE=SINGLE) nucleus cannot start if DTP=RM is specified.

PARM-ERROR 82

Explanation During session open, the system detected that a Delta Save logging (DLOG) area was installed but parameter DSF was not set to YES. DSF=YES must be specified to run with the Delta Save Facility.

Action Restart the nucleus with parameter DSF=YES.

Alternatively, restart the nucleus with parameter DSF=NO; the nucleus then removes the DLOG area and runs in non-Delta Save mode.

Caution: After switching to non-Delta Save mode, it is not longer possible to perform delta save operations.

PARM-ERROR 83

Explanation Initialization of the Delta Save Facility failed. A preceding Delta Save operator message indicates the cause of the failure.

Action Check messages from ADADSF.

PARM-ERROR 84

Explanation The DSF logging area could not be removed. Another Adabas cluster nucleus is already running with Delta Save Facility active.

Action Start the nucleus with DSF=YES.

PARM-ERROR 85

- Explanation** The previous nucleus session terminated with Work overflow. The nucleus has no free space on Work part 1 for protection information that will be produced during session autorestart.
- Action** In a cluster environment (Adabas Cluster Services or Parallel Services), start a different cluster nucleus (possibly a new one) with sufficient free space on Work part 1. In a non-cluster environment (base Adabas), restore and regenerate the database.

PARM-ERROR 86

- Explanation** VOL-SER table could not be established.

PARM-ERROR 87

- Explanation** Entire Conversion Services (ECS) initialization failed.

PARM-ERROR 88

- Explanation** A database that uses Universal Encoding Support (UES) needs a version 7 or above Adabas router. If the database uses UES features, it cannot work with an Adabas router (ADASVC) version 6.2 or below.
- Action** Install a version 7.1 or above router (ADASVC).

PARM-ERROR 90

- Explanation** Invalid ADATCP configuration or UES=NO. Running with TCPIP=YES requires universal encoding support.
- Action** Check and correct, if necessary, the TCPURL parameter. Install UES and specify UES=YES.

PARM-ERROR 91

- Explanation** Adabas cluster initialization failed. Either the program was not running authorized or the GETMAIN failed.
- Action** Ensure that the program is APF-authorized. Review the space requirements for your system. If you are unable to determine the problem, contact your Software AG technical support representative.

PARM-ERROR 92

Explanation During session open, an attempt to join the Adabas cluster communication group failed. This error initializing the Adabas cluster messaging service is preceded by other messages explaining the specific error.

PARM-ERROR 93

Explanation Connect to lock structure failed.

Action Review the lock structure definition requirements. If you are unable to determine the problem, contact your Software AG technical support representative.

PARM-ERROR 94

Explanation Connect to cache structure failed.

Action Review the cache structure definition requirements. If you are unable to determine the problem, contact your Software AG technical support representative.

PARM-ERROR 95

Explanation Communication with other active Adabas cluster nuclei failed.

Action Review the requirements for communication between cluster nuclei running on the same operating system image and between operating system images running members of the cluster. If you are unable to determine the problem, contact your Software AG technical support representative.

PARM-ERROR 96

Explanation Inconsistent structure name. Another Adabas cluster nucleus is already running with a different CLUCACHENAME or CLULOCKNAME parameter.

Action Ensure that all nuclei in a sysplex cluster use the same coupling facility cache and lock structure names.

PARM-ERROR 97

Explanation Incompatible global parameters. Another Adabas cluster nucleus is already running with incompatible global parameters that cannot be modified online.

Action Reset nonmodifiable global ADARUN parameters the same for all cluster nuclei. You may be required to stop nuclei, change the parameter settings, and restart.

PARM-ERROR 98

Explanation Locking/unlocking an Adabas cluster resource failed.
Action Contact your Software AG technical support representative.

PARM-ERROR 99

Explanation Internal error.
Action Contact your Software AG technical support representative.

PARM-ERROR 100

Explanation There are more than 31 nuclei in an Adabas Parallel Services cluster; this is not allowed.
Action Reconfigure your Adabas Parallel Services cluster so that you have 31 or fewer participating Adabas nuclei.

PARM-ERROR 101

Explanation Invalid parameters specified with CLOGMRG=YES; LOGGING=YES is required; dual or multiple CLOGs are required.
Action Specify the correct ADARUN parameters and restart the session.

PARM-ERROR 102

Explanation A cluster nucleus was started after abnormal termination with a different WORK data set. The PPT indicates that the previously used WORK data set still contains data, but this Cluster Service or Parallel Service nucleus was started with a different WORK data set.
Action Restart the cluster nucleus with the previously used WORK data set. Change the WORK data set only after normal termination.

PARM-ERROR 103

Explanation Incompatible usage of dual PLOG data sets.

If the first active nucleus uses PLOG data sets, all subsequent nuclei *must* use PLOG data sets. If the first active nucleus does not use PLOG data sets, all subsequent nuclei *must not* use PLOG data sets.

PARM-ERROR 104

Explanation Incompatible usage of UEX2 or UEX12.

If the first active nucleus uses either UEX2 or UEX12, all subsequent nuclei *must* use either UEX2 or UEX12. If the first active nucleus does not use UEX2 or UEX12, all subsequent nuclei must *not* use UEX2 or UEX12.

PARM-ERROR 105

Explanation Improper configuration of Global Resource Serialization (GRS). A resource lock acquired by this nucleus was ineffective against a peer nucleus.

Action Contact your system programmer to ensure that GRS is configured in a way that GRS resource locks are mutually effective against one another on all systems on which you intend to run Cluster Services nuclei.

PARM-ERROR 106

Explanation When LOCAL=YES is specified, all cluster nuclei for a database must start on the same system.

Action If LOCAL=YES is the intended parameter setting, start all cluster nuclei for the database on the same system. Otherwise, change the parameter setting to LOCAL=NO.

PARM-ERROR 107 Replication initialization error

Explanation An error occurred during initialization of replication. Refer to the messages preceding Parm-Error 107 to determine what action to take.

Action Correct the condition specified in the message(s) displayed before Parm-Error 107 and restart initialization of replication.

If the replication definitions are stored on the Replicator system file and a change must be made to the Event Replicator Server definitions, complete the following steps:

1. Temporarily set the ADARUN parameter RPLPARMS to NONE.
2. Start the Event Replicator Server.
3. Make the related changes to the replication definitions in the Replicator system file.
4. Shut down the Event Replicator Server.
5. Change the ADARUN parameter RPLPARMS back to its original value.
6. Start the Event Replicator Server.

PARM-ERROR 109

Explanation The Adabas nucleus tried to load a valid license module (load module ADALIC), but errors occurred. Other error messages providing more information about the error accompany this nucleus startup error

Action Verify that you have received a valid Adabas license (via the installation media) and that it was installed correctly, according to the Adabas database installation steps specific to your operating environment. If problems persist, contact your Software AG technical support representative for assistance.

PARM-ERROR 110

Explanation An error occurred when the Adabas nucleus called a hyperdescriptor exit for initialization.

Action Investigate the response code and subcode to determine the reason for the error.

PARM-ERROR 111

Explanation A parameter value for cluster nuclei is invalid:

- MXCANCEL must be between 15 and 2,147,483,647 seconds.
- MXCANCELWARN must be zero (0) or between 4 and (MXCANCEL-1) seconds.
- MXMSG must be between 15 and 32,767 seconds.
- MXMSGWARN must be zero (0) or between 4 and (MXMSG-1) seconds.
- MXSTATUS must be zero (0) or between 15 and 21,474,836 seconds.
- MXWTOR must be zero (0) or between 15 and 64,800 seconds.

Action Correct the invalid parameter value to one of the valid values listed above.

PARM-ERROR 113

Explanation GETMAIN above the 2G bar failed. The memory-related parameters are probably too big.

Action Verify that the requested 64-bit space is available to the nucleus.

PARM-ERROR 115

Explanation An error occurred initializing ADASMF

Action Review other messages accompanying or preceding this error to determine what happened and what action should be taken.

PARM-ERROR 116

Explanation Invalid parameters were specified with the LOGWARN ADARUN parameter. Either ADARUN parameter UEX2 or UEX12 must be supplied when the LOGWARN parameter has been specified.

Action Remove the LOGWARN parameter or specify a UEX2 or UEX12 ADARUN parameter with it.

PARM-ERROR 117

Explanation Invalid parameters were specified for the ASSOSPACEWARN or DATASPACEWARN ADARUN parameter.

Action Correct the specification for ASSOSPACEWARN or DATASPACEWARN ADARUN parameter.

PARM-ERROR 118

Explanation An invalid autoincrease parameter was specified. The AUTOINCASSOTHRESHOLD or AUTOINCDATATHRESHOLD were not set to "0" or in the range from 50-100.

Action Correct the invalid parameter value and try again.

PARM-ERROR 119

Explanation Autoincrease ADARUN parameters are only permitted in z/OS environments. An attempt to use one or more AUTOINC* parameters was made in a non-z/OS environment.

Action Remove the AUTOINC* parameters from the ADARUN input or set the values to zero.

PARM-ERROR 120

Explanation An invalid autoincrease AUTOINCxxxxTOTAL parameter was specified. The specification for the AUTOINCASSOTOTAL or AUTOINCDATATOTAL parameter is smaller than the currently allocated size for the ASSO or DATA data set or exceeds 2,147,483,647 blocks or 16,777,215 blocks (3-byte RABNs).

Action Correct the invalid parameter value and try again.

PARM-ERROR 121

Explanation An invalid parameter value was specified for AUTOINCASSOSIZE or AUTOINCDATASIZE. The value was specified in blocks, but the size specified was smaller than the number of blocks per track for the device.

The value must be either zero (0) or a number not smaller than the device track size. In z/OS environments, the minimum extent size is one track.

Action Correct the invalid parameter value and try again. Specify a size that is either zero (to disable autoincrease for the component) or the minimum number of blocks for one full track.

PARM-ERROR 123

Explanation UPDATECONTROL / INDEXUPDATE parameter conflict:
UPDATECONTROL=NODELAY is permitted only if INDEXUPDATE=ADVANCED is specified.

Action Specify either INDEXUPDATE=ADVANCED or UPDATECONTROL=DELAY (or omit the UPDATECONTROL parameter) and start the nucleus again.

PARM-ERROR 124

Explanation The software level of this nucleus is not compatible with that of active cluster nuclei. See the preceding ADAX6C messages for details.

Action Check the Release Notes to confirm this is an incompatible combination. For more information contact your Software AG technical support representative.

PARM-ERROR 127

Explanation Error in cluster-wide Work access. A preceding message indicates the nature of the error.

PARM-ERROR 128 Invalid parameter specified with ZIIP=YES: – {(list of possible reasons)}

Explanation An Adabas component or feature is being used or has been specified that is not supported by Adabas for zIIP (AZPAD). The message shows a list of components or features that are not compatible with ZIIP=YES.

Action Either remove the ZIIP parameter or specify ZIIP=NO, or remove or deactivate the specified component or feature that is not supported with ZIIP=YES.

PARM-ERROR 129 zIIP initialization failed

Explanation The initialization of the zIIP-related services of Adabas failed. A preceding ADAZ nn message provides more information about the failure.

Action Consult the documentation for the ADAZ nn message preceding this error message.

10 Adabas Response Codes

After each Adabas command is processed, a response code is returned in bytes 11 and 12 of the ACB or in the ACBX. Some response codes also return a subcode in the rightmost two bytes of the ACB's Additions 2 field (offset 45-48) or in the ACBX's Error Subcode (ACBXERRC) field (offset 115-116). This section describes those response codes and subcodes.



Note: Proprietary functions of Adabas may also return response codes and subcodes, some of which are not described here. Refer to the documentation for those functions for more information.

Response code 0 indicates that the Adabas command was processed successfully; any other response code is returned as a result of an error during command processing.

All Adabas commands resulting in a response code other than 0 (ADARSP000), 1 (ADARSP001), and 145 (ADARSP145) restore all Adabas control block fields except the response code field (see the Adabas Command Reference documentation) to the contents the fields held at the beginning of command execution.

For internal errors, contact your Adabas technical support representative.

Response 0

Origin	Mainframe and open systems
Explanation	The command was executed successfully.

Response 1

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
1	An online SAVE operation cannot be executed without the nucleus' PLOG.
2	The selected record is not allowed.
3	S2 command did not have enough space.
4	S2/S9 internal program error.
5	System was not in save status at the end of an online ADASAV.

Note: When one of the subcodes 2-4 is present, the cause could be an Sx command using security-by-value that found at least one ISN.

Open Systems

An ISN list could not be sorted as a result of an excessive number of resulting ISNs, or because during a non-descriptor search a value larger than the corresponding field length in the FDT was found, or because the ISN quantity returned does not correspond with the actual number of records found.

For an S9 command, this response indicates that there is no space available for additional temporary working space. For an S2 command, this response is only a warning and the S2 becomes an S1.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Increase the ADARUN LS parameter value.

Open Systems

Provide sufficient disk space for temporary working space or adapt the FDT to the real field length.

Response 2**Origin**

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

This response code can only occur with a BT, ET or RI command. The BT, ET or RI command executes successfully. One of the following has occurred, depending on the subcode:

Subcode	Meaning
1	Adabas attempted to hold an ISN already being held by another user.
2	The number of ISNs as specified in the ISN buffer was too large compared to the ISN buffer length (ET or BT command with the M option).
4	ISN is not on hold during multifetch ET/BT. ET/BT has successfully executed the ISNs so far released. The remaining ISNs are still on hold.
5	An RI command with ISN=0 could not release from hold status all records held by the user, as requested, because one or more records had been updated earlier in the same transaction. Updated records cannot be released from hold status prior to transaction end. All records that had not been updated have been released from hold status.

Open Systems

The required function has not been executed completely. For an OP command with command option 2 = E or for an RE command, the specified record buffer length was shorter than the length of the ET data read. The record buffer has been truncated.

For an A1//N1/N2 command, a descriptor value with the TR option is larger than 1144 bytes. In this case, only the first 1144 bytes are stored in the index. Search operations for truncated values may be inexact since only the first 1144 bytes are evaluated. The first 2 bytes of the Additions 2 field contain the number of descriptor values truncated, the third and fourth bytes contain the field name of the descriptor value that is truncated.

For an S1/S2/S4/S9 command, the resulting ISN list may not represent the exact result: this is because the search values and the values in the database were truncated after 1144 bytes during the search operation of an S1/S2/S4 command and during the sort operation of an S2/S9 command.

Subcode 5 is set if a RI command with ISN=0 could not release from hold status all records held by the user, as requested, because one or more records had been updated earlier in the same transaction. Updated records cannot be released from hold status prior to transaction end. All records that had not been updated have been released from hold status.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Open Systems

For an OP or RE command, increase the record buffer length or ignore the warning.

For an S1/S2/S4/S9 command, either perform a post-selection using the complete field values, perform your own sort operation using the complete field values, or ignore the warning.

Response 3

Origin

Mainframe and open systems

Explanation

One of the following has occurred:

- An end-of-file or end-of-list condition was detected.
- A program tried to read or change a multicient file's record using either a blank or incorrect-length owner ID, or an owner ID that is not allowed for the record.

The following are some possible subcodes:

Subcode	Meaning
1	An end-of-file or end-of-list condition was detected (L3/L6 on a non-expanded file).
4	End of LOB value reached. An attempt was made to read a LOB value segment that begins after the end of the value. This response code/subcode is given to an L1/L4 command with Command Option 2 set to L if the ISN Lower Limit value is greater than or equal to the length of the LOB value being read.
66	A program tried to read or change a multicient file's record using either a blank or incorrect-length owner ID, or an owner ID that is not allowed for the record.
249	<p>Adabas Vista has determined that no data is available to satisfy this command due to one of the following reasons:</p> <ul style="list-style-type: none"> ■ A partitioned file end-of-file or end-of-list condition was detected. ■ None of the partitions were available/online and all of them have the file parameter <code>Critical</code> set to NO. <p><i>Action:</i> No action is required.</p>

Response 4

Origin	Mainframe systems
Explanation	The internal Adabas TRS storage directory is full.
Action	Free some of the active queries.

Response 7

Origin	Mainframe systems only
Explanation	A complex search command was rejected because it was estimated that it would exceed the maximum search time TLSCMD.

Response 8

Origin	Mainframe systems only
Explanation	The current user's command was interrupted to prevent a Work overflow because of a pending backout operation.
Action	The value specified for the LP parameter might have to be increased.

Response 9

Origin	Mainframe and open systems
Explanation	The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

A subcode indicating the specific cause and action for this response code appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACB's Error Subcode (ACBXERRC) field. The following are the subcodes and their meanings:

Subcode	Meaning
1	The user was backed out because the hold queue was full. <i>Action:</i> Set the number of hold queue elements (ADARUN NH parameter) higher, or tune the application to issue more frequent ET commands.
2	The transaction time limit (TT) has been exceeded, and the transaction was backed out. <i>Action:</i> Correct the cause of the timeout, then restart the transaction.
3	The transaction was backed out and one of the following occurred: <ul style="list-style-type: none"> ■ The transaction non-activity time limit (TNAE, TNAX, or TNAA) has been exceeded. ■ The user was stopped by the STOPF or STOPI operator, or an Adabas Online System command.

Subcode	Meaning
	<ul style="list-style-type: none"> ■ A security violation response code has been returned for an ET-logic user. Information about response codes for security violations is provided in the Adabas Security documentation. ■ When a new user issues an OP cmd with the same user ID (in ADD1) as an earlier user did and the earlier user was inactive for more than 60 seconds, the new user can, by issuing a second OP cmd again (the first OP cmd will get response code 9, subcode 64), take over the user ID of the earlier user. When the earlier user becomes active again, this subcode can be received. ■ A potential dead lock situation was detected and in that moment was signaled as response code 145 subcode 9. The following Adabas call then gets response code 9 subcode 3. <p><i>Action:</i> Correct the cause of the timeout, then restart the transaction.</p>
15	<p>The user was backed out because a pending Work area overflow occurred during the user's transaction. Adabas decides to back out a transaction when its start on Work is approximately 1/4th of ADARUN parameter LP away from the current position on Work.</p> <p><i>Action:</i> Either reduce the transaction length (number of updates) or duration (time between transaction start and end) to lessen the data protection area requirement, or increase the data protection area on Work (ADARUN parameter LP).</p>
17	<p>At the end of an online recovery process that was initiated after the failure of a peer nucleus in an Adabas cluster, the nucleus was unable to reacquire the ETID specified by the user in the Additions 1 field of the OP command.</p> <p><i>Action:</i> (In the application program:) Redo the OP command with the ETID specified in the Additions 1 field to reacquire the user ID. Contact your Software AG technical support representative.</p>
18	<p>The user's active transaction was interrupted and backed out because a peer nucleus in an Adabas cluster terminated abnormally.</p> <p><i>Action:</i> (In the application program:) Rerun the transaction.</p>
19	<p>The user's active command was interrupted and stopped because a peer nucleus in an Adabas cluster terminated abnormally. If the interrupted command was using a command ID (CID), the command ID is deleted.</p> <p><i>Action:</i> (In the application program:) Clean up and reacquire the current context pertaining to Adabas command IDs; rerun the transaction.</p>
20	<p>The Adabas cluster nucleus assigned to the user terminated while the user had an open transaction. The transaction has been or will be backed out.</p> <p><i>Action:</i> (In the application program:) If the user was defined with a user ID (ETID) in the Additions 1 field of the OP command, redo the OP command</p>

Subcode	Meaning
	to reacquire the ETID; clean up and reacquire the current context pertaining to Adabas command IDs; rerun the transaction.
21	The user's active command was waiting for an ISN in hold status when the user was backed out and closed due to a timeout or a STOP command.
22	The user's active command was waiting for free space in the work pool when the user was backed out and closed due to a timeout or a STOP command.
23	The user's command was routed to a different cluster nucleus than the one used by previous commands. The user's open transaction has been backed out. It is also possible that the user had already been timed out earlier. <i>Action:</i> Restart the transaction and any open read sequences.
24	The user's command was routed to a different cluster nucleus than the one used by previous commands. The user had owned EXU or EXF control over one or more files or had started the Adabas session with an OP command with R-option. As a consequence of creating a new session for the user with the new nucleus, the EXU/EXF control or file list specified in the OP command are no longer in effect. <i>Action:</i> Restart the Adabas session with a new OP command.
25	The user's command was routed to a different cluster nucleus than the one used by previous commands. The user had started the Adabas session with an OP command with ETID. As a consequence of creating a new session for the user with the new nucleus, the user is no longer associated with that ETID. <i>Action:</i> Restart the Adabas session with a new OP command.
26	The user's command was routed to a different cluster nucleus than the one used by previous commands. Some cluster nucleus terminated abnormally while the new nucleus was creating a new session for the user. <i>Action:</i> Restart the Adabas session with a new OP command.
62	An OP (open) command was issued without a user/ET ID, which is required for this type of application or environment. <i>Action:</i> Correct the program to specify a user/ET ID, and rerun the program.
63	An OP command was given for an ET user not in ET status. The user is backed out with an Adabas-generated BT command, and the operation is closed. <i>Action:</i> Repeat the OP call.
64	An OP command was issued with an 8-byte ET ID that already exists.

Subcode	Meaning
66	<p>An Adabas session with OPENRQ=YES was active and the user issued an Adabas command without having issued an OP command.</p> <p><i>Action:</i> Ensure that all users issue an OP command as the first Adabas command.</p>
67	<p>Insufficient Work part 1 space for open command with ETID definition when trying to read the user profile.</p>
68	<p>The user queue element has been deleted. Most likely the command was thrown back due to ISN contention or space shortage. The space shortage is normally workpool space; if this is the case, the LWP parameter setting should be increased.</p>
73	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session had an externally-controlled transaction, the outcome of which was “in doubt”. ATM forcibly resolved the “in doubt” transaction. There is a possibility that ATM’s resolution of the transaction might be inconsistent with the intended outcome.</p> <p>Check that the outcome of the session’s Adabas changes, in its previous transaction, was consistent with its changes to non-Adabas resources.</p> <p>Check the external transaction coordinator for reasons why the original transaction might have been left in the “in doubt” state. If the external coordinator indicates that the transaction was completed, and if the relevant system logs give no indication of the cause of the problem, contact your Software AG support representative.</p>
74	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client’s database session has lost its ETID. If a transaction was in progress, ATM attempted to back it out from all affected databases and release all held records.</p> <p>Issue a new OP command to the database.</p>
75	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>Either a commit operation involving an external transaction coordinator failed, or resynchronization with an external transaction coordinator caused the transaction to be backed out. In the first case, ATM attempted to back out the transaction.</p> <p>For the first case, check the external transaction coordinator for the reason. Check for error messages from ATM transaction managers or the ATM client proxy of the failing job.</p>
76	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred while an ATM transaction manager was attempting to rebuild the transaction hierarchy of a client session that has migrated from</p>

Subcode	Meaning
	<p>another ATM transaction manager's domain as a result of dynamic transaction routing. ATM attempted to back out the transaction.</p> <p>Check the status of the transaction using Online Services. Check for error messages from ATM transaction manager or the ATM client proxy of the failing user.</p>
77	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>This message indicates that the client session had an open transaction and has been migrated from one node to another within a cluster (Sysplex), but ATM could not handle the transaction safely because no Migrated Transaction Record (MTR) file had been defined. The transaction was therefore backed out.</p> <p>Define and create an MTR file, and restart the ATM transaction managers and clustered application environments in the COR group.</p>
78	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>It was not possible to commit the client session's transaction because of a pending ET syncpoint on a target database. This could be because of a concurrent online save operation, database termination, or a SYNCC operator command. Backout of the incomplete transaction was attempted.</p> <p>Restart the transaction when the pending ET syncpoint has been completed.</p>
79	<p>Used by Adabas System Coordinator to signal the (optional) terminal timeout. Refer to the description of Generate RSP009/79 in the Adabas System Coordinator Parameters documentation for more information.</p>
80	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session was not at ET status in the target database. Backout of the incomplete transaction was attempted.</p> <p>Restart the transaction.</p>
81	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>A memory shortage in the ATM transaction manager's address space caused the current global transaction to be backed out.</p> <p>Increase the amount of memory available to the ATM transaction manager, restart it, then restart the transaction.</p>
82	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>A memory shortage occurred in the ATM transaction manager's address space, and ATM attempted to back out the current global transaction.</p> <p>Increase the amount of memory available to the ATM transaction manager, restart it, then restart the transaction.</p>

Subcode	Meaning
83	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred during a commit or backout operation for a global transaction. ATM attempted to back the transaction out.</p> <p>If the cause of the error is not apparent from console messages, contact your Software AG technical support representative.</p>
84	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>ATM reported conflicting use of an ETID. For an RE command, this subcode can be returned if the client is known to ATM but has no ETID.</p> <p>The client should issue a CL command to each open database; then re-open.</p>
85	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The global transaction time limit (TMGTT) has been exceeded, and an attempt has been made to back out the global transaction.</p> <p>Correct the cause of the timeout, then restart the transaction.</p>
86	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The global transaction time limit (TMGTT) has been exceeded, and the global transaction has been backed out.</p> <p>Correct the cause of the timeout, then restart the transaction.</p>
90	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The ATM client proxy detected either an inconsistency between its view of the client session's status and the ATM transaction manager's view, or that the transaction manager had restarted. It attempted to back out on all target databases.</p> <p>Close the client's sessions and start them again.</p>
91	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>Transactions on a target database were being quiesced, or an administrator issued a "stop" request for the session's transaction via ATM Online Services or operator command, or there was a pending ET syncpoint on the database. Backout of the incomplete transaction was attempted.</p> <p>Restart the transaction when all required target databases are available.</p>
92	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>Transactions on a target database were being quiesced, or an administrator issued a stop request for the user via ATM Online Services or operator command, or there was a pending ET syncpoint on the database. The incomplete transaction was backed out.</p> <p>Restart the transaction when all required target databases are available.</p>

Subcode	Meaning
93	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred while ATM was attempting either to start a new global transaction or to bring a new database into a transaction. The client proxy backed out changes from all databases.</p> <p>The next command issued returns details of the error that caused the backout. Check the meaning of the response code and act accordingly.</p>
94	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred while ATM was attempting either to start a new global transaction or to bring a new database into a transaction. The client proxy attempted to back out changes from all databases.</p> <p>The next command issued returns details of the error that caused the backout. Check the meaning of the response code and act accordingly.</p>
95	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session's transaction was controlled by an external transaction coordinator, which reported that the transaction has been backed out.</p> <p>Restart the transaction.</p>
96	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session's transaction was controlled by an external transaction coordinator, which reported "backed out, outcome pending" for the transaction. This means that backout has begun for the transaction, and will be completed when all the resource managers involved in it are able to comply with the backout request.</p> <p>Restart the transaction.</p>
97	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The CICS Resource Manager Interface is in use, and the ATM client proxy detected that the client session's Task Interface Element (TIE) was being used by another session.</p> <p>This can occur if all of the following are true:</p> <ul style="list-style-type: none"> ■ Natural is being used, in such a way that two Adabas sessions are maintained for each client; ■ The client control Transaction Model is set to MESSAGE; ■ Natural parameters are set such that Natural might not generate OP commands for all database sessions. <p>You can make sure that Natural generates OP commands by using a non-blank ETID, or by means of Natural's DBOPEN parameter.</p>

Subcode	Meaning
	<p>The condition can also occur if all of the following are true:</p> <ul style="list-style-type: none"> ■ Natural is being used, in such a way that two Adabas sessions are maintained for each client; ■ The Adabas System Coordinator has timed out Natural's "system" session. <p>In this case, a new Natural LOGON might clear the condition. Otherwise terminate the session and start a new session.</p> <p>If the error persists, contact your Software AG support representative.</p>
98	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session was executing in serial mode, and requested that changes be committed. Some of the changes were committed, and some were backed out.</p> <p>Examine the results of the transaction. If necessary, correct the result by manual intervention.</p>
99	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session incurred a security response code; ATM backed out the user's changes.</p> <p>If security permissions are not adequate, correct them and rerun the transaction.</p>
249	<p>In Adabas Vista, all transaction activity by the client has been backed out for one of the following reasons:</p> <ul style="list-style-type: none"> ■ The client is using multiple (different) ETIDs which have collided against a particular database. <p><i>Action:</i> Review the client's use of ETIDs with respect to the current translation rules and/or partitioned files.</p>

Open Systems

This response is caused by one of the following:

- The last user transaction has been backed out by Adabas (ET logic users only) or an exclusive control user (non-ET user) or an access-only user exceeded the Non-Activity Time Limit;
- The user session was abnormally terminated by the operator and the user issued a command;
- The protection log area (= WORK container) was too small and an internal BT was executed.

The ADDITIONS 2 field in the control block contains additional information:

First two bytes	Third and fourth bytes	Explanation
0	TT	Transaction timeout
1	TN	Non-activity timeout
2	ST	STOP user
3	LP	WORK overflow
5	SE	Security
6	DL	Deadlock
8	OP	Open transaction
9	OR	Open required
10	RR	Replication recording failed One of the internal Adabas commands issued for replication recording got an unexpected response code, for example 77. This response code is included in the control block in the field ACBXSUBR (only if you use the ACBX interface) and displayed in an RPLIRSP message in the nucleus log.

	First two bytes	Third+ fourth bytes
	-----	-----
Transaction timeout :	0	TT
Non-activity timeout:	1	TN
STOP user :	2	ST
WORK overflow :	3	LP
Security :	5	SE
Deadlock :	6	DL
Open transaction :	8	OP
Open required :	9	OR

The information in the first two bytes is represented as an integer, and the third and fourth bytes are alphanumeric.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

User actions are described in the subcode list in the explanation.

Open Systems

Check the appropriate reason. If the Adabas nucleus was started without the option OPEN_REQUIRED, and the reason for response 9 was a non-activity timeout or a

STOP user, users who started their sessions with an OP command must re-issue their OP command under the following circumstances:

- if they set a User ID
- if they specified restricted file lists
- if they had user-specific timeout values
- if they were not ET users.

If too many transactions are backed out because of a Work overflow, the size of the Work container should be increased.

Response 10

Origin Mainframe systems only
Explanation Too many occurrences for a periodic group.

Response 16

Origin Open systems only
Explanation An error occurred in an MC call during subcommand processing. The error code and additional information can be found in the control block of the subcommand. The first 2 bytes of the Additions 2 field contain the number of the subcommand in binary format. The third and fourth bytes of the Additions 2 field contain the offset of the subcommand's control block in the MC call's record buffer in binary format. All subcommands before the one that failed were executed.
Action Correct the failed subcommand if necessary and re-issue the subcommands beginning with the one that had failed.

Response 17

Origin Mainframe and open systems
Explanation A subcode indicating the specific cause and action for this response code appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field. The following are the subcodes and their meanings:

Subcode	Meaning
1	The program tried to access system file 1 or 2, and no OP command was issued. <i>Action:</i> Restructure the program to begin with an OP command.
2	The program tried to access system file 1 or 2, and the user is not authorized. <i>Action:</i> Change the program to avoid the access.

Subcode	Meaning
4	<p>One of the following occurred:</p> <ul style="list-style-type: none"> ■ The specified file number is invalid. The file number might be equal to "0" or greater than the maximum allowed. ■ When running with ADARUN DTP=RM or DTP=TM, an attempt was made by a non-Adabas Transaction Manager user to access/update an Adabas Transaction Manager system file.
5	<p>The file is either not loaded, or has been locked by another user for privileged use.</p> <p>On mainframe systems, for ADAORD and ADAINV utility operations, the write phase has started and use of the file is now blocked for the type of operation you requested.</p>
6	<p>On mainframe systems, an E1 (delete record) command was given without specifying a valid file number.</p> <p>On open systems, the file to be created already exists.</p>
7	The program tried to perform an LF command on system file 1 or 2.
8	<p>On mainframe systems, the program tried to access a file that was not listed in the file list of an open (OP) executed with the R option.</p> <p>On open systems, an ET user with a restricted file list and ACC = file number attempted to issue a UPD command, or a user with a restricted file list attempted to touch a file that is not in the file list</p>
9	<p>The file that the program attempted to access is completely locked. This may occur because of a LOCKU operation or because the maximum number of logical file extents that can fit into the FCB has been reached.</p> <p><i>Action:</i> If the file was locked using a LOCKU operation and keeping the lock in place is no longer warranted, use the UNLOCKU operation to free the lock. If the file is locked because the maximum number of file extents has been reached, use ADAORD to reorder the file into fewer extents, then use UNLOCKU to free the lock. Note that in the latter case, if you DELETE or REFRESH the file, Adabas also frees the lock.</p>
10	The program attempted to access a file which is locked with exclusive EXU status.
11	An LF command (read FDT) was run on a file that is not loaded; neither the FCB nor the FDT exists.
12	File has been locked with LOCKF.
13	A file is password-protected and the password was specified, but the corresponding security file is missing (not loaded).
14	A command was issued against a LOB file. Commands involving LB fields should be directed against the associated base file, not the LOB file.
15	A file is being loaded so its information is temporarily unavailable.

Subcode	Meaning
16	<p>On mainframe systems, an attempt was made to perform an update (e.g. A1, E1, N1/2) against a file loaded with the attribute RPLUPDATEONLY=YES or READONLY=YES.</p> <p>On open systems, the file was locked by ADAOPR.</p>
17	<p>An attempt was made to perform an update (e.g. A1, E1, N1/2) against a file loaded with the attribute READONLY=YES.</p>
18	<p>File has been locked with ALOCKF.</p>
21	<p>On mainframe systems, there was not enough space for encoding elements (ECSE).</p> <p>On open systems, a two-byte file number was used against a lower version database that does not support large file numbers.</p>
22	<p>On mainframe systems, the required ECS objects needed for conversion between user and system data representation could not be loaded.</p> <p>On open systems, the file control block (FCB) is invalid (corrupted).</p>
23	<p>ECS object could not be located. The following objects must be available in the encoding objects library: File Alpha, File Wide EDD, User Alpha, User Wide EDD, and the PTOs for the combinations between file/user alpha/wide encodings.</p> <p><i>Action:</i> Check that the required EDD and PTO objects are available.</p>
24	<p>ECS function get_attribute() failed.</p> <p><i>Action:</i> The function's return code is logged with the nucleus message ADAN7A.</p>
25	<p>One of the following occurred: - A required encoding attribute was missing in an ECS object (encoding type, class, and flags) - The default space character length was > 4 - Default space table allocation failed - If DBCS-only plane exists, wide space character was undefined, or the length > 4, or wide space table allocation failed</p>
29	<p>An Adabas Review communication error has occurred. Contact your Software AG support representative.</p>
52	<p>A non-Adabas target was called.</p>
99	<p>The file's FTD is corrupted.</p> <p><i>Action:</i> To resolve the problem, repair the file by running a restore/regenerate from a consistent state.</p>
249 (0x00F9)	<p>While attempting to satisfy a partitioned file command, Adabas Vista detected the unavailability of an FDT – this is invalid for one of the following reasons:</p> <ul style="list-style-type: none"> ■ None of the partitions were available/online and at least one of them has the file parameter <code>Critical</code> set to YES.

Subcode	Meaning
	<ul style="list-style-type: none"> ■ None of the partitions were available/online and all of them have the file parameter <code>Critical</code> set to <code>NO</code> and the command can not be satisfied with a "no data" response such as RSP003. <p>An error occurred when Adabas Vista (open systems) tried to access a file that was not listed in the file list of an <code>OP</code> command executed with the <code>R</code> option.</p> <p><i>Action:</i> Ensure at least one of the file partitions is available/online or review the program logic.</p>

Response 18**Origin**

Mainframe and open systems.

Explanation

Invalid file number usage. The file number was modified between successive L2/L5 calls or between successive L x and S x calls.

Action

Correct the file number.

Response 19**Origin**

Mainframe and open systems.

Explanation

An attempt was made to update a file which is either already open for read access or can only be opened for read access. The leftmost two bytes of ACB's Additions 2 field or the ACBX's File Number (ACBXFNR) field may contain the file number.

Action

Do not attempt to update a file with read-only access.

Response 20**Origin**

Mainframe and open systems.

Explanation

One of the following invalid values was used for a command ID value:

- Binary zeros
- Blanks
- The high-order byte contains the hexadecimal value "FF", but there is no automatic command ID generation
- The three high-order bytes contain the ASCII string "SYN".

Action

Correct the command ID and avoid using any of these invalid command ID values.

Response 21

Origin

Mainframe and open systems

Explanation

An invalid command ID value was detected. One of the following explanations or subcodes is provided:

Subcode	Meaning
1	The command ID value was not found in the sequential command table. This is not an initial call and there was no previous initial call, or the command ID was deleted or lost in a timeout or recovery action.
3	The command ID value specified for the L3/L6 command was assigned to another Lx command.
5	The command ID value specified for the L9 command was assigned to another Lx command.
6	Unexpected last file in chain.
7	The command ID value specified was assigned to a different file.
8	The command ID value specified for the Sx command is for a sorted ISN list; the ISN list was not in ISN sequence.
9	An application running with PREFETCH=YES or PREFETCH=OLD attempted to dynamically reverse the read direction of an L3/L6/L9 command. This is not allowed.
10	The master file number is not the same as it was in the initial call for this command ID.
12	ACB(X)Add1 altered after initial call.
13	S9 ISN list already sorted
14	Not a chained file as expected.
15	Not an L2 sequence as expected.
16	Chained file transformed ISNs not permitted.
17	CID does not exist for chained file.
18	File was not master file as expected.
19	Special L3 started on a valid file number and subsequent L3 issued with the API option.
20	Chained file ISNs not transformed.
21	Special L3 system area not as expected. System area changed.
22	The command ID value specified was assigned to a different file and FBL is not equal to zero.
23	Incorrect CID for sort function.
249 (0x00F9)	An invalid command ID value was detected by Adabas Vista (open systems): <ul style="list-style-type: none"> ■ The command ID value specified with the N option of an L1/L4 command was not found.

Subcode	Meaning
	<ul style="list-style-type: none"> ■ The command ID value specified with the N option of an L1 / L4 command does not correspond to an ISN list. ■ One or both of the ISN lists referred to in the ADDITIONS 1 field of an S8 command do not exist. <p><i>Action:</i> Review the program logic.</p>

Action Correct the command ID.

Response 22

Origin

Mainframe and open systems

Explanation

The command or command option is invalid. A subcode indicating the specific cause and action for this response code appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field.

When using the LNCSTUB module on mainframe systems, this response code may indicate problems with the initial call (IC) to the Adabas CICS command-level link component. If the Adabas control block shows a command code of "IC", the link routine being used may not be at the proper release level or may not be the command-level version.

The following are the subcodes and their meanings:

Subcode	Meaning
1	The nucleus detected an invalid command code.
2	This command cannot be issued by an ACC (access only) user; and update command cannot be issued by an access-only user.
3	This command cannot be performed on a read-only nucleus; an update command cannot be issued for a read-only database session.
4	This privileged command was issued without a previous OP (open) command.
5	The command is not valid for a nonprivileged user.
6	The command was rejected by user exit 11.
7	Incorrect command options were specified for a privileged command.
8	The command is invalid for an ET user in preliminary ET status. First complete the transaction using Adabas Transaction Manager.
9	The current user is not authorized to issue an ET/BT command.
10	The C2 command is no longer permitted.
11	The C3 command can only be issued by EXU users.
12	The L1/4 command with the option "F" is not valid for expanded files.
13	The call issued is not permitted when the database is in a suspend state.

Subcode	Meaning
14	Invalid privileged command.
15	An L1/L4 command specified the multifetch option ("M" or "O") was not combined with either the "I" or "N" option.
16	The user does not have "privileged" command authorization.
17	A refresh file (E1 command with ISN zero) is not permitted during online save database or file.
18	Applications using the ADALNK X'48' call logic receive this response when the logic has been suppressed.
19	On mainframe systems, a special utility command was issued for an obsolete subfunction. On open systems, an ET or BT with command option "S" was issued without subtransactions being enabled for the current Adabas user session by specifying command option "S" in the OP command.
21	One of the following occurred: <ul style="list-style-type: none"> ■ A BT command was issued by a non-ET logic user. ■ An ET command was issued for a distributed transaction managed by Adabas Transaction Manager; ET commands are invalid for a distributed transaction managed by Adabas Transaction Manager.
22	The current transaction has already been heuristically terminated or the command is not allowed within an MC sequence.
23	One of the following occurred: <ul style="list-style-type: none"> ■ The last MC subcommand is not ET. ■ A BT command was issued for a distributed transaction managed by Adabas Transaction Manager; BT commands are invalid for a distributed transaction managed by Adabas Transaction Manager.
24	One of the following occurred: <ul style="list-style-type: none"> ■ An ET or CL command with user data is not allowed for read-only access to a database. ■ CL is invalid because the user has a transaction in progress that is managed by Adabas Transaction Manager.
25	A command was sent from an Event Replicator Server to an Adabas nucleus, but the Adabas nucleus is not running with ADARUN REPLICATION=YES.
26	An attempt was made by an Adabas nucleus to connect to an Event Replicator Server when the target of the message is actually another Adabas nucleus, not an Event Replicator Server.
28	A replicated utility may not be executed for a replicated file when the Adabas nucleus is running in single-user mode.

Subcode	Meaning
29	An error occurred during a connection attempt by an Event Replicator Server database. Ensure that you are trying to connect to another Adabas nucleus and not an Event Replicator Server and try again.
31	API file delete not permitted: not API loaded.
32	An attempt was made to update a replicated file in single-user-mode. Replicated files can be updated only in multi-mode; replication is not supported in single-mode. However, a nucleus with replication support can be started in single-mode for maintenance purposes.
33	A shared hold status request (with command option 3 set to "C", "Q", or "S") is not allowed for a command with prefetch (command option 1 set to "P"). On open systems, the command option "S" is not allowed for an S9 command with a non-blank Additions 4 field.
34	On open systems, the command was rejected by user exit 11.
35	The command cannot be executed with the nucleus parameter NT=1.
36	The descending option "D" is not allowed for the command.
37	On mainframe systems, a shared hold status request (command option 3 is set to "C", "Q", or "S") is not allowed for a non-ET user. On open systems, a shared hold status request (command option 3 is set to 'C', 'Q', or 'S') is not allowed for a non-ET user.
38	A shared hold status request for a sequential read command (command option 3 is set to "Q") is not allowed for an L4 command without the N-option, nor is it allowed for an S4 command without a command ID (CID) or with an ISN buffer length other than 4 bytes.
39	A shared hold status request for a sequential read command (command option 3 is set to "Q") is not allowed for a command with a multifetch (command option 1 is set to "M" or "O"). Also, a shared hold status request (with command option 3 set to "C", "Q", or "S") is not allowed for a read command with prefetch (command option 1 is set to "P").
40	A keep-in-shared-hold-status request (with command option 3 set to "H") is not allowed for an ET or BT command with multifetch or prefetch (command option 1 is set to "M" or "P").
41	A request to read the next portion of a LOB value (command option 2 is set to "L") is not allowed for an L1/L4 command with multifetch (command option 1 is set to "M" or "O") or prefetch (command option 1 is set to "P").
42	On open systems, for an A1 command with command option 2 = "T", the current time is still the same as the value of the field with SY=TIME in the database.
48	An obsolete internal request to shut down Adabas, supposedly coming from Entire Net-Work, has been issued and rejected.
50	The Router (LCC) detected an invalid command code. This may also arise when a new ACBX-type call is presented to a back-level router.

Subcode	Meaning
51	A client call with the ADARUN parameter PREFETCH=OLD has multiple APLX buffers or the contents of APLX+4(chained APLX) is non-zero. To resolve this, use the ADARUN parameter setting PREFETCH=YES.
52	A non-Adabas target was called.
53	Invalid file specified for an Adabas Online System function.
54	The user was stopped with STOPUR or STOPSUR.
55	The command is returned because the command queue timeout time specified by the DELCQ operator command or the AUTOCQTIME ADARUN parameter was reached or exceeded for the command.
1005	The command code is invalid.
1006	The ACBX is invalid (not first buffer).
1007	The ABD is invalid.
1008	The ABD type is invalid.
1009	More than one search buffer specified.
1010	More than one value buffer specified.
1011	More than one ISN buffer specified.
1012	The number of search and value buffers do not match.
1013	The number of format and record buffers do not match.
1015	A streaming logic error occurred.

Action Correct the command code or command option or the previous OP command, and rerun the program.

Response 23

Origin Mainframe and open systems

Explanation An invalid starting ISN was specified for an L2/L5 command sequence:

- The ISN was not assigned to a record in the file; or
- The ISN was greater than the MAXISN in effect for the file.

Open Systems

On open systems the following subcodes may occur:

Subcode	Meaning
249 (0x00F9)	An invalid ISN was detected by Adabas Vista (open systems). The starting ISN specified for an L2/L5 command sequence is not consistent with the definitions for the partitioned file. <i>Action:</i> Review the program logic.

Action Correct the ISN.

Response 24

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

For an S9 command:

- The ISN list in the ISN buffer was already sorted; or
- The ISN list in the ISN buffer contained an invalid ISN; or
- The "D" option was specified when trying to sort an ISN list by ISN.

Open Systems

An ISN is equal to "0" or is greater than or equal to the first free ISN found in the ISN buffer. The Additions 2 field contains the value of the invalid ISN in 4 byte binary format.

Action Correct the ISN buffer.

Response 25

Origin Mainframe and open systems

Explanation The ISN specified in ISN lower limit field for an S1/S4 or S2/S9 command was not found.

Open Systems

On open systems the following subcodes may occur:

Subcode	Meaning
249 (0x00F9)	An invalid ISN was detected by Adabas Vista (open systems). The ISN specified in the ISN Lower Limit field for an S2 command when retrieving a group of ISNs from a saved ISN list was not found. <i>Action:</i> Review the program logic.

Action Correct the ISN lower limit.

Response 26

Origin Mainframe and open systems

Explanation An invalid ISN buffer length for an S9 command was detected. The number of ISNs to be sorted as provided in ISN quantity is equal to "0".

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
2	An S9 command with an ISN buffer contains ISNs that are higher than the TOP-ISN of the file.

Action Correct the ISN buffer length.

Response 27

Origin Mainframe systems only

Explanation Sufficient work space was not available to accommodate the combined sizes of the search and value buffers as indicated in the search buffer length and value buffer length fields.

Subcode	Meaning
1	Sufficient work space was not available to generate the format translation.

Response 28

Origin Mainframe and open systems

Explanation The first two bytes of the Additions 1 field contained an invalid descriptor for an L3/L6 or S2/S9 command.

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
1	The field was not a descriptor.
2	The use of the descriptor is not supported (for example, phonetic descriptors or the descriptor is contained within a periodic group).
3	The descriptor was changed between successive calls.
4	There is a mismatch of the descriptor names in the Additions 1 field and the search buffer.
5	An initial L3 or L6 call contains no trailing blanks in the Additions 1 field.
7	ADAINV is inverting the file and using the descriptor.
8	The descriptor is missing in the file index.
9	An internal error occurred during SB interpretation.

Action Correct the Additions 1 field.

Response 29

Origin Mainframe and open systems

Explanation In an L3 or L6 command, a value repositioning was attempted (bytes 3-8 of the Additions 1 field contain spaces) and the Command Option 2 field did not contain the value "A", "D", or "V". The command ID is released.

Action Correct the Additions 1 or Command Option 2 field.

Response 34

Origin Mainframe systems only

Explanation An invalid command option has been detected.

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
1	An invalid command option has been specified in one of the command option fields.
2	The R option has been specified for the C5 command, but replication is not active.
9	A record buffer must be specified for this command but is missing (not specified of length zero).

Action Either remove the invalid command option or replace it with a valid option.

Response 35

Origin Mainframe systems only

Explanation The user/DBA attempted to perform a function for a noncluster Adabas nucleus that is available only for an Adabas cluster database.

Action Either perform the function against a cluster database or change the function.

Response 39

Origin Mainframe systems only

Explanation A logically deleted descriptor was used as a search criterion or was specified in the first two bytes of the Additions 1 field for an L3, L6, L9, S2, or S9 command.

Action Remove the use of the logically deleted descriptor and inform your database administrator about the problem.

Response 40

Origin Mainframe and open systems

Explanation A syntax error was detected in the format buffer.

Mainframe Systems

On mainframe systems, one of the following subcodes may be used:

Subcode	Meaning
1	Syntax error in format buffer; possible premature end of buffer segment.
2	Syntax error in the format buffer -- bad first or second character of field name or missing "/".
3	Text literal has no ending quote or is too long (more than 255 characters).
4	Text literal is empty.
5	Expected delimiter missing.
6	Conditional format criterion has no closing parentheses ")".
7	The conditional format criterion is empty.
8	Invalid field name, format, or search operator.
9	One of the following occurred: <ul style="list-style-type: none"> ■ An invalid edit mask number (greater than 15) was specified. ■ A syntax error in the conditional format criterion was found. ■ Multiple format buffer segments are specified with conditional format criterion.
10	Invalid character following field name specification.
11	Invalid index specification for MU field in PE group.

Subcode	Meaning
12	Expected number missing or too large ($\geq 2^{31}$).
13	Syntax error in LOB segment specification.
14	Syntax error in L element specification.
15	Syntax error in D element specification (daylight savings time indicator).
16	Invalid Date-Time edit mask specification.
17	MU/PE index range specification invalid for LOB segment notation.

On mainframe systems, the following information is returned in the Additions 2 field of the control block:

- The leftmost two bytes contain the two characters being inspected when the error was detected.
- The rightmost two bytes contain the subcode.

Open Systems

One of the following format buffer errors occurred.

- The terminating period was missing;
- The first position contains a period, this only applies to N1 or N2 commands;
- Length and/or format specified with a range definition;
- An invalid element was detected;
- A field segment notation was not correct: it must be specified either as (*byte-number*, *length*) or as (*byte-number*, *length*, *length-2*), where *byte-number* must be either "*" or a decimal number, and *length* and *length-2* are decimal numbers. These numbers must be less than 2,147,483,648;
- A field segment notation was specified for a range of MU fields or for a range of fields within a periodic group.

On open systems, the following information is returned in the Additions 2 field of the control block:

- The leftmost two bytes contain the number of the byte (in binary format) relative to the beginning of the format buffer where the error was detected.
- The rightmost two bytes contain the name of the field being processed when the error was detected.

Action

Correct the format buffer.

Response 41

Origin

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One or more specification errors exist in the format buffer. When possible, the short name of the field for which the error occurred is stored at offset 2 of the ACB's Additions 2 field or in the ACBX's Error Character Field (ACBXERRB).

The following specification errors may have been made:

Note: A collation descriptor (COLDE) can only be specified in the format buffer of the L9 command and only when the decode option has been specified in the user exit. The value returned is not the index value but the original field value.

Subcode	Meaning
1	Spacing element <i>nX</i> with <i>n=0</i> or <i>n>255</i> not allowed.
2	An invalid sequence of format buffer elements was specified.
3	Miscellaneous types of specification errors were found in the format buffer.
4	A field name was undefined or not elementary.
5	Format without fields.
6	A group field cannot be specified if the group contains a LOB (LB) field.
7	A field name is undefined.
8	Invalid use of <i>f1dD</i> , <i>f1dL</i> , <i>f1d,*</i> or <i>E(date-time-mask)</i> notation.
9	Elementary field in PE group: 1-N notation not permitted with LOB (LB) fields or <i>f1dD</i> notations.
10	A LOB (LB) field, <i>f1dL</i> (length indicator notation) or <i>f1d,*</i> (asterisk notation) are not permitted with an L9 command.
11	A length indicator (<i>f1dL</i>) or asterisk notation (<i>f1d,*</i>) are only permitted for LA and LOB (LB) fields.
12	LA or LOB (LB) fields are not permitted with 1-N notation, <i>f1da-f1db</i> (field series) notation or old MU syntax.
13	LA or LOB (LB) fields are not permitted with <i>f1dC,*</i> (count indicator) or <i>f1da-f1db,*</i> (field series notation).
14	Asterisk notation and length indicator notation combinations (<i>f1dL,*</i>) are not permitted.
15	SQL significance indicator and asterisk notation combinations (<i>f1dS,*</i>) are not permitted.
16	Length indicator (<i>f1dL</i>), asterisk notation (<i>f1d,*</i>) or daylight savings time indicator notation (<i>f1dD</i>) are not permitted for a group field.

Subcode	Meaning
17	Daylight savings time indicator notation (<i>f1dD</i>) cannot be combined with asterisk notation (<i>f1d,*</i>) or a length indicator notation (<i>f1dL</i>).
18	Daylight savings time indicator notation (<i>f1dD</i>) is only permitted for fields defined with the TZ option.
20	Daylight savings time indicator notation (<i>f1dD</i>) is not permitted with count indicator (<i>f1dC</i>) or field series notation (<i>f1da-f1db</i>).
21	Old MU syntax is not permitted with daylight savings time indicator notation (<i>f1dD</i>).
22	An invalid length or format has been specified with daylight savings time indicator notation (<i>f1dD</i>); if specified it must be 2,F.
23	An invalid length or format has been specified with length indicator notation (<i>f1dL</i>); if specified it must have length 4 and format B.
24	A phonetic, collation, or hyperdescriptor was specified.
25	Date-time edit mask notation (<i>E(date-time-mask)</i>) is not permitted with daylight saving time indicator notation (<i>f1dD</i>), asterisk notation (<i>f1d,*</i>), or length indicator notation (<i>f1dL</i>).
26	Date-time edit mask (<i>E(date-time-mask)</i>) notation requires format P, U, F, or B.
27	Date-time edit mask (<i>E(date-time-mask)</i>) notation and edit mask notation (E0-E15) are not permitted together.
28	Date-time edit mask (<i>E(date-time-mask)</i>) notation and count indicator notation(<i>f1dC</i>) are not permitted together.
30	Date-time edit mask (<i>E(date-time-mask)</i>) notation is only permitted for a field defined with a date-time edit mask.
31	Daylight savings time indicator notation (<i>f1dD</i>), length indicator notation (<i>f1dL</i>), and asterisk notation (<i>f1d,*</i>) are not permitted together with LOB segment notation.
32	LOB segment notation is permitted only for LOB (LB) fields.
33	More than one LOB segment with *-position not permitted.
34	Length/format override not permitted for LOB segment notation.
35	Invalid byte number and length parameters in LOB segment notation.
36	Invalid length-2 parameter in LOB segment notation; must be equal to length parameter.
37	Invalid syntax with daylight saving time indicator in format buffer.

Open Systems

An error was detected in the format buffer:

- The field name specified is reserved for edit mask usage;
- An index was equal to 0;

- A length specified or taken from the FDT standard length is greater than the maximum length of the required format;
- *nnnX* was specified with *nnn* greater than 253;
- A literal with more than 253 characters was specified;
- A subdescriptor, superdescriptor, phonetic descriptor, hyperdescriptor or a collation descriptor was specified;
- A field specified was not present in the file;
- A periodic group name appears without an index;
- A length and/or format was used with a group notation;
- A field in a periodic group was specified without an index;
- A range notation with a group name or a multiple-value field as the first or last element was specified;
- A reference was made to the count of a multiple-value field contained in a periodic group, and no index was included to indicate the periodic group occurrence for which the count was to be returned;
- A collation descriptor with the option HE was specified for an L9 command.
- A count specification was made for a field which was neither a multiple-value field nor was contained within a periodic group;
- A count for a non-multiple value field within a periodic group was specified;
- A length and/or format specification was used with a periodic group notation;
- A (regular or periodic) group containing a multiple-value field was specified;
- Invalid index usage;
- A descending index range was specified;
- A double index was used for a non-periodic field;
- A multiple-value field with an index specification and a multiple-value field without an index specification were used;
- A value cannot be converted to the required format (READ command) or converted to the FDT standard format (UPDATE command);
- The S element was applied to a field that does not have the NC option;
- A field with the NC option was used more than once together with its S element;
- The add option is not compatible with the format/length;
- The specification of a character set was invalid;
- A field was specified with an edit mask not allowed for the field;
- A field segment notation '(byte-number,length)' or '(byte-number,length,length-2)' was not correct: byte-number + length must be less than or equal to the maximum value length + 1, and length-2 must be equal to length. The maximum value for LB fields is 2,147,483,643, for LA fields 16381, and for other values 253 bytes;
- Segment notation is only allowed for values with the format 'A'.

The following information is returned in the Additions 2 field of the control block:

- The leftmost two bytes contain the number of the byte (in binary format) relative to the beginning of the format buffer where the error was detected.
- The rightmost two bytes contain the name of the field being processed when the error was detected.

Action Correct the specification error and reissue the command or job. For more information about syntax rules for multiple field and periodic group indexing, refer to the Adabas Command Reference documentation.

Response 42

Origin Mainframe systems only

Explanation A space problem occurred. The following are the subcodes and their meanings:

Subcode	Meaning
1	The Work pool was too small to store a user format. <i>Action:</i> Increase the LWP specification and retry .
2	The internal format buffer was too small to store a user format (translated into internal structure). <i>Action:</i> Increase LFP specification and retry.

Action See the actions described in the subcodes.

Response 43

Origin Mainframe and open systems

Explanation In an L9 command, the descriptor specified in the format buffer did not agree with the descriptor specified in the search buffer.

Action Correct the format buffer or the search buffer.

Response 44

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following format buffer errors occurred (subcodes are shown in the leftmost column):

Subcode	Meaning
1	The specified format is not allowed for an update operation. A possible reason for this is the presence of a conditional format buffer with an update operation.
2	The L9 command's format buffer format is not allowed for other commands.
3	The specified format is not allowed for an update operation. A possible reason for this is the presence of a conditional format buffer with an update operation.
4	The L9 command's format buffer format is not allowed for other commands.
5	Format used for L9 can only contain field and an optional daylight savings time indicator (<i>f1dD</i>).
6	Fixed point format must have length 2, 4, or 8.
7	Conditional format and more than one format buffer was specified.
8	The current Adabas call provides a different number of format buffers than the format reference by CID.
9	Number of format buffer segments (ABDs) is zero.
10	AAS, AA, AA is invalid.
12	L option specified but the format has no LOB segment with *-position.

Open Systems

One of the following situations occurred:

Subcode	Meaning
1	<ul style="list-style-type: none"> ■ The format buffer is invalid for use with an UPDATE command (A1), ADD command (N1/N2): <ul style="list-style-type: none"> ■ Format buffer contains overlapping fields, e.g., GL1-3, GL2-4; ■ Format buffer contains an 1-N element, e.g., GL1-N; ■ There is not a 1:1 relation between an L element and the subsequent corresponding element with '*' length; ■ A READ command uses a format buffer from the format pool, which was previously used by update or add command, and which contains an invalid conversion.
12	L option is specified but the format has no LOB section with *-position.
13	The format buffer for an A1 commands with command option 2='T' did not contain a last-update-timestamp system generated field.

Note: Subcodes associated with response 44 are stored in the first two bytes of the Additions 2 field (ACB) and in the error subcode field (ACBX).

Action

Correct the format buffer or use a different read or update command.

Response 45**Origin** Mainframe and open systems**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.**Mainframe Systems**

The internal format buffer space has been exceeded. Either the LWP parameter setting is too small or the internal format buffer requires more than 2 G.

Open Systems

Multiple field or periodic group overflowed when using the N suffix in the format buffer for update.

The following information is returned in the Additions 2 field of the control block:

- The first two bytes will contain the number of the byte (in binary format) relative to the beginning of the record where the error was detected;
- The third and fourth bytes will contain the name of the field being processed when the error was detected.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.**Mainframe Systems**

Increase the size of the LWP parameter and try again. If the problem persists, contact your Software AG technical support representative for assistance.

Open Systems

Because the multiple field or periodic group reached its absolute limit, the application must be redesigned.

Response 46**Origin** Mainframe and open systems**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Subcode	Meaning
1	Too many TBLES elements for this user.
2	The maximum value for the NQCID parameter was exceeded (the number of TBI and/or TBQ elements is greater than NQCID).

Open Systems

Mismatch of format buffer usage for the supplied command ID.

- A command ID of global ID format buffer has been found in the format pool and has a different file number to the file supplied by the caller;
- The file number was changed in subsequent Adabas calls with the same normal or global command ID.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Adjust the size of the NQCID parameter and try again.

Open Systems

Check the command IDs used in the call and try again.

Response 47

Origin

Mainframe and open systems

Explanation

The maximum value for the NISNHQ parameter was exceeded. The following subcodes appearing in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field provide more detailed information.

Subcode	Meaning
1	<p>An attempt was made to put too many ISNs in hold. The maximum number of ISNs that can be put in hold is specified by the NISNHQ parameter and can be overridden via the Additions-4 field (bytes 3-4) of the user's OP command and via the user profile.</p> <p><i>Action:</i> Increase the value of the NISNHQ parameter or the maximum number of ISNs that the user can put in hold specified in the Additions-4 field (bytes 3-4) of the OP command or in the user profile. Alternatively, modify the application program to store fewer ISNs in hold at the same time.</p>
2	The hold queue was full. If another user has put the maximum number of ISNs in hold, that other user is backed out and will next receive response

Subcode	Meaning
	code 9, subcode 1. The user who is given the response code 47 is not backed out; this user should issue an ET or BT command to release the ISNs from hold. <i>Action:</i> Increase the value of the NH parameter. Alternatively, modify the application program to store fewer ISNs in hold at the same time.

Action Increase the value of the NISNHQ parameter by modifying its ADARUN parameter value in the nucleus startup file, or (on open systems) using ADAOPR.

Response 48

Origin Mainframe and open systems

Explanation An error occurred during the processing of a command such as OP or N1. Refer to the hexadecimal subcode that appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field.

Subcode	Meaning
	File(s) not available at open time. This is the default message displayed with this response code if another subcode is not provided.
1	A specified file is locked against the requested use.
2	A specified file is currently in conflicting use.
3	A utility cannot start because an online save operation is in progress.
4	A specified file is already locked or being used by an EXU/EXF or utility user. Use operator command DLOCKF to display file locks, DNFV to display a summary of the current file usage.
5	A utility requiring exclusive database control cannot start because an online save operation is in progress.
6	A utility that requires exclusive database control cannot start because the user queue is not empty.
7	The requested file lock cannot be granted because the file is being used. Use operator command DNFV to display a summary of the current file usage, DFILES to display current users of the file.
8	The user ID specified in the open (OP) command is already in use by another user.
9	An EXU/EXF/UTI lock was requested in the open command, but the file is currently in the file list of a user in UPD/EXU/EXF/UTI status.
10	An EXF/UTI lock was requested in the open command, but the file is currently in the file list of a user in ACC status.
11	A nonprivileged user issued an open (OP) command to a nucleus in UTIONLY (utilities only) status.
13	Online file save attempting to run on an advance-locked file.

Subcode	Meaning
14	UPD/ACC open attempted against advance-locked file.
15	A file requested for an online utility (Adabas Online System or ADADBS) or an E1 program refresh is currently being used.
16	ACODE or WCODE was specified in the record buffer on the command but the nucleus was not activated with UES support.
17	A specified file is locked against the requested use and is advance-locked. The data in the file is not accessible. This can happen if a utility aborts or an autorestart fails.
18	<p>On mainframe systems, this means that a second command was issued by a user who is participating in a two-phase commit (preliminary ET completed; final ET outstanding) or whose transaction has been heuristically terminated.</p> <p>On open systems, this means that the index of the specified file is not accessible. This can happen if a utility aborts or if the index has been disabled by ADAREC REGENERATE or an autorestart.</p>
19	The file number is zero or is greater than the maximum number of files allowed for the database (based on the MAXFILES parameter setting when the database was defined using the ADADEF utility).
20	A regenerate/backout with exclusive database control is rejected because there are in-doubt transactions or heuristically terminated transactions on Work part 4.
21	File is locked for utility usage.
22	An attempt was made to release an advance-lock, but the lock was not set.
23	An advance-lock operation was attempted for a file that has not been loaded.
24	An advance-lock operation was attempted for a file that is already advance-locked.
25	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session has an open global transaction that could not be backed out because it is under the control of an external transaction coordinator and its status is "in doubt".</p> <p>Depending on the transaction coordinator, you may have a choice of actions:</p> <ul style="list-style-type: none"> ■ Wait for the external transaction coordinator to complete or back out the existing transaction. ■ Use the coordinator's facilities to force completion or removal of the transaction. ■ Restart the transaction coordinator to cause resynchronization of in-doubt transactions. ■ Use ATM Online Services to force backout of the local, Adabas-related part of the global transaction.

Subcode	Meaning
	Caution: Using ATM Online Services to force backout of the local, Adabas-related part of the global transaction could result in loss of transaction integrity.
26 - 30	Reserved for Adabas Transaction Manager. These subcodes are given only when Adabas Transaction Manager is in use. Please read the Adabas Transaction Manager documentation for more information.
31	File locked for normal usage
32	A file is in use by an exclusive update (EXU) user. An update request from another user is not permitted.
33	A file is locked for exclusive file control (EXF) or utility update (UTI) usage. The request from a user with a different type is not permitted.
34	An advance-lock operation was performed on a read-only nucleus.
35	An advance-lock operation was performed during an online save.
36	Nucleus in REGENERATE/NOAUTOBACKOUT state.
257 - 260	Reserved for use by Event Replicator for Adabas on open systems.

On open systems, the corresponding file number is returned in the first two bytes of the Additions 2 field in binary format except for value 8 in the third and fourth byte. The value 0 means the whole database.

Action

The following user actions are possible:

- Wait for the other user or utility to finish, then retry the command.
- Make the file available for all users (on open systems, if value 16 occurred in bytes 3 and 4).
- Restore or unlock the file (on open systems, if value 17 occurred in bytes 3 and 4).
- Rebuild the file's index (on open systems, if value 18 occurred in bytes 3 and 4).
- On open systems, if the value in bytes 3 and 4 of the Additions 2 field is 8, and the nucleus was started with the OPEN_REQUIRED option, you can reissue the OP command immediately. This will cause the other user with the same user ID to be stopped, unless that user is currently active.
- On open systems, if a utility receives a response 48 because non-utility users are still active, you can lock the file with ADAOPR LOCK. This ADAOPR command stops all non-utility users from accessing the file and allows only utility users to access the file until it is unlocked again.

On mainframe systems, if a utility receives a response 48 because non-utility users are still active, you can lock the file with ADADBS MODFCB FILEREADONLY. The FILEREADONLY command stops all non-utility users from accessing the file and allows only utility users to access the file until it is unlocked again.

Response 49

Origin Mainframe and open systems

Explanation The compressed record was too long. It exceeds the maximum permitted compressed record length for the file.

On open systems, the first two bytes of the Additions 2 field contain the length of the compressed record in binary format.

On mainframe systems, the following subcodes may be indicated:

Note: This response code always means that the compressed record is too long and there are duplicate meanings for subcodes but the subcode can help your Software AG technical support representative analyze where in the code we are giving the response. This can be useful for debugging purposes. Please always provide the subcode when communicating about this response code with your Software AG technical support representative.

Subcode	Meaning
	File(s) not available at open time. This is the default message displayed with this response code if another subcode is not provided.
1	Multiple-value (MU) field.
2	Periodic (PE) group field.
3	MU field.
4	PE group.
5	PE group level.
6	Remaining fields.
7	Record too long for protection logging (internal error).
8	A compressed record exceeds the permitted length. The error was detected when updating a multiple field.
9	Exceeded segment length maximum.
10	Long alpha or wide field.
11	New compressed record too long
12	Old version MU update.
13	The MU field was defined with an index
14	An MU update caused the compressed record to become too long.
15	An MU update caused the compressed record to become too long.
16	An MU update caused the compressed record to become too long.
17	MU update, MU count > 1
18	An update to an LA field caused the compressed record to become too long.
19	LOB value too long. An attempt was made to update a LOB value segment that ends after the maximum allowed length of LOB value. This response code/subcode combination is produced as a result of an L1/L4 command

Subcode	Meaning
	with Command Option 2 set to "L" but with the ISN Lower Limit value greater than or equal to the length of the LOB value being read.
20	Compressed Data Storage record too long. A LOB update attempted to make a long LOB value (greater than 253 bytes) short (less than or equal to 253 bytes), but the base record was too long to embed the short LOB value. This condition was detected when the LOB value was being read from the LOB file.
21	Compressed Data Storage record too long. A LOB update attempted to make a long LOB value (greater than 253 bytes) short (less than or equal to 253 bytes), but the base record was too long to embed the short LOB value. This condition was detected when an attempt was made to insert the short LOB value into the base record.
90	Segment too long
96	Compressed record too long
99	Exceeded segment length maximum

Action On open systems, add a new DATA extent with sufficient block size (block size \geq compressed record size + 8). Alternatively you can start the nucleus with `OPTIONS=AUTO_EXPAND`; then the Adabas nucleus automatically creates a new DATA extent with sufficient block size.

Response 50

Origin Mainframe and open systems

Explanation A syntax error in the record buffer was detected during processing of an OP command, an invalid character set was specified, an invalid time zone was specified, or an invalid file number (zero or greater than maxfiles) was specified.

On open systems, the first two bytes of the Additions 2 field contain the number of bytes (in binary format) relative to the beginning of the record buffer where the error was detected. If a time zone problem occurs, the two right-most bytes of the Additions 2 field in the ACB will contain a subcode; in an ACBX, the Error Subcode field will contain the subcode.

Subcode	Meaning
31	Time zone not found in ADAZON directory. The specified time zone was not found in the ADAZON directory. Verify the time zone was specified correctly. If it was, contact your Software AG technical support representative for assistance.
32	Time zone pool full. No more time zone information could be loaded. Increase the size of the ADARUN LTZ parameter and restart the nucleus.
33	Open error on DD:TZINFO(MEMBER). Contact your Software AG technical support representative for assistance.

Subcode	Meaning
34	I/O error on DD:TZINFO(MEMBER). Contact your Software AG technical support representative for assistance.
35	Invalid data in TZ file. Contact your Software AG technical support representative for assistance.
36	Invalid transition time in TZ file. Contact your Software AG technical support representative for assistance.

Action Correct the record buffer and try again.

Response 51

Origin Mainframe and open systems

Explanation An error in the record buffer was detected during processing of an OP command.

One of the keywords EXU, UPD, ACC or WCHARSET is duplicated.

On open systems, the following information is returned in the Additions 2 field of the control block:

- the first two bytes contain the number of bytes (in binary format) relative to the beginning of the record buffer where the error was detected;
- the third and fourth bytes contain the open mode that failed (ACC =1, UPD = 2, EXU = 4, WCHARSET = 128)

Action Correct the record buffer and try again.

Response 52

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following errors occurred while processing the record, value, or search buffer. In an ACB, the rightmost two bytes of the Additions 2 field contain the subcode; for subcodes 1-5, the leftmost two bytes contain the Adabas name of the field where the error occurred. In an ACBX, the subcode is stored in the Error Subcode (ACBXERRC) field; for subcodes 1-5, the Adabas field name where the error occurred is stored in the Error Character Field (ACBXERRB).

Subcode	Meaning
1	Invalid packed or unpacked decimal value in record buffer.
2	Invalid length for variable-length field specified in record buffer.
3	Invalid null value or no value at all provided for field with NN option.
4	Invalid value for S element in record buffer.
5	Invalid value for S element in value buffer.
6	Encoding a collation descriptor value failed: the collation descriptor exit issued a return code.
7	Decoding a collation descriptor value failed: the collation descriptor exit issued a return code.
99	An invalid field length was specified.

Open Systems

- The value of a G format field was not in floating point format;
- The value of a P format field was not in packed decimal format;
- The value of a U format field was not in unpacked decimal format;
- A variable-length field was specified without a length parameter;
- The SQL null value indicator (S element) has a value of less than -1;
- A field with the NN option is forced to take the SQL null value;
- The resulting value exceeds 4 bytes (longword) if the format is F, or exceeds the maximum (format dependant) length;
- No record with the specified ADAM key was found.

The following information is returned in the Additions 2 field of the control block:

- The first two bytes contain the number of the byte (in binary format) relative to the beginning of the record/value buffer where the error was detected. This value is -1 if a field with the NN option is forced to take the SQL null value.;
- The third and fourth bytes contain the name of the field being processed when the error was detected.

Action Correct the format, record, value, or search buffer and try again.

Response 53

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following errors occurred:

Subcode	Meaning
0	<p>The record buffer is too small.</p> <p><i>Action:</i> If the record buffer size:</p> <ul style="list-style-type: none"> ■ conflicts with the lengths specified in the format buffer, change either the record buffer size or the format buffer specifications to resolve the conflict. ■ conflicts with the established global format ID (GFID), either release the GFID or change the record buffer size to match the GFID. ■ default is too small to hold the records in the file including the DVT when running the ADAULD utility, increase the size of the record buffer by setting the ADAULD LRECL parameter. See the Adabas Utilities documentation for more information.
1	<p>The record buffer is too small. When locating a variable field in the input record, the required buffer length exceeded the given length.</p> <p><i>Action:</i> Verify that the record buffer content matches the given format and that sufficient space for variable fields is provided in the record buffer.</p>
2	<p>The ISN buffer is too small.</p> <p><i>Action:</i> Increase the size of the buffer.</p>
3	<p>The record buffer is too small. When locating a variable field within a group in the input record, the required record buffer length exceeded the given length.</p> <p><i>Action:</i> Verify that the record buffer content matches the given format and that sufficient space for variable fields is provided in the record buffer.</p>
4	<p>The record buffer is too small. When locating a field with A,* notation in the input record, the required record buffer length exceeded the given length.</p> <p><i>Action:</i> Verify that the record buffer content matches the given format and that sufficient space for variable fields is provided in the record buffer.</p>
7	<p>At least one of the record buffers was too small for the data defined in the corresponding format buffer.</p>
8	<p>The referenced existing format buffer requires more space than that given in one of the record buffers.</p> <p>If this subcode occurs using ADACMP DECOMPRESS, the LRECL of the output record is too small.</p>
249	<p>In Adabas Vista, the record buffer provided for an L9 command with 'I' option against a partitioned file is not large enough to hold the full list of ISNs.</p> <p><i>Action:</i> Increase the size of the record buffer.</p>

Open Systems

The record buffer was too small, or the ISN buffer was too small for a requested multifetch command. The following information is returned in the Additions 2 field of the control block:

- The first two bytes contain the expected buffer size in binary format. This value is -1 if the command would have exceeded the maximum record size.
- The third and fourth bytes contain the name of the buffer that was too small. ("RB" or "IB"). If the error occurred while using a hyperdescriptor exit, the name of the hyperdescriptor exit is stored here.

Action Increase the record buffer or ISN buffer size, as appropriate.

Response 54

Origin Mainframe and open systems

Explanation The record buffer for a C3, C5, or ET command is too long. The maximum allowed size is 2048 bytes. The following subcodes provide more information:

Subcode	Meaning
1	The record buffer for the C3 command is too long.
2	The record buffer for the C5 command is too long.
3	The record buffer for the ET command is too long.

Action Correct the record buffer specification, then reissue the C3, C5, or ET command.

Response 55

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following occurred:

- During a read-type operation, a field defined with the SQL null (NC) option contained a null value, but the format buffer held no "S" (significant null) indicator for the field.

In an ACB, the Additions 2 may contain the field name in the leftmost two bytes; the rightmost two bytes may contain the offset into the record buffer. In an ACBX, the Error Character Field (ACBXERRB) may contain the field name; the Error Offset in Buffer (ACBXERRA or ACBXERRG) fields may contain the offset into the record buffer.

- Attempted format conversion was not possible due to incompatible data formats or other compatibility problems.

In an ACB, the Additions 2 will contain the field name in the leftmost two bytes; the rightmost two bytes will contain the offset into the record buffer. In an ACBX, the Error Character Field (ACBXERRB) will contain the field name; the Error Subcode (ACBXERRC) field will contain the subcode.

Subcode	Meaning
0	Conversion error on record decompression.
1	Invalid conversion between formats.
2	Invalid length for fixed encoding. For example, user encoding Unicode with code-point size of 2 bytes and no even length specified.
4	Conversion error of a floating-point field (underflow) when converting to/from a non-IBM floating-point format.
5	One of the following conditions exists: <ul style="list-style-type: none"> ■ Format conversion of a field with the NV option is not allowed. ■ In a read command (Lx, Sx), the format buffer of a field containing a null value is defined with the NC option, but without the NN option, and is missing the SQL significance indicator (S). For read-type commands, the S indicator is required when the NC fields are defined without the NN option. If the S indicator is not present when a read command detects an NC-specified field and the field actually contains a null value, this response code and subcode are returned.
6	An invalid length was specified (for example, a wide character field in Unicode encoding must have an even length).
7	Invalid conversion between formats (different case than subcode 1).
8	Conversion error of a floating-point field (overflow) when converting to/from a non-IBM floating-point format.
9	A one-byte field was provided in the record buffer for the occurrence count of an MU field or PE group in a file with extended MU/PE limits. A two-byte occurrence count value is expected.
10	A field using the NC field option has a null value and no S indicator was specified in the format buffer.
20	Unsupported date-time conversion -- internal error.
21	Date-time value outside valid range. The valid range depends on the date-time edit masks being used in the format or search buffer and the FDT.
22	Invalid local time – (non-existing local time in the gap that occurs when switching from standard to daylight saving time or when the time zone advances GMT offset)
23	Year outside range of 1-9999.
24	Month outside range of 1-12.

Subcode	Meaning
25	Day outside range of 1-n.
26	Hours outside range of 0-24.
27	Minutes outside range of 0-59.
28	Seconds outside range of 0-59.
30	Accessing a field defined with option TZ but no time zone was specified in the user session. Issue the OP command with TZ='timezone' parameter in the record buffer to set the time zone for the user session.
31	Invalid daylight saving offset given (<i>fldD</i>) for date-time and time zone.
n	Data between user and system data representation could not be converted without error and 2-byte error code from ECS.
254	Numeric field length in format shorter than the field length in the FDT.
255	Field length exceeded maximum for variable fields.

Entire Conversion Service (ECS) error codes are described in *Entire Conversion Service (ECS) Errors*, elsewhere in the Adabas Messages documentation.

Open Systems

A format, length conversion, or truncation error occurred while processing field values in the record buffer or value buffer.

- The value for an FI field is too long;
- The resulting value exceeds the border of the FI field;
- Truncation error of numeric field;
- Truncation of alphanumeric fields or truncation of numeric fields which are converted to alphanumeric, except when OPTIONS=TRUNCATION is enabled in ADANUC;
- A value defined without LA or L4 option with variable length is larger than 253 bytes. This may happen for Unicode fields after conversion to another encoding.
- The length specified for a Unicode field for a character set with fixed character length is not a multiple of the character length: in particular, the length for UTF-16 based character sets must be a multiple of 2, and the length for UTF-32 based character sets must be a multiple of 4;
- The specified value is not a valid date/time value;
- The field does not contain a valid date/time value. This can happen if the value was stored without a date/time edit mask;
- A date/time field with option TZ was specified in the format or search buffer, but there was no time zone specified in an OP command for the current Adabas user session;
- The attempted format conversion was not possible due to incompatible data formats or other compatibility problems.

The following information is returned in the first two bytes of the Additions 2 field, and in the case of an ACBX, also in the field ACBXERRC:

Subcode	Meaning
0	Conversion error.
1	Truncation error.
2	Internal structure error.
5	Internal error.
20	Unsupported DATETIME conversion.
21	Date/time value outside valid range. The valid range depends on the date-time edit masks being used in the format or search buffer and the FDT.
22	Date/time value specified in gap when switching from standard time to daylight saving time.
24	Month not between 1 and 12.
25	Day not between 1 and n, where n is the number of days of the month specified.
26	Hours not between 0 and 24.
27	Minutes not between 0 and 59.
28	Seconds not between 0 and 59.
30	Internal error: missing time zone element for conversion with time zone.
31	Invalid daylight saving offset given (fldD) for date/time and time zone.

The field name is returned in the third and fourth byte of the Additions 2 field, and in the case of an ACBX in the field ACBXERRB.

In addition, the following information is returned in the case of an ACBX call:

- The offset in the record or value buffer in ACBXERRA;
- The type of buffer in ACBXERRD ('R' for error in record buffer, 'V' for error in value buffer).

Action

Depending on the reason:

- Correct the appropriate buffer and try again;
- If the time zone specification in the OP command is missing, execute an appropriate OP command;
- On open systems, if a record structure error is indicated, run ADAVFY FIELD against the corresponding file. If this produces errors, then the file must be unloaded, decompressed, recompressed and reloaded;
- On open systems, subcodes 2 and 5 should never occur; you should, therefore, contact your nearest support center if you receive one of these subcodes. A copy of the command log and an export copy or backup of the files accessed will help us to analyze the problem.

Response 56**Origin** Mainframe and open systems**Explanation** One of the following occurred:

Subcode	Meaning
.	The descriptor value was too large. Descriptor values are limited to 1144 bytes.
<i>n</i>	The collation value exceeded the maximum 253 bytes. The subcode <i>n</i> is the collation descriptor exit number.

Action Store a shorter descriptor value or collation value.

On open systems, you also can specify the TR option for the descriptor, which truncates larger descriptor values before they are stored in the index. Note that with the TR option, search results may be inaccurate: this is because values that are identical in the first 1144 bytes are considered to be equal to each other.

Response 57**Origin** Mainframe and open systems**Explanation** In an L9 command, the descriptor specified in the format or search buffer or in the Additions 1 field was invalid or the descriptor was not specified:

- The field name specified may not be the name of a descriptor.
- The descriptor specified may be a phonetic descriptor or a hyperdescriptor, which are not allowed in an L9 command.
- On open systems, the descriptor specified may be a collation descriptor with the option HE.

Action Correct the descriptor in the format buffer, search buffer, or Additions 1 field and try again.**Response 58****Origin** Mainframe systems only**Explanation** The format could not be found (as defined within format selection criteria).**Action** Adjust the format specification and try again.

Response 59

- Origin** Mainframe systems only
- Explanation** Format conversion of a subfield is not possible. The source field has fixed point (F) or floating point (G) format.
- Action** Correct the field for which you are attempting format conversion and try again.

Response 60

- Origin** Mainframe and open systems
- Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

A syntax error was detected in the format or search buffer. Generally in an ACB, the first two bytes of the Additions 2 field contain the two characters under inspection when the error was detected and the rightmost two bytes of the Additions 2 field in the ACB contain one of the following subcodes. In an ACBX, the Error Character Field (ACBXERRB) contains the two characters under inspection when the error was detected and the Error Subcode (ACBXERRC) field contains one of the following subcodes.

Subcode	Meaning
1	Premature end of search buffer.
2	Syntax error in search buffer; possibly a bad field name.
3	Text literal has no ending quote or is too long (more than 255 characters).
4	Text literal is empty.
5	Expected delimiter missing.
6	Soft coupling criterion has not closing parenthesis (")").
7	Soft coupling criterion is empty.
8	Invalid field name, format, or search operator.
9	Invalid edit mask number (greater than 15).
10	Invalid character following field name specification.
11	Invalid specification of MU field in PE group.
12	Expected number missing or too large (greater than 2 ³¹).
13	Syntax error in LOB segment specification.
14	Syntax error in length indicator notation (L) specification.
15	Syntax error in daylight savings time notation (D) specification.
16	Invalid date-time edit mask specification.
17	MU/PE index range specification is invalid for LOB segment notation.

Open Systems

A syntax error was detected in the search buffer.

The following information will be returned in the Additions 2 field of the control block:

- The first two bytes will contain the number of the byte (in binary format) relative to the beginning of the search buffer where the error was detected;
- The third and fourth bytes will contain the name of the field being processed when the error was detected.

Action Correct the format or search buffer and try again.

Response 61

Origin Mainframe and open systems

Explanation An error was detected in the search buffer, value buffer, or during an S8 command.

Mainframe Systems

On mainframe systems, one of the following subcodes may also be included with this response code:

Subcode	Meaning
2	An invalid value operator was detected in the search buffer.
3	An invalid logical operator was specified for an S8 command - Command Option 2.
7	This subcode indicates that one of the following errors occurred: <ul style="list-style-type: none"> ■ The length of a descriptor value was greater than 253. ■ Invalid file number specification. ■ Invalid selection criteria for an Event Replicator for Adabas initial-state definition. ■ Invalid usage of the "S" or "N" operator. ■ The element order was invalid. ■ The specified field was not a descriptor. ■ The specified field has the "LA" option active. ■ A descriptor contained in a periodic group was specified without an index. ■ Invalid connection of partial criteria or different indices were used for a descriptor contained within a periodic group. ■ Invalid periodic group index.

Subcode	Meaning
	<ul style="list-style-type: none"> ■ Invalid or disallowed use of a phonetic descriptor. ■ A descriptor derived from or contained in a periodic group is not allowed. ■ The FROM-TO operator was specified with a phonetic descriptor. ■ Invalid FROM-TO range specification, or the FROM value was greater than the TO value. ■ The BUT-NOT value was outside the range of the preceding FROM-TO range. ■ An invalid command option was specified for ISN LIST processing (S8 command). ■ The search buffer "S" significant null indicator was specified with a value operator other than "EQ" (equals), which is not allowed.
8	An invalid FROM-TO range was specified. The BUT-NOT value was outside the range of the preceding FROM-TO value.
9	An invalid search criteria was specified.

Open Systems

On open systems, an error was detected in the search or value buffer, or during an S8 command:

- Invalid command option 2 specified for ISN LIST processing (S8 command);
- Invalid element or element order;
- The specified field was neither a descriptor, subdescriptor, superdescriptor nor a phonetic descriptor;
- Invalid connection of partial criteria and/or different indices used for a descriptor contained within a periodic group;
- Invalid use of a phonetic descriptor;
- Invalid periodic group index;
- Invalid index usage;
- The length of a descriptor value was greater than 253 or greater than the permitted length for the required format;
- Invalid format type;
- Invalid file number specification;
- Invalid usage of the S operator - FROM value greater than TO value;
- Invalid usage of the N operator - BUT NOT value was outside the range of the preceding FROM-TO range;
- Invalid comparator;
- The value in the value buffer cannot be converted into the field's FDT format;

- The specified file name is not an ADAM key while using the V option with an A1 or E1 command;
- Invalid value given in the value buffer while using the V option with the A1 or E1 command;
- Invalid usage of the C option - only allowed for collation descriptors;
- A field was specified with an edit mask that is not allowed for the field.

The following information is returned in the Additions 2 field of the control block (not for the S8 command):

- The first two bytes will contain the number of the byte (in binary format) relative to the beginning of the search buffer where the error was detected;
- If the third byte is zero, the fourth byte contains more information about the error:
 - Fourth byte 1: invalid length.

Otherwise the third and fourth bytes will contain the name of the field being processed when the error was detected.

Action Correct the search or value buffer or S8 command and try again.

Response 62

Origin Mainframe and open systems

Explanation One of the following has occurred:

- The length of the search or value buffers as specified in the search and value buffer length fields, respectively, was not sufficient to accommodate the search criteria specified.
- The first character in the search buffer was a period (.).
- The search buffer does not contain a period (.).

Action Correct the search or value buffer and try again.

Response 63

Origin Mainframe and open systems

Explanation The command ID value specified in the search buffer was invalid.

On open systems, the value in the first two bytes of the Additions 2 field indicates the reason (2 byte binary format):

Subcode	Meaning
1	The command ID value specified in the search buffer was not found.
2	The associated ISN list is not sorted in ISN sequence (it has been generated by an S2/S9 command).
3	The command ID was not used in the previous FIND in which the SAVE ISN LIST option was used.

Action Correct the command ID in the search buffer and try again.

Response 64

Origin Mainframe systems only

Explanation This response code is used for communication with Adabas utilities and Adabas Online System (AOS), and was returned because the requested function could not be performed on the Adabas system (including checkpoint and security) files or because an error occurred in an AOS or utility function.

The following table shows some of the subcodes that may be returned:

Subcode	Meaning
61	No or duplicate field(s) (see 'xx'); where xx is the first duplicate field encountered. If no field definitions were specified an FC is returned.

Action Refer to the ADAREP output report for a list of the system files, or to the subcodes in the job output for more information. For AOS, a subcode is displayed in the error message, following the AOS module number. For utility functions, the subcodes may be described within the message text.

If you do not understand the action to take for a response code 64 or subcode, note the subcode and the function that caused the response code, and call your Software AG technical support representative for assistance.

Response 65

Origin Mainframe systems only

Explanation An internal error occurred. The nucleus detected a space calculation error.

Action Contact your Software AG technical support representative for assistance.

Response 66

Origin	Mainframe systems only
Explanation	An incompatible owner ID was detected during an update operation on a multicient file. The owner ID may be blank, or too long.
Action	Contact your Software AG technical support representative for assistance.

Response 67

Origin	Mainframe systems only
Explanation	One of the following errors occurred:

Subcode	Meaning
.	An internal error occurred while executing an Sx command.
2	An error occurred during superfield generation.

Action	Retain all related information, and contact your Software AG technical support representative for assistance.
---------------	---

Response 68

Origin	Mainframe systems only
Explanation	A nondescriptor field was used as a search criterion, and the non-descriptor search facility has been set OFF (the default for this facility is ON).
Action	The ADARUN parameter NONDES has been set to reject non-descriptor searches; either reset the NONDES parameter to its default value, or remove non-descriptor searches from your application. Natural provides a trace facility which locates such Natural application characteristics. Contact Software AG for details.

Response 70

Origin	Mainframe systems only
Explanation	An overflow occurred in the table of sequential commands.
Action	The DBA may increase the value used for the LQ parameter or RC commands may be used.

Response 71

Origin	Mainframe systems only
Explanation	An overflow occurred in the table of resulting ISN lists.
Action	The DBA may increase the value used for the LI parameter or RC commands may be used.

Response 72

Origin Mainframe and open systems

Explanation One of the following errors occurred:

Subcode	Meaning
6	The NU parameter is too small for the execution of a session autorestart. It is smaller than it was in the previous Adabas nucleus session that failed. In a cluster nucleus, the NU parameter is smaller than in the nucleus that had established the global lock structure.
7	An overflow occurred in the user queue.
8,9	An overflow occurred in the user queue file list pool.

Action The DBA may increase the value used for the NU parameter.

Response 73

Origin Mainframe and open systems

Explanation An overflow occurred in the section of the Work data set (mainframe systems) or the temporary working space (open systems) in which resulting ISN lists are stored.

On open systems, please note that for read-only databases, temporary working space is only created if a location for it is explicitly specified (environment variable `TEMPLOCn` or entries for `TEMPORARY_LOCATION` in the file `DBnmn.INI`); otherwise only some of the space in the Adabas buffer pool is used for storing the ISN lists.

Action On mainframe systems, the DBA may increase the size of the Work data set and/or the number of saved ISN lists during an Adabas session may be decreased.

On open systems, provide enough temporary working space. For read-only databases, specify the location for the temporary working space explicitly or increase the size of the Adabas buffer pool (`ADANUC` parameter `LBP`).

Note: The processing of ISN lists was changed for Adabas Version 5.1. If you get this error with an Adabas Version 3 database, please refer to the Adabas Version 3 documentation.

Response 74

Origin Mainframe and open systems

Explanation No space was available on the Work data set for complex find commands.

Action On open systems, increase the size of the Work data set.

On mainframe systems, increasing the size of the Work data set alone will not solve this problem. Instead, set the value of `LWKP2` (`WORK-PART-2`) to a higher value than the calculated one (whatever that might be). Then increase the size of the Work data set to ensure there is sufficient space for `WORK-PART-3`.

Response 75

Origin Mainframe and open systems

Explanation Attempts to allocate additional Associator or Data Storage extents for a file were issued, but the maximum number of extents that can be handled by the FCB have already been allocated.

On mainframe systems, BT (backout) or autorestart processing could cause the file to be locked because of inadequate extent space (see response code 48, ADARSP048).

On open systems, the last extent is allocated only for a command which is being backed out and for AUTORESTART and ADAREC REGENERATE. The first two bytes of the Additions 2 field contain the highest possible extent number (in binary format). The third and fourth bytes indicate where the overflow occurred. Possible values are: "DS" (Data Storage), "AC" (Address Converter), "NI" (Normal Index) and "UI" (Upper Index).

Action On mainframe systems, ask your DBA for assistance; Associator or Data Storage extents may have to be reallocated.

On open systems, unload the file and reload it with appropriate initial allocations.

Response 76

Origin Mainframe and open systems

Explanation An overflow occurred in an inverted list index (the maximum is 15 levels).

Action Unload and reload the file with an appropriate padding factor for the Associator.

Response 77

Origin Mainframe and open systems

Explanation Sufficient space was not available for a required Associator or Data Storage extent.

On mainframe systems, the following subcodes further define the error:

Subcode	Meaning
1	FST empty.
2	AC START RABN not available.
3	AC END RABN not available.
4	FST will not fit into five ASSO blocks.
5	FST exhausted trying to allocate AC extent.
6	ASSO space allocation RABN not on device.
7	ASSO space on required device not available.
8	FROM RABN available, but contiguous space is not sufficient.
9	Data Storage space of the requested size is not available.
10	Data Storage space on the same device as the previous extent is not available.

Subcode	Meaning
11	FST is empty, or data storage for the current MAXRECL value is not available.
12	FST empty.

On open systems, the third and fourth bytes of the Additions 2 field contain either "AS" (Associator) or "DS" (Data Storage). You can also get the response 77 if you specified an explicit RABN for an Associator or Data Storage extent and the requested space is not available at the requested RABN. Please note that Adabas distinguishes between small (< 16KB) and large (>= 16KB) index blocks. This means that a response 77 can be returned even though there are enough free Associator blocks, but the free Associator blocks have the wrong size.

Action

On mainframe systems, ask your DBA for assistance; Associator or Data Storage extents may have to be reallocated.

On open systems, add a new Associator or Data Storage extent to the database using the ADADBM utility or specify a RABN where the requested space is available.

Note: Response 77 can sometimes be prevented by enabling database autoexpand to execute in the online mode (specify the open systems nucleus parameter OPTIONS=AUTO_EXPAND).

Response 78

Origin

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The cause of this response is indicated by one of the following subcodes:

Subcode	Meaning
1	The AC file cannot be increased; only one file extent is permitted.
2	The file contains more than either 4 billion or 16 MB of ISNs, depending on the ISN length, or if ISNREUSE is in effect, the file has reached TOPISN and is very fragmented and too much effort would be needed to search for a free ISN.

Open Systems

An overflow occurred in the free space table (FST) as a result of Associator or Data Storage fragmentation, or the maximum number of DSST extents has already been allocated.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

If the file has reached the 16-MB limit, you might convert it to a file with the 4-byte ISN option or to an expanded file. If ISNREUSE is in effect, ADABAS ISNREUSE=ON, RESET can be used to reset the rotating ISN pointer or the file can be reloaded to eliminate the fragmentation.

If the file has NOACEXTENSION specified, look for alternatives to increase the file size such as adding an additional file to the expanded file chain. If the file is not part of an expanded file chain, you may want to reload the file to remove the restriction.

Open Systems

If it is an FST problem, reorder the database. If it is a DSST problem, which can only occur in the context of a utility, refer to the message DSSTALL for further information.

Response 79

Origin

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

A collation descriptor exit or hyperdescriptor exit error occurred. The following table describes the possible subcodes for this response code and their meanings:

Subcode	Meaning
1	Either a collation descriptor exit (subcode CDX n where n is the one-byte binary collation descriptor exit number) or a hyperdescriptor exit ("hyperdescriptor exit") was not specified ADARUN.
5	The hyperdescriptor exit stub was called for an extended MU/PE file.
6	Improper use of the parameter list was detected by the Hyperdescriptor Exit Stub. The most likely reason is that a hyperdescriptor exit using the Adabas 8 parameter structures is linked to the Hyperdescriptor Exit Stub.
7	The Hyperdescriptor Exit Stub could not resolve the HEXOLD external reference.
8	Improper use of the parameter list was detected. The second word of the parameter list was modified.
9	A hyperdescriptor exit did not return an output parameter area address.
10	A hyperdescriptor exit rejected the call by setting a nonzero return code in the output parameter header.

Open Systems

A hyperdescriptor exit is not available to the nucleus. The following information is returned in the Additions 2 field of the control block:

- The first two bytes contain the number of the hyperdescriptor exit,;
- The third and fourth bytes contain the name of the hyperdescriptor.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The following table describes the actions you should take for each possible subcode for this response code:

Subcode	User Action
1	Reissue ADARUN with the CDX nn or HEX nn parameter. For more information about ADARUN parameters, read <i>Adabas Initialization (ADARUN Statement)</i> , in <i>Adabas Operations Manual</i> ; for more information about user exits and hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
5	The Hyperdescriptor Exit Stub may not be used with extended MU/PE files. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
6,7	Investigate the Hyperdescriptor Exit Stub link job. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
8	A likely cause of the error is that a pre-Adabas 8 hyperdescriptor exit was called without a linked Hyperdescriptor Exit Stub. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
9	Hyperdescriptor exits must return an output parameter area address upon return. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
10	Investigate the hyperdescriptor exit to determine why the call was rejected.

Open Systems

Define the hyperdescriptor exit and restart the nucleus.

Response 81

Origin

Mainframe systems only

Explanation

An MU or PE field error occurred, as described by the subcode:

Subcode	Meaning
1	The PE index is greater than 191 (if the maximum number of PE field occurrences is 191).
2	The PE index is greater than 65534 (if the maximum number of PE field occurrences is 65534).
3	The MU index is greater than 65534 (if the maximum number of MU field occurrences is 65534).
4	The MU index is greater than 191 (if the maximum number of MU field occurrences is 191).

Action Correct the MU or PE field problem and try again. If the problem persists, contact your Software AG technical support representative for assistance.

Response 82

Origin Mainframe systems only

Explanation A hyperdescriptor exit routine returned an invalid ISN.

Action Correct the hyperdescriptor exit routine logic and restart the nucleus.

Response 83

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

A hypertable overflow occurred.

Open Systems

A hyperdescriptor exit routine returned an invalid ISN.

The following information will be returned in the Additions 2 field of the control block:

- The first two bytes contain the offset the invalid ISN in the specified ISN buffer in binary format;
- The third and fourth bytes contain the name of the hyperdescriptor.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Open Systems

Correct the hyperdescriptor exit routine and restart the nucleus.

Response 84

Origin

Mainframe systems only

Explanation

Too many values were present for a subdescriptor or a superdescriptor.

Action

Reduce the number of subdescriptor or superdescriptor values and try again.

Response 85

Origin

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Too many descriptor values were present for an update or add record command.

Open Systems

The descriptor value table space cannot be allocated from the buffer pool.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Open Systems

Increase the size of the LBP parameter.

Response 86

Origin

Mainframe and open systems

Explanation

A hyperdescriptor exit return error occurred for one of the following reasons:

- An incorrect sign for a packed descriptor value was created.
- A value with an incorrect length byte was returned.
- The ISN was changed by an update command.

On open systems, the following information is returned in the Additions 2 field of the control block:

- The first two bytes contain a value. This value can be:

- 1 the hyperdescriptor pool exceeds the nucleus buffer pool
 - 2 the hyperdescriptor exit has returned an invalid pointer, length or count value
 - 3 an element in the user-defined format buffer is not a parent field of the hyperdescriptor
 - 4 - 255 Adabas response code
 - >255 user-defined error return for hyperdescriptor exit routine
- The third and fourth bytes contain the name of the hyperdescriptor or the name of the parent field.

Response 87**Origin**

Mainframe systems only

Explanation

The Adabas buffer pool is locked; it is too small to accommodate all blocks needed for (parallel) command execution.

Action

Check the length of the buffer pool (LBP) as follows:

Subcode	User Action
1	Check the LBP value with DPARM.
2	Increase the ADARUN LBP parameter value.
3	Retry the operation. If the error recurs, call your Software AG support representative for assistance.

Response 88**Origin**

Mainframe and open systems

Explanation

This response code generally occurs when there is a workpool (LWP) shortage. Sufficient work pool space is not available or the sort work space is too small (even if only one user is active).

On mainframes systems, when this response code occurs, refer to the hexadecimal subcode that appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field. This subcode describes what kind of operation encountered the error.

The following table describes the mainframe subcodes and provides recommended actions.

Subcode	Operation Encountering the Workpool Shortage	Action
1	Only active command is waiting for workpool space.	Increase the ADARUN LWP setting and try again.
	During session autorestart, insufficient workpool or user queue space was encountered.	Increase ADARUN LWP and NU parameter settings and try again.
2	Only active command is waiting for workpool space.	Increase the ADARUN LWP setting and try again.
3	A command waiting for workpool space was interrupted for transaction backout.	
4	A1 command	
5	E1 command	
7	Superfield value generation	
8	N1 command	
9	OP command	
10	Descriptor value generation	
11	Hyperdescriptor value generation	
12		
13	Subdescriptor value generation	
15	DTP=RM: A getmain error during Work-Part-4 initialization.	
16	Hard-coupled file update processing encountered a workpool shortage.	
17	A session autorestart encountered a workpool shortage.	
22	Online reorder by descriptor	
23	Online invert	
24	Open one of the Work data sets in a cluster	
25	Session autorestart in a cluster	
79	Work pool shortage during release of advanced lock function.	
80	Work pool shortage during insert (N1/N2-command) of spanned record	
96	Internal command queue full	
98	Cluster with DTP=RM: Recovery of distributed transactions encountered a workpool shortage.	
99	ET command with P-option	
	Descriptor value generation for multi-client file	
	Single-user mode: Command initialization	

Subcode	Operation Encountering the Workpool Shortage	Action
	Replication: Setup of initial-state process	
	DTP=RM: Insufficient user queue space during Work-part-4 initialization	Increase the ADARUN NU setting and try again.

Action For mainframe systems, review the actions described in the table above.

For open systems, verify the parameter values for the database that relate to the working storage allocation. Ask your DBA to increase the size of the LWP or LS parameter, as necessary.

Response 89

Origin Mainframe systems only

Explanation The UQE was already in use, and an attempt was made to execute two commands at the same time for the same user.

Response 94

Origin Mainframe systems only

Explanation An I/O error occurred on DDWORKR4.

Response 95

Origin Mainframe systems only

Explanation An I/O error occurred on the Work LP area.

Response 96

Origin Mainframe systems only

Explanation An error occurred during ADARES REPAIR utility execution.

Subcode	Meaning
2	An I/O error occurred during nucleus termination; Additions 2 may contain RABN.

Response 97

Origin Mainframe systems only
Explanation An I/O error occurred during buffer flush. Additions 2 may contain RABN.

Response 98

Origin Open systems only
Explanation A uniqueness violation of a unique descriptor was detected during a store or update processing if subtransactions are not activated, or otherwise at end of a subtransaction. The third and fourth bytes of the Additions 2 field contain the name of the descriptor which caused the uniqueness conflict.
Action Check the descriptor values.

Response 99

Origin Mainframe and open systems
Explanation An I/O error occurred.
 On open systems, the first 2 bytes of the Additions 2 field (in binary format) contain the extent number. The third and fourth bytes contain the container type ("AS" for ASSO, or "DS" for DATA or "WO" for WORK).
Action On open systems, check whether any disk devices have gone offline or check the error log for hardware errors.

Response 101

Origin Mainframe and open systems
Explanation An error has occurred using one of the client-based Adabas add-on products such as Adabas System Coordinator or Adabas Fastpath.

Mainframe Systems

On mainframe systems, one of the following subcodes may also be included with this response code:

- Subcodes of 20 or less are produced by Adabas Fastpath when an error occurs during the processing of an Adabas command..
- Subcodes of 21 or greater are produced by Adabas System Coordinator.

Refer to the hexadecimal subcode that appears in the command's Adabas control block, Additions 2 field, low-order (rightmost) two bytes. The subcodes are described in the table below:

Subcode	Meaning
2	L3/L9 direct optimization internal error. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "2".
6	L3 direction change error. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "6".
7	Direction change integrity check error. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "7".
8	Default response to internal service commands in the database. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "8".
9	Optional response for Read Ahead Update warning messages. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "9".
10	Error following a PLEX move. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "A".
21	Session cleanup error. This is an internal error in Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative.
22	You are using the CORS09 client component in a zIIP enabler for Natural environment and Natural zap NA97065 is not applied. <i>Action:</i> Apply Natural zap NA97065.
23	Session create error. This is probably due to insufficient memory. <i>Action:</i> Increase the job region size. If the problem persists, contact your Software AG technical support representative.
25	CAB: Allocation failed. Insufficient memory was available for CAB. This is an Adabas System Coordinator error. <i>Action:</i> Increase the job region size. Note: This subcode is not subject to COR Debug.
26	Incorrect use of asynchronous Adabas calls. <i>Action:</i> Contact your Software AG technical support representative. Note: This subcode is not subject to COR Debug.
28	Internal thread concurrency error. <i>Action:</i> Contact your Software AG technical support representative. Note: This subcode is not subject to COR Debug.
29	Internal command error: Value buffer is not present. <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
30	<p>Internal command error: Illegal function.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
31	<p>Error allocating the internal job-structure.</p> <p><i>Action:</i> Increase the job region size. If the problem persists, contact your Software AG technical support representative.</p>
32	<p>Internal command error: Insufficient record buffer.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
33	<p>Internal command error: Record buffer is not present.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
34	<p>Internal command error: Incorrect value buffer format.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
35	<p>Memory allocation failure. Insufficient memory was available for an internal area needed for NIM support. This is an Adabas System Coordinator error.</p> <p><i>Action:</i> Increase the job region size.</p> <p>Note: This subcode is not subject to COR Debug.</p>
38	<p>Internal command error: Unsupported memory function</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
43	<p>Initialization Error. An error occurred during job initialization in Adabas System Coordinator.</p> <p><i>Action:</i> Ensure that correct runtime controls were defined for the job. If problem persists, contact Software AG Support.</p>
46	<p>CAS: No group header record. This error appears if Adabas System Coordinator fails to find a header record for the required System Coordinator group.</p> <p><i>Action:</i> First check that you have a valid CORCFG module pointing to the correct database and file number for your configuration file. Ensure that the load library containing CORCFG is included in the load library concatenation of the job. If CORCFG is present and correct, logon to SYSCOR and verify that you have valid Daemon Group parameters for the job you are running. If all parameters are correct, contact your Software AG technical support representative for assistance.</p>
49	<p>Internal eventing error: Illegal request.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
50	<p>Internal error processing add-on products.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>

Subcode	Meaning
53	<p>This job is not defined to use the daemon.</p> <p><i>Action:</i> Review and correct the installation for this job.</p>
54	<p>Internal services error.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
55	<p>Latency processing error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
56	<p>Latency processing error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
59	<p>CORSnn: Critical products. One or more products have been defined as "Critical" in the Corrdinator configuration file, and one of the following errors was detected:</p> <ul style="list-style-type: none"> ■ The Adabas System Coordinator Kernel module (CORKRN) was not found. ■ Adabas System Coordinator initialization has failed. There will be a Coordinator message indicating the cause of the initialization failure. <p><i>Action:</i> Determine the cause of the concurrent command and modify the application to remove it.</p> <p>Note: This subcode is not subject to COR Debug.</p>
60	<p>CORKRN: Critical Products. One or more products have been defined as "Critical" in the Adabas System Coordinator configuration file, and the product has indicated a critical error during initialization.</p> <p><i>Action:</i> Determine the cause of the concurrent command and modify the application to remove it.</p>
62	<p>CORS02/CORS12: Subsystem storage protect facility not activated. Com-plete has been customised to operate with mixed thread keys, but the IBM subsystem Storage Protection override facility is not enabled. Adabas System Coordinator requires this facility to support mixed thread keys in Com-plete.</p> <p><i>Action:</i> Either activate the Subsystem Storage Protection override facility in this system OR change the Com-plete thread groups to operate in Com-plete's key only (see the description of the THREAD-GROUP parameter in the Com-plete documentation).</p>

Subcode	Meaning
	Note: This subcode is not subject to COR Debug.
64	<p>Net-Work Clustering: Node not member of Group. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
65	<p>Net-Work Clustering: Message segment protocol error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
66	<p>Net-Work Clustering: Message sequence error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
67	<p>z/OS only: Invalid SVC is being used for the execution of an Adabas call.</p> <p><i>Action:</i> Review and correct the installation. If the problem persists, contact your Software AG technical support representative.</p>
68	<p>z/OS only: The batch Adabas System Coordinator client component (CORS01) is being incorrectly used for a Multi-TCB job.</p> <p><i>Action:</i> Refer to installation step "Add the System Coordinator to the Adabas Client" in the Installation Procedure section of the Adabas System Coordinator Installation documentation for information regarding the available CORS0<i>n</i> client components and their applicability to different job types.</p> <p>If the problem persists, contact your Software AG technical support representative.</p>
69	<p>Insufficient memory to initialize runtime controls. There is insufficient memory for COR to initialize. This is an Adabas System Coordinator error.</p> <p><i>Action:</i> Increase the memory available to the job.</p>
81	<p>Internal UB Getmain error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
82	<p>Invalid session pointer. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
83	<p>Internal session UB not found. This is an internal error.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>

Subcode	Meaning
84	<p>Internal error in Adabas buffer analysis. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
85	<p>Internal thread getmain error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Increase the job region size and rerun the job. If the problem persists, contact your Software AG technical support representative.</p>
86	<p>Invalid command block pointer. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
87	<p>Client versioning has not been installed correctly.</p> <p><i>Action:</i> Check the job for any console messages and ensure that client versioning is installed correctly.</p>
88	<p>Adabas CICS link module and TRUE have not been installed correctly.</p> <p><i>Action:</i> Ensure that the Adabas CICS link module and TRUE are installed correctly. This must be done to enable Adabas System Coordinator to operate in a CICS job.</p> <p>Note: This subcode is not subject to COR Debug.</p>
89	<p>The NIM subtask is in the process of being detached.</p> <p><i>Action:</i> None, this subcode simply indicates that a NIM subtask was still issuing Adabas commands when it was terminated by the main NIM task.</p> <p>Note: This subcode is not subject to COR Debug.</p>
90	Internal handshake token validation error.
91	<p>Latency processing error (no facility). This is an internal error in Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
92	<p>Asynchronous call with no CAB. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
93	<p>Latency processing error (memory). This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Increase the job region size. If the problem persists, contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>

Subcode	Meaning
94	<p>Latency processing lock error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
95	<p>Daemon latency processing error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Ensure that the System Coordinator daemon is available.</p> <p>If the client that receives this error is using the COLAT daemon latency disk file to manage their session-related information, then this subcode may be indicative that the disk file is full. If so, check the daemon job log for any accompanying error messages.</p> <p>If the problem persists, contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
96	<p>Latency processing error (facility deleted). This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
97	<p>Latency processing lock error when using daemon latency.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
102	<p>Latency processing unlock error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
103	<p>Latency processing error for IMS.</p> <p><i>Action:</i> Increase the size of the Daemon latency /pulse services shared memory area size in the COR daemon parameters.</p> <p>Note: This subcode is not subject to COR Debug.</p>
200	<p>When running Multi-system dynamic transaction routing (z/OS only), there was an error writing to the Coupling Facility Cache structure.</p> <p><i>Action:</i> Refer to the accompanying COR010S message in the daemon.</p>

Subcode	Meaning
	Note: This subcode is not subject to COR Debug.
201	<p>When running Multi-system dynamic transaction routing (z/OS only), there was an error reading from the Coupling Facility Cache structure.</p> <p><i>Action:</i> Refer to the accompanying COR009S message in the daemon.</p> <p>Note: This subcode is not subject to COR Debug.</p>
202	<p>When running Multi-system dynamic transaction routing (z/OS only), an incorrect record was read from the Coupling Facility Cache structure.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
203	<p>When running Multi-system dynamic transaction routing (z/OS only), there was a memory shortage in the local daemon when attempting communications with a peer daemon.</p> <p><i>Action:</i> Increase the region size for the daemon. If the problem persists, contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
204	<p>When running Multi-system dynamic transaction routing (z/OS only), there was a protocol error in the local daemon when attempting communications with a peer daemon.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
205	<p>When running Multi-system dynamic transaction routing (z/OS only), a peer daemon returned an error when contacted by the local daemon.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
206	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was an internal problem identifying the correct facility.</p> <p><i>Action:</i> Contact your Software AG technical support representative. Note: This subcode is not subject to COR Debug.</p> <p>Note: This subcode is not subject to COR Debug.</p>

Subcode	Meaning
207	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was a memory shortage in the local daemon.</p> <p><i>Action:</i> Increase the region size for the daemon. If the problem persists, contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
208	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was a protocol error in the local daemon when attempting communications with a peer daemon.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
209	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, a peer daemon returned an error.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
210	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was an internal error with the facility size.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
211	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, the facility could not be moved into daemon managed shared memory in the local daemon due to a lack of space.</p> <p><i>Action:</i> Refer to the daemon group member parameter Daemon latency/pulse services and increase the size of the dataspace. If the problem persists, contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
212	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was an internal error writing to daemon managed shared memory.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>

Subcode	Meaning
213	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was a protocol error in the local daemon when attempting to remove the facility from a peer daemon.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
214	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, a peer daemon returned an error when instructed to remove a facility.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>

Open Systems

On open systems, one of the following Adabas System Coordinator subcodes may also be included with this response code:

Subcode	Meaning
1 (0x0001)	<p>The standard Adabas or Entire Net-Work ADALNKX library could not be loaded.</p> <p><i>Action:</i> Check that the ADALNKX parameter in the Initialisation File (cor.cfg) is set correctly and that the library exists.</p>
2 (0x0002)	<p>The standard Adabas or Entire Net-Work ADALNKX library could not be loaded.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
3 (0x0003)	<p>The standard Adabas or Entire Net-Work ADALNKX library does not export all expected functions.</p> <p><i>Action:</i> Check that the ADALNKX parameter in the Initialisation File refers to an ADALNKX library and not an ADALNK or ADALNK32 library.</p>
4 (0x0004)	<p>Adabas did not return the database architecture information in the ISN lower limit field when an OP command was issued to the Configuration File.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>

Subcode	Meaning
5 (0x0005)	<p>The path to the Initialisation File (<i>cor.cfg</i>) could not be determined.</p> <p><i>Action:</i> Check the HKLM\SOFTWARE\Software AG\Adabas System Coordinator registry key and ensure the Path value is set correctly (Windows).</p> <p>Check that the \$CORDIR and \$CORVERS environment variables are set correctly (Unix).</p>
6 (0x0006)	<p>The ADALNKX parameter could not be read from the Initialization File (<i>cor.cfg</i>).</p> <p><i>Action:</i> Check that the Initialization File exists and that the ADALNKX parameter is set correctly.</p>
7 (0x0007)	<p>The LFILE parameter could not be read from the Initialization File.</p> <p><i>Action:</i> Check that the Initialization File (<i>cor.cfg</i>) exists and that the LFILE parameter is set correctly.</p>
8 (0x0008)	<p>An incompatible version of an Adabas add-on product is installed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
9 (0x0009)	<p>An incompatible version of an Adabas add-on product is installed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
10 (0x000A)	<p>The library for an Adabas add-on product could not be loaded.</p> <p><i>Action:</i> Check that the Adabas add-on product is installed correctly.</p>
11 (0x000B)	<p>The library for an Adabas add-on product could not be unloaded.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
12 (0x000C)	<p>The address or length of the format, record, search, value or ISN buffer appears to be invalid.</p> <p><i>Action:</i> Check the buffer addresses passed to the <i>adabas()</i> function and the lengths specified for the buffers in the Adabas control block.</p>

Subcode	Meaning
13 (0x000D)	The CORADC load module could not be fetched (Mainframe). <i>Action:</i> Check that \$STEPLIB environment variable is correct and that the CORADC load module exists in the specified data set.
14 (0x000E)	Port range exhausted (there are not enough allocated to this computer). <i>Action:</i> Configure a larger port range for the Adabas System Coordinator Computer using System Management Hub.
15 (0x000F)	Port conflict (the allocated port is in use by another application). <i>Action:</i> Assign a different port to the Adabas System Coordinator daemon or change the port range for the Adabas System Coordinator computer using System Management Hub.
16 (0x0010)	Computer name could not be generated. <i>Action:</i> The Adabas System Coordinator Launch Control could not generate a unique computer name for the machine. Create an Adabas System Coordinator computer for this machine manually using System Management Hub.
17 (0x0011)	The FDT of the Configuration File is not compatible with Adabas System Coordinator. <i>Action:</i> Check that the database and file numbers are correct.
18 (0x0012)	The version of Adabas is not compatible with Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative.
19 (0x0013)	The SAGABS library could not be loaded. <i>Action:</i> Check that the SAGABS library is installed.
20 (0x0014)	The SAGABS library could not be unloaded. <i>Action:</i> Contact your Software AG technical support representative.
21 (0x0015)	The SAGABS library is not compatible with Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
22 (0x0016)	Port conflict (the allocated port is in use by another Adabas System Coordinator Group). <i>Action:</i> Assign a different Group Services port to the Adabas System Coordinator Computer using System Management Hub.
23 (0x0017)	Unable to spawn process (the command line parameters specified for the process are invalid). <i>Action:</i> Contact your Software AG technical support representative.
24 (0x0018)	Length of compressed record buffer length exceeds limit. <i>Action:</i> Contact your Software AG technical support representative.
25 (0x0019)	Length of compressed record buffer could not be determined. <i>Action:</i> Contact your Software AG technical support representative.
26 (0x001A)	Product not installed or not configured correctly. <i>Action:</i> Check that the Adabas add-on product is installed correctly.
27 (0x001B)	Configuration file version does not match the running version. <i>Action:</i> Contact your Software AG technical support representative.
28 (0x001C)	Configuration file layout is not as expected for a configuration file. <i>Action:</i> Contact your Software AG technical support representative.
29 (0x001D)	The installed Adabas version does not correctly process LF 'S' commands (Adabas 6.1.9 or earlier). <i>Action:</i> Contact your Software AG technical support representative.
30 (0x001E)	The installed Adabas version does not support LF 'I' commands (unzapped Adabas 8.2.2 or earlier). <i>Action:</i> Contact your Software AG technical support representative.
31 (0x001F)	Migration of the Configuration File was unsuccessful. <i>Action:</i> Check the output of the migration process for errors. If the reason for an unsuccessful migration cannot be

Subcode	Meaning
	determined, contact your Software AG technical support representative.
52 (0x0034)	Exception reading/writing pointer. <i>Action:</i> Contact your Software AG technical support representative.
0000A001-FFFFA001	A TCP/IP error occurred. <i>Action:</i> The left-hand side of the subcode contains the operating system error code.
0000A002-FFFFA002	A DNS error occurred. <i>Action:</i> The left-hand side of the subcode contains the operating system error code.

Response 102

Origin Mainframe systems only
Explanation Space calculation error.
Action Retry the open operation.

Response 105

Origin Mainframe systems only
Explanation An ADAECS error occurred. Please check for an accompanying ADAN7A message with further information.

Response 106

Origin Mainframe systems only
Explanation The prefetch table record buffer specified in the UDB is too small.

Response 107

Origin Mainframe systems only
Explanation Either a GETMAIN error occurred or there was insufficient space when performing prefetch. Prefetch is switched off.

Response 109

Origin Mainframe systems only
Explanation The specified command ID is already active on another database for this user.

Response 110

Origin Mainframe systems only
Explanation The command ID pool is full.
Action Increase the size of either or both the ADARUN NQCID or NU parameters.

Response 113

Origin Mainframe and open systems
Explanation The specified ISN was invalid for one of the following reasons:

- An HI command was issued with ISN less than MINISN or with an ISN equal to zero (0).
- An N2 command was issued with ISN equal to 0 or larger than the MAXISN in effect for the file.
- An N2 command was issued and the specified ISN was assigned to another record in the file.
- An A1, L1/L4, or S1/S2/S4 (with FB) command was issued for a nonexistent ISN, or an E1 command for a nonexistent ISN other than zero.
- An L3/L6 command found an ISN in the index which did not exist in the address converter.
- An N1/N2 command tried to access a file protected by security-by-value, but the command user is not authorized to access the file.
- A read or update command tried to access a multiclient file's record using either a blank or incorrect-length owner ID, or an owner ID that does not apply to the record.
- An RI command was issued for a record that has been updated earlier in the same transaction. The record cannot be released from hold status prior to transaction end. Subcode 5 is issued for this reason.
- Subcode 19 is given when a base file record is not found in the address converter (AC). At the end of a LOB update in the LOBfile, the associated base file record no longer existed.
- Subcode 249 is given only when Adabas Vista is in use. Refer to the Adabas Vista documentation for more information.

Open Systems

On open systems, the following subcodes may occur:

Subcode	Meaning
249 (0x00F9)	An invalid ISN was detected by Adabas Vista (open systems). The ISN specified for an E1, HI or L1 command is not consistent with the definitions for the partitioned file. <i>Action:</i> Review the program logic

Action Correct the ISN problem and try again.

Response 114

Origin Mainframe and open systems

Explanation A refresh file function using the E1 command was issued (E1 with ISN=0), and one of the following situations has occurred.

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following subcodes may be present:

Subcode	Description
1	A file refresh is not permitted for the file because either <ul style="list-style-type: none"> ■ the file parameter setting is PGMREFRESH=NO (can be checked with ADAREP or via Adabas Online Services (AOS) Display File) ■ or the command ID field (ACBCID or ACBXCID) is not all blanks.
2	The user has not completed transactions to the file. Updates have been performed or records are still in hold, but the user has not issued an ET or BT command to commit or back out the updates.
3	Other users are accessing or updating the file. This is determined by the user access or update counts available internally to Adabas.
4	The file is a multiclient file and the user is not a superuser.

Open Systems

One of the following situations has occurred:

- PGM_REFRESH is not specified for the file.
- The user session is not at ET status.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

If you forgot to specify the ISN for the E1 command, the CID setting is incorrect, the command was not issued at ET status or the user is no superuser: correct your program accordingly.

If other users are accessing or updating the file STOP these users.

If PGMREFRESH=YES was not specified for the file in question, specify PGMREFRESH=YES for the file with ADADBS or Adabas Online Services (AOS) or load the file with the appropriate ADALOD parameter.

Open Systems

If you forgot to specify the ISN for the E1 command, or the command was not issued at ET status, correct your program. If PGM_REFRESH was not specified for the file in question, specify PGM_REFRESH for the file with ADADBM.

Response 123

Origin

Mainframe systems only

Explanation

An error was reported by the Adabas cluster messaging service on the sender's side. The message was not sent. One of the following subcodes may be present:

Subcode	Meaning
4	No valid destination(s)
8	Too many destinations
12	Invalid message type
16	Invalid environment
20	Send buffer length exceeded
24	Receive buffer length exceeded
28	No replies or acknowledgment(s) before the message timed out. For more information about the timeout value, refer to descriptions of the ADARUN MXMSG parameter.
32	Unable to allocate AXMCB
36	Timed out on originating system
40	Timed out on destination system
44	Canceled on destination system
48	Receive error on destination system
52	Unable to allocate buffer
56	Too many buffer elements
80	Messaging is inactive
96	Terminate member unsuccessful
128	Other Trans- <u>port</u> service error

Action If you are unable to resolve the problem, contact your Software AG technical support representative.

Response 124

Origin Mainframe systems only

Explanation An error was reported by the Adabas cluster messaging service on the receiver's side. The message was sent. One of the subcodes described for response code 123 (ADARSP123) may be present.

Action If you are unable to resolve the problem, contact your Software AG technical support representative.

Response 125

Origin Mainframe systems only

Explanation An internal error occurred when one cluster nucleus attempted to issue an internucleus command to one or more of the other cluster nuclei. This condition usually leads to abnormal termination.

Action Contact your Software AG technical support representative.

Response 126

Origin Mainframe systems only

Explanation A messaging error occurred during internucleus communication:

- The nucleus did not respond within the allotted time (see the ADARUN MXMSG parameter); or
- One or more problems occurred in what could be a broadcast; that is, a communication with multiple targets. In this case, each individual ACB contains either response code 0 (ADARSP000) or 123 (ADARSP123) or 124 (ADARSP124).

Action If you are unable to resolve the problem, contact your Software AG technical support representative.

Response 129

Origin Mainframe systems only

Explanation In an Adabas cluster environment, the user attempted to perform an Adabas function that is not yet supported by Adabas cluster nuclei.

Response 130

Origin Mainframe systems only

Explanation An error identified by one of the following subcodes occurred in an Adabas cluster environment:

Subcode	Description
1	A user table entry (UTE/PLXUSER) was not found in the MPM 8 call. This may indicate that a command was directed to an Adabas Cluster Services or Adabas Parallel Services nucleus ID (NUCID), not the DBID.
2	A user table entry (UTE/PLXUSER) was not found in the MPM 12 call.
9	The associated PLXUSER(UTE) was unsuitable at command initiation. One possibility is that the UQE of the user was deleted between the time the user's command was routed to one nucleus in the cluster and the time that nucleus selected the command for processing. Another possibility is that the PLXUSER and UQE UID string did not match because the PLXUSER may have been released and possibly reassigned to another user.
10	The associated PLXUSER(UTE) was unsuitable at command completion. The PLXUSER and UQE UID string did not match because the PLXUSER may have been released and possibly reassigned to another user.
11	No Work data set entry in active PPT block (bad PPT block).
12	Invalid internal NUCID (internal error) - accompanied by message ADAX3E.
13	Invalid external NUCID (bad PPT block, internal error) - accompanied by message ADAX3F.
14	Work data set already open for same internal NUCID, other external NUCID - accompanied by message ADAX3G.
15	Work data set already open for same external NUCID, other internal NUCID - accompanied by message ADAX3H.
16	Different Work data set already open for same peer nucleus - accompanied by message ADAX37.
17	Work data set of peer nucleus could not be opened - accompanied by message ADAX32.
18	I/O error when trying to read Work data set of peer nucleus - accompanied by message ADAX3C.
19	Unexpected (invalid) data in Work data set of peer nucleus - accompanied by message ADAX3D.
20	Mismatching DBID in Work data set.
21	Mismatching Adabas version indicator in Work data set.
22	Work data set written by non-cluster nucleus.
23	Partially written block in Work data set protection data extension area - accompanied by message ADAX5H.

Action For subcode 1, correct the application program attempting to issue commands using the NUCID. If that is not the case, or for other subcodes, contact your Software AG technical support representative for assistance.

Response 131

Origin Mainframe systems only

Explanation In most cases this response code will be given to the user in the URBRRSP field of the URBR block with the subcode in the URBRSUB field. The subcode appears either in the low-order (rightmost) two bytes of the additions 2 field or in the URBRSUB field. It indicates the specific cause and action for this response code. The following are the subcodes and their meanings:

Subcode	Meaning
1	The combination of URBD plus payload data does not fit in the output buffer. <i>Action:</i> Change the subscription definition to make the record shorter.
2	The subscription user exit set a value in URBREERRC. <i>Action:</i> Check the URBREERRC field and correct the error if appropriate.
3	There is insufficient space in the nucleus replication pool. In other words, the value specified by LRPL has been exceeded. <i>Action:</i> Increase the LRPL size of the nucleus and try again.
4	There is insufficient space in the Event Replicator Server replication pool. In other words, the value specified by LRPL has been exceeded. <i>Action:</i> Increase the size of the LRPL parameter and try again.
5	The subscription user exit modified data length (URBDLEND) to an invalid value. <i>Action:</i> Check the subscription user exit.
6	The response destination (URBIRNAM) specified in a client request is undefined or not usable for sending the response. <i>Action:</i> Correct the status request to specify the name of an existing destination definition.
7	Both the subscription (URBISNAM) and the destination (URBIDNAM) to be specified in a status request are missing. At least one of them must be specified. <i>Action:</i> Correct the status request.
8	The subscription (URBISNAM) specified in a status request is undefined. <i>Action:</i> Correct the status request.

Subcode	Meaning
9	<p>The initial state name specified was not found.</p> <p><i>Action:</i> Correct the initial-state request.</p>
10	<p>The destination for response in URBI following URBI 1 is not equal to those of URBI 1.</p> <p><i>Action:</i> Correct the initial-state request.</p>
11	<p>The initial state name in URBI following URBI 1 is not equal to that of URBI 1.</p> <p><i>Action:</i> Correct the initial-state request.</p>
12	<p>The combination of DBID and file specified in the initial-state request is not found in the initial-state definition.</p> <p><i>Action:</i> Correct the initial-state request.</p>
14	<p>Not all combinations of DBID and file are specified in the initial-state request. A URBI must be sent for each DBID/file specified in the initial-state definition.</p> <p><i>Action:</i> Correct the initial-state request.</p>
15	<p>Field URBILEND is invalid.</p> <p><i>Action:</i> Correct the initial-state request.</p>
16	<p>The specified ISNLIST is invalid.</p> <p><i>Action:</i> Correct the initial-state request.</p>
17	<p>The initial-state process has been stopped by an operator request.</p> <p><i>Action:</i> No action is required.</p>
18	<p>Different request tokens have been specified in different URBI elements in the same message.</p> <p><i>Action:</i> Correct the initial-state request.</p>
19	<p>Selection data is not allowed for an initial-state definition for all records or for destination open/close client requests.</p> <p><i>Action:</i> Correct the initial-state or destination open/close client request.</p>
20	<p>Invalid input data for decompression was found during the subscription phase.</p> <p><i>Action:</i> Check the index of the replicated file.</p>
22	<p>The file/DBID supplied for the initial-state process is deactivated for replication.</p> <p><i>Action:</i> Check the cause of deactivation and repeat the request after reactivation.</p>

Subcode	Meaning
23	<p>Invalid UES parameter in URBI . URBIARC, URBIACOD, and URBIWCOD must contain invalid values and must not be all blanks.</p> <p><i>Action:</i> Verify that the URBIARC, URBIACOD, and URBIWCOD elements are not all blanks.</p>
24	<p>Invalid UES parameter in URBI.</p> <p>URBIARC, URBIACOD and URBIWCOD must be zero for input requests where encoding and architecture is not evaluated -- that is, for status requests, destination open/close requests, "initial state all records" or "initial state ISN list" requests.</p> <p><i>Action:</i> The URBIARC, URBIACOD, and URBIWCOD elements must be zeros for "initial state all records" requests, "initial state ISN list" requests, status requests, or destination open/close requests. Verify that this is the case.</p>
25	<p>The unused URBIRES1 and URBIRES2 fields must contain binary zeros for all requests.</p> <p><i>Action:</i> Verify that these fields contain binary zeros.</p>
26	<p>The destination (URBIDNAM) specified in a client request is either undefined or not usable for sending the response.</p> <p><i>Action:</i> Correct the client request.</p>
27	<p>No active destinations for status request.</p> <p><i>Action:</i> No action is required.</p>
28	<p>An initial-state request was issued to an Event Replicator Server address space that was terminating as a result of an ADAEND or HALT command. An initial-state request may only be issued when the Event Replicator Server is active.</p> <p><i>Action:</i> Reissue the initial-state request when the Event Replicator Server has been restarted.</p>
30	<p>Unknown response destination name in URBIRNAM for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
31	<p>Unknown destination name in URBIDNAM for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
32	<p>Unknown or omitted subscription name in URBISNAM for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>

Subcode	Meaning
33	<p>Destination in URBIDNAM is not related to subscription in URBISNAM for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
34	<p>Subscription in URBISNAM has no resend buffer defined for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
35	<p>Transaction in URBITSNR for subscription in URBISNAM was not found in the resend buffer. The transaction may have been overwritten in the circular resend buffer.</p> <p><i>Action:</i> Check the source of the transaction number.</p>
36	<p>The subscription in URBISNAM is not active.</p> <p><i>Action:</i> No action is required.</p>
37	<p>An invalid transaction was found in the resend buffer. This is an internal error.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>
38	<p>There are no active destinations for a prior-transaction request.</p> <p><i>Action:</i> No action is required.</p>
39	<p>URBILEND must be zero for prior-transaction requests.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
40	<p>URBIDBID and URBIFNR may not be specified for this type of client request.</p> <p><i>Action:</i> Correct the client request.</p>
41	<p>URBIINAM may not be specified for prior-transaction requests.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
42	<p>UES parameters URBIARC, URBIACOD and URBIWCOD may not be specified for prior-transaction requests.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
43	<p>Reserved fields URBIRES1 and URBIRES2 must be zero for prior-transaction requests.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
44	<p>Number of active concurrent initial-state requests exceeded IMAXREQ.</p> <p><i>Action:</i> Increase the IMAXREQ setting or reduce the number of active concurrent initial-state requests.</p>

Subcode	Meaning
45	Input request URBH eyecatcher is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
46	Input request URBHLEN is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
47	Input request URBHBORD is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
48	Input request URBHVERS is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
49	Input request message truncated. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
50	Input request URBHLENT is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
51	Input request URBILENH is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
52	Input request URBILEND is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
53	Input request URBILEN is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .

Subcode	Meaning
54	<p>Input request reserved area is not zero.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
55	<p>Input request more than one status received.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
56	<p>Input request invalid URBI request received.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
57	<p>Input request different interleaved requests received.</p> <p><i>Action:</i> Verify that you are submitting only one kind of request to the Event Replicator Server. Only one type can be submitted at a time (for example, you cannot request initial-state processing and transaction status information requests in the same message).</p> <p>Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
58	<p>Invalid destination for response.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
59	<p>A replay request was issued for a database not defined to the Event Replicator Server.</p> <p><i>Action:</i> Correct the DBID in the replay request or define the database to the Event Replicator Server.</p>
60	<p>Invalid replay token. The replay token is not defined or is outdated.</p> <p><i>Action:</i> Specify a valid replay token.</p>
61	<p>Invalid request sent to Event Replicator Server. RBL is insufficient, no FB provided on Init handshake or other such errors.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>
62	<p>After an Adabas failure and session autorestart, replication data was recovered for which a matching FDT was no longer available. The FDT had been changed or deleted by a utility operation. Adabas suppressed the record images of the replicated records, because without a matching FDT, the Event Replicator Server could not process them.</p>

Subcode	Meaning
	<i>Action:</i> Use application-specific means to bring the replicated data in sync again, if necessary.
63	The file specified in a C5 command with R-option is not replicated. <i>Action:</i> Specify the file number of a replicated file.
64	The filter defines a comparison between two field types for which a comparison is invalid. <i>Action:</i> Correct the filter definition.
65	The filter refers to a field that is not defined in the internal format buffer. <i>Action:</i> Correct the filter definition or define the field in the database.
66	The filter defines a comparison against a field that is not selectable as it has no type (for example, a superdescriptor). <i>Action:</i> Correct the filter definition.
67	The filter uses values in an FLIST specification that are invalid or out of range. <i>Action:</i> Correct the filter definition.
69	Replay for same DBID/FNR already running.
71	Date/time format or value incorrect for replay. <i>Action:</i> Check the syntax of the specified date and time values. Do not specify future date and time values.
72	Incorrect replay parameters. <i>Action:</i> Check and correct the specified replay parameters.
73	A subscription involved in the replay was inactive at the beginning of replay processing or was deactivated while the replay was running. <i>Action:</i> Reactivate the deactivated subscription and rerun the replay process for the subscription.
74	A destination involved in the replay was inactive at the beginning of replay processing or was deactivated while the replay was running. <i>Action:</i> Reactivate the deactivated destination and rerun the replay process for the destination.
75	A replay destination that was defined without SLOG was closed at the beginning of replay processing or while the replay was running. <i>Action:</i> Reopen the closed destination and rerun the replay process for the destination.

Subcode	Meaning
76	<p>ADARPL terminated abnormally.</p> <p><i>Action:</i> Investigate the cause of the error, correct it, and run a new replay job.</p>
77	<p>Invalid replay status transition. Events that change the status of a replay process occurred in an unexpected order.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>
78	<p>New transactions from Adabas could not be kept on hold during a replay in synchronized mode.</p> <p><i>Action:</i> Run a new replay process involving the same subscriptions and destinations as the previous replay process to recover the replication data that Adabas produced while the first replay was running.</p>
79	<p>A replay process was canceled by a user (RPLCLEANUP operator command).</p> <p><i>Action:</i> If appropriate, run another replay job with corrected parameters.</p>
80	<p>A timeout occurred while the Event Replicator Server was waiting for the end of a synchronization process after reactivating replication for a file in Adabas. The synchronization process ends when all transactions have finished that had updated the file before it was reactivated.</p> <p><i>Action:</i> Wait until the Event Replicator Server reports the activation of the file (ADAF2L message). Then run a new replay job.</p>
81	<p>A utility other than ADARPL specified a replay token when connecting to the Event Replicator Server.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>
82	<p>The Event Replicator Server is not connected to Adabas at the start of a replay process with the TOKEN parameter.</p> <p><i>Action:</i> Start Adabas and let it connect to the Event Replicator Server. When running a replay with the TOKEN parameter, Adabas must be active.</p>
83	<p>Neither a subscription nor a destination was specified in a replay request.</p> <p><i>Action:</i> Specify at least one subscription or destination.</p>
84	<p>A replay in replay-only mode was requested, but replication data from Adabas would flow through an active subscription-destination pair involved in the replay. For a replay in replay-only mode, some subscriptions and destinations must be inactive such that no data from Adabas can flow through the same subscription-destination pairs as the replay data from ADARPL.</p> <p><i>Action:</i> Change the replay parameters or the activation status of the subscriptions or destinations involved in the replay.</p>

Subcode	Meaning
85	<p>A file involved in the replay was inactive at the beginning of the replay or deactivated while the replay was running.</p> <p><i>Action:</i> Reactivate the deactivated file and rerun the replay process for the subscriptions involved in the replay that get data from the file.</p>
86	<p>Invalid format buffer was specified for destination-type Adabas update commands.</p> <p><i>Action:</i> Correct the format buffer.</p>
87	<p>An unexpected message sequence number was encountered.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
88	<p>An unrecognized eye-catcher was encountered in control block following the URBH.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
89	<p>The same subscription name was specified more than once for an Adabas automated replay (defined using the Adabas Event Replicator Subsystem).</p> <p><i>Action:</i> Verify that a subscription is specified only once in an automated replay, and try again.</p>
90	<p>The same destination name was specified more than once for an Adabas automated replay (defined using the Adabas Event Replicator Subsystem).</p> <p><i>Action:</i> Verify that a destination is specified only once in an automated replay, and try again.</p>
91	<p>The replay start date and time were not supplied for an automated replay (defined using the Adabas Event Replicator Subsystem) or for multiple destination open/close client requests.</p> <p><i>Action:</i> Verify that a destination is specified only once in an automated replay or in multiple destination open/close client requests and try again.</p>
92	<p>The timeout parameter specified for an automated replay was too high.</p> <p><i>Action:</i> Reduce the timeout parameter value and try again.</p>
93	<p>PLOG information was not recorded in the Event Replicator Server system file.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
94	<p>The AI/BI format buffer was used also for the key. An attempt was made to decompress a key value, but the related format buffer is for data storage and not for a key.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>

Subcode	Meaning
95	<p>An attempt to set user/Event Replicator Server encoding 01-RPEQU * failed. This might occur if you are using enhanced filtering logic and UES SACODE/SWCODE/SARC values are set for a subscription.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
96	<p>The Adabas nucleus that was the target of an initial-state request returned response code 148 (ADARSP148), indicating it is not available.</p> <p><i>Action:</i> Start the targeted Adabas nucleus and retry the initial-state request.</p>
97	<p>A format buffer was specified which contains a LOB field, which is not supported.</p> <p><i>Action:</i> Correct the format buffer.</p>
99	<p>The subscription name (URBISNAM) specified in the destination open/close client request contains a value other than spaces.</p> <p><i>Action:</i> Correct the destination open/close client request by setting this field to spaces.</p>
100	<p>The transaction sequence number (URBITSNR) specified in a destination open/close client request contains a value other than binary zeroes.</p> <p><i>Action:</i> Correct the destination open/close client request by setting this field to binary zeroes.</p>
101	<p>The destination open/close request failed on some tasks.</p> <p><i>Action:</i> Investigate the cause of the error.</p>
102	<p>The destination open/close request failed.</p> <p><i>Action:</i> Investigate the cause of the error.</p>
103	<p>The destination open/close request was not performed because the destination's status was already in the state being requested. In other words, the destination was already opened or closed.</p> <p><i>Action:</i> No action is required.</p>
104	<p>Begin byte in field filter is longer than the field length.</p> <p><i>Action:</i> Adjust the specifications for the beginning byte or length and try again.</p>
105	<p>Begin byte plus the portion length in the field filter is longer than the field length.</p> <p><i>Action:</i> Adjust the specifications for the beginning byte or the portion length and try again.</p>

Subcode	Meaning
106	Begin byte or length not supported for field with format U, P, F, G, or W. <i>Action:</i> Specifying a beginning byte or length is only supported for alphanumeric and binary fields. Change the field on which you are working or abandon this attempt.
107	Length value invalid for field. <i>Action:</i> Adjust the length specification and try again.
108	Input request URBI eyecatcher is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
109	An Adabas security (ADASCR) function has been invalidly replicated to a subscription file defined with SFSECURITYFILE=NO. <i>Action:</i> Ensure the subscription file definition used for the security file is defined with SFSECURITYFILE=YES.
110	An invalid Adabas security (ADASCR) pseudo transaction has been replicated to the Event Replicator Server. <i>Action:</i> Contact your Software AG technical support representative for assistance.
111	A replicated record (e.g., delete, insert, refresh, or update) has been invalidly replicated to a subscription file defined with SFSECURITYFILE=YES. <i>Action:</i> Ensure that the subscription file definitions for a file, other than a security file, is defined with SFSECURITYFILE=NO.
118	Replay-Only Replay is not allowed if one or more destinations involved are closed. <i>Action:</i> Ensure that the destination(s) selected for replay-only mode replay processing are not closed.

Action Perform the action provided for the appropriate subcode in the subcode table.

Response 132

Origin Mainframe and open system

Explanation The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

This response code indicates that an error occurred while Adabas was reading or updating a *LOB file*. The subcode indicates the kind of error.

If the subcode is less than 256, it is the same as the original response code that occurred during LOB file processing. The most likely subcodes are listed in the table below. For subcodes not listed, see the description of the Adabas response code with the same value.

If the subcode is greater than 256, it signals an error condition unique to the processing of LOB files. These subcodes are listed in the table below.

Subcode	Description
8	A LOB file operation was aborted due to a pending backout of the user's command or transaction. One reason for this backout may be that the user's transaction occupied too much space on the protection area on the Work data set (see response code 9 (ADARSP009), subcode 15).
17	The LOB file is not loaded.
48	The LOB file is locked for exclusive read or update by another user.
65	An internal error in the work pool space calculation occurred for LOB file processing.
113	A LOB file segment record was not found in the Address Converter element referred to by the LOB file index. Either the LOB file is physically inconsistent or an illegal concurrent LOB file update occurred during the LOB file read operation.
145	An attempt failed to put a LOB file segment record on hold for a user, because it was already held by another user. This subcode indicates illegal update contention for the same large object field value. The base file-LOB file pair is possibly inconsistent.
165	The LOB file descriptor is not found in the index; The LOB file index is bad.
172	An ISN in the LOB file index is bad. The LOB file may be physically inconsistent.
175	The descriptor value in a LOB file segment record differs from the descriptor value in the LOB file index. Either the LOB file is physically inconsistent or an illegal concurrent LOB file update occurred during the LOB file read operation.
177	A LOB file segment record was not found in the Data Storage block referred to by the Address Converter. Either the LOB file is physically inconsistent or an illegal concurrent LOB file update occurred during the LOB read operation.
257	An error in the base file-LOB file linkage exists; a file with LB fields is not really the <i>base file</i> of the <i>LOB group</i> .
258	An error in the base file-LOB file linkage exists; the file linked to the base file of a LOB group is not really a LOB file.
259	An error in the base file-LOB file linkage exists; the LOB file linked to a base file of a LOB group refers back to a different base file (or none at all).
260	An error in the base file-LOB file linkage exists; either no LOB file was linked to a base file or the LOB file number is invalid.

Subcode	Description
261	The LOB file has been left in an inconsistent state by an aborted utility execution.
262	An LB field length element specification error occurred in the format buffer ('xxL,4,B' was expected).
263	An invalid LOB file segment descriptor was encountered. The set of LOB file segment records associated with one LB field value is inconsistent. Either the LOB file is bad or an illegal concurrent LOB file update occurred during the LOB file read operation.
264	An invalid LOB file segment record was encountered. The contents of a LOB file record are inconsistent. The LOB file is bad.
265	The length of an LB field value in the LOB file differs from the length stored in the associated base file record. Either the base file and the LOB file are out-of-sync or an illegal concurrent LOB file update occurred during the LOB file read operation.
266	A bad LB field value reference was encountered in a base file record. The base file is bad.
267	An LB field value referred to in a base file record is not present in the LOB file. Probably, the base file and the LOB file are out-of-sync.
268	Internal LOB update error. At the end of a LOB update in the LOB file, the LOB value reference or placeholder was not found in the associated base file record where it was expected. Possibly, the base file record was changed in parallel.
270	Internal LOB update error. At the end of a LOB update in the LOB file, the base record was not in exclusive hold status anymore.
297	A planned feature for large object (LB) fields (for example, character code conversion of LB field values) is not yet supported.
298	Too many (more than 32,767) LB field occurrences were specified in the format buffer.
299	An internal error occurred due to LOB file processing.

Open Systems

LOB data processing may fail because of concurrent updates. If a new attempt to process the LOB data also fails, this response code is returned. The subcode (field ACBXERRC in the ACBX) provides more information:

Subcode	Description
297	A planned feature for large object (LB) fields (for example, character code conversion of LB field values) is not yet supported.
300	The referential integrity and uniqueness checks done by subtransactions are currently not compatible with commands that modify LOB values.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Resolve the problem described in the subcode list in the explanation.

Open Systems

If one of the subcodes above occurs, you must change the program that is making the Adabas calls.

If the subcode (field ACBXERRC in the ACBX) is not one of the subcodes mentioned above, and if the response code 132 is reproducible even though the accessed LOB fields are not being updated, contact your Software AG technical support representative.

Response 133

Origin Mainframe systems only

Explanation An error was detected when an attempt was made to replicate a compressed record. The subcode identifies the kind of error.

Subcode	Description
1	The function is not permitted for this type of file. The file is a LOB-file.
2	The compressed input record length is invalid .
11	The record structure is invalid.
12	An invalid elementary empty field was encountered. The structure does not agree with the FDT definition.
13	An invalid multiple-field count was encountered.
14	An invalid periodic group count was encountered.
15	An invalid structure of an elementary field was encountered.
65	A space calculation error occurred.

Response 134

Origin Mainframe systems only

Explanation An error was detected when creating system fields. The subcode identifies the kind of error.

Subcode	Description
1	An invalid update parameter was encountered (logic error).
2	The field is not a system field.
4	The file does not support a setting of MUPEX=2 (number of MU occurrences greater than 191).

Response 136**Origin**

Mainframe systems only

Explanation

This response code is used for communication with Adabas utilities and Adabas Audit Administration (SYSALAA) or Adabas Online System (AOS). The system returns this error because the requested function could not be performed on the Adabas system and its files, or because an error occurred in a SYSALAA/AOS or utility function.

Action

For SYSALAA/AOS, a subcode is displayed in the error message or a descriptive message indicates the error that occurred. For utility functions, the subcodes may be described within the message text or a descriptive message indicates the error that occurred. If you do not understand the action to take, note the subcode and the function that caused the response code and call your Software AG technical support representative for assistance.

Response 144**Origin**

Mainframe and open systems

Explanation

One of the following occurred:

- The ISN specified with an update (A1) command was not in hold status for the user and command option H was not specified.
- An ET or BT command specifying the M (multifetch) option specified an ISN in the ISN buffer that is not in hold status for the user. All currently held ISNs are released from hold status.

In this case on open systems, the first 2 bytes of the Additions 2 field (in binary format) contain the offset of that ISN in the ISN buffer.

Action

Put the ISN in hold status before using the A1 command or the multifetch ET or BT commands.

If Adabas Transaction Manager is in use, verify that the setting for the Transaction Model parameter is appropriate for the program that was executing and is also appropriate for the runtime environment in use.

Response 145

Origin Mainframe and open system

Explanation The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

On mainframe systems, one of the following situations occurred:

- An N1/N2 command was issued, but no hold queue entry was available.
- A command was issued with the return option specified that attempted to hold an ISN already in the hold queue for another user. The command is not placed in wait status.

Use the subcode associated with this response code to further clarify why this response occurred.

Subcode	Meaning
0	N2 command for an existing ISN was issued.
1	Hold queue space problem detected. The user is the only active user and is running with the -R option.
2	The ISN was held by someone else. The read request is running with the -R option.
8	The hold status of a record could not be upgraded from shared to exclusive because another user was already waiting to do the same. The two users became deadlocked.
9	Two or more users became deadlocked while holding ISNs and attempting to put more ISNs in hold status.

Open Systems

On open systems, one of the following situations occurred:

- An attempt was made to insert a record using an N2 command with an ISN that is in hold status.
- An attempt was made to hold an ISN which was in hold status for another user and the R option is specified. In this case, the Additions 2 field contains the binary value 0;
- Hold queue overflow. In this case, the Additions 2 field contains a value not equal to 0.

Note: This hold queue overflow error can only occur with Adabas versions < 5.1.

Response 146

Origin Mainframe and open systems

Explanation The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

An invalid buffer length was detected by the Adabas interface routine. If the command uses a classic ACB, the buffer is larger than 32,767. If the command uses an ACBX, the buffer is greater than 2,147,483,647, or the send length in the ABD is greater than the buffer length. The subcode identifies the buffer type:

Subcode	Buffer Type
1	Format buffer
2	Record buffer
3	Search buffer
4	Value buffer
5	ISN buffer
6	User information buffer
7	Performance buffer
8	Multifetch buffer

Open Systems

An invalid buffer length was detected by the Adabas interface routine, in an MC call, or one of the following errors occurred for a multifetch command:

- the buffer header was invalid (both offsets are set)
- at least one ISN buffer offset was not divisible by 4
- the start offset was outside the multicall buffer range
- the record buffer was not large enough to contain all subcommand control blocks.

The value in the Additions 2 field identifies the buffer: the first 2 bytes contain the buffer number in binary format, the last two bytes contain the buffer name, as shown in the following table:

Bytes 1-2	Bytes 3-4
1	FB (format buffer)
2	RB (record buffer)
3	SB (search buffer)
4	VB (value buffer)
5	IB (ISN buffer)

Action Correct the buffer length and try again.

Response 147

Origin Mainframe and open systems

Explanation The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The ISN was invalid. The ISN transformation resulted in a negative ISN or an ISN greater than the maximum ISN permitted for the file.

Open Systems

A user buffer is not accessible by the Adabas interface routine.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Open Systems

Check whether the control block, format buffer, value buffer, record buffer and ISN buffer have valid addresses and lengths. Check whether the control block, ISN buffer and record buffer are write-protected.

Response 148

Origin Mainframe and open systems

Explanation The Adabas nucleus was either not active or not accessible (a call could not be sent to the Adabas nucleus when the command was issued). In an ACB, refer to the hexadecimal subcode that appears in the low-order (rightmost) two bytes of the Additions 2 field; in an ACBX, refer to the binary subcode that appears in the Error Subcode (ACBXERRC) field.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

The following are the decimal equivalents of the subcodes and their meanings:

Subcode	Occurrence Location	Description	Action
0	open systems	No active database server was found, either local or remote.	Start the nucleus and reissue the command.
1	mainframe systems	Exclusive database control requirement conflicts with read-only nucleus status.	Remove the READONLY=YES parameter setting for the nucleus and restart it.

Subcode	Occurrence Location	Description	Action
2	mainframe systems	A nonprivileged call was made to the nucleus while it was in utility-only (UTI) mode.	Remove the UTIONLY=YES parameter setting for the nucleus and restart it.
3	mainframe and open systems	The nucleus is performing shutdown processing (an ADAEND operation) and will not accept new users or new transactions. Either a new user is attempting to begin operation or an existing user in ET status is trying to continue operation.	Wait for the nucleus to shut down, restart it, and reissue the command.
4	mainframe systems	A utility with exclusive database control is running.	Either stop the utility or wait for its processing to complete (this is preferred) and try again.
5	mainframe systems	A single-user nucleus could not start operation due to an error that could not be corrected.	Verify that single-user mode has been set up correctly and restart the nucleus.
8	mainframe systems	A user is performing a logical ADALNK call. The IDT for the call has not been allocated.	On BS2000 systems, check the setting of the parameter accessed by the link name DDLNKPAR or DDCARD, or in the macro B2CONFIG of the module SSFB2C. Also check the IDTNAME parameter of the database to be accessed.
21	open systems	Entire Net-Work access communication has failed. The first two bytes of the Additions 2 field contain an error number.	Refer to your Entire Net-Work documentation for further information.
22	open systems	There is a problem with the Adabas IPC (Interprocess communication) driver. The first two bytes of the Additions 2 field contain an error number.	Shut down the nucleus, if it is still active, and restart it. If the error still occurs, try issuing the command <code>showipc -kd <dbid></code> , then restart the nucleus and reissue the command.
23	Adabas open systems version 3.1 only	There is a problem attaching the Adabas IPC (Interprocess communication) driver's shared memory	Shut down the nucleus, if it is still active, and restart it. If the error still occurs, try issuing the command <code>showipc -kd <dbid></code> ,

Subcode	Occurrence Location	Description	Action
			then restart the nucleus and reissue the command.
24	open systems	The ADALNK shared library cannot be loaded correctly.	Check the locations and permissions of the ADALNK shared library.
26	open systems	An IPC (Interprocess communication) problem occurred during open processing, e.g. the shared memory could not be attached.	One reason for these messages may be that someone has deleted an IPC resource. If this is the case, shut down the nucleus, if it is still active, and restart it.
27	open systems	An IPC (Interprocess communication) problem occurred during a read in the message queue.	If the error still occurs, try issuing the command <code>showipc -kd <dbid></code> , then restart the nucleus and reissue the command.
28	open systems	An IPC (Interprocess communication) problem occurred during a write in the message queue.	Another reason these messages may occur may be that the IPC resources are not sufficient. In this case, increase the IPC resources, or decrease the values of some nucleus parameters on which the required amount of IPC resources depends., or stop some other process that also consumes IPC resources. For more information about IPC resources, refer to the section <i>Increasing System V IPC Resources</i> in the Adabas open systems installation documentation.
29	UNIX platforms only	IPC (Interprocess communication) resources exist, but the database server was not active.	Issue the command <code>showipc -kd <dbid></code> , restart the nucleus, and reissue the command.
50	mainframe systems	At command completion RSP148 was set but without a subcode. This subcode is set to indicate the command was processed by the target. This often occurs in a Cluster or Parallel Services	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
		environment when one of the targets is no longer active.	
51	mainframe systems	The command router found no suitable target. The target was determined not to be an Adabas Cluster Services or Adabas Parallel Services database.	Contact your Software AG support representative for assistance.
52	mainframe systems	The command router found no suitable target. The target was determined to be an Adabas Cluster Services or Adabas Parallel Services database.	Contact your Software AG support representative for assistance.
53	mainframe systems	The command router found a suitable target but the target became inactive while queuing the command.	Contact your Software AG support representative for assistance.
54	mainframe systems	When the caller attempted to retrieve the results of a completed command the target was no longer active.	Contact your Software AG support representative for assistance.
55	mainframe systems	The target became inactive while the caller was attempting to retrieve the results of a completed command.	Contact your Software AG support representative for assistance.
58	mainframe systems	An error occurred while POSTing the Adabas nucleus ECB after queuing a command.	This may be seen if the nucleus is terminating. Otherwise contact your Software AG support representative for assistance.
59	mainframe systems	This subcode is set as a default in the first stage of command routing.	Contact your Software AG support representative for assistance.
61	mainframe systems	A command sent from a nucleus to another nucleus caused an ABEND while the caller was attempting to initiate the command. The target may have become inactive. The ABEND was intercepted and recovered.	This may be seen if the target nucleus is terminating. Otherwise contact your Software AG support representative for assistance.
64	mainframe systems	A command sent from a nucleus to another nucleus caused an ABEND while the caller was	This may be seen if the target nucleus is terminating. Otherwise

Subcode	Occurrence Location	Description	Action
		attempting to retrieve the results of a completed command. The target may have become inactive. The ABEND was recovered by ADAMPM.	contact your Software AG support representative for assistance.
101/201	mainframe systems	Set in SVCCLU when a specifically designated local nucleus is not available for a physical call. The 201 subcode appears when this subcode is set on a remote node. See the note on ACB(X)ADD2 for information how to identify the remote node.	Contact your Software AG support representative for assistance.
102/202	mainframe systems	Set in SVCCLU when a specifically designated remote nucleus is not available for a physical call. The 202 subcode appears when this subcode is set on a remote node. See the note on ACB(X)ADD2 for information how to identify the remote node.	Contact your Software AG support representative for assistance.
103/203	mainframe systems	Target ID disagreement between IDTE and PLXNUC. The 203 subcode appears when this subcode is set on a remote node. See the note on ACB(X)ADD2 for information how to identify the remote node.	Contact your Software AG support representative for assistance.
104/204	mainframe systems	Unable to find PLXMAP matching an existing PLXUSER. The 204 subcode appears when this subcode is set on a remote node. See the note on ACB(X)ADD2 for information how to identify the remote node.	Contact your Software AG support representative for assistance.
105/205	mainframe systems	Entire Net-Work unavailable, cannot route existing user to remote nucleus. The 205 subcode appears when this subcode is set on a remote node. See the note on ACB(X)ADD2 for information how to identify the remote node.	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
106/206	mainframe systems	Entire Net-Work unavailable, cannot route new user to remote nucleus. The 206 subcode appears when this subcode is set on a remote node. See the note on ACB(X)ADD2 for information how to identify the remote node.	Contact your Software AG support representative for assistance.
107/207	mainframe systems	No open nucleus available for a new remote user. The 207 subcode appears when this subcode is set on a remote node. See the note on ACB(X)ADD2 for information how to identify the remote node.	Contact your Software AG support representative for assistance.
108/208	mainframe systems	Incorrect PLXMAP update received by LOCAL=YES nucleus. The 208 subcode appears when this subcode is set on a remote node. See the note on ACB(X)ADD2 for information how to identify the remote node.	Contact your Software AG support representative for assistance.
109/209	mainframe systems	An internal command used to synchronize across multiple nodes was received for an Adabas Parallel Services database. Such databases may execute on only one node. Depending on intersystem communications timing this may occur as a database is changed from Adabas Cluster Services to Adabas Parallel Services. Otherwise this is a logic error.	Contact your Software AG support representative for assistance.
110/210	mainframe systems	Unable to assign specified nucleus to remote user. The physical command arrived via Entire Net-Work for a specific nucleus, but the specified nucleus is on another system. Only one Entire Net-Work transmission is allowed. The 210 subcode appears when this subcode is set on a remote node. See the note on ACB(X)ADD2 for information how to identify the remote node.	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
1019	open systems	No active database found.	Contact your Software AG support representative for assistance.
1020	open systems	The Entire Net-Work relay failed.	Contact your Software AG support representative for assistance.
1021	open systems	EC: Not XTS directory information available.	Contact your Software AG support representative for assistance.
1022	open systems	No context found.	Contact your Software AG support representative for assistance.
1023	open systems	No local database found.	Contact your Software AG support representative for assistance.
1024	open systems	Invalid context found.	Contact your Software AG support representative for assistance.
1025	open systems	General logic error; no XTS found.	Contact your Software AG support representative for assistance.
1026	open systems	A server shutdown occurred.	Contact your Software AG support representative for assistance.
1027	open systems	A server overload occurred.	Contact your Software AG support representative for assistance.
1028	open systems	The server rejected a call.	Contact your Software AG support representative for assistance.
1029	open systems	No such DBID.	Contact your Software AG support representative for assistance.
1030	open systems	The database is inactive.	Contact your Software AG support representative for assistance.
1031	open systems	No response.	Contact your Software AG support representative for assistance.
1032	open systems	An invalid protocol was found.	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
1033	open systems	An unknown response occurred.	Contact your Software AG support representative for assistance.
1034	open systems	Remote communication is not allowed.	Contact your Software AG support representative for assistance.

Action Review the user actions provided in the explanation above.

Response 149

Origin Open systems only

Explanation A communication error was detected. The Additions 2 field contains the system service completion code which caused the error response.

Subcode	Description
1035	Context allocation failed.
1036	Inconsistent architecture encountered.
1037	XTS error 149/224 occurred.

Action Contact your Software AG technical support representative for assistance.

Response 150

Origin Open systems only

Explanation Too many database nuclei have been used in parallel. The Additions 2 field contains the maximum number of nuclei allowed in parallel.

Action Do not use more database IDs in a single program than the value given in the Additions 2 field.

Response 151

Origin Mainframe and open systems

Explanation A command queue overflow occurred.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Action The DBA may increase the value of the NC parameter or the command may be issued when there is a lower level of command activity.

If you are running Entire System Server and receive this response code, your database administrator should increase the size of the NCQE parameter. For more information, refer to the startup parameter documentation included in your Entire System Server administration documentation.

Response 152

Origin Mainframe and open systems

Explanation The internal user buffer was not large enough to contain the user buffer areas.

Action On mainframe systems, the DBA should increase the value of the LU parameter used by the Entire Net-Work nucleus.

If you are running Entire System Server and receive this response code, your database administrator should increase the size of the IUBL parameter. For more information, refer to the startup parameter documentation included in your Entire System Server administration documentation.

On open systems, contact your Software AG technical support representative.

Response 153

Origin Mainframe and open systems

Explanation A second Adabas call was issued while the first one was still being processed.

Subcode	Description
1050	A thread is pending.
1051	A user ID is pending.

Action Issue only one call at a time.

Response 154

Origin Mainframe and open systems

Explanation One of the following occurred:

- The Adabas call was canceled by the user (open systems).
- The command was rejected because it resulted in a trigger being fired, but the queue is full at this time. (mainframe)

Action On open systems, no action is required for this informational message. On mainframe systems, retry the command.

Response 155

Origin	Mainframe systems only
Explanation	A command resulted in a pre-command trigger being fired. The triggered procedure returned a nonzero command, so the command was not executed.
Action	Check the Additions 4 field for the error returned from the procedure.

Response 156

Origin	Mainframe systems only
Explanation	A command resulted in a post-command trigger being fired. The triggered procedure returned a nonzero command, indicating an unsuccessful execution of the procedure.
Action	Check the Additions 4 field for the error returned from the procedure.

Response 157

Origin	Mainframe systems only
Explanation	A command resulted in either a pre- or post-command trigger being fired; however, Adabas Triggers has been shut down with the option to reject all commands that result in a trigger being fired.
Action	Determine the cause of the shut-down and resolve the problem. If rejection of commands is not the required action in such a situation, then set the error action field in the Adabas Triggers profile to halt or ignore.

Response 159

Origin	Mainframe systems only
Explanation	The Adabas link module is missing or invalid. One of the following occurred: <ul style="list-style-type: none">■ No Adabas link module is linked to the Natural nucleus and the Adabas link module specified in the Natural profile parameter ADANAME could not be loaded.■ (CICS only) The loaded Adabas link module is macro-level in a command-level only environment.
Action	Check the setting of the Natural profile parameter ADANAME and/or provide the correct version of the Adabas link module in one of the current STEPLIBs.

Response 160

Origin	Mainframe systems only
Explanation	Too many Associator and Data Storage blocks were marked as active in the buffer pool for a single command.

Response 161

Origin Mainframe systems only
Explanation The RABN chain in the header list of the Adabas buffer pool is invalid.

Response 162

Origin Mainframe and open systems
Explanation No additional space is available for the Adabas buffer pool.
Action Increase the value of the ADARUN LBP parameter.
 On open systems, because the buffer pool overflow is normally caused by too many blocks in the buffer pool waiting to be written to disk, specifying a low value for the WRITE_LIMIT parameter is recommended.

Response 163

Origin Mainframe systems only
Explanation The RABN to be linked into the RABN header chain is already in the chain.

The following table shows some of the subcodes that may be returned:

Subcode	Description
1	The RABN to be linked into the RABN header chain is already in the chain.
2	A file extent overlap exists such that the same data storage RABN has been assigned to two different files.
3	A supposedly unused data storage RABN is already in use.
4	A file extent overlap exists such that the same Associator RABN has been assigned to two different files.
5	A supposedly unused Associator RABN is already in use.

Action Contact your Software AG technical support representative for assistance.

Response 164

Origin Mainframe systems only
Explanation Too many work areas were allocated for the command.

Response 165

Origin	Mainframe and open systems
Explanation	<p>A descriptor name was either invalid or did not exist in the descriptor value table (DVT). For expanded files: the descriptor does not exist on all component files.</p> <p>On open systems, this error may occur during ADAREC generate if one of the following occurs:</p> <ul style="list-style-type: none"> ■ A file was loaded with an incorrect FDT. ■ ADAINV was not reexecuted following a stop at a SYNTP checkpoint. <p>In an ACB, the leftmost two bytes of Additions 2 may contain the descriptor name; in an ACBX, the Error Character Field (ACBXERRB) may contain the descriptor name. If this occurred for an expanded file, check to see if there is an FDT mismatch between the components of the file.</p> <p>On open systems, bytes 3 and 4 of the Additions 2 field contains the name of the descriptor that caused the error.</p>
Action	On open systems, if the error is not a handling error, run the INDEX option of ADAVFY and contact your Software AG technical support representative.

Response 166

Origin	Mainframe and open systems
Explanation	<p>An error was detected in an inverted list index; a descriptor value was not found during a delete operation. The cause may be damage in the Associator.</p> <p>On open systems, bytes 3 and 4 of the Additions 2 field contains the name of the descriptor that caused the error.</p>
Action	<p>On open systems perform the following steps:</p> <ol style="list-style-type: none"> 1. Locate the descriptor that caused the error in the Additions 2 field of the user control block; 2. Run the VERIFY option of ADAINV for this descriptor and save the output; 3. Reinvert the descriptor; 4. If necessary, restart the database (if this is possible); 5. Send the following information to your Software AG technical support representative: <ul style="list-style-type: none"> ■ The output of the VERIFY option of ADAINV; ■ All available PLOGs; ■ The FDT of the file containing the error; ■ If the nucleus crashed, the crash directory.

Response 167

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The field in a coupled file does not exist or the coupled list is invalid.

Open Systems

An error was detected in an inverted list index; a descriptor value was already present during an insert operation.

Bytes 3 and 4 of the Additions 2 field contains the name of the descriptor that caused the error.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Open Systems

Complete the following steps:

1. Locate the descriptor that caused the error in the Additions 2 field of the user control block;
2. Run the VERIFY option of ADAINV for this descriptor and save the output;
3. Reinvert the descriptor;
4. If necessary, restart the database (if this is possible);
5. Send the following information to your nearest support center:
 - The output of the VERIFY option of ADAINV;
 - All available PLOGs;
 - The FDT of the file containing the error;
 - If the nucleus crashed, the crash directory.

Response 168

Origin Mainframe systems only

Explanation An internal command ID required during coupling processing was not found.

Response 170**Origin** Mainframe and open systems**Explanation** The Adabas RABN required for the command could not be located for one of the following reasons:

- The buffer segment was called with a RABN of zero.
- The specified RABN does not belong to this database and is invalid.

On open systems, the Additions 2 field contains the invalid RABN in 4 byte binary format.

Action On open systems, run the LOST, INDEX and DATA options of ADAVFY for the file in question and contact your Software AG technical support representative.**Response 171****Origin** Mainframe systems only**Explanation** The constant set used by Adabas could not be located.**Response 172****Origin** Mainframe and open systems**Explanation** On mainframe systems, an ISN was less than the MINISN or greater than the MAXISN setting in effect for the file.

On open systems, the maximum possible ISN of the file was reached and no more can be allocated.

Action On open systems, if the file contains significantly less than 2^{32} records, you should unload the file with ADAULD and reload it with ADAMUP without USERISN. However, you must be aware that problems may arise if the ISNs have semantics for you - if, for example, you use the ISNs to reference records in this file, additional reorganization of these references will be necessary. The alternative to unloading and reloading the data is to split up your data into more than one file, and to adapt your application accordingly.**Response 173****Origin** Mainframe and open systems**Explanation** An invalid Data Storage RABN was detected.

On open systems, the Additions 2 field contains the invalid RABN in 4 byte binary format.

Action On open systems, run the DATA option of ADAVFY for the file in question and contact your Software AG technical support representative.

Response 174

Origin Mainframe systems only

Explanation For an L2/L5 command with start ISN, the Data Storage RABN stored in the address converter for the file is invalid.

Response 175

Origin Mainframe systems only

Explanation An inconsistency was detected between the index and Data Storage.

This response code can be expected when reading a descriptor value for a ciphered file if an incorrect cipher code was used.

Subcode	Meaning
99	On logical reads and simple searches without hold, the index value is compared with the value from the data record to ensure consistency. When the values do not match, the read or search is repeated in order to avoid the effects of a possible parallel update. If the values still do not match, response 175 is given.

Action Run the ADACHK utility against the file, and contact your Software AG technical support representative.

Response 176

Origin Mainframe and open systems

Explanation Either an inconsistency was detected in an inverted list or an internal error occurred during inverted list processing.

On open systems, the Additions 2 field contains the inconsistent RABN in 4-byte binary format.

On mainframe systems, the following possible subcodes are associated with this response code:

Subcode	Meaning
2	Bad index
3	Invalid search request
4	Invalid format indicator or field not found in FDT/SDT
11	Invalid search request
12	Bad index block
13	Bad UI block
14	Mismatch block length
15	Bad MI block

Subcode	Meaning
16	Mismatching block length
17	Bad NI block
18	Bad ISN count
21	Bad index block
22	Mismatching block length
23	Invalid ISN count
29	Inactive index block
31	Bad index block
32	Mismatching block length
33	Invalid ISN count
39	Inactive index block
41	Bad index block
42	Mismatching block length
43	Bad MI block
44	Bad NI block
81	Invalid level indicator
82	Bad element position in block
83	Position in block did not match element lengths
84	Bad MI block
85	Bad NI block
86	Bad NI block
87	Invalid ISN count
88	Position in block did not match element lengths
89	Index block not active
91	Wrong level
92	Mismatching block length

Action

On mainframe systems, run an appropriate ADACHK utility function to determine whether an inconsistency exists in an inverted list. If not, contact your local Software AG technical support representative. Make sure to report the subcode to your Software AG technical support representative.

On open systems, check if an autorestart or an ADAREC REGENERATE have disabled the index. If not, run the INDEX option of ADAVFY for the file in question. If the INDEX option signaled errors, you should recreate the entire inverted list with ADAINV REINVERT ALL or contact your Software AG technical support representative.

Response 177

Origin Mainframe and open systems

Explanation A record could not be found in the Data Storage block in which it should have been contained as indicated by the address converter. On mainframe systems, if this response code is returned to the ADAULD UNLOAD utility function with the parameter SORTSEQ, the file might be inconsistent and data lost.

Subcode 19 is issued because the base file record was not found in Data Storage. At the end of a LOB update in the LOB file, the associated base file record was no longer present in the data storage block.

Action On mainframe systems, check the file with the ADACHK ACCHECK utility function and contact your Software AG technical support representative.

On open systems, run the AC option of ADAVFY for the file in question and contact your Software AG technical support representative.

Response 178

Origin Mainframe systems only

Explanation An internal error occurred when updating a multiple-value field:

Subcode	Meaning
1	Inconsistency in descriptor value table (DVT).
2	An inconsistency was detected between the field definition table (FDT) and the internal format buffer.
3	Inconsistency when updating a phonetic descriptor.

Response 179

Origin Mainframe systems only

Explanation Internal error; identifier could not be found in Work part 3.

Response 181

Origin Mainframe systems only

Explanation Autobackout was executed and the start of a transaction could not be located.

Response 182

Origin Mainframe and open systems

Explanation Necessary ET data was not found in the appropriate Work block.

Action On open systems, save WORK1 and send it to your nearest Software AG technical support representative together with a description of what caused the pending autorestart and, if possible, the dump directory and the PLOG. Then restore and regenerate the database.

Response 183

Origin Mainframe systems only

Explanation An internally assigned number for a database I/O operation was detected as invalid.

Response 184

Origin Mainframe systems only

Explanation A phonetic field name could not be found.

Response 185

Origin Mainframe systems only

Explanation The ADAM field could not be found in the compressed record.

Response 186

Origin Mainframe systems only

Explanation A wrong cipher code has been specified or a compressed data record is bad (does not conform to the Field Description Table).

The leftmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field contain the field or descriptor name where the error was detected. The rightmost two bytes of the same ACB or ACBX field contain an internal code identifying the routine that detected the error.

Action If the file that was accessed when this response code occurred is ciphered, check whether the correct cipher code has been specified. Correct the cipher code, if necessary.

If the error is not due to an incorrect cipher code, run the ADACMP DECOMPRESS INFILE utility function to unload and decompress all records of the file. ADACMP will write records where it detects errors to its error dataset (DD/FEHL). Contact your Software AG technical support representative for assistance.

Response 187

Origin Mainframe systems only

Explanation The response indicates that an invalid Data Storage block was detected while locating a record by ISN. One of the following error conditions occurred:

- An invalid block length (negative) was encountered.
- An invalid record length (not positive) was encountered.
- The sum of the record lengths is not equal to the block length plus 4.

The Additions 2 field contains the Data Storage block number where the error was detected.

Action Contact your Software AG technical support representative for assistance.

Response 196

Origin Open systems only

Explanation Referential integrity has been violated. Bytes 3 and 4 of the Additions 2 field contain the name of the violated constraint. Bytes 1 and 2 of the Additions 2 field contain the reason as a two-byte binary number:

Subcode	Meaning
1	Required ISN in hold by another user
3	Maximum number of ISNs held by one user is reached
5	Check integrity mismatch, required value not found during check
7	Double update to a record within a cascade detected
8	Limit of stacked commands reached

Action Handle the referential integrity violation, for example, write an error message.

Response 197

Origin Mainframe systems only

Explanation The DEUQ pool is too small.

Action Increase the ADARUN LDEUQP parameter.

Response 198

Origin Mainframe systems only

Explanation An attempt was made to duplicate a descriptor value for a unique descriptor. In an ACB, the leftmost two bytes of the Additions 2 field may contain the descriptor name; in an ACBX, the Error Character Field (ACBXERRB) may contain the descriptor name. The following subcodes may accompany this response code:

Subcode	Meaning
1	Unique descriptor insert failed; value already exists in the index.
2	Unique descriptor insert failed; value in use by another user on this nucleus.
3	Unique descriptor insert failed; value in use by another user on another cluster nucleus.
4	Unique descriptor insert failed; the value we are attempting to insert in the NI block is already there.

Response 199**Origin**

Mainframe systems only

Explanation

An inconsistency in the inverted list index was found during an update operation. In an ACB, the leftmost two bytes of Additions 2 may contain the descriptor name; in an ACBX, the Error Character Field (ACBXERRB) may contain the descriptor name. This response code can also occur if UTYPE=EXU was specified for an ADARES BACKOUT operation that uses the sequential (SIBA) log.

Response 200**Origin**

Mainframe and open systems

Explanation

Either an invalid cipher code or an Adabas SAF Security or Adabas security violation was detected.

The command could not satisfy the necessary security checks. This response code may be accompanied by one of the following subcodes:

Subcode	Meaning
0	A standard user check failed.
1	There is no free user file cache entry for a workstation user.
2	A cross-level security check failed.
3	No security information is available for the command.
4	A timeout occurred during a workstation logon.
5	An internal SAF Kernel error occurred.
6	A failure occurred during a newcopy/restart operation. The nucleus terminates.
7	A request to make an ABS security check was not of the correct format.
8	A security violation occurred while a file was being loaded into an existing expanded file chain.
11	User is not permitted to do a SEARCH command.
12	User is not permitted to do a SEARCH command.
13	User is not permitted to do a SEARCH command.

Subcode	Meaning
14	An invalid cipher code was encountered during update.
15	User is not permitted to read FDT (LF command).
16	Remote workstation user has supplied a new password or passphrase but there is a mismatch with the old: <ul style="list-style-type: none"> ■ old password with new passphrase ■ old passphrase with new password Passwords and passphrases should not be mixed.
17	Remote workstation user has supplied a password phrase but the detected version of SAFPSEC does not support password phrases. Either: <ul style="list-style-type: none"> ■ SAFPSEC is an old version that does not support password phrases or ■ SAFPSEC is capable of supporting passphrases but has been assembled with an incorrect REL= parameter (see the installation documentation for more details)
21	User's SAF ID is unknown.
22	User's SAF ID has changed.
24	Remote workstation logon failure; user-id is not defined.
25	Remote workstation logon failure; invalid password / password phrase.
26	Remote workstation logon failure; invalid new password / new password phrase.
27	Remote workstation logon failure; user-id revoked.
28	Remote workstation logon failure; logon not allowed at this time/date.
30	A utility function-level authorization check failed. The user is not permitted to perform this utility function.
1060	Open systems ADASAF phase 1 failed.
1061	Open systems ADASAF phase 1 failed with response.
1062	Open systems ADASAF phase 2 failed.

For more information about Adabas SAF Security, read the Adabas SAF Security documentation.

Action

Resolve the security error, perhaps by simply supplying the correct password.

Response 201

Origin Mainframe and open systems
Explanation The specified password was not found.
Action Supply the correct password.

Response 202

Origin Mainframe and open systems
Explanation An attempt was made to use a file for which the user is not authorized, or the file password is being changed, or, if Adabas Security is being used, the file has attached Security By Value on this field.
Action Either correct the authorization, or retry the operation with the new password, or, if Adabas Security is being used, remove the Security By Value on the field before the operation on the file can be retried.

Response 203

Origin Mainframe systems only
Explanation An attempt was made to delete a record in a file for which the user is not authorized.

Response 204

Origin Mainframe and open systems
Explanation On mainframe systems, a password pool overflow occurred.
On open systems, the password supplied is already in use.
Action On open systems, change the password to one that is not already existing.
On mainframe systems, check and possibly increase the value specified for ADARUN LCP parameter in the Adabas nucleus.

Response 207

Origin Mainframe systems only
Explanation Adabas SAF Security completed phase 1 of logon and requested phase 2. This is an internal Adabas SAF Security and ADALNK two-phase response code for a remote workstation logon. This code is normally not displayed or presented.
For more information, read your Adabas SAF Security documentation.
Action Send a phase 2 logon request to Adabas SAF Security.

Response 208

Origin Mainframe and open systems

Explanation As an Adabas SAF Security remote user, you should execute a phase 1 logon. The logon ID and your password are sent to Adabas SAF Security. This response indicates that two-phase logon can continue.

For more information, read your Adabas SAF Security documentation.

Subcode	Meaning
1066	Open systems ADASAF phase 1 error exit.
1067	Open systems ADASAF phase 2 error exit.

Action If the user application receives this response, it is on a workstation platform that does not have the proper Adabas link routine installed. This response code is intercepted by the workstation Adabas link routine and phase 1 logon is performed.

Response 209

Origin Mainframe systems only

Explanation Adabas SAF Security detected an expired password on the server. The workstation user's password has expired. This code is normally not returned to the application. Instead the workstation user is prompted to enter a new password.

Action Create a valid password on the server for ACF2, RACF, or Top Secret. Entire Net-Work users may use the Adabas SAF Security feature.

Response 210

Origin Mainframe and open systems

Explanation On mainframe systems, a logical ID was greater than 255 (internal error).

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, a receive buffer was lost in NETRDI.

Action On open systems, the DBA may increase the value of the NAB or NC parameters in the NETRDI in the target node.

Response 211**Origin** Mainframe and open systems**Explanation** On mainframe systems, an invalid ID table index in the UB (internal error) occurred.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, a remote utility cannot be executed because OPTIONS = LOCAL_UTILITIES is set for the database.

Action On open systems, contact the DBA of the remote database.**Response 212****Origin** Mainframe and open systems**Explanation** On mainframe systems, an invalid input/output buffer was encountered for an internal command.

On open systems, a requested function is not implemented in the target architecture.

Action On open systems, execute the utility on the target node.**Response 213****Origin** Mainframe systems only**Explanation** ID table not found (SVC not properly installed).

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

The following table describes the possible subcodes that might occur if an Adabas DBID/SVC routing table error occurs:

Subcode	Meaning
16	The specified SVC number does not correspond to a currently installed SVC on the z/OS or z/VSE system. Check to be sure that the specified SVC number is correct and, if it is, ensure that an Adabas SVC is installed using that SVC number.
20	The specified SVC number corresponds to an installed SVC on the z/OS or z/VSE system, but the SVC is not an Adabas SVC. Ensure that the provided SVC number is correct and, if it is, determine why the SVC installed for that number is not an Adabas SVC for z/OS or z/VSE.

Action Inform the DBA. The Adabas installation procedure was not properly executed.

Response 214

Origin Mainframe systems only
Explanation Internal command issued from Adabas version 4 ADALNK.

Response 215

Origin Open systems only
Explanation The Adabas interface (adalnkx, adalnk, adalnknc) used by the application program, or the Entire Net-Work version used is not supported by the Adabas nucleus. For example, the Adabas nucleus Version 6.1 does not support the Adabas interface of Version 5.1. If a 32-bit version and a 64-bit version of Adabas exists for an operating system, the 64-bit nucleus does not support the Adabas interface of the 32-bit version - 32-bit applications must use the 32-bit mode Adabas interface of the 64-bit version.

Note: The compatible Entire Net-Work versions supported by an Adabas open systems version are documented in the Adabas open systems Release Notes.

Action If you are using an incompatible version of Entire Net-Work, upgrade it to a compatible version. Check the definition of the environment variable PATH (Windows) or LD_LIBRARY_PATH (UNIX). If the application has been linked with the s-bit on UNIX, it is necessary that the correct Adabas interface has been installed with \$SAG = /opt/softwareag.

Response 216

Origin Mainframe and open systems
Explanation Command rejected by user exit.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
1070	UEX_ACBX_0 command rejected.

Response 217

Origin Mainframe systems only
Explanation Command rejected by user exit.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Response 218**Origin**

Mainframe systems only

Explanation

The following table describes the subcodes that appear with this response code, clarifying why the response was received.

Subcode	Meaning
00 or 01 or 02	The UB (TP monitor user block) pool is too small. There must be at least one user block for each concurrent user. This is controlled by the TP monitor link routines. The GETMAIN for the UB failed.
13 or 15 or 17	An error has occurred during the freeing of the UB and Work areas for a TL call. This may indicate an internal product error or a TP monitor storage overlay. Contact Software AG technical support for assistance.
72	An IPC (Interprocess communication) message call parameter error occurred. This may indicate an internal product error or a TP-monitor storage overlay. Contact Software AG technical support for assistance.
73	The IPC message caller did not provide a pointer to the extended user ID block. This is probably an internal product error. Contact Software AG technical support.
74	An IPC message internal work area is corrupted. This may indicate an internal product error or a TP monitor storage overlay. Contact Software AG technical support for assistance.
75	An IPC message call parameter error occurred. This is probably an internal product problem. Contact Software AG technical support for assistance.
76	The extended user ID data provided to the IPC Message Call is either binary zeroes or blank. This is probably an internal product error. Contact Software AG technical support.
77	A getmain failed for the work area used in an IPC Message Call. Determine why the TP monitor is running short of storage. The storage will be acquired in the AMODE of the calling program, usually 31-bit for Natural transactions.
78	An invalid IPC work area has been provided by the caller for a TS call. This is probably an internal product error. Contact Software AG technical support.
79	An error occurred during freemain done for a TS call. This may indicate an internal product error or a TP monitor storage overlay. Contact Software AG technical support for assistance.
100	Unable to communicate with the Adabas Directory Server. Check the LTCPSET parameters ADIHOST and ADIPOINT.
101	An error occurred when closing a socket. Contact Software AG technical support for assistance.
102	A socket could not be allocated. Contact Software AG technical support for assistance.

Subcode	Meaning
103	The TCP/IP socket could not connect to the database. Check that the database is active.
104	Unable to establish a context on the database. Contact Software AG technical support for assistance.
110	Internal error processing a parameter list. Contact Software AG technical support for assistance.
111	An error occurred when sending data on a socket. Contact Software AG technical support for assistance.
120	Unable to receive results due to no database context. Contact Software AG technical support for assistance.
121	An attempt has been made to receive results from a database which has not previously been contacted. Contact Software AG technical support for assistance.
122	Unable to receive results due to no client context on the database. Contact Software AG technical support for assistance.
123	An error occurred when receiving data on a socket. Contact Software AG technical support for assistance.
130	The RCVTIME has been exceeded whilst waiting to receive data on a socket.

Action

In the case of subcode zero, 01 or 02 increase the UB pool by respecifying the NUBS parameter in the link routines. See the LGBLSET macro information in the Adabas Installation documentation.

In all other cases, either the program executing the IPC (Interprocess communication) message has provided invalid parameters, or there are internal product problems such as storage overlay conditions. Contact Software AG technical support for assistance.

Response 219

Origin

Mainframe systems only

Explanation

This response code should only occur when Adabas Transaction Manager is being used.

Subcode	Meaning
2	The global transaction is not in the status that allows the call.
3	Two transaction ID (XID) entries exist.
4	The "R" and "J" options are not supported; or this is not a global transaction. The transaction ID (XID) does not exist or cannot be found (or example, when the given XID does not belong to the UQE).

Subcode	Meaning
5	The record or value buffer definition may be invalid; for example, the length size may be invalid (less than or equal to 144 bytes); or the value buffer content may be invalid; for example, it may not contain a valid transaction ID (XID).
6	The user is not an update or ET user or is already involved in a global transaction or the user is already on PET (preliminary end-of-transaction) status.
7	A protocol error occurred: The user has been copied to Work 4 or the transaction was backed out.
8	A protocol error occurred: The transaction was terminated or the user has no transaction ID (XID) or the recover call for an active user is not permitted.
9	The system is currently locked due to a pending Work area 4 or DDWORKR4 overflow.
10	The call is not permitted; either ADAEND or an ET-sync point is in process for the nucleus. Force the ATM nucleus to backout (BT) the transaction.
11	The user has not made any updates. A preliminary ET command, therefore, is not permitted.
12	A logic error occurred.
20	The transaction ID (XID) is unknown. This error occurs only in a cluster environment.

Response 220

Origin

Mainframe systems only

Explanation

The request was rejected by Entire Net-Work due to a shortage of short term buffers.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Action

For BS2000 systems running Sockets 2.2 or later, check the address space limit using the SHOW-USER-ATTRIBUTES command in the field ADDRESS-SPACE-LIMIT (the value is in megabytes). If necessary, increase it using the MODIFY-USER-ATTRIBUTES command from a privileged user ID.

For BS2000 systems running Sockets 2.1 or earlier, increase the CMSIZE parameter to enlarge the common memory pool, as long as there is enough room in the address space. Then restart Entire Net-Work.

For z/OS and z/VSE, increase the region size.

Response 221

Origin Mainframe systems only

Explanation The LU size of the remote partner is smaller than the size required for the Adabas request.

Action Either increase the size specified for the LU= parameter on the remote system, or modify the application to reduce its buffer sizes.

Response 222 - 223 (reserved)

Response 224

Origin Mainframe and open systems

Explanation An Adabas command has been timed out by Entire Net-Work. The request waited for a reply for a longer time period than specified by the REPLYTIM parameter in either the Entire Net-Work NODE statement or the SET operator command. The reply may be delayed or lost due to a target malfunction, or because of a connecting link failure. If you are using Natural, and all connections are verified, check the ADAMODE setting. The ADAMODE=0 setting is the only option Entire Net-Work supports.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the ACB Additions 2 field (ACBADD2) or the ACBX Error Subcode field (ACBXERRC) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
1	If the message was compressed using zEDC compression services and the attempt to decompress the message failed, subcode 1 is placed in the rightmost two bytes of the ACB Additions 2 field (ACBADD2) or the ACBX Subcomponent Response Code field (ACBXSUBR).
1076	An XTS timeout error occurred.

Action Check the node and remote database or contact your database administrator for assistance.

Response 225

Origin Mainframe and open systems

Explanation A command was issued from a server, such as an Adabas nucleus, to another server, such as Entire Net-Work. The command did not complete within a prescribed time period. The issuer proceeds and no longer expects a response to the command.

Note that the command may still execute in the target. There will be no notification to the issuer if it does. The target may display message ADAM92, User Gone, if the target attempts to notify the issuer of command completion.

The subcode identifies the environment from which the command was issued.

Subcode	Issuer
1	ADAMPM
2	Adabas nucleus, thread-synchronous command
3	Adabas nucleus, not thread-synchronous. Under z/OS, the command was TCB-synchronous.

Action Contact your Software AG technical support representative for assistance if the reason for the command's failure to complete cannot be identified.

Response 226 - 227 (reserved)

Response 228

Origin Mainframe systems only

Explanation This response is issued by an Adabas link routine. It indicates that an ASCII-formatted user request has been issued against an EBCDIC-formatted database that is not properly configured to handle the translation:

1	The SVC is not a valid Adabas version 7 SVC.
2	The database is not UES-enabled.

Action Ensure that your Adabas installation is for a supported version and that the database is UES-enabled. Refer to the UES information.

Response 229

Origin Mainframe systems only

Explanation The Entire Net-Work 5 convertor detected an inconsistency or error in the application format buffer or search buffer and is unable to correctly translate the user's data.

Response 230

Origin Open systems only

Explanation The protocol defined by the X/Open XA specification is violated. This happens, for example, if a user tries to issue an ET call for an XA transaction.

Action Follow the XA specification.

Response 231-239

Explanation These response codes are assigned in some Adabas user exits, and have meanings as defined by the user. One example is the response code in the ADALOG log data field issued by user exit 4.

Action Refer to the description of user exits in the Adabas user, hyperdescriptor, and collation descriptor exits documentation for more information.

Response 240

Origin Mainframe systems only

Explanation Adabas Transaction Manager encountered an error. The error code can be found in the Adabas control block Additions 2 field, in the low-order (rightmost) two bytes. A response code may occur in the first two bytes of the Additions 2 field.

Action Check the meaning of the Adabas Transaction Manager error code. If the cause of the problem is not apparent, contact your Software AG technical support representative.

Response 241

Origin Mainframe and open systems

Explanation The explanation for this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Adabas Transaction Manager (ATM) received an unexpected Adabas response code. The subcode and response code can be found, in that order, in the Adabas control block Additions 2 field. If a positive response code value appears in the Additions 2 field, the response code was detected by the ATM transaction manager. If a negative response code value appears in the Additions 2 field, take its complement: this is the response code received by the client proxy's attempt to communicate with the ATM transaction manager.

Open Systems

The system cannot load the specified user exit shared library or dynamic load library, or the specified function does not exist in this shared library or dynamic load library. If the function does not exist in the shared library or dynamic load library, bytes 1 and 2 of the Additions 2 field contain the system's error number in binary format, otherwise these two bytes contain 0. Bytes 3 and 4 of the Additions 2 field contains the number of the ADALNK user exit which failed in binary format.

Subcode	Meaning
1080	UEX_ACBX_0 load failed.
1081	UEX_ACBX_1 load failed.

Action**Mainframe Systems**

Check the meaning of the Adabas response code and subcode. If the cause of the problem is not apparent, contact your Software AG technical support representative.

Open Systems

Make sure that you use the correct environment variable for the user exit.

Response 242**Origin**

Mainframe and open systems

Explanation

The explanation for this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The Adabase Transaction Manager (ATM) or ATM client proxy was unable to determine the status of the caller's transaction. There might be an ATM error code in the Adabas control block Additions 2 field, in the low-order (rightmost) two bytes.

Open Systems

A double allocation has been detected between two or more files or a file and the free space table.

Action**Mainframe Systems**

Check the meaning of the Adabas Transaction Manager error code, if one is present. Otherwise, determine the status of the global transaction using Online Services. If the required action is not apparent, contact your Software AG technical support representative.

Open Systems

Run ADAVFY without any options to find out which parts of which files are affected. Contact your nearest support center with the output from ADAVFY.

Response 243

Origin Mainframe and open systems

Explanation The explanation for this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The Adabas Transaction Manager (ATM) or client proxy received an unsolicited syncpoint request. The action taken or the status of the global transaction that was open is indicated by a subcode in the Adabas control block Additions 2 field, in the low-order (rightmost) two bytes.

Subcode	Explanation and Recommended Action
1	The unsolicited syncpoint request was accepted. The status of the current global transaction is not known. Use Online Services to determine the status of the global transaction.
2	The unsolicited syncpoint request was accepted. The client session's global transaction has been committed.
3	The unsolicited syncpoint request was accepted. The client session's global transaction has been backed out.
4	The unsolicited syncpoint request was accepted. The client session's global transaction had mixed completion (partially backed out, partially committed).
5	The unsolicited syncpoint request was accepted. The client session's global transaction is in backout.
6	The unsolicited syncpoint request was accepted. The client session's global transaction is in commit.
7	The unsolicited syncpoint request was accepted. The client session had no global transaction open.
12	The unsolicited syncpoint was attempted, but ATM returned response code 148 (ADARSP148) so the outcome is not known.
16	The unsolicited syncpoint request was rejected.

Open Systems

An invalid FCB extent has been detected for a file.

Action

Mainframe Systems

Review the Adabas Transaction Manager's TMSYNCMGR parameter and the TransactionControl, Client-sideTransactionManager, and HostSystemTransactionManager client runtime controls for the failing job.

Open Systems

Contact your nearest support center.

Response 245**Origin** Mainframe and open systems**Explanation** On mainframe systems, this response code is issued for communication problems between add-on products that use the system coordinator (COR) interface to Adabas; that is, Adabas Fastpath, Adabas Vista, Adabas SAF Security, and Adabas Transaction Manager.

Subcode	Meaning
1	Internal error.
2	A required module could not be loaded. This is probably an installation error.

On open systems, pending utility entries exist in the UCB.

Action On mainframe systems, for subcode 1, contact your Software AG technical support representative. For subcode 2, consult the installation instructions for the add-on product.

On open systems, delete the entries with RESET = UCB before executing RECOVER, but ensure that the utilities which own the UCB entries are no longer running.

Response 246**Origin** Open systems only**Explanation** Utility communication block (UCB) overflow.**Action** Execute the RESET function of ADADBM to remove unused entries from the utility communication block if the utilities that own them are no longer running.**Response 247****Origin** Open systems only**Explanation** Correct ID not found in the utility communication block.**Action** The utility cannot be restarted. Delete the utility communication block entry and rerun the utility.**Response 248****Origin** Mainframe and open systems**Explanation** This response code is returned by Data Archiving for Adabas processing. Subcodes are returned in big-endian byte order in the Additions-2 field of the Adabas control block and conform to the format 0xhhhhChhh where C is the subcode category. The subcodes below are listed in Category order.

Category 0 subcodes:

Subcode	Meaning
1 (0x00000001)	<p>No architecture/version information returned by Adbas in the response to the OP command.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
2 (0x00000002)	<p>Cannot recall archived data because the architecture of the target database is not compatible with the architecture to the original database.</p> <p><i>Action:</i> Choose a different mixture.</p>
3 (0x00000003)	<p>Either the Extractor/Accumulator versions are not compatible or the Adbas version of the database being archived from or recalled to is not supported.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
4 (0x00000004)	<p>The FDT of the file into which data is being recalled or archived is not compatible with the FDT of the original file.</p> <p><i>Action:</i> Check that FDTs of the files are compatible.</p>
5 (0x00000005)	<p>Cannot coerce a value specified for the extraction criteria to the specified type.</p> <p><i>Action:</i> Check that the values and types defined for the extraction criteria are correct.</p>
6 (0x00000006)	<p>Date specified for the extraction criteria is prior to the earliest supported data.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
7 (0x00000007)	<p>Unsupported date/time pattern in extraction criteria.</p> <p><i>Action:</i> Set a correct pattern in the extraction criteria. Contact Software AG Support.</p>
8 (0x00000008)	<p>Database from which data is being archived or recalled into is not on the local machine.</p> <p><i>Action:</i> Check the action is correctly configured. The source database must be local to the Extractor and target database local to the Accumulator.</p>
9 (0x00000009)	<p>Cannot load the Adbas System Coordinator library.</p> <p><i>Action:</i> Check that Adbas System Coordinator is installed correctly.</p>
10 (0x0000000A)	<p>An incompatible version of Adbas System Coordinator is installed.</p>

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
11 (0x0000000B)	An incompatible version of Adabas System Coordinator is installed. <i>Action:</i> Contact your Software AG technical support representative.
12 (0x0000000C)	Cannot parse FDT. <i>Action:</i> Contact your Software AG technical support representative.
13 (0x0000000D)	Cannot generate FDU from FDT. <i>Action:</i> Contact your Software AG technical support representative.
14 (0x0000000E)	Cannot create format buffer for the whole FDT. <i>Action:</i> Contact your Software AG technical support representative.
15 (0x0000000F)	PE or MU field(s) not defined correctly. <i>Action:</i> Check that the PE/MU fields in the Extractor/Accumulator filtering and Archive search fields are defined correctly.
16 (0x00000010)	Field does not exist in the FDT. <i>Action:</i> Check that the fields in the Extractor/Accumulator filtering and Archive search fields are defined correctly.
17 (0x00000011)	Recall of a filtered archive using the 'Replace duplicate unique descriptors' option failed because the format/record buffer could not be parsed. <i>Action:</i> Contact your Software AG technical support representative.
18 (0x00000012)	Recall of a filtered archive using the 'Replace duplicate unique descriptors' option failed because the conflicting descriptor does not appear in the format/record buffer. <i>Action:</i> Choose different recall options for handling duplicate unique descriptors or ensure that all UQ fields are included in a filtered archive.
19 (0x00000013)	Internal record buffer overflow. <i>Action:</i> Contact your Software AG technical support representative.
20 (0x00000014)	Internal format buffer overflow.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
21 (0x00000015)	Internal search buffer overflow. <i>Action:</i> Contact your Software AG technical support representative.
22 (0x00000016)	Internal value buffer overflow. <i>Action:</i> Contact your Software AG technical support representative.
23 (0x00000017)	No extraction criteria were specified and there are no DE fields in the FDT. <i>Action:</i> Contact your Software AG technical support representative.
24 (0x00000018)	No Computer record for the current Adabas System Coordinator Group Leader. <i>Action:</i> Check that the correct Repository is being used and that the Adabas System Coordinator Computer is still defined.
25 (0x00000019)	No archive service definition for the Extractor/Accumulator computer. <i>Action:</i> Check that the correct Repository is being used and that the Data Archiving Service is still defined for Adabas System Coordinator Daemon.
26 (0x0000001A)	No Computer or Daemon record for the Extractor/Accumulator computer. <i>Action:</i> Check that the correct Repository is being used and that the Adabas System Coordinator Computer and Daemon is still defined.
27 (0x0000001B)	No Action record found for the current archive/recall/search operation. <i>Action:</i> Check that the correct Repository is being used and that the Action record is still defined.
28 (0x0000001C)	No Vault Validation record found. <i>Action:</i> Check that the validation is correctly configured for this vault.
29 (0x0000001D)	No Vault PATH information for this computer. <i>Action:</i> Check that a Vault Path is defined for the Extractor, Accumulator and ADR Service computers.

Subcode	Meaning
30 (0x0000001E)	Attempt to recall an archive using Extractor/Accumulator computers that not sharing the same Repository. <i>Action:</i> Extractor/Accumulator computers for a recall must share the same Repository.
31 (0x0000001F)	No Plan record found for the current archive/recall/search operation. <i>Action:</i> Check that the correct Repository is being used and that the Plan record is still defined.
32 (0x00000020)	Archive failed due to invalid/unsupported Extractor settings. <i>Action:</i> Contact your Software AG technical support representative.
33 (0x00000021)	Archive failed due to invalid/unsupported Transfer settings. <i>Action:</i> Contact your Software AG technical support representative.
34 (0x00000022)	Archive failed due to invalid/unsupported Accumulator settings. <i>Action:</i> Contact your Software AG technical support representative.
35 (0x00000023)	Recall failed due to invalid or unsupported Extractor settings. <i>Action:</i> Contact your Software AG technical support representative.
36 (0x00000024)	Recall failed due to invalid or unsupported Transfer settings. <i>Action:</i> Contact your Software AG technical support representative.
37 (0x00000025)	Recall failed due to invalid or unsupported Accumulator settings. <i>Action:</i> Contact your Software AG technical support representative.
38 (0x00000026)	Extractor terminated because the Accumulator is not active. <i>Action:</i> Check the response and subcode for the Accumulator in Current or Completed Activities.
39 (0x00000027)	Accumulator timed-out waiting for the Extractor. <i>Action:</i> Check the response and subcode for the Extractor in Current or Completed Activities.
40 (0x00000028)	Message protocol error/incompatibility. <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
41 (0x00000029)	<p>Message protocol error/incompatibility.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
42 (0x0000002A)	<p>Message protocol error/incompatibility.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
43 (0x0000002B)	<p>Message protocol error/incompatibility.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
44 (0x0000002C)	<p>Message protocol error/incompatibility.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
45 (0x0000002D)	<p>Timeout waiting for lock on archive in Vault.</p> <p><i>Action:</i> Retry the operation and/or check for competing operations.</p>
46 (0x0000002E)	<p>Version mismatch between Data Archiving for Adabas runtime and Vault contents.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
47 (0x0000002F)	<p>Invalid/corrupt archive in Vault.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
48 (0x00000030)	<p>Archive in Vault contains data not supported by this version of the Data Archiving for Adabas runtime.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
49 (0x00000031)	<p>Archive size would exceed limit.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
50 (0x00000032)	<p>Invalid/unsupported Vault operation.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
51 (0x00000033)	<p>Archive does not exist in Vault.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
52 (0x00000034)	<p>Vault path does not exist.</p>

Subcode	Meaning
	<i>Action:</i> Check that the Vault Path defined for the Extractor, Accumulator and ADR Service computers is correct.
53 (0x00000035)	Access denied to Vault Path. <i>Action:</i> Check that the Extractor, Accumulator and ADR Service computers have the correct filesystem permissions for the Vault Path.
54 (0x00000036)	Logical error manipulating Vault contents. <i>Action:</i> Contact your Software AG technical support representative.
55 (0x00000037)	Extractor/Accumulator failed to load. <i>Action:</i> Check the response and subcode for the Extractor/Accumulator in Pending, Current and Completed Activities.
56 (0x00000038)	Extractor/Accumulator failed to load. <i>Action:</i> Contact your Software AG technical support representative.
57 (0x00000039)	Length of compressed record exceeds limit. <i>Action:</i> Contact your Software AG technical support representative.
58 (0x0000003A)	Length of decompressed record exceeds limit. <i>Action:</i> Contact your Software AG technical support representative.
59 (0x0000003B)	Cannot determine the default codepage for the system. <i>Action:</i> Contact your Software AG technical support representative.
60 (0x0000003C)	Invalid/unsupported codepage specified for archive or recall. <i>Action:</i> Check that the codepage specified for in the Extractor/Accumulator settings in the Action or recall request.
61 (0x0000003D)	'Use default' codepage specified for archive or recall and there is no default UES AMODE= setting for the database. <i>Action:</i> Specify the codepage explicitly or configure the default AMODE= setting for the database.
62 (0x0000003E)	No Search record found. <i>Action:</i> Check that the correct Repository is being used and that the Search Record is still defined for the Action.

Subcode	Meaning
63 (0x0000003F)	<p>Cannot search archive because the data was not archived in compressed format.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
64 (0x00000040)	<p>Invalid search (search buffer).</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
65 (0x00000041)	<p>Invalid search (value buffer).</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
66 (0x00000042)	<p>Value buffer for search could not be converted from the UI codepage to the codepage of the archived data.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
67 (0x00000043)	<p>'Use default' codepage specified for archive or recall and there is no default UES WMODE=setting for the database.</p> <p><i>Action:</i> Specify the codepage explicitly or configure the default WMODE= setting for the database.</p>
68 (0x00000044)	<p>Task already locked.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
69 (0x00000045)	<p>License file is missing.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
70 (0x00000046)	<p>License key is invalid.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
71 (0x00000047)	<p>License has expired.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
72 (0x00000048)	<p>License is for a different operating system.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
73 (0x00000049)	<p>License is for a different product.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>

Subcode	Meaning
74 (0x0000004A)	License is for a different version. <i>Action:</i> Contact your Software AG technical support representative.
75 (0x0000004B)	Functionality restricted, Community edition. <i>Action:</i> License file required for full functionality.
76 (0x0000004C)	No license file found. <i>Action:</i> Contact your Software AG technical support representative.
77 (0x0000004D)	Duplicate archive identifier detected in the Vault. <i>Action:</i> Contact your Software AG technical support representative.
78 (0x0000004E)	Filename conflict detected in the Vault. <i>Action:</i> Contact your Software AG technical support representative.
79 (0x0000004F)	Some or all of the data for an archive is missing from the Vault. <i>Action:</i> Contact your Software AG technical support representative.
80 (0x00000050)	Vault or archive damaged. <i>Action:</i> Contact your Software AG technical support representative.
81 (0x00000051)	ADR plug-in library could not be loaded. <i>Action:</i> Contact your Software AG technical support representative.
82 (0x00000052)	Incompatible ADR plug-in library. <i>Action:</i> Contact your Software AG technical support representative.
83 (0x00000053)	Occurrence 'N' cannot be specified for a PE/MU LOB field in an Extractor Filter (Open Systems only). <i>Action:</i> Correct the format buffer in the Extractor Filter Settings.
84 (0x00000054)	An Extractor Filter must contain at least one non-LOB field. <i>Action:</i> Correct the format buffer in the Extractor Filter Settings.
85 (0x00000055)	The data being archived or recalled contains LOB fields but no LOB file number has been specified.

Subcode	Meaning
	<i>Action:</i> Specify a LOB file number, for recalls set in the recall settings and for archive set in the Accumulator settings in the Action.
86 (0x00000056)	License file does not provide the Price Units required by the system. <i>Action:</i> Contact your Software AG technical support representative.
87 (0x00000057)	License file does not provide the Price Quantity required by the system. <i>Action:</i> Contact your Software AG technical support representative.
88 (0x00000058)	License file does not provide Extended Rights. <i>Action:</i> Contact your Software AG technical support representative.
89 (0x00000059)	The file size of the archive file checked by the validation process is incorrect. <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
90 (0x0000005A)	The number of records in the archive file checked by the validation process is incorrect. <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
91 (0x0000005B)	The check sum for the archive file checked by the validation process is incorrect. <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
92 (0x0000005C)	The lengths of the records in the archive file checked by the validation process are incorrect. <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
93 (0x0000005D)	License file does not provide Archive to Vault required by the system. <i>Action:</i> Contact your Software AG technical support representative.
94 (0x0000005E)	License file does not provide Transfer to Adabas required by the system.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
95 (0x0000005F)	License file does not provide Delete from Adabas required by the system. <i>Action:</i> Contact your Software AG technical support representative.
96 (0x00000060)	Inconsistency in join data for archive. <i>Action:</i> Contact your Software AG technical support representative.
97 (0x00000061)	Inconsistent object/archive identifiers for archive. <i>Action:</i> Contact your Software AG technical support representative.
98 (0x00000062)	File list for action does not match the archive data. <i>Action:</i> Contact your Software AG technical support representative.
99 (0x00000063)	Archive identifier does not match API data. <i>Action:</i> Contact your Software AG technical support representative.
100 (0x00000064)	Group, plan or name of action does not match API data. <i>Action:</i> Contact your Software AG technical support representative.
101 (0x00000065)	File list for action does not match API data. <i>Action:</i> Contact your Software AG technical support representative.
102 (0x00000066)	Duplicate activity encountered. <i>Action:</i> Delete activity from Activities List and rerun.
103 (0x00000067)	Related file record is missing. <i>Action:</i> Contact your Software AG technical support representative.
104 (0x00000068)	Recall target record is missing. <i>Action:</i> Contact your Software AG technical support representative.
105 (x00000069)	Recall target information is not valid. <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
106 (x0000006A)	<p>Maximum number of related files exceeded.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
107 (x0000006B)	<p>Maximum number of transfer destinations exceeded.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
108 (x0000006C)	<p>Transfer destination not defined.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
109 (x0000006D)	<p>Maximum number of related files or transfer destinations exceeded.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
110 (x0000006E)	<p>Invalid related file.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
111 (x0000006F)	<p>Invalid transfer destination.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
112 (0x00000070)	<p>Archive, recall or search failed.</p> <p><i>Action:</i> Check the response and subcode for the Extractor/Accumulator in Completed Activities.</p>
113 (0x00000071)	<p>Archive, recall or search incomplete.</p> <p><i>Action:</i> Records have been skipped due to contention or errors.</p>
114 (0x00000072)	<p>Invalid settings specified for file in action.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
115 (0x00000073)	<p>Recall configuration records inconsistent.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
116 (0x00000074)	<p>Recall configuration records inconsistent.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
117 (0x00000075)	<p>API library is not installed.</p>

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
118 (0x00000076)	API library could not be loaded. <i>Action:</i> Contact your Software AG technical support representative.
119 (0x00000077)	Entry-point symbol missing from API library. <i>Action:</i> Contact your Software AG technical support representative.
120 (0x00000078)	Wrong version of API library. <i>Action:</i> Contact your Software AG technical support representative.
121 (0x00000079)	Fault detected in API library. <i>Action:</i> Contact your Software AG technical support representative.
122 (0x0000007A)	API library is missing. <i>Action:</i> Contact your Software AG technical support representative.
123 (0x0000007B)	No data returned by API. <i>Action:</i> Contact your Software AG technical support representative.
124 (0x0000007C)	Incorrect API parameters specified by user. <i>Action:</i> Contact your Software AG technical support representative.
125 (0x0000007D)	Memory allocation failed in API. <i>Action:</i> Contact your Software AG technical support representative.
126 (0x0000007E)	Internal API error. <i>Action:</i> Contact your Software AG technical support representative.
128 (0x00000080)	Incorrect parameter passed to API. <i>Action:</i> Contact your Software AG technical support representative.
129 (0x00000081)	API notification failed (state inconsistent). <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
130 (0x00000082)	<p>API library name is too long.</p> <p><i>Action:</i> Reduce the length of the API library name.</p>
131 (0xhhhh0083)	<p>Error occurred while processing the Extraction Syntax. An extended error code (identified by hhhh) may also be reported for subcode 131.</p> <p><i>Action:</i> Check the Extraction Syntax and if the error persists contact your Software AG technical support representative providing the full subcode value and the Extraction Syntax being used.</p>
132 (0x00000084)	<p>No dynamic extraction object code exists</p> <p><i>Action:</i> Ensure that you have successfully saved and compiled your dynamic extraction syntax.</p>
133 (0x00000085)	<p>Duplicate Related file record with differing scopes.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
134 (0x00000086)	<p>API To-Do list locked, it is already in use by another process.</p> <p><i>Action:</i> Ensure that only one application/process accesses a To-Do list at any one time.</p>
135 (0x00000087)	<p>Extractor data targets do not match those in the Repository.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
136 (0x00000088)	<p>Extractor/Accumulator was terminated unexpectedly or cancelled by the user.</p> <p><i>Action:</i> Check the response and subcode for the Extractor/Accumulator in Pending, Current and Completed Activities.</p>
137 (0x00000089)	<p>Accumulator terminated because the Extractor is not active.</p> <p><i>Action:</i> Check the response and subcode for the Extractor in Current Activities or Recently Completed.</p>
138 (0x0000008A)	<p>An archive activity could not be resumed/restarted because the FDT of one of the Source Files has been changed since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
139 (0x0000008B)	<p>An archive activity could not be resumed/restarted because the Codepage setting for a Source File or the AMODE/WMODE</p>

Subcode	Meaning
	<p>settings for the associated database have been changed since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
140 (0x0000008C)	<p>An archive activity could not be resumed/restarted because the Computer defined for the Extractor or Accumulator has been changed since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
141 (0x0000008D)	<p>An archive activity could not be resumed/restarted because the Source or Target File definitions for the Action have been changed since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
142 (0x0000008E)	<p>The Extractor was unable to read the FCB of one of the Source Files.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
143 (0x0000008F)	<p>The FCB of the Source Files is in a format not recognised by the Extractor.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
144 (0x00000090)	<p>An archive activity could not be resumed/restarted because one of the Source Files has been reloaded since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
145 (0x00000091)	<p>An archive activity could not be restarted because the archive could not be validated, the repair was unsuccessful.</p> <p><i>Action:</i> Review the meaning of any log messages written at the time of the failure and, if necessary, contact your Software AG technical support representative.</p>
146 (0x00000092)	<p>An archive activity could not be validated/restarted because one of the archive file segments is missing.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
147 (0x00000093)	<p>Invalid archive identifier.</p>

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
148 (0x00000094)	Length mismatch detected whilst updating archive file record. <i>Action:</i> Contact your Software AG technical support representative.
149 (0x00000095)	No Vault record found. <i>Action:</i> Check that the Vault defined for the Plan or Action exists.
150 (0x00000096)	The ADR Service does not support the granularity setting configured for the Vault. <i>Action:</i> Contact your Software AG technical support representative.
151 (0x00000097)	Vault path does not exist. <i>Action:</i> Check that the Vault Path defined for the Extractor, Accumulator and ADR Service computers are correct.
152 (0x00000098)	An archive activity could not be validated/restarted because too many archive file segments exist. <i>Action:</i> Contact your Software AG technical support representative.
153 (0x00000099)	Timed-out whilst caching Vault content on local Computer. <i>Action:</i> Contact your Software AG technical support representative.
154 (0x0000009A)	Vault path does not exist. <i>Action:</i> Check that the Vault Path defined for the Extractor, Accumulator and ADR Service computers are correct.

Category 7 subcodes:

Subcode	Meaning
0xhhhh7004	An error has occurred whilst accessing a Vault where hhhh is the operating system error code. Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes). If the cause of the error is not apparent, contact your Software AG technical support representative.
0xhhhh700B	An error has occurred whilst writing to a Vault where hhhh is the operating system error code.

Subcode	Meaning
	<p>Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).</p> <p>If the cause of the error is not apparent, contact your Software AG technical support representative.</p>

Category A subcodes:

Subcode	Meaning
0xhhhhA001	<p>A TCP/IP error has occurred where hhhh is the operating system error code.</p> <p>Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).</p> <p>If the cause of the error is not apparent, contact your Software AG technical support representative.</p>
0xhhhhA002	<p>A DNS error has occurred where hhhh is the operating system error code.</p> <p>Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).</p> <p>If the cause of the error is not apparent, contact your Software AG technical support representative.</p>

Response 249

Origin

Mainframe and open systems

Explanation

Mainframe Systems

Adabas Vista uses a default Adabas response code 249 for all processing errors. This response code can be changed by using the Job Parameter function of Adabas Vista Online Services.

The following table describes each of the subcodes possible for response code 249. Adabas Vista issues these subcodes as well to provide additional information.

Subcode	Meaning
1	<p>The partitioned file concurrency limit has been reached.</p> <p><i>Action:</i> Increase the partitioned file concurrency limit using the File Partitioning function of Adabas Vista Online Services.</p>
6	<p>The job parameter <code>Enable Multiple Updates</code> is set to NO. After updating one database, the user attempted to update a second database in the same transaction.</p> <p><i>Action:</i> Review the job parameter <code>Enable Multiple Updates</code> in the Job Parameter function of Adabas Vista Online Services.</p>
8	<p>This partitioned file has been defined with an unsupported Partitioning Field. The Partitioning Field may not be:</p> <ul style="list-style-type: none"> ■ A multiple value field ■ An item in a periodic group ■ A field with format F, G, or W ■ A variable length field ■ A field with the long alphanumeric (LA) attribute ■ A SUPDE or SUPFN of format Alphanumeric with at least one parent of format W <p><i>Action:</i> Review the partitioning criteria.</p>
9	<p>One of the following errors was detected while processing a partitioned file:</p> <ul style="list-style-type: none"> ■ A distributed access can not be successfully processed due to the client encoding being incompatible with Vista's record collating process. ■ A command can not be successfully processed due to the client encoding being incompatible with the defined partition criteria. <p><i>Action:</i> Review the use of client encodings.</p>
10	<p>One of the following errors was detected in the Adabas search buffer while processing a partitioned file:</p> <ul style="list-style-type: none"> ■ the specified field is not in the Adabas FDT. ■ an S or N operator is used incorrectly. ■ a superdescriptor with a variable-length parent field is not allowed. ■ coupled file syntax is not allowed. ■ the value1 operator (EQ, GE, GT, etc.) is unknown. ■ a connecting operator (D, O, R, etc.) is unknown. ■ a command ID enclosed in parentheses is not allowed ■ a memory request failed. ■ collation descriptors are not supported.

Subcode	Meaning
	<i>Action:</i> Review and correct the application program.
12	<p>Runtime controls have been changed dynamically without the client previously resetting all Adabas context to null. In this situation Vista is forced to discard all Adabas context and alert the application with this response.</p> <p><i>Action:</i> Avoid this response by ensuring the client has no Adabas context prior to the runtime controls being changed.</p>
14	<p>One of the following errors was detected in the Adabas format or record buffer while processing a update/store for a partitioned file:</p> <ul style="list-style-type: none"> ■ The partitioning field specified in the format buffer could not be located in the Adabas FDT (N1 and N2). ■ An Adabas field specified in the format buffer could not be located in the Adabas FDT (N1, N2 and A1). ■ The partitioning field value specified in the record buffer is inconsistent with the defined partitioning criteria for the file (N1 and N2). ■ The partitioning field value specified in the record buffer is inconsistent with the partition criteria defined to the partition identified by the ISN in the Adabas control block (N2 only). ■ The partitioning field value specified in the record buffer is null and the Store Control Option is set to 2 (N1 only). ■ The partitioning field/value has not been specified and no target partition has been identified (N1 and N2). <p><i>Action:</i> Review application program and partitioning criteria.</p>
15	<p>The partitioning field value specified in the record buffer of the A1 command is inconsistent with the partition criteria defined to the partition identified by the ISN in the Adabas control block.</p> <p>Such an update requires the relocation of the ISN to another partition, which is not allowed.</p> <p><i>Action:</i> Review the application program. Use a delete and store as an alternative.</p>
16	<p>An ISN has been detected that is invalid for one of the following reasons:</p> <ul style="list-style-type: none"> ■ The partition identifier extracted from the Adabas Vista ISN is not consistent with any partition defined to the partitioned file. ■ The Adabas ISN read from a partition is greater than the TOPISN value defined for the partition. ■ An attempt to store a record has resulted in an Adabas ISN greater than the TOPISN value defined for the partition.

Subcode	Meaning
	<ul style="list-style-type: none"> ■ (Extreme partitioned files only) The number of partitions is greater than the limit of 255. ■ (Extreme partitioned files only) The application-supplied ISN is no longer associated with this partitioned file. <p><i>Action:</i> For Standard partitioned files, review the application program, the partition definitions, and check TOPISN setting. For Extreme partitioned files, review the application's use of the supplied ISN.</p>
21	<p>One of the following errors occurred while processing Distributed Lock Mode (DLM) against a partitioned file:</p> <ul style="list-style-type: none"> ■ Prefetch/multifetch options on a distributed access L6command are not allowed for DLM options 2 and 3. ■ DLM option 4 is specified and a distributed accessS4 or L6 command was issued. ■ DLM option 3 is specified and the distributed access data integrity check failed. <p><i>Action:</i> Review the application and use of the DLM option.</p>
22	<p>The client runtime control for CL convergence is set to reject when your Vista rules used during runtime result in activity for multiple source databases converging into a single target database. With this setting the CL command cannot be processed by Vista because it would result in the loss of cursor/transaction activity in the target database for source database(s) beyond the one indicated in this CL command which would result in unpredictable results and errors if those other source databases are used further.</p> <p><i>Action:</i> Review the application program and the convergent translation/partitioning rules or alter the CL convergence runtime control setting.</p>
25	<p>One of the following unsupported commands has been issued:</p> <ul style="list-style-type: none"> ■ an S5 command (partitioned files only) ■ a C5 command ■ a BT command with Command Option 2 set to F (any transaction will have been backed out) ■ an L1 command with Command Option 1 or 2 set to F <p><i>Action:</i> Review application program.</p>
28	<p>An update command has been issued to a partitioned file; however, the target partition does not have the option ACCESS=FULL.</p> <p><i>Action:</i> Review application program and partition ACCESS options.</p>

Subcode	Meaning
31	<p>An existing Command ID has been reused after the client's translation context has been modified but this now references a different file, which is an illegal situation and is therefore rejected.</p> <p><i>Action:</i> Review programming practices for changing client contexts.</p>
32	<p>Partitioned files can not be subjected to a change in client context</p> <p><i>Action:</i> Review programming practices for changing client contexts.</p>
36	<p>A session-related memory allocation failed during an inter-system dynamic transaction routing operation, the client session is unable to continue. This sub-code may not indicate an error on this current Adabas command, but it indicates that an internal error has prevented the Vista session continuing successfully.</p> <p><i>Action:</i> Increase the shared memory available.</p>
37	<p>A file-related memory allocation failed during an inter-system dynamic transaction routing operation, the client session is unable to continue using the file. This sub-code may not indicate an error on this current Adabas command, but it indicates that an internal error has prevented the Vista session continuing successfully with one of the files currently being used so Vista is alerting you immediately.</p> <p><i>Action:</i> Increase the shared memory available.</p>
39	<p>An L1 (get next) command was issued but the supplied command ID is not currently active.</p> <p><i>Action:</i> Review application program.</p>
45	<p>An error has occurred during the processing of a distributed L3/L9 command against a partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
50	<p>An A1 command was issued without the H option and the DLM option is set to 1. However, the ISN to be updated has not been previously read by a hold command.</p> <p><i>Action:</i> Review application program and use of DLM option.</p>
51	<p>The number of segmented buffers used by this ACBX call against a Partitioned File is greater than the maximum allowed.</p> <p><i>Action:</i> Reduce the number of segmented buffers.</p>
52	<p>The file parameter Enable ISN Positioning is set to NO and one of the following commands was issued:</p> <ul style="list-style-type: none"> ■ L1 with Command Option 2 set to I

Subcode	Meaning
	<ul style="list-style-type: none"> ■ L2/5 with starting ISN ■ L3/6 with starting ISN ■ Sx with the ISN Lower Limit field specified <p><i>Action:</i> Review application program and the file parameter Enable ISN Positioning.</p>
60	<p>A memory request failed.</p> <p><i>Action:</i> Review the memory availability of the</p> <ul style="list-style-type: none"> ■ host TP system; ■ host operating system; and ■ global common memory pool (BS2000 only; specified in the Adabas System Coordinator group definition).
65	<p>One of the following invalid values was used for a command ID value:</p> <ul style="list-style-type: none"> ■ X'00000000' ■ X'40404040' <p><i>Action:</i> Do not use the above command ID values.</p>
70	<p>Support for the use of this API has been withdrawn.</p> <p><i>Action:</i> Please refer to the currently supported APIs or, alternatively, contact your Software AG technical support representative to discuss your requirements.</p>
72	<p>An ET Data related command has been issued, but the runtime control (see <i>Database Number for ET Data</i>, in the <i>Adabas Vista Parameters</i> manual) is not set to a specific database number and Vista has been unable to establish a target database to satisfy the command.</p> <p><i>Action:</i> Review the runtime control <i>Database Number for ET Data</i>, in the <i>Adabas Vista Parameters</i> manual, to specifically identify the database number to be used.</p>
74	<p>A sequence direction change has been detected during an L3 or L9 command against a Partitioned File whose Command ID sequence has been previously subjected to multifetch.</p> <p><i>Action:</i> Review the program logic.</p>
81	<p>An error has occurred during the processing of an L1 'get next' command against a partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>

Subcode	Meaning
86	<p>The Adabas Vista database process is not installed. It must be installed on all Adabas databases which contain Adabas Vista partitions. This subcode indicates that a database</p> <ul style="list-style-type: none"> ■ is not running with ADARUN VISTA=YES; or ■ is not running Adabas version 7 or above. <p><i>Action:</i> Refer to the Adabas Vista installation procedures.</p>
96	<p>An error has occurred during the parsing of the Format Buffer during the processing of an Ax or Nx command against a partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
106	<p>The configuration for the first-level null definition policy for this target category (mode) is set to reject "null" as the outcome of translation processing.</p> <p><i>Action:</i> Review the null definition policy for the target category (mode) used if you do not wish to receive this error.</p>
107	<p>Translation processing has been configured to disallow redirection to a different target category (mode).</p> <p><i>Action:</i> Remove the redirection rule(s) or review the category adjustment policy for the target category (mode) in use.</p>
108	<p>The configuration for the first-level null definition policy redirects to another target category (mode) which in turn has resulted in a "null" outcome. The second-level null definition policy is set to reject such an outcome.</p> <p><i>Action:</i> Review the translation rules in use to avoid a null result or alter the null definition policies.</p>
109	<p>Translation processing has detected a recursive redirection.</p> <p><i>Action:</i> Review the translation rules in use.</p>
112	<p>An error has occurred during the processing of the current command.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
116	<p>A command has been issued against a partitioned file which has the Shared Partition option set to YES for one or more of its partitions. However, the partitioning field defined does not exist in the Adabas FDT.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>

Subcode	Meaning
117	<p>One of the following errors occurred while processing the record, value, or search buffer:</p> <ul style="list-style-type: none"> ■ A P format field value was not in packed decimal format. ■ A U format field value was not in unpacked decimal format. ■ The attempted format conversion was not possible because of incompatible data formats or other compatibility problems. ■ The field length was zero or not consistent with the field format. <p><i>Action:</i> Check field values for correct formats and lengths.</p>
119	<p>One of the following has occurred:</p> <ul style="list-style-type: none"> ■ Runtime configuration on behalf of this client was unsuccessful and Adabas Vista has been defined as “critical” using the Critical Product Support feature of the Adabas System Coordinator. ■ The Adabas Vista configuration file was not available during an attempt to satisfy an Adabas Vista API request. <p><i>Action:</i> Check the availability of the configuration file.</p> <p>If the client runtime control Error Reporting WTO option is set to YES, this error may be accompanied by an AVI-0017-10 console message.</p>
120	<p>The client previously issued a command to a source file for which Vista was unable to determine the existence of any translation rules due to the configuration file not being available at the time. Subsequently, Vista has detected the availability of the configuration file and has determined the existence of a translation rule for this source file. This subcode is returned the next time the client attempts to access the source file.</p> <p><i>Action:</i> Review the availability of the configuration file.</p>
122	<p>An invalid partitioned file definition has been found in the Adabas Vista configuration file.</p> <p><i>Action:</i> Check the file definition using Adabas Vista Online Services.</p>
123	<p>An invalid translation rule has been found in the Adabas Vista configuration file.</p> <p><i>Action:</i> Check the rule using Adabas Vista Online Services.</p>
124	<p>An error in the record buffer was detected during processing of an OP command.</p>
126	<p>One of the following errors occurred while processing an S8 command:</p> <ul style="list-style-type: none"> ■ An invalid command ID was specified in the Additions 1 field. ■ Different file numbers were detected for ISN lists. ■ An error occurred while processing a subsequent S8 call.

Subcode	Meaning
	<i>Action:</i> Review the application program.
127	<p>One of the following errors occurred while processing an S2 command:</p> <ul style="list-style-type: none"> ■ An invalid sort sequence was specified. ■ An invalid ISN was detected during processing. ■ An error was detected during ISN processing. <p><i>Action:</i> Review the application program.</p>
128	<p>One of the following errors occurred while processing an S9 command:</p> <ul style="list-style-type: none"> ■ The command ID value specified was assigned to another command. ■ An invalid sort sequence was specified. ■ An invalid ISN buffer length was detected. ■ The number of ISNs to be sorted as provided in ISN quantity is equal to 0. ■ The command ID value specified in Additions 4 was not found. ■ An invalid ISN was detected during processing. ■ An error was detected during ISN processing. <p><i>Action:</i> Review the application program.</p>
129	<p>The command limit defined for this source file has been exceeded.</p> <p><i>Action:</i> Review the command limit.</p>
131	<p>A requested file refresh of a partitioned file has failed due to an unexpected Adabas response code. The partitioned file is in a partially refreshed state.</p> <p><i>Action:</i> Review the Adabas response code.</p>
133	<p>One of the following errors occurred whilst processing a direction change during an L9 command sequence:</p> <ul style="list-style-type: none"> ■ A second direction change for this sequence was attempted. ■ A format override cannot be processed. ■ A length override greater than specified in the FDT cannot be processed. ■ A length override has been specified with complex search criteria. <p><i>Action:</i> Review the use of the L9 command and the Adabas Vista restrictions.</p>
134	<p>An S2 command to continue a sequence has been received. The sequence was not started by an S2 command.</p> <p><i>Action:</i> Amend the command sequence to process either all S1 commands, or all S2 commands, as appropriate.</p>
200	ISN quantity is too high on this Sx command.

Subcode	Meaning
	<i>Action:</i> Perform a more specific Sx .
201	<p>One of the following errors occurred while initializing AVIKRN:</p> <ul style="list-style-type: none"> ■ The dynamic load failed. ■ The version is not compatible. <p><i>Action:</i> Check the Adabas Vista installation procedures.</p>
250	<p>ISN error when issuing ACBX style RI shared-hold calls with ACBXCOP3 set to "S" .</p> <p><i>Action:</i> Check ISN usage on shared-hold commands.</p>
305	<p>An error has occurred while attempting to access an Extreme partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
496	<p>The session is not compliant with correct distributed transaction processing. Read <i>Transaction Directives</i>, in <i>Adabas Vista Programming Guidelines</i> for a more detailed explanation of this subcode.</p> <p><i>Action:</i> Adhere to correct distributed transaction processing.</p>
532	<p>This session has not complied with the correct transactional processing behavior when using the discrete file setting.</p> <p><i>Action:</i> Review the discrete file setting and ensure correct transactional processing.</p>
588	<p>For ACBX calls, a conflict with shared hold status option "H" has been detected. The client session is using this option in a conflicting manner during an ET or BT sequence after a commit/backout process has been performed. The transaction outcome is unaffected but records may no longer be in shared hold status.</p> <p><i>Action:</i> Review usage of this option.</p>

Open Systems

In Adabas Vista (open systems) an error occurred during command execution. One of the following subcodes may occur:

Subcode	Meaning
1 (0x0001)	An inconsistency in an internal data structure was detected. This may indicate a code fault within Adabas Vista. <i>Action:</i> Contact your Software AG technical support representative.
2 (0x0002)	An inconsistency in an internal data structure was detected. This may indicate a logic error within Adabas Vista. <i>Action:</i> Contact your Software AG technical support representative.
3 (0x0003)	The S9 command is not supported on partitioned files. <i>Action:</i> Review the program logic.
4 (0x0004)	The F option for an L1 command is not supported on partitioned files. <i>Action:</i> Review the program logic.
5 (0x0005)	The F option for a BT command is not supported. <i>Action:</i> Review the program logic.
6 (0x0006)	The ISN buffer for a BT or ET command with the M option is not consistent with ISN Buffer Length in the Adabas control block. <i>Action:</i> Review the program logic.
7 (0x0007)	The maximum number of active command ID values has been reached. <i>Action:</i> Review the program logic.
8 (0x0008)	The command ID value specified for TBLES/TBQ (sequential) or TBI (ISN list) command is already in use by a different TBLES/TBQ or TBI command. <i>Action:</i> Review the program logic.
9 (0x0009)	Adabas Vista is not compatible with the installed version of Natural, Adabas or Entire Net-Work. <i>Action:</i> Contact your Software AG technical support representative.
10 (0x000A)	The definitions for partitioned file do not exist. <i>Action:</i> Review the partition definitions in SYSAVI.
11 (0x000B)	The partitioning field does not exist in the FDT. <i>Action:</i> Review the partition definitions in SYSAVI.
12 (0x000C)	The field type in the partition definition does not match the field type in the FDT. <i>Action:</i> Review the partition definitions in SYSAVI.
13 (0x000D)	The type for the partitioning field is not suitable. <i>Action:</i> Review the partition definitions in SYSAVI.

Subcode	Meaning
14 (0x000E)	The format buffer specified for an N1 or N2 command does not contain the partitioning field. <i>Action:</i> Review the program logic.
15 (0x000F)	The value of the partitioning field in the record buffer specified for an N1 or N2 command could not be converted to the standard field length and format. <i>Action:</i> Review the program logic.
16 (0x0010)	The value of the partitioning field in the record buffer specified for an A1 , N1 or N2 command does not correspond to any partition defined for the file. <i>Action:</i> Review the partition definitions in SYSAVI.
17 (0x00011)	The value of the partitioning field in the record buffer specified for an A1 command would require the ISN to be relocated to a different partition. <i>Action:</i> Review the program logic.
18 (0x00012)	The ISN and the value of the partitioning field in the record buffer specified for an N2 command do not correspond to the same partition. <i>Action:</i> Review the program logic.
19 (0x00013)	The license is not valid for this operating system. <i>Action:</i> Contact your Software AG technical support representative.
20 (0x00014)	The license has expired. <i>Action:</i> Contact your Software AG technical support representative.
21 (0x00015)	The license file could not be found. <i>Action:</i> Contact your Software AG technical support representative.
22 (0x00016)	The license key is invalid. <i>Action:</i> Contact your Software AG technical support representative.
23 (0x00017)	The license is for a different version of the product. <i>Action:</i> Contact your Software AG technical support representative.
24 (0x00018)	The license is not for this product. <i>Action:</i> Contact your Software AG technical support representative.
25 (0x00019)	The ISN of a record read from a partition or the ISN of a record stored using an N1 command is too large. <i>Action:</i> Check the settings for the Adabas file to ensure that the ISN values cannot exceed the highest value defined for the partition in SYSAVI.

Response 250

Origin Mainframe and open systems

Explanation On mainframe systems, the ACBX (ACBX) failed validation. The following subcodes are possible:

Subcode	Meaning
1	Unsupported ACBX version
2	ADACBX provided without UBE.
3	ACBX file number > 65,535.
4	Reserved field not zero.
5	ACBX length incorrect

On open systems, a requested function is not yet implemented.

Action On mainframe systems, if subcode 3 occurs, notify your Software AG technical support representative. If any of the other subcodes occur, correct the ACBX specification and rerun.

On open systems, wait for a later version of Adabas.

Response 251

Origin Mainframe and open systems

Explanation On mainframe systems, an error occurred in Adabas cluster processing. Under certain conditions, the Adabas cluster SVC (SVCCLU) component of the ADASVC returns response code 251 in the ACB's response code field, along with a hexadecimal subcode (listed below in decimal) in the low-order (rightmost) two bytes of the Additions 2 field. In the case of an ACBX, the ADASVC returns response code 251 in the ACBX's Response Code (ACBXRSP) field and the subcode in the Error Subcode (ACBXERRC) field.

- If the local SVCCLU detects the condition, the subcode will range from 2 through 30.
- If a remote SVCCLU detects the condition, it will range from 102 through 130.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
2	The remote cluster nucleus to which the user is assigned cannot be accessed.
4	There are no user table entries (UTES) available for use.
5	Internal error. The nucleus specified by an internal command was not found.
7	Internal error. The user was assigned to a remote nucleus by the local system but the remote system found that the nucleus was not active.
9	Internal error. The 28-byte user ID is all zeros.
17	Entire Net-Work is not active.
19	Internal error. Invalid internal command code.
20	Remote nuclei are active; command must be assigned remotely but the remote nuclei are not accepting commands.
21	The remote image to which the user is assigned has no usable nuclei.
22	An attempt was made to assign a user remotely but Entire Net-Work is not active.
25	No system image target
26	System image target changed
27	Internal error.
28	Version mismatch between the PLXCB and the SVCCLU part of the ADASVC.
29	Probably, you used a NUCID value from a restricted range. Otherwise, this is an internal error. <i>Action:</i> Ensure that the NUCID assignments are valid.
30	More than 32 NUCIDs were detected for the same SVC/DBID combination. <i>Action:</i> Reduce the number of NUCIDs on the SVC/DBID to 32.
41	An invalid PLXCB dataspace ALET was detected during command initiation. The PLXCB is unusable. The ALET has been removed from the IDTH prefix.
45	An invalid PLXCB dataspace ALET was detected during command completion. The PLXCB is unusable. The ALET has been removed from the IDTH prefix.
43	An invalid PLXCB dataspace header was detected. The PLXCB is unusable. The ALET has been removed from the IDTH prefix.
44	A program check occurred while using the PLXCB dataspace ALET. The PLXCB is unusable. The ALET has been removed from the IDTH prefix. Under z/OS a software LOGREC (EREP) record was created.
51	All open nuclei on this node have reached the maximum number of users and are not accepting additional new users.

On open systems, an invalid utility call - versions conflict occurred.

Action For internal errors on mainframe systems, contact your Software AG technical support representative. For all other mainframe errors except as noted, contact your systems administrator.

On open systems, check whether the utilities and database nuclei are of the same version. Contact your Software AG technical support representative for assistance.

Response 252

Origin Mainframe and open systems

Explanation On mainframe systems, an error occurred during Adabas SVC processing (post error).

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, an invalid subroutine call - coding error occurred. This response may also be returned on setting the Entire Net-Work timeout via Adaset Timeout if Entire Net-Work is not correctly installed.

Action For open systems, contact your Software AG technical support representative.

Response 253

Origin Mainframe and open systems

Explanation On mainframe systems, an error occurred processing a buffer.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

The following subcodes are possible:

Subcode	Meaning
0	Buffer length 0 (ACB user only)
1	Format buffer address zero
2	Record buffer address zero
3	Search buffer address zero
4	Value buffer address zero
5	ISN buffer address zero
6	User information buffer address zero
7	Performance buffer address zero
8	Multifetch buffer address zero
9	Unsupported ABD buffer type
10	Attached buffer overrun

Subcode	Meaning
11	Unsupported ABD version
12	ACBX not accepted by target
13	Unable to convert ACBX to ACB
14	ALET value not permitted
15	Unable to process 64-bit buffer address
16	Invalid buffer location indicator
17	Logic error locating ABD
18	More than 65,535 ABDs of any single type.
19	Reserved field not zero
20	ADABDX length incorrect
1xx	An error occurred attempting to allocate a Pause Element. The subcode is 100 (decimal) added to the return code from the z/OS IEAVAPE service. <i>Action:</i> Refer to IBM z/OS documentation for IEAVAPE for an explanation of its return code. Contact your Software AG support representative for assistance.
2xx	An error occurred attempting to pause using a Pause Element. The subcode is 200 (decimal) added to the return code from the z/OS IEAVPSE service. <i>Action:</i> Refer to IBM z/OS documentation for IEAVPSE for an explanation of its return code. Contact your Software AG support representative for assistance.

On open systems, the system file is not loaded or inconsistent.

Action

For mainframe systems, subcodes 10 and 17 are internal logic errors; notify your Software AG support representative. For all other subcodes, correct the buffer specification error and rerun.

On open systems, check the system files by running ADAVFY.

Response 254

Origin

Mainframe systems only

Explanation

A validation error occurred during command completion processing while attempting to return results to the caller.

One of the following has occurred:

- An internal error occurred during processing of an attached buffer (buffer overflow)
- The CT parameter limit was exceeded. Message ADAM93 (or a similar message) is printed or displayed on the console.

If the CT parameter limit was exceeded, the nucleus terminated the user, generated the equivalent of a BT command internally, released the CQE and attached buffer space, and issued ADAM93 (or a similar message).

If the user was not terminated, the subcode in the right-most two bytes of the ACB's Additions 2 field or the subcode in the ACBX's Error Subcode (ACBXERRC) field describes the failed validity check.

- If you are running with Entire System Server, the TIME parameter limit was exceeded. Message ADAM93 (or a similar message) displays on the console.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
1	UBCQEX is less than or equal to zero
2	UBCQEX is greater than CQHNCQES
3	CQEFLAG is not equal to CQEFAB plus CQEFW16
4	CQEAUB is not equal to A'UB
5	CQEAUPL is not equal to A'APL
6	The low-order 6 bytes of CQECKSUM does not equal UBCKSUM
7	CQE was timed out
8	An inconsistency in the CQE such as the following: <ul style="list-style-type: none"> ■ The CQE was unexpectedly taken by another call . ■ The user buffer (UB) is not receiving expected user information. ■ The target move data length is inconsistent.
9	Record buffer overflow
10	ISN buffer overflow
11	Inconsistent format buffer length
12	Inconsistent search buffer length
13	Inconsistent value buffer length
14	Inconsistent user buffer length
15	Invalid attached buffer ABD index (internal logic error)
16	Buffer overflow; see ACBXERRD and ACBXERRE

Action

Ensure that the caller's control structures and parameters are not altered while the command is being processed. If you are unable to resolve the error, notify your Software AG support representative.

Response 255

Origin Mainframe and open systems

Explanation On mainframe systems, all attached buffers were allocated at the time the command was processed. Buffer allocation "high water marks" may not reflect this condition when no buffer allocation occurs.

Note: A Response 255 may also be issued by Entire Net-Work and in these circumstances the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, the Adabas command could not be processed because not enough Adabas nucleus or operating system resources are available. The value in the first two bytes of the Additions 2 field indicates the reason (2-byte binary format).

Action On open systems, perform the following actions, based on the subcode:

Subcode	Action
1	No space is available for the attached buffers. Increase the LAB (length of attached buffers) parameter.
2	No space is available in the client ID table. Increase the NCL (number of client threads) parameter.
3	Message queue generation failed. Increase the corresponding operating system parameters (please refer to the Adabas open systems installation documentation for further information).
4-6	An internal error occurred; an unexpected response code was received from a system function. Contact your Software AG technical support representative.
7 (only with ADALNKX)	The ADAMPLNK executable could not be loaded. Make this module available.
8	No space is available for extended attached buffers. Increase the value of the LABX (length of extended attached buffers) parameter.

VIII

SNA Sense Codes

11 SNA Sense Codes

Code	Explanation
082D	LU busy.
1801	Resource not available.
2001	Sequence numbering out of sequence after VTAM ABEND: /DADM PNET,vr,VARY,INACT,siehost,siegat /DADM PNET,vr,VARY,ACT,siehost,siegat

IX

12 Software AG Licensing Messages

The messages in this document may be produced by Software AG mainframe license processing or when using the license utility, LICUTIL.

MLC1001 CPU-ID {cpuid} is not defined in your product license

Explanation The CPU ID listed in the message (*cpuid*) is not defined in your product license. Either your license file is invalid or you have attempted to run the Software AG mainframe product on a machine for which it is not licensed.

Action Install and run the Software AG product on the machine for which it is licensed. If the problem persists, contact your Software AG sales representative for assistance.

MLC1002 LPAR name {lparname} is not defined in your product license

Explanation The LPAR name listed in the message (*lparname*) is not defined in your product license. Either your license file is invalid or you have attempted to run the Software AG mainframe product on a machine for which it is not licensed.

Action Install and run the Software AG product on the machine for which it is licensed. If the problem persists, contact your Software AG sales representative for assistance.

MLC1003 Machine capacity {value} higher than MSUs in your product license

Explanation The machine or the partition capacity (*value*) of the CEC or LPAR respectively on which you have attempted to install and run the Software AG mainframe product exceeds the capacity allowed in your product license. Either your license file is invalid or you have attempted to run the Software AG mainframe product on a machine for which it is not licensed.

Action Contact your Software AG sales representative for assistance.

MLC1004	The product license will expire on {date}
Explanation	This warning message provides the date (YYYY/MM/DD) when the license will expire for this Software AG mainframe product. The product cannot be started with the current product license after this date. For example, an expiration date of 2018/09/05 indicates that you can still work on 2018/09/05 until 23:59 (local time) but need a new license from the next day (2018/09/06).
Action	No action is required for this warning message. However, you should contact your Software AG sales representative to obtain an updated license soon.
MLC1005	We assume CPU-ID {cpuid} as your DR or DR testing environment
Explanation	The CPU ID listed in the message (<i>cpuid</i>) is not defined in your product license. Therefore, we assume that you are running in a disaster recovery environment.
Action	If you are running in a disaster recovery environment, no action is required for this warning message. If you are not running in a disaster recovery environment, contact your Software AG sales representative to obtain an updated license.
MLC2001	The product license is invalid
Explanation	Your product license is invalid.
Action	Contact your Software AG sales representative for assistance.
MLC2002	The product license key is invalid
Explanation	The license file for the Software AG mainframe product is invalid.
Action	Verify that the license file was transferred correctly to the mainframe host and that it is still in ASCII format. If the problem persists, contact your Software AG sales representative for assistance.
MLC2003	The product license is not for {value}
Explanation	The license file for the Software AG mainframe product is not for the operating system (OS), product code, or product version listed in the message (<i>value</i>).
Action	Use the correct license file. If the problem persists, contact your Software AG sales representative for assistance.
MLC2004	The product license has expired on {date}
Explanation	The product license has expired. The date (YYYY/MM/DD) it expired is given in the message (<i>date</i>).
Action	Contact your Software AG sales representative for assistance.

MLC2005	Tag missing in product license: {tagname}
Explanation	The tag with the name listed in the message (<i>tagname</i>) is missing in your product license.
Action	Contact your Software AG sales representative for assistance.
MLC2006	Invalid tag value in product license: {tagname}
Explanation	The value of the tag with the name listed in the message (<i>tagname</i>) is invalid in your product license.
Action	Contact your Software AG sales representative for assistance.
MLC2007	Current CPU-ID not found for product license check
Explanation	The CPU ID of the CPU on which the product license check was run is not found in the license file.
Action	Contact your Software AG sales representative for assistance.
MLC2008	The number of MSU values in the product license is incorrect
Explanation	The machine capacity covered by the product license is incorrect.
Action	Contact your Software AG sales representative for assistance.
MLC2009	ExtendedRights setting {value} not allowed under this system
Explanation	The ExtendedRights setting listed in the message (<i>value</i>) is not supported by your system.
Action	Contact your Software AG sales representative for assistance.
MLC2010	Soft capping is not allowed with ExtendedRights {value}
Explanation	Your product license does not allow soft capping with the ExtendedRights setting listed in the message (<i>value</i>).
Action	Contact your Software AG sales representative for assistance.
MLC2011	Defined hardware class in the license exceeded {value}
Explanation	The hardware class (PriceQuantity) in your product license is too small for the current machine (<i>value</i>).
Action	Contact your Software AG sales representative for assistance.

MLC2012	The number of zIIPs ({value}) exceeds the license definition
Explanation	The number of zIIP processors in the current machine exceeds the number of zIIPs (PriceQuantity) in your product license.
Action	Contact your Software AG sales representative for assistance.
MLC2013	The number of zIIP values in the product license is incorrect
Explanation	The number of zIIP values (zIIPs) in your product license does not match with the number of LPAR values (LPARs).
Action	Contact your Software AG sales representative for assistance.
MLC3001	Invalid LCPCB length
Explanation	The license check routine has been incorrectly called.
Action	Contact your Software AG support representative for assistance.
MLC3002	Work area too small
Explanation	The size of the work area for the license check routine is too small.
Action	Contact your Software AG support representative for assistance.
MLC3003	Invalid function code
Explanation	The license check routine has been incorrectly called.
Action	Contact your Software AG support representative for assistance.
MLC3004	Invalid operating system
Explanation	The ID of the operating system passed through the license check routine is invalid.
Action	Contact your Software AG support representative for assistance.
MLC3005	Invalid product code
Explanation	The product code passed through the license check routine is invalid.
Action	Contact your Software AG support representative for assistance.
MLC3006	Invalid product version
Explanation	The product version passed through the license check routine is not numeric.
Action	Contact your Software AG support representative for assistance.

MLC3007	Invalid current date
Explanation	The current date passed through the license check routine is invalid. The date must be in the format <i>yyyy-mm-dd</i> . The dash (-) delimiters are not checked but the numbers must be a valid year, month and day, respectively.
Action	Contact your Software AG support representative for assistance.
MLC3008	Tag not found
Explanation	The license check routine cannot find the requested XML tag.
Action	Contact your Software AG support representative for assistance.
MLC3009	Component Id tag not found
Explanation	The license check routine cannot find the XML tag <code>Component Id</code> .
Action	Contact your Software AG support representative for assistance.
MLC3010	Invalid search tag
Explanation	The XML search tag requested by the license check routine is invalid.
Action	Contact your Software AG support representative for assistance.
MLC3011	Insufficient I/O area size
Explanation	The size of the I/O area for the license check routine is too small.
Action	Contact your Software AG support representative for assistance.
MLC3012	Output record length too small
Explanation	The length of the output record for the license check routine is too small.
Action	Contact your Software AG support representative for assistance.
MLC3013	Error message text not found
Explanation	The license check routine cannot find the text that belongs to the requested error message.
Action	Contact your Software AG support representative for assistance.

MLC3014	Too many errors occurred
Explanation	The license check routine detected too many errors. Some messages are lost.
Action	Contact your Software AG support representative for assistance.
MLC9001	License exceeds maximum size of 8000
Explanation	Your license file is too large.
Action	Contact your Software AG sales representative for assistance.
MLC9002	Error opening license file input
Explanation	An error occurred during an attempt to open the license file input.
Action	Investigate the cause of the error, paying special attention to the corresponding error messages produced by the operating system. Contact your Software AG sales or support representative for assistance.
MLC9003	Error reading license file input
Explanation	An error occurred during an attempt to read the license file input.
Action	Investigate the cause of the error, paying special attention to the corresponding error messages produced by the operating system. Contact your Software AG sales or support representative for assistance.
MLC9004	Error opening license file assembler output
Explanation	An error occurred during an attempt to open the license file assembler output.
Action	Investigate the cause of the error, paying special attention to the corresponding error messages produced by the operating system. Contact your Software AG sales or support representative for assistance.
MLC9005	Error writing license file assembler output
Explanation	An error occurred during an attempt to write the license file assembler output.
Action	Investigate the cause of the error, paying special attention to the corresponding error messages produced by the operating system. Contact your Software AG sales or support representative for assistance.

MLC9006	License converted to assembler output records written to output file
Explanation	The license file was successfully converted to an assembler source module. Output records were written to the output file.
Action	No action is required for this informational message.
MLC9007	Error loading license module {modulename} {errorcode}
Explanation	The LOADLIC function (z/OS only) tried to load a license module from the load library and received an error (<i>errorcode</i>) from the operating system.
Action	Correct the LICUTIL input, removing duplicate LICUTIL function calls. Check that the license module (<i>modulename</i>) is in the load library, that the correct library is referenced in the JCL, and that the module name is specified correctly in the LOADLIC statement (case sensitive, a blank between LOADLIC and <i>modulename</i>).
MLC9010	LOADLIC can only be issued once, before any DISPLAY, CHECK, MAKE or READ
Explanation	The LOADLIC function (z/OS only) can only be performed once per LICUTIL session. LOADLIC must not be preceded by the DISPLAY, CHECK or READ function. These functions can only locate the license module <i>after</i> the LOADLIC.
Action	Correct the LICUTIL input, removing duplicate LICUTIL function calls. Change the call order so that the LOADLIC precedes any DISPLAY, CHECK or READ.

X Universal Encoding System (UES) Component Error Codes

13 Universal Encoding System (UES) Component Error Codes

■ Entire Conversion Service (ECS) Errors	330
■ Open Virtual Operating System Interface (OVO) Errors	332
■ COX* Universal Encoding System Conversion (UES) Errors	333

This chapter describes error codes issued by Adabas UES components and listed in other Adabas error messages.

Entire Conversion Service (ECS) Errors

The following table describes the error codes that might be produced by the Entire Conversion Service (ECS) component of Adabas UES code.

Error Code	Description
10	Error in CV call
11	Index value exceeds the maximum
12	Indexed LB cannot be used
13	Null repeat count detected
14	Data to be translated does not conform to the layout buffer
15	Send buffer length is invalid
16	TS or CVBU had already been initialized
18	Null length value specified
19	Repeat count/index value must be at least 2 digits long
20	ts_build_lb called before ts_alloc_lb was called
21	Element length exceeds the maximum
22	Error in floating point convert
23	Underflow or overflow in floating point conversion
24	TS routines called out of sequence
25	Error reading ASCII-EBCDIC mod file
26	Error opening ASCII-EBCDIC mod file
27	Syntax error in ASCII-EBCDIC mod file
28	Error opening Encoding Descriptor Definition file
29	Error reading Encoding Descriptor Definition file
30	Incomplete Encoding Descriptor Definition
31	Invalid modal escape sequence
33	Multi-thread serialization error
34	Memory allocation error
35	EDD Compile error. Invalid sequence of sections
36	Encoding Definition compilation failed
37	Invalid value for keyword
38	Subspace Dimensions Inconsistent

Error Code	Description
39	Unable to translate Encoding Descriptor Definition input line or unable to translate for output file processing
40	Invalid PVO passed to SPO allocate routine
41	Thread file resource failed
42	Write Buffer allocation failed
43	Actual fixed code point size to big
44	Logic error calculating relative char index
45	Logic error generating actual code point
46	Error reading a ECS object file
47	Logic error finding PTO to load
48	Allocated / read PTO is inconsistent EDD's PTO's out of sync
49	Relative to Character error: invalid relative index
50	Relative to Char error: out buffer overflow
51	EDD management logic error, expected entity not found
52	Bind utility object not found
53	Dangling PTO found
54	Character could not be converted to rel index
55	Translation buffer overflow. Truncation of non blank character
56	No thread local LBT available
57	Multi-thread Lock failed
58	Default translate objects not found
59	Bind statement syntax error in init file
60	Thread resource unavailable
61	Local objects present or already connected
62	Error when saving dynamic PTO: either UNICODE is source or target or I/O error
63	General character translation error
64	Invalid conversion handle
65	Handle capacity exceeded.
66	Runtime parameter could not be set
101	Invalid float field length
102	Warning - invalid flag or flags detected in RDA header
103	Invalid source floating point number
104	Warning - underflow occurred in float conversion
106	Warning - overflow occurred in the float conversion
107	Bad conversion parameters: source/destination encodings are equal or both UNICODE encodings
108	Multi-thread allocation error

Error Code	Description
109	Inline Work area allocation failed
110	Warning - truncation of nonblank characters
111	No DBCS PVO available
112	Bad untranslatable character
113	Bad fill character
114	DBCSONLY conversion of non-DBCS character
115	Non UNICODE character has no UNICODE PRECOMPOSED equivalent. Thus it cannot be decomposed.
116	Invalid modal fill. i.e., length > 0 but no room for mode change
121	Invalid integer field length
166	Runtime parameter could not be set

Open Virtual Operating System Interface (OVO) Errors

The following table describes the error codes that might be produced by the Open Virtual Operating System Interface (OVO) component of Adabas UES code.

Error Code	Description
-1	Parameter error
-2	No more space available
-3	String truncated
-4	File already open
-5	Invalid file name
-6	End of file or directory
-7	Operating system error (e.g., file/member not found or locale not supported)
-8	Undefined file handle
-9	File is not open
-10	New File already exists
-11	File not opened for read/write
-12	Function not supported
-13	File does not exist
-14	I18N Conversion not supported
-15	Unable to convert string (file name)
-16	Internal structure corrupted
-17	File locked by other process

COX* Universal Encoding System Conversion (UES) Errors

COX01I	ADACOX exit V{v.r.1} {date} active
Explanation	Informational message showing the version and assembly date of the ADACOX module.
COX02I	ADACOX converting {source} to {target}
Explanation	Informational message indicating that conversions from source to target will be done by ADACOX.
COX03I	ADACOX {source} to {target} count {number} AVG {time (usec)}
Explanation	Informational message at session termination. This message is output only if ADACOX has performed conversions between source and target encodings. <i>number</i> shows the number of conversions and time the average time for conversion in microseconds.

XI

User Abend Codes

14 User Abend Codes

The decimal abend (abnormal end) codes described in this chapter occur in ADAI_{nn}, ADARUN, and in some utility messages or during replication or transaction manager processing. The message ADAM99 presents both system and nucleus STAE abend codes in hexadecimal; in this case, a nucleus abend code must first be changed to decimal before the description can be located here.

Most abend codes (except 20) result from errors that normally require assistance from your Adabas support technical representative. If abend codes 23 or 24 occur, save the Work data set. For all abend codes, save any dumps and note any messages or other indications that the system issues. Advise your Adabas technical support representative of the error.



Note: Entire Net-Work issues only the abend code 253 to indicate an abnormal termination occurred. The abend (abnormal end) codes described in this chapter are issued primarily by Adabas modules operating with Entire Net-Work. Specific information related to an error is given in the messages written to the print data set.

Code	Module	Explanation
15	(nucleus)	Workpool too small to execute session autorestart.
16	(nucleus)	DTP=RM: Two-phase commit logic error.
17	(nucleus)	DTP=RM: Work-part-4 overflow.
19	(nucleus)	DTP=RM: Two-phase commit logic error.
20	(nucleus)	Error during system startup (refer to descriptions of nucleus startup errors in <i>Adabas Messages and Codes</i>).
21	(nucleus)	I/O error during asynchronous buffer flush (Asso/Data/Work/PLOG).
22	(nucleus)	I/O error on sequential PLOG and PLOGRQ=YES/FORCE in effect.
23	(nucleus)	WORK overflow.
24	(nucleus)	Autostart canceled - protection area inconsistent.
25	(nucleus)	Logical I/O error: Adabas was unable to track one or more I/O operations).

Code	Module	Explanation
26	(nucleus)	Adabas session canceled by operator command.
27	(nucleus)	Session ended due to work pool space problems.
28	(nucleus)	Nucleus problem during an asynchronous buffer flush.
29	(nucleus)	Adabas Transaction Manager (ATM) initialization failed. Review the console messages for further information about the error.
30	(nucleus)	Adabas Transaction Manager (ATM) interface error.
31	(nucleus)	Insufficient workpool space for only active command.
32	(nucleus)	Internal error processing search algorithm 3 command.
33	(nucleus)	Logic error during file number validation.
33	ADARAC	Recovery Aid logic error.
34	utilities	Abnormal termination with dump.
35	utilities	Abnormal termination without dump.
36	utilities	I/O error occurred while writing to DDDRUCK or DDPRINT. Check JCL.
37	(nucleus)	ET post logic error.
38	(nucleus)	Unexpected response code for internal command.
39	(nucleus)	Fatal internal response code occurred during asynchronous buffer flush.
40	(nucleus)	Getmain failure early during session start.
40	ADACOM	Fatal error during ADACOM processing (cluster environments).
41	ADADSFN	Fatal error during Delta Save Facility processing.
42	(nucleus)	A security violation occurred at startup.
43	(nucleus)	Logic error in command selection (freeze table).
44	(nucleus)	Logic error in an FST write or an online process.
45	(nucleus)	Logic error in asynchronous buffer flush by volume (with ASYTVS=YES)
46	(nucleus)	Logic error in the buffer pool manager.
47	(nucleus)	Logic error in thread management
48	(nucleus)	Logic error in ADANCX (cluster environments).
49	(nucleus)	General internal error (various reasons)
50	(nucleus)	Logic error in SRB code (Adabas Cluster Services)
51	(nucleus)	Logic error in dynamic Work access
52	(nucleus)	STCK clock not running
53	(nucleus)	Logic error in global hold queue element lock handling
54	(nucleus)	Logic error in global file lock handling
55	ADACLU	Fatal error during ADACLU processing (cluster environments).
56	(nucleus)	Logic error in ET synchronization process

Code	Module	Explanation
57	(nucleus)	Unexpected error during online recovery
58	(nucleus)	Error in protection record bookkeeping
59	(nucleus)	Logic error during large object (LB) processing
60	(nucleus)	Unique descriptor update logic error
61	(nucleus)	Logic error in system field update
65	(replication)	Fatal error related to replication processing.
66	(replication)	Logic error in initial-state processing
67	(replication)	Logic error in SLOG handling
70	(nucleus)	Parallel Services nucleus canceled by peer nucleus
71	(nucleus)	Logic error or bad data in protection data area extension on Work data set
72	(nucleus)	Logic error in protection data publishing
79	(nucleus)	Uncorrectable intracluster communication failure
80	(nucleus)	Logic error in update tracking
82	(nucleus)	Logic error in file activity bookkeeping
83	(nucleus)	Logic error in extended MU/PE handling
84	(nucleus)	Logic error in spanned record handling
85	(nucleus)	Logic error in spanned record read-lock handling
86	(nucleus)	Logic error in Adabas Fastpath multifetch processing
87	(nucleus)	Logic error in multiple buffers
89	(nucleus)	Logic error during global update command synchronization
90	(nucleus)	Logic error when updating a compressed record
91	(nucleus)	Internal error
92	(nucleus)	Logic error during increase of an address converter extent
93	(nucleus)	Logic error when processing an online function
94	(nucleus)	Logic error in special descriptor decompression
95	(nucleus)	Logic error during AAD,AA handling
96	(nucleus)	Logic error in command selection
108	ADATRA	Failure to load and install the trace module
109	ADAZIP	Fatal error related to the execution of Adabas code on a System z Integrated Information Processor (zIIP)
220	MPMVSE	FREEVIS problem
221	MPMVSE	Invalid operating system
222	MPMVSE	Invalid function
227	MPMBS2	Wrong ADARER module found
228	MPMBS2	STXIT not successfully installed
229	MPMBS2	Invalid function in dependent MPM call

Code	Module	Explanation
231	MPMBS2	The command queue referenced in the ID table does not match the target ID in the call
232	MPMBS2	The ID table is being referenced but the MPM has a zero (0) address
233	MPMBS2	Adabas canceled in BOURSE WAIT (see the ADAM82 message description in <i>Adabas Messages and Codes</i>).
234	MPMBS2	Enqueue to IDT failed (BS2000)
235	MPMBS2	Unable to acquire memory for MPM client table UTAB (BS2000)
245	MPMMVS	Error locating ADAIOR in ESTAE recovery routine
246	RAOSSYDI (Adabas Review)	An error occurred when writing a message to the console (WTO).
247	MPMMVS	Unsuccessful STAE
248	MPMMVS or MPMF4	Invalid operating system or RMODE; for MPMF4, invalid operating system or RMODE; or CID GETMAIN failed The operating system check did not recognize a "known" operating system. The known system is z/OS. For z/OS: if the nucleus is running AMODE 31, then RMODE 24 was not set for at least one Adabas module other than ADALNK.
249	MPMMVS	Invalid function
251	ADARST	Unrecoverable abend of the Adabas Review subtask ADARST. See the ADAM90 message description.
252	IORSUB	Unrecoverable subtask abend. See the ADAM90 message description.
253	MPMIND	Nonrecoverable abend (caused by STAE/STXIT processing program check or nucleus abend) See the ADAM99 message description in <i>Adabas Messages and Codes</i> .
254	MPMIND	Invalid function in abnormal termination Recovery exit
255	MPMIND	Invalid function
257	MPMVSE	Return code on 24-call from FREEVIS
435	ADASIP	The specified subsystem name is already being used by another ADABAS SVC. This ABEND is accompanied by message ADAS16. Select another subsystem name and rerun the job.
436	ADASIP	The currently installed SVC is using a different subsystem. This ABEND is accompanied by message ADAS16 and may be overridden by the FORCE=Y parameter.
437	ADASIP	There are one or more potentially active targets in the IDT of the specified SVC. This ABEND is accompanied by message ADAS17 and may be overridden by the FORCE=Y parameter.
454	SVCVSE	SVC 04-call buffer address error
455	SVCVSE	SVC 16-call buffer address error
456	SVCVSE	SVC work area allocation error
470	SIPMVS	SVCMVS load error
471	SIPMVS	Incorrect SVCMVS

Code	Module	Explanation
472	SIPMVS	SSCT disappeared
473	SIPMVS	ADASIR non-zero return code
474	SIPMVS	SVC table entry changed
475	SIPMVS	SSCT already exists
476	LNKBS2	Request for user buffer memory in ADALNK failed
	SIPMVS	GETMAIN error
477	SIPMVS	Incorrect ADASIR
478	SIPMVS	ADASIR load error
479	SIPMVS	ADASIR or ADASVC were not found in the load libraries provided to the ADASIP job
480	SIPMVS	Open error
481	SIPMVS	EXEC PARM error
482	SIPMVS	SIPMVS not authorized
485	LNKBS2	Unsupported function
	LNKBTO	
	LNKIX1	
486	SVC MVS	Invalid PCR04 call
487	SVC MVS	Caller specified an unknown or invalid target. This is possibly caused by restarting an already active target using FORCE=YES.
488	SVC MVS	Invalid PCR16 call
489	SVC MVS	Invalid 48-call parameters
490	MPMBS2	Target ID table may only be changed by a communicator
	SVC MVS	
491	SVC MVS	SVC 12-call without 16-call required
	SVCVSE	
492	SVC MVS	Active dormant LX
493	SVC MVS	Invalid 00-call parameters
494	SVC MVS	Caller not authorized
496	SVC MVS	No IDT
497	SVC MVS	Invalid function
498	LNKBTO	Invalid UB
	LNKIX1	
499	LNKBTO	Length of user info less than zero
	LNKIX1	
500	LNKBS2	Error in link initialization routine
	LNKBTO	
	LNKIX1	

Code	Module	Explanation
501	LNKBTO	Incorrect router version
	LNKIX1	
502	LNKBTO	User exit before-call increased length of user info
	LNKIX1	
509	IORMVS	DEB error
513	SVCVSE	Invalid SVC-08 call
515	IORIND	GTALNK error
516	IORIND	RWINT error
517	IORIND	RWINT Cache Fast Write request error
519	IORIND	UPELE error
539	IORSUB	FVSE error
540	IORSUB	FVST error
545	IORMVS	BCP storage error
547	IORMVS	Initialization error
548	IORMVS	BCP error
549	IORMVS	DLECB error
550	IORMVS	QEDIT (block) error
551	IORMVS	CHKIO error
559	IORMVS	Incorrect SVC version
560	IORMVS	Maximum blocks/track > minimum, I/O error, global sequential BLKSIZE too big, or invalid number (ECBS)
561	IORMVS	EVENTS error
563	IORBS2	Invalid TDCE found during ADAIOR INIT
564	IORBS2	Failure to load ADAIOI or AT when trying to enable EVENT NAME
565	IORBS2	ECB list overflow
566	IORBS2	Invalid SOLSIG return code
567	IORBS2	Cannot load ADAONR
568	IORBS2	BCP error
569	IORBS2	WTOR error
570	IORBS2	CHKIO error
571	IORBS2	Invalid ECB type
572	IORBS2	Invalid event checksum
573	IORBS2	SOLSIG RC operator commands/EOC
574	IORBS2	No multiple RSOFEI postcode mem
577	LNKCX	User exit before-call increased length of USER INFO
578	IORVSE	CHKIO error

Code	Module	Explanation
579	LNKCX	Error in link initialization routine
580	LNKCX	Length of user info less than 0 (greater than 32K)
581	LNKCX	Incorrect router version
582	LNKCX	Invalid UB
583	IORMVS	QEDIT (CIBCTR) error
584	LNKCX	Unsupported function
591	IORVSE	EVENTS error
592	IORVSE	GETDVS error
593	IORVSE	IVST error
594	USBTO	Invalid RMODE
595	IORVSE	EXTRACT error
596	IORVSE	GETLBL error
597	IORVSE	TOPMSG error
598	IORMVS	ADECB error
599	IORVSE	ADECB error
600	IORVSE	DLECB error
601	IORVSE	SUBSID error, invalid version, or ADAIOI could not be loaded
602	IORVSE	CKTDC error
603	IORVSE	Global sequential block size too big or invalid number (ECBS)
604	IORVSE	GETTVS error
605	IORVSE	Invalid printer device
606	LNKBS2	Unsupported ADALNK function code
607	LNKBS2	UB flags in ADALNK asynchronous call incorrectly set
608	LNKBS2	Length of user info less than 0 (greater than 32K)
609	LNKBS2	Unable to acquire ID table common memory
610	LNKBS2	User information length at ADALNK before-call too small
611	LNKBS2	WAIT error
612	RERBS2	IDT (identification table) common memory not accessible in router
613	RERBS2	Invalid router function code
614	SVCVSE	Invalid function via caller
615	SVCVSE	No IDT (identification table)
616	SVCVSE	Invalid 00-call parameters
617	SVCVSE	Invalid 40-caller
618	SVCVSE	Caller specified an unknown or invalid target. This is possibly caused by restarting an already active target using FORCE=YES.
619	LNK _{xx}	Invalid SVC number in link routine

Code	Module	Explanation
	SVCVSE	Power job error in SVC
620	IORIND	IOR fatal error
622	LNK _{xx}	Invalid SAVE area in UB (LUEXIT1). SAVE area (USERSAV) in the Adabas link routine was less than 72 bytes and user exit 1/2 (B/A in Adabas 7) was invoked.
627	IORVSE	64-bit I/O not supported for dev
628	IORVSE	GETMAIN error during startup
	IORMVS	
629	IORVSE	ADAOPTD could not be found, or could not be loaded into storage
631	IORVSE	GETVIS failed for sequential file table
632	IORVSE	No more slots in sequential file table
633	IORVSE	Internal error file name not found
634	IORVSE	Return code from LABEL macro greater than 4
635	IORVSE	PFIX/PFREE issued from dynamic partition
639	LNK _{CX}	A CICS GETMAIN request failed.
640	LNK _{BS2}	No memory available for BS2000 LNK anchor block
640	ADALNK	No memory available for LNK anchor block (BS2000)
641	LNK _{BS2}	The SM6 ADALNK detected a router at 5.2 SP5 level or lower. The ID Table must be initialized with an Adabas nucleus at level 5.2 SP6 or higher.
642	LNK _{BS2}	The ADALNK cannot read the DDLNKPAR parameter file; the file may be empty, or it may be an ISAM file. Use a SAM/V data set that was created by EDT.
643	LNK _{BS2}	The ADALNK detected a syntax error in the DDLNKPAR parameters. Correct the syntax and rerun.
645	LNK _{CX}	The CICS macro level interface is not supported for CICS/ESA 3.2 and above.
646	IOR _{BS2}	Cannot read the SYSDTA data set; see the message ADAI56 description.
647	LNK _{BTO}	Invalid reentrant work area address
	LNK _{I_X1}	
648	LNK _{I_X1}	Invalid AIBTDLI entry address
649	LNK _{CX}	CICS TWA not present or too short
	LNK _{I_X1}	AIBTDLI INQY ENVIRON call failed
652	LNK _{BS2}	Invalid PAL
	LNK _{BTO}	
	LNK _{CX}	
	LNK _{I_X1}	
653	LNK _{CX}	Attempted double wait on UB element

Code	Module	Explanation
654	ADALNK	ADALNK: unsupported operating system version, unsupported HSI. Adabas version 6.1 and above requires BS2000 version 10 and above and XS31 hardware.
655	ADALNK	Incompatible versions of ADALNK and ADAL2P. Check library assignments; check TSOSLNK/BINDER protocols. See message ADAK09.
656	ADALNI	An internal error occurred when the IMS link routine could find the proper IMS structures to properly set the value for the <i>userid</i> (the last eight bytes of the 28-byte Adabas communication ID). When this user abend occurs, contact your Software AG support representative and provide a dump including the registers at time of the abend so the reason code stored in R15 can be seen and evaluated.
657	LNCBTO	Dynamic SVC lookup table missing
	LNCCKX	
	LNCIX1	
658	LNCBTO	LNCUES module not available to ADALNK
	LNCCKX	
	LNCIX1	
659	SVC MVS	PC routine invoked by invalid caller.
660	LNCCKX	CICS instructed ATM to perform a single-phase commit, but the outcome of the attempted commit could not be determined.
661	SVC MVS	Name/Token service error.
662	LNCBTO	Program cancel from UEXITR
	LNCCKX	
	LNCIX1	
663	LNCCKX	LNCSTUB DCI initialization failed
664	LNCBTO	SVC incompatible with install program
	LNCCKX	
	LNCIX1	
	SVC MVS	
	SVCVSE	
665	SVC MVS	Invalid SVC caller
	SVCVSE	
666	RERBS2	Invalid AB deallocation length
	SVC MVS	
	SVCVSE	
667	SVC MVS	Unsupported z/OS release or missing CPU features. ArchLvl 2 (64-bit) is required.

Code	Module	Explanation
668	ATMCXRMI	A syncpoint operation was triggered by an Adabas command, but the user's communication ID was not known
	LNKCX	
	LNKIX1	
669	SVCMVS	S64 recovery routine manager error.
670	link routines	The CICS EXTRACT command used to obtain the Adabas Task Related User Exit (TRUE) global work area failed. The Adabas 8 or enhanced Adabas 7 CICS environment is not correctly established. To determine the cause, consult the messages associated with starting the Adabas TRUE issued from ADAENAB (if you are running Adabas 7) or from ADACIC0 (if you are running Adabas 8).
671	RERBS2	Attempted router call to shared 64-bit storage Recovery Routine Manager (RRM) on BS2000. Not available on this platform.
672	SVCMVS	IDT extension not provided. Possible incorrect version of ADASIR (z/OS) or ADAIPR (z/VSE).
	SVCVSE	
673	SVCMVS	Invalid PCRCLU caller.
674	link routines	A version 8 call using the ACBX has been made, but the link routine did not detect a valid reentrancy token in direct call (field APLXRTOK) of the Adabas 8 parameter list.
675	LNKCX	ADL consistency exit not linked
676	link routines	The work area passed to an Adabas 8 link routine in the direct call (field APLXRTOK of the APLX) was invalid, or the attempt to obtain storage for the work area failed.
677	LNKCX	CICS GETMAIN for a UB failed
678	link routines	The Adabas 8 link routine could not find the address of a link global table, either because it was not linked with the Adabas 8 link routine, or because an attempt to load the link globals table failed. In BS2000 environments, the memory pool accessed does not contain an Adabas ID table.
679	LNKBS2	Unable to set up the DBID/IDT Table (Get Memory error)
	LNKBTO	ADATMZ invalid header provided
680	LNKBS2	Could not get router ID table memory pool. Check the ID table name in the parameter file/module.
	LNKBTO	ADATMZ unable to obtain work area
	LNKCX	
681	LNKCX	There was insufficient SAF authorization to issue a CICS EXTRACT EXIT command. Ensure that all users of the Adabas link module have UPDATE access to the EXITPROGRAM CICS command resource identifier.
682	LNKCX	TRUE name cannot be located

Code	Module	Explanation
683	LNKBTO	Multiple ECB wait not supported
687	IOSMVS	Error queuing parallel request
688	ADAIOR	Fatal error during a switch from SRB to TCB mode when Adabas is zIIP-enabled
689	ADAIOR	Fatal error during a switch from TCB to SRB mode when Adabas is zIIP-enabled
690	ADAIOR	A call has been issued in SRB mode, but Adabas is not zIIP-enabled
691	IOSMVS	Error leaving or joining enclave
692	ADAIOS	Dataset allocation error
800	NETSIP/OS	Invalid operating system detected - not MVS
801	NETSIP/OS	Parameter error detected
802	NETSIP/OS	Addressing or residency mode, authorization error or operating system is not a virtual machine guest
803	NETSIP/OS	Error detected during program loading or validation
804	NETSIP/OS	Space allocation failure
806	NETSIP/OS	NETSIR initialization failed

XII

■ 15 AAF* - Adabas SAF Security Messages	351
■ 16 SAF Return Codes	357
■ 17 SAF Internal Function Codes	359
■ 18 AAS* - Adabas Administration Services Messages	361
■ 19 AAUD* - AUDITLOG Messages	409
■ 20 ACLX* - Adabas Review Interface Messages	411
■ 21 ADAA* Adabas Auditing Messages	413
■ 22 ADACM* - ADATCP Messages	419
■ 23 ADAD* Abend Code Messages	425
■ 24 ADAE* Adabas SAF Security (ADASAF) Messages	427
■ 25 ADAF* - Event Replicator for Adabas Messages	431
■ 26 ADAH* - Dump Formatter Status Messages	543
■ 27 ADAI* - ADAIOR System Messages	545
■ 28 ADAJ* System Messages	565
■ 29 ADAK* System Messages	567
■ 30 ADAL* - Command Log (CLOG) System Messages	579
■ 31 ADAM* -- ADAMPM System Messages	583
■ 32 ADAQ* - Adabas Review Hub Messages	601
■ 33 ADAR* System Messages	605
■ 34 ADAS* (Adabas SVC) System Messages	611
■ 35 ADASIP* (Adabas z/VSE SVC) System Messages	619
■ 36 ADASM* Adabas SMF Processing Messages	629
■ 37 ADAU* Utility Status Messages	631
■ 38 ADAX* - Adabas Cluster Nucleus Messages	649
■ 39 ADAZ* - ADAZIP System Messages	697
■ 40 AFP* - Adabas Fastpath Messages	701
■ 41 APSPSX* - ADAECS or ADATCP Messages	711
■ 42 AREV* - Adabas Review Hub Messages	713
■ 43 ARF* - Adabas Event Replicator Subsystem Messages	719
■ 44 ARMT* - Adabas Review Interface Messages	759
■ 45 ARST* - Adabas Review Interface Messages	761
■ 46 ART* - Event Replicator Target Adapter Messages	763

■ 47 ARVU* - Adabas Review Interface Messages	799
■ 48 ARXM* - Event Replicator for Adabas Messages for Event Replicator Target Adapter	811
■ 49 ATM* - Adabas Transaction Manager Messages	815
■ 50 Adabas Transaction Manager Error Codes	845
■ 51 AVInnn - Adabas Vista Database Processing Messages	861
■ 52 AVI-xxxx-xx - Adabas Vista Processing Messages	863
■ 53 CAS* - Adabas System Coordinator Cluster Application Service Messages	865
■ 54 COR* - Adabas System Coordinator Kernel Messages	871
■ 55 CORD* - Adabas System Coordinator Daemon Messages	883
■ 56 CWARN* - Caching Facility Error Messages	897
■ 57 DSF* - Delta Save Facility Messages	901
■ 58 DSP* - Cluster Data Space (ADADSP) Messages	927
■ 59 LNKRVX* Adabas Review Link Routine Messages	933
■ 60 PLI* - ADACOM Initialization Messages	935
■ 61 PLX* - ADACLU Messages	951
■ 62 PL6* - PRILOG6 Print Program Messages	963
■ 63 POP* - Adabas System Coordinator Server Component Messages	967
■ 64 Adabas Review 00xxx Messages	971
■ 65 Adabas Review 20xxx Messages	1037
■ 66 REVH* - Adabas Review Hub Messages	1069
■ 67 RTP* - Adabas Review Trans- port Messages	1075
■ 68 RVCL* - Adabas Review Batch Client Reporting (REVCLRP) Messages	1077
■ 69 SAF* - SAF Daemon Messages	1081
■ 70 SAGE* - z/VSE Batch Job Exit Utility Messages	1085
■ 71 SAGI* - Batch Initialization Messages (z/VSE Only)	1087
■ 72 SEFM* - ADASAF SAF Interface and SAF Security Kernel Messages	1091
■ 73 SM-PIN* - PIN Routine Messages	1103
■ 74 XTS* - Software AG Internal Transport Subsystem Messages	1105

15 AAF* - Adabas SAF Security Messages

AAF001 Unable to load required modules

Explanation A required module could not be loaded. Operation terminates with an abend U0042.

Action Check that all required modules are available.

AAF002 Unable to allocate required storage

Explanation There is insufficient memory available for ADASAF to operate. Operation terminates with an abend U0042.

Action Increase the amount of memory (above the 16-megabyte line) available to the failing job.

AAF003 dbid Unable to allocate NRS storage

Explanation ADASAF needs approximately 2KB of memory below the 16-megabyte line. If the memory is not available at initialization (or after a `newcopy` operator command), ADASAF issues this message and operation terminates.

Action Ensure that enough memory is available.

AAF004 dbid Module xxxxxxxx not loaded

Explanation The indicated module could not be loaded during initialization or during the `newcopy` operator command. If the module is required (rather than optional), operation terminates.

Action Ensure that the module is available.

AAF005 dbid Invalid parameters detected

Explanation One or more invalid parameters were specified in DDSAF. Operation terminates.
Action Correct the invalid parameters.

AAF006 dbid Allocation of user file cache failed

Explanation ADASAF allocates a user file cache above the 16-megabyte line. If the storage is not available at initialization (or after a `newcopy` operator command), ADASAF issues this message and operation terminates.
Action Ensure that enough storage is available or reduce the `MAXFILES` parameter (this may adversely affect performance).

AAF007 dbid INPUT PARAMETER

Explanation ADASAF echoes the parameters read from DDSAF for information and auditing purposes.
Action None.

AAF008 dbid Invalid parameter: INPUT PARAMETER

Explanation ADASAF detected incorrect input in DDSAF. AAF008 is issued for each invalid parameter found and is followed by message AAF005.
Action Correct the invalid parameter.

AAF009 dbid Allocation of Password/Cipher Code cache failed

Explanation There is insufficient storage available above the 16-megabyte line to allocate the table. Each entry requires 16 bytes and the table has a 32-byte header. Operation terminates.
Action Ensure that enough storage is available.

AAF010 dbid Password/Cipher Code cache too small - increase MAXPC

Explanation ADASAF found more passwords and/or cipher codes in RACF than it could store in its table. Operation terminates.
Action Increase the `MAXPCC` parameter.

AAF011 dbid Error extracting Passwords/Cipher Codes from RACF

Explanation ADASAF could not extract passwords and cipher codes from RACF. Operation terminates.
Action Check that you have specified the correct resource class and entity name format. Activate tracing and check for any errors or warnings. Check the system log for RACF messages.

AAF012 dbid Adabas SAF VX.X.X is active in XXXX mode

Explanation ADASAF has successfully initialized in FAIL or WARN mode, as indicated by XXXX.
Action None.

AAF013 dbid Nucleus Administration (DBADMIN) is active in XXXX mode

Explanation The DBADMIN configuration parameter is set to Y enabling nucleus administration function security in FAIL or WARN mode, as indicated by XXXX
Action None.

AAF015 dbid Newcopy of Configuration module failed

Explanation After a *newcopy* operator command, ADASAF was unable to reload SAFCFG. Operation terminates.
Action This error occurs only if there is a shortage of storage or the module SAFCFG was deleted from the load library after initialization. Determine which of these is the case and correct it.

AAF016 dbid Newcopy reinitialization failed

Explanation This message appears after a failure during *newcopy* processing. It should be accompanied by a more detailed error message specifying the nature of the failure.
Action Take the action recommended by the accompanying message.

AAF017 dbid Not APF authorized

Explanation ADASAF must run APF-authorized. Operation terminates.
Action Check that all STEPLIBs are in the APF list and that ADARUN is linked with AC(1).

AAF018 dbid No security details for job JOBNAME

Explanation This message appears when an unsecured Adabas call is received from the indicated job.
Action The most likely cause is an installation error, either of the Adabas Router security extensions or of the Adabas link module.

AAF019 dbid ADASAF initialization error(s) - Nucleus will terminate

Explanation This message appears after an initialization error and is preceded by a more specific error message.
Action Take the action recommended by the accompanying message.

AAF020 dbid Unable to add ADASAF Smart Management PIN

Explanation This message appears during initialization if ADASAF fails to activate its Adabas Error Handling interface.

Action None. ADASAF continues, with its Error Handling interface disabled.

AAF021 dbid NOTOKEN is set - calls from unsecured clients are allowed

Explanation The configuration option NOTOKEN has been activated. No security checks will be performed for unsecured mainframe clients.

Action None.

AAF022 dbid Incompatible Configuration module detected

Explanation ADASAF has detected an incompatible Configuration module. The nucleus session terminates.

Action Ensure that the Configuration module is created using the macros supplied with the version of ADASAF you wish to use.

AAF023 dbid Invalid xxx parameter returned by ADASAFX2

Explanation Your password/cipher code exit has returned incorrect data, as indicated by xxx:

- type: the returned code type was neither password nor cipher code
- code: no password/cipher code was returned
- file: no file number was returned

The nucleus session terminates.

Action Correct your exit.

AAF024 ADASAF installation error: SAFPMAC not linked REUSable

Explanation ADASAF cannot initialize because the module SAFPMAC has not been linked with the REUS attribute. The nucleus session terminates.

Action Ensure that SAFPMAC is linked REUS, NORENT.

AAF028 dbid SAF Kernel initialization error - Nucleus will terminate

Explanation The SAF Kernel could not initialize for some reason (indicated by a SEFMxxx message preceding the AAF028 message). The Adabas nucleus terminates.

Action Correct the problem which prevents the SAF Kernel from initializing (for example, increase region size or modify SAFCFG options) and restart the Adabas nucleus.

AAF029 dbid No access to class/resource

Explanation The execution security check made when starting a nucleus or utility has failed. The job abends U0042. *Class* and *resource* show the resource class and profile name against which the check was made.

Action Check that the security class and resource name are correct and that they have been defined to the external security system, with the appropriate access permissions.

AAF030 dbid Incompatible version of SAFKRN detected

Explanation The SAFKRN module in use by this nucleus or daemon is not compatible with this version of Adabas SAF Security.

Action Ensure that you use the correct version of the Adabas Limited libraries, as documented in the Installation Prerequisites section Adabas Limited Library.

AAF031 dbid Utility execution permitted because FAILUTI=NO

Explanation An Adabas utility security check failed. However, the utility is allowed to execute because the SAFCFG FAILUTI parameter is set to NO.

Action None.

AAF032 dbid Ignoring invalid SAFTRT

Explanation A site defined translation table SAFTRT has been detected which does not begin with the eye-catcher "SAFTRT" and is therefore determined to be invalid. The default internal translation table will be used instead.

Action Check the SAFTRT assembly and ensure the site defined translation table is of the correct format. Refer to the sample SAFTRT member supplied on Adabas Limited source library for the correct format.

AAF033 dbid Incompatible version of SAFPSEC detected

Explanation The SAFPSEC module in use by this nucleus or daemon is not compatible with the currently installed version of Adabas SAF Security.

Action Ensure that you use the correct version of the Adabas Limited libraries, as documented in the "Adabas Limited Library" section of the "Software Prerequisites" section of the Adabas SAF Security Installation.

AAF034 dbid SNEWCOPY in progress – operator command ignored

Explanation Adabas SAF Security operator commands are ignored while newcopy processing is in progress.

Action Wait a while and issue the operator command again.

AAF036 dbid UTI value and utility version incompatible. Default to UTI=1

Explanation The utility version is not compatible with a UTI configuration parameter value greater than 1. The current setting is overridden with the default value of 1.

Action None.

AAF037 dbid XXXXXXXXX version not supported

Explanation The version of the grouping table indicated by XXXXXXXXX is not compatible with the version of Adabas SAF Security.

Action Assemble a grouping table that is compatible with the version of Adabas SAF Security.

AAF038 dbid No access to the following resource for class XXXXXXXX:{ resource-name}

Explanation The security check made when starting a nucleus or utility has failed. XXXXXXXX and *resource-name* show the resource class and resource name against which the check was made.

Action Check that the security class and resource name are correct and that they have been defined to the external security system, with the appropriate access permissions.

AAF101 SAF VIOLATION

Explanation The operator command is not permitted for this Adabas nucleus.

Action Review operator command security definitions for this Adabas nucleus.

AAF102 NO ADAEOPTB

Explanation ADAEOPTB (operator command grouping table) is in use but does not contain an entry for this operator command.

Action Ensure the operator command was entered correctly. Review the contents of ADAEOPTB and add this command if necessary.

AAF103 AAF NOT FOUND

Explanation ADAEOPV could not locate the Adabas SAF Security load module.

Action Review the Adabas SAF Security installation and ensure that it is active in this Adabas nucleus.

16 SAF Return Codes

ADASAF and the SAF Security Kernel display an eight-byte code containing various return and reason codes from SAF. This information is shown in a number of messages denoted "SSSSSSSS".

The SAF and ADASAF return codes contains the following structure:

Position Within Message Code	Information Content
Byte: 1	SAF return code (R15 after RACROUTE)
Byte: 2	Function code (see section <i>SAF Internal Function Codes</i>)
Byte: 3	RACROUTE return code
Byte: 4	RACROUTE reason code
Byte: 5-8	Internal reason code

The SAF trace messages written to DDPRINT, when GWMSGGL is not 0, include the first four bytes of the following information, printed as eight hexadecimal digits. The ADASAF trace messages include the first four bytes of the following information, also printed as eight hexadecimal digits:

Position Within Trace Message	Information Content
Digits 1 and 2	SAF return code (R15 after RACROUTE)
Digits 3 and 4	Function code (see section <i>SAF Internal Function Codes</i>)
Digits 5 and 6	RACROUTE return code
Digits 7 and 8	RACROUTE reason code

Refer to the *IBM Security Server RACROUTE Macro Reference* manual for a thorough explanation of all possible return/reason codes. CA-Top Secret and CA-ACF2 can provide different return code values in some circumstances.

17 SAF Internal Function Codes

SAF Security Kernel and ADASAF internal function codes include:

Function Code (Hex)	Description
00	Authorize Natural Library
04	Authorize Adabas access
08	Authorize SYSMAIN function
0C	Authorize Natural system files
10	Authorize Natural program execution
14	Authorize Broker service
18	Authorize Entire Net-Work access (Net-Work SAF Security) or Adabas cross-level access (Adabas SAF Security) or RPC execution (Natural SAF Security).
1C	Authorize SQL Server access
44 or 6C	Authenticate user

18

AAS* - Adabas Administration Services Messages

AAS0001I	Processing ADABAS v6.3 only
Explanation	Adabas Administration Services is processing Adabas 6.3 databases only.
Action	No action is required for this informational message.
AAS0002I	Processing ADABAS v6.4 only
Explanation	Adabas Administration Services is processing Adabas 6.4 databases only.
Action	No action is required for this informational message.
AAS0003I	Unable to load the AIF library rc={respcode}
Explanation	Adabas Administration Services was unable to load the required AIF library. The response code from the attempt is given in the message.
Action	Review the meaning of the response code to identify and resolve the problem. If the problem persists, contact your Software AG technical support representative.
AAS0004I	Unable to identify Adabas path and load the AIF library
Explanation	Adabas Administration Services was unable to identify the Adabas database location and load the AIF library.
Action	Contact your Software AG technical support representative for assistance.
AAS0005I	Adabas Path={path}
Explanation	Adabas Administration Services located the Adabas database at the path identified in the message.
Action	No action is required for this informational message.

AAS0006I	Adabas Administration Service for {platform} is initializing on {date}
Explanation	Adabas Administration Services is initializing. The platform on which it is initializing and the date are given in the message.
Action	No action is required for this informational message.
AAS0007I	Product Information : Version={version} Patch Level={number}
Explanation	This message displays general information about the installed Adabas Administration Services.
Action	No action is required for this informational message.
AAS0009I	Total Service Requests {count}
Explanation	This message provides the total number of requests made to the service.
Action	No action is required for this informational message.
AAS0010I	Process Resources: FSIZE ({d}/{d}) NOFILE ({d}/{d})
Explanation	This message provides information to Software AG technical support.
Action	No action is required for this informational message.
AAS0011I	Total Direct Clients {count}
Explanation	This message provides the total number of direct clients connected to the service.
Action	No action is required for this informational message.
AAS012I	Total Relayed Clients {count}
Explanation	This message provides the total number of relayed clients connected to the Kernel.
Action	No action is required for this informational message.
AAS0013I	Period time {n}h.{n}m.{n}s
Explanation	This message provides the length of time the service has been running.
Action	No action is required for this informational message.
AAS0014I	Administration Messages {count}
Explanation	This message provides the total number of administration messages made to the service.
Action	No action is required for this informational message.

AAS0015I	e-Business Communication Errors {count}
Explanation	This message provides the total number of communication errors that occurred with the service.
Action	No action is required for this informational message.
AAS0016I	Total Service Replies {count}
Explanation	This message provides the total number of replies made by the service.
Action	No action is required for this informational message.
AAS0017I	Total Service Input Bytes {count}
Explanation	This message provides the total number of bytes input to the service.
Action	No action is required for this informational message.
AAS0018I	Adabas Administration Service initialization complete
Explanation	Adabas Administration Services has initialized successfully.
Action	No action is required for this informational message.
AAS0019I	Total Service Output Bytes {count}
Explanation	This message provides the total number of bytes output by the service.
Action	No action is required for this informational message.
AAS0020I	ADABAS Version={v.r.s.m}
Explanation	This message identifies the version of the Adabas database.
Action	No action is required for this informational message.
AAS0021I	Unable to find ADABAS 6.3 registry RGS rc={resp-code}
Explanation	Adabas Administration Services was unable to locate the Adabas 6.3 registry. The response code from the attempt is given in the message.
Action	Review the response code to determine what the problem is and how to repair it. Contact your Software AG technical support representative if you need assistance.

AAS0022I	Unable to determine the ADABAS version
Explanation	Adabas Administration Services was unable to determine the Adabas version.
Action	No action is required for this informational message.
AAS0023I	Disconnection notified by remote Service={service name}
Explanation	The remote service listed in the message has successfully disconnected. The reference number (<i>ref-num</i>) given in the message is for internal Software AG use only.
Action	No action is required for this informational message.
AAS0024I	This log file is being closed by {user-name}
Explanation	The log file is being closed by a user of the System Management Hub or the NETSTOP utilities. A new <i>net-work.log</i> file is being created.
Action	No action is required for this informational message.
AAS0025I	DBID={dbid} is now registered on the local service
Explanation	An Adabas database with the identified database number is now registered on the local service.
Action	No action is required for this informational message.
AAS0026I	DBID={dbid} no longer registered on the local service
Explanation	The Adabas database with the identified database ID is no longer registered with the local service.
Action	No action is required for this informational message.
AAS0027I	ADABAS Version mismatch; expected {version1} found {version2}
Explanation	Adabas Administration Services encountered a mismatch between the expected Adabas version and the actual Adabas version.
Action	No action is required for this informational message.
AAS0028I	Immediate disconnection of DBID={dbid}
Explanation	The identified database has indicated an immediate disconnection.
Action	No action is required for this informational message.

AAS0029I	DBID={dbid} is now connected to the local service
Explanation	The identified e-business Adabas database is now active on the local service.
Action	No action is required for this informational message.
AAS030I	Information from Internal Transport Subsystem: {info}
Explanation	Information from the internal transport subsystem used by Adabas Administration Services is provided in this message.
Action	No action is required for this informational message.
AAS0032I	Total CPU Time since started {n}h.{n}m.{n}s
Explanation	This message provides the total CPU time that occurred since the SERVICE started.
Action	No action is required for this informational message.
AAS0035I	Adabas Administration Service Name={name}
Explanation	The name of the Adabas Administration Services is given in the message.
Action	No action is required for this informational message.
AAS0037I	Service={servicename}
Explanation	This message identifies the name of the service
Action	No action is required for this informational message.
AAS0038I	Nodes {count}
Explanation	This message provides the number of nodes that the service knows about.
Action	No action is required for this informational message.
AAS0039I	Connected Nodes Count {count}
Explanation	This message provides the number of nodes to which the service is connected.
Action	No action is required for this informational message.
AAS0040I	*****Periodic statistical data report*****
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.

AAS0041I	Current Direct Clients {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of current direct clients connected to this service.
Action	No action is required for this informational message.
AAS0042I	Current Relayed Clients {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of current relayed clients connected to this service.
Action	No action is required for this informational message.
AAS0043I	Total Memory Allocations {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0044I	Total Memory Frees {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0045I	Databases {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0046I	Active Databases {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0047I	Local Adabas calls {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.

AAS0048I	Host Counter {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of hosts connected to this service.
Action	No action is required for this informational message.
AAS0049I	Number of Work Units Processed {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0056I	Messages Processed {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0057I	Ping Counter {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of pings to this service.
Action	No action is required for this informational message.
AAS0058I	Contexts Processed {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of contexts processed by the service.
Action	No action is required for this informational message.
AAS0059I	Contexts Active {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of active contexts.
Action	No action is required for this informational message.
AAS0060I	Service Inbound Requests/Sec{rate}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the rate (requests per second) at which inbound requests have been processed by the service.
Action	No action is required for this informational message.

AAS0061I	Service Outbound Requests/Sec {rate}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the rate (requests per second) at which outbound requests have been processed by the service.
Action	No action is required for this informational message.
AAS0062I	Service Inbound Data Rate (b/s) {rate}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the rate (bytes per second) at which inbound data has been processed by the service.
Action	No action is required for this informational message.
AAS0063I	Service Outbound Data Rate (b/s) {rate}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the rate (bytes per second) at which outbound data has been processed by the service.
Action	No action is required for this informational message.
AAS0064I	Database Requests/Second {rate}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0065I	Database Replies/Second {rate}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0066I	Database Request Data Rate (b/s) {rate}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.

AAS0067I	Database Reply Data Rate (b/s) {rate}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0068I	Percentage of CPU Usage {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0069I	Time since started {hh:mm:ss}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0071I	Thread {thread-number} Work Units Completed {count}
Explanation	This message is one of many messages that comprise the Periodic Statistical Data Report.
Action	No action is required for this informational message.
AAS0072I	Disconnection indication from DBID={dbid}
Explanation	The identified database has indicated an immediate disconnection.
Action	No action is required for this informational message.
AAS0073I	Current CPU usage {value}
Explanation	The current CPU usage is shown in the message.
Action	No action is required for this informational message.
AAS0074I	Disconnection from Service={servicename}
Explanation	An attempt to disconnect from a service occurred.
Action	No action is required for this informational message.

AAS0075I	Outbound connection to Service={servicename}
Explanation	An outbound connection exists for the service listed in the message.
Action	No action is required for this informational message.
AAS0076I	Outbound connection to Service={servicename} failed rc={rsp}
Explanation	The outbound connection for the service listed in the message failed. The response code from the attempt is also given in the message.
Action	Make sure the node of the outbound connection is up and that its parameters are configured correctly. Then refresh the service connections, restarting it if necessary to do so.
AAS0077I	Service listening on TCPIP port={portnum}
Explanation	A service is listening on the TCP/IP port listed in the message.
Action	No action is required for this informational message.
AAS0078I	Service listening on SSL port={portnum}
Explanation	A service is listening on the SSL port listed in the message.
Action	No action is required for this informational message.
AAS0079I	SMH server listening on TCPIP port={portnum}
Explanation	The SMH server is listening on the TCP/IP port listed in the message.
Action	No action is required for this informational message.
AAS0080I	DBID={dbid} has now started on the local service
Explanation	The identified database is now active on the local service and can now be accessed.
Action	No action is required for this informational message.
AAS0081I	Local DBID={dbid} is no longer available
Explanation	The identified database has been deactivated on the local node and is therefore no longer available to any clients.
Action	No action is required for this informational message.

AAS083I	Shutdown request received from {agent}
Explanation	A shutdown request for Adabas Administration Services has been received.
Action	No action is required for this informational message.
AAS084I	Signal value={signal}
Explanation	The UNIX signal value is given in the message.
Action	No action is required for this informational message.
AAS0085E	e-Business server failed with error={number}
Explanation	The message indicates that the service failed. An error number is provided in the message.
Action	Contact your Software AG technical support representative for assistance.
AAS0086I	Periodic ping of classic node={node-name} took {nnnn} milliseconds
Explanation	As the result of a periodic heartbeat operations, this classic node was sent a ping message to check its connection path. The classic node replied within the time indicated.
Action	No action is required for this informational message.
AAS0087I	Periodic ping of DBID={dbid} took {nnnn} milliseconds
Explanation	As the result of a periodic "heartbeat" operation, this database was sent a "PING" message to check its availability. The database replied within the time indicated.
Action	No action is required for this informational message.
AAS0088I	Continuation of previous log file, renamed to {netxxxx.log}
Explanation	The log file is renamed to <i>netxxxx.log</i> , where <i>xxxxxx</i> is a number. This message appears as the first line on a continuation log file.
Action	No action is required for this informational message.
AAS0089I	e-Business server incoming connection
Explanation	An incoming service connection is described in the message. The reference number (<i>ref-num</i>) listed in the message is for internal Software AG use only.
Action	No action is required for this informational message.

AAS0090I	e-Business server is now connected to {nodename}
Explanation	The identified server is now connected to the local node. The reference number (<i>ref-num</i>) listed in the message is for internal Software AG use only.
Action	No action is required for this informational message.
AAS0091I	Servers {nnnnnnnn}
Explanation	This message is part of the periodic statistical data report.
Action	None. This message is informational only.
AAS0092I	Service={servicename} is registered
Explanation	The identified service is now accessible from the local node.
Action	None. This message is informational only.
AAS0093I	Immediate disconnection from Service={servicename}
Explanation	An immediate disconnection for the named service occurred. The reference number (<i>ref-num</i>) given in the message is for internal Software AG use only.
Action	No action is required for this informational message.
AAS0094I	Command Parameter={num} {value}
Explanation	The setting of a user command parameter is given in the message.
Action	No action is required for this informational message.
AAS0097I	Listening for clients on TCPIP port={portnum}
Explanation	This message identifies the TCP/IP port number on which the services is listening for clients.
Action	No action is required for this informational message
AAS0098I	Listening for clients on SSL port={portnum}
Explanation	This message identifies the SSL port number on which the services is listening for clients.
Action	No action is required for this informational message

AAS0099I	Adabas Administration Service is terminating
Explanation	The Adabas Administration Services is terminating.
Action	No action is required for this informational message.
AAS0102W	No outbound connections defined for this configuration
Explanation	No outbound connections have been defined for this configuration.
Action	No action is required for this warning message.
AAS0103W	Adabas Context={context} DBID={dbid} Deleted
Explanation	The Adabas context listed in the message has been deleted for the database listed in the message.
Action	No action is required for this warning message.
AAS0104W	Remote access for WCP services has been disabled
Explanation	Remote access to Entire Net-Work open system services has been disabled.
Action	No action is required for this warning message.
AAS0105W	Remote access for WCL services has been disabled
Explanation	Remote access for Entire Net-Work Client services has been disabled.
Action	No action is required for this warning message.
AAS0106W	Remote access for ART services has been disabled
Explanation	Remote access for Event Replicator Target Adapter services has been disabled.
Action	No action is required for this warning message.
AAS0108W	Adabas Context={context} DBID={dbid} Owners={id} Set for deletion
Explanation	The Adabas context listed in the message for the database and owners listed in the message is scheduled for deletion.
Action	No action is required for this warning message.
AAS0109W	Local DBID={dbid} starting, but previous location was remote
Explanation	A database has started on the local node; however, this database ID was previously used by another database on a remote node.
Action	This indicates a configuration error that needs to be corrected.

AAS0111I	Trace level set to {trclevel} by SMH user
Explanation	The trace level has been reset by a System Management Hub (SMH) user. The new trace level is given in the message.
Action	No action is required for this informational message.
AAS0112I	Ping request received from the user; Target={target ID} Length={length} Count={number}
Explanation	A user has requested a PING operation to the target ID identified in the message. PINGs are used to test the integrity of a remote connection to the path to a database.
Action	No action is required for this informational message.
AAS0113I	Start new log file requested by the user
Explanation	A user has requested that the current logging file be closed and a new log file started.
Action	No action is required for this informational message.
AAS0114W	No directory information for {server-ID}
Explanation	An internal error occurred for a service. It was not possible to create the definitions for a database to allow it to be accessed by clients.
Action	Restart the service.
AAS0115W	Unidentified database ping reply received
Explanation	A PING message was received for which there was no PING request. This indicates that a logical messages sequencing failure occurred at a remote database.
Action	If the error persists, restart the remote database.
AAS0116W	Calling DBID={dbid} failed rc={rc-code}
Explanation	Following a connection by a database (message AAS0029I), the service tried to send a simple Adabas command to the database to test the integrity of the communications path. This test failed. The database is not registered at the local node nor is it broadcast to other nodes. This error normally results from a failure to provide an XTSaccess URL for the database in the Directory Server. The Adabas response code from the connection attempt is given in the message. For complete information on Adabas response codes, refer to the <i>Adabas Messages and Codes Manual</i> .
Action	Verify that you have provided an XTSaccess URL for the database in the Directory Server and try again.

AAS0117W	DBID={dbid} is now connected as e-business
Explanation	An Adabas database has connected previously as a classic or local database, disconnected, and is now being connected as an e-business database. This may be intentional or it may be a configuration error.
Action	No action is required for this informational message.
AAS0118W	DBID={dbid} issued an e-business disconnection
Explanation	A database was originally connected as a classic or local database, but an e-business disconnection was received. The database is not disconnected.
Action	If the error persists, contact your Software AG technical support representative.
AAS0119W	Duplicate URL={url} for target={targetid} in the Directory Server
Explanation	A duplicate URL has been found for a target definition in the Directory Server. The URL and the target ID are given in the message.
Action	No action is required for this warning message.
AAS0120W	URL={url} for Target={targetid} has a syntax error
Explanation	A syntax error was discovered in the URL for a target definition in the Directory Server. The URL and the target ID are given in the message.
Action	No action is required for this warning message.
AAS0121I	ClientId={client-id} Host={host-id} Port={portnum} connected; Current Clients={count}
Explanation	This message indicates that an incoming client connection was made and identifies the client ID, the host ID, the port number, and the number of current active client connections.
Action	No action is required for this informational message.
AAS0122I	ClientId={client-id} disconnected; Current Clients={count}
Explanation	This message indicates that a client connection was dropped and identifies the client ID and the number of current client connections.
Action	No action is required for this informational message.

AAS0123W	Service not defined
Explanation	A service definition has not been defined in this Adabas Administration Services implementation.
Action	No action is required for this informational message.
AAS0125W	Client Access not defined
Explanation	A client access definition has not been defined in this Adabas Administration Services implementation.
Action	No action is required for this informational message.
AAS0127I	Listening Port={port}
Explanation	The listening port is given in the message.
Action	No action is required for this informational message.
AAS0128I	Listening Port={port}
Explanation	The listening port is given in the message.
Action	No action is required for this informational message.
AAS0131I	ClientId={client-id} Relaying to DBID={dbid}
Explanation	The client named in the message is relaying data to the Adabas database identified in the message.
Action	No action is required for this informational message.
AAS0132I	ClientId={client-id} Local Calls to DBID={dbid}
Explanation	The client named in the message is making local calls to the Adabas database identified in the message.
Action	No action is required for this informational message.
AAS0133I	ClientId={client-id} Host={hostname} Port={port} is a privileged client={client-id} Current Clients={count}
Explanation	The client on the host machine and port number listed in the message is a privileged client.
Action	No action is required for this informational message.

AAS0150I	Service {servicename} connected via remote Service={servicename} reference={refnum}
Explanation	A service-to-service connection has occurred. If a service was started as a Windows service and subsequently shut down by means of the Services Control Panel, this informational message is added to the log.
Action	No action is required for this informational message.
AAS0151I	DBID={dbid} connected via remote Service={servicename} reference={refnum}
Explanation	A service-to-service connection has occurred and databases known to the remote service are now known to both.
Action	No action is required for this informational message.
AAS0156I	DBID={dbid} rejected for traffic relay
Explanation	A database was rejected for traffic relay, as defined by the service filter settings. The service will not process requests for the database with the database ID given in the message.
Action	No action is required for this informational message.
AAS0158I	DBID={dbid} verified and active reference={refnum}
Explanation	During the periodic check of its known connections, the service has verified that its connection to the database listed in the message is valid and active.
Action	No action is required for this informational message.
AAS0159I	DBID={dbid} rejected by filter
Explanation	A e-business database was rejected by a filter, as defined by the service filter settings. The service will not process requests for the database with the database ID given in the message.
Action	No action is required for this informational message.
AAS0163I	Adabas={dbid} has been started
Explanation	The database listed in the message has been started.
Action	No action is required for this informational message.

AAS0164I	Adabas={dbid} has been stopped
Explanation	The database listed in the message has been stopped.
Action	No action is required for this informational message.
AAS0203E	Connection from {node} rejected by filters; node in the rejected list
Explanation	An attempt to connect by the node referenced in the message was rejected by filters. The node is included in the rejected filter list.
Action	No action is necessary unless you want a connection by the node to be accepted. If you do, adjust the parameters on the Service Filters panel in SMH.
AAS0208E	Unexpected error in registering database={dbid} rc={rsp}
Explanation	An unexpected error has occurred while registering the identified database; the return code is provided.
Action	Take corrective action as indicated by the following internal transport subsystem message.
AAS0209E	Connection from {node} rejected by filters; node not in the accepted list
Explanation	An attempt to connect by the node referenced in the message was rejected by filters. The node is <i>not</i> included in the accepted filter list.
Action	No action is necessary unless you want a connection by the node to be accepted. If you do, adjust the parameters on the Service Filters panel in SMH.
AAS0210E	ClientId={client-id} Host={host} Port={port} rejected; Host not accepted by filter
Explanation	The client on the host machine and port listed in the message has been rejected because the host machine is not accepted by the filter settings.
Action	No action is necessary unless you want a connection to be accepted. If you do, adjust the parameters on the Service Filters panel in SMH.
AAS0211E	e-Business database connecting with an invalid DBID={dbid}
Explanation	An e-business database has connected to the service but has indicated a database number that is not in the valid range of 0 - 65535.
Action	Change the database ID to the valid range.

AAS0212E	Unsolicited connection attempt from {node} being rejected
Explanation	A node with an unknown node name attempted to connect to the service while the SECURE parameter was set to ON.
Action	Define the node to Adabas Administration Services.
AAS0213E	Host={hostname} not accepted by filter
Explanation	The host machine listed in the message is not accepted by the filter settings.
Action	No action is necessary unless you want a connection to the host machine to be accepted. If you do, adjust the parameters on the Service Filters panel in SMH.
AAS0215E	ART callback routine rc={rsp}
Explanation	An error occurred in the Event Replicator Target Adapter callback routine. The response code is given in the message.
Action	Contact your Software AG technical support representative.
AAS0216E	AAS callback routine rc={rsp}
Explanation	An error occurred in the Adabas Administration Services callback routine. The response code is given in the message.
Action	Contact your Software AG technical support representative.
AAS0217E	WCP callback routine rc={rsp}
Explanation	An error occurred in the Entire Net-Work LUW callback routine. The response code is given in the message.
Action	Contact your Software AG technical support representative.
AAS0218E	AAS callback routine rc={rsp}
Explanation	An error occurred in the Adabas Administration Services callback routine. The response code is given in the message.
Action	Contact your Software AG technical support representative.
AAS0219E	Relay callback routine for ClientId={client-id} DBID={dbid} zero length message
Explanation	A zero length message was received during a relay routine.
Action	If the problem persists, contact your Software AG support representative.

AAS0220E	Local database started with an invalid identifier={dbid}
Explanation	A local database has started with an ID of less than 1 or greater than 65535. The startup is being ignored and the database is inaccessible from this service.
Action	Check the database configuration files.
AAS0221E	Local database is starting with a conflicting DBID={dbid}
Explanation	A local database has started with an ID that is already in use by another database known to this service. The duplicate will be ignored.
Action	This indicated a configuration error that needs to be corrected.
AAS0223E	Unexpected error in registering Service={servicename} rc={rsp}
Explanation	An internal error occurred registering Adabas Administration Services. The response code is given in the message.
Action	Contact your Software AG technical support representative for assistance.
AAS0228E	Adabas call to DBID={dbid} failed rc={rsp}
Explanation	An internal failure occurred during an Adabas call to a database. The database referenced in the Adabas call and the return code from the call are given in the message.
Action	Verify that the Adabas call is valid for the database. If the problem persists, contact your Software AG support representative.
AAS0229E	Adabas ACBX call to DBID={dbid} failed rc={rsp} acbxrc={acbxrc} acbxerrc={acbxerrc}
Explanation	An internal failure occurred during an Adabas ACBX call to a database. The database referenced in the Adabas call, the return code from the call, the extended Adabas control block (ACBX) return code, and the ACBX error code are given in the message.
Action	Verify that the Adabas call is valid for the database. If the problem persists, contact your Software AG support representative.
AAS0230E	Adabas ACBX call to DBID={dbid} failed OP not secure acbxrc={acbxrc} acbxerrc={acbxerrc}
Explanation	An internal failure occurred during an Adabas ACBX call to a database because the OP command was not secure. The database referenced in the Adabas call, the extended Adabas control block (ACBX) return code, and the ACBX error code are given in the message.
Action	Verify that the Adabas call is valid for the database. If the problem persists, contact your Software AG support representative.

AAS0231E	Adabas ACBX call to DBID={dbid} failed No valid OP cmd acbxrc={acbxrc} acbxerrc={acbxerrc}
Explanation	An internal failure occurred during an Adabas ACBX call to a database because the OP command was not valid. The database referenced in the Adabas call, the extended Adabas control block (ACBX) return code, and the ACBX error code are given in the message.
Action	Verify that the Adabas call is valid for the database. If the problem persists, contact your Software AG support representative.
AAS0232E	Invalid e-Business DBID={dbid}; disconnecting
Explanation	An invalid Adabas DBID was encountered. Connections to the database are disconnected.
Action	If the error persists, contact your Software AG technical support representative.
AAS0233E	Unknown e-business DBID={dbid}; disconnected ...
Explanation	An unknown Adabas DBID was encountered and is disconnected.
Action	If the error persists, contact your Software AG technical support representative.
AAS0235E	Unknown e-business Server={server-id}
Explanation	An unknown server (identified in the message) was encountered.
Action	If the error persists, contact your Software AG technical support representative.
AAS0237E	Unable to spawn a new process for {xxxx}
Explanation	The UNIX system is overloaded and will not allow the creation of new processes.
Action	Contact your Software AG technical support representative.
AAS0238E	Syntax error in URL={url} for target={target-id}
Explanation	A syntax error occurred during Adabas Administration Services processing. The URL in error and the target ID for the URL are given in the message. This error can occur if manual updates to URL connection information are attempted.
Action	Contact your Software AG technical support representative for assistance.

AAS0239E **EBZProxy callback routine for ClientId={client-id} DBID={dbid} completion rc={code}**

Explanation A proxy error occurred. The client ID, database ID, and the return code from the attempt are given in the message.

Action Make sure the proxy nodes are all up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.

AAS0240E **EBZServer callback routine for ClientId={client-id} DBID={dbid} completion rc={code}**

Explanation An Adabas Administration Services error occurred. The client ID, database ID and the return code from the attempt are given in the message.

Action Make sure the Adabas Administration Services nodes are all up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.

AAS0241E **EBZClient callback routine for ClientId={client-id} DBID={dbid} completion rc={code}**

Explanation An Adabas Administration Services error occurred. The client ID, database ID and the return code from the attempt are given in the message.

Action Make sure the Adabas Administration Services nodes are all up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.

AAS0242E **Failed to relay request to ClientId={client-id} DBID={dbid} rc={code}**

Explanation An attempt to relay a request to a database failed. The database ID and the return code from the attempt are given in the message.

Action Make sure the Adabas Administration Services nodes and the database in question are all up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.

AAS0243E **ACBX request for Classic DBID={dbid} is not supported**

Explanation An attempt to make an Adabas ACBX call to a classic (pre-Version 6 on open systems or pre-Version 8 on mainframe systems) Adabas database was made. ACBX calls are only allowed against Adabas 8 (or later) databases.

Action Resolve the error (either run the ACBX call against a valid database or change the call to an ACB call) and try again.

AAS0245E	DBID={dbid} is invalid; request rejected
Explanation	A request was made to an invalid database.
Action	Correct the database specification and try again.
AAS0246E	DBID={dbid} is inactive; request rejected
Explanation	A request was made to an inactive Adabas database.
Action	Start the Adabas database and try again.
AAS0247E	DBID={dbid} Invalid or deleted context={context-id}; request rejected
Explanation	A communication error occurred. The request is rejected. The database ID of the database to which the request was directed is given in the message.
Action	Verify that all connections and the database in question are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
AAS0248E	Outbound connection failure; unknown target
Explanation	An outbound connection was attempted but failed because the target could not be identified..
Action	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
AAS0249E	Invalid DBID={dbid}, no corresponding Service defined
Explanation	A communication error occurred. The request is rejected. The database ID of the database to which the request was directed is given in the message.
Action	Verify that all connections and the database in question are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
AAS0251E	Unknown request ClientId={client-id} DBID={dbid}, disconnecting ...
Explanation	An unknown client request was encountered. The client ID and Adabas database ID are given in the message.
Action	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.

AAS0252E	ClientId={client-id} Host={hostname} Port={port} rejected; The Number of client connections cannot exceed={count}
Explanation	A client request was not processed because the number client connections has been exceeded. The client ID, host name, port number, and maximum number of client connections are given in the message.
Action	Verify that the maximum number of client connections is set correctly. If the problem persists, contact your Software AG support representative for assistance.
AAS0253E	Replying to ClientId={client-id} DBID={dbid} failed rc={code}
Explanation	An attempt to reply to a client failed. The client ID, Adabas database ID, and return code from the attempt are given in the message.
Action	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
AAS0254E	ClientId={client-id} Host={hostname} Port={port} rejected; The CPU Threshold={percentage} exceeds maximum allowed={value}
Explanation	The client on the host machine and port listed in the message was rejected because the CPU threshold was exceeded.
Action	Increase the CPU threshold setting. If the problem persists, contact your Software AG support representative for assistance.
AAS0255E	ClientId={client-id} DBID={dbid} Replying error={error}
Explanation	An attempt to reply to a client failed. The client ID, Adabas database ID, and error from the attempt are given in the message.
Action	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
AAS0256E	DBID={dbid} is non accessible mainframe database; client traffic not allowed
Explanation	An attempt to connect to a mainframe database failed. The Adabas database ID is given in the message.
Action	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
AAS0258E	Context={context} DBID={dbid} set for deletion; request rejected
Explanation	An attempt to delete the Adabas context listed in the message for the database listed in the message failed.
Action	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.

AAS0304S	Unable to add a Directory Server entry
Explanation	The Adabas Administration Services was unable to add a Directory Server entry.
Action	Contact your Software AG technical support representative for assistance.
AAS0305S	AIF exit error={error}
Explanation	An AIF exit error occurred.
Action	Contact your Software AG technical support representative for assistance.
AAS0310S	Work Semaphore failed in thread {thread-number}, error={error-number}
Explanation	The Adabas Administration Services threading mechanism failed.
Action	Repeated occurrences of this message may require a restart of the service.
AAS0311S	Threading yield: failed in thread {thread-number}, error={error-number}
Explanation	The Adabas Administration Services threading mechanism failed.
Action	Repeated occurrences of this message may require a restart of the service.
AAS0312S	Invalid message eyecatcher received
Explanation	An internal Adabas Administration Services error occurred.
Action	Contact your Software AG technical support representative for assistance.
AAS0313S	Invalid message version received
Explanation	An internal Adabas Administration Services error occurred.
Action	Contact your Software AG technical support representative for assistance.
AAS0314S	Invalid message segment received
Explanation	An internal Adabas Administration Services error occurred.
Action	Contact your Software AG technical support representative for assistance.
AAS0315S	Request failed to wake work semaphore rc={rcode}
Explanation	The Adabas Administration Services semaphoring mechanism failed. The return code from the call is given in the message.
Action	Contact your Software AG technical support representative for assistance.

AAS0316S	Thread wakeup call failed rc={rcode}
Explanation	The Adabas Administration Services threading mechanism failed. The return code from the call is given in the message.
Action	Repeated occurrences of this message may require a restart of the service.
AAS0317S	Unable to remove Directory Service Server={serverid} Url={url}
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
AAS0318S	Local database resources problem. Increase NU parameter
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
AAS0319S	Unable to remove Directory Service Dbid={dbid} Url={url}
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
AAS0402F	Unable to continue due to a severe error at startup
Explanation	A severe error occurred when the Adabas Administration Services tried to start up. The cause is shown in a previous message.
Action	Contact your Software AG technical support representative for assistance.
AAS0407F	Thread create for TimerThread failed rc={rcode}
Explanation	The threading mechanism failed. The return code is given in the message.
Action	Repeated occurrences of this message may require a restart of the service.
AAS0408F	Semaphore for WorkSemaphore failed rc={rcode}
Explanation	The threading mechanism failed. The return code is given in the message.
Action	Repeated occurrences of this message may require a restart of the service.
AAS0409F	Thread create for thread {thread-number} failed rc={rcode}
Explanation	The threading mechanism failed. The return code is given in the message.
Action	Repeated occurrences of this message may require a restart of the service.

AAS0414F	Remote Directory Server cannot be accessed
Explanation	Adabas Administration Services could not access the remote Software AG Directory Server.
Action	Contact your Software AG technical support representative for assistance.
AAS0415F	CFG Directory Server cannot be accessed
Explanation	A Directory Server problem occurred.
Action	Make sure no Directory Server or Adabas Administration Services installation files were deleted and that your user ID has security access to use all files in the installation directories. If the problem persists, contact your Software AG support representative for assistance.
AAS0601E	Internal error={errorcode}
Explanation	An internal error occurred. The error code is given in the message.
Action	Analyze the error description to try to identify and resolve the problem. If the problem persists, contact your Software AG technical support representative for assistance.
AAS0602E	Node is unreachable. It may not be active or there may be a configuration problem. Detailed error response was: {response}
Explanation	A node cannot be reached. The response from the connection attempt is given in the message.
Action	Verify that the node is started. If it is, analyze the installation of the node to identify and resolve any configuration problem that may exist. If the problem persists, contact your Software AG technical support representative for assistance.
AAS0603E	Service={service-id} already exists in the Directory Server
Explanation	An attempt to add a service to the System Management Hub (SMH) was made, but the service already is added.
Action	No action is required for this informational message.
AAS0604I	{definition} successfully added to SMH management; refreshing the tree...
Explanation	The definition listed in the message was successfully added to SMH.
Action	No action is required for this informational message.

AAS0605E	Service={service-id} not found in the Directory Server
Explanation	The service listed in the message was not found in the Adabas Directory Server.
Action	If you cannot identify and resolve the problem, contact your Software AG technical support representative for assistance.
AAS0606I	{definition} successfully deleted from SMH management; refreshing the tree...
Explanation	The definition listed in the message was successfully deleted from SMH.
Action	No action is required for this informational message.
AAS0607E	No client entries found
Explanation	No client configuration definitions were found to manage in the System Management Hub (SMH).
Action	Verify that the client service is started. Client configuration definitions cannot be reviewed in the System Management Hub (SMH) unless the client service is started. If the problem persists, contact your Software AG technical support representative for assistance.
AAS0608E	No service definitions found in the Directory Server
Explanation	No service definitions were found in the Adabas Directory Server, so no server machines can be listed in the System Management Hub (SMH).
Action	Verify that Adabas Administration Services has been installed and that its service has been started.
AAS0609E	Incompatible version of Net-Work
Explanation	The version of Adabas Administration Services you are trying to use is incompatible with the Adabas Administration Services SMH agent.
Action	Contact your Software AG technical support representative for assistance.
AAS0610I	Ping request returned in {number} milliseconds
Explanation	The ping request was returned in the number of milliseconds listed in the message.
Action	No action is required for this informational message.

AAS0611I	No databases found on Service={service-id}
Explanation	No databases were found on the service listed in the message.
Action	No action is required for this informational message.
AAS0612E	Service is unreachable rc={rcode}
Explanation	An error occurred during an attempt to communicate with a node. The return code is given in the message.
Action	Use the return code to determine what the problem is and resolve it. Then try again. If the problem persists, contact your Software AG technical support representative.
AAS0613I	No adjacent services found on Service={service-id}
Explanation	No connection were made. Either the service is down or there is a configuration error.
Action	No action is required for this informational message.
AAS0614I	No clients found on Service={service-id}
Explanation	No clients were found on the service listed in the message.
Action	No action is required for this informational message.
AAS0615I	No hosts connected to Service={service-id} found
Explanation	No hosts were found connected to the service listed in the message.
Action	No action is required for this informational message.
AAS0616I	Shutdown initiated
Explanation	Shutdown processing has been started.
Action	No action is required for this informational message.
AAS0617I	No such configuration
Explanation	A configuration was referenced that does not exist.
Action	No action is required for this informational message.
AAS0618E	Return code {rc} received
Explanation	The return code listed in the message was received during Adabas Administration Services processing.
Action	Analyze the return code to see if you can diagnose and resolve the problem. If the problem persists, contact your Software AG technical support representative.

AAS0619E	Invalid context
Explanation	An invalid context was encountered.
Action	Verify that all connections and the database in question are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
AAS0620E	Invalid Client
Explanation	An invalid client was encountered.
Action	Verify that all clients are configured correctly. If the problem persists, contact your Software AG support representative for assistance.
AAS0621I	New log file started
Explanation	A new log file has been started.
Action	No action is required for this informational message.
AAS0622I	Trace level set
Explanation	A new trace level has been set.
Action	No action is required for this informational message.
AAS0623I	Stats level set
Explanation	A new statistics level has been set.
Action	No action is required for this informational message.
AAS0624I	Dump configuration initiated
Explanation	A dump configuration has been initiated.
Action	No action is required for this informational message.
AAS0625E	Invalid DBID
Explanation	An invalid Adabas database ID has been specified.
Action	Specify a correct database ID.

AAS0626E	Invalid Host
Explanation	An invalid host was specified.
Action	Specify a valid host name.
AAS0627E	Directory Server is unreachable. It may not be active or there may be a configuration problem. Detailed error response was: {error}
Explanation	A problem occurred during an attempt to communicate with the Adabas Directory Server.
Action	Verify that the Adabas Directory Server is stated and try again. If the problem persists, contact your Software AG technical support representative.
AAS0628I	Connect procedure has been initiated
Explanation	A connection attempt was started.
Action	No action is required for this informational message.
AAS0629I	Disconnect procedure has been initiated
Explanation	A disconnection attempt was started.
Action	No action is required for this informational message.
AAS0630I	Delete procedure successful
Explanation	The deletion attempt was successful.
Action	No action is required for this informational message.
AAS0631E	Invalid Node
Explanation	An attempt was made connect to an invalid node.
Action	Refresh your SMH screens. The node was probably deleted since you started your SMH session.
AAS0632E	Service already connected
Explanation	An attempt occurred to connect to a service that is already connected.
Action	If you are having problems communicating with the service and you are getting this error, contact your Software AG technical support representative for assistance.

AAS0633E	Service already disconnected
Explanation	An attempt was made to disconnect a service that is already disconnected.
Action	No action is required for this information message.
AAS0634E	Unknown return code {rcode} received
Explanation	An unknown return code was received. The return code is given in the message.
Action	Contact your Software AG technical support representative for assistance.
AAS0635E	XTS library cannot be loaded
Explanation	The Software AG Transport Subsystem library could not be loaded.
Action	Contact your Software AG technical support representative for assistance.
AAS0636E	Configuration already defined
Explanation	An attempt was made to configure a service that is already configured.
Action	Try specifying a different service name for the service you are allocating. If the problem persists, contact your Software AG technical support representative.
AAS0637E	Invalid request
Explanation	An invalid request was attempted.
Action	If you cannot identify and resolve the problem, contact your Software AG technical support representative for assistance.
AAS0638E	Failure to create file
Explanation	An attempt to create a file was unsuccessful.
Action	If you cannot identify and resolve the problem, contact your Software AG technical support representative for assistance.
AAS0639E	Unknown command code {cmd-code} received
Explanation	An unknown command request was received. The command code is given in the message.
Action	If you cannot identify and resolve the problem, contact your Software AG technical support representative for assistance.

AAS0640I	Service {servicename} configured successfully
Explanation	The service definition configuration attempt was successful. The service definition name is given in the message.
Action	No action is required for this informational message.
AAS0641I	Client {name} configured successfully
Explanation	The client configuration attempt was successful. The client configuration name is given in the message.
Action	No action is required for this informational message.
AAS0642I	Migrating {service-id} Service successful
Explanation	An attempt to migrate a service definition from an older version of Adabas Administration Services to a newer version was successful. The name of the service is given in the message.
Action	No action is required for this informational message.
AAS0643I	Service {service-id} migrated from WCP73
Explanation	The service listed in the message has been migrated from a previous version.
Action	No action is required for this informational message.
AAS0644E	Invalid entry
Explanation	An invalid entry was specified.
Action	Contact your Software AG technical support representative for assistance.
AAS0645I	Modification procedure successful
Explanation	The modification was successful.
Action	No action is required for this informational message.
AAS0646E	Invalid data
Explanation	Invalid data was specified.
Action	Correct the data and try again. If the problem persists, contact your Software AG technical support representative.

AAS0647I	Client {name} deleted successfully
Explanation	The attempt to delete the client configuration was successful.
Action	No action is required for this informational message.
AAS0648I	Service {name} deleted successfully
Explanation	The attempt to delete the service definition was successful.
Action	No action is required for this informational message.
AAS0649I	Service {name} is active, deletion failed
Explanation	An attempt to delete a service definition was made, but the service is running.
Action	Stop the service before attempting to delete it.
AAS0650I	Service {name} is active, starting not initiated
Explanation	An attempt to start a service was made, but the service is already running.
Action	No action is required for this informational message.
AAS0651I	Startup initiated for Service {name}
Explanation	The service is starting.
Action	No action is required for this informational message.
AAS0652I	Unable to start this Service
Explanation	The Keservicernel cannot be started for some reason.
Action	Examine the service log file for reasons for the failure, make appropriate corrections, and try again. If the error persists, contact your Software AG technical support representative for assistance.
AAS0653I	Set parameters successful
Explanation	The parameter changes were successfully processed.
Action	No action is required for this informational message.
AAS0654I	No services available
Explanation	No service definitions have been defined, so none are available.
Action	Define some service definitions.

AAS0655I	Client {client-id} migrated from WCL13
Explanation	The client listed in the message has been migrated from a previous version of Entire Net-Work.
Action	No action is required for this informational message.
AAS0656E	Service={name} cannot have more than 8 characters
Explanation	The name of a service definition cannot exceed eight characters. An attempt was made to specify a name longer than eight characters and the name specified is given in the message.
Action	Reduce the length of the name of the service definition.
AAS0657E	XTS function cannot be loaded
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
AAS0658E	A valid (non-zero) port has to be specified
Explanation	The port number was not specified or is invalid.
Action	Specify a valid port number.
AAS0659E	A valid (non-zero) host has to be specified
Explanation	A host name was not specified or is invalid.
Action	Specify a valid host name.
AAS0660E	Data segment unknown={data}
Explanation	Data received by the SMH agents is not recognized.
Action	Contact your Software AG technical support representative for assistance.
AAS0670E	No URL available in the Directory Server for the target server
Explanation	An internal error occurred in a Directory Server definition.
Action	Contact your Software AG technical support representative for assistance.

AAS0671E	Adabas Administration Service={service-id} has to be unique across the network
Explanation	The name of a service must be unique across the network. A name that has already been used was specified.
Action	Change the service name so it is unique.
AAS0672I	Default client cannot be deleted
Explanation	You cannot delete the default client configuration that is distributed with Adabas Administration Services.
Action	No action is required.
AAS0673E	DBID syntax error; follow this rule : n1 or n1,n2 or n1-n2, or n1,n2,n2,n4-n5
Explanation	The list of databases was not specified correctly. The syntax for a list of databases is given in the message.
Action	Correct the list of databases.
AAS0674E	Trace syntax error; follow this rule : nnnnn or 0xnnnn
Explanation	The trace information was not specified correctly. The correct syntax for trace information is given in the message.
Action	Correct the trace information.
AAS0675E	UNSOLICITED values are YES or NO
Explanation	An invalid value for the UNSOLICITED parameter was specified. Valid values are "YES" or "NO".
Action	Specify a valid value for the parameter.
AAS0676E	Adabas timeout cannot be less than 5 seconds
Explanation	An invalid value was specified for the ADABAS_TIMEOUT parameter. The value cannot be less than 5 seconds.
Action	Specify a valid value for the parameter.
AAS0677I	Command sent to Service {service-id}
Explanation	The command was sent to the service listed in the message.
Action	No action is required for this informational message.

AAS0678E	The timer timeout has to be between 1 and 3600 seconds
Explanation	An invalid value was specified for the TIMER_TIMEOUT parameter. The value must be between 1 and 3600 seconds.
Action	Specify a valid value for the parameter.
AAS0679E	The statistics logging period has to be between 1 and 1440 minutes
Explanation	An invalid value was specified for the STATISTICS_INTERVAL parameter. The value must be between 1 and 1440 minutes.
Action	Specify a valid value for the parameter.
AAS0680E	The log size value has to be between 1MB and 500MB
Explanation	An invalid value was specified for the LOGSIZE parameter. The value must be between 1 and 500 megabytes.
Action	Specify a valid value for the parameter.
AAS0681E	The remote check period has to be between 0 and 1440 minutes
Explanation	An invalid value was specified for the PING_DB_INTERVAL parameter. The value must be between 1 and 1440 minutes.
Action	Specify a valid value for the parameter.
AAS0682E	The local check period has to be between 5 and 600 seconds
Explanation	An invalid value was specified for the CHECK_DBS_INTERVAL parameter. The value must be between 5 and 600 seconds.
Action	Specify a valid value for the parameter.
AAS0683E	Port={port} value has to be between 0 and 65535
Explanation	An invalid port number was specified.
Action	Specify a valid port number.
AAS0684E	Service ID value has to be between 1 and 65535
Explanation	An invalid value was specified for the service ID. The value must be between 1 and 65535.
Action	Specify a valid service ID.

AAS0685E	Client name={name} cannot have more than 16 characters
Explanation	An invalid client configuration name was specified. The client configuration name cannot exceed 16 characters.
Action	Specify a valid client configuration name.
AAS0686E	Relay values are YES or NO
Explanation	An invalid value was specified for the RELAY_VALUES parameter. Valid values are "YES" or "NO".
Action	Specify a valid value for the parameter.
AAS0687E	Port={port} value has to be between 1 and 65535
Explanation	An invalid port number was specified. Valid values must lie between "1" and "65535".
Action	Correct the port number and try again.
AAS0689E	Port={port} string is not numerical
Explanation	An invalid port number was specified.
Action	Specify a valid port number.
AAS0690E	Numerical values required for parameter={parameter-name}
Explanation	A non-numeric value was specified for a parameter when a numeric value is expected. The parameter name is given in the message.
Action	Specify a valid value for the parameter.
AAS0691E	AUTOSTART/AUTOSTOP values are YES or NO
Explanation	An invalid value was specified for the AUTOSTART or AUTOSTOP parameters. Valid values are "YES" or "NO".
Action	Specify a valid value for the parameter.
AAS0692E	No entry found in Directory Server
Explanation	No entry definitions were found to manage in the Adabas Directory Server and, consequently, in the System Management Hub (SMH).
Action	Verify that the service for Adabas Administration Services is started. Service definitions cannot be reviewed in the System Management Hub (SMH) unless the server service is started.

AAS0693E	No Net-Work 7.X.X found in Directory Server
Explanation	No Entire Net-Work 7.2 node definitions were found to manage in the Adabas Directory Server and, consequently, in the System Management Hub (SMH).
Action	If you have any Entire Net-Work 7.2 nodes to be managed, you must first add them in SMH.
WCP0693E	No Net-Work 7.X.X found in Directory Server
Explanation	No Entire Net-Work 7.2 node definitions were found to manage in the Adabas Directory Server and, consequently, in the System Management Hub (SMH).
Action	If you have any Entire Net-Work 7.2 nodes to be managed, you must first add them in SMH.
AAS0694E	The DBID has to be between 1 and 65535
Explanation	An invalid Adabas database ID was specified. Valid database IDs are between 1 and 65535.
Action	Specify a valid database ID.
AAS0695E	Service={name} should not include the #. []=* characters
Explanation	The name of a service definition was specified with one of the special characters listed in the message.
Action	Specify a valid service definition name.
WCP0695E	Kernel={name} should not include the # . [] = \ * characters
Explanation	The name of a Kernel definition was specified with one of the special characters listed in the message. These characters cannot be used in a Kernel definition name.
Action	Specify a valid Kernel definition name.
AAS0696E	Client name should not include the #. []=* characters
Explanation	The name of a client configuration was specified with one of the special characters listed in the message. These characters cannot be used in a client configuration name.
Action	Specify a valid client configuration name.

AAS0697E	The WCP72 Service does not appear to be local
Explanation	The Entire Net-Work 7.2 node cannot be found and does not appear to be installed on the local machine.
Action	Correct the Entire Net-Work 7.2 node definition in SMH to point to the correct host machine.
AAS0698E	Duplication
Explanation	An attempt to add a definition that has already been added. The definition you tried to add is not added.
Action	No action is required for this informational message.
AAS0699E	Service file does not exist (it could be deleted)
Explanation	An attempt to delete a service failed; it is possible that it was already deleted.
Action	No action is required for this informational message.
AAS0700E	No entries found
Explanation	No definitions were found to manage in the System Management Hub (SMH).
Action	Verify that the service for Adabas Administration Services is started. Kernel definitions cannot be reviewed in the System Management Hub (SMH) unless the server service is started. If the problem persists, contact your Software AG technical support representative for assistance.
AAS0701E	No Server entries found
Explanation	No Adabas Administration Services entries were found to manage in the System Management Hub (SMH).
Action	Verify that the service for Adabas Administration Services is started. Service definitions cannot be reviewed in the System Management Hub (SMH) unless the Adabas Administration Services service is started. For more information, read <i>Starting and Stopping Adabas Administration Services</i> in your Adabas Administration Services documentation. If the problem persists, contact your Software AG technical support representative for assistance.
AAS0702E	Service={servicename} name cannot be numeric only
Explanation	The service name cannot contain only numeric values.
Action	Specify a valid service name.

AAS0703E	Client name={client-id} cannot be numeric only
Explanation	The client name cannot contain only numeric values.
Action	Specify a valid client name.
AAS0704W	No such entry in the Directory Server, please refresh!
Explanation	An attempt to reference an entry in the Directory Server failed.
Action	Refresh your SMH display to obtain the latest Directory Server entries.
AAS0705E	Port value has to be between 1 and 65535
Explanation	An invalid port number was specified.
Action	Specify a valid port number. For more information, read <i>Port Number Reference</i> , elsewhere in this documentation.
AAS0706E	Retry string not numerical
Explanation	The retry count specification was not numeric.
Action	Specify a numeric retry count.
AAS0707E	Retry interval string not numerical
Explanation	The retry interval specification was not numeric.
Action	Specify a numeric retry interval.
AAS0708E	Host Name={name} should not include the # []=* characters
Explanation	The host name was specified with one of the special characters listed in the message. These characters cannot be used in a host name.
Action	Specify a valid host name.
AAS0709I	No additional parameters supplied
Explanation	No additional parameters were supplied for the Adabas Administration Services configuration.
Action	No action is required for this informational message.

AAS0710E	Port={port} value has to be between 1 and 65535
Explanation	An invalid port number was specified.
Action	Specify a valid port number. For more information, read <i>Port Number Reference</i> , elsewhere in this documentation.
AAS0711E	Port2={port2} has to be greater than Port1={port1}
Explanation	When specifying a range of port numbers, the second port number should be larger than the first port number in the range. The port numbers specified are given in the message.
Action	Specify a valid range of port numbers.
AAS0713E	DBID={dbid} string is not numerical
Explanation	The Adabas database ID specified was not numeric.
Action	Specify a numeric database ID.
AAS0714E	DBID2={dbid2} has to be greater than DBID1={dbid1}
Explanation	When specifying a range of Adabas database IDs, the second database ID should be larger than the first database ID in the range. The database IDs specified are given in the message.
Action	Specify a valid range of database IDs.
AAS0715E	Empty string
Explanation	A blank string was specified for a parameter.
Action	Specify a valid value for the parameter.
AAS0716E	At least one access definition has to be selected
Explanation	An attempt to add an access definition was made but no access type was selected (for example, Classic, e-business Client, e-business SSL Client, etc.).
Action	Select an access type when adding an access definition.
AAS0717I	No listens found on Service={service-id}
Explanation	No active access entries were found for the active service.
Action	No action is required for this informational message.

AAS0718I	No connections found on Service={service-id}
Explanation	No active connection entries were found for the active service.
Action	No action is required for this informational message.
AAS0719E	REMEMBER_DBID values are YES or NO
Explanation	An invalid value was specified for the REMEMBER_DBID parameter. Valid values are "YES" or "NO".
Action	Specify a valid value for the parameter.
AAS0720E	The number of active clients has to be between 5 and 65535
Explanation	An invalid value was specified for the MAX_CLIENTS parameter. Valid values must be between 5 and 65535.
Action	Specify a valid value for the parameter.
AAS0721E	Timeout error; check if the Service is down
Explanation	A system timeout error occurred.
Action	Verify that the service is not down. If it is, restart it. If the problem persists, contact your Software AG technical support representative.
AAS0722E	DBID={dbid} not defined
Explanation	An Adabas database ID was not specified or an invalid one was specified.
Action	Specify a valid database ID.
AAS0723E	DBID={dbid} not active
Explanation	The Adabas database is not active.
Action	Start the database.
AAS0724E	Service={service-id} not defined
Explanation	An attempt was made to ping a service, but the service does not exist.
Action	Refresh your System Management Hub displays. The node may have been deleted since you started this SMH session.

AAS0725E	Service={service-id} not active
Explanation	An attempt was made to ping a service, but the service was not active.
Action	Start the node if you wish.
AAS0726E	No entry available
Explanation	An attempt was made to review an entry that is no longer available.
Action	Refresh your System Management Hub displays. The entry may have been deleted since you started this SMH session.
AAS0727E	Empty Service name
Explanation	No service definition name was specified.
Action	Specify a valid service definition name.
AAS0728E	Empty Client name
Explanation	No client configuration name was specified.
Action	Specify a valid client configuration name.
AAS0729E	Empty Host name
Explanation	No host name was specified.
Action	Specify a valid host name.
AAS0730E	Empty DBID string
Explanation	No Adabas database ID was specified.
Action	Specify at least one database ID.
AAS0731E	Empty Port string
Explanation	No port number was specified.
Action	Specify a valid port number. For more information, read <i>Port Number Reference</i> , elsewhere in this documentation.
AAS0732E	No Client definitions found in the Directory Server
Explanation	No client configuration definitions were found in the Adabas Directory Server.
Action	Verify that the service for Adabas Administration Services is started. Client configuration definitions cannot be reviewed in the System Management Hub (SMH) unless the service is started. If the problem persists, contact your Software AG technical support representative for assistance.

AAS0733E	Connection URL syntax error
Explanation	A syntax error exists in a connection URL. Entire Net-Work cannot make the connection.
Action	Contact your Software AG technical support representative for assistance.
AAS0734E	Connection with the same NODENAME already defined
Explanation	An attempt was made to define a connection to the same node twice. Only one connection definition is needed.
Action	Make sure that there is only one connection definition for the node.
AAS0735E	Host Name={hostname} not defined in DNS
Explanation	The host identified in the message is not defined in the DNS.
Action	Contact your Software AG technical support representative for assistance.
AAS0736E	Host Name={hostname} not defined in DNS
Explanation	The host identified in the message is not defined in the DNS.
Action	Contact your Software AG technical support representative for assistance.
AAS0738E	Target is down or not defined in the Directory Server
Explanation	A connection attempt was made to a target that is not correctly defined to Adabas Administration Services.
Action	Verify that the target definition is correct and complete (no required parameters are undefined) and try again. If the error persists, contact you Software AG technical support representative for assistance.
AAS0739E	Incoming Service already connected
Explanation	An attempt was made to define two connections for the same incoming service. Only one connection definition is needed.
Action	Make sure that only one connection definition exists for the incoming service. If the problem persists, contact your Software AG technical support representative for assistance.

AAS0740E	Connection failure; reason={rsncode}
Explanation	An attempt to make a defined connection failed. The reason code is given in the message.
Action	Analyze the reason code and try to resolve the problem. If the problem persists, contact your Software AG technical support representative for assistance.
AAS0741E	The SERVICE_THREADS value has to be between 5 and 1024
Explanation	The value of the SERVICE_THREADS parameter is not correct. It must be a numeric value between 5 and 1024.
Action	Correct the value and try again.
AAS0742E	No data available
Explanation	The service log file cannot be found.
Action	Contact your Software AG technical support representative.
AAS0743E	MULTIPLEX values are YES or NO
Explanation	An invalid value was specified for the MULTIPLEX parameter. Valid values are "YES" or "NO".
Action	Correct the value and try again.
AAS0744E	NOLOCAL values are YES or NO
Explanation	An invalid value was specified for the NOLOCAL parameter. Valid values are "YES" or "NO".
Action	Correct the value and try again.
AAS0745E	NOREMOTE values are YES or NO
Explanation	An invalid value was specified for the NOREMOTE parameter. Valid values are "YES" or "NO".
Action	Correct the value and try again.
AAS0746E	LOAD_BALANCING values are YES or NO
Explanation	An invalid value was specified for the LOAD_BALANCING parameter. Valid values are "YES" or "NO".
Action	Correct the value and try again.

AAS0747E	The maximum CPU threshold has to be between 10 and 99
Explanation	An invalid value has been specified for the MAX_CPU_THRESHOLD parameter.
Action	Correct the value and try again.
AAS0749E	STATISTICS_DETAILS values are YES or NO
Explanation	An invalid value was specified for the STATISTICS_DETAILS parameter. Valid values are "YES" or "NO".
Action	Correct the value and try again.
AAS0750E	USE_LOCAL_ADABASES values are YES or NO
Explanation	An invalid value was specified for the USE_LOCAL_ADABASES parameter. Valid values are "YES" or "NO".
Action	Correct the value and try again.
AAS0751E	Service={service-id} is not set to process local databases
Explanation	The service listed in the message is not defined to process local databases.
Action	Correct the USE_LOCAL_ADABASES parameter value in the service definition and try again.
AAS0752E	DATE_STAMP values are YES or NO
Explanation	An invalid value was specified for the DATE_STAMP parameter. Valid values are "YES" or "NO".
Action	Correct the value and try again.
AAS0753E	The CHECK_CXT_INTERVAL value has to be 0 or between 60 and 24*60*30 seconds
Explanation	An invalid value was specified for the CHECK_CXT_INTERVAL parameter. Valid values are zero (0) seconds or lie between 60 seconds and 43,200 seconds (24 * 60 * 30).
Action	Correct the value and try again.
AAS0754I	Service {service-id} migrated from WCP74
Explanation	The service listed in the message was successfully migrated from the 7.4 version of Entire Net-Work.
Action	No action is required for this informational message.

AAS0755I	Client {client-id} migrated from WCL14
Explanation	The client listed in the message was successfully migrated from the 1.4 version of Entire Net-Work Client.
Action	No action is required for this informational message.
AAS0756E	DBID={dbid} not accessible
Explanation	The database listed in the message could not be accessed.
Action	No action is required for this informational message.

19 AAUD* - AUDITLOG Messages

These are messages produced by Adabas AUDITLOG processing.

AAUD01 **{dbid} {userid} {xyyyy} description fnr={nnnn} rsp{zzz}/{ccc}**

Explanation The message describes the dbid, userid, originator for the product code that the function was issued for along with an explanation of the function and an indicator if the function was successful or not.

dbid	5-byte database ID where command was issued.
userid	8-byte user ID of user initiating command for z/OS. 8-byte jobname of job that executed the command for z/VSE. 8-byte TSN of job for BS2000. "*unknown" will be displayed if there is no userid or UQE found. Tip: This can occur in system generated functions such as online recovery.
xxx	3-byte product code (ADA, AFP, AVI, COR, AAF, ACF, DSF, TSP, EAB, ALS or ARF).
yyy	3-byte originator (UTI, AOS, AUX). Note: If command is not from AOS or AUX, "UTI" will be displayed. This can also be an internal type utility call.
description	31-byte description of function requested.
nnnn	5-byte file number if it pertains to function; otherwise blank. fnr=' ' signifies all files.
zzz	Response code or zero.
ccc	Subcode (only displayed if response code not 0).

Examples

```
20:45:23 AAUD01 00199 USAXXX ADAUTI Mod parms AUDITLOG ↵  
rsp064/005  
20:45:23 AAUD01 00199 USAXXX ADAUTI Mod parms AUDITLOG ↵  
rsp000  
20:55:24 AAUD01 00199 USAXXX ADAUTI ALOCKF set advance-lock ↵  
fnr= 1 rsp000
```

Action No action required. The message is informational.

AAUD99 {dbid}{userid} CMD:{XX} OP2:{YY} unknown

Explanation User ID on DBID executed the CMD/OP2 but it was unknown by the AUDITing routine.

XX	2-byte command code.
YY	2-byte command option 2.

Action Investigate what the user was doing and if necessary discuss with Software AG.

20

ACLX* - Adabas Review Interface Messages

These are messages produced by Adabas Review processing.



Note: Some of the ACLX* messages are preceded by the Adabas database ID. These database IDs are not shown in the message texts in this documentation.

ACLX01	Old RUBX arrived
Explanation	A RUBX for Adabas Review 4.4 or earlier has been received by the Adabas 8.2 nucleus. The older RUBX has been translated into a new format. This causes some performance degradation. New fields which do not exist in Adabas Review 4.4 are not translated.
Action	Determine which ADALNK contains an old Adabas Review module.
ACLX02	REV45 RUBX arrived and ignored
Explanation	A RUBX for Adabas Review 4.5 or later has been received by an Adabas 8.1 nucleus. The newer RUBX is ignored. The RUBX fields in Adabas Review are empty.
Action	Use the Adabas LX library for Adabas Review 4.5 or use Adabas 8.2.
ACLX03	{dbid} Client Report requires CLOGL=8
Explanation	Adabas Review client reports run only if ADARUN CLOGLAYOUT=8 is specified in the Adabas nucleus. An attempt was made to run a client report when CLOGLAYOUT=8 was <i>not</i> specified. The client reports will not run at all or some fields in the report will be empty.
Action	Specify ADARUN CLOGLAYOUT=8 in the concerning ADABAS nucleus and start the nucleus again.

21 ADAA* Adabas Auditing Messages

 **Note:** Each of the messages in this section starts with the relevant database ID.

ADAA01	{yyyy.mm.dd hh.mm.ss} No connection attempts will be made as a {yyyy.mm.dd hh.mm.ss} result of the AUDCONNECT request
Explanation	This message is printed as a result of the AUDCONNECT operator command (issued to an Auditing Server). The message is printed when no connection attempts will be made as a result of the AUDCONNECT operator command.
Action	Analyze the AUDCONNECT operator command you issued for invalid Adabas database IDs that might have been specified.
ADAA0G	{yyyy.mm.dd hh.mm.ss} A connection will be attempted {yyyy.mm.dd hh.mm.ss} with database id
Explanation	This message is printed as a result of the AUDCONNECT operator command (issued to an Auditing Server). The message is printed for each Adabas database for which the Auditing Server attempts a connection.
Action	No action is required for this informational message.
ADAAE2	Analytics activated for file {nnnnn} due to request from ADADBS/AOS
Explanation	Analytics was activated for file <i>nnnnn</i> . The second message only appears if the reason code indicates the request was from ADADBS or AOS.
Action	No action is required for this informational message.

ADAAE6	{yyyy.mm.dd hh.mm.ss} No connection attempts will be made as a {yyyy.mm.dd hh.mm.ss} result of the AUDCONNECT request
Explanation	This message is printed as a result of the AUDCONNECT operator command (issued to an Adabas nucleus). The message is printed when no connection attempts will be made as a result of the AUDCONNECT operator command.
Action	Analyze the AUDCONNECT operator command you issued for invalid Auditing Server IDs that might have been specified.
ADAAEG	{yyyy.mm.dd hh.mm.ss} A connection will be attempted {yyyy.mm.dd hh.mm.ss} with server id
Explanation	This message is printed as a result of the AUDCONNECT operator command (issued to an Adabas nucleus). The message is printed for each Auditing Server ID for which the nucleus attempts a connection.
Action	No action is required for this informational message.
ADAAKX	Requested storage exceeds maximum GETMAIN of 2,147,483,647 bytes
Explanation	A GETMAIN storage request would have exceeded the maximum amount that can be requested. Review the global definition settings for Subtasks and Maximum output size. The number of Subtasks + 1 for the main task is multiplied by the Maximum output size. In addition, storage for additional control blocks related to the number of Subtasks, is added to the total and the result is used in the GETMAIN storage request.
Action	Either reduce the size of the Maximum output size or reduce the number of Subtasks, so that the GETMAIN size is less than the maximum size allowed.
ADAAPM	The parameter {xxxxxxxx} must be in a group of file parameters
Explanation	The parameter must be preceded by an ADAANP FILE statement.
Action	Check the parameter; correct the error and rerun the job.
ADAAPN	The parameter {xxxxxxxx} must be in a group of global parameters
Explanation	The parameter must be preceded by an ADAANP GLOBAL statement.
Action	Check the parameter; correct the error and rerun the job.

ADAAPO	Only YES or NO are valid values for parameter {xxxxxxxxxx}
Explanation	Only YES or NO are valid values for this parameter.
Action	Check the parameter; correct the error and rerun the job.
ADAAAP	Only YES, NO, or FIELDS are valid values for parameter {xxxxxxxxxx}
Explanation	Only YES, NO or FIELDS are valid values for this parameter.
Action	Check the parameter; correct the error and rerun the job.
ADAAPQ	Invalid Adabas field name xx contained in parameter {xxxxxxxxxx}
Explanation	The Adabas field name does not conform to Adabas field name standards and will not be included in the list of field names.
Action	Check the parameter; correct the error and rerun the job.
ADAAPR	Parameter FSERVERID GSERVERID must be in the range 1 - 65535
Explanation	Only numbers in the range from 1 through 65535 are allowed.
Action	Check the parameter; correct the error and rerun the job.
ADAAPS	Parameter GAPWARNINCREMENT must be in the range 1 - 99
Explanation	Only numbers in the range from 1 through 99 are allowed.
Action	Check the parameter; correct the error and rerun the job.
ADAAPT	Parameter GAPWARNINTERVAL must be non-zero
Explanation	Only a non-zero value is allowed.
Action	Check the parameter; correct the error and rerun the job.
ADAAPU	Parameter GAPWARNMESSAGELIMIT must be non-zero
Explanation	Only a non-zero value is allowed.
Action	Check the parameter; correct the error and rerun the job.
ADAAPV	Parameter GAPWARNPERCENT must be in the range 1 - 99
Explanation	Only numbers in the range from 1 through 99 are allowed.
Action	Check the parameter; correct the error and rerun the job.

ADAAPW **Parameter FSERVERID | GSERVERID must not be equal to the current database ID**

Explanation The value cannot be equal to the current database ID.

Action Check the parameter; correct the error and rerun the job.

ADAAPX **Parameter FLIST contains invalid file number {nnnnnnnnnn}**
Parameter FLIST contains invalid file range {nnnnnnnnnn} - {nnnnnnnnnn}
From file number will be set to 1
To file number will be set to maximum file number {nnnnnn}

Explanation The parameter contains an invalid file number or range.

An invalid file number will not be included in the file list.

If both numbers in a file range are invalid and the FROM value is not 0, the file range will not be included in the file list

If the FROM value is 0 it will be set to 1, the lowest possible value.

If the TO value is greater than the maximum file number and the FROM value is 0 or a valid value, the TO value will be set to the maximum file number.

Action Check the parameter; correct the error and rerun the job.

ADAAPY **Required FLIST parameter is missing from the group of file parameters**
The group of file definitions will not be used

Explanation The FLIST parameter is required and missing from the group of file parameters. The group of file parameters will not be used.

Action Check the parameter; correct the error and rerun the job.

ADAAP0 **All files within the FLIST parameter are invalid**
The group of file definitions will not be used

Explanation All the files specified in the FLIST parameter were invalid. The group of file definitions will not be used.

Action Check the parameter; correct the error and rerun the job.

ADAATA **Load failed for {mmmmmmmm}**

Explanation The load of the ADAABK/ADAAMT module has failed. The module name is given as *mmmmmmmm*.

Action Ensure the given module is available to the Analytics Server. Contact your DBA, system support personnel, or Software AG technical support if further assistance is needed.

ADAATB	{YYYYYY} INIT call failed
Explanation	An error occurred during the initialization phase of YYYYYY. Where YYYYYY is either ADAABK or ADAAMQ and the text is followed by either 'GETMAIN failed' or the return code and reason code.
Action	Determine the reason for the failure based on the supplied reason code and correct the condition. Contact your DBA, system support personnel, or Software AG technical support if further assistance is needed.
ADAATC	Connect failed Error info
Explanation	The Connect to the messaging system failed. The second line contains the Broker ID or the MQSeries queue manager name. The third line contains the error information.
Action	Determine the reason for the failure based on the supplied reason code and correct the condition. Contact your DBA, system support personnel, or Software AG technical support if further assistance is needed.
ADAATF	Disconnect failed Error info
Explanation	The Disconnect to the messaging system failed. The second line contains the Broker ID or the MQSeries queue manager name. The third line contains the error information.
Action	Determine the reason for the failure based on the supplied reason code and correct the condition. Contact your DBA, system support personnel, or Software AG technical support if further assistance is needed.
ADAATG	{YYYYYY} TERM call failed
Explanation	An error occurred during the termination phase of YYYYYY. Where YYYYYY is either ADAABK or ADAAMQ and the text is followed by return code and reason code.
Action	Determine the reason for the failure based on the supplied reason code and correct the condition. Contact your DBA, system support personnel, or Software AG technical support if further assistance is needed.
ADAATH	Delete failed for {YYYYYY}
Explanation	An attempt to delete the module YYYYYY from storage failed. Where YYYYYY is either ADAABK or ADAAMQ. This should not occur and should be reported to your local support center.
Action	Contact your local support center.

ADAA1U	{nnn} output subtasks have been detached
Explanation	The Analytics Server output subtask termination process has completed. The total number of subtasks that have been terminated is given in the message (<i>nnn</i>).
Action	No action is required for this informational message.
ADAA1V	Subtask {nnn} detach error {eee} occurred
Explanation	An error occurred while an Analytics Server output subtask was being detached. The subtask number (<i>nnn</i>) and the error number (<i>eee</i>) are given in the message.
Action	Analytics Server termination continues. Contact your DBA, system support personnel, or Software AG technical support for assistance.
ADAA1W	Waiting for the termination of analytics server output subtasks
Explanation	The termination of Analytics Server output subtasks is in progress.
Action	No action is required for this informational message.
ADAA1X	{nnn} output subtasks to be attached
Explanation	The Analytics Server is preparing to attach output subtasks.
Action	No action is required for this informational message.
ADAA17	All output subtasks could not be initialized
Explanation	One or more Adabas Analytics Server output subtasks could not be started successfully. One possible reason for this might be that the default subtask wait time (or the time specified by the SUBTASKWAIT parameter) is insufficient for your system. For more information about the SUBTASKWAIT parameter, refer to <i>SUBTASKWAIT (Subtask Wait Time) Parameter</i> , in the <i>Adabas Analytics</i> documentation.
Action	Evaluate the setting of the SUBTASKWAIT parameter for your Adabas Analytics Server and consider increasing it (or setting it if it has not been set). If you still need assistance or the problem persists, contact your DBA, system support personnel, or Software AG technical support.

22

ADACM* - ADATCP Messages

ADACM007E	PARM ERROR
Explanation	One of the parameters passed within the URL was incorrect.
Action	Ensure that the URL includes valid values for all required elements: the API name (protocol), stack ID, and port number. Correct the URL and try again.
ADACM008E	INVALID VALUE IN PORT= PARAMETER
Explanation	The port that was specified in the URL was not valid.
Action	The port number can be 1-5 bytes; it cannot be zero (0) or greater than 65535.
ADACM009E	URL=url ALREADY {ACTIVE CLOSED}
Explanation	Either the URL is already opened (ACTIVE) or already closed (CLOSED).
Action	Ensure that the URL includes valid values for all required elements: the API name (protocol), stack ID, and port number. Correct the URL and try again.
ADACM010E	URL=url NOT FOUND
Explanation	The URL itself was not found.
Action	Ensure that the URL includes valid values for all required elements: the API name (protocol), stack ID, and port number. Correct the URL and try again.
ADACM011I	URL=url HAS BEEN {CLOSED OPENED}
Explanation	Either the URL was successfully closed or opened.
Action	None. This message is for information only.

ADACM012E	THE NETWORK IS DOWN
Explanation	ADATCP cannot be started because the network is not active.
Action	Check that the stack specified in the URL is active. If it is, contact your systems administrator.
ADACM013E	NO BUFFER SPACE IS AVAILABLE
Explanation	No buffer space is available to ADATCP to allocate its control blocks.
Action	Ensure that sufficient storage is available on the system.
ADACM014E	THE LINK HAS BEEN SEVERED
Explanation	An error caused TCP/IP or ADATCP to terminate.
Action	This message is issued along with another message that explains the reason for the termination. Refer to the other message.
ADACM015E	TCP/IP IS NOT INSTALLED OR ACTIVE
Explanation	The TCP/IP stack specified in the URL is not installed or not active.
Action	Check that the specified URL is the one intended. If so, either install the specified stack or start it.
ADACM016E	THE SOCKET DESCRIPTOR TABLE IS FULL
Explanation	The maximum number of socket descriptors has been reached: no more sockets can be created.
Action	Increase the maximum number of sockets that can be created.
ADACM017I	TCP/IP HAS TERMINATED
Explanation	Unless this message is accompanied by an error message, TCP/IP has terminated normally.
Action	If an error message accompanies this message, refer to that message. Otherwise, this message is for information only.
ADACM018E	THE API CANNOT LOCATE THE TCP/IP SPECIFIED
Explanation	The stack specified in the URL is not valid: TCP/IP cannot initialize.
Action	Ensure that the stack is available on the system and that it is active.

ADACM019E	THE TCP/IP NAME SPECIFIED IS NOT VALID
Explanation	The TCP/IP name specified in the URL is not valid.
Action	Check that the URL contains the correct stack name. If so, ensure that the stack is available on the system and that it is active.
ADACM020E	TCP/IP FAILED TO LOAD
Explanation	The TCP/IP stack specified in the URL cannot be initialized.
Action	Ensure that the TCP/IP stack specified is correct and that it is active. If it is correct and active, contact the systems administrator.
ADACM021E	UNABLE TO ALLOCATE STORAGE FOR SOCKETCB
Explanation	ADATCP is unable to allocate the necessary storage.
Action	Ensure that adequate storage is available on the system.
ADACM022E	INVALID OPERATING SYSTEM FOR API=HPS
Explanation	The operating system specified in the URL is incorrect.
Action	The only operating systems currently supported are OES and HPS.
ADACM023E	UNABLE TO INITIALIZE TCP/IP INTERFACE
Explanation	The TCP/IP stack specified in either the URL or the protocol that was used is invalid.
Action	Check that the URL or protocol contains the correct stack name. If so, ensure that the stack is available on the system and that it is active.
ADACM024E	UNABLE TO GET A SOCKET
Explanation	The system is unable to create a new socket. This may be caused by an incorrect stack. If an error number accompanies this message, it will inform you if the problem is inadequate system resources (ENOBUFS) or access denied (EACCES).
Action	Ensure that the correct stack is being used. If the problem is inadequate system resources, contact your systems administrator. Contact your security administrator for system access problems.
ADACM025E	UNABLE TO BIND SOCKET TO LOCAL SYSTEM
Explanation	ADATCP was unable to bind the socket to the local system. Another application may be using the port specified in the URL.
Action	Use the TSO NETSTAT command to check current use of the specified port. If something else is using the port, terminate ADATCP and change the port in the URL.

ADACM026E	UNABLE TO ACCEPT CONNECTIONS
Explanation	ADATCP is unable to accept connections from client applications. This may indicate a shortage of buffer space or that the maximum number of socket descriptors have already been created/opened.
Action	Ensure that adequate buffer space is available to the system. If necessary, increase the maximum number of sockets available to the system.
ADACM027E	UNABLE TO LISTEN FOR NEW CONNECTIONS
Explanation	ADATCP is unable to listen for new connections. This usually indicates that the system resources available to complete the call are inadequate. If an error number is supplied with this message, it will help to identify the problem.
Action	If system resources are inadequate, contact your systems administrator.
ADACM028E	UNABLE TO SET SOCKOPT REUSEADDR OPTION
Explanation	An attempt to allow currently used local addresses to be bound failed. This may indicate inadequate system resources. If an error number is supplied with this message, it will help to identify the problem.
Action	If system resources are inadequate, contact your systems administrator.
ADACM029E	UNABLE TO GIVESOCKET TO NEW THREAD
Explanation	ADATCP was unable to give control of a socket to a different process. This error occurs only if there is a problem with the socket itself. If an error number is supplied with this message, it will help to identify the problem.
ADACM030E	UNABLE TO CREATE A NEW THREAD
Explanation	The system was unable to create a new thread. This indicates inadequate system resources or memory to create the thread.
Action	Contact your systems administrator.
ADACM031E	UNABLE TO CLOSE THE REQUESTED SOCKET
Explanation	ADATCP attempted to close a socket that was being used by another thread in the same process. This occurs only when the system is terminating due to some other error.
Action	Check the console for other messages.

ADACM032E	UNABLE TO MALLOC STORAGE
Explanation	ADATCP was unable to allocate storage. This may indicate that inadequate storage is available on the system.
Action	Contact your systems administrator.
ADACM034E	UNABLE TO RECEIVE DATA
Explanation	ADATCP cannot receive data from a client. This may indicate that the connection between ADATCP and the client has been severed during a transaction or that system resources are inadequate to complete the call. The error number supplied with this message will identify the problem.
Action	Contact your systems administrator.
ADACM035E	UNABLE TO TAKE THE SOCKET
Explanation	The process that send requests to and from Adabas was unable to take control of the socket that was passed to it by the listening task.
Action	Check the error number and the return code that accompany this message.
ADACM036E	UNABLE TO SET THE CANCEL TYPE
Explanation	The main request task is unable to set the cancel type for the thread that is currently running.
Action	Check the error number and the return code that accompany this message.
ADACM037E	UNABLE TO SEND DATA
Explanation	ADATCP is unable to send data from a client. The error number issued with this message indicates whether the problem is a severed connection between ADATCP and the client or insufficient system resources to complete the call.
Action	Check the error number issued with this message.
ADACM038E	UNABLE TO CLOSE THE SOCKET
Explanation	ADATCP attempted to close a socket while it was being used by another thread in the same process. This occurs if the system has tried to terminate due to another error.
Action	Check for other messages issued to the console.

ADACM039E

CONTEXT TABLE FULL

Explanation

The number of connections has reached a predefined limit; no entries can be added to the user context table.

Action

Increase the ADARUN NU parameter value to the required number of entries and restart ADATCP.

23

ADAD* Abend Code Messages

ADAD01 {**version**} {**job-name**} **abend code** {**code**}

Explanation This message is displayed on SYSLOG when an abend condition occurs within ADALNK.

Action ADALNK issues the following information:

version	the Adabas version
job-name	the z/VSE job name
code	the abend code

24

ADAE* Adabas SAF Security (ADASAF) Messages



Note: Each of the messages in this section starts with the relevant database ID.

ADAE01	Unable to load required modules
Explanation	A required module could not be loaded. Operation terminates with an abend U0042.
Action	Check that the modules NA2PMAC and ESICFG are available.
ADAE02	Unable to allocate required storage
Explanation	There is insufficient storage available for ADASAF to operate. Operation terminates with an abend U0042.
Action	Increase the amount of storage (above the 16-megabyte line) available to the failing job.
ADAE03	Unable to allocate NRS storage
Explanation	ADASAF needs approximately two KB of storage below the 16-megabyte line. If the storage is not available at initialization (or after a newcopy operator command), ADASAF issues this message and operation terminates.
Action	Ensure that enough storage is available.
ADAE04	Module {module-name} not loaded
Explanation	The indicated module could not be loaded during initialization or during the newcopy operator command. If the module is required (rather than optional), operation terminates.
Action	Ensure that the module is available.

ADAE05	Invalid parameters detected
Explanation	One or more invalid parameters were specified in DDSAF. Operation terminates.
Action	Correct the invalid parameters.
ADAE06	Allocation of user file cache failed
Explanation	ADASAF allocates a user file cache above the 16-megabyte line. If the storage is not available at initialization (or after a newcopy operator command), ADASAF issues this message and operation terminates.
Action	Ensure that enough storage is available or reduce the MAXFILES parameter (this may adversely affect performance).
ADAE07	{input-parameter}
Explanation	ADASAF echoes the parameters read from DDSAF for information and auditing purposes.
ADAE08	Invalid parameter: {input-parameter}
Explanation	ADASAF detected incorrect input in DDSAF. ADAE08 is issued for each invalid parameter found and is followed by ADAE05.
Action	Correct the invalid parameter.
ADAE12	ADASAF is active in {FAIL WARN} mode
Explanation	ADASAF has successfully initialized in the mode indicated.
ADAE15	NEWCOPY of parameter module failed
Explanation	After a NEWCOPY operator command, ADASAF was unable to reload ESICFG. Operation terminates.
Action	This error occurs only if there is a shortage of storage or the module ESICFG was deleted from the load library after initialization. Determine which of these is the case and correct it.
ADAE16	NEWCOPY reinitialization failed
Explanation	This message appears after a failure during NEWCOPY processing. It should be accompanied by a more detailed error message specifying the nature of the failure.
Action	Take the action recommended by the accompanying message.

ADAE17	Not APF-authorized
Explanation	ADASAF must run APF-authorized. Operation terminates.
Action	Check that all STEPLIBs are in the APF list and that ADARUN is linked with AC(1).
ADAE18	No security details for job {job-name}
Explanation	An Adabas command received from the named job had no security credentials attached to it. The command is rejected with response code 200 (ADARSP200), subcode 3.
Action	Ensure that the security exits are correctly installed in the Adabas SVC and that the source job has been configured correctly to support SAF security systems.

25

ADAF* - Event Replicator for Adabas Messages

These are the messages produced by Event Replicator for Adabas processing.



Note: Some of the ADAF* messages are preceded by the Adabas or Event Replicator Server database ID. These database IDs are not shown in the message texts in this documentation.

ADAF01	Replication GETMAIN failed
Explanation	Getmain for Replication area failed or there was insufficient storage available.
Action	Rectify the Getmain problem and rerun the job.
ADAF02	READONLY=YES not allowed
Explanation	READONLY=YES is not allowed for an Event Replicator Server.
Action	Supply correct parameters and rerun the job.
ADAF03	DTP=TM not allowed
Explanation	DTP=TM is not allowed for an Event Replicator Server.
Action	Supply correct parameters and rerun the job.
ADAF04	LRPL specification too low
Explanation	The LRPL must be at least 20,000.
Action	Supply correct parameters and rerun the job.

ADAF05	MODE=SINGLE not allowed
Explanation	MODE=SINGLE is not allowed for an Event Replicator Server.
Action	Supply correct parameters and rerun the job.
ADAF06	Program {module} could not be loaded
Explanation	An Event Replicator Server module could not be loaded.
Action	Ensure that the module listed in the message is in the Adabas load library concatenation and retry the job. Ensure the versions of Adabas and Event Replicator for Adabas are compatible.
ADAF07	STP=YES not allowed
Explanation	STP=YES not allowed for an Event Replicator Server.
Action	Supply correct parameters and rerun the job.
ADAF08	REPLICATION=YES not allowed
Explanation	Conflicting parameters - REPLICATION=YES not allowed for this Event Replicator Server database.
Action	Supply correct parameters and rerun the job.
ADAF09	{parm} specification too low [{explanation} . {explanation}]
Explanation	This message can have multiple texts, as listed below: <ul style="list-style-type: none"> ■ xxxxx NT specification too low. NT must be greater than or equal to 15. ■ xxxxx LU specification too low, minimum is 167000 ■ xxxxx NAB specification too low, minimum is 41 <p>In all cases, the value specified for the named parameter is too low. In some cases the minimum value is given in the message.</p>
Action	Increase the value of the named parameter and rerun the job.
ADAF10	Load of {module} failed.
Explanation	An attempt to load the module listed in the message failed.
Action	Ensure that the module is in the Adabas load library concatenation and retry the job.

ADAF11	Error opening DDKARTE
Explanation	The cause is probably a misspelled keyword.
Action	Check the JCL; correct the error and rerun the job.
ADAF12	I/O error reading DDKARTE
Explanation	The cause is probably a misspelled keyword.
Action	Check the JCL; correct the error and rerun the job.
ADAF13	Parameter error, name not ADARPD
Explanation	The cause is probably a misspelled keyword.
Action	Check the parameter input, correct the error, and rerun the job.
ADAF14	Parameter error, missing separator
Explanation	The cause is probably incorrect parameter input.
Action	Check the parameter input, correct the error, and rerun the job.
ADAF15	Parameter error, invalid syntax
Explanation	The cause is probably incorrect parameter input.
Action	Check the parameter input, correct the error, and rerun the job.
ADAF16	Parameter error, keyword not unique
Explanation	The cause is probably incorrect parameter input.
Action	Check the parameter input, supply the correct keyword in full length, and rerun the job.
ADAF17	Parameter error, unknown parameter
Explanation	The cause is probably a misspelled keyword.
Action	Check the JCL; correct the error and rerun the job.
ADAF18	{jjjj.mm.tt} {hh.mm.ss }{cc} {cmd} to DBID {dddd} FNR {ffff} RSP {rrr} Subcode {ssss}
Explanation	A command (<i>cc</i>) to the target DBID/FNR (<i>dddd</i> and <i>ffff</i>) identified in the message failed. The response code (<i>rrr</i>) with subcode (<i>ssss</i>) are also given in the message. If the command is not an S4 command, the text "ISN <i>iiiiiii</i> " is appended to this message text, listing the ISN number.

Action Investigate the reason for the response code and subcode on the target database and correct the problem. The command did not complete on the target database.

ADAF19 **Parameter error, too many values in list**

Explanation The cause is probably incorrect parameter input.

Action Check the parameter input. Supply no more than the maximum number of parameter values permitted, and rerun the job.

ADAF1A **Terminating with replication data outstanding for the following:**

Reptor {dbid}

File {filename}

PLOG INFORMATION

Explanation The nucleus has terminated with replication data outstanding for the Event Replicator Servers and files listed in the message. This message is issued when a HALT command is issued for an Adabas nucleus for which replication is active (REPLICATION=YES). If an Event Replicator Server is available, outstanding replication data for this nucleus has been sent to the Event Replicator Server.

More than one Event Replicator Server may appear in the message if the Adabas nucleus sends data to more than one Event Replicator Server; likewise, more than one file may appear in the message if replication data for more than one file is outstanding at the time of the HALT. And finally, PLOG information appears after the file message lines if one or more replication pseudo transactions exist with PLOG information.

Action Check for message [ADAF1Q](#) to verify the Event Replicator Server successfully processes all previously sent replication data for this database. If an Event Replicator Server was not available at the time of the HALT, an initial-state request may be used to synchronize a file.

ADAF1B **Event Replicator Server {dbid} has disconnected**

Explanation The Event Replicator Server listed in the message has disconnected from the nucleus.

Action No action is required for this informational message.

ADAF1C **Connected to local Event Replicator Server {dbid}**

Explanation The nucleus has connected to the Event Replicator Server listed in the message.

Action No action is required for this informational message.

ADAF1D	Reconnected to local Event Replicator Server {dbid}
Explanation	The nucleus has reconnected to the Event Replicator Server listed in the message. This may happen if the Event Replicator Server was terminated but the nucleus remained active, and then the Event Replicator Server restarted.
Action	No action is required for this informational message.
ADAF1E	Waiting for replication data to be processed by Event Replicator Server {dbid}
Explanation	The nucleus is waiting for the Event Replicator Server listed in the message to finish processing data. When the Event Replicator Server has completed the work, the nucleus will terminate.
Action	Start the Event Replicator Server if it is not currently active.
ADAF1F	Disconnected from Event Replicator Server {dbid}
Explanation	The nucleus has disconnected from the Event Replicator Server listed in the message.
Action	No action is required for this informational message.
ADAF1G	Crosscheck for database {dbid} failed with response code {rrr/sss}
Explanation	The Event Replicator Server attempted to do a crosscheck for the database listed in the message, but received the response and subcode (<i>rrr/sss</i>) listed in the message during the attempt.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF1H	Event Replicator Server {dbid} shutting down
Explanation	The Event Replicator Server listed in the message is shutting down.
Action	No action is required for this informational message.
ADAF1I	Event Replicator Server {dbid} not present
Explanation	The nucleus tried to communicate with the Event Replicator Server listed in the message, but the Event Replicator Server is not available.
Action	Start the Event Replicator Server.

ADAF1J	Crosscheck aborted. Unable to obtain 48,000 bytes from LWP Increase LWP to allow crosscheck to execute
Explanation	The Event Replicator Server requires 48,000 bytes of storage from the Adabas work pool to run the crosscheck function.
Action	Increase the LWP parameter setting for Adabas and retry. For more information, read about the ADARUN statement and its LWP parameter in your Adabas operations documentation.
ADAF1K	Replication deactivated for file {file} due to {reason}
Explanation	Replication has been deactivated by the Adabas nucleus for the identified file. The <i>reason</i> will be one of the following: <ul style="list-style-type: none">■ replication pool overflow■ request from Event Replicator Server■ request via operator command/AOS
Action	If the deactivation reason is "replication pool overflow", consider increasing the value of the LRPL parameter. For other reasons, this message is for information only.
ADAF1L	replication pool usage {increased decreased} to {more less} than {number} %
Explanation	These messages begin when replication pool usage first exceeds the value of ADARUN parameter RPWARNPERCENT. Further messages appear at usage intervals specified by ADARUN parameter RPWARNINCREMENT.
Action	If the usage is not anticipated, you may want to adjust ADARUN parameter LRPL to increase the size of the replication pool. Adjust ADARUN parameters RPWARNPERCENT and RPWARNINCREMENT to control when warning messages are issued.
ADAF1M	Starting replication pool warning suppression {number} replication pool warnings suppressed
Explanation	A number of ADAF1L messages warning of a replication pool shortage have been issued. In order to avoid flooding the console, additional messages are suppressed for a period after a threshold is reached. When the suppression period has expired, the Event Replicator Server will display the number of suppressed message lines and then start printing replication pool usage warning messages again. The number of messages issued before suppression is specified by ADARUN parameter RPWARNMESSAGELIMIT. The suppression interval is specified by ADARUN parameter RPWARNINTERVAL.
Action	No action is required for these informational messages. If needed, adjust the ADARUN parameters RPWARNMESSAGELIMIT and RPWARNINTERVAL to control message traffic.

ADAF1N	Invalid Input Message: {<message block>}						
Explanation	<p>The Event Replicator Server received a message from an input queue but could not process it because some data structure was not correctly interpreted.</p> <p><message block> gives additional information:</p> <ul style="list-style-type: none"> ■ URBH - The URBH message header could not be processed ■ URBH - Input message truncated ■ URBI - The URBI message structure could not be processed 						
Action	For the memory shortage check if the LRPL needs to be increased. If the input message is truncated, increase the size of the input queue buffer parameter, IQBUFLN. In the other cases make sure that the input requests are set up correctly.						
ADAF1O	{invalid destination message}'						
Explanation	This message may appear with multiple texts, all relating to an invalid destination setting, as described in the following table:						
	<table border="1"> <thead> <tr> <th>Message Text</th> <th>Explanation</th> </tr> </thead> <tbody> <tr> <td>Invalid Response Destination: <i>destination</i></td> <td>The response destination supplied for an initial-state request is invalid. The invalid destination is listed in the message.</td> </tr> <tr> <td>Initial-state request rejected. Response: <i>rrr</i> Subcode <i>ssss</i></td> <td>This message is printed on the console. It indicates that the initial-state request was rejected because the destination for the response was not supplied.</td> </tr> </tbody> </table>	Message Text	Explanation	Invalid Response Destination: <i>destination</i>	The response destination supplied for an initial-state request is invalid. The invalid destination is listed in the message.	Initial-state request rejected. Response: <i>rrr</i> Subcode <i>ssss</i>	This message is printed on the console. It indicates that the initial-state request was rejected because the destination for the response was not supplied.
Message Text	Explanation						
Invalid Response Destination: <i>destination</i>	The response destination supplied for an initial-state request is invalid. The invalid destination is listed in the message.						
Initial-state request rejected. Response: <i>rrr</i> Subcode <i>ssss</i>	This message is printed on the console. It indicates that the initial-state request was rejected because the destination for the response was not supplied.						
Action	Make sure that the input request sets up the correct destination for response.						
ADAF1P	One or more File destinations are defined but CLOG is not active						
Explanation	One or more File destination definitions are being used, but the CLOG to which the replication TLOG URBLTDOD records will be routed is not identified in the Event Replicator Server startup JCL. The File destinations are set to "Unavailable" and processing continues.						
Action	Identify the CLOG in the Event Replicator Server startup JCL and try again.						
ADAF1Q	All in-flight transactions from terminated nuclei have been fully processed						
Explanation	The Event Replicator Server has finished processing in-flight transactions for nuclei terminated previously via HALT.						
Action	No action is required for this informational message.						

ADAF1R	Request to database {dbid} to terminate initial-state processes failed with response {rrrrr} / {sssss} Request to database {dbid} / {nucid} to terminate initial-state processes failed with response {rrrrr} / {sssss}
Explanation	The Event Replicator Server has been terminated by a halt request. During termination processing, one or more initial-state requests were found to be active on the database or database and nucleus listed in the message. The request to the nucleus to terminate the initial-state processes failed with Adabas response code and subcode (<i>rrrrr/sssss</i>) given in the message.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF1S	{Starting input request error message suppression} {number} input request message lines suppressed
Explanation	Errors were detected in messages from a target application on an Event Replicator Server input queue. In order to avoid flooding the console, the Event Replicator Server starts suppressing messages for approximately one minute after a threshold is reached. When the suppression period has expired, the Event Replicator Server will display the number of suppressed message lines and then start printing input transaction error messages again. This message can have multiple texts, all relating to error message suppression: <ul style="list-style-type: none">■ Starting message suppression■ <i>nnnn</i> message lines suppressed
ADAF1T	Adabas could not inform Reptor about deactivation of replication for file {file}.
Explanation	Replication for a file was being deactivated by the Adabas nucleus. Adabas was unable to acquire sufficient resources to notify the associated Event Replicator Server.
Action	Execution continues. This is often the result of a shortage in the replication pool. Increasing the value of the LRPL parameter may alleviate the shortage.
ADAF1U	Adabas replication pool overflow Failed to allocate {size} bytes for {use}.
Explanation	There was not enough free storage in the replication pool to satisfy the request.
Action	Execution continues. Increasing the value of the LRPL parameter may alleviate the shortage.

ADAF1V	<p>Input request {type}: {error} URBIRTOK: {token} URBIRNAM:{destination} URBIDNAM:{destination} URBISNAM:{subscription} URBITSNR:{number}</p>
Explanation	<p>A replication status or prior-transaction request has an error, and a response code and subcode could not be sent via a URBS status message. The <i>type</i> appearing in the message identifies the request type and will be either "STAT" (replication status) or "TRAN" (prior-transaction). The <i>destination</i>, <i>subscription</i> and <i>number</i> are taken from the URBI for the request. The <i>number</i> will appear only for "TRAN" requests.</p> <p>The following <i>errors</i> can appear in the message if the request <i>type</i> is either "STAT" or "TRAN":</p> <p>URBIARC/ACOD/WCOD not zero URBIRES1/URBIRES2 not zero</p> <p>The following <i>errors</i> can appear in the message only if the request <i>type</i> is "STAT":</p> <p>Storage shortage in RPL pool URBIRNAM undefined/unusable URBIDNAM and URBISNAM omitted URBISNAM undefined/unusable URBIDNAM undefined/unusable No active destinations</p> <p>The following <i>errors</i> can appear in the message only if the request <i>type</i> is "TRAN":</p> <p>RSP0 but URBIRNAM not active URBIRNAM is unknown URBIDNAM is unknown URBISNAM omitted or unknown URBIDNAM not in URBISNAM URBISNAM has no resend buffer URBITRNR not in resend buffer URBISNAM not active Invalid transaction in buffer No active resend destinations URBILEND not zero URBIDBID/URBIFNR not zero URBIINAM not permitted</p>
Action	<p>If the <i>error</i> indicates an RPL storage pool shortage, consider increasing the value of the LRPL parameter.</p> <p>If the <i>error</i> indicates that an invalid transaction exists in the resend buffer, an internal error has been detected. Notify your Software AG support representative.</p> <p>If the <i>error</i> indicates that there are no active destinations, this message is for information only.</p> <p>For all other <i>errors</i>, correct the status request or resend the prior-transaction request.</p>

ADAF1W	Connect to Reptor {dbid} failed with response{ rrrr/ssss}
Explanation	The Event Replicator Server listed in the message is active, but the nucleus received the response code and subcode (<i>rrrr/ssss</i>) listed in the message.
Action	Investigate the response code and subcode to identify and correct the problem. For response code 22 (ADARSP022), subcode 26, ensure that you are trying to connect to another Adabas nucleus and not an Event Replicator Server and try again.
ADAF1X	Sending data to Reptor {dbid} failed with response code {rrrr/ssss}
Explanation	An attempt to send data to the Event Replicator Server listed in the message failed with the response code and subcode (<i>rrrr/ssss</i>) listed in the message.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF1Y	Disconnecting from Reptor {dbid} failed with response code {rrr/sss}
Explanation	When the nucleus attempted to disconnect from the Event Replicator Server listed in the message, the response code and subcode (<i>rrr/sss</i>) listed in the message were received.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF1Z	TLOG event logging requested by CLOG is not active
Explanation	TLOG logging has been requested, however the CLOG to which TLOG records are written is not active.
Action	Activate the CLOG using the relevant ADARUN parameters in the Event Replicator Server.
ADAF20	{statistics}
Explanation	This message is displayed in response to the operator command DRPLSTAT. It shows the replication-related statistics for a database.
Action	No action necessary for this informational message.
ADAF21	JJJJ.MM.TT HH.MM.SS Input record not replicated: Destination {ddddddd} DBID {xxxxx} FNR {ffff} Action ISN {iiiiiii} Rsp {rrrrr} Subcode {sssss}
Explanation	A record with ISN <i>iiiiiii</i> for destination <i>ddddddd</i> DBID <i>xxxxx</i> FNR <i>ffff</i> with the action (Update, Insert, Delete, or Replace (for Initial State) received Rsp <i>rrrrr</i> Subcode <i>sssss</i>
Action	Investigate the reason for the error and correct. The command did not complete on the target.

ADAF22	Valid range for MAXOUTPUTSIZE is 32,768 to 2,147,483,647
Explanation	The parameter MAXOUTPUTSIZE has an incorrect value specified.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF23	DASUBSCRIPTION only valid for DTYPE=ADABAS
Explanation	When specifying a DESTINATION NAME parameter, the DASUBSCRIPTION keyword is only valid for DTYPE=ADABAS.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF24	Multiple function keywords - only one executed
Explanation	The parameter input has multiple function keywords within a statement, and only one is executed.
Action	Check the parameter input, correct the error, and rerun the job.
ADAF25	Close error for DDKARTE
Explanation	After reading the parameter input, there has been a close error for DDKARTE.
Action	Investigate the cause of the error; correct it, and rerun the job.
ADAF26	GETMAIN error - not enough memory
Explanation	A GETMAIN has failed to acquire memory that the Event Replicator Server requires.
Action	Check the JCL or Job; correct the error and rerun the job.
ADAF27	NAME is a required parameter
Explanation	The NAME parameter is missing from the Event Replicator Server definition being processed.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF28	DTYPE must be ADABAS, ETBROKER, FILE, MQSERIES, or NULL
Explanation	When specifying a DESTINATION parameter, there must be a DTYPE equal to ADABAS, ETBROKER, FILE, MQSERIES, or NULL.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF29	DAIFILE parameters only valid for DTYPE=ADABAS
Explanation	The parameter input has DAIFILE specified, and the DTYPE is not equal to ADABAS.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF2A	{Local Remote} ADA{vrm}/ARF{vrm} database {dbid} has connected Local database {dbid/nucid} has connected
Explanation	The nucleus has connected to the Event Replicator Server. The DBID or DBID-nucleus ID (<i>dbid/nucid</i>) combination as well as the Adabas and Event Replicator for Adabas versions (<i>ADAvrm/ARFvrm</i>) are shown in the message. In addition, the database is identified as a local or a remote database in the message.
Action	No action is required for this informational message.
ADAF2B	Database {dbid} has disconnected Database {dbid/nucid} has disconnected
Explanation	The nucleus has disconnected from the Event Replicator Server. The DBID or DBID-nucleus ID combination is shown in the message.
Action	No action is required for this informational message.
ADAF2C	{reptor-id} Handshake from Database {dbid/nucid} rejected due to RPLPARMS=NONE
Explanation	An Event Replicator Server (the ID is given in the message) has RPLPARMS set to NONE, which will reject any communication from other Adabas nuclei. The DBID or DBID-nucleus ID combination is shown in the message. This message is output only as an informational message in the Event Replicator Server syslog.
Action	If the Event Replicator Server should be communicating with other Adabas nuclei, correct the RPLPARMS parameter and recycle the Event Replicator Server. Otherwise, no action is required for this informational message.
ADAF2E	Disconnecting from database {dbid}
Explanation	The Event Replicator Server is in the process of disconnecting from the database or nucleus listed in the message. The first instance of this message occurs when the Event Replicator Server is disconnecting from a noncluster Adabas nucleus. The second instance of this message occurs when the Event Replicator Server is disconnecting from an Adabas cluster nucleus (for example, an Adabas Cluster Services or an Adabas Parallel Services nucleus). In this second instance, the Adabas cluster itself ensures that all nuclei in the cluster are informed about the Event Replicator Server disconnecting.
Action	No action is required for this informational message.

ADAF2F	Disconnected from database {dbid}
Explanation	<p>The Event Replicator Server has disconnected from the database or nucleus listed in the message.</p> <p>This message normally follows message ADAF2E and indicates that all replication data for the database has been processed when the Event Replicator Server was terminated by ADAEND. If the Event Replicator Server has been terminated via a HALT request, there is no guarantee that all data has been processed.</p> <p>The first instance of this message occurs when the Event Replicator Server has disconnected from a noncluster Adabas nucleus. The second instance of this message occurs when the Event Replicator Server has disconnected from an Adabas cluster nucleus (for example, an Adabas Cluster Services or an Adabas Parallel Services nucleus).</p>
Action	No action is required for this informational message.
ADAF2H	Discarding data in input queue for database {dbid}
Explanation	The Event Replicator Server is handling a full replication buffer by removing unprocessed data from the input queue to free storage
Action	Execution continues. The indicated database ID (<i>dbid</i>) will attempt to resend the discarded data. Increasing the value of the LRP_L parameter may alleviate the shortage.
ADAF2I	Database {dbid} not present
Explanation	The nucleus listed in the message is not currently active.
Action	Start the database.
ADAF2J	Database {dbid} objected to {count} invalid completion reports
Explanation	<p>An Adabas nucleus for the database identified in the message did not recognize some replicated transactions that the Event Replicator Server reported as successfully completed. The number of replicated transactions is also listed in the message.</p> <p>Generally, once the Event Replicator for Adabas has completed the successful processing of a replicated transaction, it reports the completion to Adabas so that Adabas can release the resources (space in its replication pool) associated with the transaction. In this case, Adabas could not identify the transactions specified by the Event Replicator for Adabas and ignored them.</p>
Action	Take note of any unusual events surrounding the message, keep the job protocols of Adabas database and the Event Replicator Server, and contact your Software AG technical support representative.

ADAF2K **Reptor could not inform destination {destination}**
about destination {deactivation | reactivation | refresh}
about subscription {subscription} {deactivation | reactivation | refresh}
about initialstate {isname} refresh
about DBID/File {dbid/file} {deactivation | activation}
about reptor termination

Explanation A resource was being deactivated, reactivated, or refreshed by the Event Replicator Server. The Event Replicator Server was unable to acquire sufficient resources to notify the affected destination.

Action Execution continues. This is often the result of a shortage in the replication pool. Increasing the value of the LRPL parameter may alleviate the shortage.

ADAF2L **Replication {deactivated | activated} for DBID/File {DBID/file}**
due to {reason}

Explanation The replication status for the identified file has changed on Event Replicator Server. The deactivation *reason* will be one of the following:

- database deactivation
- end of replay process
- file deactivation
- format buffer validation failure
- last destination deactivation
- last subscription deactivation
- not set up for ciphered source
- permanent error in subscription
- replication pool overflow
- request from Adabas (RDITYPE=Z)
- request from target application
- request via operator command/AOS
- RPLREFRESH request
- SLOG-related error
- SLOG system file full
- suspension of SLOG input

The reactivation *reason* will be one of the following:

- request from target application
- request via operator command/AOS
- request from Adabas (RDITYPE=Y)
- reactivation of destination
- reactivation of subscription

	<ul style="list-style-type: none"> ■ reactivation of database ■ begin of replay process
Action	<p>If the deactivation reason is "replication pool overflow", consider increasing the value of the LRPL parameter. For other reasons, this message is for information only.</p> <p>If the deactivation reason is "not set up for ciphered source", this indicates that the source file was found to be ciphered and that the Event Replicator could not obtain the cipher code required to process records from the security system. Evaluate previous messages for additional information.</p>
ADAF2M	Subscription {subscription} {deactivated reactivated} due to {reason}
Explanation	The replication status for the identified subscription has changed on the Event Replicator Server. See the <i>reason</i> descriptions described for message ADAF2L.
Action	If the deactivation reason is "replication pool overflow", consider increasing the value of the LRPL parameter. For other reasons this message is for information only.
ADAF2N	Destination {destination} {deactivated reactivated} due to {reason}
Explanation	The replication status for the identified destination has changed on the Event Replicator Server. See the <i>reason</i> descriptions described for message ADAF2L.
Action	If the deactivation reason is "replication pool overflow", consider increasing the value of the LRPL parameter. For other reasons this message is for information only.
ADAF2O	Replication activated for file {file} due to {reason}
Explanation	<p>Replication has been reactivated by the Adabas nucleus for the identified file. The <i>reason</i> will be one of the following:</p> <ul style="list-style-type: none"> ■ request from the Event Replicator Server ■ request via operator command/AOS ■ initial-state request
Action	No action is required. This message is for information only.

ADAF2P	Database {DBID} {deactivated reactivated} due to {reason}
Explanation	The replication status for the identified database has changed on the Event Replicator Server. See the <i>reason</i> descriptions described for message ADAF2L.
Action	If the deactivation reason is "replication pool overflow", consider increasing the value of the LRPL parameter. For other reasons, this message is for information only.
ADAF2Q	Database {dbid} terminated Database {dbid} nucleus {nucid} terminated with transactions in flight for the following files: File {file}
Explanation	The database has terminated, but the Event Replicator Server still has active transactions for the database. Execution continues.
Action	Check for the Event Replicator Server message ADAF1Q to verify that the Event Replicator Server successfully processes all replication data received from this database.
ADAF2R	Database {dbid} Database {dbid} Nucleus {nucid} Waiting for pending replication data to complete
Explanation	ADAEND has been issued to the Event Replicator Server with transactions still in progress.
Action	The Event Replicator Server will terminate only after all the transactions that are still in progress have completed.
ADAF2S	The following files in database {dbid} have replication turned on for this Reptor but are not referenced in a subscription: File {fn}
Explanation	The files listed in the message have replication turned on, but there are no matching subscriptions in the Event Replicator Server.
Action	Either add a subscription for the file in the Event Replicator Server or turn off replication for the files.
ADAF2T	Unexpected response code {rc} when reading Replicator file with command {cc}
Explanation	An error occurred while attempting to read the Replicator system file. The Event Replicator Server ID, response code (<i>rc</i>), and command code (<i>cc</i>) are given in the message.
Action	Review the response code to determine why the Replicator system file could not be read. Then take appropriate actions to correct the error. If the problem persists, contact your Software AG technical support representative for assistance.

ADAF2U	The following files in database {dbid} are defined in a subscription but do not have replication turned on for this Reptor: File {fn}...
Explanation	The files listed in the message have a subscription in the Event Replicator Server, but replication is not turned on for the files.
Action	Either turn replication on for the files or remove the subscriptions from the Event Replicator Server.
ADAF2V	Sending {deactivation reactivation} to database {DBID} failed with response code {rsp/subcode}
Explanation	A resource was being deactivated or reactivated. The Event Replicator Server attempted to notify the Adabas nucleus. The command received the unexpected response code and subcode.
Action	If the reason for the response code is not clear, contact your DBA, system support personnel, or Software AG technical support.
ADAF2W	Connect to database {dbid} failed with response code {rrr/sss}
Explanation	The Event Replicator Server attempted to connect to the database listed in the message, but received the response code and subcode (<i>rrr/sss</i>) listed in the message during the attempt.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF2X	Sending completion to {dbid} failed with response code {rrrr/ssss}
Explanation	An attempt to send information about completed transactions from the Event Replicator Server to the Adabas listed in the message (<i>dbid</i>) failed with the response code and subcode (<i>rrrr/ssss</i>) listed in the message.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF2Y	Disconnect failed with response {rrr/sss} from database {dbid}
Explanation	The Event Replicator Server attempted to disconnect from the database listed in the message, but received the response code and subcode (<i>rrr/sss</i>) listed in the message during the attempt.
Action	Investigate the response code and subcode to identify and correct the problem.

ADAF2Z	YYYY.MM.DD HH.MM.SS {event-name} must be between 0 and {n}
Explanation	An operator command to dynamically alter the level of transaction logging was entered incorrectly. This error is produced because the name of the transaction logging event or the transaction logging level specified in the command were not valid. The event name specified is listed in the message.
Action	Review and correct the command specifications and then rerun it. Valid transaction logging event names and levels are described in <i>TLOG Command</i> in <i>Event Replicator for Adabas Administration and Operations Guide</i> .
ADAF30	DTYPE=Adabas requires at least one DAIFILE
Explanation	The DAIFILE is required when DTYPE=ADABAS is specified.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF31	DAIDBID, DATDBID, and DATFILE are required for DAIFILE
Explanation	The DAIFILE parameter requires the DAIDBID, DATDBID, and DATFILE parameters be specified as well.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF32	DETBBROKERID or ETBBROKERID is required
Explanation	When specifying a DESTINATION, with DTYPE=ETBBROKER, then DETBBROKERID or ETBBROKERID is required.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF33	DMQQMGRNAME or MQQMGRNAME is required
Explanation	When specifying a DESTINATION, with DTYPE=MQSERIES, then DMQQMGRNAME or MQQMGRNAME is required.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF34	GFB is mandatory for GFORMAT
Explanation	When specifying a GFORMAT NAME, the GFB parameter is required.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF35	Invalid IQTYPE: must be ETBROKER or MQSERIES
Explanation	When specifying IQUEUE NAME, then IQTYPE must be ETBROKER or MQSERIES.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF36	IQMQQMGRNAME or MQQMGRNAME is required
Explanation	When specifying IQUEUE NAME, and IQTYPE=MQSERIES, then IQMQQMGRNAME or MQQMGRNAME is required.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF37	IQETBBROKERID or ETBBROKERID is required
Explanation	When specifying IQUEUE NAME, and IQTYPE=ETBROKER, then IQETBBROKERID or ETBBROKERID is required.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF38	Reptor must be UES enabled for: 'SACODE/SARC/SWCODE
Explanation	The Event Replicator Server is not running with UES option, and it is required for certain parameters, i.e., SARC.
Action	Examine and correct the parameter input or the Event Replicator Server.
ADAF39	SDESTINATION or SIDESTINATION is required
Explanation	When specifying SUBSCRIPTION, then SDESTINATION or SIDESTINATION is required.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF3A	The version of module ADARPD is incompatible with this Reptor
Explanation	A check was performed on the version of module ADARPD. The version of module ADARPD is incompatible with this Event Replicator Server.
Action	Ensure that all recent updates have been applied and that the load module versions in use are as delivered by Software AG. If the problem persists, contact your Software AG support representative for assistance.
ADAF3B	'parameter keyword' must be less than or equal to 65535
Explanation	The DBID value specified for the given 'parameter keyword' exceeds the maximum of 65535.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF3C	Invalid options specified for destination {dest} in subscription {sub}.
Explanation	The system file contains invalid data for destination <i>dest</i> in subscription <i>sub</i> . Only "Y" or "N" are permitted.
Action	Correct the input and restart the Event Replicator Server.
ADAF3D	FCOND must be EQ, NE, GT, LT, LE or GE
Explanation	The value entered for the FCOND parameter as part of a filter definition is incorrect. Valid values are listed in the message.
Action	Correct the FCOND parameter value.
ADAF3E	MU/PE must be in the range 1 – 191
Explanation	The value entered for either the MU or PE value of a filter definition is incorrect. Valid values must range from "1" through "191".
Action	Correct the MU or PE parameter value.
ADAF3F	{FSIMAGE FTIMAGE} must be AI or BI
Explanation	The value entered for either the FSIMAGE or FTIMAGE parameters of a filter definition are incorrect. Valid values are "AI" or "BI".
Action	Correct the FSIMAGE or FTIMAGE parameter value. Descriptions of these parameters are provided in <i>FILTER Settings in Event Replicator for Adabas Reference Guide</i> .
ADAF3G	FRECORDS - must be INCLUDE or EXCLUDE
Explanation	The value entered for the FRECORDS parameter of a filter definition is incorrect. Valid values are "INCLUDE" or "EXCLUDE".
Action	Correct the FRECORDS parameter value. A description of this parameters is provided in <i>FILTER Settings in Event Replicator for Adabas Reference Guide</i> .
ADAF3H	TLMAX and/or TLRESTART values are invalid and/or inconsistent
Explanation	The values specified for the TLMAX and TLRESTART parameters are either invalid or are not consistent with each other. Valid values for TLMAX range from 1 through 100, while the TLRESTART setting must be less than the TLMAX setting.
Action	Correct the TLMAX and TLRESTART parameter values so they are valid and consistent. Descriptions of these parameters are provided in <i>Transaction Log (TLOG) Settings in Event Replicator for Adabas Reference Guide</i> .

ADAF3I	{event-name} must be 0, 1, or n
Explanation	A parameter that sets the level of transaction logging for a transaction logging event was entered incorrectly. The name of the transaction logging event with the invalid value is listed in the message.
Action	Correct the value specified for the transaction logging event. Valid transaction logging event names and values are described in <i>Transaction Log (TLOG) Settings in Event Replicator for Adabas Reference Guide</i> .
ADAF3J	Parameter {FTIMAGE FTPE FTMU FTBEGIN FTLENGTH} may not be specified without FTARGET
Explanation	The FTIMAGE, FTPE, FTBEGIN, FTLENGTH, or FTMU parameter was specified without an associated FTARGET parameter in a filter definition.
Action	Provide an FTARGET parameter value. Descriptions of these parameters are provided in <i>FILTER Settings in Event Replicator for Adabas Reference Guide</i> .
ADAF3K	FILTER requires either FTARGET or FLIST
Explanation	A FILTER parameter was specified, but without either the FTARGET or FLIST parameters. Either FTARGET or FLIST is required, but both may not be specified.
Action	Provide either an FTARGET parameter value or an FLIST parameter value. Descriptions of these parameters are provided in <i>FILTER Settings in Event Replicator for Adabas Reference Guide</i> .
ADAF3L	FFIELD may only be specified as part of FILTER
Explanation	An attempt was made to specify the FFIELD parameter separately from a FILTER parameter. FFIELD parameters are not valid outside of FILTER parameters.
Action	Correct the syntax. Descriptions of these parameters are provided in <i>FILTER Settings in Event Replicator for Adabas Reference Guide</i> .
ADAF3M	A FILTER must specify at least one FFIELD
Explanation	A filter definition (FILTER parameter) was specified, but without at least one filter condition (FFIELD parameter).
Action	Add an FFIELD parameter to the filter definition. Descriptions of these parameters are provided in <i>FILTER Settings in Event Replicator for Adabas Reference Guide</i> .

ADAF3N	MAXFFIELDS must be a positive integer
Explanation	An incorrect value was specified for the MAXFFIELDS parameter. Valid values are positive integers.
Action	Correct the MAXFFIELDS parameter setting. Read MAXFFIELDS (<i>Maximum Number of FFIELDS</i>) Setting in <i>Event Replicator for Adabas Reference Guide</i> for more information.
ADAF3O	MAXFLISTSIZ must be in the range 1 - 32k bytes
Explanation	An incorrect value was specified for the MAXFLISTSIZ parameter. Valid values range from "1" through "32K".
Action	Correct the MAXFLISTSIZ parameter setting. Read MAXFLISTSIZ (<i>Maximum FLIST Size</i>) Setting in <i>Event Replicator for Adabas Reference Guide</i> for more information.
ADAF3P	SFFILTER {filter-name} not defined as a FILTER
Explanation	The transaction filter definition named in the message is specified to be used by an SFILE definition, but no filter definition exists by that name.
Action	Specify the name of a defined filter definition in SFFILTER parameter of the SFILE definition. SFILE definition parameters are described in <i>SUBSCRIPTION Settings</i> and filter definition parameters are described in <i>FILTER Settings</i> in <i>Event Replicator for Adabas Reference Guide</i> .
ADAF3Q	Subscription {subs-name} {event-name} must be 0, 1 or n
Explanation	The data in the Replicator system file indicates that the value associated with the event named in the message for the subscription named in the message is invalid. It must be in the range indicated. This error is caused by invalid data on the Replicator system file.
Action	Contact your Software AG technical support representative for assistance.
ADAF3R	Destination {dest-name} {event-name} must be 0, 1 or n
Explanation	The data in the Replicator system file indicates that the value associated with event named in the message for the destination named in the message is invalid. It must be in the range indicated. This error is caused by invalid data on the Replicator system file.
Action	Contact your Software AG technical support representative for assistance.

ADAF3S	DMQCCSID is valid only for a MQ Series destination when DCLASS(DEXIT) is non-blank
Explanation	The DMQCCSID destination parameter is specified for a WebSphere MQ destination definition and no DCLASS or DEXIT parameter has been specified for that destination.
Action	Either add a DCLASS or DEXIT parameter to the WebSphere MQ destination definition or change the DMQCCSID parameter setting to zero.
ADAF3T	SFREPLICATENOTCHANGED specified for subscription {subs-name}, DBID {dbid}, file {fn}, but BI and AI format buffers are not identical
Explanation	The keyword SFREPLICATENOTCHANGED was specified for the subscription, database, and file named in the message, but the BI and AI format buffers provided are not identical.
Action	Correct the definition so that the BI and AI format buffers are identical. SFILE definition parameters are described in <i>SUBSCRIPTION Settings</i> in <i>Event Replicator for Adabas Reference Guide</i> .
ADAF3U	Filter {filter-name} field name {field-name} Invalid value "{mmmm} "/X"{nnnnnnnn}" for keyword {word}
Explanation	Invalid data was found in the Replicator system file associated with the filter and field named in the message. This error is caused by invalid data in the Replicator system file.
Action	Contact your Software AG technical support representative for assistance.
ADAF3V	Multiple global settings records on the Replicator system file
Explanation	There are invalid multiple global setting records in the Replicator system file.
Action	Contact your Software AG technical support representative for assistance.
ADAF3W	{DRETRYINTERVAL DRETRYCOUNT} is only valid for an Adabas, ETBROKER, or MQSeries destination
Explanation	An attempt was made to specify a retry interval or retry count in a File or Null destination. The DRETRYINTERVAL and DRETRYCOUNT parameters are only valid Adabas, webMethods EntireX, or WebSphere MQ destination definitions.
Action	Remove the DRETRYINTERVAL or DRETRYCOUNT parameters from the File or Null destination definitions.

ADAF3X

message text

Explanation

One of two basic message texts may appear for this message ID:

Message Text	Explanation	Action
<i>RETRYINTERVAL DRETRYINTERVAL IQRETRYINTERVAL</i> must be zero or in the range 5 <= n <= 2,147,483,647	The value of the <i>RETRYINTERVAL</i> , <i>DRETRYINTERVAL</i> , or <i>IQRETRYINTERVAL</i> setting is not valid. It must be zero (0) or an integer ranging from 5 through 2,147,483,647.	Correct the value of the <i>RETRYINTERVAL</i> , <i>DRETRYINTERVAL</i> , or <i>IQRETRYINTERVAL</i> parameter. For complete information on these parameters, read <i>Event Replicator Initialization Parameters</i> , in <i>Event Replicator for Adabas Reference Guide</i> .
<i>DRETRYINTERVAL IQRETRYINTERVAL</i> is <i>value</i>	The value of the <i>DRETRYINTERVAL</i> or <i>IQRETRYINTERVAL</i> parameter is given in the message (<i>value</i>).	No action is required for this informational message.

Action

See the table above for the appropriate action to take, based on the message text that appears with this message ID.

ADAF3Y

message text

Explanation

One of two basic message texts may appear for this message ID:

Message Text	Explanation	Action
<i>RETRYCOUNT DRETRYCOUNT IQRETRYCOUNT</i> must be numeric and <= 2,147,483,647	The value of the <i>RETRYCOUNT</i> , <i>DRETRYCOUNT</i> , or <i>IQRETRYCOUNT</i> setting is not valid. It must be an integer ranging from 0 through 2,147,483,647.	Correct the value of the <i>RETRYCOUNT</i> , <i>DRETRYCOUNT</i> , or <i>IQRETRYCOUNT</i> parameter. For complete information on these parameters, read <i>Event</i>

Message Text	Explanation	Action
		<i>Replicator Initialization Parameters, in Event Replicator for Adabas Reference Guide.</i>
<i>DRETRYCOUNT IQRETRYCOUNT is value</i>	The value of the DRETRYCOUNT or IQRETRYCOUNT parameter is given in the message (<i>value</i>).	No action is required for this informational message.

Action See the table above for the appropriate action to take, based on the message text that appears with this message ID.

ADAF3Z **YYYY.MM.DD HH.MM.SS {resource} {name} not found**

Explanation An operator command to dynamically alter the level of transaction logging was entered incorrectly. This error is produced because a resource name specified in the command was not valid. The invalid resource type (*resource*) and its name (*name*) are given in the message.

Action Review and correct the command specifications and then rerun it. Valid transaction logging event names and levels are described in *TLOG Command* in *Event Replicator for Adabas Administration and Operations Guide*.

ADAF40 **SUBSCRIPTION requires either SFDBID or DBID**

Explanation When specifying SUBSCRIPTION, then sub-parameters SFDBID or DBID are required.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF41 **SUBSCRIPTION requires at least one SFILE**

Explanation When specifying SUBSCRIPTION, then at least one sub-parameters SFILE is required.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF42 **Subscription {sname} dbid {id} file {num} SFBAI and SGFORMATAI are mutually exclusive**

Explanation When specifying SUBSCRIPTION, then sub-parameters SFBAI and SGFORMATAI are mutually exclusive. The subscription name, DBID, and file number are given in the message.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF43 **Subscription {sname} dbid {id} file {num} SFBBI and SGFORMATBI are mutually exclusive**

Explanation When specifying SUBSCRIPTION, then sub-parameters SFBBI and SGFORMATBI are mutually exclusive. The subscription name, DBID, and file number are given in the message.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF44 **Subscription {sname} dbid {id} file {num} SFBKEY and SGFORMATKEY are mutually exclusive**

Explanation When specifying SUBSCRIPTION, then sub-parameters SFBKEY and SGFORMATKEY are mutually exclusive. The subscription name, DBID, and file number are given in the message.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF45 **SUBTASKS exceeds maximum of 15**

Explanation When specifying SUBTASKS, the maximum value is 15.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF46 **Parameter not allowed: 'parameter keyword'**

Explanation When specifying a parameter, a keyword has been improperly specified and is invalid.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF47 **Subscription {sname} dbid {id} file {num} requires SFBAI or SGFORMATAI**

Explanation When specifying SUBSCRIPTION, then sub-parameters SFBAI or SGFORMATAI are required. The subscription name, DBID, and file number are given in the message.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF48 **Only YES, NO, or blank are valid for: '{parameter keyword}'**

Explanation The parameter keyword listed in the message only supports YES, NO, or blank, and the input is not matching that.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF49	SFILE parameters only valid for SUBSCRIPTION
Explanation	The parameter SFILE is positioned incorrectly, and not associated with a SUBSCRIPTION.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF4A	{dbid} Recovering replication data
Explanation	While performing the session autorestart procedure to recover from the abnormal end of an Adabas nucleus, Adabas found replication data on its Work data set. Adabas is now going to try to recover any replication data that may need to be sent or resent to the Event Replicator Server(s). This message and action occurs only if the ADARUN parameter REPLICATION=YES was specified for both the Adabas nucleus that failed and the nucleus that is performing the session autorestart.
	Note that replication data from initial-state processes that were active at the time of the failure is not recovered automatically.
Action	If initial-state processes were active at the time of the failure, check whether any of them need to be rerun. If so, restart them.
ADAF4B	{dbid} Recovery statistics for Reptor {rptid} {dbid} Replicated transactions recovered = {count1} {dbid} Immediately confirmed by Reptor = {count2} {dbid} Already fully received by Reptor = {count3} {dbid} To be sent (or resent) to Reptor = {count4}
Explanation	During session autorestart, Adabas recovered replication data from the Work data set. After connecting to the Event Replicator Server, Adabas reports: <ul style="list-style-type: none"> ■ how many replicated transactions were recovered that had not been confirmed as successfully processed by the Event Replicator Server before the abnormal end of the previous Adabas session (<i>count1</i>), ■ how many of those transactions were confirmed by the Event Replicator Server when Adabas reconnected after the session autorestart (<i>count2</i>), ■ how many of those transactions the Event Replicator Server fully received from the previous session (<i>count3</i>), and ■ how many recovered transactions Adabas is going to send (or resend) to the Event Replicator Server (<i>count4</i>). <p>If files in the database are replicated via multiple Event Replicator Servers, Adabas prints one set of these messages for each Event Replicator Server.</p>
Action	No action is necessary for this informational message.

ADAF4C	{dbid} Replication data overwritten on Work {dbid} Reptor ID = {rptid} {dbid} Affected files = {fnr-list}
Explanation	<p>During session autorestart, Adabas detected that one or more Event Replicator Servers had not confirmed the complete processing of one or more older transactions that had already been overwritten on the Work data set in the previous session. It reports which Event Replicator Servers and which replicated files are involved.</p> <p>Note: This message is the forerunner of the report of the possible loss of replication data. It indicates that Adabas is unable to recover this replication data because it was already overwritten on the Work data set. However, if the Event Replicator Servers remained active across the outage of Adabas, there is a good chance that the replication data in question is still held or has already been successfully processed by the Event Replicator Servers.</p>
Action	<p><i>Do not</i> take action to recover from the loss of replication data based on this message alone. The final outcome is reported subsequently in messages ADAF4D or ADAF4E.</p> <p>If there was no backup of replication data being processed by the Event Replicator Servers at the time of the Adabas failure, consider increasing the value of the ADARUN LP parameter, so that replication data can be held longer on the Work data set.</p>
ADAF4D	{dbid} *** Replication data probably lost *** {dbid} Reptor ID = {rptid} {dbid} Affected files = {fnr-list} {dbid} From time... {timestamp1} {dbid} To time..... {timestamp2}
Explanation	<p>Replication data that was overwritten on the Work data set, as reported in an earlier ADAF4C message, has not been processed by the Event Replicator Server nor is it still available on the Event Replicator Server side. Adabas and the Event Replicator Server are unable to recover this replication data.</p> <p>The message indicates which Event Replicator Server and files may be affected, as well as the time period of the missing replication data.</p> <p>If files in the database are replicated via multiple Event Replicator Servers, Adabas prints one set of these messages for each Event Replicator Server that is implicated in the probable loss of replication data.</p>
Action	<p>Take actions to bring the original data and its replicas back in sync. The extent to which this is necessary depends on the requirements of the application using the replication system.</p>

ADAF4E	{dbid} Replication data recovered; not lost {dbid} Reptor ID = {rptid} {dbid} Affected files = {fnr-list}
Explanation	Replication data that was overwritten on the Work data set, as reported in an earlier ADAF4C message, was still available on the Event Replicator Server side and has been successfully processed by the Event Replicator Server. If the database contains files being replicated via multiple Event Replicator Servers, Adabas prints one set of these messages for each Event Replicator Server that is not implicated in the loss of replication data.
Action	No action is required for this informational message. The original data and its replicas are in sync even though not all of the replication data could be recovered from the Work data set.
ADAF4F	{dbid} No replication data to be recovered
Explanation	During session autorestart, Adabas found that all replicated transactions from the previous session had already been successfully processed by the Event Replicator Server before the previous session terminated abnormally. There was no replication data that needed to be recovered.
Action	No action required for this informational message. The original data and its replicas are in sync.
ADAF4G	TLOG suspended due to TLMAX exceeded
Explanation	TLOG logging processing has used more of the replication pool than the percentage assigned it by the TLMAX.
Action	Determine why TLOG activity is exceeding replication pool limits. Consider adjusting the size of the replication pool or adjusting the TLMAX, as appropriate.
ADAF4H	TLOGing resumed as RPL usage below TLRESTART value
Explanation	TLOG records have been removed from the replication pool because the replication pool percentage defined by the TLMAX was exceeded. TLOG usage has now fallen below the percentage specified in the TLRESTART and so TLOG processing has resumed.
Action	No action is required for this informational message.
ADAF4I	{number} TLOG records discarded
Explanation	TLOG records have been deleted from the replication pool, due to a replication pool full condition. The number of records that have been deleted is given in the message.
Action	No action is required for this informational message.

ADAF4K	ADARPL for DBID {dbid} connected, token {number}
Explanation	An instance of the ADARPL utility has established a session with the Event Replicator Server for the database identified in the message. The token number it has been assigned is also listed in the message and can be used to track the session.
Action	No action is required for this informational message.
ADAF4L	ADARPL for DBID {dbid} disconnected, token {number} Total number of transactions processed: {nnnnnnnnnn}
Explanation	An instance of the ADARPL utility has terminated its session with the Event Replicator Server for the database identified in the message. The token number listed in the message identifies the terminating session. The total number of transactions processed by the ADARPL utility is also given in the message.
Action	No action is required for this informational message.
ADAF4M	{dbid} count record images suppressed for file {fnr}
Explanation	After an Adabas failure and session autorestart, replication data was recovered for which a matching FDT was no longer available. The FDT had been changed or deleted by a utility operation. Adabas suppressed the record images of the replicated records, because without a matching FDT, the Event Replicator Server could not process them. This message displays how many record images were suppressed for which files. For each suppressed record image, the Event Replicator Server delivers the replicated record with response code 131 (ADARSP131), subcode 60 in fields URBRSP and URBRSUBC of the URBR. Unless these images had already been delivered earlier to the target application, they are lost.
Action	Use application-specific means to determine whether updates to replicated records have been lost and to get the related original data and their replicas back in sync.
ADAF4N	RPLCLEANUP unable to find any active Tokens Requested Token for RPLCLEANUP was not found
Explanation	One of the following occurred: <ul style="list-style-type: none"> ■ An RPLCLEANUP=ALL operator command was entered, but there were no ADARPL replay operations in progress. ■ An RPLCLEANUP=token operator command was entered, but there was no ADARPL replay operation in progress with the specified token.
Action	Supply a token for a replay operation that is in progress or start some ADARPL replay operations. The operator command DRPLSTAT can be used to identify active ADARPL replay tokens.

ADAF4O	RPLREFRESH requested, but refresh is already active.
Explanation	A new RPLREFRESH request has been issued but a previous RPLREFRESH command is still being processed.
Action	Wait for the previous RPLREFRESH command to be processed and reenter the command.
ADAF4P	RPLREFRESH ,ABORT requested, refresh not active
Explanation	A RPLREFRESH,ABORT command has been issued but no refresh is in progress.
Action	No action is required for this informational message.
ADAF4Q	ABORT request has been scheduled ABORT is already scheduled
Explanation	An RPLREFRESH,ABORT command has been issued and has been either accepted or rejected (when another RPLREFRESH,ABORT is already scheduled).
Action	No action is required for this informational message.
ADAF4R	Replication data received for unknown subscription {sname} from Reptor {dbid} on input queue {iqueue}
Explanation	A replicated transaction was received from an Event Replicator Server instance <i>dbid</i> for subscription <i>sub</i> on input queue <i>iqueue</i> , but no subscription definition was found. When unsolicited replication data is received on an input queue, the Event Replicator Server closes the input queue for further processing and message ADAF8G is produced.
Action	Add appropriate subscription, SFILE, and, if necessary, destination definitions to specify how the replication data should be processed. When appropriate definitions have been specified, try again.
ADAF4S	Message received with unexpected sequence number on input queue {iqueue}, from Reptor {dbid} Expected: {value1} Received: {value2}
Explanation	An out-of-sequence replicated transaction was received on the input queue <i>iqueue</i> . When this error occurs, the Event Replicator Server closes the input queue for further processing. Message ADAF8G will follow this message to indicate this action.
Action	The exact cause of the error should be determined and appropriate actions should be taken before you try again. Once you have resolved the problem, resume replication processing on the input queue by restarting the Event Replicator Server session from the failing point, using an initial-state definition if required.

ADAF4T	Input Queue: {iqueue} Truncated message received
Explanation	A truncated replicated transaction was received on the input queue <i>iqueue</i> . When this error occurs, the Event Replicator Server closes the input queue for further processing. Message ADAF8G will follow this message to indicate this action
Action	Either the IQBUFLLEN parameter on the local Event Replicator Server node or the MAXOUTPUTSIZE parameter on the remote Event Replicator Server node needs to be increased and replication processing restarted.
ADAF4U	Closing input queue {qname} due to replication pool overflow
Explanation	When a request to allocate memory on behalf of an input queue fails because the replication pool is full, the input queue will be closed. The message indicates which input queue has been closed as a result of the over flow. If the replication pool has been allocated with a large enough size, problems like this can happen if there is data backing up in the Event Replicator Server address space.
Action	Investigate why the replication pool has filled up and take appropriate action to avoid this happening into the future.
ADAF4V	Closing input queue {qname} due to unexpected input data - {bad-input-data}
Explanation	Unexpected or bad data was received on an input queue so the input queue is closed as the Event Replicator Server is not in a position to deal with the data. The <i>bad-input-data</i> listed in the message can be any of the following: <ul style="list-style-type: none">■ URBCLEN is invalid■ No prior transaction for URBC■ URBCSNAM is invalid■ URBCTSNR is invalid■ URBCRSNR is invalid■ URBCDSNR is invalid■ URBT/partial previous trans.■ Insufficient buffer for URBT■ URBTLEN is invalid■ Insufficient buffer for URB*■ Eye-catcher not URBD/URBE/URBR■ Insufficient buffer for URBE■ URBELEN is invalid■ Insufficient buffer after URBE■ URBE not followed by URBT■ Insufficient buffer for URBD■ URBDLENH is invalid

- Insufficient buffer for image
- No record for URBD
- URBDTYP is invalid
- Before image already received
- After image already received
- Insufficient buffer for URBR
- URBRLEN is invalid
- URBR TYP is invalid

To review the Event Replicator for Adabas DSECTs and the definitions of the DSECT fields listed in the *bad-input-data* above, read *Event Replicator for Adabas Programmer's Reference*, in *Event Replicator for Adabas Application Programmer's Reference Guide*.

This message is normally the result of a payload being received on an input queue that is not from another Event Replicator Server. It may be another application sending spurious data to a queue which is then picked up by the Event Replicator Server.

Action

To determine what the payload looks like, turn on transaction logging (TLOGing) for "request received" processing using the TLREQRECV system parameter. This will cause the message text to be written to the TLOG. The TLOG information can subsequently be printed using the ADARPP utility. Use the message contents to determine where the spurious data originated. If not, use webMethods EntireX tracing or WebSphere MQ facilities to determine what application is sending these messages to the Event Replicator Server.

For more information about activating transaction logging for the Event Replicator Server, read *TLREQRECV Parameter*, in *Event Replicator for Adabas Reference Guide*. For information about the ADARPP utility, read *ADARPP Utility: Print TLOG Records*, in *Event Replicator for Adabas Reference Guide*.

ADAF4W **A failure occurred while notifying the file activation driver nucleus ID {nucid} File {num} may not have been fully reactivated**

Explanation A cluster peer nucleus encountered an error when it attempted to notify the driver nucleus of an "activate file" request.

Action Reissue the file activation request.

ADAF4Z **Unexpected response code {rsp}/ {subcode} from Reptor {dbid}**

Explanation A V1 command to the Event Replicator Server identified in the message (*dbid*) returned the response code (*rsp*) and subcode (*subcode*) given in the message.

Action Investigate the response code and subcode to identify and correct the problem.

ADAF50 **GFORMAT NAME must be seven bytes or less**
Explanation The parameter GFORMAT NAME=*ggggggg* exceeds a 7 byte length restriction.
Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF51 **Destination definition not found for
Destination {dest-name} in Subscription {subs-name}**
Explanation When specifying additional parameter input for the subscription named in the message, a destination is referenced which has not been defined in the Replicator system file or in a DESTINATION initialization parameter.
Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF52 **For Subscription {sssssss}
Global format {ggggggg} not found in Global format definitions**
Explanation When specifying additional parameter input for SUBSCRIPTION NAME=*sssssss*, a global format is referenced which does not have a corresponding GFORMAT NAME=*ggggggg* parameter.
Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF53 **Subscription {sssssss} dbid {dddd} file {ffff} has a filter
format buffer specified without a filter definition**
Explanation A filter format buffer is defined at the subscription file level when no filter is defined for that subscription file. The subscription name, database ID, and file number are given in the message.
Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF54 **message-text**
Explanation This message number is associated with several possible message texts. The following table describes all of the possibilities.

Message Text	Description
Replication error: Adabas destination <i>dest-id</i> Source DBID <i>src-dbid</i> FNR <i>src-fn</i> , Target DBID <i>trg-dbid</i> FNK <i>trg-fn</i>	This message text is issued once to the console when replication to an Adabas destination fails because the status of the target file is not as expected. This message is written to both the console and DDPRINT. However, it is written only once to the console for each destination in error.
<i>yyyy.mm.dd hh.mm.ss</i> Replication error: Adabas destination <i>dest-id</i>	This message text is issued to DDPRINT every time replication to an Adabas destination fails because

Message Text	Description
Source DBID <i>src-dbid</i> FNR <i>src-fn</i> , Target DBID <i>trg-dbid</i> FNK <i>trg-fn</i>	the status of the target file is not as expected. ADAF54 messages with this message text are only written to DDPRINT; they are not written to the console.
Key: <i>dump</i>	If the DATMETHOD parameter of an Adabas destination definition is specified as KEY, this message is used to print the hexadecimal and EBCDIC dump of the key, with the offset in hexadecimal. ADAF54 messages with this message text are only written to DDPRINT; they are not written to the console.

Action See accompanying messages in DDPRINT for more information.

ADAF55 **Subscription {subname} database {dbid} file {nn}
{after|before} image uses global format buffer {gfb}**
**This global format buffer is also used
elsewhere for a key image**

Explanation When specifying additional parameter input for the subscription (*subname*), database (*dbid*), and file (*nn*) listed in the message, a global format buffer (*gfb*) is referenced in which the format buffer is for KEY, and is incorrect.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF57 **For Subscription {subname} database {dbid} file {nn}
key image uses global format buffer {gfb}**
**This global format buffer is also used
elsewhere for a DS image**

Explanation When specifying additional parameter input for the subscription (*subname*), database (*dbid*), and file (*nn*) listed in the message, a global format buffer (*gfb*) is referenced in which the format buffer is not for KEY, and is incorrect.

Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF58 **Loading exit {eeeeeeee} failed;
IOR response code {rc} Reason code {code}**

Explanation A load was issued for the exit program named in parameter SFSEXIT=*eeeeeeee*, and it was unsuccessful.

Action Investigate the cause of the error; correct it and restart the Event Replicator Server.

ADAF59	Adabas destination {dest-name} is specified in more than one subscription
Explanation	An Adabas destination is used by more than one subscription. Only one subscription may send data to an Adabas destination.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF5A	A request sent to Adabas to {activate deactivate} DBID/File {dbid/file} failed:
Explanation	<p>The Event Replicator Server requested the database listed in the message activate or deactivate the file listed in the message. This request failed due to one of the following reasons:</p> <ul style="list-style-type: none">■ The file is an invalid file.■ The file has not been defined for replication■ The file has not been defined for replication for this Event Replicator Server <p>The response code and subcode (<i>rrrrr / sssss</i>) are given in the message.</p>
Action	Check if the file is correctly defined for replication to this Event Replicator Server. If "invalid file" is indicated, check if the Event Replicator Server subscription references a file number beyond MAXFILES for the database. If a response code is given, investigate the response code and subcode to identify and correct the problem.
ADAF5H	Reptor {rpid} has successfully processed all replicated transactions from this Adabas nucleus that ended before
Explanation	The Event Replicator Server successfully processed all replicated transactions.
Action	No action is necessary for this informational message.
ADAF5P	The Reptor has no information about transactions from database {dbid} for [file {fnr} subscription {sname} destination {dname} replay process {token}]
Explanation	Following an event that may cause the loss of replication data (for example, the deactivation of a destination), this message indicates that the Event Replicator Server has been unable to track which replicated transactions were processed successfully before the event. This may happen, for example, if the Event Replicator Server has not had contact with Adabas between the start of the Event Replicator Server and the mentioned event.
Action	If replication data was lost due to the event for which this message was issued, replay the records from the PLOG data sets. During replay processing, be careful to specify a FROMDATE and FROMTIME that covers all replicated transactions that were lost.

ADAF5Q	All transactions from database {dbid} that ended before {date time} have been processed for [file {fnr} subscription {sname} destination {dname}] replay process {token}]
Explanation	Following an event that may cause the loss of replication data (for example, the deactivation of a destination), this message reports the latest known time for which replicated data was processed successfully; in other words any replicated transaction that ended before this time was <i>not</i> lost due to this event. There may or may not be replicated transactions that ended at or after this time which have been lost.
Action	If replication data was lost due to the event for which this message was issued and the lost data is to be replayed from the PLOG data sets, you could use the date and time listed in this message for the FROMDATE and FROMTIME of the replay process.
ADAF5R	Replay process started, token {ttttt}
Explanation	A replay process was started with the token shown in the message.
Action	No action is required for this informational message.
ADAF5S	{dbid} Replay process ended successfully
Explanation	The replay process referred to in the preceding ADAF4L message ended successfully. The Event Replicator Server returns response code 0 (ADARSP000) to the disconnecting ADARPL.
Action	No action is required for this informational message.
ADAF5T	Transactions from Adabas could not be held during replay
Explanation	While the replay process referred to in the previous ADAF4L message was running (in synchronized mode), Adabas sent more replication data than the Event Replicator Server was able to hold in its replication pool until the replay process is finished. The Event Replicator Server dropped the new replication data from Adabas and the replay process (ADARPL) proceeded (in replay-only mode).
Action	Run a new replay process for the same subscriptions and destinations to replay the lost replication data that Adabas produced during the first replay process.
ADAF5U	Replay process ended with response code {rrr}, subcode {sss}
Explanation	The replay process referred to in the preceding ADAF4L message has encountered an error. The response code and subcode shown in the message is returned by the Event Replicator Server to ADARPL.
Action	Investigate the cause of the error, correct it, and run a new replay job.

ADAF5V	Starting de-logging of held transactions from Adabas Replay token = {tttt}
Explanation	When the replay process (in synchronized mode) whose token is shown in the message ended, the Event Replicator Server started delogging and processing the replication data that was sent by Adabas but suspended by the Event Replicator Server while the replay process was running.
Action	No action is required for this informational message.
ADAF5W	De-logging of held transactions from Adabas completed Replay token = {tttt}
Explanation	The Event Replicator Server completed delogging and processing the transactions from the Event Replicator Server that it had suspended while a synchronized replay completed. The token for the completed replay process is listed in the message.
Action	No action is required for this informational message.
ADAF5X	Waiting for the completion of update transactions, referencing file {fnr}
Explanation	This informational message indicates that processing is waiting for the completion of all updates to the file referenced in the message.
Action	No action is required for this informational message.
ADAF5Y	All update transactions active at the time file {fnr} was activated, have completed - Notifying nucleus {nucid}
Explanation	All update transactions active have completed successfully when the file referenced in the message was activated.
Action	No action is required for this informational message.
ADAF5Z	Building pseudo transaction to inform Reptor {rpid} that file {fnr} has been activated
Explanation	This is an internal message that occurs as a result of activating the file named in the message.
Action	No action is required for this informational message.
ADAF60	At least one ISUBSCRIPTION, IDESTINATION or IFILE is required for INITIALSTATE {name}
Explanation	The initial-state definition named in the message has no associated subscriptions, destinations or files.
Action	Correct the initial-state definition and restart the Event Replicator Server.

ADAF61	DAIFILE f{####, }DAIDBID d{#### }in Destination {dddddddd} does not have a matching DBID/FILE in Subscription {sssssss}
Explanation	For DESTINATION NAME=dddddddd, the specified DAIFILE=f#### and DAIDBID=d#### parameters do not have a corresponding SFILE and SFDBID combination in the specified DASUBSCRIPTION=sssssss.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF62	FILTER {name} {filter-name} is not unique
Explanation	An attempt was made to define a filter with the name specified in the message more than once. The specified name is not unique.
Action	Change one of the duplicate filter definition names to a different, unique, name.
ADAF63	Delete failure for Exit {eeeeeeee}
Explanation	When a non-zero return code occurs in the execution of ADARPD, then any exits loaded during this execution will be deleted. There was a failure in deleting the exit program eeeeeeee.
Action	Investigate the cause of the error; correct it and restart the Event Replicator Server.
ADAF64	Invalid Resendbuffer Name {name}
Explanation	The resend buffer definition name shown in the message is not valid. The name must: <ul style="list-style-type: none"> ■ Be comprised of one to eight uppercase, alphanumeric, and national characters (@,\$,#). If the name is less than eight characters, it is automatically padded on the right with blanks. ■ Be enclosed in single quotes (') if any national characters are used. ■ Not begin with a numeric character or a blank. ■ Have no embedded blanks. ■ Not begin with the letters "SYS".
Action	Correct the name and try again.
ADAF65	GFORMAT name {ggggggg} is not unique
Explanation	Duplicate names for global format definitions have been found.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF66	IQueue name {name} is not unique
Explanation	There have been duplicate IQUEUE NAME= <i>name</i> statements found.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF67	Destination name {dddddddd} is not unique
Explanation	There have been duplicate DESTINATION NAME=dddddddd found.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF68	Input DBID d{####, }FILE f{#### }not unique in Adabas Destination {dddddddd}
Explanation	In DESTINATION NAME=dddddddd, there are duplicate DAIFILE=f#### and DAIDBID=d#### found..
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF69	Subscription name {sssssss} is not unique
Explanation	There have been duplicate SUBSCRIPTION NAME=sssssss found.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF6A	ResendBuffer {resendbuffer-name} not found for Subscription {subscription-name}
Explanation	The resend buffer name specified in the SRESENDBUFFER parameter has not been defined.
Action	Either correct the SRESENDBUFFER parameter specification or create a corresponding RESENDBUFFER definition for the resend buffer. Then restart the Event Replicator Server.
ADAF6B	Input Queue {queue} has invalid data
Explanation	An error occurred when reading the Replicator system file for the input queue named in the message.
Action	The Adabas Event Replicator Subsystem can be used to delete and correct the information. If necessary, notify support with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.
ADAF6C	Destination {dest} has invalid data in a subsequent record
Explanation	An error occurred when reading the Replicator system file for the Adabas destination named in the message.
Action	The Adabas Event Replicator Subsystem can be used to delete and correct the information. If necessary, notify support with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.

ADAF6D	Destination {dest} has invalid data
Explanation	An error occurred when reading the Replicator system file for the destination named in the message.
Action	The Adabas Event Replicator Subsystem can be used to delete and correct the information. If necessary, notify support with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.
ADAF6E	Initial state {is-name} has invalid sequence data
Explanation	An error occurred when reading the Replicator system file for the initial-state definition named in the message.
Action	The Adabas Event Replicator Subsystem can be used to delete and correct the information. If necessary, notify support with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.
ADAF6F	Subscription {subscription} has an invalid {fmtbuffertype}
Explanation	An error occurred when reading the Replicator system file for the subscription named in the message. The format buffer for this subscription had an incorrect length. The format buffer item is substituted in the message for <i>fmtbuffertype</i> . Possible values are: <ul style="list-style-type: none">■ format buffer before image■ format buffer after image■ format buffer key
Action	The Adabas Event Replicator Subsystem can be used to delete and correct the information. If necessary, notify support with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.
ADAF6G	Subscription {subscription} has invalid data (subtype n)
Explanation	An error occurred when reading the Replicator system file for the subscription named in the message. An internal structure was found to be invalid.
Action	The Adabas Event Replicator Subsystem can be used to delete and correct the information. If necessary, notify support with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.

ADAF6H	Initial State {is-name} has an invalid length for the selection criteria
Explanation	An error occurred when reading the Replicator system file for the initial-state definition named in the message. The selection criteria has an invalid length.
Action	The Adabas Event Replicator Subsystem can be used to delete and correct the information. If necessary, notify support with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.
ADAF6I	Global Format {name} has an invalid length
Explanation	An error occurred when reading the Replicator system file for the global format definition named in the message. The global format buffer has not been correctly generated.
Action	Regenerate the global format buffer using the Adabas Event Replicator Subsystem. If the problem persists, contact your Software AG customer support representative with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.
ADAF6J	Subscription {subscription} has invalid data
Explanation	An error occurred when reading the Replicator system file for the subscription named in the message
Action	The Adabas Event Replicator Subsystem can be used to delete and correct the information. If necessary, notify support with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.
ADAF6L	ADARUN RPLPARMS={parm} is specified but the Replicator file does not exist
Explanation	An Event Replicator Server has ADARUN RPLPARMS=FILE or ADARUN RPLPARMS=BOTH specified but the Replicator file does not exist.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF6M	DACTIVE must be YES or NO
Explanation	The value of the DACTIVE subparameter must be either "YES" or "NO". DACTIVE is a parameter of the DESTINATION initialization parameter.
Action	Check the parameter input, supply a valid value, and restart the Event Replicator Server.

ADAF6N	SACTIVE must be YES or NO
Explanation	The value of the SACTIVE subparameter must be either "YES" or "NO". SACTIVE is a parameter of the SUBSCRIPTION initialization parameter.
Action	Check the parameter input, supply a valid value, and restart the Event Replicator Server.
ADAF6O	Valid range for IRMSGLIMIT is 3 to 2,147,483,647
Explanation	The value of the IRMSGLIMIT initialization parameter must be between 3 and 2,147,483,647.
Action	Check the parameter input, supply a valid value, and restart the Event Replicator Server.
ADAF6P	Valid range for IRMSGINTERVAL is 1 to 2,147,483,647
Explanation	Valid values for the IRMSGINTERVAL parameter must be between 1 and 2,147,483,647.
Action	Check the parameter input; supply a correct value, and restart the Event Replicator Server.
ADAF6Q	SINCREMENTIS must be YES or NO
Explanation	Valid values for the SINCREMENTIS parameter are "YES" or "NO".
Action	Check the parameter input; supply a correct value, and restart the Event Replicator Server.
ADAF6R	Valid range for IMAXREQ is 1 to 2,147,483,647
Explanation	Valid values for the IMAXREQ parameter must be between 1 and 2,147,483,647
Action	Check the parameter input; supply a correct value, and restart the Event Replicator Server.
ADAF6S	DLOG must be YES or NO
Explanation	An invalid value was specified for the DLOG subparameter of the DESTINATION NAME parameter. Valid values are "YES" or "NO".
Action	Check the parameter input; supply a correct value, and restart the Event Replicator Server.

ADAF6T	VERIFYMODE must be {YES Y} or {NO N}
Explanation	An invalid value was specified for the VERIFYMODE parameter in the DDKARTE statements of the Event Replicator Server startup job or for the Verify Mode global value setting in the Replicator system file. Valid values for the VERIFYMODE parameter are YES or NO, with a default of NO. Valid values for the Verify Mode global value setting are Y or N, with a default of N.
Action	Correct the VERIFYMODE parameter setting or the Verify Mode global value setting, as appropriate for your Event Replicator for Adabas implementation, and try again.
ADAF6U	FBVALIDATION must be NONE, WARN, DEAC, or ABORT Format buffer validation must be N for NONE, W for WARN, D for DEAC, or A for ABORT
Explanation	An invalid value has been specified for the FBVALIDATION parameter or in the Format Buffer Validation field.
Action	Correct the input value and restart the Event Replicator Server.
ADAF6V	DATABASE DBCONNECT parameter must be YES or NO
Explanation	An invalid value was specified for the DBCONNECT parameter.
Action	Specify either "YES" or "NO" as a value for the DBCONNECT parameter or allow DBCONNECT to take the default value of "YES".
ADAF6W	DATABASE requires both DBCONNECT and ID parameters
Explanation	You must specify values for both the DATABASE DBCONNECT and ID parameters.
Action	Correct the input values and restart the Event Replicator Server.
ADAF6X	Duplicate entry for database {dbid} invalid
Explanation	Database <i>dbid</i> has been specified more than once either in the DDKARTE input or via one of the online applications in the Replicator system file.
Action	Remove all but one of the definitions for the database and restart the Event Replicator Server.
ADAF6Y	Global Format {gfb} {error}
Explanation	An error occurred when reading the Replicator system file for the global format buffer definition named in the message (<i>gfb</i>). The global format buffer has not been correctly generated. Possible errors (<i>error</i>) listed in the message are: <ul style="list-style-type: none"> ■ has invalid subtype ■ has invalid header

	<ul style="list-style-type: none"> ■ invalid field type ■ FT buffer too small
Action	Regenerate the global format buffer using the Adabas Event Replicator Subsystem. If the problem persists, contact your Software AG customer support representative with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.
ADAF6Z	Status/response {rsp} received from Reptor {rpid} on input queue {qname} TIME = {date time} RSP = {rc}, SUBC = {sc}, EXRRI = {err} INAM = {initial-state-name} SNAM = {subscription-name} DNAM = {destination-name} DBID = {dbid}, FNR = {fnr} UTOK = {token}IQNM = {queue-name}
Explanation	This informational message lists information returned from the Event Replicator Server.
Action	No action is necessary for this informational message. Review other associated messages to see if an error occurred.
ADAF70	SFDBID d{####}, SFILE f{####} not unique in Subscription {sssssss}
Explanation	In SUBSCRIPTION NAME=sssssss, there are duplicate SFDBID=d{####} and SFILE=f{####} found.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF71	Value NONE invalid in SDESTINATION for Subscription {sssssss}
Explanation	In SUBSCRIPTION NAME=sssssss, there is an SDESTINATION='NONE'. "NONE" is a reserved keyword for SIDESTINATION.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF72	SDESTINATION {sdsdsd} is not unique within Subscription {sssssss}
Explanation	In SUBSCRIPTION NAME=sssssss, there is an SDESTINATION specifying duplicate destinations of sdsdsd.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF73	SIDESTINATION {sisisi} is not unique within Subscription {sssssss}
Explanation	In SUBSCRIPTION NAME=sssssss, there is an SIDESTINATION specifying duplicate destinations of sisisi.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF74	Input DBID/File may not equal Target DBID/File in Destination {dddddddd}
Explanation	In DESTINATION NAME=dddddddd, the DBID/FILE is matching between Input DBID/FILE and Target DBID/FILE.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF75	SARC must be a value between 0 and 11
Explanation	The parameter SARC has a value not between 0 and 11.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF76	SIDESTINATION is invalid. Either specify NONE or specify the destination names
Explanation	The parameter SIDESTINATION has both NONE and destination names specified.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF77	ISUBSCRIPTION or IDESTINATION not unique
Explanation	The list of subscriptions specified in ISUBSCRIPTION parameter or list of destination specified in IDESTINATION parameter is not unique.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF78	IFILE parameters only valid for INITIALSTATE
Explanation	IFILE parameter specified without INITIALSTATE keyword.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF79	ISNLIST and SELCRIT are mutually exclusive
Explanation	Both ISNLIST and SELCRIT parameters specified.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF7A	{yyyy.mm.dd.hh.min.ss} Initial-state {status} Reptor-ID= {reptid}, FNR= {fnr}, Initial-state ID = X'is-id' Response= {rc}, Subcode= {sc} Read sequence is: {sequencetype} Nr of records processed = {num} Adabas could not inform Reptor about end of initial-state process replication is inactive
Explanation	These messages provide information on the status of an initial state. Possible values for <i>status</i> are "has started", "has ended", "terminated", "was stopped", or "error". Possible values for <i>sequencetype</i> are "ISN sequence", "Selection by ISN ", "Selection criterion (read logical)", or "Selection criterion (search command)".

Action	No action is required for this informational message.
ADAF7B	ADAF7B ISNLIST, SELCRIT or IDBID specified without IFILE parameter
Explanation	The ISNLIST, SELCRIT and IDBID parameters can be specified only with IFILE parameters.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF7C	Illegal SELCRIT expression.
Explanation	The SELCRIT parameter expression is illegal.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF7D	ResendBuffer name {resendbuffer-name} is not unique
Explanation	The resend buffer name provided in the RESENDBUFFER parameter has been defined previously. The names must be unique.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF7E	Destination {dest-name} has been changed to type NULL
Explanation	Event Replicator for Adabas is running in verify mode, so all destinations are changed to null-type destinations. This message is generated for every destination that is changed to DTYPE=NULL when VERIFYMODE=YES is specified.
Action	No action is required for this informational message.
ADAF7F	{AI BI FAI FBI KEY} decompression response {rc-code} subcode {rc-subcode} subscription {name} DBID {id} FNR {file-num} ISN {isn}
Explanation	A decompression failure occurred during the subscription phase of Event Replicator for Adabas processing. This failure is due to faulty format buffer or key data specified in a subscription definition. The specific Event Replicator for Adabas buffer is identified in the message by one of the following codes: <ul style="list-style-type: none"> ■ AI - after image ■ BI - before image ■ FAI - filter after image ■ FBI - filter before image ■ KEY - key before image
Action	Correct the format buffer or key data and try again.

ADAF7G **Successful {AI|BI|FAI|FBI|KEY} decompression for subscription {name} DBID {id} FNR {file-num} ISN {isn}**

Explanation Decompression during the subscription phase of Event Replicator for Adabas processing was successful; there were no errors.

This message is generated when Event Replicator for Adabas is running in verify mode and decompression is successful in the subscription phase.

The specific Event Replicator for Adabas buffer is identified in the message by one of the following codes:

- AI - after image
- BI - before image
- FAI - filter after image
- FBI - filter before image
- KEY - key before image

Action No action is required for this informational message.

ADAF7H **Misuse of A() or X() notation: {value}**

Explanation The value listed in the message does not obey the rules and restrictions governing the use of A() or X() notation as part of FLIST data. For more information, please read *Rules for Writing Filter Conditions in Adabas Event Replicator Subsystem User Guide*.

Action Check the FLIST input, correct the error, and restart the Event Replicator Server.

ADAF7I **Misuse of commas in FLIST: {list}**

Explanation The list given in the message does not obey the rules and restrictions governing the use of comma characters as part of FLIST data. For more information, please read *Rules for Writing Filter Conditions in Adabas Event Replicator Subsystem User Guide*.

Action Check the FLIST input, correct the error, and restart the Event Replicator Server.

ADAF7J **Misuse of wildcharacter in value: {value}**

Explanation The value listed in the message does not obey the rules and restrictions governing the use of wildcard characters as part of FLIST data. For more information, please read *Rules for Writing Filter Conditions in Adabas Event Replicator Subsystem User Guide*.

Action Check the FLIST input, correct the error, and restart the Event Replicator Server.

ADAF7K	Invalid hexadecimal input for X() notation: {value}
Explanation	The value listed in the message expects to use X() notation but the data between the parentheses does not represent valid hexadecimal data.
Action	Check the FLIST input, correct the error, and restart the Event Replicator Server.
ADAF7L	Filter {filter}, Group {group}, Condition {condition} inconsistent with value list.
Explanation	The filter identified by the <i>filter</i> , <i>group</i> and <i>condition</i> listed in the message specifies FLIST data which cannot be evaluated against the FCOND operation specified. For the correct usage, please read <i>Rules for Writing Filter Conditions</i> in <i>Adabas Event Replicator Subsystem User Guide</i> .
Action	Modify the FLIST input or the FCOND parameter to correct the error. Then restart the Event Replicator Server.
ADAF7M	When specified, SELCRIT must be nonblank
Explanation	The parameter SELCRIT contains only blanks.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAF7N	SDEACTIVATE must be YES or NO
Explanation	An invalid value was specified for the SDEACTIVATE parameter.
Action	Correct the value and try again.
ADAF7O	Subscription {subname} database {dbid} file {nn} {before after key} image uses global format buffer {gfb} This global format buffer contains field table information. It may not be used by more than one combination of database and file
Explanation	A global format buffer (GFB) definition contains a field table and is used for more than one combination of database ID and file number. This is not allowed.
Action	Correct the subscription so that the GFB field table is used for a single combination of database ID and file number.
ADAF7P	Subscription {subname} database {dbid} file {nn} {before after key} image uses global format buffer {gfb} This global format buffer is also used by subscription {subname} database {dbid} file {nn} A global format buffer may not be used for the same file number on different databases
Explanation	A global format buffer (GFB) definition is used by a subscription for the same file number on different databases. This is not allowed.
Action	Correct the subscription so that the GFB is used properly.

ADAF7Q	IDBID {idbid}, IFILE {fn} not unique in initial-state
Explanation	The initial-state database ID and file number are not unique for the initial-state definition, although they must be.
Action	Correct the initial-state definition so that it includes unique database ID and file number combinations.
ADAF7X	DAREPLICATEUTI=YES requires DREPLICATEUTI=YES
Explanation	An attempt was made to turn on utility replication for a file (DAREPLICATEUTI) in an Adabas destination, without also turning on utility replication for the Adabas destination in general.
Action	Correct the parameter input and restart the Event Replicator Server.
ADAF7Z	DREPLICATEUTI must be YES or NO
Explanation	An invalid value was specified for the DREPLICATEUTI parameter. Valid values are "YES" or "NO".
Action	Correct the parameter input and restart the Event Replicator Server.
ADAF80	Invalid INITIALSTATE definition NAME={is-name} Destination {dname} in subparameter IDESTINATION undefined
Explanation	The initial-state definition named in the message is invalid because the destination specified in the IDESTINATION parameter is not defined in the Replicator system file or by a DESTINATION initialization parameter. The destination name is also given in the message.
Action	Correct the destination that is referenced by the IDESTINATION parameter of the initial-state definition or add an appropriate destination definition to the Replicator system file or Event Replicator Server startup job, if necessary. You can add and modify replication definitions using initialization parameters or the Adabas Event Replicator Subsystem. Once the definitions and parameters are correctly specified, restart the Event Replicator Server.
ADAF81	Invalid INITIALSTATE definition NAME={is-name} Wrong IFILE supplied
Explanation	The IFILE parameter of the initial-state definition is incorrect. Either IFILE=0 is specified or the IFILE parameter is omitted.
Action	Correct the initial-state parameter specifications. Once the definitions and parameters are correctly specified, restart the Event Replicator Server.

ADAF82	Invalid INITIALSTATE definition NAME={is-name} Subscription {sname} in subparameter ISUBSCRIPTION undefined
Explanation	The initial-state definition named in the message is invalid because the subscription specified in the ISUBSCRIPTION parameter is not defined in the Replication system file or by a SUBSCRIPTION initialization parameter. The subscription name is also given in the message.
	One or more subscriptions specified in ISUBSCRIPTION parameter are not defined in SUBSCRIPTION settings.
Action	Correct the subscription that is referenced by the ISUBSCRIPTION parameter of the initial-state definition or add an appropriate subscription definition to the Replicator system file or Event Replicator Server startup job, if necessary. You can add and modify replication definitions using initialization parameters or the Adabas Event Replicator Subsystem.
	Once the definitions and parameters are correctly specified, restart the Event Replicator Server.
ADAF83	Invalid INITIALSTATE definition NAME={is-name} None of the specified destinations receive data from subscription {sname}
Explanation	The initial-state definition named in the message is invalid because none of the destinations receive data from the subscription specified in the ISUBSCRIPTION parameter.
Action	Correct the ISUBSCRIPTION parameter to identify the correct subscription or update the associated subscription definition so it sends data to one of the destinations specified in the initial-state definition. You can add and modify replication definitions using initialization parameters or the Adabas Event Replicator Subsystem.
	Once the definitions and parameters are correctly specified, restart the Event Replicator Server.
ADAF84	Invalid INITIALSTATE definition NAME={is-name} None of the specified or implied destinations receive data from database {dbid} / file {fnr}
Explanation	The initial-state definition named in the message is invalid because none of the destinations listed in the initial-state definition receive data from the database and file listed in the message.
Action	Correct one or more of the following, as necessary: <ul style="list-style-type: none"> ■ Correct the ISUBSCRIPTION parameter in the initial-state definition to identify the correct subscription. ■ Update one or more SFILE definitions within the associated subscription definition so it sends data from the database and file listed in the message.

You can add and modify replication definitions using initialization parameters or the Adabas Event Replicator Subsystem.

Once the definitions and parameters are correctly specified, restart the Event Replicator Server.

ADAF85 **DARC must be a value between 0 and 3**
Explanation The parameter DARC has a value that is not between 0 and 3.
Action Check the parameter value, correct the error, and restart the Event Replicator Server.

ADAF86 **Invalid INITIALSTATE definition NAME={is-name}**
INITIALSTATE with IFILE requires either IDBID or DBID
Explanation Neither IDBID nor DBID specified for IFILE parameter.
Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAF87 **AMI R={request} Q={details} RC={nnn}/{nnn}/{xxxxxxx}/{xxxxxxx}**
Explanation This message is issued when an error is encountered while communicating with the Adabas Messaging interface. When the error occurs as a result of a configuration or other expected error, a preceding message will have been issued to give more detailed information as to what the problem may be. If the error is not expected, you will need to use the information in this message along with the documentation from your messaging system to determine what caused the error.

R = Identifies the request that was issued.

Q = Gives 8 bytes of detail about the resource where the problem occurred. In some cases, such as the broker ID or the MQ Manager, only the first 8 bytes are given to indicate what was involved.

RC = Provides the Adabas Messaging Interface return and reason code and the underlying messaging subsystem return and reason codes respectively to help with error diagnosis.

Action If the message is preceded by another message indicating what the problem was, proceed based on that message. If the error was unexpected, try to determine from the messaging system response and reason codes what the problem was. If this fails, contact your Software AG technical support representative.

- **Messaging System incorrect** - For WebSphere MQ, the queue manager is not known to WebSphere MQ. For webMethods EntireX, the broker ID is not accessible on the system. You must review the parameter definitions associated with the destinations and/or input queues and ensure that the appropriate definitions have been set up correctly in WebSphere MQ or webMethods EntireX.
- **Messaging System resource error** - There is a resource problem in the WebSphere MQ queue manager or webMethods EntireX being used as the message transport. Review the details of the following message to determine what the resource problems may be.
- **Insufficient storage** - An attempt to get memory failed. You must review the size of the Event Replicator Server address space.

Action See listings of failure reasons above.

ADAF8C {dddddd} {request} for {resource} failed: {reason}

Explanation This message is issued when an error occurs during Event Replicator Server processing of resources associated with the messaging system being used.

The *request* value in the message is the request that was issued (e.g. INIT, SEND, RECEIVE etc.)

The *resource* listed in the message is the resource on which the request failed. For example, when a SEND fails to a specific destination, *resource* will be the name of the destination where the failure occurred.

The *reason* listed in the message is the reason for the failure. The following reasons can occur due to configuration or resource issues while running the Event Replicator Server. If any other reason appears, please contact your local support center.

- **Queue name unknown** - For WebSphere MQ, the queue name associated with the destination or input queue has not been defined to the WebSphere MQ system. For EntireX Broker, the service name associated with the destination or input queue has not been defined to broker. You must review the parameter definitions associated with the destination or input queue and ensure that the appropriate definitions have been set up correctly in WebSphere MQ or EntireX broker.
- **Messaging System incorrect** - For WebSphere MQ, the queue manager starting with the 8 characters in yyyyyyyy is not known to WebSphere MQ. For webMethods EntireX, the Broker ID starting with the 8 characters in yyyyyyyy is not accessible on the system. You must review the parameter definitions associated with the destinations and/or input queues and ensure that the appropriate definitions have been set up correctly in WebSphere MQ or EntireX broker.
- **Messaging System resource error** - There is a resource problem in the WebSphere MQ queue manager or webMethods EntireX being used as the message transport. Review the details of the following message to determine what the resource problems may be.
- **Insufficient storage** - An attempt to get memory failed. You must review the size of the Event Replicator Server address space.

- *Destination is full* - The destination specified by *yyyyyyyy* is full. This indicates that the WebSphere MQ Queue Manager or webMethods EntireX has refused to accept any more data. The Event Replicator Server will periodically retry to send the data and, when it successfully manages to send data, will revert back to normal mode and send data as it arrives at the Event Replicator Server. The destination reaches capacity if the data consumer does not remove data from the destination more quickly than the Event Replicator Server can send data to that destination.

Action See listings of failure reasons above.

ADAF8D **delete failed for {yyyyyyyy}**

Explanation An attempt to delete the module *yyyyyyyy* from storage failed. This should not occur and should be reported to your local support center.

Action Contact your local support center.

ADAF8E **Open or Close already in progress for {queue-name}**

Explanation A request has been received to open or close a queue which is already in the process of being opened or closed.

Action Retry the request after the outstanding open or close request has completed.

ADAF8F **Input queue {queue-name} already opened**

Explanation A request to open the input queue listed in the message failed because the queue was already open.

Action Verify that you have specified the correct queue in the request and try again.

ADAF8G **Close for input queue {queue-name }successful**

Explanation The input queue close request completed successfully.

Action No action is required for this informational message.

ADAF8H **Open for input queue {queue-name } {status}**

Explanation The input queue open request either completed successfully or failed, as specified in the message (*status*). The name of the input queue is given in the message.

Action No action is required for this informational message.

ADAF8I	Warning: one or more destinations defined with DLOG=YES but SLOG file is not loaded
Explanation	You have specified DLOG=YES on the definition of one or more destinations, but an SLOG file has not been defined to the Event Replicator for Adabas.
Action	Determine if DLOG=YES is required and, if so, define an SLOG file to the Event Replicator Server. For more information, read <i>Setting Up Subscription Logging in Event Replicator for Adabas Administration and Operations Guide</i> .
ADAF8J	SLOG cleanup process starting
Explanation	The SLOG cleanup process has started.
Action	No action is required for this informational message.
ADAF8K	{xx,xxx,xxx,xxx} items deleted for {destination {destname}} {replay instance that started at {date} {time}}
Explanation	One of the following occurred: <ul style="list-style-type: none"> ■ The Event Replicator Server destination identified in the message had data on the SLOG. However, when the Event Replicator Server was initialized, the destination had the SLOG facility turned off, so the data on the SLOG file is deleted. ■ In a previous Event Replicator Server session, a replay process that started at the date and time given in the message had data on the SLOG. When the Event Replicator Server was initialized, the replay-related data was deleted from the SLOG file. <p>The number of transactions deleted from the SLOG file is given in the message.</p>
Action	No action is required for this informational message.
ADAF8L	SLOG cleanup process {aborted completed halted}
Explanation	The SLOG cleanup process has finished.
Action	No action is required for this informational message.
ADAF8M	Unexpected error xxx encountered while referencing DATA storage RABN {xx,xxx,xxx,xxx}
Explanation	An unexpected error occurred related to the data storage RABN listed in the message.
Action	Identify and fix the problem from the response code and data storage RABN listed in the message or contact your Software AG technical support representative for assistance.

ADAF8N	{Open Close} request {name} for destination {destname}
Explanation	An open or close request was received or rejected for the destination named in the message. This may occur if a previous open or close request is still in progress for the destination.
Action	No action is required for this informational message.
ADAF8O	Subscription {subs-name} DBID {dbid} file {fn} filter {filter-name} group group-name condition {nnnnn} field {xx} error: {error-desc}
Explanation	An error occurred with the field, filter, and subscription named in the message. A description of the error, the database ID, file number, and condition are also listed in the message. Possible error descriptions are: <ul style="list-style-type: none"> ■ Begin byte or length not supported for field format ■ Begin byte plus length greater than field length ■ Field, PE or MU instance not found in Format buffer ■ Field specified cannot be used in field level filter ■ Field type unrecognized ■ Invalid begin byte specified ■ Invalid length specified ■ Invalid or out of range FLIST data: {data} hex: {hex} ■ Source field type incompatible with target
Action	Correct the problem indicated by the error description.
ADAF8P	Data read in SLOG for destination {destname} which now has DLOG=NO set
Explanation	SLOG data has been found for the destination listed in the message, which now has DLOG=NO set. This implies that at some point in the past, DLOG=YES was set and was subsequently changed. Be aware that this message indicates that previously logged data is now lost.
Action	If logging should not be active for the destination, this can be ignored. However, if it should be active, determine why the configuration was changed.

ADAF8Q **Data read in SLOG for destination {destname} which is not configured**
Explanation SLOG initialization processing has encountered data on the SLOG system file for the destination listed in the message. However, the destination is not defined in the current configuration. All SLOG data related to the destination will be deleted.
Action If the destination should be defined, determine why it was omitted from the configuration.

ADAF8R **Reptor initialization terminated at the request of destination output user exit {exit-name} for destination {dest-name }**
Explanation A destination output user exit requested that the Event Replicator Server terminate.
Action No action is required for this informational message.

ADAF8S **SLOG init completed successfully**
Explanation SLOG initialization processing completed successfully.
Action No action is required for this informational message.

ADAF8T **An unexpected error occurred in SLOG related processing {message-text-varies} response code {respcode} / reason code {reascode}**
Explanation An unexpected error occurred during SLOG processing. The details of the error are provided in the second line of the message, as described in the following table. The response code and reason code are also provided in the message.

Message Text	Description
Adabas Call Failed CMD= <i>command</i>	During SLOG processing, an Adabas call failed. The message provides the Adabas CMD that failed and provides associated reason and response codes.
Error returned from Adabas L3 read in RPSLI	An unexpected response code was received from Adabas during SLOG initialization.
Failure to acquire WORK pool space	During SLOG processing, an attempt to acquire work pool storage space failed.
L3 request on SuperDescriptor S1 failed	During SLOG read processing, an unexpected error occurred while reading the S1 descriptor.
L3 request on SuperDescriptor S2 failed	During SLOG read processing, an unexpected error occurred while reading the S2 descriptor.
Workpool storage request failed for CQE	Insufficient storage was available to initialize the Event Replicator Server SLOG facility.

Action Investigate the response and reason codes to determine the cause of the problem and correct it. If you get the "Workpool storage request failed for CQE" message text, verify that sufficient storage is available for Event Replicator Server initialization.

ADAF8U	Destination {destname} open failed Destination {destname} opened on some tasks Destination {destname} opened on all tasks								
Explanation	This is an informational message that indicates the result of an open request for the destination listed in the message.								
Action	If the open request failed, review associated messages to determine why it failed; then correct the problem. Otherwise, no action is required for this informational message.								
ADAF8V	Destination {destname} already open								
Explanation	A request to open the destination listed in the message failed because the destination was already open.								
Action	Verify that you have specified the correct destination in the request and try again.								
ADAF8W	Destination {destname} close failed Destination {destname} closed on some tasks Destination {destname} closed on all tasks								
Explanation	This is an informational message that indicates the result of a close request for the destination listed in the message.								
Action	If the close request failed, review associated messages to determine it failed; then correct the problem. Otherwise, no action is required for this informational message.								
ADAF8X	Destination {destname} already closed								
Explanation	A request to close the destination listed in the message failed because the destination was already closed.								
Action	Verify that you have specified the correct destination in the request and try again.								
ADAF8Y	{message-text}								
Explanation	<table border="1"> <thead> <tr> <th>Message Text</th> <th>Explanation</th> </tr> </thead> <tbody> <tr> <td>Terminating with data in SLOG for database-related input transactions</td> <td>The Event Replicator Server terminated with database-related input transactions from the Adabas nucleus logged on the SLOG system file.</td> </tr> <tr> <td>The database-related input transactions on the SLOG system file contain only FCB/FDT data</td> <td>This message may appear with the one above. The Event Replicator Server terminated with database-related input transactions on the SLOG file that contained only FCB or FDT data. This indicates that no replicated input transactions are pending on the SLOG system file at the end of the last session.</td> </tr> <tr> <td>Terminating with data in SLOG for destination <i>destname</i></td> <td>The Event Replicator Server terminated with logged data on the SLOG system file for the destination listed in the message.</td> </tr> </tbody> </table>	Message Text	Explanation	Terminating with data in SLOG for database-related input transactions	The Event Replicator Server terminated with database-related input transactions from the Adabas nucleus logged on the SLOG system file.	The database-related input transactions on the SLOG system file contain only FCB/FDT data	This message may appear with the one above. The Event Replicator Server terminated with database-related input transactions on the SLOG file that contained only FCB or FDT data. This indicates that no replicated input transactions are pending on the SLOG system file at the end of the last session.	Terminating with data in SLOG for destination <i>destname</i>	The Event Replicator Server terminated with logged data on the SLOG system file for the destination listed in the message.
Message Text	Explanation								
Terminating with data in SLOG for database-related input transactions	The Event Replicator Server terminated with database-related input transactions from the Adabas nucleus logged on the SLOG system file.								
The database-related input transactions on the SLOG system file contain only FCB/FDT data	This message may appear with the one above. The Event Replicator Server terminated with database-related input transactions on the SLOG file that contained only FCB or FDT data. This indicates that no replicated input transactions are pending on the SLOG system file at the end of the last session.								
Terminating with data in SLOG for destination <i>destname</i>	The Event Replicator Server terminated with logged data on the SLOG system file for the destination listed in the message.								

Message Text	Explanation
Terminating with data in SLOG for replay with token <i>token</i>	The Event Replicator Server terminated with logged data on the SLOG system file for the instance of the replay process identified by the token given in the message.

Action No action is required for these informational messages. Once the Event Replicator Server is restarted, this data will be cleared from the SLOG file.

ADAF8Z {Statistics }

Explanation This message is displayed in response to the operator command DRPLPARM. It shows the replication-related parameters.

Action No action is required for these informational messages.

ADAF90 {*nnn*} output subtasks to be attached

Explanation The Event Replicator Server is preparing to attach output subtasks.

Action None required. This message is for information only.

ADAF91 subtask *nnn* attach error *nnn* occurred

Explanation An error occurred while an Event Replicator Server output subtask was being attached.

Action Contact your DBA, system support personnel, or Software AG technical support.

ADAF92 {*type*} subtasks have been initialized

Explanation All of the Event Replicator Server subtasks of the specified *type* (input or output) have been successfully attached.

Action None required. This message is for information only.

ADAF93 {*nnn*} input subtasks to be attached

Explanation This message indicates the number *nnn* of subtasks that will be attached.

Action None required. This message is for information only.

ADAF94 {*nnn*} [{input}] subtasks have been detached

Explanation The Event Replicator Server input or output subtask termination process has completed. The total number of subtasks that have been terminated is given in the message (*nnn*)

Note: If the message is for input subtask termination, the word "input" is included in the message text. If the word "input" is not included in the message text, the message is for output subtask termination.

Action	No action is required for this informational message.
ADAF95	All {type} subtasks could not be initialized
Explanation	One or more Event Replicator Server subtasks of the specified <i>type</i> (input or output) could not be started successfully. One possible reason for this might be that the default subtask wait time (or the time specified by the <code>SUBTASKWAIT</code> parameter) is insufficient for your system. For more information about the <code>SUBTASKWAIT</code> parameter, read <i>SUBTASKWAIT (Subtask Wait Time) Parameter, in the Event Replicator for Adabas Reference Manual</i>
Action	Evaluate the setting of the <code>SUBTASKWAIT</code> parameter for your Event Replicator Server and consider increasing it (or setting it if it has not been set). If you still need assistance or the problem persists, contact your DBA, system support personnel, or Software AG technical support.
ADAF96	[[input]] subtask {nnn} detach error {eee} occurred
Explanation	An error occurred while an Event Replicator Server input or output subtask was being detached. The subtask number (<i>nnn</i>) and the error number (<i>eee</i>) are given in the message. Note: If the message is for input subtask termination, the word "input" is included in the message text. If the word "input" is not included in the message text, the message is for output subtask termination.
Action	Adabas termination continues. Contact your DBA, system support personnel, or Software AG technical support for assistance.
ADAF97	waiting for the termination of Reptor [[input]] subtasks
Explanation	The termination of Event Replicator Server input or output subtasks is in progress. Note: If the message is for input subtask termination, the word "input" is included in the message text. If the word "input" is not included in the message text, the message is for output subtask termination.
Action	None required. This message is for information only.
ADAF98	Error encountered while attempting to {<action>} input queue {iiiiiii} {<additional information>}
Explanation	This message has multiple texts, as described in the following table.

Message Text	Explanation
Error encountered while attempting to terminate input queue <i>iiiiiii</i> F= <i>fffffffff/yyyyyyy</i> <i>nnn/xxxxxxxx/yyyyyyy</i>	An error was encountered while attempting to terminate input queue <i>iiiiiii</i> . The request that was issued (<i>fffffffff</i>) is given in the message and contains values such as INIT, SEND, and RECEIVE . The return code and reason codes are given as values for RC= <i>nnn/nnn/xxxxxxxx/yyyyyyy</i> in the message. The underlying messaging subsystem return and reason codes respectively are given to help with error diagnosis.
Error encountered while attempting to Disconnect from input queue manager ' <i>manager name</i> ' F= <i>fffffffff</i> RC= <i>nnn/nnn/xxxxxxxx/yyyyyyy</i>	The input queue manager disconnect from the given queue <i>manager name</i> has failed. The request that was issued (<i>fffffffff</i>) is given in the message and contains values such as INIT, SEND, and RECEIVE . The return code and reason codes are given as values for RC= <i>nnn/nnn/xxxxxxxx/yyyyyyy</i> in the message. The underlying messaging subsystem return and reason codes respectively are given to help with error diagnosis.
Error encountered while attempting to Connect to input queue manager ' <i>manager name</i> ' F= <i>fffffffff</i> RC= <i>nnn/nnn/xxxxxxxx/yyyyyyy</i>	The input queue manager connect to the given queue <i>manager name</i> has failed. The request that was issued (<i>fffffffff</i>) is given in the message and contains values such as INIT, SEND, and RECEIVE . The return code and reason codes are given as values for RC= <i>nnn/nnn/xxxxxxxx/yyyyyyy</i> in the message. The underlying messaging subsystem return and reason codes respectively are given to help with error diagnosis.
Error encountered while attempting to Initialize <i>mmmmmmm</i> RC= <i>nnn/nnn</i>	ADAETB/ADAMQS initialization has failed. The module name is given in the message as <i>mmmmmmm</i> . The return and reason codes are also given in the message.

Action

Determine the reason for the failure based on the supplied reason code and correct the condition. Contact your DBA, system support personnel, or Software AG technical support if further assistance is needed.

ADAF99 {<item>} is unavailable

Explanation This message has multiple message texts, as described in the following table.

Message Text	Explanation
Destination <i>dddddddd</i> is unavailable	The destination name <i>dddddddd</i> is not available.
Input Queue <i>iiiiiii</i> is unavailable	The input queue name <i>iiiiiii</i> is not available.

Action Ensure the destination or input queue is correctly defined and assigned.

ADAF9A {yyyyyyyyyy} error in output subtask {nnn}

Explanation An error has occurred during the processing of output subtask number *nnn*. The *yyyyyyyyyy* in the message indicates whether the error occurred during initialization, processing or termination logic on the output subtask. This message is always preceded by a message with more information about where the problem lies.

When this occurs during initialization processing, the subtask will not initialize and Event Replicator Server initialization processing will terminate. When this occurs during termination processing of a subtask, termination processing will continue but one or more resources may be left in an invalid state.

Action This message will have been preceded by an error messaging indicating the error. Correct the problem based on this preceding error message.

ADAF9B {xxxxxxxxxxxx} error in input subtask {nnn}

Explanation This indicates that an error has occurred during the processing of input subtask number '*nnn*'. '*yyyyyyyyyy*' indicates whether the error occurred during initialization, processing or termination logic on the input subtask. This message is always preceded by a message with more information about where the problem lies.

When this occurs during initialization processing, the subtask will not initialize and Event Replicator Server initialization processing will terminate. When this occurs during termination processing of a subtask, termination processing will continue but one or more resources may be left in an invalid state.

Action This message will have been preceded by an error messaging indicating the error. Correct the problem based on this preceding error message.

ADAF9C	Input Queue: {xxxxxxx} Open failed: {xxxxxxxxxxxxxxxxxxxxxxx}
Explanation	This message indicates that the attempt to open the indicated Input Queue failed. The reason code indicates why the open attempt failed. This will normally occur if the input queue has not been properly defined to the messaging system or there are insufficient resources to open the queue.
Action	Determine the reason for the failure based on the supplied reason code and correct the condition. This will normally occur because the IQUEUE definition is invalid or the appropriate WebSphere MQ or webMethods EntireX resources have not been defined for the queue. In rare circumstances, this may occur due to a shortage of storage; in this case, increase the region size and rerun the job.
ADAF9D	date time {{Initial-state} {ADARPL/ADALOD}} process is running
Explanation	The initial-state, replay, or database load process is running.
Action	No action is necessary for this informational message.
ADAF9E	Invalid output returned from Destination user exit {exit-name} {error-text}
Explanation	The destination output user exit named in the message returned invalid data. Additional error text in the message further describes error. Possible error texts are: <ul style="list-style-type: none"> ■ A message length of 0 was specified for a Send request ■ Send request length exceeds max message length of <i>nnnn</i> ■ Control block URBY contains invalid return code =<i>nnn</i> ■ Send message/get same transaction return code issued after 1st exit call ■ Message text unavailable for error code = <i>yyy</i> ■ Destination <i>dest-name</i> closed by subtask =
Action	Investigate the causes of the user exit failure and fix them.
ADAF9F	Unable to acquire a UQE, response code {rc}, subcode {sc} Format buffer validation will not be done for Subscription {name}
Explanation	Format buffer validation, initiated because the FBVALIDATION parameter was turned on, could not be performed because a user queue element, which is used to store pointers to the internal format buffers and other information, could not be acquired. The response code (<i>rc</i>) and subcode (<i>sc</i>) are given in the message.
Action	Investigate the response code and subcode to identify and correct the problem.

ADAF9H	<p>Format buffer validation failed Response code {rc}, subcode {sc}, field name '{fldname}' Subscription {sname}, Database {dbid}, File {num}, XXX Global Format Buffer {gfb-name}</p>
Explanation	<p>An attempt to validate a format buffer failed. This validation attempt occurred because the FBVALIDATION parameter was turned on. The response code (<i>rc</i>), subcode (<i>sc</i>), subscription name (<i>sname</i>), database ID (<i>dbid</i>), file number (<i>num</i>), and global format buffer definition name (<i>gfb-name</i>) are given in the message.</p>
Action	<p>Correct the named format buffer and try again.</p>
ADAF9I	<p>FCB/FDT retrieval error, response code {rc}, subcode {sc} Format buffer validation will not be done for: Subscription files referencing Database {dbid}, File {num}</p>
Explanation	<p>Format buffer validation, initiated because the FBVALIDATION parameter was turned on, was not performed for subscriptions that reference the database (<i>dbid</i>) and file number (<i>num</i>) listed in the message. The response code (<i>rc</i>) and subcode (<i>sc</i>) are also given in the message. This failure occurred because a request for the FCB/FDT of a file has failed. These control blocks are used by the format buffer validation process.</p> <p>Although the message indicates format buffer validation will not be done as a result of the error, it does not mean that format buffer validation will be performed if the parameter is set to NONE. It is considered a warning message when format buffer validation was not requested to highlight a risk and the need to check that all is well based on the new and/or changed resource parameters implemented by the RPLREFRESH.</p> <p>For example, if a Subscription was changed and later an error detected as a result of this change, the Subscription may be deactivated and that could be a major issue.</p>
Action	<p>Investigate the response code and subcode to identify and correct the problem.</p>
ADAF9J	<p>Replay jobstream generated Replay jobstream generation failed ADARAG {function} return code {rc} DDJCLIN failed to open DDJCLOUT failed to open DDJCLIN missing %KARTE or %SEQUENTIAL DDJCLIN has multiple %KARTE or %SEQUENTIAL</p>
Explanation	<p>These are informational messages about ADARPL utility processing. For further details about how to use this facility, read <i>ADARPL Utility: PLOG Replication Replay</i>, in the <i>Event Replicator for Adabas Reference Guide</i>.</p> <p>The ADARAG internal routine is used to:</p> <ul style="list-style-type: none"> ■ Open DDJCLOUT ■ Write record to DDJCLOUT and DDDRUCK ■ Close DDJCLOUT

- Generate DD statement and write it to DDJCLOUT and DDDRUCK
- Open DDJCLIN
- Get record from DDJCLIN
- Close DDJCLIN

Action If the ADARAG routine fails, report the return code to your Software AG technical support representative.

ADAF9K **CBuf {resendbuffer-name} {function} F/RC {f/rc} Dep Ret/Rsn {ret/rsn}**

Explanation An error was reported by the circular resend buffer manager for the named resend buffer. The function listed in the message will be one of the following:.

Create DSP
Delete DSP
Obtain ALET
Rlse ALET

The internal service numeric function and return codes are shown in *f* and *rc* settings in the message and the platform-dependent return and reason codes are also shown. Under z/OS, circular resend buffers are implemented as dataspaces. The z/OS DSPSERV function creates and deletes dataspaces, and the ALESERV function administers ALETs.

Action If the reason for the error code is not clear, contact your DBA, system support personnel, or Software AG technical support representative.

ADAF9L **Unexpected return code {rc} received acquiring Reptor information from a peer nucleus**

Explanation An unexpected error occurred when a second or subsequent cluster nucleus starts.

Action Analyze the return code given the message and react accordingly. Contact your Software AG technical support representative for assistance.

ADAF9M **Insufficient WORK pool space available. Increase LWP.**

Explanation There was insufficient work pool space available to the Event Replicator Server.

Action Increase the setting of the ADARUN LWP parameter for the Event Replicator Server. The stop and restart the Event Replicator Server.

ADAF9N	Peer nucleus {nucid} is starting a connection to Reptor {dbid}
Explanation	A cluster nucleus is connecting to the Event Replicator Server.
Action	No action is required for this informational message.
ADAF9O	Peer nucleus {nucid} encountered response {rrrrr} communicating with Reptor {dbid}
Explanation	When the cluster nucleus attempted to communicate with the Event Replicator Server listed in the message, the response code (<i>rrrrr</i>) listed in the message was received.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF9P	Connection to Reptor {dbid} terminated due to insufficient free space in a peer nucleus replication pool
Explanation	An Adabas cluster database was not able to connect to an Event Replicator Server due to insufficient replication pool free space in one of the cluster nuclei.
Action	Consider increasing the value of the LRPL parameter for the cluster nuclei.
ADAF9Q	Cluster database {dbid} aborted its connection attempt
Explanation	The Event Replicator Server has detected an unsuccessful connection from a cluster database.
Action	Examine all error messages in the cluster nuclei job logs to determine the reason for the failed connection attempt.
ADAF9R	Abort connection call to Reptor {dbid} failed with response {rrrrr/sssss }
Explanation	When the cluster database attempted to disconnect from the Event Replicator Server listed in the message, the response code and subcode (<i>rrrrr/sssss</i>) listed in the message were received.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF9S	Auto-restart connect call to Reptor {dbid} failed with response {rrrrr/sssss}
Explanation	A cluster nucleus that has completed auto-restart processing was not able to connect to the Event Replicator Server listed in the message. The response code and subcode (<i>rrrrr/sssss</i>) listed in the message were received.
Action	Investigate the response code and subcode to identify and correct the problem.

ADAF9T	Initial connect to Reptor {dbid} failed with response {rrrrr/ sssss}
Explanation	When the cluster database attempted to connect to the Event Replicator Server listed in the message, the response code and subcode (<i>rrrrr/ sssss</i>) listed in the message were received.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF9U	Completion of connection to Reptor {dbid} failed with response {rrrrr/ sssss}
Explanation	The cluster database was unable to connect to the Event Replicator Server listed in the message. The response code and subcode (<i>rrrrr/ sssss</i>) listed in the message were received.
Action	Investigate the response code and subcode to identify and correct the problem.
ADAF9V	Starting a cluster connection to Reptor {dbid}
Explanation	An Adabas cluster database is attempting to connect to an Event Replicator Server.
Action	No action is required for this informational message.
ADAF9W	Cluster connected to Reptor {dbid}
Explanation	An Adabas cluster database successfully connected to an Event Replicator Server.
Action	No action is required for this informational message.
ADAF9X	Cluster database {dbid} is connecting
Explanation	The Event Replicator Server is processing a connection request from a cluster nucleus.
Action	No action is required for this informational message.
ADAF9Y	Cluster auto-restart handshake call processed for database {dbid / nucid}
Explanation	The Event Replicator Server has reconnected to a cluster nucleus that has completed auto-restart processing.
Action	No action is required for this informational message.

ADAF9Z	Cluster database {dbid} has connected
Explanation	The Event Replicator Server has successfully connected to a cluster nucleus.
Action	No action is required for this informational message.
ADAF A0	Refresh requested for {resource} {name}
Explanation	An RPLREFRESH command has been entered to refresh the resource named in the message.
Action	No action is required for this informational message.
ADAF A1	Refresh failed: parameter processing error
Explanation	An RPLREFRESH command has been entered, but cannot be processed due to an error return from the input parameter processing routines.
Action	Examine the DDPRINT output for messages relating to specific parameter errors, correct these errors, and restart the Event Replicator Server.
ADAF A2	Modifying an existing resendbuffer is not allowed
Explanation	You cannot use the RPLREFRESH command to dynamically refresh a resend buffer definition; you can only add or delete a resend buffer definition using RPLREFRESH. To modify a resend buffer definition for a running Event Replicator Server, complete the steps described in <i>Resend Buffer Modification and Refresh Requirements</i> , in <i>Event Replicator for Adabas Administration and Operations Guide</i> .
Action	No action is required for this informational message.
ADAF A3	Request invalid when RPLPARMS not set to FILE Request invalid when reptor system file does not exist
Explanation	An RPLREFRESH command has been entered, but can only be processed when the ADARUN RPLPARMS parameter is set to "FILE" and a Replicator system file is defined in the Event Replicator Server.
Action	Ensure that ADARUN RPLPARMS parameter is set to "FILE" and that a Replicator system file is defined in the Event Replicator Server as described in the Event Replicator for Adabas installations instructions. Then restart the Event Replicator Server.
ADAF A4	Refresh Aborted
Explanation	An RPLREFRESH , ABORT command has been successfully processed.
Action	No action is required for this informational message.

ADAF A5	Refresh exceeded time limit waiting for quiesce of resources
Explanation	An RPLREFRESH command could not be processed as the relevant resources had not entered a quiescent state within five minutes.
Action	Ensure that the resources being refreshed are not actively in use by the Event Replicator Server before attempting to reenter the RPLREFRESH command.
ADAF A6	{Add Modify Delete} requested for subscription {sub}
Explanation	An RPLREFRESH command has requested to add, modify or delete subscription <i>sub</i> .
Action	No action is required for this informational message.
ADAF A7	{Add Modify Delete} requested for subscription {sub} successful
Explanation	An RPLREFRESH command request to add, modify, or delete subscription <i>sub</i> has been processed successfully.
Action	No action is required for this informational message.
ADAF A8	Subscription {sub} does not contain files required for Adabas destination {dest}
Explanation	Adabas destination <i>dest</i> is defined with a DBID/File combination for which there is no match in subscription definition <i>sub</i> .
Action	Ensure that the all of the Adabas destination's input DBID/File combinations are matched in the subscription.
ADAF A9	Adabas destination {dest} also used by subscription {sub}
Explanation	An Adabas destination may only be assigned for use by one subscription at a time.
Action	Remove destination <i>dest</i> from the SDESTINATION parameter or from the destination name list for subscription <i>sub</i> and restart the Event Replicator Server.
ADAF AA	Resendbuffer {buf} does not exist
Explanation	The resend buffer named in the message has not been defined.
Action	Specify a correctly defined resend buffer definition before attempting to refresh the subscription.
ADAF AC	One or more format buffers failed format buffer validation
Explanation	Format buffer validation has been set to "ABORT" or "DEAC" and one or more of the format buffer definitions has been found to be invalid.
Action	Inspect the format buffer definitions and correct any errors before restarting the Event Replicator Server.

ADAFAD	Subscription {sub} release for FBs failed rsp {rc}
Explanation	As part of a refresh of subscription <i>sub</i> , an internal Event Replicator Server cleanup failed with the response given in the message. The refresh will proceed despite this message.
Action	Report this message and the response code to your Software AG support representative.
ADAFAE	Subscription {sub} not found
Explanation	An RPLREFRESH command was entered to delete a subscription, but the named subscription cannot be found.
Action	If the intention was to ensure that subscription <i>sub</i> be removed from the Event Replicator Server definitions, then no further action is required. Otherwise correct the RPLREFRESH command to delete a subscription that currently exists.
ADAFAF	Subscription {sub} in use by initial state request {istate}
Explanation	An RPLREFRESH command was entered to delete subscription <i>sub</i> , but it has been found to be still in use by initial state definition <i>istate</i> .
Action	Remove the subscription from the initial-state subscription list before restarting the Event Replicator Server.
ADAFAG	Destination {dest} has remaining SLOG data
Explanation	An RPLREFRESH command was entered to refresh a subscription using destination <i>dest</i> , for which there is still data in the SLOG. The subscription is therefore not in a quiescent state and so the refresh cannot yet be implemented. An ADAFAI message will follow stating that the refresh is scheduled.
Action	Wait for the subscription to return to a quiescent state and then the refresh can be implemented. If the subscription returns to a quiescent state in the next five minutes, this will happen automatically; otherwise, you will have to request the refresh again.
ADAFAH	{Add Modify Delete} requested for destination {dest}
Explanation	An RPLREFRESH command has requested to add, modify, or delete destination <i>dest</i> .
Action	No action is required for this informational message.
ADAFAI	{Add Modify Delete} requested for destination {dest} {successful scheduled failed}
Explanation	The RPLREFRESH request to add, modify, or delete the destination definition listed in the message was processed successfully, has been scheduled for processing once the destination is in a quiescent state, or has failed. .
Action	No action is required for this informational message. If the request has failed, previous messages will give details of the failure.

ADAFAJ	DLOG=NO cannot be set for destination {dest} while data still exists on subscription log file
Explanation	An RPLREFRESH command to modify destination <i>dest</i> by setting DLOG=NO has been entered, but data for the destination still exists in the SLOG. An ADAFAI message will follow this message stating that the refresh has failed.
Action	Wait until the SLOG data for the destination has been delogged before attempting to modify the DLOG value using RPLREFRESH.
ADAFAK	Destination {dest} must be closed for requested modification
Explanation	An RPLREFRESH request to modify destination <i>dest</i> by altering one of the messaging layer parameters has been made, but the destination has not been closed. An ADAFAI message will follow this message stating that the refresh has failed.
Action	Close the destination before attempting to modify one of its messaging layer parameters.
ADAFAL	Allocation failed for storage required to implement add
Explanation	An RPLREFRESH request to add a new resource has been entered but insufficient storage is available to manage the new structures required. An ADAFAI message will follow this message stating that the refresh has failed.
Action	Make more storage available to the Event Replicator Server and restart.
ADAFAM	Destination {dest} not found
Explanation	An RPLREFRESH request was made to delete destination <i>dest</i> , or to modify a subscription to refer to it, but the destination definition cannot be found. An ADAFAI message will follow this message stating that the refresh has failed.
Action	If you intended to ensure that the destination be removed from the Event Replicator Server definitions, then no further action is required. Otherwise, correct the RPLREFRESH command to delete a destination that currently exists, or correct the subscription definition to refer to a valid destination.
ADAFAN	Destination {dest} in use by initial state request {istate}
Explanation	An RPLREFRESH request was made to delete destination <i>dest</i> , but the destination is still in use by initial state definition <i>istate</i> .
Action	Remove the destination from the initial-state destination list for the initial-state definition before restarting the Event Replicator Server.

ADAFAO	Destination {dest} in use by subscription {sub}
Explanation	An RPLREFRESH request was made to delete destination <i>dest</i> , but the destination is still in use by subscription <i>sub</i> .
Action	Remove the destination from the subscription definition before restarting the Event Replicator Server.
ADAFAP	Destination {dest} cannot be deleted while output is still in progress on destination
Explanation	An RPLREFRESH request was made to delete destination <i>dest</i> , but there are still transactions being sent to the destination or being logged to the SLOG for it. An ADAFAI message will follow this message stating that the refresh has failed.
Action	Wait until the destination is no longer in active use by the Event Replicator Server before attempting to delete it.
ADAFAQ	Destination {dest} cannot be deleted while data still exists on subscription log for destination
Explanation	An RPLREFRESH request was made to delete destination <i>dest</i> , but there is still data on the SLOG for it. An ADAFAI message will follow this message stating that the refresh has failed.
Action	Wait until all the data for the destination to be deleted is removed from the SLOG before attempting to delete it.
ADAFAR	Destination {dest} must be closed before it can be deleted
Explanation	An RPLREFRESH request was made to delete destination <i>dest</i> , but it is not closed. An ADAFAI message will follow this message stating that the refresh has failed.
Action	Close the destination before attempting to delete it.
ADAFAS	{Add Modify Delete} request for destination {dest} aborted by exit {uexit}
Explanation	AN RPLREFRESH request to add, modify or delete destination <i>dest</i> has been aborted by user exit <i>uexit</i> .
Action	Inspect your user exit to determine why the refresh has been aborted.
ADAFAT	Output still in progress for destination {dest}
Explanation	An RPLREFRESH request was made to refresh a subscription using destination <i>dest</i> , for which there is still data on the output queue. The subscription is therefore not in a quiescent state and, consequently, the refresh cannot yet be implemented. An ADAFAI message follows this message stating that the refresh is now scheduled.
Action	Wait for the subscription to return to a quiescent state and then the refresh can be implemented. If the subscription returns to a quiescent state in the next five minutes, this will happen automatically; otherwise, you will have to request the refresh again.

ADAF AU	Incoming transactions available for subscription processing
Explanation	An RPLREFRESH request was made to refresh a subscription for which there are still transactions on the subscription queue. The subscription is therefore not in a quiescent state and, consequently, the refresh cannot yet be implemented. An ADAF AI message follows this message stating that the refresh is now scheduled.
Action	Wait for the subscription to return to a quiescent state and then the refresh can be implemented. If the subscription returns to a quiescent state in the next five minutes, this will happen automatically; otherwise, you will have to request the refresh again.
ADAF AV	RECORDPLOGINFO must be {YES Y} or No N
Explanation	An invalid value was specified for the RECORDPLOGINFO parameter.
Action	Correct the parameter value and try again.
ADAF AW	{function} requested for resendbuffer {rbname}
Explanation	Add, delete, or modify processing has been requested for the resend buffer definition listed in the message. The kind of processing requested is given in the message (<i>function</i>).
Action	No action is required for this informational message.
ADAF AX	Resendbuffer {rbname} in use by subscription {sname}
Explanation	An RPLREFRESH request was made to delete resend buffer <i>rbname</i> , but the resend buffer definition is still in use by subscription definition <i>sname</i> .
Action	No action is required for this informational message. If you want to modify the resend buffer dynamically, you should follow the instructions provided in <i>Resend Buffer Modification and Refresh Requirements</i> , in <i>Event Replicator for Adabas Administration and Operations Guide</i>
ADAF AY	{function} for resendbuffer {rbname} successful
Explanation	Add, delete, or modify processing was successfully performed for the resend buffer definition listed in the message. The kind of processing requested is given in the message (<i>function</i>).
Action	No action is required for this informational message.
ADAF AZ	Input Queue {qname} not found
Explanation	An RPLREFRESH request was made to delete an input queue definition (<i>qname</i>), but the named input queue definition does not exist.
Action	Verify that the correct input queue definition was referenced in the RPLREFRESH request. If not, correct it and try again.

ADAFB1 **Error processing Replicator system file, internal command**
Error {function} -- {action}
Adabas command {command} -- {action}
RSP {rspcode} Subcode {subcode}

Explanation PLOG sequential data set information resulting from a successful ADARES PLCOPY run is maintained in the Replicator system file. This error can be caused by an Adabas command used to access the Replicator system file or by an internal system function.

The response code and subcode from processing are given in the message. In addition, the following functions (*function*) can appear:

- Error acquiring UQE
- Error setting file in use
- Error reading FCB
- Error reading FDT

Finally, the following actions (*action*) may occur in the message:

Action	Description
adding PLOG information	When this action is listed in the message, the error prevented a PLOG file description record from being inserted.
selecting PLOGs for replay	When this action is listed in the message, the error prevented a set of PLOGs from being selected. This would also prevent an ADARPL job from running.

Action If the error is from an Adabas command, investigate the response code and subcode to identify and correct the problem. If you cannot resolve it, or if you receive an internal function error, contact your Software AG technical support representative.

ADAFB2 **Selecting PLOGs for automatic Replay job generation DBID {dbid}**
{errortext}

Explanation A request to select PLOG sequential data sets was unsuccessful for the database listed in the message spanning a starting and ending date and time. One or more additional lines of error text (*errortext*) provide additional detail about the error:

Error Text	Explanation and Action
Error - No Replicator system file	PLOG data set information cannot be maintained without a Replicator system file. No ADARPL job stream can be generated. Action: Define a Replicator system file using the ADALOD utility (ADALOD LOAD FILE= <i>nn</i> , REPLICATOR).

Error Text	Explanation and Action
Error -- Internal buffer overflow selecting between <i>start date/time</i> and <i>end date/time</i>	<p>The set of PLOGs spanning the start and end date and times listed in the error text was very large and exceeded the size of an internal buffer. No ADARPL job stream can be generated.</p> <p>Action: Contact your Software AG technical support representative.</p>
Error -- No PLOGs found between <i>start date/time</i> and <i>end date/time</i>	<p>There were no PLOG sequential data sets in the Replicator system file between the start and end dates and times listed in the error text.</p> <p>Action: Verify that the requested dates and times are correct. If the requested dates and times are correct, see if you can locate PLOG sequential data sets spanning the required interval, generate and submit an ADARPL job stream manually.</p>
Error -- PLOGs out of sequence PLOG <i>start date/time1</i> session <i>session1</i> blocks <i>first - last1</i> PLOG <i>start date/time2</i> session <i>session2</i> blocks <i>first - last2</i>	<p>A PLOG sequential data set with a later date and time has either a lower session number than the previous PLOG or, if the session numbers are the same, its starting block is less than or equal to the previous PLOG's ending block. A partial ADARPL job stream may be generated, but will not execute.</p> <p>Action: Carefully examine the selected set of PLOGs to determine why the out-of-sequence condition exists. If you can resolve the sequencing, manually edit the job stream, and resubmit it. If you are unable to determine why the PLOGs are out of sequence, contact your Software AG technical support representative for assistance.</p>
Error - PLOGs missing between PLOG <i>start date/time1</i> session <i>session1</i> blocks <i>first - last1</i> PLOG <i>start date/time2</i> session <i>session2</i> blocks <i>first - last2</i>	<p>There is a gap between two successive PLOG sequential data sets for the same PLOG session. One or more blocks are missing. If all data is present, the last block number of the first PLOG plus one should be equal to the first block number of the second PLOG. A partial ADARPL job stream may be generated, but will not execute.</p> <p>Action: If you can locate a data set with the missing PLOG blocks, manually edit the generated job stream to include the missing data set in the proper sequence in the PLOG data set concatenation, and resubmit the job.</p>
Error - PLOGs missing, new session did not start with block 1 PLOG <i>start date/time</i> session <i>session</i> blocks <i>first - last</i>	<p>A new PLOG session is initiated each time the Adabas nucleus is started. The first block number in the first PLOG in the session should be "1". The identified PLOG data set is the first data set of the PLOG session found in the Replicator system file, but the first block of that</p>

Error Text	Explanation and Action
	<p>data set is not "1". A partial ADARPL job stream may be generated, but it will not execute.</p> <p>Action: If you can locate a data set with the missing PLOG blocks, manually edit the generated job stream to include the missing data set in the proper sequence in the PLOG data set concatenation, and resubmit the job.</p>
<p>Error - PLOGs missing, end-of-session not set on PLOG <i>start date/time</i> session <i>session</i> blocks <i>first - last</i></p>	<p>A PLOG session ends when the Adabas nucleus shuts down. The final PLOG data set of a session should indicate that no more blocks of the session listed in the message will be created and the next PLOG data set in sequence will be the first of a new, higher-numbered, PLOG session. A partial ADARPL job stream may be generated, but it will not execute.</p> <p>Action: If you can locate a data set with the missing PLOG blocks, manually edit the generated job stream to include the missing data set in the proper sequence in the PLOG data set concatenation, and resubmit the job.</p> <p>Action:</p>
<p>Note - PLOGs sessions <i>sess1</i> through <i>sess2</i> missing Sessions may have been used by on-line save</p>	<p>Normal PLOG session numbers increase by one when an Adabas nucleus starts. This is not an error if the missing sessions were used by an online save. An ADARPL job stream may be generated.</p> <p>Action: No action is necessary for this informational message, if the missing session numbers resulted from an online save. However, if that is not the case, and if you can locate a data set with the missing PLOG sessions, manually edit the generated job stream to include the data set in the proper sequence in the PLOG data set concatenation and resubmit the job.</p>
<p>No PLOG starts before <i>start date/time1</i> Earliest PLOG starts at <i>start date/time2</i></p>	<p>No PLOG data set was found in the Replicator system file with a start date and time less than or equal to the required start date and time. The requested start date and time is given in the error text. A partial ADARPL job stream may be generated, but it will not execute.</p> <p>Action: If you can locate additional PLOG data sets, manually edit the generated job stream to include the missing data sets at the beginning of the PLOG data set concatenation, and resubmit the job.</p>

Action

Modify the ADARPL REPLAY options or the Event Replicator for Adabas parameters based on the error in the message and rerun the job.

ADAFB3	Data found on SLOG for Replay instance started at {date} {time}
Explanation	SLOG initialization processing encountered data on the SLOG system file for a replay process from a previous session, which is identified by its start time.
Action	No action is required for this informational message.
ADAFB4	Above replay instance is not defined in this session
Explanation	The current instance of the Event Replicator Server has no information about the replay instance referred to in the preceding ADAFB3 message. It will delete all SLOG data related to this replay instance.
Action	No action is required for this informational message.
ADAFB6	Input Queue {qname} must be closed for requested operation
Explanation	A refresh request was received for an input queue definition, but the input queue definition is not closed.
Action	Close the input queue definition and try again.
ADAFB7	{operation} for Input Queue {qname} successful
Explanation	A refresh operation was processed successfully for the input queue definition listed in the message. The type of operation (add, modify, or delete) is given in the message.
Action	No action is required for this informational message.
ADAFB8	{function} requested for input queue {qname}
Explanation	Add, delete, or modify processing has been requested for the input queue definition listed in the message. The kind of processing requested is also given in the message (<i>function</i>).
Action	No action is required for this informational message.
ADAFB9	initialstate {isname} is still active
Explanation	An attempt was made to use the RPLREFRESH command to refresh the initial-state definition listed in the message, but the initial-state definition was still active, so the attempt failed.
Action	Deactivate the initial-state definition prior to running RPLREFRESH.

ADAFBA	initialstate {isname} not found
Explanation	An RPLREFRESH request was made to delete or modify initial-state definition <i>isname</i> , but the initial-state definition cannot be found. An ADAFBI message will follow this message stating that the refresh has failed.
Action	If you intended to ensure that the initial-state definition be removed from the Event Replicator Server definitions, then no further action is required. Otherwise, correct the RPLREFRESH command to modify an initial-state definition that currently exists.
ADAFBB	{function} for initialstate {isname} successful
Explanation	Add, delete, or modify processing was successful for the initial-state definition listed in the message. The kind of processing requested is also given in the message (<i>function</i>).
Action	No action is required for this informational message.
ADAFBC	Modify requested for Global Settings
Explanation	A refresh request for global settings has been received.
Action	No action is necessary for this informational message.
ADAFBD	Modify for Global successful
Explanation	A refresh request for global settings was processed successfully.
Action	No action is necessary for this informational message.
ADAFBE	{operation} requested for initialstate {isname}
Explanation	A refresh request for the initial-state definition listed in the message has been received. The operation requested is given in the message.
Action	No action is necessary for this informational message.
ADAFBF	{resource} {name} was not refreshed {reason}
Explanation	A refresh request for the resource named in the message failed because it was discovered that the resource definition had changed. The following possible reasons can appear in this message: <ul style="list-style-type: none"> ■ The defined initial state definition is unchanged ■ The defined resendbuffer definition is unchanged ■ The defined destination definition is unchanged ■ The defined global definitions are unchanged ■ The defined input queue definition is unchanged ■ The defined subscription definition is unchanged

Action	Change the resource definition and reissue the request.
ADAFBG	Refresh for {resource} {name} not implemented due to refresh failure of a dependent resource
Explanation	While executing a refresh ALL request, the refresh of the resource named in the message could not be processed because of a failure to refresh a dependent resource.
Action	Determine why the dependent resource could not be refreshed, resolve the problem, and repeat the request.
ADAFBH	Resendbuffer {rsbuf-def} will not be modified
Explanation	A resend buffer definition was changed and subsequently a RPLREFRESH command was issued. The resend buffer definition will not be modified.
Action	No action is required for this informational message.
ADAFBI	Automated reopen has been terminated for destination {dest-def}
Explanation	An attempt to close a destination definition occurred for which pending open retries are still outstanding. The pending open retries are dropped.
Action	No action is required for this informational message.
ADAFBJ	Messaging system error detected. The automatic open of the following input queues destinations will be skipped: {def-names}
Explanation	The automatic open of the input queue or destination definitions listed in the message (def-names) are skipped due to messaging system errors. Subsequent open attempts for the same messaging system manager and for the listed destinations or input queues will be skipped until their retry interval expires again.
Action	No action is required for this informational message. Review other messages preceding this one that describe the open or connect failure and react accordingly.
ADAFBK	Automated reopen has been terminated for input queue {iq-def}
Explanation	An attempt to close an input queue definition occurred for which pending open retries are still outstanding. The pending open retries are dropped.
Action	No action is required for this informational message.

ADAFBL	A subscription user exit may not be refreshed in this environment
Explanation	A refresh of subscription user exit operation cannot be processed in this environment: either Reptor is not running on z/OS operating system, or EXITLIB DD is not specified in JCL, or Reptor is not running APF-authorized.
Action	Determine why the subscription user exit could not be refreshed, resolve the problem, and repeat the request.
ADAFBM	The user exit {exit_name} is not defined
Explanation	The subscription user exit <i>exit_name</i> was not specified for any subscription.
Action	Specify the correct name of the subscription user exit and repeat the request.
ADAFBN	The user exit {exit_name} is not a subscription user exit
Explanation	An attempt was made to use the RPLREFRESH,SX= command to refresh the user exit <i>exit_name</i> , but this user exit is not a subscription user exit.
Action	Only subscription user exit can be refreshed.
ADAFBO	Subscription user exit {exit_name} was successfully refreshed
Explanation	A refresh request for subscription user exit was processed successfully.
Action	No action is necessary for this informational message.
ADAFBP	Refreshing a subscription user exit requires Adabas V8.4 or above
Explanation	Refreshing a subscription user exit requires Adabas V8.4 or above.
Action	Upgrade ADABAS to V84 or above.
ADAFBQ	Subscription user exits cannot be loaded from the EXITLIB not running APF-authorized
Explanation	Refreshing a subscription user exit requires APF-authorization.
Action	Ensure that the Reptor runs APF-authorized.
ADAFBR	Subscription user exits will be loaded from the EXITLIB
Explanation	Refreshing a subscription user exit is possible.
Action	No action is necessary for this informational message.

ADAFBZ {message-text}

Explanation Two possible message texts may be given for this message ID:

Message Text	Description
Failed to set conversion attributes to subscription flist encoding for subscription <i>subs-name</i> dbid <i>dbid</i> file <i>fn</i> response code <i>rc</i> reason code <i>rsn</i>	An error occurred related to a subscription file filter definition.
Failed to set conversion attributes to user encoding for subscription <i>subs-name</i> dbid <i>dbid</i> file <i>fn</i> response code <i>rc</i> reason code <i>rsn</i>	An error occurred related to UES translation.

The name of the affected subscription (*subs-name*), database ID (*dbid*), and file number (*fn*) are given in the message. In addition, a response code (*rc*) and reason code (*rsn*) for the error are provided.

Action Analyze the return codes given in the message texts to identify the cause of the problem.

ADAF2K message-text

Explanation The following message texts may appear for this message ID:

Message Text	Description
Error occurred during file(s) reactivation for Replay token <i>ttttt</i>	A file reactivation counter timed out during replay processing. The ADARPL replay token is given in the message (<i>ttttt</i>).
File reactivation wait timeout	A file reactivation counter timed out during replay processing.

This error message occurs during file reactivation for automated replay initialization. It is printed after the [ADAF2K](#) message.

Action Execution continues, as with the [ADAF2K](#) message. This is often the result of a shortage in the replication pool. Increasing the value of the LRPL parameter may alleviate the shortage.

ADAF3 Unexpected Response code {rc} from DBID {dbid} for {cc}-command

Explanation An unexpected response code (*rc*) was received from the database identified in the message (*dbid*) while it was processing the database command shown in the message (*cc*)

Action Analyze the response code to determine why the error occurred. Contact your Software AG technical support representative if you need additional assistance.

ADAF4	Replay token {tttt} initialization timeout
Explanation	An initialization counter timed out during replay processing. The ADARPL replay token is given in the message (<i>tttt</i>).
Action	Increase the timeout value or check the previous messages (for example ADAF2K or ADAF9) concerning the replay token <i>tttt</i> to determine where the wait occurs. Correct the problem and try again.
ADAF5	Nucleus DBID {dbid} Runs without DUAL/OCTO-PLOG
Explanation	The database identified in the message (<i>dbid</i>) runs with a dual or octo-PLOG. This message may occur when an attempt to execute an automated replay with an Adabas nucleus that executes with dual (OCTO) PLOGs. An automated replay may only be executed with an Adabas nucleus that executes with dual (OCTO) PLOGs.
Action	Make sure you run automated replay only on an Adabas nucleus that executes with dual (OCTO) PLOGs.
ADAF6	No free PLOGs available on Nucleus DBID {dbid}
Explanation	There are no free PLOGs available on the database identified in the message (<i>dbid</i>). This message occurs when a request for an automated replay was made and all PLOGs are full on the related database. When this occurs, the automated replay is rejected and this message is printed.
Action	Ensure one or more PLOG data sets are free for the related database ID (run ADARES PLCOPY).
ADAF7	FEOFPL could not be processed
Explanation	This is an informational message printed after either the ADAFC5 message or the ADAFC6 message.
Action	Resolve the problem that caused the ADAFC5 or ADAFC6 message. No action is required for this informational message.
ADAF8	Replay token {tttt} initialization canceled
Explanation	The initialization of the replay token given in the message (<i>tttt</i>) has been canceled. This is an informational message printed after either the ADAFC5 message or the ADAFC6 message.
Action	Resolve the problem that caused the ADAFC5 or ADAFC6 message. No action is required for this informational message.

ADAF C9	Waiting for PLOG Switch on Nucleus DBID {dbid} for Replay token {tttt}
Explanation	Replay processing is waiting to switch protection logs (PLOGs) on the database identified in the message (<i>dbid</i>). The replay token is also given in the message (<i>tttt</i>).
Action	No action is required for this informational message.
ADAF CA	Waiting for PLOG information from DBID {dbid} for Replay token {tttt}
Explanation	This informational message may be written in the Event Replicator Server job log during the execution of a synchronized replay (the ADARPL utility). The database ID (<i>dbid</i>) and the replay token (<i>tttt</i>) are given in the message.
Action	No action is required for this informational message.
ADAF CB	ADARPL Jobstream generation failed for Replay token {tttt}
Explanation	The ADARPL job failed for the replay token named in the message (<i>tttt</i>).
Action	Analyze other messages preceding this message and react accordingly. Contact your Software AG technical support representative for assistance.
ADAF CC	No resources modified by rplrefresh all as no resource definitions have changed
Explanation	A refresh all command was issued but the resource definitions in the active Event Replicator Server and the parameters provided are the same.
Action	Change the resource definition parameters and reissue the command.
ADAF CD	Rplrefresh,all failed due to replication pool overflow
Explanation	A request to get storage from the replication pool failed.
Action	Determine why the replication pool is full. If possible, resolve the problem. If you need assistance, contact your Software AG technical support representative.
ADAF CE	Open of File destination {name} failed as CLOG is not active
Explanation	A command was issued to open a file destination (for example, DTYPE=TLOG), but a command log was not defined in the Event Replicator Server.
Action	Ensure the Event Replicator Server is running with a CLOG defined if you wish to use destinations of type TLOG.

ADAFCF	Utility replication error - {error-text} DBID {dbid} FNR {fn} RSP {rc} Subcode {sc}
Explanation	<p>These messages are written when an error is encountered attempting to replicate a utility operation (for example, a file deletion) for a target Adabas DBID/file. A description of the error is provided in the message (<i>error-text</i>), in addition to the database ID, file number, and any response or subcode. Possible error texts that might appear in the message are:</p> <ul style="list-style-type: none"> ■ "Change field length " ■ "Delete file" ■ "Refresh file" ■ "Rename file" ■ "Set reuse ISN on/off" ■ "Set reuse DS blocks on/off" ■ "Modify FCB" ■ "Define file" ■ "Write FDT" ■ "Define new field" ■ "Utility type unavailable "
Action	Review the error text provided in the message and resolve the problem based on that text. If the error persists, contact your Software AG technical support representative for assistance.
ADAFCG	Destination {dest-def} - DBID/File {dbid}/{fn} DATMETHOD must be ISN or KEY
Explanation	Parameter <code>DATMETHOD</code> has been set to an invalid value in the destination definition named in the message (<i>dest-def</i>). The database and file combination for which <code>DATMETHOD</code> has been set are also listed in the message.
Action	Correct the <code>DATMETHOD</code> setting.
ADAFCH	Destination {dest-def} - DBID/File {dbid}/{fn} {parm-name} cannot be specified with DATMETHOD=ISN
Explanation	An invalid combination of parameter definitions has been specified in the destination definition named in the message (<i>dest-def</i>). When the <code>DATMETHOD</code> parameter is set to "ISN", other parameters may not be specified. The parameter in error is listed in the message (<i>parm-name</i>). The database and file combination for which the invalid parameter combinations have been specified are also listed in the message (<i>dbid</i> and <i>fn</i>).

The following parameters cannot be specified when DATMETHOD is set to "ISN": DATKEYSB, DATKEYAIO, DATKEYAIL, DATKEYBIO, DATKEYBIL, DATKEYKYO, and DATKEYKYL.

Action Either alter the DATMETHOD parameter setting or remove the incompatible parameter setting from the destination definition.

ADAFCI **Destination {dest-def} - DBID/File {dbid}/{fn} for DATMETHOD=KEY, DATKEYSB must be specified**

Explanation The DATKEYSB parameter must be specified when the DATMETHOD parameter is set to "KEY". The destination definition containing the invalid parameters is named in the message (*dest-def*), as well as the database and file combination for which the invalid parameters were specified (*dbid* and *fn*).

Action Either alter the DATMETHOD parameter setting or add a setting for DATKEYSB.

ADAF CJ **Destination {dest-def} - DBID/File {dbid}/{fn} {parm-name} must be numeric and <= 32,767**

Explanation An invalid setting was specified for the parameter (*parm-name*) named in the message. The destination definition containing the invalid parameter is named in the message (*dest-def*), as well as the database and file combination for which the invalid parameter was specified (*dbid* and *fn*).

The parameter names that might appear in this message are: DATKEYAIL, DATKEYBIL, DATKEYKYO, and DATKEYKYL.

Action Correct the parameter setting.

ADAFCK **Destination {dest-def} - DBID/File {dbid}/{fn} if DATKEY{xx}O is specified, DATKEY{xx}L must also be specified with a value > 0**

Explanation An invalid combination of DATKEY* parameter settings was specified for the destination definition named in the message (*dest-def*). The names of the invalid parameters are listed in the message (DATKEYxxO and DATKEYxxL). Possible substitutions for the xx in the message are AI, BI, or KY. For example, if the DATKEYAIO parameter is specified, a positive, nonzero integer must also be specified for the DATKEYAIL.

The database and file combination for which the invalid parameter settings have been specified are also listed in the message (*dbid* and *fn*).

Action Correct the settings for the parameter combinations in the destination definition.

ADAFCL {message-text}

Explanation One of the following message texts is provided in this message.

Message Text	Description
Destination <i>dest-def</i> - DBID/File <i>dbid/fn</i> the sum of DATKEY _{xxO} and DATKEY _{xxL} must be <= 2,147,483,647	The sum of the DATKEY* parameters listed in the message must be less than or equal to 2,147,483,647 bytes. The names of the parameters are listed in the (DATKEY _{xxO} and DATKEY _{xxL}). Possible substitutions for the <i>xx</i> in the message are AI or BI.
Destination <i>dest-def</i> - DBID/File <i>dbid/fn</i> the sum of DATKEYKYO and DATKEYKYL must be <= 32,767	The sum of the DATKEYKYO, and DATKEYKYL parameters listed in the message must be less than or equal to 32,767 bytes.

The destination definition containing the parameters is named in the message (*dest-def*), as well as the database and file combination for which the parameters were specified (*dbid* and *fn*).

Action Correct the settings for the parameters in the destination definition.

ADAFCM Destination {dest-def} - DBID/File {dbid}/{fn} for DATMETHOD=KEY, DATKEYAIL must be specified and greater than 0

Explanation The DATKEYAIL parameter must be specified when the DATMETHOD parameter is set to "KEY". The destination definition containing the invalid parameters is named in the message (*dest-def*), as well as the database and file combination for which the invalid parameters were specified (*dbid* and *fn*).

Action Either alter the DATMETHOD parameter setting or add a setting for DATKEYAIL.

ADAFCN Destination {dest-def} - DMAXOUTPUTSIZE must be greater than 4,096, less than 2,147,483,648 or 0

Explanation An invalid value for the DMAXOUTPUTSIZE parameter was specified in the destination definition named in the message (*dest-def*). Valid values must be zero (0) or range between 4096 bytes and 2,147,483,648 bytes.

Action Specify a valid value for the DMAXOUTPUTSIZE parameter

ADAFCO	Destination {dest-def} DAERROR-must be BACKOUT, CLOSE or ALTACTION
Explanation	An invalid value for the DAERROR parameter was specified in the destination definition named in the message (<i>dest-def</i>). Valid values are "BACKOUT", "CLOSE" or "ALTACTION".
Action	Specify a valid value for the DAERROR parameter.
ADAFCP	Key value is not unique More than one record was found with this key value
Explanation	Replication failed because a key value was not unique across records. This message is accompanied by other messages that provide more information about the problem.
Action	Determine why the key values are not unique and review the other messages for a better understanding of the problem. Contact your Software AG technical support representative if you need assistance.
ADAFQ	Destination {destid} is being closed
Explanation	Event Replicator for Adabas is closing the destination identified in the message (<i>destid</i>) because of replication errors that occurred for it. This message is accompanied by other messages that provide more information about the problem.
Action	No action is required for this informational message.
ADAFCR	The transaction will be backed out and skipped
Explanation	Event Replicator for Adabas is backing out and skipping a transaction because of replication errors that occurred for it. This message is accompanied by other messages that provide more information about the problem.
Action	No action is required for this informational message.
ADAFCS	Response 145 (the record is held by another user) has been encountered while processing an initial-state transaction. The records already processed will be committed. Processing will continue with the rest of the initial-state transaction
Explanation	A replication error occurred while processing an initial-state transaction. Response 145 is issued. This message is accompanied by other messages that provide more information about the problem.
Action	Review the other messages to further understand the problem. Contact your Software AG technical support representative if you need assistance.

ADAFCT	Response 145 (the record is held by another user) has been encountered. The current transaction will be backed out and restarted once the ISN is available.
Explanation	A replication error occurred because a record is held by another user. Response 145 is issued. This message is accompanied by other messages that provide more information about the problem.
Action	Review the other messages to further understand the problem. Contact your Software AG technical support representative if you need assistance.
ADAFCU	The record to be {deleted updated} does not exist on the target DBID/file
Explanation	A replication error occurred when the record to be deleted or updated (as specified in the message) does not exist in the target database file. This message is accompanied by other messages that provide more information about the problem.
Action	Review the other messages to further understand the problem with the record. Contact your Software AG technical support representative if you need assistance.
ADAFCV	The record to be inserted already exists on the target DBID/file
Explanation	A replication error occurred when the record to be inserted already exists in the target database file. This message is accompanied by other messages that provide more information about the problem.
Action	Review the other messages to further understand the problem. Contact your Software AG technical support representative if you need assistance.
ADAFCW	The {delete update insert} is part of a transaction with the resend flag set
Explanation	A replication error occurred when an insert, update or delete (as specified in the message) request fails because the transaction has its resend flag set. This message is accompanied by other messages that provide more information about the problem.
Action	Review the other messages to further understand the problem. Contact your Software AG technical support representative if you need assistance.
ADAFCX	The record will be inserted
Explanation	Event Replicator for Adabas will insert the replicated record, even though replication problems have occurred. This message is accompanied by other messages that provide more information about the problem.
Action	No action is required for this informational message.

ADAFCY	The record will updated
Explanation	Event Replicator for Adabas will update the replicated record, even though replication problems have occurred. This message is accompanied by other messages that provide more information about the problem.
Action	No action is required for this informational message.
ADAF CZ	The above error will be ignored
Explanation	Event Replicator for Adabas will ignore the error described by the previous error message, even though replication problems have occurred. This message is accompanied by other messages that provide more information about the problem.
Action	No action is required for this informational message.
ADAFNA	Connect to Reptor {id} failed, target is not a Reptor
Explanation	An attempt was made by an Adabas nucleus to connect to an Event Replicator Server when the target of the message is actually another Adabas nucleus, not an Event Replicator Server. The Event Replicator Server ID is given in the message.
Action	Ensure that you are trying to connect to another Adabas nucleus, not an Event Replicator Server, and try again.
ADAFNB	Connect to Reptor {reptid} failed, the level of the Reptor is incompatible with this Adabas nucleus
Explanation	The Event Replicator for Adabas version running in the Adabas nucleus is incompatible with the Event Replicator for Adabas version running in the Event Replicator Server nucleus. The software (i.e., Adabas or Event Replicator for Adabas) level in the source nucleus must be less than or equal to the software level in the Event Replicator Server.
Action	Analyze the use of the Adabas and Event Replicator Server nucleuses to determine which version should be used on each. Then update the software accordingly. Contact your Software AG technical support representative if you need assistance.
ADAFNC	Connect to Reptor {reptid} failed with response code {rc}/{sc}
Explanation	A connection to the Event Replicator Server named in the message (<i>reptid</i>) failed. The response code and subcode (<i>rc</i> and <i>sc</i>) are given in the message.
Action	Analyze the response code and subcode to determine why this problem is occurring.

ADAFND	Cluster connection to Reptor {id} was not successful
Explanation	This message is written in each cluster nucleus when a cluster connection is not successful. Earlier messages for one or more of the cluster nuclei give the reason why the connection was not successful. Normally, the connection will not be successful when the Event Replicator Server is not active. The database ID of the Event Replicator Server is given in the message.
Action	Analyze the messages for each of the cluster nuclei to determine the cause and resolution of this problem.
ADAFNE	{yyyy.mm.dd} {hh.mm.ss} A connection will be attempted {yyyy.mm.dd} {hh.mm.ss} with Reptor {id}
Explanation	This message is printed as a result of the RPLCONNECT operator command (issued to an Adabas nucleus). The message is printed for each Event Replicator Server ID for which the nucleus attempts a connection.
Action	No action is required for this informational message.
ADAFNF	{yyyy.mm.dd} {hh.mm.ss} No connection attempts will be made as a {yyyy.mm.dd} {hh.mm.ss} result of the RPLCONNECT request
Explanation	This message is printed as a result of the RPLCONNECT operator command (issued to an Adabas nucleus). The message is printed when no connection attempts will be made as a result of the RPLCONNECT operator command.
Action	Analyze the RPLCONNECT operator command you issued for invalid Event Replicator Server IDs that might have been specified.
ADAFNG	Cluster connection command V2/{xxx}/{yyy} ended with response code {rc}
Explanation	In a cluster, one Adabas nucleus is the driver of the cluster connection with the Event Replicator Server. This message is written in the Adabas nucleus that is the driver of the cluster connection with the Event Replicator Server when an unexpected error occurs on the V2 command. The V2 command type <i>xxx</i> , subtype <i>yy</i> and response code <i>rc</i> , are given in the message.
Action	Analyze the response code and subcode to determine why this problem is occurring.
ADAFOA	Destination {xxxxxxxx} {xxxxxxxx} RC=X' {xx} '/X' {xxxxxxxx}'
Explanation	Destination <i>xxxxxxxx xxxxxxxx</i> (access method macro) failed with <i>return code/reason code</i> .
Action	Verify that the JCL DD statement for the sequential file destination is using allowable parameters for the utility/job that failed. Lookup the return and reason codes for the QSAM access method macro that failed.

ADAF0B	Destination {xxxxxxx} file attributes are invalid
Explanation	Destination xxxxxxxx is using invalid attributes for the file.
Action	Verify that the correct attributes are specified for the sequential file, e.g. record format, blocksize, and record length.
ADAFP0	DQFULLDELAY is only valid for an ETBROKER or MQSeries destination
Explanation	An attempt was made to specify a destination full delay interval for an Adabas, file, or null destination. The DQFULLDELAY parameter is only valid for webMethods EntireX or WebSphere MQ destination definitions.
Action	Remove the DQFULLDELAY parameter for the Adabas, file, or null destination and try again.
ADAFP1	GQFULLDELAY must be in range 5 – 300
Explanation	An invalid specification was made for the GQFULLDELAY parameter. The GQFULLDELAY parameter setting must be an integer between "5" and "300".
Action	Correct the GQFULLDELAY specification and try again.
ADAFP2	{dbid} STATINTERVAL must be 0 or in the range 60 - 86,400
Explanation	An invalid value was specified for the STATINTERVAL initialization parameter. The STATINTERVAL parameter specifies the interval (in seconds) at which interval statistics are published by the Event Replicator Server. Valid values are 0 or an integer in the range 60 through 86,400.
Action	Correct the invalid parameter specification and try again.
ADAFP3	{dbid} DSTATLOG must be YES or NO
Explanation	An invalid value was specified for the DSTATLOG initialization parameter. The DSTATLOG parameter indicates whether a destination should receive interval statistics from the Event Replicator Server. Valid values are YES or NO.
Action	Correct the invalid parameter specification and try again.
ADAFP4	IQETBSCONV must be YES or NO
Explanation	An invalid specification was made for the IQETBSCONV parameter. The IQETBSCONV parameter setting must be "YES" or "NO".
Action	Correct the IQETBSCONV specification and try again.

ADAFP5	DETBSCONV must be YES or NO
Explanation	An invalid specification was made for the DETBSCONV parameter. The DETBSCONV parameter setting must be "YES" or "NO".
Action	Correct the DETBSCONV specification and try again.
ADAFP6	DETBTOKEN DETBUSERID is not allowed when DETBSCONV=NO
Explanation	An invalid specification was made for the DETBTOKEN DETBUSERID parameter. The DETBTOKEN DETBUSERID parameter is not allowed when DETBSCONV=NO.
Action	Correct the DETBTOKEN DETBUSERID specification and try again.
ADAFP7	IQETBTOKEN IQETBUSERID is not allowed when IQETBSCONV=NO
Explanation	An invalid specification was made for the IQETBTOKEN IQETBUSERID parameter. The IQETBTOKEN IQETBUSERID parameter is not allowed when IQETBSCONV=NO.
Action	Correct the IQETBTOKEN IQETBUSERID specification and try again.
ADAFP8	Subscription {xxxxxxx} database {nnnnn} file {nnnnn} after/before/key image uses global format buffer {xxxxxxx} This global format buffer is optimized for processing initial state data only The subscription destination {xxxxxxx} cannot be used because: - It allows normal data to be sent and/or does not allow for initial state data - Or it is not an ETB, MQ Series, or Null destination - Or the destination parameter DCLASS is not set to SAGTARG
Explanation	During session startup or an operator RPLREFRESH command, an optimized global format buffer was found to be in error for one or more of the reasons listed.
Action	Make the necessary corrections to ensure the optimize global format buffer meets all of the list requirements and restrictions.
ADAFP9	DARC is only valid for an ETBROKER, MQSERIES, or NULL destination
Explanation	The DARC parameter can only be specified in a webMethods EntireX, WebSphere MQ, or Null destination definition. It is not valid for any others.
Action	Remove the DARC parameter from this destination definition.
ADAFP10	MAXRECORDSIZE must be greater than 0 and less than or equal to 50% of LRPL and less than or equal to 32767'
Explanation	An invalid value for the MAXRECORDSIZE parameter has been specified. Valid values must be greater than zero (0), with a maximum of 32,767 bytes or 50% of the ADARUN LRPL parameter setting, whichever is larger.
Action	Correct the setting of the MAXRECORDSIZE parameter.

ADAFPC	MAXVARRECORDSIZE must be greater than 0 and less than or equal to 50% of LRPL and less than or equal to 32767
Explanation	An invalid value for the MAXVARRECORDSIZE parameter has been specified. Valid values must be greater than zero (0), with a maximum of 32,767 bytes or 50% of the ADARUN LRPL parameter setting, whichever is larger.
Action	Correct the setting of the MAXVARRECORDSIZE parameter.
ADAFPD	MAXVARRECORDSIZE must be less than or equal to MAXRECORDSIZE
Explanation	The setting of the MAXVARRECORDSIZE or the MAXRECORDSIZE parameter is not accurate. The setting for MAXVARRECORDSIZE must be less than or equal to the setting for MAXRECORDSIZE.
Action	Correct the setting of either the MAXVARRECORDSIZE or the MAXRECORDSIZE parameter, as appropriate for your site.
ADAFPE	DEVENTLOG must be YES or NO DEVENTLOG is {x} DEVENTLOG must be Y or N
Explanation	An invalid value (x) was specified for the DEVENTLOG initialization parameter. Valid values are YES (Y) or NO (N).
Action	Correct the DEVENTLOG specification and try again.
ADAFPF	LOGINPUTTRANSACTION must be ALL or NO or in the range 1 <=n<=99
Explanation	An invalid value was specified for the LOGINPUTTRANSACTION initialization parameter. Valid values are ALL, NO, or an integer from 1-99.
Action	Correct the LOGINPUTTRANSACTION specification and try again.
ADAFPG	Same {type} service is defined for both destination {destname} and input queue {queue name}
Explanation	The same webMethods EntireX (Broker) service or WebSphere MQ (MQSeries) queue is defined for both a destination and input queue definition. The <i>type</i> of service (Broker or MQSeries), the destination definition name (<i>destname</i>) and the input queue definition name (<i>queue name</i>) are given in the message.
Action	Correct either the destination or input queue definition so they do not use the same webMethods EntireX service or WebSphere MQ queue.

ADAFPH	For subscription {subname}, DBID {dbid}, FNR {fnr} The Subscription SFILE keyword parameter SFSEXIT must be specified when SFREPLICATEDELETE=UPDATE
Explanation	The SFREPLICATEDELETE parameter was set to "UPDATE", but no value was specified for the SFSEXIT parameter. If you specify SFREPLICATE=UPDATE, you must also specify a value for the SFSEXIT parameter. The subscription definition name (<i>subname</i>) as well as the database ID (<i>dbid</i>) and file number (<i>fnr</i>) are given in the message.
Action	Either change the value of SFREPLICATEDELETE so it is no longer set to "UPDATE" or supply a value for the SFSEXIT parameter. Then try again.
ADAFPI	For subscription {subname}, DBID {dbid}, FNR {fnr} Only YES, NO, or UPDATE are valid for: '{parameter} {keyword}'
Explanation	A value other than YES, NO, or UPDATE was specified for the parameter (<i>parameter</i>) and keyword (<i>keyword</i>) named in the message. The subscription definition name (<i>subname</i>) as well as the database ID (<i>dbid</i>) and file number (<i>fnr</i>) are given in the message.
Action	Correct the parameter or keyword setting and try again.
ADAFPJ	For subscription {subname}, DBID {dbid}, FNR {fnr} The before and after image format buffers must be equal when SFREPLICATEDELETE=UPDATE
Explanation	An attempt was made to pass both before and after images to the subscription user exit because the SFILE SFREPLICATEDELETE parameter was set to "UPDATE". However, the format buffer before and after images for the physical delete transaction currently being processed were not identical. Subscription definitions with SFREPLICATEDELETE=UPDATE should not have a primary key defined to the file. The subscription definition name (<i>subname</i>) as well as the database ID (<i>dbid</i>) and file number (<i>fnr</i>) are given in the message.
Action	Contact your Software AG technical support representative for assistance.
ADAFPK	DOPEN must be YES, NO, or GLOBAL
Explanation	The value of the DOPEN subparameter must be either "YES", "NO", or "GLOBAL". DOPEN is a subparameter of the DESTINATION initialization parameter.
Action	Check the parameter input, supply a valid value, and restart the Event Replicator Server.

ADAFPL	GOPEN must be YES or NO
Explanation	The value of the GOPEN parameter must be either "YES" or "NO".
Action	Check the parameter input, supply a valid value, and restart the Event Replicator Server.
ADAFPM	{FSBEGIN FTBEGIN} must be in range 1 - 32767
Explanation	An invalid specification was made for the FSBEGIN or FTBEGIN parameters. The FSBEGIN and FTBEGIN parameter settings must be between "1" and "32,767".
Action	Correct the FSBEGIN or FTBEGIN specification and try again.
ADAFPN	{FSLENGTH FTLENGTH} must be in range 1 – 32767
Explanation	An invalid specification was made for the FSLENGTH or FTLENGTH parameters. The FSLENGTH and FTLENGTH parameter settings must be between "1" and "32,767".
Action	Correct the FSLENGTH or FTLENGTH specification and try again.
ADAFPO	{FSBEGIN FTBEGIN} plus {FSLENGTH FTLENGTH} exceed 32768 limit
Explanation	An invalid combination of specifications has been made for the FSBEGIN and FSLENGTH or for the FTBEGIN and FTLENGTH parameters. The sum of the FSBEGIN and FSLENGTH parameter specifications cannot exceed 32,768. Likewise, the sum of the FTBEGIN and FTLENGTH parameter specifications cannot exceed 32,768.
Action	Correct the FSBEGIN, FTBEGIN, FSLENGTH, or FTLENGTH specifications and try again.
ADAFPP	When SFSECURITYFILE=YES is specified: No format buffer may be specified No value may be specified for SFDEFAULTACODE The default value of YES must be in effect for: ADAFPP SFREPLICATEDELETE, SFREPLICATEINSERT, SFREPLICATENOTCHANGED, and SFREPLICATEUPDATE No value may be specified for SFSEXIT No value may be specified for SFFILTER
Explanation	One or more invalid parameters have been specified at the subscription/file level with SFSECURITYFILE=YES. This message lists the rules regarding specification of the SFSECURITYFILE parameter and others in your subscription file (SFILE) definition.
Action	Check the parameter input, supply a valid value, and restart the Event Replicator Server.

ADAFPQ	Subscription {subname1} DBID {dbid} File {fnum} has SFSECURITYFILE=YES Subscription {subname2} DBID {dbid} File {fnum} has SFSECURITYFILE={{no yes}}
Explanation	<p>This message is issued when one of two errors has occurred:</p> <ul style="list-style-type: none"> ■ The same file in the same database has SFSECURITYFILE=YES (the file is a security file that should be replicated) in one subscription definition and SFSECURITYFILE=NO (the file is not a security file) in a second subscription definition. This is invalid; the subscriptions should specify the SFSECURITYFILE parameter for the same database file in both subscriptions. Either the file is a security file or it is not. ■ Two different files in the same database have been identified as security files (both files in the same database have SFSECURITYFILE=YES) in one or more subscription definitions. Only one security file is expected per database.
Action	Check the parameter input, supply a valid value, and restart the Event Replicator Server.
ADAFPR	Subscription {sub-name} DBID {dbid} File {fnum} has SFSECURITYFILE=YES Adabas destination {dest-name} Input DBID {indbid} File {infile} Target DBID {targdbid} File {targfile} Must specify identical input and target files
Explanation	When SFSECURITYFILE=YES is specified in a subscription (indicating Adabas security definitions should be replicated for a database file) and the data from the file flows to an Adabas destination, the input file and target file must be identical in every Adabas destination that replicates data from the source database to the target database.
Action	Check the parameter input, supply a valid value, and restart the Event Replicator Server.
ADAFPS	Invalid field order number for GFB {gfb} field {fld}
Explanation	An error occurred when reading the Replicator system file for the global format definition named in the message (<i>gfb</i>). The global format buffer has not been correctly generated. The two-byte Adabas field name (<i>fld</i>) contains an invalid field order number. Field order numbers are used with composite fields and indicate the order the fields are to be concatenated. The field order number was specified for a non-primary key field or an invalid value was specified. Possible values are from "01" through "99".
Action	Correct the invalid field number and regenerate the global format buffer / GFFT using the Data Mapping Tool or Predict and reload it into the Replicator System file using the Adabas Event Replicator Subsystem. If the problem persists, contact your Software AG customer support representative with the information contained in the message. A copy of the Replicator system file may be needed for diagnosis.

ADAFPT	<p>Subscription {subsname} DBID {dbid} File {fn} has SFSECURITYFILE=YES Initial-state definition {isname} references the same DBID/file</p>
Explanation	<p>A subscription file (SFILE) definition used by the subscription (<i>subsname</i>) indicates that the database file listed in the message (<i>dbid</i> and <i>fn</i>) is a security file. The same database file is also referenced in an initial-state definition (<i>isname</i>). However, the Event Replicator for Adabas does not support the use of security files in initial-state definitions. Any security file you identify in an SFILE definition cannot also be used in an initial-state definition.</p>
Action	<p>Revise your initial-state or subscription SFILE definitions, as appropriate, so that the security file is not used in the initial-state definition. Then try again.</p> <p>For information on populating a target database with an initial snapshot of the security definitions, read <i>Initial-State Processing of Security Definitions</i>, in the <i>Event Replicator for Adabas Administration and Operations Guide</i>.</p>
ADAFPV	<p>IQOPEN must be YES, NO, or GLOBAL</p>
Explanation	<p>An invalid value was specified for the IQOPEN parameter. Valid values for the IQOPEN parameter are "YES", "NO", or "GLOBAL". IQOPEN is a parameter of the IQUEUE initialization parameter.</p>
Action	<p>Correct the parameter input and restart the Event Replicator Server.</p>
ADAFPW	<p>SLOGCHECKINTERVAL must be 0 or in the range 5 – 2880</p>
Explanation	<p>An invalid value was specified for the SLOGCHECKINTERVAL parameter. Valid values are zero (0) or an integer in the range from 5 through 2880.</p>
Action	<p>Correct the parameter and try again.</p>
ADAFPW	<p>{{asso} {data} {slogac} {slogds} {slogni} {slogui}}THRESHOLD must be in the range 0 - 100</p>
Explanation	<p>An invalid value was specified for the ASSOTHRESHOLD, DATATHRESHOLD, SLOGACTHRESHOLD, SLOGDSTHRESHOLD, SLOGNITHRESHOLD, or SLOGUITHRESHOLD parameter (as shown in the message). Valid values for any of these parameters are integers in the range from 0 through 100.</p>
Action	<p>Correct the parameter and try again.</p>

ADAFPX	{dbid} A nonzero value must be specified for at least one of the following: ASSOTHRESHOLD, DATATHRESHOLD, SLOGACTHRESHOLD, SLOGDSTHRESHOLD, SLOGNITHRESHOLD, and SLOGUITHRESHOLD
Explanation	The ASSOTHRESHOLD, DATATHRESHOLD, SLOGACTHRESHOLD, SLOGDSTHRESHOLD, SLOGNITHRESHOLD, and SLOGUITHRESHOLD parameter values are all set to zero, effectively preventing threshold monitoring from occurring in any of the areas in which it can be performed.
Action	Specify a nonzero value for at least one of the parameters ASSOTHRESHOLD, DATATHRESHOLD, SLOGACTHRESHOLD, SLOGDSTHRESHOLD, SLOGNITHRESHOLD, or SLOGUITHRESHOLD.
ADAFPY	NPADACALLS must be in range 1 – 50
Explanation	An invalid specification was made for the NPADACALLS parameter. The NPADACALLS parameter setting must be between "1" and "50".
Action	Correct the NPADACALLS specification and try again.
ADAFPZ	DQFULLDELAY must be in range 5– 300 or GLOBAL
Explanation	An invalid specification was made for the DQFULLDELAY parameter. The DQFULLDELAY parameter setting must an integer be between "5" and "300" or the word "GLOBAL".
Action	Correct the DQFULLDELAY specification and try again.
ADAFQA	DHBOPTION is only valid for destination type ETBROKER, MQSeries, or Null
Explanation	The destination DHBOPTION parameter is only valid for destination types ETBROKER, MQSERIES, or NULL.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAFQB	DHBOPTION is invalid, the only value allowed is 1
Explanation	The only valid value for the destination DHBOPTION parameter is 1.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.
ADAFQC	DHBINTERVAL is only valid for destination type ETBROKER, MQSeries, or Null
Explanation	The destination DHBINTERVAL parameter is only valid for destination types ETBROKER, MQSERIES, or NULL.
Action	Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAFQD **DHBINTERVAL must be zero or in the range from 60 through 86400**
Explanation The only valid values for the destination DHBINTERVAL parameter are 0 or a value from 60 through 86400. 0 is the default.
Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAFQE **Destination {xxxxxxx} parameter DCLASS must be set to SAGTARG when parameter DHBINTERVAL contains a value in the range 60 - 86400**
Explanation The destination DCLASS parameter must be set to SAGTARG when the destination DHBINTERVAL parameter contains a value in the range 60 through 86400.
Action Check the parameter input, correct the error, and restart the Event Replicator Server.

ADAFQF **Destination {dddddddd} is defined with DSTATLOG=YES; it cannot be used with the subscription {sssssss}.**
Explanation The destination *dddddddd* has been defined with DSTATLOG=YES and has been linked to a subscription. However, a destination defined with DSTATLOG=YES cannot be specified in a subscription.
Action Either remove the link to the subscription or specify DSTATLOG=NO for a destination you would like to link to a subscription.

ADAFR0 **Database {dbid} is running without replication enabled**
Explanation The Event Replicator Server attempted to communicate with a database defined via a subscription but found the database is running with a REPLICATION=NO setting.
 This message appears with message [ADAFR1](#).
Action Execution continues. No replication will occur for the database.

ADAFR1 **Suspending communication with database {dbid}**
Explanation Communication with the database identified in the message (*dbid*) was suspended because the database is running with a REPLICATION=NO setting.
 This message appears with message [ADAFR0](#).
Action Execution continues. No replication will occur for the database.

ADAFR2 **Reptor could not notify destination {dest1} that {utilname} for DBID {dbid} ended, token {tkn}, subscription {subs1}**
Explanation An attempt failed to log a termination event for the utility named in the message (*utilname*) with the given token (*tkn*) to a destination (*dest1*) associated with the given subscription (*subs1*).
Action Execution continues. Increasing the value of the ADARUN LRPL parameter may alleviate the shortage.

ADAFR3	Starting replication cross-check for database {dbid}
Explanation	Replication cross-check processing has started for the database listed in the message (<i>dbid</i>).
Action	No action is required for this informational message.
ADAFR4	Replication cross-check completed for database {dbid}
Explanation	Replication cross-check processing completed for the database listed in the message (<i>dbid</i>).
Action	No action is required for this informational message.
ADAFR5	Format buffer validation started for database d{bid}
Explanation	Format buffer validation processing has started for the database listed in the message (<i>dbid</i>).
Action	No action is required for this informational message.
ADAFR6	Format buffer validation completed for database d{bid}
Explanation	Format buffer validation processing completed for the database listed in the message (<i>dbid</i>).
Action	No action is required for this informational message.
ADAFR7	No errors were found during replication cross-check for database {dbid}
Explanation	No errors were found during replication cross-check processing for the database listed in the message (<i>dbid</i>).
Action	No action is required for this informational message.
ADAFR8	Replication cross-check was not processed There are no databases connect to the Reptor
Explanation	Replication cross-check processing did not occur because there are no databases connected to the Event Replicator Server (Reptor).
Action	Connect databases to the Event Replicator Server and try again.

ADAFR9	Replication is not turned on for file {nnnnn}
Explanation	This message displays when an initial-state request is made for a file that does not have replication turned on. The file number (<i>nnnnn</i>) is given in the message.
Action	Turn replication on for the file in the source Adabas database.
ADAFRA	Rejecting connection attempt from Adabas DBID {dbid} The Adabas nucleus is running with ADA{vrs}/ARF{vrs}
Explanation	The Adabas or Event Replicator for Adabas version running in the Adabas nucleus is incompatible with the Adabas or Event Replicator for Adabas version running in the Event Replicator Server nucleus. The software level in the Event Replicator Server must be greater than or equal to the software level in the source nucleus.
Action	Analyze the use of the Adabas and Event Replicator Server nucleuses to determine which versions should be used on each. Then update the software as appropriate. Contact your Software AG technical support representative if you need assistance.
ADAFRB	Replay process with token {yyyyy} is being changed from synchronized mode to replay-only mode
Explanation	This message is printed when an error occurs in the Event Replicator Server, related to the SLOG file (for example, when the SLOG file is full) and the replay process. The token ID of the replay process is given in the message (<i>yyyyy</i>). When the error occurs, this message is printed, the replay process is changed from synchronized mode to replay-only mode, and transactions on the SLOG file for this replay process are scheduled for deletion from the SLOG file.
Action	No action is required for this informational message.
ADAFRE	{yyyy.mm.dd} {hh.mm.ss} A connection will be attempted {yyyy.mm.dd} {hh.mm.ss} with database {id}
Explanation	This message is printed as a result of the RPLCONNECT operator command (issued to an Event Replicator Server). The message is printed for each Adabas database for which the Event Replicator Server attempts a connection.
Action	No action is required for this informational message.
ADAFRF	{yyyy.mm.dd} {hh.mm.ss} No connection attempts will be made as a {yyyy.mm.dd} {hh.mm.ss} result of the RPLCONNECT request
Explanation	This message is printed as a result of the RPLCONNECT operator command (issued to an Event Replicator Server). The message is printed when no connection attempts will be made as a result of the RPLCONNECT operator command.
Action	Analyze the RPLCONNECT operator command you issued for invalid Adabas database IDs that might have been specified.

ADAFRG **Unable to send event logging information to destination {destination} due to replication pool shortage**

Explanation The Event Replicator Server was unable to acquire sufficient resources to notify the affected destination.

Action Execution continues. Increasing the value of the LRPL parameter may alleviate the shortage.

ADAFRH **{message-text}**

Explanation The message text for this message varies, as described in the following table:

Message Text	Explanation
Data found in SLOG for database-related input transactions	When the Event Replicator Server initialized, it found database-related input transactions from the Adabas nucleus logged on the SLOG system file.
The database-related input transactions on the SLOG system file contain only FCB/FDT data	This message may appear with the one above. When the Event Replicator Server initialized, it found database-related input transactions on the SLOG file that contained only FCB or FDT data. This indicates that no replicated input transactions are pending on the SLOG system file at the end of the last session.

Action No action is required for this informational message.

ADAFRI **LOGINPUTTRANSACTION is set to ALL or 1-99 and the SLOG system file is not loaded**

Explanation You have specified LOGINPUTTRANSACTION as ALL or an integer from 1 to 99, but an SLOG file has not been defined for the Event Replicator Server.

Action If you really want the LOGINPUTTRANSACTION parameter set to one of these values, define an SLOG file to the Event Replicator Server. For more information, read *Setting Up Subscription Logging*, in the *Event Replicator for Adabas Administration and Operations Guide*.

ADAFRJ **Use of SLOG for database-related input transactions turned on**

Explanation Use of the SLOG system file for storing and processing database-related input transactions from the Adabas nucleus has been turned on.

Action No action is required for this informational message.

ADAFRK	Use of SLOG for database-related input transactions turned off
Explanation	Use of the SLOG system file for storing and processing database-related input transactions from the Adabas nucleus has been turned off.
Action	No action is required for this informational message.
ADAFRL	Use of SLOG for database-related input transactions suspended
Explanation	Use of the SLOG system file for storing and processing database-related input transactions from the Adabas nucleus has been suspended. Messages printed prior to this message indicate why SLOG processing was suspended.
Action	Review earlier messages to determine the cause of the problem.
ADAFRM	Use of SLOG for database-related input transactions no longer suspended
Explanation	Use of the SLOG system file for storing and processing database-related input transactions from the Adabas nucleus is no longer suspended. This processing is no longer suspended when all database-related input transactions have been deleted from the SLOG system file.
Action	No action is required for this informational message.
ADAFRN	Use of SLOG for database-related input transactions disabled
Explanation	Use of the SLOG system file for storing and processing database-related input transactions from the Adabas nucleus has been disabled. This may occur when SLOG processing of the database-related input transactions is suspended and a subsequent error occurred while attempting to delete the transactions from the SLOG system file.
Action	Review earlier messages to determine the cause of the problem.
ADAFRO	One or more database-related input transactions found for database {dbid} file {nnnn} before the related FCB/FDT
Explanation	During Event Replicator Server initialization, one or more database-related input transactions were found on the SLOG system file for the database and file listed in the message, but the related FCB and FDT information is not on the SLOG system file (it should be the first transaction for the database and file combination). Additional messages will appear indicating that replication for the database and file combination has been deactivated.
Action	Contact your Software AG support representative for assistance.

ADAFRP	Input request {type:error} URBIRTOK: {token} URBIRNAM: {destination1} URBIDNAM: {destination2}
Explanation	<p>An error occurred while processing a destination open/close client request. The type of request (<i>type</i>) is given in the message. It is either "Open Destination" or "Close Destination". The kind of error that occurred (<i>error</i>) is also given in the message along with the eight-byte target application token (<i>token</i>), the reply destination name (<i>destination1</i>), and the name of the destination that was to be opened or closed (<i>destination2</i>). Possible <i>errors</i> that could be listed include:</p> <ul style="list-style-type: none"> ■ Storage shortage in RPL pool ■ URBIRNAM undefined/unusable ■ Different response destinations ■ Multiple URBI's -- diff tokens ■ Selection data not allowed ■ URBIARC/ACOD/WCOD not zero ■ URBIREs/RES1 not zero ■ Destination unknown or unusable ■ Unknown response destination ■ DBID/FNR not allowed ■ Initial state not allowed ■ Destination not unique ■ Subscription name not allowed ■ Transaction Seq # not allowed
Action	<p>If the error indicates an RPL storage pool shortage, consider increasing the value of the ADARUN LRPL parameter.</p> <p>If the error indicates an Invalid unused URBI field(s), read about <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference Guide</i> and read about the URBI fields required for destination open and close requests. Any fields not listed in the description must be initialized to spaces (if they are defined as character format fields) or must be initialized to binary zeroes.</p> <p>If problems persist, contact your Software AG support representative for assistance.</p>
ADAFRQ	Both the {{insert and update update and insert}} attempts failed No further attempts will be made to {{insert update}} this record
Explanation	<p>This message appears when DAERROR=ALTACTION or the resend flag is set and one of the following occurs:</p> <ul style="list-style-type: none"> ■ An insert is processed and the record already exists. An attempt to update the record is performed, but fails with a RSP113; no further attempts are then made to insert or update the record.

- An update is processed and the record does not exist. An attempt to insert the record is performed, but fails with a RSP113; no further attempts are then made to update or insert the record.

This error may be caused when the ISN is larger than the MAXISN parameter setting in effect for the destination Adabas file.

Action Consider adjusting the MAXISN setting for the destination Adabas file. If the problem persists, contact your Software AG support representative for assistance.

ADAFRR Destination {dest-name} will not be opened

Explanation The destination identified in the message (*dest-name*) will not be opened. The destination was either defined with parameter DOPEN=NO or defined with parameter DOPEN=GLOBAL and the global parameter GOPEN was set to "NO".

Action No action is required for this informational message.

ADAFRT The following files in database {dbid} have replication turned on for this Reptor but are currently inactive: File {fn}

Explanation This message displays a list of files contained in an Adabas nucleus that are defined to the Event Replicator but are currently inactive (replication has been turned off for these files).

Action No action is required for this informational message. The files listed will not be replicated until they are reactivated. For information on activating database files for replication, read *Activating the Event Replicator Databases and Files* in the *Event Replicator for Adabas Administration and Operations Guide*.

ADAFRU Input queue {qname} will not be opened

Explanation The input queue identified in the message (*qname*) will not be opened. The input queue was either defined with the initialization parameter IQOPEN set to "NO" or it was defined with the initialization parameter IQOPEN set to "GLOBAL" and the global parameter GOPEN set to "NO".

Action No action is required for this informational message.

**ADAFRV Initial State {is-name} started
DBID = {dbid}, FNR = {fnr}, Initial-stateID = X'{hex-is-id}'**

Explanation This message is displayed by the Event Replicator for Adabas when processing starts for an initial-state request. It includes the database ID (*dbid*) and file number (*fnr*) the initial state requested. It also lists a unique ID (*hex-is-id*) that can be used to match the completion messages with the initial-state start messages. This is most beneficial when there are multiple initial-state processes running concurrently

Action No action is required for this informational message.

ADAFRW	Initial State {is-name} completed DBID = {dbid}, FNR = {fnr}, Initial-stateID = X'{hex-is-id}' Response = {rc}, Subcode = {sc}
Explanation	This message is displayed by the Event Replicator for Adabas when an initial-state request completes. It includes the database ID (<i>dbid</i>) and file number (<i>fnr</i>) the initial state requested. It also lists a unique ID (<i>hex-is-id</i>) that can be used to match the completion messages with the initial-state start messages. This is most beneficial when there are multiple initial-state processes running concurrently
Action	If the response code and subcode are non-zero, then they should be reviewed for the cause and corrected. The initial-state process should then be restarted. If they are zero, no action is required for this message.
ADAFRX	SLOG turned on for destination {dest-name}
Explanation	SLOG processing has been turned on for the destination listed in the message (<i>dest-name</i>).
Action	No action is required for this informational message.
ADAFRY	SLOG turned off for destination {dest-name}
Explanation	SLOG processing has been turned off for the destination listed in the message (<i>dest-name</i>).
Action	No action is required for this informational message.
ADAFS0	ETBBROKER destination input queue {<name>} connected with single conversation mode set ETBBROKER Token = ETBBROKER Userid =
Explanation	These messages are displayed whenever an ETBBROKER destination has DETBSCONV=YES or an ETBBROKER input queue has IQETBSCONV=YES. It displays the values used for the ETBBROKER API token and user ID fields.
Action	No action is required for this informational message.
ADAFS1	Destination/Input Queue: {xxxxxxx} has multi conversation mode data waiting to be consumed, switch to single conversation mode not allowed
Explanation	This error can occur whenever an ETBBROKER destination has DETBSCONV=YES or an ETBBROKER input queue has IQETBSCONV=YES. It indicates there are multi conversation mode messages waiting to be consumed from the last session and that switching to single conversation mode is not allowed until the pending messages have been consumed.

Action Bring up the Event Replicator Server nucleus with the input queue that is to receive these messages in multi conversation mode and consume the remaining messages. ADAMTR can also be used to consume them.

ADAFSA {dbid} DB ASSO threshold reached

Explanation The Adabas Associator threshold set by the ASSOTHRESHOLD parameter has been reached. This message warns you so you can address the space issues before they become a serious problem for your Event Replicator Server.

Action No action is required for this warning message. However, you might want to evaluate the Adabas Associator space usage and either increase the amount of space available for the Associator files or adjust your Adabas processing so less space is required. Alternatively, or in addition to the above adjustments, you might want to alter the setting of the ASSOTHRESHOLD parameter.

ADAFSB {dbid} DB DATA threshold reached

Explanation The Adabas Data threshold set by the DATATHRESHOLD parameter has been reached. This message warns you so you can address the space issues before they become a serious problem for your Event Replicator Server.

Action No action is required for this warning message. However, you might want to evaluate the Adabas Data space usage and either increase the amount of space available for the Data files or adjust your Adabas processing so less space is required. Alternatively, or in addition to the above adjustments, you might want to alter the setting of the DATATHRESHOLD parameter.

ADAFSC {dbid} DB SLOG AC threshold reached

Explanation The SLOG address converter (AC) threshold set by the SLOGACTHRESHOLD parameter has been reached. This message warns you so you can address the space issues before they become a serious problem for your Event Replicator Server.

Action No action is required for this warning message. However, you might want to evaluate the SLOG address converter space usage and either increase the amount of space available for the address converter or adjust your Event Replicator for Adabas processing so less space is required. Alternatively, or in addition to the above adjustments, you might want to alter the setting of the SLOGACTHRESHOLD parameter.

ADAFSD {dbid} DB SLOG NI threshold reached

Explanation The SLOG normal index (NI) threshold set by the SLOGNITHRESHOLD parameter has been reached. This message warns you so you can address the space issues before they become a serious problem for your Event Replicator Server.

Action No action is required for this warning message. However, you might want to evaluate the SLOG NI space usage and either increase the amount of space available for the normal index or adjust your Event Replicator for Adabas processing so less space is

required. Alternatively, or in addition to the above adjustments, you might want to alter the setting of the SLOGNITHRESHOLD parameter.

ADAFSE	{dbid} DB SLOG UI threshold reached
Explanation	The SLOG upper index (UI) threshold set by the SLOGUITHRESHOLD parameter has been reached. This message warns you so you can address the space issues before they become a serious problem for your Event Replicator Server.
Action	No action is required for this warning message. However, you might want to evaluate the SLOG UI space usage and either increase the amount of space available for the upper index or adjust your Event Replicator for Adabas processing so less space is required. Alternatively, or in addition to the above adjustments, you might want to alter the setting of the SLOGUITHRESHOLD parameter.
ADAFSF	{dbid} DB SLOG DS threshold reached
Explanation	The SLOG Data Storage (DS) threshold set by the SLOGDSTHRESHOLD parameter has been reached. This message warns you so you can address the space issues before they become a serious problem for your Event Replicator Server.
Action	No action is required for this warning message. However, you might want to evaluate the SLOG DS space usage and either increase the amount of space available for Data Storage or adjust your Event Replicator for Adabas processing so less space is required. Alternatively, or in addition to the above adjustments, you might want to alter the setting of the SLOGDSTHRESHOLD parameter.
ADAFSG	{dbid} DB ASSO used {nnn}% {dbid} DB ASSO allocated cylinders {nnn,nnn,nnn,nnn} {dbid} DB ASSO unused cylinders {nnn,nnn,nnn,nnn} {dbid} DB DATA used {nnn}% {dbid} DB DATA allocated cylinders {nnn,nnn,nnn,nnn} {dbid} DB DATA unused cylinders {nnn,nnn,nnn,nnn}
Explanation	The Adabas Associator and Data Storage file space usage statistics are listed in the message.
Action	No action is required for this warning message. However, since this message is issued when one or more space thresholds have been reached, we recommend that you evaluate the Adabas Associator and Data Storage space usage and either increase the amount of space available for the files or adjust your Adabas processing so less space is required.

ADAFSH {dbid} SLOG AC used {nnn}%
 {dbid} SLOG AC MAXISN {n,nnn,nnn,nnn}
 {dbid} SLOG AC TOPISN {n,nnn,nnn,nnn}
 {dbid} SLOG AC MINISN {n...,nnn}
 {dbid} SLOG AC extents nnn
 {dbid} SLOG NI used {nnn}%
 {dbid} SLOG NI allocated cylinders {nnn,nnn,nnn,nnn}
 {dbid} SLOG NI unused cylinders {nnn,nnn,nnn,nnn}
 {dbid} SLOG NI extents {nnn}
 {dbid} SLOG UI used {nnn}%
 {dbid} SLOG UI allocated cylinders {nnn,nnn,nnn,nnn}
 {dbid} SLOG UI unused cylinders {nnn,nnn,nnn,nnn}
 {dbid} SLOG UI extents {nnn}
 {dbid} SLOG DS used {nnn}%
 {dbid} SLOG DS allocated cylinders {nnn,nnn,nnn,nnn}
 {dbid} SLOG DS unused cylinders {nnn,nnn,nnn,nnn}
 {dbid} SLOG DS available cylinders {nnn,nnn,nnn,nnn}
 {dbid} SLOG DS extents {nnn}

Explanation The SLOG Associator and Data Storage file space usage statistics are listed in the message. Note that the MINISN value is only written when MINISN is greater than one.

Action No action is required for this warning message. However, since this message is issued when one or more space thresholds have been reached, we recommend that you evaluate the SLOG Associator and Data Storage space usage and either increase the amount of space available for the files or adjust your Event Replicator Server processing so less space is required.

ADAFSI {dbid} SLOG check executed, no thresholds reached.

Explanation The Adabas and SLOG Associator and Data Storage file space usage have been checked, but none of the usage thresholds have been reached. This message only appears once after the first threshold interval has passed and if no thresholds have been reached.

Action No action is required for this informational message.

ADAFSJ **ADASAF must be enabled to replicate a ciphered file**

Explanation In order to process ciphered files the Event Replicator for Adabas must be running with ADASAF and the external security system RACF.

Action The related source dbid/file will be deactivated.

ADAFSK	No cipher or password defined in security system
Explanation	The security data could not be obtained from the external security system for replication of security protected Adabas records (cipher key).
Action	The related source dbid/file will be deactivated.
ADAFSL	DB/file not defined in security system
Explanation	The related resource for the source dbid/file was not defined in the external security system (cipher key).
Action	The related source dbid/file will be deactivated.
ADAFSM	External security system is not RACF
Explanation	Only the external security system RACF can deliver security data for replication of security protected data.
Action	The related source dbid/file will be deactivated.
ADAFSN	External security system error {tffrss}
Explanation	The external security system returned an error for a security data request with the hexadecimal error information: <i>tt</i> = R15 return value, <i>cc</i> = RACROUTE code, <i>rr</i> = return code, <i>ss</i> = reason code.
Action	The related source dbid/file will be deactivated.
ADAFSP	DBID {dbid} FNR {file-number} may not be replicated The file is defined with cipher code
Explanation	Additional message printed before detailed error messages ADAFSK through ADAFSN are given.
ADAFSR	DBID {dbid} FNR {file-number} Adabas target
Explanation	Additional message printed before detailed error message ADAFSN when trying to obtain security data from the external security system for the specified Adabas target file.

26

ADAH* - Dump Formatter Status Messages

These are general status messages that describe current operating status of the dump formatting facility.

ADAH01	{dbid} Dump format called
Explanation	Issued by the Adabas extended error recovery facility at the point where dump formatting begins. Displayed on the console and written to DD/PRINT.
ADAH02	{dbid} Dump format completed
Explanation	Issued by the Adabas extended error recovery facility at the point where dump formatting terminates. Displayed on the console and written to DD/PRINT.

27

ADAI* - ADAIOR System Messages



Note: Although not considered console messages, those preceded by an asterisk (*) are also displayed on the system console.

ADAI01 {data set} {count} {READS | WRITES}

Explanation A sequential data set is closed.

The read count is shown when a sequential input data set is closed. The write count is shown when a sequential output data set is closed.

ADAI02 GETMAIN {stor-req} ({source})
GETMAIN {stor-req} {stor-avail} ({source})

Explanation The first form of the message is written whenever memory is dynamically acquired and the requested memory is available.

The second form of the message is written whenever memory is dynamically acquired and less than the requested memory is available.

In the messages, *stor-req* is the amount of memory requested, *stor-avail* is the amount of memory available, and *source* (printed only under z/VSE) is the source of the memory (GETVIS, COMREG, ADABUF).

ADAI03 {data set} | {physical-file-name} {count_r} reads
{data set} | {physical-file-name} {count_w} writes
{data set} | {physical-file-name} {count_f} format writes

Explanation A direct access data set is closed.

The *physical-file-name* indicates that the file was opened using dynamic allocation.

The read count *count_r* and write count *count_w* are shown.

The write count *countw* is the count of update writes only. If any format writes were issued, the format write count is shown in *countf*.

ADAI04 **{count} read errors**
{count} write errors

Explanation The message is written immediately following message ADAI03 when a direct access data set for which there had been read and/or write errors is closed.

ADAI05 **{count} reads using zHPF**
{countw} writes using zHPF

Explanation **Note:** This message is available in z/OS systems only.

This message is written at data set close following message ADAI03 when a direct access data set used zHPF channel programs for reads or writes.

This message is only generated when the zHPF read and write counts differ from the read and write counts in the preceding ADAI03 message.

Action No action is required for this informational message.

ADAI06 **{count} retries using ECKD**

Explanation **Note:** This message is available in z/OS systems only.

This message is written at data set close following message ADAI03. If it was necessary to retry any zHPF I/O requests using an ECKD channel program (for instance because zHPF became unavailable on the operating system), the retry count is supplied.

Action No action is required for this informational message.

ADAI20 **{dbid} dataset {physical-file-name} DD: {link-name}**

Explanation An I/O error occurred on a file opened using dynamic allocation. This message appears immediately after the [ADAI21](#) message.

ADAI21 **{dbid} IO error DD {link-name} DSN {file-name}**
RABN {bad-rabn}({start-rabn}) {oper} from {start-num} Num {num-rabn}
IOBA {ioba} CCWA {ccwa} CC {ccbs} CSW {csw} SNS {sns}
SYS {lu} IEDB {iedb} ADDR {ccw-addr} CMD {ccw-cmd} IDA {ida-data} DATA
{ccw-data}

Explanation IBM platforms only. This message occurs when a disk I/O error is reported back to ADAIOR by the operating system.

The first 3 lines of the message are sent to the console and DDPRINT. Subsequent lines are sent to DDPRINT only.

The message variables and their meanings are:

Variable	Description
<i>bad-rabn</i>	The actual failing RABN.
<i>ccbs</i>	Communications bytes from the communications control block.
<i>ccwa</i>	CCW address of failing I/O.
<i>ccw-addr</i>	The CCW address.
<i>ccw-cmd</i>	The CCW data.
<i>ccw-data</i>	Up to 16 bytes of data pointed to by the CCW.
<i>csw</i>	Channel status from the channel status word (CSW).
<i>dbid</i>	Database ID
<i>file-name</i>	The physical file name of the data set.
<i>ida-data</i>	Indirect access address of CCW data.
<i>iedb</i>	The I/O error data block (z/OS only)
<i>ioba</i>	I/O control block address for failing I/O.
<i>link-name</i>	The DD name (z/OS) or DLBL name (VSE) of the data set .
<i>lu</i>	The logical unit where the failure occurred (z/VSE only).
<i>num-rabn</i>	The number of RABNs for this part of the failing I/O operation.
<i>oper</i>	The type of operation being performed when the failure occurred as follows: Read, Write, or Format
<i>sns</i>	Additional sense byte data.
<i>start-num</i>	The start RABN for this part of the failing I/O operation.
<i>start-rabn</i>	The start RABN of the failing I/O operation.

For more information on CCW, CSW and sense data, please refer to the relevant IBM publication.

Action

Use the information provided by the message to locate a possible hardware failure. Keep the information and any dumps for later use.

If no hardware failure occurred, please contact your Software AG technical support representative.

ADAI22

ADAIOR Trace table: --> is current entry

Explanation

The ADAIOR trace table has been activated and printed.

ADAI23 **{dbid} {job-name} abend code {code}**

Explanation z/VSE and BS2000 systems only. ADAIOR is asked to abend a job. A dump is normally also provided. The message values are:

dbid	database ID
code	the abend code (refer to the abend code descriptions in chapter 4).
job-name	the z/VSE job name or BS2000 program name.

ADAI24 **{dbid} Ready for operator communication**

Explanation SYSLOG displays this message once operator communications has been requested by the operator with the z/VSE MSG command. The value *dbid* is the database ID.

Action Enter a valid Adabas command.

ADAI26 **{dbid} {job-name} completion code {code}**

Explanation BS2000 systems: This message displays the normal termination return code. If a nonzero abend code is displayed, the BS2000 program task switch 10 is set on.

z/VSE systems: The end-of-job (EOJ) "RC=(RX)" sets the return code for the operating system. The message provides the database ID (dbid), job name, and return code.

Action BS2000 systems: If job variables are installed, the abend code is passed to the controlling job variable. A job variable assigned with link "*ADA" is set with the following information:

program name (8 bytes) completion code (4 bytes) error number (5 bytes) Adabas response code (5 bytes)

z/VSE systems: For a nonzero abend code, refer to the description in chapter 4. If the DUMP option was specified, refer to the resulting dump, if needed, to determine the cause of the abend. The job step is terminated.

ADAI27 **{dbid} Timer interval exceeds maximum allowed**
{dbid} Reset to maximum

Explanation A timer request was issued that exceeds the maximum allowed by the operating system.

Action Reset the interval to the maximum allowed by your operating system.

ADAI29 **Oper cmd: {command}**
Explanation An operator command has been entered. The text of the operator command is shown in *command*.
Action No action is required for this informational message.

ADAI30 **{file-name} {number} tracks formatted**
Explanation ADAIOR has completed formatting for a direct-access file.

ADAI31 **{dbid} Opening tape file {file-name} SYS{nnn}={cuu}**
Explanation **Note:** This message is available in z/VSE systems only.

This SYSLOG message means that a tape file was opened. Meanings of the message fields are:

<i>dbid</i>	Adabas database
<i>file-name</i>	filename of the input/output file opened
<i>nnn</i>	z/VSE logical unit ID
<i>cuu</i>	physical address of the selected drive

ADAI32 **{dbid} Internal error - function {func-name} error {error}**
Explanation An internal error has occurred.
Action Make a note of all recent messages, and contact your Adabas support representative.

ADAI34 **Write to Operator failed - Reason Code {nnnnnnnn}**
Explanation A write to operator (WTO) request has returned a non-zero response code *nnnnnnnn*.
Following the ADAI34 message, the message which caused the WTO failure is written to DDPRINT as normal, and processing continues.
Action No action is required for this warning message. However, the user is advised to check the system console log for error messages issued by z/OS relating to WTO problems.

ADAI35 **zHPF channel program error – retrying I/O in ECKD mode**
Explanation **Note:** This message is available in z/OS systems only.
An I/O error has been detected for a zHPF channel program. The zHPF I/O is retried as a non-zHPF I/O and no further zHPF I/O will be attempted on this file extent during the job step.

This message is followed by message [ADAI41](#).

Action No action is required for this informational message.

ADAI39 Fixed {1 MB | 2 GB} large page allocation failed --
 {not authorized | not available | not supported}
 {R15={nnnnnnnn} R0={nnnnnnnn}}

Explanation An attempt to allocate storage using fixed one-megabyte or two-gigabyte large pages failed. One of three possible reasons is listed in the message:

Reason	Description
not authorized	The job was not authorized. Large page allocation requests require APF-authorization.
not available	Large pages are not available on your system.
not supported	Large pages not supported by your system.

When "{R15=nnnnnnnn R0=nnnnnnnn}" is shown in the message, it indicates that an unexpected return code was received from the z/OS IARV64 service.

Action No immediate action is necessary, as a storage allocation not using large pages will be attempted instead.

Action may be required to prevent this warning message from appearing when the job is next run:

- If the message indicates that the job was not authorized, ensure when rerunning the job that it is APF-authorized.
- If your system does *not* support large pages, do not use the ADARUN parameter causing the attempt to allocate using large pages. Remove it from the startup JCL of the job.
- If your system *does* support large pages of the type requested, consider increasing the number of fixed large pages specified for your operating system using the LFAREA parameter in PARMLIB member IEASYSxx. Contact your system administrator for assistance. For more information, read your IBM *MVS Initialization and Tuning* documentation.

ADAI40 zHPF unavailable – retrying I/O in ECKD mode

Explanation **Note:** This message is available in z/OS systems only.

An I/O error has been detected for a zHPF channel program, because zHPF is no longer available. The zHPF I/O is retried as a non-zHPF I/O and no further zHPF I/O will be attempted on any file until after message [ADAI42](#) is issued.

This message is followed by message [ADAI41](#).

Action No action is required for this informational message.

ADAI41 IO Retry DD {link-name} DSN {file-name}
 RABN {bad-rabn}({start-rabn}) {oper} from {start-num} Num {num-rabn}
 IOBA {ioba} TCWA {tcwa} CC {ccbs} CSW {csw} SNS {sns}
 IEDB {iedb} TCW {tcw}

Explanation **Note:** This message is available in z/OS systems only.

This message occurs when a disk I/O error on a zHPF channel program is reported back to ADAIOR by the operating system. Message ADAI41 is issued immediately following [ADAI35](#) or [ADAI40](#).

If ADAI41 is issued following [ADAI40](#), only the first three lines of message ADAI41 are generated. The first three lines of the message are sent to the console and DDPRINT. Subsequent lines are sent to DDPRINT only.

The message variables and their meanings are:

Variable	Description
<i>bad-rabn</i>	The actual failing RABN.
<i>ccbs</i>	Communications bytes from the communications control block.
<i>csw</i>	Channel status from the channel status word (CSW).
<i>dbid</i>	Database ID
<i>file-name</i>	The physical file name of the data set.
<i>ida-data</i>	Indirect access address of CCW data.
<i>iedb</i>	The I/O error data block (z/OS only)
<i>ioba</i>	I/O control block address for failing I/O.
<i>link-name</i>	The DD name of the data set.
<i>num-rabn</i>	The number of RABNs for this part of the failing I/O operation.
<i>oper</i>	The type of operation being performed when the failure occurred as follows: Read or Write
<i>sns</i>	Additional sense byte data.
<i>start-num</i>	The start RABN for this part of the failing I/O operation.
<i>start-rabn</i>	The start RABN of the failing I/O operation.
<i>tcw</i>	The TCW, TCCB and TIDAL data for the I/O.
<i>tcwa</i>	TCW address of failing I/O.

For more information on TCW, CSW and sense data, please refer to the relevant IBM publication.

Action When preceded by message [ADAI40](#), no further action is required.

When preceded by message [ADAI35](#), use the information provided by the message to locate a possible hardware failure. Keep the information and any dumps for later use.

If no hardware failure occurred, please contact your Software AG technical support representative for assistance.

ADAI42 zHPF enabled for I/O requests on supported devices

Explanation **Note:** This message is available in z/OS systems only.

zHPF has been enabled on the operating system. I/O to data sets opened in zHPF mode, on devices which support zHPF, will now use zHPF channel programs.

This message is only issued after a previous **ADAI40** message.

Action No action is required for this informational message.

ADAI44 Storage at [[address]] length [{length}] {{is | is not } backed by fixed 1MB large pages | {is | is not } backed by fixed 2GB large pages | is backed by pageable 4KB pages}

Explanation A 64-bit virtual storage area was allocated with the address and length indicated in the message.

Different message endings appear using this message ID, depending on the type of storage requested and the type of storage allocated. The following table lists the possible messages, their cause, and recommended actions you can take when they occur.

Message Ending	Description	Action
"is backed by fixed 1MB large pages"	Storage backed by fixed 1M large pages was requested via ADARUN parameters; 1M large pages are successfully being used to back the storage.	No action is required for this informational message.
"is not backed by fixed 1MB large pages"	Storage backed by fixed 1M large pages was requested via ADARUN parameters, but this request was not successful. Either the system does not support fixed 1M large pages or insufficient fixed 1MB large pages were available. Instead, the allocated storage is backed by pageable 4K pages.	Consider the following actions: <ul style="list-style-type: none"> ■ If your system does <i>not</i> support large pages, do not use the ADARUN parameter causing the attempt to allocate using large pages. Remove it from the startup JCL of the job. ■ If your system <i>does</i> support large pages of the type requested, consider increasing the number of fixed large pages specified for your operating system using the LFAREA parameter in PARMLIB member IEASYSxx. Contact your system administrator for

Message Ending	Description	Action
		assistance. For more information, read your IBM <i>MVS Initialization and Tuning</i> documentation.
"is backed by fixed 2GB large pages"	Storage backed by fixed 2G large pages was requested via ADARUN parameters; 2G large pages are successfully being used to back the storage.	No action is required for this informational message.
"is not backed by fixed 2GB large pages"	Storage backed by fixed 2G large pages was requested via ADARUN parameters, but this request was not successful. Either the system does not support fixed 1G large pages or insufficient fixed 2GB large pages were available. Instead, the allocated storage is backed by pageable 4K pages.	Consider the following actions: <ul style="list-style-type: none"> ■ If your system does <i>not</i> support large pages, do not use the ADARUN parameter causing the attempt to allocate using large pages. Remove it from the startup JCL of the job. ■ If your system <i>does</i> support large pages of the type requested, consider increasing the number of fixed large pages specified for your operating system using the LFAREA parameter in PARMLIB member IEASYSxx. Contact your system administrator for assistance. For more information, read your IBM <i>MVS Initialization and Tuning</i> documentation.
"is backed by pageable 4KB pages"	Storage backed by pageable 4K pages was requested; pageable 4K pages are successfully allocated. If 1M or 2G large pages were requested, this message appears on the operator console and on DDPRINT. If 4K pages were requested, this message appears on DDPRINT only.	No action is required for this informational message.

Action

Refer to the specific message ending in the table above to determine what action, if any, is necessary.

ADAI51 {dbid} Adabas PAM BS2000 I/O error {err-num} in file {file-name}

Explanation BS2000 systems only: A PAM I/O error occurred on DASD file *file-name*. This message is issued in conjunction with message [ADAI52](#).

- *err-num* is the DMS error code. The explanation for the error can be found out using the following online command:

```
HELP-MESSAGE DMS<err-num>
```

- *file-name* is the file name in which the error occurred.

Action Use the command /HELP-MESSAGE DMS<err-num> to describe the I/O error.

ADAI52 RABN={error-rabn} ({start-rabn}) OP={op-code} ST={fecb}

Explanation BS2000 systems only: A PAM I/O error occurred on DASD file *file-name*. This message is issued in conjunction with message [ADAI51](#).

- *error-rabn* is the RABN where the error occurred.
- *start-rabn* the RABN where the operation began.
- *op-code* comprises one or more of the following operation code values:

X'80'	READ read operation
X'40'	WRITE write operation
X'20'	FORMAT format operation
X'10'	ENDOFTRK read or write to track end
X'08'	RENOWRT no write if read-only nucleus

- *fecb* is the FECB block status used for the I/O error, and comprises the SENSE, GERAETE (device), ABM and NPA fields. For more information, contact your Software AG technical support representative.

ADAI53 {dbid} Adabas BS2000 I/O error {err-num} in file {file-name}

Explanation BS2000 systems only: This is the first part of an I/O error message. The message is followed by message ADAI54. The *err-num* is a BS2000 error code. The *file-name* shows the link name for the failed data set.

Action Use the command /HELP-MESSAGE DMS <err-num> to describe the I/O error.

ADAI54 **{dbid} Exit={value}, status={fcb-status}**
Explanation BS2000 systems only: The *value* is the error exit byte of the BS2000 FCB.
fcb-status is a six-byte status containing the following:

byte 0:	device byte
bytes 1-3:	sense bytes 1-3
byte 4:	executive flag byte
byte 5:	count of processed PAM pages

ADAI55 **{dbid} Solsig error R15={ret-code}, post-code={post-code}**
Explanation BS2000 systems only: The system received an invalid return code (*ret-code*) or post code (*post-code*) when issuing a Solsig WAIT supervisor call (SVC). *dbid* is the database ID.
Action Refer to the BS2000 System Macros manual for information about the return code.

ADAI56 **{dbid} Unexpected RC {ret-code} from {macro}**
Explanation BS2000 systems only: The data set assigned to SYSDTA is either a non-SAM/V data set, or it contains records longer than 80 bytes. The value *macro* is RDATA.

ADAI57 **{dbid} Unable to load ADAIOS**
Explanation An attempt to load ADAIOS failed. Check your LOADLIB and your partition sizes; either the partition is too small or the ADAIOS member is missing from the LOADLIB.

ADAI5X **{dbid} Subtask {name} started with TSN {xxxx}**
Explanation The subtask listed in the message (*name*) started with the TSN shown in the message (*xxxx*).
Note: This message occurs in BS2000 environments only.
Action No action is required for this informational message.

ADAI62 **{dbid} Allocation error - type {x} retcode {ret-code}**
{dbid} subcode {subcode} dataset {physical-file-name}
Explanation An attempt to allocate a file dynamically failed. *x* indicates the request type: A (allocation); D (deallocation); or I (information retrieval). The *ret-code* and *subcode* display the error code returned from the operating system.
Action Interpret the error code for your system and respond accordingly.

ADAI64 **{dbid} {File {ddname} | Dataset {dsn}} is being opened in mode {mode}**
Block size {blksize} RABN range {start-RABN} to {end-RABN}
{File {ddname} | Dataset {dsn}} is encrypted

Explanation The file (*ddname*) or dynamically allocated data set (*dsn*) is being opened in the mode (*mode*) given in the message (CKD, ECKD or zHPF). The file resides on a storage control device that supports count key data (CKD), extended count key data (ECKD) or high performance FICON (zHPF) channel commands. Adabas generates channel programs accordingly.

 The block size (*blksize*) of the data set is given in the message. It contains the blocks with numbers *start-RABN* through *end-RABN*.

 If the dataset is encrypted, an additional message line is generated to indicate this.

Action No action is required for this informational message.

ADAI65 **{dbid} EXCPVR is [NOT] being used for this run [in ESA64 mode]**

Explanation z/OS systems only: If ADAIOR is loaded from an APF-authorized library concatenation, and ADARUN is linked with the SETCODE AC(1) statement, ADAIOR then performs the channel program translation/page fixing. If "NOT" appears in the message, ADAIOR will not perform channel program translation and page-fixing to improve the performance of I/O operations.

 If EXCPVR is in use, and the operating system and processor support the allocation of real storage above the 2 gigabyte line, "in ESA64 mode" appears in the message.

Action None required. This message is for your information only. If the message says that EXCPVR is not being used, but you have set up ADAIOR in an APF-authorized library and linked ADARUN with SETCODE AC(1) to use EXCPVR, refer to the Adabas Installation documentation for more information.

ADAI66 **{dbid} ADAIO2 {error-code} {message}**

Explanation The *error-code* is the Fujitsu Technology Solutions macro return code. The *message* is one of the following produced by the database main task while attempting to start a subtask:

```

enabling subtask COM memory
Enabling wait on contingency
Enabling Wait
Entering Job
Get parameter memory
Get submit file
Opening submit file
SET FILE LINK
STXIT call error
```

The main task may not be accessible or has terminated.

Action Contact your Software AG technical support representative.

ADAI67 {dbid} ADAI2S {error-code} {message}

Explanation The *error-code* is the Fujitsu Technology Solutions macro return code. The *message* is one of the following produced while attempting to start a subtask in the subtask startup module:

Message	Description
no mother task common memory	The memory pool containing data from the mother task is not accessible. The mother task has timed out or terminated.
no enable to mother's event	Mother task-to-subtask communication cannot be established. The mother task has probably terminated.
cannot share mother's low memory	The subtask parameter address area cannot be accessed.
cannot load subtask <subtask-name>	An error occurred while loading the subtask. Check the DDLIB and BLSLIB _{nn} link names for libraries containing the subtask name (<i>subtask-name</i>) given in the message.
cannot post mother program	Communication with the mother task is no longer possible. The mother task has probably terminated.
STXIT definition error	A system error occurred while establishing the ESTAE(STXIT) exit for the subtask. Check the system resources.

ADAI68 {dbid} ADAIO2 {message}

Explanation **Note:** This message appears in BS2000 systems.

The *message* providing information about BS2000 subtasks is one of the following:

DISABLING SUBROUTINE subtask-number subtask-startname

The subtask with the number and startup name specified is being disabled.

SUBTASK POSTED RC: return-code

The subtask posted the specified return code.

Action If this message occurs because of regular disabling processing, such as through the use of the ADAEND command, no action is required.

If this message occurs because of an unexpected error, then either the additional message "SUBTASK POSTED RC: *return-code*" is printed or additional messages can be found in the subtask-specific protocol. In this case, contact your Software AG technical support representative for assistance.

ADAI69 ADALNK is running in {mode} mode

Explanation **Note:** This message appears in BS2000 systems.

ADALNK writes this message to tell you the mode it thinks it is running in where *mode* is one of the following:

BATCH/TIAM	batch or Fujitsu Technology Solutions as carrier
UTM/3GL/AMS	on UTM with an Assembler or 3rd generation language such as COBOL, C, FORTRAN, etc.
UTM/NATURAL	on UTM running Natural

Note: To suppress this message, set the B2CONFIG parameter in SSFB2C:
LNKMSG=NO

Action: No action is required for this informational message, although you can use this message for diagnosing errors.

ADAI6U File: {lllllll}, GCB Blksz {nnnnnnnnnn} > physical {mmmmmmmmmm}, decrease or format

Explanation BS2000 only: For ASSO or DATA containers, the declared size *nnnnnnnnnn* is larger than the physical size *mmmmmmmmmm* for the container on link name *llllllllll*. This happened after running the ADADBS INCREASE utility function or a wrong declaration of the size when the container was defined with the ADADEF utility. This can lead to I/O errors and database maintenance problems.

It is no longer possible to start the nucleus or run Adabas utilities other than the ADADBS, ADAFRM or ADAREP utilities.

Action: Either run the ADADBS DECREASE utility function with a size of *nnnnnnnnnn* - *mmmmmmmmmm* blocks or run the ADAFRM utility with FROMRABN=NEXT and a size of *nnnnnnnnnn* - *mmmmmmmmmm*.

ADAI6Y {file} DD{tttt}R{n }Device-Type 8f extension needs DEVICE=23{xx}
Explanation BS2000 only: An 8f device is required for the file named in the message (*file*). Other substitutions in the message are:

<i>tttt</i>	The Adabas component type. Possible values are "ASSO", "DATA", or "WORK".
<i>n</i>	The device number. Possible values range from "1" through "99".
<i>xx</i>	The valid 8f device type. Possible values range from "00" through "02".

Note: To avoid receiving this message, set the ADARUN ALLOW8F parameter to "Y".

Action: No action is required for this informational message, although you can use this message for diagnosing errors.

ADAI70 {DDCARD | DDKARTE} has invalid attribute {RECFM=x | LRECL=n }

Explanation **Note:** This message occurs only in z/OS environments.

During a request to open DDCARD or DDDRUCK, an invalid record format or record length has been detected. DDCARD and DDDRUCK are required to be in fixed record format (RECFM=F), with a record length of 80 bytes (LRECL=80).

Action: Correct the error and rerun the job.

ADAI71 Error {nn} writing console message type {x} length {nnnn}

Explanation An error has occurred processing a request to write a message to the console.

Action: Contact your Software AG technical support representative for assistance.

ADAI73 {dbid} Warning: {ddname} dataset {dsn}
 {dbid} has been added since nucleus start-up.
 {dbid} {ddname} is now required in the JCL of all nucleus and
 {dbid} utility jobs for this database.

Explanation The file or data set listed in the message (*ddname* or *dsn*) has been dynamically allocated and added to ASSO or DATA during this nucleus session. All subsequent jobs for this database need the added DD name (*ddname*) in the JCL.

This message is displayed at nucleus termination.

Action: Verify that the added data set has been included in the JCL for all nucleus and utility jobs for this database. If it has not, add appropriate JCL statements for the new data set to the jobs.

ADAI75	File {ddname} {add increase decrease} {requested detected} {nnnnn} {cylinders blocks} dataset {dsn}
Explanation	<p>This message appears when either of the following situations has occurred:</p> <ul style="list-style-type: none">■ The Adabas nucleus issued a request to add a new ASSO or DATA data set comprising the listed number of cylinders (<i>nnnnn</i>) or to increase the size of the final ASSO or DATA data set by the listed number of cylinders or blocks.■ An Adabas utility detected that a new ASSO or DATA data set comprising the listed number of cylinders (<i>nnnnn</i>) has been added or the size of the final ASSO or DATA data set has been increased by the listed number of cylinders or blocks.■ The Adabas nucleus issued a request to decrease the size of ASSO or DATA by the listed number of cylinders or blocks. <p>For an add request, the data set name requested is also listed in the message (<i>dsn</i>).</p>
Action:	No action is required for this informational message.
ADAI76	File {ddname} {add increase decrease} activated
Explanation	<p>A previous request has been activated to add a new ASSO or DATA data set, increase the size of the final ASSO or DATA data set, or decrease the size of the ASSO or DATA data set. For an add or increase, the database is now ready to make use of the additional space. For a decrease, the areas of ASSO or DATA affected are no longer available to the database.</p> <p>The DD name (<i>ddname</i>) associated with the data set is given in the message.</p>
Action:	No action is required for this informational message.
ADAI77	File {ddname} {add increase decrease revoke activate} request failed rc {cc/rsn}
Explanation	<p>A request has failed to add a new ASSO or DATA data set, increase the size of the final ASSO or DATA data set, decrease the size of ASSO or DATA, or to revoke or activate a previous request. The DD name (<i>ddname</i>) of the data set, the return code (<i>cc</i>) and the reason code (<i>rsn</i>) are given in the message.</p>
Action:	If an add, increase or decrease request fails, the nucleus will continue running with the existing ASSO and DATA data sets and data set sizes. If a revoke or activate request fails, the nucleus will terminate abnormally (internal error).
ADAI78	File {ddname} {add increase decrease} request revoked
Explanation	<p>A previous request has been revoked to add a new ASSO or DATA data set, increase the size of the final ASSO or DATA data set. or decrease the size of ASSO or DATA. An add, increase. or decrease request may be revoked if an error occurs after the request has been issued. The DD name (<i>ddname</i>) associated with the data set is given in the message.</p>

	The nucleus will continue running with the existing ASSO and DATA data sets and data set sizes.
Action:	No action is required for this informational message.
ADAI79	Preparing to extend {ddname} by {nnnnn} {cylinders blocks}
Explanation	This message appears during initialization of a request to extend the ASSO or DATA data set by the listed size (<i>nnnnn</i>). The space requested is provided either in cylinders or in blocks.
	The DD name (<i>ddname</i>) associated with the final data set comprising the ASSO or DATA database component (containers) is given in the message.
Action:	No action is required for this informational message.
ADAI83	{ENQ DEQ} failed for {DDPRINT DDDRUCK} return code {nnnn} reason code {nnnn}
Explanation	Note: This message occurs only in z/OS environments.
	An ENQ or DEQ failure occurred when writing a print line to DDPRINT or DDDRUCK.
Action	Contact your Software AG technical support representative for assistance.
ADAI84	Write to {DDPRINT DDDRUCK} failed - {SYNAD exit driven abend code {nnnnnnnn} }
	All further writes to {DDPRINT DDDRUCK} will be ignored
Explanation	Note: This message occurs only in z/OS environments.
	An attempt to write to DDPRINT or DDDRUCK has failed. The job will continue processing normally, but no further writes to DDPRINT or DDDRUCK will be attempted.
	Note that, if the Adabas nucleus issues this message for DDPRINT, Adabas shutdown statistics on DDPRINT will be lost.
Action:	Investigate the cause of the error using the diagnostic information supplied in the message.
	If the error resulted from a file full condition, consider increasing the size of the file for future Adabas nucleus or utility jobs.

- ADAI85** **Resource Manager page-free request successful**
Explanation **Note:** This message occurs only in z/OS environments.
- A Resource Manager invoked during termination has successfully page-freed areas of page-fixed storage.
- This message may appear at termination following an abnormal end or cancel request.
- Action:** No action is required for this informational message.
-
- ADAI86** **Resource Manager page-free request unsuccessful**
Return code {nnnnnnnn} Reason code {nnnnnnnn}
Explanation **Note:** This message occurs only in z/OS environments.
- A Resource Manager invoked during termination has unsuccessfully attempted to page-free areas of page-fixed storage.
- This message may appear at termination following an abnormal end or cancel request.
- Action:** Contact your Software AG technical support representative.
- If a system abend occurred, ensure that the dump is available for problem diagnosis
-
- ADAI87** **Resource Manager input parameter invalid**
Explanation **Note:** This message occurs only in z/OS environments.
- A Resource Manager invoked during termination was unable to attempt to page-free areas of page-fixed storage.
- This message may appear at termination following an abnormal end or cancel request.
- Action:** Contact your Software AG technical support representative.
- If a system abend occurred, ensure that the dump is available for problem diagnosis
-
- ADAI91** **Pause Element services initialized for zIIP**
Explanation **Note:** This message occurs only in z/OS environments.
- Event management using z/OS Pause Elements has been successfully initialized. This message is issued only when Adabas is running with ADARUN parameter ZIIP=YES.
- Action:** No action is required for this informational message.

ADAI92	Pause Element services terminated {normally * atabend * for zIIP * by Resource Manager}
Explanation	<p>Note: This message occurs only in z/OS environments.</p> <p>Event management using z/OS Pause Elements has been successfully terminated. This message is only issued when Adabas is running with ADARUN parameter ZIIP=YES.</p> <p>This message may appear at termination following an abnormal end or cancel request.</p>
Action:	No action is required for this informational message.
ADAI93	Pause Element {allocate * deallocate * pause * release} error code {ret code/rsn code}
Explanation	<p>Note: This message occurs only in z/OS environments.</p> <p>Event management using z/OS Pause Elements has returned an error. The unexpected return code (<i>ret code</i>) and reason (<i>rsn code</i>) are shown. This message is only issued when Adabas is running with ADARUN parameter ZIIP=YES.</p> <p>This message may appear at termination following an abnormal end or cancel request.</p>
Action:	<p>If this message appears at termination following an abnormal end or cancel request, no action is required.</p> <p>In any other circumstances, save the JES log, DDPRINT output and any dump of the Adabas nucleus and Contact your Software AG technical support representative for assistance.</p>
ADAI94	Storage allocation warning - descriptor {xxxx}
Explanation	<p>A storage allocation request which might result in storage fragmentation has been detected. For example, a small amount of storage is being allocated on a page boundary.</p> <p>Additional information on the length and type of storage being allocated is supplied on DDPRINT.</p>
Action:	This is an informational message only, but, if it appears, users are requested to pass details of the message to their Software AG technical support representative for further assistance.

ADAI95

Storage allocation error - descriptor {xxxx} rc {nnnnnnnn}

Explanation

A storage allocation request has failed with reason code *nnnnnnnn*.

Additional information on the length and type of storage being allocated is supplied on DDPRINT.

Further error messages may appear or an abnormal end might occur as a consequence of the storage allocation failure.

Action:

Users should review the message text and attempt to correct the condition, for example by providing more virtual storage for the job.

If the message persists, users should contact their Software AG technical support representative for further assistance.

28

ADAJ* System Messages

ADAJ00 **Reading input for file {file-name} from library {lib-name} sublib {sublibrary} member {mem-name} . {mem-type} {count} cards**

Explanation z/VSE systems only: A valid "* SAGUSER" statement was found and is being used for ADARUN/Adabas utility input. ADARUN input has the file name "CARD", and utility input has the file name "KARTE". If the library and sublibrary are not specified on the * SAGUSER statement, the message indicates which of the current LIBDEF SOURCE libraries is being used for card input.

This message is controlled by the JBXIMSG parameter in the Adabas options table, as follows:

JBXIMSG=YES	display on console and print message
JBXIMSG=PRT	(default) print the message only
JBXIMSG=NO	neither display nor print the message

ADAJ99 **File {file-name} {req-type} error on library {lib-name} . {sublibrary} member {mem-name} . {mem-type} - {error-type}**

Explanation z/VSE systems only: A * SAGUSER statement containing file and member information was read, but an error occurred. ADARUN input has the file name "CARD", and utility input has the file name "KARTE". The librarian request type (*req-type*), is one of the following:

CLOSE	LIBDEF
GET	OPEN

The requested library (*lib-name*) and sublibrary (*sublibrary*) as specified on the *SAGUSER statement are provided in the message; if neither were specified, the message is an indication that the error occurred on the current LIBDEF SOURCE concatenation.

The *error-type* can be one of the following:

SUBLIBRARY NOT FOUND

An invalid sublibrary was specified.

LIBRARY NOT FOUND

An invalid library was specified. Ensure that the DLBL and EXTENT information was supplied for the library.

MEMBER NOT FOUND

The specified member does not exist on either the specified "lib-name.sublibrary" or in the libraries of the current LIBDEF SOURCE concatenation.

NO SUBLIB SPECIFIED

A library name without a sublibrary name was specified on the *SAGUSER card.

INVALID MEMBER TYPE

An invalid member type (PROC, OBJ, PHASE or DUMP) was specified.

RETCODE *ret-code* REASON *reason-code*

An internal librarian error occurred. Refer to the librarian feedback codes for more information. "ret-code" and "reason-code" are hexadecimal values.

This message is controlled by the JBXEMSG parameter in the Adabas options table, as follows:

JBXIMSG=YES	display on console and print message
JBXIMSG=PRT	(default) print the message only
JBXIMSG=NO	neither display nor print the message

Action Correct the job setup according to the information provided above, and rerun the job.

29 ADAK* System Messages

The following messages may appear when errors occur in the Adabas CICS and BS2000 TP monitor interface operations.

When CICS is started, the Adabas TP monitor component displays several informational or error messages on the system console. These often contain the addresses of key Adabas and CICS control blocks which are useful in problem determination.

- Be sure that the console messages indicate that the Adabas TRUE environment has been properly established.
- If an error message is produced, note the CICS EIBRESP, EIBRESP2, and EIBRCODE, which is displayed.
- Note any Adabas response code (ACBRSP) displayed by the TP monitor program at CICS startup.

ADAK001 **Installation messages will be written to queue {qname} file {dname}**
Explanation This message is produced when the following ACIOPT statement is coded:

```
ACIOPT ENTRY=GLOBAL,IMSGDEST=TDQ/BOTH,IMQNAME=qname
```

It provides the name of the transient data queue (qname) where installation messages are written and the DD name (z/OS) or DLBL name (z/VSE) of the file (dname) associated with the transient data queue

Action No action is required for this informational message.

ADAK01 {dbid} Unexpected return code {ret-code} in {function}

Explanation During BS2000 TP monitor interface operations, the return code (*ret-code*) given in the message occurred in one of the following functions and for the specified reason:

Function	Reason
TRGENAMP	enable memory pool (ENAMP) to target failed
IDTENAMP	enable memory pool (ENAMP) for IDT failed
DSOFEI	building of client hard wait (DSOFEI macro) failed
DPOFEI	Building of database hard post(DPOFEI) failed
TRGENAEI	enable event (ENAEI) failed for target
SOLSIG	SOLSIG macro failed
LNKLEVEL	the ADALNK and ADARER levels disagree (see the first and last bytes of "ret-code")
POSSIG	Post(POSSIG) to database failed

Action See the BS2000 Executive Macro documentation for an explanation of "ret-code".

ADAK02 Types of LOADLIB for ADALNK ({adalnk}) and ADARER mismatch

Explanation During BS2000 TP monitor interface operations, one module was loaded from an XS library and the other from an NXS library. NXS and XS components cannot be mixed.

This message is accompanied by the ADAK01 message.

The *adalnk* field of this message has the format *xx0000yy*, where *xx* is the level of the ADALNK and *yy* is the level of the ADARER (router). The value of *yy* must be greater than or equal to the value of *xx*.

If *yy* is less than *xx*, the IDT common memory where the ADARER is loaded has been created by and loaded from an older Adabas version. For example, if *xx*=83 and *yy*=81, an Adabas 61x ADALNK is using an Adabas 53x ADARER.

Action Check the Adabas library versions of the databases that are using the IDTNAME (the default is ADABAS5B) of your ADALNK.

Either upgrade databases using older Adabas libraries to the new version, or use different IDTNAMEs for different Adabas versions.

ADAK02A Could not get Router - Error - {err}

Explanation A BS2000 attempt to access the ID table memory pool given in the parameter file or module returned the error shown in the message (*err*), probably in the enable memory pool macro (ENAMP).

This error is accompanied by the user abend 680.

Action	Check the parameter file for the IDTNAME or DBTIDT value; otherwise check the BSCONFIG(ENVNAME), IDTABEL, or MDBIDT macros in SSFB2C.
ADAK02B	DB Table Get memory - Error - {err1} or DB Table Initialization Error - {err2}
Explanation	The DBID/ID table cannot be set up or accessed. This message is accompanied by user abend 678 or 679. This is usually an error in getting memory. The error code is from a BS2000 macro.
Action	Contact your Software AG technical support representative with the error code produced.
ADAK03	Parameter error
Explanation	During BS2000 TP monitor interface operations, the ADALNK parameter service detected a syntax error.
Action	Correct the syntax and rerun.
ADAK04	The following ADALNK ({adalnk}) are used for this run
Explanation	This is the header of the ADALNK parameter listing used during BS2000 TP monitor interface operations.
Action	No action is required.
ADAK040	Enabling {nnnn} Adabas task related user exits for Version 8 of ADACIC0
Explanation	Explanation: This message is produced at the beginning of ADACIC0 installation processing and identifies the number of TRUEs that ADACIC0 is attempting to install. The number (<i>nnnn</i>) is derived from the number of ENTRY=GROUP items that were coded in the ACIOPT module
Action	No action is required for this informational message.
ADAK041	Extracting global work area (GWA)
Explanation	During CICS PLTPI processing, CICS is determining the location of the global work area (GWA) for the command-level link components.
ADAK042	Initializing Adabas link routine
Explanation	During CICS PLTPI processing, an initialization call is being made to the command-level link routine.

ADAK043	Initializing Adabas SVC communication
Explanation	During CICS PLTPI processing, the Adabas SVC environment is being established.
ADAK044	Adabas v{vrs} CICS environment established
Explanation	During CICS PLTPI processing, the CICS environment needed for the command-level link components has been built.
ADAK045	T.R.U.E. {true-name} is in use by Adabas link routine {link-name}
Explanation	This message occurs during CICS PLTPI processing and displays the task-related user exit name and the Adabas link routine with which it is associated.
ADAK046	SVC number: {svc} default DBID: {dbid}
Explanation	This message occurs during CICS PLTPI processing and displays the default SVC number and DBID.
ADAK047	UB pool address: {aaaaaaaa} NUBS: {nnnnn}
Explanation	This message occurs during CICS PLTPI processing and displays the UB pool address and NUBS value.
ADAK048	User exit after (A) address: { {aaaaaaaa} NOT IN USE }
Explanation	This message occurs during CICS PLTPI processing and displays the address of the Adabas user exit 1 (user exit A in Adabas 7) or "not in use" if the user exit is not in use.
ADAK049	User exit before (B) address: { {aaaaaaaa} NOT IN USE }
Explanation	This message occurs during CICS PLTPI processing and displays the address of the Adabas user exit B or "not in use" if user exit B is not in use.
ADAK05	DDLNKPAR {open close} error: {err}
Explanation	During BS2000 processing an attempt to access the file associated with the link name DDLNKPAR failed. The error is a DMS error code.
Action	Perform a SHOW-FILE on the file associated with the linkname DDLNKPAR. If a DMS error occurs, perform HELP_MESSAGE DMSnnnn. This should help identify the problem.

ADAK050	Review exit address: { {aaaaaaaa} NOT IN USE }
Explanation	This message occurs during CICS PLTPI processing and displays the address of the Adabas Review exit, or "not in use" if the Adabas Review exit is not in use.
ADAK051	Adabas SAF Security (ADASAF) in use
Explanation	During CICS PLTPI processing, the Adabas external security interface (ADASAF) is in use. This message is not displayed if ADASAF is not in use.
ADAK052	Adabas Transaction Manager (ATM) in use
Explanation	During CICS PLTPI processing, Adabas transactions are being coordinated through the CICS Resource Manager Interface (RMI) using the Adabas Transaction Manager (ATM). This message is not displayed if the RMI is not in use.
ADAK053	Adabas Bridge for VSAM (AVB) in use
Explanation	During CICS PLTPI processing, the Adabas Bridge for VSAM (AVB) is in use. This message is not displayed if AVB is not in use.
ADAK054	T.R.U.E. global work area (GWA) address: {aaaaaaaa}
Explanation	This message occurs during CICS PLTPI processing and displays the address allocated to the global work area.
ADAK055	Adabas link routine EPA: {aaaaaaaa}
Explanation	This message occurs during CICS PLTPI processing and displays the entry point address (EPA) of the Adabas link routine.
ADAK056	Adabas link routine D.C.I. EPA: {aaaaaaaa}
Explanation	This message occurs during CICS PLTPI processing and displays the entry point address (EPA) of the Adabas link routine direct call interface (DCI).
ADAK057	Adabas SVC IDTH address: {aaaaaaaa}
Explanation	This message occurs during CICS PLTPI processing and displays the address of the Adabas SVC IDT header.

ADAK058	RESYNC command issued
Explanation	During CICS PLTPI processing, the CICS RMI for Adabas is in use and resynchronization will now take place for any incomplete transactions involving Adabas databases.
ADAK059	ATM inactive; RESYNC deferred
Explanation	During CICS PLTPI processing, the CICS RMI for Adabas is in use and resynchronization may be required for incomplete transactions involving Adabas databases. However, the Adabas Transaction Manager (ATM) is not currently active. Resynchronization will occur when ATM is restarted.
ADAK06	ADALNK statements ignored because ADARUN statements present
Explanation	A BS2000 session is running an ADALNK with both ADARUN and link name DDCARD, together with a file on the link name DDLNKPAR. The parameters in DDLNKPAR will not be used.
Action	No action required for this informational message.
ADAK061	ADATRUE - Enable stage failed EIBRESP: {xxxxxxxx1} EIBRESP2: {xxxxxxxx2}
Explanation	The task related user exit could not be enabled due to the EIB response codes xxxxxxxx1 and xxxxxxxx2.
Action	Consult the appropriate CICS documentation to determine the cause of the error in the exec interface block (EIB).
ADAK062	ADATRUE extract GWA failed EIBRESP: {xxxxxxxx1} EIBRESP2: xxxxxxxx2
Explanation	The requested task-related user exit global storage could not be EXTRACTed due to the EIB response codes given as xxxxxxxx1 and xxxxxxxx2.
Action	Consult the appropriate CICS documentation to determine the cause of the error in extracting the global work area.
ADAK063	Initialization call to link routine failed EIBRCODE: {xxxxxxxx} ADARSP: {nnnn}
Explanation	The Initialize Link command (IL) could not be executed because of EIB response code xxxxxxxx, or Adabas response code nnnn.
Action	If the EIBRCODE field returns a non-zero value, consult the appropriate CICS documentation to determine the cause of the error. If the ADARSP returns a non-zero value, consult the response codes in chapter 2.

- ADAK064** **Adabas call to establish IDTH failed**
Explanation The address of the IDTH could not be established.
Action Most often, this is caused by an incorrect Adabas SVC number in the LGBLSET macro; otherwise, check to see that the Adabas SVC is installed, and at the correct version.
- ADAK065** **Invalid D.C.I address - cannot continue**
Explanation The address of the Direct Call Interface could not be established.
Action Verify that the correct version of the Adabas command-level link routine is installed, and that the entry point name "ENTPT=" in LGBLSET is correct.
- ADAK066** **ADACIC0 version: {version} does not match Adabas link**
Explanation The ADACIC0 version does not match the version of the ADATRUE or Adabas link routine being installed. All three modules must be at the same version for the install to succeed.
Action Verify that the correct version of all three modules is installed.
- ADAK068** **{message-text}**
Explanation Various message texts may be provided using this message number. Review the table below to determine the cause of the error and the course of action to take.

Message Text	Explanation	Action
LOAD of installation options table <i>tbl</i> failed EIBRESP: <i>eibresp</i>	The load failed for the Adabas installation options table module named <i>tbl</i> by the CICS command-level link routine module. The hexadecimal representation of the CICS EIBRESP returned by the failing EXEC CICS LOAD command is given in the message.	Determine the meaning of the EIBRESP code. Check the DFHRPL concatenated libraries to ensure that the ACIOPT module is available to the CICS region.
RMI initialization error: CMD: <i>cmd</i> RESP: <i>resp</i> RC: <i>rc</i>	The RMI initialization routine could not complete its processing due to the indicated error. The message may provide a failing CICS command (<i>cmd</i>) and response code (<i>resp</i>), or an ATM error code (<i>rc</i>) and, if relevant, Adabas response code (<i>resp</i>).	Investigate the meaning of the displayed response code and/or error code. If possible, correct the error; otherwise, report the details to your Software AG technical support representative.
Adabas installations options table	The installation options table module listed in the message (<i>tbl</i>) has been loaded but does not have valid contents.	A valid installation options table module should have the eyecatcher 'ACIOPT ' at the

Message Text	Explanation	Action
name <i>tbl</i> is invalid.		beginning of the module. Verify the module has this eyecatcher and correct accordingly.

Action The action that should be taken depends on the message text issued with this message number. Review the table above for the appropriate action.

ADAK069 {message-text}

Explanation Various message texts may be provided using this message number. Review the table below to determine the cause of the error and the course of action to take.

Message Text	Explanation	Action
Load of ACI link routine failed EIBRCODE: <i>eibrcode</i>	The load of the Adabas command-level link routine module failed. The hexadecimal representation of the CICS EIBRCODE (<i>eibrcode</i>) returned by the failing EXEC CICS LOAD command is given in the message.	Determine the cause of the failure. The reason for the failure may be determined by examining previous messages produced by the ADACIC0 installation program. These messages are written to the JES job log for z/OS and to SYSLOG for z/VSE. For more information please consult your Adabas installation documentation.
Load of DBID/SVC table <i>tbl-name</i> failed EIBRESP <i>eibrbc</i>	An attempt to load the DBID/SVC routing table named in the message (<i>tbl-name</i>) failed. The CICS EIB response code (<i>eibrbc</i>) is given in the message.	Verify that the correct DBID/SVC load module name was specified for the LGBLSET DBSVCTN parameter. If it was not, correct the name and try again. If the correct name was specified, review the CICS EIB response code to identify the nature of the failure. If the problem persists, contact your Software AG support representative for assistance.

Action The action that should be taken depends on the message text issued with this message number. Review the table above for the appropriate action.

ADAK07 LRVINFO>0 and module REVEXITB not found, processing continues

Explanation During BS2000 TP monitor interface operations, a nonzero LRVINFO parameter value was specified in the ADALNK parameter, but the Adabas Review user exit B (REVEXITB) module could not be found. Program processing continues without REVEXITB.

Action Either specify LRVINFO=0, remove the LRVINFO parameter statement, or include the REVEXITB module in the program.

ADAK070	Adabas T.R.U.E. disabled {module-name}
Explanation	A failure occurred during the execution of the enhanced installation program. The Adabas TRUE (Task Related User Exit) is disabled. The name of the Adabas TRUE module being installed is given in the message (<i>module-name</i>).
Action	Determine the cause of the failure. The reason for the failure may be determined by examining previous messages produced by the ADACIC0 installation program. These messages are written to the JES job log for z/OS and to SYSLOG for z/VSE. For more information please consult your Adabas installation documentation.
ADAK071	Adabas link routine released {module-name}
Explanation	A failure occurred during the execution of the enhanced installation program. The CICS command-level link routine has been released. The name of the Adabas CICS command-level link routine being installed is given in the message (<i>module-name</i>).
Action	Determine the cause of the failure. The reason for the failure may be determined by examining previous messages produced by the ADACIC0 installation program. These messages are written to the JES job log for z/OS and to SYSLOG for z/VSE. For more information please consult your Adabas installation documentation.
ADAK072	GETMAIN for UB-POOL failed EIBRESP: {0000nnnn}
Explanation	The CICS GETMAIN for shared storage for the Adabas user buffer pool failed. The returned value of EIBRESP from the CICS request is printed in hexadecimal at the end of the message.
Action	Consult the appropriate IBM CICS documentation for the meaning of the returned EIBRESP value.
ADAK073	Freemain for UB-POOL failed EIBRESP: {0000nnnn}
Explanation	The storage for the Adabas user buffer pool was not released. The returned value of EIBRESP from the CICS FREEMAIN request is returned at the end of the message.
Action	Consult the appropriate IBM CICS documentation for the meaning of the returned EIBRESP value.
ADAK074	Adabas DBID/SVC table in use is: {table-name}
Explanation	The LGBLSET parameters DYNDBSVC=YES and DBSVCTN= <i>dbid-svc-tbl-name</i> parameters are coded in the CICS link globals table and the named DBID/SVC routing table is found and loaded. The name of the DBID/SVC routing table is given in the message (<i>table-name</i>).
Action	No action is required for this informational message.

ADAK075	REVEXIT2 {client exit address: {address} Not Installed Not Active}
Explanation	This message provides the status of the Adabas Review client exit, REVEXIT2. If a hexadecimal address is listed in the message, the Adabas Review client exit is installed and active. If "Not Installed" is listed in the message, then the Adabas Review client exit is not linked with the globals table used by the TRUE being activated in this phase of the installation. If "Not Active" is listed in the message, the Adabas Review client exit is linked with the globals table, but RVCLNT=NO was coded before the globals table was assembled and the exit is considered inactive.
Action	No action is required for this informational message.
ADAK076	The default Hub-id is: {{hubid} Dynamic}
Explanation	If the Review client exit is installed (see ADAK075), this message is produced during the installation of the Adabas CICS components to indicate the default Adabas Review hub ID that will be used by this client exit. If the numeric hub ID is listed in the message, then this is the target where client records will be sent by default, as specified in the globals table with the REVHID keyword. If "dynamic" is listed in the message instead of a specific hub ID, then no value was given in the globals table and the caller, usually SYSREVDDB, must provide the hub ID to be used by the Adabas Review client exit.
Action	No action is required for this informational message.
ADAK08	Review exit B deactivated. processing continues
Explanation	During BS2000 TP monitor interface operations, LRVINFO=0 was either specified or omitted in the ADALNK parameter or the entire ADALNK parameter service is inactive, and the Adabas Review user exit B (REVEXITB) is present in the user program.
Action	To activate REVEXITB, specify LRVINFO=256; otherwise, no change is necessary.
ADAK080	{nnnn} of {tttt} TRUEs installed
Explanation	This message is issued at the end of ADACIC0 installation processing. It provides the actual number of TRUEs that were successfully installed (<i>nnnn</i>) and identifies the number of TRUE installations that were attempted (<i>tttt</i>).
Action	No action is required for this informational message.
ADAK09	Incompatible versions of ADALNK and ADAL2P, processing aborted
Explanation	During BS2000 TP monitor interface operations, it was determined that the versions of ADALNK and ADAL2P do not match.
Action	Check library assignments; check TSOSLNK/BINDER protocols.

ADAK10**ADUSER {type} for entry {module} RC {rc}****Explanation**

During BS2000 TP monitor interface operations, an error occurred while attempting to access the Adabas link module where *type* is either REQM for requesting memory or BIND for attempting to load; *module* is the name of the module to be accessed; and *rc* is the Fujitsu Technology Solutions macro return code.

Action

If the *type* is

- BIND, check the file link statements for the presence of the Adabas library
- REQM, there is a memory shortage in the application program address space

30

ADAL* - Command Log (CLOG) System Messages



Note: Each of the messages in this section starts with the relevant database ID.

ADAL01	CLOG not active
Explanation	The command log is sequential, and the DDLOG data set was either set to "dummy" or could not be opened. Command logging is switched off.
ADAL02	CLOGR{n} is active
Explanation	The specified command log for dual or multiple command logging is now active.
ADAL03	Command log DDCLOGR{n} has started
Explanation	Command logging has switched to data set DD/CLOGRn .
ADAL04	Warning : now it is too late to copy DDCLOGR{n} FROMBLK=blk1, FROMTIME=timestamp1 TOBLK =blk2, TOTIME=timestamp2 00199 IOR function = {fx}, response = X'{nn}' 00199 ERROR obtaining timestamp information
Explanation	The specified dual or multiple command logging data set is being overwritten with new log data, and is no longer valid. Normally, the from and to blocks and the from and to timestamps being overwritten are given in the message. However if there was a problem obtaining this block and timeout information, the 00199 messages listed above may be issued.

ADAL05	I/O error on DDCLOGR{n}. Command logging terminated
Explanation	Command logging to data set DDCLOGRn was terminated by an I/O error .
ADAL06	Command log is not available
Explanation	None of the dual or multiple command logging data sets was available (presently being copied by ADARES) . Command logging is switched off.
ADAL07	Command long could not be opened
Explanation	An invalid command logging device or size was specified, or an I/O error on either the first or last block was detected. Command logging is switched off.
ADAL08	Command log is already in use
Explanation	In a cluster nucleus, a second nucleus has been started with the same CLOG file name as one of the other nuclei in the cluster.
Action	Check the CLOG file names used in the cluster and allocate another CLOG file to one nucleus in the cluster to correct the duplication.
ADAL10	PPT error {nn} processing CLOG
Explanation	An error occurred while processing the parallel participant table (PPT). The nucleus stays up, but command logging is disabled.
Action	Collect diagnostic information such as that provided by the ADACHK PPTPRINT function. Provide the error number (<i>nn</i>) and the PPTPRINT to your Software AG technical support representative. It may be necessary to format the PPT and restart the nuclei in order to rebuild the PPT.
ADAL11	Warning - CLOG datasets have changed. PPT overwritten. Use ADARES MERGE CLOG to copy previous CLOG datasets.
Explanation	Either the CLOG data sets are different from what was specified in the last session or no CLOGs are specified but the previous CLOGs were not copied. The PPT information about these data sets is being overwritten.
Action	If the contents of the CLOGs are still needed, they must be copied with the CLCOPY function and then merged manually. If the contents are not needed, no action is required.

ADAL12	{date} {time} CLOGMRG=YES not valid. CLOGMRG not in effect.
Explanation	This message is generated if an attempt is made to initialize a non-plex/ASM nucleus (NUCID=0) with CLOGMRG=YES specified. This is an informational message only and the nucleus will come up. CLOGMRG=YES should only be specified if NUCID is greater than 0.
Action	No action is required for this informational message.
ADAL13	{dbid} {yyyy-mm-tt ss:mm:ss} REACTLOG not allowed
Explanation	An ADADBS REACTLOG request is not allowed. If there are no outstanding I/Os for the command logs, then the request to reactive the log is not allowed. The database ID associated with the command log (<i>dbid</i>) and the date and time stamp are given in the message.
Action	Try again when there are outstanding I/Os for the command logs.
ADAL14	{dbid} {yyyy-mm-tt ss:mm:ss} REACTLOG successful!
Explanation	A request to reactivate command logging was successful. The database ID associated with the command log (<i>dbid</i>) and the date and time stamp are given in the message.
Action	No action is required for this informational message.
ADAL15	{dbid} {yyyy-mm-tt ss:mm:ss} REACTLOG failed!
Explanation	A request to reactivate command logging failed. This message should be preceded by another error message describing the reason for the failure. The database ID associated with the command log (<i>dbid</i>) and the date and time stamp are given in the message.
Action	Review the other messages to resolve the problem and try again. If the problem persists, contact your Software AG technical support representative for assistance.
ADAL16	{dbid} {yyyy-mm-tt ss:mm:ss} Getmain failure
Explanation	A request for storage failed. Command logging is halted. The database ID associated with the command log (<i>dbid</i>) and the date and time stamp are given in the message.
Action	Contact your Software AG technical support representative for assistance.

31

ADAM* -- ADAMPM System Messages

ADAM001	VM/System product release level under 3 - not supported
Explanation	The z/VM version being used is not supported by the Entire Net-Work IUCV driver. The IUCV line driver cannot be opened.
Action:	Upgrade the system to the required z/VM level.
ADAM002	Line driver maximum number of connections exceeded on {type} machine
Explanation	z/VM systems only: An IUCV connection between two virtual machines could not be made because either the initiating (source) or target virtual machine exceeded the MAXCON value in the machine's CP directory. The <i>type</i> of machine (SOURCE or TARGET) that exceeded the MAXCON value is given in the message.
Action	Increase the appropriate MAXCON value and update the machine's CP directory.
ADAM003	No IUCV authorization found
Explanation	Entire Net-Work was not able to sign on to IUCV because the virtual machine was not IUCV-authorized in the CP directory. The IUCV line driver cannot be opened.
Action:	Add the required IUCV statements to the CP directory for the virtual machine.
ADAM004	No IUCV message found on link {link-name}
Explanation	The Entire Net-Work IUCV line driver attempted to receive or reply to a message that was not found in any IUCV message queue. The IUCV line terminates Entire Net-Work abnormally.
Action:	Make note of the link "link-name", any related messages and dump listings, and call your Software AG technical support for assistance.

ADAM005	IUCV {function} function error {err-num} on link {link-name} on path-ID {path}
Explanation	<p>The specified function detected error <i>err-num</i> on the specified link and path.</p> <p>This message is followed by message ADAM007. The IUCV line terminates Entire Net-Work abnormally.</p>
Action:	<p>Note the error number (<i>err-num</i>), the link (<i>link-name</i>) and any related messages, and call your Software AG technical support for assistance.</p>
ADAM006	IUCV send completion error {err-num} on link {link-name} path-ID {path}
Explanation	<p>The IUCV SEND function detected error <i>err-num</i> on the specified link and path.</p> <p>The IUCV line terminates Entire Net-Work abnormally.</p>
Action:	<p>Note the error number (<i>err-num</i>), the link (<i>link-name</i>), any related messages, and call your Software AG technical support for assistance.</p>
ADAM007	IUCV parameter block at location {location}
Explanation	<p>This message occurs after an ADAM005 error, and is followed by a hexadecimal display of the failing IUCV parameter block.</p> <p>The IUCV line terminates Entire Net-Work abnormally.</p>
Action:	<p>Retain the displayed information plus any other related error or dump information and contact your Entire Net-Work technical support representative.</p>
ADAM008	Incoming traffic impaired on link {link-name} due to buffer shortage
Explanation	<p>Incoming messages on link <i>link-name</i> are being delayed due to insufficient buffer space.</p> <p>Entire Net-Work suspends incoming data traffic until the buffer shortage is resolved.</p>
Action:	<p>Increase the short-term buffer size for a virtual machine running a non-paging guest operating system, or increase the page-fixed buffer size for a paging guest system virtual machine. Both buffers are controlled by the NODE statement parameters for the link-name's node.</p>
ADAM009	Communications impaired to link {link-name}
Explanation	<p>Communication with the specified link is impaired by insufficient buffer space on that node. Message ADAM008 occurs on that node, advising of the problem.</p> <p>The adjacent Entire Net-Work node suspends incoming data traffic until the buffer shortage is resolved.</p>
Action:	<p>Increase the short-term buffer size for a virtual machine running a non-paging guest operating system on the specified node, or increase the page-fixed buffer size for a paging guest system virtual machine. Both buffers are controlled by the NODE statement parameters for the link-name's node.</p>

ADAM01 **{version} {job-name} abend code {code}**
Explanation z/VSE systems only : An ADAMAF abend occurred. The variable message information is as follows:

<i>version</i>	Adabas version
<i>job-name</i>	the z/VSE job name
<i>code</i>	the abend code

ADAM010 **Pending connection rejected due to buffer shortage**
Explanation This node could not accept a connection due to inadequate buffer space.

The IUCV path which was initiated is not connected.
Action: Increase the short-term buffer size for a virtual machine running a non-paging guest operating system, or increase the page-fixed buffer size for a paging guest system virtual machine. Both buffers are controlled by the NODE statement parameters for the specified node.

ADAM011 **Normal communications resumed to link {link-name}**
Explanation This informational message advises that the condition causing previous impaired communications has been corrected.

A buffer shortage indicated by a message ADAM008 or ADAM009 has been resolved.
Action: No action required. This message is for your information only.

ADAM012 **Buffer program check on link {link-name}**
Explanation A program check occurred while accessing an IUCV buffer area.

Entire Net-Work terminates operation with a dump.
Action: Note the link "link-name", any related error or dump listing information, and call your Software AG technical support for assistance.

ADAM013 **{number} number of sends 2way {count-a} 1way {count-b}**
Explanation This normal termination message specifies the total number of SEND/REPLY (SEND 2WAY) and SEND 1WAY messages, as well as the counts of each type of SEND.

Entire Net-Work proceeds to terminate normally.
Action: No action required. This message is for your information only. An excessive number of SEND 1WAYs maybe an indicator that the MSGLIM parameter value is insufficient.

ADAM014	{number} number of replies non-null {count-a} null {count-b}
Explanation	This normal termination message specifies the total number of IUCV replies as well as the counts of replies containing data (non-null) and those without data (null). Entire Net-Work proceeds to terminate normally.
Action	No action required. This message is for your information only. An excessive number of null replies indicates the SEND 1WAY protocol is more suitable.
ADAM015	Incoming message exceeds buffer length on link {link-name}
Explanation	An incoming IUCV message from the link <i>link-name</i> was too long for the available buffer. Entire Net-Work terminates operation with a dump.
Action:	Increase the short-term buffer pool size (specified by the NODE statement for the specified node ID).
ADAM016	Outgoing message exceeds buffer length on link {link-name}
Explanation	An outgoing IUCV message was too large for the allocated buffer space. Entire Net-Work terminates operation on this node with a dump.
Action:	Increase the short-term buffer pool size (specified by the NODE statement for this node ID).
ADAM017	Connection to user {user-id} denied due to block length conflict
Explanation	The values specified by this node's and the partner node user-id's LINK statement MAXBLK parameters are not the same. The IUCV path that was initiated is not connected.
Action:	Correct one of the LINK statement's MAXBLK values to agree with the other.
ADAM018	Message limit on path to VMID {vm-id} INSUFFICIENT
Explanation	The maximum number of outstanding IUCV messages allowed was exceeded. The IUCV line terminates abnormally.
Action:	Correct either the IUCV LINK statement's MSGLIM parameter value, or the CP directory MSGLIMIT value.

ADAM019	Maximum block length set to {length}								
Explanation	Entire Net-Work found no MAXBLK value on the IUCV LINK statement in a paging system where a maximum block size is required. Entire Net-Work sets the block length to the page size "length".								
Action	No action is required for this informational message.								
ADAM020	Initialization error {err-num} for guest system IUCV support								
Explanation	Entire Net-Work was unable to initialize the IUCV line driver in the guest operating system. The driver is not opened. If the IUCV driver is the only driver specified, Entire Net-Work terminates operation on this node.								
Action:	Note the error number ("err-num") and guest operating system level, and call your Software AG technical support for assistance.								
ADAM021	Link {link-name} not connected error {err-code} IUCV-code {code}								
Explanation	A connection could not be made to another virtual machine. The error code "err-code" is returned by the operating system's IUCV interface; the IUCV code "code" is returned in the IPRCODE field of the IUCV parameter block. The value "code" can be one of the following IUCV CONNECT error codes:								
	<table border="1"> <tr> <td style="text-align: center;">11</td> <td>Target communicator not logged on.</td> </tr> <tr> <td style="text-align: center;">12</td> <td>Target communicator has not invoked the DECLARE BUFFER function.</td> </tr> <tr> <td style="text-align: center;">13</td> <td>The maximum number or connections for this virtual machine has been exceeded.</td> </tr> <tr> <td style="text-align: center;">14</td> <td>The maximum number or connections for the target virtual machine has been exceeded.</td> </tr> </table>	11	Target communicator not logged on.	12	Target communicator has not invoked the DECLARE BUFFER function.	13	The maximum number or connections for this virtual machine has been exceeded.	14	The maximum number or connections for the target virtual machine has been exceeded.
11	Target communicator not logged on.								
12	Target communicator has not invoked the DECLARE BUFFER function.								
13	The maximum number or connections for this virtual machine has been exceeded.								
14	The maximum number or connections for the target virtual machine has been exceeded.								
	IUCV codes 11 and 12 are two of the most common codes that can occur.								
Action:	Ensure that the virtual machine at the other end of the link is logged on, active, and authorized to use IUCV. Refer to the appropriate operating system information for the meaning of "err-code", and the corrective action. For detailed IUCV and related code information, see <i>IBM's z/VM System Programmer's Guide</i> and <i>z/VM System Facilities for Programming</i> manuals.								
ADAM022	Path to VMID {vm-id} disconnected due to interrupt queue shortage								
Explanation	The Entire Net-Work IUCV support routine was not able to save the status of an incoming IUCV interruption due to a lack of interrupt queue elements. The IUCV link is disconnected.								
Action:	Increase the value of the QSIZE parameter for NETSIR and rerun NETSIP with the REPLACE parameter								

ADAM025I	IUCV driver manually closed
Explanation	The IUCV driver has been closed either by an operator command or by SHUTDOWN processing.
Action	No action is required for this informational message.
ADAM13	{number} number of sends 2way {count-a} 1way {count-b}
Explanation	This normal termination message specifies the total number of SEND/REPLY (SEND2WAY) and SEND1WAY messages, as well as the counts of each type of SEND.
ADAM14	{number} number of replies non-null {count-a} null {count-b}
Explanation	This normal termination message specifies the total number of IUCV replies as well as the counts of replies containing data (non-null) and those without data (null).
ADAM15	Incoming message exceeds buffer length on link {link-id}
Explanation	An incoming IUCV message from the specified link exceeded the length of the available buffer. Entire Net-Work terminates with a dump.
Action:	Use the message blocking and/or compression options for the link (specified by the IUCV LINK statement), or increase the short-term buffer pool size (specified by the NODE statement for the specified node ID).
ADAM16	Outgoing message exceeds buffer length on link {link-id}
Explanation	An outgoing IUCV message was too large for the allocated buffer space. Entire Net-Work terminates operation on this node with a dump.
Action:	Use the message blocking and/or compression options for the specified link (specified by the IUCV LINK statement), or increase the short-term buffer pool size (specified by the NODE statement for this node ID).
ADAM17	Connection to user {user-id} denied due to block length conflict
Explanation	The values specified by this node's and the partner node "user-id's" LINK statement MAXBLK parameters are not the same.
Action:	Correct one of the LINK statement's MAXBLK values to agree with the other.

ADAM18	Message limit on path to VMID {vm-id} insufficient
Explanation	The maximum number of outstanding IUCV messages allowed was exceeded.
Action:	Correct either the IUCV LINK statement's MSGLIM parameter value, or the CP directory OPTION MAXCONN value.
ADAM19	Maximum block length set to {length}
Explanation	Entire Net-Work found no MAXBLK value on the IUCV LINK statement, and therefore has set the block length to the page size <i>length</i> .
ADAM20	Initialization error {err-num} for guest system IUCV support
Explanation	Entire Net-Work was unable to initialize the IUCV line driver in the guest operating system. The driver is not opened.
	If the IUCV driver is the only driver specified, Entire Net-Work terminates operation on this node.
Action:	Note the error number ("err-num") and guest operating system level, and call your Software AG technical support for assistance.
ADAM75	SVCDUMP busy
Explanation	A request to write an SVC dump has failed due to a busy condition. This indicates that the system service is active processing another SVC dump request. If the busy condition is returned from the first attempt to write to SVCDUMP, the following message is issued:
	<pre>ADAM75 SVCDUMP busy - retry ever 05 sec for 15 min</pre>
	In this case, the SVC dump request will be retried as indicated in the message.
	If the busy condition persists for the maximum time permitted, the following messages are issued and no further retries are attempted:
	<pre>ADAM75 SVCDUMP busy - dump not written ADAM78 SVCDUMP SDUMP FAILED RC rc/sc</pre>
	Dump processing then continues as if the SVCDUMP DD statement had not been specified.
Action	No action is required for this informational message.

ADAM76	Communicator unusable, remote access not possible
Explanation	This message usually follows message ADAM98 . The Communicator or Entire Net-Work cannot receive the initialization feed call. This extra message warns the operator that there is something wrong with the communicator. The database will start normally. If the MPM node is a translator or communicator, this node will go down.
Action	Do not restart the database until the problems in the Communicator or Entire Net-Work have been resolved. The operator command NWCONNECT may be used to retry establishing the Entire Net-Work DBID target. This command is not available if Adabas Cluster Services or Adabas Parallel Services is being used.
ADAM77	SVCDUMP ignored - not authorized
Explanation	An SVC dump (//SVCDUMP DD) was attempted, but the job is <i>not</i> running with APF authorization. APF authorization is required for an SVC dump. Dump processing continues as if the SVCDUMP DD statement had not been specified.
Action	No action is required for this information message.
ADAM78	SVCDUMP {SDUMP TDUMP} failed RC{rc/rsn}
Explanation	The SVC dump failed. The return code (<i>rc</i>) and reason code (<i>rsn</i>) from the IBM SDUMP macro or IBM IEATDUMP macro are given in the message.
Action	No action is required for this information message.
ADAM79	SVCDUMP {SDUMP TDUMP} written RC {rc/rsn}
Explanation	The SVC dump was written. The return code (<i>rc</i>) and reason code (<i>rsn</i>) from the IBM SDUMP macro or IBM IEATDUMP macro are given in the message or are suppressed if the return code is zero.
Action	No action is required for this information message.
ADAM81	{dbid} unexpected return code {ret-code} {information} in MACRNAME, {macro-name}
Explanation	BS2000 systems only: The BS2000 macro <i>macro-name</i> issued the unexpected return code <i>ret-code</i> . Depending on the specified macro, <i>information</i> contains more error-specific information:

Macro (<i>macro-name</i>)	Information (<i>information</i>)
ENAEI	task sequence number (<i>tttt</i>) of target hard post ID (ADA <i>tttt</i>) to enable
ENQAR	Identification table memory pool name (IDTNAME) used as lock ID
DISEI	task sequence number (<i>tttt</i>) of target hard post ID (ADA <i>tttt</i>) to disable
DISMP/CQ	task sequence number of command queue common memory to disable
POSSIG	task sequence number (<i>tttt</i>) of target hard post ID (ADA <i>tttt</i>)
ENAMP	command queue pool name. If the return code (<i>ret-code</i>) is "08...00", a common memory pool is already present, but it must be new
REQMP	command queue pool name where memory could not be obtained
STXIT	the nucleus except exit

Action:

For the ENAMP function, if *ret-code* is 08...00, a common memory pool is already present and a new pool is required. An attempt was made to bring up an active nucleus again. Do not bring up the same nucleus twice for the same task if the ENAMP function was indicated.

For the ENQAR/REQMP function, check the IDTNAME used in ADARUN, SSFB2C, or DDLNKPAR.

For ENAEI, DISEI, DISMP/CQ, and POSSIG, the task sequence numbers are those of the command queue memory post to be accessed. Check the tasks and matching IDs in your system with SHOW-USER-STATUS or in the utility program IDTLOOK.

The STXIT, contact your Software AG technical support representative.

Note: *<ret-code>* is described in the BS2000 System Macros Manual for the macro mentioned.

ADAM82**{dbid} Adabas canceled in bourse wait****Explanation**

BS2000 systems only: The Adabas nucleus was canceled while waiting for an event.

The nucleus terminates without giving control to termination recovery to reset the DIB block. The user abend code is 233.

ADAM83**{dbid text}****Explanation**BS2000 systems only: The message *text* is explained as follows:

```
New IDT created, name=idt-name, GROUPS={YES | NO}
```

The reporting task created a new ID table *idt-name* located above the 16-MB limit with the attribute GROUPS=NO (global to the machine) or GROUPS=YES (in the scope of the user logon).

```
Connected to IDT idt-name, GROUPS={YES | NO}
```

The reporting task participates in the existing ID table *idt-name* located above the 16-MB limit with the attribute GROUPS=NO (global to the machine) or GROUPS=YES (in the scope of the user logon).

```
CMDQ/AB pool enabled, LOC=loc
```

The location of the command queue (CMDQ) pool is location *loc*" which is either "above" or "below".

```
Disconnected from IDT idt-name
```

The nucleus closed out its use of ID table *idt-name*. Another nucleus or user task is holding the ID table.

```
Disconnected from CMDQ/AB pool
```

The nucleus stopped processing, but the command queue (CMDQ) pool is still being held by a user task.

```
IDT disabled, Name=idt-name
```

```
CMDQ/AB pool disabled
```

The nucleus stopped processing, and no user task is using the command queue, which is removed from the system.

ADAM86**dbid IDT CONN ERROR :{ text}****Explanation**

BS2000 systems only: An error occurred when attempting to connect to the IDT. A memory pool named by IDTNAME was found, but did not contain the expected structure. The possible message texts (*text*) are explained in the following table.

Message text	Explanation	Action
wrong ADARER version <i>nn</i> expected <i>mm</i>	The router is an older version than the caller.	Bring the whole system down and start the first nucleus/server with the newest version to allocate and fill the ID table with its version.
SMPSVC (router extension) not loaded	An attempt to allocate a new identification table (IDT) memory pool failed to load the SMPSVC module.	Check that the executable SMPSVC is present in one of the libraries in the DDLIB/BLSLIB library load stack.
DBID already in use by SMP cluster	An attempt has been made to start a nucleus with a DBID that clashes with an Adabas Parallel Services cluster.	Use another DBID for the nucleus or start it on another IDTNAME.
IDIDTID = wrong value	The start of the identification table (IDT) does not have the expected eyecatcher (IDIDTID) of "ADABAS51".	Bring the whole system down and start the first nucleus/server again to make a clean IDT.
ADARER is not a BS2000 router	The start of the identification table (IDT) memory pool contains the BS2000 Adabas router. The eyecatcher for this (RERBS2) has not been detected.	Check the value of the IDTNAME parameter in ADARUN or in DDLNKPAR. Otherwise, bring the whole system down.

ADAM88 **{dddd} Processor(s) = {n}**
Explanation BS2000 systems only. This is an information message which states how many processors (n) are available on the computer on which the database dddd is started.
Action: None required.

ADAM8B **{dbid}IDT Version {vv} date {yyyymmdd} SP {ssss}**
Explanation BS2000 systems only: This informational message identifies which IDT version (vv) is being accessed by the database (dbid) when started, its date of assembly (yyyymmdd) and the SP level (ssss).
Action: No action is required for this informational message.

ADAM8C	{dbid} Router Zaps Applied: {zzzz zzzz zzzz zzzz zzzz zzzz zzzz}
Explanation	BS2000 systems only: This informational message identifies which zaps (<i>zzzz</i>) have been applied to the IDT accessed by the database (<i>dbid</i>) when started.
Action:	No action is required for this informational message.
ADAM90	{dbid} Adabas subtask abend code {code} PSW {password} {reg0} {reg1} {reg2} {reg3} (R0-R3) {reg4 reg5 reg6 reg7} (R4-R7){ reg8 reg9 reg10 reg11} (R8-RB) {reg12 reg13 reg14 reg15} (RC-RF)
Explanation	An Adabas subtask abend occurred. The abend code, password, and register information is in the same format as the ADAM99 message. The subtask terminates with Adabas user abend 252.
ADAM91	{dbid} {target} user gone job {job-name} user ID {hex-user-id}
Explanation	Adabas tried to process a user call, but the addressed data area was not addressable, or no longer contained recognizable data. This message occurred while Adabas was receiving the command (router 08-CALL processing). The program was apparently canceled after issuing an Adabas command (router 04-CALL), perhaps due to a communication delay or timeout.
Action:	Avoid ending, abending, or cancelling the program, if possible.
ADAM92	{dbid} {target} user gone job {job-name} user ID {hex-user-id}
Explanation	Adabas tried to process a user call, but the addressed data area was not addressable, or no longer contained recognizable data. This message occurred while Adabas was posting the user after command completion (router 12-CALL processing). The program was apparently canceled after issuing an Adabas command (router 04-CALL), perhaps due to a communication delay or timeout.
Action:	Avoid ending, abending, or cancelling the program, if possible.
ADAM93	{dbid} {target} User gone job {job-name} user ID {hex-user-id}
Explanation	The user's program exceeded the ADARUN CT time allowed without receiving the results of an Adabas call (performing router 16-CALL processing). This could be caused by processing delays caused by an overloaded system or network, low priority, or teleprocessing delays. Adabas assumes that the user program has been canceled; Adabas frees the command queue element (CQE) and alternate buffers. If a user program eventually issues a router 16-CALL, a response code 254 (ADARSP254) also occurs.

Action: Consider increasing the ADARUN CT time, or otherwise increase the resources for the user program. Avoid cancelling or ending the user program, if this was done.

ADAM94 **{dbid} Post Module ADAASPE loaded**

Explanation BS2000 systems only. This is an information message stating that the Software AG internal product software (APS) posting module ADAAPSPE has been loaded into the router. This is an acknowledgment that access to APS applications is now enabled.

Action No action required for this informational message.

ADAM96 **{dbid} MPM running in XAE-{mode-type} mode under V{v }
{dbid} MPM running in {ops} - {mode-type} mode under {level}**

Explanation This message specifies the mode under which Adabas is running:

<i>ops</i>	z/VSE operating system type, either "370" or "ESA"
<i>v</i>	the z/VSE version
<i>mode-type</i>	SHARED NON-SHARED NON-SPECIFIED
<i>level</i>	the operating system level

ADAM97 **{dbid} Terminating, no longer accepting commands**

Explanation The database identified in the message is terminating and no longer accepting commands.

Action: No action is necessary for this informational message.

ADAM98 **{dbid} Target initialization error: {cause}**

Explanation ADAMPM was unable to establish interregion communication for the reason specified in the message (*cause*), which is one of the following:

Cause	Action
Communicator response code <i>rsp</i>	An unexpected response code resulted from the sign-on call to the Entire Net-Work communicator. This message can also occur when Entire Net-Work installation has not completed for some reason. Refer to the Entire Net-Work documentation for a description of the response code <i>rsp</i> .
CQ/AB incorrect key	The service's CQ and AB pool were not acquired with the correct attributes. Verify that the execution libraries are correct. If you are unable to resolve the error, contact your Software AG support representative.

Cause	Action
CQ/AB keys incompatible	The service's CQ and AB pool were not acquired with the correct attributes. Verify that the execution libraries are correct. If you are unable to resolve the error, contact your Software AG support representative.
DUP ID on node <i>node-id</i>	<p>In Entire Net-Work, target (database) IDs must be unique across all connected systems. Duplicate target IDs cannot be active on systems connected with Entire Net-Work.</p> <p>Determine the conflicting targets having the specified node ID, and choose which is to be active under the specified ID.</p>
DUPL. COMMUNIC./TRANSL.	<p>Only one communicator/translator can be active at any one time.</p> <p>Correct the problem and rerun the job.</p>
Duplicate target ID (DBID)	<p>The ID table already contains an active entry for the target ID (database ID) specified. Multiple targets with the same ID are not allowed.</p> <p>Choose which of the two targets should be active and if necessary, end the currently active target, and restart the job for the other target.</p> <p>Do not specify the FORCE=YES ADARUN parameter unless it is absolutely certain that the ID table entry now active was left behind by a target that is no longer valid. If this problem continues, retain all related information and contact the Software AG support representative.</p>
ID table full	<p>The system already holds the maximum allowed number of ID table entities that can be simultaneously active: databases, Entire Net-Work nodes, Entire System Server (Natural Process) nuclei, etc. This maximum is set during ID table initialization; the default is 10.</p> <p>Either terminate one of the active targets and restart the job, or end all active targets and reinitialize the ID table with a larger size (using ADASIP or by re-IPLing the system).</p>
Incompatible SVC version	ADASVC must be at the same or later release as ADAMPM. Verify that the SVC and the execution libraries are correct.
Internal error	Keep all dumps, messages, and other related information and contact your Software AG support representative.
Invalid ID (DA parm)	Specify a TARGETID or DATABASE parameter value in the range 1 - 65535.
Length IUB (LU parm)	Specify an LU parameter value in the range 1 - 65535.

Cause	Action
No common memory CQ/AB	The necessary common storage space for the command queue (CQ) and/or the attached buffer pool is not available. Either specify a smaller buffer requirement if possible, or re-IPL the system to free lost common storage.
No ID table	The ID table was not correctly initialized by ADASIP and/or ADASIR. For z/VM, this cause means the ID table manager virtual machine is not active. Rerun ADASIP and/or ADASIR to correctly initialize the ID table.
Number ATTBUFFS (NA-parm)	The attached buffer count (NA parameter in ADARUN) was either not specified or specified as zero, or the requested space is unavailable. Either correct the parameter or increase the region size. Restart the job.
Number CQES (NC parm)	Specify an NC parameter value in the range 1 - 32767.

ADAM99

{dbid} ADABAS ABEND CODE {code}
{error-environment-information}

Explanation

The nucleus ended abnormally. This is the result of an error detected by Adabas (user abend code) or by the operating system (system abend code). All abend code values are given in hexadecimal notation.

The abend code (*code*) format is specific to your operating system:

- z/OS: The first four bytes of the abend code are in the form *xxssuuu*. The system abend code is specified by *sss* and the user abend code (the Adabas nucleus abend code) by *uuu*. Some system abend codes also provide a four-byte reason code. System abend and reason codes are documented in *z/OS MVS System Codes*. Adabas nucleus abend codes are described elsewhere in this documentation.
- z/VSE: The first four bytes of the abend code are in the form *xxssuuu*. The system abend code is specified by *sss* and the user abend code (the Adabas nucleus abend code) by *uuu*. System abend codes are documented as cancel codes in *z/VSE Messages and Codes*. Adabas nucleus abend codes are described elsewhere in this documentation.
- BS2000: The rightmost byte shows the STXIT interrupt code. They are documented in the *Executive Macros* manual, under *Task and Program Execution Control, STXIT Procedure with Contingency Processing*.

Additional *error environment information* follows the abend code in the message text, in the following order:

- PSW: The eight-byte program status word. The rightmost four bytes are the instruction address at the time of the abend.
- EC Info: Eight bytes of additional z/OS extended control mode information, such as the instruction length code, the interrupt code, and the virtual address causing a translation exception. Refer to the IBM documentation for SDWA fields SDWAAEC1 and SDWATRAN for more details.
- R0 - R15: Contents of the general purpose registers. Each register is either four or eight bytes, depending on whether the hardware and operating system support eight-byte registers.
- AR0 - AR15: Contents of the access registers.
- The load addresses of various nucleus modules and user exits.

The following is an example of an ADAM99 message produced when a z/OS nucleus was canceled:

```
ADAM99 00226 ADABAS  Abend code 40222000 00000000
078D1000 8001EC02 00020001 00000000 (PSW, EC Info)
00000000_00000001 00000000_FFFBC5F8 (R0-R1)
00000000_00043A08 00000000_001651A0 (R2-R3)
00000000_00000000 00000000_00009C9A (R4-R5)
00000000_246FA940 00000000_0014D6EC (R6-R7)
00000000_0014D6EC 00000000_0005A988 (R8-R9)
00000000_0001EBA8 00000000_00056000 (R10-R11)
00000000_800109E0 00000000_000129D0 (R12-R13)
00000000_8001EBD4 00000000_808D6C68 (R14-R15)
00000000 00000000 00000000 00000000 (AR0-AR3)
00000000 00000000 00000000 00000000 (AR4-AR7)
00000000 00000000 00000000 00000000 (AR8-AR11)
00000000 00000000 00000000 00000000 (AR12-AR15)

ADARUN 00007A60 ADALNK 800456C0 ADAMOD 80044100 ADAMIM 80054000
ADARVU 8004CEB8 ADACLX 80051000 ADARMT 80053100 ADAMSG 8004A000
ADAIOR 800109E0 ADAIOS 80015A18 ADANCO 00055000 ADANC1 0005A800
ADANC2 00068000 ADANC3 0008C400 ADANC4 000A0800 ADANC5 000B4400
ADANC6 000C7800 ADANC7 000DBC00 ADANC8 000F4400 ADANC9 0010B000
ADANCA 00113400 ADANCB 00123000 ADANCC 00127D00 ADALOG 00135998
ADAMPM 8013C430 ADARAC 8013FF30 ADAMGR 801464F8 ADAMGI 8014AF00 ←
```

Action:

Refer to your Adabas documentation for a description of a nucleus user abend, or to the appropriate operating system documentation for a description of the system abend.

ADAML1 **Percentage of PREFTBL used {pct}**
Number of calls to ADAMLF {callcount}
Number of cmds to ADABAS {cmdcount1}
Number of cmds returned from ADAMLF {cmdcount2}
Number of over reads {count}

Explanation ADAML1 messages list statistics that are printed when a CL command is issued and the ADARUN PREFETCH and PREFSTDD parameters are set. The following table describes each message.

Message	Description
Percentage of PREFTBL used <i>pct</i>	The percentage of the ADARUN parameter PREFSTBL used for this execution.
Number of calls to ADAMLF <i>callcount</i>	The number of times that ADAMLF was entered.
Number of cmds to ADABAS <i>cmdcount1</i>	The total number of commands that were passed to Adabas for this execution.
Number of cmds returned from ADAMLF <i>cmdcount2</i>	The number of commands that were returned from the ADAMLF buffers.
Number of over reads <i>count</i>	The number of records that were prefetched that were not passed back to the caller.

Action No action is required for these informational messages.

32

ADAQ* - Adabas Review Hub Messages

ADAQ_{nn} messages are received from the Adabas Review hub.



Note: Each of the messages in this section starts with the relevant database ID.

ADAQ89	{dbid} POSSIBLE CONFLICT BETWEEN REVIEW HUB AND UEX4. RAOSEXIT DISABLED
Explanation	The Adabas Review hub was enabled by specifying a hub ID on the ADARUN REVIEW parameter. The ADARUN UEX4 parameter was also specified and the user exit 4 module was identified as RAOSEXIT, an Adabas Review user exit that is not compatible with the Adabas Review hub. The Adabas nucleus completes its initialization but no calls to user exit 4 are performed by ADALOG.
Action	If the UEX4 parameter is left over from a previous conversion, remove the parameter. Otherwise, supply the correct user exit 4 module name.
ADAQ90	{dbid} REVIEW HUB INACCESSIBLE BECAUSE REVIEW HUB ID WAS NOT SPECIFIED
Explanation	The value specified for the Adabas Review hub was invalid. The Adabas nucleus completes its initialization but no calls are made to the Adabas Review hub.
Action	Specify the correct Adabas Review hub ID value and restart the nucleus.
ADAQ91	{dbid module-name} MONITORING SYSTEM INITIALIZATION FAILED. SEE ERROR MESSAGES
Explanation	The specified monitoring system component returned a nonzero status. Any failure of this sort should be accompanied by error messages displayed by the monitoring system. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Check the monitoring system error messages, correct the cause of the error, and restart the nucleus.

ADAQ92	{dbid module-name} MONITORING SYSTEM WAS NOT LOADED. CONTACT YOUR VENDOR
Explanation	The specified monitoring system component could not be loaded. It is possible that the load library containing the expected module was not specified in the nucleus' job stream. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Correct the cause of the error and restart the nucleus.
ADAQ93	{dbid module-name} MONITORING MAY BE INCOMPLETE BECAUSE ADALOG IS NOT LOADED.
Explanation	The command logging module ADALOG was not loaded. The monitoring system will not be able to process any command log records. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Correct the cause of the error and restart the nucleus
ADAQ94	{dbid module-name} IS AN INCORRECT VERSION LEVEL. CONTACT YOUR VENDOR
Explanation	The specified module is at an incorrect version level and cannot be used with this version and/or SM-level of Adabas. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Contact your monitoring system vendor to determine if the correct module is being used or supplied.
ADAQ95	{dbid module-name} DOES NOT HAVE THE CORRECT PIM. CONTACT YOUR VENDOR
Explanation	The specified module is incompatible with this version and/or SM-level of Adabas. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Contact your monitoring system vendor to determine if the correct module is being used or supplied.
ADAQ96	{dbid module-name} CANNOT MONITOR IOR CALLS AT THIS TIME. UNUSUAL ERROR
Explanation	Adabas cannot give control to the specified monitoring system module for purposes of monitoring I/O activity. The Adabas system-dependent interface module was not properly loaded. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Note the error message number and module name and call your Software AG technical support for assistance.

ADAQ99	{dbid} REVIEW HUB ID EQUAL TO ADABAS DBID IS NOT PERMITTED. REVIEW HUB INACCESSIBLE
Explanation	The specified Adabas Review hub ID value is identical to the value specified for the DBID parameter. The Adabas Review hub cannot have the same target ID as that of the Adabas nucleus. The Adabas nucleus completes its initialization but no calls are made to Adabas Review.
Action	Correct the hub ID value on the REVIEW parameter and restart the nucleus.

33 ADAR* System Messages

All ADAR nn messages are written to the operator console.

ADAR01 {version job-name load-name} RC={ret-code}

Explanation The LOAD or CDLOAD macro failed and ADARUN was not able to load ADAIOR. ADARUN issues a message and ends with an abnormal end (abend). The value of *load-name* is either "LOAD" for LOAD (SVC 4) or "CDLO" for CDLOAD (SVC65). The value of *ret-code* is the return code from the CDLOAD or LOAD macro, and can have the following meanings:

Return codes from the CDLOAD macro include

0	successfully completed
4	GETVIS area size OK
8	specified length exceeds GETVIS area
12	insufficient GETVIS storage
16	CDLOAD directory is full
20	nonexistent phase (when RETPNF=YES)
24	move mode phase requested

Return codes from the LOAD macro include:

0	LOAD completed successfully
4	phase not found, was deleted, or recataloged
8	unrecoverable I/O error
12	invalid library/sublibrary structure found
16	address range violation: directory entry exceeds partition, or phase does not fit in partition
20	security violation

24	incompatible library directory entries: phase length, relocation state or load point/partition start or load point/entry point address differences. The library directory entry overwrites the local entry.
28	partition/logical transient area is too small

ADAR10 Logic error at {module+offset} R0={reg0} R1={reg1} R2={reg2} R3={reg3} R4={reg4} R5={reg5} R6={reg6} R7={reg7} R8={reg8} R9={reg9} RA={regA} RB={regB} RC={regC} RD={regD} RE={regE} RF={regF}

Explanation A logic error occurred during ADARAI processing either while collecting information during a utility or nucleus run, or while executing the ADARAI utility itself. The logic error is identified by the module and offset and the registers at the time of the error are provided in subsequent lines of the message.

Action: Contact your technical support representative. Provide the actions required to trigger the error and the text of the error message itself.

ADAR12 {action} error '{error}' on {file} data set

Explanation An I/O error occurred during an operation, identified by the *action* value, which was issued against a data set by the Adabas Recovery Aid collection or utility component. The data set is identified by the *file* value and the error will be identified by the *error* value.

<i>action</i>	OPEN	- data set was being opened
	CLOSE	- data set was being closed
	READ	- data set was being read
	WRITE	- data set was being written to
<i>error</i>	A description of the error that occurred	
<i>file</i>	RLOG	- error occurred on the RLOG data set
	PLOG	- error occurred on a PLOG data set
	ASSO	- error occurred on an ASSO data set

Action: The 'error' value indicates the error that occurred while accessing the identified data set.

ADAR13	Inconsistent DBID {asso-dbid}, RLOG DBID {rlog-dbid}
Explanation	The database ID for the database in the GCBs (<i>asso-dbid</i>) does not correspond with the database ID with which the RLOG was initialized (<i>rlog-dbid</i>). This message is issued by the Adabas Recovery Aid collection component and causes the utility operation or nucleus initialization request to fail.
Action:	Either the RLOG used for this utility run was not initialized to run with the database in use, or the database ID of the database was changed. In this case, the RLOG must be reinitialized using the ADARAI PREPARE function.
ADAR14	Generation {gen-num} started
Explanation	A utility operation was executed that caused a new generation to be started. The number of this new generation, which becomes the current generation, is 'gen-num'. This message is issued by the collection component of the Adabas Recovery Aid when a new generation is started.
ADAR15	ADARAI request {request} returned RC={rc} reason={reason}
Explanation	The ADARAI data collection component was called for request <i>request</i> ; however, this request terminated with a return code and reason code as shown by <i>rc</i> and <i>reason</i> respectively. If <i>rc</i> is less than 8, the request completed successfully but messages may have been issued. If <i>rc</i> is 8 or greater, the request failed.
Action:	In many cases, this error is issued due to a situation highlighted by a previous Adabas or system message. However, if there is no obvious reason why this message has been issued, report the message to your technical support representative.
ADAR16	Insufficient storage for ADARAI processing requested {reqsize} bytes obtained {stgsize} bytes
Explanation	The Adabas Recovery Aid utility component attempted to obtain <i>reqsize</i> bytes of storage for its processing but only succeeded in obtaining <i>stgsize</i> bytes of storage. ADARAI processing fails.
Action:	Increase the amount of storage available to ADARAI by at least the byte count difference between <i>reqsize</i> and <i>stgsize</i> .
ADAR17	RLOG open error DD/RLOGR1 not found
Explanation	The Adabas Recovery Aid collection or utility component attempted to open the RLOG data set DDRLOGR1 but the file was not available to the job.
Action:	Provide the DDRLOGR1 file to the job and rerun the job.

ADAR18	RLOG open error {error}
Explanation	The Adabas Recovery Aid collection or utility component attempted to open the RLOG data set ; however. an open error occurred as identified by the 'error' value. This indicates that the DDRLOGR1 file has been found but some other error occurred.
Action:	Correct the error indicated by the 'error' value and rerun the job.
ADAR19	Serious ADARAI error failure could not be set in the RLOG dataset
Explanation	When the Adabas Recovery Aid collection component encounters any sort of problem, it attempts to set the status of the current generation to indicate that problems occurred while recording the generation. In the case where this message is issued, it was not possible to set the failure in the RLOG data set. This is particularly serious because the current generation will appear to be in a normal status but data will be missing. An attempt to use this generation to recover the database will probably lead to data being lost or invalid. The Adabas Recovery Aid data collection interface terminates abnormally with abend code 33, which means that the utility or nucleus run will also be terminated abnormally.
Action:	A new generation should be started immediately for the database in question and a note kept that the generation for which this error occurred is invalid. You should then proceed to determine what the problem was based on other error messages issued prior to this error message. If necessary, contact your technical support representative for assistance.
ADAR20	The current generation is {status}
Explanation	This message is issued by the Adabas Recovery Aid collection component when the current generation has any status other than the normal status. It is issued when the ADARAI data collection interface is called to insure that the user is aware that the current generation is in a state that may not be automatically recovered.
Action:	This is an information message and may be ignored if the status of the RLOG is acceptable to the installation. If not, a new generation should be started as soon as possible and the cause of the abnormal status for the generation investigated.
ADAR21	PLOG information not found for all or some of the following blocks: PLOG number {plog} Low PLOG block number {lowblk} [NUCID {nucid}] High PLOG bkiej number {highblk} [NUCID {nucid}]
Explanation	When the Adabas Recovery Aid utility ADARAI is building a given generation, it checks to make sure that all PLOGs required by the generation are available to it. This is based on the normal sequence of PLOG entries from the start of the generation to the end of the generation. When ADARAI expects a given range of PLOG blocks to be available but cannot find the relevant PLOG in its data, this message is issued. The data values provided are as follows:

<i>plog</i>	The number of the PLOG in which the missing blocks are found.
<i>lowblk</i>	The lowest identifiable PLOG block that cannot be found. When it is nonzero, a cluster nucleus ID follows.
<i>highblk</i>	The highest PLOG block that cannot be found. When it is nonzero, a cluster nucleus ID follows.
<i>nucid</i>	When it is nonzero, a cluster nucleus ID is appended after a high or low PLOG block number.

Action: This can happen if the current generation is the subject of the operation and the nucleus was not down at the time, or the last PLOG copy job had not completed. If this is not the case, it indicates that one or more PLCOPY jobs failed to record their information on the RLOG. To determine when and why this happened, refer back to the PLOG job that copied the blocks in question to determine why the data was not written to the RLOG data set.

ADAR31 **Generation restricted due to {reason}**

Explanation After certain events on a database, ADARAI cannot generate a recovery job which will recover the database or files on the database without changes. When this occurs, the Adabas Recovery Aid collection component sets the generation into which the data is logged to the restricted status. This message is issued when this occurs and *reason* identifies why the generation was set to RESTRICTED.

Action: This message is for information only, however, it is recommended that once this message has been issued, a new generation is started as soon as possible to insure that a generation is available with a normal status.

ADAR76 **RLOG: {count-a} blocks out of {count-b} used ({nn%})**

Explanation The minimum number of generations in the RLOG data set are using more than 50% of the RABNs available on the data set. This fact is determined when the Adabas Recovery Aid collection component writes information to the RLOG data set. Successful completion of the current nucleus or utility session is not affected by the situation. The meanings of the variable values are as follows:

<i>count-a</i>	total blocks available for logging on the RLOG
<i>count-b</i>	number of blocks currently being used on the RLOG
<i>nn</i>	percentage of RLOG blocks now used

Action: None required. This message is for your information only.

- ADAR77** **Recovery log file overflow**
- Explanation** The Adabas Recovery Aid data collection component attempted to write information for the current generation; however, the current generation does not fit on the RLOG and none of the other generations on the RLOG could be deleted. RLOG logging stops. Information for the current session could not be completely logged, and no further information will be logged. This does not affect successful completion of the current nucleus or utility session.
- Action:** Run the ADARAI LIST utility function to archive the existing RLOG information and/or back up the RLOG data set. Increase the size of the RLOG. Finally, run ADARAI PREPARE followed by an ADASAV SAVE (database) to reestablish the RLOG logging operation.
-
- ADAR78** **Unknown file element created**
- Explanation** The Adabas Recovery Aid data collection component was unable to provide the ADARAI utility with information about the sequential file used during utility execution. An "unknown file element" was written to the RLOG instead of a "file element". This does not affect successful completion of the current nucleus or utility session.
- Action:** Information about this sequential file can be recorded manually for later use in the ADARAI RECOVER function. If an ADARAI RECOVER function is executed using this generation/file, the job control statements needed for this file cannot be created. Instead, the "unknown file element" will be displayed and the ADARAI RECOVER function will complete with a return code of 04. The generated job control must then be edited to add the manually recorded file information.

34

ADAS* (Adabas SVC) System Messages

ADAS00 **SIRMVS ({yyyy - mm - dd}, SM={level}, ZAP={zap-number})**
Explanation ADASIR has executed.

<i>yyyy-mm-dd</i>	the ADASIR assembly date
<i>level</i>	the maintenance (SM) level
<i>zap-number</i>	the highest zap number applied

ADAS01 **{subsysname} enter number of Adabas V{v} ID table entries (1-{nn})**
Explanation ADASIR found an invalid ID table entry.
Action Enter the decimal ID table value. ADASIR operation continues.

ADAS03 **{subsysname} Adabas V{v} ID table for SVC {svc} initialized**
Explanation ADASIR has installed the Adabas SVC and acquired the necessary storage successfully.

ADAS04 **{subsysname} Adabas V{v} ID table initialization error**
Explanation ADASIR detected one of the following possible errors:

- IDT GETMAIN failure
- a nonzero return code from ADASVC on the 56 call
- ADASIR did not set the SSCTSUSE
- the operator terminated ADASIR
- ADASIR detected a non-VS1 environment

Action ADASIR terminates, freeing any resources acquired.

ADAS05 **{subsysname} Adabas V{v} ID table parameter(s) error**
Explanation ADASIR found an invalid input parameter. The message may be followed by messages requesting reentry of the input parameters.
Action Enter the correct parameter or parameters and rerun ADASIR or enter "no" to end ADASIR operation.

ADAS06 **{subsysname} Enter Adabas V{v} ID table subpool (228 or 241) or "NO" to abort ID table initialization**
Explanation This message occurs after error ADAS05 and requests that you verify the Adabas Vv ID table subpool where v is the version of Adabas.
Action Enter either "228" (subpool 228 / fixed CSA), "241" (subpool 241 / pageable CSA) or enter "no" to end ADASIR operation.

ADAS07 **{subsysname} Enter number of Adabas V{v} ID table entries or "NO" to abort ID table initialization**
Explanation This message occurs after error ADAS05 and requests that you verify the number of IDT entries.
Action Enter a value ranging one to four digits representing the IDT entry count or enter "no" to end ADASIR operation.

ADAS08 **{subsysname} Enter Adabas V{v} SVC number (200-255) or "NO" to abort ID table initialization**
Explanation This message occurs after error ADAS05 and requests that you verify the SVC number for the version of Adabas specified.
Action Enter a three-digit SVC value ranging 200-255 or enter "no" to end ADASIR operation.

ADAS09 **{subsysname} Adabas V{v} SVC {svc} table entry at {svc-addr} invalid is {bad-entry bad-entry} should be {good-entry good-entry}**
Explanation This and any associated ADASnn messages occur when ADASIR finds an incorrect SVC table entry or when message ADAS14 was answered with "p" (prompt option). The variable values in the message have the following meanings:

<i>v</i>	version of Adabas
<i>svc</i>	SVC number
<i>svc-addr</i>	address of the SVC table entry
<i>bad-entry</i>	current SVC table entry value in error
<i>good-entry</i>	desired SVC table entry value

Action ADASIR follows this message with message ADAS10 asking if the SVC entry in error should be changed to the desired value.

ADAS10 {subsysname} should SVC table entry be changed ('Y') or should Adabas ID table initialization be aborted ('N')

Explanation This message occurs after message ADAS09 and requests that you confirm a change of the SVC table entry in error to a desired value proposed by ADASIR.

Action Enter "Y" (yes) to update the SVC entry. Entering any other value leaves the SVC entry as it was.

ADAS11 {subsysname} Adabas V{v} ID table for SVC {svc} initialized with {cccc} entries
 IDT:{address} IDTExt:{address} FIIBS:{address} RClass:{class} SSCT:{address}
 SVC:{address} VRS:{vrs} DATE:{date}

Explanation SVC with the number *svc* has been installed and the ID table storage for a count of *cccc* entries was successfully allocated. The addresses of the SVC, major CSA data structures, the SAF class name for authorization and the release and assembly date for the SVC are also provided in the message.

Action No action is required for this informational message.

ADAS12 {subsysname} Adabas V{v} ID table initialization error {n}

Explanation ADASIR detected error *n*, where *n* is one of the following:

1	The GETMAIN for the ID table was unsuccessful.
2	The Adabas SVC request to initialize the ID table returned a nonzero return code. Probable cause is that the subsystem name in the IEFSSNxx member of SYS1.PARMLIB does not match the contents of ADASVC + x'28'.
3	The Adabas SVC request to initialize the ID table did not set the correct value in the SSCT. Probable cause is an incorrect SVC number.
4	The operator terminated initialization.
7	The SVC table entry for the Adabas SVC does not contain the address of the Adabas SVC.
10	SVCUPDTE macro failure.
11	The GETMAIN for the FIIBS and IDT extension tables was unsuccessful.

Action Correct the error condition and re-IPL (if necessary) or rerun ADASIP.

ADAS13 {subsysname} leave message ADAS11 or ADAS12 (N or Y)

Explanation ADASIR keeps the display of the previous ADAS11 or ADAS12 message on the screen if you specify "Y"; otherwise, the message display is removed and lost.

Action Enter "Y" to keep the message display; otherwise, the message is removed.

ADAS14 **{subsysname} prompt operator to update SVC table entry N or P**
Explanation This message asks whether the operator should be prompted to update the SVC table entry (P) or not (N).
Action Enter "P" to prompt the operator for the SVC table entry; messages ADAS09 and ADAS10 occur when "P" is entered. Enter "N" (no prompt) to let ADASIR select the SVC value; message ADAS15 occurs when "N" is entered.

ADAS15 **{subsysname} SVC {svc} table entry changed without prompting operator**
Explanation SVC *svc* was changed without a prompt being sent to the operator.

ADAS16 **Existing ADASVC {svc} uses subsystem {subsys}**
Explanation ADASIP is being used to reinstall a copy of the Adabas SVC. Either the specified subsystem is currently being used by another SVC, or the specified SVC currently specifies a different subsystem.
Action If the error relates to the specified subsystem, it is followed by user ABEND 435. If the error relates to the specified SVC number it is followed by user ABEND 436. User ABEND 436 may be overridden by the ADASIP FORCE=Y parameter.

ADAS17 **IDT for SVC {svc} has active IDTE for target {target}**
Explanation ADASIP is being used to reinstall a copy of the Adabas SVC. The IDT being used by the currently installed SVC has a possibly active target as indicated by an active IDTE. There is one message for each such target.
Action It is followed by user ABEND 437. This ABEND may be overridden by the ADASIP FORCE=Y parameter.

ADAS20 **At {address}, {length} bytes {action} {area-description}**
Explanation When ADASIP refreshes an existing Adabas SVC, the common storage area (CSA) associated with the old SVC load module and its associated IDT-related structures is released. If a PLXCB is found, its components are released as well. This message appears for each attempt to release storage:

<i>address</i>	CSA area address, in hexadecimal
<i>length</i>	CSA area length, in hexadecimal
<i>action</i>	One of the following: CSA RELEASED RELEASE FAILED

<i>area-description</i>	One of the following: Replaced SVC IDTH / IDT / IIBS Cluster Segment PLXCB Base PLXCUSER Segment SMP Segment Fat IIBS IDTH / IDTE IDT Extension SVC Fixed Area
-------------------------	--

- ADAS21** **Replaced SVC CSA not released, {nn} pending resource managers**
- Explanation** ADASIP is being used to reinstall a copy of the Adabas SVC, replacing an existing instance that was installed in CSA with ADASIP. ADASIP cannot release the CSA storage used by the existing instance because one or more z/OS Resource Manager routines may be pending.
- Action** ADASIP installs the new SVC instance and does not release the CSA used by the previous instance.
-
- ADAS30** **nn SVC work areas released**
- Explanation** During termination, the server will release work areas that were obtained in the server's address space by the SVC to process user commands. The number of work areas is the high-water mark of the number of simultaneous processes.
- Action** Information only, no action required.
-
- ADAS31** **Service ABTERM resource manager { ADDRSPC TERM | TASK TERM }**
Service ABTERM resource manager released IDTE
- Explanation** A z/OS Resource Manager recovery routine was entered after a server address space abend to release the IDTE.
- Action** If the release was successful, it will not be necessary to specify ADARUN FORCE=YES when restarting.
-
- ADAS32** **S64 {scope} affinity resource manager {event}**
S64 object at {address}
S64 object user token is {token}
S64 {scope} affinity released
S64 {scope} affinity released {return-code}/{reason-code}
- Explanation** A z/OS Resource Manager recovery routine was entered after an abend to release a local or system affinity to a z/OS shared 64-bit addressable memory object. Any non-zero return code received from z/OS IARV64 is shown.

Action If the attempt fails, examine the IARV64 return and reason code description in IBM documentation. If the cause is not clear, notify your Software AG support.

ADAS33 **Security subsystem denied authorization**
Security subsystem or APF authorization is required
APF authorization is required
Security subsystem error SAF/Ret/Rsn SAF
{return-code}/{security-subsystem-return-code}/{security-subsystem-reason-code}

Explanation The nucleus attempted to initialize or access an ADASVC function that required authorization.

Action Provide the appropriate authorization. If the message indicates a security subsystem error, contact your security administrator or your Software AG technical support representative for assistance.

ADAS34 **Invalid pointer SAGVT**
Invalid pointer to SAGVT at {addr} cleared
{hex-storage-bytes-0-15}
{hex-storage-bytes-16-31}

Explanation The Software AG Vector Table (SAGVT) is an internal z/OS CSA structure anchored in a CVT-based field assigned by IBM to Software AG. During SVC installation and initialization, Adabas SVC processing found an entry in Software AG's assigned anchor slot that did not point to a valid SAGVT. This may be because another vendor's product is using Software AG's assigned slot or the storage was corrupted.

The invalid address and 32-bytes of storage at that address are dumped and included in the message to aid in problem determination. The SAGVT anchor slot is cleared. Expect a subsequent [ADAS35](#) message as a new SAGVT is installed.

This message appears in red on the operator's console and does not scroll off the display.

Action Contact your Software AG technical support representative.

ADAS35 **SAGVT {{installed}|{reinstalled}}**

Explanation The Software AG Vector Table (SAGVT) is an internal z/OS CSA structure anchored in a CVT-based field assigned by IBM to Software AG. During SVC installation and initialization, Adabas SVC processing did not find a usable SAGVT.

If the IBM-assigned pointer to the SAGVT is zero, a new SAGVT is allocated and installed.

If the IBM-assigned pointer to the SAGVT identifies a SAGVT version older than the one known to the installing ADASVC program, the SAGVT is reinstalled, replacing the older one.

Action No action is required for this informational message.

ADAS36	Service ABTERM resource manager task term cleanup
Explanation	A z/OS resource manager recovery routine was entered after a server address space ABEND to POST any incomplete commands and release the IDTE.
Action	No action is required for this informational message.
ADAS37	ENFReq {Listen Delete} event 53 return code {rc}
Explanation	A non-zero return code was received from an ENFREQ request to activate or delete a z/OS Event Notification Facility (ENF) exit that detects time zone and leap second changes. The return code (<i>rc</i>) is given in the message.
Action	Examine the ENFREQ return code description in IBM documentation. If the cause is not clear, notify your Software AG technical support representative.
ADAS39	ADADSP DBID {dbid} SVC {svc} AbTerm resource manager {AddrSpc term Task term cleared ALET}
Explanation	An ADADSP subtask in ADACOM failed such that it did not clean up the IDTH prefix entry for a PLXCB dataspace. The Resource Manager routine attempted recovery at either address space or task termination. If an ALET for this DBID/SVC combination was found in the IDTH prefix entry, the entry is cleared.
Action	Restart the failed ADACOM subtasks and any affected nuclei. Contact your Software AG technical support representative if the reason for the termination is unclear.

35

ADASIP* (Adabas z/VSE SVC) System Messages

ADASIP00 **Adabas V{av.ar} VSE SIP started**
SIP is running under z/VSE V{vv.vr.vm}
({yyyy-mm-dd}. SM={sm-level} , ZAP={zap-level})
SIP IS LOADING ADABAS SVC LEVEL {sv.sr.sp}
ADASIP IS LOADING ADABAS SVC AMODE={a-mode}

Explanation The ADASIP program has started. The following substitutions appear in the message:

Substitution	Description
<i>av.ar</i>	version and release of Adabas.
<i>vv.vr.vm</i>	version, release, and modification level of z/VSE
<i>yyyy-mm-dd</i>	date of ADASIP module assembly
<i>sm-level</i>	modification level of the ADASIP module
<i>zap-level</i>	Zap level of the ADASIP module
<i>sv.sr.sp</i>	version, release, and service pack of the Adabas SVC
<i>a-mode</i>	the AMODE setting of the Adabas SVC

ADASIP01 **SUBSID {macro error}**

Explanation ADASIP received a nonzero return code from the operating system.

Action: The z/VSE operating system release level is too low for installing Adabas. Refer to the Adabas Installation documentation for the minimum allowed z/VSE levels.

ADASIP02	Unsupported VSE release based upon SUBSID
Explanation	An ADASIP validation check indicates an unsupported operating system level.
Action:	The z/VSE operating system release level is too low for installing Adabas. Refer to the Adabas Installation documentation for the minimum allowed z/VSE levels.
ADASIP03	No SYSPARM value specified for SVC
Explanation	ADASIP could not find a SYSPARM input, and a zap has not be applied to the specified SVC.
Action:	Either provide the SVC with SYSPARM or apply a zap to the specified SVC with ADASIP.
ADASIP04	Default value used for the SVC
Explanation	No SYSPARM SVC has been used. ADASIP defaults to using the SVC that has a zap applied.
ADASIP05	Non-numeric data found in SYSPARM field
Explanation	Either SYSPARM or the default ADASIP SVC contains a nonnumeric value.
Action:	Correct the specified SYSPARM value, or set the default SVC value to 30.
ADASIP06	Invalid range specified for the SVC 31-256
Explanation	ADASIP found an SVC outside the allowed range in SYSPARM or the ADASIP default SVC.
Action:	Set the SVC to an unused SVC value within the allowed range. SVC ranges and recommended values are described in the Adabas Installation documentation .
ADASIP08	ADASVC{vv} was not found in the SVA
Explanation	While performing a z/VSE load, ADASIP found that the specified level ADASVC was not in the SVA.
Action:	Issue the SET SDL for ADASVC _{vv} . It may be necessary to relink the Adabas SVC with SVA using the PHASE statement if the Adabas SVC is not found in the Adabas library.
ADASIP09	No match on ID - incorrect ADASVC loaded
Explanation	ADASIP found an incorrect SVC version while attempting a load operation.
Action:	Relink ADASVC _{vv} with the correct SVC module.

ADASIP10	Unknown keyword in PARM field
Explanation	ADASIP found an incorrect keyword in the PARM field.
Action:	Correct the keyword parameter and rerun the job.
ADASIP11	Non-numeric data specified for NRIDTES
Explanation	The ADASIP NRIDTES= keyword parameter specified non-numeric data.
Action:	Correct the NRIDTES= data, then resubmit ADASIP.
ADASIP12	No overriding NRIDTES specified
Explanation	The default NRIDTES was used. No error has occurred.
ADASIP13	SVC table entry was found to be invalid
Explanation	The SVC number provided by SYSPARM is either not valid, or does not represent either the old or new version of the z/VSE Adabas SVC. This error can occur if the UPSI statement's "C" parameter specified "0".
Action:	Respecify the UPSI statement, or specify another unused SVC value. Rerun ADASIP.
ADASIP14	GETVIS failure for IDT in SVA
Explanation	The GETVIS of the IDT passed a nonzero return code back to ADASIP, meaning the GETVIS size was insufficient.
Action:	Increase the SVA GETVIS size, re-IPL the operating system, and rerun ADASIP.
ADASIP15	Router unable to initialize IDT
Explanation	ADASIP received a nonzero return code from the 56 call to the SVC.
Action:	Contact your Software AG technical support representative.
ADASIP16	WARNING -- IDT table already exists
Explanation	ADASIP detected that an IDT table for this SVC already exists.
Action:	No action is required for this warning message.
ADASIP17	Incorrect SVC suffix after comma in SYSPARM
Explanation	An attempt was made to run this program more than once for the current IPL. A second IDT for the program is not required.
Action:	Correct the SYSPARM specification for the two-byte SVC suffix, and rerun the job.

ADASIP18	Non-numeric data specified for DMPDBID
Explanation	The ADASIP DMPDBID keyword parameter contains nonnumeric data.
Action:	Correct the DMPDBID specification, and rerun the job.
ADASIP19	DBID cannot be found in IDTE
Explanation	The ADASIP program could not find an entry for the DMPDBID database in the IDT area.
Action:	Either correct the DMPDBID specification or start the specified database, then run ADASIP to perform a "snap" dump of the command queue.
ADASIP20	The IDT and SVC have been dumped to SYSLST
Explanation	A request to ADASIP to dump the IDT and then SVC via UPSI 80. No error has occurred.
ADASIP21	No IDT table was found for specified SVC
Explanation	ADASIP found that the SVC has no address for the IDT.
Action:	Specify the correct SVC, or initialize with ADASIP first.
ADASIP22	The SVC has already been installed
Explanation	ADASIP found that the same program is being run again.
Action:	The SVC is not installed and no IDT table is needed. To reinstall the same SVC, you must first perform a SET SDL.
ADASIP23	The SVC table cannot be listed under DOS/MVT
Explanation	The option to display the SVC table is specified under z/VSE.
ADASIP24	The IDT has been pagefixed by user option
Explanation	UPSI (X'20') was selected to pagefix the IDT in the system GETVIS area.
ADASIP26	Could not load the ADAOPD table
Explanation	ADASIP was unable to load phase ADAOPD.
Action:	Ensure that ADAOPD is available for loading and rerun the job.

ADASIP27	ADASVC{xx} must be AMODE=31, RMODE=24
Explanation	ADASIP detected that the Adabas SVC has invalid link-edit attributes.
Action:	Relink the Adabas SVC with the correct attributes and rerun the job.
ADASIP28	ADASIP is AMODE=31
Explanation	ADASIP detected that it is AMODE=31.
Action:	Relink ADASIP AMODE=24.
ADASIP29	PRODID macro failure
Explanation	ADASIP received a nonzero response code from the PRODID DEFINE macro.
Action:	Investigate the cause of the error. Correct it and rerun the job.
ADASIP30	ADASVC{vv} {svc} installed (Date {yyyymmdd})
Explanation	ADASIP has installed SVC number <i>svc</i> successfully.
ADASIP31	{address}=SVC address
Explanation	The SVC has been loaded at the indicated address.
ADASIP32	{address}=IDT address
Explanation	The ID table has been allocated at the indicated address.
ADASIP33	Invalid value specified for REPLACE parameter
Explanation	An invalid value was specified on the REPLACE parameter.
Action:	Specify YES, Y, NO or N for the REPLACE parameter and rerun the job.
ADASIP36	{address}=extended IIBS address
Explanation	The extended IIBS have been loaded at the indicated address.
ADASIP37	{address}=IDT Extension address
Explanation	The IDT extension has been allocated at the indicated address.
Action:	No action is required for this informational message.

ADASIP38 **{address}=SVC Work Area address**
Explanation The SVC work area has been allocated at the indicated address.
Action: No action is required for this informational message.

ADASIP39 **Error -- Targets still active on SVC{nnn}**
Explanation ADASIP detected that there are still active targets on the SVC listed in the message (*nnn*) and is unable to continue processing.
Action: No action is required for this informational message.

ADASIP40 **VSE SVC {svc} is {status} AM={a-mode} RM={r-mode} AR={reg-mode} SVCT={svc-tab-addr} MODT={svc-mod-addr}**
Explanation This message occurs when the option to list the SVC table is selected, and specifies the following values:

<i>svc</i>	the z/VSE SVC number
<i>status</i>	"USED" or "UNUSED"
<i>a-mode</i>	AMODE of this SVC, if used (24 or ANY)
<i>r-mode</i>	RMODE of this SVC, if used (24 or ANY)
<i>reg-mode</i>	access register mode of this SVC, if used (Y=yes, N=no)
<i>svc-tab-addr</i>	address of the SVC table entry for this SVC
<i>svc-mod-addr</i>	address of the SVC mode table entry for this SVC, if present

Action: None required. This message is for your information only. Do not use SVC50, even though it is indicated as "unused".

ADASIP41 **VSE SVC table audit completed**
Explanation ADASIP has completed listing the z/VSE SVC table.

ADASIP50 **The command queue has been dumped to SYSLST**
Explanation ADASIP has completed listing the command queue for the specified database.

ADASIP60	Only 1 CPU can be active during ADASIP
Action	Use "SYSDEF TD,STOP=ALL" to stop all but one CPU so that ADASIP can run. Then restart your CPUs again.
ADASIP61	Rerun ADASIP after using TDSERV to stop CPUs
Explanation	Occurs in conjunction with ADASIP60.
ADASIP62	GETVIS failed for ADASTUB module
Explanation	Not enough SVA storage to load ADASTUB.
Action	Consult with your system programmer.
ADASIP63	ADASTUB module loaded at {address}
Explanation	Information message indicating module load address.
ADASIP64	No match on ID - incorrect ADASTUB loaded
Explanation	ADASTUB phase is incorrect.
Action	Consult with your system programmer, or contact Software AG.
ADASIP65	ADASTUB SVC table not found
Explanation	ADASTUB phase is incorrect.
Action	Consult with your system programmer, or contact Software AG.
ADASIP66	ADASTUB SVC table is full
Explanation	You have more than 10 SVCs active on this z/VSE machine.
Action	Contact Software AG for information about increasing the table size.
ADASIP67	PAGEFIX for ADASIP failed
Action	Increase the SETPFIX value and rerun.
ADASIP68	PAGEFREE for ADASIP failed
Action	Consult with your system programmer.

ADASIP69	TURBO dispatcher stub active
Explanation	Adabas Turbo support is now active on this z/VSE machine.
ADASIP70	VSE supervisor hook install failed
Explanation	Either this version of the z/VSE 2 supervisor is not supported, or the vendor installation logic for the first-level interrupt handler is incorrect.
Action	Call Software AG; have message ADASIP72 available.
ADASIP71	Load of module ADASTUB failed
Explanation	The ADASTUB module was not found in the LIBDEF SEARCH chain.
ADASIP72	Code is : {code}
Explanation	Occurs after message ADASIP70.
ADASIP73	ADANCHOR incorrect or not found in SVA
Explanation	The ADANCHOR module was not found in the SVA; no SET SDL has been done.
ADASIP74	Info: Stub activated by previous ADASIP
Explanation	Adabas Turbo STUB has been installed by a previous ADASIP.
ADASIP75	ADANCHOR and ADASTUB not dumped - not active
Explanation	When attempting to dump Adabas control blocks with ADASIP, the modules were not dumped because Adabas Turbo support is not active.
ADASIP76	Adabas turbo stub not activated due to error
Explanation	An error occurred during the installation of the Adabas Turbo stub.
ADASIP77	This Adabas SVC will run in non-turbo mode
Explanation	An error occurred during the installation of the Adabas Turbo stub. This SVC will run in non-Turbo mode from now on.

ADASIP78	VSE turbo dispatcher {nn}
Explanation	Version of z/VSE Turbo Dispatcher.
ADASIP79	Should we stop the CPUs? (yes/no)
Explanation	This message appears following ADASIP60 if more than one CPU is active during ADASIP processing.
Action	Replying "no" terminates the job. Replying "yes" causes CPUs to be temporarily deactivated while ADASIP runs. ADASIP will reactivate any deactivated CPUs before terminating.
ADASIP80	SVC{nnn} Target ID {id} is active in partition {pp}
Explanation	<p>ADASIP does not allow an SVC to be reinstalled if there are active targets using the SVC, unless parameter REPLACE=YES is specified. If ADASIP parameter REPLACE=YES was specified, ADASIP replaces the current SVC regardless of any active targets.</p> <p>An attempt to reinstall an SVC by rerunning ADASIP when there are active targets using the SVC results in warning messages ADASIP80 and ADASIP81 being issued. If the reply to ADASIP81 is "no", ADASIP terminates processing. If the reply to ADASIP is "yes", ADASIP will check again for active targets. If active targets are found, messages ADASIP80 and ADASIP81 will appear again. To proceed with ADASIP processing, active targets must be terminated before replying "yes" to message ADASIP81.</p> <p>Note: ADASIP will only flag a target as active if the job which activated the target is still running.</p>
Action	No action is required for this warning message.
ADASIP81	Should we continue processing? (yes/no)
Explanation	An attempt was made to reinstall an SVC while there are active targets using the SVC. Unless the ADASIP parameter REPLACE=YES is specified, ADASIP does not allow an SVC to be reinstalled if there are active targets using the SVC. This prompt allows you to continue or stop processing.
Action	Enter "yes" to continue or "no" to terminate processing.
ADASIP85	SVA-24 storage allocated: {nnnnn}K SVA-31 storage allocated: {nnnnn}K
Explanation	ADASIP has allocated <i>nnnnn</i> K of SVA storage below (SVA-24) or above (SVA-31) the 16 MB line.
Action	No action is required for this informational message.

ADASIP86	Reuse previous ADASTUB loaded at {address}? (yes/no) SVA-31 storage allocated: {nnnnn}K
Explanation	ADASIP detected that ADASTUB has already been loaded. A SET SDL for ADANCHOR should only be issued once per IPL. However, if ADASIP is rerun, and a SET SDL for ADANCHOR is issued a second time in error, it should be possible to preserve the existing Adabas communications environment by answering "yes" to message ADASIP86.
Action	Reply "yes" to reuse the ADASTUB or "no" to load a new copy of ADASTUB. The recommended reply is "yes". Do not reply "no" to this message unless directed to do so by your Software AG technical support representative.
ADASIP87	SYSLST unavailable
Explanation	ADASIP is not able to print messages on SYSLST, as this is unavailable. Console messages only will be issued. ADASIP continues processing.,
Action	No action is required for this informational message.
ADASIP88	Invalid parameter combination
Explanation	ADASIP detected an invalid combination of PARM parameters or UPSI bytes.
Action	Correct the parameters or UPSI bytes and rerun the job.

36

ADASM* Adabas SMF Processing Messages

ADASM1	SMF=YES not allowed with MODE=SINGLE
Explanation	The specified ADARUN parameters are incompatible and cannot be specified at the same time in a nucleus startup job. The nucleus fails to initialize.
Action	Correct the ADARUN parameters and restart the nucleus.
ADASM2	ADASMF unable to obtain storage
Explanation	Sufficient virtual storage for Adabas SMF is not available. The nucleus fails to initialize.
Action	Either increase the size of the nucleus region or disable SMF recording by setting the ADARUN SMF parameter to NO.
ADASM3	SMF89 Registration return code {rc}
Explanation	The IBM z/OS service IFAUSAGE produced a non-zero return code when registering for type 89 SMF records. The nucleus initializes without registering for type 89 SMF records.
Action	The return codes are documented in the <i>z/OS MVS System Management Facilities (SMF)</i> , IBM document SA22-7630. Contact your Software AG technical support representative if you are unable to understand the error. You may disable registration attempts by setting the ADARUN SMF89 parameter to NO.
ADASM4	Invalid syntax of value for {parm}
Explanation	An error was detected in the syntax of the parameter named in the message (<i>parm</i>). The parameter may be an ADARUN parameter or an operator command operand. The invalid value is ignored.
Action	Remove or correct the specified parameter and try again.

ADASM5	Unknown detail section {dtl} ignored
Explanation	An invalid Adabas SMF record detail section mnemonic was specified in an ADARUN parameter or an operator command operand. The invalid mnemonic is given in the message (<i>dtl</i>). The invalid value is ignored.
Action	Remove or correct the specified detail section mnemonic and try again.
ADASM6	{dtl} detail section disabled, maximum size exceeded
Explanation	A single instance of the Adabas SMF record detail section listed in the message (<i>dtl</i>) exceeded the size that could be contained in a single Adabas SMF record. The specified detail section is disabled.
Action	If the detail section is a USER-type detail section, correct your SMF user exit. Otherwise, contact your Software AG technical support representative for assistance.
ADASM7	Unknown SMF operator command
Explanation	The SMF operator command was not recognized. It is ignored.
Action	Specify a valid SMF operator command.
ADASMA	Unable to get interval, using 15 minutes
Explanation	The user specified ADARUN parameter <code>SMFINTERVAL=[SUBSYS GLOBAL]</code> . ADASMF was unable to obtain a valid SMF interval from z/OS. A default interval was used. When the default interval expires, ADASMF will make another attempt to obtain the SMF interval.
Action	If this condition persists and you are not able to identify a cause, contact your Software AG Technical Support Representative for assistance.
ADASMB	Unable to set timer, interval records suspended
Explanation	ADASMF was unable to set a timer for the next interval record.
Action	Contact your Software AG Technical Support Representative for assistance. You may try Adabas operator commands to set <code>SMFINTERVAL</code> to <code>NONE</code> and then back to the original specification.

37 ADAU* Utility Status Messages

These general status messages describe current utility operating status. Often, they are the response to a DSTAT operator command.



Note: Each of the messages in this section starts with the relevant database ID.

ADAU01 {version} {job-name} {name} RC {ret-code}

Explanation

z/VSE systems only: ADAUSER cannot perform CDLOAD or LOAD ADARUN. ADAUSER provides the following information:

<i>version</i>	the Adabas version
<i>job-name</i>	the z/VSE job name
<i>name</i>	LOAD for SVC4, or CDLO for SVC65
<i>ret-code</i>	LOAD return code from the CDLOAD or LOAD supervisor call (SVC)

ADAUSER provides a dump using JDUMP, and then terminates with the information that is required to resolve the load problem.

ADAU02 {version} {job-name} {pgm} incorrect RMODE

Explanation

ADAUSER detected an RMODE error. ADAUSER provides the following information:

<i>version</i>	the Adabas version
<i>job-name</i>	the name of the z/VSE job
<i>pgm</i>	the name of the program with the incorrect RMODE

Action: Relink the program with RMODE=24.

ADAU08	Operator type-in : {command}
Explanation	This message confirms entry of the operator command <i>command</i> .
ADAU09	Invalid request -- only DSTAT allowed
Explanation	This message is a reply to a utilities operator command other than DSTAT, which is the only valid operator command at this time.
Action:	Enter the operator command DSTAT.
ADAU10	{count} blocks of {total} saved
Explanation	This message is the response to the ADASAV operator command DSTAT. The <i>count</i> value is the number of blocks already processed, and <i>total</i> is the total number of blocks to be saved.
ADAU11	{count} blocks out of {total} restored
Explanation	This message is the response to the ADASAV operator command DSTAT. The <i>count</i> value is the number of blocks already restored, and <i>total</i> is the total number of blocks to be restored.
ADAU12	Restoring protection log tape
Explanation	This message, a response to the ADASAV utility's operator command DSTAT, indicates that the second pass of the RESTONL function has begun. The file or database has been restored, and ADASAV is now processing the protection log.
ADAU13	VOLSER for {dd-name} = {volser} RABN [A D] {first-rabn#}
Explanation	This message is displayed by ADASAV when reading from or writing to a new tape. The "A" or "D" that might appear between "RABN" and the first RABN number (<i>first-rabn#</i>) stand for A ssoc or D ata.
ADAU14	ADASAV - run with save tape {session-id}
Explanation	This message shows the session number assigned to the save tape created by the save operation.
ADAU15	File {file} {added to removed from} file list ({reason})
Explanation	The specified file was added or removed from the file list for the specified reason. <ul style="list-style-type: none"> ■ Reasons for adding files: coupled or expanded file ■ Reasons for removing files: <ul style="list-style-type: none"> ■ file not loaded

- inconsistent expanded or coupled file
- file in inconsistent state
- not flagged "modified"

If the file is added to the file list, it is saved; if the file is removed from the file list, it is not saved at all.

Action: None required. This is an informational message only. To restore a file that was removed from the file list, the appropriate previous SAVE data set must be used.

ADAU16 **No file has been modified since last save; no output data set was created**

Explanation The output data set is not created because there is no change.

Action: The previous SAVE tapes should be used to restore the file. To restore a removed file, the appropriate save data set must be used.

ADAU17 **Merging DELTA SAVE tapes**

Explanation This message is the response to the ADASAV operator command DSTAT. ADASAV is currently creating a delta save data set by merging.

ADAU18 **{count} blocks out of {total} merged**

Explanation This message is a response to the ADASAV operator command DSTAT. ADASAV is currently creating a full save data set by merging. *count* blocks have already been written; *total* blocks are to be written.

ADAU19 **During restore delta phase**

Explanation This message is a response to the ADASAV operator command DSTAT. ADASAV is currently in the second phase of a delta restore operation. The full save data set has already been restored.

ADAU20 **ADADBS OPERCOM {command}**

Explanation The ADADBS OPERCOM utility issued the specified operator command.

Action: None required. This informational message informs you of any changes in file access, etc., that may result from ADADBS OPERCOM operation.

ADAU21	Sorting/loading descriptor {descriptor}
Explanation	This message is a response to ADALOD operator command DSTAT, and indicates that ADALOD is sorting and loading the inverted list for the specified descriptor.
ADAU22	Loading data storage. RECNO={count}
Explanation	This message is a response to the ADALOD operator command DSTAT, and advises that ADALOD is now loading records into data storage. Thus far, the specified number of records have been loaded.
ADAU23	Sorting ADAM records. RECNO={count}
Explanation	This message is a response to the ADALOD operator command DSTAT, and advises that ADALOD is now presorting data storage (DS) records by their ADAM keys. Thus far, the specified number of records have been sorted.
ADAU24	Computing index space for {descriptor}
Explanation	This message is a response to the ADALOD operator command DSTAT, and indicates that ADALOD is now computing index space requirements for the specified descriptor.
ADAU25	UNLOADING DATASTORAGE, FILE=file-number, RECNO=record-count
Explanation	This message is a response to the ADAORD operator command DSTAT, and indicates that ADAORD is now unloading the Data Storage for the specified file to DD/FILEA. Thus far, the number of records specified by "record-count" have been unloaded.
ADAU26	Unloading index, file={file-number}
Explanation	This message is a response to the ADAORD operator command DSTAT, and indicates that ADAORD is now unloading the inverted list for the specified file to DD/FILEA for the file "file-number".
ADAU27	Unloading DSST, file = {file-number}
Explanation	This message is a response to the ADAORD operator command DSTAT, and indicates that ADAORD is now unloading the Data Storage space table (DSST) for the specified file to DD/FILEA.

ADAU28	Unloading AC, file={file-number}
Explanation	This message is a response to the ADAORD operator command DSTAT, and indicates that ADAORD is now unloading the address converter (AC) for the specified file to DD/FILEA.
ADAU29	Loading datastorage, file={file-number}, RECNO={record-count}
Explanation	This message is a response to the ADAORD operator command DSTAT, and indicates that ADAORD is now loading the Data Storage for the specified file from DD/FILEA. Thus far, the number of records specified by "record-count" have been loaded.
ADAU30	Loading index, file={file-number}
Explanation	This message is a response to the ADAORD operator command DSTAT, and indicates that ADAORD is now loading the inverted list for the specified file from DD/FILEA.
ADAU31	Loading DSST, file = {file-number}
Explanation	This message is a response to the ADAORD operator command DSTAT, and indicates that ADAORD is now loading the Data Storage space table (DSST) for the specified file from DD/FILEA.
ADAU32	Loading AC, file={file-number}
Explanation	This message is a response to the ADAORD operator command DSTAT, and indicates that ADAORD is now loading the address converter (AC) from DD/FILEA.
ADAU33	Client option in effect for file {file-number}
Explanation	The ADAULD utility displays this message to indicate that the file being loaded has the CLIENT option in effect.
ADAU34	Blocks {block-a} - {block-n} could not be formatted Invalid SIZE parameter Blocks {block-c} – {block-d} exceed capacity of file
Explanation	The format SIZE parameter in the ADAFRM parameters for the specified file exceeds its maximum cylinder or block size. This returns a User Abend 35 from the ADAFRM utility.
Action	To format the remaining blocks, create the file with a size that can match the SIZE requested and rerun the ADAFRM job for all files not reported as formatted.

ADAU35	USERISN-option in effect for file {file-number}
Explanation	The ADAULD utility displays this message to indicate that the file being loaded has the USERISN option in effect.
ADAU36	Missing second output data set
Explanation	User exit 9 returned an indication to write a record to DDOUT2, which is not defined. All records are written to DDOUT1.
Action:	If the records are to be unloaded onto two output data sets under control of user exit 9, specify DDOUT2 and rerun the job.
ADAU37	Blocks {block-a} - {block-n} could not be formatted
Explanation	The number of blocks to be formatted must be at least the number of blocks per track. If the number of blocks to be formatted is more than the number of blocks per track, then "block-n" must be the last block of the track. Block "block-n" is not the last block of a track, or the ADAFRM SIZE parameter is less than the number of blocks per track. The partial track was not formatted.
Action:	To format the remaining blocks, specify a block range that spans a complete track.
ADAU38	File not linked into file chain
Explanation	The file has been loaded, but for some reason could not be linked into the expanded file chain. The cause could be one of the following: <ul style="list-style-type: none"> ■ another file in the chain is locked ■ the chain was modified during the load operation
Action:	Link the file into the expanded file chain using Adabas Online System (AOS).
ADAU39	No checkpoint written
Explanation	The nucleus is in read-only state. A checkpoint cannot be written.
ADAU40	Point of no return reached
Explanation	The ADAORD utility has begun its second pass. Any abend after this point requires that the file or database be restored before being used.

ADAU41	ADAORD invoked from job {job-name}
Explanation	ADAORD was started by the specified job. This message follows message ADAU40.
ADAU42	ADAVAL file={file-number}, descriptor={descriptor}
Explanation	This message occurs in response to the ADAVAL DSTAT operator command, and indicates that ADAVAL is now validating descriptor "descriptor" in file "file-number".
ADAU43	More records on ADALOD input than requested by NUMREC
Explanation	The ADALOD NUMREC parameter restricts the number of records to be loaded. In this case, the input data set contains more records than requested.
Action:	No action is required. Processing continues normally, but returns a response code of 4 (ADARSP004) to the operating system.
ADAU44	More records on ADALOD input than ISNs available
Explanation	All ISNs available in the address converter (AC) are already assigned to records in the input file, and new ISNs cannot be allocated because NOACEXTENSION is active.
Action:	Processing continues normally, but returns a response code of 4 (ADARSP004) to the operating system. If the file is part of an expanded file, you can load the remaining records into another part of the expanded file.
ADAU45	Abend during chain processing
Explanation	Warning: An abnormal termination (abend) occurred while ADALOD was updating the expanded file's chain information. The information could be inconsistent, and any further processing of the file will create incorrect results.
Action:	Perform ADAREP to create an expanded file report, and check the expanded file linkage. Any errors must be corrected before processing can continue.
ADAU46	Abend during file processing
Explanation	An error occurred while ADALOD was processing the file. The file is now in load status, but cannot be accessed.
Action:	Correct the cause of the error, and then either <ul style="list-style-type: none">■ restart the ADALOD job;■ delete the file and rerun the ADALOD job; or■ restore the SAVE file copy and rerun the ADALOD job.

ADAU47 **Abend during finishing processing**
Explanation The file processing has completed, but a problem occurred while writing either

- recovery log information; or
- the checkpoint.

Action: If necessary, ensure that you can redo the ADALOD job when a RESTORE/REGENERATE is done.

ADAU48 **Loading records with USERISN-option suppressed**
Explanation The USERISN option was in effect when the file was created by ADACMP or ADAULD. The USERISN option has been suppressed by specifying USERISN=NO. All ISNs are assigned by ADALOD.

ADAU49 **Loading records with USERISN-option in effect**
Explanation The file is loaded with the USERISN option in effect. All ISNs are taken from the input file.

ADAU50 **{function} input volume = {volume}, PLOGNUM = {session-number}**
FROMBLK = {block-number-a}, FROMTIME = {date} {time}
TOBLK = {block-number-b}, TOTIME = {date} {time}

Explanation This message is a response to the ADARES operator command, DSTAT:

<i>function</i>	either REGENERATE or BACKOUT
<i>volume</i>	the current input volume
<i>session-number</i>	the protection log number now being processed
<i>block-number-a</i> <i>block-number-b</i>	define the range of blocks (from a to b) over which the input volume has been processed
<i>date</i>	the dates derived from the timestamps of the corresponding blocks
<i>time</i>	the times derived from the timestamps of the corresponding blocks

ADAU51 **Repair {count} blocks / {record-count} records processed**
Explanation This message is a response to the ADARES operator command, DSTAT. When the message is displayed, the REPAIR function has processed "count" blocks and "record-count" records from the protection log input data set.

ADAU53	{function} copy {count} blocks copied from {log-dataset} to DDSIAUS1/2 current block = {block-number} , time = {date} / {time}
Explanation	This message is a response to the ADARES operator command, DSTAT. <i>function</i> is either PLCOPY or CLCOPY. <i>count</i> blocks have been copied from DDPLOGR1/2 or DDCLOGR1/2 to the output data set.
ADAU54	Copy {count} blocks copied from DDSIIN to DDSIAUS1/2
Explanation	This message is a response to the DSTAT operator command during ADARES operation. <i>count</i> is the number of blocks copied by the COPY function.
ADAU55	Loading records with client option in effect
Explanation	The file to be loaded will be defined as a multiclient file.
ADAU56	Loading records with client option suppressed
Explanation	The file to be loaded is a multiclient file but will be defined as normal; that is, as a non-multiclient file.
ADAU57	LWP high-water mark: {xxxx} out of {yyyy} bytes ({zz}%)
Explanation	This message reports on the percentage of the LWP work pool used. You may want to use this information to tune the LWP parameter for your installation.
ADAU58	Problem encountered with zIIP license check.
Explanation	Proceeding with ZIIP=NO.
ADAU60	{utility} password exists and has been overwritten
Explanation	The specified password for the ADASCR INSERT function already exists. The related information (file numbers, access and update levels) has been overwritten.
ADAU61	Parameter test successful
Explanation	The utility parameter test, as requested by specifying the TEST parameter, was completed successfully.

ADAU62	Unable to write checkpoints -The nucleus is not active or cannot be reached, and the Associator JCL has not been specified
Explanation	No checkpoint could be written for a MERGE function because either the Adabas nucleus was not available or the Associator job control was not specified. None. The MERGE function continues.
Action:	If a checkpoint is required, start the nucleus or provide the Associator job control for the MERGE function.
ADAU63	Starting point for ADARES REGENERATE: FROMPLOG >= {log-number} (next nucleus session)
Explanation	This message is displayed on the ADASAV job protocol at the end of an ADASAV RESTORE execution. It indicates the protection log that should be used as input to a subsequent ADARES REGENERATE job. "log-number" is the protection log number. If that session happens to be a database save operation, the session number of the next nucleus session following the save operation must be used.
Action:	If the ADASAV RESTORE execution is to be followed by an ADARES REGENERATE operation, use the protection log with the indicated nucleus session number as input for the REGENERATE function.
ADAU64	Starting point for ADARES REGENERATE: FROMPLOG >= {log-n}, FROMCP= {chk-pnt}, FROMBLK= {blk-num} [,NUCID={nucid}]
Explanation	This message is displayed on the ADASAV job protocol at the end of an ADASAV RESTORE execution. It points out the protection log (log-n) that should be input to a possible subsequent ADARES REGENERATE job, and to the checkpoint (chk-pnt) where the REGENERATE function should begin. "blk-num" is the (pre-merge) protection log block number of the checkpoint. "nucid" identifies the particular cluster nucleus where the checkpoint originally (that is, before a PLOG merge) resided.
Action:	If the ADASAV RESTORE execution is to be followed by an ADARES REGENERATE operation, use the protection log with the indicated nucleus session number as input for the REGENERATE function, and specify the "chk-pnt" checkpoint and "blk-num" as parameters.
ADAU65	Loading records from version {v} unload tape
Explanation	Adabas version "v" created the unload data set specified as input.

ADAU66	Restoring file(s) from version {v} save tape
Explanation	The save data set specified as input was created by Adabas version "v".
ADAU67	Unloading file={file-number}, RECNO={rec-count}
Explanation	In response to ADAULD operator command DSTAT, ADAULD is currently unloading file "file-number". At this point in time, "rec-count" records have been unloaded.
ADAU68	Index of file {file-number} is {compressed uncompressed}
Explanation	The utility is processing a file with a compressed or uncompressed index, as indicated.
ADAU69	DDWORK{nn} not reset. DBID is {dbid1} expected DBID is {dbid2}
Explanation	A nonempty Work data set was assigned to an ADASAV RESTOREDB job that belongs to another database. The Work data set is not reset.
ADAU70	Waiting for PLOG/CLOG switch
Explanation	The ADADBS utility issued either an FEOFPL or an FEOFCL. If there is no free PLOG or CLOG, the nucleus may potentially wait for a free PLOG/CLOG.
Action	No action is required for this informational message.
ADAU71	Locking RLOG data set for nucleus got RSP={rc}, SUBC={sc}
Explanation	The utility's request to lock the RLOG data set for the Adabas nucleus failed. The nucleus could experience a short hard wait if it attempts to access the RLOG data set at the same time as the utility.
ADAU72	Unlocking RLOG data set for nucleus got RSP={rc}, SUBC={sc}
Explanation	The utility's request to unlock the RLOG data set for the Adabas nucleus failed. An ADADBS or Adabas Online System function could experience a medium wait if it needs to be recorded in the RLOG data set.
ADAU73	Recovery Aid deactivated- re-prepare the recovery log datasets. Processing continues.
Explanation	For restoring the database, initialization of RLOG data set access failed (utility error 058). ADASAV deactivates the Recovery Aid and continues the restore. ADASAV will terminate with return code 4.
Action:	Reactivate the Recovery Aid by executing the ADARAI PREPARE function again.

ADAU74	This function execution will not be logged in the recovery log. Processing continues.
Explanation	For a utility function that does not change the database or files, initialization of RLOG data set access failed (utility error 058). The utility continues without recording its run in the recovery log and terminates with return code 4.
Action:	Determine why the utility error 058 occurred. Correct the error.
ADAU75	PLOGR {n} for NUCID= {nucid} is not empty, DSNAME= {plog-name}
Explanation	While converting from a version of Adabas that uses the parallel participant table (PPT) structure to a higher version of Adabas, the system determined that the specified protection log (PLOG) for the specified earlier version nucleus (NUCID=0 for a noncluster nucleus) remained uncopied/unmerged. The conversion fails.
Action	You can bypass this check if necessary by using the ADACNV CONVERT IGNPPT parameter.
ADAU76	Statistics interval information on {yyyy-mm-dd} at {hh:mm:ss} Total PLOG blocks read = {plogblks} Total PLOG records read = {plogrecs} Total replicated transactions = {repltx} Pending replicated transactions = {pendtx} High watermark in replication pool = {himark} Current watermark in replication pool = {currmark} Timestamp of last committed transaction - {yyyy-mm-dd hh:mm:ss}
Explanation	This message display statistics about the processing of the Event Replicator utility ADARPL.
Action	No action is required for this informational message.
ADAU77	Preparing to zap the DBID in the GCB from {old-dbid} to {new-dbid}
Explanation	The ADAZAP utility is being used to change the DBID in the GCB (RABN 1 of the DDASSOR1 dataset). This message, which is written to the DDDRUCK output of ADAZAP, reports the old DBID (before the change) and new DBID (after the change).
Action	Ensure that the ADARUN DBID parameter specifies the new DBID of the database after the change. If Adabas SAF Security is used to check the authorization of utility executions on function level, ensure that the user is authorized to run ADAZAP on both the old DBID and the new DBID.
ADAU7A	ECS error {error-number} in function {ecs-function}
Explanation	ECS is the Entire Conversion Services, a subsystem of the Adabas universal encoding support (UES) system. This message is written after a function of the subsystem has failed. The following ECS functions may return errors:

ECS LOAD	An error loading ECS. Check that the ECS load module is in the Adabas load library.
COX LOAD	An error loading ADACOX. ADACOX is loaded if the database is UES-enabled. ADACOX is the Adabas conversion exit for special conversions.
APS INIT	An error occurred during Software AG internal product software (APS - POSIX Services) initialization. Verify that the APS library is in the load library concatenation and/or that the APS parameters are specified in SYSPARM.
SLIBLOAD	An error loading SAGECS, SAGOVO, or SAGSMP2. Check that these modules from the Software AG base technology library can be found in the load library concatenation.
DDECSOJ	An error occurred during initialization while reading ECS standard conversion objects. Check that the nonexecutable binary ECS conversion object library is specified in the DDECSOJ DD statement of the JCL.
GETHANDLE <i>nnnn</i>	An error occurred reading the ECS encoding descriptor object EDD <i>nnnn</i> . Check that the nonexecutable binary ECS conversion object library is specified in the DDECSOJ DD statement of the JCL. Check that EDD <i>nnnn</i> is contained in the library. If it is not, then either an invalid number was specified or the object is missing and must be added.
GETHANDLE <i>mmmm/nnnn</i>	See the GETHANDLE <i>nnnn</i> explanation. In this case, an ECS plane table object (PTO) is missing T <i>xxx</i> 2 <i>yyy</i> where <i>xxx</i> or <i>yyy</i> are the hexadecimal value of the decimal <i>mmmm</i> or <i>nnnn</i> , respectively. For some conversion combinations, it may be necessary to request additional PTOs from your Software AG support representative.

Action: Resolve the problem and try again.

ADAU7C Entire Conversion Services {v.r.s} initialized

Explanation The specified version / revision / system-maintenance level of Entire Conversion Services has been initialized.

ADAU7D Collation exit {exit-number} initialized

Explanation The specified collation exit supporting a collation descriptor field has been initialized.

ADAU84 {message-text}

Explanation This message is issued during utility processing. The actual message text varies, depending on the utility, as described in the following table.

Message Text	Utility	Description
Checking Adabas system file with NOOPEN in effect	ADAACK or ADAICK	NOOPEN was not specified in Adabas utilities. Consequently, ADAACK or ADAICK will issue OP commands to check the files. The OP commands may cause problems for the checkpoint file or the security file, so no OP command is issued for these files and this message appears.
Retained field definition table cleared for not loaded file <i>number</i>	ADACNV	While converting a database to Version 8, ADACNV encountered one or more FDTs stored in the FDT blocks for files that are not loaded in the database. These FDTs have been removed.

NOOPEN was not specified in Adabas utilities. Consequently, ADAACK or ADAICK will issue OP commands to check the files. The OP commands may cause problems for the checkpoint file or the security file, so no OP command is issued for these files and this message appears.

Action: No action is required for this informational message.

ADAU85 **Replication for file {fnr} is switched off because either the target DBID is not equal to the original DBID or replication is not active in the target database**

Explanation The file (*fnr*) to be restored to a database with a different DBID or to a database where replication is turned off has a nonzero Event Replicator Server target DBID set in the FCB. The target DBID will be reset for this file.

Action No action is required for this informational message. The Event Replicator Server target DBID for the file is reset automatically.

ADAU86 **Possible LOB inconsistency encountered processing file {fnr}**
Out-of-sync flag is set
base file={base-fnr}, LOB file={lob-fnr}

Explanation While processing the file (*fnr*) listed in the message, which is part of a LOB file group, the utility detected that one file in the group is out-of-sync with the other file. The base file number (*base-fnr*) and the LOB file number (*lob-fnr*) are also given in the message. The utility detects this condition and ends with return code 4 or 8.

This problem can occur if, through a logically incorrect sequence of utility operations, either or both files were exported from and reimported into the database, but not put back to the same point in time. In other words, one file would contain the results of a LB field update that the other, associated, file does not contain.

Action Investigate the sequence of utility operations on the files involved and determine why they are not in sync. Take actions to bring them back in sync. Then, if necessary, run the following function to mark the two files as being in sync.

```
ADADBS MODFCB FILE=base-fnr,LOBFILE=lob-fnr
```

ADAU87 **Possible LOB inconsistency encountered processing file {fnr}**
Unable-to-track flag is set
base file={base-fnr}, LOB file={lob-fnr}

Explanation While processing the file (*fnr*) listed in the message, which is part of a LOB file group, the utility detected that utility operations had been performed on the file group that left Adabas unable to track the LOB-update-status of the files. The base file number (*base-fnr*) and LOB file number (*lob-fnr*) are also given in the message. The utility that detects this condition ends with return code 4.

The LOB-update-status values of the files in a LOB file group reflect the LOB values in a base or LOB file when the file is exported from or imported to the database. Most utility operations either preserve the LOB-update-status of a file or change it to a defined new value, but some do not. In this case, the unable-to-track flag is set to signal that Adabas has become unable to guarantee that utility operations have kept the LOB file group in sync.

Action If you know that no (logically incorrect) utility operations were performed that put the files in a LOB file group out of sync, you can use the following function to mark the two files as being in sync.

```
ADADBS MODFCB FILE=base-fnr,LOBFILE=lob-fnr
```

ADAU88 **Possible LOB inconsistency encountered processing file**
LOB-update-status mismatch
base file={base-fnr}, update-status={stat-val1}
LOB file={lob-fnr}, update-status={stat-val2}

Explanation While processing the file (*fnr*) listed in the message, which is part of a LOB file group, the utility detected that the base file and LOB file are out-of-sync. The base file number (*base-fnr*) and LOB file number (*lob-fnr*) and their respective LOB-update-status values (*stat-val1* and *stat-val2*) are also given in the message. The utility ends with return code 4 or 8.

The LOB-update-status values of the files in a LOB file group reflect the LOB values in a base or LOB file when the file is exported from or imported to the database. As LOB operations are performed on the LOB file group, the LOB-update-status value changes for both files at the same time, resulting in a status value that is different if either or both files are exported or imported again.

A mismatch condition can occur if a logically incorrect sequence of utility operations caused the files to contain the results of different LOB updates.

Action Investigate the sequence of utility operations on the files involved and determine why they are not in sync. Take actions to bring them back in sync. Then, if necessary, run the following function to make the two files as being in sync.

```
ADADBS MODFCB FILE=base-fnr, LOBFILE=lob-fnr
```

ADAU89 **Unable to establish or validate the basefile-LOB file linkage because one of the files was locked or not loaded**

Explanation ADALOD could not establish the complete linkage between the base file and the LOB file because the file specified in the BASEFILE or LOBFILE parameter was either locked or not loaded.

ADALOD sets part of the file linkage only in the file just loaded and ends with return code 4.

Action If the other file does not exist, specify the correct BASEFILE or LOBFILE parameter when loading that file. This will establish the complete base-file-LOB file linkage.

If the other file is locked, wait until the utility function that locked the files has ended. Then, check whether the base file-LOB file linkage is in place (for example, using ADAREP). If necessary, you can use the following function to reestablish the base file-LOB file linkage:

```
ADADBS MODFCB FILE=base-fnr, LOBFILE=lob-fnr
```

ADAU91 **The last formatted ISN was not set for file {fn}.
This will be set to MAXISN at utility completion.
The last formatted secondary ISN was not set for file {fn}.
This will be set to MAXISN2 at utility completion.**

Explanation The last formatted ISN or secondary ISN was not set for the file listed in the message (*fn*). When the utility completes, the last formatted ISN will be set to the value of MAXISN or the last formatted secondary ISN will be set to the value of MAXISN2.

Action No action is required for this informational message.

ADAU92 **{utility} still initializing**

Explanation This message is a response to the utility DSTAT operator command, if the corresponding utility is still in its initialization phase.

Action No action is required for this informational message.

ADAU93	ADACHK File={fn}, Processing {fx-name} in progress
Explanation	This message is returned when the DSTAT operator command is issued against a running ADACHK process. The file number (<i>fn</i>) and the ADACHK function name (<i>fx-name</i>) are given in the message. Possible function names are "ACCHECK", "DSCHECK", "ICHECK", or "VALIDATE".
Action	No action is required for this informational message.
ADAU94	MAXRECL ignored with files enabled for spanned data storage records
Explanation	The ADALOD or ADAORD utilities were run, specifying the MAXRECL parameter, against files with spanned Data Storage records. The MAXRECL parameter is ignored and the utility ends with return code 4.
Action	No action is required for this informational message.
ADAU95	MIXDSDEV ignored with files enabled for spanned data storage records
Explanation	The ADALOD utility was run, specifying the MIXDSDEV parameter, against files with spanned Data Storage records. The MIXDSDEV parameter is ignored and the utility ends with return code 4.
Action	No action is required for this informational message.
ADAULA	Error using MLC version older than {vvvv}
Explanation	The product license check works with the separate component Mainframe License Check (MLC). For a correct interaction with MLC a minimum version <i>vvvv</i> is required.
Action	Update the MLC component and rerun the job.

38

ADAX* - Adabas Cluster Nucleus Messages

ADAX01	{dbid} NUCID {nucid} on system {system} {status}
Explanation	A nucleus entered or left the Adabas cluster. Adabas nucleus cluster members that were identified as active at initialization are indicated with status 'is present'. Post-initialization changes to Adabas cluster membership are indicated with status 'has joined'; 'has withdrawn'; or 'has failed'.
Action	No action is required for this informational message.
ADAX02	{dbid} System {sysn} status monitor update missing
Explanation	XCF reported that the named system (<i>sysn</i>) is not responding. This affects all XCF users on that system, not just Adabas. Until communications are restored, all nuclei on that system may not be able to respond to critical intracluster synchronization messages before the message times out.
Action	Attempt to restore XCF communications with the named system.
ADAX03	{dbid} System {sysn} status monitor update resumed
Explanation	After missing one or more status monitoring intervals, the named system (<i>sysn</i>) is now responding to XCF communications.
Action	No action is required for this informational message.
ADAX04	{dbid} NUCID {nucid} on system {sysn} status monitor update missing
Explanation	XCF reported that the identified nucleus (<i>nucid</i>) on the identified system (<i>sysn</i>) is not updating its heartbeat monitor. It is likely that the nucleus is not able to process commands, including critical intracluster synchronization messages.
Action	Determine why the nucleus is not able to update its heartbeat monitor. The nucleus may be hung or looping, or there may be other processes in the system preventing the nucleus from getting sufficient CPU allocations.

ADAX05 **{dbid} NUCID {nucid} on system {sysn} status monitor update resumed**
Explanation The identified nucleus (*nucid*) on the identified system (*sysn*) has resumed updating its heartbeat monitor.
Action No action is required for this informational message.

ADAX07 **{dbid} Member {membername} on {systemname} reason}**
Explanation During nucleus initialization an existing nucleus had not yet synchronized by processing the ADAXCF IXCJOIN signal. This may not be an error unless the condition persists through retries of the synchronization message.

This message is always followed by message [ADAX08](#). The *membername* is the nucleus's identification to z/OS XCF. It is of the form "DB*dddd*P*pppp*N*nn*", where *dddd* is the DBID, *pppp* is the external nucleus ID (NUCID) from the ADARUN parameter, and *nn* in the internal NUCID assigned by Adabas. The identified member is on the system identified in the message in *systemname*. The specific condition is described in the message as one of the following *reasons*:

<i>reason</i>	Description	Action
Not synchronized	This nucleus responded to the synchronization query and indicated it had not yet processed the IXCJOIN signal.	The synchronization query will be retried. No action is required.
No response to synchronization	This nucleus did not respond to the synchronization query before it timed out.	The synchronization query will be retried. No action is required.
Unknown synchronization responder	This XCF member was not known to Adabas. If ADAXCF could not retrieve the member name from XCF, question marks will fill <i>membername</i> and <i>systemname</i> and there will be an associated ADAX28 message describing the return and reason codes from IXCQUERY. The response from this XCF group member is ignored.	Investigate the members of the XCF group. The z/OS operator command <code>D XCF, GROUP, groupname, {membername ALL}</code> , where <i>groupname</i> is the ADARUN parameter CLUGROUPNAME setting, may provide more information.

Action	Review the table above for appropriate actions.
ADAX08	{dbid} {nn} nuclei synced, {nn} not synced, {nn} no response
Explanation	During nucleus initialization one or more existing nuclei did not indicate they had processed the ADAXCF JOIN signal. Specific information about each nonsynchronized member is given by a previous ADAX07 messages.
	The synchronization query will be retried once. If all are not then synchronized, nucleus initialization will fail.
Action	No action is required for this informational message. Review the actions for the accompanying ADAX07 messages.
ADAX09	{dbid} Post NUC {nucid} failed - RET {return-code} RSN {reason-code}
Explanation	This message may appear when another nucleus terminates.
Action	No action is necessary if the other nucleus is terminating abnormally. If the message occurs in an otherwise normal nucleus session, contact your Software AG technical support representative.
ADAX11	{dbid} Adabas cluster messaging initialization failed
Explanation	An error described in preceding messages prevented successful initialization of Adabas cluster messaging services. Nucleus initialization fails with PARM-ERROR 092.
Action	Correct the problem identified in the preceding messages.
ADAX12	{dbid} Unable to obtain {AXMVT ADAMCB} storage
Explanation	A request to obtain storage from the work pool for Adabas cluster messaging service control structures failed. Nucleus initialization fails with PARM-ERROR 092.
Action	Increase the amount of virtual storage available. Alternatively, adjust ADARUN parameters to allow for a larger work pool or decrease ADARUN parameters NT and NU to require fewer AXMCBs.
ADAX13	{dbid} Error {subcode} replying to {nucid} message {msgnum}
Explanation	An error occurred while replying to an intracluster command originating from the nucleus whose nucleus ID is given in the message (<i>nucid</i>). The reply could not be sent. The error code given in the message (<i>subcode</i>) is one of the possible subcodes for response code 123 (ADARSP123). The originating nucleus message sequence number is also given in the message (<i>msgnum</i>).
	The originating nucleus will continue to wait for a reply until the message times out or the nonresponding nucleus ends.
Action	If the reason for the error cannot be determined and corrected, notify your Software AG technical support representative.

ADAX14 **{dbid} Statistics for {type}-type messages**
{dbid} Messages sent {nn} replies sent {nn}
{dbid} Messages arrived {nn} messages accepted {nn}

Explanation Produced during normal nucleus termination, this message provides Adabas Cluster Services messaging service statistics:

messages sent	reflects the number of internucleus messages initiated from this nucleus
messages arrived	is the count of asynchronous incoming messages queued for the nucleus (normally, the same as 'messages accepted')
messages accepted	is the count of those messages the nucleus processed (normally, the same as 'messages arrived')
replies sent	is the count of nucleus responses to accepted messages that required a response.

Action No action is required for this informational message.

ADAX15 **{dbid} AXMCB allocated {nn} used {nn} total requests {nn}**

Explanation Produced during normal nucleus termination, this message provides Adabas cluster messaging service statistics:

AXMCB allocated	number of internucleus message control blocks allocated.
AXMCB used	number of internucleus message control blocks used.
total requests	total number of requests to use the allocated internucleus message control blocks.

Action No action is required for this informational message.

ADAX16 **{dbid date time statistic}**

Explanation This message is used to display the output from the DXMSG operator command on the console.

Action No action is required for this informational message.

ADAX20 **{dbid} XCF transport initialization complete**

Explanation The z/OS XCF transport service successfully initialized.

Action No action is required for this informational message.

ADAX21

{dbid} {error-text}**Explanation**

The error specified by one of the following error texts occurred during the z/OS XCF transport service initialization check:

Error Text	Explanation	Action
Existing XCF group member <i>xcf-member</i> uses different AXMCB version	The cluster member listed in the message is not using the same version of Adabas as the other nuclei in the cluster. All Adabas sysplex cluster nuclei generate <i>xcf-member</i> names in the format: DBddddpppppNnn -where <i>dddd</i> is the database ID, <i>ppppp</i> is the nonzero nucleus ID, and <i>nn</i> is an internal ordinal identifier.	Check that all nuclei in the cluster use the same Adabas versions and the same Adabas Cluster versions.
Existing XCF group member <i>xcf-member</i> uses different DBID	An Adabas sysplex cluster nucleus that is already active in the same XCF group is using a different DBID. All Adabas sysplex cluster nuclei generate <i>xcf-member</i> names in the format: DBddddpppppNnn -where <i>dddd</i> is the database ID, <i>ppppp</i> is the nonzero nucleus ID, and <i>nn</i> is an internal ordinal identifier.	Verify that ADARUN parameters DBID and CLUGROUPNAME are correct in all nuclei participating in the sysplex cluster. Contact your Software AG technical support representative if you are unable to resolve the problem.
Incompatible AXMCB version	The Adabas Cluster Services modules you are using are not compatible with the Adabas running.	Contact your Software AG technical support representative for assistance.
Incompatible AXMVT version	The Adabas Cluster Services modules you are using are not compatible with the Adabas running.	Contact your Software AG technical support representative for assistance.
Invalid group name	The ADARUN parameter CLUGROUPNAME was omitted or invalid.	Correct the ADARUN parameter. CLUGROUPNAME must begin with an alphabetic character, may not begin with SYS, and may not be UNDESIG.
Invalid user state data from existing member <i>xcf-member</i>	The control information presented for a member already connected to the XCF group was not formatted as a proper Adabas sysplex cluster nucleus or had a different DBID. The	Identify the source of <i>xcf-member</i> . If it is an Adabas sysplex cluster nucleus, make sure the parameters NUCID, CLUGROUPNAME, and

Error Text	Explanation	Action
	<p>preexisting member may be an Adabas sysplex cluster nucleus associated with a different DBID, or it may be another process using the same XCF group name. All Adabas sysplex cluster nuclei generate <i>xcf-member</i> names in the format:</p> <p><code>DBddddppppNnn</code></p> <p>-where <i>dddd</i> is the database ID, <i>pppp</i> is the nonzero nucleus ID, and <i>nn</i> is an internal ordinal identifier.</p>	<p>DBID are correct. There may be additional information in messages generated by the other nucleus. If it is not an Adabas sysplex cluster nucleus, contact your systems programmer or support representative. If you are unable to resolve the problem, contact your Software AG technical support representative.</p>
IXCJOIN failed, duplicate NUCID and XCF member name	<p>XCF service IXCJOIN reported the member name requested by this nucleus was already active in the XCF group. The member name is derived from the ADARUN parameters DBID and NUCID and an internal number assigned during nucleus initialization. Any return and reason codes included with this message are defined in the IBM documentation entitled <i>MVS Programming: Sysplex Services Reference</i>.</p>	<p>Verify that ADARUN parameter DBID is correct and NUCID is unique among all nuclei participating in the Adabas sysplex cluster. Contact your Software AG technical support representative if you are unable to resolve the problem.</p>
IXCJOIN failed or retry count exhausted	<p>An error was reported by XCF service IXCJOIN. Message ADAX28 provides the return and reason code from IXCJOIN. These return and reason codes are defined in the IBM documentation entitled <i>MVS Programming: Sysplex Services Reference</i>. An error may result from XCF options specified for your installation by your systems programmer.</p>	<p>Contact your Adabas technical support representative if you are unable to resolve the problem.</p>
IXCMSGO failed	<p>XCF service IXCMSGO reported an error attempting to broadcast the initialization synchronization query.</p>	<p>If the error reoccurs, contact your Software AG technical support representative for assistance.</p>
IXCQUERY failed	<p>An error was reported by IBM XCF service IXCQUERY. Message ADAX28 provides the return and reason code from IXCQUERY. These are defined in the IBM documentation.</p>	<p>Contact your Adabas technical support representative for assistance.</p>

Error Text	Explanation	Action
NUCID already active	XCF initialization found an active Adabas sysplex cluster nucleus with the same NUCID.	Verify that ADARUN parameter NUCID is unique among all nuclei participating in the Adabas sysplex cluster.
Too many members exist in XCF group	IXCQUERY identified an unexpected number of preexisting members in the XCF group.	Contact your Software AG technical support representative for assistance.
Unable to synchronize	The retry count for the initialization synchronization query is exhausted. One or more existing nuclei did not report synchronization.	If the error reoccurs, contact your Software AG technical support representative for assistance.
XCF latch set creation failed	An error was reported by the IBM latch set creation routine ISGLCRT.	Contact your Software AG technical support representative for assistance.
XCF transport initialization failed	The initialization of the Adabas sysplex cluster's messaging service failed and nucleus initialization failed with PARM error 092. The reason for the failure is indicated in a previous message.	Review the previous messages to resolve the error. Contact your Software AG technical support representative for assistance.

Action The user actions are given in the table above. If the problem persists, contact your Software AG technical support representative for assistance.

ADAX22 {dbid} Status monitor update missed

Explanation This nucleus was notified by XCF that it failed to update its heartbeat monitor within the interval specified by ADARUN parameter MXSTATUS. XCF will notify all other nuclei registered to the same XCF group, each of which may issue message ADAX04.

Action Determine why this nucleus is not able to update its heartbeat monitor. The nucleus may be hung or looping, or there may be other processes in the system preventing the nucleus from getting sufficient CPU allocations.

ADAX23 {dbid} Status monitor update resumed after {nn} seconds

Explanation After missing one or more status monitoring intervals, this nucleus has resumed updating its heartbeat monitor. XCF will notify all other nuclei registered to the same XCF group, each of which may issue message ADAX05. This message reports the number of seconds (*nn*) since the missing status update was first detected and the related ADAX22 message was printed.

Action No action is required for this informational message.

ADAX24**{dbid} {error-text}****Explanation**

An error occurred while processing an incoming asynchronous message. This message appears only in the z/OS Adabas nucleus JESLOG listing, SYSLOG or operator's console. One of the following error texts is given in this message:

Error Text	Explanation	Action
AXMCB allocation failed in XCF message exit	A message control block to describe the incoming message could not be obtained from the pool.	Adjust ADARUN parameters NT and NU to increase the number of AXMCBs created at initialization. Contact your Software AG technical support representative if you are unable to resolve the problem.
Buffer allocation failed in XCF message exit	A buffer for the incoming message could not be obtained.	Provide more storage by increasing the REGION JCL parameter. Contact your Software AG technical support representative if you are unable to resolve the problem.
Invalid incoming MSGCNTL header in XCF message exit	The control information presented for the incoming message was not formatted as a proper Adabas cluster nucleus or had a different DBID. This may result if a message was sent from an XCF group member previously cited in message ADAX27.	See message ADAX27 . Contact your Software AG technical support representative if you are unable to resolve the problem.
Out of sequence or missing segments in XCF message exit	The segments of a message whose length required it to be sent in multiple segments did not arrive in the expected order.	Contact your Software AG technical support representative for assistance.
Segmented message timed out in XCF message exit	A message whose length required it to be sent in multiple segments was not complete at the expiration of the timeout interval. This may be the result of an error on the sending nucleus, an XCF error, or contention for system resources.	Contact your Software AG technical support representative if you are unable to resolve the problem.
Unable to receive segment in XCF message exit	An error was reported from the XCF IXCMMSGI service when attempting to receive the message. Message ADAX28 provides the IXCMMSGI return and reason codes. These return and reason codes are defined	Contact your Software AG technical support representative if you are unable to resolve the problem.

Error Text	Explanation	Action
	in the IBM documentation entitled <i>MVS Programming: Sysplex Services Reference</i> .	
Unable to save message segment in XCF message exit	An error was reported from the XCF IXCMSGC service when attempting to save the message. Message ADAX28 provides the IXCMSGC return and reason codes. These return and reason codes are defined in the IBM documentation entitled <i>MVS Programming: Sysplex Services Reference</i> . There may not be sufficient resources allocated in your installation to save the message.	Contact your systems programmer or technical representative to determine if XCF is experiencing a shortage of resources. Contact your Software AG technical support representative if you are unable to resolve the problem.

Action The user actions are given in the table above. If the problem persists, contact your Software AG technical support representative for assistance.

ADAX25 Status monitoring removed by XCF

Explanation The z/OS XCF service detected an error in the status monitoring exit. Status monitoring is no longer available for this member.

Action Contact your Software AG technical support representative for assistance.

ADAX26 {dbid} Invalid user state data from {xcf-member}

Explanation An error occurred when processing a member state change event generated by the z/OS XCF messaging transport service as a member attempted to join the XCF group. The control information presented for the XCF group member attempting connection was not formatted as a proper Adabas sysplex cluster nucleus or had a different DBID. The joining member may be an Adabas sysplex cluster nucleus associated with a different DBID or it may be another process using the same XCF group name. All Adabas sysplex cluster nuclei generate *xcf-member* names in the format:

```
DBddddppppNnn
```

where:

<i>dddd</i>	is the database ID
<i>ppppp</i>	is the nonzero NUCID
<i>nn</i>	is an internal ordinal identifier

The member state change event is discarded.

Action Identify the source of *xcf-member*. If it is an Adabas sysplex cluster nucleus, make sure the parameters NUCID, CLUGROUPNAME, and DBID are correct and notify your Adabas technical support representative if this does not correct the problem. There may be additional information in the messages for the nucleus attempting to join. If it is not an Adabas sysplex cluster nucleus, notify your system programmer or support representative.

ADAX27 {dbid} No room in AXCFVT table for {xcf-member}

Explanation An error occurred when processing a member state change event generated by the z/OS XCF messaging transport service.

Action Contact your Adabas technical support representative. The member state change event is discarded.

ADAX28 {dbid} {xcf-service-routine} RET {return-code} RSN {reason-code}

Explanation This message appears only in the z/OS Adabas nucleus JESLOG listing, SYSLOG, or operator's console. It is issued for certain XCF message transport service requests during initialization and termination, and whenever a request fails. Refer to IBM documentation entitled *MVS Programming: Sysplex Services Reference* for descriptions of the various return and reason codes for each XCF service.

Action This message may be associated with an error condition reflected in other messages, or may have caused an Adabas cluster message request to fail. If an associated error is identified, include this message when contacting your Software AG technical support representative.

ADAX29 {dbid} Adabas abend in XCF exit DBID {dbid} NUCID {nucid} abend {routine} S{nnn}U{nnnn} reason {rsn} PSW {psw} REG 0-3 {reg 0 reg 1 reg 2 reg 3} REG 4-7 {reg 4 reg 5 reg 6 reg 7} REG 8-B {reg 8 reg 8 reg 10 reg 11} REG C-F {reg 12 reg 13 reg 14 reg 15}

Explanation A program check or system abend was intercepted by the z/OS XCF messaging transport service FRR or ESTAE routine. The error may have occurred under an SRB.

The nucleus should terminate. A dump may be produced in SDUMP format, either in one of the nucleus-allocated files SYSUDUMP, SYSMDUMP, or SYSABEND; or in a system-allocated file such as SYS1.DUMPn.

Action Contact your Software AG technical support representative for assistance.

ADAX2A

{dbid} {message-text}**Explanation**

This message is returned by the Adabas Parallel Services messaging module ADASMM, also called the SMM facility.

One of the following message texts can appear in this message:

Message Text	Explanation	Action
Incompatible AXMVT version	The Adabas Parallel Services modules you are using are not compatible with the Adabas running.	Check that your Adabas Parallel Services library is compatible with your Adabas library. If the problem persists, contact your Software AG technical support representative for assistance.
TI-0, initialized, RC <i>return-code</i>	ADASMM initialized successfully.	No action is required for this informational message.
TI-1, cannot get work memory	The attempt to acquire memory for the ADASMM work area failed. ADASMM terminates.	Contact your Software AG technical support representative for assistance.
TI-2, cannot get PLXCB	The attempt to acquire an Adabas Parallel Services control block (MPM 76 call) failed. ADASMM terminates.	Contact your Software AG technical support representative for assistance.
TI-3, cannot load PLXDEP	The attempt to load the operating system interface module PLXDEP failed. ADASMM terminates.	Contact your Software AG technical support representative for assistance.
TI-4, memstate call NUCID: <i>nucid</i> , RC <i>return-code</i>	The specified hexadecimal return code was received from the member state table interface call for the specified nucleus ID.	Analyze the return code and correct the error.
TI-5, Error in post NUCID: <i>nucid</i> , RC <i>return-code</i>	The specified hexadecimal return code was received from the cross-memory post (MPM 80) routine to the specified nucleus ID.	Analyze the return code and correct the error.
TI-6, NUCID: <i>nucid</i> reported active - inconsistent PLXCB	A fatal error occurred during initialization. The cluster control block PLXCB reported incorrectly that the nucleus (NUCID) was active. The PLXCB is therefore inconsistent and initialization fails with response code 8 (ADARSP008).	Restart the cluster cleanly.

Message Text	Explanation	Action
<i>dbid</i> TI-9, error set process token: <i>xx</i>	A fatal error occurred in obtaining the process token value <i>xx</i> as returned from the Adabas Operating System interface ADAIOR, where <i>dbid</i> is the database ID of the SMP cluster.	Note the response code delivered and contact your Software AG technical support representative for assistance.

Action The user actions are given in the table above. If the problem persists, contact your Software AG technical support representative for assistance.

ADAX2B {*dbid*} {*message-text*}

Explanation This message is returned by the Adabas Parallel Services messaging module ADASMM, also called the SMM facility.

One of the following message texts can appear in this message:

Message Text	Explanation	Action
TT-0, SMM not yet initialized	The termination call was made without a previous successful initialization call. The SMM facility terminates.	Contact your Software AG technical support representative for assistance.
TT-1, SMM terminating	The SMM facility is terminating.	Contact your Software AG technical support representative for assistance.
TT-2, memstate call, NUCID: <i>nucid</i> , RC <i>return-code</i>	The specified hexadecimal return code was received from the member state table interface call to the specified nucleus ID.	Analyze the return code and correct the error.

Action The user actions are given in the table above. If the problem persists, contact your Software AG technical support representative for assistance.

ADAX2C {*dbid*} {*message-text*}

Explanation This message is returned by the Adabas Parallel Services messaging module ADASMM, also called the SMM facility.

One of the following message texts can appear in this message:

Message Text	Explanation	Action
SM-0, SMM not initialized yet	A send call was made without a previous successful initialization. ADASMM terminates.	Contact your Software AG technical support representative for assistance.
SM-1, timer call, RC <i>response-code</i>	The specified hexadecimal response code was returned from a call to set up a timeout interval.	Analyze the response code and correct the error.
SM-2, No UB available, RC <i>response-code</i>	The specified hexadecimal response code was returned by the call to acquire a user buffer.	Analyze the response code and correct the error.
SM-3, Cannot find ECB element	An event control block is required in order to send a message. This control block cannot be acquired because the table is full.	The size of the table is based on the ADARUN NC parameter. Increase the value of the ADARUN NC parameter to increase the table size.
SM-4, Reply error, NUCID: <i>nucid</i> , RC <i>response-code</i>	The specified hexadecimal response code was returned by the specified (external) NUCID.	Analyze the response code and correct the error.

Action The user actions are given in the table above. If the problem persists, contact your Software AG technical support representative for assistance.

ADAX2D {*dbid*} {*message-text*}

Explanation This message is returned by the Adabas Parallel Services messaging module ADASMM, also called the SMM facility.

One of the following message texts can appear in this message:

Message Text	Explanation	Action
RM-0, SMM not yet initialized	A receive call was made without a previous successful initialization. ADASMM terminates.	Contact your Software AG technical support representative for assistance.
RM-1, reply ECB not found, RC <i>response-code</i>	Every ADASMM message needs an event control block, which is held in a table. The required receive messages does not have an equivalent event control block entry set by a send.	Analyze the response code and correct the error.

Action The user actions are given in the table above. If the problem persists, contact your Software AG technical support representative for assistance.

ADAX2E **{dbid} {message-text}**

Explanation This message is returned by the Adabas Parallel Services messaging module ADASMM, also called the SMM facility.

One of the following message texts can appear in this message:

Message Text	Explanation	Action
QU-0, SMM not yet initialized	A query member call was made without a previous successful initialization. ADASMM terminates.	Contact your Software AG technical support representative for assistance.
QU-1, bad function code <i>code</i>	The calls to ADASMMQU have a function code. The function code "code" is out of range. This is an internal error. ADASMM terminates.	Contact your Software AG technical support representative for assistance.

Action The user actions are given in the table above. If the problem persists, contact your Software AG technical support representative for assistance.

ADAX2F **{dbid} TM-0, SMM not initialized yet**

Explanation This message is returned by the Adabas Parallel Services messaging module ADASMM, also called the SMM facility.

A call was made to terminate the cluster session without a previous successful initialization call.

Action ADASMM terminates.

ADAX2G **{dbid} CM-0, SMM not yet initialized**

Explanation This message is returned by the Adabas Parallel Services messaging module ADASMM, also called the SMM facility.

A cancel call was made without a previous successful initialization.

Action ADASMM terminates.

ADAX2H **{dbid} {message-text}**

Explanation This message is returned by the Adabas Parallel Services messaging module ADASMM, also called the SMM facility.

One of the following message texts can appear in this message:

Message Text	Explanation	Action
CME-0, SMM not yet initialized	A receive exit call was made without a previous successful initialization. ADASMM terminates.	Contact your Software AG technical support representative for assistance.
CME-1, cannot find ECB element	An event control block was received in the database for ADASMM. The equivalent event control block for the message that was sent cannot be found.	Ensure that the ECB for the message sent is available.
TIMEX-0, SMM not yet initialized	A timer exit call was made without a previous successful initialization. ADASMM terminates.	Contact your Software AG technical support representative for assistance.
<i>dbid</i> TIME-1, msg to <i>cccc</i> timed out	An attempt to send a message to cluster <i>cccc</i> timed out, with no response.	This is a warning. Contact your Software AG technical support representative for assistance.

Action The user actions are given in the table above. If the problem persists, contact your Software AG technical support representative for assistance.

ADAX2I {*dbid*} {*message-text*}

Explanation This message is returned by the Adabas Parallel Services messaging module ADASMM, also called the SMM facility.

One of the following message texts can appear in this message:

Message Text	Explanation	Action
SS-1, target gone, ID <i>nucid</i>	The cluster nucleus with the specified (external) NUCID left the cluster.	No action is required for this informational message.
SS-2, memstate, ID <i>int-nucid</i> IND <i>idx-num</i> EXT <i>nucid</i> state <i>nn</i>	This message provides information about calls to the member state table manager from the SMM facility where: <ul style="list-style-type: none"> ■ <i>int-nucid</i> is the nucleus indicator entry for the cluster nucleus in the member state table (internal). ■ <i>idx-num</i> is the index number of the internal nucleus indicator entry. ■ <i>nucid</i> is the user-specified (external) NUCID number, or zero (0) for a noncluster nucleus. 	No action is required for this informational message.

Message Text	Explanation	Action
	<ul style="list-style-type: none"> ■ <i>nn</i> is the status of the nucleus: 03 to activate or 00 to release. 	
SS-3, ACB to ID <i>nucid</i> , RC <i>rsp-code</i> , AD2 <i>value</i>	An error has occurred in cluster communication. The cluster nucleus that returned the message is identified by the (external) NUCID. The response code is provided as well as the contents of the command ACB's or ACBX's Additions 2 field.	This is a warning. Contact your Software AG technical support representative for assistance.

Action The user actions are given in the table above. If the problem persists, contact your Software AG technical support representative for assistance.

ADAX31 {dbid} Opening Work data set for NUCID={nucid}

Explanation This nucleus is about to open the Work data set of the nucleus with the specified (external) NUCID. Either nucleus is starting.

Action No action is required for this informational message.

ADAX32 {dbid} Open failed. IOR code=X'{rc}', system code=X'{ssss}'

Explanation This nucleus tried to open the Work data set of the nucleus with the NUCID '*nucid*' (message ADAX31), but the open failed. ADAIOR issued response code '*rc*' (in hexadecimal), and the system's return code is '*ssss*' (in hexadecimal). This message is preceded by an ADAI62 message detailing the name of the Work data set that could not be opened.

The current operation of the nucleus fails. If the nucleus was processing a request from another nucleus to join the cluster, the session start of the other nucleus will fail.

Action Determine why opening the Work data set failed. Possible causes include the following:

- the Work data set or its catalog entry is inaccessible or has been damaged; or
- the PPT block containing the name of the Work data set has been damaged.

If possible, correct the error and restart the nucleus. If this error occurs during a session autorestart and cannot be resolved, the database must be restored and regenerated.

If in doubt, contact your Software AG technical support representative.

ADAX33	{dbid} Bad Work block for NUCID={nucid} timestamp mismatch -- RABN={rrrr}
Explanation	This nucleus encountered a Work block in which the timestamp at the beginning of the block did not match the control timestamp at the end of the block. The last write of the block was incomplete, or the block has been damaged for another reason. It is inconsistent and cannot be used for recovery. The block was read from the Work data set of the nucleus with the NUCID ' <i>nucid</i> '. Its RABN is ' <i>rrrr</i> '.
Action	If this error occurs during a session autorestart, the database must be restored and regenerated. If in doubt, contact your Software AG technical support representative.
ADAX34	{dbid} Closing Work dataset for NUCID={nucid}
Explanation	This nucleus is about to close the Work data set of the nucleus with the specified (external) NUCID. Either this nucleus is terminating or the other nucleus has terminated.
Action	No action is required for this informational message.
ADAX35	{dbid} Close failed. IOR code=X'{rc}', system code=X'{ssss}'
Explanation	This nucleus tried to close the Work data set of the nucleus with the NUCID ' <i>nucid</i> ' (message ADAX34), but the close operation failed. ADAIOR issued response code ' <i>rc</i> ' (in hexadecimal), and the system's return code is ' <i>ssss</i> ' (in hexadecimal).
Action	The nucleus ignores this error and continues normally. However, it is conceivable that this error may cause a subsequent error when a Work data set is being opened. Try to determine why closing the Work data set failed, and if possible, correct the error. Consider shutting down the nucleus and restarting it to clean up any remnant of the close error.
ADAX36	{dbid} Using Work dataset for NUCID={nucid}
Explanation	This nucleus is reusing a Work data set (of the nucleus with the specified external NUCID) that it had already opened earlier.
Action	No action is required for this informational message.
ADAX37	{dbid} Mismatching Work datasets for NUCID={nucid} Old name={old-dataset-name} New name={new-dataset-name}
Explanation	This nucleus has found two different Work data sets for the nucleus with the specified (external) NUCID. The message shows the name of the data set the nucleus had already opened (' <i>old-dataset-name</i> ') and the name of the data set the nucleus was about to open (' <i>new-dataset-name</i> ').
	The current operation of the nucleus fails. If the nucleus was processing a request from the other nucleus to join the cluster, the session start of the other nucleus will fail.

Action Determine why the specified nucleus is associated with two different Work data sets. If the old data set name appears wrong or outdated, consider shutting down and restarting this nucleus (that printed this message).

ADAX38 **{dbid} Peer nucleus {nucid} is accessing different Work dataset**

Explanation Another nucleus in the cluster (with the specified external NUCID) could not open the Work data set of this nucleus because it had already opened a different Work data set for this nucleus. The other nucleus reported this error in an ADAX37 message and rejected the attempt of this nucleus to join the cluster. The session start of this nucleus fails.

Action Determine why this nucleus is associated with two different Work data sets. If the old data set name appears wrong or outdated, consider shutting down and restarting the other nucleus (that printed the ADAX37 message).

ADAX39 **{dbid} Peer nucleus {nucid} could not open Work dataset**

Explanation Another nucleus in the cluster (with the specified external NUCID) tried to open the Work dataset of this nucleus, but the open failed. The other nucleus reported the open error in an ADAX32 message. The session start of this nucleus fails.

Action Determine why opening the Work data set failed. If possible, correct the error and restart this nucleus. If this does not resolve the problem, consider shutting down and restarting the other nucleus (that printed the ADAX32 message).

ADAX3A **{dbid} Peer nucleus {nucid} got I/O error on Work dataset**

Explanation Another nucleus in the cluster (with the specified external NUCID) incurred an I/O error on the Work data set of this nucleus. The other nucleus reported the I/O error in an ADAX3C message. The session start of this nucleus fails.

Action Determine the cause of the I/O error. If possible, correct the error and restart this nucleus. If this does not resolve the problem, consider shutting down and restarting the other nucleus (that printed the ADAX3C message).

ADAX3B **{dbid} Peer nucleus {nucid} could not validate Work dataset**

Explanation Another nucleus in the cluster (with the specified external NUCID) found bad or unexpected data in the Work data set of this nucleus. The other nucleus reported the validation error in an ADAX3D message. The session start of this nucleus fails.

Action Determine whether the two nuclei really access the very same data set. This nucleus (which was starting) was accessing the data set via its DD/link-name DD/WORKR1. The other nucleus (which was already running) accessed the data set just via its name in the catalog.

If in doubt, contact your Software AG technical support representative.

ADAX3C	{dbid} I/O error on Work dataset of peer nucleus NUCID={nucid}, RABN={rrrr}
Explanation	This nucleus incurred an I/O error on RABN ' <i>rrrr</i> ' of the Work data set of the nucleus with the specified (external) NUCID and rejected the attempt of that nucleus to join the cluster. The session start of the other nucleus fails.
Action	Determine the cause of the I/O error. If possible, correct the error and restart the other nucleus. If the I/O error does not appear to be permanent, consider shutting down and restarting this nucleus.
ADAX3D	{dbid} Unexpected data in Work dataset of peer nucleus NUCID={nucid}, RABN={rrrr}
Explanation	This nucleus found bad or unexpected data in RABN ' <i>rrrr</i> ' of the Work data set of the nucleus with the specified (external) NUCID and rejected the attempt of that nucleus to join the cluster. The session start of the other nucleus fails.
Action	Contact your Software AG technical support representative.
ADAX3E	{dbid} Invalid internal NUCID {id}
Explanation	The nucleus encountered an internal NUCID (with the specified value) that was outside the allowed range of 1-32. This is an internal error.
	The current operation of the nucleus fails. If the nucleus was processing a request from another nucleus to join the cluster, the session start of the other nucleus fails.
Action	Contact your Software AG technical support representative. If the error is reproducible, provide a nucleus dump that is taken when this message is printed (e.g., on z/OS, using a SLIP trap with MSGID=ADAX3E).
ADAX3F	{dbid} Invalid external NUCID {nucid}
Explanation	The nucleus encountered an external NUCID (with the specified value) that was outside the allowed range of 1-65,000. This is an internal error.
	The current operation of the nucleus fails. If the nucleus was processing a request from another nucleus to join the cluster, the session start of the other nucleus fails.
Action	Try to determine where the invalid NUCID value originates from. If in doubt, contact your Software AG technical support representative. If the error is reproducible, provide a nucleus dump that is taken when this message is printed (e.g., on z/OS, using a SLIP trap with MSGID=ADAX3F).

ADAX3G **{dbid} Work dataset for external NUCID {nucid1} is already open for internal NUCID {id} and external NUCID {nucid2}**

Explanation The nucleus encountered two different external NUCIDs for the same internal NUCID. The message shows the internal NUCID ('*id*'), the external NUCID of a cluster nucleus ('*nucid1*') that was to be associated with the internal NUCID and the external NUCID of a nucleus ('*nucid2*') already associated with that internal NUCID.

Action Try to determine why two different nuclei in the cluster (as per their external NUCIDs) are attempting to use the same internal NUCID (the "INTNUCID" value in the ADAN03 message). The internal NUCID is derived from the PPT. Run ADACHK PPTPRINT to check the PPT and verify that every cluster nucleus is represented in the PPT.

If in doubt, contact your Software AG technical support representative.

ADAX3H **{dbid} Work dataset for internal NUCID {id1} is already open for external NUCID {nucid} and internal NUCID {id2}**

Explanation The nucleus encountered two different internal NUCIDs for the same external NUCID. The message shows the external NUCID ('*nucid*'), the internal NUCID of a cluster nucleus ('*id1*') that was to be associated with the external NUCID and the internal NUCID of a nucleus ('*id2*') already associated with that external NUCID.

Action Try to determine why the cluster nucleus with the specified external NUCID is being associated with two different internal NUCIDs (the "INTNUCID" value in the ADAN03 message). The internal NUCID is derived from the PPT. Run ADACHK PPTPRINT to check the PPT and verify that every cluster nucleus is represented in the PPT exactly once. If in doubt, contact your Software AG technical support representative.

ADAX40 **{dbid} Adabas abend in cache exit DBID {dbid} NUCID {nucid} abend {routine} S{nnn} U{nnnn }reason {rsn} PSW {psw} REG 0-3 {reg 0 reg 1 reg 2 reg 3} REG 4-7 {reg 4 reg 5 reg 6 reg 7} REG 8-B {reg 8 reg 8 reg 10 reg 11} REG C-F {reg 12 reg 13 reg 14 reg 15}**

Explanation A program check or system abend was intercepted by the z/OS XES parallel sysplex cache service FRR routine. The error occurred under an SRB.

The nucleus should terminate. A dump may be produced in SDUMP format, either in one of the nucleus-allocated files SYSUDUMP, SYSMDUMP, or SYSABEND; or in a system-allocated file such as SYS1.DUMPn.

Action Contact your Adabas technical support representative.

ADAX41	{dbid} ADANCX GETMAIN failed
Explanation	ADANCX is the nucleus extension module for Adabas cluster environments. The attempt to allocate space for this module failed.
Action	Reduce memory requirements or expand the amount of memory available.
ADAX42	{dbid} GETMAIN failed
Explanation	An attempt to allocate space failed.
Action	Reduce memory requirements or expand the amount of memory available.
ADAX43	{dbid} {ADAXEC ADASMC} initialization error - {xxx}
Explanation	Internal error.
Action	Contact your Software AG technical support representative.
ADAX44	{dbid} ADANCX cache-related GETMAIN failed
Explanation	ADANCX is the nucleus extension module for Adabas cluster environments. A second attempt to allocate space for this module failed.
Action	Reduce memory requirements or expand the amount of memory available.
ADAX45	{dbid} Unexpected cache connection error - {xxx}
Explanation	An error occurred while connecting to the sysplex cache structure. See the following messages for the reason.
Action	Correct the problem. If the action to take is not obvious, contact your Software AG technical support representative.
ADAX46	{dbid} GETMAIN failed after connect to cache
Explanation	An attempt to allocate space failed after Adabas was connected to the external cache structure.
Action	Reduce memory requirements or expand the amount of memory available.
ADAX47	{dbid} Cache connect problem RC X{'xxxxxxx'} reason X{'yyyyyyyy'}
Explanation	An error occurred while connecting to the sysplex cache structure. The 'x's identify cache-related return codes; the 'y's identify reason codes to explain the error.
Action	If you are using Adabas Parallel Services, contact your Software AG technical support representative for assistance. If you are using Adabas Cluster Services, see the IBM manual <i>MVS Programming: Sysplex Services Reference</i> for an explanation of the codes. Relevant information can be found in the Return and Reason Codes section of the macro IXLCONN. Common reason codes that occur due to configuration errors include the following:

RC	Reason	Explanation
X'08'	X'xxxx084C'	Improper SAF authorization. Adabas is not authorized to connect to the structure.
X'0C'	X'xxxx0C05'	Structure not defined in CFRM policy, possibly due to a bad structure name parameter.
X'0C'	X'xxxx0C08'	No suitable coupling facility found for structure allocation.
X'0C'	X'xxxx0C29'	The CFRM function is not active or not available.

ADAX48

{dbid} Cache disconnect RC {rrr} CRC X'{xxxxxxxx}'X reason X'{yyyyyyyy}'

Explanation

The message text of this message varies. The following table explains and describes the user action that should occur as a result of the different message texts.

Message Text	Explanation	Action
Cache disconnect RC <i>rrr</i> CRC X'xxxxxxxx'X reason X'yyyyyyyy'	An error occurred while disconnecting from the sysplex cache structure. The return codes from the ADAXEC module (<i>rrr</i>); the return codes from the cache structure (<i>xxxxxxxx</i>); and the reason codes (<i>yyyyyyyy</i>) are provided in the message to explain the error.	If you are using Adabas Parallel Services, contact your Software AG technical support representative for assistance. If you are using Adabas Cluster Services, see the IBM manual <i>MVS Programming: Sysplex Services Reference</i> for an explanation of the codes. Relevant information can be found in the Return and Reason Codes section of the macro IXLDISC.
Block <i>blk-name</i> cast-out locked at disconnect <i>nnnn</i> cast-out locks released at disconnect	A Parallel Services nucleus held a cast-out lock on one or more cache blocks when disconnecting from the global cache. The cast-out locks have been released. This may happen during an online recovery process. The first message is repeated for every block affected; the second one summarizes how many blocks were affected.	If these messages occur during online recovery, no action is required. However, if these messages appear during normal session termination, contact your Software AG technical support representative.

Action

Perform the action described in the table above.

ADAX49	<p>{dbid} Unexpected cache return code encountered {dbid} Function X'{ff}' {xxxxxxxxxxxxxxxxxxxxxxxxxxxx} {dbid} CRC X'{yyyyyyyy}' reason X'{zzzzzzz}'</p>
Explanation	An unexpected return code was returned during execution of a macro related to the cache structure.
Action	<p>If you are using Adabas Parallel Services, contact your Software AG technical support representative for assistance.</p> <p>If you are using Adabas Cluster Services, see the IBM manual <i>MVS Programming Sysplex Services Reference</i> for an explanation of the codes. Relevant information can be found in the Return and Reason Codes section of the macro IXLCACHE, in the chapter corresponding to the function displayed in the message.</p>
ADAX50	<p>{dbid} GETMAIN failed for cast-out directory buffer {dbid} Size requested X{nnnnnnnn}</p>
Explanation	An attempt to allocate space for the cast-out directory buffer failed.
Action	Reduce memory requirements or expand the amount of memory available.
ADAX51	<p>{dbid} Cache structure allocation unacceptable {dbid} Requested cache allocation values {dbid} Storage classes X'{ee}' {dbid} Cast-out classes X'{ffff}' {dbid} ADJUNCT=YES {dbid} Maximum data elements per entry X'{gg}' {dbid} Data element characteristic X'{hh}' {dbid} Actual cache allocation values {dbid} Storage classes X'{ii}' {dbid} Cast-out classes X'{jjj}' {dbid} ADJUNCT={YES NO} {dbid} Maximum data elements per entry X'{kk}' {dbid} Data element characteristic X'{mm}'</p>
Explanation	The Adabas nucleus connected successfully to the cache structure; however, the attributes of the cache structure are inappropriate for the Adabas sysplex cluster. Most likely, the cache structure is already being used by another program.
Action	Determine which other program is using the cache structure. Either terminate this other program or specify a different cache structure for use by Adabas Cluster Services.

ADAX52 **{dbid} Incompatible existing user(s) of the {dbid} cache structure {cache-structure-name}**

Explanation The cache structure with the name indicated is already being used by another Adabas cluster. Cache structure names may only be used for a single Adabas cluster of nuclei.

Action Use the cache structure name identified for use by your particular cluster.

ADAX53 **{dbid} Internal error - no available XQRB**

Explanation An internal error has occurred.

Action Contact your Software AG technical support representative for assistance.

ADAX54 **{dbid} Insufficient cache data elements**

Explanation The cache structure connected successfully; however, the number of cache data elements in the external cache structure (or global cache area) is not sufficient. There must be enough data elements to hold 80,000 or more bytes of information. The number of data elements allocated is indicated earlier in message ADAX57.

Action Increase the size of the external cache structure (or global cache area). Alternatively, modify the ADARUN parameters DIRRATIO and/or ELEMENTRATIO to ensure that enough cache data elements are allocated.

ADAX55 **{dbid} This job will now terminate**

Explanation An internal error occurred that caused the nucleus to terminate abnormally. A message issued prior to this one provides more information related to the error.

Action Contact your Software AG technical support representative for assistance.

ADAX56 **{dbid} {message-text}**

Explanation Various message texts can be associated with the message number, as described in the following table:

Message Text	Explanation
Unable to obtain PLXCB address	The nucleus is unable to locate the PLXCB in common storage.
Unable to obtain ALET of XQRB data space	The nucleus could not connect to the messaging data space.
More than 31 XQRB areas in data space	The nucleus did not find free space for its own use in the messaging data space.

Action For all possible message texts, contact your Software AG technical support representative for assistance.

ADAX57	<p>{dbid} Connected to cache structure {cache-structure-name} {dbid} Directory elements {xxxxxx} {dbid} Data elements {yyyyyy} {dbid} Data element size {zzzzzz}</p>
Explanation	An Adabas cluster nucleus successfully connected to the specified cache structure (or global cache area) in a cluster environment. This message provides a count of the cache's directory entries and data elements, along with the data element size.
Action	No action is required for this informational message.
ADAX58	<p>{dbid} Time expired waiting for notification of {dbid} existing connectors to the cache structure</p>
Explanation	The attempt to connect an Adabas cluster nucleus to the cluster cache structure in a sysplex environment timed out waiting for information about existing connections to the cache structure.
Action	Try again to start the Adabas sysplex cluster nucleus. If the error continues to occur, contact your Software AG technical support representative.
ADAX59	<p>{dbid} Unexpected return code from {ADAXEC ADASMC} {dbid} function X'ff' {xxxxxxxxxxxxxxxxxxxxxxxx} {dbid} RC {rrr}</p>
Explanation	An unexpected return code was received during a call to the referenced module. The message includes the function code and return code.
Action	Contact your Software AG technical support representative.
ADAX5A	<p>{dbid} DSST update omitted because cache or buffer pool full</p>
Explanation	<p>After data storage updates, the nucleus is unable to read a DSST block into the buffer pool or global cache or to write the updated DSST block to the cache, because the buffer pool or cache was full. It is possible that the DSST bytes for one or more of the updated data storage blocks are incorrect.</p> <p>This message is printed at most once in 10 minutes.</p> <p>Incorrect DSST bytes may have slightly adverse effects on the effectiveness of space reuse in data storage. If the associated data storage blocks are updated again, incorrect DSST bytes are implicitly corrected.</p>
Action	Either the buffer pool or the global cache or both are too small to support the number of parallel commands running in the nucleus or the whole cluster. Increase the buffer pool or global cache size.

ADAX5B	{dbid} Connecting to S64 cache at {address} {dbid} Connect to S64 cache return code {ADAIOR-return-code}/{zOS-return-code}/{zOS-reason-code} {dbid} Disconnecting from S64 cache {dbid} Disconnect from S64 cache return code {ADAIOR-return-code}/{zOS-return-code}/{zOS-reason-code}
Explanation	ADABAS Parallel Services is using z/OS shared 64-bit addressable storage as part of its cache configuration. Connecting to the S64 object establishes a local affinity and makes the object addressable. Disconnecting deletes the affinity, after which the object is no longer addressable. Any non-zero return code received from z/OS IARV64 is formatted.
Action	If the attempt fails, examine the IARV64 return and reason code description in the IBM documentation entitled <i>MVS Programming: Authorized Assembler Services Reference, Volume 2 (EDTINFO-IXGWRITE)</i> . If the cause is not clear, notify your Software AG technical support representative.
ADAX5C	{dbid} Unchanged blocks will [NOT] be written to cache
Explanation	This message reports the setting of the ADARUN CLUCACHEUNCHANGED parameter for this Adabas Parallel Services nucleus. Unchanged blocks either will or will not be written to the global cache.
Action	No action is required for this informational message.
ADAX5D	{dbid} Invalid cache token{ tt...tt} at disc
Explanation	A logic error occurred. An invalid token was passed to the cache disconnect function. If the disconnect is already identified as abnormal, termination continues. If not, the nucleus ends with abend S0C6.
Action	Contact your Software AG technical support representative for assistance.
ADAX5E	{dbid} Reducing CLUWORK1CACHE to {xx}
Explanation	The specified value for the CLUWORK1CACHE parameter is larger than NWORK1BUFFERS+1 or LP / 20, which serve as upper boundaries for this parameter. CLUWORK1CACHE is reduced to the smaller of these two values (shown as 'xx').
Action	No action is required for this informational message. If you wish to make the specified CLUWORK1CACHE value effective, increase the NWORK1BUFFERS parameter to a value greater than the desired CLUWORK1CACHE value and/or increase the LP parameter to at least 20 times the desired CLUWORK1CACHE value.

ADAX5F	{dbid} Effective CLUWORK1CACHE maximum is {xx}
Explanation	The specified value for the CLUWORK1CACHE parameter, taken in units of Work blocks, amounts to more than 1% of the total size of the data elements in the global cache structure of the cluster. To limit the portion of the cache taken away from ASSO and DATA blocks, at most 1% of the total size of the data elements will be used for protection data. This amounts to the number of Work blocks shown ('xx').
Action	No action is required for this informational message. If you wish to make the specified CLUWORK1CACHE value effective, increase the size of the cache structure such that the number of data elements times the data element size (i.e., the total size of all data elements) is at least a factor of one hundred times the CLUWORK1CACHE value times the block size of the Work data set.
ADAX5G	{dbid} Using data from protection data extension area on WORK of NUCID {nucid}
Explanation	To perform a session autorestart in the course of online or offline recovery, the nucleus is using protection data from the related extension area on the Work data set of the nucleus with the specified (external) NUCID. That nucleus was running with the parameter CLUPUBLPROT=YES and had not participated in the last buffer flush prior to the nucleus failure that triggered the autorestart. In its place, another nucleus had written any missing protection data to the extension area.
Action	No action is required for this informational message.
ADAX5H	{dbid} Partially written block in WORK part 1 extension NUCID={nucid}, RABN={rrrr}
Explanation	While recovering from the failure of one or more Adabas cluster nuclei, this nucleus encountered a Work block in the protection data extension area in which the timestamp at the beginning of the block did not match the control timestamp at the end of the block. The last write of the block was incomplete, or the block has been damaged for another reason. It is inconsistent and cannot be used for recovery. The block was read from the Work data set of the nucleus with the NUCID ' <i>nucid</i> '. Its RABN is ' <i>rrrr</i> '.
Action	Restore and regenerate the database. If in doubt, contact your Software AG technical support representative.
ADAX60	{Peer nucleus Unknown connector} {connection-name } {is already has} connected to {cache lock} structure {structure-name}
Explanation	An event occurred related to another connector of a cache or lock structure.
Action	No action is required for this informational message.

ADAX61 {date time statistic-text statistic-value}**Explanation**

Whenever a nucleus disconnects from a cache, this message is issued with cache activity statistics. These may be useful in diagnosing problems and selecting a suitable cache configuration. Bear in mind that the statistics show only one nucleus's activity. Full understanding may require examining the statistics of other nuclei.

This message is also used to display the output from the DXSTAT, DXCACHE, DXLOCK, DXFILE, and DMEMTB operator commands on the console. For examples of this message used with these commands, refer to the documentation for Adabas Cluster Services operator commands.

Here is an example of the statistics provided in this message:

```
ADAX61 Statistics at disconnect for cache C00C7231 ↵
    Cache Directory Management Activity ↵
        32,565 Read located active ↵
        5,230 Read obtained from free pool ↵
            0 Read reclaimed, first choice criteria ↵
            0 Read reclaimed, second choice criteria ↵
            0 Read reclaimed, third choice criteria ↵
            0 Read reclaimed, fourth choice criteria ↵
            0 Read unable to obtain (cache full) ↵
            0 Total number of directory reclaim ↵
attempts                                0 Number of directories examined for ↵
reclaim                                  0.000 Average number of directories examined ↵
per attempt                              680 Write obtained from free pool ↵
                                          496 Directory high-water mark (this ↵
nucleus)                                 1,134 Directory high-water mark ↵
(cluster-wide)
    Cache Write Requests ↵
        306,706 Sufficient preallocated space ↵
        235 Free space allocated ↵
        5 Space reclaimed, first choice criteria ↵
```

criteria	6,322	Space reclaimed, second choice	↔
	885	Unable to obtain space (cache full)	↔
chain	4,292	Space search examined part of space	↔
chain	3,155	Space search examined entire space	↔
attempts	7,447	Total number of space allocation	↔
examined	462,840	Number of space chain descriptors	↔
per attempt	62.151	Average number of descriptors examined	↔
		Cache Space Element Reclamation	↔
criteria	48	Elements reclaimed, first choice	↔
criteria	28,431	Elements reclaimed, second choice	↔
		Latch Attempts	↔
		Exclusive	↔
		Shared	↔
		Cache Space Chain	↔
		Get	7,455 ↔
		WaitFor	8 ↔
		Release	7,447 ↔
		Cache Directory Index	↔
		Get	5,351 ↔
249,009		5,228 Upgrade	↔
		WaitFor	0 ↔
0		0 Upgrade	↔
		Release	10,579 ↔
243,781		Cache Directory	↔
		Get	454,179 ↔
398,747		5,335 Upgrade	↔
		WaitFor	205 ↔

53	Release	459,297	↔
393,339	Cache Cast-Out Class		↔
3,510	Get	44,865	↔
0	WaitFor	0	↔
3,510	Release	44,865	↔

These statistics are described in the following table:

Message Statistic Type	Description
Cache Directory Management Activity	<p>Cache directory elements describe ASSO and DATA blocks that have been referenced. Directory elements are also used to describe unallocated space in the cache data storage pool. The number of directory elements created during cache initialization is shown in message ADAX57.</p> <p>The first reference to an ASSO or DATA block is a cache read request. If the block is already known in the cache, the existing directory element is located. Otherwise, a directory element must be allocated. If there are none in the free pool, the nucleus must search for an existing element that may be reclaimed. Directory elements for blocks that have been modified (“dirty”) and not yet written to external storage (“hardened”) may not be reclaimed. The remaining directory elements are examined to select one that describes a block that is least likely to be needed in the near future. There are four sets of criteria in order of decreasing desirability. In the best case, there is less likelihood of additional I/O from a cache miss, and in the worst case we have reclaimed an element that describes a block likely to be reused, and thus there's a higher probability of additional I/O. Factors such as the number of nuclei that have referenced the block, whether the block has been referenced recently, and the status of the block's contents are part of the selection criteria.</p> <p>If all directory elements describe dirty blocks, the cache is considered full and the directory allocation fails. The nucleus then executes a buffer flush to harden the dirty blocks, after which the request is tried again.</p> <p>A write request may also attempt to allocate a directory element to describe fragmented space. This is not a frequent occurrence.</p>

Message Statistic Type	Description
	<p>If reclaimed directory elements are a significant portion of the total activity, especially reclaims from the higher criteria, consider increasing the number of directory elements for best performance.</p> <p>The cache control structures are rebuilt as part of online recovery after a nucleus fails. This will reset the cluster-wide high water mark but will not affect the individual member high water mark.</p>
Cache Write Requests	<p>If the directory element does not already describe sufficient space to contain the block, additional space is first obtained from the free pool. If a suitable block cannot be found, space from one or more existing blocks will have to be reclaimed to assemble a contiguous area. If no suitable area can be assembled without including space containing dirty blocks, the cache is considered full. The nucleus executes a buffer flush and retries the request. As with directory elements, the selection criteria are used to reduce the chance that additional I/O will be needed because an active block was removed.</p>
Cache Space Element Reclamation	<p>The cache data element is shown in message ADAX57. A cached ASSO or DATA block requires one or more data elements.</p>
Latch Attempts	<p>Access to data structures shared among multiple nuclei is serialized by high-performance latches. These are administered entirely by the nuclei—they are not z/OS-administered latches. A latch may be acquired either exclusive or shared, and a shared latch may be upgraded to exclusive. If the latch cannot be acquired immediately, the nucleus may elect to wait for it.</p> <ul style="list-style-type: none"> ■ There is one cache space chain latch to serialize space allocations. ■ There is a directory element index latch for each index element. It is held when searching for an existing directory element. It is also held when allocating or releasing a directory element. ■ There is a separate latch to serialize updates for each directory element. ■ There is a separate latch for each cast-out class to serialize access to directory elements during buffer flushes.

Action

No action is required for this informational message.

ADAX62 **Unexpected lock return code encountered**
function {function_name}
For {lock_type}
LRC X'{ccccccc}' reason X'{rrrrrrr}'

Explanation An attempt to lock or unlock a logical resource failed.

Where *function_name* is the lock manager function name or X'xx' hexadecimal value of the function code for invalid function code; *lock_type* is the name of the lock type; its response code is *ccccccc* (in hexadecimal); and its reason code is *rrrrrrr* (in hexadecimal).

The nucleus terminates abnormally.

Action This is an unexpected error. Contact your Software AG technical support representative for assistance.

If you are using Adabas Cluster Services, see the IBM manual *MVS Programming: Sysplex Services Reference* for an explanation of the codes. Relevant information can be found in the Return and Reason Codes section of the macro IXLLOCK.

ADAX63 **Lock {connect|disconnect} problem RC X'{ccccccc}' reason X'{rrrrrrr}'**

Explanation An error occurred while connecting to or disconnecting from the lock structure. The lock manager's response code is *ccccccc*, its reason code is *rrrrrrr*. Both variables are in hexadecimal.

The nucleus terminates abnormally.

Action This is an unexpected error. Contact your Software AG technical support representative for assistance.

If you are using Adabas Cluster Services, see the IBM manual *MVS Programming: Sysplex Services Reference* for an explanation of the codes. Relevant information can be found in the Return and Reason Codes section of the macros IXCQUERY and IXLCONN for connection problems and IXLDISC for disconnection problems. Common reason codes that occur due to configuration errors during connection attempts include the following:

RC	REASON	Explanation
X'08'	X'00000024'	Structure not defined in CFRM policy.
X'08'	X'xxxx084C'	Improper SAF authorization. Adabas is not authorized to connect to the structure.
X'0C'	X'00000154'	No CFRM policy active.
X'0C'	X'xxxx0C05'	Structure not defined in CFRM policy, possibly due to a bad structure name parameter.
X'0C'	X'xxxx0C08'	No suitable coupling facility found for structure allocation.
X'0C'	X'xxxx0C29'	The CFRM function is not active or not available.

ADAX64	ADANCX lock-related GETMAIN failed
Explanation	The lock manager failed to acquire main storage.
Action	Restart the nucleus with a larger REGION parameter or make the nucleus parameters NH, NU, or LDEUQP smaller.
ADAX65	Parameter taken over: {parameter-name} old: {old-value} new: {new-value}
Explanation	This message is printed in two instances. It occurs when: <ol style="list-style-type: none"> 1. The parameter value of a newly started cluster nucleus is taken over (replaced) by the global parameter value in use by the already active cluster nuclei. The old value (<i>old-value</i>) is the parameter value read from the ADARUN statements of the starting nucleus; the new value (<i>new-value</i>) is the global parameter value in use by the already active cluster nuclei. 2. A global parameter value is changed on one nucleus in the cluster. This new parameter value is propagated to all of the other active cluster nuclei and is taken over (used) by them.
Action	No action is required for this informational message.
ADAX66	Incompatible global parameter {parameter-name} specified: {value-specified} in effect: {value-in-effect}
Explanation	An incompatible parameter value has been specified for a second or subsequent cluster nucleus when it starts. When this occurs, the starting nucleus: <ul style="list-style-type: none"> ■ Does not take over (use) the global parameter value. ■ Does not come up. <p>The parameter value specified (<i>value-specified</i>) by the second or subsequent cluster nucleus and the parameter value currently in effect (<i>value-in-effect</i>) for all cluster nuclei are given in the message.</p>
Action	Resolve the incompatibility of the parameter values so that the newly started cluster nucleus and the other active cluster nuclei can use the same parameter value.
ADAX67	Incompatible existing user(s) of the lock structure {lock-structure-name}
Explanation	The lock structure with the name specified in the message is already being used by another Adabas sysplex cluster or by other software. Lock structure names must be unique in the sysplex environment and for each Adabas nucleus cluster.
Action	Use the lock structure name that has been identified for use by your particular Adabas sysplex cluster.

ADAX68	Time expired waiting for notification of existing connectors to the lock structure
Explanation	An attempt to connect an Adabas sysplex cluster nucleus to the lock structure timed out waiting for information about existing connections to the lock structure.
Action	Determine whether any conditions exist in the coupling facility or the system itself that could interrupt the flow of information or make the flow extremely slow.
ADAX69	Lock structure too small expected min number of records {nnn,nnn,nnn}
Explanation	The lock structure defined in the CFRM policy is too small to handle the current settings of the ADARUN parameters. The minimum number of records expected by the processes is indicated.
Action	Either decrease the value of the ADARUN parameters NU, NH, or LDEUQP; or increase the size of the lock structure.
ADAX6A	Lock structure full encountered function {function_name} For {lock_type} LRC X'ccccccc' reason X'rrrrrrrr'
Explanation	An attempt to lock a logical resource failed. Where <i>function_name</i> is the lock manager function name or X'xx' hexadecimal value of the function code for invalid function code; <i>lock_type</i> is the name of the lock type; its response code is <i>ccccccc</i> (in hexadecimal); and its reason code is <i>rrrrrrrr</i> (in hexadecimal).
Action	The nucleus terminates abnormally. This is an unexpected error. Contact your Software AG technical support representative for assistance. If you are using Adabas Cluster Services, see the IBM manual <i>MVS Programming: Sysplex Services Reference</i> for an explanation of the codes. Relevant information can be found in the Return and Reason Codes section of the macro IXLLOCK.
ADAX6B	IXLEERSP request got RSP {rsp-code} RSN {reason-code}
Explanation	After a peer nucleus disconnected abnormally from the lock structure, this nucleus issued an IXLEERSP request to XES to acknowledge the peer failure, but the IXLEERSP request got the response code and reason code shown. These are documented in <i>MVS Programming: Sysplex Services Reference</i> IBM manual in the <i>Return and Reason Codes</i> section of the IXLEERSP macro. This nucleus will continue performing the online recovery process after the peer failure. It will disconnect from the lock structure as part of the recovery process, which is another way of acknowledging the peer failure to XES. However, due to the

	unsuccessful IXLEERSP request, there is a very small chance of a cluster-wide deadlock involving XES.
Action	In the case of a hangup of the online recovery process, cancel a nucleus that has not yet printed an ADAX89 message. This may unravel the deadlock. If there is no such nucleus, cancel the nucleus that will do the session autorestart, as per the ADAX89 messages. Restart the cluster after all nuclei have terminated. In either case, report the occurrence of the ADAX6B message to your Software AG technical support representative.
ADAX6C	Active nucleus {nucid} is at level V{vrsc}
Explanation	A nucleus at a different release or maintenance level is attempting to join the cluster. If the starting nucleus is known to be incompatible with the active ones initialization fails with Parm-Error 124.
Action	Check the Release Notes to see if this is an incompatible combination.
ADAX70	Connected to lock structure {lock-structure-name} number of lock entries {nnn,nnn} max number of record elements {nn,nnn}
Explanation	An Adabas cluster nucleus successfully connected to the specified lock structure in a z/OS parallel sysplex environment. This message provides <ul style="list-style-type: none"> ■ a count of lock entries; and ■ the maximum number of records elements.
Action	No action is required for this informational message.
ADAX71	Retrying cache write for RABN X'{rrrrrrrr}'
Explanation	This message identifies the RABN value in hexadecimal for which a cache write is being retried. The error leading to the write retry is identified in previous messages.
ADAX72	GETMAIN failed for lock element table size requested X{nnnnnn}
Explanation	An attempt to allocate space for the lock element table failed.
Action	Reduce the memory requirements for the table or expand the amount of memory available.

ADAX73	Lock structure size error
Explanation	An error was detected in the lock structure policy: both the SIZE and INITSIZE values are zero.
Action	Review the lock structure policy and make the necessary changes.
ADAX74	{dbid} Warning: Now it is too late to copy DDPLOGR{n}
Explanation	Corresponds to the ADAN05 message at startup, but occurs during online recovery. Adabas has begun to write data protection log data to the data set identified by DD/PLOGRn. This means that the data set can no longer be copied to tape for subsequent use as input to the REGENERATE or BACKOUT functions of the ADARES utility. A user exit 2 (dual log processing) or user exit 12 (multiple log processing) call either was not made or did not successfully copy the DD/PLOGRn data set with the ADARES utility.
Action	If the database is running without user exit 2, overwriting the PLOG data is normal and this message can be ignored. If the database is running with user exit 2, this message occurs only when the user exit asks the nucleus to proceed even though the PLOG has not been copied. Whether this is an error or not depends on the logic the user has implemented in the user exit.
ADAX75	{dbid} Protection log PLOGR{n} started
Explanation	Corresponds to the ADAN21 message at startup, but occurs during online recovery. Adabas is now ready to begin writing data protection information to the dual or multiple data protection log identified by DD/PLOGRn.
Action	Execute the PLCOPY function of the ADARES utility at this time to reinitialize the PLOGs.
ADAX76	{dbid} Nucleus run with protection log {nnnnn}
Explanation	Corresponds to the ADAN02 message at startup, but occurs during online recovery. The Adabas nucleus session has been initiated and database protection logging has been specified. Subsequent execution of the REGENERATE and BACKOUT functions of the ADARES utility for any updates applied during the session is possible.
ADAX77	{dbid} IDTH prefix problem
Explanation	A query request to ADAMPM to get the address of the IDTH failed. The nucleus terminates abnormally.
Action	This is an unexpected error. Contact your Software AG technical support representative.

ADAX78	{dbid} ADACOM is not running or CLULOCKSIZE is not specified
Explanation	While trying to connect to the global lock area, ADASML detects that either ADACOM is not running or the CLULOCKSIZE parameter is not specified. The nucleus terminates abnormally.
Action	Start ADACOM before starting the Adabas Parallel Services cluster nucleus and specify a nonzero value for the CLULOCKSIZE parameter.
ADAX79	{dbid} Global resource lock on this system is invisible to NUCID {nucid} on the system {sysname}
Explanation	Cluster Services nuclei working on the same database synchronize some of their actions using resource locks via Global Resource Serialization (GRS). During session start one nucleus detected that a resource lock it obtained was not effective against the peer nucleus with the NUCID shown, which was active on the system shown.
Action	The starting nucleus terminates with parm-error 105. Contact your system programmer to ensure that GRS is configured in a way that GRS resource locks are mutually effective against one another on all systems on which you intend to run Cluster Services nuclei.
ADAX7A	{dbid} {nnnnn} remaining users taken over by NUCID {nucid}
Explanation	When a cluster nucleus (<i>nucid</i>) running OPENRQ=NO shuts down, users who should get response code 9 (ADARSP009) may be assigned to another running nucleus. The number of users taken over (<i>nnnnn</i>) is reported in this informational message.
Action	No action is required for this informational message.
ADAX7B	{dbid} {nnnnn} remaining users not taken over by peer nuclei
Explanation	When a cluster nucleus running OPENRQ=NO shuts down, users who should get response code 9 (ADARSP009) may be assigned to another running nucleus. The number of users that could not be taken over is reported in this informational message. Users may be taken over only if peer nuclei are available and able to accept new users.
Action	No action is required for this informational message.
ADAX80	{dbid} Online recovery initiated
Explanation	An Adabas cluster nucleus initiated an online recovery process after it detected that a peer nucleus in the same cluster terminated abnormally. (Each surviving nucleus initiates its own online recovery process.) The online recovery process stops all ongoing work in the nucleus, performs a session autorestart (including the backout of all open transactions), or waits until a peer nucleus performs the session autorestart, and then resumes normal processing.

ADAX80	{dbid} Online recovery in progress
Explanation	A nucleus started while other nuclei that were already active in the same cluster were performing online recovery in response to a nucleus failure. The starting nucleus waits until the online recovery process completes and then continues with its startup sequence.
ADAX80	{dbid} {Online save Trans suspend ADAEND/halt} process canceled
Explanation	In order to recover from the failure of a peer nucleus (online recovery), the nucleus canceled <ul style="list-style-type: none">■ a running online save operation in which case the save operation fails;■ a running transaction suspension operation; or■ an ADAEND or HALT shutdown request, in which case the nucleus does not shut down after the recovery process has finished.
Action	Either restart the save operation after the online recovery process has completed successfully; or issue another ADAEND or HALT request if you still want to shut down the nucleus.
ADAX81	{dbid} Waiting for active transactions to finish
Explanation	When the online recovery process started, one or more transactions were active. The recovery process allows them to continue for a while in an attempt to bring them to normal completion.
ADAX82	{dbid} All transactions finished
Explanation	All transactions that were active when online recovery started have finished normally.
ADAX82	{dbid} {count} active transaction(s) interrupted
Explanation	A number of transactions indicated in the message were active when online recovery started but did not finish within the allotted time and were interrupted. They are backed out during online recovery. The affected users receive response code 9 (ADARSP009), subcode 18, for their next commands.
ADAX83	{dbid} Waiting for active commands to finish
Explanation	When the online recovery process was ready to interrupt all ongoing work, one or more commands were still active. The recovery process allows them to continue for a short time in an attempt to bring them to normal completion.

ADAX84	{dbid} All commands finished
Explanation	All active commands that the online recovery process was waiting for have finished normally.
ADAX84	{dbid} {count} Active command(s) interrupted
Explanation	A number of active commands indicated in the message did not finish within the allotted time and were interrupted. They are sent back to their respective users with response code 9 (ADARSP009), subcode 19. Their associated command IDs, if any, are deleted.
ADAX85	{dbid} Waiting for active I/Os to finish
Explanation	When the online recovery process interrupted all ongoing work, one or more I/Os were active. The recovery process waits for these I/Os to finish.
ADAX86	{dbid} All I/Os finished
Explanation	All I/Os that the online recovery process was waiting for have finished.
ADAX87	{dbid} Waiting for outstanding messages to be answered
Explanation	When the online recovery process interrupted all ongoing work, one or more internucleus commands were still due a response. The recovery process waits for the responses to arrive.
ADAX88	{dbid} All outstanding messages answered
Explanation	All outstanding responses for internucleus commands that the online recovery process was waiting for have arrived.
ADAX89	{dbid} Session autorestart will be done by {this peer} nucleus
Explanation	The session autorestart that is part of the online recovery process is performed either by this nucleus or by a peer nucleus, as indicated in the message.
ADAX8A	{dbid} Restarting online recovery process
Explanation	Shortly before the end of an online recovery process (following the failure of a peer nucleus), another peer nucleus has terminated abnormally. The online recovery process is restarted to recover the cluster from this latest failure.

ADAX90 **{dbid} Recovery syncpoint {syncpoint} initiated**
Explanation If more than one nucleus remains active when a peer nucleus terminates abnormally, the surviving nuclei synchronize their online recovery processes using several syncpoints, which all nuclei must reach before recovery processing can continue.

This message indicates that the nucleus that performs the session autorestart is ready to proceed when all other nuclei have reached the respective syncpoint.

ADAX91 **{dbid} Waiting on recovery syncpoint {syncpoint}**
Explanation The online recovery process is waiting for the nucleus that performs the session autorestart to initiate the recovery syncpoint indicated.

ADAX92 **{dbid} Recovery syncpoint {syncpoint} reached**
Explanation All nuclei involved in the collaborative online recovery have reached the recovery syncpoint indicated. The recovery process proceeds.

ADAX93 **{dbid} Beginning session autorestart**
{dbid} Beginning WORK4 interpretation
{dbid} WORK4 handling failed
Explanation Various message texts can appear for this message number. The explanation and action for each is given in the following table.

Message Text	Explanation
Beginning session autorestart	One of the nuclei surviving a peer failure (this nucleus) begins the key step of online recovery-the session autorestart.
Beginning WORK4 interpretation	One of the peer nuclei failed, so one of the surviving nuclei begins autorestart processing, if DTP=RM. The WORK4 interpretation must occur before the autorestart is executed.
WORK4 handling failed	WORK4 interpretation was not successful. Refer to messages ADAN85 and ADAN86 for more information. All nuclei will go down.

ADAX94 **{dbid} Session autorestart executed successfully**
{dbid} DTP=RM-USERS are copied
{dbid} DTM=RM-USER-COPY failed
{dbid} DTM=RM-USER-LOCKS not gotten
Explanation Various message texts can appear for this message number. The explanation and action for each is given in the following table.

Message Text	Explanation
Session autorestart executed successfully	The session autorestart performed during online recovery was successful. No action is required for this informational message.
DTP=RM-USERS are copied	PET/HEURI users from other nuclei are copied to the user queue of the recovery nucleus (including transaction IDs and file lists). No action is required for this informational message.
DTM=RM-USER-COPY failed	The user copy failed, probably due to a logic error. All nuclei will go down.
DTM=RM-USER-LOCKS not gotten	If DTP=RM, the nucleus must get hold queue and UQDE locks for all users on PET status who are copied to DDWORKR4. All nuclei will go down.

ADAX95

{dbid} Session autorestart failed
{dbid} Response code = {response-code}
{dbid} File number = {file-number}
{dbid} All active nuclei will go down

Explanation

The session autorestart performed during online recovery was not successful. It received the response code shown. If the response code was associated with a particular file, the file number is also shown.

This nucleus and all peer nuclei participating in the online recovery process will go down.

Action

The situation is now equivalent to that after failure of session autorestart during nucleus session start. Determine why the session autorestart failed. Consider contacting your Software AG technical support representative.

ADAX96

{dbid} Peer nucleus failed during online recovery
{dbid} This nucleus goes down too

Explanation

A second nucleus failure occurred while an online recovery process was in progress to handle the abnormal termination of a peer nucleus. All nuclei active in the Adabas cluster will go down.

Action

Restart the Adabas cluster. Determine the reasons for the first and the second failure. Consider contacting your Software AG technical support representative.

ADAX96	{dbid} Utility with exclusive database control is active {dbid} This nucleus goes down too
Explanation	A nucleus failure occurred while a utility with exclusive database control was running. All nuclei active in the Adabas cluster will go down.
Action	Restart the Adabas cluster and perform appropriate recovery actions for the utility with exclusive database control.
ADAX97	{dbid} Online recovery completed successfully {dbid} Resuming normal operation
Explanation	The online process set up to handle the abnormal termination of a peer nucleus finished successfully. The nucleus resumes normal operation.
ADAX98	{dbid} Received response code {rsp-code} from peer nucleus
Explanation	An online recovery process that was started to recover from the failure of one nucleus received a response code while communicating with another, still alive nucleus. All remaining active nuclei terminate.
Action	Restart the nuclei. The first starting nucleus performs offline recovery (that is, session autorestart).
ADAX98	{dbid} V2/{xxx} command received {rsp-rr/ss} from NUCID {nnn}
Explanation	An internal command used for inter-nucleus communication encountered a messaging failure; it got the response code/subcode shown from the peer nucleus shown.
ADAX99	{dbid} Uncorrectable intracluster communication failure
Explanation	This message may follow message ADAX9E or ADAX9H. After a messaging failure during intracluster communication the nucleus has decided to terminate itself due to an uncorrectable communication failure.
Action	<p>The nucleus terminates abnormally with user abend code 79.</p> <p>Investigate the cause of the intracluster communication failure, starting with the response code and subcode reported in one or more preceding ADAX9E messages.</p> <p>If some kind of timeout (MXMSGWARN, MXMSG, MXCANCELWARN, or MXCANCEL parameter) was involved in the failure, ensure that all cluster nuclei run with high enough priority to get sufficient resources for participating in cluster-wide business.</p> <p>Consider contacting your Software AG technical support representative.</p>

ADAX9A	{dbid} Could not determine message status for V2/{xxx} command return code = {nn}
Explanation	When a cluster nucleus tried to determine the status of an internal intracluster command (given in the message), an error occurred. The internal return code is shown. A preceding message might possibly contain more information about the error. The nucleus ignores the error and continues normally. Because it could not determine the status of the responses to the intracluster command cited, it does not warn early about outstanding responses (ADAX9B and ADAX9C messages)
Action	Contact your Software AG technical support representative.
ADAX9B	{dbid} Caution: Waiting for V2/{xxx} CMD being sent to NUCID ({nn})
Explanation	A cluster nucleus issued an XCF send request for an intracluster command (shown) to a peer nucleus (shown), but the command has not yet been sent within the time period set by the MXMSGWARN parameter. The number nn (shown) distinguishes different internal intracluster commands that may be in progress at the same time. No direct system action occurs. However, if the command is not sent or the peer nucleus does not respond within the time period set by the MXMSG parameter, either nucleus may terminate abnormally.
Action	This message is for your information. It may be useful for analysis in the case of a subsequent error.
ADAX9C	{dbid} Caution: NUCID {nucid} ({jobname}) on system {sysn} is slow to respond to internal V2/{xxx} command ({nn})
Explanation	A cluster nucleus sent an internal intracluster command (shown) to a peer nucleus (shown) in the cluster. The peer nucleus has not yet responded to the command within the time period set by the MXMSGWARN parameter. The number nn (shown) distinguishes different internal intracluster commands that may be in progress at the same time. No direct system action occurs. However, if the peer nucleus does not respond within the time period set by the MXMSG parameter, it will be canceled.
Action	This message is for your information. You may want to use the provided information (NUCID, job name, system name) to make sure that the cited peer nucleus gets sufficient resources (CPU, storage, priority) for participating in cluster-wide business.
ADAX9D	{dbid} Clear: received response to V2/{xxx} from NUCID ({nn})
Explanation	The peer nucleus listed in the message (<i>nucid</i>) that was slow to respond to an internal intracluster command (<i>xxx</i>) has finally responded. This message retracts the warning of a previous ADAX9B or ADAX9C message (shown with a matching <i>nn</i> number). The peer nucleus is no longer in danger of being canceled (for this particular intracluster command).
Action	No action is required for this informational message.

ADAX9E	{dbid} Error: V2/{xxx} {cmd} received RSP {rsp/sub} from NUCID {nucid}
Explanation	<p>The internal command listed in the message (<i>xxx</i>) and used for intracluster communication encountered a messaging failure. The response code and subcode as well as the peer nucleus are given in the message. The response code and subcode are described in <i>Nucleus Response Codes</i>, elsewhere in this guide.</p> <p>The reaction of the nucleus to this error varies, depending on the type of internal command and on the response code received. The nucleus may cancel the peer nucleus causing the error, wait for a failing peer nucleus to terminate, terminate itself due to an unhandled error condition, or pass the response code up the call chain.</p>
Action	<p>Investigate the cause of the response code and subcode to resolve the error.</p> <p>If some kind of timeout (MXMSGWARN or MXMSG parameter settings) is involved in the error, ensure that all cluster nuclei run with high enough priority to get sufficient resources for participating in cluster-wide business.</p> <p>If the problem persists, contact your Software AG technical support representative.</p>
ADAX9F	{dbid} Canceling peer nucleus {nucid} ({jobname}) on system {sysn}
Explanation	<p>This message may follow message ADAX9E. A failure occurred when a nucleus issued an intracluster command to a target peer nucleus (listed in the message) because the target nucleus did not respond to the command in time. As a result, the sending nucleus is canceling the target peer nucleus.</p> <p>The nucleus waits for the canceled peer nucleus to terminate and then performs an online recovery process.</p>
Action	<p>Investigate the cause of the intracluster communication failure, starting with the response code and subcode reported in one or more preceding ADAX9E messages.</p> <p>If some kind of timeout (MXMSGWARN or MXMSG parameter setting) was involved in the failure, ensure that all cluster nuclei run with high enough priority to get sufficient resources for participating in cluster-wide business.</p> <p>If the problem persists, contact your Software AG technical support representative.</p>
ADAX9G	{dbid} Caution: NUCID {nucid} ({jobname}) on system {sysn} was canceled; Failure notification still outstanding
Explanation	<p>The nucleus identified in the message by its nucleus ID (<i>nucid</i>), job name (<i>jobname</i>) and system name (<i>sysn</i>) was canceled, but the nucleus printing this message did not receive (within the time period set by the MXCANCELWARN parameter) the failure notifications reported in ADAX60 messages confirming that the canceled nucleus was terminated. As long as the canceled nucleus might still be active, the Adabas cluster cannot recover from the failure.</p> <p>This message might also occur if the cited nucleus has not been canceled but is failing for another reason and is slow to terminate.</p>

	<p>If the peer nucleus does not terminate within the time period set by the MXCANCEL parameter, this nucleus may ask for permission to terminate itself (if the MXWTOR parameter was set) or terminate itself without asking (if the MXWTOR parameter was not set).</p>
Action	<p>Use the provided information (nucleus ID, job name, and system name) to make sure that the canceled peer nucleus gets sufficient resources (CPU, storage, priority) for terminating.</p>
ADAX9H	<p>{dbid} Error: Canceled NUCID {nucid} ({jobname}) on system {sysn} has not terminated; unable to perform cluster recovery</p>
Explanation	<p>The nucleus identified in the message by its nucleus ID (<i>nucid</i>), job name (<i>jobname</i>) and system name (<i>sysn</i>) was canceled, but the nucleus printing this message did not receive (within the time period set by the MXCANCEL parameter) the failure notifications confirming that the canceled nucleus has terminated. As long as the canceled nucleus might still be active, the Adabas cluster cannot recover from the failure.</p> <p>This message might also occur if the cited nucleus was not canceled but failed for another reason and has not terminated.</p> <p>The nucleus printing this message terminates itself with message ADAX99 and user abend 79.</p>
Action	<p>Check the status of the cluster nucleus cited in the message. Investigate why it did not terminate after being canceled or why the nucleus that printed this message did not receive the corresponding failure notifications (reported in ADAX60 messages).</p> <p>Consider using the MXWTOR parameter to request that a cluster nucleus ask for permission before terminating itself after failing to cancel an unresponsive peer nucleus.</p> <p>Ensure that all cluster nuclei run with high enough priority to get sufficient resources for participating in cluster-wide business.</p> <p>If the problem persists, contact your Software AG technical support representative</p>
ADAX9J	<p>{dbid} Error: Canceled NUCID {nucid} ({jobname}) on system {sysn} has not ended yet. Ensure that this nucleus ends to allow Adabas cluster recovery. Will terminate at {hh:mm:ss} (after {nnn} seconds). Reply 'W'ait, 'T'erminate, or 'R'eshow message</p>
Explanation	<p>This message requests an operator response. The nucleus identified in the message by its nucleus ID (<i>nucid</i>), job name (<i>jobname</i>) and system name (<i>sysn</i>) was canceled, but the nucleus printing this message did not receive (within the time period set by the MXCANCEL parameter) the failure notifications reported in the ADAX60 messages confirming that the canceled nucleus has terminated. As long as the canceled nucleus might still be active, the Adabas cluster cannot recover from the failure.</p> <p>This message might also occur if the cited nucleus was not canceled but failed for another reason and has not yet terminated.</p>

The nucleus will wait for the time period set by the MXWTOR ADARUN parameter for either the failure notifications of the canceled peer nucleus or a response from the operator. If the nucleus receives the expected failure notifications of the canceled peer nucleus, it retracts the ADAX9J message and starts an online recovery process to recover from the failure.

Action Check the status of the other cluster nucleus cited in the message. If it terminates, this ADAX9J message will be retracted.

Respond to this message using one of the following responses:

Response	Causes the nucleus to:
R	Print the whole ADAX9J message again and continue to wait for resolution of this issue, but without setting a new time period.
T	Terminate itself with message ADAX99 and user abend 79.
W	Wait for another time period of length MXWTOR for resolution of this issue.

If you do not respond and the failure notifications of the canceled peer nucleus do not arrive by the MXCANCEL time, the nucleus terminates itself with messages ADAX9H and ADAX99 and user abend 79.

ADAX9K {dbid} Clear: Received failure notifications from NUCID {nucid}

Explanation The peer nucleus identified in the message (*nuc id*) that was slow to terminate after being canceled has finally ended. This message retracts the warning of previous ADAX9G or ADAX9J messages about outstanding failure notifications. The nucleus is no longer in danger of terminating itself (for this particular incident).

Action No action is required for this informational message.

ADAX9L {dbid} All operator queries retracted

Explanation After the operator was asked in a previous ADAX9J message to check the status of a peer nucleus that had been canceled but did not terminate, the peer nucleus has now ended. The nucleus printing this message has retracted all outstanding ADAX9J operator queries.

Action No action is required for this informational message.

ADAX9M {dbid} SMF CSHP section disabled, unable to get storage

Explanation Storage was unavailable for SMF.

Action Provide more storage and restart the nucleus.

ADAX9N	{dbid} SMF unable to get storage SMF CSHG, CSHB, CSHF, LOCK, MSGB, MSGC, MSGH sections disabled
Explanation	Storage was unavailable for SMF.
Action	Provide more storage and restart the nucleus.
ADAX9P	{dbid} Session autorestart pending waiting for peer nucleus to perform online recovery
Explanation	<p>A starting nucleus that is about to join an active cluster has found that its Work data set is not empty (i.e., contains protection data required for recovering from a preceding failure). It will wait until the already active nuclei in the cluster have completed the online recovery process triggered by the preceding failure.</p> <p>Once this has happened, the nucleus will print message ADAX9Q and continue with the session start. If no session autorestart is in progress, the nucleus will terminate with parm-error 42, because its Work data set should be empty.</p>
Action	No action is required for this informational message.
ADAX9Q	{dbid} Session autorestart finished
Explanation	The starting cluster nucleus that printed message ADAX9P has now determined that the session autorestart performed by the active cluster has completed and that its Work data set is now empty (i.e., contains no relevant protection data anymore). It will continue with the session start.
Action	No action is required for this informational message.

39

ADAZ* - ADAZIP System Messages

Adabas for zIIP provides the following messages generated by module ADAZIP. They appear only in the JESLOG listing of the Adabas nucleus, the SYSLOG, and the operator console; they do not appear in the DDPRINT output of the nucleus.

ADAZ01	{dbid} ADAZIP initialization complete
Explanation	The zIIP-related services of Adabas have been successfully initialized.
Action	No action is required for this informational message.
ADAZ02	{dbid} ADAZIP termination complete
Explanation	The zIIP-related services of Adabas have been successfully terminated.
Action	No action is required for this informational message.
ADAZ07	Unable to obtain ADAZIP WorkArea Storage
Explanation	Insufficient memory was available for the zIIP-related services of Adabas. The nucleus will abort its session start with PARM-ERROR 129, "zIIP initialization failed". A utility will terminate with error-082, "Error occurred invoking the ADAZIP initialization".
Action	Increase the amount of memory available for Adabas (region size) or decrease the amount of memory that Adabas allocates for other purposes (one of the parameters associated with memory pools, e.g., LBP, LFIOP, LWP, NU, etc.).

ADAZ08	{dbid} {serv-name} Ret/Rsn {ret-code/rsn-code}
Explanation	<p>An invocation of z/OS service <i>serv-name</i> incurred return code <i>ret-code</i> with reason code <i>rsn-code</i>. The z/OS services used by ADAZIP and their possible return codes and reason codes are described in the following IBM manuals:</p> <ul style="list-style-type: none"> ■ <i>MVS Programming: Authorized Assembler Services Reference, Volumes 1-4</i> ■ <i>MVS Programming: Workload Management Services</i> <p>For z/OS service errors that occur during initialization or termination, ADAZIP returns to its caller with an error indicator. For z/OS service errors that occur during normal processing, ADAZIP terminates abnormally with user abend code 109.</p>
Action	<p>If this message indicates an error that cannot be resolved by other means, save the JES log, DDPRINT output and any dump of the Adabas nucleus or utility and contact your Software AG technical support for assistance.</p>
ADAZ09	<p>{dbid} ABEND in SRB Mode {dbid} ABEND S{sss} U{uuuu} Reason {rsn-code} {dbid} {xxxxxxxx_xxxxxxx} {yyyyyyyyy_yyyyyyy} (PSW, EC Info) {dbid} {xxxxxxxx_xxxxxxx} {yyyyyyyyy_yyyyyyy} (R0-R1) {dbid} ... {dbid} {xxxxxxxx_xxxxxxx} {yyyyyyyyy_yyyyyyy} (R14-R15) {dbid} {xxxxxxxx} {yyyyyyyyy} {zzzzzzzz} {vvvvvvvv} (AR0-AR3) {dbid} ... {dbid} {xxxxxxxx} {yyyyyyyyy} {zzzzzzzz} {vvvvvvvv} (AR12-AR15)</p>
Explanation	<p>The nucleus ended abnormally while executing in SRB mode. This is the result of an error condition detected either by Adabas (user abend code <i>uuuu</i>, in decimal notation) or by z/OS (system abend code <i>sss</i>, in hexadecimal notation). The message shows the program status word (PSW), extended control (EC) information, 8 byte general registers, and 4 byte access registers as of the time of the abnormal end.</p> <p>In the case of a user abend 109, reason code 10 ('ABEND S000 U0109 Reason 0000000A'), the SRB was canceled by the error exit (ESTAE) of the TCB, which was invoked for a preceding error. The information in the ADAM99 message printed by the TCB will be more pertinent for the analysis of the error.</p>
Action	<p>Refer to your Adabas documentation for a description of a nucleus user abend, or to the appropriate z/OS documentation for a description of the system abend. If this message indicates an error that cannot be resolved by other means, save the JES log, DDPRINT output and dump of the Adabas nucleus and call your Software AG technical support representative for assistance.</p>

ADAZ99	Invalid PSW key - Notify Support
Explanation	Unexpected PSW key 0 was encountered. An SDUMP is created. The incorrect PSW key was reset to the nucleus initialization key.
Action	Notify your Software AG technical support representative. Forward the SDUMP created just before the message appeared.

40

AFP* - Adabas Fastpath Messages

AFP-0000-FF	NO TEXT
Explanation	This message is either <ul style="list-style-type: none">■ an unexpected error; or■ an error created intentionally by zap.
Action	Report an unexpected error to Software AG.
AFP-0001-24	ABEND PSW psw
Explanation	Indicates an abnormal termination of the asynchronous buffer manager (ABM). The PSW is displayed at the point the ABM abended.
AFP-0002-24	ABEND: NO PSW/REGS AVAILABLE
Explanation	Indicates an abnormal termination of the asynchronous buffer manager (ABM). The PSW and registers were <i>not</i> available.
AFP-0003-24	ABEND REGS - 4-GP-registers
Explanation	Normally follows message 0001 and is repeated 4 times. Each time it is repeated, a different set of 4 GP registers is displayed.
AFP-0004-xx	NEW BUFFER address, length, date, time
Explanation	A new buffer has been initialized. The address and length of the buffer is shown along with the starting date and time (in internal format, described below). Internal date format: Characters 1&2 indicate the century (for example, "01" = 21st century)

Characters 3&4 indicate the year (for example, "14" combined with century = 2014)

Characters 5-8 indicate the day of the year (for example, "210F" = 210th day of year)

Internal time format:

By way of an example, "1301501F" = 13:01:50.1

Note: For this message only, the severity code shown (xx) is overwritten with the message level buffer parameter. See the Buffer Parameters for an explanation of this parameter.

Action None, this message is for information only.

AFP-0005-04 INITIALIZATION FAILED

Explanation This is a warning that the buffer could not be initialized. It is preceded by a message showing the reason for failure.

AFP-0006-20 AUTHORIZATION FAILURE

Explanation The operating system would not permit Adabas Fastpath to perform certain commands; for example, GETMAIN.

Action Ensure that all AFPxxx and link modules are in an authorized library.

AFP-0007-10 RSP 148, RETRY: rsp, svc, dbid, fnr

Explanation The Adabas Fastpath configuration file is not active. Adabas Fastpath will retry periodically. The Adabas response code and the configuration file SVC, DBID, and FNR are shown in hexadecimal.

Action Check the status of the configuration file.

AFP-0008-20 SYSDFILE RESPONSE: rsp, svc, dbid, fnr

Explanation An invalid Adabas response code was encountered while trying to access the Adabas Fastpath configuration file. The response code and configuration file SVC, DBID, and FNR are shown, in hexadecimal.

Action Check the status of the configuration file.

AFP-0009-20 NO SYSDFILE PARAMETERS: buffer-name

Explanation Global or member buffer parameters could not be found on the Adabas Fastpath configuration file for the buffer name shown.

Action Check the status of the configuration file.

AFP-0010-20	NO SYSFILE PARAMETERS: connected-buffer-name
Explanation	Connected buffer parameters could not be found on the Adabas Fastpath configuration file for the buffer name shown.
Action	Check the status of the configuration file.
AFP-0011-20	INVALID PARAMETERS: buffer-name
Explanation	The parameters for the buffer name shown would require more memory than requested in the size parameter. Buffer initialization is terminated.
Action	Check the parameter values and adjust as necessary.
AFP-0012-20	TRAP FAILURE: buffer-name
Explanation	The asynchronous buffer manager (AFPABM) must be able to intercept any abnormal ABENDs to preserve operational integrity. Initialization failed for the buffer named while attempting to set the operating system ABEND trap.
AFP-0013-10	ALREADY ACTIVE: buffer-name
Explanation	An attempt was made to start the buffer named, which is already active.
AFP-0014-20	GETMAIN FAILED: buffer-name
Explanation	The operating system GETMAIN operation failed while initializing the named buffer.
AFP-0015-20	SEGMENTATION FAILURE: buffer-name
Explanation	A failure occurred during the preformatting stage of initialization for the named buffer.
AFP-0016-20	FILE PARAMETER ERROR: buffer-name
Explanation	An error occurred during file parameter initialization of the named buffer.
AFP-0017-20	PARAMETER(S) OVERRIDDEN: buffer-name
Explanation	The buffer parameter record on the Adabas Fastpath configuration file was updated sometime between the start and end of initialization for the buffer named.

AFP-0018-20	BUFFER SIGNON FAILURE: <i>buffer-name</i>
Explanation	Logon to the ID table failed. Possible reasons are as follows: <ul style="list-style-type: none">■ the SVC specified in the named buffer parameters could not provide Adabas communication; or■ the database number defined for the buffer was already in use by a database or another buffer.
AFP-0019-08	OPERATOR ENTERED: <i>command</i>
Explanation	The specified command is valid and recognized by the asynchronous buffer manager.
AFP-0020-14	INVALID OPERATOR COMMAND: <i>command</i>
Explanation	The specified command is not recognized as a valid command.
AFP-0021-14	COMMAND REJECTED: <i>command</i>
Explanation	The specified command is valid but processing is rejected.
AFP-0022-FF	STAT, SNAP, STOP, RESTART, NEWCOPY, HELP
Explanation	Response to the HELP command.
AFP-0023-08	SHUTDOWN ACTIVATED
Explanation	The buffer is in the process of terminating. During this process, all tasks within the Adabas Fastpath buffer are allowed to complete normally and no new tasks are started.
AFP-0024-20	NO CONNECTION TO BUFFER: <i>buffer-name</i>
Explanation	Initialization for the specified buffer could not be completed because it was not possible to obtain a buffer session area for the asynchronous buffer manager.
AFP-0025-16	SAMPLER MISSING: AFPLOOK-<i>module-name</i>
Explanation	An attempt to load the specified AFPLOOK module failed.

AFP-0028-04	NEWCOPY REQUEST
Explanation	The database component accepted a Newcopy request.
AFP-0029-04	DISCONNECT FAILURE
Explanation	The database component could not successfully disconnect.
AFP-0030-04	NO RECOVERY ACTION NEEDED
Explanation	The buffer ended abnormally but no specific action was necessary to provide an orderly shutdown.
AFP-0031-18	POSSIBLE ORPHAN: address-of-memory
Explanation	An attempt to free memory after an abnormal termination failed. The attempted address is shown and should be the same as that portrayed in message 0004.
AFP-0032-18	NOT FREED: address-of-memory
Explanation	An abnormal termination occurred. The memory address shown appears to be invalid and should be the same as that portrayed in message 0004.
AFP-0033-18	SIGNOFF FAILURE: address-of-memory
Explanation	An abnormal termination occurred while attempting to log off from the Adabas ID table.
AFP-0034-08	SNAP COMPLETED
Explanation	The snap dump of the Adabas Fastpath buffer has completed successfully. This message is issued in response to a request to snap the contents of the buffer.
AFP-0035-10	SNAP FAILED
Explanation	The snap dump of the Adabas Fastpath buffer failed.
AFP-0036-14	BUSY - PLEASE RETRY
Explanation	Adabas Fastpath processes only one operator command at a time and one is already being processed.
Action	Resubmit the failed command.

AFP-0037-18	JOB ACTIVE: job-name-and-number
Explanation	AFPABM is attempting to stop but cannot do so until all jobs have released all Adabas Fastpath resources. The job named has not yet released resources and disconnected from the Adabas Fastpath buffer.
AFP-0038-08	STATISTICS UNAVAILABLE
Explanation	The database component disconnected successfully but could not log the final statistics.
AFP-0039-10	LOG EVENT ERROR: ADABAS-cmd-code-and-rsp-code
Explanation	An invalid Adabas response code was encountered while attempting to write a statistics log to the Adabas Fastpath configuration file. The Adabas command code and response code are shown in hexadecimal.
AFP-0040-04	JOB REPORT: job-name, commands
Explanation	If the job parameter <code>Job End Stats</code> is set to <code>Y</code> , AFPABM shows the above message when the named job completes. The message shows the job name and the total number of commands for the job seen by Adabas Fastpath. Messages 0041 and 0042 should follow.
AFP-0041-04	DIRECT ACCESS: attempts, saved, RCs
Explanation	This message follows either message 0040 or 0051. It shows the Adabas Fastpath direct access optimization attempts, the number of commands saved, and the number of associated RC commands saved.
AFP-0042-04	SEQUENCE: attempts, saved, over-reads
Explanation	This message follows either message 0040 or 0051. It shows the Adabas Fastpath read-ahead optimization attempts, the number of commands saved, and the number of commands that were not needed (over-reads).
AFP-0043-08	STOP REQUESTED BY: userid
Explanation	A buffer <code>STOP</code> request was issued from SYSAFP by the user shown.
AFP-0044-08	RESTART REQUESTED BY: userid
Explanation	A buffer <code>RESTART</code> request was issued from SYSAFP by the user shown.

AFP-0045-08	LOG REQUESTED BY: userid
Explanation	A LOG request was issued from SYSAFP by the user shown.
AFP-0046-08	NEWCOPY REQUESTED BY: userid
Explanation	A NEWCOPY request was issued from SYSAFP by the user shown.
AFP-0047-08	SNAP REQUESTED BY: userid
Explanation	A STOP request was issued from SYSAFP by the user shown.
AFP-0048-18	OPERATOR CANCEL: FORCED SHUTDOWN
Explanation	The buffer is being shut down due to an operating system cancel.
AFP-0049-08	SCHEDULED FILE STOP time fnr / dbid
Explanation	The file is subject to optimization by time period and a stop time period has been reached. The scheduled stop time plus the file and database number are also shown.
AFP-0050-08	SCHEDULED FILE START time fnr / dbid
Explanation	The file is subject to optimization by time period and a new start time period has been reached. The scheduled start time plus the file and database number are also shown.
AFP-0051-04	BUFFER STATISTICS name, total-commands
Explanation	This message is issued automatically at normal buffer end or when the operator command STAT is issued. It shows the buffer name and the total number of commands seen by Adabas Fastpath. It is followed by messages 0041 and 0042.
AFP-0052-04	NEWCOPY LOADED
Explanation	The database component successfully reloaded the Adabas Fastpath nucleus.
AFP-0053-20	UNABLE TO LOAD FASTPATH MODULE: module-name
Explanation	AFPABM was unable to load the module named in the message.
Action	Check that the Adabas Fastpath library is defined to the buffer start task and that it contains the module named.

AFP-0054-20	ERROR IN LOADED FASTPATH MODULE: module-name
Explanation	AFPABM loaded the module named in the message but then found an error in it.
Action	Check that the version of Adabas Fastpath matches for AFPABM and the module named.
AFP-0059-04	JOB REPORT: Job Number
Explanation	If the job parameter <code>Job End Stats</code> is set to Y, Fastpath displays this message when the job completes. The message shows the job name and job number of the ending job (step).
AFP-0060-04	THE DATE IS: date
Explanation	This message is issued by the Adabas Fastpath buffer manager at startup and also at midnight.
AFP-0061-20	COR GROUP NAME MISMATCH
Explanation	The Adabas System Coordinator group name defined for the AFPABM does not match the group name defined for the host SYSCO daemon.
Action	Correct the group names in the defined parameters.
AFP-0063-04	UNABLE TO SAVE JOB END STATISTICS -
Explanation	The job history record could not be updated with the statistics from the named job as it finished.
Action	Check the status of the configuration file.
AFP-0065-20	DATASPACE ALLOCATION FAILURE: dataspace-name,return-code
Explanation	The allocation of the named dataspace failed during buffer initialization.
Action	Correct the dataspace name in the defined parameters.
AFP-0066-10	File DA-termination triggered for DB xxxxx Nuc yyyy
Explanation	Adabas Fastpath in the database has been unable to distribute an update. The process to terminate Direct Access optimization for at least one file has been triggered. As a result of this, one or more files, with an Update Sensitivity file parameter of 'D', may appear with a status of "DA terminated" in Adabas Fastpath online services displays.
Action	Perform the following to re-instate Direct Access optimization for the file(s) in question: <ul style="list-style-type: none">■ Ensure all Adabas System Coordinator daemons within the COR group are active.

- Schedule a stop and restart of the database/database instance identified in this message.
- Schedule an AFP RESTART of the local Adabas Fastpath buffer (this will automatically be propagated to all Adabas Fastpath buffers within the COR group).

AFP-0067-10

Connection error: product switched off for job {job-name}

Explanation

A multi-TCB job was unable to lock the resources required to attempt connection to the Fastpath Buffer.

Action

Restart the job.

AFP-0068-10

Connection for job {job-name} stalled

Explanation

A multi-TCB job was unable to lock the resources required to attempt re-connection to the Fastpath Buffer. The message will be repeated at irregular intervals every 5 to 10 minutes until either the job successfully connects or is restarted.

Action

Restart the job.

41 APSPSX* - ADAECS or ADATCP Messages

The informational messages beginning with APSPSX are ADAECS (Conversion Services) or ADATCP (TCP/IP interface) messages from the ISE/POSIX subsystem that occur when running the nucleus. The same messages appear with ADACMP and other programs that call the modules ADAECS or ADATCP.

APSPSX0008	{ADAECS ADATCP} ISE/POSIX V{vrs} system initialized nucleus size {bytes}K bytes
Explanation	The ISE/POSIX subsystem has been successfully initialized.
Action	No action necessary for this informational message.
APSPSX0012	{ADAECS ADATCP} ISE/POSIX {CDI PH FILE V{vrs}} system terminated
Explanation	The ISE/POSIX subsystem server has terminated.
Action	No action necessary for this informational message.
APSPSX0015	{ADAECS ADATCP} ISE/POSIX V{vrs} initialization in progress
Explanation	The ISE/POSIX subsystem server has started its initialization processing.
Action	No action necessary for this informational message.
APSPSX0027	{ADAECS ADATCP} initializing with configuration 'PAANCONF'
Explanation	Indicates the ISE/POSIX subsystem configuration module is being used.
Action	No action necessary for this informational message.

APSPSX0036	{ADAECS ADATCP} global environment variables processed successfully
Explanation	The global environment variable file of the ISE/POSIX subsystem was processed successfully and the global environment variables specified in the file were successfully defined.
Action	No action necessary for this informational message.
APSPSX0049	Required configuration parameter {parameter} missing or invalid
Explanation	During the initialization of a CDI protocol driver, a required configuration parameter was missing or invalid. This initialization cannot proceed.
Action	Add or correct the specified parameter and restart the nucleus. See the Adabas Installation documentation for more information.
APSPSX0050	{ADAECS ADATCP} ISE/POSIX CDI {file} protocol initialized
Explanation	The ISE/POSIX subsystem CDI protocol driver implementing the <i>file</i> protocol was successfully initialized.
Action	No action necessary for this informational message.

42

AREV* - Adabas Review Hub Messages

AREV01	{hub-id} ADAREV HUB Vv.r.s COMING UP
Explanation	The Adabas Review hub session initialization is in progress.
Action	None required. This message is for your information only.
AREV02	{hub-id} ADAREV HUB IS A C T I V E
Explanation	The Adabas Review hub system has successfully initialized.
Action	None required. This message is for your information only.
AREV03	{hub-id} ADAREV HUB IS C L O S E D
Explanation	The Adabas Review hub system has completed its session close processing.
Action	None required. This message is for your information only.
AREV04	{hub-id} OPERCOM: {command}
Explanation	The Adabas Review hub repeats the operator command before continuing.
Action	None required. This message is for your information only.
AREV05	{hub-id} OPERCOM COMPLETED
Explanation	The issued command was processed by the Adabas Review hub.
Action	None required. This message is for your information only.

AREV06 **{hub-id} NO REQUESTS ARE PRESENTLY QUEUED**
{hub-id nnn} REQUESTS ARE PRESENTLY QUEUED

Explanation This message is displayed in response to the DNC operator command. *nnn* indicates the number of command queue elements queued for processing by the Adabas Review hub.

This message is also displayed in response to a DCQ operator command in the event that there are no command queue elements waiting to be processed.

Action None required. This message is for your information only.

AREV07 **{hub-id nnn} NEXT EXPECTED SEQUENCE NUMBER**
{hub-id cqe-seq-num cqe-job-name cqe-user-id (xxx) cmd ffss}

Explanation This message is displayed in response to the DCQ operator command. The first message displays the expected sequence number *nnn* that shows which numbered command queue element is in line to be processed next. The following information is displayed for each command queue element:

<i>cqe-seq-num</i>	sequence number of the command queue element.
<i>cqe-job-name</i>	job name of the Adabas being monitored.
<i>cqe-user-id (xxx)</i>	user ID of the Adabas being monitored followed by the value in displayable character hex.
<i>cmd</i>	Adabas command used for this request.
<i>ff</i>	CQE status flags in hexadecimal:
	x'20' waiting for 16-call
	x'10' 16-call required
	x'08' attached buffers
	x'04' attached buffers required
<i>ss</i>	more CQE status flags in hexadecimal:
	x'80' in process
	x'40' ready to be selected

Action None required. This message is for your information only.

AREV08 **{hubid} ENQUEUE ON HUB {hubid} SVC {svc} FAILED**

Explanation An Adabas Review hub is started with the hub ID and SVC listed in the message, but another hub with that hub ID and SVC is already running. The new Adabas Review hub comes down.

Action Determine why one Adabas Review hub was started while another hub with the same ID was already running.

AREV70	{hub-id} TOTAL CQE USED: {uuuuu} OF {ttttt}
Explanation	This message is displayed when the Adabas Review hub is terminated. <i>uuuuu</i> is the total number of CQEs used by the hub; <i>ttttt</i> is the total number of CQEs allocated by the hub.
Action	None required. This message is for your information only.
AREV80	{hub-id} REVIEW PARAMETER IS MISSING
Explanation	An attempt was made to start a hub database, but the hub ID has not been specified in the <code>REVIEW</code> parameter.
Action	Specify the hub ID on the <code>ADARUN REVIEW</code> parameter and restart the hub database.
AREV81	{hub-id} MPM-24 CALL FAILED
Explanation	The Adabas Review hub was unable to establish interregion communication. Adabas Review terminates processing.
Action	Identify and correct the error.
AREV82	{hub-id} MPM-00 CALL FAILED
Explanation	The Adabas Review hub was unable to establish interregion communication. Adabas Review terminates processing.
Action	Identify and correct the error.
AREV83	{hub-id} IDTE FOR THIS HUB IS NO LONGER ACTIVE
Explanation	The ID table element for the hub is no longer marked as being in use by this Adabas Review. It is probable that another target (Adabas, Adabas Review, etc.) was initialized using the same DBID / Adabas Review hub ID with the <code>FORCE=YES</code> parameter. Adabas Review terminates processing.
Action	If another target was inadvertently initialized, quiesce and terminate the target and restart Adabas Review. To prevent such problems, ensure that the <code>FORCE=YES</code> parameter is not used for target initialization unless absolutely necessary.
AREV84	{hub-id} USER GONE ON MPM-8 CALL
Explanation	The Adabas Review hub tried to process a request but the addressed data area was not addressable, or no longer contained recognizable data. This error occurred while Adabas Review was receiving the request (router-08 call processing). It is probable that the client nucleus was terminated while it was sending the request to Adabas Review.
Action	None required. Adabas Review cannot process this request so it is cleared from the queue.

AREV86	{hub-id} INTERREGION COMMUNICATION COULD NOT BE ESTABLISHED
Explanation	The Adabas Review hub was unable to establish interregion communication due to an unexpected response returned from ADAMPM. Adabas Review terminates processing.
Action	Check for system messages from ADAMPM that could identify the error. If the error cannot be identified, keep all dumps, messages, and other related information and contact your Software AG support representative.
AREV87	{hub-id} OPERATOR COMMUNICATIONS COULD NOT BE ENABLED
Explanation	The Adabas Review hub could not establish operator communications. Adabas Review terminates processing.
Action	Identify and correct the error.
AREV88	{hub-id} TIMER SERVICES COULD NOT BE INITIALIZED
Explanation	The Adabas Review hub was unable to establish STIMER services. Adabas Review terminates processing.
Action	Identify and correct the error.
AREV89	{hub-id} CORRUPTED CQE ARRIVED
Explanation	A command has arrived at the Adabas Review Hub, but when it was selected for processing it was not in an acceptable state. This indicates a logic error.
Action	Contact your Software AG technical support representative for assistance.
AREV90	{hub-id} GETMAIN FAILURE, SIZE= {requested-getmain-size}
Explanation	The Adabas Review hub was unable to obtain the necessary GETMAIN space to operate. Adabas Review terminates processing. It is probable that the specified region size is too small, or the default region size is too small. SIZE is the requested GETMAIN size that could not be obtained.
Action	Increase the region size for Adabas Review and restart.
AREV91	{hub-id} MISSING OR INCOMPATIBLE REVIEW COMPONENT
Explanation	The Adabas Review hub could not load the module REVHUB or the REVHUB module that was loaded is not the correct version or SM-level. Adabas Review terminates processing.
Action	Locate the correct REVHUB module, ensure that the module is accessible by Adabas Review, and restart Adabas Review.

AREV92	{hub-id} BREAK DETECTED IN SEQUENCE NUMBERS {hub-id} EXPECTED SEQUENCE NUMBER {xxxxx} {hub-id} RECEIVED SEQUENCE NUMBER {yyyyy}
Explanation	The Adabas Review hub processes the requests in the order that the numbered requests are received. This means that Adabas Review always knows the next number in sequence that should be received. If there is a discrepancy, this message is displayed along with the expected sequence number and the sequence number actually received. A skipped or missing sequence number can indicate that a request has been dropped by the router. Adabas Review continues processing.
Action	Lost requests may indicate that the hub is overloaded. Check the client nuclei for nonzero response codes received from the hub. In some cases, the number of commands (NC) parameter needs to be increased to accommodate the load from the client nuclei. Otherwise, divide up the Adabas Review monitoring work load on multiple hubs.
AREV93	{hub-id} ERROR IN REQUEST: {command}
Explanation	Either the specified operator command was invalid or incorrectly entered. Adabas Review ignores this operator command.
Action	Ensure that the command syntax is valid, and retry the command.
AREV94	{hub-id} REVIEW NUCLEUS SESSION OPEN FAILURE
Explanation	The Adabas Review nucleus returned a non-zero status during initialization.
Action	Check all messages displayed by the Adabas Review nucleus, correct any errors, and restart Adabas Review.
AREV95	{hub-id} INCOMPATIBLE ADAMPM MODULE, CONTACT SUPPORT CENTER
Explanation	The ADAMPM module is not compatible with this version/release of Adabas Review. It is probable that the wrong Adabas load library, SM-level, or version is being used. Adabas Review terminates processing. It is probable that the wrong Adabas load library is being used.
Action	Locate the correct ADAMPM module, ensure that the module is accessible by Adabas Review, and restart Adabas Review. If the problem persists even with the correct ADAMPM module, contact your Software AG technical support representative.
AREV99	{hub-id} ADAREV HUB ABNORMALLY TERMINATED
Explanation	The Adabas Review hub is terminating due to a previous error.
Action	Correct any errors and restart Adabas Review.

43

ARF* - Adabas Event Replicator Subsystem Messages

ARF00001	Default broker name was inserted
Explanation	No default webMethods EntireX stub name was supplied on the Global Values screen. The default stub name, BROKER, is inserted.
Action	No action is required for this informational message.
ARF00002	Broker Service must be provided
Explanation	No webMethods EntireX service was provided in a webMethods EntireX destination definition. One is required.
Action	Specify a valid webMethods EntireX service ID for this destination definition.
ARF00003	Cannot enter a GFB if a format buffer is in use
Explanation	During editing of an SFILE definition, an attempt was made to specify both a format buffer and a GFB definition name for the before image, after image, or key-related before image of the SFILE. You cannot specify a format buffer if you have already specified a GFB definition name; likewise, you cannot specify a GFB definition name if you have already specified a format buffer.
Action	Specify either a format buffer or a GFB definition name, but not both.
ARF00004	Cannot save in read-only mode
Explanation	An attempt was made to save a definition in the Event Replicator Server Parameter Subsystem, but the record being edited was in read-only mode. You cannot save a definition you have not explicitly edited.
Action	Edit the definition and try again.

ARF00006	Description must not be blank
Explanation	At least one destination must be specified for a subscription definition.
Action	Specify a destination definition to be associated with this subscription definition.
ARF00007	Do not select blank entries
Explanation	An attempt was made to select a blank line on the List of Destinations screen in the Adabas Event Replicator Subsystem
Action	Select a line that is not blank but that has a destination name listed.
ARF00008	Duplicate entry not allowed
Explanation	While defining an Adabas destination definition, an attempt was made to specify a database ID and file combination twice in either the Input DBID and Input File fields or in the Target DBID and Target File fields. This is not allowed.
Action	Specify unique database ID and file combinations on the Adabas Destination Definition screen.
ARF00009	Entire Broker ID must be provided
Explanation	An attempt was made to save a webMethods EntireX destination definition when no webMethods EntireX ID was supplied.
Action	Supply a valid webMethods EntireX ID.
ARF00010	Existing Destination Updated
Explanation	The existing definition was updated in the Event Replicator Server Parameter Subsystem.
Action	No action is required for this informational message.
ARF00011	Invalid name
Explanation	An invalid name was supplied.
Action	Correct the name in the field that the Adabas Event Replicator Subsystem identifies as invalid.
ARF00012	Invalid selection character
Explanation	An invalid character was specified in the SEL column.
Action	Refer to the help for the specific screen to determine what values can be specified for the field in question and then specify a valid value.

ARF00013	Invalid value
Explanation	An invalid value was supplied in one of the fields on the Event Replicator Server Parameter Subsystem screen.
Action	Correct the value in the field that the Adabas Event Replicator Subsystem identifies as invalid.
ARF00014	Invalid Architecture value (valid: 0-2)
Explanation	An invalid value was specified for the Architecture field on the screen. Valid values range from "0" through "2".
Action	Refer to the help for the specific screen to determine what values can be specified for the field in question and then specify a valid value.
ARF00015	Invalid MAXOUTPUT value (valid: 32768-2147483647)
Explanation	An invalid value was specified in the Max Output Size field on the Global Values screen.
Action	Refer to the help for the specific screen to determine what values can be specified for the field in question and then specify a valid value.
ARF00016	Invalid Subtasks value (valid: 0-15)
Explanation	An invalid value was specified for the Subtasks field on the Global Values screen.
Action	Refer to the help for the specific screen to determine what values can be specified for the field in question and then specify a valid value.
ARF00017	MQ Queue Name must be provided
Explanation	A WebSphere MQ queue name must be specified in the MQ Queue Name field when creating a WebSphere MQ IQUEUE definition.
Action	Specify a valid WebSphere MQ queue name in the MQ Queue Name field.
ARF00018	Name is required
Explanation	An attempt was made to save a definition when no name was specified. A name must be provided for the definition.
Action	Specify a valid name for the definition.

ARF00019	Name must be provided
Explanation	An attempt was made to save a definition when no name was specified. A name must be provided for the definition.
Action	Specify a valid name for the definition.
ARF00020	New destination info added
Explanation	The destination definition has been successfully added.
Action	No action is required for this informational message.
ARF00021	New destination saved
Explanation	The destination definition has been successfully saved.
Action	No action is required for this informational message.
ARF00022	New GFB added
Explanation	The GFB definition has been successfully added.
Action	No action is required for this informational message.
ARF00024	Queue Manager Name must be provided
Explanation	An attempt was made to save a WebSphere MQ destination definition but a WebSphere MQ queue manager name was not supplied.
Action	Supply a valid WebSphere MQ queue manager name.
ARF00025	Queue Name must be provided
Explanation	An attempt was made to save a WebSphere MQ destination definition but a WebSphere MQ queue name was not supplied.
Action	Supply a valid WebSphere MQ queue name.
ARF00026	Service Class must be provided
Explanation	An attempt was made to save a webMethods EntireX destination definition but a webMethods EntireX service class name was not supplied.
Action	Supply a valid webMethods EntireX service class name.

ARF00027	Service Name must be provided
Explanation	An attempt was made to save a webMethods EntireX destination definition but a webMethods EntireX service name was not supplied.
Action	Supply a valid webMethods EntireX service name.
ARF00028	Subscription not defined
Explanation	The subscription selected for an Adabas destination definition has not yet been defined.
Action	No action is required immediately. You can save the destination definition with the invalid subscription specification, but the destination definition is marked as "pending" in the Event Replicator Server. When you create the subscription later on, the destination definition is automatically updated and the "pending" status is removed.
ARF00029	Subscription saved/updated
Explanation	The subscription definition was successfully updated and saved.
Action	No action is required for this informational message.
ARF00030	Subscription Name is required
Explanation	An attempt was made to save an Adabas destination definition when no subscription name (even a name for an as-yet undefined subscription) has been specified. A subscription definition is required for an Adabas destination definition.
Action	Specify a subscription name for the Adabas destination definition. You can press PF6 on this screen to select a subscription name from a list of the currently defined subscription definitions. In addition, you can specify the name of a subscription that has not yet been defined. In this case, the destination definition is marked as "pending" in the Event Replicator Server. When you create the subscription later on, the destination definition is automatically updated and the "pending" status is removed.
ARF00031	Subscription name must not be blank
Explanation	An attempt was made to save a subscription definition when no subscription name was specified. A name is required for a subscription definition.
Action	Specify a valid subscription name.

ARF00032	There are currently no SFILES - Press PF4 to add
Explanation	There are no SFILE definitions currently defined in the Event Replicator Server.
Action	Press PF4 to access screens that allow you to add an SFILE definition.
ARF00033	Zero entry not allowed
Explanation	A zero was entered for a database ID or file number in an Adabas destination definition. Zero values are not allowed in database IDs or file numbers.
Action	Specify a valid database ID or file number.
ARF00034	PF{nn} not defined
Explanation	A function (PF) key was pressed that is not valid for the screen.
Action	Review the function keys listed at the bottom of the screen and select a valid one for that screen.
ARF00035	Cannot enter a format buffer if GFB is in use
Explanation	During editing of an SFILE definition, an attempt was made to specify both a format buffer and a GFB definition name for the before image, after image, or key-related before image of the SFILE. You cannot specify a format buffer if you have already specified a GFB definition name; likewise, you cannot specify a GFB definition name if you have already specified a format buffer.
Action	Specify either a format buffer or a GFB definition name, but not both.
ARF00036	GFB is not defined
Explanation	The GFB definition specified for an SFILE definition is not defined in the Event Replicator Server.
Action	Specify the name of a GFB definition that has been previously defined in the Event Replicator Server.
ARF00038	Duplicate destinations not allowed
Explanation	An attempt was made to assign the same destination definition to a subscription more than once. Every destination definition specified for a subscription definition must be unique.
Action	Specify a unique destination definition name.

ARF00041	Missing or invalid destination flags
Explanation	While assigning a destination definition to a subscription definition, no values were supplied for the N (normal replicated data) or the I (initial-state replicated data) flags.
Action	Specify values for the I and N fields on the screen. Refer to help for the screen to review the valid values.
ARF00043	Invalid DBID value
Explanation	An invalid database ID was specified in an SFILE definition.
Action	Specify a valid database ID.
ARF00044	Invalid FILE value
Explanation	An invalid file number was specified in an SFILE definition.
Action	Specify a valid file number.
ARF00045	Default info updated
Explanation	The default values specified on the Global Values screen of the Adabas Event Replicator Subsystem have been successfully updated and saved.
Action	No action is required for this informational message.
ARF00046	GFB not saved
Explanation	Changes were made to a GFB definition, but the GFB definition has not been saved.
Action	Save and replace the existing GFB definition or alter the GFB definition name and save it under the new name.
ARF00047	IQUEUE definition deleted
Explanation	The selected IQUEUE definition has been successfully deleted from the Event Replicator Server.
Action	No action is required for this informational message.
ARF00048	Subscription deleted
Explanation	The selected subscription definition has been successfully deleted from the Event Replicator Server.
Action	No action is required for this informational message.

ARF00049	IQUEUE definition updated
Explanation	The IQUEUE definition was successfully updated.
Action	No action is required for this informational message.
ARF00050	IQUEUE definition saved
Explanation	The IQUEUE definition was successfully saved.
Action	No action is required for this informational message.
ARF00051	Initial State definition deleted
Explanation	The initial-state definition was successfully deleted.
Action	No action is required for this informational message.
ARF00052	Initial-State definition saved
Explanation	The initial-state definition was successfully saved.
Action	No action is required for this informational message.
ARF00053	Initial-State definition updated
Explanation	The initial-state definition was successfully updated.
Action	No action is required for this informational message.
ARF00054	SFILE deleted
Explanation	The SFILE definition was successfully deleted.
Action	No action is required for this informational message.
ARF00055	Select A,I or enter selection criteria
Explanation	This informational message informs you to specify "A" or "I" in the I field on this screen or leave the I field blank and specify selection criteria instead.
Action	In the I field on the Initial-State Definition screen, specify "A" (no filter), "I" (filter by initial-state ISN specification), or a blank (filter by selection criteria). If you specify a blank, you must also specify some selection criteria in the Selection Criteria field on the screen.

ARF00056	"I" Field must be blank for selection criteria
Explanation	An attempt was made to specify a value for the I and Selection Criteria fields on the Initial-State Definition screen. If you want to specify selection criteria, the I field must be blank.
Action	Specify a valid value in the I field or specify selection criteria in the Selection Criteria field, but not both.
ARF00057	IDBID cannot be zero
Explanation	An attempt was made to save an initial-state definition for which no values for the IDBID field were specified.
Action	Specify at least one input database ID in the IDBID field for the initial-state definition.
ARF00058	IFile cannot be zero
Explanation	An attempt was made to save an initial-state definition for which no values for the IFile field were specified.
Action	Specify at least one input file number in the IFile field for the initial-state definition.
ARF00059	Object not copied - Already exists
Explanation	While attempting to copy an Event Replicator Server definition, a duplicate name was specified.
Action	Specify a new unique definition name when copying definitions.
ARF00060	Destination of another type and same name exists
Explanation	An attempt was made to define two destination definitions with the same name, but of different types. This is not allowed.
Action	Specify a unique name each time you add a destination name to the Event Replicator Server.
ARF00061	Input DBID must be 1-65535
Explanation	An invalid value was specified for the Input DBID field on the Adabas Destination Definition screen.
Action	Specify a valid database ID for the Input DBID field. Valid values range from "1" to "65535".

ARF00062 **Target DBID must be 1-65535**
Explanation An invalid value was specified for the **Target DBID** field on the Adabas Destination Definition screen.
Action Specify a valid database ID for the **Target DBID** field. Valid values range from "1" to "65535".

ARF00063 **Input DBID/FNR and target DBID/FNR cannot be the same**
Explanation In an Adabas destination definition, the database ID and file number combination specified for the **Input DBID** and **Input File** fields were the same as those specified for the **Target DBID** and **Target File** fields. The DBID/file combinations for the input fields must be different than those specified for the target fields.
Action Specify unique DBID/file combinations for the input and target fields of an Adabas destination definition.

ARF00064 **Destination does not exist**
Explanation In a subscription definition, the name of a destination that has not yet been defined was specified on the Destination List screen.
Action Specify the name of a previously defined destination definition for the subscription.

ARF00065 **MESSAGE {number} NOT FOUND**
Explanation No help could be found for the message number you specified.
Action Verify that you have specified the correct number. To get help for Adabas Event Replicator Subsystem messages, enter:

```
msg nn
```

at the Command prompt. Specify the two-digit message number (omit the leading zeros) for *nn*.

If you have specified a valid message number and the error persists, contact your Software AG technical support representative.

ARF00066 **Invalid message number**
Explanation The message value specified during a message help request was not in a format that the Adabas Event Replicator Subsystem recognized.
Action Request message help using a valid message number format. To get help for Adabas Event Replicator Subsystem messages, enter:

```
msg nn
```

at the Command prompt. Specify the two-digit message number (omit the leading zeros) for *nn*.

If you have specified a valid message number and the error persists, contact your Software AG technical support representative.

ARF00067	DBID/FNR is not a valid Replicator file
Explanation	The database ID and file number combination specified on the Set LFILE Parameters screen were not for an Event Replicator Server.
Action	Specify the database ID and file number combination of an Event Replicator Server.
ARF00068	Existing resend buffer updated
Explanation	The resend buffer definition was successfully updated.
Action	No action is required for this informational message.
ARF00069	Invalid buffer size (VALID: 32-2097151)
Explanation	An invalid buffer size was specified for a resend buffer definition.
Action	Specify a valid buffer size. Refer to help for this screen for a range of valid values.
ARF00070	Invalid buffer name
Explanation	The resend buffer definition name specified in the subscription definition is for a resend buffer definition that has not yet been defined.
Action	Specify the name of a previously defined resend buffer definition.
ARF00071	Resend buffer definition does not exist
Explanation	The resend buffer definition specified for the subscription definition has never been defined.
Action	Specify the name of a previously defined resend buffer definition.
ARF00072	Subscription no longer available
Explanation	The subscription definition was deleted somehow (probably by somebody else) while you were working on it.
Action	Try saving it again.

ARF00073	Subscription already exists, cannot save
Explanation	An attempt was made to create a new subscription definition with the same name as an existing subscription definition.
Action	Specify a unique name for each subscription definition you define.
ARF00074	New resend buffer saved
Explanation	The resend buffer definition has been successfully saved.
Action	No action is required for this informational message.
ARF00075	GFB replaced
Explanation	The GFB definition was successfully altered and saved.
Action	No action is required for this informational message.
ARF00076	Invalid Message Limit value (valid: 3-2147483647)
Explanation	An invalid value was specified for the Input Request Message Limit field of the Global Values screen.
Action	Refer to help for this screen to review the valid values for this field. Then specify a valid value.
ARF00077	GFB is used by subscription {name} -- Not deleted
Explanation	An attempt was made to delete a GFB definition that is used by a subscription definition. The deletion attempt fails.
Action	No action is required. However, if you really need to delete the GFB definition, edit the subscription definition, specify a different GFB definition for the subscription, save the subscription definition, and try the delete attempt again.
ARF00078	Subscription name cannot be changed
Explanation	An attempt was made to change the name of an existing subscription definition on the Subscription Definition screen. Once defined, the name of a subscription definition cannot be changed.
Action	This limitation is designed to protect you from accidental replication problems. To get around this limitation, copy the subscription definition to a new name and delete the original subscription (with the original name) on the Available Subscriptions screen.

ARF00079	Invalid num of concurrent requests - (valid 1-2147483647)
Explanation	An invalid value was specified for the Num of Concurrent Initial State Requests field on the Initial-State Definition screen.
Action	Refer to the help for this screen for a description of the valid values for this field. Then specify a valid value.
ARF00080	Invalid Message Interval value - (valid 1-2147483647)
Explanation	An invalid value was specified for the Input Request Message Interval field on the Global Values screen.
Action	Refer to the help for this screen for a description of the valid values for this field. Then specify a valid value.
ARF00083	Subscription not deleted --- Used by Initial State {name}
Explanation	A request to delete a subscription was canceled because an initial-state definition makes reference to it. The name of the initial-state definition is given in the message.
Action	Delete the initial-state definition prior to deleting the subscription.
ARF00084	Subscription not deleted --- Used by Destination {name}
Explanation	A request to delete a subscription was canceled because a destination definition makes reference to it. The name of the destination definition is given in the message.
Action	Delete the destination definition prior to deleting the subscription.
ARF00085	Destination not deleted --- Used by subscription {name}
Explanation	A request to delete a destination was canceled because a subscription definition makes reference to it. The name of the subscription definition is given in the message.
Action	Delete the subscription definition prior to deleting the destination.
ARF00086	Destination not deleted --- Used by Initial State {name}
Explanation	A request to delete a destination was canceled because an initial-state definition makes reference to it. The name of the initial-state definition is given in the message.
Action	Delete the initial-state definition prior to deleting the destination.

ARF00087	GFB not deleted --- Used by subscription {name}
Explanation	A request to delete a GFB definition was canceled because a subscription definition makes reference to it. The name of the subscription definition is given in the message.
Action	Delete the GFB reference in the subscription definition prior to deleting the GFB definition.
ARF00088	LFILE allocation error
Explanation	An attempt was made to set the LFILE parameters using the Adabas Event Replicator Subsystem's Set LFILE Parameters screen, but the attempt failed.
Action	Enter Natural using the LFILE=(89, <i>nnnnn</i> , <i>nnnn</i>) session parameter where <i>nnnnn</i> , <i>nnnn</i> are the DBID and file number of the Replicator system file.
ARF00089	Natural error {eeee} occurred at line {nnnn} of program {pppppppp}
Explanation	A Natural error occurred. The Natural error number (<i>eeee</i>), the possible line number within the program (<i>nnnn</i>), and the program name (<i>pppppppp</i>) that encountered the error are given in the message.
Action	Read about the Natural error in the Natural documentation and follow the instructions described for that error.
ARF00090	Cannot save due to syntax errors
Explanation	The definition could not be saved because parameters in the definition were not specified correctly.
Action	Correct the parameters and try to save the definition again.
ARF00091	Filter not allowed if using UES conversion
Explanation	An attempt was made to supply a filter definition for a subscription that allows UES conversion. In other words, its architecture key (SARC parameter) is not "2" and a value other than "0" has been set for the user data alpha and wide settings (SACODE and SWCODE parameters). At this time, filters are only allowed on subscriptions that do not allow UES conversion. So the architecture key (SARC) must be set to "2" and the user data alpha and wide settings (SACODE and SWCODE) must be set to "0".
Action	Change the subscription definition. Either remove the filter definition specification or reset the UES field values.

ARF00092	Input FILE must be 1-5000
Explanation	An invalid value was specified for the Input File field on the Adabas Destination Definition screen. Valid values range from "1" through "5000".
Action	Specify a valid file number for the Input File field.
ARF00093	Target FILE must be 1-5000
Explanation	An invalid value was specified for the Target File field on the Adabas Destination Definition screen. Valid values range from "1" through "5000".
Action	Specify a valid file number for the Target File field.
ARF00101	A maximum of {n} entries can be selected
Explanation	More than <i>n</i> transaction filter definitions have been selected for the SFILE definition. The maximum that can be selected is listed in the message.
Action	Select the correct number of transaction filter definitions for the SFILE definition.
ARF00102	Transaction filter {name} does not exist
Explanation	This error may occur if there are concurrent updates on the same transaction filter definition. For example, if one user is modifying a definition at the same time as another user deletes it, this error occurs. The name of the transaction filter definition is given in the message.
Action	Try saving the transaction filter definition again.
ARF00103	Transaction filter name cannot be changed
Explanation	An attempt was made to change the name of an existing transaction filter definition on the Transaction Filter screen. Once defined, the name of a transaction filter definition cannot be changed.
Action	This limitation is designed to protect you from accidental replication problems. To get around this limitation, copy the transaction filter definition to a new name and delete the original transaction filter (with the original name) on the List of Transaction Filters screen.
ARF00104	No value allowed if target field empty
Explanation	If no target field is specified, no target PE, target MU, or target image can be specified.
Action	Specify a target field prior to specifying a target PE, MU, or image.

ARF00105	Invalid record for filter {name} in {linenumber}
Explanation	This error may occur if there are concurrent updates on the same transaction filter definition. For example, if one user is modifying a definition at the same time as another user deletes it, this error occurs.
Action	Try saving the transaction filter definition again.
ARF00106	Value length 0 or exceeds 254
Explanation	Either no values were specified in the target value list for the transaction filter definition or more than 254 characters were specified.
Action	Review the target value list for the transaction filter definition. If more than 254 characters were specified, change the list to specify fewer characters. If you intend to specify a blank for the target value list, make sure a blank character is coded between the quotation marks (' ').
ARF00107	Transaction filter saved/updated
Explanation	The transaction filter definition was successfully updated and saved.
Action	No action is required for this informational message.
ARF00108	Only one value allowed for condition
Explanation	More than one value was specified for an LT, LE, GT, or GE condition. Only one value is allowed for these conditions, although more than one value may be specified for the EQ and NE conditions.
Action	Specify only one value for the condition or change the type of condition.
ARF00109	Odd number of quotation marks
Explanation	A syntactical error exists in the transaction filter definition.
Action	Review the Event Replicator for Adabas documentation and the help provided with the Adabas Event Replicator Subsystem for the correct syntax of transaction filter definitions. Correct the syntactical error and try again.
ARF00110	Transaction filter deleted
Explanation	The selected transaction filter definition has been successfully deleted from the Event Replicator Server.
Action	No action is required for this informational message.

ARF00111	Transaction filter not deleted --- Used by subscription {name}
Explanation	A request to delete a transaction filter definition was canceled because a subscription definition makes reference to it. The name of the subscription definition is given in the message.
Action	Delete the transaction filter definition reference in the subscription definition prior to deleting the transaction filter definition.
ARF00112	Quotation marks in strings have to be doubled
Explanation	A syntactical error exists in the transaction filter definition.
Action	Review the Event Replicator for Adabas documentation and the help provided with the Adabas Event Replicator Subsystem for the correct syntax of transaction filter definitions. Correct the syntactical error and try again.
ARF00113	Invalid Adabas field name
Explanation	An invalid Adabas field name was specified. The field name must be two characters long with the first character alphabetic and the second character either alphabetic or numeric. No special characters are permitted.
Action	Correct the field name.
ARF00114	Possible condition values: EQ, NE, LT, LE, GT or GE
Explanation	An invalid condition value was specified. Valid values are listed in the message.
Action	Correct the condition value.
ARF00115	Transaction filter not saved
Explanation	Changes were made to a transaction filter definition, but the definition has not been saved.
Action	Save and replace the existing transaction filter definition or alter the definition name and save it under the new name.
ARF00116	New Transaction filter added
Explanation	The transaction filter definition has been successfully added.
Action	No action is required for this informational message.

ARF00117	Transaction filter replaced
Explanation	The transaction filter definition was successfully altered and saved.
Action	No action is required for this informational message.
ARF00118	Enter either a target field or a value
Explanation	Neither a target field or a target value list was specified. One of these is required for the transaction filter definition.
Action	Specify either a target field or a target value list for the transaction filter definition.
ARF00119	Number of conditions exceeds 2500 at line {number} of program {name}
Explanation	Over 2500 conditions were specified for the transaction filter definition. The maximum number of conditions you can specify for a transaction filter definition is 2500. The line number and program name are given in the message.
Action	Remove conditions from the transaction filter definition so that no more than 2500 are specified and try again.
ARF00120	Total value length exceeds 2000
Explanation	Over 2000 characters were specified in the target value list for the transaction filter definition. The maximum length of all target value lists is 2000 characters.
Action	Specify fewer values in the target value list and try again.
ARF00121	You must create the AI format buffer first
Explanation	While defining file-related parameters, an attempt was made to create a before image format buffer when an after image format buffer does not exist. The after image format buffer must be defined first.
Action	Provide an after image format buffer first.
ARF00122	AI and BI buffers must be identical
Explanation	While defining file-related parameters, if Include Identical Records is specified as "N", then the before image format buffer must be identical to the after image format buffer.
Action	Either remove the before image format buffer or make it identical to the after image format buffer.

ARF00123	No object found
Explanation	During unload processing, no object was found with the entity and name combination specified.
Action	Check the entity and name specifications and try again.
ARF00124	Cannot save with errors present
Explanation	A request to save an object failed because errors were found in the object.
Action	Correct the errors and try again.
ARF00125	AI GFB must be entered first
Explanation	An attempt was made to specify a before image global format buffer (GFB) definition, but the after image GFB definition must be defined first. This is only true if the value for the Include Identical Records field is specified as "N".
Action	Define the after image GFB first.
ARF00126	Transaction Filter is not defined
Explanation	A transaction filter name was specified but the transaction filter has not been defined.
Action	Define the transaction filter first or specify the name of a currently defined filter.
ARF00127	Cannot mix local and global format buffers
Explanation	An attempt was made to combine the use of local and global format buffers. This is not allowed if the value for the Include Identical Records field is specified as "N".
Action	Do not mix local and global format buffers.
ARF00128	BI format buffer must be deleted first
Explanation	An attempt was made to delete an after image format buffer when a before image format buffer still exists.
Action	Delete the before image format buffer first.
ARF00130	Maximum length of {parameter-name} is {nnn} characters
Explanation	The number of characters for the RPLOD or RPULD utility parameter named in the message has been exceeded. The maximum number of characters possible for the parameter is also listed in the message.
Action	Correct the parameter specification and try the load or unload function again. For complete information on the RPLOD and RPULD utility parameters, read <i>RPLOD and RPULD Utilities</i> in <i>Event Replicator for Adabas Reference Guide</i> .

ARF00131	Resend buffer definition deleted
Explanation	The resend buffer definition was successfully deleted.
Action	No action is required for this informational message.
ARF00132	Format buffer generated successfully
Explanation	The Predict function has been completed successfully.
Action	No action is required for this informational message.
ARF00133	Required Predict version: 4.4 SP1; installed: {vrsp}
Explanation	The version of Predict required to run the selected function is given in the message. The message also indicates which version of Predict is installed in the current environment: <i>vrsp</i> identifies the Predict version, release, SP level, and service pack number. If Predict is not installed in the current environment, a remark is shown for <i>vrsp</i> .
Action	Verify your environment and install the required version of Predict.
ARF00134	Global Format Buffer name must not be blank
Explanation	An attempt was made to save a global format buffer definition when no global format buffer name was specified. A name is required for a global format buffer definition.
Action	Specify a valid global format buffer name.
ARF00135	Format Buffer must be provided
Explanation	An attempt was made to save a global format buffer definition when no format buffer was supplied.
Action	Supply a format buffer and try again.
ARF00136	LFILE has not been set
Explanation	Errors occurred while attempting to save LFILE parameters on the Set LFILE Parameters screen.
Action	Supply a correct database ID and file number and try again.
ARF00137	LFILE has been set successfully
Explanation	This confirms that the LFILE settings were successfully saved or updated on the Set LFILE Parameters screen.
Action	No action is required for this informational message.

ARF00138	Replicator system file not found
Explanation	The Replicator system file specified on the Set LFILE Parameters screen cannot be found. Possible reasons are: <ul style="list-style-type: none">■ No file was loaded.■ The LFILE parameters are incorrect.
Action	Verify that a file is specified and that the LFILE settings are correct.
ARF00139	Replicator system file must be available to continue
Explanation	The Replicator system file specified on the Set LFILE Parameters screen is not available. The only function you can perform using the Adabas Event Replicator Subsystem is option "L" on the System Functions menu, which directs you to the Set LFILE Parameters screen, where you can fix the problem.
Action	Navigate to the Set LFILE Parameters screen and correct the LFILE settings. Otherwise, make the Replicator system file available and try again.
ARF00140	Field {field-name} (Adabas short name) already defined as primary key
Explanation	Only one field can be marked as the primary key. The message shows the already-defined primary key field.
Action	To define another field as the primary key, remove the existing primary key flag first.
ARF00141	Resulting format buffer is empty
Explanation	The generated format buffer does not contain any field.
Action	Check the Predict file name and the field definitions for this file in Predict.
ARF00142	Predict Generation Information unlinked
Explanation	The Predict Generation Information has been successfully unlinked (removed) from the GFB definition.
Action	No action is required for this informational message.
ARF00143	Replicator system file not available - RSP=148
Explanation	Adabas response code 148 (ADARSP148) was received while trying to communicate with the Event Replicator Server. The Natural LFILE setting points to a Replicator system file that is currently not available.
Action	Correct the LFILE setting or insure that the Replicator system file is available.

ARF00144	Database ID deleted
Explanation	The database ID entry was successfully deleted.
Action	No action is required for this informational message.
ARF00145	GFB deleted
Explanation	The GFB entry was successfully deleted.
Action	No action is required for this informational message.
ARF00146	Possible values are ...
Explanation	An invalid value was supplied in one of the fields on the Adabas Event Replicator Subsystem screen.
Action	Correct the value in the field that the Adabas Event Replicator Subsystem identifies as invalid.
ARF00147	Replay process initiated - Token={nnnnn}
Explanation	This confirms a replay operation was initiated and informs you of the token number associated with the replay process.
Action	No action is required for this informational message.
ARF00148	Insufficient space in the replication pool
Explanation	There is insufficient space in the Event Replicator Server replication pool. In other words, the value specified by LRPL has been exceeded.
Action	Increase the size of the LRPL parameter and try again.
ARF00149	Replay request for undefined database
Explanation	A replay request was issued for a database not defined to the Event Replicator Server.
Action	Correct the DBID in the replay request or define the database to the Event Replicator Server.
ARF00150	Invalid (undefined/outdated) replay token
Explanation	The replay token is invalid. Either it is not defined or it is outdated.
Action	Specify a valid replay token.

ARF00151	Requested replay in conflict with existing replay
Explanation	Replay processing for the same DBID and file number combination is already running.
Action	Request replay processing for a different DBID and file number.
ARF00152	DATE/TIME format or value incorrect
Explanation	The value specified for the date or time is not in the correct format or is an invalid value.
Action	Check the syntax of the specified date and time values. Do not specify future date and time values.
ARF00153	Incorrect replay parameters
Explanation	The specified replay parameters are incorrect.
Action	Check and correct the replay parameters and try again.
ARF00154	Replay destination without SLOG closed
Explanation	A replay destination that was defined without an SLOG was closed at the beginning of replay processing or while the replay was running.
Action	Reopen the closed destination and rerun the replay process for the destination.
ARF00155	Invalid replay status transition
Explanation	An invalid replay status transition occurred. Events that change the status of a replay process occurred in an unexpected order.
Action	Notify your Software AG technical support representative.
ARF00156	Response {nnn} Subcode {nnn} Received from replicator
Explanation	The response code and subcode listed in the message were received from the Event Replicator for Adabas.
Action	Review your Adabas documentation for the exact meaning of the listed response code and subcode. Take appropriate action, based on that description.
ARF00158	Subscription is required
Explanation	A subscription is required to submit a request to the Event Replicator Target Adapter.
Action	Supply a valid subscription definition name for the Event Replicator Target Adapter request and try again.

ARF00159	Initial-State name is required
Explanation	An initial-state definition must be specified for populate requests to the Event Replicator Target Adapter.
Action	Supply a valid initial-state definition name for the Event Replicator Target Adapter request and try again.
ARF00160	Initial-State definition not found
Explanation	The initial-state definition specified for the Event Replicator Target Adapter populate request cannot be found.
Action	Verify that the initial-state definition specified for the Event Replicator Target Adapter populate request is valid and spelled correctly. Then try again.
ARF00161	Initial-State subscription does not match screen
Explanation	The subscription specified in the Event Replicator Target Adapter populate request must match one of the subscriptions specified in the initial-state definition.
Action	Specify a subscription that is used by the initial-state definition. Then try again.
ARF00162	Initial-State DBID/FNR does not match screen
Explanation	The DBID and file number specified in the Event Replicator Target Adapter populate request do not match a DBID and file number combination specified in the initial-state definition.
Action	Specify a DBID and file number combination that is used by the initial-state definition. Then try again.
ARF00163	Subscription does not contain a valid AI GFB
Explanation	The subscription specified for the Event Replicator Target Adapter request does not include a valid after-image global format buffer. Any subscription used in an Event Replicator Target Adapter request must include a generated global format buffer and field table. Global format buffers and field tables can be generated by the Event Replicator for Adabas using appropriate Predict file definitions.
Action	Specify a subscription that includes a generated global format buffer and field table or add one to the subscription. Then try again.
ARF00164	Subscription not found
Explanation	The subscription definition specified for the Event Replicator Target Adapter request cannot be found.
Action	Verify that the subscription definition specified for the Event Replicator Target Adapter request is valid and spelled correctly. Then try again.

ARF00165	GFB not found
Explanation	The global format buffer (GFB) specified by the subscription used in the Event Replicator Target Adapter request cannot be found.
Action	Verify that the GFB definition name specified in the subscription is valid and spelled correctly. Then try again.
ARF00166	GFB does not contain field table
Explanation	The global format buffer (GFB) specified by the subscription used in the Event Replicator Target Adapter request does not include a field table. This means that the GFB definition was not generated. Only when the GFB is generated will the field table also be generated. Global format buffers and field tables can be generated by the Event Replicator for Adabas using appropriate Predict file definitions.
Action	Specify a subscription for that request that uses a generated GFB and field table or generate a GFB and field table for the subscription in the request.
ARF00167	Request successful
Explanation	The Event Replicator Target Adapter request was successfully submitted.
Action	No action is required for this informational message.
ARF00168	Response code {nnn} subcode {nnn} received from request
Explanation	The response code and subcode listed in the message were received from the Event Replicator Target Adapter request.
Action	Review your Adabas documentation for the exact meaning of the listed response code and subcode. Take appropriate action, based on that description.
ARF00169	A timeout occurred while running Synchronized Replay
Explanation	A timeout occurred while the Event Replicator Server was waiting for the end of a synchronization process after reactivating replication for a file in Adabas. The synchronization process ends when all transactions have finished that had updated the file before it was reactivated.
Action	Wait until the Event Replicator Server reports the activation of the file (ADAF2L message). Then run a new replay job.

ARF00171	There is insufficient space in the nucleus pool
Explanation	There is insufficient space in the nucleus replication pool. In other words, the value specified by LRPL has been exceeded.
Action	Increase the LRPL size of the nucleus and try again.
ARF00172	Subscription specified in a status request is undefined
Explanation	The subscription specified in a status request is undefined.
Action	Correct the subscription specified in the status request and try again.
ARF00173	The initial-state name specified was not found
Explanation	The specified initial-state name was not found.
Action	Correct the initial-state name or create an initial-state definition by that name. Then try again.
ARF00174	End date must be greater than start date
Explanation	The end date specified for the request must be later than the start date.
Action	Correct the dates and try again.
ARF00175	End time must be greater than start time
Explanation	The end time specified for the request must be later than the start time.
Action	Correct the times and try again.
ARF00178	Destination name not found
Explanation	One of the destinations requested for replay processing could not be found.
Action	Verify that the names of the destination definitions in the destination list are specified accurately. Then try again.
ARF00179	Subscription name not found
Explanation	One of the subscriptions requested for replay processing could not be found.
Action	Verify that the names of the subscription definitions in the subscription list are specified accurately. Then try again.

ARF00180	Destination is not active
Explanation	One of the destinations listed in the destination list for replay processing is not active.
Action	Either activate the destination definition or remove it from the list for replay processing. Then try again.
ARF00181	Subscription not active
Explanation	One of the subscriptions listed in the subscription list for replay processing is not active.
Action	Either activate the subscription definition or remove it from the list for replay processing. Then try again.
ARF00182	File is not active
Explanation	The file requested for replay processing is not active.
Action	Activate the file. Then try again.
ARF00183	No files for subscription
Explanation	No files were found for a subscription specified in the subscription list for replay processing.
Action	Check the subscriptions requested for replay processing and verify that they are complete and include SFILE definitions. Then try again.
ARF00185	Destination does not receive data
Explanation	One of the destinations specified in the destination list for a replay run does not receive replication data. No data can be replayed for this destination.
Action	Review the list of destinations specified for replay and alter it as necessary.
ARF00186	Subscription does not reference any destination
Explanation	A subscription definition in the subscription list for replay processing does not reference any destination definition. It is incomplete.
Action	Complete the subscription definition and try again.
ARF00187	Data from file does not flow to any destination
Explanation	A file specified for replay is not processed by any subscription, so replicated data from the file does not flow to any destination. Data for the file could not be found in the PLOG.
Action	Add the file to a subscription definition, let replication processing run for a while, and then try again.

ARF00188	No data flow for destination
Explanation	A destination definition requested for replay is not referenced by any subscription. No PLOG data exists for the destination.
Action	Add the destination to a subscription definition, let replication processing run for a while, and then try again.
ARF00189	Input queue with same name already exists
Explanation	An input queue definition with the same name already exists Each input queue definition name must be unique.
Action	Change the input queue definition name and try again.
ARF00190	PLOG records deleted
Explanation	A request to delete the selected PLOG information record and all prior PLOG information records has completed.
Action	No action is required for this informational message.
ARF00191	Duplicate destinations not allowed
Explanation	A replay request included duplicate destination names.
Action	Review the destinations you specified and remove the duplicates.
ARF00192	Duplicate subscriptions not allowed
Explanation	A replay request included duplicate subscription names.
Action	Review the subscriptions you specified and remove the duplicates.
ARF00193	Restart RPL Usage must be less than Maximum RPL Usage
Explanation	The value specified for the Restart RPL Usage global parameter setting is greater than the Maximum RPL Usage global parameter setting.
Action	Reduce the setting for the Restart RPL Usage global parameter or increase the value for the Maximum RPL Usage global parameter.
ARF00194	File-related info not deleted --- Used by Initial-State {is-def}
Explanation	A request to delete file-related information from a subscription was canceled because an initial-state definition makes reference to it. The name of the initial-state definition is given in the message.
Action	Remove references to the subscription from the initial-state definition and try again.

ARF00195	IDBID/IFILE deleted
Explanation	An IDBID/IFILE specification in an initial-state definition was successfully deleted.
Action	No action is required for this informational message.
ARF00196	Start Date/Time must be less than or equal to From Date/Time
Explanation	The start time specified for the replay request must be earlier or the same as the from time specified for the replay request.
Action	Correct the times and try again.
ARF00197	Destination Class must be present to enter data
Explanation	Data was entered in the Destination Class Parameter Data field, but no value was specified for the Destination Class field. You cannot supply a value for the Destination Class Parameter Data field without first supplying a Destination Class value.
Action	Supply a value in the Destination Class field or delete the data in the Destination Class Parameter Data field.
ARF00198	GFB must be generated by Predict
Explanation	A subscription references a destination that has a Destination Class of SAGTARG. When this condition is true, any GFB specified in the subscription must be generated by Predict. For more information on how to generate your GFBs, read <i>Generating a GFB using the Adabas Event Replicator Subsystem</i> (in <i>Adabas Event Replicator Subsystem User Guide</i>).
Action	Supply a GFB that was generated by Predict.
ARF00199	Initial-State not found
Explanation	The initial-state definition you selected to populate a database could not be found in the Replicator system file.
Action	Specify an existing initial-state definition, or add one and then select it.
ARF00200	Only type I (ISN) files can be edited
Explanation	Only files that require an ISN list as a filter can be edited on the Perform Initial-State screen. An attempt was made to edit a file that does not require an ISN list filter.
Action	Do not type an "E" next to any files that do not have a filter type of "I" (check the I column on the screen).

ARF00201 **You must enter data before submitting**
Explanation An attempt was made to submit the initial-state definition for processing, but it failed because one of the files requires an ISN list filter or a value buffer that has not yet been specified.
Action Enter an "E" next to every file on the **Perform Initial-State** screen that has a filter type of "I" or "S". Another Adabas Event Replicator Subsystem screen appears on which you can specify ISNs or a value buffer for the file.

ARF00202 **Entered ISN data is not contiguous**
Explanation The ISN list on the **Specify ISNs** screen is not specified correctly. There are blanks in the ISN list. The only characters allowed are numbers, commas, and parentheses.
Action Remove any blanks from the ISN list.

ARF00203 **Invalid characters in ISN data**
Explanation The ISN list on the **Specify ISNs** screen is not specified correctly. There are invalid characters in the ISN list. The only characters allowed are numbers, commas, and parentheses.
Action Correct the ISN list. Separate multiple ISNs with commas (no blanks). If you want to specify a range of ISNs, specify them in parentheses. For example, the following ISN list selects ISNs 111 and 222, all the ISNs between 333 and 666, and ISN 9999.

```
111,222,(333,666),9999
```

ARF00204 **Unbalanced parentheses**
Explanation The ISN list on the **Specify ISNs** screen is not specified correctly. An uneven number of open and closed parentheses are specified.
Action Verify that both an open and closed parenthesis are provided if you are specifying an ISN range. The following example correctly specifies a range of ISNs falling between 333 and 555.

```
(333,555)
```

If you are not specifying an ISN range, remove parentheses from the ISN list.

ARF00205 **Two values are required for a range**
Explanation The ISN list on the **Specify ISNs** screen is not specified correctly. An ISN range is indicated, but using only one number.
Action Verify that two numbers are provided if you are specifying an ISN range. The following example correctly specifies a range of ISNs falling between 333 and 555.

(333,555)

If you are not specifying an ISN range, remove the parentheses from the ISN list. Parentheses indicate that an ISN range is being specified.

ARF00206	Comma missing after range
Explanation	The ISN list on the Specify ISNs screen is not specified correctly. A comma is missing.
Action	Correct the use of commas in the ISN list. Commas should be used to separate individual ISNs in the list and any ISN range specifications from the rest of the list. Note the use of commas in the following correct ISN list that selects ISNs 111 and 222, all the ISNs between 333 and 666, and ISN 9999.
	111,222,(333,666),9999
ARF00207	ISN ranges must be in ascending order
Explanation	The ISN list on the Specify ISNs screen is not specified correctly. A range in the ISN list is not specified in ascending order.
	When specifying a range in the ISN list, you must be sure that the lowest ISN of the range is listed first, followed by the highest ISN in the range.
Action	Correct the ISN range specification.
ARF00208	Initial-state name not found
Explanation	The initial-state definition you selected to populate a database could not be found in the Replicator system file.
Action	Specify an existing initial-state definition, or add one and then select it.
ARF00209	Wrong ISN list
Explanation	The ISN list on the Specify ISNs screen is not the correct ISN list.
Action	Verify that the ISN list filters on the Specify ISN screens are specified correctly, as required for each file on the Perform Initial-State screen.
ARF00210	Selection data not allowed for type A initial-state
Explanation	Filter data is not allowed for the initial-state definition of filter type A records (see the I column on the Perform Initial-State screen).
Action	Do not type an "E" next to any files that do <i>not</i> have a filter type of "I" (check the I column on the screen).

ARF00211	Initial-State request received after ADAEND or HALT
Explanation	An initial-state request was issued to an Event Replicator Server address space that was terminating as a result of an ADAEND or HALT command. An initial-state request may only be issued when the Event Replicator Server is active.
Action	Reissue the initial-state request after the Event Replicator Server has been started.
ARF00212	Num of concurrent initial-state requests exceeded
Explanation	The number of active concurrent initial-state requests exceeded the IMAXREQ parameter setting. For more information about the IMAXREQ parameter, read <i>IMAXREQ</i> in <i>Event Replicator for Adabas Reference Guide</i> .
Action	Increase the IMAXREQ setting or reduce the number of active concurrent initial-state requests.
ARF00213	ISN entry too long
Explanation	The ISN list on the Specify ISNs screen is not specified correctly. An ISN in the list is longer than nine characters. An ISN in the list can be a maximum of nine characters long.
Action	Correct the ISN list. If your ISN is really larger than nine characters in length, contact your Software AG technical support representative for assistance.
ARF00214	Data missing after last comma
Explanation	The ISN list on the Specify ISNs screen is not specified correctly. A continuation in the list is indicated by a comma, but no additional ISN data is provided.
Action	Either remove the comma (if there are no additional ISNs or ISN ranges to specify) or complete the ISN list. The ISN list should not end with a comma.
ARF00215	Values cannot be specified for METHOD=ISN
Explanation	In an Adabas destination definition, the Replication Method specified was ISN for a given DBID/file combination's file-related parameters. If this parameter is set to ISN, no other file-related parameters for that DBID/file combination can be specified.
Action	Do not enter values for the other file-related parameters if the Replication Method is set to ISN. If you set the Replication Method to KEY, you may specify the other parameters.

ARF00216	Do not specify both "*" and destination names
Explanation	An automated replay request was made using an asterisk specified in the first destination space of the Destination Name List field. This includes all destination definitions in the request. If you use an asterisk to select all destinations for the replay request, you cannot also add another specific destination or select one from a list.
Action	To add a specific destination or select one from a list, remove the asterisk from the first destination space of the Destination Name List field.
ARF00217	Do not specify both "*" and subscription names
Explanation	An automated replay request was made using an asterisk specified in the first subscription space of the Subscription Name List field. This includes all subscription definitions in the request. If you use an asterisk to select all subscriptions for the replay request, you cannot also add another specific subscription or select one from a list.
Action	To add a specific subscription or select one from a list, remove the asterisk from the first subscription space of the Subscription Name List field.
ARF00218	Value buffer length must be entered
Explanation	A value buffer length was not specified on the Specify Value Buffer screen while you were trying to perform an initial-state. If a DBID/file combination includes a search buffer, a value buffer and the length of the value buffer must be specified.
Action	Enter a valid value for the length of the value buffer.
ARF00219	Duplicate source DBID/FILE combinations are not allowed
Explanation	The same DBID/file combination was defined for more than one target in an Adabas destination definition.
Action	Remove the duplicate.
ARF00220	Only valid entries can be marked
Explanation	You have selected a blank line of input and target DBIDs and files on the Adabas Destination Definition panel.
Action	Select a line that has input and target DBIDs and files specified or supply input and target DBIDs and files on the selected line.
ARF00221	Duplicate DBid and File exist -- invalid {add change}
Explanation	When specifying an SFILE definition for a subscription, you tried to add a new DBID/file combination or change a DBID/file combination but specified a combination that already exists for this subscription.
Action	Specify a unique DBID/file combination for each SFILE definition within a subscription.

ARF00222	Request rejected, a related file is not active
Explanation	After requesting that an initial-state be performed (by selecting the Perform Initial-State option on the Administration panel), the returned response and subcodes indicate that a file related to the initial-state definition you attempted to run is not active.
Action	Examine the error and current status of the file and determine why the file is not active. If the problem persists, contact your Software AG support representative for assistance.
ARF00223	Only the first {destination subscription} may have an asterisk
Explanation	When selecting a destination or subscription, only the first entry may contain an asterisk.
Action	Correct your specifications.
ARF00224	Asterisk is only allowed in the first cell
Explanation	Only the first entry may contain an asterisk.
Action	Correct your specifications.
ARF00225	Predict not available for edit
Explanation	The global format buffer (GFB) you have selected to edit was created with Predict, but predict is not available in this Natural environment.
Action	Either install Predict in this Natural environment or edit the GFB in a Natural environment in which Predict is already installed and then import the GFB into the original Natural environment.
ARF00226	Destination {destname} does not exist in a subscription
Explanation	<p>The initial-state definition includes references to both destination and subscription definitions. The destination identified in the message (<i>destname</i>) does not exist in the subscriptions of the initial-state definition being defined or modified. The Event Replicator Server detects this inconsistency and produces an error condition at startup or when an RPLREFRESH is attempted for the initial-state definition. The destinations specified in an initial-state definition must also exist in one of the subscriptions referenced by the initial-state definition.</p> <p>When both destination and subscription definitions are specified in an initial-state definition, the destinations must correlate to destinations specified by the subscriptions. Likewise, at least one destination specified by each subscription must be referenced by the initial-state definition. In addition, any destinations referenced in the initial-state definition must be identified as able to send initial-state data (using the I field on the Destination List panel within the subscription definition).</p>

Action Make sure that all of the destinations used by your initial-state definition also exist in one of the subscription destinations referenced by your initial-state definition. Then try again.

ARF00227

Destination {destname} in subsc {subname} does not send i-s data

Explanation

The initial-state definition includes references to both destination and subscription definitions. The destination listed in the message (*destname*) was found in the subscription listed in the message (*subname*), but it is not marked in the subscription definition as being able to send initial-state data. The Event Replicator Server detects this inconsistency and produces an error condition at startup or when an RPLREFRESH is attempted for the initial-state definition.

When both destination and subscription definitions are specified in an initial-state definition, the destinations must correlate to destinations specified by the subscriptions. Likewise, at least one destination specified by each subscription must be referenced by the initial-state definition. In addition, any destinations referenced in the initial-state definition must be identified as able to send initial-state data (using the **I** field on the **Destination List** panel within the subscription definition).

Action

Make sure that any destinations used by your initial-state definition and included in the associated subscription definitions are marked as able to send initial-state data. This setting is specified by setting the **I** field to "Y" on the **Destination List** panel line associated with the destination in the subscription definition. Then try again.

ARF00228

Subsc {subname} has no matching dest in i-s dest list

Explanation

The initial-state definition includes references to both destination and subscription definitions. None of the destinations specified by the subscription listed in the message (*subname*) are included in the initial-state definition, as is required. The Event Replicator Server detects this inconsistency and produces an error condition at startup or when an RPLREFRESH is attempted for the initial-state definition. The destinations specified by a subscription (that is included in an initial-state definition) must also be included in the initial-state definition.

When both destination and subscription definitions are specified in an initial-state definition, the destinations must correlate to destinations specified by the subscriptions. Likewise, at least one destination specified by each subscription must be referenced by the initial-state definition. In addition, any destinations referenced in the initial-state definition must be identified as able to send initial-state data (using the **I** field on the **Destination List** panel within the subscription definition).

Action

Make sure to include in the initial-state definition any destinations specified by any subscriptions included in the initial-state. Then try again.

- ARF00229** **Subsc {subname} has no i-s data flow for dest {destname}**
- Explanation** The initial-state definition includes references to both destination and subscription definitions. The destination listed in the message (*destname*) was found in the subscription listed in the message (*subname*), but the destination is not marked in the subscription definition as being able to send initial-state data. The Event Replicator Server detects this inconsistency and produces an error condition at startup or when an RPLREFRESH is attempted for the initial-state definition.
- When both destination and subscription definitions are specified in an initial-state definition, the destinations must correlate to destinations specified by the subscriptions. Likewise, at least one destination specified by each subscription must be referenced by the initial-state definition. In addition, any destinations referenced in the initial-state definition must be identified as able to send initial-state data (using the **I** field on the **Destination List** panel within the subscription definition).
- Action** Make sure that any destinations used by your initial-state definition and included in the associated subscription definitions are marked as able to send initial-state data. This setting is specified by setting the **I** field to "Y" on the **Destination List** panel line associated with the destination in the subscription definition. Then try again.
-
- ARF00230** **User exit required when Replicate for Delete = U**
- Explanation** When the **Replicate for Delete** field is set to "U" in an SFILE definition, a subscription user exit name must be supplied in the **Subscription User Exit** field. The subscription user exit can then process replicated physical delete transactions on your target database as you choose. It can decide if the physical delete transaction should be:
- physically deleted from your target database
 - converted to an update
 - ignored and not sent at all.
- Action** Specify a subscription user exit name or change the setting of the **Replicate for Delete** field.
-
- ARF00231** **Dest. found in Subsc. {subname} w/o matching DBid {dbid} File {fn}**
- Explanation** An input DBID/file combination was added to a destination definition, but a subscription that references the destination definition does not include a comparable SFILE definition for the DBID/file combination. You will not be able to save the destination definition until the problem is resolved.
- Action** Add the SFILE definition for the new DBID/file combination first. Then update the destination definition.

ARF00232	{xxxxxx} begin + length > 32767
Explanation	When setting Source Begin and Length values or Target Begin and Length values, the sum of these values cannot exceed 32767. You will not be able to save the transaction filter until the problem is resolved.
Action	Examine and correct the values for the appropriate Begin and Length fields. Then save or update the transaction filter definition.
ARF00233	Replic.for {fx}=N invalid when Replic.security file=Y
Explanation	When the Replicate Security File field is set to "Y", the Replicate for Delete , Replicate for Insert , and Replicate for Update fields must also be set to "Y". The Replicate Security File field specifies the value of the SFSECURITYFILE parameter.
Action	Examine and correct the values for the appropriate field. Then save or update the definition.
ARF00234	Incl.Identical Records=N invalid when Replic.security file=Y
Explanation	When the Replicate Security File field is set to "Y", the Include Identical Records field must also be set to "Y". The Replicate Security File field specifies the value of the SFSECURITYFILE parameter.
Action	Examine and correct the values for the appropriate field. Then save or update the definition.
ARF00235	Default Code={nnnn} invalid when Replic.security file=Y
Explanation	When the Replicate Security File field is set to "Y", the Default Code field must be null. The Replicate Security File field specifies the value of the SFSECURITYFILE parameter.
Action	Examine and correct the values for the appropriate field. Then save or update the definition.
ARF00236	Subscription user exit invalid when Replic.security file=Y
Explanation	When the Replicate Security File field is set to "Y", the Subscription User Exit field must be null. The Replicate Security File field specifies the value of the SFSECURITYFILE parameter.
Action	Examine and correct the values for the appropriate field. Then save or update the definition.

ARF00237	Transaction filter invalid when Replic.security file=Y
Explanation	When the Replicate Security File field is set to "Y", the Transaction Filter field must be null. The Replicate Security File field specifies the value of the SFSECURITYFILE parameter.
Action	Examine and correct the values for the appropriate field. Then save or update the definition.
ARF00238	FBs or GFBs are invalid when Replic.security file=Y
Explanation	When the Replicate Security File field is set to "Y", no format buffers or global format buffers can be specified. The values of the Before Image FB , After Image FB , Key-Related Before Image FB , Before Image GFB Name , After Image GFB Name , and Key-Related GFB Name must be null. The Replicate Security File field specifies the value of the SFSECURITYFILE parameter.
Action	Examine and correct the values for the appropriate field. Then save or update the definition.
ARF00239	Format buffer exceeds length of 32756, is = {nnnnn}
Explanation	A Predict global format buffer (a generated GFB) is exceeding the maximum length of 32756, and will be truncated. The length of the format buffer is given in the message (<i>nnnnn</i>).
Action	Modify the GFB to fit the maximum length.
ARF00240	No flow for dbid/fnr {xxxxx} {yyyyy} in {is-subscr }
Explanation	A verification process has found that the subscription specified by the initial-state definition (<i>is-subscr</i>) does not have a correct definition for the DBID/file number combination (<i>xxxxx/yyyyy</i>) given in the message.
Action	Correct the initial-state, destination, or subscription definitions and try again.
ARF00241	Dest {destname} in Subsc. {subname} w/o match DBid/file in Sub.
Explanation	A destination was added to a subscription definition, but the subscription definition does not include a comparable SFILE definition for the DBID/file combination of the destination. You will not be able to save the subscription definition until the problem is resolved.
Action	Add the SFILE definition for the new DBID/file combination first. Then update the subscription definition.

ARF00242	Dest {destname} also found in Subsc. {subsname}
Explanation	A destination was added to a subscription definition, but another subscription also references the destination. You will not be able to save the subscription definition until the problem is resolved. An Adabas destination can be referenced by no more than one subscription.
Action	Specify a different destination or otherwise update your subscription definitions so that the destination definition is referenced in only one of them.
ARF00243	File not replicated to this target
Explanation	A verification process for an initiated replication replay process has determined that the FCB of the file specified is not replicated to the definition defined here.
Action	Correct the destination or subscription definitions.
ARF00244	Destination {destname} requires DCLASS='SAGTARG'
Explanation	A Destination of <i>destname</i> has the DHBINTERVAL specified and does not have DCLASS=SAGTARG, which is required.
Action	Correct the destination definition.
ARF00245	Replay-Only selected Destination is closed
Explanation	A Destination specified in the Replay-Only replay is closed. Any Destination specified in a Replay must be in open status.
Action	Correct the destination status, or modify the Replay request.

44

ARMT* - Adabas Review Interface Messages

ARMT01	{dbid} GETMAIN FAILURE, SIZE {requested-getmain-size}
Explanation	A request for storage in the Adabas nucleus failed.
Action	Either determine what is using so much storage in the Adabas nucleus and correct the problem; or increase the available storage.
ARMT02	{dbid} ATTACH ADARST FAILURE, STRS {nn}
Explanation	The Adabas nucleus was unable to attach the subtask ADARST. STRS is the ADAIOR response code.
Action	Probably, the module ADARST is missing.
ARMT03	{dbid} CLOG TOO BIG, CLOG NOT SENT
Explanation	When an ADABAS nucleus runs Adabas Review in hub mode, the CLOG inclusive CLOG extension and control information may be bigger than around 32K. This CLOG record is not sent to the Adabas Review hub. This message is only issued one time.
Action	One of the buffers may be too big. For instance, you may set LOGRB=NO.
ARMT04	{dbid} ATTACH OF ADARST SUCCESSFUL
Explanation	The subtask ADARST was attached successfully. The database will send data to the Adabas Review hub.
Action	No action is required for this informational message.

ARMT05	{dbid} DETACH OF ADARST SUCCESSFUL
Explanation	The subtask ADARST was detached successfully.
Action	Once you have corrected the error that led to detachment of ADARST, you can reactivate the subtask using the ADARUN parameter <code>REVIEW=hubid</code> . The successful ATTACH will be acknowledged with message ARMT04. A restart of the database is in this case not necessary. If the subtask abends a second time, it will be deactivated completely and message ARST10 will be given.
ARMT06	{dbid} Review suspended, buffer unavailable. REVIEW parameter is set to NO.
Explanation	ADARMT is experiencing a temporary buffer shortage. The ADARUN parameter REVIEW is set to NO.
Action	To activate Review again, change the ADARUN REVIEW parameter.
ARMT07	{dbid} Review resumed, {nn} CLOG records skipped
Explanation	Buffers have become available after the shortage noted by message ARMT06. The number of CLOG records skipped during the shortage is given in the message (<i>nn</i>).
Action	No action is required for this informational message.
ARMT08	{dbid} Review suspended, subtask unable to initialize
Explanation	The subtask ADARST did not initialize. ADARST is detached and message ARMT05 appears. All Adabas Review processing from this nucleus is suspended.
Action	If you can correct the error that led to the initialization failure of ADARST, you can reactivate the subtask using the operator command <code>REVIEW=hubid</code> . The successful ATTACH will be acknowledged with message ARMT04. In this case, a restart of the database is not necessary. Notify your Software AG technical support representative if you are unable to resolve the initialization failure.
ARMT09	{dbid} Review Trans-Port disabled after error
Explanation	Future records will be sent to the Hub using the command queue instead of Trans-Port. There should be additional messages in the Nucleus and Hub to identify the error.
Action	Correct the error. Reestablish Trans-Port by restarting the Nucleus or Review Hub.

45

ARST* - Adabas Review Interface Messages

ARST01	{dbid} GETMAIN failure, size= {requested-getmain-size}
Explanation	A request for storage in the Adabas nucleus subtask ADARST failed.
Action	Either determine what is using so much storage in the Adabas nucleus and correct the problem; or increase the available storage.
ARST02	{dbid} LOAD FAILED FOR MODULE {module}
Explanation	The specified module cannot be loaded.
Action	Probably, the requested load module is missing.
ARST06	{dbid} Adabas Review subtask statistics {dbid} Buffers in: {count} Buffers out: {count} {dbid} UEX5 calls: {count} Timer calls: {count} posts: {count}
Explanation	This message displays ADARST shutdown statistics.
Action	None required. This message is for information only.
ARST09	{dbid} Subtask ADARST detached
Explanation	The subtask ADARST was detached for one of the following reasons: <ul style="list-style-type: none">■ An error occurred when accessing the Adabas Review hub■ The Adabas Review hub returned Adabas response code 148 (ADARSP148 - not active)
	As long as the subtask is not attached, this database will not send data to the Adabas Review hub.
Action	If the reason for the detachment is an unjustified Adabas response code 148 (ADARSP148), contact your Software AG technical support representative for assistance.

ARST10	{dbid} Unrecoverable abend in subtask ADARST
Explanation	<p>The subtask ADARST abended either due to an unrecoverable abend or to the second call of the ESTAE (in this case see previous ARST_{xx} messages).</p> <p>The subtask is deactivated and the database will not send data to the Adabas Review hub.</p>
Action	<p>It is not possible to reactive the subtask using the ADARUN REVIEW=<i>hubid</i> parameter. You must restart the database to reactivate Adabas Review.</p>
ARST11	{dbid} Abend S0D6 occurred {nnnnn} Possibly the REVIEW hubid = {hhhhh} ended abnormally.
Explanation	<p>This error messages can only occur in an Adabas nucleus, if an Adabas Review hub is installed using the Trans-port feature. For some reason the PC number for the PC call is invalid.</p> <p>The ARST07 message is issued and the ADARUN REVIEW parameter is set to NO.</p>
Action	<p>Determine the reason for the abend S0D6. It is likely that the Adabas Review hub has abended. If necessary, contact you Software AG support representative for further assistance.</p>

46

ART* - Event Replicator Target Adapter Messages

ART0102I	An Event Replicator Target Adapter engine is started and waiting for work
Explanation	An Event Replicator Target Adapter has successfully started and is waiting for work.
Action	No action is required for this informational message.
ART0103E	Unable to load resource bundle; message
Explanation	This is an internal error.
Action	Contact your Software AG technical support representative for assistance.
ART0104I	Version information {version}
Explanation	The version of the Event Replicator Target Adapter that is running is given in the message (<i>version</i>).
Action	No action is required for this informational message.
ART0105I	Engine shutdown requested
Explanation	A request has been made to shut down the Event Replicator Target Adapter.
Action	No action is required for this informational message.
ART0106I	Main processing loop shutdown requested
Explanation	A request has been made to shut down the main processing loop of the Event Replicator Target Adapter.
Action	No action is required for this informational message.

ART0107I	Operation message: {input-msg}
Explanation	An operation message (<i>input-msg</i>) is listed in the text of this message.
Action	No action is required for this informational message.
ART0108E	Invalid or unprocessed message received: {msg}
Explanation	An invalid or unprocessed message was received. The invalid message (<i>msg</i>) is provided in the text of this message.
Action	Review any previous messages to determine the primary cause of the problem. If the problem persists, contact your Software AG technical support representative for assistance.
ART0109E	Cannot connect to target
Explanation	An attempt to connect to a defined target failed.
Action	Evaluate the target definition to determine the cause of the problem. If you cannot determine the cause of the problem, contact your Software AG technical support representative for assistance.
ART0110E	Operation status: {status}
Explanation	The status of the failed operation (<i>status</i>) is provided in the text of this message. This message accompanies other error messages. Possible statuses are "Failed" and "FailedRetry".
Action	Review the other messages that accompany this one to determine the cause of the problem. If you cannot determine the cause of the problem, contact your Software AG technical support representative for assistance.
ART0111E	Incorrect message: {msg}
Explanation	The message in error (<i>msg</i>) is provided in the text of this message, which accompanies other error messages.
Action	Review the other messages that accompany this one to determine the cause of the problem. If you cannot determine the cause of the problem, contact your Software AG technical support representative for assistance.
ART0112I	Database retry count is 0
Explanation	The database retry count setting has reached the value of zero (0). No further database retries are attempted and the source is closed.
Action	Restart the database and reopen the source.

ART0113I	Waiting {secs} seconds before database retry {number} of {total}
Explanation	The Event Replicator Target Adapter is waiting the number of seconds listed in the message (<i>secs</i>) before attempting to reconnect to the source database. The retry attempt number (<i>number</i>) and the total number of retry attempts defined for the source (<i>total</i>) are also given in the message.
Action	No action is required for this informational message.
ART0114I	Attempting database retry {number} of {total}
Explanation	The Event Replicator Target Adapter is attempting to reconnect to a source database. The retry attempt number (<i>number</i>) and the total number of retry attempts defined for the source (<i>total</i>) are given in the message.
Action	No action is required for this informational message.
ART0115E	XSLT or XML document is null
Explanation	The style sheet (XSLT) or XML document to be used in Event Replicator Target Adapter processing is null or cannot be found. This is an internal error.
Action	Contact your Software AG technical support representative for assistance.
ART0116I	Committing invalid or unprocessed message
Explanation	The invalid message was committed because the Commit Unprocessed Message option was set to true. Processing continues.
Action	No action is required for this informational message.
ART0117I	IVP message received and processed
Explanation	The installation verification procedure (IVP) message was received and processed successfully.
Action	No action is required for this informational message.
ART0118I	Received {count} request
Explanation	The number of requests received is listed in the message (<i>count</i>).
Action	No action is required for this informational message.

ART0119E	Received unknown message {msg}
Explanation	An unknown message was received.
Action	Contact your Software AG technical support representative for assistance.
ART0120E	Cannot convert input message from {source} code page {num1} to {num2}
Explanation	The input message listed in the message text could not be converted from one code page (<i>num1</i>) to another (<i>num2</i>).
Action	Contact your Software AG technical support representative for assistance.
ART0121E	Current messages
Explanation	This message accompanies message ARTO108E.
Action	Review all the messages to determine the cause of the problem. If the problem persists, contact your Software AG technical support representative for assistance.
ART0122I	Problems writing file; directory must exist: {dirname}
Explanation	A file could not be written because the directory listed in the message did not exist.
Action	Create the directory and restart the Event Replicator Target Adapter.
ART0123E	Unprocessed data {count} bytes in buffer {buf}
Explanation	An internal error has occurred.
Action	Contact your Software AG technical support representative for assistance.
ART0124I	Successful database reconnect for {target} target
Explanation	An attempt to reconnect to the database target was successful.
Action	No action required for this informational message
ART0125I	Software AG License check {license}
Explanation	A Software AG license check occurred for the license shown in the message.
Action	No action required for this informational message
ART0303I	Initial-state process started for: {isname}
Explanation	The Event Replicator Target Adapter has started processing an initial-state request. The name of the initial-state definition (<i>isname</i>) is listed in the message.
Action	No action is required for this informational message.

ART0304I	Initial-state process completed for: {isname}
Explanation	The Event Replicator Target Adapter has completed processing an initial-state request. The name of the initial-state definition (<i>isname</i>) is listed in the message.
Action	No action is required for this informational message.
ART0305I	Initial-state erroneous request rejected
Explanation	An invalid initial-state request was rejected. It was not processed.
Action	No action is required for this informational message. However, you might want to review the invalid initial-state request to determine why it was not processed.
ART0307I	Normal Event Replicator Server session started message received from: {reptor-id}
Explanation	A normal Event Replicator Server session has started and a message has been received from it. The Event Replicator Server ID is listed in the message (<i>reptor-id</i>).
Action	No action is required for this informational message.
ART0308I	Event Replicator Server restart after abnormal end
Explanation	The Event Replicator Server has restarted after it ended abnormally.
Action	No action is required for this informational message although you might want to review the error messages provided by the Event Replicator Server to determine why it ended abnormally.
ART0309I	Normal Event Replicator Server session termination message received from: {reptor-id}
Explanation	A normal Event Replicator Server session has terminated. The Event Replicator Server ID is listed in the message (<i>reptor-id</i>).
Action	No action is required for this informational message.
ART0310I	Replication deactivated
Explanation	Replication has been deactivated (stopped).
Action	No action is required for this informational message.
ART0311I	Replication reactivated
Explanation	Replication has been reactivated (started).
Action	No action is required for this informational message.

ART0314I	Replay process (ADARPL) started
Explanation	The ADARPL utility has started to resend replicated data from the database protection log (PLOG) to the target RDBMS. For more information, read about the ADARPL utility in your Event Replicator for Adabas documentation.
Action	No action is required for this informational message.
ART0315I	Replay process (ADARPL) ended
Explanation	The ADARPL utility has completed resending replicated data from the database protection log (PLOG) to the target RDBMS. For more information, read about the ADARPL utility in your Event Replicator for Adabas documentation.
Action	No action is required for this informational message.
ART0316I	Event Replicator Server replication definitions refreshed
Explanation	The Event Replicator Server replication definitions have been refreshed via an RPLREFRESH command.
Action	No action is required for this informational message.
ART0317I	ADALOD UPDATE started
Explanation	A run of the ADALOD UPDATE utility function has started.
Action	No action is required for this informational message.
ART0318I	ADALOD UPDATE ended
Explanation	A run of the ADALOD UPDATE utility function has ended.
Action	No action is required for this informational message.
ART0319I	ADALOD LOAD ended. Source: {src} Target: {target}
Explanation	A run of the ADALOD LOAD utility function has ended.
Action	No action is required for this informational message.
ART0320E	Unknown status message {message}
Explanation	An unknown status message was encountered during Event Replicator Target Adapter processing. The status message is given in the message text.
Action	Contact your Software AG technical support representative for assistance.

ART0321E	Unknown URBS operation {operation}
Explanation	An unknown URBS operation was attempted. The type of operation attempted is listed in the message text.
Action	Contact your Software AG technical support representative for assistance.
ART0322E	Invalid DBID {dbid} or file number {fn}
Explanation	An invalid database ID or file number was encountered during processing.
Action	Check your GFB/GFFT definition. Contact your Software AG technical support representative for assistance.
ART0323I	Receiving LODS message: Source: {src} Target: {target}
Explanation	An ADALOD message is being received. The data source and target are listed in the message.
Action	No action is required for this informational message.
ART0324E	Receiving unknown message
Explanation	An unknown message was received during processing.
Action	Contact your Software AG technical support representative for assistance.
ART0325I	Receiving AUT1 message (Adabas utility execution)
Explanation	An AUT1 message produced by the execution of an Adabas utility is being received.
Action	No action is required for this informational message.
ART0401I	Testing database connections
Explanation	The Event Replicator Target Adapter is testing its database connections.
Action	No action is required for this informational message.
ART0402I	Database information at startup:
Explanation	This message is the introductory message for a series of other informational messages about the databases to which the Event Replicator Target Adapter has connections.
Action	No action is required for this informational message.

ART0403I	Connector protocol: {protocol-type} port: {port}
Explanation	This message lists the protocol type and port number used by the Event Replicator Target Adapter Tomcat engine.
Action	No action is required for this informational message.
ART0404I	Using connector port: {conn-port} port: {port}
Explanation	This message lists the default HTTP port number that will be used.
Action	No action is required for this informational message.
ART0405I	Adabas Replicator servlet shutdown started
Explanation	The Event Replicator Server is shutting down.
Action	No action is required for this informational message.
ART0406I	Adabas Replicator servlet shutdown complete
Explanation	The Event Replicator Server shutdown is complete.
Action	No action is required for this informational message.
ART0407I	Testing connection to database resource {id}
Explanation	A test is being performed that connects to the database resource listed in the message (<i>i d</i>).
Action	No action is required for this informational message.
ART0408I	Database testing complete
Explanation	Tests on the database have completed.
Action	No action is required for this informational message.
ART0409I	JMS information at startup:
Explanation	This message is the introductory message for a series of other informational messages about the JMS to which the Event Replicator Target Adapter has connections.
Action	No action is required for this informational message.

ART0410I	JMS testing complete
Explanation	Tests on the JMS have completed.
Action	No action is required for this informational message.
ART0411I	Generic Target information at startup:
Explanation	This message is the introductory message for a series of other informational messages about feneric targets to which the Event Replicator Target Adapter has connections (for example, a Terracotta cache target).
Action	No action is required for this informational message.
ART0412I	Generic Target testing complete
Explanation	Tests on the generic targets have completed.
Action	No action is required for this informational message.
ART0501I	EntireX Broker information {info}
Explanation	This message displays information about a webMethods EntireX source used to convey replicated Adabas data to the Event Replicator Target Adapter.
Action	No action is required for this informational message.
ART0502I	EntireX Broker source shutdown requested
Explanation	A request is being processed to close a webMethods EntireX source used to convey replicated Adabas data to the Event Replicator Target Adapter.
Action	No action is required for this informational message.
ART0503I	EntireX Broker source shutdown requested; processing: {state} userstop: {xxxx}
Explanation	A webMethods EntireX source used to convey replicated Adabas data to the Event Replicator Target Adapter is being closed. The current state of the source is displayed in the message.
Action	No action is required for this informational message.
ART0504I	EntireX Broker source close complete
Explanation	A webMethods EntireX source used to convey replicated Adabas data to the Event Replicator Target Adapter has been closed.
Action	No action is required for this informational message.

ART0505I	EntireX Broker UOW rolled back ID: {id}
Explanation	The webMethods EntireX unit of work ID was rolled back. This is an internal process.
Action	No action is required for this informational message.
ART0506I	EntireX Broker prefetch size reached: {size}
Explanation	The defined prefetch size for the webMethods EntireX source has been reached. The defined prefetch size is given in the message (<i>size</i>).
Action	No action is required for this informational message. However, you might consider increasing the defined prefetch size. Note that increasing the prefetch size will increase the memory requirements.
ART0507E	EntireX Broker send error class: {class} code: {code} message: {msg}
Explanation	An error has occurred during an attempt to send data to a webMethods EntireX source. The error class (<i>class</i>), message code (<i>code</i>) and message text (<i>msg</i>) are given in the message.
Action	Refer to your webMethods EntireX documentation for additional information.
ART0508E	EntireX Broker error class: {class} code: {code} message: {msg}
Explanation	An error has occurred during an attempt to use a webMethods EntireX source. The error class (<i>class</i>), message code (<i>code</i>) and message text (<i>msg</i>) are given in the message.
Action	Refer to your webMethods EntireX documentation for additional information.
ART0509E	EntireX Broker exception: {info}
Explanation	An exception occurred during an attempt to use a webMethods EntireX source. The exception information (<i>info</i>) is given in the message.
Action	Contact your Software AG technical support representative for assistance.
ART0510E	EntireX Broker receive error class: {class} code: {code} message: {msg}
Explanation	An error has occurred during an attempt to receive data from an webMethods EntireX source. The error class (<i>class</i>), message code (<i>code</i>) and message text (<i>msg</i>) are given in the message.
Action	Refer to your webMethods EntireX documentation for additional information.

ART0511E	EntireX Broker logon error ID: {class} service: {service} message: {msgtxt}
Explanation	An error has occurred during an attempt to log into an webMethods EntireX source. The error class (<i>class</i>), service name (<i>service</i>), and message code (<i>msgtxt</i>) are given in the message.
Action	Verify that the correct logon information (user ID, token, and password) is provided in the webMethods EntireX source definition. Correct it as necessary and try again.
ART0512E	EntireX Broker error on: {id} cause: {exx-cause}
Explanation	An error occurred during an attempt to use the webMethods EntireX source whose ID is listed in the message (<i>id</i>). The cause of the error is also listed in the message (<i>exx-cause</i>).
Action	Contact your Software AG technical support representative for assistance.
ART0513E	EntireX Broker commit error message: {err-msg}
Explanation	An error occurred during an attempt to use a webMethods EntireX source definition. The webMethods EntireX error message (<i>err-msg</i>) is listed in the message.
Action	Contact your Software AG technical support representative for assistance.
ART0514E	EntireX Broker cannot open Broker trace log file: {fn}
Explanation	An error occurred during an attempt to open the webMethods EntireX trace log file. The file name of the log file is given in the message (<i>fn</i>).
Action	Verify that the correct file name is specified for the webMethods EntireX trace log file in the webMethods EntireX definitions. If it is not, correct the name and try again. If the problem persists, contact your Software AG support representative for assistance.
ART0515I	EntireX Broker trace level: {lvl} trace file: {fn}
Explanation	This message identifies the trace level (<i>lvl</i>) and file name (<i>fn</i>) used by the Event Replicator Target Adapter for webMethods EntireX sources.
Action	No action is required for this informational message.
ART0516I	EntireX Broker receive complete: time: {count} Ms length: {length} UowStatus: {status}
Explanation	A webMethods EntireX source received data from replication. The length of time (in microseconds) for the receive operation (<i>count</i>), the length of the data received (<i>length</i>), and the unit of work status of the receive operation (<i>status</i>) are given in the message. Values for the unit of work status are "First", "Middle" or "Last".
Action	No action is required for this informational message.

ART0517E	EntireX Broker commit error class: {class} code: {code} uowid: {uowid} message: {msg}
Explanation	An error occurred during a commit attempt for the webMethods EntireX source. The error class (<i>class</i>), EntireX message code (<i>code</i>), EntireX UOWID (<i>uowid</i>) and EntireX message text (<i>msg</i>) are listed in the message.
Action	Contact your Software AG technical support representative for assistance.
ART0518E	EntireX Broker rollback error class: {class} code: {code} message: {msg}
Explanation	An error occurred during a rollback attempt for the webMethods EntireX source. The error class (<i>class</i>), EntireX message code (<i>code</i>) and EntireX message text (<i>msg</i>) are listed in the message.
Action	Contact your Software AG technical support representative for assistance.
ART0519E	EntireX Broker deregister error host: {host-id} service: {service} message: {msg}
Explanation	An error occurred during an attempt to deregister a webMethods EntireX source. The EntireX ID (<i>host-id</i>), service (<i>service</i>) and message text (<i>msg</i>) are listed in the message.
Action	Contact your Software AG technical support representative for assistance.
ART0520E	EntireX Broker user ID required
Explanation	A valid webMethods EntireX user ID is required but was not supplied.
Action	Supply a valid webMethods EntireX user ID and try again.
ART0521E	EntireX Broker token required
Explanation	A valid webMethods EntireX token is required but was not supplied.
Action	Supply a valid webMethods EntireX token and try again.
ART0601I	Save file {fn} with data: {dddd}
Explanation	An attempt to save the file listed in the message (<i>fn</i>) with the data listed in the message (<i>dddd</i>) was successful.
Action	No action is required for this informational message.

ART0602E	Read resource failed for: {resource-id} status code: {code}
Explanation	An attempt to read from the resource listed in the message (<i>resource-id</i>) failed. The status code of the attempt is given in the message (<i>code</i>).
Action	Contact your Software AG technical support representative for assistance.
ART0603I	Retrying resource read for: {resource-id}
Explanation	An attempt is being made to read from the resource listed in the message (<i>resource-id</i>).
Action	No action is required for this informational message.
ART0604E	WebDAV error: {err-code}
Explanation	A WebDAV error occurred during Event Replicator Target Adapter processing.
Action	Verify that the web service target URL is correct and try again. If the problem persists, contact your Software AG technical support representative.
ART0605E	WebDAV repository is not accessible {err-code}
Explanation	The WebDAV repository cannot be accessed.
Action	Verify that the web service target URL is correct and try again. If the problem persists, contact your Software AG technical support representative.
ART0606E	Invalid WebDAV cache size value {size}
Explanation	An invalid WebDAV cache size has been specified. The value was not numeric.
Action	Supply a valid numeric cache size and try again.
ART0607E	Cannot find generic XSLT file {filename}
Explanation	The XSLT file listed in the message (<i>filename</i>) could not be found.
Action	If the problem persists, contact your Software AG technical support representative.
ART0608E	Cannot find XSLT file {filename}
Explanation	The XSLT file listed in the message (<i>filename</i>) could not be found.
Action	If the problem persists, contact your Software AG technical support representative.

ART0609E	Create table XML message is null or base table name is null
Explanation	An internal error has occurred.
Action	If the problem persists, contact your Software AG technical support representative.
ART0610E	Cannot convert create table schema to string
Explanation	An internal error has occurred.
Action	If the problem persists, contact your Software AG technical support representative.
ART0611E	Cannot save create table schema {name} into WebDAV
Explanation	An attempt to save the schema named in the message (name) to the WebDAV repository failed.
Action	If the problem persists, contact your Software AG technical support representative.
ART0612E	Problem with managing WebDAV file {filename}
Explanation	The WebDAV file named in the message (<i>filename</i>) could not be managed.
Action	If the problem persists, contact your Software AG technical support representative.
ART0613I	Collection may not exist {colname}
Explanation	The collection named in the message (<i>colname</i>) may not exist in the WebDAV repository. The collection is created.
Action	No action is required for this informational message.
ART0614I	Retrying resource write for {res}
Explanation	An attempt is in progress to retry the resource write for the resource named in the message (<i>res</i>).
Action	No action is required for this informational message.
ART0615E	Write resource file {fn} failed {err-code}
Explanation	An attempt to write the resource file named in the message (<i>fn</i>) failed.
Action	If the problem persists, contact your Software AG technical support representative.

ART0616E	WebDAV status code {code} status message {msg}
Explanation	A WebDAV internal error has occurred.
Action	If the problem persists, contact your Software AG technical support representative.
ART0617E	Make collection {colname} failed status {stat}
Explanation	An attempt to make the collection named in the message (<i>colname</i>) failed. The status of the attempt is also given in the message (<i>stat</i>).
Action	If the problem persists, contact your Software AG technical support representative.
ART0701I	Source shutdown complete
Explanation	An attempt to shut down a source completed successfully.
Action	No action is required for this informational message.
ART0702I	Source waiting for restart after user stop or rollback
Explanation	The source is waiting to be restarted after it was manually stopped or after a rollback occurred.
Action	No action is required for this informational message. Restart the source when you are ready.
ART0703I	Retries = 0; source waiting for manual restart
Explanation	The value of the <code>Retry Count</code> parameter in the source definition has been reached. The source is waiting for a manual restart.
Action	No action is required for this informational message. Manually restart the source when you are ready.
ART0704I	Wait for retry; count: {count}
Explanation	The source is waiting between retry attempts. The retry attempt count is given in the message (<i>count</i>).
Action	No action is required for this informational message.
ART0705E	No commit/rollback listener
Explanation	An internal error has occurred.
Action	Contact your Software AG technical support representative for assistance.

ART0706E	Source message is null on commit
Explanation	An internal error has occurred.
Action	Contact your Software AG technical support representative for assistance.
ART0707E	Unsupported source type {type}
Explanation	An internal error has occurred.
Action	Contact your Software AG technical support representative for assistance.
ART0708E	Cannot open source capture file {fn}
Explanation	The file cannot be opened. Verify that the directory name exists.
Action	If the problem persists, contact your Software AG technical support representative.
ART0801I	Runtime metrics
Explanation	This message is the heading message for a series of runtime metric messages.
Action	No action is required for this informational message.
ART0802I	Resource key: {rkey}
Explanation	A resource key is listed in the message (<i>rkey</i>). Statistics about the resource are provided after the key.
Action	No action is required for this informational message.
ART0803I	Metrics key: {mkey}
Explanation	A metrics key is listed in the message (<i>mkey</i>). Metrics about the transaction identified by the metrics key are provided after the key.
Action	No action is required for this informational message.
ART0901E	Process request failed
Explanation	An Event Replicator Target Adapter process request failed. The source is shut down.
Action	Review any accompanying error messages to determine the cause of the problem. If the problem persists, contact your Software AG technical support representative.

ART0902I	Database active result: {result}
Explanation	The result of a test to see whether the database is active or not is listed in the message (<i>result</i>).
Action	No action is required for this informational message.
ART0903I	Retrying Database Transaction
Explanation	An attempt is in progress to retry the database transaction.
Action	No action is required for this informational message.
ART1001E	Exception cause: {cause}
Explanation	An Event Replicator Target Adapter process request failed. The cause of the failure is given in the message (<i>cause</i>).
Action	Contact your Software AG technical support representative for assistance.
ART1002E	Exception stack: {stack}
Explanation	An Event Replicator Target Adapter process request failed. The exception stack for the failure is given in the message (<i>stack</i>).
Action	Contact your Software AG technical support representative for assistance.
ART1005W	Unable to transform document
Explanation	The Event Replicator Target Adapter was unable to transform a document.
Action	No action is required for this warning message. Determine the reason for which the Event Replicator Target Adapter cannot transform the document and alter the conditions as necessary. Then try again.
ART1007W	An insert or update was received which occurred within an Initial State boundary
Explanation	An insert or update transaction message was received that falls within the boundaries of an ADARIS Initial State.
Action	This is a warning message informing of the situation described above. Followed by ART1008W or ART1009W if any action was taken with the message.
ART1008W	Insert changed to Delete Before Insert for file name: {file name} and time stamp: {time stamp}; Insert is within an Initial State boundary
Explanation	Warning that a record insert was changed to delete the record (if it exists) and insert the record in the current transaction. This can occur if an insert was processed during the user-defined ADARIS Initial State time boundaries for this file. The Initial State may have already picked up the new record. Avoids a Unique Key constraint error on the target.
Action	Check that the record is in sync with the Adabas source record.

ART1009W	ContinueOnSQLException dynamically turned on for file: {file name} and time stamp: {time stamp}; Update is within an Initial State boundary
Explanation	An update transaction was received that occurred during the user-defined ADARIS Initial State time boundaries for this file. The option Error Continue (<i>ContinueOnSQLException</i>) was dynamically turned on to avoid an SQL error on a record for which the update was already processed before the Initial State picked up the file.
Action	Check that the record is in sync with the Adabas source record.
ART1101I	File source configured for input directory: {dirname}
Explanation	A file source definition has been configured for the input directory listed in the message (<i>dirname</i>).
Action	No action is required for this informational message.
ART1102I	File source ready to receive data from: {dirname}
Explanation	A file source definition is ready to receive data from the directory listed in the message (<i>dirname</i>).
Action	No action is required for this informational message.
ART1103E	File source unable to get list of files
Explanation	A file source could not get a list of the files from the source.
Action	Determine why a list of files could not be obtained. Resolve the error and try again. If the problem persists, contact your Software AG support representative for assistance.
ART1104I	File source closing
Explanation	A file source is closing.
Action	No action is required for this informational message.
ART1105I	File source returning file: FILE: {dirname}-->{fn}
Explanation	The file source definition is returning the file source as part of the file source shutdown execution. The directory (<i>dirname</i>) and filename <i>fn</i>) are given in the message.
Action	No action is required for this informational message.

ART1106I	File source shutdown requested
Explanation	Shutdown of a file source was requested.
Action	No action is required for this informational message.
ART1107I	File source rollback called
Explanation	Rollback of the updates from a file source was called.
Action	No action is required for this informational message.
ART1108E	File source file does not exist {fn}
Explanation	The file source file named in the message (<i>fn</i>) does not exist. This is an internal message.
Action	Contact your Software AG technical support representative for assistance.
ART1109I	File source processing time for: {dirname}->{fn} is {num} MilliSeconds
Explanation	The processing time is given in the message for the file identified in the message.
Action	No action is required for this informational message.
ART1201I	Rollback following SQL commands
Explanation	A rollback occurred based on SQL commands.
Action	No action is required for this informational message.
ART1203W	File name not provided for operation: {op} FNR: {fnum} ISN: {isnnum}
Explanation	A file name was not provided for the operation listed in the message (<i>op</i>). The file (<i>fnum</i>) and ISN (<i>isnnum</i>) numbers are also listed in the message.
Action	No action is required for this informational message.
ART1204E	Test connection failed: {conn-name}
Explanation	A test connection to the connection listed in the message (<i>conn-name</i>) failed.
Action	Restart the database if it is down.
ART1205E	Cannot get a connection from the data source
Explanation	An attempt to connect to a data source failed.
Action	Review the data source definition and try again. If the problem persists, contact your Software AG technical support representative for assistance.

ART1206E	Cannot get metadata
Explanation	An attempt to connect to a data source failed.
Action	Review the data source definition and try again. If the problem persists, contact your Software AG technical support representative for assistance.
ART1207E	Exception obtaining table metadata: {tablename}
Explanation	An exception occurred while the Event Replicator Target Adapter was attempting to obtain metadata from a table. The name of the table is given in the message (<i>tblname</i>).
Action	Contact your Software AG technical support representative for assistance.
ART1208I	Process is continuing after the previous error
Explanation	Event Replicator Target Adapter processing is continuing in spite of a previously reported error condition.
Action	No action is required for this informational message.
ART1209I	Unable to locate table: {tablename}
Explanation	The Event Replicator Target Adapter could not locate the table listed in the message (<i>tablename</i>).
Action	No action is required for this informational message. If you really do need the Event Replicator Target Adapter to locate this table, determine why it cannot be located and try again. If the problem persists, contact your Software AG technical support representative.
ART1210I	Create index command built: {cmd}
Explanation	An internal command to create the index to a table was successfully built.
Action	No action is required for this informational message.
ART1211E	Cannot get connection to data source {name}
Explanation	An attempt to connect to the data source named in the message (<i>name</i>) failed.
Action	Verify that the database definitions are correct and that the database is active.
ART1212E	Cannot retrieve database metadata
Explanation	An attempt to retrieve metadata for the database failed.
Action	Contact your Software AG technical support representative for assistance.

ART1213E	Internal error of Sybase ASE
Explanation	An internal error occurred in Sybase ASE
Action	Contact your Software AG technical support representative for assistance.
ART1214W	Unknown data type {type} for column {colname} in metadata
Explanation	An attempt was made to specify the unknown data type listed in the message (<i>type</i>) in the column listed in the message (<i>colname</i>).
Action	Contact your Software AG technical support representative for assistance.
ART1215E	pkTableName {pkname} does not match with table name {tblname}
Explanation	A mismatch has occurred between the table and the primary key. The table name (<i>tblname</i>) and the primary key (<i>pkname</i>) are given in the message.
Action	Contact your Software AG technical support representative for assistance.
ART1216E	Cannot find previous column information
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1217F	Initial context is null
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1218F	Context lookup is null
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1219E	Unsupported driver class name for JDBC/database {dbname}
Explanation	An unsupported driver class name was specified for the JDBC database listed in the message (<i>dbname</i>).
Action	Contact your Software AG technical support representative for assistance.

ART1220E	Error obtaining connection {err-code}
Explanation	A connection to the database could not be made.
Action	Verify that the database definitions are correct and that the database is active.
ART1221E	Table {tblname} has duplicate column name {colname}
Explanation	The table named in the message (<i>tblname</i>) has two columns with the same name (<i>colname</i>).
Action	Change one of the column names and try again.
ART1222E	Cannot create statement
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1223E	Cannot connect to database {dbname}
Explanation	An attempt to connect to the database named in the message (<i>dbname</i>) failed.
Action	Verify that the database definitions are correct and that the database is active.
ART1224E	Cannot execute batch
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1225E	Cannot turn off database autocommit
Explanation	An attempt to turn off the autocommit feature of the database failed.
Action	Contact your Software AG technical support representative for assistance.
ART1226E	Cannot create executing SQL statement
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1227E	Process continuing because dbErrorContinue is TRUE
Explanation	The target database Error Continue option was set to "true" (selected or turned on), so the SQL error is ignored and processing continues.
Action	No action is required for this message.

ART1228E	Executing...{<processing information>}
Explanation	An SQL command either failed or executed successfully. The SQL command and details about its processing are given in the message (< <i>processing information</i> >). If an error occurred, and you have not selected the Error Continue option for the target database, the Event Replicator Target Adapter will stop running. For more information, read <i>Specifying Target Database Processing Option Definitions</i> in the <i>Event Replicator Target Adapter Administration Guide</i> .
Action	If the command failed, resolve the error described in the message. If necessary, contact your Software AG technical support representative for assistance.
ART1229E	Unable to load/construct DB support class for {classname}
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1230E	Update to insert mode is on but full image value is missing
Explanation	An attempt to insert an update failed because the full image of the record is missing from the database.
Action	Use Option=32 in the Event Replicator Server destination definition. For more information, refer to your Event Replicator for Adabas destination documentation.
ART1232E	Cannot insert column
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1233I	SQL command failed {cmd}
Explanation	The SQL command listed in the message (<i>cmd</i>) failed.
Action	Review other accompanying error messages to determine the cause of the problem. If the problem persists, contact your Software AG technical support representative for assistance.
ART1234I	SQL command reason {rsncode}
Explanation	The previous SQL command failed with the reason code (<i>rsncode</i>) given in the message.
Action	Review the documentation for your RDBMS to determine the cause of the problem.

ART1235W **Sync DDL value {val} is not one of the following values, ignore, warn, apply, error. Reset to ignore.**

Explanation The value for the **Adabas-RDBMS Synchronization Level** option is invalid. It has been reset to "ignore".

Action In the target database options, change the setting of the **Adabas-RDBMS Synchronization Level** option to something other than "ignore" if you want.

ART1236E **Cannot alter column {detailed-info}**

Explanation The Event Replicator Target Adapter could not alter the column described by the detailed information listed in the message (*detailed-info*) during its attempt to synchronize the RDBMS table with the Adabas file.

Action Make sure the target database supports this kind of type conversion and that this column is not a primary key and doesn't have foreign key. If the problem persists, contact your Software AG technical support representative for assistance.

ART1237W **Data type or length mismatch on column {detailed-info}**

Explanation During an attempt to synchronize the RDBMS table with the Adabas file, the Event Replicator Target Adapter determined that a data type or length mismatch had occurred for the column described by the detailed information listed in the message (*detailed-info*).

Action Issue the same message as the previous one. The Event Replicator Target Adapter will continue to run because the **Adabas-RDBMS Synchronization Level** value is set to "warn". If the problem persists, contact your Software AG technical support representative for assistance.

ART1238I **Alter column {detailed-info}**

Explanation The column described by the detailed information listed in the message (*detailed-info*) was altered in the RDBMS during Event Replicator Target Adapter synchronization between the RDBMS table and the Adabas file.

Action No action is required for this informational message.

ART1239I **Add column {detailed-info}**

Explanation The column described by the detailed information listed in the message (*detailed-info*) was added to the RDBMS during Event Replicator Target Adapter synchronization between the RDBMS table and the Adabas file.

Action No action is required for this informational message.

ART1240E	Cannot add column {detailed-info}
Explanation	The Event Replicator Target Adapter could not add the column described by the detailed information listed in the message (<i>detailed-info</i>) to the RDBMS during its attempt to synchronize the RDBMS table with the Adabas file.
Action	Make sure the target database supports adding columns. If the problem persists, contact your Software AG technical support representative for assistance.
ART1241W	Target database does not have column {detailed-info}
Explanation	During an attempt to synchronize the RDBMS table with the Adabas file, the Event Replicator Target Adapter determined that the target RDBMS is missing the column described by the detailed information listed in the message (<i>detailed-info</i>). This message is issued because the Adabas-RDBMS Synchronization Level value is set to "warn". In this case, the Event Replicator Target Adapter issues this warning message and continues processing.
Action	No action is required for this warning message.
ART1242E	Cannot find _INDEX as suffix of the PE table {tablename} primary key {key}
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1243W	Response code {nn} received for operation: {operation}
Explanation	The Event Replicator Target Adapter received an unexpected response code <i>nn</i> for the described <i>operation</i> .
Action	Please check the Replicator SYSOUT for further details.
ART1244I	Transaction {{number}} ignored as it has been previously processed.
Explanation	Transaction caching is active and the Event Replicator Target Adapter has attempted to process a transaction which has already been recorded as processes.
Action	Verify the integrity of the replicated data.
ART1245I	Transaction cache disabled.
Explanation	Informational message at startup notifying transaction caching is disabled. This is the default behavior.
Action	No action is required for this informational message.

ART1246I **Dynamically adjust flags (DeleteBeforeInsert, ContinueOnSQLException) during Initial State time stamp boundaries: ON**

Explanation Informational message displayed at startup, indicating enhanced ADARIS Initial State processing is active.

Action No action is required for this informational message.

ART1302I **Loader complete for {loader}**

Explanation The Event Replicator Target Adapter completed loading replicated data for the Oracle SQL Loader listed in the message without failing.

Action No action is required for this informational message.

ART1303E **Loader fail. Please check the log files {fn}**

Explanation An attempt to load replicated data to the database via the Oracle SQL loader failed. The log files (*fn*) that contain more information are listed in the message.

Action Review the log files for more information about the failure. If possible, correct the error and try again. If the problem persists, contact your Software AG technical support representative for assistance.

ART1304E **Loader exception**

Explanation An exception occurred during the loading process.

Action Contact your Software AG technical support representative for assistance.

ART1305E **Create table XML file {fn} does not exist**

Explanation A request to create the table in an XML file failed because the XML file could not be found. The filename of the XML file is given in the message (*fn*).

Action Contact your Software AG technical support representative for assistance.

ART1307E **Control file {fn} is not generated**

Explanation The control file listed in the message (*fn*) was not generated.

Action Contact your Software AG technical support representative for assistance.

ART1308E **Loader cannot support streaming mode**

Explanation The loader cannot support streaming mode.

Action Modify the target database options used by the database so that the **Use Stream** option is not selected (checked) and try again. For more information, read *Specifying Target Database Processing Option Definitions* in the *Event Replicator Target Adapter Administration Guide*.

ART1309E	Output file {fn} is not generated
Explanation	The output file named in the message (<i>fn</i>) was not generated.
Action	Contact your Software AG technical support representative for assistance.
ART1310I	Current configuration cannot support streaming mode; change to nonstreaming mode
Explanation	The current configuration does not support streaming mode. The Event Replicator Target Adapter turns stream mode off and retries the operation.
Action	No action is required for this informational message.
ART1311I	Current configuration cannot support loader mode; change to nonloader mode
Explanation	The current configuration does not support the database in loader mode.
Action	No action is required for this informational message.
ART1312I	Loader process running for {loader}
Explanation	The database loader process is running for the Oracle SQL Loader listed in the message.
Action	No action is required for this informational message.
ART1313I	Loader about to execute following command: {cmd}
Explanation	The database loader process is executing the command listed in the message (<i>cmd</i>).
Action	No action is required for this informational message.
ART1315I	Create loader thread
Explanation	An attempt by the Event Replicator Target Adapter to create a loader thread is in process.
Action	No action is required for this informational message.
ART1316E	Called with table: {tblname} column: {colname}
Explanation	An error occurred trying to call the table (<i>tblname</i>) and column (<i>colname</i>) whose names are listed in the message.
Action	Contact your Software AG technical support representative for assistance.

ART1318I	Initial-state running in loader mode
Explanation	The initial-state process is running in loader mode.
Action	No action is required for this informational message.
ART1319E	Cannot wait for loader process
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1320E	Cannot find control file name
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1321E	Cannot find log file name
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1322E	Cannot find bad file name
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1323E	Cannot find discard file name
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1324E	Cannot find out file name
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1325E	Create loader process failed
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.

ART1326I	Test loader process successful
Explanation	The test loader process completed successfully.
Action	No action is required for this informational message.
ART1327E	Test loader process failed, exit code {code}
Explanation	The test loader process failed with the exit code listed in the message (<i>code</i>).
Action	Contact your Software AG technical support representative for assistance.
ART1328E	Cannot create XsltWorker
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1329E	Cannot set up environment variables of file {fn}
Explanation	An attempt to set the environment variables for the file named in the message (<i>fn</i>) failed.
Action	Contact your Software AG technical support representative for assistance.
ART1330E	Cannot support current database type
Explanation	Support is not provided for the database type.
Action	Change the database type to one that is supported by the Event Replicator Target Adapter. If necessary, contact your Software AG technical support representative for assistance.
ART1331E	Worker is null
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1332E	Cannot create loader thread
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.

ART1333E	Cannot create piped stream
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1334E	Loader failed. Current mode is streaming mode, change to nonstreaming mode and retry
Explanation	The loader failed.
Action	Modify the target database options used by the database so that the Use Stream option is not selected (checked) and try again. For more information, read <i>Specifying Target Database Processing Option Definitions</i> in the <i>Event Replicator Target Adapter Administration Guide</i> .
ART1335E	Cannot write to output stream
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1336E	Parsing error {err} line {lll} column {ccc} PID {pid} CID {cid}
Explanation	A parsing error occurred. The error, line number, column number, process ID, and command ID are given in the message.
Action	Contact your Software AG technical support representative for assistance.
ART1337E	Unable to send message to the loader
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1338E	Cannot find base file name
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1339W	Current database cannot support streaming mode, reset to nonstreaming mode
Explanation	The current database does not support streaming mode. The Event Replicator Target Adapter has turned streaming mode off.
Action	No action is required for this warning message.

ART1340E	The child thread may end unexpectedly
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART1341E	Cannot find WebDAV
Explanation	The WebDAV file cannot be found.
Action	Contact your Software AG technical support representative for assistance.
ART1342E	Batch file {fn} does not exist
Explanation	The batch file named in the message does not exist.
Action	Contact your Software AG technical support representative for assistance.
ART1343W	The service name of the loader in the Target Database Options of a Teradata MLoad, {name}, has more than {num} characters. Using {xxxx} as the tdpid for this MLoad
Explanation	The service name of the loader during Teradata MLoad processing is too long. The Event Replicator Target Adapter is using the name <code>xxxx</code> for the tdpid of the MLoad processing.
Action	No action is required for this warning message.
ART1344W	The service name of the loader in the Target Database Options of a Teradata MLoad has not been informed. Attempting to use xxxx as the tdpid for ths MLoad
Explanation	The service name of the loader during Teradata MLoad processing has not been provided. The Event Replicator Target Adapter is trying to use the name <code>xxxx</code> for the tdpid of the MLoad processing.
Action	No action is required for this warning message.
ART1401I	Transform document using XSLT file: {fn} token: {token}
Explanation	The Event Replicator Target Adapter is attempting to transform the document using the XSLT file (<i>fn</i>) and token (<i>token</i>) listed in the message.
Action	No action is required for this informational message.
ART1402E	Cannot convert from UTF8 byte array to a string
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.

ART1501I	Source manager shutdown requested
Explanation	A request was made to shut down the source manager.
Action	No action is required for this informational message.
ART1502I	Source manager notified to shut down
Explanation	The source manager has been notified to shut down.
Action	No action is required for this informational message.
ART1503I	Waiting for source manager shutdown to complete
Explanation	The Event Replicator Target Adapter is waiting for the source manager to fully shut down.
Action	No action is required for this informational message.
ART1504I	Source manager is down
Explanation	The source manager shutdown has completed.
Action	No action is required for this informational message.
ART1601I	Engine manager shutdown requested
Explanation	A request was made to shut down the engine manager.
Action	No action is required for this informational message.
ART1602I	Engine manager notified to shut down
Explanation	The engine manager has been notified to shut down.
Action	No action is required for this informational message.
ART1603I	Waiting for engine manager shutdown to complete
Explanation	The Event Replicator Target Adapter is waiting for the engine manager to fully shut down.
Action	No action is required for this informational message.
ART1604I	Engine manager is down
Explanation	The engine manager shutdown has completed.
Action	No action is required for this informational message.

ART1701W	Parameter {parm} value {val} not numeric
Explanation	The parameter named in the message (<i>parm</i>) specifies a value (<i>val</i>) that is not numeric.
Action	Supply a numeric value for the parameter and try again.
ART1702W	Parameter {parm} value {val} does not end with "S"
Explanation	The parameter named in the message (<i>parm</i>) specifies a value (<i>val</i>) that does not end in an "S".
Action	Supply a value for the parameter that ends in an "S" and try again.
ART1703W	Parameter {parm} value {val} is not "true" or "false"
Explanation	The parameter named in the message (<i>parm</i>) specifies a value (<i>val</i>) that is not "true" or "false."
Action	Supply a "true" or "false" value for the parameter and try again.
ART1801E	Cannot open WebSphere MQ trace log file {fn}
Explanation	An attempt to open the WebSphere MQ trace file named in the message (<i>fn</i>) failed.
Action	Check your definition. Verify that the directory defined in your definitions exists.
ART1802E	WebSphere MQ rollback failed {err-code}
Explanation	A rollback attempt for WebSphere MQ failed.
Action	Review the webSphere MQ documentation to determine the reason for the failure.
ART1803E	WebSphere MQ logon failed host {hostid} port {portnum} error {err}
Explanation	An attempt to logon to WebSphere MQ failed. The WebSphere MQ host ID (<i>hostid</i>), port number (<i>portnum</i>), and the error number (<i>err</i>) from the attempt are given in the message.
Action	Check with your WebSphere MQ administrator to determine why the attempt failed. Resolve the problem and try again.
ART1804I	WebSphere MQ logon to host {hostid} successful
Explanation	The attempt to log onto the WebSphere MQ host named in the message (<i>hostid</i>) was successful.
Action	No action is required for this informational message.

ART1805I	WebSphere MQ receiving messages from queue {qname}
Explanation	WebSphere MQ is receiving and processing messages from the queue listed in the message (<i>qname</i>).
Action	No action is required for this informational message.
ART1806E	WebSphere MQ request failed
Explanation	A WebSphere MQ request failed.
Action	Check with your WebSphere MQ administrator to determine why the attempt failed. Resolve the problem and try again.
ART1807E	WebSphere MQ receive failed {err-code}
Explanation	A receive request via the WebSphere MQ queue failed.
Action	Check with your WebSphere MQ administrator to determine why the attempt failed. Resolve the problem and try again.
ART1808E	WebSphere MQ commit failed {err-code}
Explanation	A commit request via the WebSphere MQ queue failed.
Action	Check with your WebSphere MQ administrator to determine why the attempt failed. Resolve the problem and try again.
ART1809E	WebSphere MQ send failed {err-code}
Explanation	A send request via the WebSphere MQ queue failed.
Action	Check with your WebSphere MQ administrator to determine why the attempt failed. Resolve the problem and try again.
ART1810E	WebSphere MQ close failed {err-code}
Explanation	A close request via the WebSphere MQ queue failed.
Action	Check with your WebSphere MQ administrator to determine why the attempt failed. Resolve the problem and try again.
ART2001E	Required target configuration not found {config} or default
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.

ART2002E	Operation is null
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART2003E	Operation {opname} is not supported
Explanation	An attempt to run the operation named in the message (<i>opname</i>) failed because it is not supported.
Action	Try an operation that is supported.
ART2004E	Not SOAP element
Explanation	An internal error occurred.
Action	Contact your Software AG technical support representative for assistance.
ART3001E	Wrong factory type for {msgtype}. Type is {factype}.
Explanation	An attempt to use the wrong JMS factory type for the type of messaging specified. The message type (<i>msgtype</i>) and factory type (<i>factype</i>) are given in the message. Replicate the data to a JMS topic if you want to use publish-subscribe messaging; replicate the data to a JMS queue if you want to use point-to-point messaging.
Action	Verify the JMS target definition is specified correctly in the Event Replicator Target Adapter Administration tool. Contact your Software AG technical support representative for assistance.
ART3002E	Factory {factory} not found in the naming system.
Explanation	An attempt to access the JMS topic or queue connection factory in the system was not successful.
Action	Verify the JMS target definition is specified correctly in the Event Replicator Target Adapter Administration tool. Contact your Software AG technical support representative for assistance.
ART3003E	Error occurred while accessing factory {factory} in the naming system {system}.
Explanation	An error occurred attempting to access the JMS topic or queue connection factory named in the message in the system named in the message.
Action	Verify the JMS target definition is specified correctly in the Event Replicator Target Adapter Administration tool. Contact your Software AG technical support representative for assistance.

ART3004E	Wrong destination type for {jmsname}. Type is {factype}.
Explanation	An attempt to use the wrong type of destination was made when replicating data to JMS queues or topics. The JMS destination topic or queue name (<i>jmsname</i>) and the factory type (<i>factype</i>) are given in the message. Specify the destination as a JMS topic (as defined to webMethods Broker) if you want to use publish-subscribe messaging; specify the destination as a JMS queue (as defined to webMethods Broker) if you want to use point-to-point messaging.
Action	Verify the JMS target definition is specified correctly in the Event Replicator Target Adapter Administration tool. Contact your Software AG technical support representative for assistance.
ART3005E	Destination {dest} not found in the JNDI provider
Explanation	An internal error occurred. The destination specified in the JMS target definition was not found in the JNDI provider specified in the JMS target definition. The destination name is given in the message.
Action	Verify the JMS target definition is specified correctly in the Event Replicator Target Adapter Administration tool. Contact your Software AG technical support representative for assistance.
ART3006E	Error while accessing destination {dest}
Explanation	An internal error occurred. An error occurred during an attempt to access the destination specified in the JMS target definition.
Action	Verify the JMS target definition is specified correctly in the Event Replicator Target Adapter Administration tool. Contact your Software AG technical support representative for assistance.

47

ARVU* - Adabas Review Interface Messages

ARVU01	{dbid} GETMAIN failure, size={requested-getmain-size}, REVIEW parameter set to NO						
Explanation	ADARVU was unable to obtain the necessary GETMAIN space to operate. ADARVU terminates processing. It is probable that the specified region size is too small, or the default region size is too small. SIZE is the requested GETMAIN size that could not be obtained. The Adabas nucleus completes its initialization but no calls are made to the Adabas Review hub.						
Action	Increase the region size for Adabas and restart the nucleus. Under BS2000 increase/add the ADARUN parameter SUBMPSZ=140000000.						
ARVU02	{dbid} REVIEW HUB ID={ target-id} LOG RETD RSP {rsp} {dbid} REVIEW HUB ID= {target-id} CLS RETD RSP {rsp} {dbid} REVIEW HUB ID= {target-id} OPN RETD RSP {rsp}						
Explanation	A non-zero Adabas response was received from the Adabas Review hub with the specified target ID when ADARVU sent one of the following requests:						
	<table border="1"><tr><td>LOG</td><td>request to process a command log record.</td></tr><tr><td>CLS</td><td>close call to terminate monitoring services with the hub.</td></tr><tr><td>OPN</td><td>open call to establish monitoring services with the hub.</td></tr></table>	LOG	request to process a command log record.	CLS	close call to terminate monitoring services with the hub.	OPN	open call to establish monitoring services with the hub.
LOG	request to process a command log record.						
CLS	close call to terminate monitoring services with the hub.						
OPN	open call to establish monitoring services with the hub.						
Action	Identify the problem from the Adabas response code. If the problem is parameter settings in the hub, i.e., attached buffer size or command queue size, then the Adabas Review hub must be cycled to reset the parameters. If the Adabas response code 148 (ADARSP148) was received, the Adabas Review hub may have been terminated.						

ARVU03	{dbid} REVIEW REVIEW HUB ID {target-id} IS NOT A HUB SERVER
Explanation	The target ID specified on the REVIEW parameter is not an Adabas Review hub. The target may be another Adabas nucleus. The Adabas nucleus completes its initialization but no calls are made to the Adabas Review hub.
Action	Ensure that the REVIEW parameter specifies the correct target ID of an Adabas Review hub and restart the nucleus.
Action	The operator command REVIEWHUBID= <i>hub-id</i> may be used to change the value to a another target ID.
ARVU04	{dbid} REVIEW REVIEW HUB ID {target-id} IS NOT ACTIVE
Explanation	ADARVU received response code 148 (ADARSP148) on a request call to the Adabas Review hub. This message is displayed in conjunction with the AREV02 message.
Action	Start the appropriate Adabas Review hub.
ARVU05	{dbid} UEX5: REQUESTED WAIT FOR {nnnnn} SECONDS {dbid} UEX5: INVALID REQ ({xx}), IGNORE ASSUMED
Explanation	On any error condition, ADARVU calls user exit 5 if present. User exit 5 may return one of three possible service requests: <ol style="list-style-type: none"> 1. Wait for <i>nnnnn</i> seconds, after which ADARVU will resend the request to the Adabas Review hub. 2. Ignore the non-zero response received from the Adabas Review hub and to continue processing. 3. Immediately resend the request to the Adabas Review hub. <p>The message displays the service request received from the user exit 5. If an unknown request is received from the user exit, the request is ignored and processing continues.</p>
Action	None required, unless the fourth message is displayed. The INVALID REQ message indicates a problem with the user exit 5. Correct the problem and restart the Adabas nucleus, when possible.
ARVU06	{dbid} CHECK ADABAS MESSAGES AND CODES MANUAL
Explanation	This message is displayed in conjunction with the AREV02 message in the event that the non-zero response received by ADARVU is not a RSP 148.
Action	None required. This message is for your information only.

ARVU07	{dbid} Session open failure, module {module} could not be loaded, REVIEW set to NO
Explanation	The specified module was not found in the load library and could not be loaded. The Adabas nucleus completes its initialization but no calls are made to the Adabas Review hub.
Action	Ensure that the correct load libraries are specified for the Adabas job and restart the Adabas nucleus.
ARVU08	{dbid} NUMBER OF NON-ZERO RESPONSES FROM HUB IS {count}
Explanation	Whenever an unexpected response is received by ADARVU, the count of the number of non-zero responses is incremented and this message is displayed.
Action	None required. This message is for your information only.
ARVU09	{dbid} USER EXIT 5 {AVAILABLE UNAVAILABLE}
Explanation	During session initialization, ADARVU checks if a user exit 5 has been loaded. This message displays whether the user exit 5 was located or not.
Action	None required. This message is for your information only.
ARVU10	{dbid} REVIEW HUB {hub-id} VERSION V{nn} LOCATED
Explanation	During session initialization, ADARVU issues a call to the specified Adabas Review hub. When a successful connection is established, this message is displayed.
Action	None required. This message is for your information only.
ARVU11	{dbid} CHANGE ORDERS FROM REVIEW HUB {hub-id}
Explanation	The Adabas Review hub notified the client nucleus that it changed the monitoring or reporting status of the client nucleus. ADARVU then displays this message accompanied by the ARVU13 message set.
Action	None required. This message is for your information only.
ARVU12	{dbid} REVIEW HUB ID CHANGED FROM {hub-id} TO {hub-id}
Explanation	ADARVU detected that the hub-id specified in the REVIEW parameter was changed dynamically by an operator command.
Action	None required. This message is for your information only.

ARVU13

{dbid text}

Explanation

Possible message texts:

Message Text (<i>text</i>)	Description
{NO <i>count</i> } REVIEW REPORT(S) STARTED	In conjunction with the ARVU11 message, this message indicates the status of information transmitted from the client nucleus to the hub. If no Adabas Review report(s) are started, ADARVU does not send data to the hub. If there is at least one report started, then ADARVU transmits the command log data to the hub. <i>Action:</i> No action required. This message is for your information only.
{NO <i>count</i> } REPORTS REQUIRES BUFFERS	If at least one report requires buffers, ADARVU transmits the requested Adabas control buffer data in addition to the command log data. The <i>count</i> indicates the number of started reports and/or the number of reports requiring buffers. <i>Action:</i> No action required. This message is for your information only.
REVIEW HUB TRANSPORT INITIALIZED, MEMORY <i>mmmmmmmm</i>	BS2000: The hub started Adabas Review Transport with the memory <i>mmmmmmmm</i> . <i>Action:</i> No action Required. This message is for your information only.
RTPINIT, CANNOT GET HEADER, SIZE <i>sssssss</i> , MEMORY <i>mmmmmmmm</i>	BS2000: The hub cannot acquire an Adabas Review Transport header of size <i>sssssss</i> using memory <i>mmmmmmmm</i> . <i>Action:</i> Check memory allocation parameters in use in the Adabas Review Hub. Otherwise contact SAG Support.
RTPINIT, COULD NOT ESTABLISH EXIT FOR RTPTERM - RC <i>rrrrrrrr</i>	BS2000: The RTPTERM exit module could not be established in the Hub's task. <i>Action:</i> Send Hub output protocol to SAG Support.
RTPINIT, REVIEW HUB COULD NOT BE FOUND IN IDT	BS2000: The hub has not successfully registered with the ID Table. The IDT is a table of databases or nodes still active in the system. <i>Action:</i> Check in the output protocol for other error messages from the Adabas MPM. Otherwise contact SAG support.
RTPSSPC, HEADER HAS <i>xxxxxxx</i> AND DBID <i>ddddddd</i>	BS2000: The stored Adabas Review Transport header has an ID that is different from the one in the request. This header exists in a common memory pool and should

Message Text (<i>text</i>)	Description
	<p>have an eyecatcher of ADAPCTRA and the Hub's dbid. This doesn't check.</p> <p><i>Action:</i> Contact Software AG Support with dump and protocol information.</p>
RTPSSPC, REVIEW HUB COULD NOT BE FOUND IN IDT	<p>BS2000: The nucleus tried to access a hub with a DBID that is unknown to the system. The IDT is a table of databases or nodes still active in the system.</p> <p><i>Action:</i> Use the Utility IDTLOOK to check for active IDs in the table. Check also on the use of the GROUPS=NO/YES parameter. Otherwise, contact SAG support.</p>
RTPSSPC, REVIEW HUB <i>hubid</i> HAS BEEN REMOVED FROM THE IDT	<p>BS2000: The hub ID requested is no longer active.</p> <p><i>Action:</i> Use the Utility IDTLOOK to check for active IDs in the table. Check also on the use of the GROUPS=NO/YES parameter. Otherwise contact SAG support.</p>
THE FOLLOWING BUFFER TYPES ARE REQUIRED: <i>buffer-type-codes</i>	<p>If buffers are required, the required buffer types are listed in the message. The possible buffer type codes can be F (format buffer), R (record buffer), S (search buffer), V (value buffer), M (multifetch buffer), or I (ISN buffer).</p> <p><i>Action:</i> Verify that the correct buffers are specified. Otherwise, no action is required for this informational message.</p>
TRANSPORT INITIALIZED, MEMORY <i>mmmmmmmm</i>	<p>BS2000: The nucleus accessed the hub through the Adabas Review Transport and uses the common memory defined by mmmmmmmmm.</p> <p><i>Action:</i> No action required. This message is for your information only.</p>

ARVU16**{dbid} REVIEW IS ACCEPTING BUFFERED CLOG RECORDS****Explanation**

The Adabas Review hub accepts buffered CLOG records from the client nucleus as a way of reducing the number of cross-memory calls from the client nucleus to the hub.

Action

None required. This message is for your information only.

ARVU17	{dbid} REVIEW IS NOT ACCEPTING BUFFERED CLOG RECORDS
Explanation	The Adabas Review hub is not accepting buffered CLOG records from the client nucleus.
Action	Check the job log of the Adabas nucleus and the Adabas Review hub, why the Adabas Review hub refuses to accept buffered CLOG records.
ARVU18	{dbid} REVIEW TRANS-PORT IS INSTALLED USING PC {pc-number}
Explanation	z/OS only. The Adabas nucleus runs with the Adabas Review Trans-port feature when sending CLOG records to the Adabas Review hub.
Action	None required. This message is for your information only.
ARVU19	{dbid} REVIEW TRANS-PORT IS NOT INSTALLED
Explanation	BS2000 and z/OS only. The Adabas Review Trans-port feature is not installed.
Action	If this Adabas nucleus should run with the Adabas Review trans-port feature, check the job log of the Adabas nucleus and the job log of the Adabas Review hub why trans-port is not installed.
ARVU20	{dbid} REVIEW MODULES NOT FOUND, LOGCLEX PARAMETER IS SET TO NO
Explanation	ADARUN LOGCLEX=YES has been specified, but no Adabas Review modules are available. The Adabas nucleus changed the LOGCLEX parameter to ADARUN LOGCLEX=NO. The extended information is made available for the purpose of running Adabas Review in batch mode.
Action	Please make the Adabas Review modules available in the STEPLIB.
ARVU21	{dbid} ADAIOR REQUEST FAILED: FUNC {ff} RSP {rr}
Explanation	A request to the Adabas ADAIOR interface by the Pulse failed.
Action	Retain all dumps, messages, and other related information; contact your Software AG technical support representative.
ARVU22	{dbid} GETMAIN FAILED: INSUFFICIENT STORAGE
Explanation	A request for storage by the Pulse failed. The report is not started.
Action	Increase the region size for Adabas and restart the nucleus.

ARVU23**{dbid} INTERNAL ERROR IN {module}, subcode {n}****Explanation**

An internal error has occurred in the given Pulse module. The report is not started.

In the Pulse modules ADAPMT, ADAPSM, and ADAPST a sub code is issued:

Module	Subcode	Explanation
ADAPMT	1	Operating system erroneously VM/ESA.
ADAPMT	2	Operating system erroneously BS2000.
ADAPSM	1	ADAPLRPL work area is missing.
ADAPSM	2	The Pulse extension in CLEX is missing.
ADAPST	1	SVC number is zero. Action: Check SVC numbers in Reports.
ADAPST	2	A'ADAPCS is missing. Action: Check whether module ADAPCS is available.
ADAPST	3	A'ADAPCS is missing. Action: Check whether module ADAPCS is available.
ADAPST	4	The eye catcher in the buffer is neither 'TIMC' nor 'TERM' nor 'RSTR'.
ADAPST	5	A'ADAPCS is missing. Action: Check whether module ADAPCS is available.
ADAPST	6	A'ADAPCS is missing. Action: Check whether module ADAPCS is available.

In ADAPCS no sub code is issued.

Action

Retain all dumps, messages, and other related information; contact your Software AG technical support representative.

ARVU24**{dbid} CLUSTER SERVICES NOT ACTIVE****Explanation**

The Pulse has determined that Cluster Services statistics reporting is not possible. The report is not started.

Action

Ensure that Cluster Services is active.

ARVU25	{dbid} ADABAS rspcode {rrrrr} subcode {sssss} returned from DBID {dbid} NUCID {nucid}
Explanation	The Pulse has encountered the given Adabas non-zero response code and subcode. The report is deactivated.
Action	Identify the problem from the Adabas response code and subcode.
ARVU26	{dbid} PULSE ESTAE DRIVEN, RETRY IN PROGRESS
Explanation	The Pulse subtask has encountered an error and will attempt to recover.
Action	None.
ARVU27	{dbid} PULSE RECOVERY ATTEMPT FAILED
Explanation	The Pulse subtask attempt at error recovery failed. The report is deactivated.
Action	Retain all dumps, messages, and other related information; contact your Software AG technical support representative.
ARVU28	{dbid} Pulse task failed to attach
Explanation	The Pulse subtask could not be attached. The report is deactivated.
Action	Retain all dumps, messages, and other related information; contact your Software AG technical support representative.
ARVU29	{dbid} Pulse task now {active inactive}
Explanation	The Pulse has stopped or started.
Action	None.
ARVU30	{dbid} Invalid Pulse interval, default used
Explanation	The Pulse detected an invalid timer interval. The acceptable range is from 1 to 1440 minutes. The default interval of 15 minutes is used.
Action	Restart the report with a valid timer value.
ARVU31	{dbid} Pulse ended due to non-zero RSP codes
Explanation	The Pulse detected three non-zero Adabas response codes. The report is deactivated.
Action	Correct the cause of the non-zero response codes and restart the report.

ARVU33	{dbid} REVIEW hub CPU id different.
Explanation	This message is issued when the CPU ID of the Adabas nucleus and the CPU ID of the Adabas Review hub are different. When this happens, CLOG records to the Adabas Review hub cannot be sent via the Trans-port PC call, but must be sent via the Adabas router. The performance of the Adabas router sending mechanism is slower than the performance of Trans-port.
Action	No action is required for this informational message.
ARVU34	{dbid} REVIEW = ADABAS DBID not allowed. REVIEW = NO set.
Explanation	The ADARUN parameters DBID and REVIEW specify equivalent DBID values. The REVIEW parameter is set to NO.
Action	Specify the correct REVIEW parameter. This can be done online.
ARVU36	{dbid} Review local mode initialization failed, REVIEW set to NO.
Explanation	Review Local mode has been disabled due to an error when initializing Review. A preceding message will identify the specific error.
Action	Correct the error and restart the nucleus. In some cases it may be possible to use operator commands to assign the nucleus to a Review Hub.
ARVU38	{dbid} REVIEW record filtering started. {dbid} REVIEW record filtering stopped. {dbid} Records processed: {nnnnnnnnnn} {dbid} Records filtered: {nnnnnnnnnn}
Explanation	The status of record filtering has changed. When filtering is stopped, the number of command log records processed thus far by the filter is printed, as well as the number of records filtered from Review processing.
Action	None required. This message is informational only.
ARVU41	{dbid} BUFFER IGNORED
Explanation	Every field which could be processed by REVIEW has an indication (or attribute) whether a particular Adabas buffer (FB, RB, SB, VB, IB, MB, PB) is necessary for REVIEW to process this field. These indications (or attributes) are gathered for each report running and the indications (or attributes) for all running reports are gathered and Adabas is informed which Adabas buffers are requested by REVIEW. When Adabas sets up a command log record for REVIEW, it checks these indications in order to build the command log record with or without a particular Adabas buffer. During this process Adabas (ADARVU) checks whether the length of the actual Adabas buffer confirms the ADARUN parameter REVLOGMAX. If the value is violated the first time, the ARVU41 message is issued.
Action	Buffers are ignored. If necessary increase the value of REVLOGBMAX or deselect fields which require Adabas buffers.

ARVU42	dbid REVIEW HUB {hub-id} VERSION V{nn} NOT SUPPORTED
Explanation	During session initialization, ADARVU issues a call to the specified Adabas Review hub, running with version <i>Vnn</i> . This version is not supported; the version number is either too low or too high. The handshake command to the hub did not work, so Adabas Review will not collect any data.
Action	Start the Adabas Review hub with the appropriate version. For information about version compatibility, read <i>Adabas and Adabas Review Version Compatibility</i> , in the <i>Adabas Review Release Notes</i> .
ARVU43	{dbid} Storage keys of nucleus and hub are different.
Explanation	The storage keys of the Adabas nucleus and of the Adabas Review hub are different. Both address spaces must run under storage keys 0 or storage keys 8.
Action	Start Adabas nucleus and Adabas Review hub under the same key, i.e. storage key 0 or storage key 8.
ARVU45	{dbid} ADABAS REVIEW Main Task Statistics {dbid} Hub mode log records {n,nnn,nnn,nnn} {dbid} Local mode log records {n,nnn,nnn,nnn} {dbid} Log record filtering {dbid} Records processed {n,nnn,nnn,nnn} {dbid} Records filtered {n,nnn,nnn,nnn} {dbid} Largest log record {nn,nnn} {dbid} Successful Hub calls {n,nnn,nnn,nnn} {dbid} Unsuccessful Hub calls {n,nnn,nnn,nnn} {dbid} Storage keys of nucleus and hub are different.
Explanation	This message displays shutdown statistics for the Adabas Review components in the Adabas nucleus. ADARVU reports: <ul style="list-style-type: none">■ The number of log records processed while in Hub mode■ The number of log records processed while in Local mode■ The number of log records processed while record filtering was active■ The number of log records filtered from Review processing■ The size (in bytes) of largest log record■ The number of successful calls and Trans-Port sends to the Review Hub■ The number of unsuccessful calls and Trans-Port sends to the Review Hub
Action	None required. This message is informational only.

ARVU46	{dbid} REVIEW local mode closed now
Action	None required. This message is for your information only.
ARVU48	{dbid} Connection established with Hub {target-id}
Explanation	A handshake with the Hub completed successfully.
Action	None required. This message is for your information only.
ARVU49	{dbid} Internal error at {module X'offset}
Action	Notify your Software AG technical support representative.
ARVU50	{dbid} Connection to REVIEW Hub {target-id} has been lost
Explanation	The Hub is no longer active.
Action	If the Hub is remote from the nucleus, check the Net-Work connectivity. Restart the Hub, select another Hub, or change to LOCAL mode.
ARVU51	{dbid} Connection to REVIEW Hub {target-id} has been restored
Action	None required. This message is for your information only.
ARVU53	{dbid} Hand shake from indefinable source ignored {dbid} Hand shake from HubID={target-id} received [via NucId={nucleus ID}]
Explanation	The first form is issued when a Handshake message is not properly formatted. The second form is issued when a valid handshake message is received. The second segment of the second form is not issued when the Nucleus received the handshake directly from the Hub. The second segment indicates the handshake was forwarded from the nucleus that received the handshake directly from the Hub
Action	For the first form, check the target IDs of the Hub and other servers for conflicts. No action required for the second form. This message is for your information only.
ARVU54	{dbid} REVIEW Hub={target-id} has closed connection
Explanation	The Review Hub has disconnected from the nucleus as a result of an operator command or stopping the Hub.
Action	None required. This message is for your information only.

48

ARXM* - Event Replicator for Adabas Messages for Event

Replicator Target Adapter

ARXML001I	XML TA Exit Startup for {dest-name} - Version {n.n.n.n} Built: {yyyymmdd}
Explanation	Event Replicator Target Adapter initialization processing for destination <i>dest-name</i> has been started. The Event Replicator Target Adapter version (<i>n.n.n.n</i>) and the date (<i>yyyymmdd</i>) the Event Replicator Target Adapter code was built are also given in the message.
Action	No action is required for this informational message.
ARXML002I	XML TA Exit {dest-name} Terminating
Explanation	Event Replicator Target Adapter termination processing for destination <i>dest-name</i> has been started.
Action	No action is required for this informational message.
ARXML003I	Destination {dest-name} now active for {jobname}
Explanation	Event Replicator Target Adapter processing for destination <i>dest-name</i> has been activated. The job name (<i>jobname</i>) of the Event Replicator Server is also given in the message.
Action	No action is required for this informational message.
ARXML004I	Received {code} event for {dest-name}
Explanation	Event Replicator Target Adapter processing received the internal event code (<i>code</i>) listed in the message for destination <i>dest-name</i> .
Action	No action is required for this informational message.

ARXML005S	Required field table information missing for subscription {subs-name}
Explanation	Required field table information was missing for subscription <i>subs-name</i> during Event Replicator Target Adapter processing. This information is required for building the XML messages used in Event Replicator Target Adapter processing.
Action	<p>Verify that you have <i>generated</i> a global format buffer (GFB) for the subscription. If you do not <i>generate</i> a global format buffer using the tools provided in the Adabas Event Replicator Subsystem or if you elect to code a GFB by hand, the required field table information is not constructed for use by the Event Replicator Target Adapter. For more information, read <i>Generating a GFB using the Adabas Event Replicator Subsystem</i>, in <i>Adabas Event Replicator Subsystem User Guide</i>.</p> <p>For more information about correctly activating Event Replicator Target Adapter processing, read <i>Activating Event Replicator Target Adapter Processing</i>, in <i>Event Replicator Target Adapter User Guide</i>.</p> <p>If the problem persists, contact your Software AG support representative.</p>
ARXML006I	Schema generation for {subs-name} triggered
Explanation	An internal schema is being generated by Event Replicator Target Adapter, based on the field information provided in subscription <i>subs-name</i> . This internal schema maps the replicated data that the Event Replicator Target Adapter then transforms and applies to your relational database.
Action	No action is required for this informational message.
ARXML008S	Unsupported code page={acode}, default to CP037 Subscription={subname}, DBID={dbid}, FNR={fnr}
Explanation	<p>The code page (<i>acode</i>) listed in the message for the subscription (<i>subname</i>), DBID (<i>dbid</i>), and FNR (<i>fnr</i>) is not supported.</p> <p>Code page Cp037 will be used for the XML tags and as the code page identifier sent to Event Replicator Target Adapter. Event Replicator Target Adapter will process the data as if it were code page 37, so the data loaded into the RDBMS table(s) may be corrupted. This message is displayed once per combination of incompatible subscription, DBID, file, and code page values.</p>
Action	<p>If use of code page Cp037 is valid, no action is required for this message.</p> <p>However, if use of code page Cp037 is invalid, you will also want to verify that the data in your RDBMS table is not corrupted and correct it if it is. Then specify the correct code page in the SACODE parameter and try again.</p>

ARXML020I	No Subscription Prefix Set for destination {xxxxxxx}
Explanation	The DCLASSPARM NOSPRE was specified for destination xxxxxxxx. This indicates you do not want the subscription name to prefix the names of the tables produced by the Event Replicator Target Adapter.
Action	No action is required for this informational message.
ARXML021I	Subscription Prefix = {xxxxxxx} for destination {xxxxxxx}
Explanation	The DCLASSPARM SPRE=xxxxxxx was specified for destination xxxxxxxx. This indicates you wish to use xxxxxxxx, (xxxxxxx is 1 to 8 characters), as the subscription name to prefix the names of the tables produced by the Event Replicator Target Adapter.
Action	No action is required for this informational message.
ARXML022I	NOSPRE and SPRE are mutually exclusive SPRE (subscription prefix) will be used for destination {xxxxxxx}
Explanation	The NOSPRE and SPRE=xxxxxxx parameters were both specified and are mutually exclusive. The SPRE=xxxxxxx takes precedence and will be used for the destination xxxxxxxx.
Action	No action is required for this informational message, unless you wish to change the option that is in effect.
ARXML023I	OPTIONS 32 and 128 are mutually exclusive OPTIONS 32, full image on update will be used for destination {xxxxxxx}
Explanation	OPTIONS 32 and 128 were both specified and are mutually exclusive. OPTIONS=32 full image on update takes precedence and will be used for the destination xxxxxxxx.
Action	No action is required for this informational message, unless you wish to change the option that is in effect.
ARXML024W	Subscription {xxxxxxx} optimized GFB {xxxxxxx} PE group {xx} field count > PE occurrence range count MU field {xx} requests occurrences equal to range count All occurrences beyond range count are unavailable
Explanation	The Subscription xxxxxxxx uses optimized GFB xxxxxxxx. This GFB contains PE group xx for which the PE group field count exceeds the to range value for the MU field xx contained within it. When the GFB/GFFT is generated any MU's contained within a PE use the to range count value to specify the MU occurrences within the PE. E.g. if PE range count was 5 and the MU field was AB, then the GFB would request AB1C,AB1(1-N),AB2C,AB2(1-N),AB3C,AB3(1-N),AB4C,AB4(1-N), AB5C,AB5(1-N).

If the PE count field was 7 AB6C,AB6(1-N),AB7C,AB7(1-N) fields will not be in the record buffer, so if they contain values, these values will not be sent to the Event Replicator Target Adapter destination.

Action

This is a warning message. The GFB should be regenerated using a PE to range value large enough to generate the MU xx fields for the largest possible number of PE occurrences.

49

ATM* - Adabas Transaction Manager Messages

ATM000_FF	NO TEXT
Explanation	One of the following occurred: <ul style="list-style-type: none">■ an unexpected error■ an error created intentionally by zap.
Action	If the error was unexpected, contact your Software AG support representative.
ATM001_20	ADABAS VERSION NOT SUPPORTED BY ATM
Explanation	The Adabas Transaction Manager cannot be used with this version of Adabas.
Action	Use a version of Adabas that ATM supports.
ATM002_20	ATM DATABASE OP FAILED, RSP/SUBCODE {rsp/subcode}
Explanation	The ATM recovery database failed to open for the reason indicated.
Action	Correct the cause of the response code and restart the ATM transaction manager.
ATM003_20	UNABLE TO LOAD {module-name}
Explanation	The named module could not be loaded.
Action	Ensure that the module is in a library from which it can be loaded dynamically.

ATM005_20	Error reading TM controls; RSP/SUB: {rsp/sub}
Explanation	An unexpected response code was encountered during reading of the TM controls from the configuration file.
Action	If the cause of the error is not clear from the description of the response code, report the details to your Software AG support representative.
ATM007_20	COR GROUP ALREADY HAS MANAGER: {manager}
Explanation	The ATM manager indicated in the message is already active locally in the local COR group. It is not possible to have more than one ATM transaction manager associated with the same COR group and executing in the same location (that is, under the same Adabas ID table, or Adabas SVC).
Action	Do not attempt to run more than one ATM transaction manager under the same ID table and associated with the same COR group.
ATM010_20	GENERAL GETMAIN FAILED
Explanation	ATM was unable to acquire enough storage to initialize.
Action	Increase the amount of memory available to the job and restart it.
ATM012_20	UNABLE TO ACQUIRE STORAGE FOR {area-name}
Explanation	ATM was unable to acquire enough storage for the area named.
Action	Increase the amount of memory available to the job and restart it.
ATM013_20	INITIALIZATION ERROR. FUNCTION/RF: {function/rf}
Explanation	An error occurred during the initialization of an interface to an external transaction coordinator.
Action	Check the documentation for the external transaction coordinator being used to determine the meaning of the return code (value <i>rf</i>). If the cause of the problem is still not apparent, contact your Software AG support representative, noting the values of <i>function</i> and <i>rf</i> .
ATM014_20	RRMS LOGNAME CHECK FAILED
Explanation	This message relates to the initialization of the ATM interface with RRMS. The ATM node ID has changed since ATM was last used with this RRMS system.
Action	The node ID of the Adabas System Coordinator daemon within which the ATM transaction manager is running as a service must not be changed while there are global transactions in progress. If you have changed the Node ID and are sure that there were no incomplete global transactions, you can override this initialization error using the parameter <code>TMRESTART=FORCE</code> .

ATM015_10	RRMS LOGNAME INCONSISTENCY OVERRIDDEN
Explanation	This message relates to the initialization of the ATM interface with RRMS. The node ID of the Adabas System Coordinator daemon within which the ATM transaction manager is running as a service has changed since ATM was last used with this RRMS system. However, the inconsistency was ignored because of the setting of the parameter <code>TMRESTART</code> .
Action	None. This message is for information only.
ATM016_20	RRMS HAS LOST HARDENED RESTART DATA
Explanation	This message relates to the initialization of the ATM interface with RRMS. Because RRMS has lost some restart data, integrity cannot be guaranteed for incomplete transactions that were under the control of RRMS.
Action	If it is not possible to recover the RRMS restart data, you can use the parameter <code>TMRESTART</code> to force the ATM transaction manager to initialize. Details of any incomplete transactions are then transferred to the STJ file and can be examined using the <code>SYSATM</code> application.
ATM017_20	FAILED TO OPEN ATMLOG. RC/RF:{rc/rf}
Explanation	The ATM transaction manager was unable to open the <code>ATMLOG1</code> or <code>ATMLOG2</code> dataset.
Action	Check the definition of the <code>ATMLOG1/2</code> datasets. If the cause of the error is not apparent, report the problem to your Software AG support representative, noting the values of <code>rc</code> and <code>rf</code> .
ATM018_20	Unexpected behavior for node {dbid}
Explanation	The node (<i>dbid</i>) is expected to be an Adabas System Coordinator daemon within which an ATM transaction manager is running as a service, but its behavior is not consistent with this.
Action	Check the indicated node.
ATM019_20	RRS IS NOT ACTIVE; ATM WILL WAIT AND RETRY
Explanation	This message relates to the initialization of the ATM interface with RRMS. Initialization cannot complete because the RRS component of RRMS is not available.
Action	Report the problem to your systems programming staff. The ATM transaction manager cannot initialize until RRS is active again.

ATM020_04	RRS EXITS HAVE BEEN SET
Explanation	If the ATM transaction manager is started with the parameter <code>TMSYNCMGR=RRMS</code> , this message is issued when the ATM RRMS interface has been initialized.
ATM021_08	RRS RESTART FINISHED
Explanation	If the ATM transaction manager is started with the parameter <code>TMSYNCMGR=RRMS</code> , this message is issued when ATM transaction manager finishes telling RRS how to handle any transactions that previously failed to complete.
ATM023_04	ISN: {isn}
Explanation	This message is preceded by message ATM025 or ATM033. It indicates the ISN associated with the error.
Action	Refer to the explanation of the previously issued message.
ATM024_10	ERROR DURING DB RESTART; ID/ERR: {dbid/error-code}
Explanation	The error (<i>error-code</i>) occurred during restart processing for the database (<i>dbid</i>).
Action	Refer to the descriptions of the possible error codes . If the cause of the error is not clear, report the details to your Software AG support representative, noting the values of the variables.
ATM025_10	ERROR IN ATM RESTART; ID/RSP/SUB/CMD: {dbid/rsp/sub/cmd}
Explanation	An unexpected response code (<i>rsp</i>) was encountered during restart processing for the ATM transaction manager (<i>dbid</i>). The response code, subcode (<i>sub</i>), and command code (<i>cmd</i>) are provided. An ATM023 message may follow, providing an associated ISN.
Action	If the cause of the error is not clear from the description of the response code, report the details to your Software AG support representative, noting the values of the variables.
ATM026_10	ERROR DURING ATM RESTART; ID/ERR: {dbid/error-code}
Explanation	The error (<i>error-code</i>) occurred during restart processing for the partner ATM transaction manager (<i>dbid</i>).
Action	Refer to the descriptions of the possible error codes . If the cause of the error is not clear, report the details to your Software AG support representative, noting the values for the variables.

ATM027_10	ATM RESTART. MAX PARTNERS EXCEEDED. USER {userid}
Explanation	<p>The maximum number of partner ATM transaction managers indicated by the parameter TMNODES is not sufficient to perform restart processing for incomplete transactions.</p> <p>The error occurred while ATM was attempting restart processing for the user whose Client ID is <i>userid</i>. This message is followed by an ATM087 message providing the user's 28-byte Communication ID.</p> <p>The transaction manager continues to execute, but cannot complete restart processing for transactions affected by the error.</p>
Action	Set the TMNODES parameter and restart the ATM transaction manager.
ATM028_10	DB RESTART. MAX TARGETS EXCEEDED. USER {userid}
Explanation	<p>ATM is unable to perform restart processing for an incomplete transaction because the number of databases involved in the transaction exceeds the maximum possible.</p> <p>The error was detected while ATM was attempting restart processing for the user whose Client ID is <i>userid</i>. This message is followed by an ATM087 message providing the user's 28-byte Communication ID.</p> <p>The transaction manager continues to execute, but cannot complete restart processing for transactions affected by the error.</p>
Action	Contact your Software AG support representative.
ATM029_10	PARTNER/DB RESTART ABORTED; ID/ERR: {dbid/error-code}
Explanation	<p>The error indicated occurred during restart processing associated with the database or ATM identified by <i>dbid</i>.</p> <p>The transaction manager continues to execute, but cannot complete restart processing for transactions affected by this error.</p>
Action	Refer to the descriptions of the possible error codes . If the cause of the error is not apparent, report the details to your Software AG support representative, noting the error code.
ATM030_10	ERROR DURING TRAN RESTART; ID/ERR//COMMID: {dbid/error-code}
Explanation	<p>The error indicated occurred during restart processing for an incomplete transaction. The database associated with the error is identified by <i>dbid</i>.</p> <p>The message is followed by an ATM032 message giving the Client ID of the transaction's owner, and an ATM087 message giving the user's 28-byte Communication ID.</p>
Action	Refer to the descriptions of the possible error codes . If the cause of the error is not apparent, report the details to your Software AG support representative, noting the error code.

ATM031_10	ERROR DURING BRANCH RESYNC; ID/ERR//COMMID: {dbid/error-code}
Explanation	The error indicated occurred while ATM was attempting to synchronize restart for an incomplete transaction branch with a partner ATM transaction manager. The partner transaction manager associated with the error is identified by <i>dbid</i> . The message will be followed by an ATM032 message giving the Client ID of the transaction's owner, and an ATM087 message giving the user's 28-byte Communication ID.
Action	Refer to the descriptions of the possible error codes . If the cause of the error is not apparent, report the details to your Software AG support representative, noting the error code.
ATM032_10	RESTART ERROR FOR USER {userid}
Explanation	This message refers to a previous error message and gives the Client ID of the user associated with the previous error.
Action	Refer to details for the preceding message.
ATM033_10	ERROR DURING DB RESTART; ID/RSP/SUB/CMD: {dbid/rsp/sub/cmd}
Explanation	An unexpected response code was encountered during restart processing for database <i>dbid</i> . The response code, subcode, and command code are provided. An ATM023 message may follow, providing an associated ISN.
Action	If the cause of the error is not clear from the description of the response code, report the details to your Software AG support representative, noting the value of the variables.
ATM034_10	Register failure for {xxxxx}: DB/rsp/sub/RC: {dbid/rsp/sub/cmd}
Explanation	An unexpected condition was encountered when the transaction manager attempted to register an event with the SYSCO daemon. The type of event is identified by <i>xxxxx</i> .
Action	Please contact your Software AG support representative, noting the values of the variables given in the message.
ATM036_08	Transaction Manager initialization started
Explanation	This message appears during the initialization of an ATM transaction manager, and indicates that initialization of the transaction manager's environment has started.
Action	None. This message is for information only.

ATM037_08	COR GROUP/DAEMON: {group/jobname}
Explanation	This message is issued by an ATM transaction manager at the end of its initialization process. It identifies the Adabas System Coordinator group that the transaction manager is associated with, and the job name of its COR daemon.
Action	None. This message is for information only.
ATM038_00	FURTHER RESTART ERROR MESSAGES WILL BE SUPPRESSED
Explanation	This message is issued during ATM restart when the transaction manager has issued 100 error messages. It indicates that any further errors encountered during the restart process will be suppressed.
Action	None. This message is for information only.
ATM039_04	TRANSACTION RESTART NOT POSSIBLE FOR DB {dbid}
Explanation	This message is preceded by message ATM025. It indicates that serious errors prevent the transaction manager from restarting affected transactions.
Action	Correct the error reported in the ATM025 message; then restart the database indicated in the message.
ATM040_00	TRANSACTION RESTART DEFERRED FOR INACTIVE DB {dbid}
Explanation	This message might be issued during an transaction manager's restart processing. Incomplete transactions exist that involve the database indicated. It is not possible for the transaction manager to resolve them because the database is not available.
Action	This message is for information only. Restart processing for such transactions occurs when the indicated database is restarted.
ATM041_00	TRANSACTION RESTART DEFERRED FOR INACTIVE NODE {dbid}
Explanation	This message might be issued during an transaction manager's restart processing. Incomplete transactions exist that involve the partner transaction manager indicated by <i>dbid</i> . It is not possible for the TM to resolve them because the partner TM is not active.
Action	This message is for information only. Restart processing for such transactions occurs when the indicated TM is restarted.
ATM042_10	NUMBER OF WARNING MESSAGES SUPPRESSED: {count}
Explanation	This message is issued by an ATM transaction manager at the end of restart processing if the number of error messages during restart processing exceeded 100.
Action	This message is for information only.

ATM043_04	TRANSACTIONS COMPLETED DURING RESTART: {count}
Explanation	This message is issued by an ATM transaction manager at the end of restart processing. It indicates the number of previously incomplete transactions that were completed (by completing the commit process) during ATM restart processing.
Action	This message is for information only.
ATM044_04	TRANSACTIONS BACKED OUT DURING RESTART: {count}
Explanation	This message is issued by an ATM transaction manager at the end of restart processing. It indicates the number of previously incomplete transactions that were backed out during ATM restart processing.
Action	This message is for information only.
ATM045_04	TRANS/BRANCHES PENDING AFTER RESTART: {count}
Explanation	This message is issued by an ATM transaction manager at the end of restart processing. It indicates the number of incomplete transactions or transaction branches that could not be completed or backed out during ATM restart processing, and so remain incomplete. These transactions remain incomplete until they can be completed or fully backed out. Note: This message is issued before the transaction manager attempts to resynchronize incomplete transactions that are controlled by the CICS syncpoint manager or by RRS.
Action	This message is for information only.
ATM046_04	TRANS/BRANCHES TRANSFERRED TO STJ: {count}
Explanation	This message is issued by an ATM transaction manager at the end of restart processing. It indicates the number of incomplete transactions or transaction branches that could not be completed or backed out during the daemon recovery restart processing, and that were removed and recorded in the suspect transaction journal file in the transaction manager's recovery file. The number indicated should be zero unless the TMRESTART parameter indicates a forced restart.
Action	This message is for information only.
ATM047_20	ATM INITIALIZATION FAILED, error description
Explanation	A serious error prevented the transaction manager from initializing. Where possible an error description is provided to identify the cause of the error, otherwise "RC/RF" error codes are displayed.
Action	If the reason for the failure is not clear please contact your Software AG support representative.

ATM048_08	INITIALIZED, V{vers}, SESSION {sess}
Explanation	This message marks the successful completion of an ATM transaction manager's initialization processing. The version, release, and maintenance level of ATM are displayed, followed by the session number (sess) for this execution of the transaction manager.
Action	This message is for information only.
ATM049_04	ERRORS READING RECOVERY RECORDS: {count}
Explanation	This message appears at the end of the transaction manager's initialization processing if any errors were encountered reading recovery records.
Action	The message is for information only. For information about the errors encountered, refer to the error messages that precede this message.
ATM050_20	'SIGN-OFF' FAILED, RESPONSE CODE {rsp}
Explanation	This message can appear during the closedown process of a nucleus that was running with DTP=RM. It indicates that the nucleus called the local ATM transaction manager to notify it of the closedown, but the command failed with response code <i>rsp</i> .
Action	Nucleus termination will continue. Any incomplete global transactions will be resynchronized when the nucleus next communicates with the ATM transaction manager.
ATM051_20	'SIGN-OFF' FAILED, ERROR CODE {error-code}
Explanation	This message can appear during the closedown process of a nucleus that was running with DTP=RM. It indicates that the nucleus called the local ATM transaction manager to notify it of the closedown, but ATM returned the error-code <i>error-code</i> .
Action	Check the meaning of the given error code, to see if ATM needs any corrective action. Nucleus termination will continue. Any incomplete global transactions will be resynchronized when the nucleus next communicates with the transaction manager.
ATM052_20	PROTOCOL ERROR. ATM NOT INITIALIZED.
Explanation	This message is issued if an ATM transaction manager receives an operator command before it has completed its initialization processing.
Action	Wait, and re-issue the command later.

ATM054_20	HANDSHAKE ERROR; ID/RSP/SUB/CMD: {dbid/rsp/sub/cmd}
Explanation	An error occurred while the transaction manager was trying to handshake with the partner transaction manager identified by <i>dbid</i> . The error was an unexpected Adabas response code (<i>rsp</i>). The subcode (<i>sub</i>) and command code (<i>cmd</i>) are provided.
Action	If the cause of the error is not clear from the description of the response code, report the details to your Software AG support representative, noting the values of the variables.
ATM055_20	HANDSHAKE ERROR; ERR/QERR: {error-code/queue-error}
Explanation	An error occurred while the transaction manager was attempting to handshake with a partner transaction manager. The error code and, if applicable, a queue management error are provided.
Action	Refer to the descriptions of the possible error codes . If the cause of the error is not apparent, report the details to your Software AG support representative, noting the error code.
ATM057_10	NO FREE SLOTS IN {queue-area}
Explanation	The indicated queue area is full.
Action	Increase the relevant parameter and restart the Transaction Manager. If the indicated queue area has no associated runtime parameter, the error was most likely caused by shortage of memory. In this case, increase the amount of memory available to the Transaction Manager and restart it.
ATM058_10	MIXED TRANSACTION STATUS/RESULT REPORTED BY ATM {dbid}
Explanation	The transaction manager was attempting restart processing for incomplete transactions involving the partner transaction manager <i>dbid</i> , which was restarting. The partner transaction manager reported an inconsistent transaction status (partly committed, partly backed out). Subsequent messages identify the owner of the transaction. Likely causes include the following:
	<ul style="list-style-type: none">■ Some Adabas nucleus heuristically terminated its part of a global transaction.■ Some ATM transaction manager was started with <code>TMRESTART={FORCE FORCEALL}</code>.■ A transaction branch was forcibly terminated on request from an online services user or operator.■ Some database was restored to a status that is inconsistent with the status of other databases in the network.■ Pending restart information in some database was discarded (for example, by formatting Work or by starting with <code>ADARUN IGNDTP=YES</code>).

Action	In some of the above cases, details of the transaction (branch) might be found in an ATM transaction manager's suspect transaction journal (STJ) file. Otherwise, use Online Services or application-specific checks to determine the status of the transaction.
ATM059_10	MIXED TRANSACTION STATUS/RESULT; DBID {dbid}
Explanation	ATM was attempting restart processing for incomplete transactions involving the indicated database <i>dbid</i> , which was restarting. The transaction manager detected an inconsistent transaction status (partly committed, partly backed out). Refer to message ATM058 for likely causes.
Action	Use Online Services or application-specific checks to determine the status of the transaction.
ATM060_10	CONFLICTING TRANSACTION STATUS REPORTED BY ATM/DB {dbid}
Explanation	ATM was attempting restart processing for incomplete transactions involving the partner ATM transaction manager or database indicated by <i>dbid</i> , which was restarting. The ATM transaction manager detected an inconsistent or unknown transaction identifier (XID). Subsequent messages provide further information.
Action	Use Online Services or application-specific checks to determine the status of the transaction.
ATM061_10	MIXED TRANSACTION STATUS FOR USER {userid}
Explanation	This message indicates the Client ID of the owner of the transaction associated with a previous ATM058 or ATM059 message.
Action	Refer to the explanation of the preceding message.
ATM062_10	CONFLICTING TRANSACTION STATUS FOR USER {userid}
Explanation	This message indicates the Client ID of the owner of the transaction associated with a previous ATM060 message.
Action	Refer to the explanation of the preceding message.
ATM063_10	ERROR UPDATING PRR; RSP/SUB/CMD: {rsp/sub/cmd}
Explanation	The ATM transaction manager received an unexpected response code while attempting to update a recovery record in its recovery file. The message gives the response code (<i>rsp</i>), subcode (<i>sub</i>), and command code (<i>cmd</i>).
Action	If the cause of the error is not clear from the description of the response code, report the details to your Software AG support representative, noting the values of the variables.

ATM064_10	ERROR UPDATING PRR; ERR: {error-code}
Explanation	The ATM transaction manager encountered the indicated error code while attempting to update a recovery record in its recovery file.
Action	Refer to the descriptions of the possible error codes . If the cause of the error is not apparent, report the details to your Software AG support representative, noting the error code.
ATM067_10	UNSUPPORTED FUNCTION
Explanation	The transaction manager received a function call that is not valid.
Action	Contact your Software AG support representative.
ATM068_04	QUIESCING TRANSACTIONS FOR DB {dbid}
Explanation	The transaction manager is attempting to complete (commit or back out) all active global transactions that involve the indicated database in response to <ul style="list-style-type: none"> ■ a request from an Online Services user; or ■ an ADAEND command issued to the indicated database.
Action	This message is for information only.
ATM069_10	TRANSACTIONS CANNOT BE QUIESCED. DB/ERR: {dbid/err}
Explanation	The indicated error occurred while the transaction manager was trying to quiesce transactions involving database <i>dbid</i> . As a result, ATM was unable to complete one or more transactions.
Action	Refer to the descriptions of the possible error codes . If the appropriate action is not clear, contact your Software AG support representative.
ATM070_10	LOCAL TRAN(S) STILL IN DOUBT ON DB {dbid}
Explanation	ATM attempted to complete (commit or back out) all active global transactions that involve the indicated database, but at the end of the process, at least one transaction or transaction branch involving the database remained active.
Action	This message may be preceded or followed by messages requiring action. If so, refer to the explanations of those messages.

ATM071_10	FOLLOWING TMS IN ERROR: {id-list}
Explanation	While the ATM transaction manager was attempting to quiesce transactions on a database, it asked one or more partner managers to do the same, but one or more of them returned an unexpected error. The message lists up to four partner transaction managers that failed to carry out its request.
Action	Use Online Services to check the status of the indicated ATM nodes and, if necessary, to quiesce each transaction manager's transactions for the required database.
ATM072_10	HEURISTIC TERMINATIONS MAY RESULT
Explanation	This message is preceded by message ATM068 and one or more of the messages ATM069, ATM070, and ATM071. The database indicated in message ATM068 received an ADAEND command and asked ATM to quiesce its global transactions. At the end of the process, at least one transaction or transaction branch involving the database remained active. Any such transaction or transaction branch is heuristically terminated when its TT time limit expires, which could result in mixed completion of the related global transactions.
Action	This message warns of the impending loss of global transaction integrity for those global transactions that are still active. Use Online Services to identify the transactions that could not be quiesced. Any transaction that remains active when its TT time limit expires is heuristically committed. To prevent this, if appropriate, use Online Services to forcibly back out any such transaction.
ATM073_10	DB ACTIVITY NOT QUIESCED. CHECK ATM MANAGER {nodeid}
Explanation	A DTP=RM nucleus that received an ADAEND command requested the transaction manager with the indicated Node ID to quiesce its global transactions. The request failed.
Action	Check that the indicated transaction manager is active, and check for error messages issued by it. Use Online Services to ask the transaction manager to quiesce transactions on the database.
ATM074_10	RRMS REPORTED ERROR. FNC/RF/COMMID: {fnc/rf/comm-id}
Explanation	A problem was encountered with a transaction that is (or should be) under the control of RRMS. The RRMS function in error and its return code (values <i>fnc</i> and <i>rf</i>) are provided, together with the 28-byte Communications ID of the user who owns the transaction.
Action	Check the RRMS documentation to determine the meaning of the return code (value "rf"). If the cause of the problem is still not apparent, contact your Software AG support representative, noting the values of "fnc" and "rf".

ATM075_10	RRMS REPORTED EXIT MANAGER UNAVAILABLE
Explanation	ATM is interfacing to RRMS and has been notified that one of the RRMS exit managers has become unavailable. ATM continues to interface to RRMS once the exit manager has restarted.
Action	Report the problem to your systems programming staff.
ATM076_10	RRMS REPORTED EXITS UNSET. REASON: {rrrr}
Explanation	ATM is interfacing to RRMS and has been notified that its exits have become unavailable.
Action	Check the console log for other messages that may indicate the cause of the problem. Check the RRMS documentation to determine the meaning of the reason code (value <i>rrrr</i>). If possible, correct the problem and restart ATM. If the cause of the problem is not apparent, contact your Software AG support representative, noting the value of <i>rrrr</i> .
ATM077_10	RRS EXIT FAILED. X: {xx} R: {rr} AB: {aaaaaaaa} ABR: {nnnnnnnn}
Explanation	ATM is interfacing to RRMS and an error has occurred in one of its exit routines. The message details the exit number (<i>xx</i>), failure reason (<i>rr</i>), ABEND code (<i>aaaaaaaa</i>) and reason code (<i>nnnnnnnn</i>).
Action	If the cause of the problem is not apparent from the details of the message, contact your Software AG support representative, noting all the values given in the message.
ATM078_10	EXTERNALLY-OWNED TRANSACTION INCOMPLETE. DB/TC: {dddd/cccc}
Explanation	A database is trying to shut down in response to an ADAEND command; the ATM transaction manager has been asked to quiesce any transactions that involve the database, but has been unable to complete the process because at least one of those incomplete transactions is under the control of an external transaction coordinator. The database will not shut down until all global transactions are completed or backed out. The message identifies the database that is being shut down (value <i>dddd</i>) and the external transaction coordinator (value <i>cccc</i>).
Action	Use the facilities of the external transaction coordinator to force the completion or removal of the incomplete transactions. The transactions can be identified by the Online Services application.
ATM080_08	'STOP ALL USERS' REQUESTED BY USER {userid}
Explanation	An Online Services user issued a "stop all transactions" request. The <i>userid</i> is the last 8 bytes of the user's Communication ID.
Action	This message is for information and audit purposes only.

ATM081_08	'FORCE STOP ALL USERS' REQUESTED BY USER {userid}
Explanation	An Online Services user issued a "force stop all transactions" request. The <i>userid</i> is the last 8 bytes of the client session's Communication ID.
Action	This message is for information and audit purposes only.
ATM082_08	SELECTIVE MASS STOP USERS REQUESTED BY USER {userid}
Explanation	An Online Services user issued a selective mass "stop transactions" request. The <i>userid</i> is the last 8 bytes of the user's Communication ID.
Action	This message is for information and audit purposes only.
ATM083_08	FORCED SELECTIVE MASS STOP USERS REQUESTED BY USER {userid}
Explanation	An Online Services user issued a "forced selective mass stop transactions" request. The <i>userid</i> is the last 8 bytes of the user's Communication ID.
Action	This message is for information and audit purposes only.
ATM084_10	TRANSACTION BRANCH FORCIBLY COMPLETED. COMMID: {commid}
Explanation	In response to a "forced stop transactions" request from an Online Services user, ATM forced completion of the local branch of the transaction belonging to the client whose ID appears in the following ATM087 message. If the transaction had previously been prepared, ATM committed the branch; otherwise, ATM backed out the branch.
Action	This message is for information and audit purposes only.
ATM085_10	TRANSACTION DETAILS TRANSFERRED TO JOURNAL. COMMID: {commid}
Explanation	In response to a "forced stop transactions" request from an Online Services user, the ATM transaction manager purged the transaction (branch) belonging to the client whose ID appears in the following ATM087 message. Details of the transaction (branch) can be found in the ATM suspect transaction journal file.
Action	This message is for information and audit purposes only.
ATM086_10	RECOVERY RECORD DELETED FOR COMMID: {commid}
Explanation	In response to a request from an Online Services user, the ATM transaction manager purged from its recovery file, recovery information relating to the client whose ID appears in the following ATM087 message.
Action	This message is for information and audit purposes only.

ATM087_10	{commid}
Explanation	This message relates to the message(s) immediately preceding it, and gives the 28-byte Communication ID (<i>commid</i>) of the client session associated with the earlier message(s).
Action	Refer to the explanation of preceding message(s).
ATM088_10	ERROR TRANSFERRING TO STJ
Explanation	This message might be issued during forced restart of an ATM transaction manager, and indicates that a transaction that could not be completed could not be moved to the suspect transaction journal file. Subsequent messages provide more details of the error.
Action	Refer to explanation of following message(s).
ATM089_10	DATA TRANSFERRED TO STJ FOR USER {userid}
Explanation	This message might be issued during forced restart of an ATM transaction manager, and indicates that a transaction that could not be completed has been moved to the suspect transaction journal file. The <i>userid</i> is the Client ID of the transaction's owner.
Action	This message is for information and audit purposes only.
ATM090_04	FORCED PRR DELETION REQUESTED BY USER {userid}
Explanation	The specified user forcibly deleted a recovery record from the ATM transaction manager's recovery file using the Online Services application. The <i>userid</i> is the last 8 bytes of the user's Communication ID.
Action	The message is for information and audit purposes only.
ATM091_04	PRR DELETION FOR COMMID:
Explanation	A recovery record was deleted from the ATM transaction manager's recovery file using the Online Services application. The Communication ID of the associated user is reported in an ATM087 message immediately after the ATM091 message.
Action	The message is for information only.
ATM092_10	URID: {urid}
Explanation	This messages relates to the ATM136 message that immediately precedes it. It identifies the URID of the CICS unit of work that the ATM136 message relates to.
Action	Refer to the explanation of the ATM136 message.

ATM095_08	COMMAND NOT RECOGNIZED
Explanation	An invalid operator command was entered.
Action	Issue the command correctly.
ATM099_08	ATM CLOSEDOWN REQUESTED
Explanation	The operator entered the command <code>ATM END</code> .
Action	This message is for information only.
ATM100_08	ATM IMMEDIATE CLOSEDOWN REQUESTED
Explanation	The operator entered the command <code>ATM HALT</code> .
Action	This message is for information only.
ATM101_08	ATM CLOSEDOWN PROCESS STARTED
Explanation	The transaction manager is in the process of closing down.
Action	This message is for information only.
ATM102_10	DB CLOSEDOWN ERROR; ID/RSP/SUB/RC: {dbid/rsp/subcode/rc}
Explanation	An <code>ADAEND</code> command was entered for the database <i>dbid</i> , but the transaction manager encountered an unexpected condition during the close-down sequence. Either a response code and subcode will be given (<i>rsp/subcode</i>), or an ATM error code (<i>rc</i>).
Action	Refer to the description of the Adabas response code or the ATM error code. If the appropriate action is not clear, contact your Software AG support representative.
ATM103_08	TM END PENDING, INCOMPLETE TRANSACTIONS REMAIN
Explanation	An <code>ATM END</code> operator command was issued but the transaction manager is unable to close down immediately because of incomplete global transactions. Under these circumstances, ATM103 messages are issued for the first five of these incomplete transactions, each message displaying the client's job-name, job-number and last 8 bytes of the communication ID. These messages are repeated at 60 second intervals until the transactions are completed and close down occurs.
Action	Wait for the incomplete transactions to be resolved, or use the <code>ATM HALT</code> command to cause the transaction manager to terminate immediately, leaving the incomplete transactions to be resolved the next time it is activated.

ATM104_10	MEMORY SHORTAGE; ADAEND PROTOCOL MIGHT BE AFFECTED
Explanation	This messages can appear when a DTP=RM database is started. It indicates that certain memory areas could not be acquired. Database processing should not be affected by this condition. However, there is a possibility that the closedown protocol that happens when ADAEND is issued to the database will not proceed as normal; this could increase the risk of heuristically terminated transactions.
Action	Make more memory available to the database job and restart it.
ATM105_08	ATM closedown process ended
Explanation	The transaction manager has finished its closedown process.
Action	This message is for information only.
ATM106_04	Adabas RM {dbid} connection, type Peer TM {nodeid} connection
Explanation	This message is issued by a transaction manager approximately five minutes after start-up and hourly thereafter. It displays a list of known databases (<i>dbid</i>) and peer transaction managers (<i>nodeid</i>). A DTP=RM database is identified by the characters "RM" and the connection type may be one of the following: Local – the database is within the scope of the System Coordinator group name and is local to this transaction manager. Remote – the database is within the scope of the System Coordinator group name and is remote to this transaction manager External - the database is not within the scope of the System Coordinator group name.
Action	This message is for information only.
ATM110_04	SESSION STATISTICS:
Explanation	This message is issued during transaction manager termination. Statistical messages follow.
Action	This message is for information only.
ATM119_04	STATISTICS HAVE BEEN RESET
Explanation	This message is issued when the transaction manager's statistics are reset to zero, in response to an ATM RSTAT operator command or an equivalent request from an Online Services user.
Action	This message is for information only.

ATM120_04	DB {dbid} waiting for Transaction Manager connection
Explanation	This message is issued by a DTP=RM database that is initializing. The nucleus is required to connect to the local Transaction Manager for distributed transaction processing which has not yet occurred, initialization continues but participation in distributed transactions is not yet possible. Note: In the case of a DTP=RM nucleus which is part of an Adabas Parallel Services cluster or an Adabas Cluster Services cluster, the message gives the ID of the nucleus, not the database number of the cluster, and begins, NC <i>dbid</i> waiting for
Action	This message is for information only, connection will occur automatically when the TM is ready.
ATM121_10	DB {dbid} ATM82 (and above) - TM now runs in COR Daemon, DB {dbid} Normal termination of this node is scheduled
Explanation	This message is issued when a database is started with ADARUN DTP=TM. This method of identifying a Transaction Manager is no longer applicable, it is only required for previous releases of ATM. The database will terminate normally.
Action	Review the installation procedure for the correct way to install the Transaction Manager so that it runs in the Adabas System Coordinator daemon.
ATM122_20	DTP {operation} FAILED, DB/TM/RSP/SUB/RC: {dbid/tmid/rsp/sub/rc }
Explanation	This message can be issued by a database for which the ADARUN parameter DTP=RM was specified, or by the ATM transaction manager. It can appear during an attempt to sign a database on to a transaction manager for distributed transaction processing, or to sign the database off, as indicated by <i>operation</i> . "Sign-on" can happen during initialization of a transaction manager or when the database is started. "Sign-off" happens when the database is terminated. The message indicates that an unexpected condition was detected. It includes the <i>dbid</i> of the database, the node ID (<i>tmid</i>) of the transaction manager, and might also contain a response code (<i>rsp</i>), subcode (<i>sub</i>) and return code (<i>rc</i>) for the error.
Action	If this message indicates sign-on and is followed by an ATM124 message from the database identified in the message detail, this indicates that the error condition was transient, and that the DTP sign-on has now taken place. If there is no ATM124 message, and if the cause of the error is not clear from the description of the response code, subcode and return code, report the details to your Software AG support representative, noting the values of the variables in the message. If the message indicates sign-off, it is given for information only.

ATM124_04	DB {dbid} connected with Transaction Manager node {nodeid}
Explanation	This message is issued by a DTP=RM database or, a DTP=RM nucleus which is part of an Adabas Cluster Services or Adabas Parallel Services cluster, when it has connected with a Transaction Manager (<i>nodeid</i>).
	Under normal circumstances this message will be preceded by an ATM129 message.
	Note: In the case of a DTP=RM nucleus which is part of an Adabas Cluster Services or Adabas Parallel Services cluster, the message gives the ID of the nucleus, not the database number of the cluster, and begins, <i>Nc dbid connected with ...</i>
Action	This message is for information only.
ATM125_10	ATM NOT ACTIVE. ADAEND CANNOT COMPLETE.
Explanation	An ADAEND command was entered for database <i>dbid</i> , but the normal process of quiescing open transactions could not occur because the transaction manager was not active. The database does not close down.
Action	Activate the transaction manager and use the Online Services application to quiesce any open transactions on the database. When you are sure that all global transactions involving the database have been completed or backed out, you can close down the database with a HALT command.
	Caution: If you issue a HALT command while there are incomplete global transactions, the integrity of those transactions can no longer be guaranteed.
ATM126_04	RM disconnected — no unresolved transactions: {dbid}
Explanation	The ATM transaction manager issues this message when a DTP=RM database identified by <i>dbid</i> terminates with no outstanding transactions involving the database. If the terminating database is part of an Adabas Parallel Services or Adabas Cluster Services cluster, the value <i>dbid</i> might have the form <i>Nuc nnnnn</i> , where <i>nnnnn</i> is the ID of the terminating nucleus.
Action	This message is for information only.
ATM127_04	RM disconnected — unprepared transactions remaining: {dbid}
Explanation	The ATM transaction manager issues this message when a DTP=RM database identified by <i>dbid</i> terminates with outstanding unprepared transactions involving the database. If the terminating database is part of an Adabas Parallel Services or Adabas Cluster Services cluster, the value <i>dbid</i> might have the form <i>Nuc nnnnn</i> , where <i>nnnnn</i> is the ID of the terminating nucleus.
Action	This message is for information only.

ATM128_04	RM disconnected — prepared transactions remaining: {dbid}
Explanation	The ATM transaction manager issues this message when a DTP=RM database (<i>dbid</i>) terminates with outstanding prepared transactions involving the database. If the terminating database is part of an Adabas Parallel Services or Adabas Cluster Services cluster, the value <i>dbid</i> might have the form Nuc <i>nnnnn</i> , where <i>nnnnn</i> is the ID of the terminating nucleus.
Action	In the case of a normal database, restart the database with DTP=RM. If the message identifies a nucleus within an Adabas Parallel Services or Adabas Cluster Services cluster, and there is another nucleus in the cluster which is still executing, no action is necessary; otherwise, restart a member of the cluster, with DTP=RM. Caution: If the database is started with DTP=NO, data integrity cannot be guaranteed.
ATM129_04	DB {dbid} connecting with Transaction Manager node {nodeid}
Explanation	This message is issued by a DTP=RM database or, a DTP=RM nucleus which is part of an Adabas Cluster Services or Adabas Parallel Services cluster, when it is connecting with a Transaction Manager (<i>nodeid</i>). Under normal circumstances this message will be followed by an ATM124 message. Note: In the case of a DTP=RM nucleus which is part of an Adabas Cluster Services or Adabas Parallel Services cluster, the message gives the ID of the nucleus, not the database number of the cluster, and begins, <i>Nc dbid connecting with ...</i>
Action	This message is for information only.
ATM130_20	ATM PROXY INITIALIZATION FAILED
Explanation	This message can be issued by a job or TP system for which the client runtime control ATM=ON has been specified. It indicates a fatal error which prevented the ATM client proxy from initializing.
Action	Check for earlier messages which might indicate the reason for the failure. If the cause of the error is not clear, contact your Software AG support representative.
ATM131_10	RMI RESYNC ERROR. SYS/RC/RC2 {sys/rc/rc2}
Explanation	An error occurred during the synchronization process that takes place during ATM or CICS restart when the CICS Resource Manager Interface is in use. The message provides the System ID of the CICS system (value <i>sys</i>), a CICS or ATM error code (value <i>rc</i>), and possibly a secondary return code or Adabas response code (value <i>rc2</i>).
Action	Refer to the descriptions of the possible error codes . If possible, correct the error and restart the ATM transaction manager; otherwise report the details to your Software AG support representative.

ATM132_10	RMI RESYNC ERROR. SYS/CD/RSP {sys/cd/rsp}
Explanation	An error occurred during the synchronization process that takes place during ATM or CICS restart when the CICS Resource Manager Interface is in use. The message provides the System ID of the CICS system (value <i>sys</i>), a CICS command or function name (value <i>cd</i>), and CICS response code (value <i>rsp</i>).
Action	Refer to the CICS documentation for an explanation of the error condition. If possible, correct the error and restart CICS; otherwise report the details to your Software AG support representative.
ATM133_10	RMI SYNCPOINT ERROR. URID {urid}
Explanation	An error occurred during syncpoint processing of a transaction that was under the control of the CICS syncpoint manager. The CICS Unit-of-Recovery ID (value <i>urid</i>) belonging to the transaction is displayed.
Action	This message is followed by message ATM134, which gives more information about the error.
ATM134_10	RMI SYNCPOINT ERROR. SYS/RC/RSP {sys/rc/rsp}
Explanation	This message follows message ATM133 and provides details of an error that occurred during syncpoint processing under the control of the CICS syncpoint manager. The message provides the System ID of the CICS system (value <i>sys</i>), an ATM error code (value <i>rc</i>), and, depending on the ATM error code, a CICS or Adabas response code (value <i>rsp</i>).
Action	Refer to the relevant documentation for an explanation of the error condition. If the cause is not then apparent, report the details to your Software AG support representative.
ATM135_10	RMI RESYNC ERROR. APP/CD/RSP {app/cd/rsp}
Explanation	An error occurred during the synchronization process that takes place during ATM or CICS restart when the CICS Resource Manager Interface is in use. The message provides the Application ID of the CICS system (value <i>app</i>), a CICS command or function name (value <i>cd</i>), and an error code (value <i>rsp</i>). If the error code begins with the character "R", the remaining digits are an ATM error code; otherwise the value of <i>rsp</i> is a CICS response code.
Action	Refer to ATM error codes or to the CICS documentation, as appropriate, for an explanation of the error condition. If possible, correct the error and restart CICS and, if necessary, the ATM transaction manager; otherwise report the details to your Software AG support representative.

ATM136_10	RMI RESYNC ERROR. APP/RC {app/rc}
Explanation	An error occurred during the synchronization process that takes place during ATM or CICS restart when the CICS Resource Manager Interface is in use. The message provides the Application ID of the CICS system (value <i>app</i>) and an ATM error code (value <i>rc</i>). This message may be followed by an ATM092 message indicating the URID of the CICS unit of work for which the error occurred.
Action	Refer to the descriptions of the possible error codes . If possible, correct the error and restart the ATM transaction manager; otherwise report the details to your Software AG support representative.
ATM137_10	EXCI COMMAREA COULD NOT BE ADDRESSED
Explanation	An internal error occurred during the synchronization process that takes place during ATM restart when the CICS Resource Manager Interface is in use.
Action	Report the error to your Software AG support representative. You may bypass the problem by restarting your CICS systems after the ATM transaction manager has initialized.
ATM138_10	RMI RESYNC ISSUED. SYS {sys}
Explanation	This message can appear during restart of an ATM transaction manager or a CICS system in an environment in which some transactions are controlled by the CICS Syncpoint Manager. It indicates that resynchronization processing will be carried out for incomplete transactions controlled by the CICS system with the System ID <i>sys</i> .
Action	This message is for information only.
ATM139_10	RMI resync complete. Sys {sys}
Explanation	This message appears in an environment in which some transactions are controlled by the CICS Syncpoint Manager. The message follows restart of an ATM transaction manager or a CICS system and indicates that the synchronization process has executed for incomplete transactions controlled by the CICS system with the System ID <i>sys</i> .
Action	This message does not necessarily indicate that every incomplete transaction was resolved satisfactorily. Check the console log for other messages which might indicate a problem.
ATM140_10	ATM PROXY DETECTED {cmd} DB {dbid} RSP {rsp} AD2 Xadditions-2
Explanation	This message is issued by the ATM client proxy for the first ATM-related error incurred by each client session. The message can include a command code, Database ID, response code and Additions-2 data, providing further information about the error. This message is followed by ATM087 messages which give the 28-byte Communication ID of the client session, first in character form, and then in hexadecimal.
Action	Check the meaning of the indicated response code and Additions-2 data. If the cause of the error is not apparent, contact your Software AG support representative, noting all the values given in the message.

ATM141_04	DTP DISABLED FOR THIS JOB BY RUNTIME CONTROL
Explanation	This message is issued by the ATM client proxy. It indicates that client sessions executing within this job have been exempted from distributed transaction processing by the setting of a client runtime control.
Action	This message is for information only.
ATM144_08	SYSTEM COORDINATOR GROUP NAME NOT SPECIFIED
Explanation	This message can be issued by a client job. It indicates that the ATM client runtime controls in effect for this job do not include the name of an Adabas System Coordinator Group. ATM processing will not be activated for the job.
Action	Use the Online Services application to specify the name of the System Coordinator Group in which the job will execute.
ATM160_10	SYSCO DAEMON ERROR; ID/RSP/SUB/FNC/SBF/ERR: {id/rsp/sub/fnc/sbf/err}
Explanation	This message can appear during restart of an ATM transaction manager. It indicates that a call to an Adabas System Coordinator daemon returned an unexpected result. The message will include at least some of the following: the Node ID (<i>id</i>) of the Adabas System Coordinator daemon, the response code (<i>rsp</i>) and subcode (<i>sub</i>) returned by the Adabas System Coordinator daemon, the function and subfunction codes of the call (<i>fnc</i> and <i>sbf</i>), and an error code (<i>err</i>).
Action	If the cause of the error is not apparent from the description and content of the message, contact your Software AG support representative.
ATM163_04	ERROR DELETING PER; RSP/SUB/CMD: {rsp/sub/cmd}
Explanation	This message indicates that an error occurred while deleting a Persistent Error Record. The message contains the following diagnostic information: a response code and subcode (<i>rsp</i> and <i>sub</i>) and a command code (<i>cmd</i>).
Action	If the cause of the error is not apparent from the description and content of the message, contact your Software AG support representative.
ATM164_04	ERROR DELETING PER; ERR: {err}
Explanation	This message indicates that an error occurred while deleting a Persistent Error Record. The message contains an ATM error code (<i>err</i>).
Action	If the cause of the error is not apparent from the description and content of the message, contact your Software AG support representative.

ATM167_10	MTR PROCESSING ERROR; ID/ERR/RSP/SUB/CMD: {id/err/rsp/sub/cmd}
Explanation	This message indicates that an error occurred while processing a migrated transaction record in an Adabas Cluster Services or Parallel Services environment. The message will contain at least some of the following diagnostic information: a database or Node ID (<i>id</i>), an error code (<i>err</i>), a response code and subcode (<i>rsp</i> and <i>sub</i>) and a command code (<i>cmd</i>). The user's transaction is backed out, and a pending response code 9 (ADARSP009), subcode 77 is set.
Action	If the cause of the error is not apparent from the description and content of the message, contact your Software AG support representative.
ATM168_10	CLIENT MIGRATED, BUT NO MTR FILE DEFINED
Explanation	This message indicates that a client session that had an open transaction has been migrated from one node to another within a cluster (for example, CICSplex), but ATM cannot handle this session's transaction safely because no Migrated Transaction Record (MTR) file has been defined. The transaction is backed out, and a pending response code 9 (ADARSP009), subcode 77 is set.
Action	Define and create an MTR file, and restart the ATM transaction managers and clustered application environments in the COR group.
ATM169_10	MTR FILE IS NOT DEFINED
Explanation	This is a warning message, and it can appear during initialization of an ATM transaction manager. It indicates that no Migrated Transaction Record (MTR) file definition was found. An MTR file is required if you use application environments in which a client session that is not at global transaction status can be migrated around a cluster (for example, CICSplex, with ATM client runtime control <code>TransactionModel</code> set to DYNAMIC).
Action	If your application environments are such that no MTR file is needed, you can ignore this message, or suppress it by making a dummy MTR file definition using SYSCOR. Otherwise, define and create an MTR file, and restart the ATM transaction managers and clustered application environments in the COR group.
ATM171_08	TM tmid STARTING TRANSACTION FLUSH
Explanation	This message can be issued by a DTP=RM database when the database has received an ADAEND command. It indicates that the Transaction Manager with the given ID (tmid) is attempting to terminate any incomplete global transactions that have changed the database, so that the database can terminate cleanly. This message should be followed by either an ATM172 or an ATM173 message, indicating whether or not all relevant transactions were terminated.
Action	This message is for information only.

ATM172_10	TM tmid DID NOT COMPLETE TRANSACTION FLUSH
Explanation	This message might be issued by a DTP=RM database after message ATM171. It indicates that the Transaction Manager with the given ID (tmid) was not able to terminate all global transactions that have changed the database. This might mean that a superior TM or external transaction co-ordinator has not indicated what the outcome of a transaction should be.
Action	Use the Online Services application to identify the offending transactions. If possible, resolve any such transaction through the co-ordinator that controls the root of the transaction. If this is not possible, you might choose to use SYSATM's "stop" facility to force resolution of a transaction, if you are sure that this will not result in loss of transactional integrity.
ATM173_08	TM tmid COMPLETED TRANSACTION FLUSH
Explanation	This message might be issued by a DTP=RM database after message ATM171. It indicates that the Transaction Manager with the given ID (tmid) successfully terminated all incomplete global transactions that had changed the database.
Action	This message is for information only.
ATM174_10	NO TM ACTIVE
Explanation	This message can be issued by a DTP=RM database when the database has received an ADAEND command. It indicates that there are incomplete, prepared transactions in the database, but the Transaction Manager that owns these transactions is not currently active. The ADAEND process cannot complete until the incomplete transactions have been resolved.
Action	Restart the inactive Transaction Manager.
ATM177_08	Transaction Manager waiting for TM agent node: {nodeid}
Explanation	This message is issued when a transaction manager has restarted following a previous abnormal termination after which a peer transaction manager was established as its agent. This transaction manager has notified the agent (<i>nodeid</i>) of its restart but must wait for the agent to relinquish its agent role.
Action	This message is for information only.
ATM178_08	Agent processing relinquished for node: {nodeid}
Explanation	This message is issued when a transaction manager has relinquished its agent role at the request of a peer transaction manager (<i>nodeid</i>) which is restarting.
Action	This message is for information only.

ATM179_08	Agent initialization successful for node: {nodeid}
Explanation	This message is issued when a transaction manager successfully initializes as an agent for a peer transaction manager (<i>nodeid</i>) which has terminated abnormally.
Action	This message is for information only.
ATM180_20	Error during the opening of the recovery file: {error-code}
Explanation	This message is issued when a transaction manager is started and there is a problem opening the recovery file.
Action	Check the recovery file has been correctly defined according to the installation documentation. If the cause of the error is not apparent, report the details to your Software AG representative.
ATM181_08	Agent initialization started for node: {nodeid}
Explanation	This message is issued when a transaction manager begins initializing as an agent for a peer transaction manager (<i>nodeid</i>) which has terminated abnormally.
Action	This message is for information only.
ATM182_20	Agent initialization unsuccessful for node: {nodeid}
Explanation	This message is issued when a transaction manager unsuccessfully initializes as an agent for a peer transaction manager (<i>nodeid</i>) which has terminated abnormally. Preceding messages provide further information.
Action	This message is for information only. Other active peer transaction managers may also attempt agent initialization but, if none are successful, normal recovery processing will occur when the abnormally terminated transaction manager restarts.
ATM184_10	TMRFI allocation failed: {entity /error_code}
Explanation	This message is issued if a failure occurred when the Transaction Manager attempted to allocate an additional number of blocks from the TMRFI file. If the failure is due to the TMRFI file being full, the <i>error_code</i> is replaced by the text "File full".
	Refer to ATM186 for an explanation of the <i>entity</i> name.
Action	In the event that a "File full" condition is reported, use the entity name in the message to identify which type of record was being processed at the time and use SYSATM Recovery File Functions to browse the corresponding records currently stored in the TMRFI file and, where possible, purge those that are no longer applicable.
	For any other error condition please contact your Software AG support representative providing the job log of the ATM transaction manager and a copy of the TMRFI file as close to the time of failure as possible.

ATM185_04	TMRFI allocation successful: {entity /blocks_allocated}
Explanation	This message is issued when the Transaction Manager successfully allocates an additional number of blocks (<i>blocks_allocated</i>) from the TMRFI file. Refer to ATM186 for an explanation of the <i>entity</i> name. This message is always accompanied by message ATM187.
Action	This message is for information only.
ATM186_04	TMRFI statistics / {Text}
Explanation	<p>These messages are displayed at Transaction Manager start-up, shut-down or when an ATM DSTAT operator command is issued, and show general information about the size and usage of the TMRFI file.</p> <p>The TMRFI file manages different record types. These record types are also referred to as entities and consist of the following types:</p> <ul style="list-style-type: none">■ Recovery records (PRR)■ Suspect transaction records (STJ)■ System migration records (MTR)■ Pending response records (PER)■ ET data records (EDR) <p>These messages display the number of blocks currently reserved for use by these entities. No parameters are required to be set or maintained in relation to these entities and any additional blocks required will be allocated automatically on demand, accompanied by an ATM185 message acknowledging successful allocation, and an ATM187 message reporting the remaining number of free blocks.</p> <p>The number of free blocks reported by the ATM186 and ATM187 messages can provide an early indication of the TMRFI file becoming full.</p> <p>All the other information provided is relevant only to Software AG in the event of problems associated with the use of the TMRFI file.</p>
Action	This message is for information only.
ATM187_04	TMRFI remaining free blocks: {nnnnnnnn}
Explanation	This message displays the number of free blocks remaining in the TMRFI file. It accompanies message ATM185 when the Transaction Manager successfully allocates an additional number of blocks from the TMRFI.
Action	This message is for information only. The number of free blocks in the TMRFI file is also displayed in message ATM186 at Transaction Manager start-up, shut-down or when an ATM DSTAT operator command is issued. The number of free blocks displayed can provide an early indication of the TMRFI becoming full.

ATM188_04	RM connection pending: {dbid} Nuc {nucid}
Explanation	<p>This message is issued by the Transaction Manager as a result of one of the following events:</p> <ul style="list-style-type: none"> ■ a local DTP=RM database is active ■ a local DTP=RM nucleus which is part of an Adabas Parallel Services cluster is active ■ a local or remote DTP=RM nucleus which is part of an Adabas Cluster Services cluster is active <p>This can occur (a) if the Transaction Manager is already active and such a database or nucleus is started, or (b) such a database or nucleus is already active and the Transaction Manager is started.</p> <p>Under normal circumstances this message will be followed by an ATM190 message indicating successful connection.</p> <p>Note: The message gives the database number (<i>dbid</i>) and, in the case of a DTP=RM nucleus which is part of an Adabas Cluster Services or an Adabas Parallel Services cluster, the ID of the nucleus (<i>nucid</i>).</p>
Action	This message is for information only.
ATM189_04	RM disconnection pending: {dbid} Nuc {nucid}
Explanation	<p>This message is issued by the Transaction Manager as a result of one of the following events:</p> <ul style="list-style-type: none"> ■ a local DTP=RM database is no longer active ■ a local DTP=RM nucleus which is part of an Adabas Parallel Services cluster is no longer active ■ a local or remote DTP=RM nucleus which is part of an Adabas Parallel Services cluster is no longer active <p>This occurs when the Transaction Manager is active and such a database or nucleus is stopped. Under normal circumstances this message will be followed by an ATM126, ATM127, or ATM128 message indicating successful disconnection.</p> <p>Note: The message gives the database number (<i>dbid</i>) and, in the case of a DTP=RM nucleus which is part of an Adabas Cluster Services or an Adabas Parallel Services cluster, the ID of the nucleus (<i>nucid</i>).</p>
Action	This message is for information only.

ATM190_04	RM connected: {dbid} Nuc {nucid}
Explanation	<p>This message is issued by the Transaction Manager as a result of successfully connecting to one of the following:</p> <ul style="list-style-type: none"> ■ a local DTP=RM database ■ a local DTP=RM nucleus which is part of an Adabas Parallel Services cluster ■ a local or remote DTP=RM nucleus which is part of an Adabas Cluster Services cluster <p>This can occur (a) if the Transaction Manager is already active and such a database or nucleus is started, or (b) such a database or nucleus is already active and the Transaction Manager is started. Under normal circumstances this message will be preceded by an ATM188 message indicating pending connection.</p> <p>Note: The message gives the database number (<i>dbid</i>) and, in the case of a DTP=RM nucleus which is part of an Adabas Cluster Services or an Adabas Parallel Services cluster, the ID of the nucleus (<i>nucid</i>).</p>
Action	This message is for information only.
ATM191_04	DB {dbid} 2PC enabled with Transaction Manager node {nodeid}(L)
Explanation	<p>This message is issued by a DTP=RM database or, a DTP=RM nucleus which is part of an Adabas Cluster Services or Adabas Parallel Services cluster, when it has connected with its local (L) Transaction Manager (<i>nodeid</i>).</p> <p>Under normal circumstances this message will be preceded by ATM129 and ATM124 messages.</p> <p>Note: In the case of a DTP=RM nucleus which is part of an Adabas Cluster Services or Adabas Parallel Services cluster, the message gives the ID of the nucleus, not the database number of the cluster, and begins, <i>Nc nucid 2PC enabled</i></p>
Action	This message is for information only.
ATM192_04	DB {dbid} 2PC enabled with Transaction Manager node {nodeid}(R)
Explanation	<p>This message is issued by a DTP=RM database or, a DTP=RM nucleus which is part of an Adabas Cluster Services or Adabas Parallel Services cluster, when it has connected with a remote (R) Transaction Manager (<i>nodeid</i>).</p> <p>Under normal circumstances this message will be preceded by ATM129 and ATM124 messages.</p> <p>Note: In the case of a DTP=RM nucleus which is part of an Adabas Cluster Services or Adabas Parallel Services cluster, the message gives the ID of the nucleus, not the database number of the cluster, and begins, <i>Nc nucid 2PC enabled</i></p>
Action	This message is for information only.

50

Adabas Transaction Manager Error Codes

Although many of the following error codes are handled internally, some may appear in console messages or in the Additions 2 field of Adabas control blocks. If the required action is not clear from the explanations of the console messages or error codes, contact your Software AG technical support representative for advice.

error 012

Explanation Status conflict - transaction is in prepare phase.

error 016

Explanation Status conflict - transaction is in backout phase .

error 020

Explanation Queue management error - item not found.

error 024

Explanation Invalid service call.

error 028

Explanation Insufficient memory for a new global transaction queue entry.

error 032

Explanation Insufficient memory for a new entry in the target database list.

error 036

Explanation Attempt to add a duplicate global transaction queue element.

error 044

Explanation Invalid global transaction queue element address.

error 048

Explanation Syncpoint request did not come from CICS RMI.

error 052

Explanation Status conflict - target is in prepare phase.

error 056

Explanation Status conflict - target is in backout phase.

error 060

Explanation Queue management error.

error 064

Explanation Unexpected Adabas response code.

error 068

Explanation No target was updated.

error 072

Explanation No transaction is open.

error 076**Explanation** Transaction (branch) backed out.**error 080****Explanation** Transaction (branch) partially backed out.**error 084****Explanation** Local or remote ATM transaction manager not available.**error 086****Explanation** Backout was attempted because the global transaction time limit was exceeded.**error 088****Explanation** The ATM transaction manager did not receive the request.**error 092****Explanation** Target not prepared.**error 096****Explanation** Incorrect positioning data in service call.**error 104****Explanation** Invalid service call type.**error 108****Explanation** ETID missing or invalid.**error 112****Explanation** Function not implemented.

error 116

Explanation More than one target DB record found.

error 120

Explanation Transactions on the target database are being quiesced.

error 124

Explanation Transactions on the target database were not fully quiesced.

error 128

Explanation Heuristic completion (commit or back out) by either ATM or a DTP=RM database may have caused inconsistent ET data.

error 132

Explanation Transaction status conflict.

error 136

Explanation Unable to complete existing transaction.

error 140

Explanation ATM session number mismatch during RMI synchronization.

error 144

Explanation Handshake information buffer overflow.

error 148

Explanation ATM restart processing aborted by operator.

error 152

Explanation Error reading ET data.

error 156**Explanation** Client is already active.**error 160****Explanation** Insufficient memory for a new Adabas buffer area.**error 164****Explanation** All required target databases and ATMs are unavailable.**error 168****Explanation** Duplicate transaction coordinator record in PRR file.**error 172****Explanation** Transaction (branch) not prepared.**error 176****Explanation** Invalid status for NONDTP override.**error 180****Explanation** Committed, outcome pending.**error 184****Explanation** Transaction is in commit phase.**error 188****Explanation** A target database is not signed on for distributed transaction processing.**error 192****Explanation** A target is in commit phase.

error 196

Explanation Client proxy parameter error in V1 call forwarding.

error 200

Explanation Syncpoint request did not come from RRS.

error 204

Explanation Non-zero response set in ACB.

error 208

Explanation Handshake collision between two ATM transaction managers.

error 212

Explanation Partner ATM failed to prepare.

error 216

Explanation Partner ATM failed to commit.

error 220

Explanation Partner ATM failed to back out.

error 224

Explanation Mixed transaction completion.

error 228

Explanation An RRMS error occurred.

error 232

Explanation RRMS gave an invalid exit number.

error 236**Explanation** A CICS/RMI syncpoint operation failed.**error 240****Explanation** The RMI is not enabled.**error 244****Explanation** Command type invalid for wrapping.**error 248****Explanation** Client ID already exists in the global transaction queue.**error 252****Explanation** No free DRQ slots - TMDRQ parameter is too small.**error 256****Explanation** Command not handled - send to local ATM transaction manager.**error 260****Explanation** A CICS command issued by the synchronization manager failed.**error 264****Explanation** TRUE work area is not valid.**error 268****Explanation** TRUE has not fully initialized.**error 272****Explanation** A local database returned response code 148 (ADARSP148).

error 276

Explanation Mode override not valid in session's current status.

error 280

Explanation A session attempted to use more than 191 databases at once.

error 284

Explanation Incomplete handshake information element.

error 288

Explanation The transaction manager is running in "local only " mode (TMNODES=0).

error 292

Explanation Database ID already in the target list.

error 296

Explanation The target DB list index is full - TMTARGETSG parameter is too small.

error 300

Explanation The partner ATM node table is full - inadequate TMNODES parameter.

error 304

Explanation Insufficient memory.

error 308

Explanation No dynamic Client IDs available - TMDYNTCIDS parameter is too small.

error 312

Explanation Adabas buffer area too small.

error 316**Explanation** Invalid dynamic Client ID detected.**error 320****Explanation** Command not valid - transaction branch open.**error 324****Explanation** Client not known to local ATM transaction manager.**error 328****Explanation** Client not known to partner ATM transaction manager.**error 332****Explanation** Conflicting activity for transaction.**error 336****Explanation** Request should be sent to root ATM transaction manager.**error 340****Explanation** A session attempted to use more than 191 ATM transaction managers in the same transaction.**error 344****Explanation** 'Forget branch' failed.**error 348****Explanation** Transaction ID conflict.**error 352****Explanation** Record buffer too small.

error 356

Explanation Maximum number of open databases exceeded. Increase the appropriate client runtime control.

error 360

Explanation Transaction has been committed.

error 364

Explanation Transaction has been prepared.

error 368

Explanation Unsolicited syncpoint not allowed.

error 372

Explanation Bad return code from ADASVC.

error 376

Explanation Invalid Database ID.

error 380

Explanation A CICS command failed during an RMI syncpoint operation.

error 384

Explanation XID mismatch was detected during an RMI syncpoint operation.

error 388

Explanation RMI reported "should not be in doubt".

error 392

Explanation RMI reported the transaction "lost to cold start".

error 396

Explanation Attempt to change two DTP=ET databases in a single transaction.

error 400

Explanation Transaction's status on a DTP=ET database is not known.

error 404

Explanation A DTP=ET database failed to commit.

error 408

Explanation A DTP=ET database cannot be changed by a transaction that is controlled by an external coordinator.

error 412

Explanation Version mismatch; use ATM components of same version everywhere.

error 416

Explanation RQE overflow; DB list truncated.

error 420

Explanation An IMS TM ROLLBACK function failed; reason code in Additions-2.

error 424

Explanation Invalid request for Unsolicited Syncpoint Participant status.

error 428

Explanation DB has conflicting local/remote information.

error 432

Explanation Null Communications ID detected.

error 436

Explanation Multiple ET data records detected.

error 440

Explanation Multiple migrated transaction records were found.

error 444

Explanation The RRMS stubs have not been linked to ATMKRN in the application environment.

error 448

Explanation The client runtime control Adabas distributed transaction support is set to Yes but the Adabas CICS LGBLSET parameter RMI= is set to No. For CICS clients to successfully use RMI, both these must be set to Yes.

error 452

Explanation An unexpected return code was given by a SYSCO daemon .

error 456

Explanation An unexpected and unnecessary call was received from a SYSCO daemon .

error 460

Explanation An error occurred during the client proxy's check for DTP=RM. .

error 468

Explanation There is a non-zero response code pending for the session. .

error 472

Explanation An unexpected condition was returned by the Adabas System Coordinator's router interface. .

error 476

Explanation During a sequence of ET commands, the first of which supplied ET data, ET data was supplied on a session that used a different ETID. .

error 480

Explanation A request from the CICS RMI attempted to act on a transaction that was not owned by the CICS RMI. .

error 484

Explanation An ATM transaction manager detected an invalid service call to itself. .

error 488

Explanation An invalid communication-ID was supplied. .

error 492

Explanation An invalid communication-ID was detected in the transaction manager's queue. .

error 496

Explanation The last completed distributed transaction (either committed or undone) was not carried out fully by the application. The application is not compliant with distributed transaction processing requirements in this area. Distributed programming requires that all modified databases are either all committed (ET) or all undone (BT), otherwise the application will incur integrity problems if Adabas Transaction Manager is removed or disabled.

error 500

Explanation There was a duplicate attempt to sign a DTP=RM database on to a Transaction Manager for Distributed Transaction Processing.

error 504

Explanation There was an attempt to sign a DTP=RM database on to a remote Transaction Manager for Distributed Transaction Processing.

error 508

Explanation There was an invalid attempt to remove a database from a global transaction.

error 512

Explanation Transaction status is not known because a status-check request to the local TM returned a bad response code. .

error 513

Explanation Transaction status is not known because a status-check request to the local TM returned error 88. .

error 514

Explanation Transaction status is not known because a status-check request to the local TM returned error 412.

error 515

Explanation Transaction status is not known because a status-check request to the local TM returned error 488.

error 516

Explanation Transaction status is not known because a status-check request to the local TM returned error 60.

error 517

Explanation Transaction status is not known because an Adabas buffer area could not be acquired for a status-check operation. .

error 520

Explanation In a DTR environment, a client session has migrated to another system, but no MTR file is in use. .

error 524

Explanation A session could not be switched to serial ET / BT mode, because the local TM was already involved in the current transaction. .

error 528

Explanation The client proxy failed to provide a return code for a CICS RMI syncpoint operation.
.

error 536

Explanation An unknown TM node ID was detected while processing DTR migration. .

error 540

Explanation The “F” command option on a BT command could not be honored, because a distributed transaction was in process. .

error 544

Explanation The client session tried to change a database that’s executing outside the scope of the client session’s System Coordinator group, but this is disallowed by the Coordinate Adabas DBs Outside the Group runtime control. .

error 588

Explanation A conflict with shared hold status option “H” has been detected. The client session is using this option in a conflicting manner during an ET or BT sequence after a two-phase commit process has been performed. The transaction outcome is unaffected but records may no longer be in shared hold status. The use of this option should be reviewed. .

error 596

Explanation The client runtime control “Adabas transaction dynamics” is set to “TP” in order to prevent Adabas transactions persisting across TP message-pairs and this error indicates such a transaction has been backed out.

This error is not applicable to client environments whose Adabas transactions are able to interoperate with other open vendor transactions (client runtime control “Open distributed transaction support = Yes”).

51 AVInnn - Adabas Vista Database Processing Messages

Messages related to Adabas Vista database processing may be displayed on the operator console during an Adabas nucleus session. These messages have the format:

```
AVInnn dddd Message Text
```

where *nnn* is the message number and *dddd* is the Adabas database number.

AVI001	{dddd} Vista Database Process; Enabled
Explanation	The Adabas Vista database process has been installed and initialized on this database.
Action	None. This message is for information only.
AVI002	{dddd} Vista Database Process; Getmain Error - nnnnnnnn bytes
Explanation	The Adabas Vista database process has not been able to initialize due to insufficient memory.
Action	Increase available memory by at least the amount indicated in the message.
AVI005	{dddd} Vista Database Process; Disabled
Explanation	The Adabas Vista database process has been disabled.
Action	Refer to a previous console message for the reason.

52

AVI-xxxx-xx - Adabas Vista Processing Messages

Adabas Vista messages related to client processing have the following format:

AVI-*nnnn*-*ss* Message Text

where *nnnn* is the message number and *ss* is a hexadecimal severity code:

Severity Code	Explanation
00	Software AG use
04	Information only
10	Warnings

AVI-0013-04

Config File is now available

Explanation

This message is issued after an AVI-0013-10 message when Adabas Vista detects that the configuration file has become available again.

Action

None. This message is for information only.

AVI-0013-10

One or more users were unable to access Config File

Explanation

The Adabas Vista configuration file is not currently available. One or more users have been allowed to continue processing although the partitioning and translation capabilities of Adabas Vista are not available to the user(s) until the configuration file becomes available.

Action

Check the availability of the Adabas Vista configuration file.

AVI-0015-10	Initialization error.....ADABAS VISTA is N O T active
Explanation	Adabas Vista was unable to initialize successfully and has been deactivated.
Action	Check the message text for the reason for the failure and if necessary contact your local Software AG representative.
AVI-0017-10	Config File Error (DdbidFfnr); Rspnnnnn Srspssss
Explanation	An Adabas response code was returned when accessing the Adabas Vista configuration file and the client runtime control Error Reporting WTO option is set to YES. The returned response code and subcode are indicated in the message.
Action	Ensure that the correct configuration file database and file number are being used. Refer to the <i>Adabas Messages and Codes</i> documentation for an explanation of the response code.
AVI-0018-10	Internal error (DdbidFfnr); Rsp00249 Srspssss
Explanation	An Adabas Vista processing error occurred and the client runtime control Error Reporting WTO option is set to YES. The Database ID and File Number provided indicate the source of the error. The response code 249 (ADARSP249) may be different depending on the value provided for the client runtime control Error Response Code. The subcode of the response code is also provided.
Action	For information about the subcode provided, refer to the subcodes provided for response code 249 (ADARSP249).
AVI-0019-10	Adabas Rspnnnnn Srspssss Srce: DdbidFfnr CC Targ: DdbidFfnr CC
Explanation	An Adabas response code was returned and the Error Reporting client runtime control's WTO option is set to YES. The response code and subcode are displayed. The Srce (application) database number, file number, command code and the Targ (resulting) database number, file number, command code are also displayed.
Action	This (optional) message is provided to warn of potential Adabas issues.
AVI-0020-04	Jobname: aaaaaaa Comm-ID: hhhhhhhhhhhhhhhh (aaaaaaa)
Explanation	After an Adabas Vista console message has been issued, this message is used to help identify the user responsible.
Action	None. This message is for information only.

53 CAS* - Adabas System Coordinator Cluster Application

Service Messages

CASnnn messages are issued from the clustered application service operating in the Adabas System Coordinator component.

CAS001I JOB jobname CREATED POOL poolname AT address length

Explanation A component task of a clustered application has started. The started task (job) is defined to use SYSCO to manage application users. User information is maintained in a common memory pool so that it can be shared with other components of the application.

This message is issued when the common memory pool is created.

Action None. This message is for information only.

CAS002I JOB jobname JOINED POOL poolname AT address length

Explanation A component task of a clustered application has started. The started task (job) is defined to use SYSCO to manage application users. User information is maintained in a common memory pool so that it can be shared with other components of the application.

This message is issued when the new task joins an existing memory pool.

Action None. This message is for information only.

CAS003I	POOL poolname DELETED AT address length
Explanation	All jobs using a common memory pool have terminated. The pool is deleted and its memory is released.
Action	None. This message is for information only.
CAS004I	JOB jobname ACTIVE
Explanation	A request was received to shut down a SYSCO daemon, but client jobs are still active on this daemon.
Action	Terminate the client job(s) and re-issue the shutdown request.
CAS005I	JOB jobname CREATED POOL EXTENT poolname AT address length
Explanation	A common memory pool is full and has been dynamically extended.
Action	None. This message is for information only.
CAS006E	JOB jobname CAS MANAGEMENT TERMINATED BY HALT
Explanation	CAS management has been terminated.
Action	No action, the HALT action has taken place as requested.
CAS007I	XCF PING FROM #####
Explanation	An XCF ping has been received.
Action	None. This message is for information only.
CAS008S	CANNOT LOAD CAS KERNEL CASKRN - SHUTDOWN INITIATED
Explanation	The clustered application service (CAS) kernel module cannot be loaded.
Action	Ensure that the load library containing the kernel module is available to the Adabas System Coordinator daemon task.
CAS009I	Sysco name node system users
Explanation	The header line for the CAS010I message.
Action	None. This message is for information only.

CAS010I	#####
Explanation	The details for the CAS009I message.
Action	None. This message is for information only.
CAS011E	COMMAND FAILED, RSP=####, RC=####
Explanation	A System Coordinator operator command has failed.
Action	This message is currently issued only in response to the DN (Display Active Nodes) command. The DN command is used to display Coordinator daemon nodes in a Sysplex configuration. Message CAS011E indicates that one or more nodes could not be contacted. Check the coordinator definitions and tasks to identify any setup problems that may have caused this error. Contact your Software AG technical representative for assistance if necessary.
	In a standard (non-sysplex configuration) the command will fail and message CAS011E is the normal response. No further action is required.
CAS012E	SESSION STATUS RSP=#### / ####, NO SESSION RECOVERY WILL BE ATTEMPTED
Explanation	An attempt to read the session status record failed. The daemon cannot determine if session or pool recovery is required.
Action	Determine the reason for the read failure. It will not be possible to recover any previous failed session if the status record cannot be located.
CAS013I	NO SESSION STATUS RECORD, PREVIOUS SESSION RECOVERY WILL NOT BE ATTEMPTED
Explanation	The configuration file does not contain a session status record. This message will be issued the first time the pool recovery feature is used, or whenever a new configuration file is used.
Action	None. It is assumed there is no previous failed session to recover.
CAS014E	SESSION UPDATE RSP=#### / ####, NO SESSION RECOVERY ACTIVE FOR THIS SESSION
Explanation	An attempt to update the session status record failed. Session recovery will not be active for this daemon instance.
Action	Determine the reason for the update failure. If session and pool recovery are required, restart the daemon when the problem is resolved.

CAS015E	SESSION STATUS UPDATE RSP #### / ####
Explanation	This message can only occur during normal termination of the daemon. An attempt to update the session status record with termination information failed.
Action	Determine the reason for the update failure. The next time the daemon is started it will probably attempt session recovery, but there will be no session to recover. Messages CAS013I or CAS017S may be issued, but can be ignored.
CAS016E	SESSION ANCHOR GETMAIN ERROR, NO SESSION RECOVERY ACTIVE FOR THIS SESSION
Explanation	The session anchor is a common memory area that saves recovery information for the duration of the session. Session recovery will not be active if the anchor cannot be allocated.
	Probable cause is insufficient common memory.
Action	Review system initialization parameters and current use of common memory.
CAS017S	PREVIOUS SESSION RECOVERY NOT POSSIBLE, SESSION ANCHOR NOT FOUND OR INVALID
Explanation	This message appears if the system is restarted after a daemon failure or if the anchor memory area is freed or overwritten by any other task.
	The session anchor is a common memory area that saves recovery information for the duration of the session. The configuration file status record holds the address of this anchor. When a session fails that session anchor is preserved in common memory until a new daemon session starts and recovers the failed session.
Action	None
CAS018W	SESSION RECOVERY COMPLETED
Explanation	The daemon detected that a previous daemon session failed. Session and pool recovery was invoked and has completed successfully.
Action	None.
CAS019E	PREVIOUS SESSION RECOVERY UNSAFE, RESTART AS SOON AS POSSIBLE
Explanation	An error has been detected during session and pool recovery. There is probably a memory corruption problem in one of the pools. The session may have been partially recovered.
Action	It is probably not safe to continue with the current daemon instance. It should be canceled and restarted. If this message re-occurs, contact your Software AG technical support representative.

CAS020W	POOL ##### RECOVERED FOR JOB ##### AT #####
Explanation	The daemon detected that a previous daemon session failed. The named pool was recovered.
Action	None.
CAS02II	Msg-out Msg-rsp Msg-in Msg-segs Cq-Num Cq-Hwm Cq-Full Cq-Post RspPost
Explanation	This message is issued when a Daemon DXCF command is issued, to display XCF messaging statistics. See the description of the DXCF command for an explanation of the message content.
Action	None.
CAS022I	#####
Explanation	This is the details part of the CAS021I message heading.
Action	None.

54

COR* - Adabas System Coordinator Kernel Messages

CORnnn messages are issued by the Adabas System Coordinator kernel.

COR001S	RUNTIME ENVIRONMENT CANNOT INITIALIZE, KERNEL LOAD ERROR
Explanation	The Adabas System Coordinator client (CORsnn) failed to locate or load the runtime kernel module CORKRN.
Action	Ensure that the load library containing the kernel module is available to the TP monitor or batch job that issued the message.
COR002S	RUNTIME ENVIRONMENT CANNOT INITIALIZE, CONFIGURATION FILE RESPONSE=nnnn, SUBCODE=nnnn
Explanation	A configuration module (CORCFG) has been located that indicates the SVC, DBID, and file number of the Adabas System Coordinator configuration file. An error occurred when trying to read this configuration file.
Action	Refer to the <i>Adabas Messages and Codes</i> documentation to determine the reason for the error.
COR003S	FAILED TO REGISTER JOB WITH COR DAEMON, ERROR=nnnnnnnn. SERVICE CONTINUING IN LOCAL MODE
Explanation	The job is defined to run in daemon-mode, but an active local daemon could not be found.
Action	The job continues in local mode. COR daemon services are not available. If daemon-mode is critical to the correct operation of the job or service you should designate one or more add-on products with the "CRITICAL" specification in the COR configuration module (CORCFG). See message COR040S for further information.

COR004S **GROUP group-name NOT FOUND IN CONFIGURATION FILE RESPONSE=nnnn, SUBCODE=nnnn**

Explanation An error occurred when attempting to read the defined group parameters.

Action If the Adabas System Coordinator group parameters have not been defined, use the SYSCOR online application to define them and resubmit the job.

COR005E **RUNTIME CONFIGURATION MODULE CORCFG NOT LOCATED – INITIALIZATION RETRY LATER**

Explanation The configuration module CORCFG cannot be loaded, without it System Coordinator and related products are unable to operate. The job continues without Coordinator but it will periodically try to find CORCFG so it can activate.

Action Refer to the Adabas System Coordinator Installation documentation for information about assembling a configuration module.

COR006S **NO MEMBERS DEFINED FOR DAEMON GROUP #####**

Explanation A job is defined to expect an Adabas System Coordinator group. The group has been defined but no daemon members have been defined within the group.

Action Use the SYSCOR online application to define required daemon members in the group.

COR007E **DAEMON NOT RUNNING FOR GROUP #####, JOB ##### CANNOT INITIALIZE**

Explanation A job is defined to expect an Adabas System Coordinator group, but none of the Coordinator daemons defined in the group are active on this system.

Action After ensuring that the local Coordinator daemon is started, restart the job.

COR008S **CANNOT LOCATE ID TABLE FOR SVC nnn**

Explanation A job is defined to expect an Adabas System Coordinator group, but no ID table was found for the Adabas SVC number specified in the group definition.

Action Use the SYSCOR online application to enter the correct SVC number in the group record.

COR009S **##### IXLCACHE READ ERROR, RC=##, RSN=###**

Explanation The Coordinator daemon is running in an IBM sysplex environment and is using the coupling facility. An error occurred when trying to access data from the coupling facility cache memory. The coupling facility may be improperly set up or defined.

Action Ensure that the cache structure is defined correctly in the Adabas System Coordinator group.

COR010S	##### IXLCACHE WRITE ERROR, RC=##, RSN=###
Explanation	The Coordinator daemon is running in an IBM sysplex environment and is using the coupling facility. An error occurred when trying to write data to the coupling facility cache memory. The coupling facility may be improperly set up or defined.
Action	Ensure that the cache structure is defined correctly in the Adabas System Coordinator group.
COR011I	MEMBER ##### JOINS ##### GROUP ##### ON SYSTEM #####
Explanation	The daemon has successfully joined the group.
Action	None. This message is for information only.
COR012S	MEMBER ##### FAILED TO JOIN SYSPLEX GROUP #####, RC=##, RSN=###
Explanation	The Coordinator daemon failed to connect to the sysplex group. The sysplex may not be properly defined. The return and reason codes are from the IXCJOIN macro.
Action	Consult the <i>IBM Sysplex Services Reference</i> to determine the cause of the problem.
COR013I	MEMBER ##### LEAVES ##### GROUP ##### ON SYSTEM #####
Explanation	The Coordinator daemon has left the group.
Action	None. This message is for information only.
COR014E	MEMBER ##### ERROR LEAVING SYSPLEX GROUP #####, RC=##, RSN=###
Explanation	The Coordinator daemon failed to correctly leave the group.
Action	Consult the <i>IBM Sysplex Services Reference</i> to determine the cause of the problem.
COR015S	IXCQUERY ERROR, RC=##, RSN=###
Explanation	A z/OS IXCQUERY service failed. The return and reason codes are from the IXCQUERY macro.
Action	This is an internal error. Contact your Software AG technical support representative.
COR016S	##### IXLCONN ERROR, RC=##, RSN=###
Explanation	The Coordinator daemon is running in an IBM sysplex environment and using the coupling facility. An error occurred when trying to connect to the coupling facility cache structure defined in the Adabas System Coordinator group record.
Action	Ensure that the required cache structure is defined in the CFRM policy for this sysplex.

COR017I	NO RUNTIME CONTROL FOUND FOR ##### - ADD-ON PRODUCTS ARE DEACTIVATED
Explanation	The configuration file does not contain a runtime control record for this job. The Adabas System Coordinator and installed products will be deactivated until a run-time control is defined and the job is restarted. It is likely that the Adabas System Coordinator link stub was added to the link module but no runtime control was defined for the job.
Action	Use one of the online administration applications (SYSAVI, SYSAFP, SYSATM) to define a runtime control; then restart the job.
COR018E	##### ixlcache dirinfo error, rc=##, rsn=####
Explanation	An error occurred when retrieving directory information from the coupling facility cache structure.
Action	Consult the IBM Sysplex Services Reference to determine the cause of the error.
COR019E	##### ICXMSGO SENDTO ##### ERROR, RC=##, RSN=###
Explanation	An error occurred when sending a message from one Coordinator daemon to another in an IBM sysplex.
Action	Consult the <i>IBM Sysplex Services Reference</i> to determine the cause of the error.
COR020I	SYSPLEX INTERFACE COMMAND QUEUE AT #####
Explanation	Issued at startup of a Coordinator daemon, this message displays the address of the command queue used for communication among the Coordinator daemons.
Action	None. This message is for information only.
COR021S	IOR FAILURE FUNC ## ERRCODE ##
Explanation	An error occurred during an ADAIOR service call.
Action	Contact your Software AG technical support representative for assistance.
COR022S	##### IXLCACHE DELETE ERROR, RC=##, RSN=###
Explanation	The Coordinator daemon is running in an IBM sysplex environment and is using the coupling facility. An error occurred when trying to delete data from the coupling facility cache memory. The coupling facility may be improperly set up or defined.
Action	Ensure that the cache structure is defined correctly in the Adabas System Coordinator group.

COR023S	##### IXLCACHE STATS ERROR, RC=##, RSN=###
Explanation	The Coordinator daemon is running in an IBM sysplex environment and is using the coupling facility. An error occurred when trying to read statistical information from the coupling facility cache memory.
Action	Ensure that the cache structure is defined correctly in the Adabas System Coordinator group. Note: This message will appear if you attempt to use the SYSCOR session monitoring "Display cache statistics" service, and the Coordinator daemon is not running with a coupling facility cache structure.
COR024E	CONFIGURATION FILE database / file READ ERROR (RSP ###), OPTIONAL PRODUCT CALLS BYPASSED
Explanation	System Coordinator suffered a problem using the configuration file. The job continues running unless one or more products are identified as being critical.
Action	Investigate the cause of the bad response code and take corrective action so that it no longer occurs.
COR025E	NO DAEMON ACTIVE FOR SYSCO GROUP #####, OPTIONAL PRODUCT CALLS BYPASSED
Explanation	System Coordinator has been unable to contact a daemon in the specified group. It is able to continue running but calls to non-critical products are bypassed.
Action	Activate the daemon for the group.
COR026E	CONFIGURATION FILE database / file READ ERROR (RSP ###) JOB ##### WAITING FOR ACTIVATION
Explanation	The database containing the configuration file is not active, and it has been requested (in the CORCFG configuration module) that client jobs should wait for the file to be activated. Adabas System Coordinator will attempt to read the configuration file every 15 seconds.
Action	Activate the database containing the configuration file as soon as possible.
COR027E	NO DAEMON ACTIVE FOR SYSCO GROUP #####, JOB ##### WAITING FOR ACTIVATION
Explanation	System Coordinator has been unable to contact a daemon in the specified group. The job is paused, pending daemon activation.
Action	Activate the daemon for the group.

COR028E **CONFIGURATION FILE database / file READ ERROR (RSP ###), INITIALIZATION DEFERRED FOR JOB #####**

Explanation The job parameter could not be read from the configuration file. Initialization of System Coordinator and add-on products is deferred.

It is likely that the database containing the configuration file is inactive (response code 148, ADARSP148).

The COR client will automatically attempt a periodic retry if it receives an error reading the configuration file. This avoids the need to recycle jobs when the file becomes available again.

Action Activate the database containing the configuration file as soon as possible.

COR029E **DAEMON NOW RUNNING FOR GROUP #####, JOB #####**

Explanation System Coordinator has now detects the presence of a daemon.

Action None.

COR030I **RESPONSE ###, RETRY ACTIVE FOR FILE database / file, JOB=#####,**
COMMAND=##

Explanation Command retry has been activated for the indicated response code, and it has been specified that a console message is to be issued whenever an retry is attempted.

Action Take appropriate (installation-defined) action.

COR031I **RESPONSE ###, RETRY ABANDONED FOR FILE database / file, JOB=#####,**
COMMAND=##

Explanation The required number of command retries has been attempted, but the command has still not completed successfully. Retry is abandoned.

Action Take appropriate (installation-defined) action.

COR032S **Memory Pool enable failure, RC=#####, Pool=#####**

Explanation BS2000 only. A request to enable a memory pool has failed.

Action Contact your Software AG technical support representative.

COR033S **Memory Pool allocation failure, RC=#####,Pool=#####**

Explanation BS2000 only. There has been an error during allocation of a System Coordinator memory pool. The failure is probably due to a shortage of memory in the global memory pool defined in the Coordinator group parameter for the service.

Action Increase the size of the global memory pool in the group definition.

COR034S	KERNEL(CORKRN) NOT FOUND, SERVICE CANNOT CONTINUE
Explanation	One or more add-on products has been defined with the "CRITICAL" specification in the configuration module (CORCFG). The Coordinator kernel module could not be located and the product will not function correctly. All Adabas requests will be rejected with response 101 subcode 58.
Action	Make the load library containing the COR kernel available, and restart the job or service.
COR035S	SERVICE CANNOT CONTINUE, CRITICAL PRODUCTS ARE NOT OPERATIONAL
Explanation	One or more add-on products has been defined with the "CRITICAL" specification in the configuration module (CORCFG). System Coordinator, or the product itself has detected that some product component is missing or not operational. In Adabas client jobs all Adabas requests will be rejected with response 101 subcode 59. This message can also be issued in Adabas nucleus jobs when System Coordinator fails to find or load a critical Adabas module (usually ADALNK). There will normally be another COR or product message identifying the component in error.
Action	Correct the error and restart the job or service.
COR036S	Runtime environment cannot initialize, initial allocation failed
Explanation	The Adabas System Coordinator client (COR S_{nn}) was unable to acquire enough storage to initialize.
Action	Increase the amount of memory available to the job and restart it.
COR037I	SVC dump created
Explanation	The Adabas System Coordinator daemon has produced an SVC dump dataset as a result of an abend. This message is only issued on z/OS systems when CORCFG specifies ZOSDUMP=SVC .
Action	None
COR038E	SVC dump failed, R15: hhhhhhhh
Explanation	The Adabas System Coordinator daemon was configured to produce an SVC dump in the event of an abend. The SVC dump failed with the indicated error code (hhhhhhh) and a standard dump was produced instead.
Action	Review the IBM SDUMPX documentation to determine the reason for the failure.

COR039S **IBM STORAGE KEY OVERRIDE NOT ENABLED, COMPLETE THREAD KEYS CANNOT BE USED**

Explanation Complete thread keys can only be supported when the IBM Storage Key Override is enabled.

Action Enable IBM Storage Key Override or disable Complete thread keys.

COR040S **FAILED TO REGISTER JOB WITH COR DAEMON, ERROR=nnnnnnnn. CRITICAL SERVICE CANNOT CONTINUE**

Explanation The job is defined to run in daemon-mode, but an active local daemon could not be found. One or more add-on products have been defined with the "CRITICAL" specification in the configuration module (CORCFG). In this mode, the daemon is considered to be critical to the correct operation of the job. All Adabas requests will be rejected with response code 101 (ADARSP101), subcode 59.

Action Make sure that the Coordinator daemon is active and restart the job or service.

COR041I **REVERTING TO DEFAULT CONSOLE USAGE AFTER ERROR : #####**

Explanation System Coordinator has received an error using the alternate console and has reverted to using the default console.

Action None. This message is for information only.

COR042I **"XCF" is not supported. Terminating.**

Explanation XCF is not supported for this operating system.

Action Correct the daemon group parameters.

COR043I **Task #### is stalled by task @@@@**

Explanation This message is issued by a UTM task (#### identifies the task) when it cannot operate because another task (identified by @@@@) is blocking it. The message is issued at intervals of five minutes, until the blockage is cleared.

Action Determine if task @@@@ is looping, hanging or just running slowly. If it is looping or hanging, cancel it to clear the blockage. If it is just running slowly, the blockage will clear itself.

COR045I **Co-ordinated stop set for User=userid, TID=aaaaaaa**

Explanation This message is a response to a successful co-ordinated stop request where userid is the Adabas-assigned user ID and aaaaaaaa is the terminal ID (alphanumeric).

Action None. This message is for information only.

COR046S	SPAWN FAILED RC=##
Explanation	An internal error has occurred during daemon processing.
Action	Contact your Software AG technical support representative.
COR047S	Installation error. COR is disabled.
Explanation	An installation error has been detected. This is usually accompanied by another error message explaining the installation error.
Action	Correct the installation error and re-try. If the problem persists, contact your Software AG technical support representative for further assistance.
COR048S	PRODUCT ## PACK FAILED RC=##
Explanation	An internal error has occurred during latency processing.
Action	Contact your Software AG technical support representative.
COR049S	PRODUCT ## UNPACK FAILED RC=##
Explanation	An internal error has occurred during latency processing.
Action	Contact your Software AG technical support representative.
COR050S	LATENCY FILE ##### FAILED RC=####
Explanation	An internal error has occurred during latency processing.
Action	Contact your Software AG technical support representative.
COR052I	SERVICE ##### STARTED USING ##### LATENCY (#####)
Explanation	System Coordinator has successfully started the named service. The type of latency used and whether the service is single or multi system is also displayed.
Action	None. This message is for information only.
COR053I	SERVICE ##### ENDED
Explanation	System Coordinator has successfully ended the named service.
Action	None. This message is for information only.

COR054S	COR054S JOB ##### REQUIRES DAEMON LATENCY ON DISK; LATENCY INITIALIZATION FAILED IN DAEMON ADDRESS SPACE
Explanation	A client job has been defined to use a daemon latency file. However the daemon does not have a latency file.
Action	Correct the configuration.
COR055I	Co-ordinated stop set for STOPI=nnn
Explanation	This message is a response to a successful co-ordinated stop request where <i>nnn</i> is the dormant session time applied.
Action	None. This message is for information only.
COR060I	Connected to daemon: #####
Explanation	A client job has been defined to use a daemon service and to issue daemon communication messages and has successfully connected to daemon node #####.
Action	None. This message is for information only.
COR061I	Disconnected from daemon: #####
Explanation	A client job has been defined to use a daemon service and to issue daemon communication messages and has successfully disconnected to daemon node #####.
Action	If the disconnection is unexpected, check that the daemon is active and accessible.
COR064I	UB extension enforcement activated – length ###
Explanation	A client job has been defined to use a product that requires a UB extension of the indicated length, however the Adabas link module has not been configured to provide a suitable UB extension. System Coordinator adjusts the UB dynamically as appropriate.
Action	Correct the Adabas LGBLSET LUINFO parameter and reinstall the Adabas link module/globals table. Note: <i>this message is always issued for SPATs clients that execute participating triggers (if the SPATs job is defined to use a product that requires a UB extension).</i>
COR065I	Input parameter: #####
Explanation	The input parameter ##### included in the daemon services DDCARD input has been processed.
Action	None. This message is for information only.

COR066E	Invalid parameter: #####
Explanation	The parameter ##### included in the daemon services DDCARD input is invalid.
Action	Correct the DDCARD parameter. .
COR067E	Getmain for product parm block failed'
Explanation	The DDCARD input parameters could not all successfully be processed due a lack of memory.
Action	Increase the region size for the job.
COR069I	PMAF: eye=#### len=##### owner=### releaser=****
Explanation	This message indicates that some internal memory has been released by a different product to the one that allocated it. This is an informational message and in itself is not an indication of a problem.
Action	None. This message is for information only.
COR072I	UTM Memory Pool short on storage, Pool=#####
Explanation	A client job has been unable to allocate enough memory for the thread from the UTM Pool #####. System Coordinator will try to allocate a smaller thread, but this may limit the activity of some users.
Action	Increase the UTM Pool size in the UTM Client Runtime Controls (see <i>UTM pool settings</i> in your Adabas System Coordinator documentation).
COR073I	Configuration file database/file in use for job #####
Explanation	This message indicates that the client has successfully read the System Coordinator configuration file. It will only be issued if one of the following messages has previously indicated that there was a problem reading the configuration file: <ul style="list-style-type: none"> ■ COR002S ■ COR026E ■ COR028E
Action	None. This message is for information only.
COR074I	Dataspace ##### created, token #####
Explanation	This message indicates that the named dataspace has been created by the Adabas System Coordinator daemon.
Action	None. This message is for information only.

- COR075I** **Enabling access to #####, token #####**
Explanation This message indicates that the address space within which this job is running is about to connect to the named dataspace.
Action None. This message is for information only.

 To suppress this message, refer to the client runtime control *Daemon connection messages* in the *Adabas System Coordinator Parameters* documentation.
- COR076I** **Access to ##### enabled, token #####**
Explanation This message indicates that the address space within which this job is running has successfully connected to the named dataspace.
Action None. This message is for information only.

 To suppress this message, refer to the client runtime control *Daemon connection messages* in the *Adabas System Coordinator Parameters* documentation.
- COR077E** **Access to ##### failed, token #####**
Explanation This message indicates that the address space within which this job is running failed to connect to the named dataspace.
Action Contact your Software AG technical support representative.
- COR078E** **Error managing ##### Function=## RF=##### R0=#####**
Explanation An internal error has occurred when managing the named dataspace.
Action Contact your Software AG technical support representative.

55

CORD* - Adabas System Coordinator Daemon Messages

CORDnn messages are issued by the Adabas System Coordinator daemon.

CORD01S	CAS CANNOT INITIALIZE, GETMAIN ERROR
Explanation	The Adabas System Coordinator cannot initialize because of a memory shortage.
Action	Increase the region specification for the daemon job.
CORD02S	CAS CANNOT INITIALIZE, KERNEL LOAD ERROR
Explanation	The daemon failed to locate or load the runtime kernel module CORKRN.
Action	Ensure that the load library containing the kernel module is available to the job.
CORD03E	DDCARD OPEN ERROR: ## - TERMINATING
Explanation	The DDCARD control file could not be opened.
Action	Ensure that the daemon job has a DDCARD file containing the required control cards.
CORD04I	INPUT PARAMETER: #####
Explanation	The input parameters contained in the DDCARD file are echoed in the job message output file.
Action	None. This message is for information only.

CORD05E	INVALID PARAMETER: #####
Explanation	An invalid input parameter was found in the DDCARD file. The daemon terminates.
Action	Correct or delete the invalid parameter.
CORD06E	PRODUCT PARAMETER NOT SPECIFIED
Explanation	There was no <code>PRODUCT</code> parameter in the DDCARD file. The daemon does not know which product(s) to load.
Action	Add the required <code>PRODUCT</code> parameter and restart the daemon.
CORD07E	MPM FAILURE - FUNCTION: ## ERROR ##
Explanation	An error occurred calling <code>ADAMP</code> when trying to: <ul style="list-style-type: none">■ initialize a target (Function=00)■ sign off from the Adabas SVC (Function=20)■ sign on to the Adabas SVC (Function=24)
Action	For a sign on error, navigate to the Daemon Group Parameters in the System Coordinator Online system and ensure that the correct SVC and Node ID have been specified for the Adabas System Coordinator group. A sign-off error indicates an internal problem with the System Coordinator Daemon. Contact your Software AG technical support representative for assistance. No action is required in the Coordinator Daemon.
CORD08E	IOR FAILURE - FUNCTION: ## ERROR ##
Explanation	An error occurred during an <code>ADAIOR</code> service call.
Action	Contact your Software AG technical support representative for assistance.
CORD09I	SHUTDOWN REQUESTED
Explanation	The daemon has received a shutdown request.
Action	None. This message is for information only.
CORD10E	GETMAIN FOR COMMAND QUEUE FAILED
Explanation	The daemon cannot acquire memory for the command queue.
Action	Increase the region specification for the Adabas System Coordinator daemon task.

CORD11I	CORD11I SYSCO ##### IS ACTIVE ON NODE ##### ## CIB=#####
Explanation	The daemon successfully signed on to the Adabas SVC and is ready for communication. The message indicates the node and SVC number used.
Action	None. This message is for information only.
CORD12I	OPER TYPEIN: #####
Explanation	The operator entered a console command to the daemon. The command is echoed back to the message output file.
Action	None. This message is for information only.
CORD13E	INVALID OPERATOR COMMAND
Explanation	The command entered is not valid.
Action	Correct the command and enter it again.
CORD14I	TARGET ##### TERMINATION IN PROGRESS
Explanation	The daemon is terminating because of operator request or unrecoverable error.
Action	None. This message is for information only.
CORD15I	TARGET ##### ENDED NORMALLY
Explanation	The daemon terminated normally as a result of an operator request.
Action	None. This message is for information only.
CORD16S	TARGET ##### ENDED ABNORMALLY
Explanation	The daemon terminated abnormally as a result of a previous error.
Action	A previous message will identify the cause of the abnormal termination. Examine the message and take appropriate recovery action.
CORD17E	PRODUCT ### DUPLICATED
Explanation	The daemon has detected multiple copies of the PRODUCT= card for a single product.
Action	Remove the duplicate entries and restart the daemon.

- CORD18E** **TOO MANY PRODUCTS SPECIFIED**
Explanation The daemon has detected too many copies of the PRODUCT= card.
Action Correct the PRODUCT= cards and restart the daemon.
- CORD19E** **PRODUCT ### - WORK AREA CANNOT BE ALLOCATED**
Explanation This is an internal error.
Action Contact your Software AG technical support representative for assistance.
- CORD20E** **INVALID PARAMETERS - TERMINATING**
Explanation The daemon has detected invalid parameter cards and has shut down.
Action Correct the parameter cards and restart the daemon.
- CORD21I** **OPERATOR COMMAND PROCESSED SUCCESSFULLY**
Explanation An operator command completed successfully.
Action None. This message is for information only.
- CORD22E** **LOAD FOR MODULE: ##### FAILED**
Explanation The requested module could not be located or loaded.
Action Ensure that the requested module is available to the Adabas System Coordinator daemon task.
- CORD23I** **PARAMETERS FOR THIS RUN:**
Explanation The parameters in use in this instance of the daemon.
Action None. This message is for information only.
- CORD24I** **##### = #####**
Explanation Along with CORD23I gives details of the parameters in use in this instance of the daemon.
Action None. This message is for information only.
- CORD25E** **### IS AN INVALID PRODUCT NAME**
Explanation The daemon has detected invalid an invalid product name.
Action Correct the product name and restart the daemon.

CORD26E	PROXY MODULE ##### WAS NOT FOUND, PRODUCT ### WILL NOT BE CALLED
Explanation	The daemon has been told to run with PRODUCT= <i>mmm</i> but cannot find <i>mmm</i> PXY.
Action	Ensure the daemon has access to all the products required and restart the daemon.
CORD27S	INVALID PRODUCT TABLE ENTRY FOR ###
Explanation	This is an internal error.
Action	Contact your Software AG technical support representative.
CORD28E	CAS PROXY MODULE ##### FOR PRODUCT ### IS INVALID (BAD EYECATCHER)
Explanation	The requested module could not be located or loaded.
Action	Contact your Software AG technical support representative.
CORD29E	CAS PROXY MODULE ##### FOR PRODUCT ### IS NOT SUPPORTED BY THIS VERSION OF CAS
Explanation	This is an installation error.
Action	Ensure that all product libraries used in the daemon are the same version.
CORD30E	GETMAIN FOR PRODUCT PARM BLOCK FAILED
Explanation	A memory allocation failed during the initialization.
Action	Increase the region specification for the job.
CORD31E	CAB ALLOCATION ERROR IN MODULE SYSCORU
Explanation	A memory allocation failed during the initialization of the daemon.
Action	Increase the region specification for the job.
CORD33S	APPEND OF PRODUCT V-CON LIST FAILED.
Explanation	Explanation This is an internal error.
Action	Contact your Software AG technical support representative.

CORD34E	ASA ALLOCATION ERROR IN MODULE SYSCORU
Explanation	A memory allocation failed during the initialization of the daemon.
Action	Increase the region specification for the job.
CORD35S	CONFIGURATION MODULE ##### CORCFG CANNOT BE LOCATED
Explanation	The configuration module cannot be loaded. This module contains the SVC, DBID, and file number for reading the configuration file. The daemon will not function correctly without this module.
Action	Refer to the Adabas System Coordinator Installation documentation for information about assembling a configuration module.
CORD36S	SVC/NODE DDCARD INPUT IS INVALID WITH PRODUCT=CAS
Explanation	This is an internal error.
Action	Contact your Software AG technical support representative.
CORD37S	SYSCO DAEMON member-name NOT FOUND IN CONFIGURATION FILE, RESPONSE=nnnn, SUBCODE=nnnn
Explanation	The named Adabas System Coordinator group member was not found in the group in the configuration file. Every daemon must have an equivalent group member parameter.
Action	Add the member entry for this daemon to the appropriate Adabas System Coordinator group.
CORD38S	GROUP group-name NOT FOUND IN CONFIGURATION FILE, RESPONSE=nnnn, SUBCODE=nnnn
Explanation	The named group cannot be located.
Action	An error occurred while searching for the Adabas System Coordinator group parameters. Define the Adabas System Coordinator group. If the problem persists, contact your Software AG technical support representative.
CORD39I	SHUTDOWN PENDING
Explanation	A shutdown request was entered. One or more of the subcomponents of the Adabas System Coordinator daemon suspended the request until it completes its own shutdown processing. The daemon should terminate when this is completed.
Action	None. This message is for information only.

CORD40S	ABEND #### PSW #####
Explanation	An error occurred in the Adabas System Coordinator daemon. The registers, PSW, and failing module at the time of the error are displayed. The Adabas System Coordinator writes additional diagnostic information to the CORDUMP file, deletes any common memory pools in use, and terminates.
Action	Contact your Software AG technical support representative.
CORD41S	CSECT ##### ENTRY ##### OFFSET #####
Explanation	Additional information to CORD40S.
Action	Contact your Software AG technical support representative.
CORD42S	MODULE ##### ENTRY ##### OFFSET #####
Explanation	Additional information to CORD40S.
Action	Contact your Software AG technical support representative.
CORD43S	REGS #####
Explanation	Additional information to CORD40S.
Action	Contact your Software AG technical support representative.
CORD44I	PROXY ##### LOADED AT #####
Explanation	The address of the named proxy module.
Action	None. This message is for information only.
CORD45E	THREAD ##### TIMEOUT, TARGET=#####, USER=#####
Explanation	The Adabas System Coordinator daemon sent an Adabas command to the indicated target, and has not received a response within the timeout interval as specified by DDCARD parameter CT.
Action	Check that the target database is operating correctly. If the problem persists, try increasing the CT timeout value. If there is still a problem, contact your Software AG technical support representative.
CORD46I	##### Start pending, configuration file (dbid ##### fnr #####) not active
Explanation	An Adabas System Coordinator daemon has been started, but the required configuration file is not active. The daemon will wait for 60 seconds and try again. If the configuration file is still not active after 60 minutes the daemon will terminate.
Action	Start the database that contains the configuration file.

CORD47S	Halt-Load library is not Authorized
Explanation	z/OS only. An Adabas System Coordinator daemon has been started from a load library that is not APF-authorized.
Action	Ensure the specified load library is authorized and restart the daemon.
CORD49I	PRODUCT COMPONENT ENDED - ###
Explanation	The named product has ended.
Action	None. This message is for information only.
CORD50E	Shutdown rejected
Explanation	A daemon shutdown request was made, but there are active client DTR jobs connected to the daemon. This message will be preceded by message CAS004I, identifying the names of the active DTR job(s).
Action	Terminate the active client jobs and re-issue the shutdown request.
CORD51S	XCF CQ OVERFLOW – DAEMON RESTARTED
Explanation	There has been an overflow in the XCF command queue (see NXC parameter) of the current daemon resulting in a daemon restart.
Action	None. This message is for information only and indicates an exceptionally high volume of XCF messages in this System Coordinator group.
CORD52I	Configuration file: database / file
Explanation	This message shows the database ID and file number of the configuration file in use by this System Coordinator daemon.
Action	None. This message is for information only.
CORD53I	Alternate file : database / file
Explanation	This message shows the database ID and file number of the alternate configuration file in use by this System Coordinator daemon. The message only appears if an alternate configuration file has been specified.
Action	None. This message is for information only.

CORD54W	##### shutdown rejected, configuration file ##### / ##### not active
Explanation	An Adabas System Coordinator daemon has been instructed to terminate, but an alternate configuration file is in use and one or both configuration files is not active. Both configuration files must be available at daemon termination.
Action	Ensure that the configuration file database(s) are active.
CORD56E	Latency file error: ##### - ##### rc=#####
Explanation	A latency file error has occurred in the Adabas System Coordinator daemon. The message indicates the function attempted, the reason for failure, and a return code. Some of the more common reasons for failure are listed below, otherwise contact your Software AG technical support representative.
Action	“BR allocation failure” – review/increase the size of the COLAT latency file. “### getmain failure” - review and increase the storage available in the daemon region.
CORD57I	Recovery for ##### found ##### sessions at rest
Explanation	The Adabas System Coordinator daemon has been restarted after a failure and full crash recovery was active at the time of failure for the job/service indicated. This message identifies the number of sessions recovered for the services/job so they can continue without interruption if possible.
Action	This message is for information only, no action is needed.
CORD58I	Service AbTerm resource manager termination-type term
Explanation	The System Coordinator daemon resource manager was invoked at address-space (<i>termination-type</i> indicates AddrSpc) or task (<i>termination-type</i> indicates Task) termination .
Action	None. This message is for information only.
CORD59I	Resource manager activation failed, rc=hhhhhhhh
Explanation	The System Coordinator daemon was unable to activate its resource manager. <i>hhhhhhhh</i> indicates a reason for the failure.
Action	The daemon continues without its resource manager. Contact Software AG support to establish the reason for the failure.

- CORD60S** **Failure: Continuous Operation has been initiated for ###**
Explanation A failure has occurred in the component identified in the message. Continuous operation processing has been invoked to restart the appropriate component(s).
Action None. This message is for information only.
- CORD61I** **### STORAGE AREA RELEASED**
Explanation This is an information message during continuous operation recovery.
Action Report it to your Software AG technical support representative.
- CORD62E** **Continuous operation error: ##### rc=#####**
Explanation The System Coordinator daemon was attempting to recover following a failure but an error occurred trying to do so.
Action Contact your Software AG technical support representative.
- CORD63I** **Continuous operation recovery for ##### found ##### sessions at rest**
Explanation The Adabas System Coordinator daemon was restarted following a failure and has recovered the job/service indicated. This message identifies the number of sessions recovered for the services/job so they can continue without interruption.
Action None. This message is for information only.
- CORD64S** **Shutdown activated owing to recursive failure**
Explanation There has been more than one failure in a period of 30 minutes. Continuous operation is abandoned and the daemon terminates.
Action None. This message is for information only.
- CORD65S** **SHARED MEMORY ANCHOR AT #####**
Explanation Issued at startup of a Coordinator daemon, this message displays the address of the daemon's shared memory anchor.
Action None. This message is for information only.
- CORD66S** **SHARED MEMORY GETMAIN FAILED**
Explanation Issued at startup of a Coordinator daemon, when it has been configured to use shared memory for latency/pulse services but the attempt to allocate shared memory failed.
Action The daemon continues, using private memory for latency services (pulse services are disabled). Review the daemon's shared memory definitions and ensure that sufficient shared memory is available. Consider using a dataspace in preference to standard shared memory.

CORD70I	Resource Size Current Highwater
Explanation	CORD70I messages are displayed in response to a DRES operator command and show allocated size, current usage and high-water mark for various daemon resources.
Action	None. This message is for information only.
CORD71W	WARNING – XCF CQ 80% FULL
Explanation	This is a one time only warning message that the XCF command queue is 80% full, potentially a sign of an imminent overflow.
Action	Use the DRES operator command to monitor the XCF command queue. If a high percentage continues to be in use, this may indicate a high number of updates to files being optimized by Adabas Fastpath . This is not recommended and should be investigated. Note that if the number continues to increase then an overflow will occur when the maximum XCF command queue entries is reached, resulting in a CORD51S message and daemon auto-restart.
CORD72E	MPM FAILURE - FUNCTION: ## ERROR ## JOB=##### SESSION=#####
Explanation	An error occurred calling ADAMPM when trying to: <ul style="list-style-type: none"> ■ Get the command queue element (CQE) (Function=08) ■ Post command completion to caller (Function=12) ■ Timeout (Function=36)
Action	This message indicates a problem with the daemon caller. The message identifies the calling Job and Session ID. It may also be accompanied by an Adabas “User Gone” message (ADAM91 or ADAM92), also identifying the calling Job and Session ID. Examine the calling job to determine the reason for the failure. Probably the job has abnormally terminated. No action is required in the Coordinator Daemon.
CORD73E	Command permitted only for zIIP-enabled daemon
Explanation	The use of this operator command requires zIIP support to have been activated in the Daemon.
Action	In order to activate zIIP support for the Daemon, set ZIIP=YES in the Daemon runtime parameters.

CORD74I **zIIP-related statistics: Daemon is executing in {SRB | TCB} mode ... (processor-related statistics) ... (CPU consumption statistics) ... (SRB/TCB use statistics) ... (extended pause/release statistics) ... (type-of-work statistics) ...**

Explanation In response to the operator command DZSTAT, these messages display the zIIP-related statistics of the Daemon.

The first line shows the current execution mode: "SRB" (execution on zIIP enabled) or "TCB" (execution on zIIP disabled).

The following statistics correspond, and are equivalent to, the zIIP-related statistics at the end of the Daemon session statistics. Refer to Monitoring zIIP Usage in section "Adabas System Coordinator for zIIP" in the *Adabas System Coordinator* documentation for detailed information about the various statistical figures.

Action None. This message is for information only.

CORD75I **Daemon is now executing in TCB mode**

Explanation In response to the operator command ZIIP=NO, this message indicates the Daemon is now executing in TCB mode (disabling the use of System z Integrated Information Processors). The ZIIP parameter value was changed to NO, from YES.

Action None. This message is for information only.

CORD76I **Daemon is already executing in TCB mode**

Explanation In response to the operator command ZIIP=NO, this message indicates the Daemon was already executing in TCB mode (disabling the use of System z Integrated Information Processors). The ZIIP parameter value was not changed; it was already NO.

Action None. This message is for information only.

CORD77I **Daemon is now executing in SRB mode**

Explanation In response to the operator command ZIIP=YES, this message indicates the Daemon is now executing in SRB mode (enabling the use of System z Integrated Information Processors). The ZIIP parameter value was changed to YES, from NO.

Action None. This message is for information only.

CORD78I **Daemon is already executing in SRB mode**

Explanation In response to the operator command ZIIP=YES, this message indicates the Daemon was already executing in SRB mode (enabling the use of System z Integrated Information Processors). The ZIIP parameter value was not changed; it was already YES.

Action None. This message is for information only. .

CORD79I	Operator command not executable
Explanation	The command entered is not executable.
Action	This message should be preceded by another message which explains the reason why this command could not be executed.
CORD80E	Unable to check license
Explanation	An internal error has occurred during license validation processing.
Action	First verify that the LICMAIN (MLC) module is available in the STEPLIB, otherwise increase the region size available to the Adabas System Coordinator Daemon..
CORD81E	Error opening license file (DDLAZPAD)
Explanation	An error occurred opening the license file specified by the DDLAZPAD statement.
Action	Omit the DDLAZPAD statement and use the load module method of licensing instead.
CORD82E	Error reading license file (DDLAZPAD)
Explanation	An empty file or invalid record structure was detected.
Action	Verify that the license file has been copied correctly to the license data set. The file should not be empty and the data should not have been converted to EBCDIC (it should be in ASCII format).
CORD83E	License file size exceeds limit
Explanation	The license being read is larger than expected.
Action	Verify that you are using the original license file obtained from Software AG.
CORD84E	Error license function fx subfunction sfx returned err
Explanation	An unexpected error occurred while performing the Adabas System Coordinator for zIIP license check. The license function (<i>fx</i>), subfunction (<i>sfx</i>) and return code (<i>err</i>) are given in the message.
Action	Examine the Adabas System Coordinator Daemon JCL and verify that the AZPAD license is available as load module AZPADLIC or is assigned with the link (DD) name DDLAZPAD.

CORD85I	License check completed
Explanation	The license check completed successfully and the Adabas System Coordinator Daemon is started.
Action	None. This message is for information only.
CORD86E	License check failed (AZPAD)
Explanation	The license file is physically correct, but some license property was found that did not match your Adabas System Coordinator Daemon execution environment. This is a final message, accompanied by another message specifying details of the failure. The Adabas System Coordinator Daemon is started but will execute in TCB mode (disabling the use of System z Integrated Information Processors). The ZIIP parameter value was changed to NO, from YES.
Action	Check the accompanying message(s) for the details of the failure. If necessary, contact your Software AG technical support representative.
CORD88I	...daemon statistics...
Explanation	In response to the operator command DSTAT, these messages display either general, disk or services related daemon statistics. Refer to the DSTAT operator command in section Daemon Operator Commands of the <i>Adabas System Coordinator</i> documentation for detailed information regarding the statistics provided.
Action	None. This message is for information only.
CORD89I	Connected to Cache Facility structure #####
Explanation	The daemon has succeeded in connecting to the named Cache Facility structure. This message is only applicable for members of a daemon group defined with a System Type of IBM Parallel Sysplex.
Action	None. This message is for information only.
CORD90I	COLAT Statistics:
Explanation	These messages are displayed at Daemon start-up and show general information about the size and usage of the COLAT latency disk file. Disk blocks are allocated on demand for Jobs/Services defined to use Disk Latency.
Action	None. This message is for information only.

56

CWARN* - Caching Facility Error Messages

When errors are detected during the processing of the input statements, the appropriate warning message is displayed indicating the cause of error. The remaining portion of the statement is ignored and processing continues with the next statement. All input statements and warning messages are displayed only on DD/PRINT.



Note: Messages generated during Adabas Caching Facility operations are documented in *Adabas Console Messages (ADANnn)* starting with ADAN80.

CWARN-126	Illegal RABN range, overlapping extents
Explanation	A CASSO _{xxx} or CDATA _{xxx} parameter specified a RABN range that overlaps a previously specified RABN range. Adabas Caching Facility ignores this latest RABN range.
CWARN-127	Illegal starting/ending RABNs
Explanation	A CASSO _{xxx} or CDATA _{xxx} parameter specified an invalid RABN; that is, a RABN equal to zero, or an ASSO RABN range that falls entirely within the restricted ASSO RABNs 1-30.
CWARN-128	Retry < 60, setting to 60
Explanation	The CRETRY parameter must be set between 60 and 2,147,483,647. The specified value is less than 60; the default is 60.

CWARN-129	RABN(s) outside of GCB, RABN(s) ignored
Explanation	A CASSO _{xxx} or CDATA _{xxx} parameter specified a RABN range that exceeded the highest RABNs contained in the GCBs. Adabas Caching Facility ignores the remaining parameters that specify RABN ranges.
CWARN-130	A/D DSS < 81,920, using default size
Explanation	A CASSOMAXS or CDATAMAXS parameter specified a value less than 81,920. The default for CASSOMAXS or CDATAMAXS os used.
CWARN-131	CRETRY > 2,147,483,647, setting to maximum
Explanation	The CRETRY parameter must be set between 60 and 2,147,483,647. The specified value is greater than the maximum; the default is the maximum 2,147,483,647.
CWARN-132	CWORK2FAC/CWORK3FAC cannot exceed 100
Explanation	The percentage factor cannot exceed 100 percent. The invalid factor is ignored, and the default 0 is taken.
CWARN-133	CMAXCSPS > 16, setting to 16
Explanation	The CMAXCSPS parameter must be set between 1 and 16. The specified value is greater than 16; the default is 16.
CWARN-134	Incorrect CSTO or CWORKSTO storage type
Explanation	A CSTORAGE or CWORKSTORAGE parameter did not specify extended memory, data space, hiperspace, or 64-bit virtual storage. If the error occurred for CSTORAGE, no storage type is established. If the error occurred for CWORKSTORAGE, the default type of DATASPACE is established.
CWARN-135	CBUFNO invalid in SMP or sysplex
Explanation	The CBUFNO parameter is not supported in an Adabas Parallel Services or an Adabas Cluster Services environment. Adabas Caching Facility ignores the parameter.
CWARN-136	CEXCLUDE invalid in SMP or sysplex
Explanation	The CEXCLUDE parameter is not supported in an Adabas Parallel Services or an Adabas Cluster Services environment. Adabas Caching Facility ignores the parameter.

CWARN-140 File caching parameter error; invalid {xxxx}

Explanation

While processing a request to start caching for a file, an error was encountered in the data supplied on the request. This can be caused by errors in CFILE parameters, CFILE operator commands, or operator requests. The request is rejected and the file is not cached.

xxxx	description of error as follows:	
	File number	file number does not exist
	Scope	the scope is not ASSO, DATA, or BOTH
	Class of service	the class is not 1 through 5
	Cache type	the type is not extended memory, data spaces, hiperspace, or 64-bit virtual storage.

Note: Virtual 64 and hiperspace are not available in all environments and, if requested, may generate the above error.

Action

Correct the invalid CFILE parameter, correct the CFILE operator command, and reissue it or issue a valid Adabas Online System request.

57

DSF* - Delta Save Facility Messages

- Nucleus-Related Console Messages (DSF001 - DSF029, DSF02A-D) 902
- Utility-Related Job Protocol Messages for ADARES and ADASAV (DSF030 - DSF099) 907

This section lists and describes all messages that can occur when operating the Adabas Delta Save Facility Facility.

For messages displayed on the operator console, each line begins with the message number followed by the database ID. For messages returned in the job protocol, the message number occurs only once and the database ID is not displayed.

Nucleus-Related Console Messages (DSF001 - DSF029, DSF02A-D)

This section lists and describes all messages displayed by the Delta Save Facility during an Adabas nucleus session. These messages all appear on the operator console.

DSF001	Running with Delta Save Facility
Explanation	The nucleus has been started with ADARUN parameter DSF=YES. Delta Save functions can be performed in this nucleus session.
DSF002	The DSF logging area is not installed
Explanation	This is a Delta Save Facility status message. Delta save operations require a Delta Save logging (DLOG) area, which must be created.
Action	To run with Delta Save, use the Adabas Online System Install DSF function to define the logging area.
DSF003	DSF logging is disabled
Explanation	This is a Delta Save Facility status message. Delta save operations are not possible.
DSF004	DSF logging is enabled
Explanation	This is a Delta Save Facility status message. Delta save operations are possible in this status.
DSF005	{count} DLOG area blocks out of {total} used ({nn}%) Pending DLOG area overflow; perform Delta Save operation
Explanation	This message indicates how much of the Delta Save logging (DLOG) area is being used. The second line of the message is only printed if the DLOG area usage is 90 percent or more; that is, nearly full. If the area overflows, Delta Save operations will no longer be possible.
Action	If DLOG area overflow is pending, perform a Delta Save operation before the area overflows.

DSF006	DSF logging area not initialized Reinstall the DLOG area
Explanation	Initialization of the Delta Save logging (DLOG) area was interrupted. The DLOG area must be installed again.
Action	Remove the DLOG area and install it again.
DSF007	DSF logging area not initialized DSF logging not enabled at end of save
Explanation	Initialization of the Delta Save logging (DLOG) area was interrupted. An online full save operation was completed but Delta Save logging was not enabled at the end of the save. Delta save operations are still not possible.
Action	Remove the DLOG area and install it again. Perform another full save operation.
DSF008	I/Os initiated by Delta Save Facility: {read-count} reads, {write-count} writes
Explanation	This message, which is printed during shutdown of the Adabas nucleus, indicates the number of I/O operations initiated by Delta Save during the current nucleus session.
DSF011	Online full save operation completed
Explanation	Unless this message is displayed, an online full save operation with the Delta Save Facility is not successful, even though ADASAV may have already closed the output save data set.
Action	The Delta Save logging area is reset. If Delta Save logging was disabled, it will be enabled.
DSF012	Online Delta Save operation completed
Explanation	Unless this message is displayed, an online Delta Save operation is not successful, even though ADASAV may have already closed the output save data set.
Action	The Delta Save logging area is reset.
DSF013	Delta Save ID = {fsnum} / {dsnum} / {date-time}
Explanation	This message follows messages DSF005, DSF011, or DSF012. It displays the Delta Save identification of the most recent completed full or Delta Save operation. <i>fsnum</i> is the full save number, and <i>dsnum</i> is the number of the Delta Save operation.

DSF014	DSF login has been enabled
Explanation	This message follows messages DSF011 and DSF013 if Delta Save logging was previously disabled. It was enabled at the end of the operation. Delta save operations are now possible.
DSF015	Disable DSF requested by AOS command
Explanation	A Disable DSF command was issued by Adabas Online System.
Action	Delta Save logging will be disabled.
DSF016	DSF logging has been disabled
Explanation	The reason for this follows from a preceding message. Delta save operations are no longer possible.
Action	Perform a full save operation before retrying a Delta Save operation.
DSF017	Initializing the DSF logging area
Explanation	An Install DSF or Change DLOG Area command has been issued through Adabas Online System.
Action	The Delta Save logging area is now being initialized. Message DSF018 indicates that initialization is complete.
DSF018	The DSF logging area has been {installed changed}
Explanation	An Install DSF or Change DLOG Area command was completed.
DSF019	The DSF logging area has been removed
Explanation	A Remove DSF command was performed, or the nucleus was started with DSF=NO and has removed the Delta Save logging area.
DSF020	DSF logging area overflow
Explanation	The volume of changes made to the database exceeded the capacity of the Delta Save logging (DLOG) area. The DLOG area is full. No more Delta Save operations are possible.
Action	Delta Save logging will be disabled. Perform a full save operation before retrying a Delta Save operation. Increase the DLOG area or the frequency of Delta Save operations in order to avoid future DLOG area overflow.

DSF021	I/O error {reading writing} DLOG RABN {ravn}
Explanation	An I/O error occurred within the Delta Save logging (DLOG) area on the specified Associator RABN. If Delta Save logging is enabled, it will be disabled.
Action	Determine the cause of the I/O error and eliminate it. Remove the DLOG area and install it again.
DSF022	Fatal I/O error {reading writing} DLOG header RABN {ravn}
Explanation	An I/O error occurred on the first block (the specified RABN) of the Delta Save logging (DLOG) area. Caution: Warning: Do not try to execute a Delta Save operation if this error occurs. Even though the Delta Save may end successfully, the output may be invalid. The Delta Save Facility terminates the nucleus abnormally.
Action	Determine the cause of the I/O error and eliminate it. Remove the DLOG area and install it again.
DSF023	DLOG area header RABN {ravn} bad (# {rr}) Reinstall DLOG area or DLOG area detail RABN {ravn} bad (# {rr} at +{xxxx} Reinstall DLOG area
Explanation	An inconsistency was detected in the specified block (<i>ravn</i>) of the Delta Save logging (DLOG) area. <i>ravn</i> is the Associator block number, <i>rr</i> is an internal reason code, <i>xxxx</i> the offset within the block where the error appeared. If Delta Save logging is enabled, it will be disabled.
Action	Determine the cause of the problem; consult your Software AG technical support representative if necessary. Remove the DLOG area and install it again.
DSF024	Inconsistent Delta Save ID in DLOG RABN {ravn}
Explanation	An inconsistency was detected in the specified block (<i>ravn</i>) of the Delta Save logging (DLOG) area. <i>ravn</i> is the Associator block number. If Delta Save logging is enabled, it will be disabled.
Action	Determine the cause of the problem; consult your Software AG technical support representative if necessary. Remove the DLOG area and install it again.

DSF025	DSF logging not disabled because READONLY=YES
Explanation	An attempt to disable Delta Save logging failed because the nucleus was started with READONLY=YES.
	Another attempt will be made to disable Delta Save logging in the next nucleus session.
Action	Shut down the nucleus and restart it with READONLY=NO so that Delta Save logging can be disabled.
DSF026	Unlogged RABN(s) detected: {type start-rabn end-rabn}
Explanation	An internal cross-check detected that database blocks were written that had not been logged by Delta Save. The type (Asso/Data) and range of RABNs written are displayed.
	Delta Save logging will be disabled.
Action	This is a serious problem. Contact your Software AG technical support representative. Perform a full save operation before retrying a Delta Save operation.
DSF027	Insufficient memory (trying to allocate {count} bytes)
Explanation	The Delta Save Facility was not able to obtain sufficient memory for its operation. The number of bytes of memory specified by <i>count</i> were requested.
	The start of the nucleus session is ended.
Action	Increase the region/partition of the nucleus job/task or decrease the memory requirements derived from the nucleus parameters.
DSF028	DSF version mismatch; reinstall DLOG area
Explanation	The version of the Delta Save Facility software and the version of the Delta Save logging (DLOG) area are different and incompatible.
	If Delta Save logging is enabled, it will be disabled.
Action	Remove the DLOG area and install it again.
DSF028	Converting from DSF {xx} to DSF {yy}
Explanation	The format of the Delta Save logging (DLOG) area is converting from version <i>xx</i> to version <i>yy</i> . This occurs during conversion of an older Adabas version to a newer one.
	Depending on the versions of the Delta Save Facility (that is, <i>xx</i> and <i>yy</i>), Delta Save logging may be disabled if it is enabled.
Action	If Delta Save logging is disabled, perform a full save operation before retrying a new Delta Save operation.

DSF029	DSF internal error at ADADSFN + {offset} ({reason-code}) R0-R3 {xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx} R4-R7 {xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx} R8-R11 {xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx} R12-R15 {xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx}
Explanation	An internal error occurred at the specified <i>offset</i> in module ADADSFN. <i>reason-code</i> is an internal reason code. The register settings at the time of the error are shown.
	If Delta Save logging is enabled, it will be disabled.
Action	Consult with your Software AG technical support representative to determine the cause of the problem. Perform a full save operation before retrying a Delta Save operation.
DSF02A	Percentage error in DSF user exit; {nn}% is used
Explanation	The DSF user exit returned an invalid threshold value (percentage of DLOG area usage at or above which Adabas is to call the exit). Adabas calls the DSF user exit when the usage of the DLOG area is nn% or more.
DSF02C	Current DLOG block not found in cache, read from disk
Explanation	The DLOG block currently referenced is not in the coupling facility cache structure and must be read anew from the disk data sets.
DSF02C	Current DLOG block written to cache
Explanation	The DLOG block currently referenced is already held in the coupling facility cache structure.
DSF02D	Write of current DLOG block to cache failed
Explanation	An attempt to write the DLOG block currently referenced from a disk data set to the coupling facility cache structure failed. Probably, the cache structure is full.
Action	Enlarge the size of the cache.

Utility-Related Job Protocol Messages for ADARES and ADASAV (DSF030 - DSF099)

The messages in this section are displayed by the Delta Save Facility during ADARES or ADASAV utility execution. They can occur in Adabas utility operations, either as direct utility messages or as the result of utility-related nucleus operation.

Most messages appear in the utility job protocol (DD/DRUCK or SYSLST); others appear in the ADARUN protocol (DD/PRINT, SYS009 or SYSOUT). A few messages appear in the utility job protocol as well as on the operator console; this is indicated in the explanation of these messages.



Note: Messages begin with the relevant database ID when they are written to the operator console.

DSF030	DSIM dataset omitted from PLCOPY processing
Explanation	The ADARUN parameter DSF=YES was specified for a PLCOPY execution but no Delta Save images (DSIM) data set was supplied in the job control. No system action occurs; no online save information is extracted from the protection log.
Action	If Delta Save online save and merge operations are to be performed, specify a DSIM data set for the PLCOPY executions.
DSF031	SYN1 checkpoint encountered on protection log PLOGNUM={plog-number} BLOCKNUM={ravn}
Explanation	A SYN1 checkpoint (online save start) was found on the protection log. The protection log number is <i>plog-number</i> , the SYN1 block number is <i>ravn</i> . The Delta Save Facility starts extracting online save information from the protection log and writing it to the Delta Save images (DSIM) data set.
DSF032	SYN2 checkpoint encountered on protection log PLOGNUM={plog-number} BLOCKNUM={ravn}
Explanation	A SYN2 checkpoint (online save end) was found on the protection log. The protection log number is <i>plog-number</i> , the SYN2 block number is <i>ravn</i> . The Delta Save Facility stops extracting online save information from the protection log. The Delta Save images (DSIM) data set is marked ready for merge.
DSF033	SYN1 checkpoint ignored on protection log. PLOG and block numbers different from parameters checkpoint found has PLOGNUM={plog-number}, SYN1={block-number}
Explanation	A SYN1 checkpoint (online save start) was found on the protection log. The protection log number is <i>plog-number</i> , the SYN1 block number is <i>block-number</i> . These values are different from the PLOGNUM and SYN1 parameters specified for the COPY function. The Delta Save Facility does not start extracting online save information from the protection log. The SYN1 checkpoint is ignored.

DSF033	SYN1 checkpoint ignored on protection log DSIM dataset already completed
Explanation	<p>A SYN1 checkpoint (online save start) was found on the protection log but the Delta Save images (DSIM) data set is by now ready for merge.</p> <p>The SYN1 checkpoint is ignored.</p>
DSF033	SYN1 checkpoint ignored on protection log DSIM dataset status incorrect: {status-code}
Explanation	<p>A SYN1 checkpoint (online save start) was found on the protection log but the Delta Save images (DSIM) data set is not in a correct status. The current DSIM status <i>status-code</i> is shown.</p> <p>The SYN1 checkpoint is ignored.</p>
Action	Rebuild the DSIM data set using the ADARES COPY function.
DSF033	SYN1 checkpoint ignored on protection log online save operation started afterwards
Explanation	<p>A SYN1 checkpoint (online save start) was found on the protection log but was written before the start of the online save operation associated with the DSIM data set. Therefore, the checkpoint does not indicate the start of the online save operation for which information is to be extracted from the protection log.</p> <p>The SYN1 checkpoint is ignored.</p>
Action	None. If there is only one SYN1 checkpoint on the protection log to be copied and the message cannot be otherwise explained, check whether the Adabas nucleus and the ADASAV utility that is executing the online save operation were running on different machines or on different divisions of the same machine. If so, ensure that the local times of these two machines or divisions are accurately synchronized.
DSF034	SYN2 checkpoint ignored on protection log DSIM dataset status incorrect: {status-code}
Explanation	<p>A SYN2 checkpoint (online save start) was found on the protection log but the previous SYN1 checkpoint was ignored because of the incorrect status of the Delta Save images (DSIM) data set. The current DSIM status <i>status-code</i> is shown. See the corresponding DSF033 message.</p> <p>The SYN2 checkpoint is ignored.</p>
Action	Rebuild the DSIM data set using the ADARES COPY function.

DSF036	DSIM dataset opened with status: {status}
Explanation	(printed on the ADARUN protocol) The Delta Save images (DSIM) data set has been opened. Its current status is shown.
DSF037	DSIM dataset status changed to: {status}
Explanation	(printed on the ADARUN protocol) The Delta Save images (DSIM) data set status has been changed to the new one shown.
DSF038	DSIM dataset closed with status: {status}
Explanation	(printed on the ADARUN protocol) The Delta Save images (DSIM) data set has been closed. Its current status is shown.
DSF039	DSIM dataset completed DSIM dataset statistics: {nn}% full {asso-count} ASSO block images written {data-count} DATA block images written {ac-count} new AC blocks recorded
Explanation	<p>The Delta Save images (DSIM) data set has been completed and marked ready for merge. Statistics displayed include</p> <ul style="list-style-type: none">■ its percentage of use;■ the number of Asso and Data block images contained in the DSIM data set (block counts do not differentiate several images of the same block); and■ the number of address converter blocks allocated during the associated online save operation and recorded in the DSIM data set.
DSF040	[[dbid]] Waiting for DSIM dataset
Explanation	<p>This message, which is printed on the operator console with a <i>dbid</i> and on the ADARUN protocol without a <i>dbid</i>, indicates that the Delta Save images (DSIM) data set is not yet ready for merge. The DSIMWAIT parameter has been specified to wait for the completion of the DSIM data set.</p> <p>The Delta Save Facility waits until the DSIM data set is ready for merge, or until the maximum wait time (DSIMWAIT) has been exceeded.</p>
DSF041	DSF logging area {nn}% full at begin of save
Explanation	This message indicates how much of the Delta Save logging (DLOG) area is already being used at the beginning of a Delta Save operation.

DSF042	[[{dbid}] {offline online} {full delta} save operation completed DSID= {fsnum dsnum date-time}]
Explanation	<p>The specified type of save operation was completed successfully. The ID of the Delta Save operation (DSID) is displayed: <i>fsnum</i> and <i>dsnum</i> are the numbers of the full and Delta Save operation, respectively.</p> <p>For an offline save operation, this message is also written to the operator console with a <i>dbid</i>. For an online save, the Adabas nucleus writes equivalent information in the DSF011-DSF013 messages.</p> <p>For an offline save operation, the Delta Save logging (DLOG) area is reset. For a full save operation, if Delta Save logging was disabled, it will be enabled</p> <ul style="list-style-type: none"> ■ by ADASAV for an offline save operation; or ■ by the nucleus for an online save operation.
DSF043	[[{dbid}] DSF logging enabled by offline full save
Explanation	<p>This message occurs following message DSF042. Delta Save operations are now possible. Unless this message is displayed, an offline full save operation with the Delta Save Facility is not successful, even though ADASAV may have already closed the output save data set.</p> <p>This message is also written to the operator console with a <i>dbid</i>.</p>
DSF044	Delta Save statistics: {asso-count} ASSO blocks to be saved {data-count} DATA blocks to be saved
Explanation	(printed at the beginning of a Delta Save operation) The number of Associator and Data Storage blocks to be saved.
DSF045	Input {offline online} {full data} save tape opened DSID= {fsnum lowdsnum-hidsnum date-time}
Explanation	In a MERGE or RESTORE DELTA operation, an input save data set with the stated Delta Save identification was opened. <i>fsnum</i> is the full save number; <i>lowdsnum</i> the low Delta Save number, and <i>hidsnum</i> the high Delta Save number of the save data set.
DSF045	Input {offline online} Delta Save tape opened (concatenated) DSID= {fsnum lowdsnum-hidsnum date-time}
Explanation	In a MERGE or RESTORE DELTA operation, an input Delta Save data set with the stated Delta Save identification was opened. The Delta Save data set was concatenated to another Delta Save data set. <i>fsnum</i> is the full save number; <i>lowdsnum</i> the low Delta Save number, and <i>hidsnum</i> the high Delta Save number of the save data set.

DSF045	Input online Delta Save tape opened (unloaded DSIM) DSID= {fsnum / dsnum / date-time}
Explanation	In a MERGE or RESTORE DELTA operation, an input online Delta Save data set with the stated Delta Save identification was opened. The Delta Save data set is an unloaded DSIM data set. <i>fsnum</i> is the full save number; <i>dsnum</i> the Delta Save number of the save data set. If the originating DSIM data set was (re)built from the PLOG using the ADARES COPY function, the DSID is unknown and shown as zeros.
DSF046	Restored delta without full save input DSID of database = {fsnum hidsnum date-time}
Explanation	In a delta restore operation without full save input the database has the stated Delta Save identification. The associated full and Delta Save data sets were restored previously. The value <i>fsnum</i> denotes the full save number, <i>hidsnum</i> is the highest Delta Save number of the save data sets already restored.
DSF047	[[dbid]] Output offline {full delta} save tape completed DSID= {fsnum lowdsnum-hidsnum date-time}
Explanation	In a MERGE operation, the indicated output save data set has been completed. Its Delta Save identification is shown. <i>fsnum</i> denotes the full save number. <i>lowdsnum</i> is the low Delta Save number and <i>hidsnum</i> is the high Delta Save number. This message is also written to the operator console with a <i>dbid</i> .
DSF047	[[dbid]] Output online Delta Save tape completed (unloaded DSIM) DSID= {fsnum dsnum date-time}
Explanation	In a MERGE operation, an unloaded DSIM Delta Save data set with the Delta Save identification shown has been written. <i>fsnum</i> denotes the full save number; <i>dsnum</i> is the Delta Save number. If the originating DSIM data set was (re)built from the PLOG using the ADARES COPY function, the DSID is unknown and shown as zeros. This message is also written to the operator console with a <i>dbid</i> .
DSF048	[[dbid]] Restore of {(merged) full (concatenated) delta } save tape [(s)] completed restored Delta Save ID= {fsnum lowdsnum-hidsnum / date-time}
Explanation	A phase of a delta restore operation has been completed. One or more save tapes have been restored. Their combined Delta Save identification is shown. A subsequent delta restore operation without full save input may begin with the Delta Save data set that has the next higher Delta Save identification. <i>fsnum</i> is the full save number. The value <i>lowdsnum</i> is the low Delta Save number, and <i>hidsnum</i> is the high Delta Save number. This message is also written to the operator console with a <i>dbid</i> .

DSF049	DSIM dataset statistics: {asso-count} ASSO blocks present {data-count} DATA blocks present
Explanation	This message is printed when the Delta Save images (DSIM) data set is examined and matches one of the online save input data sets. It is also printed when the DSIM data set is to be unloaded. The DSIM data set contains <i>asso-count</i> different Associator blocks and <i>data-count</i> different Data blocks to take part in the operation.
DSF050	DSF logging are not installed
Explanation	Without a Delta Save logging (DLOG) area installed and Delta Save logging enabled, it is not possible to perform Delta Save operations. The Delta Save operation is abnormally terminated.
Action	Use Adabas Online System to install a DLOG area and perform a full save operation to enable Delta Save logging.
DSF051	DSF logging not enabled
Explanation	Delta Save logging must be enabled before Delta Save operations are possible. The attempted Delta Save operation is abnormally terminated.
Action	Perform a full save operation to enable Delta Save logging.
DSF052	DSIM dataset omitted from online save operation
Explanation	When running with Delta Save (ADARUN parameter DSF=YES is specified), a Delta Save images (DSIM) data set must be provided for an online full or Delta Save operation. The online save operation is abnormally terminated.
Action	Supply a DSIM data set for the online save operation or perform the save operation offline.
DSF053	DSIM dataset not ready for save
Explanation	The Delta Save images (DSIM) data set must be "not in use" to be eligible for a Delta Save Facility online save operation. The current status of the DSIM data set is different, as shown. The online save operation is abnormally terminated.
Action	Determine whether the DSIM data set is required for merging a previously created online save tape. If not, reset the DSIM data set (using ADAFRM function DSIMRESET) and rerun the save operation.

DSF054	Online save failed at ET synchronization
Explanation	<p>Execution of ET-synchronization at the end of the online save operation was not successful. The Delta Save logging (DLOG) area was not reset. Delta Save logging remains disabled if it was disabled before, or enabled if it was enabled before. A subsequent ADASAV error message indicates the nucleus response code for the failed ET-synchronization.</p> <p>Although it has already been closed, the created save data set must not be used for later merge or restore operations.</p> <p>The online save operation is abnormally terminated.</p>
Action	Eliminate the cause of the error and rerun the online save operation.
DSF055	Online save successful in spite of nucleus response
Explanation	<p>Execution of ET-synchronization at the end of the online save operation was successful. The Delta Save logging (DLOG) area was reset. Afterwards, an error occurred and caused a nucleus response code to be returned to ADASAV. A subsequent ADASAV error message indicates the response code returned by the nucleus. If Delta Save logging was disabled before, it has been enabled.</p> <p>ADASAV prints an error message but continues operation. When terminating normally, it will set condition code 4.</p>
Action	The created save tape is valid and may not be dropped if Delta Save operations are to follow later on. Otherwise the succeeding Delta Save data sets cannot be merged and/or restored.
DSF057	Unloading DSIM dataset
Explanation	Only the DSIM data set has been specified for processing. No full or Delta Save input data set has been supplied.
Action	ADASAV unloads the DSIM data set to the sequential output save data set and frees the DSIM data set for the next online save operation.
DSF058	[[{dbid}]] Full save tape restored-DSF logging enabled restored Delta Save ID = {fsnum / lowdsnum - hidsnum / date-time}
Explanation	<p>A full save tape created by the Delta Save Facility was restored. The Delta Save identification of the restored database is shown. <i>fsnum</i> is the full save number; <i>lowdsnum</i> is the low delta save number; and <i>hidsnum</i> is the high Delta Save number of the save data sets restored.</p> <p>This message is also written to the operator console with a <i>dbid</i>.</p> <p>Delta Save logging was enabled in the restored database.</p>
Action	The next save operation can be a Delta Save. Its result can be merged with the full save that was input to the restore operation.

DSF059	Removing DSF logging area (DSF=NO specified)
Explanation	A full save created by the Delta Save Facility is to be restored but the ADARUN parameter DSF=NO has been specified. The Delta Save logging (DLOG) area will be removed. The restore operation continues normally.
Action	None required. If the restored database is to be run with the Delta Save Facility, install the DLOG area again.
DSF060	Insufficient inputs for merge or restore delta
Explanation	The input data set requirements for <ul style="list-style-type: none"> ■ functions MERGE and RESTORE DELTA: at least one full or Delta Save data set must be supplied. ■ unloading the DSIM data set (function MERGE): only the DSIM data set must be supplied. No full or Delta Save input is allowed. <p>The MERGE or RESTORE DELTA operation is abnormally terminated.</p>
Action	Supply suitable input data sets. If the function is RESTORE DELTA, rerun the job with RESTORE instead of RESTORE DELTA.
DSF061	Input save tape coming from wrong database
Explanation	In a merge or delta restore operation, the database ID of an input save data set is different from that specified in the ADARUN DBID parameter. Both database IDs are shown. The merge or delta restore operation is abnormally terminated.
Action	Supply the proper save tape or correct the ADARUN DBID parameter.
DSF062	Invalid specification of input data sets in JCL/JCS
Explanation	In a merge or delta restore operation, the input save data sets are not specified correctly: <ul style="list-style-type: none"> ■ a Delta Save data set is supplied instead of a full save data set; ■ a full save data set is supplied instead of a Delta Save data set; ■ a gap exists in the DD-names/link-names for the Delta Save data sets; ■ a save data set was not created by a save operation with the Delta Save Facility; ■ a save data set was not created at the current Adabas level; ■ the input data set does not contain a save data set header record; ■ the input data set was not created by ADASAV. <p>The merge or delta restore operation is abnormally terminated. The DD-name/link-name of the offending input data set is displayed.</p>

Action Supply the proper input save tapes and rerun the job.

DSF063 DSIM dataset missing or in wrong status

Explanation The original or unloaded Delta Save images (DSIM) data set is required for processing an online save data set in a MERGE or RESTORE DELTA operation, but it either

- has not been specified;
- has an incorrect status; or
- has been specified in the wrong logical sequence.

The MERGE or RESTORE DELTA operation is abnormally terminated.

Action Provide the correct DSIM data set; rebuild it if necessary. Rerun the job.

DSF065 Input full and Delta Save tapes not fitting together

Explanation The specified input full and Delta Save data sets do not cover a continuous sequence of save operations. Their Delta Save identifications (DSIDs) do not match, because one or more of the following is true:

- the full save numbers are not the same;
- the sequence of delta save numbers is not ascending without gaps (overlapping delta save numbers are allowed);
- in the sequence of full and Delta Save inputs, unloaded DSIM data sets are not specified directly after the associated online save.
- the dates and times are not ascending.

For a RESTORE DELTA operation without full save input, the DSID of the database takes part in this matching of DSIDs. The DSIDs matched have been displayed in previous messages.

The MERGE or RESTORE DELTA operation is abnormally terminated.

Action Provide the correct input save data sets in the correct sequence. Rerun the job.

DSF066 DSIM dataset does not match online save tape

Explanation A provided original or unloaded Delta Save images (DSIM) data set is not the one associated with the specified input online save data set. It does not contain the block images written during the online save operation that created the save data set.

The DSIM data set's full save number, Delta Save number, and database ID are shown. Further, the protection log number and protection log block number of the save operation's SYN1 checkpoint are displayed for both the DSIM data set and the online save data set. For associated online save and DSIM data sets, these SYN1-related numbers must be identical.

The MERGE or RESTORE operation is abnormally terminated.

Action	Provide the right DSIM data set and/or input save data sets. Rerun the job.
DSF067	Mismatching merge/restore pattern
Explanation	The delta merge/restore pattern specified in the PATTERN parameter does not match the input full and Delta Save data sets supplied.
	The delta merge or delta restore operation is abnormally terminated.
Action	Check and correct the PATTERN parameter and the job control statements. Rerun the job.
DSF068	Invalid save data set concatenation
Explanation	Another data set was concatenated to one of the input data sets (the DD-name/link-name of the input data set is shown). Input save data set concatenation is allowed only if <ul style="list-style-type: none"> ■ the function is RESTORE DELTA (not MERGE); and ■ save data sets are concatenated to the last input save in logical sequence. The MERGE or RESTORE DELTA operation is abnormally terminated.
Action	Correct the specification of input data sets and rerun the job.
DSF070	DSIM dataset smaller than specified
Explanation	An I/O error occurred when Delta Save Facility tried to read the last block of the Delta Save images (DSIM) data set. It is probably smaller than specified.
	Building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.
Action	Correct the DSIMSIZE parameter or supply a correct DSIM data set. If the function was PLCOPY, rebuild the DSIM data set using the COPY function. Otherwise, rerun the COPY function.
DSF071	Protection log and DSIM dataset do not match
Explanation	The protection log and the Delta Save images (DSIM) data set belong to different databases. The two database IDs are shown.
	No online save information will be extracted from the protection log during this ADARES execution. Building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.

Action Provide the correct protection log or rebuild the DSIM data set. If the function was PLCOPY, rebuild the DSIM data set using the COPY function. Otherwise rerun the COPY function.

DSF072 Cannot locate SYN1 checkpoint on protection log

Explanation The specified SYN1 checkpoint on the protection log was not found. The specified SYN1 position and the current position on the protection log are shown.

No online save information will be extracted from the protection log during this ADARES execution. Building the DSIM data set is discontinued. The COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified, a subsequent ADARES error abnormally terminates the function.

Action Supply matching protection log and parameter inputs, then rerun the job.

DSF074 Discontinuity in protection log processing

Explanation The first block of the protection log to be processed is not continuous with the last block processed before. Extracting block images for building the Delta Save images (DSIM) data set must proceed in sequence. The current position on the protection log and the last position of the previous PLCOPY execution are shown.

No online save information will be extracted from the protection log during this ADARES execution. Building the DSIM data set is discontinued. The PLCOPY function will continue processing. When terminating normally, the function will set condition code 4.

Action Rebuild the DSIM data set using the COPY function.

DSF075 DSIM dataset overflow

Explanation The Delta Save images (DSIM) data set is not large enough to hold all block images written during the accompanying online save operation. This DSIM data set cannot be used for merging.

The DSIM data set is set to an error status. The PLCOPY function will continue processing. When terminating normally, the function will set condition code 4.

Action Enlarge the DSIM data set and rebuild it using the COPY function before performing the merge operation.

DSF076	DSIM dataset overflow
Explanation	<p>The Delta Save images (DSIM) data set is not large enough to hold all block images written during the accompanying online save operation. This DSIM data set cannot be used for merging.</p> <p>The DSIM data set is set to an error status. The COPY function will continue processing. When terminating normally, the function will set condition code 4. If no sequential output data set was specified, a subsequent ADARES error abnormally terminates the function.</p>
Action	Augment the DSIM data set and run the COPY function again before performing the merge operation.
DSF079	Illegal multiple use of DSIM dataset detected
Explanation	<p>The Delta Save images (DSIM) data set was modified by another utility while</p> <ul style="list-style-type: none"> ■ the ADARES PLCOPY or COPY function was writing online save information extracted from the protection log to it; or ■ the ADASAV MERGE function was reading online save information from it. <p>The DSIM data set is inconsistent.</p> <p>In ADASAV, the MERGE function is abnormally terminated. In ADARES, the DSIM data set is set to an error status. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.</p>
Action	Avoid parallel usage of the DSIM data set in the future. If the function was PLCOPY, rebuild the DSIM data set using the COPY function. If the function was COPY, rerun the COPY function. If the function was MERGE, rebuild the DSIM data set using the COPY function and rerun the MERGE function.
DSF080	Error occurred during execution of read DLOG {ior-error-text} ASSO RABN: {dec-rabn} ({hex-rabn})
Explanation	<p>An I/O error occurred when the Delta Save Facility was trying to read a block from the Delta Save logging (DLOG) area. An ADAIOR error text is given. The affected Associator RABN is shown in decimal <i>dec-rabn</i> and hexadecimal <i>hex-rabn</i> formats.</p> <p>The save function is abnormally terminated.</p>
Action	Determine the cause of the I/O error and eliminate it. Remove the DLOG area and install it again. Perform a full save operation.

DSF081	Error occurred during execution of write DLOG {ior-error-text} ASSO RABN: {dec-rabn} ({hex-rabn})
Explanation	<p>An I/O error occurred when the Delta Save Facility was trying to write a block to the Delta Save logging (DLOG) area. An ADAIOR error text is given. The affected Associator RABN is shown in decimal <i>dec-rabn</i> and hexadecimal <i>hex-rabn</i> formats.</p> <p>The save function is abnormally terminated.</p>
Action	Determine the cause of the I/O error and eliminate it. Remove the DLOG area and install it again. Perform a full save operation.
DSF082	Error occurred during execution of open DSIM {ior-error-text}
Explanation	<p>An error occurred when the Delta Save Facility was trying to open the Delta Save images (DSIM) data set. An ADAIOR error text is given. The job control is probably incorrect, or the DSIMDEV parameter is missing or wrong.</p> <p>In ADASAV, the function is abnormally terminated. In ADARES, no online save information will be extracted from the protection log during this ADARES execution. Building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.</p>
Action	Check and correct the job control and/or the DSIMDEV parameter. If the function was ADARES PLCOPY, rebuild the DSIM data set using the ADARES COPY function. Otherwise rerun the job.
DSF083	Error occurred during execution of read DSIM {ior-error-text} RABN: {dec-rabn} ({hex-rabn})
Explanation	<p>An I/O error occurred when the Delta Save Facility was trying to read a block from the Delta Save images (DSIM) data set. An ADAIOR error text is given. The affected DSIM RABN is shown in decimal <i>dec-rabn</i> and hexadecimal <i>hex-rabn</i> formats.</p> <p>In ADASAV, the function is abnormally terminated. In ADARES, no more online save information will be extracted from the protection log during this ADARES execution. Building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.</p>
Action	Determine the cause of the I/O error and eliminate it. Rebuild the DSIM data set.

DSF084	Error occurred during execution of write DSIM {ior-error-text} RABN: {dec-rabn} ({hex-rabn})
Explanation	<p>An I/O error occurred when the Delta Save Facility was trying to write a block to the Delta Save images (DSIM) data set. An ADAIOR error text is given. The affected DSIM RABN is shown in decimal <i>dec-rabn</i> and hexadecimal <i>hex-rabn</i> formats.</p> <p>In ADASAV, the function is abnormally terminated. In ADARES, no more online save information will be extracted from the protection log during this ADARES execution. Building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.</p>
Action	Determine the cause of the I/O error and eliminate it. Rebuild the DSIM data set.
DSF085	Error occurred during execution of close DSIM {ior-error-text}
Explanation	<p>An error occurred when the Delta Save Facility was trying to close the Delta Save images (DSIM) data set. An ADAIOR error text is given.</p> <p>In ADASAV, the function is abnormally terminated. In ADARES, the PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.</p>
Action	Determine the cause of the error and eliminate it.
DSF086	Error occurred while executing open input save {dd-name} {ior-error-text}
Explanation	<p>An error occurred when the Delta Save Facility was trying to open an input save data set. The DD/link name of the data set and an ADAIOR error text are given. A job control statement is probably incorrect.</p> <p>The function is abnormally terminated.</p>
Action	Determine the cause of the error and eliminate it. Rerun the job.
DSF087	Error occurred while executing read input save {dd-name} {ior-error-text}
Explanation	<p>An error occurred when the Delta Save Facility was trying to read from an input save data set. The DD-name/link name of the data set and an ADAIOR error text are given.</p> <p>The function is abnormally terminated.</p>
Action	Determine the cause of the error and eliminate it. If the save data set turns out to be readable, rerun the job.

DSF088	Error occurred while executing close input save {dd-name} {ior-error-text}
Explanation	An error occurred when the Delta Save Facility was trying to close an input save data set. The DD/link name of the data set and an ADAIOR error text are displayed. The function terminates abnormally.
Action	Determine the cause of the error and eliminate it.
DSF089	GETMAIN error - not enough virtual memory
Explanation	Sufficient virtual memory could not be obtained for Delta Save Facility processing. The number of bytes requested and obtained are shown in decimal and hex format. In ADASAV, the function is abnormally terminated. In ADARES, building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.
Action	Increase the partition/region of the job. If the function was ADARES PLCOPY, rebuild the DSIM data set using the ADARES COPY function. Otherwise rerun the job.
DSF090	Incorrect database version
Explanation	The Delta Save Facility requires a database at Adabas version 5.3 SP3 or above. The requested function cannot be executed. The internal version indicator found in the GCBs is shown in hexadecimal format. The function is abnormally terminated.
Action	To use the Delta Save Facility, convert the database to Adabas version 5.3 SP3 or above.
DSF091	Incorrect version of DLOG area
Explanation	The Delta Save logging (DLOG) area was installed by another, incompatible version of the Delta Save Facility. The internal version indicator and the version of the Delta Save Facility software are displayed in hexadecimal format. The function is abnormally terminated.
Action	Use a compatible version of the Delta Save Facility software, or remove the DLOG area and install it again.

DSF092	Incorrect version of DSIM dataset
Explanation	<p>The Delta Save images (DSIM) data set was created by another, incompatible version of the Delta Save Facility. The internal version indicator and the version of the Delta Save Facility software are displayed in hexadecimal format.</p> <p>In ADASAV, the function is abnormally terminated. In ADARES, building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.</p>
Action	Use a compatible version of the Delta Save Facility software, or rebuild the DSIM data set using the ADARES COPY function.
DSF093	Error during input save tape processing
Explanation	<p>An error was detected while processing a record from an input save data set. Probably the save data set is invalid. The DD/link name of the save data set, an internal reason code, and the serial block number in decimal and hexadecimal are shown. The requested function cannot be completed.</p> <p>The function is abnormally terminated.</p>
Action	Check for invalid concatenation of save data sets and correct it, if found. Consult your Software AG technical support representative, if necessary.
DSF094	Error during input save tape processing
Explanation	<p>Either some important control information is not consistent for all records of an input save data set, or the serial block numbers within an input save data set are not in ascending order, increasing by one. Probably the save data set is invalid. The DD/link name of the save data set is shown.</p> <p>The function cannot be completed, and is abnormally terminated.</p>
Action	Check for invalid concatenation of save data sets and correct it, if found. Consult your Software AG technical support representative, if necessary.
DSF095	Internal error during protection log processing
Explanation	<p>An error was detected in a protection log block processed by the Delta Save Facility. The protection log number, the block number and offset within the block, and an internal reason code are displayed in decimal format, the block number and offset also in hex format. A DSIM data set cannot be built.</p> <p>Building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.</p>
Action	Check for and correct any mistake in the specification of protection log data sets. Consult your Software AG technical support representative, if necessary.

DSF096	Damaged DLOG area block detected
Explanation	<p>An inconsistent block was encountered in the Delta Save logging (DLOG) area. The bad RABN is shown in decimal and hex format, plus an internal reason code. The Delta Save operation cannot be completed.</p> <p>The Delta Save operation is abnormally terminated.</p>
Action	<p>Consult your Software AG technical support representative to determine the cause of the error. Disable Delta Save logging, remove the DLOG area, and install it again. Perform a full save operation.</p>
DSF097	Damaged DSIM block detected
Explanation	<p>An inconsistent block was encountered in the Delta Save images (DSIM) data set. The bad RABN is shown in decimal and hex format, plus an internal reason code. The requested Delta Save Facility function cannot be completed.</p> <p>In ADASAV, the function is abnormally terminated. In ADARES, building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.</p>
Action	<p>Consult your Software AG technical support representative to determine the cause of the error. Rebuild the DSIM data set using the ADARES COPY function.</p>
DSF098	Damaged DLOG extension block detected
Explanation	<p>An inconsistent block was encountered in a file-specific extension of the Delta Save logging (DLOG) area. The file number, the RABN of the inconsistent block, and an internal reason code are shown. A Delta Save operation is not possible.</p> <p>The Delta Save operation is abnormally terminated.</p>
Action	<p>Consult your Software AG technical support representative to determine the cause of the error. Save and restore or reorder the file in question. Then rerun the Delta Save operation.</p>
DSF099	DSF internal error at {module + offset} trace: {trace-info} R0-R3 {xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx } R4-R7 {xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx } R8-R11 {xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx } R12-R15 {xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx }
Explanation	<p>An internal error occurred in the indicated module at the specified offset. Some internal trace information as well as the register settings at the time of the error are shown. The requested Delta Save Facility function cannot be completed.</p> <p>In ADASAV, the function is abnormally terminated. In ADARES, building the DSIM data set is discontinued. The PLCOPY or COPY function will continue processing. When terminating normally, the function will set condition code 4. If no output data</p>

set was specified for the COPY function, a subsequent ADARES error abnormally terminates the function.

Action

Consult your Software AG technical support representative to determine the cause of the error.

58

DSP* - Cluster Data Space (ADADSP) Messages

ADADSP messages apply only to Adabas Parallel Services.

All of the following messages are printed first to the system log and then later to the `Dssdddd` data set (where `ss` is the last two digits of the SVC number and `dddd` is the DBID) that was automatically created for cluster data space message output.

Each message begins with a timestamp in the format `hh:mm:ss`, followed by the message number and text.

DSP001	Initializing DBID={dbid} [SVC={svc}] [IDTNAME={idtname}]
Explanation	ADACOM is initializing an ADADSP subtask for the processing of a Adabas Parallel Services cluster database that might subsequently be started.
Action	No action is required for this informational message.
DSP002	Data space acquisition authority acquired Data space acquisition handled by job {jobname}
Explanation	Data space acquisition authority is granted to the first ADACOM to start and the name of that ADACOM job is displayed. Subsequent ADACOMs set to manage the same DBID will not be granted the authority to allocate data spaces, since they have already been allocated.
DSP003	Dataspace being allocated is {PLXCB cache lock message} Name is {data-space-name} {Size in decimal bytes: {number-of-bytes} not allocated - length is zero not allocated - size is less than 4096 bytes} {function completed normally data spaces already allocated} Dataspace may already exist, attempting delete
Explanation	ADACOM is in the process of allocating a data space of the specified type (PLXCB, cache, lock, or message) with the specified name and the specified size. A PLXCB data

space is allocated during ADACOM initialization when it is requested by initialization parameters. Its size is based on the number of users specified to ADACOM. Cache, lock and message data spaces are allocated when the first Parallel Service database starts and only if a valid size is provided: see the ADARUN CLUCACHESIZE and CLULOCKSIZE parameters.

The operating system does not allow data spaces with sizes less than 4096 decimal bytes (internal error). If the allocation parameters are valid, the data spaces are allocated when the first cluster nucleus starts. Once data spaces are allocated for a cluster, they are not reallocated when subsequent cluster nuclei start.

If the first member nucleus of an ADABAS Parallel Services cluster attempts to allocate a dataspace, a dataspace may already exist, possibly as the result of a previous abend for which recovery was unsuccessful. The deletion attempt will generate DSP005 messages, after which the allocation attempt will be retried.

Similarly, if a PLXCB dataspace entry is found in the IDTH prefix when attempting to allocate a new PLXCB, the IDTH prefix entry is first cleared.

Action If you receive an error due to invalid sizes, review your ADARUN parameters, correct the error, and restart ADACOM. All other messages are for information only and require no action.

DSP004 **Unable to delete/exit - NUCS up**
Checking every 5 seconds
Next message in 5 minutes

Explanation This message occurs when an ADADSP subtask of ADACOM has been asked to exit or to delete the shared dataspace of an Adabas Parallel Services cluster, but one or more cluster nuclei are still active. An ADADSP subtask exits when an ADAEND command is issued to ADACOM for the associated the DBID/SVC (or DBID/IDTNAME) combination.

Action ADACOM should come down automatically when the last cluster nucleus terminates. If it does not, issue a CANCEL command to terminate it.

If ADACOM is canceled while Adabas Parallel Services nuclei are active on the associated database, these nuclei will most likely incur program checks and terminate abnormally. Thus, ADACOM should be canceled only when none of its ADADSP subtasks holds dataspace for active Adabas Parallel Services nuclei, so as not to crash the Adabas Parallel Services cluster(s).

DSP005 **Dataspace being deleted is {data-space-name}**
Function completed normally | Error: abend code {abend-code}, reason code {reason-code} | Error: return code {ret-code}, reason code {reason-code}}

Explanation The specified cluster data space is being deleted. Either the deletion is completed successfully or an IBM error code and reason code are returned.

Action	If the data space is successfully deleted, no action is required. If an IBM error and reason code are returned, refer to your IBM manuals to identify and correct the specified error.
DSP006	Unable to secure process token
Explanation	The ADADSP subtask of ADACOM failed to obtain its own process token, which Adabas Parallel Services nuclei need to communicate with ADADSP. The ADADSP subtask terminates abnormally. Adabas Parallel Services nuclei for the associated database cannot start.
Action	Contact your Software AG technical support representative for assistance.
DSP007	Length of process token too long
Explanation	The process token of the ADADSP subtask of ADACOM is invalid. The ADADSP subtask terminates abnormally. Adabas Parallel Services nuclei for the associated database cannot start.
Action	Contact your Software AG technical support representative for assistance.
DSP008	Unable to open output data set
Explanation	The ADADSP subtask of ADACOM failed to open its message output data set. The data set has the DD-name or link name <i>Dssdddd</i> in z/OS and z/VSE environments, or <i>Diidddd</i> in BS2000 environments, where <i>ss</i> represents the last two digits of the SVC number, <i>ii</i> represents the fourth and last nonblank character of the IDT name, and <i>dddd</i> is the database ID.
	ADADSP will continue to run, but write its messages only to the console.
Action	Contact your Software AG technical support representative for assistance.
DSP010	{x}64 object being allocated is {cache lock message} {x}64 object may already exist at {address} Attempting delete Allocation token is {token} Requested size in {MB GB} (rounded) is {size} Function completed normally Storage allocated but not backed by large pages Address is {address} Error: return code 12, reason code {zOS-return-code} {zOS-reason-code} Error: abend code {system-code}, reason code {reason-code}
Explanation	This series of messages describe an attempt to allocate 64-bit addressable memory object of the specified type. The <i>x</i> before the "64" in the message identifies the type of 64-bit addressable memory: "S" (shared addressable memory), "G" (2G large page addressable memory), or "L" (1M large page addressable memory).

If the allocation is successful, the address of the object is shown. If ADAIOR reports return code 12, the z/OS return and reason codes are shown. If the request resulted in an abend, the system and reason codes are shown.

If the first member nucleus of an Adabas Parallel Services cluster attempts to allocate a S64 object, one may already exist, possibly as the result of a previous abend for which recovery was unsuccessful. The deletion attempt will generate DSP011 messages, after which the allocation attempt will be retried.

If "Storage allocated but not backed by large pages" is printed, insufficient large pages of the type requested (1M large pages or 2G large pages) were available. Instead, storage was allocated and backed by pageable 4 kilobyte pages. In this case, the same action applies as given for the [ADAN8G message](#).

If the "Error" line is printed, the storage allocation request failed. The message reports the system return code and reason code of the IARV64 macro used for the allocation request.

Action If the request fails, examine the z/OS IARV64 abend, return, and reason code descriptions in IBM documentation. If the cause is not clear, notify your Software AG technical support representative.

DSP011 **{x}64 object being deleted is {cache | lock | message}**
{x}64 object may already exist at {address}
Allocation token is {token}
Actual size in {MB | GB} is {size}
Address is {address}
Function completed normally
Error: return code 12, reason code {zOS-return-code} {z/OS-reason-code}
Error: abend code {system-code}, reason code {reason-code}

Explanation This series of messages describe an attempt to delete a shared 64-bit addressable memory object of the specified type. The *x* before the "64" in the message identifies the type of 64-bit addressable memory: "S" (shared addressable memory), "G" (2G large page addressable memory), or "L" (1M large page addressable memory).

If ADAIOR reports return code 12, the z/OS return and reason codes are shown. If the request resulted in an abend, the system and reason codes are shown.

Specifically, what is being deleted is the z/OS system affinity. A z/OS S64 memory object will not actually be deleted until all local affinities are also deleted. A local affinity is created when a Parallel Services nucleus establishes a connection with the S64 object in its own address space. Local affinities are deleted when the nucleus ends.

If the "Error" line is printed, the deletion request failed. The message reports the system return code and reason code of the IARV64 macro used for the deletion request.

Action If the request fails, examine the z/OS IARV64 abend, return, and reason code descriptions in IBM documentation. If the cause is not clear, notify your Software AG technical support representative.

DSP012	Unable to obtain ALET for PLXCB dataspace Return code {return code} reason code {reason code}
Explanation	An attempt to obtain an ALET for the PLXCB dataspace was unsuccessful. The return and reason codes are from the operating system service. Under z/OS the service is ALESERV.
Action	Use operating system documentation to understand the return and reason codes. Contact your Software AG technical support representative if the reason for the failure is unclear.
DSP013	Unable to get PLXCB local map storage
Explanation	An attempt to acquire ADACOM local storage into which the PLXCB would be mapped was unsuccessful.
Action	Contact your Software AG technical support representative if the reason for the failure is unclear.
DSP014	Unable to map PLXCB dataspace to local storage Return code {return code} reason code {reason code}
Explanation	The request to map the PLXCB into ADACOM local storage was unsuccessful. The return and reason codes are from the operating system service. Under z/OS the service is IARVSERV.
Action	Use operating system documentation to understand the return and reason codes. Contact your Software AG technical support representative if the reason for the failure is unclear.
DSP015	PLXCB dataspace mapped to local storage {address}
Explanation	The PLXCB was mapped to the specified address in ADACOM local storage.
DSP016	Unable to obtain ALET for nucleus address space Return code {return code} reason code {reason code}
Explanation	A nucleus requested ADACOM map the PLXCB dataspace into nucleus local storage. An attempt to obtain an ALET for the nucleus address space was unsuccessful. The return and reason codes are from the operating system service. Under z/OS the service is ALESERV.
Action	Use operating system documentation to understand the return and reason codes. Contact your Software AG technical support representative if the reason for the failure is unclear.

- DSP017** **Unable to map PLXCB dataspace to nucleus storage**
- Explanation** A nucleus requested ADACOM map the PLXCB dataspace into nucleus local storage. The request to map the PLXCB into local storage was unsuccessful. The return and reason codes are from the operating system service. Under z/OS the service is IARVSERV.
- Action** Use operating system documentation to understand the return and reason codes. Contact your Software AG technical support representative if the reason for the failure is unclear.
-
- DSP018** **Resource manager return codes {summary}/{address space end}/{task end}**
- Explanation** An attempt to establish Resource Manager recovery routines was unsuccessful. These routines clear the IDTH prefix entry for a PLXCB dataspace in the event of ALET-related program checks in ADACOM that cannot be handled by normal error processing. The return and reason codes are from the operating system service. Under z/OS the service is RESMGR.
- Action** Use operating system documentation to understand the return and reason codes. Contact your Software AG technical support representative if the reason for the failure is unclear.
-
- DSP099** **SVC={svc}, DBID={dbid} ADADSP {exiting | ended}**
- Explanation** The ADACOM support for the specified Adabas Cluster Services or Adabas Parallel Services dataspace is terminating.

59

LNKRVX* Adabas Review Link Routine Messages

LNKRVX090	Enhanced Review processing terminated
Explanation	This message is issued after an error is detected when the link routine attempts to initialize the environment for Review exits. The reason for the failure is provided by one or more previously issued message or messages.
Action	Review other previously issued messages to determine the cause of the error.
LNKRVX091	GETMAIN failed for Review exit work area
Explanation	The storage for the REVEXIT1 (REVEXITB) work area was not available. No Adabas Review processing is possible for this task or job step.
Action	Contact your Software AG technical support representative for assistance.
LNKRVX092	GETMAIN failed for REVEXIT2 work area
Explanation	The storage required to support REVEXIT2 client monitoring is not available. Client monitoring will not be possible but standard REVEXIT1 (REVEXITB) processing may be possible.
Action	Contact your Software AG technical support representative for assistance.
LNKRVX093	Primary Revexit work area header invalid
Explanation	The header for the primary Adabas Review work area appears to be invalid. Adabas Review processing cannot continue.
Action	Contact your Software AG technical support representative for assistance.

LNKR VX094	REVEXIT2 work area invalid
Explanation	The work area for REVEXIT2 (client monitoring) appears to be invalid or corrupted. Adabas Review client monitoring cannot continue.
Action	Contact your Software AG technical support representative for assistance.
LNKR VX095	Handshake with Review Hub: {hub-id} failed RSP: {rc} Sub: {sc}
Explanation	The handshake to establish communication with the Adabas Review hub listed in the message (<i>hub-id</i>) failed with the Adabas response code (<i>rc</i>) and the Adabas subcode (<i>sc</i>) given in the message. Adabas Review client monitoring cannot continue for this task or job step.
Action	Evaluate the returned Adabas response code and subcode to determine the action to take to correct the issue. For example, if the Adabas response code is 148, ensure that the specified Adabas Review hub is up and running.
LNKR VX096	Review monitoring is {ON OFF}
Explanation	This message indicates the new or current state of Adabas Review client monitoring. It is issued in response to a request from SYSREVD B to activate or deactivate client monitoring for the Adabas link routine.
Action	No action is required for this informational message.
LNKR VX097	PC number zero after V4 call, Transport not active
Explanation	The handshake to establish communications between the link routine, REVEXIT2 and the Adabas Review hub has failed because the Adabas Review Trans- port software is not running.
Action	Restart the Adabas Review Trans- port software.

60

PLI* - ADACOM Initialization Messages

ADACOM messages apply only to Adabas nucleus cluster environments.

All `PLInnn` messages are printed on the console. Messages in the range 0-49 are issued by the ADACOT module attached to a particular SVC/DBID set and are sent to the SYSOUT data set that is dynamically allocated for that particular module. Messages in the range 50 and above are issued by ADACOM and are written to the COMPRINT data set. Each message begins with a timestamp in the format "hh:mm:ss".

PLI002 **Initializing DBID={dbid} SVC={svc message(s)}**

Explanation This message identifies the ADACOM that is initializing by its database ID and SVC settings. It is followed by one or more relevant initialization message(s) (check the following possible PLI002 messages):

Message Text	Explanation
Acquiring new PLXCB	Having determined that no Adabas cluster control block (PLXCB) currently exists, ADACOM is attempting to acquire a new one.
Cannot change number of users now. There are NUCS/ADACOMS active	Once the cluster is active; that is, once a nucleus or ADACOM starts, the PLXCB NU parameter is set and cannot be changed without bringing down the entire cluster, changing the parameter value, and restarting. If you need to change the PLXCB NU parameter value, terminate all cluster nuclei, ADACOMS, and users and restart.
Cannot free PLXCB at this time. There are NUCS/ADACOMS active	Once the cluster is active; that is, once a nucleus or ADACOM starts, the PLXCB NU parameter is set and cannot be changed without bringing down the entire cluster, changing the parameter value, and restarting.

Message Text	Explanation
DBID is zero	This is an internal error. The ADACOM terminates abnormally (abends) the subtask for this DBID/SVC combination. Contact your Software AG technical support representative for assistance.
FORCE=YES detected -- initialization continues	The incompatible PLXCB version described in earlier lines will be released and initialization will continue.
Freeing old PLXCB	The NU parameter value is being changed or the FORCE option was specified for this DBID/SVC. The old environment is being freed.
GETMAIN failed for PLXCB	An attempt to acquire GETMAIN space for a new Adabas cluster control block (PLXCB) failed. The ADACOM subtask terminates abnormally (abends). Ensure that sufficient space is available to allocate the PLXCB and resubmit the job.
IDTHPRFX not found	This is an internal error. Contact your Software AG technical support representative for assistance. ADACOM terminates abnormally (abends) the subtask for this DBID/SVC combination.
Max users capped at upper limit	The maximum size of the PLXUser pool is 14,913,014 elements.
Max users for image <i>number-of-users</i>	Displays the maximum number of users (NU) allowed for the operating system image.
Obtain of IDTHPRFX failed	The IDTH prefix created when the IDT was created accommodates 15 cluster DBIDs. It was necessary to acquire storage to extend the IDTH prefix for additional DBIDs. Insufficient storage was available (in z/OS this is ECSA). Increase the region size to resolve this problem. For additional assistance, contact your Software AG technical support representative.
PLXCB is located at <i>address</i>	The location of the PLXCB, either new or existing, is provided. If the PLXCB was allocated in a dataspace the address is the ADACOM local storage into which it is mapped.
PLXCB version is <i>vrs</i> <i>program</i> program level is <i>vrs</i>	An existing PLXCB is of a version incompatible with the specified program.
Incompatible ADASVC Version	ADASVC must be at the same or higher version and release as ADACOT.
PLXCB dataspace is <i>name</i> ALET <i>ALET</i>	The PLXCB dataspace was created.

Message Text	Explanation
Processed NU=O request	The system has processed the NU=0 parameter. The old environment has been freed and no new one was created.
PSW key <i>pswkey</i> not compatible with PLXCB key <i>plxcbkey</i>	A previously allocated PLXCB cannot be used because of a difference between the PSW and storage keys. Run ADACOM in the PLXCB key or delete the existing PLXCB and reallocate it in the desired key.
This SVC/DBID combination will terminate	Previously described errors prevent initialization. ADACOM terminates abnormally (abends) the subtask for this DBID/SVC combination.

PLI003 **SVC={svc} DBID={dbid} OPERATOR COMMAND: {command}**
Explanation Confirms the operator command just issued and the SVC/DBID combination for which it is issued.

PLI004 **{imagename} NUCID={nucid} UP={x} LO={y} RO={z }#USERS={n} #CMNDS={n} LURA={n} RULA={n}**

PLI004 **{jobname}{ nucid x y z n..... n.....}**
Explanation This message is issued in response to an ADACOM DN or DIM operator command. It displays the status of the cluster nuclei located on the named image, which may be local or remote images. There is one header line for each image which may be followed by detail lines for each active nucleus. The following table describes the components of this message:

Message Component	Description
<i>imagename</i>	The name of the local image.
NUCID= <i>nucid</i>	The unique cluster nucleus identifier.
UP= <i>x</i>	Specifies whether (Y or N) the specified nucleus is available for normal processing.
LO= <i>y</i>	Specifies whether the specified nucleus is on the local image and open (Y); or on the local image and closed (N).
RO= <i>z</i>	Indicates that the specified nucleus is not on a remote image (N).
#USERS= <i>n</i>	The number of users that have been assigned to and are currently active for the specified nucleus.
#CMNDS= <i>n</i>	The number of commands currently incomplete.
LURA= <i>n</i>	The number of users remotely assigned to the local image.
RULA= <i>n</i>	The number of users locally assigned to the remote image.
<i>jobname</i>	The name of the ADACOM job or started task.

There may be conditions that prevent displaying active nuclei. These lines may appear instead of active nucleus detail lines.

Message Text	Explanation
** Image has no active NUCs **	There are no active cluster nuclei to display on the local image.
* Local network down - no remote information *	No information is available about remote images because the local Entire Net-Work is not active.
No NUCs up or remote network down	No information is available from a remote image. Either there are no active nuclei on the remote image or the remote Entire Net-Work is not active.
* Remote images not detected *	The specified image is not local and that ADACOM does not detect the presence of a remote image with the specified name.

- PLI005** **** Image has no active NUCs ****
Explanation This message follows PLI004 for either a DIM or DN command when there are no active cluster nuclei to display on the local image.
- PLI009** **Invalid command: ***
Explanation The command entered is not a valid ADACOM command. This message follows PLI060, which displays the invalid command entered.
Action Check the command used; reenter a valid ADACOM command.
- PLI010** **Command executed**
Explanation This message follows PLI060 for the SN command and indicates that the SN command with the parameters specified in PLI060 has been successfully executed.
- PLI012** **{module} load failed - exiting**
Explanation The module listed in the message (*module*) could not be loaded. The affected task abends.
Action Ensure the named module is available in the load library concatenation. If you are unable to resolve the error, contact your Software AG technical support representative.

PLI013	Unable to set timer - exiting
Explanation	An internal error occurred while executing STIMERM. The affected ADACOT module abends.
Action	Contact your Software AG technical support representative.
PLI014	PSW key {pswkey} not compatible with PLXCB key {plxcbkey}
Explanation	A previously allocated PLXCB cannot be used because of a difference between the PSW and storage keys.
Action	Run the ADACOM in the PLXCB key, or delete the existing PLXCB and reallocate it in the desired key.
PLI015	Work area GETMAIN failed
Explanation	The attempt to allocate space for an ADACOT work area failed. The affected SVC/DBID combination abends.
Action	Increase the region size.
PLI016	IDTH prefix is not valid
Explanation	An internal error occurred: IDTHPRFX is invalid. The affected ADACOT module abends.
Action	Contact your Software AG technical support representative.
PLI017	Number of IDTE entries is zero
Explanation	An internal error occurred: the IDTH is invalid. The affected ADACOT module abends.
Action	Contact your Software AG technical support representative.
PLI018	ADACOT initialization failed
Explanation	The PLXINIT module failed during initialization. The affected ADACOT module abends.
Action	Contact your Software AG technical support representative.
PLI019	Get IDTH failed
Explanation	ADACOT was unable to obtain the address of the IDTH. The affected ADACOT module abends.
Action	Contact your Software AG technical support representative.

PLI020	SVC={svc} DBID={dbid} ADACOT {exiting ended}
Explanation	This message occurs whenever an SVC/DBID combination terminates for any reason.
PLI021	Network detected down
Explanation	ADACOM detected that the local Entire Net-Work is not active.
PLI022	Network detected up and available
Explanation	ADACOM detected that the local Entire Net-Work is active and processing commands.
PLI023	No PARMs allowed for "DN"
Explanation	A parameter was supplied when issuing the ADACOM command DN. No parameters are allowed for the DN command. This message follows PLI060 which indicates the command and parameters issued.
Action	Remove the parameter(s) and issue DN again.
PLI024	Invalid system name
Explanation	The DIM command allows you to optionally supply an image name as a parameter. The DIM command was issued with a parameter value, but the value supplied is not a valid image name. This message follows PLI060 which indicates the command and parameters issued.
Action	Supply a valid image name and issue DIM again.
PLI027	CMDMGR=NO specified
Explanation	CMDMGR=NO was specified in the ADACOM; ADACOM quiesces after setting the environment.
PLI028	Net-Work not available RSP {rc}/{sc}
Explanation	ADACOM detected an active Entire Net-Work address space and issued a periodic internal command to verify that Entire Net-Work is accepting and processing commands. The internal command received an unexpected response code and subcode, which are given in the message (<i>rc/sc</i>). This usually indicates a problem with Entire Net-Work.
Action	Review the response code and subcode to determine the cause of the problem. If the problem persists, contact your Software AG technical support representative for assistance.

PLI030	Invalid NUC specification
Explanation	This message follows PLI060 for the SN command and indicates that the specified nucleus ID is not valid.
Action	Specify a valid nucleus ID and issue the command again.
PLI031	Command must specify "OP/CL"
Explanation	This message follows PLI060 for the SN command and indicates that the required parameters OP/CL were not specified.
Action	Specify the required parameters and issue the command again.
PLI032	Too many parameters
Explanation	This message follows PLI060 for the SN command and indicates that too many parameters have been specified when opening or closing one or more remote nuclei. Remote nuclei are always opened to local users only.
Action	Remove the erroneous parameter(s) and issue the command again.
PLI034	Local NUC(s) not found
Explanation	This message follows PLI060 for the SN command and indicates that the local nucleus specified was not found on the local image. If LCLALL was used in the command, no cluster nuclei were found on the local image.
PLI035	"ALL" not valid for "OP/CL"
Explanation	This message follows PLI060 for the SN command. "ALL" is not a valid parameter. You must indicate whether you want to open or close all local nuclei (LCLALL) or all remote nuclei (RMTALL). You cannot open or close all cluster nuclei on all images at once. You can, of course, open a specified nucleus or all nuclei on a specified remote image, if you choose.
Action	Specify the required parameters and issue the command again.
PLI036	Too few parameters - need "LCL/GBL"
Explanation	This message follows PLI060 for the SN command. When opening or closing nuclei on local images, you must indicate whether you are opening them to local users only (LCL) or to all cluster users (GBL).
Action	Specify the required information and issue the command again.

PLI038 **Only "LCL" or "GBL" after "OP/CL"**
Explanation This message follows PLI060 for the SN command. When opening or closing nuclei on the local image, your only choices are to open the nuclei to local users only (LCL) or to all cluster users (GBL). No other options are allowed.
Action Specify LCL or GBL and issue the command again.

PLI039 **Remote NUC(s) not found**
Explanation This message follows PLI060 for the SN command and indicates that the remote nucleus specified was not found on any remote image. If a remote image was specified, no cluster nuclei were found on that image. If RMTALL was used in the command, no cluster nuclei were found on any remote image.

PLI040 **Cannot exit now - dataspace are allocated**
Explanation There are active Adabas Parallel Services nuclei that have active dataspace, or a PLXCB dataspace is being used and one or more Adabas Parallel Services or Adabas Cluster Services nuclei are active.
Action Terminate any Adabas Parallel Services or Adabas Cluster Services nuclei and try again.

PLI041 **Valid PARMs: PLXCP, PLXNUC, PLXMAP, IDTE, FIIBS, PLXUSER, CLUDSP, IDTH, IDTHPRFX**
Explanation A DUMP operator command was entered with an operand other than one of the valid ones listed in the message.
Action Reissue the command with a correct operand.

PLI042 **{message-text}**
Explanation Various message texts are associated with this message number. Each is described in the following table:

Message Text	Explanation
Only N=X, where X is prefix, is valid	A DUMP PLXUSER command was entered with an invalid operand. <i>Action:</i> Reissue the command with a correct operand.
The prefix is missing or now "=" specified	A DUMP PLXUSER command was entered with invalid syntax or an invalid operand. <i>Action:</i> Reissue the command with a correct operand.

Message Text	Explanation
There are no active users at this time	A DUMP PLXUSER command was entered. There is nothing to list. <i>Action:</i> No action is necessary for this informational message.
There are no active IDTEs at this time	A DUMP IDTE command was entered. There is nothing to list. <i>Action:</i> No action is necessary for this informational message.
Extended storage IIBs are not in use	A DUMP FIIBS command was entered. There is nothing to list. <i>Action:</i> No action is necessary for this informational message.
Extended storage but fat IIBS not in use	A DUMP FIIBS command was entered. There is nothing to list. <i>Action:</i> No action is necessary for this informational message.
No FIIBS in use at this time	A DUMP FIIBS command was entered. There is nothing to list. <i>Action:</i> No action is necessary for this informational message.
There are no valid maps at this time	A DUMP PLXMAP command was entered. There is nothing to list. <i>Action:</i> No action is necessary for this informational message.
There are no active entries	A DUMP IDTHPRFX command was entered. There is nothing to list. <i>Action:</i> No action is necessary for this informational message.
There are no active NUCs at this time	A DUMP PLXNUC command was entered. There is nothing to list. <i>Action:</i> No action is necessary for this informational message.
<i>dbid</i> Unable to allocate PLXMAP for <i>system-target</i> on <i>system-name</i>	A PLXMAP update was received from a remote system for which there was no existing PLXMAP. A free PLXMAP slot could not be located. The update is discarded. <i>Action:</i> This may occur if systems containing cluster nuclei were removed from the sysplex and other systems

Message Text	Explanation
	containing nuclei were added. If ADACOM is running, issue the DUMP PLXMAP command to examine the assignment of each PLXMAP. Contact your Software AG technical support representative for assistance.

PLI048 **Unable to DEQ {resource}**
Explanation An internal error occurred: ADACOT was unable to release serialization for the named resource. The affected ADACOT module abends.
Action Contact your Software AG technical support representative.

PLI049 **RSP {rsp/node-subcode} from {target} {system}**
Explanation An attempt was made to update PLXCB structures on another operating system image participating in Adabas Cluster Services (ALS). The response code (*rsp*) and subcode (*subcode*) given in the message indicate an unexpected condition. The Entire Net-Work node ID may also be given in the message (*node*) if Entire Net-Work does not have connectivity to the remote system or if there are problems in the PLXCB structures on the remote system.
Action If the reason for the response code is not clear and you cannot resolve the error by analyzing it, contact your Software AG technical support representative.

PLI050 **Initializing ADACOM**
Explanation This is the first message produced when ADACOM is starting.

PLI052 **Commands will go to SVC={svc},DBID={dbid}**
Explanation A MODIFY command was issued to change the SVC/DBID combination that is to receive all following MODIFY commands.

PLI053 **Remainder of input line ignored**
Explanation Characters were found at the end of a SVC=*svc*,DBID=*dbid* when no comma follows the SVC/DBID combination. Note that the SVC=*svc* and DBID=*dbid* can be in any order.

PLI054	Duplicate SVC= or DBID=
Explanation	A MODIFY command to change the SVC/DBID combination for commands was issued with more than one SVC= or DBID=.
Action	Reissue the command with only one SVC/DBID parameter set.
PLI055	Invalid SVC or DBID number
Explanation	A MODIFY command to change the SVC/DBID combination for commands was issued with a nonnumeric, invalid, or out of range SVC or DBID number.
Action	Reissue the command with a valid SVC/DBID parameter set.
PLI056	Invalid character in command
Explanation	A MODIFY command to change the SVC/DBID combination for commands was issued and no comma between SVC=svc and DBID=dbid.
Action	Correct the format and reissue the command.
PLI057	DBID= or SVC= missing
Explanation	A MODIFY command to change the SVC/DBID combination for commands was issued and either SVC= or DBID= missing.
Action	Add the required parameter and reissue the command.
PLI058	SVC/DBID pair not active in this ADACOM
Explanation	A MODIFY command to change the SVC/DBID combination for commands was issued and the SVC/DBID pair was not specified in the input stream.
Action	Specify the required parameters and reissue the command.
PLI059	SVC/DBID pair processing has ended
Explanation	A MODIFY command to change the SVC/DBID combination for commands was issued and the SVC/DBID pair processing has ended either from NU=0 or an abend.
Action	If you are unable to determine and correct the problem, contact your Software AG technical support representative.
PLI060	SVC={svc} DBID={dbid} operator command : {command}
Explanation	This message indicates that the specified command has been issued from the ADACOM identified by the SVC and DBID listed.

PLI062 Command queued

Explanation A command is queued for execution. The results of the command will appear in the output data set for the SVC/DBID combination to which the command was issued.

PLI063 Processing: ADACOM SVC={svc},DBID={dbid},NU={users text}

Explanation Issued during initialization for each input line from DDKARTE or for an ADACOM operator command establishing or modifying support for a DBID/SVC pair. The text of the line appears to the right of the colon.

text	Explanation
Initialization complete	Issued as text for PLI063 if NU does not equal 0 and the startup for the SVC/DBID pair was successful.
<i>program</i> Initialization failed or incomplete	Issued as text for PLI063 when the initialization process encounters an error for a SVC/DBID pair. The error may indicate a problem allocating a corresponding SYSOUT data set. Initialization for the other pairs continues.
<i>program</i> detached in initialization	An error in initialization was detected. The ADACOM subtask for <i>program</i> was detached.
Processing ended normally	Issued as text for PLI063 if NU=0 was specified and the PLXCB was processed normally.

Action If you are unable to determine and correct the problem with the SVC/DBID parameter set, contact your Software AG technical support representative.

PLI064 ADACOM exiting

Explanation This is the last message produced when the ADACOM job is terminating as a result of an ADAEND command or an error situation.

PLI065 Initialization complete for all DBID/SVC pairs

Explanation ADACOM has initialized all specified DBID/SVC pairs. See the preceding PLI063 messages for the status of each pair's initialization.

Action No action is necessary for this informational message.

PLI066 Minimum ADASVC level is V84 for PLXCB dataspace

Explanation A request to create a PLXCB dataspace failed because ADASVC is not at the proper minimum level.

Action Upgrade ADASVC or request the PLXCB be allocated in common memory.

PLI068	Unrecognized parameter
Explanation	During initialization when processing input from DDKARTE, an unrecognized parameter was encountered on the card. ADACOM abends.
Action	Check the DDKARTE parameters. If you are unable to determine and correct the problem, contact your Software AG technical support representative.
PLI069	Duplicate parameter
Explanation	Issued on initialization when processing input from DDKARTE and a duplicate parameter entry is seen. ADACOM abends.
Action	Correct the parameter entries and rerun the job.
PLI070	Invalid numeric
Explanation	Issued on initialization when an SVC or DBID number is recognized as invalid. ADACOM abends.
Action	Correct the parameter entries and rerun the job.
PLI071	SVC or DBID not specified
Explanation	Issued on initialization when an SVC or DBID number is recognized as invalid. ADACOM abends.
Action	Correct the parameter entries and rerun the job.
PLI072	IDTH not found
Explanation	Issued during initialization when the required IDTH control block cannot be found. ADACOM abends.
Action	If you are unable to determine and correct the problem, contact your Software AG technical support representative.
PLI073	Number of IDTEs is zero
Explanation	Issued during initialization when the number of IDTEs specified in the IDTH is zero. ADACOM abends.
Action	If you are unable to determine and correct the problem, contact your Software AG technical support representative.

PLI074	Duplicate SVC/DBID combo
Explanation	Issued during initialization if two input cards from DDKARTE specify the same SVC/DBID combination. ADACOM abends.
Action	Correct the parameter entries and rerun the job.
PLI076	Input must begin with "ADACOM"
Explanation	Issued during initialization when an input card from DDKARTE does not begin with "ADACOM" followed by at least one space. ADACOM abends.
Action	Correct the format of the parameter entries and rerun the job.
PLI077	ADACOM IS SHUTTING DOWN [SVC={svc},DBID={dbid} ADACOM PROCESSING COMPLETE]
Explanation	Issued as the result of an ADAEND command or internal error causing an orderly shutdown. The part of the message enclosed in brackets is issued when an SVC/DBID combination has ended processing.
Action	If you are unable to determine and correct the problem, contact your Software AG technical support representative.
PLI078	Previous task has not ended
Explanation	Duplicate SVC/DBID combination in startup JCL. ADACOM abends.
Action	Correct the JCL and rerun.
PLI079	Error obtaining {CLUCONB CLUDSPB }
Explanation	This message indicates a GETMAIN failure at startup (ADACOM abends) or while dynamically adding an SVC/DBID combination (the system continues running).
Action	At startup, increase the region size and rerun. When dynamically adding an SVC/DBID combination, either terminate ADACOM, increase the region size, and rerun; or start a second ADACOM.
PLI080	UID mismatch freeing PLXUSER/UTE at {address} attempting to delete UID {uid1} UTE {uid2}
Explanation	ADACOM did not find the expected user ID string when attempting to release a PLXUSER (UTE).
Action	If the UTE value is all zeros, the UTE was already free. This can come about if an error recovery routine such as a z/OS ESTAE attempts to clean up by issuing CL commands. Natural has error recovery that may do this, particularly if a Natural program is canceled. If this is not the case, or the UTE is non-zero, this is an internal logic error. Contact your Software AG technical support representative.

PLI090 **Not APF authorized - exiting**
Explanation ADACOM must run with z/OS APF authorization.
Action Ensure that all load libraries are APF-authorized and rerun.

PLI093 **PLXUSER X2/{code} RSP {rsp}/{node}-{subcode} {target}**
Explanation An Adabas ADACOM job servicing Adabas Cluster Services or Adabas Parallel Services nuclei issued an internal X2 command to release a PLXUSER representing a user either originating from or routed to another system. Such users have PLXUSERS on both systems. The command failed with the displayed response code and subcode.

The *code* listed in the message identifies the reason for the X2 command:

Code	X2 Command Reason
8014	Delete PLXUSER on remote system.
8020	Query PLXUSER status for a user originating from a remote system.
8024	Query PLXUSER status for a local user assigned to a remote system.

Action If the PLXUSER cannot be released at this time, attempts will be made at intervals to release it. Contact your Software AG technical support representative for assistance if the reason for the response code cannot be identified.

PLI910 **Unable to determine Net-Work DBID target holder**
Explanation No image in the network holds the DBID as a network target and this nucleus failed in its attempt to establish it. This is an error condition. Commands from users in an image with no active nucleus and no active ADACOM I get response code 148 (ADARSP148).

Action Either start up a different node in the network or shut down and restart an existing node to see if the problem resolves itself. If the problem persists, the user should contact Software AG Customer Support.

PLI920 **NET-WORK DBID target held by {image-system-name}**
Explanation The remote image, identified in the message by its system name, holds the DBID as a network target.

Action No action is required for this informational message.

PLI930	NET-WORK DBID target owned on this image
Explanation	The image in which this nucleus is active holds the DBID as a network target.
Action	No action is required for this informational message.

61 PLX* - ADACLU Messages

ADACLU messages apply only to Adabas nucleus cluster environments.

All of the following messages are both printed on the console and written to the DD/PRINT data set.

Each message begins with a timestamp in the format *hh:mm:ss* and a job name.

The *dbid* and *nucid* are shown as five numeric characters with leading zeros.

PLX042 {dbid} X0 failed NW RSP {rsp/node-subcode}

Explanation An internal command to Entire Net-Work was issued to retrieve the Entire Net-Work node name. It failed with the response code (*rsp*) and subcode (*subcode*) listed in the message. If the response code was set by Entire Net-Work, the message may contain the N-W node number (*node*).

Action Verify that Entire Net-Work is active. If so, issue the Entire Net-Work command `D T` to examine the target list and confirm Entire Net-Work is active and responsive. Contact your Software AG technical support representative if you are unable to resolve the error.

PLX043 {dbid} Net-Work detected {up|down}

Explanation This message occurs during initialization or whenever a nucleus detects a change of status for an Entire Net-Work. Normally only one nucleus on a system will issue this and process the change of state event. If the new state is up, it will be followed by messages PLX044, PLX048 and PLX088. PLX087 will be issued on other member nuclei.

Action No action is required for this informational message.

PLX044	{dbid} System image target {target} established
Explanation	During initialization or whenever an Entire Net-Work becomes active, the system target is defined to it. The system target is needed to support command routing to remote systems and to update PLXCB structures on systems with no nuclei. It is issued only by the nucleus that issued PLX043 when it detected that Entire Net-Work has started.
Action	No action is required for this informational message.
PLX045	{dbid} Unable to allocate PLXMAP for {system-target} on {system-name} [{svc}]
Explanation	A PLXMAP update was received from a remote system for which there was no existing PLXMAP. A free PLXMAP slot could not be located. The update is discarded. This may occur if systems containing cluster nuclei were removed from the sysplex and other systems containing nuclei were added. On some platforms the system name is followed by the SVC number being used on the named system.
Action	If ADACOM is running, issue the <code>DUMP PLXMAP</code> command to examine the assignment of each PLXMAP. Contact your Software AG technical support representative for additional assistance.
PLX046	{dbid} Feed{acquire release} target {target} failed NW RSP {rsp/node-subcode nuclid}
Explanation	A nucleus was unsuccessful when attempting to acquire or release the Entire Net-Work target. This may be either the DBID target or the system image target. The response and subcode are set by Entire Net-Work (NW). Most common is response code 145 (ADARSP145), indicating that the DBID target is already defined on another node. In that case the node in the message is where the target is currently held. This error may occur when an Entire Net-Work becomes unavailable or when the target is not in the correct state for the action.
Action	Issue the Entire Net-Work command <code>D T</code> to examine the target. Contact your Software AG technical support representative if you are unable to resolve the conflict.
PLX047	{dbid} No suitable system found for DBID target
Explanation	Entire Net-Work must be active and there must be at least one active nucleus if the system is to hold the DBID target. A poll of all systems with active nuclei found no such suitable system.
Action	Start a nucleus or Entire Net-Work on a system to which the DBID target may be assigned.

- PLX048** **{dbid} System {system-name}/{(svc)} selected for DBID target**
- Explanation** After polling systems with active nuclei, the system named in the message (*system-name*) was selected as the most suitable to hold the DBID target. It is issued only by the nucleus that issued PLX043 when it detected that Entire Net-Work has started. On some platforms the system name is followed by the SVC number being used on the named system
- Action** No action is required for this informational message.
-
- PLX049** **{dbid}PLXMAP {cmd} RSP {rsp/node-subcode} from {target} on {system-name}/{(svc)}**
- Explanation** A PLXMAP update containing information about active nuclei and load-balancing information was attempted for the system named in the message (*system-name*). The update failed with the response and subcode given in the message. The command may be V2, implying the update was sent using Adabas messaging (XCF for Cluster Services) or X3, implying the update was sent using Entire Net-Work. If a PLXMAP exists for the named system, the load balancing counters and nucleus information may be cleared. On some platforms the system name is followed by the SVC number being used on the named system
- Action** If you are unable to identify a cause for the error, contact your Software AG technical support representative for assistance.
-
- PLX050** **{dbid} ADACLU INIT DBID={dbid} NUCID={nucid}**
- Explanation** The cluster nucleus listed in the message (*nucid*) for the cluster identified in the message (*dbid*) is initializing its PLXCB structures. It is followed by one or more relevant initialization messages:

Message Text	Explanation
Acquiring new PLXCB	Having determined that no Adabas cluster control block (PLXCB) currently exists, ADACLU is attempting to acquire a new one.
Cannot change number of users now. There are NUCS/ADACOMS active	Once the cluster is active; that is, once a nucleus or ADACOM starts, the PLXCB NU parameter is set and cannot be changed without bringing down the entire cluster, changing the parameter value, and restarting. If you need to change the PLXCB NU parameter value and resize the PLXCB, terminate all cluster nuclei, ADACOMs, and users, and restart.
Cannot free PLXCB at this time. There are NUCS/ADACOMS active	Once the cluster is active; that is, once a nucleus or ADACOM starts, the PLXCB NU parameter is set and cannot be changed without bringing down the entire cluster, changing the parameter value, and restarting.

Message Text	Explanation
	If you need to change the PLXCB NU parameter value and resize the PLXCB, terminate all cluster nuclei, ADACOMs, and users, and restart.
Freeing old PLXCB	The NU parameter value is being changed. The old environment is being freed.
GETMAIN failed for PLXCB	An attempt to acquire GETMAIN space for a new Adabas cluster control block (PLXCB) failed. The cluster nucleus terminates abnormally (abends). Ensure that sufficient space is available to allocate the PLXCB structures and resubmit the job.
IDTHPREFIX not found	This is an internal error. The nucleus terminates abnormally (abends). Contact your Software AG technical support representative for assistance.
Max users capped at upper limit	The maximum size of the PLXUser pool is 14,913,014 elements.
Max users for image <i>number-of-users</i>	Displays the maximum number of users (NU) allowed for the operating system image.
Obtain of IDTHPREFIX failed	The IDTH prefix created when the IDT was created accommodates 15 cluster DBIDs. It was necessary to acquire storage to extend the IDTH prefix for additional DBIDs. Insufficient storage was available (in z/OS this is ECSA). Increase the region size to resolve this problem. For additional assistance, contact your Software AG technical support representative.
PLXCB is located at <i>address</i>	The location of the PLXCB, either new or existing, is provided. If the PLXCB was allocated in a dataspace the address is the nucleus local storage into which it is mapped.
PLXCB dataspace is <i>name</i> ALET <i>ALET</i>	A PLXCB dataspace is being used.
PLXCB version is <i>vrs</i> Program level is <i>vrs</i>	An existing PLXCB is of a version incompatible with this nucleus. The nucleus terminates abnormally (abends).
Incompatible ADASVC Version	ADASVC must be at the same or higher version and release as ADACLU.
PSW key <i>pswkey</i> not compatible with PLXCB key <i>plxcbkey</i>	A previously allocated PLXCB cannot be used because of a difference between the PSW and storage keys. Run the cluster in the PLXCB key or delete the existing PLXCB and reallocate it in the desired key.
PLXCB dataspace ALET not found	The ALET to access the PLXCB dataspace was not found. Details may be found in ADACOM messages. The nucleus terminates abnormally (abends).

Message Text	Explanation
PLXCB dataspace ALET invalid	The ALET provided by ADACOM to access the PLXCB dataspace is invalid. The nucleus terminates abnormally (abends).
PLXCB dataspace failed validation	The PLXCB dataspace is not correctly populated. The nucleus terminates abnormally (abends).
Unable to get PLXCB local map storage	The attempt to acquire nucleus local storage into which the PLXCB would be mapped was unsuccessful. Details may be found in ADACOM messages. The nucleus terminates abnormally (abends).
Unable to map PLXCB dataspace	The call to ADACOM to map the PLXCB into nucleus local storage was unsuccessful. Details may be found in ADACOM messages. The nucleus terminates abnormally (abends).
Unable to get Home ASID SToken	The operating system request to acquire a token for the nucleus address space was unsuccessful.

- PLX051** **{dbid} IDTH prefix is not valid**
Explanation The IDT table header has been corrupted. The Adabas cluster terminates abnormally (abends).
Action Reinstall the Adabas SVC to reconstruct the IDT.
- PLX052** **{dbid} Number of IDTE entries is zero**
Explanation The ID table header has been corrupted. The Adabas cluster terminates abnormally (abends).
Action Reinstall the Adabas SVC to reconstruct the IDT.
- PLX053** **{dbid} GETMAIN for CLUPLXB failed**
Explanation GETMAIN for CLUPLXB is acquired above the 16MB line in ECSA. You have insufficient space these for CLUPLXB.
Action Increase the space available to CLUPLXB in ECSA.
- PLX054** **{dbid} MPM initialization failed**
Explanation This is an internal error. The Adabas cluster terminates abnormally (abends).
Actions: Contact your Software AG technical support representative.

PLX055	{dbid} GETMAIN for CQXE failed
Explanation	Virtual storage was insufficient to allocate the CQXE structures.
Action	Increase the virtual storage available and restart the nucleus.
PLX056	{dbid} Dataspace/S64 acquisition failed
Explanation	The Adabas Parallel Services nucleus was unable to connect to a storage object. Further details are available in the associated ADACOM job's messages.
Action	If the cause is not clear after examining the messages in the associated ADACOM, notify your Software AG technical support representative.
PLX057	{dbid} Dataspace/S64 delete failed
Explanation	The Adabas Parallel Services nucleus was unable to delete a storage object. Further details are available in the associated ADACOM job's messages.
Action	If the cause is not clear after examining the messages in the associated ADACOM, notify your Software AG technical support representative.
PLX058	{dbid} ALSERV failed
Explanation	An error occurred attempting to define an ALET to access shared dataspace.
Action	If the cause is not clear after examining the messages in the associated ADACOM, notify your Software AG technical support representative.
PLX059	{dbid} pointer to IDTH is zero
Explanation	This is an internal error. The Adabas cluster terminates abnormally (abends).
Action	Contact your Software AG technical support representative.
PLX060	{dbid} Invalid function code for ADACLU
Explanation	This is an internal error. The Adabas cluster terminates abnormally (abends).
Action	Contact your Software AG technical support representative.
PLX061	{dbid} No useable PLXNUC found
Explanation	This is an internal error. The Adabas cluster terminates abnormally (abends).
Action	Contact your Software AG technical support representative.

PLX062	{dbid} Job is not authorized
Explanation	Adabas Cluster Services and Adabas Parallel Services nuclei must run with z/OS APF authorization.
Action	APF-authorize all load libraries.
PLX064	{dbid} Maximum NUCID is 65000
Explanation	The range of valid NUCIDs is 1-65000. The Adabas cluster terminates abnormally (abends).
Action	Provide a valid NUCID for the cluster nucleus and restart.
PLX066	{dbid} Duplicate NUCID in active PLXNUC
Explanation	An active PLXNUC entry was found in the PLXCB structure for the same NUCID as the starting nucleus.
Action	Nucleus IDs must be unique. If the PLXNUC entry is the result of an earlier nucleus that failed in such a way that it could not be deactivated, the ADARUN FORCE=YES parameter will allow the PLXNUC to be overwritten. Note that incorrect or inappropriate use of FORCE=YES, such as when the NUCID is still active, may cause all nuclei in the cluster to fail and expose the database to corruption.
PLX067	{dbid} Initialization of ADACLU complete
Explanation	The Adabas cluster initialized successfully.
Action	No action is required for this informational message.
PLX068	{dbid} Termination of ADACLU beginning
Explanation	This message is informational only. It indicates whether shutdown processing for ADACLU has begun.
Action	No action is required for this informational message.
PLX069	{dbid} Termination of ADACLU complete
Explanation	This message is informational only. It indicates whether shutdown processing for ADACLU has been completed.
Action	No action is required for this informational message.

PLX071 **{dbid} ADACLU - Invalid CLUINTER eyecatcher**
{dbid} ADACLU - Invalid thread number
{dbid} ADACLU - CLUINTER in use

Explanation These are internal errors. The Adabas cluster terminates abnormally (abends).

Action Contact your Software AG technical support representative.

PLX073 **{dbid} NUCID in use as a cluster DBID**

Explanation The NUCID cannot be the same as any DBID using the same IDT (ADASVC instance).

Action Specify a different NUCID and resubmit the job.

PLX074 **{dbid} CLUFREEUSER command accepted**

Explanation The CLUFREEUSER command syntax and operands have been validated.

Action No action is required for this informational message.

PLX075 **{dbid} CLUFREEUSER invalid syntax starting {text}**

Explanation An error was detected in the syntax or operands of a CLUFREEUSER operator command.

Action Reissue the CLUFREEUSER operator command with correct syntax and operands.

PLX076 **{dbid} {message-text}**

Explanation Various message texts (*message-text*) are associated with this message number. Each is explained in the following table:

Message Text	Explanation
No users were deleted	The CLUFREEUSER operator command was issued, but no eligible users were found to delete.
Not deleted pending RSP 9/20 <i>is number-of users</i>	The CLUFREEUSER operator command was issued but the FORCE parameter was not specified and the number of users specified were pending a response code 9 (ADARSP009), subcode 20.
Number of users deleted is <i>number</i>	The CLUFREEUSER operator command was issued and the number of users listed in the message were deleted.

Action No action is required for these informational messages.

PLX078	{dbid} A local single nucleus is already up (an IDTE is active for this DBID)
Explanation	An Adabas Cluster Services or Adabas Parallel Services nucleus is attempting to start, but there is already an active single nucleus with the same DBID.
Action	Stop the single nucleus and try again.
PLX080	UID mismatch freeing PLXUSER/UTE {address} {reason} UID {uid1} UTE {uid2}
Explanation	ADACLU did not find the expected user ID string when attempting to validate or release a PLXUSER (UTE).
Action	If the UTE value is all zeros, the UTE was already free. This can come about if an error recovery routine such as a z/OS ESTAE attempts to clean up by issuing CL commands. Natural has error recovery that may do this, particularly if a Natural program is canceled. If this is not the case, or the UTE is non-zero, this is an internal logic error. Contact your Software AG technical support representative.
PLX084	{dbid} Net-Work DBID target not held
Explanation	During initialization, termination, or when an Entire Net-Work change of state is detected, the Entire Net-Work DBID target was found not to be assigned to any system.
Action	No action is required for this informational message.
PLX085	{dbid} Net-Work DBID target not acquired
Explanation	The Entire Net-Work DBID target could not be successfully assigned or acquired. This message is accompanied by others such as PLX046, PLX047, PLX048, and PLX089.
Action	If you are unable to determine the cause of the error, contact your Software AG technical support representative for assistance.
PLX086	{dbid} Net-Work DBID target acquired by {system-name}/{svc}
Explanation	This message is issued when a nucleus has detected the DBID target is either released or not assigned, a suitable system was selected to acquire the target, and a nucleus on the system identified in the message (<i>system-name</i>) has successfully acquired the Entire Net-Work DBID target. On some platforms the system name is followed by the SVC number being used on the named system.
Action	No action is required for this informational message.
PLX087	{dbid} Net-Work DBID target held by{system-name}/{svc}
Explanation	During initialization, termination or when an Entire Net-Work change of state is detected, the Entire Net-Work DBID target was found to be assigned to the system named in the message. This message is issued by all member nuclei whenever the DBID target assignment changes. On some platforms the system name is followed by the SVC number being used on the named system.
Action	No action is required for this informational message.

PLX088	{dbid} Net-Work DBID target acquired by this image
Explanation	This nucleus has successfully acquired the Entire Net-Work DBID target.
Action	No action is required for this informational message.
PLX089	{dbid} Net-Work DBID target released by this image
Explanation	The last nucleus, on the system to which the Entire Net-Work DBID target is assigned, is terminating. The DBID target is released and may be acquired by another system, should a suitable one become available.
Action	No action is required for this informational message.
PLX090	{dbid} Attempting to create dataspace/S64
Explanation	The nucleus has signaled ADACOM to attempt to allocate cluster data spaces and shared 64-bit addressable memory objects.
Action	No action is required for this informational message.
PLX091	{dbid} Attempting to delete dataspace/S64
Explanation	This nucleus is terminating and is the last nucleus of this DBID. ADACOM has been signaled to delete cluster data spaces and shared 64-bit addressable memory objects.
Action	No action is required for this informational message.
PLX092	{dbid} Dataspace/S64 deleted
Explanation	The cluster data spaces and shared 64-bit addressable memory objects have been successfully deleted.
Action	No action is required for this informational message.
PLX093	PLXUSER X2/{code} RSP {rsp}/{node}-{subcode} {target}
Explanation	An Adabas Cluster Services or Adabas Parallel Services nuclei issued an internal X2 command to release a PLXUSER representing a user either originating from or routed to another system. Such users have PLXUSERS on both systems. The command failed with the displayed response code and subcode.
	The <i>code</i> listed in the message identifies the reason for the X2 command:

Code	X2 Command Reason
8014	Delete PLXUSER on remote system.
8020	Query PLXUSER status for a user originating from a remote system.
8024	Query PLXUSER status for a local user assigned to a remote system.

Action If the PLXUSER cannot be released at this time, attempts will be made at intervals to release it. Contact your Software AG technical support representative for assistance if the reason for the response code cannot be identified.

PLX097 {dbid} Dataspaces acquired

Explanation The cluster data spaces and shared 64-bit addressable memory objects have been successfully allocated.

PLX099 {dbid} ADACOM not available

Explanation ADACOM cannot be found.

Action Determine why ADACOM is not available and correct the problem. Then restart.

PLX101 {dbid} NUCID {nucid} not found

Explanation The nucleus entered in a TARGET operator command was not active. The nucleus ID (nucid) is given in the message.

Action Try again, specifying the nucleus ID of an active nucleus or using another form of the TARGET operator command.

PLX102 {dbid} No active nuclei on {system}

Explanation No active nuclei were found on the system image entered in a TARGET operator command.

Action Try again, specifying the name of a system image with one or more active nuclei or using another form of the TARGET operator command.

**PLX103 {dbid} Active nuclei under multiple SVCs on {system-name}
Reissue TARGET command using NUCID
NUCID {nucid} SVC {svc}**

Explanation A TARGET operator command specified the name of a system. There are multiple Entire Net-Work nodes on the named system with active Adabas Cluster Services nuclei, each node using a different SVC. There will be one instance of the detail line for every active nucleus on the named system.

Action Select any nucleus ID active on the desired Entire Net-Work node. Reissue the operator command and specify the selected NUCID instead of the system name. Note that the specific nucleus may not be the one to service the request. The NUCID is used only to select a candidate nucleus from the set of active nuclei.

62 PL6* - PRILOG6 Print Program Messages

- Messages from the System-Dependent Component 965

PL6000I	Card read =>{control-card}
Explanation	The PRILOG6 input control card that was read is displayed in the message
Action	No action is required for this informational message.
PL6001E	Unrecognized input card
Explanation	One of the control cards read was not recognized by PRILOG6.
Action	Ensure that all cards either being with PRILOG6 or an asterisk (*) for a comment line.
PL6002E	Invalid parm: {parameter}
Explanation	The specified input parameter or value in the PRILOG6 control cards is invalid.
Action	Correct the identified parameter and rerun the program.
PL6003W	CLOGLAYOUT is x
Explanation	This informs the user as to the CLOGLAYOUT being processed. x is the CLOGLAYOUT type (usually 8, older CLOGs maybe 5).
Action	This is an information message.
PL6004E	VERBOSE parameter requires another qualifier
Explanation	The PRILOG FIELDS VERBOSE parameter requires a qualifier. This error occurs when the parameter FIELDS=(VERBOSE) is input, when the specification should be, for example, FIELDS=(LIST,VERBOSE).
Action	Correct the identified parameter and rerun the program.
PL610I	{nnnnnnnn} records skipped because CLOG created with LOGCB=NO
Explanation	This message list the number of CLOG records (<i>nnnnnnnn</i>) that have been skipped because they do not contain ACB/ACBX data as defined by the ADARUN parameter LOGCB=NO.
Action	No action is required for this informational message.
PL611E	no records read from DDCLOGIN
Explanation	The file linked to DDCLOGIN is either empty or is of the wrong type. This may be accompanied by PL6D02 or PL6D03 messages.
Action	Check the JCL link statement DDCLOGIN and the file linked to it. Correct and rerun the job.

Messages from the System-Dependent Component

PL6D01	DDCARD file failed to open, using defaults
Explanation	The input card file could not be opened.
Action	If the defaults are used, there are no input cards and this file is not required. The message can be ignored. The default values are CLOGLAYOUT=5 and FIELDS=(LIST). If values other than the defaults are required, ensure that the file is available and rerun the job.
PL6D02	DDCLOGIN file failed to open - no reports
Explanation	The file containing the CLOG records did not open. No reports are printed.
Action	Ensure that the file is properly allocated and rerun the job.
PL6D03	DDCLOGIN must be DSORG PS/VB - no Reports
Explanation	The file containing the CLOG records was of the wrong type and not opened. The file on the DDCLOGIN link name should be sequential (DSORG PS) and variable-blocked (RECFM=VB). No reports are printed.
Action	Check the attributes of the file on the DDCLOGIN link name. Reallocate and rerun the job.

63 POP* - Adabas System Coordinator Server Component

Messages

POPnnn messages are issued from the Adabas System Coordinator Adabas server component.

POP000I	Adapop V##### initialised, EP=##### CIB=#####
Explanation	The database interface to the Adabas System Coordinator has been initialized successfully.
Action	None. This message is for information only.
POP001S	Adapop cannot initialise, getmain error
Explanation	ADAPOP cannot initialise because of a memory shortage.
Action	Increase the region specification for the database job.
POP002S	Adapop initialisation failed, kernel load error
Explanation	ADAPOP failed to locate or load the runtime kernel module CORKRN.
Action	Ensure that the load library containing the kernel module is available to the database job.
POP003E	Database proxy module ##### for product ### is invalid (bad eyecatcher)
Explanation	The database component for the indicated product is invalid.
Action	Check and correct the installation.

POP004E	Database proxy module ##### for product ### is not supported
Explanation	The database component for the indicated product is not supported by this version of the Adabas System Coordinator Adabas server component.
Action	The affected product is disabled for this Adabas nucleus. Ensure that you use the correct product versions.
POP005E	Memory shortage alert-no memory for COR threads, add-ons are deactivated
Explanation	An Adabas option command cannot be completed because of a memory shortage.
Action	The affected commands will receive RSP101/24. There is a possibility that some critical command-related processing was not able to be performed in the case where this message appears. The most critical situation is where Adabas Fastpath is in full operation for the database (beyond a simple AFLOOK sample). In this case Fastpath will attempt to automatically switch off optimization for the database to ensure there is no risk to the coherence between cache and database content. The administrator should check to make sure this has happened and if there is any doubt, manually stop the optimization for the database - or shut the entire Fastpath caching down. More memory needs to be made available to the System Coordinator within the database job. This may be achieved by making more memory available to the job (increasing REGION size etc.) or if there is no more memory available for the job then reducing LBP (or similar) by 1 megabyte should alleviate the problem when the database is next recycled.
POP006S	Append of product v-con list failed
Explanation	This is an internal error.
Action	Contact your Software AG technical support representative.
POP007S	ADAPOV load error
Explanation	The anchor module ADAPOV cannot be loaded. This module is distributed with the main Adabas libraries and should always be present. Failure to load this module could cause problems with the initialization of the Adabas System Coordinator component.
Action	Ensure that the load library containing ADAPOV is available to the job.
POP008E	IOR failure - function: ## error ##
Explanation	An internal error occurred during the processing of an operating system dependent function.
Action	Contact your Software AG technical support representative for assistance.

POP009I	Adapop running in DEMO mode
Explanation	<p>Adapop is running in DEMO mode because Adabas System Coordinator is not available to this job.</p> <p>This message normally indicates that this Adabas nucleus is running with ADARUN FASTPATH=YES and/or ADARUN VISTA=YES for the purpose of using the AFPLOOK and/or AVILOOK command samplers which are supplied with the Adabas distribution library.</p> <p>Note:</p> <p>The presence of this POP009I message when any of the products below are in use indicates that the product(s) may not be operating as intended. For example, if Adabas Fastpath is in use, this nucleus will not be eligible for command optimization:</p> <ul style="list-style-type: none"> ■ Adabas Fastpath ■ Adabas Vista ■ Adabas Transaction Manager ■ Adabas SAF Security <p>For successful product operation, the database process must be correctly enabled by the availability of the Adabas System Coordinator load library. If necessary, refer to the relevant product's installation guide.</p>
Action	If you have Adabas System Coordinator installed at your site then make it available to this job. Otherwise this message is for information only.
POP010E	Incompatible version of SAFADA detected
Explanation	A security check has been requested but the database proxy module SAFADA for product Adabas SAF Security is not at the required maintenance level.
Action	Apply all available Adabas SAF Security maintenance from Empower.
POP011E	Database proxy module SAFADA for product AAF is not available
Explanation	The database is configured to require the mandatory presence of Adabas SAF Security's database proxy module SAFADA
Action	Ensure Adabas SAF Security's database proxy module SAFADA is available to the database.

64

Adabas Review 00xxx Messages

REV00MNF **Message {msg-id} not found in {logon-id}**
Explanation A message inquiry was made for a message number that is not known to Adabas Review. This will happen if an invalid message number is entered.
Action If the message number is for an Adabas Review message, contact your Software AG technical support representative.

REV00001 **Welcome to Adabas Review V {v.r.s} running under {tp-monitor}**
Explanation This message welcomes users to Adabas Review and indicates the environment under which they are running.

v.r.s	the version, revision, and SP level.
tp-monitor	the active TP monitor.

Action This message is for information only.

REV00002 **Review command must begin with subsystem code**
Explanation An invalid command was entered from the Adabas Review main menu. All commands from the main menu must begin with a subsystem code as shown on the screen.
Action Enter a valid command.

REV00003 **THIS FIELD IS NOT ALLOWED FOR DETAIL REPORTS**
Explanation The specified field is not allowed for detailed reports.
Action Remove the incorrect field.

REV00004	Enter Review command
Explanation	Adabas Review is waiting for terminal input.
Action	Press a valid PF key or enter an Adabas Review command.
REV00005	Invalid command
Explanation	An invalid command was entered into the Adabas Review command line.
Action	Press a valid PF key or enter a valid Adabas Review command.
REV00006	Press 'Enter' to continue initialization process
Explanation	During Adabas Review initialization a series of messages are displayed. Adabas Review will pause whenever a page is full or on the last page.
Action	Press ENTER.
REV00008	No online system of Review is available
Explanation	Adabas Review has determined that there are no online systems available to the user. There are two possible causes: <ol style="list-style-type: none">1. the installation of Adabas Review has not been fully completed.2. Adabas Review is installed, but your profile prohibits you from accessing the available systems.
Action	Contact your Adabas Review administrator.
REV00011	Interval statistics profile has been created
Explanation	During Adabas Review initialization, the interval statistics profile record was created.
Action	This message is for information only.
REV00012	Report has been saved
Explanation	The request to save a report definition to the Adabas Review repository has completed successfully.
Action	This message is for information only.

REV00013	Now viewing current data
Explanation	You are now viewing current data as opposed to historical data.
Action	This message is for information only.
REV00014	{user-id} is not authorized to use Review
Explanation	Either you have not been defined to Adabas Review, or you are not authorized to use Adabas Review.
Action	Contact your Adabas Review administrator.
REV00015	Report name is required
Explanation	An attempt was made to edit/copy a report without a name.
Action	Enter a name in the report name field.
REV0001	At least one item must be selected
Explanation	An attempt was made to add a report without selecting any items to be used as report criteria.
Action	Select one or more fields to be used as criteria by entering a number in its ORDER field.
REV00020	Order number must not exceed 20 (max number of items)
Explanation	A number greater than 20 was entered into one of the ORDER fields.
Action	Enter a number between 1 and 20.
REV00021	Order number must be unique
Explanation	Duplicate ORDER numbers have been detected.
Action	Enter a unique number in each ACCT ORDER to be included in the report.
REV00025	Now viewing historical data
Explanation	You are now viewing historical data as opposed to current data.
Action	This message is for information only.

REV00026	Report was not saved
Explanation	The request to save a report was not successful. This is usually caused by responding NO when asked if you want to replace the report that was previously saved under the same name.
Action	This message is for information only.
REV00002	There are no detailed records for this report
Explanation	<i>A detailed response time</i> report was requested but there are no detail records for the selected report.
Action	This message is for information only.
REV00028	Report was not refreshed
Explanation	This indicates that a request to restart a report was not successful.
Action	This message is for information only.
REV00029	Invalid reply
Explanation	An invalid reply was given to an Adabas Review prompt.
Action	Enter a valid reply.
REV00030	Report has been purged
Explanation	This confirms that the purge report request was successful.
Action	This message is for information only.
REV00032	Report not found
Explanation	An attempt to access a report has failed because the report is not active.
Action	This message is for information only.
REV00033	Unknown return code from purge - RC= {ret-code}
Explanation	An unknown return code was returned from the purge reports program due to an internal error.
Action	If the problem reoccurs, contact your Software AG technical support representative.

REV00035	This is the oldest historical snapshot
Explanation	This is the oldest historical snapshot; the NEXT command cannot be entered.
Action	This message is for information only.
REV00036	Do not enter {x} and a direct command
Explanation	A reply was entered into an Adabas Review prompt field and a direct command was entered simultaneously.
Action	Either answer the Adabas Review prompt or enter a direct command, but not both.
REV00037	Invalid response - only valid response is {xxx}
Explanation	An invalid response was detected and Adabas Review is prompting the user with the correct response.
Action	Enter a valid response.
REV00038	Report status has been changed
Explanation	This confirms that a request to activate or deactivate a report was successful.
Action	This message is for information only.
REV00040	Redisplay buffer full - Redisplay unavailable
Explanation	The redisplay is unavailable because more than 5000 lines were displayed.
Action	As a workaround, the report data can be printed via the HC command and other tools can be used to scroll through this output.
REV00043	You must reply 'Y' or 'N'
Explanation	An invalid reply was given in response to an Adabas Review prompt that requires a reply of either yes ("Y") or no ("N").
Action	Reply "Y" or "N".
REV00044	Value must be between 0 and 100
Explanation	The value entered was not within the range 0 and 100.
Action	Enter a value between 0 and 100.

REV00045	Do not mark blank lines
Explanation	A selection was marked on a line that does not have a value or any data to select.
Action	Mark a valid selection or enter an Adabas Review command.
REV00046	Do not mark deleted reports
Explanation	A character was placed in the select field of a report that was just deleted.
Action	Do not place a character in this field.
REV00047	Invalid character
Explanation	An invalid character was entered into an Adabas Review field.
Action	Enter a valid character.
REV00050	Non-zero return code from FREEMAIN
Explanation	An unexpected return code has occurred while trying to free storage. The return code is also displayed.
Action	If the problem recurs, contact your Software AG technical support representative.
REV00054	Now creating sample report {report-name}
Explanation	When Adabas Review is invoked online for the first time, it adds sample Adabas reports to its system file.
Action	This message is for information only.
REV00055	Select a historical snapshot
Explanation	Select a historical snapshot.
Action	This message is for information only.
REV00057	Use of function is prohibited
Explanation	An attempt was made to perform an Adabas Review function that is not permitted for the user.
Action	Contact your Adabas Review administrator.

REV00058	There are no saved reports to list
Explanation	A request to list report definitions was made but there are no definitions to list.
Action	This message is for information only.
REV00059	Operator command issued
Explanation	The operator command was issued to Com-plete.
Action	This message is for information only.
REV00060	No report selected to view
Explanation	An attempt was made to perform an Adabas Review View function, but no report was selected
Action	Access a report using a List or Edit function and the retry the View function.
REV00062	No data has been accumulated for this report
Explanation	A request to display a report cannot be satisfied because the report has not yet accumulated any data.
Action	Determine if the report criteria is correct and if so, try again later or else add a new report.
REV00064	Invalid function
Explanation	An invalid function was entered.
Action	Enter a valid function.
REV00065	DBID missing
Explanation	DBID= was entered on the Adabas Review command line of the Adabas Communication Statistics display, but no corresponding DBID number was given.
Action	Enter DBID= <i>nnn</i> where <i>nnn</i> is a valid DBID number.
REV00066	Invalid cursor position
Explanation	The cursor was placed at an invalid location on a screen that senses the cursor position to perform a function.
Action	Place the cursor at a valid position or enter an Adabas Review command.

REV00068	Invalid logical operator
Explanation	An invalid logical operator was entered. Valid operators are: =,;, <, >, EQ, NE, LT, GT, LE, GE
Action	Enter a valid logical operator.
REV00072	Mark one line only
Explanation	More than one line was marked to perform a report function. This is not allowed.
Action	Mark only one line at a time.
REV00073	Invalid character in select column
Explanation	A line has been marked with a character that has no assigned function.
Action	Mark lines using valid characters.
REV00074	Invalid Transaction Summary option
Explanation	An invalid option was entered into the Transaction Summary Option field in the Edit Report screen.
	Valid options are NONE, SUM, and DET.
Action	Enter a valid option.
REV00078	Report was not purged
Explanation	The request to purge a started report was not performed.
Action	This message is for information only.
REV00079	Invalid message prefix
Explanation	An inquiry was made for a message number that has an invalid prefix. Message numbers must start with REV.
Action	Enter the MSG command using a valid message number.
REV00080	Com-plete functions are not valid under CICS
Explanation	A Com-plete performance monitor function was attempted. This is not valid under CICS.
Action	This message is for information only.

REV00081	Review is not compatible with this version of Com-plete
Explanation	A Com-plete performance monitor function was attempted on a version of Com-plete earlier than version 4.4.
Action	Install the current version of Com-plete.
REV00082	Select a buffer pool or enter a Review command
Explanation	The Adabas Review buffer pool function is waiting for terminal input.
Action	Select a buffer pool by name or enter an Adabas Review command.
REV00083	Syntax error in scan command
Explanation	A syntax error was detected while processing a scan command on the ET display.
Action	This message is for information only.
REV00084	Invalid buffer pool name
Explanation	The buffer pool selection entered cannot be identified.
Action	Enter a valid buffer pool name or enter an Adabas Review command.
REV00085	Command not allowed in history mode
Explanation	The command entered is not allowed in history mode.
Action	Do not enter command.
REV00086	No ADAB control block found
Explanation	The Adabas Communication Statistics function was invoked, but there has not been any database access since Com-plete was started. Therefore, there is no database information to display.
Action	Try again later.
REV00087	{nn} Reports removed from AUTOSTART status
Explanation	This confirms that the indicated report definitions have been changed from AUTOSTART to NON-AUTOSTART status.
Action	This message is for information only.

REV00091	Invalid command code
Explanation	An invalid code was entered for a command.
Action	Enter a valid command code.
REV00092	Report has been started
Explanation	This confirms that the request to start a report was successful.
Action	This message is for information only.
REV00093	Syntax error(s) in report definition
Explanation	The request to start an online report has failed because of syntax errors in the report definition.
Action	Correct the report definition and start the report again.
REV00094	Adabas response code {rsp}
Explanation	Adabas has responded with a non-zero response code.
Action	Use the <i>Adabas Messages and Codes</i> documentation to determine the problem.
REV00095	Report was not started
Explanation	The request to start a report was not successful.
Action	This message is for information only.
REV00096	User profile is being held by another user
Explanation	An attempt was made to access a user profile that is being updated by another user.
Action	Edit the user profile again. Ensure that the changes made to profile do not affect the changes that you are making.
REV00097	User profile not specified
Explanation	The purge user (PU) command was given without specifying a user profile.
Action	When using the purge user (PU) command, specify the user profile you wish to purge. The format for the command is PU <i>uuuuuu</i> where <i>uuuuuu</i> is the user profile.

REV00098	User profile was not purged
Explanation	A request was made to purge a user profile. When Adabas Review asked for a confirmation, the user decided not to purge the user profile.
Action	This message is for information only.
REV00099	User profile was not found
Explanation	An attempt was made to delete a user profile that was not found in the Adabas Review repository.
Action	Check to make sure the user ID you specified is correct.
REV00100	User profile has been purged
Explanation	This confirms that a request to purge a user profile was successful.
Action	This message is for information only.
REV00101	New user profile
Explanation	The profile that you are editing is new.
Action	You may now customize the new user profile. To save this new profile, press PF5or issue the SAVE command.
REV00102	User profile was not saved
Explanation	A request was made to save the changes made to a user profile. When Adabas Review asked for a confirmation, the user decided not to save the changes.
Action	This message is for information only.
REV00104	Return code {ret-code} received from {program-name}
Explanation	An unexpected return code was received from one of Adabas Review's programs.
Action	Record the error message and contact your Software AG technical support representative.
REV00105	User profile has been saved
Explanation	The changes made to the user profile have been saved.
Action	This message is for information only.

REV00106	No Review control block found
Explanation	(CICS Only) This message appears when <i>REVTAB</i> has not been defined as a resident program.
Action	Contact your Software AG technical support representative.
REV00108	Default user profile has been added
Explanation	This message appears the first time Adabas Review is invoked after installation. A DEFAULT user profile is added to the Adabas Review repository, which allows all users to perform all functions of Adabas Review including the ability to maintain user profiles.
Action	A logical procedure at this point would be to invoke the user profile system and add yourself as able to maintain user profiles. Then update the DEFAULT profile so that general users cannot maintain user profiles.
REV00111	No storage available to start report
Explanation	A request to start a report has failed due to insufficient storage. This is probably because of other reports that are using most or all of the storage allocated to Adabas Review.
Action	Purge one of the already existing reports or try again later.
REV00116	Statistics profile was not saved
Explanation	The statistics profile was not saved.
Action	This message is for information only.
REV00120	Users attached for test simulation
Explanation	This confirms that users have been attached to simulate a load on Com-plete.
Action	This message is for information only.
REV00121	Error {error-number} attaching users
Explanation	An error has occurred while trying to attach users for load simulation.
Action	If the problem reoccurs, contact your Software AG technical support representative.

REV00123	Statistics profile has been saved
Explanation	The statistics profile has been saved.
Action	This message is for information only.
REV00124	TID number must be numeric
Explanation	A TID number was entered into the SA screen via the T= or TID= command but is was not numeric.
Action	Enter a numeric TID number.
REV00125	Report definition has been saved successfully
Explanation	This confirms that the request to save a report definition was successful.
Action	This message is for information only.
REV00129	Report definition not found
Explanation	An attempt was made to retrieve a report definition but no report definition by that name was found.
Action	Determine the correct name or create a new definition.
REV00132	Interval may not be greater than 1440 minutes
Explanation	The interval may not be greater than 1440 minutes.
Action	This message is for information only.
REV00133	Review is terminating
Explanation	A request was made to start, view, or list a report, but Adabas Review is in the process of terminating.
Action	This message is for information only.
REV00134	Duplicate report name - report not started
Explanation	An attempt to start an Adabas report has failed because a report with the same name is already active.
Action	Purge the currently active report and retry or start a report with a different name.

REV00135	Review command not provided
Explanation	An attempt was made to communicate with the Adabas Review exit but no Adabas Review command was provided.
Action	Provide an Adabas Review command.
REV00137	Insufficient storage to issue Review command
Explanation	The Adabas Review exit routine is not accepting communications due to insufficient storage.
Action	Purge at least one of the started reports.
REV00138	Insufficient storage to start report
Explanation	An attempt to start an Adabas Review report has failed due to insufficient storage.
Action	Purge an active report and retry.
REV00139	Invalid SUMMARY, MAX or MIN field
Explanation	An attempt to start an Adabas Review report has failed because fields were marked as Sum, Min, Max, or Avg, but these fields are only allowed to be Order fields.
Action	Make the fields Order fields only.
REV00140	An invalid value was specified in the RULE
Explanation	An attempt to start an Adabas Review report has failed because values specified in the Rule where either too long, or in case of numbers with a decimal point, the formatting is not correct.
Action	Specify a correct value in the RULE.
REV00141	Format buffer error
Explanation	A format buffer error has occurred while trying to communicate with the Adabas Review exit routine.
Action	Contact your Software AG technical support representative.
REV00144	Display program not found
Explanation	An attempt to view an active report has failed because the display program for this report cannot be found.
Action	Generate a display program by resaving the report definition, if it is available, or change the display program name on the LS screen to a program name that is known to be acceptable for this report.

REV00145	Natural error: {error-number}
Explanation	A Natural error condition occurred. The Natural error message number is displayed.
Action	Reference the Natural online message utility for an explanation of the error.
REV00146	Report definition was not saved
Explanation	The request to save a report definition was canceled by the user in response to an overlay warning.
Action	This message is for information only.
REV00147	Too many fields - exceeds max linesize - save canceled
Explanation	The request to save a report definition was canceled because the resulting generated display program would have exceeded the maximum allowable line size.
Action	Reduce the number of fields and try again.
REV00148	DBID has been changed
Explanation	This confirms that the request to change the target DBID was successful.
Action	This message is for information only.
REV00149	There are no started reports
Explanation	A request to list started reports was made but there are no started reports to list.
Action	This message is for information only.
REV00150	Detailed reports cannot be viewed online
Explanation	Only summary reports can be viewed online. Detailed reports are printed at Adabas termination time.
Action	This message is for information only.
REV00151	Insufficient storage to reactivate report
Explanation	An attempt was made to reactivate a report that was deactivated by Adabas Review due to insufficient storage. The report cannot be reactivated.
Action	Use the refresh (RF) command to purge the existing data and start accumulating new information.

REV00152	Report has been refreshed
Explanation	This confirms that a refresh (RF) command was successful.
Action	This message is for information only.
REV00153	There are no history reports
Explanation	A request to List History Reports was canceled because there are no history reports to list.
Action	This message is for information only.
REV00155	DBID must be between 0 and 255.
Explanation	An attempt was made to change the DBID number to less than 0 or greater than 255.
Action	Enter a DBID number in the range of 0 to 255.
REV00156	Invalid AND/OR field
Explanation	A value other than AND or OR was entered into the AND/OR field of the selection criteria on the Processing Rules screen.
Action	Enter AND or OR.
REV00157	No field specified
Explanation	No field name was specified for the entered criteria on the Edit Report screen.
Action	Enter a field name.
REV00158	AND/OR field not followed by another condition
Explanation	AND or OR was entered into the AND/OR field of the Processing Rules screen but no condition followed.
Action	Either remove the AND/OR or enter another condition.
REV00159	AND/OR field missing
Explanation	More than one condition was coded on the Processing Rules screen, but no AND/OR was coded for the previous condition.
Action	Enter AND/OR on the previous condition

REV00160	OPERATOR field missing
Explanation	The OPERATOR field has been left blank on a condition.
Action	Fill in the OPERATOR field.
REV00161	VALUE field missing
Explanation	The VALUE field has been left blank on a condition.
Action	Fill in the VALUE field.
REV00162	Invalid OPERATOR field
Explanation	An invalid operator was entered into the OPERATOR field of the Processing Rules screen.
Action	Enter a valid operator.
REV00163	Invalid field name
Explanation	An invalid field name was entered on the Edit Report screen.
Action	Press PF11 for a list of valid field names.
REV00169	ORDER number too high
Explanation	A number greater than 20 was entered into the ORDER field of the Edit Report screen. 20 is the highest number that can be entered.
Action	Enter a number between 1 and 20.
REV00170	{field-name} is not a valid field for SUM, AVG, PCT or ROUND
Explanation	A field was marked for SUM, AVG, PCT, or ROUND on the Edit Report screen, but the field marked is not a numeric field. Fields must have a numeric output to be eligible for SUM, AVG, PCT, or ROUND.
Action	Place a number in the ORDER column, and remove any marks for SUM, AVG, PCT, or ROUND.
REV00171	SAVE/START canceled by operator
Explanation	The request to save a report definition was canceled by the user in response to an overlay warning.
Action	This message is for information only.

REV00175	Invalid value
Explanation	An invalid value was entered as part of a logical condition on the Edit Report screen.
Action	Enter a valid value.
REV00176	Internal storage error
Explanation	An internal storage management error has occurred within the Adabas Review nucleus.
Action	If the problem recurs, contact your Software AG technical support representative.
REV0017	ROUND is only valid on fields with an ORDER number
Explanation	A rounding factor was specified for a field that does not also have an order number specified.
Action	Enter a number in the ORDER field, or remove the rounding factor.
REV00179	You must enter ORDER, SUM, MIN, MAX, PCT or AVG
Explanation	A field was entered on the Edit Report screen but no action was specified; i.e. ORDER, SUM, MIN, MAX, PCT, or AVG.
Action	Enter a number in the ORDER field and/or an X in one or more of the SUM, MIN, MAX, PCT, or AVG fields
REV00180	Invalid data in ROUND column
Explanation	The data entered into the round column of the Edit Report screen was not numeric.
Action	Enter a number with or without a decimal into the round field.
REV00181	ADACALL must be an integer between 0 and 32,767
Explanation	ADACALL specifies the maximum number of Adabas calls an application can make before the Com-plete / Adabas interface forces the application to be rolled out. This parameter is ignored if ADAROLL=NO is specified.
Action	Enter a number between 0 and 32,767.
REV00182	ADALIMIT must be an integer between 0 and 32,767
Explanation	ADALIMIT specifies the number of Adabas calls that may be made by an online transaction without any intervening terminal I/O. Programs that exceed this limit are canceled.
Action	Enter a number between 0 and 32,767.

REV00183	ADAROLL must be 'ALWAYS', 'NEVER', or less than 30.99
Explanation	ADAROLL specifies the amount of time Com-plete will wait for Adabas calls before rolling out the program making the call.
Action	Enter ALWAYS, NEVER, or a number less than 30.99.
REV00184	ADACALL for DBID {dbid} has been changed to {yyyyy} by {user-id}
Explanation	The ADACALL parameter for the specified database was changed to yyyyy through the facilities provided by the Adabas Communication Statistics function (Adabas Calls from Com-plete) in Adabas Review DC.
Action	This message is for information only.
REV00185	ADALIMIT for DBID {dbid} has been changed to {yyyyy} by {user-id}
Explanation	The ADALIMIT parameter for the specified database was changed to yyyyy through the facilities provided by the Adabas Communication Statistics function (Adabas Calls from Com-plete) in Adabas Review DC.
Action	This message is for information only.
REV00187	Only 'Y' and 'N' are valid values
Explanation	The letter "Y" (yes) and the letter "N" (no) are the only two valid values for this field.
Action	Enter "Y" if you wish the APPLYMOD to be active; or enter "N" if you wish to deactivate the applymod.
REV00188	The ADABAS/COM-PLETE parameters have been updated
Explanation	This message confirms that the Adabas / Com-plete parameters have been successfully updated.
Action	This message is for information only.
REV00190	Invalid cursor placement for requested function
Explanation	The cursor must be placed on a line that contains valid data.
Action	Place cursor on a line with valid data.
REV00193	Too many {xxx} fields
Explanation	xxx is ORDER, SUM, MIN, MAX, AVG, or ROUND. There were too many of the indicated fields to process. When all field names are combined, they will not fit into an 80-byte statement. The 80-byte statements are used internally by Adabas Review for report definition storage.
Action	Reduce the number of fields by one until the message disappears.

REV00195	Invalid page number entered
Explanation	A number was entered on the Adabas Review command line that was greater than the actual number of pages available.
Action	Enter a valid page number.
REV00196	Roll buffer not allocated
Explanation	The roll buffer is not allocated.
Action	This message is for information only.
REV00197	Roll data sets not allocated
Explanation	The roll data sets are not allocated.
Action	This message is for information only.
REV00198	User not logged on
Explanation	The user is not logged on.
Action	This message is for information only.
REV00199	Invalid wrap option
Explanation	An invalid wrap option was specified in the report definition. The option must be NONE, STD, or HIGH.
Action	This message is for information only.
REV00200	Low water mark must be less than high water mark
Explanation	The low water mark specified was higher than or equal to the high water mark.
Action	Enter a number less than the high water mark.
REV00202	Review is not installed in database {dbid}
Explanation	An attempt was made to either start a report or to list started reports against a database that either does not have Adabas Review installed as a user exit 4 or does not currently have LOGGING turned on.
Action	Verify that Adabas Review is installed on the target DBID. If it is, ensure that ADARUN LOGGING=YES has been specified and that LOGGING has not been subsequently disabled from the operator console.

REV00203	Report hard copy has been queued
Explanation	This confirms that a request to send report output to a hardcopy device completed successfully, and that the report is either now printing or has been placed on the queue to be printed.
Action	This message is for information only.
REV00205	Invalid display program name
Explanation	An attempt was made to change the display program name using the CP command of the List Reports screen, but the new name is blank or invalid.
Action	Enter a valid program name.
REV00206	Display program name has been changed
Explanation	This confirms that the request to change the display program name using the CP command of the List Report Definitions screen was successful.
Action	This message is for information only.
REV00207	Report definition was purged by another user
Explanation	The report definition selected is being purged by another user.
Action	This message is for information only.
REV00209	Invalid character in report name
Explanation	An invalid character such as a quotation mark or a period was used as part of the report name.
Action	Remove the invalid character from the report name.
REV00210	Invalid start/stop date
Explanation	A date range was entered for viewing a history report but the date(s) are not valid. This may mean that the starting date is greater than the ending date, or that invalid numeric data or an invalid date format has been entered.
Action	Enter a valid date range in the form of <i>yyyy-mm-dd</i> or press ENTER to default to the maximum date range.

REV00211 **History reports must be purged from the expanded list**
Explanation An attempt was made to purge a history report from the LH screen. This is not a valid LH function. The list must be expanded using the EX command before history reports can be purged.
Action Enter EX in the SEL column next to the report to be purged. An expanded list will appear from which the Purge History Report (PH) function can be executed.

REV00212 **Enter date range**
Explanation This prompts you to enter a date range before viewing a history report. The maximum date range (all dates) is the default.
Action Enter a date range in the form of *yyyy-mm-dd*, or press ENTER to default to the maximum date range.

REV00214 **Display program regeneration complete**
Explanation The request to regenerate display programs has completed successfully.
Action This message is for information only.

REV00217 **Review system file not available**
Explanation Adabas Review attempted to read information from its system file but received an Adabas response code of 148 (ADARSP148).
Action Bring up the database that has the Adabas Review repository and make sure that the FILE parameter has been specified correctly.

REV00218 **Default system must be 'DB', 'DC', 'MM', or 'NM'**
Explanation An invalid value was entered for default system. The valid system codes are:

DB	Database (Adabas Review)
DC	Data Communication
MM	Main Menu
NM	Natural Monitor

Action Enter a valid system code.

REV00219	Input not numeric
Explanation	A value was entered into a field that is intended to accept numeric data only.
Action	Enter a valid numeric value.
REV00220	Auto regenerate started
Explanation	The subtask to generate auto-report definitions was successfully started.
Action	This message is for information only.
REV00221	Auto regenerate already active
Explanation	The subtask to generate auto-report definitions is still active from a previous execution.
Action	Wait a few seconds and try the command again.
REV00222	Auto regenerate failed
Explanation	The subtask to regenerate auto-report definitions was not attached and did not run.
Action	Check your Adabas STEPLIB and make certain that the module RAOSAUTO is present.
REV00223	UEX4 version error
Explanation	The Adabas UEX4 module RAOSEXIT is not the correct version.
Action	Verify that Adabas Review has been correctly installed.
REV00224	MSG function not available from this screen
Explanation	The Adabas Review message help subsystem is not available from this screen.
Action	Perform the MSG function from another screen.
REV00225	DBID must be between 1 and 65535
Explanation	The target database ID must be in the range between 1 and 65535.
Action	Enter a database ID in the specified range.
REV00226	SVC is zero
Explanation	The SVC specified cannot be zero (0).
Action	Enter a correct SVC number.

REV00227	Target type must be 'ADA', 'NET', 'NPR', or 'TPF'
Explanation	The target type must be one of the specified values.
Action	Enter the correct target type.
REV00228	DBID for Adabas target type must be less than 255
Explanation	If the target type is <i>ADA</i> , then the target database ID must be in the range of 1 to 255.
Action	Enter a database ID in the specified range.
REV00229	Field value must be 'Y' or 'N'
Explanation	An invalid value was entered for the field.
Action	Enter a valid field value: either yes ("Y") or no ("N").
REV00230	No target definition found for target {target-id}
Explanation	The target definition did not exist for the requested target.
Action	Define the target.
REV00231	Target definition for DBID {dbid} saved
Explanation	The target definition was successfully saved.
Action	This message is for information only.
REV00234	Default definition cannot be purged
Explanation	The default definition for target 00000 cannot be purged.
Action	This message is for information only.
REV00235	Target definition(s) purged successfully
Explanation	The target definitions marked for purge were successfully deleted.
Action	This message is for information only.
REV00236	No target definition exists for DBID dbid and default is not present
Explanation	The target definition for the database specified did not exist, and there was also no default definition.
Action	Add the target definition for the specified target.

REV00237	Generate started
Explanation	The subtask to generate report definitions was successfully started.
Action	This message is for information only.
REV00238	Generate already active
Explanation	The subtask to generate report definitions is still active from a previous execution.
Action	Wait a few seconds and try the command again.
REV00239	Generate failed
Explanation	The subtask to generate report definitions was not attached and did not run.
Action	Check your Adabas STEPLIB and make certain that the module RAOSAUTO is present.
REV00240	Function canceled
Explanation	The requested function was terminated by user request and was not performed.
Action	This message is for information only.
REV00241	Review file set successfully
Explanation	The Adabas Review data file's database ID and file number were set successfully.
Action	This message is for information only.
REV00242	Unable to open command log file for output
Explanation	A report was started with the logging option set to "Y" (yes), but the file specified for output cannot be opened. The report is started without logging.
Action	If this is an online report, make sure the DSN field of the Report Options screen is set to a valid command log output file. If this is a batch report, make sure the DSN= parameter of the LOG statement is set to a valid command log output file.
REV00243	Adabas Online Services is not installed
Explanation	The request to invoke Adabas Online System (AOS) from Adabas Review has failed because AOS is not installed in the current Natural system file.
Action	This message is for information only.

REV00244	Components not installed properly
Explanation	The installation process did not complete successfully.
Action	Make sure that all INPL and IUPD media are properly installed.
REV00245	PF{nn} not defined
Explanation	The PF key that was pressed is not defined to perform a function.
Action	Press a valid PF key.
REV00246	Press 'PF3' to exit or 'PF5' to save the profile
Explanation	To exit without saving the changes made to a user profile, press PF3. To save the changes made to a user profile, press PF5.
Action	See explanation.
REV00247	Userid must be specified
Explanation	A user ID must be specified.
Action	Enter a user ID.
REV00248	Natural error {error-number} has occurred on line {line-number} of program {program-name}
Explanation	A Natural error has occurred in one of Adabas Review's programs.
Action	Record the information given in the message and contact your Software AG technical support representative.
REV00249	Command log data set already in use
Explanation	A report was started with the logging option set to "Y" (yes), but the specified output data set is already in use by another report. The report is started without logging.
Action	Either use another data set, or purge the report that is using the command log data set.
REV00250	Logging is not valid for summary reports
Explanation	LOGGING was specified on the Report Options screen for a summary report. Only detail reports can perform the LOGGING function.
Action	Either set LOGGING to "N" or set SUM/DETAIL to "D".

REV00252	At least one field is required
Explanation	An attempt was made to save a report definition with no fields to be displayed. At least one field is required to save a report.
Action	Correct the report definition and press PF5to save the report definition.
REV00253	There are no report definitions on file
Explanation	A request to list report definitions cannot be satisfied because there are no definitions to list.
Action	This message is for information only.
REV00254	At least one order field is required
Explanation	An attempt to save a summary report failed because there are no ORDER fields. At least one ORDER field is required for summary reports.
Action	Make at least one field an ORDER field and save the report.
REV00255	Report definition conversion complete
Explanation	The process of converting Adabas Review report definitions has completed.
Action	This message is for information only.
REV00256	History file conversion complete
Explanation	The process of converting Adabas Review history reports completed.
Action	This message is for information only.
REV00257	User profile conversion complete
Explanation	The process of converting Adabas Review user profiles has completed.
Action	This message is for information only.
REV00258	Report definition conversion was canceled
Explanation	The process of converting Adabas Review report definitions was canceled at the request of the user. Any reply other than "yes" or "change" on the LFILE confirmation screen will cause this message.
Action	This message is for information only.

REV00259	History file conversion was canceled
Explanation	The process of converting Adabas Review history reports was canceled at the request of the user. Any reply other than "yes" or "change" on the LFILE confirmation screen will cause this message.
Action	This message is for information only.
REV00260	User profile conversion was canceled
Explanation	The process of converting Adabas Review user profiles was canceled at the request of the user. Any reply other than "yes" or "change" on the LFILE confirmation screen will cause this message.
Action	This message is for information only.
REV00261	There are no report definitions to convert
Explanation	An attempt was made to convert report definitions, but there are none to convert. Adabas Review only converts report definitions that do not already exist in the target Adabas Review repository.
Action	This message is for information only.
REV00262	There are no history reports to convert
Explanation	An attempt was made to convert Adabas Review history reports, but there are none to convert.
Action	This message is for information only.
REV00263	There are no user profiles to convert
Explanation	An attempt was made to convert Adabas Review user profiles, but there are none to convert. Adabas Review only converts user profiles that do not already exist in the target Adabas Review repository.
Action	This message is for information only.
REV00264	Error {error-number} while trying to convert report definitions
Explanation	Either an Adabas or a Natural error has occurred while trying to convert report definitions.
Action	Follow the Adabas or Natural procedures for error correction.

REV00265	Error {error-number} while trying to convert history reports
Explanation	Either an Adabas or a Natural error has occurred while trying to convert history reports.
Action	Follow the Adabas or Natural procedures for error correction.
REV00266	Error {error-number} while trying to convert user profiles
Explanation	Either an Adabas or a Natural error occurred while trying to convert user profiles.
Action	Follow the Adabas or Natural procedures for error correction.
REV00267	Do not try to convert to and from the same file
Explanation	An attempt was made to run an Adabas Review conversion program with identical TO and FROM files.
Action	Correct the LFILE for the TO or FROM file.
REV00268	Invalid file number
Explanation	The user attempted to change the database ID and file number of the Adabas Review repository. The file number specified was not an Adabas Review file.
Action	Specify a correct Adabas Review DBID/file number.
REV00269	No active targets found on SVC {svc}
Explanation	No active database targets were found on the SVC number specified in the message.
Action	Verify that the target definitions are defined to the correct SVC number.
REV00270	Database {dbid} is a Natural Process target
Explanation	The target selected is an Entire System Server (formerly Natural Process) target type.
Action	This message is for information only.
REV00271	Database {dbid} is not active
Explanation	The database selected is not active.
Action	This message is for information only.

REV00272	Database {dbid} is a non-Adabas target
Explanation	The database selected is a non-Adabas type target.
Action	This message is for information only.
REV00273	Report is already suspended
Explanation	An attempt was made to suspend a report that was is already suspended.
Action	This message is for information only.
REV00274	Invalid OP summary option
Explanation	An invalid option was entered on the Edit Report screen for the OP summary parameter.
Action	Enter a valid option.
REV00275	New report definition
Explanation	A new report definition is being created.
Action	Enter the parameters for the new report definition or exit.
REV00276	Report is already active
Explanation	An attempt was made to reactivate a report that was already active.
Action	This message is for information only.
REV00277	History data has been purged
Explanation	Historical data was purged.
Action	This message is for information only.
REV00278	History data was not purged
Explanation	Historical data was not purged.
Action	This message is for information only.
REV00279	History data not found
Explanation	Historical data was not found.
Action	This message is for information only.

REV00280	Available storage in thread insufficient
Explanation	The available storage in the thread is insufficient.
Action	Contact your Software AG technical support representative.
REV00281	An invalid request or an invalid FQE was found
Explanation	An invalid request or an invalid free queue element (FQE) was found.
Action	Contact your Software AG technical support representative.
REV00282	No response time report definition was specified
Explanation	No response time report definition was specified.
Action	Contact your Software AG technical support representative.
REV00283	Report definition has been purged
Explanation	Report definition has been purged.
Action	This message is for information only.
REV00284	Report definition was not purged
Explanation	Report definition was not purged.
Action	This message is for information only.
REV00285	Invalid device type for download
Explanation	An attempt was made to download a report but the Natural session is not in PC mode.
Action	If the device is a PC using Entire Connection, set your Natural session to PC mode by entering %+ on the command line, and reenter the DL command.
REV00286	Duplicate order numbers
Explanation	More than one field has the same order number on the Edit Report screen.
Action	Make each order number unique.
REV00288	Report is not active
Explanation	An attempt was made to perform a function on a started report, but no started report with the specified report name was found.
Action	This message is for information only.

REV00289	LOG command not allowed while viewing data
Explanation	An attempt was made to issue the LOG command while viewing a report.
Action	Stop viewing the report and reissue the LOG command.
REV00290	Adabas Review logging status changed
Explanation	The Adabas Review dynamic logging options have been updated.
Action	This message is for information only.
REV00291	Error returned during LOG request - {nnnn}
Explanation	The LOG command was issued and an error occurred during processing. nnnn = the response code associated with the error.
Action	Follow the Adabas or Natural procedures for error correction.
REV00292	Review not installed on database
Explanation	While attempting to view the buffer pool display, Adabas determined that Adabas Review was not installed on that database and issued a response code.
Action	This message is for information only.
REV00293	Function restarted due to Adabas rsp code 9
Explanation	An Adabas Review function was restarted from the beginning because an Adabas response code 9 (ADARSP009) was received.
Action	This message is for information only.
REV00294	NM component not installed
Explanation	An attempt was made to enter Adabas Review NM, but the NM component was not on the installation media.
Action	Determine whether the NM component was actually purchased. If it was purchased, then you may have inadvertently received the wrong Adabas Review installation media. Contact your Software AG representative.
REV00295	Select a history report
Explanation	An attempt was made to view a list of dates and times of history records for a response time report without specifying the name of the report.
Action	Specify the response time name.

REV00296	TID must be between 1 and 65,535
Explanation	The terminal ID (TID) must be between 1 and 65,535.
Action	Enter a valid TID number.
REV00297	Invalid TID specified
Explanation	An invalid terminal ID (TID) was specified.
Action	Enter a valid TID number.
REV00299	Function has been discontinued
Explanation	The current version of Adabas Review no longer supports the requested function.
Action	Refer to the <i>Adabas Review User</i> documentation for a list of available features and functions.
REV00300	Report not on file
Explanation	The requested report definition could not be found in the Adabas Review data file.
Action	This message is for information only.
REV00301	No OP summary information available
Explanation	No OP summary information was available for the report specified.
Action	This message is for information only.
REV00306	First field cannot be a buffer segment
Explanation	A DB report was defined with the first field as a buffer segment (FBSEG01, RBSEG01 ETC). The first field cannot be a buffer segment.
Action	Make another field the first field.
REV00307	No resident PGMLIB defined
Explanation	A request was made to view a list of programs in the resident program library buffer, but none were defined to Com-plete.
Action	This message is for information only.

REV00308	No resident programs defined
Explanation	A request was made to view a list of programs in the resident programs, but none where defined to Com-plete.
Action	This message is for information only.
REV00309	Unable to locate Adabas IDTH
Explanation	Adabas Review was unable to locate the Adabas IDT header.
Action	Contact your Software AG technical support representative.
REV00310	Unable to load ADALDI
Explanation	Adabas Review was unable to load the ADALDI text module from the Adabas TXTLIB.
Action	Verify that the Adabas TXTLIB is accessible from your z/VM machine.
REV00311	Database {dbid} has been ignored
Explanation	The specified database has been ignored because an entry for the DBID was found in the IGNORE table in program N-IGNORE. No STATUS information is returned for this database.
Action	If STATUS information for the database should be returned, edit and STOW the program N-IGNORE.
REV00312	Insufficient storage to reset stopwatch
Explanation	An attempt to reset the stopwatch was unsuccessful due to insufficient storage.
Action	Try again later.
REV00313	Only 'ON' and 'OFF' are valid values
Explanation	A value other than ON or OFF was entered.
Action	Enter ON or OFF.
REV00314	Command log data set switched
Explanation	The command log data set was switched successfully.
Action	This message is for information only.

REV00315	Command logging is not active for report
Explanation	Adabas Review command logging is not active for the specified report.
Action	Choose a report that has command logging.
REV00316	Invalid subpool ID
Explanation	The subpool ID specified was invalid.
Action	Select a valid subpool.
REV00317	There are no transaction summary records
Explanation	A Response Time Report was requested but no transaction summary records exist for the selected report.
Action	This message is for information only.
REV00318	There are no OP summary records
Explanation	A Response Time Report was requested but no OP summary records exist for the selected report.
Action	This message is for information only.
REV00319	Too many "AND" fields in selection criteria
Explanation	The AND fields in the selection criteria have resulted in a data string that is too long for Adabas Review to process.
Action	Reduce the number of AND statements and resave the report.
REV00320	Too many "OR" fields in selection criteria
Explanation	The OR fields in the selection criteria have resulted in a data string that is too long for Adabas Review to process.
Action	Reduce the number of OR statements and resave the report.
REV00321	Target SVC cannot be greater than 255
Explanation	A value larger than allowed was entered in the SVC field of the target definition. The maximum value for this field is 255.
Action	Enter the correct SVC number.

REV00322	User has already been canceled
Explanation	The user specified in the cancel function has already been canceled.
Action	This message is for information only.
REV00323	TID {terminal-id} canceled
Explanation	The specified terminal ID has been canceled.
Action	This message is for information only.
REV00325	TERMINAL {terminal-name} canceled
Explanation	The specified terminal has been canceled.
Action	This message is for information only.
REV00326	TID {terminal-id} not found
Explanation	The terminal ID specified in the cancel, pick, or force function could not be found.
Action	This message is for information only.
REV00327	User {user-id} not found
Explanation	The user specified in the cancel, pick, or force function could not be found.
Action	This message is for information only.
REV00328	Terminal {terminal-name} not found
Explanation	The terminal name specified in the cancel, pick, or force function could not be found.
Action	This message is for information only.
REV00329	Invalid TID specified
Explanation	The terminal ID number specified in the cancel, pick, or force function was not a valid numeric value.
Action	This message is for information only.
REV00330	Response time report - {report-name} STARTED
Explanation	The specified Adabas Review response time report was successfully autostarted.
Action	This message is for information only.

REV00331	No autostarted reports found to start
Explanation	No Adabas Review Response Time reports were found to autostart.
Action	This message is for information only.
REV00332	One report has been autostarted
Explanation	Adabas Review has started one autostarted response time report.
Action	This message is for information only.
REV00333	{count} reports have been autostarted
Explanation	Adabas Review started the specified number of autostarted response time reports.
Action	This message is for information only.
REV00334	History task recovery from Adabas time-out
Explanation	The Adabas Review history interval task successfully recovered from an Adabas timeout (response code 9, ADARSP009).
Action	This message is for information only.
REV00335	RNMH history task initializing in Natural
Explanation	The Adabas Review history interval task successfully invoked Natural and is initializing.
Action	This message is for information only.
REV00336	History task terminating. Unable to locate RNMTAB
Explanation	The Adabas Review history interval task terminated because it was unable to locate RNMTAB.
Action	Check that RNMTAB has been defined to CICS as a resident PPT entry, and that RNMTAB is available to CICS.
REV00337	History task terminating. Unable to load {module-id}
Explanation	The Adabas Review history interval task terminated because it was unable to locate the RNMCIICS.
Action	Check that RNMCIICS has been defined to CICS as a PPT entry and that RNMCIICS is available to CICS.

REV00338	History task terminating. Natural error {error-number} detected during initialization
Explanation	The Adabas Review history interval task terminated because it encountered a Natural error during initialization.
Action	Investigate the Natural error indicated, correct the problem, and restart the history subsystem.
REV00339	History task terminating. NM data file has not been initialized
Explanation	The Adabas Review history interval task terminated because it detected that the Adabas Review Natural Monitor data file was not initialized.
Action	Verify that the INSTALL program has been executed to initialize the Adabas Review Natural Monitor data file.
REV00340	History task terminating. Non-recoverable Natural error detected
Explanation	The Adabas Review history interval task terminated because it encountered an error in Natural from which it could not recover.
Action	Investigate the Natural error indicated, correct the problem, and restart the history subsystem.
REV00341	History task terminating normally
Explanation	The Adabas Review history interval task terminated normally.
Action	This message is for information only.
REV00342	History task terminating. Maximum reinitialization counter exceeded
Explanation	The Adabas Review history interval task terminated because the counter for maximum reinitializations was exceeded.
Action	Check messages sent to Adabas Review prior to this message to determine why the history task has reinitialized so many times.
REV00343	History task terminating
Explanation	The Adabas Review history interval task terminated.
Action	Check other Adabas Review messages issued prior to this message to determine if an error condition was encountered.

REV00344	TID {terminal-id} canceled by {user-id} at terminal {terminal-name}
Explanation	The user with the specified terminal ID was canceled by another user at another terminal.
Action	This message is for information only.
REV00345	User {user-id} canceled by {user-id} at terminal {terminal-name}
Explanation	The user with the specified user ID was canceled by another user at another terminal.
Action	This message is for information only.
REV00346	Terminal {terminal-name} canceled by {user-id} at terminal {terminal-name}
Explanation	The terminal with the specified name was canceled by another user at another terminal.
Action	This message is for information only.
REV00347	TID {terminal-id} forced
Explanation	The user with the specified terminal ID was forced.
Action	This message is for information only.
REV00348	User {user-id} forced
Explanation	The user with the specified user ID was forced.
Action	This message is for information only.
REV00349	Terminal {terminal-name} forced
Explanation	The terminal with the specified name was forced.
Action	This message is for information only.
REV00350	TID {terminal-id} forced by {user-id} at terminal {terminal-name}
Explanation	The user with the specified terminal ID was forced by another user at another terminal.
Action	This message is for information only.
REV00351	User {user-id} forced by {user-id} at terminal {terminal-name}
Explanation	The user with the specified user ID was forced by another user at another terminal.
Action	This message is for information only.

REV00352	Terminal {terminal-name} forced by {user-id} at terminal {terminal-name}
Explanation	The terminal with the specified name was forced by another user at another terminal.
Action	This message is for information only.
REV00353	User must be canceled before force
Explanation	A CANCEL command must be issued for a user before a FORCE command can be issued.
Action	This message is for information only.
REV00354	Invalid autostart option
Explanation	An invalid response time report autostart option was specified. The value must be "Y" or "N".
Action	Specify valid value.
REV00355	Invalid history refresh option
Explanation	An invalid response time report history refresh option was specified. The value must be "Y" or "N".
Action	Specify a valid value.
REV00356	Value must be in range {range-start} through {range-end}
Explanation	The value specified is invalid for the field. Valid values are denoted by <range-start> through <range-end> in the message.
Action	Specify a valid value in the range specified.
REV00357	History task terminating. Review NM incorrectly installed
Explanation	The Adabas Review history interval task terminated because it was unable to verify that the Adabas Review Natural Monitor code was correctly linked with the Natural nucleus.
Action	Verify that the Adabas Review NM code is correctly linked with the Natural nucleus.
REV00359	Report definition has been copied
Explanation	The request to copy a report definition was successful.
Action	This message is for information only.

REV00360	Review repository not available
Explanation	An Adabas response code 148 (ADARSP148) was received while trying to store information in an Adabas Review repository.
Action	Insure that the database ID and file number are correct and that the database is available.
REV00361	Database {dbid} inactive or invalid. Type 'TECH' for reason
Explanation	The user attempted to perform an Adabas Review function against a database that was inactive, did not have Adabas Review installed, or was not running a compatible version of Adabas Review.
Action	From the Database System menu, type TECH to determine why the current Adabas Review database is invalid and correct the error.
REV00362	Review is not installed in database {dbid}
Explanation	Using the DBID= command, the user attempted to change the Adabas Review database being accessed. The database selected did not have Adabas Review installed.
Action	Verify that the database specified in the DBID= command is a valid Adabas Review database.
REV00363	Database {dbid} is not active
Explanation	Using the DBID= command, the user attempted to change the Adabas Review database being accessed. The database selected was not active (Adabas response code 148, ADARSP148).
Action	Verify that the database specified in the DBID= command is a valid Adabas Review database and that it is active.
REV00364	Database {dbid} is below Review V3.4
Explanation	Using the DBID= command, the user attempted to change the Adabas Review database being accessed. The database selected has an invalid version of Adabas Review installed.
Action	Verify that the database specified in the DBID= command is a valid Adabas Review database.
REV00365	Response code {rsp} received accessing DBID {dbid}
Explanation	Using the DBID= command, the user attempted to change the Adabas Review database being accessed. The user received the indicated response code.
Action	Verify that the database specified in the DBID= command is a valid Adabas Review database.

REV00366	TECH command only available from the DB system main menu
Explanation	The user attempted to executed the TECH command from an Adabas Review panel other than the Database System menu. The Adabas Review TECH command is only executable from the Database System menu.
Action	Execute the TECH command from the Database System menu.
REV00367	Display program does not match report
Explanation	A VIEW or VW command terminated because the display program invoked was generated for a different report.
Action	Regenerate the display program for the report that failed using the RG function of the List Reports screen.
REV00368	Parentheses are required for a list or range
Explanation	A list or range of values was entered without parentheses into a processing rule.
Action	Include the values within parentheses.
REV00369	Unpaired parentheses
Explanation	The number of opening and closing parentheses are unequal.
Action	Include a closing parentheses for each opening parentheses.
REV00370	Invalid HELP command
Explanation	An invalid command was entered into the command line of a help screen.
Action	Enter a valid command or press a valid PF key.
REV00371	GENAUTO is not available in CMS
Explanation	A GENAUTO (or GA) command was entered but is not implemented in z/VM.
Action	This message is for information only.
REV00372	Download is invalid from this screen
Explanation	DOWNLOAD (or DL) was entered from a screen where the DOWNLOAD command is invalid.
Action	Enter DL into the SEL column of the List Started Reports screen.

REV00373	MAX K must be at least {n} K
Explanation	The MAX K value specified in the report options must be at least 4K for z/OS and z/VSE and at least 8K for BS2000.
Action	Specify a value for MAX K that is at least the minimum.
REV00374	WRAPPING=Y only allowed on sequence reports
Explanation	The WRAPPING value can only be set to "Y" for a SUMMARY report with SEQUENCE as the first display field.
Action	Only specify WRAPPING=Y for SUMMARY reports with SEQUENCE as the first field.
REV00375	Invalid page size - must be 1-255
Explanation	The page size entered on the Report Options screen is invalid. The value must be between 1 and 255.
Action	Enter a valid page size.
REV00385	Value must be greater than 0.
Explanation	The value must be greater than 0.
Action	This message is for information only.
REV00386	FNR must be between 1 and 254
Explanation	An attempt was made to change the FNR number to less than 1 or greater than 254.
Action	Enter a FNR number in the range of 1 to 254.
REV00388	Invalid line size - must be 72-255
Explanation	The line size entered on the Report Options screen is invalid. The value must be between 72 and 255.
Action	Enter a valid line size.
REV00390	List not sorted due to excessive report data
Explanation	The expanded list of history report occurrences could not be sorted because the resulting ISN list was too large. The list is displayed unsorted.
Action	Increase the value in the LS ADARUN parameter.

REV00391	History report compression complete
Explanation	The request to compress a history report completed successfully.
Action	This message is for information only.
REV00392	File is in use by another compression process
Explanation	An attempt was made to compress a history report but another report was being compressed at the time. This message can also occur if a CH function did not complete successfully.
Action	If another report is being compressed, wait until it completes and try again. If a CH function failed, you must run the RESET function. To run the RESET function: <ol style="list-style-type: none">1. Enter RESET HISTORY FILE on the command line of the DB System menu.2. Follow the instructions on the screen.
REV00393	Compression will not be performed
Explanation	A reply of "N" was given in response to the confirmation prompt prior to compressing a history report.
Action	This message is for information only.
REV00394	History file does not need resetting
Explanation	A request to reset the history file was made but the file does not need resetting.
Action	This message is for information only.
REV00395	History file has been reset
Explanation	This confirms that the history file has been reset. This essentially unlocks the lock that was placed on the file during a CH function.
Action	None if the message says HISTORY FILE HAS BEEN RESET. If the message also says DATA WAS LOST, restore the history file to a state prior to when the failing CH function was performed.
REV00396	Duplicate field in "AND" expression
Explanation	A logical "AND" expression contains a duplicate field name in a processing rule. When using "AND" to connect fields, each field name can be used only once per expression.
Action	Remove the duplicate field name from the expression.

REV00397	Target DBID has been changed
Explanation	The target DBID has been successfully changed for the report definition.
Action	This message is for information only.
REV00398	Bufferpool reports cannot be printed or downloaded
Explanation	The graphical bufferpool reports cannot be downloaded or printed: they may only be viewed.
Action	Use the VW command to view the report.
REV00399	AA is not available in VM/CMS
Explanation	The AA function is not available in z/VM.
Action	This message is for information only.
REV00400	Non zero response from target ={ nnn}
Explanation	A non-zero response code was returned from the specified target.
Action	Determine why the non-zero response code occurred.
REV00401	Report defaults were saved
Explanation	The report defaults were saved successfully.
Action	No action is required for this informational message.
REV00402	No matching reports to generate
Explanation	GENAUTO was started in local mode, but there are no autostarted reports with DBID-TO-MONITOR set to the local DBID. No autostarted reports will be generated.
Action	No action is required for this informational message.
REV00403	Update completed
Explanation	The report options were updated successfully.
Action	No action is required for this informational message.
REV00404	No changes to update
Explanation	A request to update reports was unnecessary because no changes were made.
Action	No action is required for this informational message.

REV00405	Cannot start a rpt that monitors a hub
Explanation	A request to start a report was unsuccessful because the DBID-TO-MONITOR was set to the Adabas Review hub ID. Adabas Review reports can only monitor Adabas targets.
Action	Correct the report and retry.
REV00406	Only one buffer segment allowed per report
Explanation	More than one buffer segment was defined in a report. Only one buffer segment per report is allowed.
Action	Correct the report and retry.
REV00407	There are no history records to convert
Explanation	An attempt was made to convert history records, but there are no history records to convert.
Action	No action is required for this informational message.
REV00408	Only 1 order field allowed with sum exit
Explanation	A summary exit was specified, but more than one order field was chosen for the report. Summary exit reports are limited to one (1) order field.
Action	Reduce the number of order fields to 1.
REV00409	Pulse report cannot be purged
Explanation	A request was made to purge the Pulse report. The Pulse report cannot be purged.
Action	No action is required for this informational message.
REV00410	Report defaults not saved
Explanation	A user canceled a prompt to confirm the saving of report defaults.
Action	No action is required for this informational message.
REV00411	{xxxxxxx} cannot be edited
Explanation	The EP command was used to edit a display program, but the display program is for a fixed format report. Since these programs are specific, not dynamic, no source code is available to the user.
Action	No action is required for this informational message.

REV00412	NUCID {nnnnn} is not available
Explanation	An attempt was made to change the nucleus ID with which Adabas Review communicates, but the requested nucleus ID was not available.
Action	Enter the NUC LIST command to obtain a list of available nucleus IDs and try again.
REV00413	NUCID only valid for cluster databases
Explanation	A user executed the NUCID or NUC LIST command for a non-cluster database.
Action	No action is required for this informational message.
REV00414	Duplicate field names not allowed
Explanation	Two or more fields with the same name were entered on the ER screen. This is not allowed.
Action	Remove the duplicate fields.
REV00415	Detail printer not available
Explanation	A request to start a detail report failed because there was no detail printer available.
Action	Delete another detail report first or provide more printers in the startup JCL. Then try again.
REV00416	Invalid data in rules value
Explanation	An invalid character was entered into a processing rules value.
Action	Remove the invalid character from the rules value and try again.
REV00417	Pulse interval must not be greater than 1440
Explanation	The pulse interval was incorrectly specified for a Pulse report.
Action	Specify a value between 1 and 1440 and try again.
REV00418	Display program is not delivered in source form
Explanation	An attempt to edit the display program BUFFPOOL, PU-00001 or CS-00001 failed because it is not delivered as source.
Action	No action is required for this informational message.

REV00419	List size exceeded
Explanation	The maximum list size of 10 has been exceeded in a processing rule.
Action	Limit the list size to 10 and try again.
REV00420	Unable to obtain SVC list
Explanation	An AA command was issued, but the list of SVCs cannot be accessed.
Action	Make certain that ADATMZ exists and is accessible from the current Adabas Review hub or database. Then try again.
REV00421	There are no targets for this SVC
Explanation	After an AA command, an SVC was selected, but there are not targets available for that SVC.
Action	No action is required for this informational message.
REV00422	Only order fields are allowed for detailed reports
Explanation	SUM, MIN, MAX, AVG, or ROUND were selected on the Edit Reports screen, but the report is a detailed report. ORDER is the only valid entry for a detailed report.
Action	Remove the invalid entries and try again.
REV00423	Report type changed -- defaults were reset
Explanation	While editing a report, the detail/summary report type was changed. Each report type requires its own set of default report options. The default report options for the new report type have now been loaded.
Action	No action is required for this informational message. Press PF2 to make any necessary changes to the report options.
REV00424	Unable to retrieve data from target {nnnnn}
Explanation	For reasons unknown to Adabas Review, the requested target was unable to supply AA information.
Action	No action is required for this informational message.
REV00425	Parameter input is missing or invalid
Explanation	The expected parameter input was either missing or has invalid data.
Action	Correct the input data and try again.

REV00426	Value for {keyword} is missing or invalid.
Explanation	The parameter input for a keyword was either missing or has invalid data.
Action	Correct the keyword input and try again.
REV00427	{TARGET DBID FILE} is not available
Explanation	The parameter input for a SET command keyword refers to an unavailable destination.
Action	Correct the keyword data or make sure the destination is available.
REV00428	{TARGET ID DBID FILE} has been set to {nnnnn}
Explanation	A SET command changed the target ID, database ID, or file successfully.
Action	No action is required for this informational message.
REV00429	SET program has terminated with errors
Explanation	The SET program encountered errors. The error will have been more clearly identified in a previous message.
Action	Correct the error and try again.
REV00430	More than 256 target definitions on file
Explanation	The maximum number of target definitions has been exceeded.
Action	Limit the number of targets to 256.
REV00431	Cannot save report due to error
Explanation	An attempt to save a report was unsuccessful because there was an error in the report definition.
Action	Correct the report definition and try again.
REV00432	There are no REVIEW hubs running on SVC {nnn}
Explanation	The AH (Available Review Hubs) command was entered but there are no hubs running in the current SVC to display.
Action	No action is required for this informational message.

REV00433 ADATMZ cannot be loaded

Explanation Upon initialization, SYSREVDDB calls a program named ADATMZ. This program was not available.

Action Make certain ADATMZ is installed and available to SYSREVDDB. If you are running Adabas Review in a CICS environment, verify that ACITMZ is installed. For more information, read the Adabas Review installation documentation.

If the problem persists, contact your Software AG technical support representative.

REV00434 ADATMZ: {message-text}

Explanation Upon initialization, SYSREVDDB calls a program named ADATMZ. One of the following messages (*message-text*) is included in the message and describes the error that has occurred with ADATMZ.

Message Text	Explanation	Action
No Adabas SVCs found	An internal error has occurred.	Contact your Software AG technical support representative for assistance.
No active targets for an SVC		
IDTHE appears to be invalid		
Invalid or unknown function		
Caller has answer area no answer count		
GETMAIN for SVC table failed		
GETMAIN for target table failed		
Load of link routine failed	ADATMZ dynamically loads ADALNKR. If ADALNKR cannot be loaded, subsequent calls to ADATMZ can cause this problem.	Be sure that the ADATMZ and ADALNKR modules, which are available in the Adabas or WAL load libraries, are all available for the TP monitor.
Load of CCSTCK routine failed	ADATMZ dynamically loads CCSTCK. If CCSTCK cannot be loaded, subsequent calls to ADATMZ can cause this problem.	Be sure that the ADATMZ and CCSTCK modules, which are available in the Adabas or WAL load libraries, are all available for the TP monitor.
Initialization call to DEPRTR failed	An internal error has occurred.	Contact your Software AG technical support representative for assistance.
No SVC table address provided by caller		
SVC table address inconsistent with PAL		

Message Text	Explanation	Action
No SVC count provided by caller		
Invalid SVC number too low	The version of ADATMZ that was loaded is too low.	Install the current version of ADATMZ. Contact your Software AG technical support representative for assistance.
Invalid SVC number too high	The version of ADATMZ that was loaded is too high.	Install the current version of ADATMZ. Contact your Software AG technical support representative for assistance.
No SVC <i>tbladdr</i> on get target call	An internal error has occurred.	Contact your Software AG technical support representative for assistance.
No target <i>tbladdr</i> on get target call		
No target table length		

REV00435

Buffer Pool reports cannot have DBID=ALL

Explanation

A value of "ALL" was specified as the DBID to monitor while attempting to start a report. Buffer Pool reports must only collect data from a single database, specifying "ALL" for them is not allowed. The report will not be started.

Action

Specify a numeric DBID for the Buffer Pool report.

REV00436

Invalid field for client report

Explanation

A reporting field was referenced in a client report that was not valid for client reports. Client reports have a restricted set of available fields. A complete list of these fields is provided in ????

Action

Specify a valid field name.

REV00437

The maximum number of fields has been selected

Explanation

While selecting fields for a report using the online field selection screens, the maximum allowable number of fields you can select has been reached. All fields selected beyond the maximum are ignored.

Action

Specify fewer fields, ensuring that only the most important fields are selected.

REV00438	Invalid field for a database report
Explanation	A client reporting field was referenced in a database report. This field is only permitted in a client report.
Action	Specify a valid field name.
REV00439	Warning: A client report has been started. If client monitoring is not turned on, no client monitoring will be collected. Press ENTER to exit
Explanation	This message appears in a pop-up box whenever a client report is started. It warns you that if client reporting has not been started, no client reporting data will be collected.
Action	No action is required for this informational message. Press the ENTER key to remove the pop-up box containing the message.
REV00440	Redisplay buffer full - Redisplay unavailable
Explanation	The Redisplay function is unavailable because more than 5000 lines were displayed.
Action	As a workaround, the report data can be printed using the HC command and other tools might be used to scroll through that output.
REV00441	Report name cannot be 'ALL'
Explanation	The name "ALL" was used as a report name in the report definition editor. The word "ALL" is reserved in Adabas Review and cannot be used as a report name.
Action	Specify a different name.
REV00442	The display program has not been generated yet
Explanation	An attempt was made to edit the display program for a report but the display program has not yet been generated. This is most likely due to having copied a report where the display program name shows as "NEED RG" or "NEED RU".
Action	Enter RG or RU on the command line to generate the display program.
REV00443	Userid is required
Explanation	User profiles require a unique user or group ID in the User ID / Group ID field. You cannot create a user profile without one.
Action	Specify a valid user or group ID for the user profile. Valid user or group IDs are eight alphanumeric characters long and begin with either a letter or a national (\$, @, or #) character.

REV00444	Group must be "Y" or "N"
Explanation	The setting for the Group access rule in the user profile definition is not "Y" (yes) or "N" (no). These are the only valid values for the field.
Action	Specify either "Y" or "N" for the Group access rule.
REV00445	Description is required
Explanation	User profiles require a description in the Description field.
Action	Specify up to 20 alphanumeric characters for the description.
REV00446	At least one report type must be "Y" for "EDIT REPORTS=Y"
Explanation	When the Edit Reports? access rule in a profile is set to "Y", at least one of the other edit report access rules must also be set to "Y". The other edit report access rules are Edit Bufferpool Reports? , Edit Client Reports? , Edit Cluster Reports? , Edit Database Reports? , and Edit Pulse Reports? .
Action	Either set the Edit Reports? access rule to "N" or specify "Y" for one of the other edit report access rules.
REV00447	All report types must be "N" for "EDIT REPORTS=N"
Explanation	When the Edit Reports? access rule in a profile is set to "N", none of the other edit report access rules may be set to "Y". The other edit report access rules are Edit Bufferpool Reports? , Edit Client Reports? , Edit Cluster Reports? , Edit Database Reports? , and Edit Pulse Reports? .
Action	Either set the Edit Reports? access rule to "Y" or specify "N" for all of the other edit report access rules.
REV00448	Cannot save - This is the only Administrator profile
Explanation	An attempt has been made to alter and save the only administrator profile so that it is no longer an administrator profile. Adabas Review will not allow you to turn the default profile or any administrator profile into a non-administrator profile if another administrator profile is not available.
Action	If you intend to change the only administrator profile to a non-administrator profile, first create another administrator profile. You can then alter and save the original administrator profile as you wish.

- REV00449** **Cannot purge - This is the only administrator profile**
Explanation An attempt has been made to delete the only administrator profile so that there is no longer an administrator profile. Adabas Review will not allow you to delete an administrator profile if another administrator profile is not available.
Action If you intend to delete this administrator profile, first create another administrator profile. You can then delete the original administrator profile.
- REV00450** **Monitor DBID {dbid} prohibited by profile**
Explanation An attempt has been made to create, start or alter a report for a DBID that is not included in the DBID list of your user profile.
Action Contact your system administrator to change your user profile or change the DBID you are trying to monitor in the report.
- REV00451** **User profiling is already installed**
Explanation An attempt was made to install the user profiling system when it is already installed.
Action No action is necessary for this informational message.
- REV00453** **You must enter at least one DBID**
Explanation When editing an Adabas Review user profile, the option **Monitor All Targets?** was set to "N", however, a DBID was not specified. At least one DBID must be specified if this option is set to "N".
Action Specify at least one DBID or set **Monitor All Targets?** to "Y".
- REV0454** **Profile reset to default values**
Explanation All values for the user profile you are viewing have been reset to the factory values.
Action No action is required for this informational message.
- REV00455** **Group must be 'Y' or 'N'**
Explanation An invalid or blank value was entered in the **Group Profile?** option of the user profile. This option must be set to either "Y" or "N".
Action Specify a valid value for the **Group Profile?** option.

REV00456	Info: Both "ALL TARGETS" and specific DBIDs are defined
Explanation	The user profile option Monitor All Targets? was set to Y but there are DBIDs listed. This is perfectly valid; in this case, the listed DBIDs have no effect on processing. However, if you later set the option to "N", the listed DBIDs will become the only valid DBIDs for the user.
Action	No action is necessary for this informational message.
REV00457	Invalid user ID
Explanation	The user ID entered on the user profile screen is invalid. User IDs must begin with a letter followed by any combination of alphanumeric or national (@#\$) characters.
Action	Specify a valid user ID.
REV00458	Review Client engine status has been turned {ON OFF}
Explanation	The Review Client status was toggled either on or off, as shown in the message.
Action	No action is required for this informational message.
REV00459	Review exit 2 is not installed
Explanation	While using the CM function, a call to communicate with client monitoring has determined that REVEXIT2 is not properly installed.
Action	Verify that the installation of REVEXIT2 has been performed correctly. For more information, refer to your Adabas Review (Phase 2) installation documentation.
REV00460	Review exit 2 is not active
Explanation	While using the CM function, a call to communicate with client monitoring has determined that REVEXIT2 is not active. It is possible to have REVEXIT2 linked into the link routine but not have it set to active in the LNKGBLS tables.
Action	Verify that the installation of REVEXIT2 has been performed correctly. For more information, refer to your Adabas Review (Phase 2) installation documentation.
REV00461	Response {nnn} received from REVEXIT2
Explanation	While using the CM function, a non-zero response code was returned from REVEXIT2. This is rare.
Action	Verify that the installation of REVEXIT2 has been performed correctly. For more information, refer to your Adabas Review (Phase 2) installation documentation. If you need additional assistance, contact your Software AG support representative.

REV00462	Ending apostrophe missing
Explanation	While editing the report processing rules for a report, an argument was specified with unpaired apostrophes.
Action	Correct the argument syntax and try again.
REV00463	Ending apostrophe incorrectly placed
Explanation	While editing the report processing rules for a report, an apostrophe was incorrectly used.
Action	Correct the syntax and try again.
REV00464	The maximum number of fields has been selected
Explanation	The maximum field limit has been reached. You cannot select any more fields.
Action	Evaluate the fields you have selected, removing ones you don't really need and adding ones you do, but be sure to stay within the maximum field limit.
REV00465	Unable to obtain SVC list
Explanation	While trying to use the AA function, the Adabas Review nucleus was unable to obtain the list of available SVCs on the current LPAR.
Action	Verify your Adabas Review installation is correct. If the problem persists, contact your Software AG support representative for assistance.
REV00466	Report option defaults converted successfully
Explanation	While editing a preexisting report after upgrading Adabas Review from version 4.4, the report defaults were converted to the current standard.
Action	No action is required for this informational message.
REV00467	Invalid character in field name
Explanation	While editing a report, an invalid character was used in one of the field names.
Action	Correct the field name syntax and try again.
REV00468	Cannot EC a non-client report
Explanation	An attempt was made to edit a non-client report using the EC command. The EC command only edits client reports.
Action	Use the ER command to edit a non-client report.

REV00469	Command line entries are not valid here
Explanation	When entering Adabas Review for the first time after upgrading from a previous version, a user profile conversion takes place. The only actions allowed are on the screen. Command line entries are not allowed for this special one-time event.
Action	Do not enter data on the command line while this conversion is taking place.
REV00470	NUCID only valid in local mode
Explanation	The NUCID command was used but SYSREVDDB is currently communicating with an Adabas Review hub. The NUCID command is only valid when SYSREVDDB is communicating with a local mode target.
Action	Do not use the NUCID command in hub mode.
REV00471	No NUCID was selected
Explanation	PF5 was pressed on a NUCID list screen but no NUCID was selected.
Action	Select a NUCID or use PF3 to exit the NUCID screen.
REV00472	NUCID has been changed
Explanation	Upon request, the NUCID was successfully changed.
Action	No action is required for this informational message.
REV00473	CM function only available in hub mode
Explanation	An attempt to turn on the client report engine using the CM command was made in local mode. The CM command is available only in hub mode.
Action	Operate Adabas Review in hub mode before attempting to start the client reporting engine.
REV00474	Parameter missing or invalid
Explanation	The required NAME parameter was omitted or invalid when using the batch Natural Review program COPYREP.
Action	Add or correct the parameter and rerun the job.
REV00475	Parameter is missing or invalid
Explanation	The required NEWNAME parameter was omitted or invalid when using the batch Natural Review program COPYREP.
Action	Add or correct the parameter and rerun the job.

- REV00476** **Invalid parameter specified**
Explanation When using a batch Natural Review program, an unknown or invalid parameter keyword was specified.
Action Correct the error and rerun the job.
- REV00477** **STACKPARAM= is incorrectly specified**
Explanation The optional STACKPARAM parameter was incorrectly specified when using the batch Natural Review program COPYREP.
Action Correct the error and rerun the job.
- REV00478** **NAME= and NEWNAME= parameters are required**
Explanation While using the batch Natural Review program COPYREP, both of the required parameters NAME= AND NEWNAME= were missing.
Action Supply the correct parameters and rerun the job.
- REV00479** **Undefined keyword in input**
Explanation When using the batch Natural Review program COPYREP, an unknown parameter keyword was specified. Valid keywords are NAME, NEWNAME, STACKPARAM and GO=YES.
Action Supply only valid parameters and rerun the job.
- REV00480** **Words in report names must be separated by periods**
Explanation While using a batch Natural Review program that requires a report name as input, the report name did not have periods between each word. This is required to allow Natural to pass the parameters to the Adabas Review program correctly.
Action Always place periods between words in report names. Correct the specification and rerun the job.
- REV00481** **Report already exists**
Explanation The new report name specified in the batch Natural Review program COPYREP already exists. COPYREP will not overwrite an existing report; instead it terminates with response code 12.
Action Specify a unique name for the new report name or delete the report definition that already exists.

REV00482	Report definition has been purged
Explanation	This message confirms that the request to purge a report definition was successful.
Action	No action is necessary for this informational message.
REV00483	GO= parameter is incorrectly specified
Explanation	The GO= parameter specified in the batch Natural Review program COPYREP is specified incorrectly. The only valid syntax for this parameter is GO=YES.
Action	Correct the error and rerun the job.
REV00484	INVALID COST OPERATOR
Explanation	An invalid cost operator was entered on the Edit Report screen. Valid cost operators are: <ul style="list-style-type: none">■ "+": Plus -- add the cost factor to the field value.■ "-": Minus -- subtract the cost factor from the field value.■ "*": Multiply -- multiply the field value by the cost factor.■ "@": Fixed -- apply a fixed cost to each command select by the report.
Action	Enter a valid cost operator if you want to use the cost feature.
REV00485	COST FACTOR REQUIRED IF OPERATOR IS PROVIDED
Explanation	A cost operator was entered on the Edit Report screen but no cost factor was provided. Both an operator and a cost factor must be specified to use the cost feature.
Action	Specify a cost factor for the field in addition to the operator or remove the cost operator from the field specification on the Edit Report screen.
REV00486	COST OPERATOR REQUIRED IF FACTOR IS PROVIDED
Explanation	A cost factor was entered on the Edit Report screen but no cost operator was provided. Both an operator and a cost factor must be specified to use the cost feature.
Action	Specify a cost operator for the field in addition to the cost factor or remove the cost factor from the field specification on the Edit Report screen.
REV00487	COST FACTOR MUST BE A POSITIVE VALUE
Explanation	A cost factor was provided on the Edit Report screen but the value is zero or negative. The values must be a positive or negative integer. Negative values can only be specified if the cost operator is "*" or "@".
Action	Specify a valid cost factor and try again.

- REV00488** **COST FACTOR IS NOT NUMERIC**
Explanation A cost factor was entered on the Edit Report screen that was not numeric. Only numeric values are valid.
Action Specify a numeric value for the cost factor.
- REV00489** **ERROR WHILE TRYING TO RECATALOG USER EXIT**
Explanation During the first invocation of Adabas Review after a new installation or upgrade, an error occurred compiling and cataloging a user exit. The reason for the error cannot be determined.
Action If the problem persists, examine and correct any user written exits. If no user exit has been written or modified, contact your Software AG technical support representative.
- REV00490** **COST FACTOR can only have 7 numeric digits**
Explanation A COST factor was entered on the Edit Report screen with eight numeric numbers and no decimal points. The maximum number of numeric digits is seven.
Action Enter a value with no more than seven numeric digits. You may place a decimal point anywhere in the field if desired.
- REV00491** **COST OPERATOR '@' CAN ONLY BE USED FOR THE 'COMMANDS' FIELD**
Explanation A COST factor was entered on the Edit Report screen for the field COMMANDS but the operator was not the "@" operator. The only operator allowed for the field COMMANDS is "@", indicating a FIXED cost. No other reporting field may use the "@" operator.
Action Either change the field name to something other than COMMANDS or change the Cost operator to "@" and try again.
- REV00492** **COST IS ONLY VALID FOR SUM FIELDS**
Explanation A COST factor was entered into the ER screen for a field that is not a summary field. If the field does not have the SUM slot checked then COST is not possible.
Action Correct the ER screen and try again.
- REV00493** **THIS FIELD IS NOT ALLOWED FOR DETAIL REPORTS**
Explanation A field was entered on the ER screen for a detail report that can only be used in a summary report.
Action Remove the offending field.

REV00494	TARGET NAME MUST NOT BE BLANK
Explanation	The Target Name field must contain an alpha-numeric value. The field must not be all blanks.
Action	Enter a valid Target Name.
REV00495	REVIEW COMMANDS MUST BE 'Y' OR 'N'
Explanation	The Review Commands fields must contain a "Y" or an "N". All other values, including blank are invalid.
Action	Enter "Y" or "N".
REV00496	INVALID SYNTAX IN START PARAMETERS
Explanation	The Review command START or ST was entered into the command line to start an online report. The parameter data following the START command contained invalid syntax.
Action	Correct the error and re-submit.
REV00497	DBID VALUE IS NOT VALID
Explanation	The Review command START or ST was entered along with a DBID parameter. The DBID parameter data contains invalid syntax.
Action	Correct the error and re-submit.
REV00498	DBID KEYWORD MUST BE FOLLOWED BY "="
Explanation	The Review command START or ST was entered along with a DBID keyword. The DBID keyword must be followed by an equal sign (=). The equal sign was either missing or was an incorrect character.
Action	Correct the error and re-submit.
REV00499	DBID KEYWORD MUST BE PRECEDED BY ","
Explanation	The Review command START or ST was entered along with a DBID keyword. The DBID keyword must be preceded by a comma. The comma was either missing or was an incorrect character.
Action	Correct the error and re-submit.

REV00500	INVALID NUCID
Explanation	In LOCAL mode within a cluster environment, an attempt was made to alter the current nucleus ID, but the value entered was not valid. Valid values are 1 through 65535. Only numeric characters are allowed.
Action	Re-enter the nucleus ID using a valid value.
REV00501	CHANGE DBID PARAMETER ERROR(S)
Explanation	During a CHANGE DBID FROM operation, one or more parameter values were incorrect.
Action	Re-enter the CHANGE DBID command using valid values.
REV00502	INVALID INPUT PARAMETER(S)
Explanation	During a CHANGE DBID FROM operation, one or more parameter values were incorrect.
Action	Re-enter the CHANGE DBID command using valid values.
REV00503	FROM DBID IS INVALID
Explanation	During a CHANGE DBID FROM operation, the FROM DBID value was not valid. Valid values are 1-65535, ALL or NONE.
Action	Re-enter the CHANGE DBID command using valid values.
REV00504	INVALID DBID VALUE
Explanation	During a CHANGE DBID FROM operation, one or more of the DBID values were not valid. Valid values are 1-65535, ALL or NONE.
Action	Re-enter the CHANGE DBID command using valid values.
REV00505	FROM AND TO DBID CANNOT BE THE SAME
Explanation	During a CHANGE DBID FROM operation, both DBID values were identical. The values must be different.
Action	Re-enter the CHANGE DBID command using valid values.
REV00506	NO DBID(S) WERE CHANGED
Explanation	During a CHANGE DBID FROM operation, no DBIDs were found that match the FROM value.
Action	No action is required for this informational message.

REV00507	1 DBID HAS BEEN UPDATED
Explanation	During a CHANGE DBID FROM operation, one DBID was found that matched the FROM value and was updated with the TO value.
Action	No action is required for this informational message.
REV00508	{nnn} DBIDS HAVE BEEN UPDATED
Explanation	During a CHANGE DBID FROM operation, multiple DBIDs were found that matched the FROM value and were updated with the TO value. <i>nnn</i> will show the number of reports updated.
Action	No action is required for this informational message.
REV00509	Invalid parameter for "ZIIP" command
Explanation	During a CHANGE DBID FROM operation, multiple DBIDs were found that matched the FROM value and were updated with the TO value.
Action	No action is required for this informational message.
REV00510	Review started with ZIIP=NO, zIIP disabled
Explanation	zIIP is installed, but Adabas Review was started with ZIIP=NO. The zIIP interface is disabled and cannot be turned on online, while Adabas Review is running.
Action	Start Adabas Review with ZIIP=YES.
REV00511	zIIP not installed
Explanation	An attempt to read the zIIP status returned a blank return character, indicating that zIIP is not installed.
Action	Install Adabas Review zIIP.
REV00512	Unkown data getting zIIP state: {X}
Explanation	An attempt to read the zIIP status returned an unkown return character for the zIIP state.
Action	Contact Software AG support.
REV00513	zIIP already switched on
Explanation	The command ZIIP=YES was issued, but zIIP is already active. zIIP state did not change.
Action	No action is required for this informational message.

REV00514	zIIP switched on
Explanation	The command ZIIP=YES was issued and zIIP was switched from inactive to active.
Action	No action is required for this informational message.
REV00515	Rsp=402, zIIP not supported
Explanation	An attempt was made to switch the zIIP state, but zIIP is not supported.
Action	Install Adabas Review zIIP.
REV00516	Unkown response code setting zIIP state: {nnn}
Explanation	An attempt was made to switch the zIIP state. But zIIP returned an unkown response code.
Action	Contact Software AG support.
REV00517	zIIP already switched off
Explanation	The command ZIIP=NO was issued, but zIIP is already inactive. zIIP state did not change.
Action	No action is required for this informational message.
REV00518	zIIP switched off
Explanation	The command ZIIP=NO was issued and zIIP was switched from active to inactive.
Action	No action is required for this informational message.
REV00519	Display of "ZIIP" statistics not allowed
Explanation	The display of zIIP statistics is disabled in the SYSREVDDB user profile settings.
Action	Enable zIIP statistics in the user profile.
REV00520	Use of "ZIIP YES/NO" command not allowed
Explanation	The use of the ZIIP YES/NO command is disabled in the SYSREVDDB user profile settings. ZIIP YES/NO changes the zIIP state (active/inactive).
Action	Enable ZIIP YES/NO command in the user profile.

REV00521	"ZIIP" command not allowed in User Profile System.
Explanation	An attempt was made to switch the zIIP state, but zIIP is not supported
Action	Issue the command outside the User Profile System.
REV00522	zIIP on Target must be Y(es) or N(o).
Explanation	The input value for the field "zIIP on Target" must be Y(es) or N(o). No means no zIIP clause will be generated in the parameters for autostarting. This equals to ZIIP=NO. Yes means ZIIP=YES will be generated.
Action	Enter correct value.
REV00523	Function "RG" not available for this report type.
Explanation	Display programs for Buffer Pool reports (BUFFPOOL) or for Pulse Reports (PU-00001) cannot be generated. They are delivered.
Action	If missing, move a backup copy to SYSREVDDB.
REV00524	No targets are available for this SVC.
Explanation	On the Active Adabas SVCs screen, an SVC was selected but the SVC has no target associated with it.
Action	No action is required for this informational message.
REV00525	Report and saved definition do not match; REFRESH/REGEN necessary.
Explanation	Before a VW/VX command is executed, the running report and the saved definition will be checked. This is done by comparing the Account Record Length. For a running report this value is returned from the IN command. For the saved definition this value is calculated. If the calculation is not possible, e.g. because a user-defined variable is missing, the check will be ignored and the VW/VX will be executed without check.
Action	Refresh the running report and/or regenerate the report and the display program with its original definition.
REV00526	In local mode the DBID to monitor may be the local DBID only.
Explanation	Adabas Review running in local mode can collect data on its local DBID only. Thus the DBID-to-be-monitored and the local DBID must be the same. Use the HUB mode to monitor several different DBIDs.
Action	Enter the local DBID or ALL as DBID-to-be-monitored and/or update the report definition.

- REV00527** **No NUCID found for TARGET {dbid}.**
- Explanation** An attempt to read NUCID(s) from a local DBID did not return any NUCID. Most probably the DBID is not a cluster. Or the Adabas call to read the NUCIDs failed.
- Action** Enter the correct local TARGET DBID or check the Adabas cluster environment.
-
- REV00528** **TARGET not initialized, set to default value {dbid}.**
- Explanation** The Adabas Review local or HUB TARGET *dbid* was not yet initialized, i.e. the value was 0. The TARGET has been set to the default value, derived from the REVIEW-DB *dbid* or the user profile.
- Action** No action required if the TARGET is the desired one. Otherwise set the TARGET in advance with the batch Natural SET command.

65

Adabas Review 20xxx Messages

REV20001

Error in parameters as follows

Explanation

An error was detected during the parameter processing phase of Adabas Review. All parameters are processed for further error diagnosis. However, no data is handled by the Adabas Review processor. This message is followed by one of the PRM nnn error messages shown below.

Message ID	Message Text	Explanation
PRM001	Invalid statement name format	The format of the statement name (the first item of the parameter statement) is not correct.
PRM002	Statement name must be followed by a blank	The basic syntax of the parameter statement requires a blank. The parameter processor cannot correctly identify the statement.
PRM003	Unidentified statement name	The parameter processor has located a statement name that is not valid.
PRM004	Invalid separator	A character other than a comma or an equal sign was used as a delimiter.
PRM007	Insufficient positional parameters defined	More positional parameters were entered than were allowed.
PRM008	Null value invalid for required parameter	Values must be provided for all required parameters.
PRM009	Unidentified keyword	An invalid keyword has been identified.
PRM010	List-format value not allowed	Only a single value may be specified for the parameter.
PRM011	Invalid hex digit	Hexadecimal digits must be 0-9 or A-F.
PRM012	Length exceeded	The parameter supplied is longer than allowed.

Message ID	Message Text	Explanation
PRM013	Unexpected end-of-file	The parameter statements terminated prematurely. The parameter processor was expecting more input.
PRM014	Premature end of hex value	A trailing quote was not supplied to terminate a hexadecimal value.
PRM015	Invalid continuation statement	A statement has not been continued properly.
PRM016	Premature end of statement	The current statement ended abnormally; a comma, parenthesis, or quote may be missing.
PRM017	Invalid character in numeric parameter value	Only the characters 0-9 are allowed in numeric fields.
PRM018	Excessive numeric value length	The numeric value is too large for the parameter.
PRM019	Invalid parameter value	The value specified is not allowed for this parameter.
PRM020	Numeric value too large for processing	The numeric value is too large for the parameter to be processed.
PRM021	Parameter value truncated	Some parameter values were lost due to truncation.
PRM022	List size exceeded	Too many entries have been specified in a list of values.
PRM023	Required parameter missing	A required parameter is missing; it must be provided before execution can proceed.
PRM024	Parameter mutually exclusive to one of the other parameters	A specified parameter is mutually exclusive with one of the other specified parameters; only one of the mutually-exclusive parameters may be specified.

Action Correct the error and resubmit the job.

REV20002 Invalid file-type

Explanation An invalid INPUT statement file-type parameter has been detected. Processing is discontinued.

Action Correct the error and resubmit the job.

REV20003	Invalid file-type
Explanation	An invalid INPUT statement file-type parameter has been detected. Processing is discontinued.
Action	Correct the error and resubmit the job.
REV20004	Prior REPORT statement missing
Explanation	A valid REPORT statement must precede all other parameter statements except the INPUT statement. Processing is discontinued.
Action	Define a valid REPORT statement and resubmit the job.
REV20005	Invalid printer line size
Explanation	The printer line size must be at least 72 positions and cannot exceed 255 positions. Processing is continued with the default size of 133.
Action	To avoid the usage of the default and this message, define a valid LINE SIZE statement and resubmit the job.
REV20007	Detail report exceeds line size
Explanation	The number of printable characters for the report exceeds the report line size.
Action	Increase the report line size if possible, or reduce the report data to be displayed.
REV20008	INVALID FIELD NAME IN DISPLAY STATEMENT <i>fieldname</i>
Explanation	The field <i>fieldname</i> is not allowed in a DISPLAY statement.
Action	The report will be started without this field. The field name is either spelled incorrectly, or the field is not allowed for this TYPE of CLASS of report.
REV20010	Invalid field name in SUM statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20011	Invalid field name in MINIMUM statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.

REV20012	Invalid field name in MAXIMUM statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20013	Invalid field name in AVERAGE statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20014	Invalid field name in PERCENT statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20015	Invalid field name in COST statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20016	Invalid field usage for MINIMUM statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20017	Invalid field usage for MAXIMUM statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.

REV20018	Invalid field usage for SUM statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20019	Invalid field usage for AVERAGE statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20020	Invalid field usage for COST statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20021	Invalid field usage for PERCENT statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20022	ACCOUNT statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports.
Action	The statement is ignored and processing continues. Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20023	SUM statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports.
Action	The statement is ignored and processing continues. Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20024	MINIMUM statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports.
Action	The statement is ignored and processing continues. Specify this statement following a valid REPORT statement with TYPE=SUMMARY.

REV20025	MAXIMUM statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports. The statement is ignored and processing continues.
Action	Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20026	AVERAGE statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports. The statement is ignored and processing continues.
Action	Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20027	PERCENT statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports. The statement is ignored and processing continues.
Action	Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20028	Applymod {nn} has been turned {ON OFF} by {user-id}
Explanation	The applymod <i>nn</i> has been turned ON/OFF by the user <i>user-id</i> .
Action	This message is for information only.
REV20029	Invalid COST value
Explanation	COST may be specified as field/operator/value, where valid operators are * (TIMES), + (PLUS), and - (MINUS). Fixed costs may be specified using the reserved word FIXED with an operator of @ (AT). Positive and negative values are allowed with or without a single imbedded decimal point.
Action	A value of 0 is assumed. Correct the value and resubmit the job.
REV20030	Invalid COPY file-type
Explanation	An invalid COPY statement file-type parameter was detected.
Action	The COPY statement is ignored and processing is continued. Correct the statement and resubmit the job if necessary.
REV20031	Termination task attached successfully
Explanation	Termination task attached successfully.
Action	This message is for information only.

REV20032	Termination task not found in the program library
Explanation	Termination task not found in the program library.
Action	Contact your Software AG technical support representative.
REV20033	I/O error occurred while loading termination task
Explanation	I/O error occurred while loading termination task.
Action	Contact your Software AG technical support representative.
REV20034	Sever parameter error(s)
Explanation	A parameter error of some significance was reported. All parameters are processed for further error diagnosis. However, the run is discontinued before any input data is processed.
Action	Correct the error and resubmit the job.
REV20035	Severe parameter error(s)
Explanation	A parameter error of some great significance has occurred. Parameter validation is terminated.
Action	Correct the error and resubmit the job.
REV20036	Report discontinued due to LIMIT parameter
Explanation	The report has been discontinued due to the LIMIT parameter. The LIMIT parameter on the report statement has been exceeded.
Action	This message is for information only.
REV20037	Summary report exceeds line size
Explanation	The number of printable characters for the report exceed the report line size.
Action	Increase the report line size if possible or reduce the report data to be displayed.
REV20038	Termination task initiated
Explanation	Termination task initiated.
Action	This message is for information only.

REV20039	Open operation failure on printer
Explanation	An error occurred attempting to open the above file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20040	Open operation failure on copy
Explanation	An error occurred attempting to open the copy file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20041	Open operation failure on log input
Explanation	An error occurred attempting to open the log input file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20042	Output error on printer
Explanation	An error occurred attempting to output to the printer file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20043	Output error on copy
Explanation	An error occurred attempting to output to the copy file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20044	Close operation failure on {file-name}
Explanation	An error occurred while Adabas Review attempted to close the specified file.
Action	This message is for information only.
REV20045	{YYYY-MM-DD hh:mm:ss} ADABAS RESPONSE CODE {rrr/sssss}
Explanation	A non-zero Adabas response code with subcode <i>sssss</i> has occurred during writing of the Adabas Review history file. In Review batch this was the result of the interaction with Adabas because of the COPY statement with FILETYPE=ADABAS.
Action	In the case of response 148, the history records will be stored on RVUALT file if this is specified in the Hub JCL. In the case of response 9, the Review Hub will do an OP command and re-execute the command.

In the case of any other response code, the data will not be written to the Review history file, but the processing of the report will continue. As long as the reason for the error is not repaired, the following write to the Review history file might end in the same error.

REV20046	Interval statistics task terminating
Explanation	Adabas Review detected that an EOJ command was issued to the Complete nucleus. Adabas Review terminates the interval task and starts the termination task.
Action	This message is for information only.
REV20047	Interval statistics task started
Explanation	The Adabas Review Interval Statistics task has been started.
Action	This message is for information only.
REV20048	No interval statistics record found
Explanation	Adabas Review unsuccessfully attempted to load the interval statistics record from its system file.
Action	Contact your Adabas Review administrator.
REV20049	{xxxxxxxxxxx} will be saved every {nnn} mins
Explanation	The Adabas Review interval statistics task will save the data from the function or subsystem xxxxxxxxxxxx every nnn minutes.
Action	This message is for information only.
REV20050	{nnnnnnnn} Task attached successfully
Explanation	The Adabas Review task nnnnnnnn was attached successfully.
Action	This message is for information only.
REV20051	No dummy TID available for use by {nnnnnnnn} task
Explanation	Adabas Review was unable to attach the nnnnnnnn task because no dummy TID was available for use by the attached program.
Action	If this problem happens frequently, the system programmer responsible for Complete maintenance should be requested to increase the value of the NOTIBS keyword argument in the TIBTAB definition.

REV20052	{nnnnnnnn} Task not found in the program library
Explanation	Adabas Review was unable to attach the <i>nnnnnnnn</i> task because the program to be attached was not found in the Com-plete program library data set.
Action	Request that the system programmer responsible for Com-plete catalog the program.
REV20053	CLASS=CLIENT only in hub mode allowed
Explanation	The CLASS parameter was invalidly set to "CLIENT" in Adabas Review local mode for automatically started reports. You can only set the CLASS parameter to "CLIENT" in hub mode.
	Adabas Review processing continues, but the report is treated as a non-client report.
Action	Remove the CLASS=CLIENT specification from the parameters in Adabas Review local mode.
REV20054	TARGET=0 not allowed
Explanation	This message is produced in the RVUPRT00 member as an error message when the target database ID is zero, blank, or unassigned in the REVUAUT1 or RVUAUT2 file. Blank or unassigned targets default to a value of zero. Targets of zero are not allowed in autostarted reports.
Action	Update the TARGET parameter setting with a valid database ID.
REV20055	Unknown return code from attach
Explanation	The Adabas Review master interval statistics task was unable to attach the interval task because it received an unknown return code.
Action	Contact your Software AG technical support representative.
REV20056	{xxxxxxxxxxxxxxx} Task incorrectly linked
Explanation	The Adabas Review task has detected that <ul style="list-style-type: none"> ■ the module U2DENQ was not linked in; or ■ the incorrect version of U2DENQ was linked in.
Action	Rerun the link job provided in the Adabas Review source library, ensuring that the JCL is correct.

REV20061	Master interval task already active
Explanation	An attempt was made to start the master interval statistics task but the task was already active.
Action	Do not attempt to start the master interval task.
REV20062	Termination task terminated
Explanation	The termination task has ended.
Action	This message is for information only.
REV20063	{error-type} Error {error-number} occurred on line {line-number} of program {program-name}
Explanation	An error has occurred while executing the specified program: error-type = Command Processing Logon Processing Object Time Non-correctable Syntax
Action	Record message and contact your Software AG technical support representative.
REV20101	History file population started
Explanation	The Adabas Review history file task has been started.
Action	This message is for information only.
REV20102	History file population completed
Explanation	The Adabas Review history file task has completed execution.
Action	This message is for information only.
REV20103	Adabas RSP = {rrr} SUB {sssss} received
Explanation	The Adabas Review history file task received a non-zero Adabas response code <i>rrr</i> with subcode <i>sssss</i> .
Action	Evaluate the severity of the response code and perform the required steps to resolve the problem.

REV20104	History task posted for work
Explanation	The Adabas Review history file task has posted for work. This means that a detailed report with a COPY statement with FILETYPE=ADABAS is active and has selected data to write out to the Adabas Review history file.
Action	This message is for information only.
REV20105	History task waiting for work
Explanation	The Adabas Review history file task is waiting for work.
Action	This message is for information only.
REV20106	History task error during FREEMAIN
Explanation	The Adabas Review history file task received a nonzero return code attempting to free storage.
Action	Contact your Software AG technical support representative.
REV20107	History task unable to open RVUALT
Explanation	An error has occurred while attempting to open the RVUALT file.
Action	Verify that the JCL is correct and that the RVUALT file is available.
REV20108	{dbid} Review suspended, buffer unavailable
Explanation	REVIEW local mode is experiencing a temporary buffer shortage. CLOG records cannot be sent to the sub task REVIEWB. They are skipped until message REV20109 indicates that buffers are again available.
Action	Try to find the reason of buffer shortage.
REV20109	{dbid} Review resumed, {nn} CLOG records skipped
Explanation	Buffers have become available after the shortage noted by message REV20108. The number of CLOG records skipped during the shortage is given in the message (<i>nn</i>).
Action	Try to find the reason of buffer shortage.
REV20110	Corrupted length arrived from Natural. Length truncated to 65535
Explanation	A corrupted length value arrived in the format buffer of a search buffer from Natural. The corrupted length value is truncated to 65535.
Action	Contact your Software AG technical support representative for assistance in resolving the problem.

REV20111	SVC number {nnn} is invalid
Explanation	An invalid SVC number was used (for example, in the history file definition). The Adabas call will not be executed.
Action	Specify a valid SVC number for the Adabas call.
REV20112	RAOSSORT internal error
Explanation	An internal error occurred in the Adabas Review sort routine RAOSSORT. The sum of offset and length for sorted data is too big. The sort request is not performed.
Action	Contact your Software AG technical support representative to obtain a fix for this error.
REV20113	Sort option SUMFIELD not permitted.
Explanation	The sort option, SUMFIELD, was specified for a report, but there are no summary fields in the report.
Action	Remove the SUMFIELD sort option from the report or specify summary fields for the report. Then try again.
REV20114	Sort option SUMFIELD not permitted Report name: {rptname}
Explanation	The sort option, SUMFIELD, was specified for a report, but there are no summary fields in the report.
Action	Remove the SUMFIELD sort option from the report or specify summary fields for the report. Then try again.
REV20115	Field {fn} does not fit into report {rrrr}
Explanation	The field listed in the message (fn) is a valid field name, but it does not fit into the printed report or history file, because the record length is not big enough. As a result, the field is empty in the report or history file. <i>rrrr</i> is the report name truncated to 29 characters.
Action	Omit this field or increase the record size.
REV20118	RVUAUT1 selected. RVUAUT2 selected.
Explanation	The user has to specify two data definition job control statements <pre>//RVUAUT1 DD ...</pre> or <pre>//RVUAUT2 DD ...</pre>

- Action** This message tells the user which statement is selected by Adabas Review.
 This message is for your information only.
- REV20119** **Catastrophic error, no registers available, check dump.**
Explanation An abend occurred, the REVIEW Estae got control, but the data were corrupted so completely that the ESTAE cannot continue its work.
Action This message is for your information only. Check the dump to find the error. Contact your Software AG technical support representative.
- REV20120** **Review {v.r.s} running with Adabas {n.n}**
Explanation Adabas Review has been given control for the first time where *v . r . s* is the Adabas Review version and *n . n* is the Adabas version.
Action This message is for information only.
- REV20121** **Attach for Review subtask failed**
Explanation Adabas Review attempted to attach an operating system subtask but received a nonzero return code from this action.
Action Examine the messages displayed by the operating system and correct the problem. The possibility exists that the address space, region, or partition was not large enough to attach the task, or the attached module RAOSRE VW was not in the library concatenations so it could not be found to be loaded.
- REV20122** **REV20122 - Adabas Review ESTAE exit driven.**
REV20122 - ADABAS REVIEW now disabled.
REV20122 - ABEND 000xx000 PSW xxxxxxxx xxxxxxxx
REV20122 - R0 xxxxxxxx - R1 xxxxxxxx - R2 xxxxxxxx - R3 xxxxxxxx
REV20122 - R4 xxxxxxxx - R5 xxxxxxxx - R6 xxxxxxxx - R7 xxxxxxxx
REV20122 - R8 xxxxxxxx - R9 xxxxxxxx - R10 xxxxxxxx - R11 xxxxxxxx
REV20122 - R12 xxxxxxxx - R13 xxxxxxxx - R14 xxxxxxxx - R15 xxxxxxxx
REV20122 - Dump has been taken.
Explanation The main task of Adabas Review had an abend. The REVIEW ESTAE got control and issued these messages and was forced to write a dump. The Adabas nucleus will continue working, but Review will be disabled.
Action This message is for your information only. Check the dump to find the error. Contact your Software AG technical support representative.

REV20123	ESTAE driven recursively.
Explanation	The REVIEW ESTAE is called a second time, although REVIEW should run disabled.
Action	This message is for your information only. Check the dump to find the error. Contact your Software AG technical support representative.
REV20124	Allocation for Review buffer pool failed
Explanation	Adabas Review unsuccessfully acquired storage for the Adabas Review buffer. The size of the buffer is determined by the BUFFMB parameter on the Adabas Review INPUT statement.
Action	Increase the size of the address space, region, partition, or virtual machine that Adabas Review is executing or decrease the size of the Adabas Review buffer.
REV20125	Review subtask successfully attached
Explanation	Adabas Review successfully attached an operating system subtask.
Action	This message is for information only.
REV20126	Review subtask detached
Explanation	Adabas Review successfully detached an operating system subtask during its termination logic.
Action	This message is for information only.
REV20127	REV20127 - ADABAS REVIEW forced abnormal termination. REV20127 - R0 - nnnnnnnnn R1 - nnnnnnnnn R2 - nnnnnnnnn R3 - nnnnnnnnn REV20127 - R4 - nnnnnnnnn R5 - nnnnnnnnn R6 - nnnnnnnnn R7 - nnnnnnnnn REV20127 - R8 - nnnnnnnnn R9 - nnnnnnnnn RA - nnnnnnnnn RB - nnnnnnnnn REV20127 - RC - nnnnnnnnn RD - nnnnnnnnn RE - nnnnnnnnn RF - nnnnnnnnn
Explanation	The Review subtask REVIEWB or the Review batch module REVIEWB found an internal serious error. REVIEWB is disabled.
Action	This message is for your information only. Check the dump to find the error. Contact your Software AG technical support representative.
REV20128	Attach for history subtask failed
Explanation	Adabas Review attempted to attach an operating system subtask but received a nonzero return code from this action.
Action	Examine the messages also displayed by the operating system and correct the problem. The possibility exists that the address space, region, or partition was not large enough to attach the task, or the attached module was not in the library concatenations so it could not be found to be loaded.

REV20129 **History subtask detached**
Explanation Adabas Review successfully detached an operating system subtask during its termination logic.
Action This message is for information only.

REV20130 **History subtask successfully attached**
Explanation Adabas Review successfully attached an operating system subtask.
Action This message is for information only.

REV20141 **GETMAIN for spare area failed**
Explanation This message indicates a specific phase of Adabas Review execution.
Action This message is for information only.

REV20142 **RCSBINIT - Review initialization started**
Explanation This message indicates a specific phase of Adabas Review execution.
Action This message is for information only.

REV20143 **Storage available: {nnnn}**
 Storage allocated: {nnnn}
 Storage free: {nnnn}
Explanation Depending on the message text given, the following applies:

Message	Explanation	Action
Storage available: <i>nnnn</i>	The value <i>nnnn</i> is 90% of the value displayed in the z/OS control block field LDAELIM. This value is calculated by the trans- port routines. If the value is zero, for instance in non-transport case, all REV20143 are not issued.	These values are generated by Review internal processes, and are informational only.
Storage allocated: <i>nnnn</i>	The value <i>nnnn</i> is the value found in the z/OS control block field LDAELOAL.	If the value is too big, try to find out, who allocated that storage.
Storage free: <i>nnnn</i>	The value <i>nnnn</i> is the difference of the above two values. This value shows the additional buffer space for trans- port.	If the value is too low, try to find out why it is too low. When this value approaches to zero, CLOG records sent to the REVIEW hub are skipped.

REV20144	Trans-Port activity Records queued {qnn} Records skipped {snn}
Explanation	This message displays the number of records from clients that have been queued (<i>qnn</i>) and skipped (<i>snn</i>) via Trans-Port to the Adabas Review hub. Records are skipped when no storage is available to send them to the hub
Action	To resolve the storage problem, you might choose to increase the number of attached buffers (NAB ADARUN parameter) used during the Adabas Review session.
REV20145	Free main error, length is zero
Explanation	An internal error occurred freeing storage; a length of zero is requested.
Action	Contact your Software AG technical support representative for assistance.
REV20146	RCSBSUM - summary processing
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.
REV20147	RCSBFINI - called for termination
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.
REV20148	RCSBREIN - reinitialization
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.
REV20149	Review is operative
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.
REV20150	File RVUALT can not be opened
Explanation	This is an internal error that rarely occurs.
Action	Contact your Software AG technical support representative.

REV20151	Now switching logs from {clog-dataset1} to {clog-dataset2}
Explanation	A LOG switch is in progress. The FROM data set can now be copied. The TO data set will receive command log output.
Action	This message is for information only.
REV20152	Now it's too late to copy {output-data set}
Explanation	The specified output data set is open for output. The data in this data set can no longer be copied.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4rs003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of your Adabas Review installation.
REV20153	RAOSAUTO subtask detached
Explanation	The RAOSAUTO subtask has been detached successfully.
Action	This message is for information only.
REV20154	Auto regenerate started
Explanation	The RAOSAUTO automatic regeneration subtask started successfully.
Action	This message is for information only.
REV20155	Auto regenerate completed
Explanation	The RAOSAUTO automatic regeneration subtask has completed successfully.
Action	This message is for information only.
REV20156	Response code {rsp} for {cmd} command to DBID= {dbid} ,FNR= {fnr}
Explanation	The RAOSAUTO automatic regeneration subtask issued an Adabas call and received the response indicated in the message.
Action	Verify that the LFILE/NTFILE statement for Adabas Review points to the correct DBID and FNR for the Adabas Review data file.
REV20157	GETMAIN failed
Explanation	A request for a GETMAIN failed in RAOSSYDR. The Adabas task (in hub mode) or the Adabas Review task (in local mode) will be shut down immediately.
Action	Increase the region size for the Adabas task.

REV20158	Doing open call because of Resp 9
Explanation	The Adabas Review history task had to perform an OP (open) call during history data population because an Adabas response code 9 (ADARSP009) was encountered.
Action	This message is for information only.
REV20159	Freemain failed
Explanation	A request for a FREEMAIN to RAOSSYDR failed.
Action	Contact your Software AG technical support representative.
REV20160	History file population failed
Explanation	An error was encountered during Adabas Review history file population and the history subtask was unable to continue.
Action	Check additional warning messages issued by subtask.
REV20161	{nnnnn} ET commands were issued
Explanation	The number of ET commands issued by the Adabas Review history task was <i>nnnnn</i> . The ET commands were issued to synchronize history file population.
Action	This message is for information only.
REV20162	Load failed for {module-name}
Explanation	A request for a LOAD to RAOSSYDR failed. The requested module was not found in the STEPLIB.
Action	Check the STEPLIB to be sure that the module is present.
REV20163	Immediate recovery for RVUALT required
Explanation	The Adabas Review history task encountered an error during history file population and could not continue processing.
Action	Copy the RVUALT data file to another sequential data file and reinitialize Adabas Review.
REV20164	Open failed for {xxxxxxx}
Explanation	A request for an OPEN for DD or file name <i>xxxxxxx</i> to RAOSSYDR failed.
Action	Check that the required DD card or FILEDEF is present in the task job stream.

REV20165	The value of field {fieldname} is {value} It is too big, {trunc-value} stored instead.
Explanation	When storing data into the history file it was detected that the value (<i>value</i>) of the field listed in the message (<i>fieldname</i>) is bigger than the maximum field length allowed in the history file. Storing such a data can result in later Adabas response code 55 (ADARSP055). The value is therefore truncated (<i>trunc-value</i>) and stored instead.
Action	Contact your Software AG support representative about this message to avoid this in the future.
REV20166	Record to {xxxxxxx} skipped, because > 32K
Explanation	While writing a CLOG record, Adabas Review determined that the record was larger than 32767 bytes. Records larger than 32767 bytes are not written to the data set. The DD name or link name of the data set is given in the message (<i>xxxxxxx</i>). This message is issued only one time.
Action	Contact your Software AG technical support representative.
REV20167	Big amount of storage requested.
Explanation	More than 2 GB of storage was erroneously requested.
Action	Determine why such a large amount of storage was erroneously requested. If the problem persists, contact your Software AG technical support representative for assistance.
REV20180	Requested buffer too big.
Explanation	An amount of requested storage is too large.
Action	Determine why such a large amount of storage was erroneously requested and who requested it. If the problem persists, contact your Software AG technical support representative for assistance.
REV20184	Command log records selected: {nnnnnnnnnnnn}
Explanation	This message is issued at shut down of REVIEW. It displays the number of command log records arriving the sub task REVIEWB.
Action	No action is required for this informational message.

REV20185	Unable to load user exit {module-name} - RC {xx} ({xx})
Explanation	The Adabas Review command log processor was unable to load the specified user exit module to copy Adabas Review command logs.
Action	Ensure that the module exists in one of the libraries accessible by Adabas Review.
REV20186	ADAIOR {function} request failed
Explanation	Internal error occurred.
Action	Contact your Software AG technical support representative.
REV20187	Function {function} no longer supported by interface
Explanation	Internal error occurred.
Action	Contact your Software AG technical support representative.
REV20189	{nnnnnnnnnn} Command log record(s) skipped.
Explanation	The number of records which were not sent to subtask REVIEWB because they were sent from the history feature is given in the message (<i>nnnnnnnnnn</i>).
Action	If this database contains a history file, no action is required for this informational message. If this database does not contain a history file, determine why history records are being sent to this database.
REV20190	User parm error - {text}
Explanation	A syntax error was recognized when file RVUFLD was read (custom reporting fields). Possible texts include the following:
	<pre> CANNOT LOCATE USERFLD INVALID NAME PARAMETER INVALID INTYPE PARAMETER INVALID OUTTYPE PARAMETER INVALID HEADER PARAMETER INVALID ADANAME PARAMETER INVALID CALC PARAMETER PREVIOUS PARM LEN TOO LONG PREVIOUS PARM NOT NUMERIC DELIMITER <=> NOT FOUND KEYWORD MISSING OR NOT RECOGNIZED </pre>
Action	Correct the syntax error and restart Adabas Review.

REV20191	Adabas {vrs} not supported
Explanation	In local mode when Adabas Review is called by Adabas, the Adabas Review nucleus verifies that the Adabas version is for a compatible version. If it is incompatible, this message appears. This message identifies the incompatible version of Adabas (<i>vrs</i>). The connection between the two products will not work, and Adabas Review will not collect any data.
Action	Call compatible versions of Adabas Review from the Adabas nucleus. For information about version compatibility, read <i>Adabas and Adabas Review Version Compatibility</i> , in the <i>Adabas Review Release Notes</i> .
REV20192	Only CLOGLAYOUT=8 supported
Explanation	Adabas Review received erroneous CLOG records with CLOGLAYOUT not set to "8". Only CLOGLAYOUT=8 is supported.
Action	In this version of Adabas, only CLOGLAYOUT 8 should be produced. Check the version of Adabas that is being used.
REV20199	Old CLEX from prior ADA V {vr} arrived and will be converted
Explanation	Adabas Review received a call from an Adabas version <i>v.r</i> (or earlier) database. The internal structure of the CLEX is converted to the new format of the CLEX.
Action	No action is required for this informational message.
REV20229	Corrupted record skipped
Explanation	When analyzing command log records with batch program REVIEWB, corrupted command log records may occur. Instead of abending the batch job, the record is skipped and the message REV20229 is issued. The number of these messages is limited to 20 messages.
Action	Find out why there are corrupted command log records. This may involve editing the CLOG and manually looking for inconsistencies. For REVIEW this message is for information only.
REV20230	Number of corrupted record skipped: {nnnnnn}
Explanation	This message is issued after the sequence of skipped records with message REV20229 is finished.
Action	This message is for information only. See also action for REV20229.

REV20231	Report interval reached {report-name }
Explanation	The report named in the message (<i>report-name</i>) was suspended because the time interval specified in the Review Option screen or in the RVUAUT1/2 data set was reached.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4rs003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.
REV20232	Report {report-name }{status-message}
Explanation	One of the following status messages applied to the specified report:
	<code>DEACTIVATED DUE TO MAXSTORE LIMIT EXCEEDED</code>
	The specified active report stopped collecting data because all storage space allocated by the MAXSTORE parameter has been used.
	<code>DEACTIVATED DUE TO STORAGE ALLOCATION FAILURE</code> ↩
	The specified active report stopped collecting data because no more storage is available in the address space/partition.
	<code>ENCOUNTERED STORAGE ALLOCATION FAILURE, REINITIALIZATION SCHEDULED</code>
	The specified active report stopped collecting data because no more storage is available in the address space/partition. All reports will be reinitialized.
	<code>DEACTIVATED DUE TO HASH TABLE MANAGER INITIALIZATION ERROR</code>
	The specified active report could not collect data because of an error in the hash table manager.
	<code>DEACTIVATED DUE TO HASH TABLE MANAGER FIND ERROR</code>
	The specified active report could not collect data because of an error in the hash table manager.
	<code>DEACTIVATED DUE TO TERMINATION PROCESSING STORAGE ALLOCATION FAILURE</code>
	The specified active report could not perform termination processing because no more storage is available in the address space/partition.

HISTORICAL DATA COLLECTION DEACTIVATED DUE TO STORAGE ALLOCATION FAILURE

The specified report could not perform historical data collection because no more storage is available in the address space/partition.

Action Investigate the cause of the specific error. In the event of a failure in the hash table manager, contact your Software AG technical support representative.

REV20233 **Parameter error(s) encountered processing RVUEXI parameter file**

Explanation Parameter error(s) were encountered when Adabas Review was processing the RVUEXI parameter file specified in the Adabas startup procedure.

Action Refer to the RVUEXP output file to determine the parameters that were in error and correct the specified parameters.

REV20234 **Report suspended {reportname}**

Explanation The report named in the message (*reportname*) was suspended for one of the following reasons:

- The CL, PS, SU, or RF command was issued from within SYSREVDDB.
- The time specified in the INTERVAL option for the report was exceeded.

Action No action is required for this informational message. It can be switched on or off by applying the optional zap RY4*rs*003, where *r* is the release number and *s* is the system maintenance level of Adabas Review you have installed.

REV20235 **Report restarted {reportname}**

Explanation The report named in the message (*reportname*) was restarted automatically after a suspension because the report RESTART option is set to "Y".

If a report is suspended with the SU command within SYSREVDDB, it is restarted no matter how the RESTART option is set.

Action No action is required for this informational message. It can be switched on or off by applying the optional zap RY4*rs*003, where *r* is the release number and *s* is the system maintenance level of Adabas Review you have installed.

REV20236 **Report {reportname} started by {userid}**

Explanation The report named in the message (*reportname*) was started as an autostarted report during Adabas Review startup, manually, or after the RF command was issued within SYSREVDDB. The user ID (Natural *INIT-USER value, if this is zero the value UNKNOWN will be displayed) shown in the message is either "AUTOSTRT" if the report is autostarted or the name of the user who started or refreshed the report.

Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4 <i>rs</i> 003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.
REV20237	Report resuspended {reportname}
Explanation	The report named in the message (<i>reportname</i>) was suspended for one of the following reasons: <ul style="list-style-type: none"> ■ The CL, PS, SU, or RF command was issued from within SYSREVDDB; ■ The time specified in the INTERVAL option for the report or the MAXK limit was exceeded; or ■ There are internal storage limitations or errors.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4 <i>rs</i> 003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.
REV20238	Report MAXK suspended {reportname}
Explanation	The report named in the message (<i>reportname</i>) was suspended because the storage maximum specified in the MAXK report option was exceeded. If the report RESTART option is set to "N", message REV20232 is also printed.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4 <i>rs</i> 003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.
REV20239	Field {fldname} is not a client report field
Explanation	The field name given in the message (<i>fldname</i>) was requested for a client report, but is not valid for client reports. Adabas Review processing continues normally, but the values for the field are empty.
Action	Remove the field from the client report.
REV20241	A buffer will not fit into LORECR
Explanation	During conversion of log records to the Adabas Review internal command log record (LORECR) format, a buffer would not fit into LORECR due to LORECR size limitations. The information of this buffer is cut and you may not be able to find the desired buffer information in the report output.
Action	If the data in the affected buffer is not used in a report definition, this error can be ignored as it causes no consequences. However, if this error causes data to be missing, contact your Software AG technical support representative for assistance.

REV20253 **This version of ADATMZ does not support all features
ADATMZ version is {v.r.s}**

Explanation The module ADATMZ was loaded from either the WAL or the ADA library. The ADATMZ version loaded does not support all of the features needed for the current Adabas Review version. The current version of ADATMZ is given in the message (*v . r . s*).

Action Check the Adabas Review version to find out more about the new features and, if necessary, specify a newer WAL or ADA library to obtain the newer version of the ADATMZ module.

REV20255 **{parameter} set too low or missing**

Explanation The parameter of the INPUT statement named in the message (*parameter*) is set too low or is not coded. A possible parameter that may appear in this message is the BUFFMB parameter. The following table describes this parameter further:

Parameter	Description	Minimum Value
BUFFMB	The size of the Adabas Review buffer pool in MB. The default value is 10.	1

Adabas Review runs with the minimum value setting of this parameter. If this setting is too small for a hub environment running Trans-*port*, command log records might be lost.

For more information about the INPUT statement, read *INPUT Statement*, in the *Adabas Review User Guide*.

Action Increase the value setting of the buffer parameter, as described above.

REV20257 **Rpt '{rptname}' was stopped by {userid}**

Explanation The report named in the message (*rptname*) was stopped using the PS command on the Started Reports screen by the user with the user ID (Natural *INIT-USER value, if this is zero the value UNKNOWN will be displayed) listed in the message (*userid*).

Action No action is required for this informational message.

REV20258 **For {dsname} no valid data set found.**

Explanation For the logging file with dataset name *dsname* there is no internal AMT found. Either the *dsname* is incorrect or this dataset is not defined for the Adabas Review system.

Action Check either the Adabas nucleus JCL (in local mode) or the Adabas Review HUB JCL (in Hub mode) against the report definitions and correct one of them.

REV20259	REVIEW field {fieldname} cannot be stored into history file.
Explanation	While building the record buffer for writing the report data to the history file, Adabas Review detected an invalid length definition for the field <i>fieldname</i> in its internal tables.
Action	Contact your Software AG technical support representative.
REV20260	CLEX conversion caused buffer truncation
Explanation	While converting the CLEX from version 82 to 83 format, the command log record had to be cut to 32764 bytes. The message is issued only once upon the first occurrence of this event. It is for informational purpose only.
Action	No action is required for this informational message.
REV20261	Rpt {rptname} put on {queue} for sec={nnnn}
Explanation	The report named in the message (<i>rptname</i>) was placed into the queue <i>queue</i> for <i>nnnn</i> seconds. The <i>queue</i> could be either ACTI or SCHD.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4 <i>rs</i> 003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.
REV20262	Rpt {rptname} {variable message text}.
Explanation	The auto started scheduled report named in the message (<i>rptname</i>) has invalid schedule data as indicated in the <i>variable message text</i> . The auto started scheduled report is not scheduled.
	The variable message text content can be one of the following:
	<ul style="list-style-type: none"> ■ schedule start not before schedule end The point in time specified by SCHED-STRTDAT and SCHED-STRTTIME is not before the point in time specified by SCHED-ENDDATE and SCHED-ENDTIME. ■ schedule duration larger than interval SCHED-DURATION and SCHED-INTERVAL have been specified and SCHED-DURATION is larger than SCHED-INTERVAL. If specified, SCHED-INTERVAL has to be larger than SCHED-DURATION. ■ invalid schedule start/end date/time One of the parameters SCHED-STRTDAT, SCHED-STRTTIME, SCHED-ENDDATE, SCHED-ENDTIME contains an invalid date or time value. ■ schedule end in the past The point in time specified by SCHED-ENDDATE and SCHED-ENDTIME is before the actual time.
Action	Correct the scheduling data of your report definition accordingly.

REV20263	Set timer failed rpt {rptname} RC={nnn} secs={nnnnnnnnnnn}
Explanation	While processing the scheduled report <i>rptname</i> Adabas Review failed to set a timer for either the active or waiting processing phase of the report with the specified return code (RC= <i>nnn</i>) for the specified amount of seconds (secs= <i>nnnnnnnnnnn</i>).
Action	Contact your Software AG technical support representative.
REV20300	zIIP-related statistics for {XXXX} enclave
Explanation	The message is the header of the following zIIP statistics for the REVIEW enclave. <i>XXXX</i> will be replaced by the actual enclave name. Possible enclave names are <ul style="list-style-type: none"> ■ REVHUB ■ REVHIST ■ REVAUTO ■ REVIEWB
Action	No action is required for this informational message.
REV20301	ADAZIP function {XXXX} got rc {yy}.
Explanation	REVIEW encountered during a call to ADAZIP a none zero return code. <i>XXXX</i> will indicate the ADAZIP function invoked and <i>yy</i> will be the return code. The following function abbreviations are used. <ul style="list-style-type: none"> ■ Init Initialize ADAZIP session. ■ Term Terminate ADAZIP session ■ 2SRB Switch into SRB mode ■ 2TCB Switch into TCB mode ■ CSRB Cancel SRB (unused) ■ Stat get zIIP statistics from ADAZIP ■ QPrq queue a parallel request
Action	Contact your Software AG technical support representative.

REV20302	REVIEWB buffer processing stats maximum records in 1 period : {n} REVIEWB processing periods : {n} maximum 4K buffers queued : {n} maximum 32K buffers queued : {n}
Explanation	<p>The message is the header of the following REVIEWB buffer processing statistics.</p> <ul style="list-style-type: none"> ■ maximum records in 1 period specifies the maximum of records REVIEWB has processed during one processing period, i.e. between 2 wait situations. ■ REVIEWB processing periods specifies the number of processing periods executed during the life of the REVIEWB subtask. ■ maximum 4K buffers queued specifies the maximum of 4k buffers queued for the REVIEWB subtask at any time in the life of the subtask. ■ maximum 32K buffers queued specifies the maximum of 32k buffers queued for the REVIEWB subtask at any time in the life of the subtask.
Action	No action is required for this informational message.
REV20303	REVIEWB switch to supervisor state failed REVIEWB continues without ADAZIP
Explanation	<p>The message is issued if the switch to supervisor state failed. Supervisor state is necessary to operate in SRB mode. In order to do so REVIEW has to be loaded from an APF authorized library.</p> <ul style="list-style-type: none"> ■ maximum 32K buffers queued specifies the maximum of 32k buffers queued for the REVIEWB subtask at any time in the life of the subtask.
Action	Start REVIEW from an APF-authorized load library.
REV20304	Log record from database {XXXXX-YYYYY} received, but database not in client database table found.
Explanation	The message is issued if a log record from a database is received which is not registered in REVIEW. The log record is ignored. REVIEW continues processing.
Action	Contact your Software AG technical support representative.

REV20309	REVIEW starting with ZIIP={XXX}
Explanation	The message indicates with which ZIIP parameter value Adabas Review is starting. XXX could be either YES or NO. If you have specified ZIIP=YES in RVUAUT1/2 data set and ZIIP=NO is printed in the REV20309 message, you probably have a license key problem. Check the DDPRINT data set for license key messages. The AZPAD license is necessary to start with ZIIP=YES.
Action	Supply the correct AZPAD license either as load module or in a DDLAZPAD DD statement.
REV20310	REVIEW started with ZIIP=NO Switch to ZIIP=YES not allowed
Explanation	Adabas Review was started with ZIIP=NO and an operator command ZIIP=YES was issued. This is not allowed.
Action	Start Adabas Review with ZIIP=YES in the INPUT statement in order to switch zIIP mode during an Adabas Review session.
REV20311	REVIEW is already executing in SRB mode
Explanation	An operator command ZIIP=YES was issued while Adabas Review already executes in SRB mode. Nothing was changed.
Action	No action is required for this informational message.
REV20312	REVIEW is already executing in TCB mode
Explanation	An operator command ZIIP=NO was issued while Adabas Review already executes in TCB mode. Nothing was changed.
Action	No action is required for this informational message.
REV20313	REVIEW is now executing in SRB mode
Explanation	An operator command ZIIP=YES was issued while Adabas Review was executing in TCB mode. Adabas Review switches into SRB mode.
Action	No action is required for this informational message.

REV20314	REVIEW is now executing in TCB mode
Explanation	An operator command ZIIP=NO was issued while Adabas Review was executing in SRB mode. Adabas Review switches into TCB mode.
Action	No action is required for this informational message.

66

RE VH* - Adabas Review Hub Messages

RE VH03	{hub-id} Database {dbid} [- {nuc-id}] has registered.
Explanation	When a database nucleus initializes, the nucleus sends a call to the hub specified on the ADARUN parameter REVIEW to determine whether an Adabas Review hub is active. When it receives the call, the Adabas Review hub displays this message identifying the DBID of the database nucleus. If the database nucleus is a member of an Adabas Parallel Services or Adabas Cluster Services cluster, then the corresponding nucleus ID is also displayed.
Action	No action is required for this informational message.
RE VH04	{hub-id} Client Monitoring {jobname} has registered.
Explanation	When client reporting initializes, the nucleus sends a call to the hub specified on the ADARUN parameter REVIEW to determine whether an Adabas Review hub is active. When it receives the call, the Adabas Review hub displays this message identifying the job name of the client nucleus.
Action	No action is required for this informational message.
RE VH06	{hub-id} Database {{dbid} {nucid}} has checked out.
Explanation	When a database nucleus is closing, the nucleus calls the hub identified on the ADARUN REVIEW parameter. When it receives the call, the hub displays this message identifying the DBID of the database nucleus. If the database nucleus is a member of an Adabas Parallel Services or Adabas Cluster Services cluster, then the corresponding nucleus ID is also displayed.
Action	No action is required for this informational message.

- RE VH07** **{hub-id} Database {dbid} no longer registered.**
Explanation The specified database nucleus was deleted from the hub's registered client list.
Action None required. This is for your information only.
- RE VH10** **{hub-id} Database {dbid} was sent a message.**
Explanation When there is a change in the monitoring or reporting status of a database nucleus by Adabas Review, the hub sends a notification to the client nucleus. This message is displayed when the notification is sent to the client nucleus.
Action No action is required for this informational message.
- RE VH11** **{hub-id} { NO | {count} } started reports.**
{hub-id} { NO | {count} } reports requiring buffers.
Explanation These messages are displayed in conjunction with the REVH10 message and indicate the status of information transmitted to the database nucleus by the hub.
count indicates the number of started reports and/or the number of reports requiring buffers.
Action None required. This message is for your information only.
- RE VH12** **{hub-id} Outbound message to database {{dbid}|{nucid}} received RSP {rsp/subcode}**
Explanation This message is displayed at the completion of a notification call to a database nucleus identified by the database ID (*dbid*) or nucleus ID (*nucid*) given in the message. In cluster environments, a nucleus ID is listed; in all other environments, a database ID is listed. A response code of zero indicates that the message was successfully received.
Action No action is required for this informational message.
- RE VH13** **{hubid} Dbid Nucid Last-act Rpts Buffers Log-records**
{hubid dbid nucid last-act-time globrpts/dbrpts buffers log-recs}
{hubid} CL {jobname last-act-time clientrpts/dbrpts} ----- {log-recs}
Explanation This message is displayed in response to the DCLIENT operator command. A title that reads "*hubid* Dbid Nucid Last-act Rpts Buffers Log-records" appears as the first REVH13 message. Thereafter, the following information is supplied under the corresponding column titles for each client nucleus registered with the hub:

<i>buffers</i>	<p>The buffers requested for this client are displayed in the following format <i>frsvtom</i>, where:</p> <ul style="list-style-type: none"> ■ <i>f</i>: An "F" appears here if a format buffer was requested. ■ <i>r</i>: An "R" appears here if a record buffer was requested. ■ <i>s</i>: An "S" appears here if a search buffer was requested. ■ <i>v</i>: A "V" appears here if a value buffer was requested.
----------------	--

	<ul style="list-style-type: none"> ■ <i>i</i>: An "I" appears here if an ISN buffer was requested. ■ <i>o</i>: An "O" appears here if an I/O list buffer was requested. ■ <i>m</i>: An "M" appears here if a multifetch buffer was requested <p>If a buffer type was not requested, a dash ("-") appears in the appropriate location above.</p> <p>Note: In the case of the client report line in this message (the line starting with CL), there are no buffers, so dashes will appear in this section.</p>
<i>clienrpts</i>	The number of client reports running.
<i>dbid</i>	The database ID of the client nucleus.
<i>dbrpts</i>	The number of database-specific reports running for this client.
<i>globrpts</i>	The number of DBID=ALL reports running for this client.
<i>hubid</i>	The Adabas Review hub ID.
<i>jobname</i>	The job name of the client reporting client.
<i>last-act-time</i>	The time of last activity or the time when the last command log record was received from the client nucleus, in <i>hh:mm:ss</i> format.
<i>log-recs</i>	The number of command log records received from the client nucleus. For client report entries, this is the number of all command log records received from the client address space identified by the job name given in the message (<i>jobname</i>).
<i>nucid</i>	If the client nucleus represents an Adabas Parallel Services or Adabas Cluster Services database, the number of the nucleus within the cluster is also displayed.

The last line of the message lists the number of client reports running in the hub.

Action

No action is required for this informational message.

REVH14

{hub-id} Client {dbid} is not registered.

Explanation

This message is displayed in response to an operator command that requested a service for a nonexistent client nucleus. The requested client nucleus could not be found in the hub's registered client list.

Action

Ensure that the correct client nucleus ID is properly specified and reenter the operator command.

REVH15	{hub-id} No databases registered.
Explanation	An operator command requested a service or status and there are no database nuclei presently listed in the hub's registration list.
Action	None required. This is for your information only.
REVH16	{hub-id} The REVIEW Hub is not running APF authorized.
Explanation	To use the Trans-port feature of the Adabas Review hub under z/OS, the load library needs to be APF-authorized.
Action	APF-authorize the load library if you want to use the Trans-port feature.
REVH17	{hub-id} Trans-port is disabled.
Explanation	The reason is provided in the previous message.
Action	The Trans-port feature is not available in z/VSE environments. To use the Trans-port feature in other supported operating environments, refer to the previous message.
REVH21	{hub-id} A database register attempt failed due to missing DBID value.
Explanation	The hub received a call from an unknown database. The hub ignores the request.
Action	None required. This is for your information only.
REVH22	{hub-id} Insufficient space to register database {dbid}.
Explanation	The hub was unable to insert a new database into its registration list. The client is given a non-zero response to prevent further communication. The hub continues processing and the registration of the new client is ignored.
Action	Enter a <code>DCLIENT=ALL</code> operator command and review the list of clients. If there is a possibility of deleting a non-active client, then enter the <code>STOPCLIENT=dbid</code> operator command to stop the client from sending data, followed by a <code>DELCLIENT=dbid</code> to release the space in the registration list. To initiate the registration of the previously rejected client, start an Adabas Review report for that client.
REVH24	{hub-id} REVIEW nucleus terminated. REVIEW hub aborting.
Explanation	The Adabas Review nucleus terminated abnormally. The hub can no longer process Adabas Review data and will terminate.
Action	Check all messages from Adabas Review to determine the cause of the abnormal termination of the Adabas Review nucleus. Correct the problem and restart Adabas Review.

REVH25	{hub-id} REVIEW buffer shortage.
Explanation	The hub incurred a shortage of the REVIEW buffer. The value for the available storage can be determined by the BUFFMB parameter of the INPUT statement
Action	See the <i>Adabas Review User</i> documentation.
REVH26	{hubid} Handshake command for database {{dbid} {nucid}} issued UBRSP={ubrsp}
Explanation	For diagnostic purposes, a handshake trace from the Adabas Review hub to the databases is activated. The Adabas Review hub issues a handshake command to a database because a report for this database is started, changed, or stopped. When the Adabas Review hub is brought down via ADAEND, the handshake command for the databases is also issued. UBRSP=8 indicates that the command is immediately complete and a 16-call is not required. UBRSP=4 indicates that the call is not complete and a 16-call is required. Either a database ID (<i>dbid</i>) or nucleus ID (<i>nucid</i>) is given in the message. In cluster environments, a nucleus ID is listed; in all other environments, a database ID is listed.
Action	No action is required for this informational message.
REVH27	{hubid} Handshake command for database {{dbid} {nucid}} has completed {hubid} RSP={acbrsp/acbsubcode}, ACBRSP={acbrsp}
Explanation	For diagnostic purposes, a handshake trace from the Adabas Review hub to the databases is activated. An Adabas X'1C' call with UB was sent to a database by the Adabas Review hub and message REVH26 was issued. A 16-call was issued (if required) and the command completed with the indicated response code and subcode. Note: ACBRSP=148 most likely means the database was not active. Either a database ID (<i>dbid</i>) or nucleus ID (<i>nucid</i>) is given in the message. In cluster environments, a nucleus ID is listed; in all other environments, a database ID is listed.
Action	No action is required for this informational message.
REVH29	{hubid} No UB available for command to database {dbid}
Explanation	There are not sufficient user blocks to add or communicate with a new database. The Adabas Review hub abends.
Action	This may be a transient condition if the hub is servicing many clients in a very busy system. Issue the STARTCLIENT operator command to reinitiate handshaking. If this does not resolve the error, try decreasing the number of clients or increasing the number of user blocks. The number of user blocks can be increased by an optional zap which increases the value HUBMXCL is increased. For more information, or if this does not resolved the error, contact your Software AG technical support representative.

REVH30	{hubid} Logic error completing command to database {dbid}
Explanation	A command sent from the hub to a client was thought to be complete, but the 16-call did not mark it as complete. This is normally a logic error, but it might also occur during hub termination if the client was unresponsive..
Action	Contact your Software AG technical support representative if this does not relate to an unresponsive client during hub termination.
REVH31	{hubid} Invalid storage key {x}
Explanation	The Adabas Review hub can only run in storage key 0 or 8.
Action	Start the Adabas Review hub again under storage key 0 or storage key 8.
REVH32	{hubid} Error initializing zIIP environment – Error Code: {xx}
Explanation	During initialization of the zIIP environment an error has occurred.
Action	Restart the Adabas Review hub with INPUT ... ZIIP=NO.

67

RTP* - Adabas Review Trans-port Messages

RTP001	Review Abend in RTPSSPC Abend S{syscode} U{usrcode} Reason {rsncode} Hub ID {hubid} PASN {pasn} SASN {sasn} PSW {psw} {extended-information} {general-registers} {access-registers}
Explanation	<p>A program check or system abend was intercepted by the Adabas Review Trans-port ARR routine. This message appears in the Trans-port caller's listings and the system console.</p> <p>The caller does not abend, but the data being sent to the Adabas Review hub may be discarded. A system dump is attempted.</p>
Action	Contact your Software AG technical support representative for assistance.
RTP002	Review Abend in RTPSSPC Abend S{syscode} U{usrcode} SDWA Not Available
Explanation	<p>A program check or system abend was intercepted by the Adabas Review Trans-port ARR routine. This message appears in the Trans-port caller's listings and the system console.</p> <p>z/OS did not provide a System Diagnostic Work Area (SDWA), which reduces the amount of information available.</p> <p>The caller does not abend, but the data being sent to the Adabas Review hub may be discarded. A system dump is attempted.</p>
Action	Contact your Software AG technical support representative for assistance.

RTP003	System Dump Accepted
Explanation	The error described in preceding messages RTP001 or RTP002 is recorded in a system dump. Additional dump details are in the system log and the hub's listing.
Action	Contact your Software AG technical support representative for assistance.
RTP004	SDUMPX failed Reason {rsncode}
Explanation	A system dump was attempted after the error described in the preceding messages RTP001 or RTP002 . z/OS was unable to schedule the dump.
Action	Check the IBM documentation for the SDUMPX service to determine the meaning of the reason code given in the message. Contact your Software AG technical support representative for assistance.
RTP005	SRB Mode - Dump may be incomplete or some data my have changed
Explanation	The error described in preceding messages RTP001 or RTP002 is recorded in a system dump but Trans-ort was unable to synchronize with the dump process. Additional dump details are in the system log and the hub's listing.
Action	Contact your Software AG technical support representative for assistance.

68

RVCL* - Adabas Review Batch Client Reporting

(REVCLRP) Messages

RVCL001	Review Client Reporting has been {started stopped}
Explanation	Adabas Review client reporting has been started or stopped. (REVEXIT2 has successfully been changed to the requested state: ON or OFF.)
Action	No action is required for this informational message.
RVCL002	Review Client Reporting is currently {on off unavailable}
Explanation	The current status of Adabas Review client reporting is listed in the message.
Action	No action is required for this informational message.
RVCL003	Unexpected error while resetting state
Explanation	While performing the STATUS function, an error occurred resetting the original state after processing. This is due to a very small window of opportunity where an externally controlled process was altered. An example would be if the Adabas Review hub was terminated during the time when the STATUS call has started but not completed.
Action	Retry the operation.
RVCL004	Invalid function code
Explanation	An invalid function code was specified in RVCLFUNC. Valid function codes are "ON", "OFF" or "STATUS".
Action	Specify a valid function code in RVCLFUNC and try again.

RVCL005	Non-zero response from link routine
Explanation	An error condition exists. Output fields RVCLRSP and RVCLRESN will contain the response and reason codes returned by the Adabas link routine, ADALNK. Note: These fields were set by ADALNK, not REVCLRP.
Action	Examine the response code and reason codes to understand the problem and fix it. If you need assistance, contact your Software AG technical support representative.
RVCL006	Review Client Reporting was already {on off}
Explanation	A request was made to change the state of client reporting, but client reporting was already in that state.
Action	Determine whether the request to change the state was requested correctly. If not, correct the request and try again.
RVCL007	REVEXIT2 is not installed
Explanation	An attempt to call REVCLRP was made from an application, but the REVEXIT2 link routine is not currently installed. REVEXIT2 is required for client reporting.
Action	Contact your Software AG technical support representative for assistance.
RVCL008	Insufficient storage for REVEXIT2
Explanation	There is not enough memory available for REVEXIT2 to operate.
Action	Provide more storage and try to run the job that calls REVCLRP again.
RVCL009	The hand shake with the Review hub failed
Explanation	The Trans-Port service was not able to communicate properly with the Adabas Review hub because the PC number was zero.
Action	Contact your Software AG technical support representative; be prepared to provide a dump and protocol information.
RVCL010	The internal Trans-Port mechanism failed
Explanation	Attempts to communicate with the Adabas Review hub failed. Output fields REVCLRSP and RVCLRESN will be set with the response and reason codes from REVCLRP. If the response and reason codes are 148/50, then the hub was terminated after client reporting (REVEXIT2) was activated.
Action	If the response and reason codes are 148 and 50 (respectively), restart the hub and try again. If the response and reason codes are not 148 and 50, contact your Software AG technical support representative for assistance.

RVCL011	Adabas response 148 was received contacting the hub
Explanation	The Adabas Review hub is not available.
Action	Start the Adabas Review hub and try again.

69 SAF* - SAF Daemon Messages

The following messages may be issued by the SAF daemon.

SAF001I	Unable to load required module: {xxxxxx}
Explanation	The SAF kernel or one of the modules it needs could not be loaded. Ensure that all SAF modules (including those created by installation assembly jobs – SAFCFG, SAFPSEC and SAFPMAC) are available.
SAF002I	Unable to obtain anchor storage
Explanation	A memory allocation failed during initialization. Increase the region size.
SAFD01S	SAF CANNOT INITIALISE, GETMAIN ERROR
Explanation	There is insufficient memory for the SAF daemon to initialize. Increase the region size.
SAFD02S	SAF CANNOT INITIALISE, KERNEL LOAD ERROR
Explanation	Installation error (SAFCKN load module not available). Ensure that all required load modules are available.
SAFD03E	DDCARD open error: ## - terminating
Explanation	The SAF daemon was unable to open DDCARD. Ensure that the DDCARD DD statement is specified correctly.

SAFD04I	Input parameter: {xxx}
Explanation	The daemon echoes the values of the supplied DDCARD parameters.
SAFD05E	Invalid parameter: {#####}
Explanation	DDCARD contained an invalid parameter. The SAF daemon terminates. Correct the parameter in error.
SAFD06E	Product parameter not specified
Explanation	DDCARD did not contain PRODUCT=SAF. Ensure that PRODUCT=SAF and DEFAULT=SAF are both specified.
SAFD07E	MPM failure - function: ## error ##
Explanation	The SAF daemon received an error from ADAMPM. This message will usually be preceded by an explanatory message. If in doubt, contact your Software AG technical support representative for assistance.
SAFD08E	IOR failure - function: ## error ##
Explanation	An error occurred during an ADAIOR service call. Contact your Software AG technical support representative for assistance.
SAFD09I	Shutdown requested
Explanation	The SAF daemon has been instructed to shut down.
SAFD10E	Getmain for command queue failed
Explanation	The SAF daemon failed to allocate its command queue. Increase the region size.
SAFD11I	SAF Kernel is active on node {nnnnn sss }CIB={aaaaaaa}
Explanation	The daemon is now active and ready to receive security requests; nnnnn is the node ID, sss is the SVC number, and aaaaaaa is the address of the daemon's main storage area.
SAFD12I	Oper type in: SAF {xxxxx}
Explanation	Message 12I is issued before processing of an operator command.

SAFD13E	Invalid operator command
Explanation	An invalid operator command was entered.
SAFD14I	Target {nnnnn} termination in progress
Explanation	Message 14I is issued during daemon termination (nnnnn is the daemon's node ID).
SAFD15I	Target {nnnnn} ended normally
Explanation	Message 15I is issued during daemon termination (nnnnn is the daemon's node ID).
SAFD22E	Load for module: {#####} failed
Explanation	The indicated module could not be loaded. Ensure that it is available.
SAFD25E	{###} is an invalid product name
Explanation	An invalid PRODUCT= parameter was specified in DDCARD.
SAFD26E	Proxy module SAFPTY was not found, product SAF will not be called
Explanation	Ensure that SAFPTY and all other required load modules are available.
SAFD30E	Getmain for product parm block failed
Explanation	A memory allocation failed during initialization. Increase the region size.
SAFD31E	Cab allocation error in module syscoru
Explanation	A memory allocation failed during initialization. Increase the region size.
SAFD34E	UAB allocation error in module syscoru
Explanation	A memory allocation failed during initialization. Increase the region size.
SAFD40S	Abend {code} Psw {pppppppp pppppppp}
Explanation	Message 40S is issued during abnormal termination. It shows the abend code, Program Status Word, module that abended and register contents. In the event of an abend, please ensure you collect the messages, the dump and any trace messages or snaps that have been generated.

SAFD42S **Module {module} entry {entry-point} offset {offset}**
Explanation Message 42S is issued during abnormal termination. It shows the abend code, Program Status Word, module that abended and register contents.

In the event of an abend, please ensure you collect the message, the dump and any trace messages or snaps that have been generated.

SAFD43S **Regs 00-03 {register contents}**
 Regs 04-07 {register contents}
 Regs 08-11 {register contents}
 Regs 12-15 {register contents}
Explanation Message 43S is issued during abnormal termination. It shows the abend code, Program Status Word, module that abended and register contents.

In the event of an abend, please ensure you collect the message, the dump and any trace messages or snaps that have been generated.

70

SAGE* - z/VSE Batch Job Exit Utility Messages

These messages are written over the redisplayed SAGUSER batch control statements, starting in column 26, by the Software AG job exit utility (batch) for z/VSE systems.

SAGE020 - SAGIPT not found in the SDL

Explanation An entry for the phase SAGIPT was not found in the SDL.

The SAGUSER control statements cannot be processed.

Action Verify that the phase SAGIPT was loaded into the SVA (using the SET SDL command). Load the phase if required, run the program SAGINST, and resubmit the job.

SAGE021 - DD name table not found

Explanation The control table used by the job control exit cannot be found.

The SAGUSER control statements cannot be processed.

Action Verify that the program SAGINST ran correctly. If not, rerun it and verify that one of the following messages is displayed: SAGI005, SAGI006, or SAGI016.

SAGE022 - No room in DD name table

Explanation The control table used by the job control exit is full.

The SAGUSER control statements cannot be processed.

Action Wait until some of the currently running jobs have completed and rerun the job that received the error message.

SAGE023 - Invalid or missing FILE=

Explanation The SAGUSER control statement does not contain a "FILE=" parameter.

The SAGUSER control statement cannot be processed.

Action Add the correct file designation to the control statement and rerun the job.

SAGE024 - Invalid or missing MEMBER=

Explanation The SAGUSER control statement does not contain a "MEMBER=" parameter.

The SAGUSER control statement cannot be processed.

Action: Add the correct member designation to the control statement and rerun the job.

SAGE025 - Invalid SAGUSER control statement

Explanation The SAGUSER control statement does not contain any valid keyword parameters.

The SAGUSER control statement cannot be processed.

Action Add the correct parameters to the control statement and rerun the job.

71 SAGI* - Batch Initialization Messages (z/VSE Only)

These messages are written to the operator console and to SYSLST by the optional Adabas job exit. See the Adabas Installation documentation for more information.

SAGI001	Software AG job exit V{v} installed
Explanation	The Software AG job control exit is active.
Action	SAGUSER control statements will be processed.
SAGI005	Table allocated (low) ADDR={addr}
Explanation	The SAGUSER table was allocated in system GETVIS below the 16-MB line at the address indicated.
SAGI006	Table allocated (high) ADDR={addr}
Explanation	The SAGUSER table was allocated in system GETVIS above the 16-MB line at the address indicated.
SAGI010	Software AG job exit already installed
Explanation	The Software AG job control exit can be installed only once.
Action	No action is required if the Software AG job exit is actually installed. If it is not, perform an IPL and reestablish the job control exit chain.

SAGI016	Table already allocated ADDR={addr}
Explanation	The program SAGINST has already allocated the DD name table.
Action:	No action is required if the Software AG job exit is actually installed. If it is not, perform an IPL and reestablish the job control exit chain.
SAGI091	Unable to locate \$JOBEXIT in SDL
Explanation	The entry for phase \$JOBEXIT was not found in the SDL. The Software AG job exit cannot be installed.
Action:	Get information on the version, release, and service pack number of the operating system and call Software AG for support.
SAGI092	Unable to locate SAGJBXT in SDL
Explanation	The entry for phase SAGJBXT was not found in the SDL. The Software AG job exit cannot be installed.
Action	Verify that phase SAGJBXT was loaded into the SVA.
SAGI093	Phase SAGJBXT in error
Explanation	The phase SAGJBXT loaded into the SVA is not the job control exit supplied by Software AG. The Software AG job exit cannot be installed.
Action	Verify a probable error during the linkage edit of SAGJBXT.
SAGI095	Unable to determine VSE level
Explanation	Information about z/VSE (i.e., version and release) could not be found in the supervisor. The Software AG job exit cannot be installed. A storage dump is produced.
Action	Obtain the z/VSE version and release level; call Software AG for support.
SAGI096	SAGJBXT ID not found in \$JOBEXIT table
Explanation	An entry for SAGJBXT was not found in the \$JOBEXIT table (for z/VSE 1.2 and above). The Software AG job exit cannot be installed.
Action:	Add an entry for SAGJBXT in \$JOBEXIT and retry the program SAGINST.

SAGI097	SAGJBXT phase {phase} not found
Explanation	The phase for SAGJBXT was found in the \$JOBEXIT table (for z/VSE 1.2 and above), but the phase has not been loaded into the SVA. The Software AG job exit cannot be installed.
Action	Verify that phase SAGJBXT was loaded into the SVA.
SAGI098	SAGJBXT phase {phase} not in SVA
Explanation	The phase for SAGJBXT was found in the \$JOBEXIT table (for z/VSE 1.2 and above) and has been loaded, but not into the SVA. The Software AG job exit cannot be installed.
Action:	Verify that phase SAGJBXT was loaded into the SVA.
SAGI099	SAGJBXT phase {phase} not valid
Explanation	The phase for SAGJBXT was found in the \$JOBEXIT table (for z/VSE 1.2 and above) and has been loaded, but not into the SVA. The Software AG job exit cannot be installed.
Action:	Verify that phase SAGJBXT was loaded into the SVA.
SAGI101	Allocation error (high) RC={ret-code}
Explanation	An attempt to allocate space for the DD name table in 31-bit mode failed. The return code is from the GETVIS macro. The Software AG job exit will not process SAGUSER statements.
Action:	Verify that enough storage is available in the SVA for the DD name table; then rerun SAGINST.
SAGI102	Allocation error (low) RC={ret-code}
Explanation	An attempt to allocate space for the DD name table in 24-bit mode failed. The return code is from the GETVIS macro. The Software AG job exit will not process SAGUSER statements.
Action:	Verify that enough storage is available in the SVA for the DD name table; then rerun SAGINST.

72 SEFM* - ADASAF SAF Interface and SAF Security Kernel

Messages

- Operator Command Messages (SEFM900+ Series) Adabas SAF Securityoperator command messages SAF Security Kerneloperator command messages 1096

ADASAF displays an eight-byte code containing various return codes from SAF. This information is shown in a number of messages denoted *sssssss*.

The ADASAF return code "sssssss" contains the following structure:

Position	Information Content	
Byte: 1	SAF return code	
Byte: 2	Function code. ADASAF internal function codes (hex) include:	
	04	Authorize Adabas access
	44 or 6C	Authenticate user
Byte: 3	Return code from security system, for example RACF	
Byte: 4	Reason code from security system, for example RACF	
Bytes: 5 - 8	SAF reason code	

Refer to the IBM manual External Security Interface (RACROUTE) Macro Reference manual for z/OS for a thorough explanation of all possible return/reason codes. CA-Top Secret and CA-ACF2 can provide different return code values in some circumstances.

BLS0334 **SYMBOL 'NETSAF' CANNOT BE FOUND. LOADING ABORTED**

Explanation This message should be ignored.

SEFM001 **{sssssss} : {user} : {resource}**

Explanation The security system determined that the user identified in the message (*user*) does not have authorization for the resource listed in the message (*resource*). System return and reason codes are given in the hexadecimal string *sssssss*. This message is displayed when access has been denied to a particular resource.

SEFM002 ***{XX} to request FF : {user} : {resource}**

Explanation An unexpected response code (*XX*) was received from the SAF Security Kernel for the user identified in the message (*user*) when requesting function *FF* to be performed on the resource specified in the message (*resource*).

SEFM004 ***Natural programs not extracted**

Explanation The SAF Security Kernel was not able to extract a list of protected program objects from the security system on behalf of Natural users.

Action Obtain a trace of SAF call RACROUTE EXTRACT from the security system and contact your Software AG technical support representative. ACF2 and Top Secret users should ensure that the protected programs have been extracted from the security system and supplied to the SAF Security Kernel via the SEFEXT DD statement in the daemon started task JCL.

SEFM006	*ADARSP {XX}({xx}) to request FF : {user}
Explanation	The SAF Security Kernel returned the Adabas response code (<i>XX</i>) and subcode (<i>xx</i>) shown in the message to request <i>FF</i> for the user shown in the message (<i>user</i>).
Action	Ensure that the SAF Kernel started task is active. Check its output for error messages. Take the necessary remedial action indicated by the Adabas response code.
SEFM008	*SAF Gateway (V{v.r}) started * SAF Security Kernel (V{x.x.x} - BUILD {xxxx}) started
Explanation	Entire Net-Work SAF Security Interface (ADASAF) startup completed or the SAF Security Kernel initialized successfully.
Action	No action is required for this informational message.
SEFM009	Module {module-name} not loaded
Explanation	Entire Net-Work SAF Security Interface could not load the module listed in the message (<i>module-name</i>).
Action	Ensure that the module is in the STEPLIB and that the region size is sufficient.
SEFM013	*Less {memory storage} acquired than specified
Explanation	The SAF Security Kernel or the Entire Net-Work SAF Security Interface (ADASAF) were not able to allocate all the memory or storage required to satisfy the buffer size specified in its parameters. Operation continues.
Action	Ensure that the region size is sufficient and the parameters are appropriate.
SEFM014	*No {memory storage}could be acquired
Explanation	Entire Net-Work SAF Security Kernel or the SAF Security Interface (ADASAF) could obtain no storage or memory at system startup. Operation has terminated. Operation has terminated.
Action	Ensure that the region size is sufficient and system parameters are appropriate.
SEFM015	*Logic error - {XXXX} for request FF : {user}
Explanation	The SAF Security Kernel suffered an internal error. A general restart is performed and the operation continues.
Action	Keep all information written to DDPRINT and contact your Software AG technical support representative.

SEFM016	*SAF logoff failed {sssssss} ACEE AAAA : {user}
Explanation	The SAF Security Kernel was unable to logoff <i>user</i> from the security system. The SAF error code is <i>sssssss</i> .
Action	Contact your Software AG technical support representative.
SEFM017	*Insufficient space to initialize - make Natural buffer {XX}
Explanation	The Natural SAF interface requires a larger value to be specified for NSFSIZE.
Action	Increase the Natural NSFSIZE parameter.
SEFM020	*GETMAIN failed / IDSIZE error
Explanation	The Natural SAF interface could not acquire storage from the designated IDMSBUF.
Action	Increase Natural region and/or thread size.
SEFM021	*Illegal storage use / relocation problem
Explanation	Internal problem in Natural SAF storage use.
Action	Contact your Software AG technical support representative.
SEFM025	*Natural IDMSBUF parameter is not defined
Explanation	The Natural NSFSIZE parameter has not been specified.
Action	Ensure NSFSIZE is set correctly in the Natural parameters.
SEFM026	*Natural protected programs not extracted code: {XX}
Explanation	The list of protected programs could not be returned from the SAF Security Kernel to Natural.
Action	Ensure the same copy of the configuration module SAFCFG is used by all system components. Check that the GWSTYP parameter defined in SAFI010 and STY parameter in SAFI020 are both correctly set for the installed security system and that all installation requirements have been met.
SEFM028	*System files not found in environment table
Explanation	The current Natural system files were not matched in the table defining all possible system file sets.
Action	Ensure that the environment definitions in Natural Security are correct.

SEFM029	*Error in communications layer - check installation procedure
Explanation	Possible reasons for error: Adabas link module installed into this component is not reentrant.
SEFM030	*SQL table / VIEview could not be identified for file ({XX},{YY})
Explanation	Interface could not identify table name for DBID/FNR of an SQL request.
Action	Ensure interface is correctly installed, then contact your Software AG technical support representative.
SEFM031	*DBID / FNR identified with SQL request not recognized {XXXX}
Explanation	Interface component could not determine the DBID/FNR associated with this SQL request.
Action	Contact your Software AG technical support representative.
SEFM041	*Interface installed for Net-work
Explanation	The interface is installed for operation with Entire Net-Work.
Action	No action is required for this informational message.
SEFM049	*User type T not permitted by installed options
Explanation	The SAF Kernel will not permit user type <i>T</i> to operate using the currently installed options.
SEFM050	*Error writing SMF record : {XX}
Explanation	The stated error occurred when an SMF record was being written.
SEFM051	*SAFPRINT dataset not defined, DDPRINT will be used
Explanation	SAFPRINT=Y is set in SAFCFG, but no SAFPRINT dataset is defined.
SEFM060	* RACLIST REQUESTED FOR CLASS ccccccc
Explanation	The specified security class ccccccc has been configured to use FASTAUTH in SAFCFG. This message indicates the start of the RACLISTing process for this class.
Action	No action is required for this informational message.

SEFM061	* RACLIST SUCCESSFUL FOR CLASS ccccccc
Explanation	This message indicates RACLISTing has been successful for class ccccccc.
Action	No action is required for this informational message.
SEFM062	* RACLIST FAILED FOR CLASS ccccccc ERROR sssssss
Explanation	This message indicates RACLISTing has failed for class ccccccc. The FASTAUTH option for this class cannot be honoured, authorization checks will be performed using RACROUTE REQUEST=AUTH (the default).
Action	Refer to SAF Return Codes for information on how to interpret the error code sssssss.
SEFM205	*CPU identity : {cpuid}
Explanation	The interface component linked to Entire Net-Work displays the CPU ID of the host machine.
Action	No action is required for this informational message.
SEFM210	*SAF Gateway is active for Entire Net-Work
Explanation	The Entire Net-Work SAF Security Interface is active.
Action	No action is required for this informational message.
SEFM255	*Unauthorized use of request
Explanation	Attempted illegal use of security request.
Action	Contact your Software AG technical support representative.

Operator Command Messages (SEFM900+ Series) Adabas SAF Securityoperator command messages SAF Security Kerneloperator command messages

The following messages are displayed in response to operator commands:

SEFM900	* Operator issued command: {command}
Explanation	Entire Net-Work SAF Security Interface (ADASAF) or the SAF Security Kernel received the operator command identified in the message.
Action	No action is required for this informational message.

SEFM901

* SAF server - General statistics (at {hhhhhhh})

* SAF Security Kernel - General statistics (at {hhhhhhh})

Explanation

The operator command for general statistics was issued. Here is an example of the statistics messages produced for the SAF server:

```
SEFM901 * SAF SERVER - GENERAL STATISTICS (AT hhhhhhhh)
SEFM902 * RESOURCE      CHECK(+VE) CHECH(-VE) CHECK SAVED OVERWRITES ←
LEN
SEFM903 * APPLICATION          1          0          0          ←
0      8
SEFM903 * ADABAS                0          0          0          ←
0     32
SEFM903 * SYSMAIN                0          0          0          ←
0     13
SEFM903 * SYSTEM FILE           2          0          0          ←
0     24
SEFM903 * PROGRAM                0          0          0          ←
0     17
SEFM903 * BROKER                 0          0          0          ←
0     32
SEFM903 * NET-WORK               0          0          0          ←
0      0
SEFM903 * SQL SERVER             0          0          0          ←
0      0
SEFM904 * USERS - ACTIVE: 1 FREE: 55 OVEWRITES: 0
```

Here is an example of the statistics messages produced for the SAF Security Kernel. The address in the first line is the address of the SAF Kernel's storage cache.

```
SEFM901 * SAF SECURITY KERNEL - SERVER STATISTICS (AT 12C47000)
SEFM902 * RESOURCE      CHECK(+VE) CHECH(-VE) CHECK SAVED OVERWRITES ←
LEN
SEFM903 * APPLICATION          10          0          0          ←
0      8
SEFM903 * DBMS CHECK            0          0          0          ←
0     17
SEFM903 * SYSMAIN                0          0          0          ←
0     21
SEFM903 * SYSTEM FILE           2          0          0          ←
0     40
SEFM903 * PROGRAM                0          0          0          ←
0     17
SEFM903 * BROKER                 0          0          0          ←
0     68
SEFM903 * NET-WORK               0          0          0          ←
0     17
SEFM903 * SQL SERVER             0          0          0          ←
0     32
SEFM904 * CACHED USERS:          1 HIGH WATERMARK:      1 MAX USERS: ←
5545
```

```
SEFM905 * OVERWRITES:          0 AUTHENTICATED:          0 DENIED:          ↵
          0
```

Action No action is required for this informational message.

SEFM902 - 905 {statistics}

Explanation Various statistics for the SAF server and the SAF Security Kernel are displayed. See message [SEFM901](#).

Action No action is required for this informational message.

SEFM909 * {SAF Gateway | SAF Security Kernel} - shutdown initiated

Explanation The operator issued a command to shut down Entire Net-Work SAF Security Interface or the daemon started task (SAF Security Kernel). This message is also issued when a secure Adabas nucleus, Net-Work node or Adabas SQL server terminates.

Action No action is required for this informational message.

SEFM910 *{SAF Server | SAF Security Kernel} - list all active users

Explanation The operator issued a command to display a list of currently active users.

The following is a sample of the output produced for the SAF server:

```
SEFM910 * SAF SERVER - LIST ALL ACTIVE USERS
SEFM911 * USERID      CHECK(+VE) CHECH(-VE) CHECK SAVED OVERWRITES ↵
BUFF
SEFM912 * K11079          3           0           0           ↵
0 0
```

The following is a sample of the output produced for the SAF Security Kernel:

```
SEFM910 * SAF GATEWAY - LIST ALL ACTIVE USERS
SEFM911 * USERID CHECK(+VE) CHECH(-VE) CHECK SAVED OVERWRITES BUFF
SEFM912 * K11079          3           0           0           0 0
```

Action No action is required for this informational message.

SEFM911 *{userid} . . .

Explanation The operator issued a command to display statistics specific to a currently active user.

The following is a sample of the output produced for the SAF server:

```

SEFM911 * NXB          CHECK(+VE) CHECH(-VE) CHECK SAVED OVERWRITES ←
  BUFF
SEFM912 * APPLICATION      1          0          0          ←
0  0
SEFM912 * DBMS CHECK      0          0          0          ←
0  0
SEFM912 * SYSMAIN        0          0          0          ←
0  0
SEFM912 * SYSTEM FILE    2          0          0          ←
0  0
SEFM912 * PROGRAM        0          0          0          ←
0  0
SEFM912 * BROKER         0          0          0          ←
0  0
SEFM912 * NET-WORK       0          0          0          ←
0  0
SEFM912 * SQL SERVER     0          0          0          ←
0  0

```

The following is a sample of the output produced for the SAF Security Kernel:

```

SEFM911 * SJU          CHECK(+VE) CHECH(-VE) CHECK SAVED OVERWRITES ←
  BUFF
SEFM912 * APPLICATION    10          0          0          ←
0  10
SEFM912 * DBMS CHECK     0          0          0          ←
0  0
SEFM912 * SYSMAIN        0          0          0          ←
0  0
SEFM912 * SYSTEM FILE    2          0          0          ←
0  2
SEFM912 * PROGRAM        0          0          0          ←
0  0
SEFM912 * BROKER         0          0          0          ←
0  0
SEFM912 * NET-WORK       0          0          0          ←
0  0
SEFM912 * SQL SERVER     0          0          0          ←
0  0

```

Action

No action is required for this informational message.

SEFM913	* No active users found in SAF {Server Gateway Security Kernel}
Explanation	No active users were found in Entire Net-Work SAF Security Interface (ADASAF) or in the SAF Security Kernel.
Action	No action is required for this informational message.
SEFM914	* Requested user {userid} not found in SAF {Server Gateway Security Kernel}
Explanation	The requested user was not found in the Entire Net-Work SAF Security Interface (ADASAF) or in the SAF Security Kernel.
Action	No action is required for this informational message.
SEFM915	SEFM915 * SAF Security Kernel - snap of server memory
Explanation	This message is issued in response to an SSNAP operator command and is followed by a sequence of SEFM916 messages.
Action	No action is required for this informational message.
SEFM916	* {hhhhhhhh hhhhhhhh hhhhhhhh hhhhhhhh hhhhhhhh.x.X.Y}/
Explanation	This message contains the results of an SSNAP command. Each SSNAP snaps up to 256 bytes and shows the address, the hexadecimal storage contents, and the interpretation.
Action	No action is required for this informational message.
SEFM918	* Supplied address is outside of legal range
Explanation	An attempt was made to snap storage outside the bounds of the SAF Kernel's cache.
SEFM919	*Operator command did not contain required arguments
Explanation	A required parameter was omitted from an operator command. For example, SUSTAT with no userid specified.
Action	Correct the operator command and try again.
SEFM920	SSNAP, SSTAT, SUSERS, SUSTAT, SREST, SNEWCOPY, SLOGOFF, STRACE
Explanation	This message is issued in response to an SHELP operator command and lists the valid SAF Kernel operator commands.
Action	No action is required for this informational message.

SEFM921	* Memory allocation failure - users cannot be logged off
Explanation	The SAF Kernel was unable to obtain temporary storage (approximately 16Kb) to log users off in response to an SREST , SNEWCOPY or SLOGOFF operator command.
Action	Increase the region size.
SEFM922	* User {userid} logged off
Explanation	This message is issued in response to an SLOGOFF operator command. The indicated user has been logged off from the security system.
Action	No action is required for this informational message.
SEFM923	* User {userid} not logged off - user not found
Explanation	This message is issued in response to an SLOGOFF operator command. The requested user could not be found in the SAF Kernel's cache.
Action	Verify the correct user ID was specified.
SEFM924	* User {userid} not logged off - return code {ZZ}
Explanation	This message is issued in response to an SLOGOFF operator command. An internal error (indicated by ZZ) occurred while attempting to log the requested user off.
Action	Evaluate the return code to determine the cause of the error.
SEFM928	* Invalid trace setting - must be 0, 1, 2 or 3
Explanation	The STRACE operator command was issued with an invalid trace setting.
Action	Correct the trace setting and try again.
SEFM929	* Invalid SAF Security Kernel operator command
Explanation	An invalid SAF Security Kernel operator command was entered.
Action	Specify a valid SAF Security Kernel operator command.

73

SM-PIN* - PIN Routine Messages

This section describes the messages produced in the plug-in (PIN) modules of the error handling and message buffering facility.

SM-PINTAUTOR1 File number not found in thread

Explanation An autorestart error occurred and PINAUTOR attempted to exclude the file from autorestart processing. Because the file number is not contained in the thread, it is not possible to exclude the file and the nucleus terminates.

Action Follow normal procedures for the parameter error 31 message.

SM-PINAUTOR2 Will exclude file {file-number} from autorestart

Explanation The parameter error 31 message is related to the file number indicated in the message. The file has now been excluded from autorestart processing and an attempt will be made to perform autorestart without the file.

Action An excluded file may become inconsistent and need to be restored from a backup using ADASAV RESTORE.

SM-PINAUTOR3 Maximum number of files excluded from autorestart

Explanation The maximum number of files allowed to be excluded has been exceeded.

Action Adjust the number of files allowed for exclusion in ADASMXIT and retry autorestart, or restore and regenerate your database.

SM-PINAUTOR4 File or response code invalid for exclusion

Explanation The file or response code has been specified as ineligible for exclusion in ADASMXIT.

Action Modify the ADASMXIT table to allow the response code or file and retry autorestart or follow the same recovery guidelines as for a parameter error 31.

SM-PINAUTOR5 Not possible to exclude RSP {response-code}

Explanation The response code encountered may not be excluded

Action Follow the recovery guidelines as specified for a parameter error 31

SM-PINAUTOR6 Cannot exclude system file

Explanation The error relates to the checkpoint or security file. It is not possible to exclude either of these files.

Action Follow the recovery guidelines as outlined for a parameter error 31.

74 XTS* - Software AG Internal Transport Subsystem

Messages

▪ Warnings	1106
▪ Errors	1108
▪ Generic TCP/IP Messages	1122

The Software AG internal transport subsystem Messages and Codes documentation provides information for each warning and error message that you can encounter using the internal transport subsystem of Software AG products.

This documentation is organized as follows:

<i>Warnings</i>	Provides the message ID, message text, and a brief explanation for each warning message.
<i>Errors</i>	Provides the message ID, message text, and a brief explanation for each error message.
<i>Generic TCP/IP Messages</i>	Lists the message ID and message text for each generic TCP/IP error. For complete information on the TCP/IP error conditions, refer to your TCP/IP documentation.



Note: The internal component API returns warnings as positive values and errors as negative values.

Warnings

XTS0000W	XTS Success
Explanation	The transport subsystem processing completed successfully.
XTS0001W	XTS No LISTEN has been issued
Explanation	A server has only XTSconnect entries and no XTSlisten. It is possible for a server to connect only to a proxy, and the warning helps applications determine if XTSlisten is missing.
XTS0003W	XTS Load message file failed
Explanation	The transport subsystem failed to load the <i>XTS.MSG</i> file. This file contains text for the error messages; there is an internal table also, so <i>XTS.MSG</i> is not mandatory.
XTS0004W	XTS Client already registered
Explanation	Multiple <code>XtsBindClient</code> calls occurred for the same client. Only the first call is considered.

XTS0005W	XTS More data
Explanation	The receive buffer defined by a transport subsystem send and wait call is not big enough to get all data received by the transport subsystem. A subsequent call has to be made to receive all data.
XTS0006W	XTS No SSL random file warning
Explanation	There is no random file defined for a transport subsystem/Secure Sockets Layer (SSL) application; a random file usage by SSL is highly recommended.
XTS0007W	XTS Notify connect
Explanation	This is a receive callback notification for an incoming connection.
XTS0008W	XTS Notify disconnect
Explanation	This is a receive callback notification for a disconnection.
XTS0009W	XTS Notify broadcast
Explanation	This is a receive callback notification for a broadcast attempt.
XTS0010W	XTS Notify unsupported
Explanation	This is a receive callback notification when protocols set by XTSlisten are not supported.
XTS0011W	XTS Notify message reference dead
Explanation	This is a receive callback notification indicating the active message references are deleted when a client disconnects.
XTS0012W	XTS Notify outbound connect
Explanation	This is a receive callback notification for an outbound connection.
XTS0013W	XTS Notify listen failure
Explanation	This is a notification to the callback routine submitted by XtsRegisterByTargetName or XtsRegisterByTargetId indicating a failure of an XTSlisten URL.

XTS0014W **XTS Notify connect failure**
Explanation This is a notification to the callback routine submitted by `XtsRegisterByTargetName` or `XtsRegisterByTargetId` indicating a failure of an XTSconnect URL.

XTS0015W **XTS Notify end broadcast**
Explanation This is a notification to the callback routine submitted by `XtsRegisterByTargetName` or `XtsRegisterByTargetId` indicating an end broadcast message was received from another node.

Errors

XTS0050E **XTS Semaphore Error**
Explanation A failure to create a semaphore occurred. Contact Software AG customer support.

XTS0051E **XTS Memory Allocation Error**
Explanation A failure to allocate memory occurred. Contact Software AG customer support.

XTS0052E **XTS Server already registered**
Explanation The transport subsystem server is already registered.

XTS0053E **XTS Incorrect URL**
Explanation A URL with a syntax error was encountered. Check the Directory Server repositories.

XTS0054E **XTS Failure Loading Protocol Handler**
Explanation A failure to load protocol handlers (for example, `Xtstcp.lib`) occurred. It was probably caused by a configuration problem. Contact Software AG customer support.

XTS0055E **XTS Protocol Init failed**
Explanation A protocol initialization failure occurred. Contact Software AG customer support.

XTS0056E	XTS Invalid protocol type
Explanation	The specified protocol is not supported by the transport subsystem. This is possibly and error in URL syntax.
XTS0057E	XTS Listen Failed
Explanation	A listen failed. Check the log file for protocol-specific errors. This is caused mostly by trying to listen on a port taken by another server.
XTS0058E	XTS Accept Failed
Explanation	The accept failed. Check the log file for protocol-specific errors.
XTS0059E	XTS Connect Failed
Explanation	The connect failed. Check the log file for protocol-specific errors.
XTS0060E	XTS No directory information
Explanation	No XTSaccess information is provided for the server to which the application wants to connect. Please add a target definition through the Directory Server.
XTS0061E	XTS Failure to create a thread
Explanation	A failure to create a thread occurred. Contact Software AG customer support
XTS0062E	XTS Timeout error
Explanation	A failure to connect or send data in the time set by the user occurred. To complete the connect or send, repeat the call or increase the timeout value.
XTS0063E	XTS Send Failed
Explanation	A completion code is returned to the send callback routine when send fails. Check the log file for the protocol-specific error code.
XTS0064E	XTS Invalid reference
Explanation	An invalid message reference was passed by the user.

XTS0065E	XTS Send incomplete
Explanation	A send was interrupted by a client disconnection.
XTS0066E	XTS No such server
Explanation	A nonexistent server name was passed by the user. It applies to the transport subsystem statistics and dumps calls.
XTS0069E	XTS Resolve Target failed
Explanation	The client failed to send a handshake message to the server; Error caused by the server going down or a protocol send error.
XTS0070E	XTS Resolve Target Reply failed
Explanation	The server failed to reply to the client during handshaking. This error is caused by the client going down or by a protocol send error.
XTS0071E	XTS Target cannot be resolved
Explanation	The client failed to resolve the target name. This error is caused by different names used by the server and the client but with the same address.
XTS0072E	XTS Not initialized
Explanation	The transport subsystem call was submitted before the transport subsystem was initialized. Errors were returned by XtsShutdown, XtsSendMessageByRT, and the transport subsystem statistics call.
XTS0073E	XTS Bind Client failed
Explanation	The client bind failed because of a protocol send error or because the server went down.
XTS0074E	XTS Too many user threads
Explanation	The number of user threads in existence reached the maximum (64). Stop creating new user threads or reduce their time to live (timeout).

XTS0075E	XTS Created thread failed
Explanation	The transport subsystem failed to create a new user thread. This is an SMP error, possibly because of the limitations of the number of threads that a system can support. Contact Software AG customer support.
XTS0077E	XTS Conversion failed
Explanation	The conversion between wide character and MBNS failed. Contact Software AG customer support.
XTS0078E	XTS No Target Name
Explanation	The target name is a zero pointer. Pass a valid string.
XTS0079E	XTS No Client Name
Explanation	The client name is a zero pointer. Pass a valid string.
XTS0082E	XTS Zero Length not accepted
Explanation	The length of the data to be sent is zero, Make the length a positive number.
XTS0083E	XTS Target ID Out of Range
Explanation	The target ID value is bigger than "2113929215".
XTS0084E	XTS Channel Inactive
Explanation	The server-client connection was no longer active when XtsSendByRt or XtsBindClient were called. This error is generated by a client going down during the call.
XTS0085E	XTS Disconnect message
Explanation	A client or server disconnection was detected during a transport subsystem call.
XTS0086E	XTS Hash table error
Explanation	An internal transport subsystem hash table error occurred. Contact Software AG customer support.

XTS0087E	XTS Thread key error
Explanation	An allocate/delete thread memory failure occurred. Contact Software AG customer support.
XTS0088E	XTS No CONNECT or LISTEN has been issued
Explanation	A server registration failed to submit at least one listen or connect. Check the XTSlisten or XTSconnect URL parameters.
XTS0089E	XTS Protocol not supported
Explanation	An attempt was made to use XtsBindClient over the RAW or XTSDS protocol. This feature is not supported.
XTS0090E	XTS Single Thread not supported
Explanation	This error code is returned when the transport subsystem call does not support the single thread feature. Examples include XtsRegisterServerByName(ID) and XtsGiveThread.
XTS0094E	XTS Zero pointer
Explanation	A zero pointer was passed by the user. This is an invalid value.
XTS0095E	XTS Hash table full
Explanation	An internal transport subsystem hash table error occurred. Contact Software AG customer support.
XTS0096E	XTS Send User Exit failed
Explanation	The user exit send routine failed. Check the user exit code.
XTS0097E	XTS Recv User Exit failed
Explanation	The user exit receive routine failed. Check the user exit code.
XTS0098E	XTS Load User Exit failed
Explanation	The transport subsystem failed to load the user exit library. Check the environment or the user exit routine names.

XTS0100E	XTS Shutdown in process
Explanation	This error code is returned when the transport subsystem is in shutdown mode (because XtsShutdown was called by another thread).
XTS0101E	XTS Route Timeout
Explanation	The proxy cannot deliver the message because the route timeout was insufficient. Change the route timeout.
XTS0102E	XTS Route Table overflow
Explanation	The proxy cannot deliver the message because of a route table overflow. Repeat the transport subsystem call.
XTS0103E	XTS Route TTL expired
Explanation	The proxy cannot deliver the message because the route time to live was insufficient. Change the time to live time.
XTS0104E	XTS Route failed
Explanation	The proxy cannot deliver the message because of a route failure. Repeat the transport subsystem call.
XTS0105E	XTS Null parameter
Explanation	A null parameter is encountered when a notify callback routine registration is called.
XTS0106E	XTS Connection Rejected
Explanation	The connection was rejected by the notify callback routine.
XTS0107E	XTS Replica redirected
Explanation	The connection was redirected by the callback routine.
XTS0108E	XTS timeout - connect in progress
Explanation	A timeout error occurred, but connection is in progress. Submit the call again or increase the timeout value.

XTS0109E	XTS invalid session
Explanation	An invalid session handle was used by the transport subsystem session calls.
XTS0110E	XTS invalid key
Explanation	An invalid session handle was used by the transport subsystem session calls.
XTS0111E	XTS Count converters failed
Explanation	The count of available converter names failed.
XTS0112E	XTS Convert enum failed
Explanation	The enumeration of text converter names failed.
XTS0113E	XTS Buffer too small
Explanation	The text conversion buffer is not big enough..
XTS0114E	XTS No more ports available
Explanation	No replicated server ports are available .
XTS0115E	XTS Text converter library load failed
Explanation	The load of the transport subsystem converter ending failed.
XTS0116E	XTS Text converter resolve failed
Explanation	The text converter interface function could not be resolved.
XTS0117E	XTS Name to EDDkey map failed
Explanation	The ICU converter name to Software AG ECS EDD key conversion failed..
XTS0118E	XTS XDS library loading failed
Explanation	The XDS library used by ADVDIR could not be loaded.

XTS0119E	XTS DS access time out error
Explanation	A timeout occurred accessing the Directory Server (the default timeout is one minute).
XTS0120E	XTS Failed to set ECS environment
Explanation	A failure occurred when setting the ECS environment.
XTS0121E	XTS Set UDP Port failed
Explanation	The UDP port selected by user cannot be used (because it is used by another application).
XTS0122E	XTS Sync and async send in raw mode not allowed
Explanation	Using synchronous and asynchronous calls on the same channel is not allowed.
XTS0123E	XTS Unknown received buffer
Explanation	The transport subsystem received an unknown buffer from an application.
XTS0124E	XTS Function retired
Explanation	The transport subsystem function is not supported any longer.
XTS0126E	XTS invalid duplicate server
Explanation	This error is generated when the same server is registered again with a different protocol than the one used when it was first registered.
XTS0127E	XTS Fatal error
Explanation	An internal error occurred, indicating a severe transport subsystem code problem. Contact Software AG customer support.
XTS0128E	XTS Load library failed
Explanation	The transport subsystem failed to load a library (the log file indicates which one).

XTS0129E	XTS Key not found
Explanation	The key used to retrieve transport subsystem parameters does not exist.
XTS0130E	XTS Xts.Config Key not found
Explanation	The key used by the user to retrieve transport subsystem parameters from <i>xts.config</i> file does not exist.
XTS0131E	XTS No directory information for XTS profile
Explanation	The profile is not defined in the Directory Server.
XTS0132E	XTS Load function failed
Explanation	A failure occurred loading a function (the name of the function and the name of the library are in the log file).
XTS0150E	XTS SSL init failed
Explanation	The transport subsystem failed to initialize the Secure Sockets Layer (SSL) library. Check the log file for the SSL error messages.
XTS0151E	XTS SSL Verify CA locations failed
Explanation	The Secure Sockets Layer (SSL) failed to load the CA certificates. Probable causes include an invalid path specification or nonexistent CA certificates.
XTS0152E	XTS SSL Certificate file not specified
Explanation	No Secure Sockets Layer (SSL) certificate was specified.
XTS0153E	XTS SSL Invalid Certificate
Explanation	The URL-specified Secure Sockets Layer (SSL) certificate has an invalid format.
XTS0154E	XTS SSL Invalid Key File
Explanation	The URL-specified Secure Sockets Layer (SSL) key file has an invalid format.

XTS0155E	XTS SSL Invalid Key
Explanation	The Secure Sockets Layer (SSL) key specified by the user is invalid.
XTS0156E	XTS SSL Connect failed
Explanation	A Secure Sockets Layer (SSL) connect failed (caused by an SSL handshaking error). Check the log file for the Secure Sockets Layer (SSL) error messages.
XTS0157E	XTS SSL Accept failed
Explanation	A Secure Sockets Layer (SSL) accept failed (caused by an SSL handshaking error). Check the log file for the SSL error messages.
XTS0158E	XTS SSL Read failed
Explanation	A Secure Sockets Layer (SSL) read failed. Check the log file for the SSL error messages.
XTS0159E	XTS SSL Write failed
Explanation	A Secure Sockets Layer (SSL) write failed. Check the log file for the SSL error messages.
XTS0163E	XTS SSL Failed loading library
Explanation	A failure to load the Secure Sockets Layer (SSL) library occurred. Check the environment.
XTS0167E	XTS SSL Illegal host name
Explanation	The peer certificate subject name and host name are different, indicating an illegal connection.
XTS0168E	XTS SSL No local certificate
Explanation	There is no local Secure Sockets Layer (SSL) certificate.
XTS0169E	XTS SSL No remote certificate
Explanation	There is no local Secure Sockets Layer (SSL) certificate.

XTS0170E	XTS SSL insufficient user memory
Explanation	There is insufficient user memory for returning the requested data.
XTS0171E	XTS SSL certificate rejected
Explanation	The certificate was rejected during verification.
XTS0172E	XTS SSL zero length message return
Explanation	The Secure Sockets Layer (SSL) write or read routines returned an invalid zero value. Contact Software AG customer support.
XTS0173E	XTS SSL want read error
Explanation	The Secure Sockets Layer (SSL) write routine returned want read error code. Contact Software AG customer support. This is a transport subsystem internal sequence error.
XTS0174E	XTS SSL want write error
Explanation	The Secure Sockets Layer (SSL) read routine returned want write error code. Contact Software AG customer support. This is a transport subsystem internal sequence error.
XTS0200E	DS Open File failed
Explanation	A failure to open a file occurred. Check if the file exists and that the path is correct.
XTS0201E	DS Incomplete Entry
Explanation	A URL syntax error occurred. Check the log file for detailed information.
XTS0203E	DS Service not provided
Explanation	An invalid Directory Service selection was made.
XTS0204E	DS Null parameter
Explanation	A Directory Service call was encountered with a null parameter.

XTS0205E	DS Incomplete Entry
Explanation	An attempt to add an incomplete URL record was made.
XTS0206E	DS Topic Not Defined
Explanation	The user tried to use a qualifier unknown to the Directory Server.
XTS0207E	DS Unknown request
Explanation	An unknown XTSDS request was encountered. Check the syntax of the Directory Server call.
XTS0208E	DS No Entries
Explanation	The Directory Server or configuration file contains no entries for the specified target.
XTS0209E	DS Delete Failed
Explanation	A Directory Service delete call failed. Check the log file for detailed information.
XTS0210E	DS Connection Failed
Explanation	Connection to the Directory Server failed.
XTS0211E	DS Bind Failed
Explanation	Deprecated message.
XTS0212E	DS Search Failed
Explanation	Retrieve URL command failed.
XTS0213E	DS Add Failed
Explanation	Addition of a new URL failed.
XTS0214E	DS Already Exists
Explanation	An attempt was made to add a record that already exists.

XTS0215E	DS Failure Loading Service Handler
Explanation	A failure occurred loading a directory service. Check the environment. Contact Software AG customer support.
XTS0216E	DS Wrong directory parameter
Explanation	Unknown directory parameter.
XTS0217E	DS not Initialized
Explanation	Directory Server was not initialized before usage.
XTS0218E	DS Invalid target Name
Explanation	The target name contains one of the following characters: "#", ".", "[", "]", "=", "\", "\", or "*". The target name is invalid.
XTS0219E	DS Incomplete request
Explanation	An incomplete XTSDS request was caused by a zero value of the target, qualifier, or user data.
XTS0220E	DS No URL entries
Explanation	The XTSDS server does not have any URL to return for the retrieve call.
XTS0221E	DS XDS error
Explanation	An XDS processing error occurred..
XTS0222E	DS Rollback is not implemented
Explanation	No Directory Service rollback was performed..
XTS0223E	DS OVO error
Explanation	An OVO error occurred during Directory Service processing.

XTS0224E	DS One time set violation
Explanation	A one-time setting function was called multiple times. A programs encoding mode cannot change once it is set.
XTS0225E	DS Encoding conflict
Explanation	The INIDIR file encoding conflicts with programs encoding.
XTS0226E	DS Create file failed
Explanation	The file creation failed during Directory Service processing..
XTS0227E	DS IO file failed
Explanation	A file I/O error occurred during Directory Service processing.
XTS0228E	DS Wrong file format`
Explanation	The INIDIR file format was not recognized.
XTS0229E	DS Send buffer bigger than maximum allowed
Explanation	An internal transport subsystem error occurred, generated when a URL is added or deleted from the Directory Server and its size exceeds 65520 bytes.
XTS0230E	DS Invalid Service
Explanation	Invalid type of service used.
XTS0231E	DS Invalid Header
Explanation	Invalid Directory Service header used for communication.
XTS1000E	XTS Unknown error = {code}
Explanation	This message is returned by XtsGetMessage when it cannot find text for a given error code.

Generic TCP/IP Messages

XTS1001E	TCP/IP Operation not permitted
XTS1002E	TCP/IP No such file or directory
XTS1003E	TCP/IP No such process
XTS1004E	TCP/IP Interrupted function call
XTS1005E	TCP/IP I/O error
XTS1006E	TCP/IP No such device or address
XTS1007E	TCP/IP Arg list too long
XTS1008E	TCP/IP Exec format error
XTS1009E	TCP/IP Bad file number
XTS1010E	TCP/IP No children
XTS1011E	TCP/IP Operation would cause deadlock
XTS1012E	TCP/IP Not enough core
XTS1013E	TCP/IP Permission denied

XTS1014E	TCP/IP Bad address
XTS1015E	TCP/IP Block device required
XTS1016E	TCP/IP Mount device busy
XTS1017E	TCP/IP File exists
XTS1018E	TCP/IP Cross-device link
XTS1019E	TCP/IP No such device
XTS1020E	TCP/IP Not a directory
XTS1021E	TCP/IP Is a directory
XTS1022E	TCP/IP Invalid argument
XTS1023E	TCP/IP File table overflow
XTS1024E	TCP/IP Too many open sockets
XTS1025E	TCP/IP Inappropriate ioctl for device
XTS1026E	TCP/IP Text file busy
XTS1027E	TCP/IP File too large

XTS1028E	TCP/IP No space left on device
XTS1029E	TCP/IP Illegal seek
XTS1030E	TCP/IP Read-only file system
XTS1031E	TCP/IP Too many links
XTS1032E	TCP/IP Broken pipe
XTS1033E	TCP/IP Argument too large
XTS1034E	TCP/IP Result too large
XTS1035E	TCP/IP Resource temporarily unavailable
XTS1036E	TCP/IP Operation now in progress
XTS1037E	TCP/IP Operation already in progress
XTS1038E	TCP/IP Socket operation on non-socket
XTS1039E	TCP/IP Destination address required
XTS1040E	TCP/IP Message too long
XTS1041E	TCP/IP Protocol wrong type for socket

XTS1042E	TCP/IP Bad protocol option
XTS1043E	TCP/IP Protocol not supported
XTS1044E	TCP/IP Socket type not supported
XTS1045E	TCP/IP Operation not supported
XTS1046E	TCP/IP Protocol Family not supported
XTS1047E	TCP/IP Address family not supported by protocol family
XTS1048E	TCP/IP Address already in use
XTS1049E	TCP/IP Cannot assign requested address
XTS1050E	TCP/IP Network is down
XTS1051E	TCP/IP Network is unreachable
XTS1052E	TCP/IP Network dropped connection on reset
XTS1053E	TCP/IP Software caused connection abort
XTS1054E	TCP/IP Connection reset by peer
XTS1055E	TCP/IP No buffer space available

XTS1056E	TCP/IP Socket is already connected
XTS1057E	TCP/IP Socket is not connected
XTS1058E	TCP/IP Cannot send after socket shutdown
XTS1059E	TCP/IP Too many references
XTS1060E	TCP/IP Connection timed out
XTS1061E	TCP/IP Connection refused
XTS1062E	TCP/IP Too many levels of symbolic links
XTS1063E	TCP/IP File name too long
XTS1064E	TCP/IP Host is down
XTS1065E	TCP/IP No route to host
XTS1066E	TCP/IP Directory not empty
XTS1067E	TCP/IP Too many processes
XTS1068E	TCP/IP Too many users
XTS1069E	TCP/IP Disc quota exceeded

XTS1070E	TCP/IP Stale NFS file handle
XTS1071E	TCP/IP Too many levels of remote in path
XTS1072E	TCP/IP Device not ready
XTS1073E	TCP/IP Write-protected media
XTS1074E	TCP/IP Unformatted media
XTS1075E	TCP/IP No connection
XTS1076E	TCP/IP Old, currently unused AIX errno
XTS1077E	TCP/IP Restart the system call
XTS1078E	TCP/IP Invalid file system control data
XTS1079E	TCP/IP Media surface error
XTS1080E	TCP/IP I/O completed, but needs relocation
XTS1081E	TCP/IP No attribute found
XTS1082E	TCP/IP Out of STREAM resources
XTS1083E	TCP/IP System call timed out

XTS1084E	TCP/IP Next message has wrong type
XTS1085E	TCP/IP Protocol error
XTS1086E	TCP/IP No message on stream read queue
XTS1087E	TCP/IP fd not associated with a stream
XTS1088E	TCP/IP Security authentication denied
XTS1089E	TCP/IP Not a trusted program
XTS1090E	TCP/IP Illegal byte sequence
XTS1091E	TCP/IP Network subsystem is unavailable
XTS1092E	TCP/IP WINSOCK.DLL version out of range
XTS1093E	TCP/IP Successful WSAStartup not yet performed
XTS1094E	TCP/IP Cross mount point (not really error)
XTS1095E	TCP/IP cannot start operation
XTS1096E	TCP/IP Cannot access a needed shared library
XTS1097E	TCP/IP operation (now) in progress

XTS1098E	TCP/IP Lib section in a.out corrupted
XTS1099E	TCP/IP Attempting to link in too many shared libraries
XTS1100E	TCP/IP Cannot exec a shared library directly
XTS1101E	TCP/IP Graceful shutdown in progress
XTS1102E	TCP/IP Streams pipe error
XTS1103E	TCP/IP Structure needs cleaning
XTS1104E	TCP/IP Not a XENIX named tip file
XTS1105E	TCP/IP No XENIX semaphores available
XTS1106E	TCP/IP Is a named type file
XTS1107E	TCP/IP Remote I/O error
XTS1108E	TCP/IP No medium found
XTS1109E	TCP/IP Wrong medium type
XTS1111E	TCP/IP Host not found
XTS1112E	TCP/IP Non-authoritative host not found

XTS1113E	TCP/IP This is a non-recoverable error
XTS1114E	TCP/IP Valid name, no data record of requested type
XTS1115E	TCP/IP Resource unavailable
XTS1116E	TCP/IP Operation canceled
XTS1118E	TCP/IP Disc quota exceeded
XTS1119E	TCP/IP Identifier removed
XTS1120E	TCP/IP Too many open files
XTS1122E	TCP/IP Multihop attempted
XTS1123E	TCP/IP No locks available
XTS1124E	TCP/IP The link has been severed
XTS1125E	TCP/IP No message of the desired type
XTS1126E	TCP/IP Function not supported
XTS1127E	TCP/IP Directory not empty
XTS1128E	TCP/IP Operation not supported

XTS1129E	TCP/IP Value too large to be stored in data
XTS1130E	TCP/IP Stale NFS file handle
XTS1131E	TCP/IP There is no more data available
XTS1132E	TCP/IP The call has been canceled
XTS1133E	TCP/IP Invalid procedure table from service provider
XTS1134E	TCP/IP Invalid service provider version number
XTS1135E	TCP/IP Unable to initialize a service provider
XTS1136E	TCP/IP System call failure
XTS1137E	TCP/IP Service not found
XTS1138E	TCP/IP Type not found
XTS1139E	TCP/IP There is no more data available
XTS1140E	TCP/IP The call has been canceled
XTS1141E	TCP/IP Refused
XTS1142E	TCP/IP Cbannel number out of range

XTS1143E	TCP/IP Level 2 not synchronized
XTS1144E	TCP/IP Level 3 halted
XTS1145E	TCP/IP Level 3 reset
XTS1146E	TCP/IP Link number out of range
XTS1147E	TCP/IP Protocol driver not attached
XTS1148E	TCP/IP No 43 CSI structure available
XTS1149E	TCP/IP Level 2 halted
XTS1150E	TCP/IP Invalid exchange
XTS1151E	TCP/IP Invalid request descriptor
XTS1152E	TCP/IP Exchange full
XTS1153E	TCP/IP No anode
XTS1154E	TCP/IP Invalid request code
XTS1155E	TCP/IP Invalid slot
XTS1156E	TCP/IP File locking deadlock error

XTS1157E	TCP/IP Bad fon file fmt
XTS1158E	TCP/IP Process died with the lock
XTS1159E	TCP/IP Lock is not recoverable
XTS1160E	TCP/IP Machine is not on the network
XTS1161E	TCP/IP Package not installed
XTS1162E	TCP/IP The object is remote
XTS1163E	TCP/IP Advertise error
XTS1164E	TCP/IP Mount error
XTS1165E	TCP/IP Communication error on send
XTS1166E	TCP/IP Locked lock was unmapped
XTS1167E	TCP/IP Name not unique on network
XTS1168E	TCP/IP FD invalid for this operation
XTS1169E	TCP/IP Remote address changed

XIII

Utility Messages and Codes

The Adabas utilities issue return/condition codes, and may also display error messages. This chapter lists, alphabetically by utility, the utility error messages and describes the utility nonzero return codes.

Utility Error Messages

Utility messages are displayed following a title line showing the utility name. The message line itself is displayed, followed by the same "explanation" and/or "action" information shown in this chapter.

Variable information such as jobname, data set name, return code, abend code, or nucleus response code may occur in the message line or in the text following the actual message. These variables are represented in lowercase as either "xxx...xxx" or as "reason", "nucleus-response", "job-name", "ret-code", and so on. In the actual message these notations are replaced with the actual values. Generally, variables within parentheses () are hexadecimal and those without parentheses are decimal.

When a message includes a nucleus response or abend code, the specific code description identifies the cause. See the description of [nucleus response codes](#) and [abend codes](#).

Utility Return Codes

When an Adabas utility returns control to the operating system and no abend has occurred, the utility writes a return codes in the rightmost positions of general register 15:

Code	The utility operation ...
0	was successful.
4	was successful but encountered a warning condition.
8	was not successful.



Note: Utilities that terminate with return code 4 write "...terminated with warning" as the last message. This indicates that, although the utility function completed successfully, circumstances may have rendered the result of the function different from that which was expected. The job protocol contains one or more related warning or error messages.

Return codes are supported by operating system as described in the following table:

Operating System	Return Code Support
z/OS	See the job control language reference manuals for job step condition code information.
z/VSE	Return codes are supported.
BS2000	Return codes are supported using job variables. For more information, see the Adabas Installation documentation, section <i>How to Manage Job Variables in the Adabas Environment</i> .

Depending on the operating system and the utility, the return code can be tested to determine the utility job status:

- A zero return code always indicates successful completion of the utility.
- The meanings of return codes 4 or 8 depend on the utility in operation at the time.

These unsuccessful return code (RC) meanings are described here in alphabetical order by Adabas utility.

ADAACK Return Codes

Return Code 4

Explanation

One of the following occurred:

- Warning: The last formatted ISN is not set.
- Warning: The last formatted AC2 ISN is not set.

Return Code 4 or 8

Explanation Database inconsistency.

ADACHK Return Codes**Return Code 0**

Explanation ADACHK was successful.

Return Code 4

Explanation ADACHK was successful but encountered a warning condition.

With the ADACHK utility, a return code of 4 indicates that either the number of unreachable index blocks is greater than zero or any `CHKnnnW` (warning) message was received.

Return Code 8

Explanation ADACHK encountered an error condition but then continued.

With the ADACHK utility, a return code of 8 indicates that a database inconsistency was encountered.

Return Code 20

Explanation The function could not be completed.

The operation encountered an error condition but did not terminate abnormally because `NOUSERABEND` was specified.

ADACMP Return Codes**Return Code 4**

Explanation One of the following occurred:

- At least one rejected record occurred during processing.
- The utility has processed only the base file of a LOB group (a base file and its associated LOB file) without the associated LOB file.

Return Code 8

Explanation The utility detected inconsistencies between the files in a LOB group (a base file and its associated LOB file).

ADADBS Return Codes

Return Code 4

Explanation One of the following occurred:

- CHANGE, NEWFIELD, or RELEASE: The operation was performed on a component file of an expanded file. The other component files must be processed explicitly.
- MODFCB DATAPFAC: The Data Storage padding factor (DATAPFAC) setting is ignored for files containing spanned records. The following warning will also appear if DATAPFAC is specified for a file that has data storage spanning enabled:

```
*****DATAPFAC is ignored for files with spanned data storage ↵  
enabled*****
```

- MODFCB MAXRECL: The MAXRECL must be the same for all component files.
- OPERCOM ADAEND/CANCEL: The Adabas nucleus was not active.
- OPERCOM CLUFREEUSER: One or more otherwise eligible UTEs were not deleted because they were due a response code 9 (ADARSP009), subcode 20, and FORCE was not specified.
- OPERCOM DUQE: The user queue element (UQE) for the specified user ID was not found.
- RESETDIB: The IDENT job name was not found.

Return Code 8

Explanation One of the following occurred:

- DELETE: The file to be deleted was not found.
- OPERCOM STOPU: The function received an Adabas response code.
- RELEASE: An invalid descriptor name was specified, or the function received an Adabas response code.

ADADEF Return Codes**Return Code 4**

Explanation NEWWORK: Attempt to write RLOG information or close RLOG data set failed.

ADADCK Return Codes**Return Code 4 or 8**

Explanation Database inconsistency.

ADAICK Return Codes**Return Code 4**

Explanation One of the following occurred:

- GETMAIN failed.
- ICHECK detected WARNING-163 (unreachable index blocks).
- Warning-171: The last formatted ISN is not set.
- Warning-171: The last formatted AC2 ISN is not set.

Return Code 8

Explanation Database inconsistency.

ADAINV Return Codes**Return Code 4**

Explanation One of the following occurred:

- The utility's DIB entry was removed by another user during ADAINV operation.
- (all functions) Attempt to write RLOG information or close RLOG database failed.
- ADAINV was restarted, but at least one of the descriptors to be inverted was already in the index. The index is correct.
- ADAINV INVERT was run on a component file of an expanded file. The other component files must be explicitly inverted.

ADALOD Return Codes

Return Code 4

Explanation

One of the following occurred:

- More DDEBAND records were available than specified by the NUMREC parameter.
- More DDEBAND records were available than ISNs for those records.
- The utility's DIB entry was removed by another user during ADALOD operation.
- The file to be loaded could not be added to the expanded file chain.
- (all functions) Attempt to write RLOG information or close RLOG data set failed.
- In an UPDATE function, the allocation of a file-specific DLOG extension failed. ADALOD completed the UPDATE function, but marked the whole file as changed; it did not log the Data Storage and address converter RABNs of blocks that were actually changed.
- The utility has processed files in a LOB group (a base file and its corresponding LOB file) that were incorrectly linked to each other or marked as being out-of-sync.
- The utility has been unable to establish or validate the base-to-LOB file linkage in a LOB group because one of the files was locked or otherwise unavailable.
- The utility has been unable to validate the base-to-LOB file consistency in a LOB group because some input records were not loaded due to the use of the SKIPREC/NUMREC parameters.
- The utility has processed a file in a LOB group (a base file and its corresponding LOB file) where Adabas has been unable to track whether the two files in the group have stayed in sync.

Return Code 8

Explanation

One of the following occurred:

- The input records loaded in a file in a LOB group (a base file and its associated LOB file) were unloaded from a file that had been marked as being out-of-sync with the other file.
- The file in a LOB group (a base file and its associated LOB file) that was loaded or updated had a different status with respect to LOB updates than the other file in the LOB group.
- Inconsistencies were detected in a LOB file from which LOB values were to be deleted.

ADAORD Return Codes

Return Code 4

Explanation

One of the following occurred:

- The utility's DIB entry has been removed by another user during ADAORD operation.
- (all functions) Attempt to write RLOG information or close RLOG data set failed.
- RESTRUCTURE functions: Initialization of RLOG processing failed.
- RESTRUCTUREDB: Attempt to initialize RLOG access failed.
- RESTRUCTUREF: Attempt to initialize RLOG access failed.
- A system file was excluded from ADAORD STORE operation.
- MAXRECL was specified for a component of an expanded file. Ensure that the same MAXRECL is specified for all components.
- Allocation of the DLOG extension failed.
- Nonzero return code received from ADARAC.
- The utility has processed files in a LOB group (a base file and its corresponding LOB file) that were incorrectly linked to each other or marked as being out-of-sync.

ADARAI Return Codes

Return Code 4

Explanation

ADARAI RECOVER cannot create the job control statements needed for the sequential file used during utility execution. The message "unknown file element" is returned and the RECOVER function completes with return code 4. The generated job control must then be edited. See message ADAR78.

ADAREP Return Codes

Return Code 4

Explanation

One of the following occurred:

- An overlap of file extents or of file extents and free space extents was detected.
- A gap between file extents or between file extents and free space extents was detected.
- A checkpoint contains an unknown checkpoint type or format.
- The field definition table (FDT) does not exist for the existing file control block (FCB).
- The FCB contains an invalid file number.

- A bad ISN/RABN length indicator was detected in the FCB.
- At least one parent field in the FDT has no corresponding special descriptor table (SDT) field.
- An invalid FDT/SDT length was detected.
- The count of coupled files is greater than 18.
- There are inconsistencies in the expanded file chain.
- The volume serial number could not be identified.
- For a report from an online save tape, either no protection log was specified, an invalid protection log was specified, or an error was encountered while processing the protection log.
- CPLIST or CPEXLIST was specified in conjunction with SAVETAPE.
- FROMDATE, TODATE, FROMSESSION, or TOSESSION was specified without CPLIST or CPEXLIST.
- NOCOUNT was not specified in conjunction with SAVETAPE.
- An error occurred converting the mirror table to version 7 format.
- All components of an expanded file did not have the same MAXRECL.
- The utility has processed files in a LOB group (a base file and its corresponding LOB file) that were incorrectly linked to each other or marked as being out-of-sync.

ADARES Return Codes

Return Code 4

Explanation

One of the following occurred:

- (all functions) Attempt to write RLOG information or close RLOG data set failed.
- COPY: A block count mismatch occurred.
- PLCOPY: Attempt to initialize RLOG access failed.
- PLCOPY: Attempt to open Adabas nucleus failed with a response code other than zero or 148 (ADARSP148).
- PLCOPY: No protection log data sets are currently at completion. No data will be copied or merged at this time.
- PLCOPY: Warning! The supplied input intermediate data set is empty. This should only happen on the initial run of ADARES. Processing continues.
- COPY/CLCOPY/PLCOPY: No records to be copied.
- COPY/PLCOPY/CLCOPY: The Associator data sets could not be opened; therefore, no checkpoints have been written.
- The point indicated by TOPLOG/TOBLK/TOCP could not be found.
- BACKOUT and REGENERATE: No records to be processed were found.

- REGENERATE found batch utility runs which must first be executed before REGENERATE can complete.
- The parallel participant table (PPT) indicates that there are currently no PLOGs to be copied for this cluster database.
- The parallel participant table (PPT) indicates that there are currently no CLOGs to be copied for this cluster database.
- The utility has processed a file in a LOB group (a base file and its corresponding LOB file) where Adabas has been unable to track whether the two files in the group have stayed in sync.

Return Code 8**Explanation**

One of the following occurred:

- (Adabas Delta Save Facility Facility) An error occurred in a PLCOPY or COPY function when processing the delta save images (DSIM) data set. Building the DSIM data set was discontinued. The PLCOPY or COPY function continued normally. RC 8 is also given in all cases where the DSIM data set is necessary but is not available or is not usable.
- REGENERATE or BACKOUT function determined that one or more files in the file list were in an inconsistent state; that is, in load, reorder, refresh, or restore status. Processing continues for all other files in the file list.

Return Code 16**Explanation**

An error occurred after the PLCOPY/CLCOPY function successfully closed the DD/SIAUS1 or DD/SIAUS2 data set. The error message is printed in DD/DRUCK.

ADASAV Return Codes**Return Code 4****Explanation**

One of the following occurred:

- (all functions) Attempt to write RLOG information or close RLOG data set failed.
- (Adabas Delta Save Facility Facility) The nucleus returned a response code after ET synchronization at the end of an online save operation, but the online save operation was nevertheless completed successfully. The response code was ignored by ADASAV.
- The utility's DIB entry was removed by another user during ADASAV operation.
- MERGE: Attempt to initialize RLOG access failed.
- REPLICATION FOR FILE file-number IS SWITCHED OFF BECAUSE REPLICATION IS NOT ACTIVE.

- RESTORE (database) or RESTORE GCB: Attempt to initialize RLOG access failed.
- RESTORE could not be performed for a file that was already present because OVERWRITE was not specified.
- RESTONL (database) or RESTONL GCB: Attempt to initialize RLOG access failed.
- SAVE could not be performed on a file that was inaccessible. The file is in load, refresh, reorder, or restore status.
- SAVE FILE: Attempt to initialize RLOG access failed.
- The utility has processed files in a LOB group (a base file and its corresponding LOB file) that were incorrectly linked to each other or marked as being out-of-sync.

Return Code 16

Explanation (Adabas Delta Save Facility Facility) An error occurred after a full or delta save operation completed successfully.

ADASEL Return Codes

Return Code 4

Explanation No records were found matching the selection criterion.

ADAULD Return Codes

Return Code 4

Explanation One of the following has occurred:

- No records were found using ADAULD selection criteria/values.
- UNLOAD: Attempt to initialize RLOG access failed.

Return Code 8

Explanation The nucleus returned a non-zero response code. Depending on the ERRLLIM parameter of ADAULD UNLOAD, the function may continue. Unloaded data can be used, but records may be missing depending on the particular response code returned.

ADAVL Return Codes**Return Code 4**

Explanation Not all files were validated.

Return Code 8

Explanation Database inconsistency.

ADAWRK Return Codes**Return Code 4**

Explanation No autorestart information available on Work Part 1

Return Code 8

Explanation Autorestart will not complete successfully .

Return Code 20

Explanation This return code is returned instead of an abend when the NOUSERABEND parameter is specified.

75

Errors Common to All Utilities

ERROR-001	Error occurred during opening input file DDKARTE : {reason}
Explanation	The cause is probably a misspelled keyword.
Action	Check the JCL; correct the error and rerun the job.
ERROR-002	I/O error occurred during read on file DDKARTE : {reason}
Explanation	The cause is probably a misspelled keyword.
Action	Check the JCL; correct the error and rerun the job.
ERROR-003	Parameter error, invalid utility name
Explanation	The cause is probably a misspelled keyword.
Action	Check the parameter input; correct the error and rerun the job.
ERROR-004	Parameter error, missing separator
Action	Correct the parameter error or supply the missing separator. Rerun the job.
ERROR-005	Parameter error, invalid syntax
Action	Supply the correct parameter value and rerun the job.
ERROR-006	Parameter error, keyword not unique
Action	Check the parameter input; supply the correct keyword in full length and rerun the job.

ERROR-007	Parameter error, unknown parameter
Explanation	The cause is probably a misspelled keyword.
Action	Check the parameter input; correct the error and rerun the job.
ERROR-008	Parameter error, unknown function
Explanation	The cause is probably a misspelled keyword.
Action	Check the parameter input; correct the error and rerun the job.
ERROR-009	Parameter error, too many values in a list
Action	Check the parameter input. Supply no more than the maximum number of parameter values permitted, and rerun the job.
ERROR-010	Invalid or missing level number
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-011	Invalid or missing field length
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-012	Missing '=' (equal sign)
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-013	Invalid or missing field option
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-014	Missing '(' (left parenthesis)
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.

ERROR-015	Missing ')' (right parenthesis)
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-016	Invalid or missing start position
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-017	Invalid or missing end position
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-018	More than one parent for sub-field/descriptor
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-019	More than 20 parents for super-field/descriptor
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-020	Only one parent for super-field/descriptor
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-021	Syntax error, invalid character found
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-022	Invalid or missing hyperdescriptor exit number or collating exit number
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.

ERROR-023	No or more than 20 parents for a hyperdescriptor
Action	See the ADACMP discussion in the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-024	Invalid field name
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-025	Reserved field name used
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-026	Invalid field format specification
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-027	Invalid or conflicting field options used
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-028	Invalid MU/PE repeat factor
Action	See the Adabas Utilities documentation for more information about field definition syntax. Correct the error and rerun the job.
ERROR-029	Multiple function keywords detected
Explanation	This utility performs only one function per execution.
Action	Check the parameter input; correct the error and rerun the job.
ERROR-030	Error occurred during execution of open ASSO : {reason}
Explanation	The cause is probably incorrect JCL (DDASSOR1, ..., DDASSOR5) or an inconsistent database.
Action	Investigate the cause of the error; correct it and rerun the job.

ERROR-031	Error occurred during execution of read ASSO : {reason} RABN : {nnnn} ({xxxxxxx})
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-032	Error occurred during execution of write ASSO : {reason} RABN : {nnnn} ({xxxxxxx})
Action	Investigate the cause of the error; correct it and rerun the job.
	Note: If this error occurs in a BS2000 environment when running ADAFRM, please check that the size of the container is track-rounded. For more information, read <i>Splitting Data Sets Across Volumes</i> under <i>BS2000 Device Types and Block Sizes</i> , in the <i>Adabas BS2000 Installation Guide</i> .
ERROR-033	Error occurred during execution of close ASSO : {reason}
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-034	Error occurred during execution of open DATA : {reason}
Explanation	The cause is probably incorrect JCL (DDDATAR1, ..., DDDATAR5) or an inconsistent database.
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-035	Error occurred during execution of read DATA : {reason} RABN : {nnnn} ({xxxxxxx})
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-036	Error occurred during execution of write DATA : {reason} RABN : {nnnn} ({xxxxxxx})
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-037	Error occurred during execution of close DATA : {reason}
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-038	Error occurred during execution of open WORK : {reason}
Explanation	The cause is probably incorrect JCL (DDWORKR1) or an inconsistent database.
Action	Investigate the cause of the error; correct it and rerun the job.

ERROR-039 Action	Error occurred during execution of read WORK : {reason} RABN : {nnnn} ({xxxxxxxx}) Investigate the cause of the error; correct it and rerun the job.
ERROR-040 Action	Error occurred during execution of write WORK : {reason} RABN : {nnnn} ({xxxxxxxx}) Investigate the cause of the error; correct it and rerun the job.
ERROR-041 Action	Error occurred during execution of close WORK : {reason} Investigate the cause of the error; correct it and rerun the job.
ERROR-042 Explanation Action	Error occurred during execution of open TEMP : {reason} The cause is probably incorrect job control (DD/TEMPR1). Investigate the cause of the error; correct it and rerun the job.
ERROR-043 Action	Error occurred during execution of read TEMP : {reason} RABN : {nnnn} ({xxxxxxxx}) Investigate the cause of the error; correct it and rerun the job.
ERROR-044 Action	Error occurred during execution of write TEMP : {reason} RABN : {nnnn} ({xxxxxxxx}) Investigate the cause of the error; correct it and rerun the job.
ERROR-045 Action	Error occurred during execution of close TEMP : {reason} Investigate the cause of the error; correct it and rerun the job.
ERROR-046 Explanation Action	Error occurred during execution of open SORT : {reason} The cause is probably incorrect job control (DD/SORTR1 or DD/SORTR2). Investigate the cause of the error; correct it and rerun the job.
ERROR-047 Action	Error occurred during execution of read SORT : {reason} RABN : {nnnn} ({xxxxxxxx}) Investigate the cause of the error; correct it and rerun the job.
ERROR-048 Action	Error occurred during execution of write SORT : {reason} RABN : {nnnn} ({xxxxxxxx}) Investigate the cause of the error; correct it and rerun the job.

ERROR-049	Error occurred during execution of close SORT : {reason}
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-051	Error occurred during execution of open {dataset/file} : {reason}
Explanation	The cause is probably incorrect JCL.
Action	The correct JCL must be supplied to the function. Please also ensure that the DEVICE parameter is correct. If this is for a PLCOPY job and the PLOGs to be copied are from a cluster database, the NOPPT parameter should be specified. If no JCL is supplied or the open fails, the following will be displayed: "The Associator data set(s) could not be opened <i>nn - return code explanation</i> ." Processing continues. If you are using mixed devices for different data sets of the database when running the ADACNV utility, you might also specify the PLOGDEV parameter in the ADACNV run.
ERROR-052	Error occurred during execution of read {dataset}/{file} : {reason} RABN : {nnnn} ({xxxxxxxx})
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-053	Error occurred during execution of write {dataset/file} : {reason} RABN : {nnnn} (xxxxxxxx)}
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-054	Error occurred during execution of close {dataset/file} : reason}
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-055	Encoding key value exceeds maximum of 4095
Explanation	Valid encoding keys are in the range 1-4095.
Action	See the Adabas Utilities documentation for a list of valid encoding keys.
ERROR-057	Utility function not permitted by Adabas SAF Security
Explanation	Adabas is running with the Adabas SAF Security, which has been configured to provide protection at the utility function level (SAFCFG parameter UTI=2) or the utility function/file level (UTI=3). Adabas SAF Security has not permitted the execution of the specified utility function (if UTI=3, on the specified files) by the current user.
Action	Determine whether the current user ought to be able to execute the specified function (on the specified files) or whether this function should be run by another user (or not at all).

ERROR-058	Recover log not available
Explanation	The Adabas Recovery Aid is active, but an error occurred when the utility attempted to initialize RLOG data set processing.
Action	ADARAC returns reason code <i>rr</i> : reason text . See also the accompanying ADARxx message.
ERROR-059	Error during recovery logging
Explanation	The utility was not able to record its operation in the recovery log. The utility continues and will terminate with return code 4.
Action	ADARAC returns reason code <i>rr</i> : reason text . See also the accompanying ADARxx message.
ERROR-060	{blocks}-Extent space allocation failed for file {file-number(s)}
Explanation	An attempt to allocate an AC extent of size <i>blocks</i> for the file or files specified failed. Probable causes of the failure include <ul style="list-style-type: none"> ■ not enough free space available. ■ conflicting XXRABN parameter. ■ enough free space available, but not on devices that can satisfy the MAXRECL value for this file. ■ only one AC extent permitted. ■ If ISNSIZE=3, more than 16,777,215 (X'FF FF FF) ISNs; if ISNSIZE=4, more than 4,294,967,294 (X'FF FF FF FE) ISNs. ■ more than 5 extents.
Action	Correct the error and rerun the job.
ERROR-062	For file {filename} the sum of numbers of DATA extents, AC extents, UI extents, and NI extents is too big or DATA extent or AC extent is zero. Check ASSO RABN {rabn}
Explanation	A database problem exists. The sum of Data Storage, address converter (AC), and inverted list (UI and NI) extents is too large or the Data Storage or address converter extents are zero.
Action	Contact you Software AG technical support representative for assistance.

ERROR-064	Error writing DSST : {response-code}
Explanation	The nucleus returned response code "nn" while writing the DSST to the database. The file(s) being accessed remain(s) in an inaccessible state.
Action	Investigate the cause of the problem; correct the error and rerun the job.
ERROR-065	Database ID mismatch: the ADARUN DBID is {dbid-a} but the GCB contains DBID {dbid-b}
Explanation	One of the following occurred: <ul style="list-style-type: none">■ the wrong database was accessed; or■ an input parameter specified an incorrect database ID.
Action	Correct the error and rerun the job.
ERROR-066	File {file-number} is password protected
Explanation	A password-protected file "file-number" cannot be processed without the nucleus. The nucleus is required to access the Adabas security file and to validate the supplied password.
Action	Start the Adabas nucleus and rerun the job.
ERROR-067	Invalid or missing password for file {file-number}
Explanation	The requested file "file-number" is password protected.
Action	Supply the correct password and rerun the job.
ERROR-068	Utility communication block overflow
Explanation	Too many utilities are running in parallel.
Action	Inform your database administrator.
ERROR-069	Checkpoint block overflow
Explanation	The Associator block containing data for checkpoints written offline is filled.
Action	Start the nucleus to pick up information currently stored in the offline checkpoint area; then rerun the job.

ERROR-070	Error writing checkpoint: {response-code}
Explanation	The nucleus returned the specified response code while writing a checkpoint.
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-071	Invalid value for parameter {parm}. Only values "YES" or "NO" are allowed.
Explanation	An invalid parameter value was specified for the parameter named in the message (<i>parm</i>). The only valid values are "YES" or "NO".
Action	Supply the correct parameter value and rerun the job.
ERROR-072	Unexpected nucleus response {nucleus-response-code} {subcode}- {description}
Explanation	An unexpected nucleus response occurred. The Adabas response code, subcode, and a description of the problem are provided in the message. For more information about the response code, refer to <i>Adabas Response Codes</i> , elsewhere in this guide.
Action	Note and keep any related error information or output. Inform your DBA. If necessary, contact your Software AG technical support representative.
ERROR-073	Record too long for output data set
Explanation	An attempt was made to write a record to the sequential output data set. The length of the requested record exceeded the maximum record length permitted by the I/O system.
Action	Inform your database administrator.
ERROR-074	{file-number} is an invalid file number
Explanation	The supplied file number: <ul style="list-style-type: none">■ is zero;■ is greater than the MAXFILES parameter in effect for the database;■ has been duplicated in the file list specified; or■ represents a system file and is greater than 5000.
Action	Supply a correct file number and rerun the job.

ERROR-075	The parameter {parameter} is mutually exclusive to one or more other parameters supplied in the input
Explanation	The setting of the specified parameter conflicts with at least one other parameter setting in the related utility job. See the description of the utility syntax in the Adabas Utilities documentation for more information.
Action	Change or remove one of the mutually exclusive parameter settings, and rerun the job.
ERROR-076	Mandatory parameter {parameter} missing
Action	Add this parameter and rerun the job.
ERROR-077	I/O error during execution of a sequential read on file {ddname} : {reason}
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-078	Error occurred during opening of file {ddname} for output: {reason}
Explanation	The cause is probably a misspelling of the DDNAME, incorrect JCL, etc.
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-079	Error occurred during closing of output file {ddname} : {reason}
Explanation	The cause is probably a misspelling of the DDNAME, incorrect JCL, etc.
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-080	Error occurred during execution of write command to file {ddname} : {reason}
Explanation	The cause is probably a misspelling of the DD/NAME, incorrect JCL, an incorrect record or block size specification, or some similar problem.
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-081	Error occurred during opening/closing of input file {ddname} : {reason}
Explanation	An error occurred attempting to open or close the input file identified in the message (<i>ddname</i>). The reason code (<i>reason</i>) for the failure is given in the message. The cause is probably a misspelling of a job control statement name or other JCL error.
Action	Investigate the cause of the error; correct it and rerun the job.

ERROR-084	GETMAIN error - not enough virtual memory requested length = {count} ({hex-count}) bytes memory gotten = {count} ({hex-count}) bytes
Action	Rerun the job in a larger partition/region.
ERROR-085	GETMAIN Error - not enough virtual memory Reported by ADAIOR function {fxname}
Explanation	A GETMAIN error occurred. There is not enough virtual memory to process the ADAIOR function referenced in the message (<i>fxname</i>).
Action	Rerun the job in a larger partition or region.
ERROR-086	Invalid { ASSO DATA } RABN {nnnn} : {reason}
Explanation	This RABN is not defined in the database.
Action	Check the input parameters; correct the error and rerun the job.
ERROR-087	{device} is an unknown disk device type
Explanation	An invalid or unknown device type was found during processing.
Action	Check the input parameters; correct the error and rerun the job.
ERROR-088	ADALNK and/or ADANUC not present
Explanation	The Adabas installation procedure was not properly executed.
Action	Inform your database administrator.
ERROR-089	Utility not permitted to run
Explanation	Another utility has exclusive database control. The table displayed below the message on the terminal screen shows the current contents of the utility communications block. One of the jobs displayed has exclusive database control.
Action	Wait until that job has ended and retry this function.
ERROR-090	Utility not permitted to run; file number {file-number} is locked by another utility
Explanation	The table displayed below the message on the terminal screen shows the current contents of the utility communications block. One of the jobs displayed has exclusive file control.
Action	Wait until that job has ended, and then retry this function.

ERROR-091	Utility not permitted to run
Explanation	Concurrent jobs are not allowed to run against the database. In this case, <ul style="list-style-type: none"> ■ the nucleus or another utility is active; or ■ the nucleus was started with ADARUN READONLY=YES.
Action	Determine which utility/nucleus is already active. Wait until that utility/nucleus has ended and retry this function. If the nucleus was started with READONLY=YES, shut it down and restart with READONLY=NO.
ERROR-092	Utility not permitted to run
Explanation	The Adabas nucleus returned response "nn -xxx nucleus response -xxx". The nucleus cannot allow access to the requested file.
Action	Analyze the nucleus response code . Correct the error and rerun the job.
ERROR-093	Utility not permitted to run
Explanation	Pending autorestart detected.
Action	Restart the nucleus to perform the autorestart. Perform a shutdown after successful nucleus start if required. Rerun this job.
ERROR-094	Utility not permitted to run
Explanation	The version of the accessed database conflicts with the version of the active utility. Either the version indicator in the GCBs or the version indicator returned by the Adabas nucleus is not correct. The version indicator found is "version" (the text of the messages supplies the actual version indicator value).
Action	Correct the database or load library specification and rerun the job.
ERROR-098	File {file-number} cannot be processed
Explanation	The file comes from a database with a higher version number, and uses features not supported in the current nucleus version.
Action	It is not possible to process this file using the current version of the Adabas nucleus or utilities.
ERROR-099	Internal error at {xxxxxx}+{yyyyyy}
Explanation	Register contents at time of error:

R0-R3	xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
R4-R7	xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
R8-R11	xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
R12-R15	xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx

Action Inform your database administrator.

ERROR-101 Value for unique descriptor {xx} in file {yy} already present

Explanation Input data is invalid; the specified file *yy* cannot be processed. ISN=*nnnn* DE-VALUE: *llvvvvvvvv* The descriptor value (DE-VALUE) comprises the length of the descriptor value (*ll*) followed by the actual value (*vvvvvvvv*).

Action Rerun the utility with unique input data.

ERROR-102 An attempt was made to create a 16th index level for file {xxx}

Explanation No more than 15 levels are permitted.

Action Rerun this function with a smaller value for ASSOPFAC, the Associator padding factor.

ERROR-103 File number {file-number} is not accessible

Explanation One of the following occurred:

- A previous function to LOAD, REFRESH, REORDER, or RESTORE the file was interrupted. It is inconsistent.
- A RESTONL FMOVE function or RESTONL FILE function with parameter ALLOCATION=NOFORCE was interrupted; continuing the function with RESTPLOG is not possible.

Action Delete the file or overwrite it using ADAORD STORE or ADASAV RESTORE/RESTONL.

ERROR-104 File number {file-number} is already loaded

Explanation The file being accessed is already present in the database.

Action Look at the database report. Delete the file or choose another file number, then rerun the job.

ERROR-105	File number {file-number} is not loaded
Explanation	The file being accessed is not present in the database.
Action	Check the file number; correct it and rerun the job.
ERROR-106	Compressed record too long
Explanation	ISN of record = nnnn Length of record = nnn bytes Maximum record length = nnn bytes The characteristics of the data storage device do not allow such a record to be stored.
ERROR-107	The value of the `SORTSIZE' parameter and the size of the SORT dataset do not match.
Explanation	The data set is smaller than specified.
Action	Supply the correct size and rerun the job.
ERROR-108	The value of the `TEMPSIZE' parameter and the size of the TEMP dataset do not match.
Explanation	The data set is smaller than specified.
Action	Supply the correct size and rerun the job.
ERROR-109	Workpool (LWP) too small
Explanation	At least <i>nnnn</i> K of space is required. A larger value will increase performance.
Action	Increase the ADARUN LWP parameter value and rerun the job.
ERROR-110	SORT dataset too small
Explanation	Sorting may require either a larger SORTRn/DDSORTRn data set size, or two Sort data sets with a SORTSIZE equal to the combined size of both data sets.
Action	Supply a larger sort data set and increase the appropriate SORTSIZE= parameter. Decreasing the LWP parameter specified with the job might also help. The rules for the sort data set space calculation are described in the Adabas Utilities documentation. Rerun the job using the RESTART parameter.
ERROR-111	Invalid value for the parameters MINISN and/or MAXISN
Explanation	The MINISN and MAXISN parameter values must satisfy the following expression: <ul style="list-style-type: none"> ■ If the ISNSIZE is 3: $0 < \text{MINISN} \leq \text{MAXISN} < (\text{MINISN} + 16,777,215)$ ■ If the ISNSIZE is 4: $0 < \text{MINISN} \leq \text{MAXISN} < (\text{MINISN} + 4,294,967,294)$
Action	Supply the correct parameter value and rerun the job.

ERROR-112	Function not permitted
Explanation	An attempt was made to access an Adabas system file. This is not permitted.
Action	Correct the error and rerun the job.
ERROR-113	Invalid value for the parameter {parameter}
Explanation	An invalid value was specified for the parameter named in the message (<i>parameter</i>). The only values allowed are YES or NO.
Action	Supply the correct parameter value and rerun the job.
ERROR-114	Invalid value for the parameter ASSOPFAC or DATAPFAC
Explanation	The value for a padding factor must be in the range 1 to 90%.
Action	Supply the correct parameter value and rerun the job.
ERROR-115	Invalid value for the parameter MAXRECL
Explanation	The value for MAXRECL must be all of the following: <ul style="list-style-type: none">■ greater than 4;■ less than or equal to the Work block size minus 94;■ less than or equal to the Data Storage block size minus 4;■ equal to the MAXRECL of the anchor file (for components of expanded files).
Action	Supply the correct parameter value and rerun the job.
ERROR-116	Invalid value for the parameter MAXFILES
Explanation	The value for the parameter MAXFILES must meet the following requirements: <ul style="list-style-type: none">■ the parameter value must be in the range 3 to "nnnn" where "nnnn" is the Associator block size minus 1.■ the first (MAXFILES*5)+30 blocks must fit into the first Associator extent.
Action	Supply the correct parameter value and rerun the job.
ERROR-117	Parallel usage of {dataset-name} dataset
Explanation	<i>data-set-name</i> RABN <i>rabn-number</i> (<i>value</i>) was overwritten by another utility.
Action	Rerun the job, and avoid parallel usage of the "data-set-name" data set.

ERROR-118	The maximum record length of the {ddname} dataset is not large enough to accommodate the record length of the input file.
Explanation	The maximum record length (MAXRECL) of the file identified in the message (<i>ddname</i>) is not long enough for the data intended to be written to it.
Action	Correct the MAXRECL setting of the data set so it is equal to or larger than the maximum record length of the records being input. Then resubmit the job.
ERROR-120	Invalid value for parameter `ISNSIZE`
Explanation	Either 3 or 4 may be specified for this parameter.
Action	Check the parameter input; correct any errors, then rerun the job.

76 ADAACK Utility Messages

ERROR-121	Error counter reached maximum (ERRLIM)
ERROR-122	Invalid value for parameter file
Explanation	A range of file numbers must be supplied in ascending order.
Action	Supply the correct parameter value and rerun the job.
ERROR-123	Invalid or missing FROMISN/TOISN parameter
ERROR-125	Invalid block length for DS block {xxxxxxx} ({nnnn})
ERROR-126	AC Element contains DS RABN {xxxxxxx} ({nnnn}) (duplicate ISN)
ERROR-127	AC element contains DS RABN {xxxxxxx} ({nnnn})
ERROR-128	ISN {xxxxxxx} ({nnnn}) not found AC element contains DS RABN {xxxxxxx} ({nnnn})
ERROR-129	Wrong value for first unused ISN found in FCB
Explanation	FCB+ISNU (offset X`44') contains xxxxxxxx (nnnn) Actual first unused ISN= xxxxxxxx (nnnn)

ERROR-130	Invalid datastorage block/record length. DS RABN = {xxxxxxx} ({nnnn})
Explanation	The sum of all record lengths in the block must be equal to the block length minus 4.
Action	Run the ADACHK DSCHECK utility function to obtain more information.
ERROR-131	ISN found in DS record is greater or equal to the first unused ISN in the file.
Explanation	The ISN found in a Data Storage record is greater or equal to the first unused ISN in the address converter.
ERROR-132	Invalid secondary ISN values in FCB
Explanation	When spanned records are enabled, the first unused secondary ISN in the secondary address converter (used to map secondary ISNs to the RABNs of secondary records) must not be more than one higher than the maximum ISN included in the secondary address converter. In addition, the maximum ISN included in the secondary address converter must be the same as the highest allocated ISN for the secondary address converter.
ERROR-133	AC2-element contains DS-RABN {xxxxxxx} ({nnnn}) (duplicate ISN)
Explanation	When spanned records are enabled, a secondary address converter element contains a duplicate ISN.
ERROR-134	AC2-element contains DS-RABN {xxxxxxx} ({nnnn}) and Secondary ISN {xxxxxxx}- ({nnnn}) not found in data storage or DS Block={xxxxxxx}- ({nnnn}), ISN={xxxxxxx}- ({nnnn})
Explanation	When spanned records are enabled, a mismatch exists between the secondary address converter elements and Data Storage.
ERROR-135	Wrong value for first unused AC2 ISN found in FCB
Explanation	When spanned records are enabled, the first unused secondary ISN in the FCB and the first unused ISN in the secondary address converter do not match.
ERROR-136	AC2 ISN found in DS-record is greater or equal to the first unused AC2 ISN in the file
Explanation	When spanned records are enabled, the secondary ISN found in the Data Storage record is larger than or equal to the first unused ISN in the secondary address converter.

ERROR-137	Spanned Data Storage record flag bits are invalid Secondary ISN {xxxxxxx} ({nnnnn}) in DS-RABN {xxxxxxx} ({nnnnn}) Flag bits are {xx}
Explanation	When spanned records are enabled, the Data Storage RABN listed in the message is invalid.
Action	For further details, run the ADACHK DSCHECK utility function and then run the ADACHK print utility functions (DATAPRINT and DSIMPRINT) on the listed Data Storage RABN.
ERROR-138	Invalid rotating ISN {isn-num}
Explanation	This ISN is outside the valid range.
Action	Research the problem and contact your Software AG technical support representative for assistance.
ERROR-139	Cannot keep more than 500 million ISNs in core
Explanation	The number of ISNs requested for the ADAACK utility exceeded the limit that can be requested.
Action	Limit the ISN range and rerun the ADAACK job.
ERROR-140	Invalid ISN values in FCB
Explanation	The first unused ISN must not be higher than the maximum ISN (MAXISN) plus 1. The maximum ISN must correspond to the highest allocated ISN.
ERROR-141	AC2 table overflow
Explanation	When spanned records are enabled, a secondary address converter table overflow occurred.
ERROR-142	AC2 ISN {xxxxxxx} ({nnnn}) not found AC2 element contains DS RABN {xxxxxxx} ({nnnn})
Explanation	When spanned records are enabled, a Data Storage RABN was found in the secondary address converter (AC2), but not in Data Storage.
ERROR-143	Invalid rotating AC2 ISN {isn-num}
Explanation	This secondary address converter ISN is outside the valid range.
Action	Research the problem and contact your Software AG technical support representative for assistance.

- ERROR-144** **AC2 RABN {nnnnnnnn} ({nnnnnnnn}) is invalid**
- Explanation** The secondary address converter RABN listed in the message is invalid.
- Action** Print the contents of the Associator blocks using the ADACHK ASSOPRINT utility function. Then contact your Software AG technical support representative for assistance.
-
- ERROR-145** **Invalid ISN values in FCB**
- Explanation** Invalid ISN values were found in the FCB.
- The top ISN must not be higher than the last formatted ISN.
 - The last formatted ISN must not be higher than the MAXISN.
- Action** Contact your Software AG technical support representative for assistance.
-
- ERROR-146** **Invalid secondary ISN values in FCB**
- Explanation** Invalid secondary ISN values were found in the FCB.
- The top AC2 ISN must not be higher than the last formatted AC2 ISN.
 - The last formatted AC2 ISN must not be higher than the AC2 MAXISN.
- Action** Contact your Software AG technical support representative for assistance.
-
- ERROR-147** **Error in description of DSST extent number {nnnn}**
Reason : Blocksize of last DSST extent RABN is not equal to the value in the DSST extent description
- Explanation** The extent block sizes in the Data Storage space tables (DSST) do not match.
- Action** Contact your Software AG technical support representative for assistance.

77

ADACDC Utility Messages

ERROR-121	Open failed for {filename} file
Explanation	ADACDC attempted to open the file <i>filename</i> but the open failed. Processing cannot continue with this file; utility execution is terminated.
Action	Provide the missing file in the ADACDC job.
ERROR-122	Read error for {filename} file
Explanation	An error occurred reading the file <i>filename</i> ; utility execution is terminated. This error generally occurs when the format of the file indicated is not valid.
Action	Ensure that the file in question has a valid format as specified in the ADACDC documentation. In addition, check any special considerations for the operating system where the utility is being executed.
ERROR-123	Write error for {filename} file
Explanation	An error occurred writing to the file <i>filename</i> ; utility execution is terminated. This error normally occurs when the output file is full, but it may also occur when the format of the file indicated is not valid.
Action	If the file is full, increase the size of the file and rerun the job. Otherwise, ensure that the file in question has a valid format as specified in the ADACDC documentation. In addition, check any special considerations for the operating system where the utility is being executed.

ERROR-124	Unable to write data to {filename} file
Explanation	The ADACDC utility was not able to write data to the file <i>filename</i> because the amount of data to be written exceeded the maximum data that could be written to this file. Additional input in the message indicates the length of data that was to be written and the maximum data that can be written to the file.
Action	Increase the block size on the file to accommodate the largest record that may be written to the file.
ERROR-125	Invalid transaction file `CDCTXI`
Explanation	The ADACDC utility opened the CDCTXI file and successfully read the first record; however, the first record is not a transaction file record produced by the ADACDC utility.
Action	Supply a valid input transaction file to the utility or specify the RESETTXF so that the CDCTXI specification is ignored if the file name is correct.
ERROR-126	Inconsistent PLOG input provided: current DBID={olddbld} PLOG={oldplog} BLOCK={oldblock} received DBID={newdbld} PLOG={newplog} BLOCK={newblock} PLOGS provided to ADACDC must be in sequence
Explanation	The ADACDC utility encountered inconsistent input while processing the input PLOG data. It was expecting the next block based on the values <i>olddbld</i> , <i>oldplog</i> , and <i>oldblock</i> , but found that the next block to be processed was <i>newdbld</i> , <i>newplog</i> , and <i>newblock</i> . This can occur if <ul style="list-style-type: none">■ a PLOG is encountered that was produced by a different database ID;■ <i>newplog</i> and <i>oldplog</i> are the same, but <i>newblock</i> is not 1 more than <i>oldblock</i>, or <i>newplog</i> is less than <i>oldplog</i>.
Action	PLOGs must be provided to the ADACDC utility in the chronological order in which they were created. Provide the PLOG input in the correct chronological order. If this has occurred due to information on the input transaction file and you still wish to process the PLOGs provided, specify the RESETTXF option.
WARNING-127	Conversion error, Response Code=55. Length error decompressing field file={file} ISN={isn} fieldname={name} PE-INDEX={peindex} The record for the ISN will be written with a flag indicating that the record was not decompressed successfully. This occurs when the decompressed value for the field is longer than the default length for the field in the FDT. Data can legally be written longer than this value or the FDT definition may have changed.
Explanation	An error occurred while decompressing a record (on file <i>file</i> for ISN number <i>isn</i> , field name <i>name</i> , and PE Index <i>peindex</i>) before writing it to the primary output file. The record cannot be decompressed. This can occur if

	<ul style="list-style-type: none"> ■ the FDT for a file has changed; or ■ a data area longer than the default for the field in the FDT has been written, which can legally occur.
	The record is written with an indication that decompression failed.
Action	If the FDT has changed, the record cannot be decompressed unless the FDT is changed back. If the record(s) being written are longer than the default value for the field in the FDT, either increase the default value to accommodate the larger field sizes or avoid writing fields longer than the default value.
WARNING-128	Input transaction file is empty
Explanation	The CDCTXI file was successfully opened but was empty; no transaction information is available.
Action	If you are aware that the input transaction file is empty, you can ignore this warning; however, if you expect the input transaction file to contain some data, you need to determine why ADACDC is seeing an empty file.
ERROR-129	{value} invalid for PHASE parameter
Explanation	The <i>value</i> specified for the PHASE parameter is invalid.
Action	Specify "1", "2", or "BOTH", as appropriate.
WARNING-130	FDT for file {file} not found
Explanation	A data record is decompressed before writing to the primary output file. Before the record can be decompressed, the FDT for the file <i>file</i> must exist in the database. In this case, the FDT was not found; so the record could not be decompressed. Processing for the file is disabled after this message is issued.
Action	Make the FDT for the file available again in the database and rerun the job with FILE=file to process the records for the file in question.
ERROR-131	Database ID mismatch ADARUN DBID={rundbid}, extract file DBID={extdbid}
Explanation	The first record was read from the extract file provided for a phase 2 execution of the ADACDC utility. This record indicates that the extract file was generated for the <i>extdbid</i> database; however, the ADARUN DBID is <i>rundbid</i> .
Action	Run the phase 2 job using the correct database.

WARNING-132	Inconsistent NOET specification transaction data on CDCTXI ignored
Explanation	ADACDC detected that NOET was specified on the previous run of ADACDC, but not on this run-or vice versa. Changing the NOET parameter between runs renders the data on the transaction file redundant; therefore, this data is ignored.
Action	If this is expected, the message may be ignored. If it is not expected, you should determine why the ADACDC utility is being run with different options.
WARNING-133	Decompressed record too long. Response Code=53 Length error decompressing entire record file={file} ISN={isn} The record for the ISN will be written with a flag indicating that the record was not decompressed successfully. This will occur when the maximum length available on the CDCEXT/CDCOUT output file is insufficient to contain the decompressed record. Increase the maximum record length for the output file.
Explanation	Before writing the ISN (<i>isn</i>) for the file (<i>file</i>) to the primary output data set, an attempt was made to decompress the data. This attempt failed because the maximum length of output that can be written to the primary output data set is not large enough to accommodate the decompressed record. The record is written to the primary output data set with an indicator in the CDCO/CDCH header that the record is still in compressed format.
Action	Increase the block size of the primary output data set. If the data record requires more than 32K when decompressed, it cannot be supported by the ADACDC utility.
WARNING-134	Error occurred during the data decompression for File={file}, ISN={isn}, SeqNumber={seqnum}, RC={rc}, ResponseCode={rspcode}, ResponseSubcode={subcode} was given from the decompression routine. Report this to your DBA. The record will be written with a flag 'Still compressed'.
Explanation	A decompression error occurred while decompressing the data record for the unique sequential number <i>seqnum</i> for ISN <i>isn</i> on file <i>file</i> prior to output to the primary output data set. The return code (<i>rc</i>), response code (<i>rspcode</i>), and subcode (<i>subcode</i>) are given in the message. The record is written to the primary output data set with an indicator in the CDCO/CDCH header that the record is still in compressed format.
Action	Report the error to your DBA.

ERROR-135	Error limit exceeded
Explanation	The error limit is exceeded if the combined number of WARNING-127, WARNING-133, or WARNING-134 messages exceeds 99. This error generally indicates a fundamental problem with FDT definition(s) that should be corrected.
Action	Correct the reason for some or all of the warning messages and rerun the job.
WARNING-136	PLOG(S) may be missing current={currplog} next=nextplog
Explanation	While reading the input PLOGs, ADACDC detected that the PLOG number jumped from <i>currplog</i> to <i>nextplog</i> indicating that PLOG numbers in between may have been skipped. This can legally occur during online saves because they increase the session number without the PLOG number being changed. This causes the next PLOG started to use a number more than 1 greater than the previous PLOG. If that does not explain the difference, verify that all appropriate PLOGs for the database have been provided in sequence.
ERROR-137	PLOG {plognumber} not of current version
Explanation	PLOGS of earlier Adabas versions cannot be handled by this version of ADACDC.
Action	Use the ADACDC from the load library of the appropriate version.
ERROR-138	PLOG {plognumber} was produced by a cluster nucleus session and has not been merged yet
Explanation	The protection log (PLOG) was created by an Adabas cluster nucleus and has not yet been merged with other PLOGs using an ADARES PLCOPY procedure.
Action	Use the ADARES PLCOPY function before extracting data using ADACDC.
WARNING-142	IGNORESPANNED parameter specified, Spanned record has been skipped
Explanation	The IGNORESPANNED parameter was supplied. All spanned records found in the PLOG will be ignored.
Action	If processing spanned records is required, omit the IGNORESPANNED parameter and rerun the ADACDC job. Otherwise, no action is required for this informational message.

- WARNING-143** **Secondary spanned segment without associated primary spanned segment encountered for File = {file}, Primary ISN = {isn}, SeqNumber = {seqnum}. Such spanned record cannot be decompressed.
The record will be written with a flag 'Still compressed'.**
- Explanation** A standalone secondary segment (that is, a secondary segment without a primary segment) of the spanned record identified with the unique sequential number *seqnum* for primary ISN *isn* on file *file* was encountered in the protection log (PLOG). This segment cannot be decompressed. The record is written to the primary output data set with an indicator in the CDCH header that the record is still in compressed format.
- Action** No action is required for this informational message. Probably Adabas was started with the ADARUN nucleus parameter SRLOG=UPD, which instructs the nucleus to write to the PLOG only modified spanned record segments. If it is necessary to include all spanned PLOG records into ADACDC processing, restart the Adabas nucleus after changing the ADARUN SRLOG parameter to ALL or PART.
-
- ERROR-144** **ISN chain for spanned record is not intact.
File={file}, Primary ISN = {isn}, SeqNumber = {seqnum}.
Report this to your DBA.**
- Explanation** The primary and secondary segments of a spanned record are connected using their ISNs. A secondary segment was found in the PLOG with a different ISN from what was expected.
- Action** Report this problem to your DBA.
-
- ERROR-145** **Length of compressed spanned record exceeds the maximum PLOG/TXI record length multiplied by SEGLFAC value.
File = {file}, Primary ISN = {isn}, SeqNumber = {seqnum}.
Report this to your DBA.**
- Explanation** The length of the buffer for assembling spanned records is not large enough to contain the complete spanned record.
- Action** Report this problem to your DBA.
-
- ERROR-146** **Number of segments in spanned record exceeds SEGLFAC value.
File = {file}, Primary ISN = {isn}, SeqNumber = {seqnum}.
Report this to your DBA.**
- Explanation** The number of segments of a spanned record exceeds the SEGLFAC value (maximum number of spanned record segments allowed in one spanned record).
- Action** Report this problem to your DBA.

ERROR-147	MAXLOGRECLEN value less than minimum. Must be at least 32768 bytes.
Explanation	The value specified for the MAXLOGRECLEN parameter is too small. Valid values must be at least 32768 bytes.
Action	Correct the parameter value and rerun the job.
ERROR-149	The DST parameter also requires the TZ parameter.
Explanation	If you specify the DST parameter, you must also specify a valid TZ parameter.
Action	Supply the correct parameter values and rerun the job.
WARNING-150	TZ parameter not defined for utility run. Field(s) with TZ option from file {fnr} are presented in UTC format.
Explanation	If you do not specify the TZ parameter, values of date-time fields with TZ option are not converted to local time but left in UTC format.
Action	Supply the TZ parameter for the desired local time or set TZ='Etc/UTC' (to avoid the warning message) and rerun the job.
ERROR-151	The time zone specified by the TZ parameter is invalid. Response subcode is {nn}. Report this to your DBA. Subcode significance: Subcode 31 - Timezone not found Subcode 32 - Timezone pool full Subcode 33 - Open error on DD:TZINFO(member) Subcode 34 - I/O error on DD:TZINFO(member) Subcode 35 - Invalid TZINFO file contents Subcode 36 - Inv. transition time in TZ file
Explanation	The specified timezone could not be processed.
Action	Depending on the subcode, verify that the correct timezone was specified, that TZINFO assigns to the Timezone library (ADA <i>vr</i> s.TZ00) and that the timezone file is unmodified. Supply the correct parameter values and rerun the job. If the error cannot be solved, contact your Software AG technical support representative for assistance.
ERROR-152	Problem encountered attempting to invoke the external sort routine, Return Code = {rc} {ior-rc}=RC from IOR
Explanation	An error occurred during an attempt to invoke the external sort routine. The return code (<i>rc</i>) and IOR return code (<i>ior-rc</i>) are given in the message.
Action	Investigate the return code to determine why the problem occurred. Make appropriate corrections and rerun the job.

78

ADACHK Utility CHK* Messages

CHK001I	ASSO block {nnn} (x'xxxxxxxx') - FCB of file {x}.
	Print ASSO block {nnn} (x'xxxxxxxx') thru {nnn2} (x'xxxxxxxx') .
Explanation	This message provides the ASSO block number (<i>nnn</i>), its hexadecimal value (<i>xxxxxxxx</i>) and, possibly, the file number (<i>x</i>) being processed by ADACHK. An alternate version of this message provides a range of block numbers (with hexadecimal values) being printed.
Action	No action is required for this informational message.
CHK002I	Dump ASSO block {nnn} (x'xxxxxxxx') [thru {nnn2} (x'xxxxxxxx')].
Explanation	This message provides the ASSO block number (<i>nnn</i>) and its hexadecimal value (<i>xxxxxxxx</i>) being dumped by ADACHK. An alternate version of this message provides a range of block numbers (with hexadecimal values) being dumped.
Action	No action is required for this informational message.
CHK003I	File {fn} is an ADABAS system file. Print it in dump format only.
Explanation	File <i>fn</i> is a system file. Therefore it will not be printed in interpreted format.
Action	No action is required for this informational message.
CHK006I	Errors in {function} are detected. {Structure} will be printed in dump format.
Explanation	Errors in the function were detected and the structure in error will not be printed in interpreted format.
Action	No action is required for this informational message.

CHK007I	{rabn type} RABN {nn} (x'xxxxxxx') is {status} {rabn type} RABN {nn} (x'xxxxxxx') - {nn} (x'xxxxxxx') are {status}
Explanation	The RABN type (FST, DSST, PPT) is empty or unused.
Action	No action is required for this informational message.
CHK008I	Errors in {function} are detected. {Function2} function cannot be executed/printed.
Explanation	Due to errors in function <i>function</i> , <i>function2</i> could not be executed or printed.
Action	No action is required for this informational message.
CHK009I	GCB contains error(s). GCB will be printed in dump format.
Explanation	Errors were found validating the GCB. The GCB will be printed in dump format.
Action	No action is required for this informational message.
CHK011I	No records loaded in {fn}.
Explanation	The specified file has no records loaded.
Action	No action is required for this informational message.
CHK012I	The Adabas nucleus is currently down and a pending autorestart has been detected. Any errors reported after this point may be transient and may be repaired with the autorestart.
Explanation	This warning is returned when ADACHK receives a response code 148 (ADARSP148) on a call to the nucleus and detects that there is still a DIB entry, indicating a pending autorestart. It is possible that errors reported prior to this message can also be related to the autorestart, depending on the timing and when ADACHK detects the nucleus status change.
Action	If any errors are reported, to be sure they are real (and not due to the autorestart), clear the autorestart or restart the nucleus. Otherwise, no action is required for this informational message.
CHK014W	WARNING: Records from ciphered file {fn} cannot be checked/printed without code. Please supply correct cipher code.
Explanation	The ciphered file cannot be checked or printed without the cipher code.
Action	Specify the correct cipher code and rerun the job.

CHK015I	Error while reading {struct}
Explanation	An error was encountered while reading the structure (<i>struct</i>) listed in the message.
Action	No action is required for this informational message. Review additional messages produced with this message for more information.
CHK016I	DATA RABN {ravn} (x'xxxxxxxx') contains error(s). It has been skipped from further processing .
Explanation	The Data Storage RABN listed in the message has errors and is being skipped from further processing.
Action	No action is required for this informational message. Additional messages may also be produced; review any additional messages for more information.
CHK017I	No nucleus verification calls were made.
Explanation	This message displays when no nucleus calls are made.
Action	No action is required for this informational message.
CHK021I	ISNs greater or equal to the first unused ISN = {nnn} (x'xxxxx') were omitted.
Explanation	A range of ISNs was specified and any ISN greater than or equal to the first unused ISN was omitted.
Action	No action is required for this informational message.
CHK022I	ISNs less or equal to the start ISN = {nnn} (x'xxxxx') were omitted.
Explanation	A range of ISNs was specified and any ISN less or equal to the start ISN was omitted.
Action	No action is required for this informational message.
CHK023I	Further checks of file were skipped.
Explanation	: Due to another error, further checking on this file is terminated.
Action	No action is required for this informational message. Review additional messages produced with this message for more information.
CHK024I	Spanned record with primary ISN {isn} (x'xxxxxxxx') from DS RABN {ravn} (x'xxxxxxxx') can not be assembled because of error printed above. This record is skipped from further processing.
Explanation	Due to the additional error printed, the spanned data storage record could not be assembled.
Action	No action is required for this informational message. Review accompanying messages for more information and suggested actions.

CHK025I	The Adabas nucleus is currently {state}.
Explanation	This messages is issued when the nucleus changes states. Possible values for <i>state</i> in the message include "ACTIVE", "INACTIVE", "READONLY", and "DOWN WITH DIB ENTRY".
Action	No action is required for this informational message.
CHK026I	The MAXCALLS parameter limit has been exceeded for file {nn}. Therefore, no further nucleus calls will be made to ensure that errors are real. Any errors reported after this point may be due to concurrent updates. To distinguish persistent errors from transient errors, please run with a higher MAXCALLS parameter or wait for less activity on the file.
Explanation	This warning message is received when the MAXCALLS limit has been reached. The file number (<i>nn</i>) is given in the message.
Action	Increase the size of your MAXCALLS parameter setting to distinguish persistent errors from transient errors. If that does not work, wait for less activity on the file.
CHK121E	ERROR: Invalid LA or SP call detected by the nucleus.
Explanation	The LA or SP call issued to the Adabas nucleus was not recognized or returns an invalid response code.
Action	Contact your Software AG technical support representative for assistance.
CHK122E	ERROR: ISN size in FCB is not equal to 3 or 4 bytes or expected sum (ISN size + RABN size) mismatch with the current. Current ISN size in FCB is {xxx}.
Explanation	An ISN size problem was encountered.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK123E	ERROR: {nnnnn} in FCB (offset x'{xxxx}') is invalid. Reasons: {rsns}
Explanation	The value (<i>nnnnn</i>) in the FCB is invalid. The reasons (<i>rsns</i>) are given in the message. Possible reasons are: <ul style="list-style-type: none">■ Number of <i>type</i> extents should not be zero.■ Offset to <i>type</i> extents should not be zero or greater than ASSO block length.■ Inconsistent offset and number. If one is zero, then other should also be zero.■ First <i>type</i> RABN is greater than last <i>type</i> RABN.■ First unused <i>type</i> RABN should be in the range from first <i>type</i> RABN to last <i>type</i> RABN + 1.■ First <i>type</i> RABN - <i>nnn</i> (x'xxxx')■ Last <i>type</i> RABN - <i>nnn</i> (x'xxxxx')■ First unused <i>type</i> RABN - <i>nnnx'xxxxx')</i>

	<ul style="list-style-type: none"> ■ Offset to <i>type</i> extents - x'xx' ■ Number of <i>type</i> extents - x'xx'
Action	Review the reasons supplied with this message to determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK124E	ERROR: {AC AC2} ISN = {isn} (x'xxxx') found in DS RABN = {rabn} is greater than or equal to the first actual unused {AC AC2} ISN = {isn2} (x'xxxx') Offset to record in DS block - x'xx' May be that value of first unused {AC AC2} ISN in FCB is incorrect.
Explanation	The ISN found in a Data Storage record is greater than or equal to the first unused ISN in the address converter (AC) or the ISN found in a spanned Data Storage record is greater than or equal to the first unused ISN in the secondary address converter (AC2).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK125E	ERROR: FDT length {nnnnn} (x'xxxx') in FCB does not match with the actual FDT length {nnnnn} (x'xxxx').
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK126E	ERROR: Invalid block length x'xxxxxx' in DS RABN {rabn} (x'xxxxxx').
Explanation	The block length field contains either a negative value or a number larger than the physical block size.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK127E	ERROR: The total length of processed records in DS RABN {rabn} (x'xxxx') exceeds the block length minus 4. Offset to current processed record in DS block - x'xxxx'.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK128E	ERROR: Invalid record length x'xxxxxxxx' was found in DS RABN {rabn} (x'xxxx'). Offset to record in DS block - x'xxxxxxxx'. The sum of all record lengths in the DS-Block is not equal to the BLOCKLENGTH minus 4.'
Explanation	The record length is negative, zero, or greater than the permitted maximum length (set by the MAXRECL parameter).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK129E	ERROR: Invalid ISN equal to {nnnn} (x'{xxxx}') was found in DS RABN {ravn} (x'{xxxxxxxx}). Offset to record in DS block - x'{xxxx}'.
Explanation	The ISN shown in the message (<i>nnnn</i>) was not found in the Data Storage block.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK130E	ERROR: Spanned record with ISN = {isn} (x'{xxxxxxxx}') in DS RABN {ravn} (x'{xxxxxxxx}') contains inconsistencies. A spanned DS record must be either a primary or a secondary record. Both are not permitted. Offset to record in DS block - x'{xxxx}' ERROR: Spanned record with ISN = {isn} (x'{xxxxxxxx}') in DS RABN {ravn} (x'{xxxxxxxx}') contains inconsistencies. A spanned DS record must be either a primary or a secondary record. Neither is not permitted. Offset to record in DS block - x'{xxxx}' ERROR: Spanned record with ISN = {isn} (x'{xxxxxxxx}') in DS RABN {ravn} (x'{xxxxxxxx}') contains inconsistencies. ISN of this spanned record field is zero or exceeds the maximum possible ISN. Offset to record in DS block - x'{xxxx}' ERROR: Spanned record with ISN = {isn} (x'{xxxxxxxx}') in DS RABN {ravn} (x'{xxxxxxxx}') contains inconsistencies. Master ISN field is zero or exceeds the maximum possible ISN. Offset to record in DS block - x'{xxxx}' .
Explanation	The header (primary) or secondary record of the spanned Data Storage record with the ISN number listed in the message (<i>isn</i>) is erroneous. Note: This message has several variations in its text, as shown above.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK131E	ERROR: Primary spanned record with ISN = {nnnn} (x'{xxxxxxxx}') in DS RABN {ravn} (x'{xxxxxxxx}') contains inconsistencies. {rsns}
Explanation	Errors were encountered with the primary spanned record identified in the message. Possible reasons for the error (rsns) are also provided in the message. Possible reasons are: <ul style="list-style-type: none">■ ISN of this record and Master ISN fields should be the same. Offset to record in DS block - x'xxxx'.■ Next ISN field is zero or exceeds the maximum possible ISN. Offset to record in DS block - x'xxxx'.
Action	Review the reasons supplied with this message to determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK132E	ERROR: Invalid ISN number {nnnn} (x'xxxxxxxx') was found in DS RABN {rabn} (x'xxxxxxxx'). ISN exceeds the maximum possible ISN. Offset to record in DS block - x{xx}'.
Explanation	The ISN number listed in the message (<i>nnnn</i>) and found in the Data Storage RABN listed in the message exceeds the maximum possible ISN.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK133E	ERROR: Duplicate AC/AC2 ISN = {nnnn} (x'xx') was found in DS RABN {rabn} (x'xxxxxxxx'). Offset to record 1 in DS block - x'xxxx'. Offset to record 2 in DS block - x'xxxx'.
Explanation	Duplicate ISNs within on Data Storage block were found. ISNs must be unique.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK134E	ERROR: The FSTTO value is less than FSTFROM. Offset to incorrect FST element is x'xx'.
Explanation	An error was encountered in the free space table (FST).
Action	Repair the FST using Adabas Online System or the ADADBS RECOVER utility function.
CHK135E	ERROR: The FST element count is invalid. Current value is {nnnn}.
Explanation	An error was encountered in the free space table (FST).
Action	Repair the FST using Adabas Online System or the ADADBS RECOVER utility function.
CHK136E	ERROR: Free Space Table is not sorted, run RECOVER.
Explanation	An error was encountered in the free space table (FST).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK137E	ERROR: The FSTTYPE is invalid. Current value is x'xxxx'. Offset to incorrect FST element is x'xx'.
Explanation	An error was encountered in the free space table (FST).
Action	Repair the FST using Adabas Online System or the ADADBS RECOVER utility function.

CHK138E	ERROR: Error while reading the last {ASSO DATA} RABN {ravn}.
Explanation	A error was encountered reading the last Associator or Data Storage RABN shown in the message (<i>ravn</i>).
Action	Use the ADAREP utility to check the database RABN allocations and correct them, as necessary.
CHK139E	ERROR: {ASSO DATA} extents are not in ascending order.
Explanation	The Associator or Data Storage extents are not in ascending order.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK140E	ERROR: {ASSO DATA} extent descriptions do not fit into GCB2.
Explanation	The length of all of the extent descriptions (Associator, Data Storage, and DSST) exceed the block length.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK141I	ADACHK reestablishing communication with nucleus after a RSP-22.
Explanation	This message is issued when ADACHK gets a response code 22 (ADARSP022) back from a privileged call. This usually happens when the nucleus is restarted while ADACHK is active.
Action	No action is required for this informational message.
CHK142I	ADACHK is unable to verify the following error with the nucleus due to an unexpected nucleus response {nnn}.
Explanation	This warning message indicates that an error could not be verified with the nucleus; the response code is given in the message (<i>nnn</i>).
Action	Investigate the cause of the error, based on the information provided for the response code. Correct the error and rerun the job. If the problem persists, contact your Software AG technical support representative for assistance.
CHK143E	ERROR: FDT with length x'{xxxx}' does not fit into the FDT RABNs. First FDT RABN in FCB – {ravn1}. Last FDT RABN in FCB – {ravn2}.
Explanation	An FDT error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK144E	ERROR: Length of PPT entry in RABN {ravn} at offset x'{xxxx}' is invalid. Current value is x'{xxxx}'.
Explanation	The length of the PPT entry exceeds the highest length allowed or is less than the lowest possible length.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK145E	ERROR: PPTID in RABN {ravn} at offset x'{xx}' is invalid. Current value is x'{xxxx}'.
Explanation	A PPT error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK146E	ERROR: RABN {ravn} (x'{xxxxxxxx}') outside type{ASSO DATA MI NI UI} extents was found in type {{MI} {UI}} element. RABN contained incorrect type {{MI} {UI}} element is {n} (x'{xxxx}'). Offset to incorrect {type} element is x'{xxxx}'.
	ERROR: RABN {ravn} (x'{xxxxxxxx}') outside type {ASSO DATA MI NI UI} extents. Offset to RABN in FCB - x'{xxxx}', {rsn}
Explanation	An RABN error occurred. In one version of this message, a reason is supplied. Possible reasons include: <ul style="list-style-type: none"> ■ First AC RABN ■ First AC2 RABN ■ First DATA RABN ■ First FDT RABN ■ First NI RABN ■ First reusable NI RABN ■ First reusable UI RABN ■ First UI RABN ■ Last AC RABN ■ Last AC2 RABN ■ Last DATA RABN ■ Last FDT RABN ■ Last NI RABN ■ Last UI RABN ■ Last used DATA RABN ■ Last used UI RABN ■ Last used NI RABN ■ RABN of Highest Index block

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK147E **ERROR: Database ID equals zero.**

Explanation A database ID of zero was encountered.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK148E **ERROR: The highest possible file number in database is invalid. Current value is {nn}.**

Explanation A file number error was encountered. File numbers cannot exceed 5000.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK149E **ERROR: The value for RABNSIZE field in the GCB must be 3 or 4. Current value is {nnnn}.**

Explanation An error occurred with the value of the RABNSIZE field.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK150E **ERROR: Highest file number currently loaded is invalid. Current value is {nn}.**

Explanation The highest file number loaded exceeds the highest file number defined for the database.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK151E **ERROR: First or last PPT RABN equals zero.**

Explanation The first and last PPT RABN values must be nonzero values.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK152E **ERROR: Work dataset definitions from GCB are invalid.**

Explanation One or more of the Work definitions (device, RABN, etc.) in the GCB are invalid.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK153E	ERROR: The value for the number of {ASSO DATA DSST} extents is equal to zero or more than 99.
Explanation	An error occurred with the number of Associator, Data Storage, or DSST extents.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK154E	ERROR: Description of ASSO, DATA and DSST extents must fit into one ASSO block.
Explanation	An error occurred with the number of Associator, Data Storage, or DSST extents.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK155E	ERROR: The last RABN of the first ASSO extent must be greater than size of ASSO fixed part. Current value is {nnnn} (x'xxxx').
Explanation	An error occurred with the Associator.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK156E	ERROR: First FCB RABN must be equal to 31. Current value is {nnnn}.
Explanation	An error occurred with the FCB.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK157E	ERROR: Error in description of DSST extent number {nnnn}. Reasons: {rsns}.
Explanation	An error occurred with the DSST extent number given in the message (<i>nnnn</i>). Reasons (<i>rsns</i>) for the error are also given in the message. Possible reasons include: <ul style="list-style-type: none"> ■ Top DATA RABN mapped by last DSST extent is not equal to maximum DS RABN. ■ First RABN is greater than last RABN of DSST extent. ■ Last RABN of DSST extent is greater than TOP ASSO RABN. ■ First and last RABN of DSST extent are zero. ■ Blocksize of last DSST extent RABN is not equal to the value in DSST extent description. ■ Top DATA RABN mapped by DSST extent is zero. ■ Top DATA RABN mapped by DSST extent is more than maximum. ■ DATA blocksize mapped by DSST extent is not equal to the real DATA blocksize.
Action	Review the reasons supplied with this message to determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK159E	ERROR: First DSF RABN is greater than last DSF RABN.
Explanation	The first DSF RABN is greater than the last one.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK160E	ERROR: Index block RABN = {rabn} (x'{xxxxxxx}') contains incorrect block length - x'{xx}'.
Explanation	An incorrect block length was encountered.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK161E	ERROR: FST entry contains RABNS that do not belong to the database. Offset to incorrect FST element is x'{xx}'.
Explanation	The FST contains RABNs that do not belong to this database.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK162E	ERROR: Total length of indices from RABN = {rabn} (x'{xxxx}') exceeds the used block length.
Explanation	The total length of the RABN indices exceeds the used block length.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK163E	ERROR: Index element in the index block RABN = {rabn} (x'{xxxxxxx}') contains incorrect length of DE value - x'{x}'. Offset to incorrect element in the block - x'{xx}'.
Explanation	An index element error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK164E	ERROR: NI element in the index block RABN {rabn} (x'{xxxxxxx}') contains incorrect ISN {nnnn} (x'{xxxxxxx}') in the ISN list. Offset to incorrect NI element x'{xx}'.
Explanation	The ISN list for one value in an NI block must be in strict ascending sequence. If not, this message occurs. This message also occurs if an ISN is not less than the first unused ISN specified in the file control block (FCB). This can also occur if the ISN is zero.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK165E	ERROR: Index block RABN = {ravn} (x'xxxxxxxx') contains incorrect level indicator - x'x' .
Explanation	The level indicator in the index block does not indicate the correct level as expected.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK166E	ERROR: Number of empty blocks {nnnn} in the empty {UI NI} index block chain exceeds possible maximum {nnnn}. Reason may be the existence of empty block with invalid forward pointer causing the chain to loop into itself.
Explanation	The forward pointer in an element of the empty NI/UI block chain contains an invalid RABN. This forward pointer should contain either a RABN of another empty NI/UI block or a zero to indicate the end of the chain. However, there is an invalid forward pointer value causing the chain to return into itself.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK167E	ERROR: Logical length of empty {UI NI} block RABN = {ravn}> (x'xxxxxxxx') should be 0006.
Explanation	An invalid logical length of an empty block was encountered.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK168E	ERROR: Empty {UI NI} block RABN = {ravn} (x'xxxxxxxx') contains incorrect forward pointer. Forward pointer RABN = {ravn} (x'xxxxxxxx') is outside used {UI NI} extents.
Explanation	The forward pointer in an element of the empty NI/UI block chain contains an invalid RABN. This forward pointer should contain a RABN of another empty NI/UI block or should contain a zero to indicate the end of the chain.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK169E	ERROR: NI values of descriptor {fld} are not in ascending order. RABN {ravn} (x'xxxxxxxx'), offset to element x'xx'.
Explanation	When processing the index for one descriptor (in an L9 sequence), the NI block values should be in ascending sequence. This message occurs if either of the following occurs: <ul style="list-style-type: none"> ■ The values within one block are not strictly increasing (equal values are considered an error); ■ The first value in an NI, MI, or UI block is less than the last value in the previous block (equal values are allowed).

- Action** Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
- CHK170E** **ERROR: Index element contains invalid packed value. RABN {rabn} (x'xxxxxxxx'), offset to element x'xx', DE name {desc}.**
- Explanation** An index element error was encountered.
- Action** Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
- CHK171E** **ERROR: NI element in the index block RABN = {rabn} (x'xxxxxxxx') contains zero ISN count. Offset to incorrect NI element is x'xx'.**
- Explanation** The ISN count in an NI element should not be zero.
- Action** Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
- CHK172E** **ERROR: fieldName {fld} - EXI-OPT for SDTE Element is invalid - EXI but not UQ-DE in PE.**
- Explanation** A field error was encountered.
- Action** Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
- CHK173E** **ERROR: Invalid FDT length. Total FDT length x'xxxx' is not equal to the sum of FDT parts x'xxxx'.**
- Explanation** The defined length of the FDT is not equal to the sum of its parts.
- Action** Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
- CHK174E** **ERROR: Invalid length {nn} for field {fld}. The maximum permitted length for format type {format} is {nnn}.**
- Explanation** An invalid field length was encountered.
- Action** Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK175E	ERROR: More than one Parent Field with MU option is not permitted for sub-/superfield {fld} .
Explanation	A subfield or superfield cannot have more than one parent field with the MU option.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK176E	ERROR: The Parent field {fld} for field {fld} has invalid attributes. Subcode is {nnnn} : 1) FROM/TO value(s) = 0; 2) FROM > TO; 3) TO > permitted maximum.
Explanation	An invalid parent field was encountered. The parent field has invalid attributes.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK177E	ERROR: The Parent field {fld} for {descriptor-type} is a Group field.
Explanation	The parent field for a descriptor field is a group field. Possible descriptor types appearing in this message are: "Phonetic Descriptor", "Hyperc Descriptor", "Collating Descriptor", "Sub-/Super Descriptor", "Elementary", and "Special".
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK178E	ERROR: {descriptor-type} has invalid offset to Parent field. Parent field cannot be found in FDT.
Explanation	The parent field for a descriptor cannot be found. Possible descriptor types appearing in this message are: "Phonetic Descriptor", "Hyperc Descriptor", "Collating Descriptor", "Sub-/Super Descriptor", "Elementary", and "Special".
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK179E	ERROR: The field {fld} is found more than once.
Explanation	A field error occurred; the field is found more than once.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK180E	ERROR: The Parent field {fld} for Phonetic Descriptor {descriptor} is invalid. Possible reasons: {rsns}.
Explanation	The parent field for a phonetic descriptor is invalid. Reasons (<i>rsns</i>) for the error are provided in the message. Possible reasons include: <ul style="list-style-type: none">■ Parent field is a field within a Periodic group.■ Parent field does not have alpha format.■ Field is not the parent of phonetic descriptor.■ Field is the parent of more than one phonetic descriptor.■ Field is the MU field but phonetic descriptor is not.
Action	Review the reasons supplied with this message to determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK181E	ERROR: The Parent field {fld} for sub-/super field/descriptor {descriptor} has Floating Point format .
Explanation	A parent field error occurred; the parent field for the subfield, superfield, subdescriptor, or superdescriptor has floating point format.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK182E	ERROR: Field {fld} has an inconsistent field level structure.
Explanation	A field error occurred. The field has an inconsistent field level structure.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK183E	ERROR: The Parent field {fld} for sub-/superfield/descriptor {descriptor} has the LA or LOB option set.
Explanation	A parent field error occurred; the parent field for the subfield, superfield, subdescriptor, or superdescriptor has the LA or LB (large object) options set.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK184E	ERROR: Invalid format x'{x}' for {descriptor-type} field {fld}.
Explanation	A descriptor field format error occurred, Possible descriptor types appearing in this message are: "Phonetic Descriptor", "Hyperc Descriptor", "Collating Descriptor", "Sub-/Super Descriptor", "Elementary", and "Special".
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK185E	ERROR: Field {fld} is not Parent of sub-/superfield/descriptor {descriptor}.
Explanation	A parent field error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK186E	ERROR: UQ-Option for Non-Descriptor field {fld} is not permitted.
Explanation	The UQ option is not permitted for a non-descriptor field.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK187E	ERROR: The Field {fld} has the FI- and DE-Options. This is not permitted for a field within a Periodic Group.
Explanation	A field defined within a periodic group has the FI and DE options defined as well. This is not allowed.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK188E	ERROR: Missing length for field {fld} with FI-Option.
Explanation	The length is missing for a field with the FI option specified.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK189E	ERROR: FI- and NU-Option are mutually exclusive: field {fld}.
Explanation	A field has both the FI and NU options defined; these options are mutually exclusive.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK190E	ERROR: TZ option is invalid with current datetime edit mask: field {fld}; datetime edit mask {edit-mask }.
Explanation	A time zone processing error occurred. The TZ option is invalid with the current datetime edit mask.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK191E	ERROR: Length of Group {group-fld} with MU field must be zero.
Explanation	A group field length error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK192E	ERROR: Invalid length x'{xxxx}' of Group {group-fld}.
Explanation	A group field length error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK193E	ERROR: System restriction: Too many fields in the FDT.
Explanation	There are too many fields in the FDT. A maximum of 3214 is possible.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK194E	ERROR: Invalid field {fld} position within the PE Group. Position from FDT - {nnnnn} (x'{xxxx}'). Actual position - {nnnn} (x'{xxxx}') .
Explanation	A PE group field position error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK195E	ERROR: The last field {fld} in the FDT cannot be a group.
Explanation	The last field in the FDT cannot be a group.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK196W	WARNING: ADACHK is not permitted to run for file {fn}. Another utility has the file locked.
Explanation	Another Adabas utility has locked the file (<i>fn</i>) listed in the message, so the ADACHK utility cannot run on the file.
Action	Issue a DUQA or DDIB command to determine what utility has the file locked and to remove the UQE or DIB entry. Then try to run the ADACHK job again.

CHK197E	ERROR: Invalid field name syntax for {fld}.
Explanation	An invalid field name was found while processing the SDT.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK198E	ERROR: {AC AC2} ISN = {nnnn} (x'xxxxxxxx') was found in DS RABNs more than once (duplicate ISN). DS RABN for this ISN from {AC AC2} is {rabn} (x'xxxxxxxx'). ISN also found in DS RABN {rabn} (x'xxxxxxxx').
Explanation	The ISN number listed in the message (<i>nnnn</i>) appears in two Data Storage records. ISNs should be unique. Note: If the Data Storage RABNs associated with the duplicate ISNs contain errors, this message will be duplicated because the ISN is duplicated. This could occur with the CHK248E message if the ISN of the secondary address converter is duplicated and the duplicate secondary ISNs point to a primary ISN that was not found or could not be assembled.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK199E	ERROR: Collating Descriptor Exit for field {fld} is not in range 1 - 8.
Explanation	A collating descriptor exit error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK200E	ERROR: NU option set for Parent field {fld} but does not set for sub-/superfield/descriptor {descriptor}.
Explanation	A parent field specification error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK201E	ERROR: Hyper Descriptor Exit for field {fld} is not in range 1 - 31.
Explanation	The hyperdescriptor exit specified for a field is not in the correct range.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK202E	ERROR: Number of Parent fields for {fld} exceeds the permitted maximum (20).
Explanation	The number of parent fields specified for a field exceeds the maximum.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK203E	ERROR: Field {fld} with NB option requires LA or LB option.
Explanation	A field with the NB option is not specified with the LA or LB options.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK204E	ERROR: The SUPERFIELD/DESCRIPTOR {descriptor} must not have both NU and NC Parent Fields.
Explanation	A superfield or superdescriptor cannot have both NU and NC parent fields.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK205E	ERROR: More than 254 elementary fields in PE-Group {nnnnn}.
Explanation	There are too many elementary fields in a PE group. The number of elementary fields (<i>nnnnn</i>) is given in the messages.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK206E	ERROR: Field {fld} has the LA or LB option: - it must have Alphanumeric format or - it must have Wide format, - it must neither have the FI option nor the DE option.
Explanation	A field specified with the LA or LB option has been incorrectly defined.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK207E	ERROR: EXI Option is not allowed for field {fld}. This field is not a descriptor and/or does not contain fields from PE-group.
Explanation	A field is defined incorrectly.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK208E	ERROR: Field {fld} in Group {group} has invalid option: {option}.
Explanation	A field in a group has an invalid option.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK209E	ERROR: Group {group} is not marked as having a {LOB VAR. LENGTH MU} field but contains {LOB VAR. LENGTH MU} field {fld}.
Explanation	A group field is not identified as containing large object (LB option), variable length, or MU fields, but one or more of the fields in the group are defined as large object, variable length or MU fields.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK210E	ERROR: LB-Option and LA-Option are mutually exclusive. Field {fld}.
Explanation	A field is defined with both the LB and LA options; these options are mutually exclusive.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK211E	ERROR: Field {fld} with NB option requires NC or NU option.
Explanation	An NB field is not defined with the NC or NU options; one of these options is required.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK212E	ERROR: Invalid SDT length x'{xxxx}'.
Explanation	An SDT length error was encountered.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK213E	ERROR: Datetime edit mask conflicts with format: field {fld}; format {format}; datetime edit mask {edit-mask} .
Explanation	A specified date-time edit mask conflicts with the field format.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK214E	ERROR: TZ option is invalid without the datetime edit mask: field {fld} .
Explanation	The TZ option cannot be specified with out the date-time edit mask.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK215E	ERROR: Unknown Datetime edit mask: field {fld} .
Explanation	An invalid date-time edit mask was specified for a field.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK216E	ERROR: Field length is too short for current Datetime edit mask: field {fld}; length {nn}; datetime edit mask {edit-mask}.
Explanation	The field length is too short for the date-time edit mask that was specified.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK217E	ERROR: Incorrect count of fields (x'{x}') in Group {group} .
Explanation	An incorrect number of fields was encountered in a group.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK218E	ERROR: All specified RABNs exceed last physical RABN. Last physical RABN is {ravn} %-(x'{xxxxxxx}').
Explanation	RABNs that exceed the last physical RABN were found in the INPUT parameter. These RABNs are ignored.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK218I	RABNs exceed last physical RABN were found in input parameters. These RABNs are ignored. Last physical RABN is {ravn} -(x'{xxxxxxx}') .
Explanation	RABNs that exceed the last physical RABN were found in the INPUT parameter. These RABNs are ignored.
Action	No action is required for this informational message.

CHK219E	ERROR: FDT extent definition in FCB for File {fn} is invalid. First FDT RABN = {rabn1} (x'xxxxxxxx') at offset x'{xx}' exceeds last FDT RABN = {rabn2} (x'xxxxxxxx') at offset x'{xx}'.
Explanation	An FDT extent error occurred for a file.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK220E	ERROR: FDT definition in FCB for File {fn} is invalid. FDT length x'xxxx' at offset x'{xx}' is invalid .
Explanation	An FDT definition in the FCB for a file is invalid.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK221E	{ACCHECK CHECK DSCHECK ICHECK VALIDATE} is not performed for File {fn}. Reasons: {rsns}
Explanation	The ADACHK function listed in the message was not performed for the file listed in the message (<i>fn</i>). Reasons (rsns) for the error are also given in the message. Possible reasons include: <ul style="list-style-type: none"> ■ Error in FCB has been detected. ■ Error in FDT has been detected. ■ Error in NI extent definition in FCB has been detected. ■ Error in UI extent definition in FCB has been detected. ■ Error in UI/NI definitions in FCB has been detected. ■ File is CHECKPOINT file. ■ File is SECURITY file. ■ Not all DEs could be processed. ■ Number of NI extents in FCB equal 0 ■ Number of UI extents in FCB equal 0. ■ There are no descriptors in this file. ■ There are no records in the file. ■ There are no NI elements for this file. ■ There are no UI elements for this file. ■ There are no UI/NI elements for this file. ■ There are no valid DE names in DESCRIPTOR parameter.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK222E	ERROR: Descriptor {descriptor} not in ascending sequence is found in RABN = {rabn} (x'xxxxxxxx'), offset x'xx' .
Explanation	Each U3 element contains the field name for the descriptor. Field names must be in ascending sequence. The field name that is out of sequence is identified in the message (<i>descriptor</i>).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK223E	ERROR: ISN/RABN are not zero in UI element of empty descriptor {descriptor}, RABN {rabn}n (x'xxxxxxxx'), offset x'xx' .
Explanation	An error occurred with the UI element of an empty descriptor.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK224E	ERROR: LOB Info entries definition in FCB is invalid. {msg-continuation}
Explanation	The following possible message continuations (<i>msg-continuation</i>) can be included in the message: <ul style="list-style-type: none">■ Inconsistent offset to 1st LOB Info entry x'xx' (offset in FCB - x'xx') and Number of LOB Info entries x'xx' (offset in FCB - x'xx'). If one is zero, then other should also be zero.■ Offset to 1st LOB Info entry x'xx' (offset in FCB - x'xx') should not be zero or greater than ASSO block length.■ LOB Info entry (offset in FCB - x'xxxxx') contains invalid Base/LOB file number <i>fn</i> (x'xxxxx'). Base/LOB file number should not be zero or greater than <i>nn</i> (x'xxxxx') -maximum file number in database.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK225E	ERROR: {xxxx} definition does not fit into one ASSO block. Offset to {xxxx} - x'xx'; Number of {xxxx} - x'xx'.
Explanation	An Adabas element or extent definition does not fit into one ASSO block, where <i>xxxx</i> represents the element or extent name and can be one of the following: <ul style="list-style-type: none">■ AC extents■ AC2 extents■ Couple elements■ DATA extents■ last formatted AC■ last formatted AC2

	<ul style="list-style-type: none"> ■ LOB Info entries ■ maximum AC ■ maximum AC2 ■ NI extents ■ UI extents
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK226E	ERROR: Couple elements definition in FCB (offset x'{xx}') is invalid. {msg-continuation}
Explanation	The following possible message continuations (<i>msg-continuation</i>) can be included in the message: <ul style="list-style-type: none"> ■ Inconsistent values in offset to 1st couple element and number of couple elements. If one is zero, then other should also be zero. ■ Offset to 1st couple element should not be zero or greater than ASSO block length. ■ Number of coupled files should not be greater than 18.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK227E	ERROR: Couple element in FCB (offset x'{xx}') is invalid. Coupled file number and Descriptor names should be defined.
Explanation	An FCB couple element error occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK228E	ERROR: Invalid DSST entry was found. DSRABN = x'{xxxxxxx}' ({ravn}) Actual value x'{xxxxxxx}', Value from DSST x'{xxxxxxx}' DSSTRABN = x'{xxxxxxx}' ({ravn}>), Offset = x'{xx}' .
Explanation	An invalid DSST entry was encountered.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK229E	ERROR: All specified ISNs do not belong to the given file. Processing aborted .
Explanation	An ISN error was encountered.
Action	Analyze and correct the supplied parameters and rerun.
CHK230I	MAXCALLS will be ignored due to the NOSYNC or UTYPE specification. Message is only given once and only if an error is encountered.
Explanation	This message is received when MAXCALLS is specified with UTYPE=EXU.EXF or NOSYNC. MAXCALLS does not pertain when any of these parameters are specified.
Action	No action is required for this informational message.
CHK231I	Invalid internal error call {n} passed to ADACHK error routine.
Explanation	A call was made to an internal routine to process a possible transient error but an invalid call type was detected.
Action	Save this message and contact your Software AG technical support representative for assistance.
CHK233E	ERROR: Only single FILE must be specified in conjunction with {parm} parameter .
Explanation	Only a single file number can be specified with the parameter listed in the message (<i>parm</i>).
Action	Analyze and correct the supplied parameters and rerun.
CHK234E	ERROR: Only single FILE and single ISN must be specified in conjunction with COMPREC parameter .
Explanation	Only a single file number and a single ISN can be specified with the COMPREC parameter.
Action	Analyze and correct the supplied parameters and rerun.
CHK235E	ERROR: {AC AC2} ISN {isn} was not found in DS block {blk} specified by AC/AC2 element.
Explanation	A mismatch exists between the address converter (AC) or the secondary address converter (AC2) elements and Data Storage or when spanned records are enabled. An ADACHK ASSOPRINT and DATAPRINT of the specific RABNs will help analyze further.
Action	Contact your Software AG technical support representative for assistance.

CHK236E	ERROR: AC/AC2 ISN {nnnnn} was not found in AC/AC2. The highest ISN in AC/AC2 is {nnnnnnn}. May be FCB contains incorrect AC/AC2 extent descriptions or invalid first unused ISN.
Explanation	The first unused ISN in the FCB and the first unused ISN in the address converter or the secondary address converter do not match when spanned records are enabled,. An ADACHK ASSOPRINT and FCBPRINT of the specific RABNs will help analyze further.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK237E	ERROR: Function is not specified.
Explanation	No ADACHK function was supplied for the run.
Action	Analyze and correct the supplied parameters and rerun.
CHK238I	{ASSO DATA} RABNs {ravn1} - (x'xxxxxxxx') - {ravn2} - (x'xxxxxxxx') from specified RABN range is outside of extents for file {fn}. Only {ASSO DATA} RABN(s) which belong to the file will be processed. Run ADAREP utility to obtain information about file extents.
Explanation	The RABNs listed in the message are outside the range of extents for the file and will not be processed.
Action	Run the ADAREP utility to obtain information about the file extents.
CHK239E	ERROR: {ASSO DATA} RABNs {ravn}>(x'xxxxxxxx') from specified RABN range is outside of extents for file {fn}. Run ADAREP utility to obtain information about file extents.
Explanation	The RABNs listed in the message are outside the range of extents for the file and will not be processed.
Action	Run the ADAREP utility to obtain information about the file extents.
CHK240E	ERROR: Parameter {parm} is not allowed for function {function} .
Explanation	An invalid parameter (<i>parm</i>) was specified for the ADACHK function (<i>function</i>) identified in the message.
Action	Analyze and correct the supplied parameters and rerun.

CHK241E **ERROR: The file number in the FCB of File {fn} is invalid. Current value is {nnnn} (x'{xxxx}').**

Explanation An FCB error occurred for the file listed in the message (*fn*).

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK242E **ERROR: Invalid parameter UTYPE = {utype} Value of parameter UTYPE must be ACC / UTI / EXU (default is ACC).**

Explanation An invalid value was specified for the UTYPE parameter.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK243E **GCB2 contains error(s). Processing terminated.**

Explanation An error occurred with the secondary general control block (GCB2).

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK244E **ERROR: The value of parameter MAXDESCLEN = {length} is not in a range 10-255**

.

Explanation An invalid value was specified for the MAXDESCLEN parameter.

Action Analyze and correct the supplied parameters and rerun.

CHK245E **ERROR: {ASSO | DATA} FROM-TO RABNs is outside of extents for file {fn}. Run ADAREP utility to obtain information about file extents .**

Explanation Associator or Data Storage RABNs are outside the range of extents for the file.

Action Run the ADAREP utility to obtain information about the file extents.

CHK246E **ERROR: File {fn} is incorrect. File number must be only in range 1 - {maxfiles} .**

Explanation An invalid file number was specified.

Action Analyze and correct the supplied parameters and rerun.

CHK247I **ERROR: File {fn} is not loaded.**

Explanation The file number listed in the message (*fn*) is not loaded. Typically, this occurs when a range of files is specified and LAYOUT=LONG. This notifies you of the files in the specified range that were not loaded.

Action No action is required for this informational message.

CHK248I	Files exceed the highest file currently loaded were found in input parameters. These Files are ignored. The highest file currently loaded is {fn}.
Explanation	File numbers exceeding the highest file currently loaded were found in the input parameters and will not be processed.
Action	No action is required for this informational message.
CHK249E	ERROR: In parameter(s) File {fn1} {nnnn} -(x'{xxxx}') - {fn2} - (x'{xxxx}') start of range value exceeds end of range value.
Explanation	The file number range specified for the run was not specified in ascending order. All file number ranges must be supplied in ascending order.
Action	Correct the file number range specification and rerun the job.
CHK250E	ERROR: Invalid parameter LAYOUT = {layout}. Value of parameter LAYOUT must be LONG / MEDIUM / SHORT (default is SHORT).
Explanation	An invalid value was specified for the LAYOUT parameter. Valid values are LONG, MEDIUM, or SHORT.
Action	Specify a valid value for the LAYOUT parameter or remove the LAYOUT parameter from the run (it will then default to SHORT). Then rerun the ADACHK job.
CHK251I	Parameter FILE is omitted. All files will be processed.
Explanation	The FILE parameter has been omitted for this ADACHK run. All files will be processed.
Action	No action is required for this informational message.
CHK252E	ERROR: Parameter {parm} is essential for function {fxname}.
Explanation	The parameter named in the message (<i>parm</i>) is required for the function named in the message (<i>fxname</i>), but was not provided.
Action	Supply the parameter (and appropriate parameter value) and try again.
CHK253E	ERROR: The value of parameter NUMBER = {value} is not in range 1 - 8.
Explanation	An invalid value has been specified for the NUMBER parameter. Valid values range from 1 through 8.
Action	Correct the NUMBER parameter and try again.

CHK254E	ERROR: Parameter {parm1} must be specified in conjunction with {parm2} parameter(s).
Explanation	The parameter named in the message (<i>parm1</i>) was not specified in conjunction with other parameters it requires. The other required parameters are also named in the message (<i>parm2</i>).
Action	Specify all required parameters (and dependent parameters) in the job and try again.
CHK255E	ERROR: Parameter {parm1} cannot be specified in conjunction with {parm2} parameter(s).
Explanation	The parameter named in the message (<i>parm1</i>) was specified in conjunction with other parameters it cannot be specified with. The parameters it is in conflict with are also named in the message (<i>parm2</i>).
Action	Correct the parameter specifications and try again.
CHK256E	ERROR: Highest Index level in FCB is not from 3 to 15 range. Current value is {n} (x'{x}'), offset in FCB - x'{xx}' .
Explanation	An index error in the FCB was encountered.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK257E	ERROR: Rotating ISN {nnnn} (x'xxxxxxxx') in {AC AC2} in FCB is incorrect. It should not be zero or greater than the {highest allocated topisn+1} {AC AC2} ISN {nnnn} (x'xxxxxxxx'). Offset to the rotating {AC AC2} ISN in FCB - x'xxxx'. Offset to the {highest allocated topisn+1} {AC AC2} ISN in FCB - x'xxxx'.
Explanation	An error occurred with the rotating ISN in the address converter or the secondary address converter.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK258E	ERROR: The {AC AC2} ISN is not set. Offset to the {AC AC2} ISN in FCB - x'xx}' .
Explanation	An ISN error occurred in the address converter or the secondary address converter.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK259E	ERROR: The {AC AC2} ISN {nnnn} (x'xxxx') exceeds the {AC AC2} ISN {nnnn} (x'xxxx'). Offset to the AC ISN in FCB - x'xx'. Offset to the AC2 ISN in FCB - x'xx' .
Explanation	An ISN error occurred in the address converter or the secondary address converter.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK260E	ERROR: 1st unused {AC AC2} ISN {nnnn} (x'xxxx') must not be higher than the {AC AC2} ISN {nnnn} (x'xxxx'), plus 1. Offset to the 1st unused {AC AC2} ISN in FCB - x'x'. Offset to the {AC AC2} ISN in FCB - x'xx' .
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK261E	ERROR: DS RABN {ravn} (x'xxxxxxxx') is more than maximum DS RABN mapped by last DSST extent .
Explanation	A Data Storage RABN is higher than the maximum Data Storage RABN mapped by the last DSST extent.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK262E	ERROR: The maximum {AC AC2} ISN {nnnn} (x'xxxxxxxx') must correspond to the highest allocated {AC AC2} ISN {nnnn} (x'xxxxxxxx'). Offset to the maximum {AC AC2} ISN in FCB - x'xxxx'. Offset to the highest allocated {AC AC2} ISN in FCB - x'xxxx}0'.
Explanation	An ISN error occurred in the address converter or the secondary address converter.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK263I	Invalid first reusable {NI UI} RABN has been detected in FCB. The chain of empty {NI UI} index blocks will not be checked.
Explanation	An invalid RABN was encountered in the FCB.
Action	No action is required for this informational message.
CHK264E	ERROR: Field {nn} has invalid packed value x'xxxxxxxx'.
Explanation	The packed value of a field is invalid.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK265I **The NOSYNC parameter has been specified. Therefore, no nucleus calls will be made to ensure that errors are real. Therefore, any errors reported may be due to concurrent updates. To distinguish persistent errors from transient errors, please remove the NOSYNC parameter.**

Explanation This message appears when the NOSYNC parameter has been specified.

Action No action is required for this informational message.

CHK266I **Dump {type} block {nnnn} (x'{xxxx}').**

Explanation Dump information is provided in this message.

Action No action is required for this informational message.

CHK267E **ERROR: Offset is bigger than ASSO block size. Type block RABN {ravn} (x'{xxxxxxxx}') at offset x'{xx}' .**

Explanation A requested offset is larger than the Associator block size.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK268E **ERROR: {block} {type} Padding factor {nn} for file {fn} is invalid. The value must be specified in the range 1-90 .**

Explanation The padding factor for a file is invalid.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK269E **ERROR: Invalid syntax of CODE parameter.**

Explanation An error was encountered with the specification of the CODE parameter.

Action Correct the syntax of the CODE parameter and try again.

CHK270W **WARNING: Parameter {parm1} is incompatible with {parm2} parameter. {parm2} parameter is ignored.**

Explanation Incompatible parameters were specified. One of the parameters is ignored.

Action Correct the specified parameters and rerun the ADACHK job.

CHK271E	ERROR: {AC AC2} ISN = {nnnn} (x'xxxx') was found in DS RABN = {rabn1} (x'xxxxxxxx'). DS RABN for this ISN from {AC AC2} is {rabn2}> (x'xxxxxxxx') .
Explanation	An ISN error occurred in the address converter or the secondary address converter.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK272E	ERROR: {AC AC2} ISN = {nnnn} (x'xxxxxxxx') was not found in any DS RABN. {AC AC2} element contains DS RABN = {rabn} (x'xxxxxxxx') .
Explanation	An ISN error occurred in the address converter or the secondary address converter.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK273I	The UTYPE={EXF EXU} parameter has been specified. Therefore, no nucleus calls are necessary to ensure that errors are real.
Explanation	This message is given when UTYPE=EXF or UTYPE=EXU is specified. It is only given once if an error is encountered.
Action	No action is required for this informational message.
CHK274E	ERROR: {AC AC2} element of ISN {nnnn} (x'xxxxxxxx') from ASSO RABN {rabn} (x'xxxxxxxx') contains invalid DS RABN {rabn} (x'xxxxxxxx'). This RABN does not belong to any of the file extents.
Explanation	The primary (AC) or secondary (AC2) address converter element for the ISN shown in the message (<i>nnnn</i>) contains a DS RABN that does not belong to the file extents.
Action	Perform an FCBPRINT to check the file extents and identify the problem. Contact your Software AG technical support representative for assistance if necessary.
CHK275E	ERROR: Segment count in spanned record with ISN = {nnnnn} exceeds maximum.
Explanation	The spanned Data Storage chain with the ISN shown in the message (<i>nnnn</i>) has more than the maximum number of segments allowed.
Action	Contact your Software AG technical support representative for assistance.
CHK276E	ERROR: Secondary record in DS RABN {rabn} (x'xxxxxxxx') contains an inconsistent value of primary ISN {nnnn} (x'xxxxxxxx').
Explanation	An error was encountered with the secondary ISN or spanned Data Storage chain. If the nucleus is active, this message will be preceded by additional messages to aid in resolving the issue.
Action	Run the ADACHK DATAPRINT utility function against the Data Storage RABN to obtain more information. Contact your Software AG technical support representative for assistance.

CHK277E	ERROR: Invalid value {nn} (x'{xx}') for number of ISNs per {AC AC2} block. Offset to invalid value in FCB - x'{xx}' .
Explanation	An ISN error occurred in the address converter or the secondary address converter.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK278E	ERROR: {AC AC2} ISN = {nnnn} (x'{xxxx}') greater than last {AC AC2} ISN = {nnnn} (x'{xxxx}') was found in DS RABN {ravn} (x'{xxxxxxxx}') .
Explanation	An ISN error occurred in the address converter or the secondary address converter.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK279E	ERROR: The parent field {fld} for Collating Descriptor {desc} must have either ALPHA or WIDE format.
Explanation	A collating descriptor was defined without a parent field in alphabetic or wide-character format.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK280E	ERROR: Formats of subfield/subdescriptor {desc} and its parent field {fld} are not the same .
Explanation	The formats of the subfield or subdescriptor and the parent field are not the same.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK281E	ERROR: The superfield/superdescriptor {desc} has invalid format. Permitted format for such field is either ALPHA or WIDE or BINARY.
Explanation	The superfield or superdescriptor has an invalid format.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK282E	ERROR: The sub-/superfield/descriptor {desc} has unpermitted format. Permitted format is either FIXED or FLOAT.
Explanation	The subfield, superfield, subdescriptor, or superdescriptor has an invalid format.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK283E	ERROR: Duplicate ISN {nnnn} (x'{xxxx}') found in DS RABNs - {ravn1} (x'{xxxxxxxx}') and {ravn2} (x'{xxxxxxxx}') .
Explanation	A duplicate ISN was found in Data Storage.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK284E	ERROR: Secondary ISN {nnnn} (x'{xxxxxxxx}') found in DS RABN {ravn} (x'{xxxxxxxx}') but not referenced by a primary ISN.
Explanation	A secondary ISN was found that has no corresponding primary ISN. Note: Before this error is printed, ADACHK rereads the associated blocks to see if it can rectify the error on its own. If so, the transient error count is incremented and no error is printed. If it cannot rectify the error and the nucleus is down, the error is printed. If it cannot rectify the error and the nucleus is up, a call to the nucleus is made to determine if there is indeed a problem with the ISN and if it has been abandoned. In verifying the original error, if the nucleus finds another error, the error will be returned to ADACHK and ADACHK will print both this error and the additional error found. The additional errors that would precede this message are listed below. These will only occur if the nucleus is up.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK284W	WARNING: Secondary ISN {nnnn} (x'{xxxx}') in DS RABN {ravn} (x'{xxxxxxxx}') but not referenced by a primary ISN. Removing the FROMRABN/TORABN parameter will most likely resolve the warning .
Explanation	A secondary ISN was found that has no corresponding primary ISN.
Action	Remove the FROMRABN and TORABN parameter settings and try again.
CHK285E	ERROR: Duplicate secondary ISN {nnnn} (x'{xxxx}') found in DS RABNs - {ravn1} (x'{xxxxxxxx}') and {ravn2} (x'{xxxxxxxx}') .
Explanation	A duplicate secondary ISN was found.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK286E	ERROR: File {fnr} is coupled to file {fnr2}. File {fnr2} is currently not loaded.
Explanation	The coupled file has not been loaded or has been removed.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK287I	A call was just made to the nucleus to confirm if a CHK284E error was real or transient. The nucleus encountered the following error attempting the validation.
Explanation	ADACHK made a call to the nucleus to determine whether error CHK284E was caused by a secondary ISN that was abandoned was transient or real. In validating the error, the nucleus, encountered one of the following different errors: CHK274E , CHK276E , CHK288I , CHK289I , CHK290I , CHK291E , CHK292E , CHK293E , CHK294E , or CHK295E . After one of these errors is printed, CHK284W is also printed.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK288I	Unrecognized error {nn} returned from the nucleus for ADACHK type {xx}.
Explanation	ADACHK attempted to call the nucleus to validate the error displayed below. The nucleus returned an unexpected error code <i>nn</i> for function type <i>xx</i> . The original error will be displayed since ADACHK was unable to verify with the nucleus.
Action	This informational error message should be reported to your Software AG technical support representative.
CHK289I	Invalid primary ISN parameter {parm} (x'xxxxxxxx') passed from ADACHK to the nucleus. The primary ISN provided was either zero or greater than the first unused ISN.
Explanation	ADACHK attempted to call the nucleus to validate the error displayed below. The primary ISN passed was invalid. The original error will be displayed since ADACHK was unable to verify with the nucleus.
Action	This informational error message should be reported to your Software AG technical support representative so this internal error can be corrected.
CHK290I	Invalid secondary ISN parameter 18 (x'xxxxxxxx') passed from ADACHK to the nucleus. The secondary ISN provided was either zero or greater than the first unused secondary ISN.
Explanation	ADACHK attempted to call the nucleus to validate the error displayed below. The secondary ISN passed was invalid. The original error will be displayed since ADACHK was unable to verify with the nucleus.
Action	This informational error message should be reported to your Software AG technical support representative so this internal error can be corrected.

CHK291E	The spanned DS header for the primary ISN {nnnn} (x'xxxxxxxx') in DS RABN {ravn} (x'xxxxxxxx') was invalid. [A spanned DS record must be either a primary or a secondary record. Both are not permitted. Offset to record in DS block - x'xxxx']
Explanation	The header of the primary spanned record with the ISN number listed in the message (<i>nnnn</i>) is erroneous. Possible causes include: <ul style="list-style-type: none"> ■ The spanned Data Storage header indicator for a primary record is incorrectly set. Either the primary spanned record bit or the secondary spanned record bit should be on (but not both). ■ The next ISN in the spanned Data Storage header is invalid.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK292E	The spanned DS header for the secondary ISN {nnnn} (x'xxxxxxxx') in DS RABN {ravn} (x'xxxxxxxx') was invalid.
Explanation	The header of the secondary spanned record with the ISN number listed in the message (<i>nnnn</i>) is erroneous.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK293E	Secondary ISN {nnnn} (x'xxxxxxxx') in DS RABN {ravn} (x'xxxxxxxx') points to an invalid next ISN.
Explanation	The secondary header segment points to a next ISN that is erroneous.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK294E	The AC2 has the secondary ISN {nnnn} (x'xxxxxxxx') in DS RABN {ravn} (x'xxxxxxxx') but the ISN is missing in the DS RABN.
Explanation	The secondary address converter indicates that the secondary ISN shown in the message (<i>nnnn</i>) is in the Data Storage RABN listed in the message (<i>ravn</i>), but the ISN is missing in the Data Storage RABN.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK295E **Primary ISN {nnnn} (x'{xxxxxxxx}') in DS RABN {ravn} (x'{xxxxxxxx}8') points to an invalid next ISN.**

Explanation The primary header segment points to a next ISN that is erroneous.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK296I **A call was just made to the nucleus to confirm the validity of the spanned DS storage chain. The nucleus encountered the following error attempting the validation.**

Explanation While attempting to validate the consistency of the spanned Data Storage storage chain, one of the following additional errors was encountered: [CHK274E](#), [CHK275E](#), [CHK289I](#), [CHK291E](#), [CHK292E](#), [CHK293E](#), [CHK295E](#), [CHK297E](#), [CHK298E](#), [CHK299E](#), [CHK337E](#), [CHK338E](#), or [CHK339E](#). After one of these errors is printed, either a compression error (CRV* message) or [CHK276E](#) is also printed.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK297E **Invalid block length or record length in DS RABN {ravn} (x'{xxxxxxxx}') for primary ISN {nnnn} (x'{xxxxxxxx}').**

Explanation An invalid block length or record length was detected. This may be preceded by error [CHK142I](#). An unexpected nucleus response code was received.

Action Investigate the cause of the error, based on the information provided for the response code from [CHK142I](#). Then correct the record or block listed in this message (CHK297E) and rerun the job. If the problem persists, contact your Software AG technical support representative for assistance.

CHK298E **Invalid block length or record length in DS RABN {ravn} (x'{xxxxxxxx}') for secondary ISN {nnnn} (x'{xxxxxxxx}').**

Explanation An invalid block length or record length was detected for a secondary ISN. This may be preceded by error [CHK142I](#). An unexpected nucleus response code was received.

Action Investigate the cause of the error, based on the information provided for the response code from [CHK142I](#). Then correct the record or block listed in this message (CHK297E) and rerun the job. If the problem persists, contact your Software AG technical support representative for assistance.

CHK299E **The primary ISN is invalid in the spanned DS record header of primary ISN {nnnn} (x'{xxxxxxxx}') in DS RABN {ravn} (x'{xxxxxxxx}').**

Explanation There is an inconsistency in the primary ISN found in the header for the primary ISN.

Action Run an ADACHK DATAPRINT job of the Data Storage RABN for further analysis. Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK300E	ERROR: Descriptor {desc} is not found in FDT, RABN {ravn} (x'xxxxxxxx'), offset x'xx' .
Explanation	A descriptor was found in a U3 block that is not in the field definition table (FDT). Every field in the index must be a descriptor if the file is coupled: a subdescriptor, superdescriptor, hyperdescriptor, or phonetic descriptor, a coupling descriptor, or a collation descriptor.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK301E	ERROR: FDT and Index control bytes mismatch for DE {desc} is found in RABN {ravn} (x'xxxxxxxx') offset x'xx' .
Explanation	An FDT and index control byte mismatch occurred for the descriptor (<i>desc</i>) listed in the message. The comparison of the two compares the control byte IXUCTL of the index with the control byte FDTF of the FDT.
Action	When this error occurs, dump and print the FDT using the ADACHK FDTPRINT utility and the index block in question with ASSOPRINT. Then contact your Software AG support representative for assistance.
CHK302E	ERROR: First element of DE {desc} is found but upper index element found in RABN {ravn}> (x'xxxxxxxx'), offset x'xx' does not indicate the first element of descriptor .
Explanation	The upper index blocks contain index entries for one or more descriptors. The first element for a given descriptor contains the first element bit, or FE BIT. A missing FE bit can result in incorrect index positioning or Adabas response codes.
Action	Document the error. Try to fix the error as soon as possible, for example by reinverting the descriptor where the error occurred.
CHK304E	ERROR: Duplicate element of empty DE {desc} is found in RABN {ravn} (x'xxxxxxxx'), offset x'xx'.
Explanation	There are at least two U3 entries for an empty descriptor. Each descriptor has at least one entry on the U3 level. There may be several entries for one descriptor when the descriptor spans several MI blocks, because each MI block has an entry on the U3 level. Although there are no MI blocks for an empty descriptor, there must be one (and only one) U3 entry.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK305E	ERROR: {desc1}/{desc2} DE names do not agree. {idx-level} index element located in RABN {ravn} (x'xxxxxxxx'), offset x'xx'. {idx-level} index element located in RABN {ravn} (x'xxxxxxxx'), offset x'xx' .
Explanation	Each upper-level index element contains the field name for the descriptor, and also points to a lower-level block. The field name in the first element in the lower-level block must agree with the field name in the higher-level element.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK306E	ERROR: {desc1}/{desc2} DE values do not agree. {idx-level} index element located in RABN {ravn} (x'xxxxxxxx'), offset x'xx'. {idx-level} index element located in RABN {ravn} (x'xxxxxxxx'), offset x'xx' .
Explanation	Each U3 element contains a value and an MI RABN. The first MI element (in the MI block pointed to by the U3 element) should contain the same value as the U3 element. If not, this message occurs. This message also occurs if an MI element contains a value that is greater than the value in the first NI element (in the NI block pointed to by the MI element).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK307E	ERROR: {idx-level1}/{idx-level2} ISNs do not agree. {idx-level1} index element located in RABN {ravn} (x'xxxxxxxx'), offset x'xx'. {idx-level2} index element located in RABN {ravn} (x'xxxxxxxx'), offset x'xx' .
Explanation	Each MI element points to an NI block. If the first ISN in the ISN list for the first NI element (in that NI block) is not the lowest ISN for that value, then that NI element ISN should be equal to or greater than the MI ISN. If the NI ISN is less, this message occurs.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK308I	The following secondary ISN error could not be fully verified by the nucleus.
Explanation	A secondary ISN with no master ISN was found. The master ISN is needed to confirm if the error is real or transient. Most likely this is due to the timing of the spanned data storage update.
Action	No action is required for this informational message.

CHK309E	ERROR: MI ISN {nnnn} (x'xxxx') is invalid. It should be zero. RABN {ravn} (x'xxxxxxxx'), offset to element x'xx', DE name {desc} .
Explanation	An error occurred with the MI ISN.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK310E	ERROR: Error initializing collating user exit. Return Code = {rc} .
Explanation	An error occurred initializing the collating user exit.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK311E	ERROR: Collating user exit is not loaded.
Explanation	The collating user exit is not loaded.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK312E	ERROR: Descriptor {desc} was found in FDT but has not been checked in indices because of errors detected above .
Explanation	A descriptor was found in the FDT but was not checked due to other processing errors.
Action	Review other errors that appear with this one to resolve the error.
CHK313W	WARNING: Error in FCB related to COUPLED facility has been detected. ICHECK function will be executed without COUPLED indices checks .
Explanation	An FCB error related to the coupling facility has been encountered.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK314E	ERROR: {DATA UI NI AC AC2} extent {nnnn} (x'xxxx') - {nnnn} (x'xxxx') overlaps {DATA UI NI AC AC2} extent {nnnn} (x'xxxx') - {nnnn} (x'xxxx') .
Explanation	An error with the extents listed in the message occurred.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK317I	Errors in extents are detected. Checking for gaps and overlaps cannot be performed.
Explanation	An internal error processing the extent overlap and gap checking has been detected.
Action	This is an informational message only and processing will continue. Please run an ADAREP to determine if gaps or overlaps exist and contact your Software AG technical support representative if you need assistance or suspect an error.
CHK318E	ERROR: # {NI UI} blocks processed greater than # {NI UI} blocks used .
Explanation	In performing the index check, a count is taken of the UI blocks read. The number of blocks used is the sum of the number of blocks used in each UI extent, which depends on the first RABN and first unused RABN for each extent. If the number of blocks processed exceeds the number used, at least one ix-block-number RABN occurs in more than one of that block type, because each ix-block-number RABN processed is checked to be sure it is within the used portion of some extent of the same index block type.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK319E	ERROR: Gap between extents: {from-blk} {to-blk} {type} {fn} .
Explanation	The extents that have gaps are printed.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK320E	ERROR: Extents overlap: {from-blk} {to-blk} {type} {fn}.
Explanation	The extents that have gaps are printed.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK321E	ERROR: Wrong pointer to last parent of super/hyper descriptor. Bad FDT, expected value: {nn1}, value found {nn2} .
Explanation	An error occurred with a pointer in the FDT.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK322E	ERROR: Problem encountered attempting to invoke the external sort routine, Return Code = {ioerror} .
Explanation	An error occurred attempting to invoke the external sort routine.
Action	Diagnose and correct the external sort problem. The return code is given in the message. Rerun ADACHK if necessary.

CHK323I	Start verification of expanded file chains.
Explanation	The consistency checking of the expanded file chains is in progress. This occurs at the beginning of ADACHK. If LAYOUT is specified, the expanded file chain is specified.
Action	No action is required for this informational message.
CHK324I	End verification of expanded file chains.
Explanation	The consistency checking of the expanded file chains has completed. If any errors were encountered, they would be displayed above this message.
Action	No action is required for this informational message. The consistency checking of the expanded file chains has completed. If any errors were encountered, they would be displayed above this message.
CHK325E	ERROR: File {fnr} has ISN overlap with previous file in chain.
Explanation	There is an overlap of ISNs between files in the chain.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK326E	ERROR: File {fnr} has incorrect anchor {fnr}.
Explanation	The expanded file has an incorrect anchor file.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK327E	ERROR: MAXRECL {maxrecl} for file {fnr} does not match the MAXRECL {maxrecl} of the anchor {fnr}.
Explanation	The MAXRECL of files in the chain must match.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK328E	ERROR: The next file {fnr} was already found in a chain.
Explanation	The expanded file was already found in the expanded file chain.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK329E	ERROR: File {fnr} does not belong to a chain but has next {fnr} and anchor {fnr}.
Explanation	The file does not belong to an expanded file chain but contains chain information.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK330E	ERROR: Error initializing hyperexit number {nn}. Return Code = {rc}.
Explanation	An error was returned attempting to initialize the hyperexit listed in the message (<i>nn</i>).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK331W	WARNING: File {fnr} received an unexpected nucleus response {rspcode}.
Explanation	An unexpected nucleus response code was received.
Action	Analyze and determine the cause of the response code to determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK332E	ERROR: Response code {rc} subcode {sc} occurred while processing ISN = {nnnn} in file = {fn}.
Explanation	A problem in the spanned Data Storage record chain has been identified. Processing for this record will stop.
Action	Review preceding messages for more detail on the spanned Data Storage error.
CHK333W	WARNING: Sort encountered an unusual record. Record skipped.
Explanation	The sorter encountered a non-zero return code. Additional error information may be displayed if available.
Action	Provide the job output to your Software AG technical support representative for assistance.
CHK334E	ERROR: Empty field format detected.
Explanation	The descriptor format of zero was detected. Please investigate the cause.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK335E	ERROR: Nucleus verification check detected {AC AC2} element of ISN {isn} (x'xxxxxxxx') from ASSO RABN {ravn} (x'xxxxxxxx') contains invalid DS RABN {ravn} (x'xxxxxxxx'). This RABN does not belong to any of the file extents.
Explanation	This error can only occur if the nucleus is active. It is an additional check the nucleus makes to ensure that the Data Storage RABN found in the address converter is actually in the file extents. If it finds a problem, this error is printed. Typically, a CHK274E message will also be reported.
Action	Contact your Software AG technical support representative for assistance.
CHK335I	ASSO block between 10 and 14 requested, printing entire FST.
Explanation	The entire FST will be printed in its entirety.
Action	No action is required for this informational message.
CHK336W	WARNING: Nucleus must be active to do a REPAIR.
Explanation	REPAIR was specified in an ADACHK DSCHECK run, but the nucleus was not up at the time the repair was attempted. This error may appear multiple times if there are several DSST errors and the nucleus is down the entire time.
Action	Bring the nucleus up and try again.
CHK337E	The primary ISN {nnnn} (x'xxxxxxxx') was not found in DS RABN {ravn} (x'xxxxxxxx').
Explanation	The primary ISN was not found in the DS RABN as expected.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK338E	The secondary ISN {nnnn} (x'xxxxxxxx') was not found in DS RABN {ravn} (x'xxxxxxxx').
Explanation	The secondary ISN was not found in the DS RABN as expected.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK339E	The ISN is invalid in the spanned DS record header of secondary ISN {nnnn} (x'xxxxxxxx') in DS RABN {ravn} (x'xxxxxxxx').
Explanation	The ISN in the secondary ISN header is invalid.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK340I **A call was just made to the nucleus to confirm if a validation error was real or transient. The nucleus encountered the following error attempting the validation.**

Explanation ADACHK made a call to the nucleus to confirm if a ADACHK VALIDATE error was transient or real. In validating the error, the nucleus encountered a different error which is displayed below.

Action No action is required for this informational message. Refer to the additional message for information about the new error encountered.

CHK341E **A spanned DS record was found for file {fn} in DS RABN {rabn} (x'xxxxxxxx'). This file does not allow spanned DS records.**

Explanation The nucleus encountered a spanned Data Storage record for a file that does not allow spanned Data Storage records.

Action Contact your Software AG technical support representative for assistance.

CHK342E **Invalid ISN parameter 901 (x'xxxxxxxx') passed from ADACHK to the nucleus.**

Explanation The ISN passed to the nucleus for validation was invalid for the file.

Action Contact your Software AG technical support representative for assistance.

CHK343E **Length of DE = {xx} value passed is invalid. Length = {nn}.**

Explanation An internal error occurred during an attempt by ADACHK to call the nucleus to determine the type of index error that occurred. An invalid length (*nn*) for the descriptor (*xx*) value was specified.

Action Contact your Software AG technical support representative for assistance.

CHK344E **DE = {fld} is not found in the index.**

Explanation The descriptor passed to the nucleus for validation was not found in the index.

Action Contact your Software AG technical support representative for assistance.

CHK345E **Primary indicator not set for what was expected to be a primary ISN; DS RABN {rabn} (x'xxxxxxxx') .**

Explanation The ISN being validated was determined to be for a spanned Data Storage record, but did not have the primary indicator set.

Action Contact your Software AG technical support representative for assistance.

CHK346E	The DS RABN {rabn} (x'xxxxxxxx') passed to the nucleus for verification does not belong to any of the file extents. Error sequence number {n}
Explanation	The Data Storage RABN passed from ADACHK to the nucleus did not belong to the file extents.
Action	Contact your Software AG technical support representative for assistance.
CHK347I	A call was just made to the nucleus to confirm if an index type error was real or transient. The nucleus encountered the following error attempting the validation.
Explanation	ADACHK made a call to the nucleus to determine if the index error was transient or real. In validating the error, the nucleus encountered one of the following errors: CHK343E , CHK348E , CHK349E , CHK350E , CHK351E , CHK352E , or CHK408E .
Action	No action is required for this informational message. Review the action for the other error messages that appear with this message.
CHK348E	Invalid sub-function parameter {xx} passed from ADACHK to the nucleus.
Explanation	An internal error occurred during an attempt by ADACHK to call the nucleus to determine the type of index error that occurred. The invalid subfunction shown in the message (xx) was requested.
Action	Contact your Software AG technical support representative for assistance.
CHK349E	Invalid number of RABN/update count pairs: {nn} passed from ADACHK to the nucleus.
Explanation	An internal error occurred during an attempt by ADACHK to call the nucleus to determine the type of index error that occurred. An invalid number of RABN/update count pairs (nn) was specified.
Action	Contact your Software AG technical support representative for assistance.
CHK350E	Invalid target index level {nn} passed from ADACHK to the nucleus.
Explanation	An internal error occurred during an attempt by ADACHK to call the nucleus to determine the type of index error that occurred. An invalid index level (nn) was specified.
Action	Contact your Software AG technical support representative for assistance.
CHK351E	Invalid index RABN {rabn} (x'xxxxxxxx') passed from ADACHK to the nucleus. The RABN does not belong to any of the file extents.
Explanation	An internal error occurred during an attempt by ADACHK to call the nucleus to determine the type of index error that occurred. One or more of the index RABNs specified in the index RABN/update count pairs was outside of the file extents. The first invalid RABN encountered is shown in the message (rabn).
Action	Contact your Software AG technical support representative for assistance.

CHK352E	The record buffer specified could not hold all records.
Explanation	An internal error occurred during an attempt by ADACHK to call the nucleus to determine the type of index error that occurred. The record buffer specified could not contain all blocks to be returned from the nucleus.
Action	Contact your Software AG technical support representative for assistance.
CHK353I	Problem attempting read of last type RABN NN (x'xxxx'). JCL may not be correct.
Explanation	There was an error attempting to read the RABN.
Action	No action is required for this informational message.
CHK355I	ADACHK function {ACCHECK DSCHECK ICHECK VALIDATE} in progress.
Explanation	When specifying LAYOUT=LONG with the CHECK function, this message displays which function is currently in progress.
Action	No action is required for this informational message.
CHK356W	WARNING: Unreachable {NI UI} blocks were detected.
Explanation	An NI or UI index block exists that is not used and is not in the unused RABN chain.
Action	No immediate action is required. However, the RABN block cannot be used until either the Associator is reordered or an UNLOAD/LOAD sequence is performed.
CHK357E	Error: First element of MI block with the forward index compression option on must not be compressed. MI RABN {rabn} (X'xxxxxxxx'), offset X'xxxx'.
Explanation	The first element of an MI block is compressed and the forward index compression option is on. This is an error.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK358E	ISNs are not in ascending sequence in MI block. MI RABN {rabn} (X'xxxxxxxx'), offset X'xxxx'.
Explanation	The ISNs in the MI block are not in ascending sequence.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK359E	Error: MI value/ISN LE previous NI value/ISN. {idx-level1} index element located in RABN {rabn} (x'xxxxxxxx'), offset x'xx'. Current {idx-level2} element located in RABN {rabn} (x'xxxxxxxx'), offset x'xx' .
Explanation	An MI element has a value that is less than or equal to the value in the last NI element in the previous NI block. If the values are equal, the ISN in the MI element must be greater than the ISN in the previous NI element.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK361W	WARNING: Nucleus must be active to reset the rotating AC ISN pointer.
Explanation	RESET was specified for the ACSCAN function but the database was not currently active.
Action	Please retry the operation with the nucleus active.
CHK362E	ADACHK is unable to RESET the ISN due to the following unexpected nucleus response {nn}
Explanation	The call to the Adabas nucleus received the above response code and therefore the RESET did not execute successfully.
Action	Determine the cause of the response and correct it. If you need assistance, contact your Software AG technical support representative.
CHK363E	ERROR: The Parent field {fld} for sub-/superfield/descriptor {descriptor} has the LOB option set.
Explanation	A parent field error occurred; the parent field for the subfield, superfield, subdescriptor, or superdescriptor has the LB (large object) option set.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK401W	WARNING: File {fn} is in LOAD status.
Explanation	A previous ADALOD failed for the file.
Action	Correct the file status and rerun ADACHK: <ul style="list-style-type: none"> ■ restart the ADALOD job; ■ delete the file and rerun the ADALOD job; or ■ restore the SAVE file copy and rerun the ADALOD job.

CHK402W	WARNING: File {fn} is in REORDER status.
Explanation	A previous reorder failed for the file.
Action	Correct the file status and rerun ADACHK. Delete the file or overwrite it using ADAORD STORE or ADASAV RESTORE/RESTONL.
CHK403W	WARNING: File {fn} is in RESTORE status.
Explanation	A previous ADASAV job failed.
Action	Correct the file status and rerun ADACHK. Delete the file or overwrite it using ADAORD STORE or ADASAV RESTORE/RESTONL.
CHK404W	WARNING: File {fn} is in REFRESH status.
Explanation	A previous REFRESH job against the file was interrupted.
Action	Correct the file status and rerun ADACHK. Delete the file or overwrite it using ADAORD STORE or ADASAV RESTORE/RESTONL.
CHK405W	WARNING: Cannot validate CHECKPOINT FILE = {fn}.
Explanation	An error occurred while validating the checkpoint file.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK408E	ERROR: Invalid field name {fld} in DESCRIPTOR parameter.
Explanation	The descriptor passed to the nucleus for validation was not a valid descriptor.
Action	Contact your Software AG technical support representative for assistance.
CHK406W	WARNING: Cannot validate SECURITY FILE = {fn}.
Explanation	An error occurred while validating the security file.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK411E	ERROR: Parameter SORTTYPE is incorrect. Values of SORTTYPE can only be INTERNAL or EXTERNAL .
Explanation	An invalid value was specified for the SORTTYPE parameter. Valid values are INTERNAL or EXTERNAL.
Action	Specify a valid value for SORTTYPE and rerun the ADACHK job.

CHK412E	ERROR: ERRLIM = {errlim} is exceeded. Processing terminated .
Explanation	The value of the ERRLIM parameter has been exceeded.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK413E	ERROR: Parameter {parm} is incorrect.
Explanation	The parameter listed in the message (<i>parm</i>) is specified incorrectly.
Action	Correct the parameter specification and rerun the ADACHK job.
CHK414E	ERROR: Length of DE = {desc} from DATA exceeds the maximum possible = 15. DE-format - {PACKED UNPACKED}, ISN = {nnnn} (x'xxxx'), Length = {len}.
Explanation	The length of the descriptor from Data Storage exceeds the maximum possible length.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK415E	ERROR: Value of DE = {value} from DATA is incorrect. DE-format - {PACKED UNPACKED}, ISN = {nnnn} (x'xxxx'), Length = {len}, Value = x'xx' .
Explanation	The value of a descriptor from Data Storage is invalid.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CHK416W	WARNING: Value for field {fld} has been truncated. Errors for this field may be due to truncated values. Specify a larger MAXDESCLEN to avoid truncation of data storage record field values .
Explanation	The value for the field listed in the message (<i>fld</i>) has been truncated.
Action	Increase the setting of the MAXDESCLEN parameter to avoid truncation of the Data Storage field values. Then run the ADACHK job again.
CHK417I	The longest truncated field value was {nn} bytes. This value belongs to descriptor {desc}. Specify MAXDESCLEN at least this size on next run.
Explanation	This message provides information about field values truncated during ADACHK processing.
Action	Specify a setting for the MAXDESCLEN parameter that is at least the value specified in the message (<i>nn</i>). Then rerun the ADACHK job again.

CHK418E **The value for LWP is invalid. Minimum is 102400 (100K). Maximum is 2147483647 (x'xxxxxxxx')** or 9223372032559808512 (x'xxxxxxxxxxxxxxxxxxx') when running in a virtual 64bit environment.

Explanation The specified value for the LWP parameter is invalid.

Action Correct the LWP value and try again.

CHK498I **{function} started ***** ' {date} {time}'.**

Explanation The date and time that the function started are given in the message. Valid function names are ACCHECK, DSCHECK, ICHECK, ASSOPRINT, CLOGPRINT, DATAPRINT, DSIMPRINT, DSSTPRINT, FCBPRINT, FDTPRINT FSTPRINT GCBPRINT, NIPRINT, PLOGPRINT, PPTPRINT, RLOGPRINT, SORTPRINT, TEMPPRINT, UIPRINT, VALIDATE, WORKPRINT, and CHECK.

Action No action is required for this informational message.

CHK499I **{function} ended ***** ' {date} {time}'.**

Explanation The date and time that the function ended are given in the message. Valid function names are ACCHECK, DSCHECK, ICHECK, ASSOPRINT, CLOGPRINT, DATAPRINT, DSIMPRINT, DSSTPRINT, FCBPRINT, FDTPRINT FSTPRINT GCBPRINT, NIPRINT, PLOGPRINT, PPTPRINT, RLOGPRINT, SORTPRINT, TEMPPRINT, UIPRINT, VALIDATE, WORKPRINT, and CHECK.

Action Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CHK997I **Invalid input parameters for {fx}.
{ravn-list}.**

Explanation Invalid parameters were specified for the ADACHK function (*fx*) listed in the message. A list of RABNs in the Associator, Data Storage, Work and DSST is displayed.

Action Correct the input parameters for the ADACHK function listed in the message. Then rerun the ADACHK job.

79

ADACHK Utility CRV* Decompression Messages

CRV001E	ERROR: Invalid length for non null suppressed field {fld}.
Explanation	A compressed field that is not null-suppressed has a length indicator of x'00', x'01', x'8000', x'8001', or x'8002'.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV002E	ERROR: Insufficient record length for field {fld}.
Explanation	A field with FI option has a length that exceeds the remaining record length.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV003E	ERROR: Field length exceeds 253 bytes for field {fld}.
Explanation	A field whose exclusive length exceeds 253 and is not defined with LA option. Note: Embedded LOB values for fields defined with LB option should not exceed 253 bytes.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV004E	ERROR: End of FDT encountered before end of record.
Explanation	The end of the FDT has been reached but not the end of the record (an MU or PE at the end of the FDT can repeat).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CRV005E	ERROR: LOB indicator exists for field {fld} but field does not have LB option.
Explanation	A LOB reference indicator exists for a field not defined with LB option.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV006E	ERROR: LOB reference is not properly formatted for field {fld}.
Explanation	A LOB reference is not properly formatted (e.g. x'CO' is not followed by x'80').
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV007E	ERROR: Insufficient length remaining for LOB reference for field {fld}.
Explanation	A LOB reference exceeds the remaining record length.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV008E	ERROR: Field {fld} defined with FI option but flagged as empty.
Explanation	The field identified in the message (<i>fld</i>) is defined with the FI (fixed format) option but appears to be empty.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV009E	ERROR: Field {fld} defined with NN option but flagged as empty.
Explanation	The field identified in the message (<i>fld</i>) is defined with the NN (not null) option but appears to be empty.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV010E	ERROR: Field {fld} defined without NU and NC option but flagged as empty.
Explanation	The field identified in the message (<i>fld</i>) is empty but is defined without either the NU (null suppression) or NC (not counted) options.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CRV012E	ERROR: Alpha field {fld} has last byte of blank with inconsistent options.
Explanation	An alphanumeric field without the NB option and with the NU option has a last byte of x'40'. This is not possible unless the field has a one-byte length of x'02' or is defined with the FI option.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV013E	ERROR: Value for packed field {fld} exceeds 15 bytes.
Explanation	A packed/unpacked field with (exclusive) length exceeding 15
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV014E	ERROR: Packed field {fld} not correctly compressed.
Explanation	A packed/unpacked field has a leading x'00' as its first byte, indicating it might not be correctly compressed. This is not possible unless the field has the FI option.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV015E	ERROR: Packed field {fld} not null-suppressed.
Explanation	A packed/unpacked field defined with NU option and with x'02' as its length where the data byte is x'0D' or x'0F' (e.g. the field should have been null-suppressed).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV016E	ERROR: Packed field {fld} contains invalid data.
Explanation	A packed/unpacked field is not a properly packed value (e.g. any numbers ending with x'nA', x'nB'', x'nC', or x'nE' are invalid).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV017E	ERROR: Value for binary field {fld} exceeds 126 bytes.
Explanation	A binary field has a (exclusive) length exceeding 126 bytes.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CRV018E	ERROR: Binary field {fld} not correctly compressed.
Explanation	A binary field with leading x'00' as its first byte has a one-byte length that exceeds x'02' (e.g. the field is not properly compressed). This is not applicable if the field is defined with the FI option.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV019E	ERROR: Binary field {fld} not null-suppressed.
Explanation	A binary field defined with NU option and with x'02' as its length, but the data byte is x'00' (indicating the field should have been null-suppressed).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV020E	ERROR: Value for float field {fld} exceeds 8 bytes.
Explanation	A floating point field cannot exceed eight bytes. in second record at offset x1B6 zapped float field length from x04 to x0A
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV021E	ERROR: Float field {fld} not correctly compressed.
Explanation	A floating point field with a trailing x'00' as its last byte has a one-byte length that exceeds x'02' (e.g. the field is not properly compressed). This is not applicable if the field is defined with the FI option.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV022E	ERROR: Float field {fld} not null-suppressed.
Explanation	A floating point field is defined with the NU option, but the data bytes are all x'00's (e.g. the field should have been null-suppressed).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV023E	ERROR: length for wchar field {fld} exceeds 252 or is less than wchar length.
Explanation	A wide field is defined with a length that is less than the length of the defined wide space length (e.g. 2-byte wide space length + 1).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CRV024E	ERROR: wchar field {fld} not correctly compressed.
Explanation	A wide field is defined without the NB option and with the NU option, but ends with the defined wide space.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV025E	ERROR: wchar field {fld} not null-suppressed.
Explanation	A wide field is defined without the NB option and with the NU option, but ends with the defined wide space. This is not an error if the entire field contains only one wide space.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV026E	ERROR: Value for fixed field {fld} exceeds 8 bytes.
Explanation	A fixed point field has a (exclusive) length that exceeds 8 bytes.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV028E	ERROR: Fixed field {fld} not null-suppressed.
Explanation	A fixed point field is defined with the NU option, but the data bytes are all x'00's (e.g. the field should have been null-suppressed).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV029E	ERROR: MU Field {fld} has an invalid count.
Explanation	A field is defined as an MU field, but has an MU count of zero.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV030E	ERROR: MU Field {fld} has two byte value. File not defined with two byte MUs.
Explanation	A two-byte MU count is indicated (x'C0') for a field, but the field is not defined with a two-byte MU/PE option.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CRV031E	ERROR: MU Field {fld} has invalid two byte value.
Explanation	A two-byte MU count is indicated (x'C0') for a field, but the next byte is not x'02'.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV032E	ERROR: MU Field {fld} at end of record.
Explanation	The record ends with an MU count (one-byte or two-byte field).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV033E	ERROR: PE Field {fld} has an invalid count.
Explanation	A field is defined as a PE field, but has a PE count of zero or a count greater than 191.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV034E	ERROR: PE Field {fld} has two byte value. File not defined with two byte PEs.
Explanation	The record ends with a PE count (a one-byte or two-byte field).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV035E	ERROR: PE Field {fld} has invalid two byte value.
Explanation	A two-byte PE count is indicated (x'C0'), but the file is not defined with a two-byte MU/PE option.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV036E	ERROR: PE Field {fld} at end of record.
Explanation	The record cannot end with a PE count. This is invalid.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV037E	ERROR: Remaining MU occurrences for {fld} but insufficient data in record.
Explanation	Remaining MU occurrences are indicated in the MU count, but the end of the record has been reached.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

CRV038E	ERROR: Remaining PE occurrences for {fld} but insufficient data in record.
Explanation	Remaining PE occurrences are indicated in the PE count, but the end of the record has been reached.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV039E	ERROR: Wchar field {fld} encountered for file without UES support.
Explanation	A wide character field was encountered in a file without universal encoding support (UES).
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.
CRV040E	ERROR: Wchar field {fld} length is invalid.
Explanation	The Wchar length is invalid.
Action	Determine the cause of the error and correct it. If you need assistance, contact your Software AG technical support representative.

80

ADACHK Utility SRT* Sort Messages

SRT001I **Sort statistics: {statistic-messages}**

Explanation

This message lists various statistics about ADACHK sort processing, as described in the following table.

Statistic Message Text	Description
Number of sort records: <i>nnn</i> records	Displays the number of records that were sorted.
Size of sort records: <i>nnn</i> bytes	Displays the cumulative size of the records that were sorted.
Size of compressed records: <i>nnn</i> bytes	Displays the cumulative size of any compressed records that were processed.
Highest RABN used: <i>nnn</i>	Displays the highest RABN written to the sort data sets during sort processing.
Number of subsequences: <i>nnn</i>	Displays the number of sorted lists created from the input records. When the sorted records are output, the available sort pool storage must be large enough to hold at least one block for every subsequence (sorted list) created during processing.
Size for merging available: <i>nnn</i> bytes	Displays the storage size available in the sort pool to store the data blocks read from the sort data set.
Size for merging used: <i>nnn</i> bytes	Displays the storage size used in the sort pool used to store the data blocks read from the sort data set during sort processing.
Sort completed successfully	Displays that sort processing completed successfully.

Action

No action is required for this informational message.

SRT002E **Sort pool allocation failed**
{storage-stats}

Explanation This message indicates that the requested storage was not obtained. More detail is found in the storage statistics shown in the message:

Storage Statistic Text	Description
IOR/system error codes: <i>codes</i>	Displays the IOR and system error codes produced by sort processing.
Storage requested: <i>nnn</i> bytes	Displays the amount of storage requested.
Storage allocated: <i>nnn</i> bytes	Displays the amount of storage allocated for sort processing.

Action To resolve this error, do one or more of the following things:

- Reduce the value setting of the LWP parameter for the ADACHK run.
- Depending on your operating system, increase the region size for ADACHK processing.
- Depending on your operating system, use 64-bit virtual storage be used by specifying the ADARUN parameter V64BIT=YES.

SRT003E **Sort pool full**
{sort-pool-stats}

Explanation This message indicates that the sort pool is full. More detail is found in the sort pool statistics shown in the message:

Sort Pool Statistic Text	Description
Number of input records: <i>nnn</i> records	Displays the number of records input to sort processing.
Size of input records: <i>nnn</i> bytes	Displays the cumulative size of the records input to sort processing.
Size of compressed records: <i>nnn</i> bytes	Displays the cumulative size of any compressed records that were input to sort processing.
Too many subsequences: <i>nnn</i> Increase size of Sort Pool	Indicates that there was not enough sort pool storage available to store one block per subsequence (sorted list) at the same time.
Increase size of Sort Pool or specify Sort data set(s) DDSORTR1/2	Indicates that there was not enough sort pool storage available for sort processing.

Action To resolve this error, do one or more of the following things:

- Increase the value setting of the LWP parameter for the ADACHK run.

- Provide one or more sort data sets (DDSORTR1 and DDSORTR2) in the job for the ADACHK run.

SRT004E

Invalid return code from sort exit**Exit: {exitname} return code {rc}****Explanation**

An unexpected response code occurred from the sort processing exit E15/E35.

Action

If you are using the internal sort facility (SORTTYPE=INTERNAL), contact your Software AG technical support representative for assistance. If you are using an external sort facility (SORTTYPE=EXTERNAL), contact the provider of the sort package for assistance.

SRT005E

Sort failed. Please refer to previous messages for details.**Explanation**

The sorter task failed. More information is provided in other SRT* messages.

Action

Contact your Software AG technical support representative for assistance.

SRT006E

Input record/byte counts not equal to output record/byte counts: {processing-stats}**Explanation**

This message indicates that a sort processing error occurred because the count of the input records (or bytes) to the sorter task did not match the count of the output records (bytes) from the sorter task. More detail is found in the sort processing statistics shown in the message:

Sort Processing Statistic Text	Description
Number of input records: <i>nnn</i> records	Displays the number of records input to sort processing. This text indicates that the sorter task was terminated abnormally while running the input phase or immediately after it is finished.
Size of input records: <i>nnn</i> bytes	Displays the cumulative size of the records input to sort processing. This text indicates that the sorter task was terminated abnormally while running the input phase or immediately after it is finished.
Size of compressed input records: <i>nnn</i> bytes	Displays the cumulative size of any compressed records that were input to sort processing. This text indicates that the sorter task was terminated abnormally while running the input phase or immediately after it is finished.
Number of output records: <i>nnn</i> records	Displays the number of records output from sort processing. This text indicates that the sorter task was terminated abnormally while running the output phase or immediately after it is finished.
Size of output records: <i>nnn</i> bytes	Displays the cumulative size of the records output from sort processing. This text indicates that the sorter task was terminated abnormally while running the output phase or immediately after it is finished.

Sort Processing Statistic Text	Description
Size of compressed output records: <i>nnn</i> bytes	Displays the cumulative size of any compressed records that were output from sort processing. This text indicates that the sorter task was terminated abnormally while running the output phase or immediately after it is finished.

Action Contact your Software AG technical support representative for assistance.

SRT007E Invalid invocation of ADASOR/ADAS6R/{mod} Reason code {rsn}

Explanation The sorter task was invoked with faulty or illogical parameters. This messages may be printed more than one time.

Action Make note of the reason code provided in the message and contact your Software AG technical support representative for assistance.

SRT009E SORT dataset too small

Explanation This message indicates that sort data set is too small for sort processing. More detail is found in the sort processing statistics shown in the message:

Sort Processing Statistic Text	Description
Number of input records: <i>nnn</i> records	Displays the number of records input to sort processing. This text indicates that the sorter task was terminated abnormally while running the input phase or immediately after it is finished.
Size of input records: <i>nnn</i> bytes	Displays the cumulative size of the records input to sort processing. This text indicates that the sorter task was terminated abnormally while running the input phase or immediately after it is finished.
Supply a larger SORT dataset. See the Adabas Utilities manual for instructions on how to calculate the SORT dataset size.	Indicates that a larger sort data set is needed.

Action To resolve this error, consider doing one or more of the following things:

- If only one sort file was used for the run (DDSORTR1), specify a second sort data set (DDSORTR2).
- Increase the size of the sort data set(s).

SRT019I	{time-of-day} Start of {phase-name}
Explanation	This messages identifies each phase of the sorter task when they start.
Action	No action is required for this informational message.
SRT020I	{time-of-day} End of phase-name, duration: {nnn} Min {nn} Sec {nnnnnn} Micro
Explanation	This messages identifies each phase of the sorter task when they finish and provides the duration time of the phase.
Action	No action is required for this informational message.
SRT022I	Sort aborted by user
Explanation	The sorter task was aborted by the user.
Action	No action is required for this informational message.
SRT023E	The properties of the Sort Data Sets do not match for device type. Supply identical properties for the SORT datasets and rerun the job.
Explanation	The device types of the sort data sets must be identical.
Action	Correct the ADACHK JCL/JCS and use two sort data sets with identical device types.
SRT025E	Internal error at xxxxxx Register contents at time of error: {register-contents} Inform your DBA
Explanation	An internal error occurred while the sorter was runnign in 64-bit mode. The left and right halves of the register contents are displayed in the message.
Action	Contact the database administrator (DBA) for your system.
SRT026I	Highest RABN formatted: {nnn}
Explanation	The highest RABN formatted during sort processing is given in the message.
Action	No action is required for this informational message.
SRT027I	Sort pool allocation not successful {storage-stats} Continue with reduced Sort pool size.
Explanation	This message indicates that the requested storage was not obtained. The sorter will continue using a sort pool size reduced to the amount of storage that could be obtained. More detail is found in the storage statistics shown in the message:

Storage Statistic Text	Description
Storage requested: <i>nnn</i> bytes	Displays the amount of storage requested.
Storage allocated: <i>nnn</i> bytes	Displays the amount of storage allocated for sort processing.

Action

No action is required for this informational message. However, after reviewing the statistics shown in the message, consider the following possible actions.

- Review the size of the LWP ADARUN parameter specified.
- Determine if the use of sort data sets is appropriate for this job. For more information, read *Sort Data Set Considerations*, in the *Adabas Utilities Manual*.
- Increase the region size.
- If possible, switch to 64-bit addressing mode.

81 ADACMP Utility Messages

ERROR-121 Invalid value for parameter RECFM

Explanation This parameter is required for z/VSE only. Valid values are:

RECFM=F	fixed
RECFM=FB	fixed blocked
RECFM=V	variable
RECFM=VB	variable blocked
RECFM=U	undefined

Action Supply the correct parameter value and rerun the job.

ERROR-122 Missing function code

Explanation One of the keywords COMPRESS or DECOMPRESS must be specified.

Action Supply the required function keyword to the input and then rerun the job.

ERROR-123 Missing field definition table (FDT)

Explanation The parameter input must contain either the field definition table or the parameter "FDT=file-number".

Action Add a valid FDT parameter, and then rerun the job.

ERROR-124	Error reading field definition table (FDT)
Explanation	The nucleus returned response code <i>nn</i> while reading the field definition table (FDT). "response" is the nucleus response.
Action	Investigate the cause of the error; correct it and rerun the job.
ERROR-125	Invalid value for parameter `UTYPE'
Explanation	Valid values are UTYPE=EXU or UTYPE=EXF.
Action	Supply the correct parameter value, and then rerun the job.
ERROR-126	Invalid input data set
Explanation	The input data set (EBAND/DDEBAND) must have a record format of variable or variable blocked.
Action	Supply a correct input data set and rerun the job.
ERROR-127	Syntax / semantic error found during field definition table (FDT) compilation
Explanation	...cause of message displayed here... Some of the causes are: <ul style="list-style-type: none">■ an SQL null field (NC) was specified with the NU (null suppression) option, or for a fixed-point (FI) field type.■ a multiple-value (MU) field or an occurrence in a periodic (PE) group was specified as an SQL null value (NC option) field.■ more than 254 elementary fields were defined in the specified (`xx') periodic (PE) group.
Action	Correct the field definition table (FDT) definition, and then rerun the job.
ERROR-128	Invalid value for the parameter `CODE'
Explanation	The value specified for the CODE parameter is either incorrect, or the CODE parameter is not valid in this case.
Action	Either remove the CODE parameter, or specify at most eight digits, or blanks. Rerun the job. Refer to the Adabas Security documentation for more information.

ERROR-129 The supplied format buffer is wrong

Explanation "FORMAT=XXXXXXXX" or "FORMAT=*" is incorrect.

Action Specify a correct value for format, and then rerun the job.

ERROR-130 Hyperexit not loaded

Explanation The hyperdescriptor exit number *nnnn* has not been defined to ADACMP.

Action Add the HEXnn parameter to the ADARUN input, and rerun the job. The HEX parameter nn defines the hyperdescriptor exit to ADACMP.

ERROR-131 Invalid value for the 'SORTSEQ' parameter

Explanation The following values are allowed:

SORTSEQ=ISN	to process an ISN sequence.
SORTSEQ=DE	where DE is any descriptor whose parent field is not an MU field or contained in a periodic group; that is not a phonetic descriptor or hyperdescriptor and does not have the NU option.

Action Supply the correct parameter value, and rerun the ADACMP job.

ERROR-132 Descriptor {desc-name} for file {file-number} has the 'NU' option

Action Select another descriptor, or add the parameter NU to the utility input. In this case, records may be lost. See the ADACMP utility description in the Adabas Utilities documentation for more information.

ERROR-133 Parameter ETID not allowed

Explanation The ADACMP utility ETID parameter may only be specified if the INFILE parameter is also specified.

Action Check the parameter input, correct any incompatibility or other error, and then rerun the job.

ERROR-135 Incorrect FDT found in input data set

Explanation One of the following is the case:

- the field definition table (FDT) expected in the first record is missing, or
- the FDT structure read from the input data set does not satisfy the rules.

Action Check whether the input data set is valid. Supply a correct input data set and rerun the job.

ERROR-136	Parameter error
Explanation	At least one of the parameters UACODE, UWCODE, FACODE, FWCODE, or FWUCODE contains an invalid value. Valid encoding values are 0-4095.
Action	Correct the encoding key value and rerun the job.
ERROR-137	Parameter error
Explanation	The architecture key parameter UARC contains an invalid value. Valid values are 0-11.
Action	Correct the architecture key value and rerun the job.
ERROR-138	UES object {object} failed to load
Explanation	The required UES object specified was not loaded. It is likely that the object does not exist in the UES data set.
Action	Locate the required object and load it.
ERROR-139	UES internal error
Explanation	This error usually results when at least one required UES object is missing.
Action	Determine which object(s) is missing and reload it.
ERROR-140	UES initialization failed
Explanation	Additional error messages follow that indicated the source of the error.
Action	Correct the problem and rerun the job.
ERROR-141	UACODE/UWCODE/UARC specified, but no FACODE/FWCODE specified or implied
Explanation	The utility does not have access to the nucleus information about the file. You must specify all values.
Action	Either remove the user encoding values (UACODE/UWCODE/UARC) or specify the file encoding values (FACODE/FWCODE) as well.
ERROR-142	Wide field detected but length uneven
Explanation	The length must be a multiple of the wide character size without a remainder to accommodate only full characters. For example, when using a three-byte character size, the length must be evenly divisible by 3; for a four-byte character size, the length must be evenly divisible by 4.
Action	Correct the problem and rerun the job.

ERROR-143	Wide field detected but FUCODE not specified
Explanation	Wide fields must specify code page information; that is, a wide-character field encoding such as FWCODE=4095 (Unicode).
Action	Correct the problem and rerun the job.
ERROR-144	Invalid ET-ID
Explanation	When running DECOMPRESS on a multicient file, Adabas processes either <ul style="list-style-type: none">■ the entire file if ET-ID is not specified; or■ the selection of records allowed for the client identified by ET-ID. The user ID referred to by the `ETID' parameter is either not defined or has not been assigned an owner ID.
Action	Investigate the cause of the error; correct it; and rerun the job.
ERROR-145	Invalid spanned record encountered Input record count = {count}
Explanation	An ADACMP DECOMPRESS run encountered an invalid spanned compressed record in the input.
Action	Contact your Software AG support representative for assistance.
ERROR-148	DDFEHL record length too small Must be at least 500 bytes
Explanation	The DDFEHL error data set must have a record length of at least 500 bytes to accommodate the ADAF header and the initial logical record segment.
Action	Assign a larger sequential record length to the DDFEHL data set and try again.
ERROR-149	MAXLOGRECLN less than minimum Must be at least 32768 bytes
Explanation	The value specified for the MAXLOGRECLN parameter is too small; it must be at least 32768 bytes.
Action	Supply the correct parameter value and then rerun the job.
ERROR-150	HEADER=YES but first input record does not have a valid ADAH header
Explanation	The HEADER parameter was set to "YES" for an ADACMP COMPRESS run, but the first uncompressed input record does not have a valid ADAH header.
Action	Review the input records and determine whether the input records are in error or whether the HEADER parameter should be set to "NO" instead. if the problem persists, contact your Software AG support representative for assistance.

ERROR-151	DDAUSBA record length too small Must be at least {number} bytes
Explanation	The DDAUSBA data set record length is too small for ADACMP DECOMPRESS processing. If the HEADER parameter is set to "NO", the minimum length is the length of the record descriptor word (RDW) plus one byte. if the HEADER parameter is set to "YES", the minimum length is the length of the RDW plus the length of the ADAH or ADAC header plus one byte.
Action	Assign a larger sequential record length to DDAUSBA and try again.
ERROR-152	DDAUSB1 record length too small. Must be at least {nnn} bytes.
Explanation	The DDAUSB1 data set record length is too small for COMPRESS with LOBVALUES=YES. The record length must be large enough to accommodate the compressed record length determined by the LOBDEVICE parameter and control information.
Action	Assign a larger sequential record length to DDAUSB1 or reevaluate the LOBDEVICE parameter setting. Then try again.
ERROR-153	Code specified but LOB fields exist for file
Explanation	The CODE parameter is not supported for files containing large object (LB option) fields.
Action	Specify a different file or remove the CODE parameter and try again.
ERROR-154	LOBVALUES=YES but no LOB fields exist for file.
Explanation	The LOBVALUES parameter should only be set to YES for input files that have large object (LB) fields.
Action	Investigate the cause of the error and try again.
ERROR-155	LOBVALUES=YES with DECOMPRESS requires INFILE.
Explanation	The ADACMP DECOMPRESS function that specifies LOBVALUES=YES requires that the INFILE parameter be set to the <i>base file</i> of a <i>LOB file group</i> in order to populate the LOB values in the uncompressed records.
Action	Specify an INFILE parameter and try again.

ERROR-156	Decompress of a LOB file is not permitted.
Explanation	You cannot run the ADACMP DECOMPRESS function on a <i>LOB file</i> . It can only be specified on the <i>base file</i> of a <i>LOB file group</i> .
Action	Ensure the input file is specified correctly and is not a <i>LOB file</i> and try again.
ERROR-157	Invalid LOB information detected for file {filenum}
Explanation	The ADACMP DECOMPRESS INFILE with LOBVALUES=YES did not detect a valid <i>LOB file</i> . Either no <i>LOB file</i> is associated with the <i>base file</i> referenced in the message (<i>filenum</i>) or the <i>LOB file</i> information in the <i>base file</i> is invalid.
Action	Ensure the specified <i>base file</i> is properly associated to a <i>LOB file</i> and try again.
ERROR-158	Error during hyperexit call
	A call to hyperexit number {nn} resulted in a response 79 with subcode {code}
Explanation	A hyperdescriptor exit call failed with response code 79 (ADARSP079) and the subcode given in the message.
Action	Investigate the subcode to determine the reason for the error.
ERROR-159	Invalid LOB field specification in FORMAT parameter
Explanation	The FORMAT parameter contains an invalid LB (large object) field specification.
Action	Review the restrictions for specifying LB fields in the FORMAT parameter with LOBVALUES=NO. Correct the FORMAT parameter and rerun the job.
ERROR-161	The DST parameter also requires the TZ parameter
Explanation	If you specify the DST parameter, you must also specify a valid TZ parameter.
Action	Supply the correct parameter values and rerun the job.
ERROR-162	The TZ parameter is required when the FDT has a field with the TZ option
Explanation	A field with the TZ option was found in the FDT, but the TZ parameter was not specified in the ADACMP run.
Action	Supply the correct parameter values and rerun the job.
ERROR-163	The time zone specified by the TZ parameter is invalid
Explanation	An invalid time zone value was specified in the TZ parameter. The time zone specified must be a valid time zone name contained in the TZINFO member of the Adabas time zone library (ADAvrs.TZ00).
	Adabas uses the time zone data taken from the tz database , which is also called the zoneinfo or Olson database. The specific list of time zone names that Adabas supports in any given release can be found in the TZINFO member of the Adabas time zone

library (ADAvrs.TZ00). For more information about the TZINFO member of the time zone library, read *Supported Time Zones*, in the *Adabas DBA Tasks Manual*.

Action Supply a valid parameter value and rerun the job.

**ERROR-164 FACODE should be an EBCDIC type and a Single Byte Coding System
Check supplied UES Encodings.**

Explanation A code system specified in the FACODE parameter is not known or is not EBCDIC or is not a single-byte encoding system.

Action Check the documentation section *Supplied UES Encodings* in the *Adabas User, Hyperdescriptor, Collation Descriptor, and SMF Exits Manual* for the valid code and correct the job parameter accordingly.

82

ADACNV Utility Messages

This document describes conversion errors that might occur.

ERROR-121	Version {to-version} not supported
Explanation	Version number specified with parameter "TOVERS" is not supported by ADACNV.
Action	Change the parameter to a supported version and rerun the utility.
ERROR-122	Conversion not permitted for version 5.1 and below
Explanation	The current version of the database is 5.1 or below. Conversion could only be performed from version 5.2 and above.
Action	Convert the database to version 5.2 by starting and stopping the version 5.2 Adabas nucleus, then rerun ADACNV.
ERROR-123	Conversion not possible because the DIB block is not empty
Explanation	The DIB block is not empty, conversion is not possible.
Action	Shut down the Adabas nucleus, wait for all utilities to complete, and rerun ADACNV.
ERROR-125	Conversion not possible because of pending autorestart
Explanation	The Work data set is not empty. Conversion is not possible.
Action	To remove the pending autorestart, restart the nucleus and end it normally.

ERROR-126	DDFILEA block size too small
Explanation	The DDFILEA block size ("block size" bytes) is too small to write a record with a length of "length" bytes.
Action	Assign DDFILEA to a device type with a larger sequential block size.
ERROR-127	Conversion to version {vr} not possible. FDT for file {fn} does not fit into 4 ASSO blocks.
Explanation	You cannot convert to the version listed in the message (<i>vr</i>) because the file listed in the message (<i>fn</i>) does not fit into four Associator blocks.
Action	Delete the file listed in the message (<i>fn</i>) and rerun the ADACNV job.
ERROR-132	DDFILEA (FILEA) structure mismatch
Explanation	DDFILEA (FILEA) has an invalid structure. This is probably a job control (JCL) statement error.
Action	Correct any error and rerun the ADACNV job.
ERROR-133	File {fn} has version {vr} feature on, backward conversion impossible
Explanation	You cannot convert to the version you requested because at least one version <i>vr</i> feature was used for the file listed in the message (<i>fn</i>).
Action	Remove the version <i>vr</i> features and rerun the ADACNV job.
ERROR-134	Conversion not possible because protection log has not been copied
Explanation	The PLOGRn data set is not free. Conversion fails.
Action	Run ADARES PLCOPY to free the PLOG data set(s); then rerun the ADACNV job.
ERROR-135	Conversion not possible because alternate RABNS are assigned
Explanation	Alternate RABNs are not supported by Adabas version 7.2 and above.
Action	Use ADAORD to reorder the database before converting it from a version of Adabas version 7.1 or below to Adabas version 7.2 or above.
ERROR-136	Open PLOGR{n} error for NUCID= {nucid}, DSNAME= {plog-name}
Explanation	The parallel participant table (PPT) entry contains a protection log (PLOG) data set with the specified number and name. ADACNV was unable to open the data set. The data set may have been deleted, or it may not be cataloged, or it may contain PLOG data that has not yet been copied.
Action	Provide access to the specified data set or use the IGNUPT parameter and rerun the job.

ERROR-137	I/O error reading PLOGR{n} for NUCID= {nucid} , DSNAME= {plog-name}
Explanation	The parallel participant table (PPT) entry contains a protection log (PLOG) data set with the name and number specified. ADACNV was unable to read the first block of this data set. The data set has probably been destroyed.
Action	Determine the cause of the error; correct it and rerun the job.
ERROR-138	Conversion is not permitted for Event Replicator Servers.
Explanation	Backward conversion of an Event Replicator Server is not supported prior to Adabas version 7.4.
Action	Investigate the cause of the error.
ERROR-139	Conversion is not permitted when a {REPLICATOR SLOG} file is loaded.
Explanation	Backward conversion of a database is not possible when a Replicator or SLOG system file is loaded.
Action	Investigate the cause of the error.
ERROR-140	ASSO RABN allocation failed An attempt was made to allocate {n} ASSO blocks
Explanation	The allocation of the PPT area failed. An attempt was made to allocate <i>n</i> ASSO blocks.
Action	Correct the error and rerun the job.
ERROR-141	Conversion back to V74 not possible
Explanation	The database has more than five physical ASSO or DATA extents. It cannot be reverted back to an Adabas 7 database.
Action	Contact your Software AG technical support representative for assistance.
ERROR-142	Conversion back to V74 not possible
Explanation	One or more system file numbers is greater than 255.
Action	Adjust the system file numbers so they are less than 255 and try again.
ERROR-144	Conversion not required
Explanation	The Adabas version of the database is the same as the version requested in the ADACNV run.
Action	No action is required for this informational message.

ERROR-145 **Conversion back to V74 not possible. More than 6 user system files exist.**
Explanation Adabas 7 allowed a maximum of six user system files (files loaded with the SYSFILE option). More than six user system files currently exist.
Action Unload, delete, and reload the additional user system files without the SYSFILE option. Then rerun this utility.

ERROR-146 **Conversion back to V74 not possible. Unknown system file {nnnnn} exists.**
Explanation The user system file identified in the message (*nnnnn*) exists in the reserved area of the GCB.
Action Unload, delete, and reload the system file with the SYSFILE option to place the file number in the correct area of the GCB. Then rerun this utility.

ERROR-147 **File {nnnn} has new index structure active.
Backward conversion prior to V83 is not allowed**
Explanation The file identified in the message (*nnnn*) is using a new index structure. It cannot be converted backward to a version prior to Adabas 8.3
Action Run ADAREP to identify all files that have the advanced index structure. For those files, ADAREP prints the line 'Index structure . . . Advanced' in the file detail section. Eliminate the new index structure, then rerun this utility. There are a number of ways the new index structure can be eliminated:

- Unload, delete, and reload the file.
- Run the ADAORD REORASSO utility function.
- Run the ADAORD REORDB utility function.
- Run the ADAORD REORFASSO utility function for that file.
- Run the ADAORD REORFILE utility function for that file.
- Run the ADAORD RESTRUCTUREDDB utility function followed by the ADAORD STORE utility function.
- Run the ADAORD RESTRUCTUREF utility function followed by the ADAORD STORE utility function for that file.

Conversion to version {yy} feasible

Explanation In the first phase of conversion, this message is printed to indicate that the conversion of the database is possible.

Point of no return reached

Explanation The ADACNV utility has begun its final pass. Any abend after this point requires a new run of the utility with the RESTART parameter.

Conversion from version {xx} to version {yy} started

Explanation In the first phase of conversion, a conversion step has started.

Conversion is completed

Explanation The conversion step has been successfully completed.

The mirror table (ASSO RABN 7) has been cleared

Explanation Adabas Reflective Database is not supported by Adabas version 7 and above.

The BUB (ASSO RABN 2) has been cleared**Alternate RABN definitions were found but no alternate RABNS were assigned**

Explanation Alternate RABNs are not supported by Adabas version 7.2 and above.

Security by value converted normally

Explanation Security-by-value conversion has been successfully completed.

Some FST entries are deleted

Explanation At least one FST entry does not fit into one FST block due to the FST structure change. The entry or entries with the smallest RABN range(s) are deleted.

ADACNV finishes with a warning and response code 4 (ADARSP004).

Action Run ADAORD REORDB after conversion.

83

ADADBS Utility Messages

ERROR-114	Invalid value for parameter ASSOPFAC or DATAPFAC
Explanation	The value for a padding factor must be in the range 1 to 90%.
Action	Correct the parameter value and rerun the job.
ERROR-121	Invalid encoding value (1-4095)
Explanation	A valid encoding value is in the range 1 through 4095.
Action	Supply a valid encoding value for the parameter and rerun the job.
ERROR-122	Invalid file number specification
Explanation	Depending on the function to be performed, one or more file numbers must be supplied.
Action	Supply the correct parameter value and rerun the job. Refer to the Adabas Utilities documentation for more information.
ERROR-123	Invalid value for the parameter MODE
Explanation	Either ON or OFF is required to specify the new mode for reuse of DS or ISNs.
Action	Supply the correct parameter value and rerun the job.
ERROR-124	Invalid value for the parameter PRTY
Explanation	A valid value is in the range 1 through 255.

ERROR-125	Invalid value for the parameter ASSOSIZE/DATASIZE
Explanation	One of the parameters ASSOSIZE or DATASIZE is mandatory. You cannot use both.
Action	Supply the correct parameter value and rerun the job.
ERROR-126	Invalid value for a SIZE parameter
Explanation	Either the <code>xxSIZE</code> parameter specified an incorrect value, or more than one <code>xxSIZE</code> parameter was specified.
Action	Supply the correct parameter value and rerun the job. Only one SIZE parameter can be specified. The value must be specified in blocks. Choose one of the following sizes: <ul style="list-style-type: none">■ ACSIZE■ DSSIZE■ NISIZE■ UISIZE
ERROR-127	Invalid value for the parameter LENGTH, OPTION, or FORMAT
Explanation	The following rules apply: <ul style="list-style-type: none">■ P is the only acceptable value for FORMAT.■ Only one of the LENGTH, OPTION, or FORMAT parameters can be specified.■ If specified, the value of the LENGTH parameter must be greater than zero and less than or equal to the permitted maximum according to the requested field's format.■ If specified, the only OPTION parameter value permitted is LA.
Action	Supply the correct parameter value and rerun the job.
ERROR-128	Invalid value for the parameter TODATE
Explanation	The parameter TODATE must be specified in the format: TODATE=YYYYMMDD
Action	Supply the correct parameter value and rerun the job.

ERROR-129	Mandatory parameter user ID missing
Explanation	The priority is assigned to a specific user which is uniquely identified by its user ID. The user ID parameter is missing.
Action	Supply the correct parameter value and rerun the job.
ERROR-130	Invalid value for the parameter descriptor
Explanation	The value is one of the following: <ul style="list-style-type: none">■ missing;■ not found in the FDT; or■ found in the FDT, but is not a descriptor.
Action	Supply the correct parameter value and rerun the job.
ERROR-131	Invalid value for the parameter name
Explanation	A valid value for the NAME parameter is required.
Action	Supply the correct parameter value and rerun the job.
ERROR-132	Jobname or IDENT parameter missing
Explanation	Specify at least one of these parameters. Data integrity may be lost if the whole DIB block is reset. The DDIB operator command may be used to obtain information about the current contents of the DIB.
Action	Supply the correct parameter value and rerun the job.
ERROR-133	Invalid or missing field name
Explanation	One of the following conditions exists: <ul style="list-style-type: none">■ Field name is missing;■ Field name not found in FDT;■ Field is a group, subdescriptor.....;■ Field has FI option.
Action	Supply the correct parameter value and rerun the job.

ERROR-134	Invalid value for the parameter {parameter}
Explanation	The only valid values for the parameter listed in the message are YES or NO.
Action	Supply the correct parameter value and rerun the job.
ERROR-135	Missing parameter for OPERCOM function
Explanation	At least one valid operator command must be supplied.
Action	Supply a valid operator command and rerun the job.
ERROR-137	Size must be specified in cylinders
Explanation	ASSOSIZE and/or DATASIZE cannot be specified in blocks.
Action	Supply the correct parameter value in number of cylinders and rerun the job.
ERROR-138	Size must be specified in blocks
Explanation	ASSOSIZE and/or DATASIZE cannot be specified in cylinders.
Action	Supply the correct parameter value in number of blocks and rerun the job.
ERROR-139	Invalid data set number
Explanation	See the Adabas Utilities documentation for a description of data set numbers.
Action	Supply the correct parameter value, and rerun the job.
ERROR-140	Invalid value for MAXDS, MAXNI or MAXUI
Explanation	The values for these parameters must be specified in blocks.
Action	Supply a correct parameter value and rerun the job.
ERROR-141	Missing function parameter
Explanation	The specific ADADBS function was not specified in the ADADBS job.
Action	Specify the appropriate function parameter as described in the Adabas Utilities documentation, and rerun the ADADBS job.
ERROR-142	Invalid value for SECUID
Explanation	An invalid value was specified for the SECUID operator command. Only values of ALLOW , REQUIRE or WARN are allowed.
Action	Supply the correct parameter value and rerun the job.

ERROR-143	Invalid value for PGMREFRESH
Explanation	Only "yes" or "no" are allowed as parameter values.
Action	Supply the correct parameter value and rerun the job.
ERROR-144	Invalid value for parameter REVIEW
Explanation	The values NO, LOCAL or hub are allowed.
Action	Supply the correct parameter value and rerun the job.
ERROR-145	Invalid Adabas state for "TRAN SUSPEND/RESUME"
Explanation	An online database or file save is executing, or Adabas is still processing the last TRAN SUSPEND and TRAN RESUME function.
ERROR-146	TRESUME timer expired before resume occurred
Explanation	You ran the TRAN RESUME job, but the timer set by TRESUME (defaults to 120 seconds unless set in the JCL) had already expired. Once the timer expires, Adabas immediately begins to return to "normal status".
ERROR-147	"TRAN SUSPEND" already in progress
Explanation	A TRAN SUSPEND is running. Either the timer must expire or a TRAN RESUME job must be successfully executed before another TRAN SUSPEND job can be started.
ERROR-148	No previous "TRAN SUSPEND" to resume
Explanation	No TRAN SUSPEND job has been started.
ERROR-149	Invalid when Adabas is "MODE=SINGLE"
Explanation	Adabas is running in single-user mode. MODE=MULTI is required.
ERROR-150	ET-SYNC failed
Explanation	The ET-SYNC was not successful; the database cannot be quiesced.
Action	Contact your Software AG technical support representative.

ERROR-151	TARGET is invalid.
Explanation	Replication with TARGET = DBID, NUCID, 0, or greater than 65535 is not allowed.
Action	Supply the correct parameter value and rerun the job.
ERROR-152	Parameters NOKEY and KEY are mutually exclusive.
Explanation	Specifying both NOKEY and KEY is not allowed.
Action	Supply the correct parameter value and rerun the job.
ERROR-153	Conflicting parameter for replication OFF.
Explanation	Additional parameters are not allowed.
Action	Supply the correct parameter value and rerun the job.
ERROR-154	Invalid KEY for replication. The specified KEY field <field> is not defined as a descriptor on the file to be replicated.
Explanation	A replication key field must be defined as a descriptor.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-155	Invalid KEY for replication. The specified KEY field <field> does not exist on the file to be replicated.
Explanation	The specified replication key field must exist.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-156	Invalid replication request.
Explanation	REPLICATION ON was attempted for a file that is already replicated.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-157	Invalid replication request.
Explanation	A REPLICATION MODIFY or REPLICATION OFF was attempted for a file that is not currently replicated.
Action	Investigate the cause of the error. Correct it and rerun the job.

ERROR-158	Invalid FILE for replication.
Explanation	A replicated file must exist on the database and may not be an Adabas system file or ciphered.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-159	Invalid replication request.
Explanation	REPLICATION ACTIVATE was attempted for a file that already has replication activated.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-160	Parameters ACTIVATE and DEACTIVATE are mutually exclusive.
Explanation	Specifying both ACTIVATE and DEACTIVATE is not allowed.
Action	Supply the correct parameter value and rerun the job.
ERROR-161	Invalid value for parameter DSBI.
Explanation	The only valid values for DSBI are "ON" or "OFF".
Action	Supply the correct parameter value and rerun the job.
ERROR-162	Conflicting parameter for replication ON.
Explanation	ACTIVATE / DEACTIVATE may not be specified.
Action	Supply the correct parameter value and rerun the job.
ERROR-163	Event Replicator Server function only allowed for Event Replicator database
Explanation	The ADADBS function is only valid for an Event Replicator Server.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-164	The specified destination {destination} was not found.
Explanation	The destination listed in the message is not defined to the Event Replicator Server.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-165	The specified subscription {subscription} was not found.
Explanation	The subscription listed in the message is not defined to the Event Replicator Server.
Action	Investigate the cause of the error. Correct it and rerun the job.

ERROR-166	The specified DBID was not found.
Explanation	The specified DBID is not defined to the Event Replicator Server.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-167	The specified FILE/DBID was not found.
Explanation	The specified file for the specified DBID is not defined to the Event Replicator Server.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-168	The specified destination {destination} was already {active inactive}.
Explanation	The Event Replicator Server detected the destination listed in the message was already active or inactive.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-169	The specified FILE/DBID was already {active inactive}.
Explanation	The Event Replicator Server detected the specified file for the specified DBID was already active or inactive.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-170	The specified subscription {subscription} was already {active inactive}.
Explanation	The Event Replicator Server detected the subscription listed in the message was already active or inactive.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-172	Invalid value for DBID.
Explanation	DBIDs greater than 65535 are not allowed.
Action	Supply the correct parameter value and rerun the job.
ERROR-173	{CLOSE OPEN} failed for specified destination {destination-name}
Explanation	ADADBS detected that the Event Replicator Server could not CLOSE or OPEN the destination listed in the message.
Action	Investigate the cause of the error. The Event Replicator Server job log will provide more details on why the request failed.

ERROR-174	The specified input queue {queue-name} was not found.
Explanation	The input queue (IQUEUE) listed in the message is not defined to the Event Replicator Server.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-175	{CLOSE OPEN} failed for specified input queue {queue-name}
Explanation	ADADBS detected that the Event Replicator Server could not CLOSE or OPEN the input queue (IQUEUE) listed in the message.
Action	Investigate the cause of the error. The Event Replicator Server job log will provide more details on why the request failed.
ERROR-176	Missing parameter: DESTINATION or IQUEUE required
Explanation	Either DESTINATION or IQUEUE must be specified for the OPEN and CLOSE functions.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-178	The specified destination {dest-name} may not be active Data still exists on the SLOG system file for this inactive destination
Explanation	An attempt was made to activate the destination named in the message (<i>dest-name</i>) while transactions for the destination still exist on the SLOG system file from the last time it was activated.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-179	The specified DBID/file may not be activated The SLOG has been suspended for database-related input transactions and one or more transactions exist on the SLOG system file for this inactive DBID/file
Explanation	An attempt was made to activate a DBID/file combination that was deactivated because the SLOG system file was full.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-182	No file number given
Explanation	The mandatory operand, FILE, was not specified with the MUPEX or RECORDSPANNING function.
Action	Supply the correct parameter value and rerun the job. For more information, read about the MUPEX and RECORDSPANNING functions of the ADADBS utility in your Adabas utilities documentation.

ERROR-183	Invalid MUPECOUNT option (1/2)
Explanation	A value other than "1" or "2" was specified for the MUPECOUNT parameter in an ADADBS MUPEX function run. The only valid values for MUPECOUNT are "1" or "2".
Action	Supply the correct parameter value and rerun the job. For more information, read about the MUPEX function of the ADADBS utility in your Adabas utilities documentation.
ERROR-184	MUPECOUNT specification is invalid. The file contains a PE and has records.
Explanation	To set the MUPECOUNT parameter to "1", the file must either be empty or have no PE fields. To set the MUPECOUNT to "2", the file cannot contain a PE field that is part of a DE field unless the file is empty.
Action	Supply the correct parameter value or release the descriptors and rerun the job. For more information, read about the MUPEX function of the ADADBS utility in your Adabas utilities documentation.
ERROR-186	Conflicting file options
Explanation	One of the following circumstances occurred: <ul style="list-style-type: none">■ The file specified is a system file.■ The file specified is a coupled file.■ The file specified is an ADAM file.■ The file specified is a replicated file.■ Only privileged commands are permitted against this file.■ The file specified is in load status.■ MIXDSDEV is not permitted for spanned data storage files.
Action	Correct the file or parameters and rerun the ADADBS job.
ERROR-187	TIMELIMIT exceeded
Explanation	The RECORDSPANNING or SPANCOUNT functions's time limit (set by the TIMELIMIT parameter) was exceeded.
Action	Change the TIMELIMIT parameter value and rerun the job. For more information, read about the RECORDSPANNING and SPANCOUNT functions of the ADADBS utility in your Adabas utilities documentation.

ERROR-188	Invalid RECORDSPANNING request
Explanation	The MODE=OFF parameter of the RECORDSPANNING function cannot be specified for a file that already contains spanned data storage records.
Action	Ensure that the specified file contains no spanned data storage records and then rerun the ADADBS job. For more information, read about the RECORDSPANNING function of the ADADBS utility in your Adabas utilities documentation.
ERROR-189	An I/O error occurred
Explanation	An I/O error occurred executing the specified function
Action	Research and correct the cause of the error and rerun the ADADBS job.
ERROR-190	File specified is not spanned
Explanation	The file specified does not have spanned data storage records enabled.
Action	Specify a file with spanned data storage records enabled and rerun the ADADBS job.
ERROR-191	Replication may not be turned on for a file with spanned data storage records.
Explanation	Replication may not be turned on for a file with spanned Data Storage records.
Action	Review and correct the parameters specified in the ADADBS run and ensure that you are not trying to replicate a file containing spanned records. Then try running the job again.
ERROR-194	Replication not active for Adabas
Explanation	Input information to ADADBS is requiring that the Adabas database have REPLICATION=YES (replication must be active) specified in the parameters to accomplish the request. However, replication for the database is not active.
Action	Examine the input to ADADBS for correctness. You may have to modify, stop, and restart the Adabas database to allow replication to be active.
ERROR-195	Anchor file must be specified
Explanation	A value for the ANCHOR parameter must be specified. To perform properly, the ADADBS EXPFILE utility needs to know the number of the anchor file of an expanded file chain.
Action	Supply a valid value for ANCHOR and rerun the job.

ERROR-196	INSERT or REMOVE must be specified
Explanation	Either the INSERT or REMOVE parameter must be specified for the ADADBS EXPFILE utility function. They are mutually exclusive parameters.
Action	Supply either the INSERT or REMOVE parameter, as appropriate, and rerun the job.
ERROR-197	Specified field is not a descriptor
Explanation	The field specified in the FIELD parameter was not a descriptor. When specifying the NOUQ option in an ADADBS CHANGE operation, the field must be a unique descriptor (DE,UQ option) field.
Action	Correct the parameter values for the ADADBS CHANGE operation and rerun it.
ERROR-198	Specified descriptor is not unique
Explanation	The field specified in the FIELD parameter was not a unique descriptor. When specifying the NOUQ option in an ADADBS CHANGE operation, the field must be a unique descriptor (DE,UQ option) field.
Action	Correct the parameter values for the ADADBS CHANGE operation and rerun it.
ERROR-199	Insufficient work space for Online Reorder
Explanation	The internal workarea is insufficient for the requested reorder.
Action	Contact your Software AG technical support representative for assistance.
ERROR-200	Invalid function specified
Explanation	The nucleus did not recognize the call it received. An invalid function or value was specified.
Action	Correct the parameter values and utility function specifications as required and rerun the job.
ERROR-201	Invalid function for current N{n}LOG
Explanation	An invalid value was specified for the current NCLOG or NPLOG specifications. Running the ADADBS ADDCLOG, ADDPLOG, DELCLOG, or DELPLOG utility functions is invalid when running with dual CLOGs or PLOGs.
Action	Make sure the Adabas nucleus startup job specifies the NCLOG and NPLOG ADARUN parameters and that it is not using dual CLOGs and PLOGs. Then verify that the settings of the NCLOG and NPLOG ADARUN parameters are set to integers in the range 2 through 8 (inclusive). Correct any invalid parameters and rerun the job.

ERROR-202	ENQ for PPT failed
Explanation	An error occurred during the PPT enqueue process.
Action	Contact your Software AG technical support representative for assistance.
ERROR-203	No PPT entries found
Explanation	No entries were found in the current PPT.
Action	Obtain an PPTPRINT and contact your Software AG technical support representative for assistance.
ERROR-204	PPT not consistent or invalid request
Explanation	The entry Adabas is trying to locate in the PPT was not found.
Action	Check the current PPT structure and make sure the requested function was valid and that the correct data set was specified for the ADADBS run. make appropriate corrections and rerun the job.
ERROR-205	Error with DD{n}LOGR{x} data set
Explanation	An error occurred during an attempt to process the specified CLOG or PLOG data set in the Adabas startup JCL.
Action	Check your startup JCL, make appropriate corrections, and retry the function.
ERROR-206	Dataset name length error
Explanation	The nucleus detected an invalid length in the parameter passed to it.
Action	Contact your Software AG technical support representative for assistance.
ERROR-207	Dataset already in use
Explanation	The CLOG or PLOG data set that was requested in the ADADBS run to be added or deleted is already in use.
Action	Specify a CLOG or PLOG data that is not in use and retry the function.
ERROR-208	{x}LOG data set must be supplied
Explanation	The CLOG or PLOG data set to be added or deleted using the ADADBS function must be specified in the Adabas startup JCL.
Action	Correct the startup JCL, restart Adabas, and retry the function.

ERROR-209	SLOG file can only be {deleted refreshed} with RPLPARMS=NONE
Explanation	The Event Replicator Server SLOG file can only be deleted or refreshed when the Event Replicator Server is started with the ADARUN parameter RPLPARMS set to "NONE."
Action	Restart the Event Replicator Server with RPLPARMS=NONE.
ERROR-210	Replicator file can only be {deleted refreshed} when RPLPARMS is set to NONE or PARMS
Explanation	The Event Replicator Service Replicator system file can only be deleted or refreshed when the Event Replicator Server is started with the ADARUN parameter RPLPARMS set to "NONE" or "PARMS".
Action	Restart the Event Replicator Server with RPLPARMS=NONE or RPLPARMS=PARMS.
ERROR-211	NUCID must be supplied
Explanation	No nucleus ID was specified during an attempt to run the ADADBS utility function to dynamically add or delete a CLOG or PLOG data set in a cluster environment. The NUCID parameter is required in a cluster environment.
Action	Specify the nucleus ID where you are trying to add or delete the CLOG or PLOG data set using the NUCID parameter and try again.
ERROR-212	DD{n}PLOGR{x} must be copied. Then retry function.
Explanation	The PLOG data set identified in the message (<i>DDn PLOGRx</i>) has not been copied.
Action	Copy or format the specified data set and retry the function.
ERROR-213	Invalid record buffer length
Explanation	The record buffer length is invalid.
Action	Contact your Software AG technical support representative for assistance.
ERROR-214	Missing or too many fields in FIELDLIST
Explanation	The FIELDLIST parameter is missing or contains more than 800 fields.
Action	Investigate the cause of the error. Either supply a FIELDLIST parameter or reduce the number of fields listed on the FIELDLIST parameter. Then rerun the job.

ERROR-215	Field does not exist in the FDT
Explanation	The FIELDLIST parameter contains a field that does not exist in the FDT for the file.
Action	Correct the FIELDLIST parameter specification and then rerun the job.
ERROR-216	Field is a descriptor
Explanation	The FIELDLIST parameter contains a descriptor field. Descriptor fields cannot be deleted.
Action	Correct the FIELDLIST parameter specification and then rerun the job.
ERROR-217	Field is a parent of a Sub-, Super-, Hyper-, Phonetic, or Collating descriptor
Explanation	The FIELDLIST parameter contains a subdescriptor, superdescriptor, hyperdescriptor, phonetic descriptor, or collating descriptor field. These types of fields cannot be deleted.
Action	Correct the FIELDLIST parameter specification and then rerun the job.
ERROR-218	Additions 1 field setting is invalid
Explanation	The Additions 1 field for an Adabas command contains an invalid value.
Action	Contact your Software AG technical support representative for assistance.
ERROR-219	Duplicate fieldname detected in FIELDLIST
Explanation	The FIELDLIST parameter contains a duplicate field; a field is listed more than once.
Action	Correct the FIELDLIST parameter specification and then rerun the job.
ERROR-220	Function not allowed for LOB file
Explanation	The file specified in the FILE parameter is a large object (LOB) file. You cannot delete fields from a LOB file.
Action	Correct the FILE parameter specification and then rerun the job.
ERROR-221	Field is parent of Subfield or Superfield
Explanation	The FIELDLIST parameter contains a subfield or superfield. These types of fields cannot be deleted.
Action	Correct the FIELDLIST parameter specification and then rerun the job.

ERROR-222	Trying to delete a field already deleted
Explanation	The FIELDLIST parameter in an ADADBS DELFN run includes a field that was already deleted.
Action	Correct the FIELDLIST parameter specification and then rerun the job.
ERROR-223	Trying to undelete a non-deleted field
Explanation	The FIELDLIST parameter in an ADADBS UNDELFN run includes a field that has not been deleted, so it cannot be undeleted.
Action	Correct the FIELDLIST parameter specification and then rerun the job.
ERROR-224	File is security protected
Explanation	The file specified in the FILE parameter is security protected, but no value was specified for the PASSWORD parameter.
Action	Supply a valid password in the PASSWORD parameter and try again.
ERROR-225	Invalid FDT detected
Explanation	The FDT for the file specified in the FILE parameter is invalid.
Action	Contact your Software AG technical support representative for assistance.
ERROR-226	Trying to delete a field that has the NN option on
Explanation	The FIELDLIST parameter contains a field that has the NN option on. Fields with the NN option on cannot be deleted.
Action	Correct the FIELDLIST parameter specification and then rerun the job.
ERROR-229	{ddname} could not be opened {ior-rsp} - {reason} Sub-code = {subcode}
Explanation	The data set identified by the DD name (<i>ddname</i>) given in the message could not be opened during a dynamic add or increase attempt. Possible causes include a misspelling or a JCL error. The ADAIOR response code (<i>ior-rsp</i>), the error text (<i>reason</i>) associated with the response code, and the system error code (<i>subcode</i>) are given in the message. The system error code, if nonzero, should be reported if you contact Software AG technical support about this error.
Action	Investigate the cause of the error. Correct it and rerun the job. If you need additional assistance, contact your Software AG technical support representative; be sure to provide the reason and system error code.

ERROR-230	{ddname} I/O error reading RABN {ravn} {ior-rsp} – {reason} * The dataset is not formatted or * The dataset has not yet been increased or * The newly increased area is not formatted.
Explanation	During a dynamic database add or increase attempt, an error occurred reading the data set identified by the DD name (<i>ddname</i>) given in the message. Possible causes include an unformatted data set, a data set that has not yet been increased, or a newly increased data set area that has not been formatted. The RABN (<i>ravn</i>) that ADADBS tried, but failed to read, the ADAIOR response code (<i>ior-rsp</i>) and explanation (<i>reason</i>) are given in the message.
Action	Investigate the cause of the error. Correct it and rerun the job. If you need additional assistance, contact your Software AG technical support representative; be sure to provide the reason.
ERROR-231	RPLCHECK issued to a non-Reptor Adabas
Explanation	The RPLCHECK operator command was issued in an ADADBS OPERCOM utility run against a database that was <i>not</i> an Event Replicator Server. The RPLCHECK command can only be issued against Event Replicator Servers.
Action	Verify that this is the command you want to run. If it is, verify that you are running it against an Event Replicator Server.
ERROR-232	Command invalid for non-cluster Adabas
Explanation	The operator command was issued in an ADADBS OPERCOM utility run against a database that was not running as a cluster nucleus (CLUSTER=SYSPLEX or CLUSTER=LOCAL). The command can only be issued against a cluster nucleus.
Action	Verify that this is the command you want to run. If it is, verify that you are running it against a cluster nucleus.
ERROR-233	Invalid value for parameter MXCANCEL
Explanation	The value specified for the MXCANCEL parameter is invalid. MXCANCEL values must be greater than or equal to 15.
Action	Supply the correct parameter value and rerun the job.
ERROR-234	Invalid value for parameter MXCANCELWARN
Explanation	The value specified for the MXCANCELWARN parameter is invalid. MXCANCELWARN values must either be zero (0) or a value greater than or equal to 4 and less than the value of the MXCANCEL parameter.
Action	Supply the correct parameter value and rerun the job.

ERROR-235	Invalid value for parameter MXMSG
Explanation	The value specified for the MXMSG parameter is invalid. MXMSG values must be greater than or equal to 15 and less than or equal to 32767.
Action	Supply the correct parameter value and rerun the job.
ERROR-236	Invalid value for parameter MXMSGWARN
Explanation	The value specified for the MXMSGWARN parameter is invalid. MXMSGWARN values must either be zero (0) or a value greater than or equal to 4 and less than the value of the MXMSG parameter.
Action	Supply the correct parameter value and rerun the job.
ERROR-237	Invalid value for parameter MXSTATUS
Explanation	The value specified for the MXSTATUS parameter is invalid. MXSTATUS values must either be zero (0) or a value that is greater than or equal to 15.
Action	Supply the correct parameter value and rerun the job.
ERROR-238	Invalid value for parameter MXWTOR
Explanation	The value specified for the MXWTOR parameter is invalid. MXWTOR values must either be zero (0) or a value greater than or equal to 15 and less than or equal to 64800.
Action	Supply the correct parameter value and rerun the job.
ERROR-239	File {nnnn} is greater than the MAXFILES defined for the database
Explanation	The file number specified is invalid. The file number must be less than the MAXFILES defined for the database.
Action	Supply the correct parameter value and rerun the job.
ERROR-240	Invalid file range specified
Explanation	The file range is invalid, for example the starting value is less than the ending value.
Action	Correct the file range and rerun the job.
ERROR-241	Duplicate keyword parameter or missing, "CHANGE" function request
Explanation	Invalid parameters were provided to the ADADBS CHANGE function.
Action	Supply the correct parameter values and rerun the job.

ERROR-262	Invalid value for AUDITLOG Only the value 'CONSOLE' is allowed.
Explanation	Invalid parameter specified. Only the value "CONSOLE" is allowed.
Action	Supply the correct parameter values and rerun the job.
ERROR-263	FEOFAL applies to an Audit Server only
Explanation	The ADADBS OPERCOM FEOFAL can only be applied to an Adabas Audit Server.
Action	Ensure the target of the FEOFAL command is an Adabas Audit Server.
ERROR-264	FEOFCL does not apply to an Audit Server
Explanation	The ADADBS OPERCOM FEOFCL cannot be applied to an Adabas Audit Server.
Action	Ensure the target of the FEOFCL command is not an Adabas Audit Server. For Adabas Audit Servers, use the FEOFAL command.
ERROR-265	Invalid value for parameter AUDCONNECT
Explanation	Only valid DBIDs, auditing server IDs, or ALL are allowed.
Action	Supply the correct parameter value and rerun the job.

84 ADADCK Utility Messages

ERROR-121 Invalid record length found

Explanation The record length is negative, zero, or greater than the permitted maximum (MAXRECL value).

DSRABN=xxxxxxxx (nnnn), OFFSET=xxxxxx (nnn)

ERROR-123 Duplicate ISN found

Explanation The same ISN is found twice in the same DS block.

DSRABN=xxxxxxxx (nnnn), OFFSET=xxxxxx (nnn)

ERROR-124 Invalid DSST entry found

Explanation The following information is provided to identify the error:

DSRABN=xxxxxxxx (nnnn), REQUIRED % x, PRESENT % x,
DSSTRABN=xxxxxxxx (nnnn), OFFSET=xxxxxx (nnn)

Block size minus padding = xxxxx (nnn) Size of block in use = xxxxx (nnn)

ERROR-125	Invalid record length
Explanation	The DSCHECK function found that either the sum of all record lengths in one Data Storage block is not equal to the block length minus 4; or that the record length is zero. <div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 10px auto;">DSRABN=xxxxxxxx (nnnn), OFFSET=xxxxxx (nnn)</div>
ERROR-127	Invalid block length
Explanation	The block length field contains either <ul style="list-style-type: none">■ a negative value; or■ a number larger than the physical block size. <div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 10px auto;">DSRABN=xxxxxxxx (nnnn), OFFSET=xxxxxx (nnn)</div>
ERROR-128	Invalid ISN found
Explanation	An ISN was detected that is either zero or greater than the maximum allowed (TOPISN) value.
ERROR-130	Spanned record with ISN {isnumber} DS RABN {rabn} One of the following errors occurred: Neither primary spanned record bit nor secondary spanned record bit is switched on.
Explanation	The header of the spanned record with the ISN number listed in the message (<i>isnumber</i>) is erroneous.
Action	Correct the ISN or the ISN of the next spanned record or switch on the primary spanned record bit or the secondary spanned record bit (but not both). To correct the header of a spanned record, contact your Software AG technical support representative.
ERROR-131	Spanned data storage record with ISN {isnumber} DS RABN {rabn} contains inconsistencies. One of the following errors occurred: ISN of next secondary spanned record is zero. Bits of secondary spanned record and primary record are both switched on.
Explanation	The header of the primary spanned record with the ISN number listed in the message (<i>isnumber</i>) is erroneous.

Action	Correct the ISN of the primary spanned record, correct the ISN of the next secondary spanned record, or switch off the secondary spanned record bit. To correct the header of a spanned record, contact your Software AG technical support representative.
ERROR-132	Secondary spanned record with ISN {isnnumber} not found.
Explanation	The header of the secondary spanned record with the ISN number listed in the message (<i>isnnumber</i>) cannot be found in Data Storage.
Action	Contact your Software AG technical support representative for assistance.
ERROR-133	Duplicate primary spanned DS ISN {isnnumber} found - DS RABN {ravn} also found in DS RABN {ravn2}
Explanation	The ISN number listed in the message (<i>isnnumber</i>) appears in two primary spanned records in Data Storage in the container blocks listed in the message (<i>ravn</i> and <i>ravn2</i>). ISNs should be unique.
Action	Contact your Software AG technical support representative for assistance.
ERROR-134	Duplicate secondary spanned DS ISN {isnnumber} found - DS RABN {ravn}
Explanation	The ISN number listed in the message (<i>isnnumber</i>) appears in two secondary spanned records in Data Storage. ISNs should be unique.
Action	Contact your Software AG technical support representative for assistance.
ERROR-135	Secondary spanned record with ISN {isnnumber1} not found. Secondary ISN {isnnumber2} DSRABN {ravn} points to secondary ISN which was not found in data storage
Explanation	The ISN for a secondary spanned record listed in the message (<i>isnnumber1</i>) could not be found in Data Storage. The ISN of the secondary spanned record that points to this ISN is also given in the message (<i>isnnumber2</i>).
Action	Contact your Software AG technical support representative for assistance.
ERROR-136	Secondary ISN {isnnumber} found in Data Storage RABN {ravn} but not referenced by a primary ISN.
Explanation	A secondary spanned record was found in Data Storage is not referenced by a primary ISN. The ISN of the secondary spanned record is given in the message (<i>isnnumber</i>).
Action	Contact your Software AG technical support representative for assistance.

- ERROR-137** **Primary ISN {isnnumber1} not found. Primary ISN was referenced in secondary ISN {isnnumber2} DS RABN {ravn} - removing from the FROMRABN/TORABN will most likely resolved the warning.**
- Explanation** The ISN for a primary spanned record that was referenced by a secondary spanned record was not found in Data Storage during the ADADCK run. The ISN numbers for both the primary spanned record (*isnnumber1*) and the secondary spanned record (*isnnumber2*) are given in the message.
- The most likely cause of this error is that the FROMRABN and TORABN parameters were specified for the ADADCK run and the FROMRABN parameter references a secondary RABN rather than a primary RABN. We recommend that the FROMRABN parameter reference a primary RABN instead.
- Action** If you have used the FROMRABN parameter, verify that it points to a primary RABN and not a secondary RABN. Then try the job again. You might also consider removing the FROMRABN and TORABN parameters from the run.
- If problems persist, contact your Software AG technical support representative for assistance.
-
- ERROR-138** **Primary spanned master ISN {isnnumber} - ({hexisnumber}) does not match ISN {isnnumber2} - DS RABN {ravn}**
- Explanation** In a primary spanned record, the master ISN (*isnnumber*) should match the primary ISN (*isnnumber2*). This is not the case for the Data Storage record with the RABN given in the message (*ravn*).
- Action** Contact your Software AG technical support representative for assistance.

85

ADADEF Utility Messages

ERROR-121

Missing function parameter

Action

Add one of the following parameters and rerun the job:

- ADADEF DEFINE - define a new database
- ADADEF NEWWORK - define a new work

ERROR-122

Invalid value for the parameter DBID

Explanation

The value for the database ID must be in the range 1 to 65,535.

Action

Supply the correct parameter value and rerun the job.

ERROR-123

Checkpoint-file definition missing in parameter-list

Explanation

Each Adabas database requires a checkpoint file.

Action

Add the following parameter and rerun the job.

```
ADADEF FILE=xx,CHECKPOINT, ...
```

ERROR-124

Multiple system file definition not permitted

Explanation

The Adabas checkpoint and security file can be defined only once per database.

Action

Supply the correct parameter value and rerun the job.

ERROR-125	Invalid value for the parameter WORKSIZE
Explanation	The value of the WORKSIZE parameter must be at least 300 + WALT + number of blocks per track.
Action	Increase the WORKSIZE value and rerun the job.
ERROR-126	ADADEF not permitted to run
Explanation	An attempt was made to run ADADEF in parallel with an active nucleus. The Adabas nucleus returned response "response-code". (A short explanation is given here).
Action	The only acceptable response code is 148 (ADARSP148). Shut down the nucleus and rerun the job.
ERROR-127	Inconsistent parameter list
Explanation	A corresponding extent parameter is required for ASSOSIZE/ASSODEV/AALT, and DATASIZE/DATADEV/DALT.
Action	Supply the correct parameter value and rerun the job.
ERROR-128	File type missing or invalid
Explanation	The file number must be followed by a keyword defining the type of the system file to be loaded.
Action	See the Adabas Utilities documentation for further information. Supply the correct parameter value and rerun the job.
ERROR-129	DSST-extent space allocation failed
Explanation	Not enough free Associator space is available to allocate a DSST extent.
Action	Supply a larger Associator extent and rerun the job.
ERROR-132	Database not formatted
Explanation	The supplied ASSO contains valid GCBs.
Action	Run ADAFRM before running ADADEF, or specify the OVERWRITE parameter in the ADADEF job.
ERROR-133	Invalid size specification
Explanation	The (ASSOSIZE / DATASIZE / WORKSIZE) parameter value specified for (DDASSO / ASSOR1/2, DDDATA / DATARn, or DDWORK / WORKR1) is greater than the space physically available (an actual parameter / job control value is printed with the message text).
Action	Supply the correct parameter value, and rerun the job.

ERROR-134	No database to be overwritten
Explanation	The parameter OVERWRITE was specified, but the data sets assigned do not contain a database.
Action	Remove the OVERWRITE parameter, and rerun the ADADEF job.
ERROR-135	Value of parameter MAXRECL too large
Explanation	The MAXRECL value is either <ul style="list-style-type: none">■ greater than the default value "def-value"; or■ less than 7.
Action	Supply the correct MAXRECL parameter value, and rerun the ADADEF job.
ERROR-136	Invalid value for the parameter RABNSIZE
Explanation	Either 3 or 4 may be specified for the RABNSIZE parameter.
Action	Correct the value specified for the RABNSIZE parameter and rerun the ADADEF job.
ERROR-137	Dataset size too large
Explanation	The DATA/ASSO/WORK data set SIZE parameter value exceeds the maximum <i>nnnn</i> blocks.
Action	Correct the value specified for the specified data set SIZE parameter and rerun the ADADEF job.
ERROR-138	Cannot set UES=NO while file {file-number} loaded
Explanation	The specified file contains at least one element such as a wide-character formatted field that require the database to be enabled for universal encoding; that is, UES=YES is required.
Action	Reexamine your need to set UES=NO and adjust the file accordingly.
ERROR-139	Specify UES=NO to disable UES
Explanation	It is not possible to turn UES off by setting all <i>xx</i> CODE parameters to 0. ADADEF does not differentiate between a parameter set to zero (0) and a parameter not specified.
Action	To disable UES, set the UES parameter equal to NO.

ERROR-141	FACODE should be an EBCDIC type and a Single Byte Coding System Check supplied UES Encodings.
Explanation	A code system specified in the FACODE parameter is not known or is not EBCDIC or is not a single-byte encoding system.
Action	Check the documentation section <i>Supplied UES Encodings</i> in the <i>Adabas User, Hyperdescriptor, Collation Descriptor, and SMF Exits Manual</i> for the valid code and correct the job parameter accordingly.
ERROR-144	TIMEZONE parameter deficient - Reason code: rc 04: wrong TIMEZONE value 08: ADAZON not loaded 12: Region not found 16: Member not found 20: time zone not found
Explanation	It is not possible to establish a default timezone.
Action	Correct input dependent on the reason code. Add a valid Adabas-supported timezone name or a blank string (' '). In the utility job include the TZINFO data definition statement (DD, LINK, or DLBL statement) identifying the most recent TZ library or sublibrary

86

ADADRU Utility Messages

DRU121E	File {fnr} exceeds maximum file number {nnn} in database.
Explanation	The supplied file number <i>fnr</i> exceeds the highest file number <i>nnn</i> in the database.
Action	Specify a valid file number and rerun the job.
DRU122E	For parameter File {n-m} start of range value should be less than or equal to end of range value. This parameter is ignored.
Explanation	The start file number <i>n</i> cannot be greater than the end file number <i>m</i> .
Action	Specify a valid file number range and rerun the job.
DRU123E	The value of parameter {PASSOSPACE PDATASPACE PFILESACE}={val} can be only SUMMARY or DETAIL.
Explanation	The value (<i>val</i>) specified for the PASSOSPACE, PDATASPACE, or PFILESACE parameter is invalid. Only values of SUMMARY or DETAIL can be specified.
Action	Specify a correct value for the associated parameter (DETAIL or SUMMARY) and rerun the job.
DRU124E	Range or list of files not allowed for parameters FROMRABN / TORABN.
Explanation	Only a single file can be specified for ADADRU runs that also specify the FROMRABN or TORABN parameters.
Action	Either restrict the ADADRU run to a single file or remove the FROMRABN and TORABN parameters. Then rerun the job.

DRU125E	Parameter FROMRABN / TORABN requires specification of either PASSOSPACE or PDATASPACE parameter.
Explanation	The FROMRABN / TORABN parameters can be specified with the parameters PASSOSPACE / PDATASPACE. The FROMRABN and TORABN parameters cannot be used with parameter PFILESSPACE.
Action	Specify correct parameters and rerun the job.
DRU126E	The value of FROMRABN={fromravn} parameter should be less than or equal to the value of TORABN={toravn} parameter. This extent FROMRABN - TORABN is ignored.
Explanation	The FROMRABN value should be less than or equal to the TORABN value.
Action	Specify valid values for the FROMRABN and TORABN parameters and rerun the job.
DRU127E	Parameters PFILESSPACE / PASSOSPACE / PDATASPACE are mutually exclusive. Use only one of them.
Explanation	The PFILESSPACE, PASSOSPACE, and PDATASPACE parameters are mutually exclusive; only one of these parameters can be specified in an ADADRU run.
Action	Correct the ADADRU parameters and rerun the job.
DRU128E	The value of parameter SAMPLING={nnn} is not in a range 10-100.
Explanation	The value specified for the SAMPLING parameter must be in a range from 10 to 100 percent.
Action	Specify a valid value for the SAMPLING parameter and rerun the job.
DRU129E	The value of parameter INCRUSAGE={nnn} is not in a range 1-50.
Explanation	The value specified for the INCRUSAGE parameter should be in a range from 1 to 50 percent.
Action	Specify a valid value for the INCRUSAGE parameter and rerun the job.
DRU130E	The value of parameter INCRNUMREC={nnn} is not in a range 1-10000.
Explanation	The value specified for the INCRNUMREC parameter should be in a range from 1 to 10000 records.
Action	Specify a valid value for the INCRNUMREC parameter and rerun the job.

DRU131E	The value of parameter INCRRECLN={nnn} is not in a range 6-5000.
Explanation	The value specified for the INCRRECLN parameter should be in a range from 6 to 5000 bytes.
Action	Specify a valid value for the INCRRECLN parameter and rerun the job.
DRU132E	The value of parameter ERRLIM={nnn} is not in a range 1-255.
Explanation	The value specified for the ERRLIM parameter should be in a range from 1 to 255.
Action	Specify a valid value for the ERRLIM parameter and rerun the job.
DRU133E	The value of parameter OUTPUT error. Parameter OUTPUT can be: XML XML,UTF8 ,XML ,UTF8 UTF8,XML
Explanation	The value specified for the OUTPUT parameter can only be one of the values shown in the message. No other value is valid.
Action	Correct the OUTPUT parameter accordingly (or remove the OUTPUT parameter from the run) and rerun the job. For complete information about the OUTPUT parameter in an ADADRU run, read the ADADRU utility documentation.
DRU134E	ERROR: Parameter ACODE error. Parameter ACODE can be: GCB or FCB or CodePage or omitted.
Explanation	The value specified for the ACODE parameter can only be one of the following: "GCB", "FCB", or a numeric code page (CodePage). The code page is used to convert file names in the XML document. No other value is valid.
Action	Correct the ACODE parameter accordingly (or remove the ACODE parameter from the run) and rerun the job. For complete information about the ACODE parameter in an ADADRU run, read the ADADRU utility documentation.
DRU135E	File 0 is invalid.
Explanation	The file number cannot be equal to 0.
Action	Specify a valid file number and rerun the job.

DRU136E	ISN {isn} is invalid, File {fnr}. Run check utilities to obtain more information.
Explanation	One of the following errors was detected in the spanned record with ISN <i>isn</i> in file <i>fnr</i> : <ul style="list-style-type: none">■ The header indicates that the record with the ISN given in the message (<i>isn</i>) is not the primary record, although this record was identified by the primary address converter (AC) and not by the secondary address converter (AC2);■ The ISN (<i>isn</i>) of the primary record is greater than the maximum ISN for the file (<i>fnr</i>) on which ADADRU processing should occur.
Action	Run the ADACHK utility to obtain more information. If the problem persists, contact your Software AG technical support representative for assistance.
DRU137E	AC2 ISN={isn} does not exist in Secondary AC. File {fnr}, Primary ISN={ppp}. Run check utilities to obtain more information.
Explanation	The header of the primary segment of the spanned record with ISN= <i>ppp</i> points to the next (secondary) segment of the spanned record with ISN <i>isn</i> , but the secondary segment does not exist in the secondary address converter (AC2).
Action	Run the ADACHK utility to obtain more information. If the problem persists, contact your Software AG technical support representative for assistance.
DRU138E	AC2 ISN={isn} not found in DATA block={ravn}, specified by AC2 element. File {fnr}, Primary ISN={ppp}. Run check utilities to obtain more information.
Explanation	The secondary segment of the spanned record with ISN= <i>isn</i> does not exist in the Data Storage block <i>ravn</i> , where this segment should reside according to contents of secondary address converter (AC2) element.
Action	Run the ADACHK utility to obtain more information. If the problem persists, contact your Software AG technical support representative for assistance.
DRU139E	AC2 ISN={isn} is invalid, File {fnr}, DATA block={ravn}. Run check utilities to obtain more information.
Explanation	One of the following errors was detected in the secondary record with AC2 ISN= <i>isn</i> , stored in the Data Storage block <i>ravn</i> , file number <i>fnr</i> : <ul style="list-style-type: none">■ The header indicates that the current record is not the secondary record, although this record is identified by means of the secondary address converter (AC2), not the primary address converter (AC);■ The AC2 ISN <i>isn</i> of the secondary record is greater than the maximum AC2 ISN for file <i>fnr</i>.

Action	Run the ADACHK utility to obtain more information. If the problem persists, contact your Software AG technical support representative for assistance.
DRU140E	File {fnr} is not loaded. Processing of this file terminated.
Explanation	File <i>fnr</i> was explicitly specified in ADADRU input parameters, but the file does not exist in the database.
Action	Check the file number; correct it if required, and rerun the job.
DRU141E	For File {fnr} more than 8 FROMRABN-TORABN values specified. The extraneous extent is ignored.
Explanation	During consolidation of input parameters for the file listed in the message (<i>fnr</i>), ADADRU detected that the number of ranges specified using the FROMRABN and TORABN parameters exceeds eight. Only eight FROMRABN and TORABN parameter pairs can be specified in a single ADADRU run. ADADRU processing of the file continues using the first eight FROMRABN – TORABN values specified.
Action	No action is required for this informational message. However, you may want to adjust the job to specify only eight FROMRABN-TORABN parameter pairs and rerun it.
DRU142E	ERRLIM={nnn} for File {fnr} is exceeded. Processing of this file terminated.
Explanation	The number of ADADRU errors that have occurred for the file listed in the message (<i>fnr</i>) exceeds the error limit (<i>nnn</i>) specified by the ERRLIM parameter.
Action	Specify a greater value for the ERRLIM parameter and rerun the job or determine the reason for all of the errors, resolve them, and rerun the job.
DRU143E	Reports for a file are not printed because some errors were detected for File {fnr}.
Explanation	Some errors were detected for the file listed in the message (<i>fnr</i>). Processing continues if the error limit specified by the ERRLIM parameter is not exceeded.
Action	No action is required for this informational message. However, you may want to determine the reason for the errors, resolve them, and rerun the job.

DRU144E	Printed report is incomplete because some errors were detected for File {fnr}.
Explanation	Some errors were detected for the file listed in the message (<i>fnr</i>). Processing continues if the error limit specified by the ERRLIM parameter is not exceeded. The printed report will be incomplete.
Action	No action is required for this informational message. However, you may want to determine the reason for the errors, resolve them, and rerun the job.
DRU145E	Invalid internal structure for {ASSO DATA} RABN={ravn} File {fnr}. Run check utilities to obtain more information.
Explanation	An invalid internal structure in the ASSO NI block or Data Storage block RABN identified in the message (<i>ravn</i>) has been detected. The affected file is also listed in the message (<i>fnr</i>). Processing continues if the error limit specified by the ERRLIM parameter is not exceeded.
Action	No action is required for this informational message. However, you may want to determine the reason for the error, resolve it, and rerun the job.
DRU146E	RABN={ravn} for File {fnr} is not ASSO Normal Index.
Explanation	The internal structure of the ASSO NI block with the RABN listed in the message (<i>ravn</i>) is invalid for file <i>fnr</i> . A one-byte level indicator (third byte) in the ASSO block <i>ravn</i> does not contain x'01' value – the level indicator for a Normal Index. Normally this message is followed by the DRU145E message which gives additional information. Processing continues if the error limit specified by the ERRLIM parameter is not exceeded.
Action	No action is required for this informational message. However, you may want to determine the reason for the error, resolve it, and rerun the job.
DRU147W	Parameters OUTPUT/ACODE duplicate definition, last value ignored.
Explanation	An error occurred in the parameter definition for the utility. Either the OUTPUT or ACODE parameter has been declared twice. You can specify a single OUTPUT parameter (with or without an associated ACODE parameter) or a single ACODE parameter in an ADADRU run. You cannot specify two OUTPUT parameters or two ACODE parameters in an ADADRU run.
Action	Review the ADADRU parameter specifications and correct them so only one OUTPUT parameter (with or without a single ACODE parameter) is specified. Then rerun the job.

DRU148E	OPEN/CLOSE error on link llllllll.
Explanation	A file used by ADADRU on the link/DD name llllllll cannot be opened or closed .
Action	Check the ADADRU utility job for the existence of the link/DD name. If it exists, check the status of the file associated with it. Correct appropriately and re-run the job.
DRU149E	Missing or incorrect utility function.
Explanation	An attempt has been made to run the ADADRU utility without the SPACEUSAGE keyword. The SPACEUSAGE keyword is required.
Action	Supply the missing SPACEUSAGE keyword and rerun the job.
DRU151W	FREEMAIN Error encountered in ADADRU at offset {nnn}. Length = {len} bytes. Address = {addr}.
Explanation	The internal error occurred in the ADADRU utility during memory release.
Action	Save the ADADRU output and contact your Software AG technical support representative for assistance..
DRU152E	Next File {fnr} (Seq.number {n}) in chain of expanded file not loaded. Previous File in chain={ccc}, Anchor File {fff}. The chain of expanded file is interrupted. Processing of this chain terminated.
Explanation	The next file (<i>fnr</i>) with the sequence number <i>n</i> in the chain of the expanded file is not loaded in the database. The previous file in the chain is file <i>ccc</i> ; the anchor file in the chain is file <i>fff</i> .
Action	Verify that next file number <i>fnr</i> is specified correctly. Correct it as necessary and rerun the job. If the problem persists, contact your Software AG technical support representative for assistance.
DRU153E	Anchor File {fnr} in chain of expanded File {fff} not loaded. The chain of expanded file is interrupted. Processing of this chain terminated.
Explanation	The anchor file (<i>fnr</i>) in the chain of the expanded file <i>fff</i> is not loaded in the database.
Action	Verify that the anchor file number <i>fnr</i> is specified correctly. Correct it as necessary and rerun the job. If the problem persists, contact your Software AG technical support representative for assistance.

DRU154E	LOB File {fnr} is not loaded for base File {bbb}. LOB file will not be processed.
Explanation	The large object (LOB) file identified in the message (<i>fnr</i>) for the associated base file (<i>bbb</i>) is not loaded in the database. The LOB file will not be processed by ADADRU.
Action	No action is required for this informational message. However, if you want the LOB file processed with its associated base file by ADADRU, load the LOB file into the database. Then rerun the ADADRU job.
DRU155E	Base File {fnr} is not loaded for LOB File {lob}. LOB base file will not be processed.
Explanation	The base file identified in the message (<i>fnr</i>) for the associated large object (LOB) file (<i>lob</i>) is not loaded in the database. The base file will not be processed by ADADRU.
Action	No action is required for this informational message. However, if you want both the LOB file and its associated base file processed by ADADRU, load the base file into the database. Then rerun the ADADRU job.
DRU157E	Write error ee on link llllllll .
Explanation	The file access on link/DD name llllllll has reported an internal error ee on write.
Action	Contact Software AG as to what the error ee means. There may be an explanation in the system messages or DDPRINT of the job.
DRU158E	{FROMRABN TORABN}=0 is incorrect. File group are ignored.
Explanation	Either the FROMRABN or TORABN parameters has been set to zero (0). This is not a valid specification for either parameter.
Action	Specify valid values for FROMRABN and TORABN and rerun the job.
DRU159I	File {fnr} is not loaded. Processing of this file skipped.
Explanation	File <i>fnr</i> was implicitly specified in ADADRU input parameters (inside a specified range of files). However, this file does not exist in the database and so it is skipped by ADADRU processing.
Action	Check the file number, correct it if required and rerun the job.

DRU161W	File {fnr}, part {nnn} of expanded file will be processed in chain of all parts of expanded file. Anchor File {nnn}.
Explanation	This message identifies how processing will occur for a file within an expanded file. It informs you that file <i>fnr</i> is part <i>nnn</i> of an expanded file and will be processed in the chain of all parts of the expanded file. The anchor file of the expanded file chain is given in the message (<i>nnn</i>).
Action	No action is required for this informational message.
DRU162W	File {fnr}, will be processed after end of process of all parts of expanded file. Anchor File {nnn}.
Explanation	This message identifies how processing will occur for a file that is not part of an expanded file. It informs you that file <i>fnr</i> will be processed after processing has completed for all parts of the expanded file. The anchor file of the expanded file chain is given in the message (<i>nnn</i>).
Action	No action is required for this informational message.
DRU163W	No data for {rptarea}.
Explanation	The report area identified in the message (<i>rptarea</i>) is absent in SUMMARY report for the file because there is not data for the report area. Possible values for <i>rptarea</i> are: <ul style="list-style-type: none">■ “Block filling level” report (Part 1);■ “Block filling level” report (Part 2);■ “Number of records per block” report;■ “Number of elements per block” report;■ “Normal records length” report; and■ “Spanned records length” report
Action	No action is required for this informational message.
DRU164E	Parameter File should be specified before other parameters related to this file group.
Explanation	The FILE parameter is specified in the ADADRU run, but not immediately after the SPACEUSAGE keyword. ADADRU processing assumes all files for the database should be processed for the run and any specifications on the FILE parameter are ignored.
Action	Correct the ADADRU SPACEUSAGE parameters, specifying the FILE parameter as the first parameter in the run after the SPACEUSAGE keyword.

DRU165W	No data for {ASSO NORMAL INDEX DATA STORAGE} detail report for File {fnr}.
Explanation	Errors occurred during report processing. Consequently, the ASSO Normal Index detail report or Data Storage detail report are not created for file listed in the message (<i>fnr</i>).
Action	No action is required for this informational message.
DRU166E	{ASSO DATA} FROM-TO RABNs are outside of extents for file {fnr} or these RABNs are not ASSO NI RABNs. Run ADAREP utility to obtain information about file extents.
Explanation	The RABNs specified by the FROMRABN and TORABN parameters are not located in the ASSO/DATA extents for the file listed in the message (<i>fnr</i>) or they are not of the required NIRABN type.
Action	Run the ADAREP utility to obtain information about the valid ASSO/DATA extents of the file. Then specify the correct RABN range for the ADADRU run using the FROMRABN and TORABN parameters and rerun the ADADRU job.
DRU169I	{ASSO DATA} RABNs {fromrabn – torabn} from specified RABN range are outside of extents for file {fnr} or these RABNs are not ASSO NI RABNs. Only RABN(s) which belong to the file will be processed. Run ADAREP utility to obtain information about file extents.
Explanation	The RABNs specified by the RABN range shown in the message (<i>fromrabn - torabn</i>) are not located in the ASSO or DATA extents for the file listed in the message (<i>fnr</i>) or they are not of the required NIRABN type. Only the RABNs that belong to the file will be processed by ADADRU.
Action	Run the ADAREP utility to obtain information about the valid ASSO/DATA extents of the file. Then specify the correct RABN range for the ADADRU run using the FROMRABN and TORABN parameters and rerun the ADADRU job.
DRU170E	{ASSO DATA} RABNs {fromrabn – torabn} from specified RABN range are outside of extents for file {fnr} or these RABNs are not ASSO NI RABNs. Run ADAREP utility to obtain information about file extents.
Explanation	The RABNs specified by the RABN range shown in the message (<i>fromrabn - torabn</i>) are not located in the ASSO or DATA extents for the file listed in the message (<i>fnr</i>) or they are not of the required NIRABN type. Only the RABNs that belong to the file will be processed by ADADRU.
Action	Run the ADAREP utility to obtain information about the valid ASSO/DATA extents of the file. Then specify the correct RABN range for the ADADRU run using the FROMRABN and TORABN parameters and rerun the ADADRU job.

DRU200I	The input parameters accepted.
Explanation	The input parameters specified for the ADADRU run have been accepted.
Action	No action is required for this informational message.
DRU203I	***** SPACEUSAGE-{N} started ***** {date time}
Explanation	ADADRU SPACEUSAGE function with the sequence number <i>N</i> has been started.
Action	No action is required for this informational message.
DRU204I	Error message(s) were issued for this SPACEUSAGE. Processing of this function terminated.
Explanation	During processing of the ADADRU input parameters, serious errors were found,. These errors are mentioned in previous error message(s).
Action	Correct the ADADRU SPACEUSAGE parameters and rerun the job.
DRU205I	***** SPACEUSAGE-{N} ended *****
Explanation	The ADADRU SPACEUSAGE function with the sequence number <i>N</i> has ended.
Action	No action is required for this informational message.

87

ADAFRM Utility Messages

ERROR-121	Missing function
Explanation	At least one of the following functions must be specified: ASSOFRM, DATAFRM, WORKFRM, CLOGFRM, PLOGFRM, RLOGFRM, TEMPFRM, SORTFRM, DSIMFRM, ASSORESET, DATARESET, WORKRESET, or DSIMRESET.
Action	Supply the correct parameter value and rerun the ADAFRM job.
ERROR-122	Invalid data set number
Explanation	See the Adabas Utilities documentation for a description of data set numbers.
Action	Supply the correct parameter value and rerun the ADAFRM job.
ERROR-124	Will not reset ASSO control blocks
Explanation	Resetting Associator blocks with the range 1-30 is rejected.
ERROR-125	Missing ASSO data sets
Explanation	Job control statements defining the Associator must be included for both the ADAFRM utility job for the ASSOFRM, DATAFRM, TEMPFRM and WORKFRM functions when the FROMRABN parameter is specified, and when running the ASSORESET, DATARESET, and WORKRESET ADAFRM functions.
Action	Supply the required JCL/JCS job control, and rerun the ADAFRM job.

ERROR-126	Invalid size value specified
Explanation	The SIZE value specified with FROMRABN=NEXT is not valid. The range of blocks to be formatted is not contained in the free space table.
Action	Supply a valid SIZE parameter value and rerun the job.
ERROR-127	Invalid FROMRABN value specified
Explanation	For the ASSOFRM and DATAFRM functions, valid FROMRABN values include a numeric starting RABN value or FROMRABN=NEXT.
Action	Supply a valid FROMRABN value and rerun the job.
ERROR-128	Invalid VOLIOCOUNT value specified
Explanation	An invalid value was specified for the VOLIOCOUNT parameter. VOLIOCOUNT must be a numeric value. Refer to the ADAFRM parameter descriptions in the <i>Adabas Utilities Manual</i> for the range of valid values.
Action	Supply a valid VOLIOCOUNT value and rerun the job.
ERROR-129	Duplicate format request detected
Explanation	An attempt to format the same data set from the start multiple times has been detected. The same data set cannot be formatted more than once in a single execution of ADAFRM.
Action	Supply valid data set information and rerun the job.

88

ADAICK Utility Messages

ERROR-121	{block-number} block contains invalid packed value
Explanation	The format indicator in the U3 element is "U" or "P", and the value in the "block-number" block is not a valid packed decimal number.
ERROR-122	{value1} {value2} values do not agree
Explanation	<p>Each U3 element contains a value and an MI RABN. The first MI element (in the MI block pointed to by the U3 element) should contain the same value as the U3 element. If not, this message occurs.</p> <p>This message also occurs if an MI element contains a value that does not agree with the value in the first NI element (in the NI block pointed to by the MI element).</p>
ERROR-123	{block-number} block contains incorrect block/value length
Explanation	<p>The two-byte inclusive length at the beginning of each index block defines the logical end of that block. Each block contains variable length elements. The length of each element depends on the length of the value within the element (for NI blocks, it also depends on the ISN count).</p> <p>In processing an index block (left to right), the end of each element is compared to the logical end of the block (as defined by the logical block length). If the end of the element is less than the logical end of the block, what follows is taken as the next element, and processing continues. If the block and element ends are equal, the block is considered to be correct. If the element end is greater than the block end, this message occurs.</p>

ERROR-124 **MI ISN should be zero**
Explanation Each MI element points to an NI block. If the first ISN in the ISN list for the first NI element in that NI block is the lowest ISN for that value, then the "MI ISN" (in the MI element) should be zero. If the MI element is not zero, this message occurs.

ERROR-125 **MI/NI ISNS do not agree**
Explanation Each MI element points to an NI block. If the first ISN in the ISN list for the first NI element (in that NI block) is not the lowest ISN for that value, then that NI element should agree with the "MI ISN". If it does not agree, this message occurs.

ERROR-126 **NI/MI/UI values not increasing**
Explanation In processing the index for one descriptor (in an L9 sequence), the NI block values should be in ascending sequence. This message occurs if either of the following occurs:

- The values within one block are not strictly increasing (equal values are considered an error);
- The first value in an NI, MI, or UI block is less than the last value in the previous block (equal values are allowed).

ERROR-127 **NI block contains zero ISN count**
Explanation The ISN count in an NI element should not be zero.

ERROR-128 **NI block contains invalid ISN**
Explanation The ISN list for one value in an NI block must be in strict ascending sequence. If not, this message occurs. This message also occurs if an ISN is not less than the "first unused ISN" specified in the file control block (FCB).

ERROR-129 **{block-number} block contains incorrect level indicator**
Explanation The third byte in the "block-number" block should contain the following value:

Block Type	Value
U13	0D
U12	0C
U11	0B
U10	0A
U9	09
U8	08
U7	07

Block Type	Value
U6	06
U5	05
U4	04
U3	03
M1	02
N1	01

If the third byte does not contain the correct value, this message occurs.

ERROR-130 RABN outside ASSO extents

Explanation An attempt was made to read a block outside the RABN limits specified by the Associator extents for the general control blocks (GCBs).

ERROR-131 {block-number} RABN outside extents

Explanation A "block-number" RABN is outside the RABN limits defined by the file control block (FCB) UI extents, or an NI RABN is outside the limits defined by the NI extents.

ERROR-132 [AC2] DS RABN {rabn} outside extents

Explanation The Data Storage (DS) RABN given in the message (*rabn*) appears in an address converter (DS RABN) or secondary address converter (AC2 DS RABN) block and is outside the limits defined by the file control block (FCB) DS extents.

ERROR-133 {AC|AC2} MAX ISN should be {value}

Explanation This message occurs if the top ISN value in the file control block (FCB) is incorrect.

The FCB contains the top ISN for each address converter (AC) or secondary address converter (AC2) extent. This is the ISN that corresponds to the last RABN in the last block for that extent. This ISN depends on the top ISN of the previous extent, on the number of blocks in the extent, and on the number of ISNs per block.

ERROR-134 ISN {isn-number} not LT FCB+44 {value} (1ST unused ISN)

or

AC2 ISN {isn-number} not LT FCB+38 {value} (1ST unused AC2 ISN)

Explanation Address converter or secondary address converter (AC2) elements which correspond to ISNs greater than or equal to the first unused ISN (specified in the FCB) must all contain 00000000 or FFFFFFFE. Otherwise, this message occurs. The ISN (*isn-number*) and its value (*value*) are given in the message.

ERROR-135	FCB file number incorrect
Explanation	The requested file number, plus the RABN specified in file 1 FCB's GCB minus one, is assumed to be the FCB RABN for the requested file. The file number specified in that block does not agree with the requested file number.
ERROR-136	FCB highest index level not 3 through 15
Explanation	The highest index level specified in the file control block (FCB) must range 3 through 15, inclusively.
ERROR-137	FCB highest index RABN outside UI extents
Explanation	The highest index RABN specified in the file control block (FCB) must be within the upper index extents (also specified in the FCB).
ERROR-138	First RABN greater than last RABN
Explanation	The extent just printed is invalid because the first RABN is greater than the last RABN.
ERROR-139	{block-number} extent overlaps FST extent {value1} through {value2}
Explanation	The extent specified in the file control block (FCB) overlaps a free extent specified in the free space table (FST).
ERROR-141	FCB {MAXISN MAX AC2 ISN} expected should be {allocated-maxisn}
Explanation	The file's MAXISN setting does not correspond to the MAXISN determined by the MAXISN value (<i>allocated-maxisn</i>) based on the allocated address converter (MAXISN) or secondary address converter (MAX AC2 ISN) extents.
ERROR-142	NR {ix-block-number} blocks processed greater than NR blocks used
Explanation	In performing the index check, a count is taken of the UI blocks read. The "number of blocks used" is the sum of the number of blocks used in each UI extent, which depends on the first RABN and first unused RABN for each extent. If the number of blocks processed exceeds the number used, at least one "ix-block-number" RABN occurs in more than one of that block type, because each "ix-block-number" RABN processed is checked to be sure it is within the used portion of some extent of the same index block type.

ERROR-143	Field names not in ascending sequence - {field-name}
Explanation	Each U3 element contains the field name for the descriptor. Field names must be in ascending sequence. "field-name" is the name of the field that is out of sequence.
ERROR-144	{block-number} field names do not agree
Explanation	Each upper-level index element contains the field name for the descriptor, and also points to a lower-level block. The field name in the first element in the lower-level block must agree with the field name in the higher-level element.
ERROR-145	RABN is outside used ranges
Explanation	The forward pointer in an element of the empty NI/UI block chain contains an invalid RABN. This forward pointer should contain a RABN of another empty NI/UI block, or should contain a zero to indicate the end of the chain.
ERROR-146	Logical block length should be 0006
Explanation	Every empty NI/UI block chained in the empty block chain must have a logical block size of X'0006'. This includes the length field itself (two bytes) and the logical forward pointer to the next block in the chain (four bytes).
ERROR-147	Empty block chain loops back on itself
Explanation	The forward pointer in an element of the empty NI/UI block chain contains an invalid RABN. This forward pointer should contain either a RABN of another empty NI/UI block, or a zero to indicate the end of the chain. However, there is an invalid forward pointer value causing the chain to return into itself.
ERROR-148	Descriptor {desc-name} not found in FDT
Explanation	A descriptor was found in a U3 block that is not in the field definition table (FDT). Every field in the index must be a descriptor if the file is coupled: a sub-/super-/hyper- or phonetic descriptor, a coupling descriptor, or a collation descriptor.
ERROR-149	Descriptor {desc-name} found in FDT but not in U3
Explanation	Every descriptor, sub-/super-/hyper- or phonetic descriptor, coupling descriptor, or collation descriptor must have at least one entry in a U3 block. If there are no values for this descriptor, an empty element is stored (value length=0, ISN=0, RABN=0).

ERROR-150	{ISN AC2 ISN} not found in DS block specified by {AC AC2} element
Explanation	An ISN discrepancy was found between the address converter (AC) or secondary address converter (AC2) and Data Storage. For better analysis of the problem, run the ADACHK ACCHECK utility function.
ERROR-151	Invalid ISN {xxxxxxx} ({nnnnnnnn}) found in RABN {xxxxxxx} ({nnnnnnnn}) offset in DS Block {xxxxxxx}
Explanation	The physical ISN found in the RABN listed in the message in the Data Storage record at the given offset is either zero or is greater than the permitted maximum for the file, based on the ISNs listed in the address converter (ISN) or the secondary address converter (AC2 ISN).
ERROR-152	FDT end reached before record end
Explanation	While decompressing a Data Storage record, ADAICK reached the end of the field definition table (FDT) before finding the end-of-record. This indicates that the compressed record has an incorrect structure.
ERROR-153	Record length is incorrect
Explanation	Either the block length of a Data Storage block is wrong, or the length of a record stored within this block is wrong. The sum of all record lengths, plus 4, should equal the logical block size of the Data Storage block.
ERROR-154	Invalid PE count
Explanation	A periodic group count in a compressed Data Storage record is either 0 or greater than the allowed maximum.
ERROR-155	Invalid MU count
Explanation	A multiple-value field count in a compressed Data Storage record is either 0 or greater than the allowed maximum.
ERROR-156	Invalid CX byte
Explanation	The value for an empty field counter in a compressed Data Storage record that contains X'C0'. Any value from X'C1' through X'FF' is permitted.

ERROR-157	Invalid value length
Explanation	The length of a value in a compressed Data Storage record is wrong. A valid length value is either X'01' through X'7F' or X'8001' through X'80FF'.
ERROR-158	Invalid packed decimal number
Explanation	A packed value within a compressed Data Storage record contains invalid digits.
ERROR-159	ISN/RABN not zero for empty descriptor
Explanation	If a descriptor has no values/ISNs, a value of X'00' is stored in the U3 block to indicate an empty descriptor. The following values for MIRABN and ISN must be zero.
ERROR-160	Invalid value for rotating ISN in FCB
Explanation	The value for the rotating ISN must be less than or equal to the highest ISN, plus 1.
ERROR-161	Duplicate element for empty descriptor
Explanation	There are at least two U3 entries for an empty descriptor. Each descriptor has at least one entry on the U3 level. There may be several entries for one descriptor when the descriptor spans several MI blocks, because each MI block has an entry on the U3 level. Although there are no MI blocks for an empty descriptor, there must be one (and only one) U3 entry.
ERROR-162	Wrong pointer to last parent of super/hyperdescriptor
Explanation	The field descriptor table (FDT) contains an entry pointing to the last parent field of a super- or hyperdescriptor. The pointer contains the wrong value.
WARNING-163	Unreachable index blocks
Explanation	An index block exists that is neither used nor in the unused RABN chain.
Action	No immediate action is needed; however, the RABN block cannot be used until either the Associator is reordered or an UNLOAD/LOAD sequence is performed.
ERROR-164	Error initializing collating user exit - return code={return-code}
Explanation	An error occurred while the collation descriptor user exit was being initialized.
Action	Investigate the cause of the error; correct it; and rerun the job.

ERROR-165	Collating user exit not loaded
Explanation	The collation descriptor user exit requested is not loaded.
Action	Load the exit and rerun the job.
ERROR-166	Invalid value for number of ISN per {AC AC2} block in FCB
Explanation	The value for number of ISNs per address converter (AC) or secondary address converter (AC2) block must be the block size of the corresponding address converter, in bytes, divided by the size of the ISN (either 3 or 4 bytes).
Action	Correct the value provided in the file control block (FCB).
ERROR-167	First element without FE bit
Explanation	The upper index blocks contain index entries for one or more descriptors. The first element for a given descriptor contains the <i>first element bit</i> or <i>FE BIT</i> . A missing FE bit can result in incorrect index positioning or Adabas response codes.
Action	Document the error. Try to fix the error as soon as possible, for example by reinverting the descriptor where the error occurred.
ERROR-168	FDT and index control byte mismatch, DE = {dd}
Explanation	An FDT and index control byte mismatch occurred for the description (<i>dd</i>) listed in the message. The comparison of the two compares the control byte IXUCTL of the index with the control byte FDTF of the FDT.
Action	When this error occurs, dump and print the FDT using the ADAICK FDTPRINT utility. Then contact your Software AG support representative for assistance.
ERROR-169	FDT length in FCB does not match with the FDT, FNR={nnnnn}
Explanation	The length fields found in FDTHLL and YFDTL are not equal. The file number is given in the message.
Action	When this error occurs, dump and print the FCB using the ADAICK FCBPRINT utility for the file listed in the message. Then contact your Software AG support representative for assistance.
ERROR-170	{RABN-errormsgtext}
Explanation	This error can have two different messages, as described in the following table:

Message Text	Description
RABN <i>rabn</i> not in extent	The RABN named in the message does not exist in the extent description of the GCBs.
RABN <i>rabn</i> not in extent, file <i>file</i>	The RABN named in the message does not exist in the extent description of the file.

These messages may occur after an ADAICK DATAPRINT or ADAICK DSCHECK run.

Action For either error message, run ADAICK GCBPRINT. If you receive the second message (RABN *rabn* NOT IN EXTENT, FILE *file*), also run ADAICK FCBPRINT for the file named in the message.

Then contact and send the output from these runs (as appropriate) to your Software AG support representative for assistance.

ERROR-171 **File {fnr} not found or out of range, maxfiles {maxfnr}**

Explanation The file number specified in the FILE= parameter (*fnr*) is not in the database. The maximum file number (*maxfnr*) for the database is also shown in the message.

Action Run an ADAREP utility job on the database to determine the available file numbers for the database. Then correct the ADAICK utility input parameters accordingly and try again.

ERROR-172 **Invalid segment count for spanned DS record**

Explanation The number of spanned record segments has exceeded the maximum of 5.

Action Rebuild the file. Contact your Software AG technical support representative for assistance.

ERROR-173 **Next ISN is zero for master ISN**

Explanation The header of a primary spanned record lists zeros as the ISN for the next secondary record in the spanned record.

Action Contact your Software AG technical support representative for assistance.

ERROR-174 **Offset bigger than ASSO block size**

Explanation During the formatted print of an ASSO block, ADAICK tried to print out data behind the ASSO block.

Action Check the concerning ASSO block. This error may occur if the number of extents is erroneously too big.

- ERROR-176** **Last formatted ISN exceeds MAX ISN**
Last formatted AC2 ISN exceeds AC2 MAX ISN
- Explanation** This error occurs when one of the following invalid conditions occurs:
- The last formatted ISN is higher than the MAXISN.
 - The last formatted AC2 ISN is higher than the AC2 MAXISN.
- Action** Contact your Software AG technical support representative for assistance.
-
- ERROR-177** **Top ISN exceeds last formatted ISN**
Top AC2 ISN exceeds last formatted AC2 ISN
- Explanation** This error occurs when one of the following invalid conditions occurs:
- The top ISN is higher than the last formatted ISN.
 - The top AC2 ISN is higher than the last formatted AC2 ISN.
- Action** Contact your Software AG technical support representative for assistance.

89

ADAINV Utility Messages

ERROR-121 Invalid descriptor field list for invert

Explanation The field name "xx" is either

- not found in the FDT; or
- already a descriptor.

Action Supply the correct parameter value and rerun the job.

ERROR-122 TEMP data set too small; input record count = {count}

Action Supply a larger TEMP data set/file. See the Adabas Utilities documentation for information about calculating TEMP space.

ERROR-123 Invalid or missing couple descriptor

Explanation One of the supplied descriptor names

- is not supplied;
- is not found in the FDT;
- is not a descriptor;
- is a descriptor contained in a periodic group; or
- has a format/length that is incompatible with the other descriptor.

Action Supply the correct parameter value and rerun the job.

ERROR-124	Couple index overflow for file {file-number}
Explanation	This file is already coupled to 18 others; this is the maximum.
ERROR-125	Files already coupled
Explanation	Utility function cannot be processed.
ERROR-126	Coupling not possible
Explanation	<p>This error occurred because</p> <ul style="list-style-type: none">■ a file cannot be coupled to itself;■ expanded files cannot be coupled;■ multicient files cannot be coupled; and■ only file numbers less than 255 can be coupled. <p>The ADAINV function cannot be processed.</p>
ERROR-127	Missing utility function
Explanation	INVERT or COUPLE must be entered, then rerun ADAINV.
ERROR-128	Invalid value for the parameter 'CODE'
Explanation	The value specified for the CODE parameter is either incorrect, or the CODE parameter is not valid in this case.
Action	Either remove the CODE parameter, or specify at most eight digits, or blanks. Rerun the job. Refer to the Adabas Security documentation for more information.
ERROR-129	An attempt was made to create a 16TH index level
Explanation	No more than 15 index levels are possible.
Action	Try this function again with a smaller value for ASSOPFAC.
ERROR-130	Error initializing collating user exit - return code={return-code}
Explanation	An error occurred while the collation descriptor user exit was being initialized.
Action	Investigate the cause of the error; correct it; and rerun the job.

ERROR-131	Collating user exit not loaded
Explanation	The collation descriptor user exit requested is not loaded.
Action	Load the exit and rerun the job.
ERROR-132	Couple index not allocated for file {file} The FCB does not have available space for a couple index.
Explanation	ADAINV detected that there is not enough room in the FCB to allocate couple information.
Action	Correct the error and rerun the job.
ERROR-133	Invalid file requested (file number = {nnn})
Explanation	The ADAINV INVERT and ADAINV COUPLE functions cannot be performed on a LOB file; it is not allowed.
Action	Supply correct file numbers for the FILES parameter and rerun the job.
ERROR-134	The database is active but the utility communications block (DIB) is missing the nucleus entry
Explanation	The ADAINV utility determined the nucleus was active without a DIB entry.
Action	Check the job to ensure the correct ASSO, DATA, and WORK data sets are specified for the given DBID.

90

ADALOD Utility Messages

ERROR-121	Requested restart not possible
Explanation	This error may occur for one of the following reasons: <ul style="list-style-type: none">■ There is no job to be restarted.■ A fundamental parameter value has been changed.■ The previous job abended before reaching the first restart point (the file is not in load status).■ The previous job abended in a state from which no restart is possible (the file is in load status).
Action	Correct the cause of the error, and rerun the ADALOD job.
ERROR-122	TEMP data set too small; input record count= {count}
Action	Supply a larger TEMP data set/file. See the Adabas Utilities documentation for information about calculating TEMP space.
ERROR-123	Missing utility function
Action	Supply either LOAD or UPDATE as the ADALOD function in the parameter input and rerun the ADALOD job.
ERROR-124	Multiple utility functions supplied
Action	Supply either LOAD or UPDATE as the ADALOD function in the parameter input and rerun the ADALOD job.

ERROR-125	Parameter 'ADAMPARM' for non-ADAM-file not permitted
Action	Either add the parameter ADAMFILE or remove the ADAMPARM parameter and rerun the ADALOD job.
ERROR-126	Invalid value for the parameter 'ADAMPARM'
Explanation	The value for this parameter must be in the range 1 to 255.
Action	Supply the correct parameter value and rerun the ADALOD job.
ERROR-128	Parameter 'ADAMDE' for non-ADAM-file not permitted
Action	Either supply the parameter ADAMFILE as well, or remove the ADAMDE parameter. Rerun the ADALOD job.
ERROR-129	Parameter 'ADAMDE' mandatory for ADAM file
Action	Supply the correct parameter value and rerun the job.
ERROR-130	Parameter 'ADAMOFLOW' for non-ADAM file not permitted
Action	Either supply the parameter ADAMFILE as well, or remove the 'ADAMOFLOW' parameter. Rerun the ADALOD job.
ERROR-131	Invalid value for the parameter 'UQDE': {field-name} is not a valid descriptor name
Explanation	The field to be defined as a unique descriptor is invalid. Either it is a simple field and not a descriptor, or the field name is unknown, or it is a descriptor in a periodic group. Probable cause is a misspelling of the descriptor name.
Action	Supply the correct UQDE parameter value and rerun the ADALOD job.
ERROR-132	Invalid 'ADAMDE' field: {field-name} ; conflicting field attributes or unknown descriptor name
Explanation	An ADAM descriptor must meet all the following: <ul style="list-style-type: none">■ Be a single field (no MU option)■ Be a unique descriptor■ Not be contained in a periodic group■ Not have the NU option■ Have a default length (cannot be variable)
Action	Supply the correct parameter value and rerun the ADALOD job.

ERROR-133	Invalid value for the parameter 'ADAMOFLOW'
Explanation	The value must be smaller than DSSIZE.
Action	Supply the correct parameter value and rerun the job.
ERROR-134	Incorrect FDT found in input data set
Explanation	Either the field definition table (FDT) expected in the first record is missing from the data set or the FDT structure read from the data set does not satisfy the rules.
Action	Verify that the input data set is valid. Supply a correct input data set and rerun the job. If the problem persists, contact your Software AG technical support representative for assistance.
ERROR-135	FDT structure mismatch
Explanation	The field definition table (FDT) from the input data set and the FDT from file "file-number" are not the same (the displayed message text contains an actual file number).
	One of the following has happened:
	<ul style="list-style-type: none">■ The file is to be updated and the FDT from the input data set does not match the FDT from the file; or■ The file has been deleted with "KEEPFDT" and the FDT from the input data set does not match that old FDT; or■ The FDT from the input data set does not match the FDT from the anchor of the expanded file.
Action	Check your input data set and your FILE and ANCHOR parameters. If the ADALOD LOAD function was being run, consider using the IGNFDT parameter (refer to the Adabas Utilities documentation for more information).
ERROR-136	FDT larger than 4 ASSO blocks
Explanation	System restriction: the FDT is too large for the device type in use. A load is not possible.
ERROR-137	The input data set/file DDEBAND or DDISN does not have the record format variable or variable blocked (V or VB)
Explanation	The specified input data set is invalid.
Action	Supply a correct input data set and rerun the ADALOD job.

ERROR-138	invalid USERISN {isn-number} found input record count = {count}
Explanation	The USERISN <i>isn-number</i> : <ul style="list-style-type: none">■ is greater than MAXISN or less than MINISN; or■ does not belong to any ISN range of the expanded file. The displayed message text contains actual ISN and count values.
ERROR-139	ISNPOOL overflow ('LIP' parameter value too small) {count} records already read from DDISN
Explanation	Each single ISN requires four bytes, each ISN range requires eight bytes of storage.
Action	Increase the size of the ISN pool (LIP). Supply the correct parameter value and rerun the ADALOD job.
ERROR-142	Duplicate USERISN {isn-number} found
Explanation	One of the following occurred: <ul style="list-style-type: none">■ The supplied USERISN was already present in the file being processed; or■ The ISN appeared twice in the input data set. The record cannot be added.
ERROR-143	{file-type} file already present
Explanation	The requested system file is already present. The file cannot be loaded.
Action	Check the current system file assignments on the ADAREP report.
ERROR-144	Already 10 Adabas system files defined
Explanation	A maximum of ten Adabas system files (files loaded with the SYSFILE file type) are already present. The file cannot be loaded.
Action	Check current system file assignments on the ADAREP report.
ERROR-145	Invalid FDT format
Explanation	The structure of the input FDT is incorrect.
Action	Ensure that your input data set was created using the ADACMP or ADAULD utility.

ERROR-146	Invalid list of DELISNS
Explanation	The DELISN parameter list is wrong, or the input from the DDISN file contains incorrect data.
Action	Check for <ul style="list-style-type: none">■ descending or overlapping ISN ranges■ the same ISN specified more than once■ invalid record length (not a multiple of 4 or 8) The accessed ISN was "isn-number" (the displayed message contains an actual ISN value). Check your input and rerun the ADALOD job.
ERROR-147	Invalid ISN range
Explanation	The ISN range defined by MINISN and MAXISN is invalid. The range conflicts with another ISN range of the expanded file.
Action	Correct the parameter values and then rerun the ADALOD job.
ERROR-148	File {file-number} is not/cannot be anchor of an expanded file
Explanation	The specified file is <ul style="list-style-type: none">■ part of an existing expanded file, but not the anchor file; or■ a coupled or multiclient file and therefore cannot be an anchor file.
ERROR-149	Compressed record too long
Explanation	Input record count = "count-a" Length of record = "count-b" bytes Maximum record length = "count-c" bytes The record is longer than allowed by the MAXRECL parameter or by the characteristics of the data storage device.
ERROR-150	Invalid ISN to be deleted (was) found
Explanation	At least one ISN of the "range" <ul style="list-style-type: none">■ is greater than MAXISN or less than MINISN; or■ does not belong to any ISN range within the expanded file.

ERROR-151	Increasing MAXISN not allowed
Explanation	The file has been loaded with the NOACEXTENSION parameter. It is therefore not possible to increase MAXISN.
Action	Remove the MAXISN parameter, and then rerun the ADALOD job.
ERROR-152	Conflicting USERISN options
Explanation	There are two possible situations: <ol style="list-style-type: none"> 1. The existing file is defined with the USERISN option, but the records from the input file are not defined with the USERISN option. 2. The USERISN options for the file to be loaded and those from the anchor of the expanded file do not match.
Action	Respectively: <ol style="list-style-type: none"> 1. Consider using the USERISN option for the records from the input file, correct the file, and rerun the ADALOD job. 2. Check your input file and the USERISN parameter, correct any error, and then rerun the ADALOD job.
ERROR-153	Invalid ISN for hyperdescriptor {desc-name}
Explanation	The ISN returned from the hyperdescriptor exit <ul style="list-style-type: none"> ■ is less than MINISN or greater than MAXISN; or ■ belongs to another part of the expanded file. <p>Original ISN: (isn-number) Modified ISN: (isn-number) Record count: (count)</p>
ERROR-155	Adabas nucleus required
Explanation	The Adabas nucleus must be active when <ul style="list-style-type: none"> ■ a file is being loaded that has file selection criteria (expanded file component); or ■ records are being loaded with a new owner ID.
Action	Start the nucleus, then rerun the ADALOD job.

ERROR-156	Conflicting owner-ID length
Explanation	One of the following caused the message to occur: <ul style="list-style-type: none"> ■ The LOWNERID parameter value is not in the range 0-8; or ■ The ETID owner ID is longer than LOWNERID (or longer than the owner ID length of the file to be updated).
Action	Supply the correct LOWNERID value, then rerun the ADALOD job.
ERROR-157	Conflicting usage of 'LOWNERID' and 'ETID'
Explanation	The input file is being loaded/added <ul style="list-style-type: none"> ■ with owner IDs, but the owner IDs are not present and the ETID parameter is missing; or ■ without owner IDs, but the ETID parameter is specified.
Action	Supply the correct parameter value for one or both of the parameters, then rerun the ADALOD job.
ERROR-158	Invalid owner-ID in input record
Explanation	The owner ID is too long to fit into the record of the file being loaded or added. Input record count = (count)
Action	Specify an appropriate owner ID, then rerun the ADALOD job.
ERROR-159	Undefined ETID
Explanation	One of the following is the case: <ul style="list-style-type: none"> ■ The user ID referred to by the ETID parameter is not defined; or ■ The user has not been assigned an owner ID.
Action	Specify an parameter value, then rerun the ADALOD job.
ERROR-160	Descriptor value too long
Explanation	A descriptor value together with the owner ID is longer than 253 bytes. Input record count = (count) Descriptor name = (desc-name)
Action	Specify an appropriate combination of owner ID and descriptor value, then rerun the ADALOD job.

ERROR-161	Conflicting {parameter} parameter
Explanation	The "parameter" parameter is invalid as given or implied. It must be the same as for the anchor of the expanded file.
Action	Specify the correct parameter value, then rerun the ADALOD job.
ERROR-162	Hyperdescriptor ISN changed in non-USERISN file
Explanation	The ISN assigned to a descriptor value was modified by a hyperdescriptor exit but the file is not a USERISN file. Changing hyperdescriptor ISNs is only permitted in USERISN files.
Action	Correct the USERISN setting of the file.
ERROR-163	Invalid value for parameter 'ALLOCATION'
Explanation	Valid values are ALLOCATION={FORCE NOFORCE}.
Action	Supply the correct parameter value and rerun the job.
ERROR-164	TEMP block size too small
Explanation	An attempt to store data in a temp block failed because the temp block size is not large enough to hold the amount of data to be stored.
Action	Choose a temp device type with block size equal to or greater than the Associator block size plus 16. Then rerun the job.
ERROR-165	Conflicting file encodings
Explanation	The file encodings on the input media do not match the existing file. They must be the same as the existing file.
Action	Adjust the file encodings and rerun the job.
ERROR-166	Wide fields exist, but the database is not UES-enabled
Explanation	A file with wide-character (W) format fields cannot be loaded until the database is UES enabled.
Action	Enable the database for universal encoding and rerun the job.
ERROR-167	Error initializing collating user exit - return code={return-code}
Explanation	An error occurred while the collation descriptor user exit was being initialized.
Action	Investigate the cause of the error; correct it; and rerun the job.

ERROR-168	Collating user exit not loaded
Explanation	The collation descriptor user exit requested is not loaded.
Action	Load the exit and rerun the job.
ERROR-169	Conflicting '{RPLKEY RPLDSBI}' parameter.
Explanation	The RPLKEY or RPLDSBI parameter (as specified in the message) is invalid as given or implied. It is only valid when RPLTARGETID is specified.
Action	Supply the correct parameter value and rerun the job.
ERROR-170	Invalid 'RPLKEY'-Field: 'field-name'
Explanation	The field to be defined as a replication key is invalid. Either the field name is undefined, or it is not a descriptor.
Action	Supply the correct parameter value and rerun the job.
ERROR-171	RPLTARGETID is specified but the database is not enabled for replication.
Explanation	RPLTARGETID is not valid unless replication is active.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-172	RPLTARGETID = DBID or greater than 65535 is not allowed.
Explanation	Loading a file with RPLTARGETID = DBID is not allowed. The valid range for RPLTARGETID is 1 through 65535.
Action	Supply the correct parameter value and rerun the job.
ERROR-173	RPLTARGETID is not allowed for ciphered files.
Explanation	Ciphered files may not be replicated.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-174	A REPLICATOR file may only be loaded on an Event Replicator Server.
Explanation	The Replicator system file may only be loaded on a database that has been defined as an Event Replicator Server.
Action	Investigate the cause of the error.

ERROR-175	Error loading module ADARPU: {reason}
Explanation	ADALOD was unable to load module ADARPU for the reason listed in the message.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-176	Load of a new file with RPLLOAD=YES requires a non-zero RPLTARGETID
Explanation	When loading a new file when replication has been activated using the RPLLOAD=YES parameter, a target Event Replicator Server must be specified by the RPLTARGETID parameter.
Action	Supply the correct parameter value and rerun the job.
ERROR-177	ADALOD terminated due to the above replication related errors
Explanation	A replication error caused ADALOD to terminate. An earlier error message explains the detailed cause of the error.
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-178	Update with RPLLOAD=YES may only be executed with a replicated file
Explanation	When updating a file with replication activated by specifying the RPLLOAD=YES parameter, the file must already be defined as replicated.
Action	Correct the error and rerun the job.
ERROR-179	An Event Replicator database may only contain the files CHECKPOINT, SECURITY, REPLICATOR, and SLOG
Explanation	A database defined as an Event Replicator Server (created with ADADEF DEFINE REPTOR=YES) must not contain user files or system files not related to replication.
Action	Do not attempt to load files other than CHECKPOINT, SECURITY, REPLICATOR, or SLOG files.
ERROR-180	MU/PE index size mismatch during update. File index size = {n} byte(s). DDEBAND index size = {n} byte(s).
Explanation	The size of the MU/PE indices in the target Adabas file do not match the size of the indices in the input data. ADALOD processing has stopped. As of Adabas 8, an MU/PE index can be either one or two bytes. When doing an update to an existing file with compressed input from either an ADACMP or ADAULD run, it is possible that the size of the MU/PE indices in the existing Adabas file will not match the size of the indices in the ADACMP or ADAULD input. To determine what size indices are used in a file, run an ADAREP report.
Action	Correct the settings for the compressed MU/PE sizes, if appropriate, using the ADACMP MUPEX and MUPECOUNT parameters and retry. If errors persist, contact your Software AG support representative.

ERROR-183	Base file {base-fnr} does not fit to LOB file {lob-fnr}
Explanation	When asked to load a LOB file, ADALOD found that the file specified in the BASEFILE parameter is not suitable for use as the base file for this LOB file, for one of the following reasons: <ul style="list-style-type: none">■ The supposed base file does not contain large object (LOB) fields.■ The file's LOB information does not refer to the specified LOB file.■ The file's UES encoding information is different from that of the LOB file.
Action	Specify correct FILE and BASEFILE parameters and try again.
ERROR-184	LOB file {lob-fnr} does not fit to the base file {base-fnr}
Explanation	When asked to load a base file, ADALOD found that the file specified in the LOBFILE parameter is not suitable for use as a LOB file for this base file, for one of the following reasons: <ul style="list-style-type: none">■ The supposed LOB file is not a LOB file.■ The file's LOB information does not refer to the specified base file.■ The file's UES encoding information is different from that of the base file.
Action	Specify correct FILE and LOBFILE parameters and try again.
ERROR-185	Parameter {parm-name} not allowed for LOB file
Explanation	The parameter specified in the message (<i>parm-name</i>) cannot be used for a LOB file.
Action	Load the LOB file without this parameter.
ERROR-186	DDISN/DELISN delete of an ISN with a LOB reference is not allowed. ISN = {nnnnnn}
Explanation	When performing ADALOD UPDATE operations on a large object (LOB) base file, you are not allowed to delete ISNs that contain references to LOB values that are outsourced in the associated LOB file. This is true whether deleting ISNs using the DELISN keyword or a DDISN data set to specify the ISNs to be deleted. The file is now in an inaccessible state.
Action	Restore the file from backup or reload it and remove the DDISN/DELISN deletion of the ISN(s) containing LOB references. Then resubmit the ADALOD UPDATE job.

ERROR-187	ANCHOR parameter not allowed for a file with LOB fields
Explanation	A file with large object (LOB) fields cannot be an expanded file.
Action	Load the file as a simple (non-expanded) file. Consider using the ISNSIZE=4 parameter setting.
ERROR-189	The database is active but the utility communications block (DIB) is missing the nucleus entry
Explanation	The ADALOD utility determined the nucleus was active without a DIB entry.
Action	Check the job to ensure the correct ASSO, DATA, and WORK data sets are specified for the given DBID.
ERROR-190	SYFMAXUV parameter value is invalid. A value between 0 and 20 is required.
Explanation	An invalid value was specified for the SYFMAXUV parameter. A value between 0 (zero) and 20 is expected.
Action	Correct the parameter setting and try again.
ERROR-192	RPLINITERROR parameter value is invalid. Valid values are 'CONTINUE' or 'FAIL'. Supply the correct parameter value and rerun the job.
Explanation	An invalid value was specified for the RPLINITERROR ADALOD LOAD parameter. The RPLINITERROR parameter specifies the behavior of the ADALOD LOAD utility if replication errors occur when ADALOD LOAD replication is requested (the RPLLOAD parameter is set to YES or FILE). Valid settings for the RPLINITERROR parameter are "CONTINUE" or "FAIL".
Action	Correct the invalid parameter specification and try again.
ERROR-193	RPLLOAD is not allowed for files with spanned data storage records
Explanation	ADALOD parameter RPLLOAD may not be set to FILE or YES when loading a file with spanned data storage records.
Action	Do not specify the RPLLOAD parameter when running ADALOD for a file with spanned data storage records.
ERROR-196	An SLOG system file may only be loaded on a Reptor database.
Explanation	The SLOG system file may only be loaded on a database that has been defined as an Event Replicator Server.
Action	Correct the parameters and rerun the job.

ERROR-901	Unexpected Event Replicator Server response {rc}, subcode {sc} , location {loc}. Replication has failed due to the above errors. ADALOD will continue but the changes will not be replicated. Replication has been deactivated for file {fnr}.
Explanation	ADALOD communication to the Event Replicator Server has failed with the response and subcodes listed in the message and at the location listed in the message. ADALOD LOAD replication was requested during the run (RPLLOAD was set to "YES" or "FILE"), but failed. ADALOD LOAD processing will continue because the RPLINITERROR parameter was set to "CONTINUE". The last line ("Replication has been deactivated for the file <i>fnr</i> ") appears only if the RPLERRORDEACTFILE parameter was set to "YES". The file number for which replication was deactivated is given in the message.
Action	Verify and correct (if necessary) the ADALOD parameters and JCL. Refer to the Adabas response code descriptions for information about the response code and subcode to resolve any errors. If necessary, contact your Software AG support representative for further assistance.
ERROR-902	Duplicate Replication jobs for the same file are not allowed
Explanation	Multiple replication jobs cannot run concurrently for the same file.
Action	Verify and correct (if necessary) the replication job parameters for correct information concerning replication. If problems persist, contact your Software AG support representative for assistance.
ERROR-903	RPLCLEANUP was issued for this ADALOD token
Explanation	An RPLCLEANUP was issued for the Event Replicator Server. This removed the ADALOD token and communication to the Event Replicator Server is no longer possible for this job.
Action	Determine why the operator RPLCLEANUP command was issued. Prepare for file recovery as necessary before rerunning ADALOD.
ERROR-904	Event Replicator Server {id} replication pool overflow
Explanation	The replication pool for the Event Replicator Server listed in the message has an overflow condition, which is a critical error.
Action	Refer to the Event Replicator Server job's system log for error messages, which may provide possible actions to take to resolve the problem.

ERROR-905	Database {dbid} not defined to Event Replicator Server {id}
Explanation	The Adabas database with the database ID (<i>dbid</i>) listed in the message is not defined to the Event Replicator Server (<i>id</i>) listed in the message.
Action	Verify and correct the JCL or input parameters for the ADALOD run. If they are correct, modify the Replicator system file definitions. Then try the ADALOD run again.
ERROR-906	Event Replicator Server {id}, no active subscription or destination for file {number}.
Explanation	No active destination or subscription could be found for the file listed in the message (<i>number</i>) on the Event Replicator Server (<i>id</i>) named in the message.
Action	First verify and correct (as necessary) the file number or the Event Replicator Server target ID for the ADALOD run. If they are correct, modify the Replicator system file subscription and destination definitions. Then try the ADALOD run again.
ERROR-908	The versions of ADALOD and ADARPU are incompatible
Explanation	ADALOD and ADARPU are internally not the correct versions.
Action	Verify and correct (if necessary) the JCL allocation of libraries and input parameters to ADALOD. If problems persist, contact your Software AG service representative for assistance.
	Verify and correct (if necessary) the JCL allocation of libraries or input parameters to ADALOD. If problems persist, contact your Software AG service representative for assistance.
ERROR-909	Internal error in ADARPU+{offset} Register contents at time of error: R0-R3 {#####} {#####} {#####} {#####} R4-R7 {#####} {#####} {#####} {#####} R8-R11 {#####} {#####} {#####} {#####} R12-R15 {#####} {#####} {#####} {#####} Inform your DBA
Explanation	ADARPU has failed with an internal error at the offset given in the message.
Action	Contact your Software AG support representative and provide details of the failure.
ERROR-910	ADARPU cannot load program ADAMGT
Explanation	ADARPU could not load program ADAMGT.
Action	Verify and correct (if necessary) the JCL allocation of libraries and input parameters to ADALOD. If problems persist, contact your Software AG service representative for assistance.

ERROR-911	ADAMSG is incompatible with ADARPU
Explanation	ADARPU has detected an invalid version of ADAMSG.
Action	Verify and correct (if necessary) the JCL allocation of libraries and input parameters to ADALOD. If problems persist, contact your Software AG service representative for assistance.
ERROR-912	The source database Adabas version is not compatible with the Reptor Adabas version
Explanation	The version of Adabas or the Event Replicator used by the Adabas database is not the same as the version of Adabas or Event Replicator used by the Event Replicator Server.
Action	Resolve the discrepancy in Adabas or Event Replicator versions before you try again.

91 ADAMER Utility Messages

ERROR-122	Incorrect FDT found in input data set
Explanation	The structure of the FDT read from the input data set does not satisfy the rules.
Action	Check whether the input data set is valid. Supply a correct input data set and rerun the job.
ERROR-124	Invalid value for the parameter ADAMDE
Explanation	The name of the ADAM descriptor was not found in the FDT.
Action	Supply ADAMDE=ISN or ADAMDE=xx, where "xx" is any valid descriptor name. Then rerun the job.
ERROR-125	Invalid ADAMDE field: {xx}
Explanation	Conflicting field attributes or unknown descriptor name. An ADAM descriptor must <ul style="list-style-type: none">■ be a single field (no MU option);■ be a unique descriptor;■ not be contained in a periodic group;■ not have the NU option;■ have a default length (cannot be variable).
Action	Supply the correct parameter value and rerun the job.

ERROR-126	Invalid value for the parameter BITPARM
Explanation	See the Adabas Utilities documentation for further information.
Action	Supply the correct parameter value and rerun the job.
ERROR-127	Data Storage size too small
Explanation	The amount of Data Storage to store the records is greater than the data size parameter.
Action	Supply the correct parameter value and rerun the job.
ERROR-130	Input data set has spanned records. ADAM files may not be spanned.
Explanation	The input data set has spanned record support active. The spanned record option is not allowed for ADAM files.
Action	Check whether the input data set is valid. Supply a correct input data set and rerun the job.
ERROR-131	Input data set is a LOB file. ADAMER is not allowed for LOB files.
Explanation	The input data set is a large object (LOB) file. LOB files may not be input to ADAMER.
Action	Check whether the input data set is valid. Supply a correct input data set and rerun the job.

92

ADAMTR Utility Messages

ERROR-121	Parameter MTYPE must be set to ETBROKER or MQSERIES
Explanation	An invalid value was specified for the MTYPE parameter of the ADAMTR utility.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-122	Parameter ETBROKERID must be specified when MTYPE=ETBROKER Parameter ETBSERVICE must be specified when MTYPE=ETBROKER Parameter ETBSERVICENAME must be specified when TYPE=ETBROKER Parameter ETBSERVICECLASS must be specified when MTYPE=ETBROKER Parameter MQQNAME must be specified when MTYPE=MQSERIES Parameter MQQMGRNAME must be specified when MTYPE=MQSERIES
Explanation	The listed, required parameters are missing for the selected MTYPE.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-123	ETBROKER parameters may not be specified when MTYPE=MQSERIES MQSeries parameters may not be specified when MTYPE=ETBROKER
Explanation	Improper parameters have been specified for the selected MTYPE.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-124	Load failed for {ADAETB ADAMQS}
Explanation	The module listed could not be loaded by the job.
Action	Check the job output or JCL, correct the error, and rerun the job.

ERROR-125	INIT call failed. Return code {rcrc}, Reason code {reason}
Explanation	The INIT call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-126	CONNECT call failed “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The CONNECT call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-127	OPEN call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The OPEN call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-128	RECEIVE call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The RECEIVE call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-129	BACKOUT call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The BACKOUT call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-130	COMMIT call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The COMMIT call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.

ERROR-131	CLOSE call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The CLOSE call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-132	DISCONNECT call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The DISCONNECT call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-133	TERM call failed. Return code {xxxxxxx} Reason code {xxxxxxx}
Explanation	The TERM call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-134	Parameter PRINT must be set to YES or NO
Explanation	An invalid value was specified for the PRINT parameter of the ADAMTR utility.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-135	Parameter ETBSCONV must be set to YES or NO
Explanation	An invalid value was specified for the ETBSCONV parameter of the ADAMTR utility.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-136	Parameters ETBTOKEN and/or ETBUSERID are only allowed when parameter ETBSCONV=YES
Explanation	A value was specified for the ETBTOKEN and/or ETBUSERID parameters when ETBSCONV was set to NO.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-137	ETBBROKER Service has multi conversation mode data waiting to be consumed, switch to single conversation mode not allowed
Explanation	This error occurs whenever the parameter ETBSCONV is set to YES and there are multi conversation mode messages waiting to be consumed from the last session. Switching to single conversation mode is not allowed until the pending multi conversation mode messages are consumed.
Action	Run ADAMTR with ETBSCONV set to NO and consume the pending multi conversation mode messages.

93

ADAMTS Utility Messages

ERROR-121	Parameter MTYPE must be set to ETBROKER or MQSERIES
Explanation	An invalid value was specified for the MTYPE parameter of the ADAMTS utility.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-122	Parameter ETBROKERID must be specified when MTYPE=ETBROKER Parameter ETBSERVICE must be specified when MTYPE=ETBROKER Parameter ETBSERVICENAME must be specified when TYPE=ETBROKER Parameter ETBSERVICECLASS must be specified when MTYPE=ETBROKER Parameter MQQNAME must be specified when MTYPE=MQSERIES Parameter MQQMGRNAME must be specified when MTYPE=MQSERIES
Explanation	The listed, required parameters are missing for the selected MTYPE.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-123	ETBROKER parameters may not be specified when MTYPE=MQSERIES MQSeries parameters may not be specified when MTYPE=ETBROKER
Explanation	Improper parameters have been specified for the selected MTYPE.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-124	Open failed for file MTSIN
Explanation	The file allocated by the MTSIN DD statement could not be opened.
Action	Check the job output or JCL, correct the error, and rerun the job.

ERROR-125	Load failed for {ADAETB ADAMQS}
Explanation	The module listed could not be loaded by the job.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-126	INIT call failed. Return code {rcrc}, Reason code {reason}
Explanation	The INIT call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-127	CONNECT call failed “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The CONNECT call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-128	OPEN call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The OPEN call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-129	SEND call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The SEND call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-130	CLOSE call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The CLOSE call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.

ERROR-131	DISCONNECT call failed. “{Return-code}” “{reason-code}” “{messaging-system-return-code}” “{messaging-system-reason-code}”
Explanation	The DISCONNECT call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-132	TERM call failed. Return code {xxxxxxx} Reason code {xxxxxxx}
Explanation	The TERM call failed for the selected MTYPE.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-133	Read of MTSIN failed
Explanation	A problem occurred while attempting to read MTSIN. The cause is probably a JCL error.
Action	Check the job output or JCL, correct the error, and rerun the job.
ERROR-134	Parameter ETBSCONV must be set to YES or NO
Explanation	An invalid value was specified for the ETBSCONV parameter of the ADAMTS utility.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-135	Parameters ETBTOKEN and/or ETBUSERID are only allowed when parameter ETBSCONV=YES
Explanation	A value was specified for the ETBTOKEN and/or ETBUSERID parameters when ETBSCONV was set to NO.
Action	Check the parameter input, correct the error, and rerun the job.
ERROR-136	ETBBROKER Service has multi conversation mode data waiting to be consumed, switch to single conversation mode not allowed
Explanation	This error occurs whenever the parameter ETBSCONV is set to YES and there are multi conversation mode messages waiting to be consumed from the last session. Switching to single conversation mode is not allowed until the pending multi conversation mode messages are consumed.
Action	Run ADAMTR with ETBSCONV set to NO and consume the pending multi conversation mode messages.

94

ADAORD Utility Messages

ERROR-121	DDFILEA block size too small
Explanation	The DDFILEA block size ("count-a" bytes) is too small to write a "record-type" record with a length of "count-b" bytes (file "file-number"). Actual values are provided in the message text.
Action	Assign DDFILEA to a device type with a greater sequential block size.
ERROR-122	DDFILEA structure mismatch
Explanation	DDFILEA has an invalid structure (probably a job control statement error).
Action	Correct any error and rerun the ADAORD job.
ERROR-123	No utility function given
Action	Supply one of the following keywords and rerun the job: REORDB, REORASSO, REORDATA, REORFILE, REORFASSO, REORFDATA, RESTRUCTUREF, RESTRUCTUREDB, STORE. See the Adabas Utilities documentation for further information.
ERROR-124	At least one file required
Explanation	An empty file list is not permitted for the functions REORFILE, REORFASSO, REORFDATA and RESTRUCTUREF and STORE.
Action	Supply the correct parameter value, and rerun the ADAORD job.

ERROR-125 **The value for the MAXFILES parameter is less than the highest loaded file number (MAXFILES={count}, highest loaded file number={file-number})**

Action Increase the MAXFILES value and rerun the job.

ERROR-126 **DATASTORAGE record too long. The record with ISN {isn-number} in file {file-number} has a length of {count} bytes. The maximum permitted record length is {maxcount} bytes.**

Explanation The record with ISN *isn-number* in file *file-number* has a length of *count* bytes. The maximum permitted record length is *maxcount* bytes (actual values are given in the message text). This file cannot be processed by ADAORD.

ERROR-127 **Input data set does not contain data for file {file-number}**

Explanation Either a wrong input (DDFILEA) is supplied, or a wrong file is requested.

Action Supply the correct parameter value and rerun the ADAORD job.

ERROR-128 **I/O count mismatch**

Explanation The number of records read from DDFILEA is different from the number of records written to DDFILEA.

DDFILEA : count-a WRITES DDFILEA : count-b READS

Not all files included in processing are currently accessible.

Action Check the job control to see whether there is a multivolume problem. Restore the save tape and rerun the ADAORD job.

ERROR-129 **Invalid value for the 'SORTSEQ' parameter for file {file-number}**

Explanation Allowed values are:

- SORTSEQ=ISN, to process in ISN sequence
- SORTSEQ=DE, where DE is any descriptor whose parent is neither an MU field nor contained in a periodic group, is not a hyperdescriptor or phonetic descriptor, and is not defined with the null suppression (NU) option.

Action Supply the correct parameter value and rerun the ADAORD job.

ERROR-130	Invalid value for the parameter 'NEWDBID'
Explanation	The value for the database ID must be in the range 1 to 65,535.
Action	Supply the correct NEWDBID parameter value and rerun the ADAORD job.
ERROR-131	The descriptor {xx} for file {file-number} has the 'NU' option
Explanation	NU option descriptors must not be used to control the sort sequence of reordering; this may cause a physically inconsistent database.
Action	Select another descriptor for the sort sequence. Then rerun ADAORD. See the Adabas Utilities documentation for more information.
ERROR-132	DSST-space allocation failed
Explanation	Not enough space is left in the Associator to allocate the DSST.
Action	Reduce the value for the MAXFILES parameter and rerun the ADAORD job.
ERROR-133	The MAXISN value specified for file {file-number} is less than the current TOPISN
Explanation	The MAXISN parameter setting must be greater than the TOPISN value listed in the ADAREP report. TOPISN is the highest current ISN allocated for records in the specified file (the file number is given in the message text), and cannot be defined.
Action	Specify the correct MAXISN value and rerun the ADAORD job.
ERROR-134	FST (Free Space Table) not available
Explanation	The free space table is locked by the nucleus or by another utility.
Action	Try rerunning the ADAORD job later.
ERROR-135	MAXISN parameter conflicts with NOACEXTENSION
Explanation	For file "file-number", the NOACEXTENSION option is in effect, but the MAXISN value supplied (new-value) is greater than the old MAXISN (old-value). (Actual file and MAXISN values are given in the message text.)
Action	Supply the correct MAXISN value and rerun the ADAORD job.
ERROR-137	Alternate RABNs cannot be allocated
Explanation	An attempt was made to allocate "count" ASSO/DATA alternate RABNs starting from RABN "start-rabn".
Action	Investigate and correct the cause of the error, and rerun the job.

ERROR-138	Inconsistent file list
Explanation	File "file-number" is either a coupled file or part of an expanded file, but not all related files have been included in the file list.
Action	Supply the correct file list, and rerun the ADAORD job.
ERROR-139	Overwrite system file not possible
Explanation	An attempt was made to overwrite the checkpoint or security file with a file having another file number.
Action	Correct the file number to the original and rerun the ADAORD job.
ERROR-141	Invalid ISN detected
Explanation	The invalid ISN (isn-number) was detected in file (file-number). The ISN is either <ul style="list-style-type: none"> ■ equal to zero; or ■ greater than MAXISN (max-isn-val).
Action	Repair the file and reexecute ADAORD.
ERROR-142	Duplicate ISN detected
Explanation	ISN (isn-number) is contained twice in file (file-number).
Action	Correct the file and reexecute ADAORD.
ERROR-143	DLOG area allocation failed
Explanation	The allocation of the DSF logging area failed. An attempt was made to allocate (count) blocks starting at Associator RABN (ravn-number).
Action	Correct the RABN assignment and reexecute ADAORD.
ERROR-144	Error on DDFILEA
Explanation	After reopening DDFILEA for input, the first record read did not have record number 1. Not all the files included in the processing are currently accessible.
Action	Check the JCL to determine whether there is a multivolume problem. Restore your save tape and rerun the ADAORD job.

ERROR-145	Storing {CHECKPOINT SECURITY} file not allowed
Explanation	A version 5.2 or below checkpoint file cannot be converted by ADAORD STORE to version 5.3 or above. A version 5.3 or below security file cannot be converted by ADAORD STORE to version 6.1 or above.
Action	Remove the checkpoint or security file from the file list and rerun ADAORD.
ERROR-146	Descriptor not found
Explanation	The nucleus returned response code 57 (ADARSP057): the descriptor "xx" for file "file-number" could not be found. ADAORD cannot unload the index for this file.
Action	Run the ADACHK ICHECK utility function for this file; remove the error and rerun the ADAORD utility run.
ERROR-147	Duplicate file number detected
Explanation	The file "file-number" was specified twice (the actual file value is provided in the message text).
Action	Correct the error and rerun the job.
ERROR-148	Partial overwrite of coupled/expanded files
Explanation	The file "file-number-a" is coupled with or, in an expanded file, linked to the file "file-number-b", which is not part of the STORE operation (the actual file values are provided in the message text). This STORE operation cannot be serviced because it would result in a logical data inconsistency.
Action	Check the STORE function parameter input; correct the error and then rerun the STORE job.
ERROR-149	Invalid value for parameter 'ALLOCATION'
Explanation	Valid values are ALLOCATION=FORCE NOFORCE.
Action	Supply the correct parameter value and rerun the job.
ERROR-150	Invalid EXCLUDE parameter
Explanation	The file number given in the message either has not been specified at all for REORDER/STORE, or has been specified twice in the EXCLUDE parameter.
Action	Correct the error and rerun the job.

ERROR-151	File {file-number} is a physically coupled file The ISNSIZE cannot be modified
Explanation	A coupled index contains the ISNs of the file it is coupled to. These ISNs have the byte-size specified by the other file's ISNSIZE. Even if the other file is also modified by ADAORD, the ISNSIZE cannot be modified using the coupled index.
Action	Remove the ISNSIZE parameter or modify the file-list.
ERROR-152	Overwrite system file not possible
Explanation	The Replicator or SLOG system file may not be overwritten by a non-system file with the same file number.
Action	Correct the file number to the original and rerun the ADAORD job.
ERROR-153	Storing Replicator/SLOG file not allowed
Explanation	The file on the input media is not a valid Replicator or SLOG system file.
Action	Remove the Replicator or SLOG system file from the file list and rerun ADAORD.
ERROR-154	A Reptor database may only contain the files CHECKPOINT, SECURITY, REPLICATOR, and SLOG
Explanation	A database defined as an Event Replicator Server (created with REPTOR=YES) must not contain user files or system files not related to replication.
Action	Do not attempt to store files other than CHECKPOINT, SECURITY, REPLICATOR, or SLOG on Event Replicator Servers.
ERROR-155	The MAXISN2 value specified for file {file-number} is less than the current TOP AC2 ISN
Explanation	The MAXISN2 parameter setting must be greater than the TOP AC2 ISN value listed in the ADAREP report. TOP AC2 ISN is the highest current secondary ISN allocated for secondary spanned records in the specified file (the file number is given in the message text), and cannot be defined.
Action	Specify the correct MAXISN2 value and rerun the ADAORD job.
ERROR-156	Invalid value for the parameter MAXISN2
Explanation	The MAXISN2 parameter values must satisfy the following expressions: <ul style="list-style-type: none"> ■ If the ISNSIZE is 3, the value of MAXISN2 must be greater than zero, but less than or equal to 16,777,215 (0 < MAXISN2 <= 16,777,215). ■ If the ISNSIZE is 4, the value of MAXISN2 must be greater than zero and less than or equal to 4,294,967,294 (0 < MAXISN2 <= 4,294,967,294).
Action	Supply the correct MAXISN2 parameter value and rerun the job.

ERROR-157	Maximum number of user system files defined File {file-number} was originally loaded with the SYSFILE option, but the maximum number of user system files already exists.
Explanation	The limit of ten user system files has already been reached.
Action	Unload, delete, and reload one of the user system files without the SYSFILE option. Then rerun this utility.
ERROR-158	The database is active but the utility communications block (DIB) is missing the nucleus entry
Explanation	The ADAORD utility determined the nucleus was active without a DIB entry.
Action	Check the job to ensure the correct ASSO, DATA, and WORK data sets are specified for the given DBID.
ERROR-163	A replication system file may only be stored on a Reptor database.
Explanation	The replication system file may only be stored on a database that has been defined as a replication server.
Action	Investigate the cause of the error.
ERROR-164	An SLOG system file may only be stored on a Reptor database.
Explanation	The SLOG system file may only be stored on a database that has been defined as a replication server.
Action	Investigate the cause of the error.

95

ADAPLP Utility Messages

ERROR-121

Missing function

Explanation

One of the following function codes is required:

- PLOGPRI
- SPLOGPRI
- WORKPRI

Action

Supply the correct function value and rerun the job.

ERROR-122

Invalid value for the parameter 'TYPE'

Explanation

Valid values are:

- TYPE=ALL
- TYPE=ASSO
- TYPE=DATA
- TYPE=REPR
- TYPE=SAVO
- TYPE=ET
- TYPE=C1
- TYPE=C5
- TYPE=VEKZ
- TYPE=EEKZ

Action

See the ADAPLP utility description in the Adabas Utilities documentation for more information.

- ERROR-123** **Missing ASSO data sets**
Explanation The Associator data set(s) is required for the WORKPRI function.
Action Correct the job control statements to specify the required ASSO data sets, and rerun the ADAPLP job.
- ERROR-124** **There is a discrepancy between the protection record and the ADABAS version**
Explanation The version indicates that the timestamp should be included on the protection record but it was missing.
Action Check how this protection record was created and correct the protection record. Otherwise, contact customer support with information on how the protection record was created (nucleus or utility DDPRINT) and provide a copy of the input dataset used for ADAPLP along with the ADAPLP output.

96

ADAPRI Utility Messages

ERROR-121	Missing function
Explanation	At least one valid function must be supplied: ASSOPRI, DATAPRI, WORKPRI, TEMPPRI, SORTPRI, CLOGPRI, PLOGPRI, and RLOGPRI, or DSIMPRI.
Action	Supply the correct parameter value and rerun the ADAPRI job.
ERROR-122	Missing ASSO data sets
Explanation	The Associator data set(s) is required for the following functions: ASSOPRI, DATAPRI, WORKPRI.
Action	Add the appropriate data set to the job control JCL/JCS, and rerun the ADAPRI job.
ERROR-123	Invalid RABN range
Explanation	The TORABN value cannot be less than the FROMRABN value.
Action	Provide the correct parameter values and rerun the ADAPRI job.
ERROR-124	Invalid 'NUMBER' parameter
Explanation	NUMBER must be 1 through 8. The parameter is valid only for the CLOGPRI and PLOGPRI functions.
Action	Provide the correct parameter value, and rerun the ADAPRI job.

97 ADARAI Utility Messages

- ADARAI Error Messages Written to the Output Recovery Job (ERROR-160 - ERROR-169) 1356

This document describes general ADARAI errors (errors 117-159), ADARAI errors written to the output recovery job (errors 160 to 169), and informational ADARAI messages.

ERROR-117	DSIMSIZE/DSIMDEV parameters required
Explanation	ADARAI RECOVER was invoked for a database where the Delta Save Facility was active. In order to run correctly, ADARAI must know the DSIM device type and size of the DSIM data set. This could not be established using the RLOG and the parameters were not provided to ADARAI; therefore, ADARAI operation cannot continue.
Action	Specify the DSIMDEV and DSIMSIZE parameters to ADARAI.
ERROR-118	Skeleton for {job-control} contains a {keyword} placeholder. This is not permitted for this skeleton
Explanation	The skeleton job control for the <i>job-control</i> step in the supplied skeleton job control contained a <i>keyword</i> place holder. This placeholder is not permitted in the <i>job-control</i> step.
Action	Modify the 'job-control' step in the skeleton to remove the 'keyword' placeholder specification.
ERROR-119	Skeleton for {job-control} contained two or more {keyword} placeholder definitions
Explanation	The skeleton job control for the <i>job-control</i> step in the supplied skeleton job control contained two or more <i>keyword</i> placeholders prior to the next step. Each placeholder should only be specified once in each job control step in the skeleton; otherwise, ADARAI cannot determine which one to use.
Action	Modify the 'job-control' step in the skeleton to only specify the 'keyword' placeholder once.
ERROR-120	Skeleton for {job-control} did not contain required {keyword} placeholder
Explanation	The skeleton job control for the <i>job-control</i> step in the supplied skeleton job control did not contain the <i>keyword</i> placeholders anywhere prior to the next step. In order to insert the correct replacement data in the appropriate place in the skeleton, the <i>keyword</i> placeholder must be provided at some point in the <i>job-control</i> skeleton.
Action	Modify the 'job-control' step in the skeleton to include the 'keyword' placeholder specification.
ERROR-121	Invalid file number {file-number} is an invalid file number
Explanation	The file number <i>file-number</i> is greater than the maximum permitted for the database.
Action	Supply a valid file number and rerun the job.

ERROR-122	Specified DRIVES parameter {drives} larger than original DRIVES parameter {original}
Explanation	The ADARAI RECOVER DRIVES parameter was set to <i>drives</i> , however, the original save job was originally run with DRIVES= <i>original</i> . The DRIVES parameter specified for ADARAI RECOVER must be equal to, or less than the original DRIVES parameter. ADARAI ignores the specification and uses the original DRIVES parameter.
Action	Modify the DRIVES parameter to use a valid value.
ERROR-124	Invalid file number requested. There is not recovery log information for the following file number (s): File={nn}
Explanation	The file is not known to the recovery log (RLOG). If the file was created by an ADADBS operation, the required checkpoint was not included in the checkpoint file, and the RLOG has no record of the change.
Action	Supply correct file numbers and rerun the job.
ERROR-127	RLOG is incorrect version. Execute PREPARE function and rerun the job
Explanation	The RLOG is from a version of the recovery aid prior to version 7.1, but the newer Adabas recovery aid requires an RLOG created by the updated ADARAI PREPARE function.
Action	Run the ADARAI PREPARE function to convert the RLOG.
ERROR-130	Parameter RLOGSIZE missing or invalid. A minimum of {nn} blocks is required
Action	Supply a valid RLOGSIZE parameter and rerun the job.
ERROR-131	Invalid value for parameter MINGENS. The value for this parameter must be in the range 4 through 32
Action	Supply a valid MINGENS parameter and rerun the job.
ERROR-133	Missing or invalid JCL pattern
Explanation	The input parameter list does not contain a valid pattern string for the JCL to be generated.
Action	Supply a correct JCL/JCS pattern and rerun the job. See the Adabas Utilities documentation for the syntax description.

ERROR-136	Invalid value for the RELGEN parameter
Explanation	The value is either greater than MINGENS - 1 or, for a Recovery operation, points to a nonexistent generation.
Action	Supply a valid RELGEN parameter and rerun the job.
ERROR-138	ADARES PLCOPY not acknowledged
Explanation	The Adabas nucleus is not up. ADARAI called the user exit 2 (dual log processing) or user exit 12 (multiple log processing) to submit a job to copy pending data from a protection log. ADARAI waited for the copy to complete; however, the copy did not complete in the time that ADARAI was waiting.
ERROR-139	ADARES PLCOPY not acknowledged
Explanation	The Adabas nucleus was called with a FEOFPL command to close and copy the current dual or multiple protection log. ADARAI waited for a copy to be submitted and completed as a result of this command; however, the copy did not complete in the time that ADARAI was waiting.
ERROR-140	ADARAI not permitted to run. The Adabas nucleus returned response {nnn}.
Explanation	The only acceptable response is 148.
Action	Shut down the nucleus and rerun the job.
ERROR-141	Internal error occurred in module RAGDOS: GETVIS failure occurred for PUTSPOOL buffer
Action	Increase the size of the partition GETVIS and rerun the job.
ERROR-142	Internal error occurred in module RAGDOS: PUTSPOOL job submission error. Internal return code is {X'nnn}'
Action	See the <i>IBM POWER Installation and Operations Manual</i> for corrective action. Then rerun the job.
ERROR-143	Internal error occurred in module RAGDOS: Invalid calling function determined
Action	Contact your Software AG technical support representative.

ERROR-144	Internal error occurred in module RAGDOS: CDLOAD failure for ADAIOI
Action	Check the return code for CDLOAD for corrective action and rerun the job.
ERROR-145	Internal error occurred in module RAGDOS: CDLOAD failure for ADAOPTD
Action	Check the return code for CDLOAD for corrective action and rerun the job.
ERROR-146	Internal error occurred in module RAGDOS: SUBSID error
Action	Check the return code for SUBSID for corrective action and rerun the job.
ERROR-147	Internal error occurred in module RAGDOS: GETVIS error
Action	Check the return code for GETVIS for corrective action and rerun the job.
ERROR-148	Internal error occurred in module RAGDOS: DLBL record length limit
Action	Contact your Software AG technical support representative.
ERROR-149	Internal error occurred in module RAGDOS: JCL buffer exceeded
Action	Contact your Software AG technical support representative.
ERROR-150	Internal error occurred in module RAGDOS: LUB tabe exceeded
Action	Contact your Software AG technical support representative.
ERROR-156	Invalid JCL control keyword
Action	Supply a correct JCL/JCS input and rerun the job.
ERROR-157	Generation {nn} is {xxxxxxx}
Explanation	ADARAI was not able to LIST or RECOVER a generation because the generation is either erroneous or restricted.
Action	Determine the reason for the problem, correct it, and rerun the job.
ERROR-158	ADARAI not permitted to run. The Adabas nucleus returned response {rc}, subcode {sc}
Explanation	ADARAI was unable to run because of the problem indicated by the Adabas nucleus response code <i>rc</i> and, if relevant, the subcode <i>sc</i>
Action	See the Adabas response code/subcode descriptions .

ERROR-159	ADARAI PREPARE not permitted to run
Explanation	The RLOG is in an invalid state for PREPARE. If the RLOG is in use, issue an ADARAI REMOVE for the RLOG. If this is a new RLOG, it must be formatted before running ADARAI PREPARE. The RLOGSIZE defined using ADARAI PREPARE must be the same as that previously defined by the SIZE parameter of the ADAFRM RLOGFRM function.
Action	Use ADARAI REMOVE to deactivate the RLOG, or ADAFRM RLOGFRM to reformat the RLOG before running ADARAI PREPARE.

ADARAI Error Messages Written to the Output Recovery Job (ERROR-160 - ERROR-169)

The following errors are written directly to the output recovery job to

- ensure that the job cannot run without modification, and
- identify the point in the job generation where the error was encountered.

ERROR-160	The generation used to create the following job was {status}
Explanation	The generation used to generate the job had a status other than "normal". This indicates that ADARAI determined at some time during the creation of the generation that the job it would generate could not run without changes by the user.
Action	Determine the reason for the status and modify as appropriate. When the generation is "restricted", a later message indicates where the generation actually became restricted. Generally, such jobs run successfully with intervention. If the generation is "erroneous", it is impossible to know what caused this during the recovery phase; therefore, you must determine what caused the problem and correct it in the recovery job if possible and appropriate.
ERROR-161	No full save data set available in generation
Explanation	The generation being recovered has no full save data set associated with it. This should only occur for the first generation allocated by default after the RLOG is prepared.
Action	Determine the last full save data set prior to the generation and insert a step to restore this prior to using the generated recovery job. Any steps that took place between the time the full save was taken and the RLOG became available must also be inserted here to insure that the recovery job runs and that the resulting data is valid.

ERROR-162	Missing PLOG data set information PLOG number = {plog} low PLOG block = {lowblk} [NUCID {nucid}] high PLOG block = {highblk} [NUCID {nucid}]
Explanation	During the generation of the recovery job, ADARAI determined that it needed the range of PLOG blocks listed in the message; however, these PLOG blocks were not recorded in the generation being recovered. This may occur if the generation was restricted, or a PLCOPY step to copy a PLOG failed to record its execution on the RLOG data set. When it is nonzero, a cluster nucleus ID is appended after the low and high PLOG block number.
Action	Determine the PLOG on which the range of blocks is located and add this data set to the job at the appropriate point as identified by the location of the message.
ERROR-163	Generation became restricted following this step
Explanation	This identifies the point in the recovery job at which the generation became "restricted" and the reason why it was restricted. With user intervention, it should be possible to handle the reason for the generation becoming restricted and thus to enable the recovery job to successfully recover the database.
Action	Take appropriate action to handle the reason for the restriction.
ERROR-164	No session end record found Insure all PLOGs are included prior to next utility run
Action	ADARAI encountered an off-line utility execution at a point where a session start record was found but no session end record was found. This indicates that the nucleus session terminated abnormally prior to the off-line utility being executed. This means that ADARAI cannot determine precisely what the last PLOG block of that session was and can only attempt to include all PLOG blocks it knows about for that session.
Action	Ensure that all PLOGs for that particular session are provided to the REGENERATE prior to the utility step about to be executed. Additional PLOGs for the session, not known to ADARAI, can be added at the end of the DD/SIIN statement.
ERROR-165	No RESTPLOG entry found
Explanation	A RESTONL request was encountered that is normally followed by a RESTPLOG entry indicating the PLOGs that must be provided to the RESTONL for it to complete successfully. In this case, no RESTPLOG entry could be found relating to the RESTONL function that was encountered. Under normal circumstances, this can only occur if the RESTONL function fails during the PLOG processing stage and the RESTPLOG is not repeated stand-alone.
Action	Determine if the RESTPLOG was in fact successfully issued but not recorded on the RLOG. If so, the appropriate PLOGs can be added to the RESTONL step based on the information in the RESTPLOG job itself.

ERROR-166	No starting PLOG information found
Explanation	While building the recovery job, ADARAI encountered a utility operation that was run online; however, no preceding nucleus sessions start record was encountered. This can only occur if the generation is "restricted" or the session start logging to the RLOG failed.
Action	If there is no reasonable explanation why this occurred, contact your Software AG technical support representative.
ERROR-167	RESTPLOG encountered out of sequence SYN1 PLOG block ={plogblk} [NUCID {nucid}] SYN2 PLOG block ={plogblk} [NUCID {nucid}]
Explanation	Under normal circumstances, a RESTPLOG request is only encountered in association with a RESTONL utility operation. In this case, a RESTPLOG was encountered for the PLOG blocks identified with no preceding RESTONL request. When it is nonzero, the cluster nucleus ID is appended after the block number.
Action	Determine how the RESTPLOG entry occurred at that point and determine if the recovery job will run successfully without that step.
ERROR-168	Job contains one or more errors
Explanation	While building the recovery job, ADARAI detected one or more errors that have rendered the generated recovery job not executable.
Action	Correct the errors identified earlier in the job and run the job if it can be successfully repaired based on the errors that have occurred.
ERROR-169	The previous step was incomplete
Explanation	The ADARAI data collection mechanism was notified that the step prior to this message was preparing to complete its processing; however, a 'commit' record was not written for the utility execution indicating that either it did not run to completion or the commit record could not be written.
Action	Determine the reason for the failure to complete the information on the RLOG. If the recovery job can run successfully without the failing step, remove the step completely from the recovery job. If required, make the appropriate corrections to the job step.
INFO-001	The following PLOG numbers were not used: low PLOG number {lowplog} [NUCID {nucid}] high PLOG number {highplog} [NUCID {nucid}]
Explanation	During its PLOG validation processing, ADARAI checks to see whether the PLOG session numbers it encounters are in sequential ascending order (e.g., PLOG 8 follows PLOG 7, PLOG 7 follows PLOG 6 and so on). When it encounters a situation where this is not the case, this message is issued identifying the range of 'missing' PLOGs. This can occur when online saves are used. When it is nonzero, a cluster nucleus ID is appended after the session number.

INFO-002**File number {file} deleted****Explanation**

During optimized ADARAI RECOVERY processing, a deleted file may simply not figure in the recovery job itself. This message is issued to register the fact that the file number `file` was deleted during the generation being recovered.

98

ADAREP Utility Messages

ERROR-121	Nucleus returned response {resp-code} while reading/opening the checkpoint file. ({nucleus-response})
Explanation	Refer to chapter 3 for the meaning of "resp-code".
Action	Investigate the cause of the error. Correct it and rerun the job.
ERROR-122	Inconsistency detected between FST and GCB (internal error)
Explanation	The FST contains RABNs that do not belong to the database.
Action	Repair the FST using Adabas basic system or ADADBS recover.
ERROR-123	Inconsistency between DSST and FCB file extent (internal error)
Explanation	A(DSST-EXTENT-ENTRY) = xxxxxxxx A(FCB-EXTENT-ENTRY) = xxxxxxxx
Action	Inform your database administrator (DBA) of the error.
ERROR-124	Inconsistency between file {file-name} and GCB (internal error)
Explanation	The file extents contain RABNs that do not belong to the database.
Action	Repair the file using RESTORE and REGENERATE.
ERROR-125	Inconsistency in mirror block (internal error)
Explanation	The mirror table has an incorrect structure; it cannot be interpreted.
Action	Repair the mirror table using ADAREF; then mirror your database again.

ERROR-126	Invalid parameter value for parameters FROMDATE/TODATE or FROMSESSION/TOSESSION
Action	Supply the correct parameter value and rerun the job.
ERROR-127	Invalid FROMDATE / TODATE parameter
Explanation	The FROMDATE / TODATE parameters must have the format yyymmdd.
Action	Supply the correct parameter value and rerun the job.
ERROR-128	Invalid save tape supplied
Explanation	The data set supplied as the DD/SAVE input data set is not a save tape.
Action	Supply a valid save tape and rerun the job.
ERROR-129	Save tape must be from V71 or higher
Explanation	The supplied save tape was not created using Adabas version 7.1 or above.
Action	Supply a save tape created using Adabas version 7.1 or above and rerun the job.
ERROR-130	ECS error. See ADAU7A in DDPRINT
Explanation	An attempt has been made to access a UES code page, typically with the ACODE parameter.
Action	The ADAU7A message is probably as follows: <pre>ADAU7A ECS ERROR -7 IN FUNCTION GETHANDL 0888</pre> It may be that the ACODE code supplied is not in the DDECSOJ data set or library, or that the DDECSOJ DD card or link name has not been supplied. Check the JCL and rerun the job.
ERROR-131	Statement OUTPUT error. Statement OUTPUT can be: XML XML,UTF8 ,XML ,UTF8 UTF8 UTF8,XML
Explanation	The OUTPUT parameter statement has been incorrectly specified.
Action	Check the options supplied with the list in the error message. Correct it and rerun the job.

ERROR-132	Statement ACODE error. Statement ACODE can be: For DBName - GCB or CodePage or omitted For FileName - GCB or FCB or CodePage or omitted For CheckPoint - GCB or CodePage or omitted
Explanation	The ACODE parameter statement has been incorrectly specified.
Action	Check the options supplied with the list in the error message. Correct it and rerun the job.
ERROR-133	Parameter PRINT must either be ON or OFF or omitted
Explanation	The PRINT parameter statement has been incorrectly specified.
Action	Check the options supplied in the error message. Correct it and rerun the job.
ERROR-134	At least one output media must be enabled. Set PRINT=ON or a valid value for the OUTPUT parameter or set both
Explanation	The combination of values for the OUTPUT and PRINT parameter statement has been incorrectly specified.
Action	Check the options supplied in the error message. Correct it and rerun the job.
WARN-135	Ignored invalid value for parameter CP: {invalid_value}
Explanation	The parameter CP has been incorrectly specified.
Action	Remove the invalid keyword and rerun the job.
ERROR-136	Parameter CP only allowed when CPLIST or CPEXLIST specified
Explanation	The parameter CP has been incorrectly specified.
Action	Remove the CP parameter or add the CPLIST/CPEXLIST parameter and rerun the job.
ERROR-137	At least one valid value for parameter CP is required
Explanation	The parameter CP has been incorrectly specified.
Action	Use one or more values from the following list for the CP parameter and rerun the job. Valid keywords for the CP parameter are: <ul style="list-style-type: none">■ SESSION■ NUCLEUS■ ADASAV■ ADAINV■ ADAORD■ ADADEF

- ADARES
- ADALOD
- ADAULD
- ADAZAP
- SYSAOS
- ADADBS
- ADASCR
- EXF
- EXU

99 ADARES Utility Messages

This document describes general and warning ADARES messages.

ERROR-121	Protection log number mismatch
Explanation	The protection log number specified by the PLOGNUM/FROMPLOG parameter could not be found on the input log media.
Action	Supply a correct protection log data set and rerun the job.
ERROR-122	FROMCPC/FROMBLK not found
Explanation	The start checkpoint/block number specified in the FROMCPC/ FROMBLK parameter could not be found on the protection log number "log-number" (the actual log number is shown in the message text).
Action	Supply the correct parameter value and rerun the job.
ERROR-123	Ending block number not found
Explanation	The block number specified in the TOBLK parameter could not be found on the protection log input.
Action	Supply the correct parameter value and rerun the job.
ERROR-124	Invalid log number specification
Explanation	The nucleus is not able to obtain the number of the last block written to the sequential protection log data set for the requested session <i>session-id</i> .
Action	Contact your Software AG technical support representative.

ERROR-125	Dual log modified during copy run
Explanation	User exit 2 of the nucleus is <ul style="list-style-type: none">■ used: the copy run was started twice using the exit; or■ not used: the nucleus started writing to the part of the dual log being copied before the copy run finished.
Action	Save the ADARES output and contact your Software AG technical support representative.
ERROR-126	Invalid FROMBLK/FROMCP/TOBLK/TOCP values
Explanation	Missing or invalid FROMCP or TOCP specification.
Action	See the Adabas Utilities documentation for further information.
ERROR-127	Database ID mismatch
Explanation	The ADARUN DBID is "dbid-a", but the DDSIIN input data set contains data for DBID "dbid-b", on block "block-number", "session-id". Either the wrong database is accessed, or the utility input parameter specifies a wrong database ID.
Action	Correct the error and rerun the job.
ERROR-128	Inconsistent file list
Explanation	File "file-number" is either a coupled file or part of an expanded file; however, not all corresponding files have been included in the file list.
Action	Supply a correct file list, or specify the IGNORECOUPLE/IGNOREEXP parameters, then rerun the ADARES job.
ERROR-129	Empty PLOG data set for backout
Explanation	PLOGR1/R2 are empty. Backout from disk is not possible.
Action	Save the ADARES output and contact your Software AG technical support representative.
ERROR-130	PLOG data set not yet copied
Explanation	An attempt was made to read from data set (name), but this data set has not been copied.
Action	Run the ADARES function PLCOPY first to save the contents of the dual or multiple protection log data set, then rerun this job.

ERROR-131	TOCP/TOBLK not found on dual protection log
Explanation	The requested checkpoint for backout DPLOG is not on the data set (name).
Action	Supply a correct protection log and rerun the job.
ERROR-132	Invalid value for the parameter 'DSRABN'
Explanation	One of the following is required: <ul style="list-style-type: none">■ a single RABN; or■ an ascending range of RABNs.
Action	Supply the correct parameter value and rerun the job.
ERROR-133	Conflicting FROMPLOG/TOPLOG parameters
Explanation	For the REGENERATE function, the value for TOPLOG must not be less than the value specified for FROMPLOG. For the BACKOUT function, the inverse must be true: the FROMPLOG value must not be less than the TOPLOG value.
Action	Supply a correct parameter value and rerun the ADARES job.
ERROR-134	Protection log number mismatch
Explanation	The protection log data sets are not supplied in the correct order: the current protection log number has number (log-number-a); the previous had number (log-number-b).
Action	Supply the correct sequence of protection logs and rerun the job.
ERROR-135	TOBLK/TOCP not found on sequential protection log
Explanation	The specified TOBLK does not contain the TOCP. The input has been processed, including the block specified by TOBLK.
Action	Supply the correct parameter value and rerun the ADARES job.
ERROR-136	Invalid block number found
Explanation	The blocks of the current PLOG are not supplied in the correct order, or the first block of a PLOG does not have number 1. The block just read has number (block-number) on protection log number (log-number). The displayed message text contains actual block and log numbers.
Action	Supply the correct sequence of protection logs and rerun the job.

ERROR-137	Missing function parameter
Explanation	The ADARES statement did not specify an ADARES function.
Action	Supply an ADARES function (BACKOUT, CLCOPY, COPY, MERGE, PLCOPY, REGENERATE, REPAIR) and rerun the ADARES job.
ERROR-138	DBID mismatch
Explanation	On PLOG number (log-number), block number (block-number), DBID (dbid-a) was found, but the PLOG DBID parameter value is (dbid-b).
Action	Supply the correct PLOG input and rerun the ADARES job.
ERROR-139	DDSIIN input error
Explanation	Sessions to be copied include both PLOG and SAVE sessions.
Action	Supply the correct input and rerun the ADARES job.
ERROR-140	DDSIIN input error
Explanation	Timestamps are not ascending in session number "session-id". The block in error has number (block-number).
Action	Supply the correct input and rerun the ADARES job.
ERROR-141	Parameter {parameter} not allowed in MODE=SINGLE
Explanation	The parameter parameter cannot be specified in single-user mode.
Action	Rerun the job with the ADARUN parameter MODE=MULTI.
ERROR-142	Parameter {parameter} not allowed without DSF
Explanation	The parameter is only available when the Delta Save Facility is installed.
System Action:	ADARES terminates abnormally.
Action	If the Delta Save Facility is installed, specify ADARUN DSF=YES and rerun the job.
ERROR-143	Error during DSIM data set processing
Explanation	An error occurred while the Delta Save Facility was processing (building) the delta save images (DSIM) data set. The DSIM data set has not been built correctly. The reason for the error is indicated by a preceding Delta Save error message. This ADARES error message is only issued if the COPY function is executed without a sequential output data set.
System Action:	ADARES terminates abnormally.
Action	Determine and eliminate the cause of the error; then rerun the job.

ERROR-144	Parameter AUTOBACKOUT not allowed
Explanation	The AUTOBACKOUT parameter is allowed only when the TOCP parameter value is also specified.
Action	Correct the input parameter specifications, then rerun the ADARES job.
ERROR-145	Invalid EXCLUDE parameter
Explanation	The file number provided in the message either has not been specified at all for REGENERATE/BACKOUT, or has been specified twice in the EXCLUDE parameter.
Action	Correct the error and rerun the job.
ERROR-146	File excluded from REGENERATE
Explanation	<p>The REGENERATE function excluded one or more files from the regeneration. Possible causes:</p> <ul style="list-style-type: none">■ The nucleus returned a response code for the file.■ ADARES encountered a utility checkpoint on the PLOG that pertained to the file, indicating a problem with the setup of the job (for example, wrong RAID parameter; wrong PLOG). <p>If a file is excluded from regeneration in a job built by the Adabas Recovery Aid, an internal error is indicated.</p>
Action	Determine the cause of the error and correct the job. If necessary, contact your technical support representative for help restarting the recovery process.
ERROR-147	Invalid value for parameter 'ALLOCATION'
Explanation	Valid values are ALLOCATION={FORCE NOFORCE}.
Action	Supply the correct parameter value and rerun the job.
ERROR-148	Nucleus 'NU' parameter value too small
Explanation	Currently, more than `NU' number of users have open transactions.
Action	Increase the nucleus `NU' value and rerun the job.
ERROR-149	Missing or mismatching RLOGDEV parameter
Explanation	The specified or implied RLOGDEV parameter does not match the RLOG device type stored in the GCBs.

RLOGDEV parameter	= device type
RLOG device type	= device type

The RLOGDEV parameter must be correct so that ADARES COPY/PLCOPY executions can be recorded in the recovery log even if the GCBs have been damaged.

Action Supply the correct parameter value and rerun the job.

ERROR-151 Error occurred during {CLCOPY|PLCOPY|PPT} ENQ

Explanation An error occurred while enqueueing the CLCOPY, PLCOPY, or PPT during the ADARES copy process.

Action Contact your Software AG technical support representative.

ERROR-152 ADARES BACKOUT DPLOG not allowed for a cluster database.

Explanation The ADARES function BACKOUT DPLOG may not be used for an Adabas cluster database. ADARES BACKOUT may be used, but a merged protection log is required as input.

Action Use the PLCOPY function to merge the protection logs and supply the sequential data set.

**ERROR-153 Invalid NUMLOG parameter specified
The value specified was {nn}**

Explanation When manually merging command logs in an Adabas cluster environment, the NUMLOG parameter maximum number is 32.

Action Specify the correct number of cluster command logs to be merged.

ERROR-154 {OPEN | CLOSE} error on {MERGIN1 | MERGIN2} file

Explanation An error occurred while opening or closing the intermediate data set supplied for the protection or command log merge process in an Adabas cluster environment.

Action Contact your Software AG technical support representative.

ERROR-155 Read error on {MERGIN1 | MERGIN2} file. System error={nnnnnnnn}

Explanation An error occurred while reading the intermediate data set supplied for the protection or command log merge process in an Adabas cluster environment.

Action Contact your Software AG technical support representative.

ERROR-156	Write error {MARGIN1 MARGIN2} file. System error={nnnnnnnn}																		
Explanation	An error occurred while writing to the intermediate data set supplied for the protection or command log merge process in an Adabas cluster environment.																		
Action	Contact your Software AG technical support representative.																		
ERROR-157	Incorrect {MARGIN1 MARGIN2} file supplied																		
Explanation	An incorrect intermediate data set was supplied for the protection or command log merge process in an Adabas cluster environment.																		
Action	Contact your Software AG technical support representative.																		
ERROR-158	Inconsistency detected with header flag partial merge indicator is not set correctly																		
Explanation	During the protection or command log merge process in an Adabas cluster environment, an inconsistent indicator was detected for the merge status of a log.																		
Action	Contact your Software AG technical support representative.																		
ERROR-159	Invalid {READ WRITE} container function requested for merge process																		
Explanation	An error occurred when attempting a read or write to the PLOG or CLOG data set.																		
Action	Contact your Software AG technical support representative.																		
ERROR-160	Internal processing error encountered with the merge process - subcode {n}																		
Explanation	An internal protection or command log processing error was detected with one of the following subcodes:																		
	<table border="1"> <tr> <td>1</td> <td>An attempt was made to open a log multiple times.</td> </tr> <tr> <td>2</td> <td>The log I/O table is full.</td> </tr> <tr> <td>3</td> <td>An error occurred reading the PLOGR1 or CLOGR1 data set in the parallel participant table (PPT).</td> </tr> <tr> <td>4</td> <td>An error occurred reading the PLOGR2 or CLOGR2 data set in the parallel participant table (PPT).</td> </tr> <tr> <td>5</td> <td>Neither log was selected for the merge process.</td> </tr> <tr> <td>6</td> <td>An error occurred in the log buffering.</td> </tr> <tr> <td>7</td> <td>The log buffer flag is incorrect.</td> </tr> <tr> <td>8</td> <td>An internal error occurred while processing log records. An attempt was made to read past end-of-file.</td> </tr> <tr> <td>9</td> <td>An internal error occurred while attempting to update the log status at the end of the merge process.</td> </tr> </table>	1	An attempt was made to open a log multiple times.	2	The log I/O table is full.	3	An error occurred reading the PLOGR1 or CLOGR1 data set in the parallel participant table (PPT).	4	An error occurred reading the PLOGR2 or CLOGR2 data set in the parallel participant table (PPT).	5	Neither log was selected for the merge process.	6	An error occurred in the log buffering.	7	The log buffer flag is incorrect.	8	An internal error occurred while processing log records. An attempt was made to read past end-of-file.	9	An internal error occurred while attempting to update the log status at the end of the merge process.
1	An attempt was made to open a log multiple times.																		
2	The log I/O table is full.																		
3	An error occurred reading the PLOGR1 or CLOGR1 data set in the parallel participant table (PPT).																		
4	An error occurred reading the PLOGR2 or CLOGR2 data set in the parallel participant table (PPT).																		
5	Neither log was selected for the merge process.																		
6	An error occurred in the log buffering.																		
7	The log buffer flag is incorrect.																		
8	An internal error occurred while processing log records. An attempt was made to read past end-of-file.																		
9	An internal error occurred while attempting to update the log status at the end of the merge process.																		
Action	Contact your Software AG technical support representative.																		

ERROR-161	Invalid PPT detected
Explanation	An invalid parallel participant table (PPT) was detected in an Adabas cluster environment.
Action	Contact your Software AG technical support representative.
ERROR-162	The PLOG merge process encountered an invalid protection record
Explanation	An error occurred while processing a protection record.
Action	Save the ADARES output and contact your Software AG technical support representative.
ERROR-164	The intermediate data set did not contain as many records as expected
Explanation	The input contains <i>xxx</i> number of records but <i>yyy</i> number of records were expected.
Action	Supply the correct intermediate data sets.
ERROR-165	The JCL supplied for the ADARES PLCOPY NOPPT produced an error
Explanation	ADARES detected that either no DD statements were provided or the DD statement was in error for the PLCOPY NOPPT function.
Action	Correct the JCL and resubmit the job.
ERROR-166	Invalid input was supplied to the MERGE CLOG function
Explanation	One or more of the data sets supplied to the ADARES MERGE CLOG function was in error. The input is expected to be sequential data sets and CLOGLAYOUT=5 must have been used to create the original CLOG.
Action	Correct the input and resubmit the MERGE CLOG job.
ERROR-167	The JCL supplied for the ADARES MERGE CLOG function produced an error
Explanation	ADARES detected that either no DD statements were provided or the DD statement was in error for the MERGE CLOG function.
Action	Correct the JCL and resubmit the job.
ERROR-168	The NUMLOG parameter specified was {xx} but {yy} data sets were supplied
Explanation	The ADARES MERGE CLOG function parameter NUMLOG specified a different number of data sets (xx) from the number that were actually supplied as input to the function (yy).
Action	Change the NUMLOG parameter specification or change the input data sets specified so that the two values (xx and yy) match. Then resubmit the job.

ERROR-169	An empty data set was supplied as input to the MERGE CLOG function
Explanation	ADARES detected an empty input data set.
Action	Remove the data set and adjust the NUMLOG value; or supply a valid data set. Then resubmit the job.
ERROR-170	Parameter SBLKNUM is only allowed if NOPPT
Explanation	The SBLKNUM parameter is only allowed in conjunction with the NOPPT parameter.
ERROR-171	The PPT is required for a PLCOPY from a cluster database. This is not possible because the open of the ASSO failed. Please rerun PLCOPY with NOPPT specified and the PLOG DD-statements supplied in the JCL.
Explanation	<p>Prior to ERROR-171, the following should be seen: "The Associator data set(s) could not be opened. <i>nn - return code explanation.</i>" Processing continues.</p> <p>The open of the ASSO failed. After checking the PLOGs, it was determined that the PLOG to be copied was from a cluster database. Either the ASSO must be restored or the PLCOPY NOPPT function must be executed copy off the PLOGs. All pertinent PLOG DD-statement from the cluster should be supplied as input to the NOPPT function.</p>
ERROR-172	Incorrect PLOGs supplied
Explanation	This error occurs if you attempt to run a regenerate using PLOGs that are not at the Adabas 7.2 or 7.4 level (or later). ADARES cannot use PLOGs from a backlevel version.
Action	<p>If you need to run an ADARES job that spans Adabas versions, the ADACNV utility must be part of the recovery process. Here is an example of the recovery steps:</p> <ol style="list-style-type: none"> 1. Run an ADASAV RESTORE job against the old version database. 2. Start the nucleus of the old version database. 3. Run an ADARES job using ADARES REGENERATE PLOGNUM=<i>old-plognr</i>, where <i>old-plognr</i> is the PLOG number for the old database. 4. Shut down the nucleus of the old version database. 5. Run an ADACNV CONVERT job on the old version database to produce a new version database. 6. Start the nucleus of the new version database. 7. Run an ADARES job using ADARES REGENERATE PLOGNUM=<i>new-plognr</i> , where <i>old-plognr</i> is the PLOG number for the new database.

Warning - Input intermediate data set is invalid

Explanation NOPPT was specified and an invalid intermediate data set was supplied. Some of the protection records may be missing from the merged output.

System Action: Since NOPPT was specified, processing continues and a condition code of 4 is returned.

Warning - The PPT has been cleared

Explanation The parallel participant table (PPT) has been cleared since the last merge. Protection log data may be lost.

System Action: Processing continues under the assumption that the database has been restored.

Action Ensure that clearing the PPT was intended.

The PPT indicates that there are currently no PLOGS to be copied for this database

Explanation There are no PLOGs to be copied.

Action Determine the cause of the error. If necessary, contact your Software AG technical support representative for assistance.

Warning - CLOG is from a cluster database. A normal CLCOPY will run, since the PPT is not accessible. A subsequent CLOG MERGE must be run to merge the CLOG data sets.

Explanation Prior to the warning, the following should be seen: "The Associator data set(s) could not be opened. *nn - return code explanation.*" Processing continues.

The open of the ASSO failed. After checking the CLOGs, it was determined that the CLOG to be copied was from a cluster database. A normal CLCOPY (non-merge) will run. A subsequent CLOG should run to merge the CLOG data sets.

100

ADARPE Utility Messages

ERROR-121	EXTRACT={name}: Value must be set to YES or NO for parameter {parmname}
Explanation	The setting of parameter <i>parmname</i> in extract <i>name</i> is not valid. Valid settings are YES or NO.
Action	Correct the parameter and try again.
ERROR-122	EXTRACT={name}: Parameter IMAGE must be set to BI, AI or BOTH.
Explanation	The value of the IMAGE parameter has been incorrectly specified in extract <i>name</i> .
Action	Correct the parameter and try again.
ERROR-123	EXTRACT={name}: Parameter TRANSACTIONLEVEL must be set to NONE, RECORD, or TRANSACTION.
Explanation	The value of the TRANSACTIONLEVEL parameter has been incorrectly specified in extract <i>name</i> .
Action	Correct the parameter and try again.
ERROR-124	EXTRACT={name}: Parameter MODIFICATIONTYPE must be a selection of INSERT/UPDATE/DELETE/ISTATE/ALL.
Explanation	The value of the MODIFICATIONTYPE parameter has been incorrectly specified in extract <i>name</i> .
Action	Correct the parameter and try again.

ERROR-125	OUTPUTFILE={file} has been specified in EXTRACT={name1}, and EXTRACT={name2}.
Explanation	The OUTPUTFILE parameter for two different extracts refers to the same output file. They must be unique.
Action	Correct the OUTPUTFILE parameter and try again.
ERROR-126	{type} failure on {{outputfile} {outputexit}}={{filename} {exitname}} for EXTRACT={name}, RC={rc}
Explanation	A close, open, write, delete, or load (<i>type</i>) failure occurred for the output or exit file listed in the message. The name of the extract and the return code from processing are also given in the message.
Action	Correct the JCL or parameters and try again.
ERROR-127	{type} failure by User Exit={exitname} for EXTRACT={name}, RC={rc} User Exit error code={errorcode}
Explanation	An initialize, terminate, or processing (<i>type</i>) error occurred for the user exit named in the message. The name of the extract and the return and error codes from processing are also given in the message.
Action	Correct the JCL or parameters and try again.
ERROR-128	When TRANSACTIONLEVEL=TRAN or RECORD is specified, both MERGIN1 and MERGIN2 must be present, and must be the same type of file with the same or a larger record size as the CLOG input file
Explanation	When TRANSACTIONLEVEL parameter is set to "TRAN" or "RECORD", the MERGIN1 and MERGIN2 data sets are required. They must be the same file type and their record sizes must be at least as large (or larger) as the CLOG input file.
Action	Correct the JCL or parameters and try again.
ERROR-129	The combination of PAYLOADDATA=YES, PAYLOADPREFIX=NO, and RECORDPREFIX=YES is invalid.
Explanation	An invalid combination of parameters was specified.
Action	Correct the parameters and try again.
ERROR-130	Failure on writing to PRINT file. Consult Software Support.
Explanation	A failure occurred writing to the PRINT file. Additional messages should be present.
Action	Examine the additional messages and see if you can resolve the problem. If the problem persists, contact your Software AG technical support representative.

ERROR-131	Open failed for file DDCLOG with returned code of {rc}
Explanation	An attempt to open the DDCLOG file failed. The return code of the attempt is given in the message.
Action	Correct the JCL or parameters and try again.
ERROR-132	Invalid parameters supplied
Explanation	The specified parameters are not valid.
Action	Examine the additional message to fully identify the problem. Then correct the JCL or parameters and try again.
ERROR-133	A record that was not a V52 or V8 CLOG record was encountered
Explanation	The input file for the CLOG appears corrupted or incorrect.
Action	Correct the JCL or parameters and try again. If the problem persists, contact your Software AG technical support representative.
ERROR-134	NAME parameter is required for EXTRACT
Explanation	No value was supplied for the NAME parameter (the extract name). A value for this parameter is required in an ADARPE run.
Action	Supply a NAME parameter setting and try again.
ERROR-135	NAME={name} is not unique across EXTRACTs.
Explanation	The name specified for an extract is not unique; the same name was specified for different extracts. Extract names must be unique.
Action	Specify a unique name for the extract and try again.
ERROR-136	Specified destinations are not unique.
Explanation	The same destination was specified more than once. Destinations listed in an individual DESTINATIONS parameter must be unique.
Action	Correct the destination list and try again.
ERROR-137	Specified subscriptions are not unique.
Explanation	The same subscription was specified more than once. Subscriptions listed in an individual SUBSCRIPTIONS parameter must be unique.
Action	Correct the subscription list and try again.

ERROR-138	OUTPUTFILE parameter is required for EXTRACT.
Explanation	No value was supplied for the OUTPUTFILE parameter. A value for this parameter is required in an ADARPE run.
Action	Supply an OUTPUTFILE parameter setting and try again.
ERROR-139	At least one EXTRACT must be specified.
Explanation	No EXTRACT parameter was specified. At least one EXTRACT parameter is required in an ADARPE run.
Action	Supply an EXTRACT parameter and try again.
ERROR-140	Parameters specified require parameter TRANSACTIONLEVEL=RECORD
Explanation	When the EXTRACT parameter is specified TRANSACTIONLEVEL=RECORD must also be specified.
Action	Specify the TRANSACTIONLEVEL=RECORD parameter and try again.
ERROR-141	Parameters specified require parameter TRANSACTIONLEVEL=TRAN
Explanation	When the EXTRACT parameter is specified TRANSACTIONLEVEL=TRAN must also be specified.
Action	Specify the TRANSACTIONLEVEL=TRAN parameter and try again.

101

ADARPL Utility Messages

ERROR-121	Date and time must be reasonable. Time is invalid without a Date. Date must be entered in the form YYYYMMDD. Time must be entered in the form HHMMSSSTH.
Explanation	One or more of the specified date and time fields appear invalid.
Action	Correct the date and time entries and try again.
ERROR-122	FROMDATE/FROMTIME not found.
Explanation	Supplied Protection Log dataset does not contain information within time frame FROMDATE/FROMTIME - TODATE/TOTIME.
Action	Supply a correct Protection Log dataset and rerun the job.
ERROR-123	RPLDSBI must be a string of Y, N or Placeholders in single quotes.
Explanation	The RPLDSBI parameter has been specified incorrectly. The RPLDSBI parameter must be specified in single quotes and one Y or N value must be specified for each file specified for the ADARPL run (for example RPLDSBI='Y,N,N,Y,Y,N,Y').
Action	Correct the RPLDSBI parameter and try again.
ERROR-124	TOTIME, FROMTIME and RESENDTIME require their respective DATE value.
Explanation	A TOTIME, FROMTIME, or RESENDTIME parameter was specified without the corresponding *DATE parameter.
Action	Specify the corresponding TODATE, TOTIME, or RESENDDATE parameter with the appropriate *TIME parameter and try again.

ERROR-125	Invalid RPLTARGETID or RPLTARGETS. The value supplied must be a positive integer less than or equal to 65535.
Explanation	An invalid value was specified for the RPLTARGETID or RPLTARGETS parameters. Valid values for these parameters range from "1" to "65535"; values higher than "65535" are invalid.
Action	Correct the target IDs and try again.
ERROR-126	No. of RPLTARGETS, RPLKEY, and RPLDSBI must be equal to No. of FILES.
Explanation	An incorrect number of values was specified for the RPLTARGETS, RPLKEY, or RPLDSBI parameters. The number of values must match the number of files specified by the FILES parameter for the ADARPL run.
Action	Correct the parameter values and try again.
ERROR-127	RPLTARGETID and RPLTARGETS parameters are mutually exclusive.
Explanation	An attempt was made to specify both the RPLTARGETID and RPLTARGETS parameters in the same ADARPL run. This is invalid.
Action	Specify one or the other parameter and try again.
ERROR-128	Event Replicator Server {id}, no active subscription or destination for file {number}.
Explanation	No active destination or subscription could be found for the file listed in the message on the Event Replicator Server named in the message.
Action	First verify and correct (as necessary) the file number or the Event Replicator Server target ID for the ADARPL run. If they are correct, modify the Replicator system file subscription and destination definitions. Then try the ADARPL run again.
ERROR-129	Database {dbid} not defined to Event Replicator Server {id}.
Explanation	The database with the database ID listed in the message is not defined to the Event Replicator Server listed in the message.
Action	Verify and correct the JCL or input parameters for the ADARPL run. If they are correct, modify the Replicator system file definitions. Then try again.
ERROR-130	Event Replicator Server {id} replication pool overflow.
Explanation	The replication pool for the Event Replicator Server listed in the message has an overflow condition, which is a critical error.
Action	Refer to the Event Replicator Server job's system log for error messages, which may provide possible actions to take.

ERROR-131	RPLKEY and RPLDSBI are only valid with RPLTARGETID or RPLTARGETS.
Explanation	An attempt to specify the RPLKEY or RPLDSBI parameters was made without also specifying either a RPLTARGETID or RPLTARGETS parameter. When specifying the RPLKEY and RPLDSBI parameters, a corresponding RPLTARGETID or RPLTARGETS parameter must be specified.
Action	Correct the input parameters and try again.
ERROR-132	Dates and times must conform to the following general rule: FROMDATE/TIME <= RESENDDATE/TIME <= TODATE/TIME
Explanation	The date and time values specified for the ADARPL run violate one or more of the following rules: <ul style="list-style-type: none">■ FROMDATE and FROMTIME parameter values must specify dates and times earlier than those specified for the RESENDDATE and RESENDTIME parameters■ RESENDDATE and RESENDTIME parameter values must specify dates and times earlier than those specified for the TODATE and TOTIME parameters.
Action	Correct the date and time parameters and rerun the ADARPL job.
ERROR-133	The file number cannot exceed 65535.
Explanation	The file number specified on the FILES parameter was greater than "65535", which is invalid. Valid values for the FILES parameter range from "1" through "65535".
Action	Correct the file number and rerun the job.
ERROR-134	REPLAY is a required input parameter.
Explanation	An attempt to run the ADARPL utility without specifying the REPLAY parameter. You cannot run the ADARPL utility without specifying the REPLAY parameter.
Action	Add the REPLAY parameter and rerun the ADARPL job.
ERROR-135	The Adabas nucleus is currently NOT active.
Explanation	An attempt was made to run the ADARPL utility was made when the Adabas nucleus was not active. The Adabas nucleus must be active to run ADARPL.
Action	Activate the Adabas nucleus and try again.

ERROR-136	A resp 50 has been received during the Adabas open, probable invalid file number specified.
Explanation	An error occurred trying to open one of the file numbers specified for the ADARPL run.
Action	Verify and correct the file numbers specified for the ADARPL run and then rerun the job.
ERROR-137	Invalid block number found. The blocks of the current PLOG are not supplied in the correct order. The block counts must be ascending by 1. Current block count = {count} Protection Log Number = {number} Supply the correct sequence of protection logs and rerun the job.
Explanation	ADARPL has detected an incorrect protection log. The current block count is shown, as well as the protection log number to assist diagnosis.
Action	Verify and check the PLOG data sets specified in the ADARPL job.
ERROR-138	DBID mismatch. DBID on PLOG does not match DBID-parameter Supply the correct PLOG input and rerun the job.
Explanation	ADARPL has detected a DBID mismatch.
Action	Verify and check the PLOG data sets and the DBID parameter specified in the ADARPL job.
ERROR-139	ADARPL replication pool overflow. Increase LRPL parameter and rerun the job.
Explanation	ADARPL has exceeded the replication pool size allocated via the LRPL parameter.
Action	Verify and check the input parameter LRPL specified in the ADARPL job, and increase it, as necessary, for successful job execution.
ERROR-140	Unexpected Event Replicator Server response {rsp}.
Explanation	ADARPL has received a non-zero response code from the Event Replicator Server.
Action	Use the response code in the error message to analyze and correct the problem.

ERROR-141	RPLCLEANUP was issued for this ADARPL token
Explanation	An operator command of RPLCLEANUP was issued and the ADARPL token was removed. Further execution is not possible.
Action	Verify and determine why the RPLCLEANUP operator command was issued.
ERROR-142	Duplicate ADARPL jobs for the same FNR are not allowed
Explanation	ADARPL has detected a concurrent execution of another ADARPL against the same file number on this DBID.
Action	Verify the execution of ADARPL jobs or check that the input parameters to ADARPL are correct.
ERROR-143	Parameter RPLSORT must be set to YES or NO
Explanation	ADARPL has detected that the setting for the RPLSORT parameter is incorrect.
Action	Verify that the input parameter RPLSORT is set to "YES" or "NO".
ERROR-144	RPLTARGETID or RPLTARGETS must be specified if FILES are not specified
Explanation	ADARPL has detected that the parameters RPLTARGETID or RPLTARGETS is required because the FILES parameter is not specified.
Action	Verify and check the input parameters to the ADARPL job for correct information, specifying RPLTARGETID or RPLTARGETS if required.
ERROR-145	Invalid TOKEN or PLOGDBID or ORIGINDBID The value supplied must be a positive integer less than or equal to 65535.
Explanation	ADARPL had detected a TOKEN, PLOGDBID, or ORIGINDBID value which is not a valid number.
Action	Review and change, if necessary, the number listed in the ADARPL parameters. Then run the ADARPL job again.
ERROR-146	RPLTARGETID must be specified if TOKEN is specified
Explanation	ADARPL has detected a TOKEN parameter in the same run in which an RPLTARGETID parameter was not specified. When you specify the TOKEN parameter, you must also specify the RPLTARGETID parameter.
Action	Review and change the ADARPL parameters, as necessary. Then run the ADARPL job again.

ERROR-147	When parameter TOKEN is specified, only the following additional parameters are valid: LRPL, NU, and RPLTARGETID
Explanation	ADARPL has detected a TOKEN parameter in the same run as another ADARPL parameter that is not allowed when the TOKEN parameter is specified. Only the LRPL, NU, and RPLTARGETID parameters can be specified in an ADARPL run using TOKEN.
Action	Review and change the ADARPL parameters, as necessary. Then run the ADARPL job again.
ERROR-148	TOKEN {token} not found in Event Replicator Server
Explanation	There are no replay processes active with the token number listed in the message.
Action	Review and change the ADARPL RPLTARGETID and TOKEN parameters, as necessary. Then run the ADARPL job again.
ERROR-149	TOKEN {token} was not an ADARPL token.
Explanation	The token listed in the message is a valid token number, but is not for a replay process.
Action	Review and change the ADARPL TOKEN parameter, as necessary. Then run the ADARPL job again.
ERROR-150	RPLSORT missing, possibly the Adabas is not connected to the Event Replicator Server
Explanation	ADARPL has detected that the Event Replicator Server does not have information about RPLSORT, which is provided during an initialization handshake between an Adabas database and an Event Replicator Server.
Action	Verify that the Adabas database and the Event Replicator Server have established communication.
ERROR-151	File {number} is not the anchor file in the expanded file chain
Explanation	The file listed in the message is not the anchor file in the Adabas expanded file chain. Only the anchor file can be specified in the FILES parameter.
Action	Specify the file number of the anchor file in the expanded file chain and try again.
ERROR-152	Incomplete transaction found on PLOG
Explanation	A transaction started before the input PLOG data set specified for replay processing and ended after the FROMDATE and FROMTIME replay specifications.
Action	Add the preceding PLOG data set in sequence to the input PLOG data sets for replay processing and try again.

ERROR-153	Incomplete transaction found on PLOG
Explanation	The ET record was not found for a transaction that was to be included in replay processing.
Action	Add the next PLOG data set in sequence to the input PLOG data sets for replay processing and try again.
ERROR-154	File {num} not loaded in database {dbid}
Explanation	An attempt to run the ADARPL utility failed because the file specified for the run does not exist in the specified database. The file number and database ID are given in the message.
Action	Verify that the correct file number is specified and that the file does exist in the database. Then try again.
ERROR-155	Version of ADABAS is not compatible with version of PLOG.
Explanation	The version of PLOG is higher than the version of Adabas used to create the PLOG.
Action	Resolve the discrepancy in Adabas or PLOG versions before you try again.
ERROR-156	The source database Adabas version is not compatible with the Reptor Adabas version
Explanation	The version of Adabas or the Event Replicator used by the Adabas database is not the same as the version of Adabas or Event Replicator used by the Event Replicator Server.
Action	Resolve the discrepancy in Adabas or Event Replicator versions before you try again.
ERROR-157	Either PLOGFILES specified for the master file only, or not all files of expanded file chain specified
Explanation	A file number specified in PLOGFILES parameter is a component of an expanded file chain. At this time, the PLOGFILES parameter cannot specify files in an expanded chain and cannot be specified if any of the files listed in the FILES parameter is for a file in an expanded chain.
Action	Correct the ADARPL parameters and try again.
ERROR-158	The value for STATINTERVAL parameter must be between 60 and 2,147,483,647 sec. or 0.
Explanation	Invalid value specified for STATINTERVAL. Valid values are 0 or an integer in the range from 60 to 2,147,483,647.
Action	Correct the parameter value and try again.

ERROR-159	Replay of spanned DS records is not supported.
Explanation	The ADARPL utility may not be used with a file with spanned DS record support turned on.
Action	Adjust the ADARPL job so that files with spanned Data Storage records are not included in the run.
ERROR-160	ADARPL No more UQE's available. Increase NU parameter and rerun the job.
Explanation	There are no User Queue Elements available. Specify a NU value that is greater than or equal to the maximum number of users that have open transactions simultaneously.
Action	Correct the parameter value and try again.
ERROR-161	Inconsistent transaction found on PLOG
Explanation	The sequence of before and after images is incomplete.
Action	Add the missing PLOGs in correct sequence to the input PLOGs and re-run the job.

102

ADARPP Utility Messages

ERROR-121	Parameter PRINT must be set to DUMP, FORMAT or BOTH
Explanation	An invalid value was specified for the ADARPP PRINT parameter. Valid values are listed in the message.
Action	Correct the value and try again.
ERROR-122	Date and time must be reasonable. Date must be entered in the form YYYYMMDD. Time must be entered in the form HHMMSSSTH.
Explanation	An invalid value was specified for a date or time parameter in an ADARPP run. The date must be later than 1982 and the time value must be less than 24 hours.
Action	Correct the relevant date or time parameter and try again.
ERROR-123	Parameter STATE must be set to YES, or NO.
Explanation	An invalid value was specified for the ADARPP STATE parameter. Valid values are listed in the message.
Action	Correct the value and try again.
ERROR-124	Print level must be in the range 0 to n inclusive for {parameter}
Explanation	The print level specified for the ADARPP parameter identified in the message is invalid.
Action	Review the valid settings for the named print parameter, correct the value, and try again.

ERROR-125	Record number {nnn}: URBLTYPE: {aa} is not supported. Consult Software Support.
Explanation	The record contains an unknown record type value.
Action	Contact your Software AG technical support representative.
ERROR-126	FROMDATE and FROMTIME must be <= to TODATE and TOTIME
Explanation	The date and time specified by the ADARPP FROMDATE or FROMTIME parameters is later than the date and time specified by the TODATE and TOTIME parameters. This is invalid.
Action	Correct the appropriate date or time value and try again.
ERROR-127	Parameter TIMEZONE must be set to MACHINE, LOCAL, or an integer value in the range -23 to +23. When entering + or -, enclose the number in single quotes.
Explanation	An invalid value was specified for the ADARPP TIMEZONE parameter. Valid values are listed in the message.
Action	Correct the value and try again.
ERROR-128	Record number {nnn}: URBLPTYP {nn} is inconsistent with eye-catcher {aaaa}, Consult Software Support.
Explanation	The record contains a data type that is not consistent with the actual data.
Action	Contact your Software AG technical support representative.
ERROR-129	Record number {nnn}: URBLPTYP {nn} is not supported. Consult Software Support.
Explanation	The record contains an unknown data type value.
Action	Contact your Software AG technical support representative.
ERROR-130	Failure on writing to print file. Consult Software Support.
Explanation	An error occurred when a record was being written to the report file.
Action	Contact your Software AG technical support representative.
ERROR-131	Open failed for file DDCLOG with returned code of {nn}.
Explanation	No DDCLOG file was specified in the ADARPP JCL.
Action	Correct the JCL and rerun the job.

ERROR-132	Invalid parameters supplied.
Explanation	At least one parameter value was invalid.
Action	Check all error messages to identify the invalid parameter values, make corrections to the values, and try again.
ERROR-133	{nnnn} CLOG records were read, and {nnnn} records were selected for printing.
Explanation	A summary of the CLOG records read and selected for printing is listed in the message. This is part of the summary report at the end of the print file.
Action	No action is necessary for this informational message.
ERROR-134	PAGESIZE must be 20 or greater
Explanation	An invalid value was specified for the ADARPP PAGESIZE parameter. Valid values must range from 20 or greater.
Action	Correct the value and try again.

103

ADASAV Utility Messages

ERROR-95	DIB disappeared
Explanation	The DIB entry in the Utility Communications Block (UCB) that the utility created at the begin of its processing is no longer present at its end. Another utility may have modified files that were supposed to be locked. The result of this utility execution may be inconsistent.
Action	Determine what happened to the DIB entry. Then rerun the utility to ensure utility execution is consistent for all files. If the problem persists, contact your Software AG technical support representative.
ERROR-121	Wrong protection log tape The wrong Protection Log tape has been mounted. The requested Protection Log has DBID {dbid-a}, Session Number {sess-a}, NUCID {nucid-a}. The supplied Protection Log is from DBID {dbid-ba}, Session Number {sess-b}, NUCID {nucid-b}.
Explanation	The wrong protection log tape has been mounted. The requested protection log has DBID (<i>dbid-a</i>), session number (<i>sess-a</i>). The supplied protection log is from DBID (<i>dbid-b</i>), session number (<i>sess-b</i>). Either there is a mismatch in the information provided or the checkpoint needed was not found on the PLOG provided.
Action	Supply the correct tape and start an ADASAV job using the RESTPLOG function.

ERROR-122	{chkpt}-checkpoint not found
Explanation	<p>One of the following has occurred:</p> <ol style="list-style-type: none"> 1. The SYN1/SYN4 checkpoint is not contained in the protection log block (block-number); or 2. The SYN2/SYN5 checkpoint is not contained anywhere on the protection log; or 3. Another SYN1/SYN4 checkpoint was encountered before the expected SYN2-SYN5 checkpoint. <p>The wrong protection log has been mounted, or the wrong SYN1-SYN4 checkpoint has been specified.</p>
Action	Supply the correct protection log and parameters. For case 1 or 2, continue with the RESTPLOG function. For case 3, repeat the RESTONL function.
ERROR-123	The input tapes of a multivolume save set are mounted in the wrong order. ADASAV is not able to continue
Explanation	The RESTORE function expects the REST _n /DDREST _n data sets to be presented in the order in which they were created.
Action	Ensure that the input tapes are mounted in the correct order; then rerun the job.
ERROR-124	Invalid file list parameter
Explanation	<p>One of the following occurred:</p> <ul style="list-style-type: none"> ■ No file numbers, invalid file numbers, or duplicate file numbers were specified in the FILES, FMOVE, NEWFILES, or EXCLUDE parameter. ■ More file numbers were specified in the NEWFILES parameter than in the FILES or FMOVE parameter. ■ A file specified in the EXCLUDE parameter was not specified in the FILES, FMOVE, or NEWFILES parameter.
Action	Supply the correct parameter value and rerun the job.
ERROR-125	Missing function code
Explanation	Either SAVE or RESTORE is required.
Action	Supply the correct parameter value and rerun the job.

ERROR-126	Only one function at a time allowed
Explanation	Either SAVE or RESTORE is required: not both.
Action	Supply the correct parameter value and rerun the job.
ERROR-127	Invalid value for the parameter DRIVES
Explanation	The value for this parameter must be greater than or equal to 1 and less than or equal to 8. The default value is 1.
Action	Supply the correct parameter value and rerun the job.
ERROR-128	All parts of an expanded file must be restored together. At least the parameter FILE={file-number} is missing
Action	Include all files of this expanded file in the file list, then rerun the ADASAV job.
ERROR-129	Invalid value for the parameter NEWDBID
Explanation	A correct value is in the range 1 to 65,535.
Action	Supply the correct parameter value and rerun the job.
ERROR-130	Invalid value for the parameter PERDRIVE
Explanation	The number of values in the parameter list for PERDRIVE must be equal to the value of the DRIVES parameter.
Action	Supply the correct parameter value and rerun the job.
ERROR-131	Input save tape created {ONLINE OFFLINE}
Explanation	The incorrect type of ADASAV restore function was used for the type of output save tape from the previous ADASAV SAVE operation.
Action	Use the RESTONL function for restoring a tape saved with the nucleus online, and also provide the associated protection log. Use the RESTORE function for restoring a tape saved with the nucleus offline.
ERROR-132	First block on restore tape is not a GCB
Explanation	An invalid input for RESTORE is supplied. The RESTORE input must have been produced by a previous ADASAV SAVE execution.
Action	Supply a correct input and rerun the job.

ERROR-133	Restore tape does not have the correct version
Explanation	For the RESTORE FILES function, the restore tape must have been produced by a version 5.1 or above ADASAV SAVE execution. For the RESTORE (database) or RESTORE GCB function, the restore tape must have been produced by an ADASAV SAVE execution with the same version as is used for the restore.
Action	Supply a correct input and rerun the job.
ERROR-134	Different types for restore
Explanation	The ADASAV restore source and destination device types are different. ADASAV restore functions cannot accept different source and output device types or extents.
Action	Respecify the output to the same device type or extent as the restore function source, and resubmit the job. For more information, see the Adabas Utilities documentation.
ERROR-135	Save tape does not contain a whole database
Explanation	The save data set cannot be restored because: <ul style="list-style-type: none"> ■ The save data set is a file save data set that can be restored only with RESTORE/RESTONL FILE/FMOVE; ■ The save data set is a delta save data set that can be restored only in combination with a full database save data set (using RESTORE DELTA).
System Action:	The RESTORE database or RESTORE GCB function is abnormally terminated.
Action	Provide the right save data set or specify the correct restore function.
ERROR-136	Restore database online not permitted
Explanation	The ADASAV RESTORE Open command received a nucleus response code of (resp-code - explanation). The nucleus is active, which is not allowed during a RESTORE database operation.
Action	Ensure that the correct nucleus has been accessed; if so, shut down the nucleus and then rerun the ADASAV RESTORE job.
ERROR-137	An attempt was made to restore file no. {file-number} into a database with a MAXFILE-value of {count}
Action	Correct either the file number or change the MAXFILE value in the database.

ERROR-138	File {file-number} not found on save tape
Action	Supply a correct input data set containing the specified file, or remove the file number from the parameter list.
ERROR-139	Coupled files must all be restored together. File {file-number-a} is coupled to file {file-number-b}
Action	Include all files coupled together in the file list and rerun the job.
ERROR-140	No files selected for SAVE/RESTORE
Action	Supply a correct file list using the FILE or FMOVE parameter and rerun the job.
ERROR-141	Supplied {value} is smaller than currently used
Action	Supply a larger value for the parameter specified in place of "value" in the message, and rerun the job. Refer to the Adabas Utilities documentation for more information.
ERROR-142	Invalid value for parameter {parameter}
Explanation	One of the followed is the case: <ul style="list-style-type: none">■ An attempt was made to increase MAXISN but the file was defined with NOACEXTENSION; or■ The specified size (in cylinders) is too large.
ERROR-143	Restore database not permitted. Another utility has exclusive control of the database
Explanation	ADASAV RESTORE expects to get a Response Code returned that indicates that the database is down. However, ADASAV RESTORE was returned a sub code indicating that another utility currently has exclusive control of the database.
Action	Ensure the correct nucleus has been accessed; if so, wait for the other utility to run before running the ADASAV RESTORE.
ERROR-144	File number {file-number} is already present and cannot be overwritten
System Action:	This file is removed from the file list. ADASAV will continue.

ERROR-145	An existing database cannot be overwritten
Explanation	The Associator used for output already contains a database.
Action	The OVERWRITE parameter may be used to overwrite an existing database.
ERROR-146	ADASAV not permitted to run
Explanation	One of the following is the case: <ul style="list-style-type: none"> ■ The Adabas nucleus is active but running without a protection log; or ■ A save operation is already active.
Action	Correct the cause of the problem and rerun the job.
ERROR-148	Invalid value for the 'PERDRIVE' parameter
Explanation	The total of all values supplied for this parameter must equal the number of entries in the VOLSER table displayed with this message.
Action	Respecify the PERDRIVE parameter, and rerun the job.
ERROR-150	Nucleus response {resp-code} at the end of the online save operation
Explanation	See Adabas Response Codes for the explanation of nucleus response codes. The proper synchronization of the nucleus protection log (PLOG) and the output of the SAVE run is not possible.
Action	Rerun the ADASAV SAVE job. If the error occurs again, consult your Software AG technical support representative.
ERROR-151	Invalid value for the 'BUFNO' parameter
Explanation	The highest value permitted for BUFNO is 255.
Action	Respecify the BUFNO value, then rerun the ADASAV job.
ERROR-152	Partial overwrite of coupled files
Explanation	The file "file-number-a" is coupled to file "file-number-b", which is not selected for the RESTORE operation (actual file values are displayed in the message text). This RESTORE cannot be serviced because it would result in a logical data inconsistency.
Action	Check the RESTORE function parameter input; correct the error and then rerun the RESTORE job.

ERROR-153	Partial overwrite of expanded file
Explanation	The file "file-number-a" is part of an expanded file. It is linked to the file "file-number-b", which is not selected for the RESTORE operation (actual file values are displayed in the message text). This RESTORE cannot be serviced because it would result in a logical data inconsistency.
Action	Check the RESTORE function parameter input; correct the error and then rerun the RESTORE job.
ERROR-154	The parameter {parm} is not allowed with range of files
Explanation	The parameter named in the message (<i>parm</i>) cannot be specified in the same ADASAV run that specifies a range of files in the FILES or FMOVE parameter.
Action	Remove the parameter and rerun the job.
ERROR-155	Invalid restore operation
Explanation	An attempt was made to: <ul style="list-style-type: none">■ overwrite an Adabas system file with a disparate system file or a non-system file;■ introduce a second system file into a database where the corresponding system file already exists;■ restore a user-defined system file into a database where the GCBs' system file list is full; or■ restore a checkpoint or security file from Adabas version 5.
Action	Correct the file specification and, if appropriate, rerun the ADASAV job.
ERROR-156	Active nucleus required
Explanation	The Adabas nucleus must be active to <ul style="list-style-type: none">■ check the replication log information for the files being saved; or■ clear the replication log for files being restored.
Action	Start the Adabas nucleus, then rerun the ADASAV job.
ERROR-157	Part of the database not physically allocated
Explanation	Some of the blocks to be saved/restored lie within physically unallocated database storage. Probably an ADADBS or Adabas Online System "increase" was run without first providing the associated physical storage.
Action	Allocate the physical storage, then rerun the ADASAV job.

ERROR-158	Incomplete restore tape
Explanation	The "associator\data" RABN "rabn-number" was not found on the restore tape. Either end-of-file (EOF) occurred, or ADASAV found "count" RABN "rabn-number" instead. Either a required tape volume is missing, or the tapes are mounted in the wrong order.
Action	Supply a correct restore tape, then rerun the ADASAV job.
ERROR-159	Inconsistent restore tape
Explanation	The restore tape does not contain the expected data. All records on the tape must contain references to DBID <i>dbid</i> , session number <i>session-id</i> , and time stamp <i>ttt</i> . A record was found that incorrectly referred to DBID <i>dbid-x</i> , session number <i>session-id-x</i> , and time stamp <i>ttt</i> .
Action	Correct the cause of the incorrect reference, then rerun the ADASAV job.
ERROR-160	Inconsistent protection log
Explanation	The Adabas protection log does not contain the expected data. The last record that was read should have contained DBID <i>dbid</i> , serial number <i>number</i> , and time stamp $\geq ttt$. However, it contained instead DBID <i>dbid-x</i> , serial number <i>number-x</i> , and time stamp <i>ttt-x</i> or the protection record lengths are inconsistent.
Action	Check protection record in dump provided and correct the cause of the incorrect reference, then rerun the ADASAV job.
ERROR-161	Error during DSF processing
Explanation	This generic error message is issued after a Delta Save error message. An error occurred while the Delta Save Facility was processing the requested function. The internal response code by Delta Save is shown.
System Action:	The function is abnormally terminated.
Action	For more information, see the Delta Save error message preceding this message.
ERROR-162	Parameter/function {function} not allowed without DSF
Explanation	The designated parameter or function is only available when the Delta Save Facility is installed.
System Action:	ADASAV terminates abnormally.
Action	If Delta Save is installed, specify ADARUN parameter DSF=YES and rerun the job.

ERROR-163	DSF logging area is installed
Explanation	The database has a Delta Save logging (DLOG) area installed, but ADASAV was not started with the Delta Save Facility.
System Action:	ADASAV terminates abnormally.
Action	Specify ADARUN parameter DSF=YES and rerun the job.
ERROR-164	DRIVES > 1 not allowed for delta merge
Explanation	There is no full save input to the MERGE function, so the output save data set will be a delta save or an unloaded DSIM data set. The DRIVES parameter is allowed only when a full save data set is merged.
System Action:	The merge function terminates abnormally.
Action	Remove the DRIVES parameter and rerun the job.
ERROR-165	Incomplete input for merging ASSO/DATA RABN {num} was not found on the input tapes; end-of-file occurred instead
Explanation	The save data set input for the merge function is incomplete. End-of-file was encountered when Associator or Data Storage RABN "num" was expected. Possibly a required tape volume is missing or input tape volumes have been concatenated so that an end-of-file mark was encountered before the last tape.
System Action:	The merge function terminates abnormally.
Action	Supply complete input data sets and rerun the job.
ERROR-165	Incomplete input for merging ASSO/DATA RABN {num1} was not found on the input tapes; ADASAV found ASSO/DATA RABN {num2} instead.
Explanation	The save data set input for the merge function is incomplete. Associator or Data Storage RABN "num2" was found when RABN "num1" was expected. Possibly a required tape volume is missing or input tapes are mounted in the wrong order.
System Action:	The merge function terminates abnormally.
Action	Supply complete input data sets and rerun the job.
ERROR-166	Conflicting parameters for restore delta
Explanation	The combination of parameters and input save data sets is invalid: <ul style="list-style-type: none"> ■ DRIVES>1 is not allowed for RESTORE GCB, RESTORE FILE, or RESTORE FMOVE with DELTA; ■ Concatenation of delta save input data sets is not allowed for RESTORE GCB, RESTORE FILE, or RESTORE FMOVE with DELTA.
System Action:	The RESTORE DELTA function terminates abnormally.
Action	Correct the arrangement of input save data sets and rerun the job.

ERROR-167 **Restore delta without full save not possible**

Explanation The full save tape was omitted the restore operation but the current status of the database does not allow this. One of the following was detected:

- The function is not RESTORE database.
- The Associator failed to open. The full save data set probably had not been successfully restored in a previous run. An ADAIOR error text is given.
- No Delta Save logging (DLOG) area is installed in the database.
- Delta Save logging is not enabled; that makes this operation invalid.
- The database has been modified since the last restore operation: the Adabas nucleus has been active, the DLOG area is not empty.
- The database has been modified since the last restore operation: a utility has changed the file indicated in the message.
- The database has been modified since the last restore operation: the DLOG header block was altered.
- A file excluded from the previous restore must now also be excluded but has not been.
- A file specified as excluded was not excluded from the previous restore.

System Action: The delta restore function terminates abnormally.

Action Provide the full save data set for the delta restore operation and rerun the job.

ERROR-168 **GCB extents changed between delta saves**

Explanation The database layout was changed by an ADADBS ADD, INCREASE, or DECREASE function (or by the equivalent Adabas Online System function). Later on, a delta save data set was produced that is now input to the restore function. ADASAV is not able to handle the changed GCBs in the second phase of the delta restore process.

System Action: The changed GCBs are written to the database. Then the delta restore function terminates abnormally.

Action There are two possible ways to correct this problem:

- Merge all input save data sets and restore the resulting merged full save data set; or
- Rerun the delta restore function without the full save data set, starting with the first delta save data set not yet restored; doing this causes ADASAV to bypass the earlier, old image of the GCBs.

ERROR-169 Incompatible RABN sizes
Explanation An attempt was made to restore one or more files from a database with "x"-byte RABNs into a database with "y"-byte RABNs.
System Action: The requested function cannot be performed.

ERROR-170 Maximum record length too big for this database
Explanation The maximum compressed record length defined for file "file-number" is too big to be compatible with the Work block size.

Maximum record length	= length
Work block size required	block-size
Work block size present	= block-size

The file can be restored only into a database with a larger Work block size.
Action Use the ADADEF NEWWORK function to define a new Work data set with a larger block size so that you can restore the file.

ERROR-171 Conflicting address converter device types for file {file-number}
Explanation The secondary address converter extent allocated by the nucleus during an online save could not be restored to the current address converter due to conflicting device types.
Action Remove the MAXISN parameter for this file and rerun the RESTONL FMOVE function.

ERROR-172 NEWFILES parameter not allowed for file {file-number}
Explanation The NEWFILES parameter must not be specified for expanded files or physically coupled files.
Action Remove the corresponding file number assignment from the NEWFILES list and rerun ADASAV.

ERROR-173 Incomplete file list for online save files
Explanation For an online SAVE FILE operation or a SAVE FILE with UTYPE=EXU, all component files of an expanded file chain and all files that are coupled must be specified explicitly in the FILES parameter (see the ADAU15 message(s) above this error message).
Action Correct the FILES parameter and rerun the job.

ERROR-174	File not eligible for RESTPLOG function file {file-number} is not in restore status
Explanation	The specified file was not being restored in a RESTONL operation that was interrupted and thus may not be selected for the RESTPLOG function.
Action	Correct the RESTPLOG parameter input and rerun the job.
ERROR-175	Invalid value for parameter 'ALLOCATION'
Explanation	Valid values are ALLOCATION=FORCE NOFORCE.
Action	Supply the correct parameter value and rerun the job.
ERROR-179	ADASAV DIB entry lost
Explanation	The DIB entry that ADASAV wrote at the beginning of the SAVE operation was no longer present at the end. It may have been removed by a nucleus that was incorrectly started with parameter IGNDIB=YES. A parallel nucleus or utility may have updated the database while ADASAV was running. The save data set may be inconsistent.
Action	Investigate the cause of the error. Correct it and rerun the job. Do not use the save data set.
ERROR-180	A Reptor database may only contain the files CHECKPOINT, SECURITY, REPLICATOR, and SLOG
Explanation	A database defined as an Event Replicator Server (created with REPTOR=YES) must not contain user files or system files not related to replication.
Action	Do not attempt to restore files other than CHECKPOINT, SECURITY, REPLICATOR, or SLOG on Event Replicator Servers. Correct the parameters and rerun the job.
ERROR-181	The database is active but the utility communications block (DIB) is missing the nucleus entry
Explanation	The ADASAV utility determined the nucleus was active without a DIB entry.
Action	Check the job to ensure the correct ASSO, DATA, and WORK data sets are specified for the given DBID.
ERROR-182	RPLTARGETID/DSBI/KEY/ACTIVE/RPLDATA only allowed when matching file provided
Explanation	One or more of the parameters listed in the message were specified in the ADASAV run without a corresponding FILES or FMOVE parameter.
Action	Supply the correct parameter and rerun the job.

ERROR-184	RPLDSBI {value} for file {fnr} must be YES, NO, or empty
Explanation	The value of the RPLDSBI parameter (<i>value</i>) for the file listed in the message (<i>fnr</i>) is incorrect. It must be YES, NO, or empty.
Action	Supply the correct parameter value and rerun the job.
ERROR-185	{parameter-name}={parameter-value} for file {fnr} must be empty when RPLTARGETID is OFF or 0
Explanation	The values of parameters RPLACTIVE, RPLDATA, RPLDSBI, or RPLKEY must not be specified because the file is not replicated (RPLTARGETID is OFF or 0). The specified parameter (<i>parameter-name</i>), its value (<i>parameter-value</i>), and the file number (<i>fnr</i>) of the ADASAV run are given in the message.
ERROR-186	RPLKEY {parameter-value} for file {fnr} must be a 2 character descriptor name, or OFF, or empty
Explanation	The value of the RPLKEY parameter (<i>parameter-value</i>) for the file (<i>fnr</i>) is invalid. It must be either a two-character field name, OFF, or empty.
Action	Correct the parameter value and rerun the job.
ERROR-188	RPLACTIVE {parameter-value} for file {fnr} must be YES, NO, or empty
Explanation	The value of the RPLACTIVE parameter (<i>parameter-value</i>) for the file (<i>fnr</i>) is invalid. It must be either YES, NO, or empty.
Action	Correct the parameter value and rerun the job.
ERROR-189	RPLDATA {parameter-value} for file {fnr} must be YES, NO, CREATE, or empty
Explanation	The value of the RPLDATA parameter (<i>parameter-value</i>) for the file (<i>fnr</i>) is invalid. It must be either YES, NO, CREATE, or empty.
Action	Correct the parameter value and rerun the job.
ERROR-190	{parameter-name} not allowed when REPLICATION=NO in the target database for the restore
Explanation	Parameters RPLACTIVE, RPLDATA, RPLDSBI, and RPLKEY are not allowed if the target database for the restore is not replicated.
Action	Correct the parameter values and rerun the job.

ERROR-191	RPLTARGETID/DSBI/KEY/ACTIVE/RPLDATA only allowed for RESTORE/RESTONL FILES/FMOVE
Explanation	Parameters RPLTARGETID, RPLACTIVE, RPLDATA, RPLDSBI and RPLKEY are not allowed for ADASAV functions other than RESTORE/RESTONL FILES, FMOVE, and GCB (with the FILES parameter).
Action	Correct the parameter values and rerun the job.
ERROR-192	ERROR LOADING MODULE ADARPV: {reason}
Explanation	ADASAV was unable to load modules ADARPV for the reason listed in the message. ADASAV calls ADARPV when the RPLLOAD parameter is set to YES or FILE.
Action	Investigate the cause of the error, correct it, and rerun the job.
ERROR-901	Unexpected Event Replicator Server response {rc}, subcode {sc}, location {loc}
Explanation	An ADASAV communication to the Event Replicator Server has failed with the response (<i>rc</i>) and subcodes (<i>sc</i>) listed in the message. The location (<i>loc</i>) is also listed in the message.
Action	Verify and correct (if necessary) the ADASAV parameters and JCL. Refer to the response code descriptions for information about the response code and subcode. If necessary, contact your Software AG support representative for assistance.
ERROR-902	Duplicate Replication jobs for the same file are not allowed
Explanation	Multiple replication jobs cannot run concurrently for the same file.
Action	Verify and correct (if necessary) the replication job parameters to ensure the correct information is provided for replication. If problems persist, contact your Software AG support representative for assistance.
ERROR-903	RPLCLEANUP was issued for this ADASAV token
Explanation	An RPLCLEANUP was issued for the Event Replicator Server. This removed the ADASAV token and communication to the Event Replicator Server is no longer possible for this job.
Action	Determine why the operator RPLCLEANUP command was issued. Prepare for file recovery as necessary before rerunning ADASAV.
ERROR-904	Event Replicator Server {id} replication pool overflow
Explanation	The replication pool for the Event Replicator Server listed in the message (<i>id</i>) has an overflow condition, which is a critical error.
Action	Refer to the Event Replicator Server job's system log for error messages which may provide possible actions to take to resolve this problem.

ERROR-905	Database {dbid} not defined to Event Replicator Server {id}
Explanation	The Adabas database with the database ID (<i>dbid</i>) listed in the message is not defined to the Event Replicator Server (<i>id</i>) listed in the message.
Action	Verify and correct the JCL or input parameters for the ADASAV run. If they are correct, modify the Replicator system file definitions. Then try the ADASAV run again.
ERROR-906	Event Replicator Server {id}, no active subscription or destination for file {number}
Explanation	No active destination or subscription could be found for the file listed in the message (<i>number</i>) on the Event Replicator Server (<i>id</i>) named in the message.
Action	First verify and correct (as necessary) the file number or the Event Replicator Server target ID for the ADASAV run. If they are correct, modify the Replicator system file subscription and destination definitions to ensure a definition exists for the file. Then try the ADASAV run again.
ERROR-908	The versions of ADASAV and ADARPV are incompatible
Explanation	The versions of ADASAV and ADARPV are internally incorrect.
Action	Verify and correct (if necessary) the JCL allocation of libraries and input parameter to ADASAV. If problems persist, contact your Software AG support representative for assistance.
ERROR-909	Internal error in ADARPV+{offset}
	Register contents at time of error:
	R0-R3 {#####} {#####} {#####} {#####}
	R4-R7 {#####} {#####} {#####} {#####}
	R8-R11 {#####} {#####} {#####} {#####}
	R12-R15 {#####} {#####} {#####} {#####}
Explanation	ADARPV has failed with an internal error at the <i>offset</i> given in the message.
Action	Contact your Software AG support representative for assistance, and provide details of the failure.
ERROR-910	ADARPV cannot load program ADAMGT
Explanation	Program ADARPV cannot load program ADAMGT.
Action	Verify and correct (if necessary) the JCL allocation of libraries and input parameters to ADASAV. If problems persist, contact your Software AG support representative for assistance.

- ERROR-911** **ADAMSG is incompatible with ADARPV**
- Explanation** Program ADARPV has detected an invalid version of program ADAMSG.
- Action** Verify and correct (if necessary) the JCL allocation of libraries and input parameters to ADASAV. If problems persist, contact your Software AG support representative for assistance.
-
- ERROR-912** **The source database Adabas version is not compatible with the Reptor Adabas version**
- Explanation** The version of Adabas or the Event Replicator used by the Adabas database is not the same as the version of the Adabas or Event Replicator used by the Event Replicator Server.
- Action** Resolve the discrepancy in the Adabas and Event Replicator Server Adabas versions before you try again.
-
- ERROR-913** **ADASAV does not support replication of spanned DS records**
- Explanation** You cannot run the ADASAV RESTORE utility with the RPLDATA parameter on files that include spanned Data Storage records.
- Action** Adjust the ADASAV RESTORE job so that files with spanned Data Storage records are not included in the run.

104

ADASEL Utility Messages

SEL001	Unexpected end-of-file on DDKARTE
Explanation	An end-of-file was reached on the DD/KARTE data set before ADASEL expected to reach an end-of-file. Most likely, the supplied input statements are incomplete.
Action	See the ADASEL syntax description in the Adabas Utilities documentation. Correct the input statements, then rerun the ADASEL job.
SEL002	Syntax - undefined, illegal or incorrect syntax positioning of a parameter or symbol
Explanation	The input string marked by "<----" does not match the ADASEL syntax.
Action	See the ADASEL syntax description in the Adabas Utilities documentation. Correct the input statement syntax, then rerun the ADASEL job.
SEL003	Statement table overflow - increase LST
Explanation	The value specified by the SET GLOBALS parameter, LST, does not define an ADASEL translation table large enough for all the statements that match the SELECT argument.
Action	Specify a SET GLOBALS statement with an LST value larger than the current specified or default value. The SET GLOBALS statement must come before the other ADASEL input statements. See the Adabas Utilities documentation for more information.
SEL004	Syntax - value length exceeds the maximum field definition limit
Explanation	The input string marked by "<----" is longer than 253 bytes.
Action	Correct the string length, then rerun the ADASEL job.

SEL005	Syntax - unexpected or missing quote
Explanation	ADASEL detected an uneven number of apostrophes ('). All alphanumeric and hexadecimal values must be specified in pairs of apostrophes; apostrophes in an alphanumeric string must be doubled (as in `...don' 't forget...')
Action	Ensure that all specified apostrophes are paired, then rerun the ADASEL job.
SEL006	Syntax - a numeric value specified for a binary field must be -2 147 483 648 < VAL < 2 147 483 647
Explanation	A binary value in an ADASEL search criterion must be in the range of a two's complement value that fits within a fullword. The value specified was not recognized to be within this range.
Action	Correct the value specification and rerun the ADASEL job.
SEL007	Syntax - missing trailing blank
Explanation	The ADASEL syntax elements must be embedded in blanks.
Action	See the ADASEL syntax description in the Adabas Utilities documentation. Correct the input statement syntax, then rerun the ADASEL job.
SEL008	Syntax - illegal hex digit or an odd number of hex digits were specified
Explanation	Hexadecimal values must be paired, and be valid characters.
Action	See the ADASEL syntax description in the Adabas Utilities documentation. Correct the input statement syntax, then rerun the ADASEL job.
SEL009	Syntax - numeric value contained more than 29 digits
Explanation	Adabas generally does not allow unpacked decimal values longer than 29 bytes.
Action	Supply a correct numeric value of 29 or fewer packed characters, then rerun the ADASEL job.
SEL010	Syntax - illegal numeric value
Explanation	The specified numeric value for the ADASEL criterion is invalid.
Action	Check the criterion specification, and then rerun the ADASEL job.

SEL011	Value table overflow - increase NV
Explanation	The ADASEL table allocated for evaluating field values is not large enough.
Action	Specify a larger table value by using the SET GLOBALS statement parameter, NV. The SET GLOBALS statement must come before the other ADASEL input statements. See the Adabas Utilities documentation for more information.
SEL012	Internal logic failure - contact your local Adabas support representative
Explanation	An internal error occurred while ADASEL was checking the input statement syntax.
Action	Record and/or save all output from the job, your input statements and any dump, then contact Software AG technical support for additional instructions.
SEL013	Invalid file number. File number must be 0<FNR<=MAXFILES (as specified for the database)
Explanation	The specified file number(s) for FILE must be greater than zero and equal to or less than the value last specified by the MAXFILES parameter in the ADADEF DEFINE utility.
Action	Ensure that the defined file(s) are correct according to MAXFILE, that the specified files actually exist and that no files have been deleted.
SEL014	File table overflow - increase NF
Explanation	The allowed number of files for ADASEL processing was exceeded.
Action	Specify a larger file table value by using the SET GLOBALS statement parameter NF. The SET GLOBALS statement must come before the other ADASEL input statements. See the Adabas Utilities documentation for more information.
SEL015	No FDT read due to absent or inaccurate ASSO data set or because the file is not loaded
Explanation	One or more of the specified files is not available for ADASEL processing. The unavailable file(s) are either locked by the Adabas nucleus, or have not been loaded into the database.
Action	Either correct the ADASEL FILE specification to remove the files in question, or resubmit the job later when the files are available.
SEL016	Syntax - invalid DATE/TIME value specified
Explanation	The "starting from" and "ending at" date/time specification was incorrect. The format may be any one of the following:
	<pre> yyyyymmdd/hhmmss J(yyyyddd hhmmss) X'xxxx xxxx'</pre>

Action	Correct the date/time specification and rerun the ADASEL job.
SEL017	Syntax - password/cipher value length exceeds 8 characters or digits
Explanation	The password/cipher specified for the ADASEL run had an incorrect length.
Action	Correct the password/cipher value and rerun the ADASEL job.
SEL018	Syntax - undefined or illegal field name
Explanation	The specified ADASEL fieldname is incorrect, or does not exist.
Action	Specify a correct fieldname, then rerun the ADASEL job.
SEL019	Syntax - field name specified is not an elementary ({name}) a group or PE ({periodic}) - group name is not permitted
Explanation	A field was specified for ADASEL that is not an elementary field, or the index value for a periodic group field was forgotten. Multiple-value and periodic group names, super-, sub-, hyper- or phonetic descriptor fields are not allowed.
Action	Respecify the field correctly, then rerun the ADASEL job.
SEL020	Syntax - invalid periodic index specified (must be 0 < PE <= 191)
Explanation	A periodic group field was specified for ADASEL with an incorrect or invalid index value.
Action	Specify the correct index value and rerun the ADASEL job.
SEL021	Syntax - illegal hyphen specified in an index
Explanation	A periodic group's field or multiple-value field's occurrence contained an illegal hyphen in the index portion of the specification.
Action	Correct the specification and rerun the ADASEL job.
SEL022	Syntax - an index is specified for a non1-indexable field name; i.e., not an MU- or PE-field
Explanation	An index value or range was specified for a field that is neither in a periodic group nor an occurrence in an multiple-value field.
Action	Remove the index value from the field specification, or correct the field name to show a periodic group or multiple-value field.

SEL023	Syntax - missing or illegal MU-index
Explanation	A multiple-value field was specified for ADASEL with an incorrect or missing index value.
Action	Specify the correct index value and rerun the ADASEL job.
SEL024	Syntax - 'FROM' index value is > 'TO' index value
Explanation	The "FROM" index specification for a multiple-value (MU) or periodic group (PE) field for the ADASEL job is greater than the "TO" index specification.
Action	Specify correct index value(s) and rerun the job.
SEL025	Syntax - fields defined with a format of float are not permitted to be specified
Explanation	A field was defined for ADASEL that is in floating-point format. Floating point fields cannot be specified in an ADASEL search argument.
Action	Respecify the ADASEL search argument using non-floating-point field name(s).
SEL026	Syntax - missing quote(s) for an alphanumeric value
Explanation	An alphanumeric value was specified without being enclosed in apostrophes ([X]'...').
Action	Correct the value specification and rerun the ADASEL job.
SEL027	Internal logic failure - contact your local Adabas support representative
Explanation	An internal logic error occurred during ADASEL processing.
Action	Record and save all output from the job, your input statements, and any dump. Then contact your Software AG technical support representative for assistance.
SEL029	Syntax - illegal FROM/THRU/BUT NOT value specified; i.e., EQUAL > THRU or BUT NOT > THRU, etc
Explanation	An incorrect ADASEL criterion value range was specified.
Action	Correct the EQUAL ..., THRU ...(through ...), and/or BUT NOT... values and rerun the ADASEL job.
SEL030	Syntax - value length exceeds the fixed length defined for this field
Explanation	The field selected by the ADASEL criterion is defined with the fixed-length (FI) option, but the value specified for the field is longer than allowed by the field's FDT definition.
Action	Correct the value size and rerun the ADASEL job.

SEL031	Syntax - maximum number of IF - levels exceeded. Increase NIF
Explanation	The number of "nested" IF levels in the ADASEL IF/THEN [ELSE] statement is more than allowed. The number of IF... levels is controlled by the ADASEL SET GLOBALS/NIF parameter.
Action	Specify a larger IF... count by using the SET GLOBALS statement parameter NIF. The SET GLOBALS statement must come before the other ADASEL input statements. See the Adabas Utilities documentation for more information.
SEL032	Syntax - Unmatched IF/ELSE statements
Explanation	ADASEL detected an IF... without an ELSE..., or vice versa. IF... and ELSE... conditional parameters must occur in pairs.
Action	Correct the ADASEL IF/ELSE syntax to create paired conditional parameters, and rerun the job.
SEL033	Syntax - Unmatched DO/DOEND statements
Explanation	ADASEL detected a DO... statement without a matching DOEND..., or vice versa.
Action	Correct the ADASEL DO...DOEND syntax to create DO...DOEND pairs, and rerun the job.
SEL034	Syntax - DDEXPA data set number specified - must be 1 - 20 inclusive
Explanation	The ADASEL output data set(s) DD/EXPAn was either not numbered or incorrectly numbered. There must be at least one output data set (DD/EXPA1), up to a maximum of twenty, numbered in adjoining ascending order (DD/EXPA1, DDEXPA2, ... DD/EXPA20).
Action	Correct the DD/EXPAn job control statement(s), and rerun the ADASEL job.
SEL035	Syntax - The year specified in the date must be 1980 or later
Explanation	The "yyyy" portion of the date specified by the ADASEL input statement must be "1980" or later.
Action	Correct the date and rerun the ADASEL job.
SEL036	Field description table overflow - increase NV
Explanation	The table for field evaluations in ADASEL is too small. Each "evaluation" of a field requires one table entry-regardless of whether only one field is evaluated many times or many fields, one time each.
Action	Specify a larger field evaluation table value by using the SET GLOBALS statement parameter, NV. The SET GLOBALS statement must come before the other ADASEL input statements. See the Adabas Utilities documentation for more information.

SEL037	An undefined ASSO device type was specified. Check the ADARUN DEVICE parameter
Explanation	A DD/ASSORn job control statement for the ADASEL job specified an incorrect or undefined Associator device type. The default device type is the type specified by the ADARUN DEVICE parameter, but other device types may have been specified for the Associator. The ADAREP utility report or Adabas Online System "Database Report" function shows the devices in use for the Associator.
Action	Correct the DD/ASSORn job control statement, and rerun the ADASEL job.
SEL038	Invalid TYPE value specified, must be AI/BI/ALL
Explanation	The ADASEL "SELECT..." specification is incorrect. The choices are before image (BI), after image (AI), or ALL.
Action	Correct the SELECT specification, then rerun the ADASEL job.
SEL039	Invalid file number specified
Explanation	The ADASEL FILE... specification specified an invalid file number. There is no FDT for a file with the specified number.
Action	Correct the SELECT specification, then rerun the ADASEL job.
SEL040	Invalid or illegal FROM/THRU ISN values specified
Explanation	An ADASEL criterion specified invalid EQUAL... and/or THRU (through)... ISN values.
Action	Correct the SELECT specification, then rerun the ADASEL job.
SEL041	I/O error on DDKARTE
Explanation	An input/output error occurred while ADASEL was reading the DD/KARTE input statements.
Action	Record and/or save all output from the job, your input statements and any dump, then contact Software AG technical support for additional instructions.
SEL043	Table overflow - too many values specified
Explanation	ADASEL encountered a record that could not be decompressed.
Action	Record and/or save all output from the job, your input statements and any dump, then contact Software AG technical support for additional instructions.

SEL044	Syntax - invalid or illegal GLOBAL parameter
Explanation	ADASEL detected an invalid SET GLOBALS statement value. The SET GLOBALS statement, which should come before the ADASEL parameters themselves, overrides default values for the ADASEL parameters.
Action	Correct the SET GLOBALS statement in the ADASEL DD/KARTE job control segment, and rerun the ADASEL job. See the Adabas Utilities documentation for more information.
SEL045	Unable to obtain sufficient memory for processing - rerun in a larger partition or address space
Explanation	The ADASEL job could not be run in the existing space.
Action	Allocate more space for this nucleus, then rerun the ADASEL job.
SEL046	Unable to process Data Storage record due to an invalid MU/PE - count or field length or header
Explanation	ADASEL detected an incorrect multiple-value field count or periodic group occurrence or a field value was specified that is incompatible with the defined field's actual length or an incorrect record's header. ADASEL could not continue processing.
Action	Correct the incompatibility, then rerun the ADASEL job.
SEL047	PE-value table overflow - increase LPV
Explanation	The table for evaluating periodic-group (PE) fields in ADASEL is too small. ADASEL normally computes this size automatically; however, there may have been more occurrences matching the search criterion than normal.
Action	Specify a larger PE field evaluation table value by using the SET GLOBALS statement parameter, LPV. The SET GLOBALS statement must come before the other ADASEL input statements. See the Adabas Utilities documentation for more information.
SEL048	DDKARTE open failed
Explanation	ADASEL was unable to open the DD/KARTE input statement data set.
Action	Ensure that the DD/KARTE statement is valid and specifies an available ADASEL job setup. Then rerun the ADASEL job.
SEL049	I/O error on DDRUCK
Explanation	The DD/DRUCK job control statement, which specifies the print output data set for ADASEL, is either incorrect or specifies an unavailable data set or device.
Action	Correct the problem and rerun the ADASEL job.

SEL050	Error during opening/closing of output file DDEXPA				
Explanation	ADASEL was unable to open/close the data set defined in JCL statement DD/EXPA.				
Action	Ensure that the DD/EXPA statement is valid and specifies an available data set. Then rerun the ADASEL job.				
SEL051	Syntax - IF statement not permitted within a DO-group				
Explanation	An ADASEL IF... statement cannot be within a DO...DOEND stream.				
Action	Move the IF... statement outside the DO...DOEND stream, or delete one of them. Then rerun the ADASEL job.				
SEL052	Syntax - GLOBAL parameter exceeds the MINIMUM/MAXIMUM values				
Explanation	ADASEL detected an invalid SET GLOBALS parameter value. The value is most likely outside the range allowed for the parameter. The following are some SET GLOBAL parameters and their allowed ranges:				
	<table border="1"> <tr> <td>LS:</td> <td>1-132</td> </tr> <tr> <td>PS:</td> <td>2-999</td> </tr> </table>	LS:	1-132	PS:	2-999
LS:	1-132				
PS:	2-999				
Action	Correct the SET GLOBALS statement in the ADASEL DD/KARTE job control segment, and rerun the ADASEL job. See the Adabas Utilities documentation for more information.				
SEL053	I/O error encountered on DDSIIN				
Explanation	The DD/SIIN job control statement, which specifies the sequential input (SIBA) log data set for ADASEL, is either incorrect or specifies an unavailable data set or device. Another possible cause is that the DD/SIIN data set is not the sequential output file from an ADARES COPY/PLCOPY operation, as required by ADASEL.				
Action	Correct the problem and rerun the ADASEL job.				
SEL054	I/O error encountered on DDEXPA				
Explanation	The DD/EXPA job control statement, which specifies the print output data set for ADASEL, is either incorrect or specifies an unavailable data set or device.				
Action	Correct the problem and rerun the ADASEL job.				

SEL055	Warning: Skipping decompressed record File={fn} ISN={isn} LRECL for DDEXPAnn should be = nnnnn or more
Explanation	While decompressing a PLOG data set, ADASEL detected a record that was successfully decompressed but that cannot be written to the output file because it does not fit into the DDEXPA nn output buffer and parameter SPANREC was not specified in the OUTPUT statement of the ADASEL job. ADASEL skips the indicated record and continues processing.
Action	The length of the given decompressed PLOG record (including headers) does not exceed the allowable maximum for VB format records, so you can either increase the LRECL value for DDEXPA nn as recommended in the message (NNNNN or more) or specify the SPANREC parameter in the ADASEL OUTPUT statement. Then rerun the ADASEL job.
SEL056	Warning: Skipping decompressed record File={fn} ISN={isn} Decompressed length={length} Use parameter "SPANREC" of OUTPUT statement for DDEXPAnn
Explanation	While decompressing a PLOG data set, ADASEL detected a record that was successfully decompressed but that cannot be written to the output file because it does not fit into the DDEXPA nn output buffer and parameter SPANREC was not specified in the OUTPUT statement of the ADASEL job. ADASEL skips the indicated record and continues processing.
Action	The length of the given decompressed PLOG record (including headers) exceeds the allowable maximum for VB format records, so this record can be written to the output file only in parts. To do this, specify the SPANREC parameter in the ADASEL OUTPUT statement and rerun the job.
SEL057	ADASEL DECOMPRESS error - processing aborted
Explanation	While decompressing a file, ADASEL detected a record that it could not decompress.
Action	Record and/or save all output from the job, your input statements and any dump, then contact Software AG technical support for additional instructions.
SEL058	File is ciphered and cannot be audited
Explanation	ADASEL cannot be run on ciphered files.
Action	Change the file specification to exclude all ciphered files, then rerun the ADASEL job.

SEL059 **Syntax - CHANGES option not permitted with selection of new or deleted records**
Explanation The CHANGES option requires both a before (BI) and after (AI) image for comparison following an update (A1/4) command. Either the BI or AI image was not available.
Action Remove the CHANGES parameter from the ADASEL syntax.

SEL060 **Change pool is too small - increase NCFLD or NCUPD and rerun**
Explanation The default values of 10 (the count of "field-name" CHANGES... statements) for the NCFLD and NCUPD SET GLOBALS parameters of the ADASEL job are not large enough. These two counts are multiplied to determine the correct value.
Action Increase one or both of the NCFLD and NCUPD parameters in the SET GLOBALS statement of the ADASEL DD/KARTE job, and rerun the ADASEL job. See the Adabas Utilities documentation for more information.

SEL061 **Syntax - PE/MU index incorrectly specified for CHANGES option**
Explanation The IF "field-name" CHANGES... conditional statement of an ADASEL job specified a multiple-value (MU) field value or periodic group (PE) occurrence index value that does not exist, or that has no before (BI) and after (AI) image. The field value or group occurrence may have been added or deleted, eliminating one of the required images.
Action The IF...CHANGES... conditional statement cannot be specified in this case. Redefine the ADASEL statement.

SEL062 **Warning: Skipping decompressed record. ADADEC RC={rc} {text}**
File={fn} ISN={isn} Field={fld} [PE-index={pe}]
Explanation While decompressing a PLOG data set, ADASEL detected a record that it could not decompress. ADASEL skips the indicated record and continues processing. The reason-code (*rc*) and the line of explanatory text (*text*) provide you with more specific information about the error:

Code	Description
4	A conversion error occurred during decompression. The explanatory text (<i>text</i>) in the message can be one of the following: <ul style="list-style-type: none"> ■ Truncation not possible ■ Conversion error ■ LOB error ■ Null value with NC option
8	The record is too long for the decompression buffer in main storage. The explanatory text (<i>text</i>) in the message can be one of the following: <ul style="list-style-type: none"> ■ Input record too long

Note: The PE-index part of the message text is only printed if the related field is an MU or PE field.

Action If necessary, record and save all output from the job, your input statements and any dump. Then contact your Software AG technical support representative for assistance.

SEL063 Utility cannot run with this version

Explanation The version indicator returned by the accessed database does not match the version of the active utility.

Action Correct the database referenced in the ADASEL job and rerun the job.

SEL065 Syntax - COUNT only valid for MU or PE field

Explanation The COUNT option of the DISPLAY instruction can only specify an MU or PE field.

Action Correct the COUNT option to specify an MU or PE field or remove the COUNT option and rerun the job.

SEL066 Syntax - DISPLAY BEFORE/BOTH must be preceded by "IF ... CHANGES"

Explanation The BEFORE and BOTH options of the DISPLAY instruction can only be specified within IF statements that contain one or more CHANGES criteria.

Action Correct the DISPLAY instruction syntax and rerun the job.

SEL067 SELECT FROM FILE not allowed with SELECT FROM USER

Explanation You cannot specify a SELECT FROM FILE parameter in the same ADASEL job as a SELECT FROM USER parameter.

Action Correct the ADASEL syntax and rerun the job.

SEL068 User table overflow -- Increase NU

Explanation The user table allocation was not large enough.

Action Increase the ADASEL NU global parameter setting (its default is 20) and rerun the job.

SEL069 Syntax - Field names not allowed with SELECT FROM USER

Explanation References to field names were found in a SELECT FROM USER parameter. In a SELECT FROM USER parameter, no field names can be specified in any associated value criteria or in DISPLAY instructions.

Action Correct the ADASEL syntax and rerun the job.

SEL075	Error encountered during CHANGE element processing
Explanation	An internal error occurred in CHANGE ELEMENT processing.
Action	Record or save all output from the job, your input statements, and any dumps. Then contact your Software AG support representative for assistance.
SEL076	Warning DDEBAND defined, ignored
Explanation	The FDTINPUT parameter was not specified for an ADASEL run, but the DDEBAND job statement was defined in the JCL for the run. The job statement is ignored.
Action	No action is required for this informational message unless you intended to pull the FDT from DDEBAND. If this is the case, specify the FDTINPUT parameter and rerun the ADASEL job.
SEL077	Warning DDSAVE defined, ignored
Explanation	The FDTINPUT parameter was not supplied in an ADASEL run, but the DDSAVE job statement was specified for the run. The job statement is ignored.
Action	No action is required for this informational message unless you intended to pull the FDT from DDSAVE. If this is the case, specify the FDTINPUT parameter and rerun the ADASEL job.
SEL078	Spanned work pool is too small -- increase LWP and rerun
Explanation	The global LWP ADARUN parameter value is not large enough. LWP specifies the size of the Adabas work pool which is used for assembling PLOG spanned records.
Action	Increase the LWP parameter setting and rerun the ADASEL job.
SEL079	Warning. Skipping spanned records
Explanation	A spanned record was encountered in the PLOG and parameter SPANREC was not specified in the OUTPUT instruction. This record cannot be processed by the ADASEL utility without the SPANREC parameter and is rejected from further processing.
Action	If spanned record processing is required, specify the SPANREC parameter in the ADASEL OUTPUT instruction and rerun the ADASEL job.
SEL080	Both DDEBAND and DDSAVE defined. Only one allowed for FDTINPUT
Explanation	Both DDEBAND and DDSAVE job control statements have been defined in the ADASEL job. Only one is allowed, not both.
Action	Correct the ADASEL job and rerun it.

SEL081	DDEBAND or DDSAVE input must be specified with FDTINPUT option
Explanation	The FDTINPUT parameter was supplied, but neither the DDEBAND or DDSAVE job control statements were included in the ADASEL job.
Action	Supply a valid DDEBAND or DDSAVE job control statement (but not both) and rerun the job.
SEL082	DDEBAND input not allowed with SELECT FROM USER
Explanation	If SELECT FROM USER is specified for an ADASEL run, DDEBAND is not allowed. Specify DDSAVE instead.
Action	Correct the ADASEL job, specifying DDSAVE and not DDEBAND if SELECT FROM USER is requested. Then rerun the job.
SEL084	Error during execution of a sequential read on file DDSAVE: {rsn-code}
Explanation	An error occurred during a sequential read of DDSAVE. The reason code (<i>rsn-code</i>) is given in the message.
Action	Record or save all output from the job, your input statements, and any dumps. Then contact your Software AG support representative for assistance.
SEL085	I/O error during execution of a sequential read on file DDEBAND: rsn-code
Explanation	An error occurred during a sequential read of DDEBAND. The reason code (<i>rsn-code</i>) is given in the message.
Action	Record or save all output from the job, your input statements, and any dumps. Then contact your Software AG support representative for assistance.
SEL086	Incorrect FDT found in input data set
Explanation	Either the field definition table (FDT) expected in the first record is missing from the data set or the FDT structure read from the data set does not satisfy the rules.
Action	Verify that the input data set is valid. Supply a correct input data set and rerun the job. If the problem persists, contact your Software AG technical support representative for assistance.
SEL087	The input data set / file DDEBAND does not have V or VB record format
Explanation	The specified input data set is invalid.
Action	Supply a correct input data set and rerun the ADASEL job.

SEL088	I/O error during opening/closing of input file DDSAVE: {rsn-code}
Explanation	An error occurred attempting to open or close the DDSAVE input file. The reason code (<i>rsn-code</i>) for the failure is given in the message. The cause is probably a misspelling of a job control statement name or other JCL error.
Action	Investigate the cause of the error; correct it and rerun the job.
SEL089	I/O error during opening/closing of input file DDEBAND: {rsn-code}
Explanation	An error occurred attempting to open or close the DDEBAND input file. The reason code (<i>rsn-code</i>) for the failure is given in the message. The cause is probably a misspelling of a job control statement name or other JCL error.
Action	Investigate the cause of the error; correct it and rerun the job.
SEL090	Invalid SAVETAPE supplied
Explanation	The data set supplied as the DD/SAVE input data set is not a save tape.
Action	Supply a valid save tape and rerun the job.
SEL091	Insufficient pool size to keep all external FDTs
Explanation	The pool size for the FDT allocation was insufficient for the number of FDTs found on the save tape. It is possible that the save tape is invalid because the pool size calculation is from the file control block (FCB).
Action	Supply a valid save tape and rerun the job.
SEL092	Differing FNRs not allowed for DDEBAND FDTINPUT
Explanation	Multiple file numbers are not allowed when DDEBAND is supplied.
Action	Correct the SELECT parameters and rerun the job.
SEL093	Requested file not found on SAVETAPE Required FNR={fnr}
Explanation	The requested file's FDT is not found on the SAVETAPE. The file number of the requested file is given in the message (<i>fnr</i>).
Action	Supply a save tape that contains the FDT needed and rerun the job. If you are unsure of the contents of a save tape, run an ADAREP report from the save tape and review its contents.

SEL094	SAVETAPE must be from V74 or higher
Explanation	The supplied save tape was not created using Adabas version 7.4 or later.
Action	Supply a save tape created using Adabas version 7.4 or later and rerun the job.
SEL096	FDT VERSION DOES NOT MATCH WITH PLOG VERSION
Explanation	The PLOG provided is for a different version than the FDT supplied on DDEBAND or DDSAVE.
Action	Supply a correct PLOG or input FDT and rerun the ADASEL job.
SEL097	Warning secondary segment without primary is rejected
Explanation	A standalone secondary segment (a secondary segment without a primary segment) of a spanned record was encountered in the PLOG. This segment cannot be processed by ADASEL and so is rejected from further processing.
Action	No action is required for this informational message. Probably, Adabas was started with the ADARUN parameter SRLOG=UPD, which instructs the nucleus to write to the PLOG only the modified spanned record segments. If it is necessary to include all spanned PLOG records in ADASEL processing, restart Adabas with the SRLOG parameter set to ALL or PART.
SEL098	Warning Fieldname {fn} for ISN={isn} could not be fully processed. The entire value is not present on the PLOG. This record is rejected for further processing
Explanation	The spanned record field (<i>fn</i>) and ISN (<i>isn</i>) identified in the message is not available in the PLOG and is specified with CHANGES or value criteria. This record is rejected for further processing.
Action	No action is required for this informational message.
SEL099	ADASEL terminating due to error
Explanation	This message typically follows another error message which contains more details about the error and indicates that ADASEL terminated abnormally because the NOUSERABEND parameter was specified.
Action	Analyze the previous errors for the run, correct the error condition, and rerun the ADASEL job.
SEL100	The Time zone specified by the TZ parameter is invalid
Explanation	An invalid time zone value was specified in the TZ parameter. The time zone specified must be a valid time zone name contained in the TZINFO member of the Adabas time zone library (ADAvrs.TZ00). Adabas uses the time zone data taken from the tz database, which is also called the zoneinfo or Olson database. The specific list of time zone names that Adabas supports in any given release can be found in the TZINFO member of the Adabas source library

	(ADAvrs.SRCE). For more information about the TZINFO member of the time zone library, read <i>Supported Time Zones</i> .
Action	Supply a valid parameter value and rerun the job.
SEL101	I/O error during opening/reading of input file TZINFO
Explanation	The time zone specified could not be loaded from the Adabas time zone library (ADAvrs.TZ00).
Action	Make sure that JCL assigns TZINFO to the Adabas time zone library (ADAvrs.TZ00). Amend the JCL and rerun the job.
SEL102	Syntax - SELECT FROM FILE not allowed with SELECT ETCMD
Explanation	An attempt to specify SELECT ETCMD FROM FILE was made. SELECT ETCMD can only be specified with FROM USER.
Action	Change the syntax to specify FROM USER instead of FROM FILE and try again.
SEL103	Syntax - DISPLAY ALL not allowed with SELECT ETCMD
Explanation	An attempt was made to specify DISPLAY ALL in the same ADASEL statement as the SELECT ETCMD parameter. When you specify SELECT ETCMD, you restrict the data to only ET data; thus it becomes an illogical condition to specify DISPLAY ALL since the data is not there.
Action	Correct the syntax and try again.
SEL104	Syntax - ISN not allowed with SELECT ETCMD
Explanation	An attempt was made to specify DISPLAY ISN in the same ADASEL statement as the SELECT ETCMD parameter. When you specify SELECT ETCMD, you restrict the data to only ET data; thus it becomes an illogical condition to specify DISPLAY ISN since the data is not there.
Action	Correct the syntax and try again.
SEL105	*** ERROR *** Field selection exceeds output buffer size
Explanation	An attempt was made to write specific fields to the EXPAN output data set and the length of the selected fields exceeds the length of the EXPAN output buffer.
Action	Reduce the number of fields selected for output and try again.

SEL106	Syntax - numeric value too large
Explanation	The specified numeric value for the ADASEL criterion is too large.
Action	Verify the criterion specification for the ADASEL run, correcting values to allowed ranges. Then rerun the ADASEL job.
SEL108	Timezone file cannot be processed or the transition times are invalid
Explanation	The timezone file cannot be processed.
Action	Make sure that the Adabas time zone library (ADAVRS.TZ00) is readable and the timezone file is unmodified. Contact your Software AG technical support representative for assistance.
SEL109	PLOG version with time prefix does not match the Adabas version
Explanation	The PLOG cannot be processed. The version indicates that a timestamp should be present and it was not. Check how the PLOG was created, making sure that the PLOG was created at the appropriate Adabas level.
Action	Contact your Software AG technical support representative for assistance, if necessary.
SEL133	Warning. PLOG has not been merged
Explanation	The PLOG was created by an Adabas cluster nucleus and has not yet been merged using the ADARES PLCOPY procedure.
Action	Merge the PLOGs using the ADARES PLCOPY function before you extract data using ADACDC.

105

ADAULD Utility Messages

This document describes ADAULD messages.

ERROR-121	Cipher-code missing
Explanation	The file is ciphered but no cipher code is supplied.
Action	Supply the correct cipher code and rerun the ADAULD job.
ERROR-122	Cipher code supplied, but file is not ciphered
Action	Remove the cipher code and rerun the ADAULD job.
ERROR-123	No records selected
Explanation	No records found according to the given search criterion. The resulting unloaded file contains only the field definition table (FDT).
ERROR-124	Error limit reached
Explanation	"error-count" errors have occurred (the displayed message contains an actual count). ADAULD execution is terminated.
ERROR-125	Invalid value for parameter 'NUMOUT'
Explanation	NUMOUT must be 1 or 2. If NUMOUT=2, user exit 9 must be loaded.
Action	Supply a correct parameter or a user exit, and rerun the job.

ERROR-126	'SELVAL' parameter missing
Action	Supply a valid selection criterion and rerun the job.
ERROR-127	Invalid value for the parameter 'LRECL' or 'LPB'
Explanation	The LRECL and LPB parameters must be less than 32,768.
Action	Supply the correct parameter value and rerun the ADAULD job.
ERROR-128	Different record lengths for DDOUT1 and DDOUT2
Explanation	The maximum record lengths of the output data sets must be equal.
Action	Supply the correct output data sets and rerun the ADAULD job.
ERROR-129	Invalid 'SORTSEQ' parameter {parameter}
Explanation	The field cannot be used to determine the unload sequence because it <ul style="list-style-type: none"> ■ is undefined; ■ is not a descriptor; ■ is a phonetic descriptor; or ■ (or part of the field) is within a periodic (PE) group.
Action	Choose another sequence, and rerun the ADAULD job.
ERROR-130	Descriptor {desc-name} has {option} option
Explanation	Unloading the file in descriptor "desc-name" sequence may lead to variations in the normal sequence (anomalies).
Action	If you nevertheless want to perform that unload sequence, supply the "option" parameter. Otherwise, choose another unload sequence. Then rerun the ADAULD job.
ERROR-131	Invalid ETID parameter
Explanation	The file to be unloaded is not defined with the multiclient option.
Action	Remove the ETID parameter and rerun the ADAULD job.

ERROR-132	Missing ETID parameter
Explanation	The file to be unloaded is defined with the multiclient option. Selecting records according to a search criterion requires that a single ETID be specified.
Action	Specify the ETID parameter, and rerun the ADAULD job.
ERROR-133	The file number supplied is a checkpoint or security file
Explanation	Checkpoint and security files may not be unloaded.
Action	Supply a correct input file and rerun the job.
ERROR-134	Invalid save tape supplied
Explanation	The data set supplied as the DD/SAVE input data set is not a save tape.
Action	Supply a valid save tape and rerun the job.
ERROR-135	Invalid protection log supplied
Explanation	Once of the following occurred: <ul style="list-style-type: none">■ The requested protection log has DBID <i>dbid1</i>, session number <i>plognum1</i>, but the supplied protection log has DBID <i>dbid2</i>, session number <i>plognum2</i>.■ The SYN1/SYN4 checkpoint is not contained in the protection log block <i>blocknumber</i>.■ The SYN2/SYN5 checkpoint is not contained anywhere on the protection log.■ Another SYN1/SYN4 checkpoint was encountered before the expected SYN2/SYN5 checkpoint.■ The supplied input tape is not a protection log.■ There is an inconsistency in the protection record.
Action	A dump will be produced to analyze the issue. Supply the correct protection log and parameters, and rerun the job.
ERROR-136	TEMP data set too small
Explanation	The temp data set is not large enough to buffer all Data Storage blocks found for file <i>file-number</i> on the protection log.
Action	Supply a larger temp data set and rerun the job.

ERROR-137	The input tapes of a multivolume save data set are mounted in the wrong order
Explanation	The tapes of a multivolume data set are mounted in the wrong order. ADAULD terminates.
Action	Supply the tapes in the correct order and rerun the job.
ERROR-138	Error during DSF processing
Explanation	An error occurred while the Adabas Delta Save Facility Facility was processing the requested function for the delta save data set. The Delta Save Facility returned the response code provided in the message.
Action	Refer to the information for the specified response code. Correct the error and rerun the job.
ERROR-139	Unload without full save not possible
Explanation	The full save tape required to unload from a delta save data set is not supplied.
Action	Supply the full save data set and rerun the job.
ERROR-140	Invalid value for the parameter CODE
Explanation	A valid value has at most eight (8) digits or blanks.
Action	Supply a valid parameter value and rerun the job.
ERROR-141	No protection log supplied
Explanation	The unloaded file was changed during an online save operation but no protection log is supplied. The unloaded data is probably inconsistent.
ERROR-142	Invalid DDISN parameter
Explanation	The DDISN parameter must not be specified if SORTSEQ= <i>descriptor</i> ,MU is also specified, or if the descriptor specified with SORTSEQ is a hyperdescriptor.
Action	Supply the correct parameter value and rerun the job.
ERROR-143	The input data set/file DDEBAND or DDISN does not have the record format variable or variable blocked (V or VB)
Explanation	The record format of DD/EBAND and DD/ISN must be V or VB.
Action	Supply the correct input and rerun the job.

ERROR-144	Invalid ET-ID
Explanation	When running DECOMPRESS on a multicient file, Adabas processes either <ul style="list-style-type: none"> ■ the entire file if ET-ID is not specified; or ■ the selection of records allowed for the client identified by ET-ID. <p>The user ID referred to by the `ETID` parameter is either not defined or has not been assigned an owner ID.</p>
Action	Investigate the cause of the error; correct it; and rerun the job.
ERROR-145	Hyperdescriptor exit was not specified in ADARUN
Explanation	While unloading a file from SAVETAPE, the descriptor value table (DVT) could not be created because the file contains a hyperdescriptor but the hyperdescriptor exit was not specified in the ADARUN parameters for the database.
Action	Specify ADARUN HEXnn parameter in the ADARUN parameters for the database and rerun the job. For more information about the HEXnn parameter, read <i>HEXnn: Hyperdescriptor User Exit in Adabas Operations</i> .
ERROR-146	Hyperdescriptor exit was not specified in ADARUN
Explanation	An error was encountered while generating the descriptor value table (DVT) when a file was being unloaded from SAVETAPE. A response code is returned. For more information, read <i>Nucleus Response Codes in Adabas Messages and Codes</i> .
Action	Investigate the cause of the error, correct it, and rerun the job.
ERROR-147	FDT plus IT prefix do not fit into the output record
Explanation	The maximum record length of the output data set is too small.
Action	Specify the correct output data set or a data set with the correct maximum record length and rerun the job.
ERROR-148	Error during hyperexit call
	A call to hyperexit number {nn} resulted in a response 79 with subcode {code}
Explanation	A hyperdescriptor exit call failed with response code 79 (ADARSP079) and the subcode given in the message during SAVETAPE processing.
Action	Investigate the subcode to determine the reason for the error.

ERROR-149 **File {nnnn} cannot be processed.
The file has spanned records.
ADAULD does not support unloading this file from a save tape.**

Explanation File contains spanned records and is not supported at this time.

Action Adjust the ADAULD job so that files with spanned Data Storage records are not included in the run.

ERROR-150 **Inconsistent SAVETAPE {tape}
The SAVETAPE tape does not contain the expected data.
All records must refer to
DBID {dbid1}, Session Number {n1}, and Time Stamp {tttt1}.
A Record was found referring to
DBID {dbid2}, Session Number {n2}, and Time Stamp {tttt2}**

Explanation The SAVETAPE identified in the message (*tape*) does not contain expected data. All records on the tape must contain references to DBID *dbid1*, session number *n1*, and time stamp *tttt1*. However, a record was found that incorrectly referred to DBID *dbid2*, session number *n2*, and time stamp *tttt2*

Action Correct the cause of the incorrect reference and rerun the ADAULD job.

**MODE=SHORT will be forced
Found field(s) defined with COLDE option**

Explanation At least one field was found with the collation descriptor option defined. In this case, MODE=SHORT is required. Adabas has forced this parameter setting.

Action None required. This message is for information only.

106

ADAVAL Utility Messages

ERROR-121	Invalid descriptor field list for validate
Explanation	The field name (field-name) is either <ul style="list-style-type: none">■ not in the FDT; or■ not a descriptor.
Action	Supply the correct parameter value, and rerun the ADAVAL job.
ERROR-122	TEMP data set too small; input record count= {count}
Action	Supply a larger TEMP data set/file. See the Adabas Utilities documentation for information about calculating TEMP space.
ERROR-130	Error initializing collating user exit - return code={return-code}
Explanation	An error occurred while the collation descriptor user exit was being initialized.
Action	Investigate the cause of the error; correct it; and rerun the job.
ERROR-131	Collating user exit not loaded
Explanation	The collation descriptor user exit requested is not loaded.
Action	Load the exit and rerun the job.

107

ADAWRK Utility Messages

ERROR-121	Invalid value for parameter TIMEZONE. TIMEZONE must be set to MACHINE, LOCAL, or an integer value in the range -23 to +23. When entering + OR -, enclose the number in single quotes. e.g. TIMEZONE='+5'
Explanation	An invalid value was specified for the TIMEZONE parameter.
Action	Supply the correct parameter value and rerun the ADAWRK job.
ERROR-122	Invalid value for parameter CHECKPOINT. Must be set to YES or NO.
Explanation	An invalid value was specified for the CHECKPOINT parameter.
Action	Supply the correct parameter value and rerun the ADAWRK job.
ERROR-124	Invalid value for parameter FORCE. Must set to YES or NO.
Explanation	An invalid value was specified for the FORCE parameter.
Action	Supply the correct parameter value and rerun the ADAWRK job.
ERROR-125	Invalid value for parameter REPLICATION. Must be set to YES, NO, DETAIL or FULL.
Explanation	An invalid value was specified for the REPLICATION parameter.
Action	Supply the correct parameter value (from those listed in the message) and rerun the ADAWRK job.

ERROR-126	Invalid value for parameter REPORTFILE. Must be set to YES or NO.
Explanation	An invalid value was specified for the REPORTFILE parameter.
Action	Supply the correct parameter value and rerun the ADAWRK job.
ERROR-127	Invalid value for parameter SUMMARY. Must be set to YES or NO.
Explanation	An invalid value was specified for the SUMMARY parameter.
Action	Supply the correct parameter value and rerun the ADAWRK job.
ERROR-128	Invalid value for parameter TRANSACTIONS. Must be set to YES, NO or FULL.
Explanation	An invalid value was specified for the TRANSACTIONS parameter.
Action	Supply the correct parameter value and rerun the ADAWRK job.
ERROR-129	Invalid value for parameter FILES. File number provided must be > 0 and < 65536.
Explanation	An invalid value was specified for the FILES parameter.
Action	Supply a file number in the correct range and rerun the ADAWRK job.
ERROR-130	Invalid range for parameter FILES. When file range provided, VALUE1 < VALUE2.
Explanation	An invalid value was specified for the FILES parameter.
Action	Ensure that when providing a range of file numbers the first value (VALUE1) is less than the second value (VALUE2), then rerun the ADAWRK job.
ERROR-131	IOR {cccc} call failed return code {rc}
Explanation	An internal call failed.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-132	Cannot identify Work data sets as no Work data sets were provided in the JCL and NOPPT was specified
Explanation	ADAWRK was unable to find Work data sets.
Action	Either include statements for the Work data sets in the JCL or remove the NOPPT parameter.

ERROR-133	TIMESTAMP mismatch on Work data set
Explanation	ADAWRK detected inconsistent timestamps in the Work data set provided.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-134	Work data set {dsn} has wrapped
Explanation	ADAWRK detected that the Work data set has wrapped and that old protection data has been overwritten. The Work data set name (<i>dsn</i>) is given in the message.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-135	While processing a non cluster Work, a cluster nucleus Work block was found
Explanation	While processing a Work data set from a non-cluster nucleus, ADAWRK detected a work block that originated from a cluster nucleus.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-136	While processing a cluster Work data set, a non cluster nucleus Work block was found
Explanation	While processing a Work data set from a cluster nucleus, ADAWRK detected a work block that originated from a non-cluster nucleus.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-137	Work block size value longer than Work block size
Explanation	While processing a Work data set, ADAWRK detected a work block with a size indicator greater than the block size of the work block.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-138	Invalid version in Work block
Explanation	While processing a Work data set, ADAWRK detected a work block with a version number that is not supported.
Action	Contact your Software AG technical support representative with the details of this message.

ERROR-139	Invalid database ID in Work block
Explanation	While processing a Work data set, ADAWRK detected a work block with a different database ID.
Action	Ensure that you have not mixed the Work files you are passing to ADAWRK.
ERROR-140	Invalid timestamp in Work block
Explanation	While processing a Work data set, ADAWRK detected a work block with an invalid timestamp.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-141	Invalid HSI record in Work block
Explanation	While processing a Work data set, ADAWRK detected a work block with an invalid HSI record.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-142	Cluster nucleus Work data set time stamps did not occur in chronological order
Explanation	While processing a cluster Work data set, ADAWRK detected timestamps that are not in the correct order.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-143	No recovery data found on provided Work data sets
Explanation	While processing the specified Work data sets, ADAWRK was unable to detect any recovery data.
Action	Ensure that you have not mixed the Work files you are passing to ADAWRK.
ERROR-145	Work data set has wrapped
Explanation	The Replication Restart Point was not found on the Work data set(s) provided. Replication information may have been lost.
Action	Contact your Software AG technical support representative with the details of this message.

ERROR-146	Invalid nucleus ID in Work block
Explanation	While processing the Work data set, an invalid nucleus ID was detected.
Action	Ensure that you have not mixed the Work files you are passing to ADAWRK.
ERROR-147	Userid cannot exceed 8 bytes
Explanation	A user ID longer than eight bytes was specified when providing a user ID to be used for selecting transactions.
Action	Correct the user ID and resubmit the job.
ERROR-148	Missing Work data set entry in PPT block
Explanation	When processing the PPT block in the specified Associator data set, a missing entry was detected.
Action	Contact your Software AG technical support representative for assistance.
ERROR-149	Invalid WORK part 1b header block for nucleus ID {id}
Explanation	While processing a Work data set, ADAWRK detected an invalid work block part 1b header for WORK data set from nucleus with nucleus ID = <i>id</i> .
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-150	Insufficient workpool space for buffers
Explanation	ADAWRK encountered a shortage of space in the Work pool during execution.
Action	Check JCL, increase region size, and resubmit the job. If the problem persists, contact your Software AG technical support representative for assistance.
ERROR-151	I/O error reading a Work data set
Explanation	ADAWRK encountered an I/O error reading a Work data set.
Action	Review the additional error message accompanying this message and rectify the problem. Then resubmit the job.
ERROR-152	I/O error reading PPT
Explanation	ADAWRK encountered an I/O error reading the PPT.
Action	Review the additional error message accompanying this message and rectify the problem. Then resubmit the job.

ERROR-153	Inconsistent Work data sets provided
Explanation	ADAWRK detected inconsistencies in the Work data sets provided.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-154	Parameter LWP must be specified in Kb, e.g. LWP=512K
Explanation	The value provided for the LWP parameter must be specified in kilobytes.
Action	Provide a value for LWP in kilobytes and try again.
ERROR-155	Parameter LWP error : must be between 100K and 1048576K
Explanation	The value provided for the LWP parameter is not in the correct range.
Action	Provide a value for LWP in the correct range and try again.
ERROR-156	Parameter error(s) detected
Explanation	This message appears when errors have been detected in parameter processing.
Action	Messages indicating which parameters are in error will have been issued earlier. Refer to these other error messages to resolve the issue. Then try again.
ERROR-157	No space in Work pool to satisfy request Please review the settings of the LWP parameter
Explanation	An internal ADAWRK storage request has failed.
Action	Consider increasing the setting of the ADAWRK LWP (length of Work pool) parameter. If this does not resolve the issue, contact your Software AG technical support representative for assistance.
ERROR-158	All Work data sets for nuclei referred to in Work-part-1 data not provided
Explanation	Records have been detected in the Work part 1 data referring to clustered nuclei, but the work data sets for the other nuclei have not been provided as input to ADAWRK in JCL. Inconsistent ADAWRK output may result.
Action	Ensure that all Work data sets for all component nuclei of the cluster are included as input to ADAWRK. Then try again.

ERROR-159	Invalid value for parameter FILES. File number specified more than once.
Explanation	The same file number has been specified more than once in the ADAWRK FILES parameter. This is invalid.
Action	Correct the parameter and try again.
ERROR-160	More than one Replication Data Begin Record received.
Explanation	More than one internal replication begin record was encountered during ADAWRK processing.
Action	Contact your Software AG technical support representative for assistance.
ERROR-161	Missing WRKC for Replication ID record
Explanation	An internal error has occurred when ADAWRK was processing a replication-related protection record. ADAWRK skips this protection record and continues processing, but its replication report may become inaccurate.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-162	Missing WRKC for Replication RDI record
Explanation	An internal error has occurred when ADAWRK was processing a replication-related protection record. ADAWRK skips this protection record and continues processing, but its replication report may become inaccurate.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-163	Missing WRKC for Replication RDB record
Explanation	An internal error has occurred when ADAWRK was processing a replication-related protection record. ADAWRK skips this protection record and continues processing, but its replication report may become inaccurate.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-164	Missing WRKU for Replication RDB record
Explanation	An internal error has occurred when ADAWRK was processing a replication-related protection record. ADAWRK skips this protection record and continues processing, but its replication report may become inaccurate.
Action	Contact your Software AG technical support representative with the details of this message.

ERROR-165	Unexpected response code {rc} subcode {sc}
Explanation	An unexpected Adabas response code has occurred when ADAWRK was opening, validating or traversing a Work data set. The response code and associated subcode are shown. ADAWRK stops processing.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-166	Partially written block in WORK Part 1 extension NUCID={id}, RABN={nnnnnn}
Explanation	While processing a Work data set, ADAWRK detected an invalid block in the Work part 1 extension (RABN=nnnnnn) on the Work data set of the nucleus with nucleus NUCID <i>id</i> .
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-167	PLOG record internal nucid > 32
Explanation	A protection record on a Work data set contains an invalid internal NUCID. ADAWRK stops processing.
Action	Contact your Software AG technical support representative with the details of this message.
ERROR-168	Inconsistency in WORK Part 1 extension NUCID={id}
Explanation	While processing a Work data set, ADAWRK detected an inconsistent block in the Work part 1 extension on the Work data set of the nucleus with NUCID <i>id</i> .
Action	Contact your Software AG technical support representative with the details of this message.
WARN-001	A timestamp was encountered reading the Work data sets indicating that ADAWRK is running against a running Adabas nucleus. ADAWRK will continue.
Explanation	ADAWRK detected that the Work data sets it is reading are being used by an active database.
Action	No action is required for this informational message.
WARN-002	Flush point values not established
Explanation	While processing the specified Work data sets, ADAWRK was unable to determine the flush point.
Action	No action is required for this informational message.

WARN-003	End of buffer flush values not established
Explanation	While processing the specified Work data sets, ADAWRK was unable to determine the end of buffer flush point.
Action	No action is required for this informational message.
WARN-004	Start of buffer flush values not established
Explanation	While processing the specified Work data sets, ADAWRK was unable to determine the start of buffer flush point.
Action	No action is required for this informational message.
WARN-005	Backward repair point values not established
Explanation	While processing the specified Work data sets, ADAWRK was unable to determine the backward repair point.
Action	No action is required for this informational message.
WARN-006	Work data set {dsn} found in PPT but not provided to ADAWRK.
Explanation	The PPT refers to a Work data set that has not been provided as input to ADAWRK in JCL. It may be that the data set has been omitted in error. Inconsistent ADAWRK output may result.
Action	If the data set was not intentionally excluded from the run, include the relevant data set as input to ADAWRK. Then try again.
WARN-007	Work data set {dsn} not found in PPT but provided to ADAWRK
Explanation	The PPT does not refer to a Work data set that has been provided as input to ADAWRK in JCL. It may be that the data set has been included in error. Inconsistent ADAWRK output may result.
Action	If the data set was not intentionally included from the run, remove the relevant data set as input to ADAWRK. Then try again.
WARN-008	Work data set for nucleus that triggered the last buffer flush not provided
Explanation	The Work data set for the nucleus that triggered the last buffer flush has not been provided as input to ADAWRK in JCL. Inconsistent ADAWRK output may result.
Action	If the data set was not intentionally excluded from the run, include the relevant data set as input to ADAWRK. Then try again.

108

ADAZAP Utility Messages

ERROR-121	Incorrect mastercode supplied
Explanation	The 8-byte mastercode specified in the MCODE parameter is incorrect.
Action	Supply the correct mastercode and rerun the job.
ERROR-122	Adabas active, ADAZAP not permitted to run
Explanation	ADAZAP runs only when the relevant Adabas nucleus is inactive.
Action	Shut down the nucleus and rerun the job.
ERROR-123	VER-string is shorted than REP-string
Explanation	The length of the string specified by VER is shorter than the string specified by REP.
Action	Specify the length of VER at least as long as the length of REP.
ERROR-124	VER and LENGTH are mutually exclusive
Explanation	The VER parameter and the LENGTH parameter may not be specified at the same time.
Action	Specify either VER or LENGTH, but not both.
ERROR-125	OFFSET is bigger than BLOCKLENGTH
Explanation	The OFFSET value specified is greater than the block length.
Action	Specify a smaller OFFSET value so that it falls within the block.

ERROR-126 **Verify not matched, string was: {string}**

Explanation The VER value specified did not match.

Action Specify the correct VER value and rerun the job.

ERROR-127 **{offset} plus {length-of-verification} exceeds block length**

Explanation The of the two values *offset* plus the *length-of-verification* string exceeds the maximum block size of the RABN being modified.

Action Check your VER value and specify an offset and a string that falls completely within the block.

WARNING-128 **End of block reached**

Explanation During a list function, the offset plus the length specified exceeded the block size.

Action No action is required for this warning message.

109

ADAZIN Utility Messages

ERROR-121	Cannot specify MODRANGE in conjunction with MOD
Explanation	The MODRANGE and MOD parameters were specified in the same ADAZIN utility run. These parameters are mutually exclusive; only one of them can be specified in the run.
Action	Correct the ADAZIN parameters and rerun the job.
ERROR-122	Invalid MODRANGE value
Explanation	The range of values specified in the MODRANGE parameter of an ADAZIN utility run is invalid.
Action	Correct the MODRANGE parameter and rerun the job.
ERROR-124	System error = x'{sys-code}' returned during execution of IOR function x'94'
Explanation	The ADAZIN utility makes use of an internal Adabas component ADAIOR. An error occurred in ADAIOR processing.
Action	Contact your Software AG technical support representative for assistance.
ERROR-126	SVC numbers must be in the range 200-255
Explanation	The SVC numbers specified by the SVC or SVCRANGE parameters in an ADAZIN utility run are invalid. SVC numbers specified by these two parameters must be in the range 200-255 (inclusive)
Action	Correct the SVC or SVCRANGE parameter and rerun the job.

ERROR-127	Invalid SVC RANGE value
Explanation	The range of values specified in the SVC RANGE parameter of an ADAZIN utility run is invalid.
Action	Correct the SVC RANGE parameter and rerun the job.
WARNING-123	Running non APF-authorized. Module information may be inconsistent with target library
Explanation	The load library specified by the DDZIN DD statement identifies a load library that is not APF-authorized. Any modules already loaded will not be loaded for this ADAZIN utility run. Processing continues, but the module information in the resulting ADAZIN report may not be consistent with the modules included in the DDZIN load library.
Action	No action is required for this warning message. However, if you make sure that all load libraries are APF-authorized, your ADAZIN reports will be more complete.
ZIN128	Cannot specify MOD RANGE/MOD in conjunction with NOMOD. NOMOD parameter will be ignored.
Explanation	The NOMOD parameter was specified in the same ADAZIN run as either the MOD RANGE or MOD parameter. The MOD RANGE, MOD, and NOMOD parameters are mutually exclusive in an ADAZIN run. The NOMOD parameter is ignored for the run.
Action	No action is required for this informational message.
ZIN129	For {member_name} V/R/S and ZAP status cannot be identified. {member-name lib_concat_num}
Explanation	The version number and zap status of the member listed in the message cannot be determined.
Action	Verify that you have specified valid member names for the run. If you have and if this problem persists, contact your Software AG technical support representative for assistance.
ZIN130	{module_name} specified in parameter {parm-name} does not exist in library.
Explanation	The module name listed in the message and specified by the parameter listed in the message does not exist in the library specified in the ADAZIN job.
Action	Verify that the correct module names are specified in the job and that the library is specified correctly. If the problem persists, contact your Software AG technical support representative for assistance.

ZIN131	Insufficient memory to build the member list of the library. List has been truncated. Increase NUMMODS parameter and rerun the job.
Explanation	Insufficient memory was available to process the members listed for an ADAZIN run.
Action	Increase the NUMMODS parameter to handle all of the specified members or reduce the number of members in the ADAZIN run. Then try again.
ZIN132	Cannot specify SVCRANGE/SVC in conjunction with NOSVC. NOSVC parameter will be ignored.
Explanation	The NOSVC parameter was specified in the same ADAZIN run as either the SVCRANGE or SVC parameter. The SVCRANGE, SVC, and NOSVC parameters are mutually exclusive in an ADAZIN run. The NOMOD parameter is ignored for the run.
Action	No action is required for this informational message.
ZIN133	SVCnn ignored. SVC numbers must be in range 200-255.
Explanation	An SVC number was specified in the SVC or SVCRANGE parameter that was out of the 200-255 range of SVC numbers.
Action	Correct the SVC number and rerun the job.
ZIN134	SVCnn is not a valid Adabas SVC routine
Explanation	An invalid SVC number was specified in the SVC or SVCRANGE parameter.
Action	Correct the SVC number and rerun the job.
ZIN135	+{nn dsname}
Explanation	The library concatenation number and the data set name for the ADAZIN run are given in the message.
Action	No action is required for this informational message.
ZIN136	No unexcluded modules found in this range
Explanation	No unexcluded modules were found in the range specified by the MODRANGE parameter.
Action	No action is required for this informational message.

Index

A

- AAF* messages, 351
- AAUD messages, 409
- abend codes
 - user, 337
- ACLX messages, 411
- acronyms in messages, 2
- ADAA* messages, 413
- ADAACK utility
 - messages, 1165
 - return codes, 1136
- Adabas
 - AAUD messages, 409
 - nucleus and utility checkpoints, 31
 - response codes, 147
- Adabas Analytics messages, 413
- Adabas Caching Facility
 - messages, 897
- Adabas Delta Save Facility Facility
 - messages, 901
- Adabas Review
 - ACLX messages, 411
 - ARMT messages, 759
 - ARST messages, 761
 - ARVU messages, 799
 - messages, 971, 1037
 - messages received from the hub, 601
 - RTP messages, 1075
 - RVCL messages, 1077
- Adabas Review hub
 - messages, 601, 713, 1069
- Adabas Review link routine messages, 933
- Adabas SAF Security
 - console and system data set messages,
 - internal function codes, 359
 - messages, 351, 1091
 - operator command messages,
 - return codes, 357
- Adabas SMF records
 - messages, 629
- Adabas Vista
 - database processing messages, 861
 - processing messages, 863
- ADACDC utility
 - messages, 1169
- ADACHK utility
 - decompression messages, 1229
 - messages, 1177
 - return codes, 1137
 - sort messages, 1237
- ADACLU
 - messages, 951
- ADACM*
 - messages,
- ADACMP utility
 - messages, 1243
 - return codes, 1137
- ADACNV utility
 - messages, 1251
- ADACOM
 - messages, 935
- ADADBS utility
 - messages, 1257
 - return codes, 1138
- ADADCK utility
 - messages, 1277
 - return codes, 1139
- ADADEF utility
 - messages, 1281
 - return codes, 1139
- ADADnn messages, 425
- ADADRU utility
 - messages, 1285
- ADADSP
 - messages, 927
- ADAE* messages, 427
- ADA ECS
 - conversion (APSPSX*) messages, 711
- ADAEOPV messages,
- ADAFRM utility
 - messages, 1297
- ADAH* messages, 543
- ADAI* messages, 545
- ADAICK utility
 - messages, 1299
 - return codes, 1139
- ADAINV utility
 - messages, 1309
 - return codes, 1139
- ADAJ* messages, 565
- ADAK messages, 567
- ADAL* messages, 579
- ADALNK
 - BS2000
 - messages, 567
- ADALOD utility
 - messages, 1313
 - return codes, 1140

ADAM* messages, 583
ADAMER utility
 messages, 1329
ADAMTR utility
 messages, 1331
ADAMTS utility
 messages, 1335
ADAORD utility
 messages, 1339
 return codes, 1141
ADAPLP utility
 messages, 1347
ADAPRI utility
 messages, 1349
ADAQ* messages, 601
ADAR* messages, 605
ADARAI utility
 messages, 1351
 return codes, 1141
ADAREP utility
 messages, 1361
 return codes, 1141
ADARES utility
 messages, 1365
 return codes, 1142
ADARPE utility
 messages, 1375
ADARPL utility
 messages, 1379
ADARPP utility
 messages, 1387
ADARUN
 messages, 23
ADAS* messages, 611
ADASAF messages, 427
ADASAV utility
 messages, 1391
 return codes, 1143
ADASEL utility
 messages, 1407
 return codes, 1144
ADASIP
 messages
 z/VSE SVC, 619
ADASM* messages, 629
ADASNAP data set, 107
ADASVC messages, 611
ADATCP
 messages, 419
 TCP/IP interface (APSPSX*) messages, 711
ADAU* messages, 631
ADAULD utility
 messages, 1425
 return codes, 1144
ADAVAL utility
 messages, 1431
 return codes, 1145
ADAWRK utility
 messages, 1433
 return codes, 1145
ADAX* messages, 649
ADAZ* messages, 697
ADAZAP utility
 messages, 1443

ADAZIN utility
 messages, 1445
APSPSX* messages, 711
AREV messages, 713
ARMT messages, 759
ARST messages, 761
ARVU messages, 799
ARXM messages, 811

B

batch
 initialization
 messages, 1087
 job exit utility
 messages, 1085

C

cache services
 messages, 897
cache space
 statistics, 78
 summary, 79
checkpoints, 31
 written by Adabas nucleus/utilities, 32
cluster data space
 messages, 927
cluster nucleus
 messages, 649
codes
 Adabas response, 147
 userabend, 337
 utility return, 1135
Command log
 messages, 579
console
 messages, 39
conversion messages
 APSPSX* for ADAECS or ADATCP, 711
CWARN* messages, 897

D

DSF* messages, 901
DSP* messages, 927
DSTAT operator command
 messages, 631
dump formatting status
 messages, 543

I

internal function codes, 1092

J

job exit utility
 messages, 1085

L

licensing

messages, 319
LNKENAB module
messages, 567
LNKR VX* messages, 933

M

messages, 413, 1105
acronyms, 2
ARXM, 811
on the console, 39
prefixes, 9
prefixes by product, 15
SAF daemon, 1081
MLC* messages, 319
multiprocessing
ADACLU messages, 951
ADACOM messages, 935

N

nucleus
checkpoints, 31
startup parameter error messages, 125

P

parameter errors, 125
PIN routine messages, 1103
PINAUTOR messages, 1103
PL6* messages, 963
PLI* messages, 935
PLX* messages, 951
prefixes, 9, 15
PRILOG6
messages, 963

R

response codes
Adabas, 147
return codes
internal function codes, 1092
structure, 1092
utility, 1135
REV00xxx messages, 971
REV20xxx messages, 1037
REXH messages, 1069
RTP messages, 1075
RVCL messages, 1077

S

SAF daemon messages, 1081
SAF Security Kernel
console and system data set messages,
internal function codes, 359
messages, 1081, 1091
operator command messages,
return codes, 357
SAF* messages, 1081
SAGE* messages, 1085
SAGI* messages, 1087

SAGUSER control statement
batch
messages written over, 1085
security messages, 427
SEFM* messages, 1091
Software AG internal transport subsystem messages, 1105
system
messages, 697

T

Trans-*port* messages, 1075

U

user
abend codes, 337
utilities
error messages and codes
common to all utilities, 1147
messages
status, 631
return codes, 1135
utility
checkpoints, 31

Z

z/VSE
job exit utility
messages, 1085

