

Adabas Review

Messages and Codes

Version 4.9.1

September 2018

This document applies to Adabas Review Version 4.9.1 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG.

Document ID: REV-MESSAGES-491-20200128

Table of Contents

Messages and Codes	v
1 About this Documentation	1
Document Conventions	2
Online Information and Support	2
Data Protection	3
2 ACLX* - Adabas Review Interface Messages	5
3 ADAK* System Messages	7
4 ADAQ* - Adabas Review Hub Messages	19
5 AREV* - Adabas Review Hub Messages	23
6 ARMT* - Adabas Review Interface Messages	29
7 ARST* - Adabas Review Interface Messages	31
8 ARVU* - Adabas Review Interface Messages	33
9 LNKRVX* Adabas Review Link Routine Messages	43
10 Adabas Review 00xxx Messages	45
11 Adabas Review 20xxx Messages	109
12 REVH* - Adabas Review Hub Messages	137
13 RTP* - Adabas Review Trans- port Messages	143
14 RVCALL* - Adabas Review RVCALL API Messages	145
15 RVCL* - Adabas Review Batch Client Reporting (REVCLRP) Messages	151
16 Adabas Response Codes	155

Messages and Codes

This documentation contains a description of the system messages and error messages for Adabas Review.

The Adabas Review Messages and Codes documentation is organized in the following topics:

<i>ACLX* - Adabas Review ADALNK Messages</i>
<i>ADAK* System Messages</i>
<i>ADAQ* System Messages</i>
<i>AREV* - Adabas Review Hub Messages</i>
<i>ARMT* - Adabas Review Hub Messages</i>
<i>ARST* - Adabas Review Hub Messages</i>
<i>ARVU* - Adabas Review Hub Messages</i>
<i>LNKR VX* Adabas Review Link Routine Messages</i>
<i>Adabas Review 00xxx Messages</i>
<i>Adabas Review 20xxx Messages</i>
<i>RE VH* - Adabas Review Hub Messages</i>
<i>RTP* - Adabas Review Trans- port Messages</i>
<i>RVCL* - Adabas Review Batch Client Reporting (REVCLRP) Messages</i>
<i>RVCALL* - Adabas Review RVCALL API Messages</i>
<i>Adabas Response Codes</i>

1 About this Documentation

▪ Document Conventions	2
▪ Online Information and Support	2
▪ Data Protection	3

Document Conventions

Convention	Description
Bold	Identifies elements on a screen.
Monospace font	Identifies service names and locations in the format <code>folder.subfolder.service</code> , APIs, Java classes, methods, properties.
<i>Italic</i>	Identifies: Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources.
Monospace font	Identifies: Text you must type in. Messages displayed by the system. Program code.
{ }	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.
	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the symbol.
[]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [] symbols.
...	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...).

Online Information and Support

Software AG Documentation Website

You can find documentation on the Software AG Documentation website at <http://documentation.softwareag.com>. The site requires credentials for Software AG's Product Support site Empower. If you do not have Empower credentials, you must use the TECHcommunity website.

Software AG Empower Product Support Website

If you do not yet have an account for Empower, send an email to empower@softwareag.com with your name, company, and company email address and request an account.

Once you have an account, you can open Support Incidents online via the eService section of Empower at <https://empower.softwareag.com/>.

You can find product information on the Software AG Empower Product Support website at <https://empower.softwareag.com>.

To submit feature/enhancement requests, get information about product availability, and download products, go to [Products](#).

To get information about fixes and to read early warnings, technical papers, and knowledge base articles, go to the [Knowledge Center](#).

If you have any questions, you can find a local or toll-free number for your country in our Global Support Contact Directory at https://empower.softwareag.com/public_directory.asp and give us a call.

Software AG TECHcommunity

You can find documentation and other technical information on the Software AG TECHcommunity website at <http://techcommunity.softwareag.com>. You can:

- Access product documentation, if you have TECHcommunity credentials. If you do not, you will need to register and specify "Documentation" as an area of interest.
- Access articles, code samples, demos, and tutorials.
- Use the online discussion forums, moderated by Software AG professionals, to ask questions, discuss best practices, and learn how other customers are using Software AG technology.
- Link to external websites that discuss open standards and web technology.

Data Protection

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

2 ACLX* - Adabas Review Interface Messages

These are messages produced by Adabas Review processing.

 **Note:** Some of the ACLX* messages are preceded by the Adabas database ID. These database IDs are not shown in the message texts in this documentation.

ACLX01	Old RUBX arrived
Explanation	A RUBX for Adabas Review 4.4 or earlier has been received by the Adabas 8.2 nucleus. The older RUBX has been translated into a new format. This causes some performance degradation. New fields which do not exist in Adabas Review 4.4 are not translated.
Action	Determine which ADALNK contains an old Adabas Review module.
ACLX02	REV45 RUBX arrived and ignored
Explanation	A RUBX for Adabas Review 4.5 or later has been received by an Adabas 8.1 nucleus. The newer RUBX is ignored. The RUBX fields in Adabas Review are empty.
Action	Use the Adabas LX library for Adabas Review 4.5 or use Adabas 8.2.
ACLX03	{dbid} Client Report requires CLOGL=8
Explanation	Adabas Review client reports run only if ADARUN CLOGLAYOUT=8 is specified in the Adabas nucleus. An attempt was made to run a client report when CLOGLAYOUT=8 was <i>not</i> specified. The client reports will not run at all or some fields in the report will be empty.
Action	Specify ADARUN CLOGLAYOUT=8 in the concerning ADABAS nucleus and start the nucleus again.

3 ADAK* System Messages

The following messages may appear when errors occur in the Adabas CICS and BS2000 TP monitor interface operations.

When CICS is started, the Adabas TP monitor component displays several informational or error messages on the system console. These often contain the addresses of key Adabas and CICS control blocks which are useful in problem determination.

- Be sure that the console messages indicate that the Adabas TRUE environment has been properly established.
- If an error message is produced, note the CICS EIBRESP, EIBRESP2, and EIBRCODE, which is displayed.
- Note any Adabas response code (ACBRSP) displayed by the TP monitor program at CICS startup.

ADAK001 **Installation messages will be written to queue {qname} file {dname}**
Explanation This message is produced when the following ACIOPT statement is coded:

```
ACIOPT ENTRY=GLOBAL,IMSGDEST=TDQ/BOTH,IMQNAME=qname
```

It provides the name of the transient data queue (qname) where installation messages are written and the DD name (z/OS) or DLBL name (z/VSE) of the file (dname) associated with the transient data queue

Action No action is required for this informational message.

ADAK01 **{dbid} Unexpected return code {ret-code} in {function}**

Explanation During BS2000 TP monitor interface operations, the return code (*ret-code*) given in the message occurred in one of the following functions and for the specified reason:

Function	Reason
TRGENAMP	enable memory pool (ENAMP) to target failed
IDTENAMP	enable memory pool (ENAMP) for IDT failed
DSOFEI	building of client hard wait (DSOFEI macro) failed
DPOFEI	Building of database hard post(DPOFEI) failed
TRGENAEI	enable event (ENAEI) failed for target
SOLSIG	SOLSIG macro failed
LNKLEVEL	the ADALNK and ADARER levels disagree (see the first and last bytes of "ret-code")
POSSIG	Post(POSSIG) to database failed

Action See the BS2000 Executive Macro documentation for an explanation of "ret-code".

ADAK02 **Types of LOADLIB for ADALNK ({adalnk}) and ADARER mismatch**

Explanation During BS2000 TP monitor interface operations, one module was loaded from an XS library and the other from an NXS library. NXS and XS components cannot be mixed.

This message is accompanied by the ADAK01 message.

The *adalnk* field of this message has the format *xx0000yy*, where *xx* is the level of the ADALNK and *yy* is the level of the ADARER (router). The value of *yy* must be greater than or equal to the value of *xx*.

If *yy* is less than *xx*, the IDT common memory where the ADARER is loaded has been created by and loaded from an older Adabas version. For example, if *xx*=83 and *yy*=81, an Adabas 61x ADALNK is using an Adabas 53x ADARER.

Action Check the Adabas library versions of the databases that are using the IDTNAME (the default is ADABAS5B) of your ADALNK.

Either upgrade databases using older Adabas libraries to the new version, or use different IDTNAMEs for different Adabas versions.

ADAK02A **Could not get Router - Error - {err}**

Explanation A BS2000 attempt to access the ID table memory pool given in the parameter file or module returned the error shown in the message (*err*), probably in the enable memory pool macro (ENAMP).

This error is accompanied by the user abend 680.

Action	Check the parameter file for the IDTNAME or DBTIDT value; otherwise check the BSCONFIG(ENVNAME), IDTABEL, or MDBIDT macros in SSFB2C.
ADAK02B	DB Table Get memory - Error - {err1} or DB Table Initialization Error - {err2}
Explanation	The DBID/ID table cannot be set up or accessed. This message is accompanied by user abend 678 or 679. This is usually an error in getting memory. The error code is from a BS2000 macro.
Action	Contact your Software AG technical support representative with the error code produced.
ADAK03	Parameter error
Explanation	During BS2000 TP monitor interface operations, the ADALNK parameter service detected a syntax error.
Action	Correct the syntax and rerun.
ADAK04	The following ADALNK ({adalnk}) are used for this run
Explanation	This is the header of the ADALNK parameter listing used during BS2000 TP monitor interface operations.
Action	No action is required.
ADAK040	Enabling {nnnn} Adabas task related user exits for Version 8 of ADACIC0
Explanation	Explanation: This message is produced at the beginning of ADACIC0 installation processing and identifies the number of TRUEs that ADACIC0 is attempting to install. The number (<i>nnnn</i>) is derived from the number of ENTRY=GROUP items that were coded in the ACIOPT module
Action	No action is required for this informational message.
ADAK041	Extracting global work area (GWA)
Explanation	During CICS PLTPI processing, CICS is determining the location of the global work area (GWA) for the command-level link components.
ADAK042	Initializing Adabas link routine
Explanation	During CICS PLTPI processing, an initialization call is being made to the command-level link routine.

ADAK043	Initializing Adabas SVC communication
Explanation	During CICS PLTPI processing, the Adabas SVC environment is being established.
ADAK044	Adabas v{vrs} CICS environment established
Explanation	During CICS PLTPI processing, the CICS environment needed for the command-level link components has been built.
ADAK045	T.R.U.E. {true-name} is in use by Adabas link routine {link-name}
Explanation	This message occurs during CICS PLTPI processing and displays the task-related user exit name and the Adabas link routine with which it is associated.
ADAK046	SVC number: {svc} default DBID: {dbid}
Explanation	This message occurs during CICS PLTPI processing and displays the default SVC number and DBID.
ADAK047	UB pool address: {aaaaaaaa} NUBS: {nnnnn}
Explanation	This message occurs during CICS PLTPI processing and displays the UB pool address and NUBS value.
ADAK048	User exit after (A) address: { {aaaaaaaa} NOT IN USE }
Explanation	This message occurs during CICS PLTPI processing and displays the address of the Adabas user exit 1 (user exit A in Adabas 7) or "not in use" if the user exit is not in use.
ADAK049	User exit before (B) address: { {aaaaaaaa} NOT IN USE }
Explanation	This message occurs during CICS PLTPI processing and displays the address of the Adabas user exit B or "not in use" if user exit B is not in use.
ADAK05	DDLNKPAR {open close} error: {err}
Explanation	During BS2000 processing an attempt to access the file associated with the link name DDLNKPAR failed. The error is a DMS error code.
Action	Perform a SHOW-FILE on the file associated with the linkname DDLNKPAR. If a DMS error occurs, perform HELP_MESSAGE DMSnnnn. This should help identify the problem.

ADAK050	Review exit address: { {aaaaaaaa} NOT IN USE }
Explanation	This message occurs during CICS PLTPI processing and displays the address of the Adabas Review exit, or "not in use" if the Adabas Review exit is not in use.
ADAK051	Adabas SAF Security (ADASAF) in use
Explanation	During CICS PLTPI processing, the Adabas external security interface (ADASAF) is in use. This message is not displayed if ADASAF is not in use.
ADAK052	Adabas Transaction Manager (ATM) in use
Explanation	During CICS PLTPI processing, Adabas transactions are being coordinated through the CICS Resource Manager Interface (RMI) using the Adabas Transaction Manager (ATM). This message is not displayed if the RMI is not in use.
ADAK053	Adabas Bridge for VSAM (AVB) in use
Explanation	During CICS PLTPI processing, the Adabas Bridge for VSAM (AVB) is in use. This message is not displayed if AVB is not in use.
ADAK054	T.R.U.E. global work area (GWA) address: {aaaaaaaa}
Explanation	This message occurs during CICS PLTPI processing and displays the address allocated to the global work area.
ADAK055	Adabas link routine EPA: {aaaaaaaa}
Explanation	This message occurs during CICS PLTPI processing and displays the entry point address (EPA) of the Adabas link routine.
ADAK056	Adabas link routine D.C.I. EPA: {aaaaaaaa}
Explanation	This message occurs during CICS PLTPI processing and displays the entry point address (EPA) of the Adabas link routine direct call interface (DCI).
ADAK057	Adabas SVC IDTH address: {aaaaaaaa}
Explanation	This message occurs during CICS PLTPI processing and displays the address of the Adabas SVC IDT header.

ADAK058	RESYNC command issued
Explanation	During CICS PLTPI processing, the CICS RMI for Adabas is in use and resynchronization will now take place for any incomplete transactions involving Adabas databases.
ADAK059	ATM inactive; RESYNC deferred
Explanation	During CICS PLTPI processing, the CICS RMI for Adabas is in use and resynchronization may be required for incomplete transactions involving Adabas databases. However, the Adabas Transaction Manager (ATM) is not currently active. Resynchronization will occur when ATM is restarted.
ADAK06	ADALNK statements ignored because ADARUN statements present
Explanation	A BS2000 session is running an ADALNK with both ADARUN and link name DDCARD, together with a file on the link name DDLNKPAR. The parameters in DDLNKPAR will not be used.
Action	No action required for this informational message.
ADAK061	ADATRUE - Enable stage failed EIBRESP: {xxxxxxx1} EIBRESP2: {xxxxxxx2}
Explanation	The task related user exit could not be enabled due to the EIB response codes xxxxxxxx1 and xxxxxxxx2.
Action	Consult the appropriate CICS documentation to determine the cause of the error in the exec interface block (EIB).
ADAK062	ADATRUE extract GWA failed EIBRESP: {xxxxxxx1} EIBRESP2: xxxxxxx2
Explanation	The requested task-related user exit global storage could not be EXTRACTed due to the EIB response codes given as xxxxxxxx1 and xxxxxxxx2.
Action	Consult the appropriate CICS documentation to determine the cause of the error in extracting the global work area.
ADAK063	Initialization call to link routine failed EIBRCODE: {xxxxxxx} ADARSP: {nnnn}
Explanation	The Initialize Link command (IL) could not be executed because of EIB response code xxxxxxxx, or Adabas response code nnnn.
Action	If the EIBRCODE field returns a non-zero value, consult the appropriate CICS documentation to determine the cause of the error. If the ADARSP returns a non-zero value, consult the response codes in chapter 2.

- ADAK064** **Adabas call to establish IDTH failed**
Explanation The address of the IDTH could not be established.
Action Most often, this is caused by an incorrect Adabas SVC number in the LGBLSET macro; otherwise, check to see that the Adabas SVC is installed, and at the correct version.
- ADAK065** **Invalid D.C.I address - cannot continue**
Explanation The address of the Direct Call Interface could not be established.
Action Verify that the correct version of the Adabas command-level link routine is installed, and that the entry point name "ENTPT=" in LGBLSET is correct.
- ADAK066** **ADACIC0 version: {version} does not match Adabas link**
Explanation The ADACIC0 version does not match the version of the ADATRUE or Adabas link routine being installed. All three modules must be at the same version for the install to succeed.
Action Verify that the correct version of all three modules is installed.
- ADAK068** **{message-text}**
Explanation Various message texts may be provided using this message number. Review the table below to determine the cause of the error and the course of action to take.

Message Text	Explanation	Action
LOAD of installation options table <i>tbl</i> failed EIBRESP: <i>eibresp</i>	The load failed for the Adabas installation options table module named <i>tbl</i> by the CICS command-level link routine module. The hexadecimal representation of the CICS EIBRESP returned by the failing EXEC CICS LOAD command is given in the message.	Determine the meaning of the EIBRESP code. Check the DFHRPL concatenated libraries to ensure that the ACIOPT module is available to the CICS region.
RMI initialization error: CMD: <i>cmd</i> RESP: <i>resp</i> RC: <i>rc</i>	The RMI initialization routine could not complete its processing due to the indicated error. The message may provide a failing CICS command (<i>cmd</i>) and response code (<i>resp</i>), or an ATM error code (<i>rc</i>) and, if relevant, Adabas response code (<i>resp</i>).	Investigate the meaning of the displayed response code and/or error code. If possible, correct the error; otherwise, report the details to your Software AG technical support representative.
Adabas installations options table	The installation options table module listed in the message (<i>tbl</i>) has been loaded but does not have valid contents.	A valid installation options table module should have the eyecatcher 'ACIOPT ' at the

Message Text	Explanation	Action
name <i>tbl</i> is invalid.		beginning of the module. Verify the module has this eyecatcher and correct accordingly.

Action The action that should be taken depends on the message text issued with this message number. Review the table above for the appropriate action.

ADAK069 {message-text}

Explanation Various message texts may be provided using this message number. Review the table below to determine the cause of the error and the course of action to take.

Message Text	Explanation	Action
Load of ACI link routine failed EIBRCODE: <i>eibrcode</i>	The load of the Adabas command-level link routine module failed. The hexadecimal representation of the CICS EIBRCODE (<i>eibrcode</i>) returned by the failing EXEC CICS LOAD command is given in the message.	Determine the cause of the failure. The reason for the failure may be determined by examining previous messages produced by the ADACIC0 installation program. These messages are written to the JES job log for z/OS and to SYSLOG for z/VSE. For more information please consult your Adabas installation documentation.
Load of DBID/SVC table <i>tbl-name</i> failed EIBRESP <i>eibrbc</i>	An attempt to load the DBID/SVC routing table named in the message (<i>tbl-name</i>) failed. The CICS EIB response code (<i>eibrbc</i>) is given in the message.	Verify that the correct DBID/SVC load module name was specified for the LGBLSET DBSVCTN parameter. If it was not, correct the name and try again. If the correct name was specified, review the CICS EIB response code to identify the nature of the failure. If the problem persists, contact your Software AG support representative for assistance.

Action The action that should be taken depends on the message text issued with this message number. Review the table above for the appropriate action.

ADAK07 LRVINFO>0 and module REVEXITB not found, processing continues

Explanation During BS2000 TP monitor interface operations, a nonzero LRVINFO parameter value was specified in the ADALNK parameter, but the Adabas Review user exit B (REVEXITB) module could not be found. Program processing continues without REVEXITB.

Action Either specify LRVINFO=0, remove the LRVINFO parameter statement, or include the REVEXITB module in the program.

ADAK070	Adabas T.R.U.E. disabled {module-name}
Explanation	A failure occurred during the execution of the enhanced installation program. The Adabas TRUE (Task Related User Exit) is disabled. The name of the Adabas TRUE module being installed is given in the message (<i>module-name</i>).
Action	Determine the cause of the failure. The reason for the failure may be determined by examining previous messages produced by the ADACIC0 installation program. These messages are written to the JES job log for z/OS and to SYSLOG for z/VSE. For more information please consult your Adabas installation documentation.
ADAK071	Adabas link routine released {module-name}
Explanation	A failure occurred during the execution of the enhanced installation program. The CICS command-level link routine has been released. The name of the Adabas CICS command-level link routine being installed is given in the message (<i>module-name</i>).
Action	Determine the cause of the failure. The reason for the failure may be determined by examining previous messages produced by the ADACIC0 installation program. These messages are written to the JES job log for z/OS and to SYSLOG for z/VSE. For more information please consult your Adabas installation documentation.
ADAK072	GETMAIN for UB-POOL failed EIBRESP: {0000nnnn}
Explanation	The CICS GETMAIN for shared storage for the Adabas user buffer pool failed. The returned value of EIBRESP from the CICS request is printed in hexadecimal at the end of the message.
Action	Consult the appropriate IBM CICS documentation for the meaning of the returned EIBRESP value.
ADAK073	Freemain for UB-POOL failed EIBRESP: {0000nnnn}
Explanation	The storage for the Adabas user buffer pool was not released. The returned value of EIBRESP from the CICS FREEMAIN request is returned at the end of the message.
Action	Consult the appropriate IBM CICS documentation for the meaning of the returned EIBRESP value.
ADAK074	Adabas DBID/SVC table in use is: {table-name}
Explanation	The LGBLSET parameters DYNDBSVC=YES and DBSVCTN= <i>dbid-svc-tbl-name</i> parameters are coded in the CICS link globals table and the named DBID/SVC routing table is found and loaded. The name of the DBID/SVC routing table is given in the message (<i>table-name</i>).
Action	No action is required for this informational message.

ADAK075	REVEXIT2 {client exit address: {address} Not Installed Not Active}
Explanation	This message provides the status of the Adabas Review client exit, REVEXIT2. If a hexadecimal address is listed in the message, the Adabas Review client exit is installed and active. If "Not Installed" is listed in the message, then the Adabas Review client exit is not linked with the globals table used by the TRUE being activated in this phase of the installation. If "Not Active" is listed in the message, the Adabas Review client exit is linked with the globals table, but RVCLNT=NO was coded before the globals table was assembled and the exit is considered inactive.
Action	No action is required for this informational message.
ADAK076	The default Hub-id is: {{hubid} Dynamic}
Explanation	If the Review client exit is installed (see ADAK075), this message is produced during the installation of the Adabas CICS components to indicate the default Adabas Review hub ID that will be used by this client exit. If the numeric hub ID is listed in the message, then this is the target where client records will be sent by default, as specified in the globals table with the REVHID keyword. If "dynamic" is listed in the message instead of a specific hub ID, then no value was given in the globals table and the caller, usually SYSREVDDB, must provide the hub ID to be used by the Adabas Review client exit.
Action	No action is required for this informational message.
ADAK08	Review exit B deactivated. processing continues
Explanation	During BS2000 TP monitor interface operations, LRVINFO=0 was either specified or omitted in the ADALNK parameter or the entire ADALNK parameter service is inactive, and the Adabas Review user exit B (REVEXITB) is present in the user program.
Action	To activate REVEXITB, specify LRVINFO=256; otherwise, no change is necessary.
ADAK080	{nnnn} of {tttt} TRUEs installed
Explanation	This message is issued at the end of ADACIC0 installation processing. It provides the actual number of TRUEs that were successfully installed (<i>nnnn</i>) and identifies the number of TRUE installations that were attempted (<i>tttt</i>).
Action	No action is required for this informational message.
ADAK09	Incompatible versions of ADALNK and ADAL2P, processing aborted
Explanation	During BS2000 TP monitor interface operations, it was determined that the versions of ADALNK and ADAL2P do not match.
Action	Check library assignments; check TSOSLNK/BINDER protocols.

ADAK10**ADUSER {type} for entry {module} RC {rc}****Explanation**

During BS2000 TP monitor interface operations, an error occurred while attempting to access the Adabas link module where *type* is either REQM for requesting memory or BIND for attempting to load; *module* is the name of the module to be accessed; and *rc* is the Fujitsu Technology Solutions macro return code.

Action

If the *type* is

- BIND, check the file link statements for the presence of the Adabas library
- REQM, there is a memory shortage in the application program address space

4 ADAQ* - Adabas Review Hub Messages

ADAQ_{nn} messages are received from the Adabas Review hub.

 **Note:** Each of the messages in this section starts with the relevant database ID.

ADAQ89 **{dbid} POSSIBLE CONFLICT BETWEEN REVIEW HUB AND UEX4.
RAOEXIT DISABLED**

Explanation The Adabas Review hub was enabled by specifying a hub ID on the ADARUN REVIEW parameter. The ADARUN UEX4 parameter was also specified and the user exit 4 module was identified as RAOEXIT, an Adabas Review user exit that is not compatible with the Adabas Review hub. The Adabas nucleus completes its initialization but no calls to user exit 4 are performed by ADALOG.

Action If the UEX4 parameter is left over from a previous conversion, remove the parameter. Otherwise, supply the correct user exit 4 module name.

ADAQ90 **{dbid} REVIEW HUB INACCESSIBLE BECAUSE REVIEW HUB ID WAS NOT
SPECIFIED**

Explanation The value specified for the Adabas Review hub was invalid. The Adabas nucleus completes its initialization but no calls are made to the Adabas Review hub.

Action Specify the correct Adabas Review hub ID value and restart the nucleus.

ADAQ91 **{dbid module-name} MONITORING SYSTEM INITIALIZATION FAILED.
SEE ERROR MESSAGES**

Explanation The specified monitoring system component returned a nonzero status. Any failure of this sort should be accompanied by error messages displayed by the monitoring system. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.

Action Check the monitoring system error messages, correct the cause of the error, and restart the nucleus.

ADAQ92	{dbid module-name} MONITORING SYSTEM WAS NOT LOADED. CONTACT YOUR VENDOR
Explanation	The specified monitoring system component could not be loaded. It is possible that the load library containing the expected module was not specified in the nucleus' job stream. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Correct the cause of the error and restart the nucleus.
ADAQ93	{dbid module-name} MONITORING MAY BE INCOMPLETE BECAUSE ADALOG IS NOT LOADED.
Explanation	The command logging module ADALOG was not loaded. The monitoring system will not be able to process any command log records. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Correct the cause of the error and restart the nucleus
ADAQ94	{dbid module-name} IS AN INCORRECT VERSION LEVEL. CONTACT YOUR VENDOR
Explanation	The specified module is at an incorrect version level and cannot be used with this version and/or SM-level of Adabas. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Contact your monitoring system vendor to determine if the correct module is being used or supplied.
ADAQ95	{dbid module-name} DOES NOT HAVE THE CORRECT PIM. CONTACT YOUR VENDOR
Explanation	The specified module is incompatible with this version and/or SM-level of Adabas. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Contact your monitoring system vendor to determine if the correct module is being used or supplied.
ADAQ96	{dbid module-name} CANNOT MONITOR IOR CALLS AT THIS TIME. UNUSUAL ERROR
Explanation	Adabas cannot give control to the specified monitoring system module for purposes of monitoring I/O activity. The Adabas system-dependent interface module was not properly loaded. The Adabas nucleus completes its initialization but no calls are made to the monitoring system.
Action	Note the error message number and module name and call your Software AG technical support for assistance.

ADAQ99	{dbid} REVIEW HUB ID EQUAL TO ADABAS DBID IS NOT PERMITTED. REVIEW HUB INACCESSIBLE
Explanation	The specified Adabas Review hub ID value is identical to the value specified for the DBID parameter. The Adabas Review hub cannot have the same target ID as that of the Adabas nucleus. The Adabas nucleus completes its initialization but no calls are made to Adabas Review.
Action	Correct the hub ID value on the REVIEW parameter and restart the nucleus.

5

AREV* - Adabas Review Hub Messages

AREV01	{hub-id} ADAREV HUB Vv.r.s COMING UP
Explanation	The Adabas Review hub session initialization is in progress.
Action	None required. This message is for your information only.
AREV02	{hub-id} ADAREV HUB IS A C T I V E
Explanation	The Adabas Review hub system has successfully initialized.
Action	None required. This message is for your information only.
AREV03	{hub-id} ADAREV HUB IS C L O S E D
Explanation	The Adabas Review hub system has completed its session close processing.
Action	None required. This message is for your information only.
AREV04	{hub-id} OPERCOM: {command}
Explanation	The Adabas Review hub repeats the operator command before continuing.
Action	None required. This message is for your information only.
AREV05	{hub-id} OPERCOM COMPLETED
Explanation	The issued command was processed by the Adabas Review hub.
Action	None required. This message is for your information only.

AREV06 **{hub-id} NO REQUESTS ARE PRESENTLY QUEUED**
{hub-id nnn} REQUESTS ARE PRESENTLY QUEUED

Explanation This message is displayed in response to the DNC operator command. *nnn* indicates the number of command queue elements queued for processing by the Adabas Review hub.

This message is also displayed in response to a DCQ operator command in the event that there are no command queue elements waiting to be processed.

Action None required. This message is for your information only.

AREV07 **{hub-id nnn} NEXT EXPECTED SEQUENCE NUMBER**
{hub-id cqe-seq-num cqe-job-name cqe-user-id (xxx) cmd ffss}

Explanation This message is displayed in response to the DCQ operator command. The first message displays the expected sequence number *nnn* that shows which numbered command queue element is in line to be processed next. The following information is displayed for each command queue element:

<i>cqe-seq-num</i>	sequence number of the command queue element.	
<i>cqe-job-name</i>	job name of the Adabas being monitored.	
<i>cqe-user-id (xxx)</i>	user ID of the Adabas being monitored followed by the value in displayable character hex.	
<i>cmd</i>	Adabas command used for this request.	
<i>ff</i>	CQE status flags in hexadecimal:	
	x'20'	waiting for 16-call
	x'10'	16-call required
	x'08'	attached buffers
<i>ss</i>	more CQE status flags in hexadecimal:	
	x'80'	in process
	x'40'	ready to be selected

Action None required. This message is for your information only.

AREV08 **{hubid} ENQUEUE ON HUB {hubid} SVC {svc} FAILED**

Explanation An Adabas Review hub is started with the hub ID and SVC listed in the message, but another hub with that hub ID and SVC is already running. The new Adabas Review hub comes down.

Action Determine why one Adabas Review hub was started while another hub with the same ID was already running.

AREV70	{hub-id} TOTAL CQE USED: {uuuuu} OF {ttttt}
Explanation	This message is displayed when the Adabas Review hub is terminated. <i>uuuuu</i> is the total number of CQEs used by the hub; <i>ttttt</i> is the total number of CQEs allocated by the hub.
Action	None required. This message is for your information only.
AREV80	{hub-id} REVIEW PARAMETER IS MISSING
Explanation	An attempt was made to start a hub database, but the hub ID has not been specified in the <code>REVIEW</code> parameter.
Action	Specify the hub ID on the <code>ADARUN REVIEW</code> parameter and restart the hub database.
AREV81	{hub-id} MPM-24 CALL FAILED
Explanation	The Adabas Review hub was unable to establish interregion communication. Adabas Review terminates processing.
Action	Identify and correct the error.
AREV82	{hub-id} MPM-00 CALL FAILED
Explanation	The Adabas Review hub was unable to establish interregion communication. Adabas Review terminates processing.
Action	Identify and correct the error.
AREV83	{hub-id} IDTE FOR THIS HUB IS NO LONGER ACTIVE
Explanation	The ID table element for the hub is no longer marked as being in use by this Adabas Review. It is probable that another target (Adabas, Adabas Review, etc.) was initialized using the same DBID / Adabas Review hub ID with the <code>FORCE=YES</code> parameter. Adabas Review terminates processing.
Action	If another target was inadvertently initialized, quiesce and terminate the target and restart Adabas Review. To prevent such problems, ensure that the <code>FORCE=YES</code> parameter is not used for target initialization unless absolutely necessary.
AREV84	{hub-id} USER GONE ON MPM-8 CALL
Explanation	The Adabas Review hub tried to process a request but the addressed data area was not addressable, or no longer contained recognizable data. This error occurred while Adabas Review was receiving the request (router-08 call processing). It is probable that the client nucleus was terminated while it was sending the request to Adabas Review.
Action	None required. Adabas Review cannot process this request so it is cleared from the queue.

AREV86	{hub-id} INTERREGION COMMUNICATION COULD NOT BE ESTABLISHED
Explanation	The Adabas Review hub was unable to establish interregion communication due to an unexpected response returned from ADAMPM. Adabas Review terminates processing.
Action	Check for system messages from ADAMPM that could identify the error. If the error cannot be identified, keep all dumps, messages, and other related information and contact your Software AG support representative.
AREV87	{hub-id} OPERATOR COMMUNICATIONS COULD NOT BE ENABLED
Explanation	The Adabas Review hub could not establish operator communications. Adabas Review terminates processing.
Action	Identify and correct the error.
AREV88	{hub-id} TIMER SERVICES COULD NOT BE INITIALIZED
Explanation	The Adabas Review hub was unable to establish STIMER services. Adabas Review terminates processing.
Action	Identify and correct the error.
AREV89	{hub-id} CORRUPTED CQE ARRIVED
Explanation	A command has arrived at the Adabas Review Hub, but when it was selected for processing it was not in an acceptable state. This indicates a logic error.
Action	Contact your Software AG technical support representative for assistance.
AREV90	{hub-id} GETMAIN FAILURE, SIZE= {requested-getmain-size}
Explanation	The Adabas Review hub was unable to obtain the necessary GETMAIN space to operate. Adabas Review terminates processing. It is probable that the specified region size is too small, or the default region size is too small. SIZE is the requested GETMAIN size that could not be obtained.
Action	Increase the region size for Adabas Review and restart.
AREV91	{hub-id} MISSING OR INCOMPATIBLE REVIEW COMPONENT
Explanation	The Adabas Review hub could not load the module REVHUB or the REVHUB module that was loaded is not the correct version or SM-level. Adabas Review terminates processing.
Action	Locate the correct REVHUB module, ensure that the module is accessible by Adabas Review, and restart Adabas Review.

AREV92	{hub-id} BREAK DETECTED IN SEQUENCE NUMBERS {hub-id} EXPECTED SEQUENCE NUMBER {xxxxx} {hub-id} RECEIVED SEQUENCE NUMBER {yyyyy}
Explanation	The Adabas Review hub processes the requests in the order that the numbered requests are received. This means that Adabas Review always knows the next number in sequence that should be received. If there is a discrepancy, this message is displayed along with the expected sequence number and the sequence number actually received. A skipped or missing sequence number can indicate that a request has been dropped by the router. Adabas Review continues processing.
Action	Lost requests may indicate that the hub is overloaded. Check the client nuclei for nonzero response codes received from the hub. In some cases, the number of commands (NC) parameter needs to be increased to accommodate the load from the client nuclei. Otherwise, divide up the Adabas Review monitoring work load on multiple hubs.
AREV93	{hub-id} ERROR IN REQUEST: {command}
Explanation	Either the specified operator command was invalid or incorrectly entered. Adabas Review ignores this operator command.
Action	Ensure that the command syntax is valid, and retry the command.
AREV94	{hub-id} REVIEW NUCLEUS SESSION OPEN FAILURE
Explanation	The Adabas Review nucleus returned a non-zero status during initialization.
Action	Check all messages displayed by the Adabas Review nucleus, correct any errors, and restart Adabas Review.
AREV95	{hub-id} INCOMPATIBLE ADAMPM MODULE, CONTACT SUPPORT CENTER
Explanation	The ADAMPM module is not compatible with this version/release of Adabas Review. It is probable that the wrong Adabas load library, SM-level, or version is being used. Adabas Review terminates processing. It is probable that the wrong Adabas load library is being used.
Action	Locate the correct ADAMPM module, ensure that the module is accessible by Adabas Review, and restart Adabas Review. If the problem persists even with the correct ADAMPM module, contact your Software AG technical support representative.
AREV99	{hub-id} ADAREV HUB ABNORMALLY TERMINATED
Explanation	The Adabas Review hub is terminating due to a previous error.
Action	Correct any errors and restart Adabas Review.

6 ARMT* - Adabas Review Interface Messages

ARMT01	{dbid} GETMAIN FAILURE, SIZE {requested-getmain-size}
Explanation	A request for storage in the Adabas nucleus failed.
Action	Either determine what is using so much storage in the Adabas nucleus and correct the problem; or increase the available storage.
ARMT02	{dbid} ATTACH ADARST FAILURE, STRS {nn}
Explanation	The Adabas nucleus was unable to attach the subtask ADARST. STRS is the ADAIOR response code.
Action	Probably, the module ADARST is missing.
ARMT03	{dbid} CLOG TOO BIG, CLOG NOT SENT
Explanation	When an ADABAS nucleus runs Adabas Review in hub mode, the CLOG inclusive CLOG extension and control information may be bigger than around 32K. This CLOG record is not sent to the Adabas Review hub. This message is only issued one time.
Action	One of the buffers may be too big. For instance, you may set LOGRB=NO.
ARMT04	{dbid} ATTACH OF ADARST SUCCESSFUL
Explanation	The subtask ADARST was attached successfully. The database will send data to the Adabas Review hub.
Action	No action is required for this informational message.

ARMT05	{dbid} DETACH OF ADARST SUCCESSFUL
Explanation	The subtask ADARST was detached successfully.
Action	Once you have corrected the error that led to detachment of ADARST, you can reactivate the subtask using the ADARUN parameter <code>REVIEW=hubid</code> . The successful ATTACH will be acknowledged with message ARMT04. A restart of the database is in this case not necessary. If the subtask abends a second time, it will be deactivated completely and message ARST10 will be given.
ARMT06	{dbid} Review suspended, buffer unavailable. REVIEW parameter is set to NO.
Explanation	ADARMT is experiencing a temporary buffer shortage. The ADARUN parameter REVIEW is set to NO.
Action	To activate Review again, change the ADARUN REVIEW parameter.
ARMT07	{dbid} Review resumed, {nn} CLOG records skipped
Explanation	Buffers have become available after the shortage noted by message ARMT06. The number of CLOG records skipped during the shortage is given in the message (<i>nn</i>).
Action	No action is required for this informational message.
ARMT08	{dbid} Review suspended, subtask unable to initialize
Explanation	The subtask ADARST did not initialize. ADARST is detached and message ARMT05 appears. All Adabas Review processing from this nucleus is suspended.
Action	If you can correct the error that led to the initialization failure of ADARST, you can reactivate the subtask using the operator command <code>REVIEW=hubid</code> . The successful ATTACH will be acknowledged with message ARMT04. In this case, a restart of the database is not necessary. Notify your Software AG technical support representative if you are unable to resolve the initialization failure.

7

ARST* - Adabas Review Interface Messages

ARST01	{dbid} GETMAIN failure, size= {requested-getmain-size}
Explanation	A request for storage in the Adabas nucleus subtask ADARST failed.
Action	Either determine what is using so much storage in the Adabas nucleus and correct the problem; or increase the available storage.
ARST02	{dbid} LOAD FAILED FOR MODULE {module}
Explanation	The specified module cannot be loaded.
Action	Probably, the requested load module is missing.
ARST06	{dbid} Adabas Review subtask statistics {dbid} Buffers in: {count} Buffers out: {count} {dbid} UEX5 calls: {count} Timer calls: {count} posts: {count}
Explanation	This message displays ADARST shutdown statistics.
Action	None required. This message is for information only.
ARST07	{dbid} Error in Trans-port call. Review parameter set to NO
Explanation	An abend occurred in the ADARST subtask of an Adabas nucleus. The abend did occur in the Adabas Review Trans-port routine. To avoid subsequent failures, the ADARUN REVIEW parameter is switched from a hub ID to "NO." The Adabas Review hub is no longer active for the Adabas nucleus.
Action	Check the abend and contact your Software AG technical support representative. If necessary, try switching the ADARUN REVIEW parameter to a hub ID again.

ARST08	{dbid} Error in a non Trans- port routine. Review parameter set to NO
Explanation	An abend occurred in the ADARST subtask of an Adabas nucleus. The abend did not occur in the Adabas Review Trans- port routine. To avoid subsequent failures, the ADARUN REVIEW parameter is switched from a hub ID to "NO". The Adabas Review hub is no longer active for the Adabas nucleus.
Action	Check the abend and contact your Software AG technical support representative. If necessary, try switching the ADARUN REVIEW parameter to a hub ID again.
ARST09	{dbid} Subtask ADARST detached
Explanation	The subtask ADARST was detached for one of the following reasons: <ul style="list-style-type: none"> ■ An error occurred when accessing the Adabas Review hub ■ The Adabas Review hub returned Adabas response code 148 (ADARSP148 - not active) <p>As long as the subtask is not attached, this database will not send data to the Adabas Review hub.</p>
Action	If the reason for the detachment is an unjustified Adabas response code 148 (ADARSP148), contact your Software AG technical support representative for assistance.
ARST10	{dbid} Unrecoverable abend in subtask ADARST
Explanation	The subtask ADARST abended either due to an unrecoverable abend or to the second call of the ESTAE (in this case see previous ARST _{xx} messages). <p>The subtask is deactivated and the database will not send data to the Adabas Review hub.</p>
Action	It is not possible to reactive the subtask using the ADARUN REVIEW= <i>hubid</i> parameter. You must restart the database to reactivate Adabas Review.
ARST11	{dbid} Abend S0D6 occurred {nnnnn} Possibly the REVIEW hubid = {hhhhh} ended abnormally.
Explanation	This error messages can only occur in an Adabas nucleus, if an Adabas Review hub is installed using the Trans- port feature. For some reason the PC number for the PC call is invalid. <p>The ARST07 message is issued and the ADARUN REVIEW parameter is set to NO.</p>
Action	Determine the reason for the abend S0D6. It is likely that the Adabas Review hub has abended. If necessary, contact you Software AG support representative for further assistance.

8

ARVU* - Adabas Review Interface Messages

ARVU01 **{dbid} GETMAIN FAILURE, SIZE= {requested-getmain-size}**
Explanation ADARVU was unable to obtain the necessary GETMAIN space to operate. ADARVU terminates processing. It is probable that the specified region size is too small, or the default region size is too small. SIZE is the requested GETMAIN size that could not be obtained. The Adabas nucleus completes its initialization but no calls are made to the Adabas Review hub.

Action Increase the region size for Adabas and restart the nucleus.

Under BS2000 increase/add the ADARUN parameter SUBMPSZ=140000000.

ARVU02 **{dbid} REVIEW HUB ID={ target-id} LOG RETD RSP {rsp}**
 {dbid} REVIEW HUB ID= {target-id} CLS RETD RSP {rsp}
 {dbid} REVIEW HUB ID= {target-id} OPN RETD RSP {rsp}
Explanation A non-zero Adabas response was received from the Adabas Review hub with the specified target ID when ADARVU sent one of the following requests:

LOG	request to process a command log record.
CLS	close call to terminate monitoring services with the hub.
OPN	open call to establish monitoring services with the hub.

Action Identify the problem from the Adabas response code. If the problem is parameter settings in the hub, i.e., attached buffer size or command queue size, then the Adabas Review hub must be cycled to reset the parameters. If the Adabas response code 148 (ADARSP148) was received, the Adabas Review hub may have been terminated.

ARVU03	{dbid} REVIEW REVIEW HUB ID {target-id} IS NOT A HUB SERVER
Explanation	The target ID specified on the REVIEW parameter is not an Adabas Review hub. The target may be another Adabas nucleus. The Adabas nucleus completes its initialization but no calls are made to the Adabas Review hub.
Action	Ensure that the REVIEW parameter specifies the correct target ID of an Adabas Review hub and restart the nucleus.
Action	The operator command REVIEWHUBID= <i>hub-id</i> may be used to change the value to a another target ID.
ARVU04	{dbid} REVIEW REVIEW HUB ID {target-id} IS NOT ACTIVE
Explanation	ADARVU received response code 148 (ADARSP148) on a request call to the Adabas Review hub. This message is displayed in conjunction with the AREV02 message.
Action	Start the appropriate Adabas Review hub.
ARVU05	{dbid} UEX5: REQUESTED WAIT FOR {nnnnn} SECONDS {dbid} UEX5: INVALID REQ ({xx}), IGNORE ASSUMED
Explanation	On any error condition, ADARVU calls user exit 5 if present. User exit 5 may return one of three possible service requests: <ol style="list-style-type: none"> 1. Wait for <i>nnnnn</i> seconds, after which ADARVU will resend the request to the Adabas Review hub. 2. Ignore the non-zero response received from the Adabas Review hub and to continue processing. 3. Immediately resend the request to the Adabas Review hub. <p>The message displays the service request received from the user exit 5. If an unknown request is received from the user exit, the request is ignored and processing continues.</p>
Action	None required, unless the fourth message is displayed. The INVALID REQ message indicates a problem with the user exit 5. Correct the problem and restart the Adabas nucleus, when possible.
ARVU06	{dbid} CHECK ADABAS MESSAGES AND CODES MANUAL
Explanation	This message is displayed in conjunction with the AREV02 message in the event that the non-zero response received by ADARVU is not a RSP 148.
Action	None required. This message is for your information only.

ARVU07	{dbid} SESSION OPEN FAILURE, MODULE {module} COULD NOT BE LOADED
Explanation	The specified module was not found in the load library and could not be loaded. The Adabas nucleus completes its initialization but no calls are made to the Adabas Review hub.
Action	Ensure that the correct load libraries are specified for the Adabas job and restart the Adabas nucleus.
ARVU08	{dbid} NUMBER OF NON-ZERO RESPONSES FROM HUB IS {count}
Explanation	Whenever an unexpected response is received by ADARVU, the count of the number of non-zero responses is incremented and this message is displayed.
Action	None required. This message is for your information only.
ARVU09	{dbid} USER EXIT 5 {AVAILABLE UNAVAILABLE}
Explanation	During session initialization, ADARVU checks if a user exit 5 has been loaded. This message displays whether the user exit 5 was located or not.
Action	None required. This message is for your information only.
ARVU10	{dbid} REVIEW HUB {hub-id} VERSION V{nn} LOCATED
Explanation	During session initialization, ADARVU issues a call to the specified Adabas Review hub. When a successful connection is established, this message is displayed.
Action	None required. This message is for your information only.
ARVU11	{dbid} CHANGE ORDERS FROM REVIEW HUB {hub-id}
Explanation	The Adabas Review hub notified the client nucleus that it changed the monitoring or reporting status of the client nucleus. ADARVU then displays this message accompanied by the ARVU13 message set.
Action	None required. This message is for your information only.
ARVU12	{dbid} REVIEW HUB ID CHANGED FROM {hub-id} TO {hub-id}
Explanation	ADARVU detected that the hub-id specified in the REVIEW parameter was changed dynamically by an operator command.
Action	None required. This message is for your information only.

ARVU13

{dbid text}

Explanation

Possible message texts:

Message Text (<i>text</i>)	Description
{NO <i>count</i> } REVIEW REPORT(S) STARTED	In conjunction with the ARVU11 message, this message indicates the status of information transmitted from the client nucleus to the hub. If no Adabas Review report(s) are started, ADARVU does not send data to the hub. If there is at least one report started, then ADARVU transmits the command log data to the hub. <i>Action:</i> No action required. This message is for your information only.
{NO <i>count</i> } REPORTS REQUIRES BUFFERS	If at least one report requires buffers, ADARVU transmits the requested Adabas control buffer data in addition to the command log data. The <i>count</i> indicates the number of started reports and/or the number of reports requiring buffers. <i>Action:</i> No action required. This message is for your information only.
REVIEW HUB TRANSPORT INITIALIZED, MEMORY <i>mmmmmmmm</i>	BS2000: The hub started Adabas Review Trans- port with the memory <i>mmmmmmmm</i> . <i>Action:</i> No action Required. This message is for your information only.
RTPINIT, CANNOT GET HEADER, SIZE <i>sssssss</i> , MEMORY <i>mmmmmmmm</i>	BS2000: The hub cannot acquire an Adabas Review Trans- port header of size <i>sssssss</i> using memory <i>mmmmmmmm</i> . <i>Action:</i> Check memory allocation parameters in use in the Adabas Review Hub. Otherwise contact SAG Support.
RTPINIT, COULD NOT ESTABLISH EXIT FOR RTPTERM - RC <i>rrrrrrrr</i>	BS2000: The RTPTERM exit module could not be established in the Hub's task. <i>Action:</i> Send Hub output protocol to SAG Support.
RTPINIT, REVIEW HUB COULD NOT BE FOUND IN IDT	BS2000: The hub has not successfully registered with the ID Table. The IDT is a table of databases or nodes still active in the system. <i>Action:</i> Check in the output protocol for other error messages from the Adabas MPM. Otherwise contact SAG support.
RTPSSPC, HEADER HAS <i>xxxxxxx</i> AND DBID <i>ddddddd</i>	BS2000: The stored Adabas Review Trans- port header has an ID that is different from the one in the request. This header exists in a common memory pool and should

Message Text (<i>text</i>)	Description
	<p>have an eyecatcher of ADAPCTRA and the Hub's dbid. This doesn't check.</p> <p><i>Action:</i> Contact Software AG Support with dump and protocol information.</p>
RTPSSPC, REVIEW HUB COULD NOT BE FOUND IN IDT	<p>BS2000: The nucleus tried to access a hub with a DBID that is unknown to the system. The IDT is a table of databases or nodes still active in the system.</p> <p><i>Action:</i> Use the Utility IDTLOOK to check for active IDs in the table. Check also on the use of the GROUPS=NO/YES parameter. Otherwise, contact SAG support.</p>
RTPSSPC, REVIEW HUB <i>hubid</i> HAS BEEN REMOVED FROM THE IDT	<p>BS2000: The hub ID requested is no longer active.</p> <p><i>Action:</i> Use the Utility IDTLOOK to check for active IDs in the table. Check also on the use of the GROUPS=NO/YES parameter. Otherwise contact SAG support.</p>
THE FOLLOWING BUFFER TYPES ARE REQUIRED: <i>buffer-type-codes</i>	<p>If buffers are required, the required buffer types are listed in the message. The possible buffer type codes can be F (format buffer), R (record buffer), S (search buffer), V (value buffer), M (multifetch buffer), or I (ISN buffer).</p> <p><i>Action:</i> Verify that the correct buffers are specified. Otherwise, no action is required for this informational message.</p>
TRANSPORT INITIALIZED, MEMORY <i>mmmmmmmm</i>	<p>BS2000: The nucleus accessed the hub through the Adabas Review Transport and uses the common memory defined by mmmmmmmmm.</p> <p><i>Action:</i> No action required. This message is for your information only.</p>

ARVU14**Explanation**

{dbid} UNEXPECTED CHANGE ORDER FROM HUB {hub-id} IS IGNORED.

ADARVU received a change order from an Adabas Review hub that is not the hub to which ADARVU is currently sending data. This may happen if another hub is initialized that has started reports for the client nucleus. ADARVU ignores the change order.

Action

Find out what has issued the strange change order.

ARVU16	{dbid} REVIEW IS ACCEPTING BUFFERED CLOG RECORDS
Explanation	The Adabas Review hub accepts buffered CLOG records from the client nucleus as a way of reducing the number of cross-memory calls from the client nucleus to the hub.
Action	None required. This message is for your information only.
ARVU17	{dbid} REVIEW IS NOT ACCEPTING BUFFERED CLOG RECORDS
Explanation	The Adabas Review hub is not accepting buffered CLOG records from the client nucleus.
Action	Check the job log of the Adabas nucleus and the Adabas Review hub, why the Adabas Review hub refuses to accept buffered CLOG records.
ARVU18	{dbid} REVIEW TRANS-PORT IS INSTALLED USING PC {pc-number}
Explanation	z/OS only. The Adabas nucleus runs with the Adabas Review Trans-port feature when sending CLOG records to the Adabas Review hub.
Action	None required. This message is for your information only.
ARVU19	{dbid} REVIEW TRANS-PORT IS NOT INSTALLED
Explanation	BS2000 and z/OS only. The Adabas Review Trans-port feature is not installed.
Action	If this Adabas nucleus should run with the Adabas Review trans-port feature, check the job log of the Adabas nucleus and the job log of the Adabas Review hub why trans-port is not installed.
ARVU20	{dbid} REVIEW MODULES NOT FOUND, LOGCLEX PARAMETER IS SET TO NO
Explanation	ADARUN LOGCLEX=YES has been specified, but no Adabas Review modules are available. The Adabas nucleus changed the LOGCLEX parameter to ADARUN LOGCLEX=NO. The extended information is made available for the purpose of running Adabas Review in batch mode.
Action	Please make the Adabas Review modules available in the STEPLIB.
ARVU21	{dbid} ADAIOR REQUEST FAILED: FUNC {ff} RSP {rr}
Explanation	A request to the Adabas ADAIOR interface by the Pulse failed.
Action	Retain all dumps, messages, and other related information; contact your Software AG technical support representative.

ARVU22	{dbid} GETMAIN FAILED: INSUFFICIENT STORAGE
Explanation	A request for storage by the Pulse failed. The report is not started.
Action	Increase the region size for Adabas and restart the nucleus.
ARVU23	{dbid} INTERNAL ERROR IN {module}
Explanation	An internal error has occurred in the given Pulse module. The report is not started.
Action	Retain all dumps, messages, and other related information; contact your Software AG technical support representative.
ARVU24	{dbid} CLUSTER SERVICES NOT ACTIVE
Explanation	The Pulse has determined that Cluster Services statistics reporting is not possible. The report is not started.
Action	Ensure that Cluster Services is active.
ARVU25	{dbid} ADABAS RSPCODE {rsp} RETURNED FROM DBID = {dbid}
Explanation	The Pulse has encountered the given Adabas non-zero response code. The report is deactivated.
Action	Identify the problem from the Adabas response code.
ARVU26	{dbid} PULSE ESTAE DRIVEN, RETRY IN PROGRESS
Explanation	The Pulse subtask has encountered an error and will attempt to recover.
Action	None.
ARVU27	{dbid} PULSE RECOVERY ATTEMPT FAILED
Explanation	The Pulse subtask attempt at error recovery failed. The report is deactivated.
Action	Retain all dumps, messages, and other related information; contact your Software AG technical support representative.
ARVU28	{dbid} Pulse task failed to attach
Explanation	The Pulse subtask could not be attached. The report is deactivated.
Action	Retain all dumps, messages, and other related information; contact your Software AG technical support representative.

ARVU29	{dbid} Pulse task now {active inactive}
Explanation	The Pulse has stopped or started.
Action	None.
ARVU30	{dbid} Invalid Pulse interval, default used
Explanation	The Pulse detected an invalid timer interval. The acceptable range is from 1 to 1440 minutes. The default interval of 15 minutes is used.
Action	Restart the report with a valid timer value.
ARVU31	{dbid} Pulse ended due to non-zero RSP codes
Explanation	The Pulse detected three non-zero Adabas response codes. The report is deactivated.
Action	Correct the cause of the non-zero response codes and restart the report.
ARVU32	{dbid} CLOG too big, No CLEX attached
Explanation	The length of CLOG and CLOG extension exceeds 65K. The CLOG extension is not attached. This message is only issued one time.
Action	An internal error occurred. Contact Software AG support.
ARVU33	{dbid} REVIEW hub CPU id different.
Explanation	This message is issued when the CPU ID of the Adabas nucleus and the CPU ID of the Adabas Review hub are different. When this happens, CLOG records to the Adabas Review hub cannot be sent via the Trans-port PC call, but must be sent via the Adabas router. The performance of the Adabas router sending mechanism is slower than the performance of Trans-port.
Action	No action is required for this informational message.
ARVU34	{dbid} REVIEW = ADABAS DBID not allowed. REVIEW = NO set.
Explanation	The ADARUN parameters DBID and REVIEW specify equivalent DBID values. The REVIEW parameter is set to NO.
Action	Specify the correct REVIEW parameter. This can be done online.
ARVU35	{dbid} ONLY CLOGLAYOUT=5/8 permitted
Explanation	There are no valid Adabas modules available which can convert CLOGLAYOUT=8 records for Adabas Review.
Action	Specify an Adabas load library from version 8.1 SP3 or later in your Adabas nucleus job.

ARVU38	<p>{dbid} REVIEW record filtering started. {dbid} REVIEW record filtering stopped. {dbid} Records processed: {nnnnnnnnnn} {dbid} Records filtered: {nnnnnnnnnn}</p>
Explanation	<p>The status of record filtering has changed. When filtering is stopped, the number of command log records processed thus far by the filter is printed, as well as the number of records filtered from Review processing.</p>
Action	<p>None required. This message is informational only.</p>
ARVU40	<p>{dbid} {xx} BUFFER TRUNCATED</p>
Explanation	<p>Every field which could be processed by REVIEW has an indication (or attribute) whether a particular Adabas buffer (FB, RB, SB, VB, IB, MB, PB) is necessary for REVIEW to process this field. These indications (or attributes) are gathered for each report running and the indications (or attributes) for all running reports are gathered and Adabas is informed which Adabas buffers are requested by REVIEW.</p> <p>When Adabas sets up a command log record for REVIEW, it checks these indications in order to build the command log record with or without a particular Adabas buffer. During this process Adabas (ADARVU) checks whether the length of the actual Adabas buffer confirms the ADARUN parameter REVLOGBMAX. If the value is violated the first time, the ARVU40 message is issued.</p>
Action	<p>The relevant buffer is truncated. If necessary increase the value of REVLOGBMAX or deselect fields which require Adabas buffers.</p>
ARVU41	<p>{dbid} BUFFER IGNORED</p>
Explanation	<p>Every field which could be processed by REVIEW has an indication (or attribute) whether a particular Adabas buffer (FB, RB, SB, VB, IB, MB, PB) is necessary for REVIEW to process this field. These indications (or attributes) are gathered for each report running and the indications (or attributes) for all running reports are gathered and Adabas is informed which Adabas buffers are requested by REVIEW.</p> <p>When Adabas sets up a command log record for REVIEW, it checks these indications in order to build the command log record with or without a particular Adabas buffer. During this process Adabas (ADARVU) checks whether the length of the actual Adabas buffer confirms the ADARUN parameter REVLOGMAX. If the value is violated the first time, the ARVU41 message is issued.</p>
Action	<p>Buffers are ignored. If necessary increase the value of REVLOGBMAX or deselect fields which require Adabas buffers.</p>

ARVU42	dbid REVIEW HUB {hub-id} VERSION V{nn} NOT SUPPORTED
Explanation	During session initialization, ADARVU issues a call to the specified Adabas Review hub, running with version <i>Vnn</i> . This version is not supported; the version number is either too low or too high. The handshake command to the hub did not work, so Adabas Review will not collect any data.
Action	Start the Adabas Review hub with the appropriate version. For information about version compatibility, read <i>Adabas and Adabas Review Version Compatibility</i> , in the <i>Adabas Review Release Notes</i> .
ARVU43	{dbid} Storage keys of nucleus and hub are different.
Explanation	The storage keys of the Adabas nucleus and of the Adabas Review hub are different. Both address spaces must run under storage keys 0 or storage keys 8.
Action	Start Adabas nucleus and Adabas Review hub under the same key, i.e. storage key 0 or storage key 8.
ARVU45	{dbid} ADABAS REVIEW Main Task Statistics {dbid} Hub mode log records {n,nnn,nnn,nnn} {dbid} Local mode log records {n,nnn,nnn,nnn} {dbid} Log record filtering {dbid} Records processed {n,nnn,nnn,nnn} {dbid} Records filtered {n,nnn,nnn,nnn} {dbid} Largest log record {nn,nnn} {dbid} Successful Hub calls {n,nnn,nnn,nnn} {dbid} Unsuccessful Hub calls {n,nnn,nnn,nnn} {dbid} Storage keys of nucleus and hub are different.
Explanation	This message displays shutdown statistics for the Adabas Review components in the Adabas nucleus. ADARVU reports: <ul style="list-style-type: none">■ The number of log records processed while in Hub mode■ The number of log records processed while in Local mode■ The number of log records processed while record filtering was active■ The number of log records filtered from Review processing■ The size (in bytes) of largest log record■ The number of successful calls and Trans-Port sends to the Review Hub■ The number of unsuccessful calls and Trans-Port sends to the Review Hub
Action	None required. This message is informational only.

9

LNKRVX* Adabas Review Link Routine Messages

LNKRVX090	Enhanced Review processing terminated
Explanation	This message is issued after an error is detected when the link routine attempts to initialize the environment for Review exits. The reason for the failure is provided by one or more previously issued message or messages.
Action	Review other previously issued messages to determine the cause of the error.
LNKRVX091	GETMAIN failed for Review exit work area
Explanation	The storage for the REVEXIT1 (REVEXITB) work area was not available. No Adabas Review processing is possible for this task or job step.
Action	Contact your Software AG technical support representative for assistance.
LNKRVX092	GETMAIN failed for REVEXIT2 work area
Explanation	The storage required to support REVEXIT2 client monitoring is not available. Client monitoring will not be possible but standard REVEXIT1 (REVEXITB) processing may be possible.
Action	Contact your Software AG technical support representative for assistance.
LNKRVX093	Primary Revexit work area header invalid
Explanation	The header for the primary Adabas Review work area appears to be invalid. Adabas Review processing cannot continue.
Action	Contact your Software AG technical support representative for assistance.

LNKR VX094	REVEXIT2 work area invalid
Explanation	The work area for REVEXIT2 (client monitoring) appears to be invalid or corrupted. Adabas Review client monitoring cannot continue.
Action	Contact your Software AG technical support representative for assistance.
LNKR VX095	Handshake with Review Hub: {hub-id} failed RSP: {rc} Sub: {sc}
Explanation	The handshake to establish communication with the Adabas Review hub listed in the message (<i>hub-id</i>) failed with the Adabas response code (<i>rc</i>) and the Adabas subcode (<i>sc</i>) given in the message. Adabas Review client monitoring cannot continue for this task or job step.
Action	Evaluate the returned Adabas response code and subcode to determine the action to take to correct the issue. For example, if the Adabas response code is 148, ensure that the specified Adabas Review hub is up and running.
LNKR VX096	Review monitoring is {ON OFF}
Explanation	This message indicates the new or current state of Adabas Review client monitoring. It is issued in response to a request from SYSREVD B to activate or deactivate client monitoring for the Adabas link routine.
Action	No action is required for this informational message.
LNKR VX097	PC number zero after V4 call, Transport not active
Explanation	The handshake to establish communications between the link routine, REVEXIT2 and the Adabas Review hub has failed because the Adabas Review Trans- port software is not running.
Action	Restart the Adabas Review Trans- port software.

10 Adabas Review 00xxx Messages

REV00MNF **Message {msg-id} not found in {logon-id}**
Explanation A message inquiry was made for a message number that is not known to Adabas Review. This will happen if an invalid message number is entered.
Action If the message number is for an Adabas Review message, contact your Software AG technical support representative.

REV00001 **Welcome to Adabas Review V {v.r.s} running under {tp-monitor}**
Explanation This message welcomes users to Adabas Review and indicates the environment under which they are running.

v.r.s	the version, revision, and SP level.
tp-monitor	the active TP monitor.

Action This message is for information only.

REV00002 **Review command must begin with subsystem code**
Explanation An invalid command was entered from the Adabas Review main menu. All commands from the main menu must begin with a subsystem code as shown on the screen.
Action Enter a valid command.

REV00003 **THIS FIELD IS NOT ALLOWED FOR DETAIL REPORTS**
Explanation The specified field is not allowed for detailed reports.
Action Remove the incorrect field.

REV00004	Enter Review command
Explanation	Adabas Review is waiting for terminal input.
Action	Press a valid PF key or enter an Adabas Review command.
REV00005	Invalid command
Explanation	An invalid command was entered into the Adabas Review command line.
Action	Press a valid PF key or enter a valid Adabas Review command.
REV00006	Press 'Enter' to continue initialization process
Explanation	During Adabas Review initialization a series of messages are displayed. Adabas Review will pause whenever a page is full or on the last page.
Action	Press ENTER.
REV00008	No online system of Review is available
Explanation	Adabas Review has determined that there are no online systems available to the user. There are two possible causes: <ol style="list-style-type: none">1. the installation of Adabas Review has not been fully completed.2. Adabas Review is installed, but your profile prohibits you from accessing the available systems.
Action	Contact your Adabas Review administrator.
REV00011	Interval statistics profile has been created
Explanation	During Adabas Review initialization, the interval statistics profile record was created.
Action	This message is for information only.
REV00012	Report has been saved
Explanation	The request to save a report definition to the Adabas Review repository has completed successfully.
Action	This message is for information only.

REV00013	Now viewing current data
Explanation	You are now viewing current data as opposed to historical data.
Action	This message is for information only.
REV00014	{user-id} is not authorized to use Review
Explanation	Either you have not been defined to Adabas Review, or you are not authorized to use Adabas Review.
Action	Contact your Adabas Review administrator.
REV00015	Report name is required
Explanation	An attempt was made to edit/copy a report without a name.
Action	Enter a name in the report name field.
REV0001	At least one item must be selected
Explanation	An attempt was made to add a report without selecting any items to be used as report criteria.
Action	Select one or more fields to be used as criteria by entering a number in its ORDER field.
REV00020	Order number must not exceed 20 (max number of items)
Explanation	A number greater than 20 was entered into one of the ORDER fields.
Action	Enter a number between 1 and 20.
REV00021	Order number must be unique
Explanation	Duplicate ORDER numbers have been detected.
Action	Enter a unique number in each ACCT ORDER to be included in the report.
REV00025	Now viewing historical data
Explanation	You are now viewing historical data as opposed to current data.
Action	This message is for information only.

REV00026	Report was not saved
Explanation	The request to save a report was not successful. This is usually caused by responding NO when asked if you want to replace the report that was previously saved under the same name.
Action	This message is for information only.
REV00002	There are no detailed records for this report
Explanation	<i>A detailed response time</i> report was requested but there are no detail records for the selected report.
Action	This message is for information only.
REV00028	Report was not refreshed
Explanation	This indicates that a request to restart a report was not successful.
Action	This message is for information only.
REV00029	Invalid reply
Explanation	An invalid reply was given to an Adabas Review prompt.
Action	Enter a valid reply.
REV00030	Report has been purged
Explanation	This confirms that the purge report request was successful.
Action	This message is for information only.
REV00032	Report not found
Explanation	An attempt to access a report has failed because the report is not active.
Action	This message is for information only.
REV00033	Unknown return code from purge - RC= {ret-code}
Explanation	An unknown return code was returned from the purge reports program due to an internal error.
Action	If the problem reoccurs, contact your Software AG technical support representative.

REV00035	This is the oldest historical snapshot
Explanation	This is the oldest historical snapshot; the NEXT command cannot be entered.
Action	This message is for information only.
REV00036	Do not enter {x} and a direct command
Explanation	A reply was entered into an Adabas Review prompt field and a direct command was entered simultaneously.
Action	Either answer the Adabas Review prompt or enter a direct command, but not both.
REV00037	Invalid response - only valid response is {xxx}
Explanation	An invalid response was detected and Adabas Review is prompting the user with the correct response.
Action	Enter a valid response.
REV00038	Report status has been changed
Explanation	This confirms that a request to activate or deactivate a report was successful.
Action	This message is for information only.
REV00040	Redisplay buffer full - Redisplay unavailable
Explanation	The redisplay is unavailable because more than 5000 lines were displayed.
Action	As a workaround, the report data can be printed via the HC command and other tools can be used to scroll through this output.
REV00043	You must reply 'Y' or 'N'
Explanation	An invalid reply was given in response to an Adabas Review prompt that requires a reply of either yes ("Y") or no ("N").
Action	Reply "Y" or "N".
REV00044	Value must be between 0 and 100
Explanation	The value entered was not within the range 0 and 100.
Action	Enter a value between 0 and 100.

REV00045	Do not mark blank lines
Explanation	A selection was marked on a line that does not have a value or any data to select.
Action	Mark a valid selection or enter an Adabas Review command.
REV00046	Do not mark deleted reports
Explanation	A character was placed in the select field of a report that was just deleted.
Action	Do not place a character in this field.
REV00047	Invalid character
Explanation	An invalid character was entered into an Adabas Review field.
Action	Enter a valid character.
REV00050	Non-zero return code from FREEMAIN
Explanation	An unexpected return code has occurred while trying to free storage. The return code is also displayed.
Action	If the problem recurs, contact your Software AG technical support representative.
REV00054	Now creating sample report {report-name}
Explanation	When Adabas Review is invoked online for the first time, it adds sample Adabas reports to its system file.
Action	This message is for information only.
REV00055	Select a historical snapshot
Explanation	Select a historical snapshot.
Action	This message is for information only.
REV00057	Use of function is prohibited
Explanation	An attempt was made to perform an Adabas Review function that is not permitted for the user.
Action	Contact your Adabas Review administrator.

REV00058	There are no saved reports to list
Explanation	A request to list report definitions was made but there are no definitions to list.
Action	This message is for information only.
REV00059	Operator command issued
Explanation	The operator command was issued to Com-plete.
Action	This message is for information only.
REV00060	No report selected to view
Explanation	An attempt was made to perform an Adabas Review View function, but no report was selected
Action	Access a report using a List or Edit function and the retry the View function.
REV00062	No data has been accumulated for this report
Explanation	A request to display a report cannot be satisfied because the report has not yet accumulated any data.
Action	Determine if the report criteria is correct and if so, try again later or else add a new report.
REV00064	Invalid function
Explanation	An invalid function was entered.
Action	Enter a valid function.
REV00065	DBID missing
Explanation	DBID= was entered on the Adabas Review command line of the Adabas Communication Statistics display, but no corresponding DBID number was given.
Action	Enter DBID= <i>nnn</i> where <i>nnn</i> is a valid DBID number.
REV00066	Invalid cursor position
Explanation	The cursor was placed at an invalid location on a screen that senses the cursor position to perform a function.
Action	Place the cursor at a valid position or enter an Adabas Review command.

REV00068	Invalid logical operator
Explanation	An invalid logical operator was entered. Valid operators are: =,;<>,EQ,NE,LT,GT,LE,GE
Action	Enter a valid logical operator.
REV00072	Mark one line only
Explanation	More than one line was marked to perform a report function. This is not allowed.
Action	Mark only one line at a time.
REV00073	Invalid character in select column
Explanation	A line has been marked with a character that has no assigned function.
Action	Mark lines using valid characters.
REV00074	Invalid Transaction Summary option
Explanation	An invalid option was entered into the Transaction Summary Option field in the Edit Report screen.
	Valid options are NONE, SUM, and DET.
Action	Enter a valid option.
REV00078	Report was not purged
Explanation	The request to purge a started report was not performed.
Action	This message is for information only.
REV00079	Invalid message prefix
Explanation	An inquiry was made for a message number that has an invalid prefix. Message numbers must start with REV.
Action	Enter the MSG command using a valid message number.
REV00080	Com-plete functions are not valid under CICS
Explanation	A Com-plete performance monitor function was attempted. This is not valid under CICS.
Action	This message is for information only.

REV00081	Review is not compatible with this version of Com-plete
Explanation	A Com-plete performance monitor function was attempted on a version of Com-plete earlier than version 4.4.
Action	Install the current version of Com-plete.
REV00082	Select a buffer pool or enter a Review command
Explanation	The Adabas Review buffer pool function is waiting for terminal input.
Action	Select a buffer pool by name or enter an Adabas Review command.
REV00083	Syntax error in scan command
Explanation	A syntax error was detected while processing a scan command on the ET display.
Action	This message is for information only.
REV00084	Invalid buffer pool name
Explanation	The buffer pool selection entered cannot be identified.
Action	Enter a valid buffer pool name or enter an Adabas Review command.
REV00085	Command not allowed in history mode
Explanation	The command entered is not allowed in history mode.
Action	Do not enter command.
REV00086	No ADAB control block found
Explanation	The Adabas Communication Statistics function was invoked, but there has not been any database access since Com-plete was started. Therefore, there is no database information to display.
Action	Try again later.
REV00087	{nn} Reports removed from AUTOSTART status
Explanation	This confirms that the indicated report definitions have been changed from AUTOSTART to NON-AUTOSTART status.
Action	This message is for information only.

REV00091	Invalid command code
Explanation	An invalid code was entered for a command.
Action	Enter a valid command code.
REV00092	Report has been started
Explanation	This confirms that the request to start a report was successful.
Action	This message is for information only.
REV00093	Syntax error(s) in report definition
Explanation	The request to start an online report has failed because of syntax errors in the report definition.
Action	Correct the report definition and start the report again.
REV00094	Adabas response code {rsp}
Explanation	Adabas has responded with a non-zero response code.
Action	Use the <i>Adabas Messages and Codes</i> documentation to determine the problem.
REV00095	Report was not started
Explanation	The request to start a report was not successful.
Action	This message is for information only.
REV00096	User profile is being held by another user
Explanation	An attempt was made to access a user profile that is being updated by another user.
Action	Edit the user profile again. Ensure that the changes made to profile do not affect the changes that you are making.
REV00097	User profile not specified
Explanation	The purge user (PU) command was given without specifying a user profile.
Action	When using the purge user (PU) command, specify the user profile you wish to purge. The format for the command is PU <i>uuuuuu</i> where <i>uuuuuu</i> is the user profile.

REV00098	User profile was not purged
Explanation	A request was made to purge a user profile. When Adabas Review asked for a confirmation, the user decided not to purge the user profile.
Action	This message is for information only.
REV00099	User profile was not found
Explanation	An attempt was made to delete a user profile that was not found in the Adabas Review repository.
Action	Check to make sure the user ID you specified is correct.
REV00100	User profile has been purged
Explanation	This confirms that a request to purge a user profile was successful.
Action	This message is for information only.
REV00101	New user profile
Explanation	The profile that you are editing is new.
Action	You may now customize the new user profile. To save this new profile, press PF5or issue the SAVE command.
REV00102	User profile was not saved
Explanation	A request was made to save the changes made to a user profile. When Adabas Review asked for a confirmation, the user decided not to save the changes.
Action	This message is for information only.
REV00104	Return code {ret-code} received from {program-name}
Explanation	An unexpected return code was received from one of Adabas Review's programs.
Action	Record the error message and contact your Software AG technical support representative.
REV00105	User profile has been saved
Explanation	The changes made to the user profile have been saved.
Action	This message is for information only.

REV00106	No Review control block found
Explanation	(CICS Only) This message appears when <i>REVTAB</i> has not been defined as a resident program.
Action	Contact your Software AG technical support representative.
REV00108	Default user profile has been added
Explanation	This message appears the first time Adabas Review is invoked after installation. A DEFAULT user profile is added to the Adabas Review repository, which allows all users to perform all functions of Adabas Review including the ability to maintain user profiles.
Action	A logical procedure at this point would be to invoke the user profile system and add yourself as able to maintain user profiles. Then update the DEFAULT profile so that general users cannot maintain user profiles.
REV00111	No storage available to start report
Explanation	A request to start a report has failed due to insufficient storage. This is probably because of other reports that are using most or all of the storage allocated to Adabas Review.
Action	Purge one of the already existing reports or try again later.
REV00116	Statistics profile was not saved
Explanation	The statistics profile was not saved.
Action	This message is for information only.
REV00120	Users attached for test simulation
Explanation	This confirms that users have been attached to simulate a load on Com-plete.
Action	This message is for information only.
REV00121	Error {error-number} attaching users
Explanation	An error has occurred while trying to attach users for load simulation.
Action	If the problem reoccurs, contact your Software AG technical support representative.

REV00123	Statistics profile has been saved
Explanation	The statistics profile has been saved.
Action	This message is for information only.
REV00124	TID number must be numeric
Explanation	A TID number was entered into the SA screen via the T= or TID= command but is was not numeric.
Action	Enter a numeric TID number.
REV00125	Report definition has been saved successfully
Explanation	This confirms that the request to save a report definition was successful.
Action	This message is for information only.
REV00129	Report definition not found
Explanation	An attempt was made to retrieve a report definition but no report definition by that name was found.
Action	Determine the correct name or create a new definition.
REV00132	Interval may not be greater than 1440 minutes
Explanation	The interval may not be greater than 1440 minutes.
Action	This message is for information only.
REV00133	Review is terminating
Explanation	A request was made to start, view, or list a report, but Adabas Review is in the process of terminating.
Action	This message is for information only.
REV00134	Duplicate report name - report not started
Explanation	An attempt to start an Adabas report has failed because a report with the same name is already active.
Action	Purge the currently active report and retry or start a report with a different name.

REV00135	Review command not provided
Explanation	An attempt was made to communicate with the Adabas Review exit but no Adabas Review command was provided.
Action	Provide an Adabas Review command.
REV00137	Insufficient storage to issue Review command
Explanation	The Adabas Review exit routine is not accepting communications due to insufficient storage.
Action	Purge at least one of the started reports.
REV00138	Insufficient storage to start report
Explanation	An attempt to start an Adabas Review report has failed due to insufficient storage.
Action	Purge an active report and retry.
REV00139	Invalid SUMMARY, MAX or MIN field
Explanation	An attempt to start an Adabas Review report has failed because fields were marked as Sum, Min, Max, or Avg, but these fields are only allowed to be Order fields.
Action	Make the fields Order fields only.
REV00140	An invalid value was specified in the RULE
Explanation	An attempt to start an Adabas Review report has failed because values specified in the Rule where either too long, or in case of numbers with a decimal point, the formatting is not correct.
Action	Specify a correct value in the RULE.
REV00141	Format buffer error
Explanation	A format buffer error has occurred while trying to communicate with the Adabas Review exit routine.
Action	Contact your Software AG technical support representative.
REV00144	Display program not found
Explanation	An attempt to view an active report has failed because the display program for this report cannot be found.
Action	Generate a display program by resaving the report definition, if it is available, or change the display program name on the LS screen to a program name that is known to be acceptable for this report.

REV00145	Natural error: {error-number}
Explanation	A Natural error condition occurred. The Natural error message number is displayed.
Action	Reference the Natural online message utility for an explanation of the error.
REV00146	Report definition was not saved
Explanation	The request to save a report definition was canceled by the user in response to an overlay warning.
Action	This message is for information only.
REV00147	Too many fields - exceeds max linesize - save canceled
Explanation	The request to save a report definition was canceled because the resulting generated display program would have exceeded the maximum allowable line size.
Action	Reduce the number of fields and try again.
REV00148	DBID has been changed
Explanation	This confirms that the request to change the target DBID was successful.
Action	This message is for information only.
REV00149	There are no started reports
Explanation	A request to list started reports was made but there are no started reports to list.
Action	This message is for information only.
REV00150	Detailed reports cannot be viewed online
Explanation	Only summary reports can be viewed online. Detailed reports are printed at Adabas termination time.
Action	This message is for information only.
REV00151	Insufficient storage to reactivate report
Explanation	An attempt was made to reactivate a report that was deactivated by Adabas Review due to insufficient storage. The report cannot be reactivated.
Action	Use the refresh (RF) command to purge the existing data and start accumulating new information.

REV00152	Report has been refreshed
Explanation	This confirms that a refresh (RF) command was successful.
Action	This message is for information only.
REV00153	There are no history reports
Explanation	A request to List History Reports was canceled because there are no history reports to list.
Action	This message is for information only.
REV00155	DBID must be between 0 and 255.
Explanation	An attempt was made to change the DBID number to less than 0 or greater than 255.
Action	Enter a DBID number in the range of 0 to 255.
REV00156	Invalid AND/OR field
Explanation	A value other than AND or OR was entered into the AND/OR field of the selection criteria on the Processing Rules screen.
Action	Enter AND or OR.
REV00157	No field specified
Explanation	No field name was specified for the entered criteria on the Edit Report screen.
Action	Enter a field name.
REV00158	AND/OR field not followed by another condition
Explanation	AND or OR was entered into the AND/OR field of the Processing Rules screen but no condition followed.
Action	Either remove the AND/OR or enter another condition.
REV00159	AND/OR field missing
Explanation	More than one condition was coded on the Processing Rules screen, but no AND/OR was coded for the previous condition.
Action	Enter AND/OR on the previous condition

REV00160	OPERATOR field missing
Explanation	The OPERATOR field has been left blank on a condition.
Action	Fill in the OPERATOR field.
REV00161	VALUE field missing
Explanation	The VALUE field has been left blank on a condition.
Action	Fill in the VALUE field.
REV00162	Invalid OPERATOR field
Explanation	An invalid operator was entered into the OPERATOR field of the Processing Rules screen.
Action	Enter a valid operator.
REV00163	Invalid field name
Explanation	An invalid field name was entered on the Edit Report screen.
Action	Press PF11 for a list of valid field names.
REV00169	ORDER number too high
Explanation	A number greater than 20 was entered into the ORDER field of the Edit Report screen. 20 is the highest number that can be entered.
Action	Enter a number between 1 and 20.
REV00170	{field-name} is not a valid field for SUM, AVG, PCT or ROUND
Explanation	A field was marked for SUM, AVG, PCT, or ROUND on the Edit Report screen, but the field marked is not a numeric field. Fields must have a numeric output to be eligible for SUM, AVG, PCT, or ROUND.
Action	Place a number in the ORDER column, and remove any marks for SUM, AVG, PCT, or ROUND.
REV00171	SAVE/START canceled by operator
Explanation	The request to save a report definition was canceled by the user in response to an overlay warning.
Action	This message is for information only.

REV00175	Invalid value
Explanation	An invalid value was entered as part of a logical condition on the Edit Report screen.
Action	Enter a valid value.
REV00176	Internal storage error
Explanation	An internal storage management error has occurred within the Adabas Review nucleus.
Action	If the problem recurs, contact your Software AG technical support representative.
REV0017	ROUND is only valid on fields with an ORDER number
Explanation	A rounding factor was specified for a field that does not also have an order number specified.
Action	Enter a number in the ORDER field, or remove the rounding factor.
REV00179	You must enter ORDER, SUM, MIN, MAX, PCT or AVG
Explanation	A field was entered on the Edit Report screen but no action was specified; i.e. ORDER, SUM, MIN, MAX, PCT, or AVG.
Action	Enter a number in the ORDER field and/or an X in one or more of the SUM, MIN, MAX, PCT, or AVG fields
REV00180	Invalid data in ROUND column
Explanation	The data entered into the round column of the Edit Report screen was not numeric.
Action	Enter a number with or without a decimal into the round field.
REV00181	ADACALL must be an integer between 0 and 32,767
Explanation	ADACALL specifies the maximum number of Adabas calls an application can make before the Com-plete / Adabas interface forces the application to be rolled out. This parameter is ignored if ADAROLL=NO is specified.
Action	Enter a number between 0 and 32,767.
REV00182	ADALIMIT must be an integer between 0 and 32,767
Explanation	ADALIMIT specifies the number of Adabas calls that may be made by an online transaction without any intervening terminal I/O. Programs that exceed this limit are canceled.
Action	Enter a number between 0 and 32,767.

REV00183	ADAROLL must be 'ALWAYS', 'NEVER', or less than 30.99
Explanation	ADAROLL specifies the amount of time Com-plete will wait for Adabas calls before rolling out the program making the call.
Action	Enter ALWAYS, NEVER, or a number less than 30.99.
REV00184	ADACALL for DBID {dbid} has been changed to {yyyyy} by {user-id}
Explanation	The ADACALL parameter for the specified database was changed to yyyyy through the facilities provided by the Adabas Communication Statistics function (Adabas Calls from Com-plete) in Adabas Review DC.
Action	This message is for information only.
REV00185	ADALIMIT for DBID {dbid} has been changed to {yyyyy} by {user-id}
Explanation	The ADALIMIT parameter for the specified database was changed to yyyyy through the facilities provided by the Adabas Communication Statistics function (Adabas Calls from Com-plete) in Adabas Review DC.
Action	This message is for information only.
REV00187	Only 'Y' and 'N' are valid values
Explanation	The letter "Y" (yes) and the letter "N" (no) are the only two valid values for this field.
Action	Enter "Y" if you wish the APPLYMOD to be active; or enter "N" if you wish to deactivate the applymod.
REV00188	The ADABAS/COM-PLETE parameters have been updated
Explanation	This message confirms that the Adabas / Com-plete parameters have been successfully updated.
Action	This message is for information only.
REV00190	Invalid cursor placement for requested function
Explanation	The cursor must be placed on a line that contains valid data.
Action	Place cursor on a line with valid data.
REV00193	Too many {xxx} fields
Explanation	xxx is ORDER, SUM, MIN, MAX, AVG, or ROUND. There were too many of the indicated fields to process. When all field names are combined, they will not fit into an 80-byte statement. The 80-byte statements are used internally by Adabas Review for report definition storage.
Action	Reduce the number of fields by one until the message disappears.

REV00195	Invalid page number entered
Explanation	A number was entered on the Adabas Review command line that was greater than the actual number of pages available.
Action	Enter a valid page number.
REV00196	Roll buffer not allocated
Explanation	The roll buffer is not allocated.
Action	This message is for information only.
REV00197	Roll data sets not allocated
Explanation	The roll data sets are not allocated.
Action	This message is for information only.
REV00198	User not logged on
Explanation	The user is not logged on.
Action	This message is for information only.
REV00199	Invalid wrap option
Explanation	An invalid wrap option was specified in the report definition. The option must be NONE, STD, or HIGH.
Action	This message is for information only.
REV00200	Low water mark must be less than high water mark
Explanation	The low water mark specified was higher than or equal to the high water mark.
Action	Enter a number less than the high water mark.
REV00202	Review is not installed in database {dbid}
Explanation	An attempt was made to either start a report or to list started reports against a database that either does not have Adabas Review installed as a user exit 4 or does not currently have LOGGING turned on.
Action	Verify that Adabas Review is installed on the target DBID. If it is, ensure that ADARUN LOGGING=YES has been specified and that LOGGING has not been subsequently disabled from the operator console.

REV00203	Report hard copy has been queued
Explanation	This confirms that a request to send report output to a hardcopy device completed successfully, and that the report is either now printing or has been placed on the queue to be printed.
Action	This message is for information only.
REV00205	Invalid display program name
Explanation	An attempt was made to change the display program name using the CP command of the List Reports screen, but the new name is blank or invalid.
Action	Enter a valid program name.
REV00206	Display program name has been changed
Explanation	This confirms that the request to change the display program name using the CP command of the List Report Definitions screen was successful.
Action	This message is for information only.
REV00207	Report definition was purged by another user
Explanation	The report definition selected is being purged by another user.
Action	This message is for information only.
REV00209	Invalid character in report name
Explanation	An invalid character such as a quotation mark or a period was used as part of the report name.
Action	Remove the invalid character from the report name.
REV00210	Invalid start/stop date
Explanation	A date range was entered for viewing a history report but the date(s) are not valid. This may mean that the starting date is greater than the ending date, or that invalid numeric data or an invalid date format has been entered.
Action	Enter a valid date range in the form of <i>yyyy-mm-dd</i> or press ENTER to default to the maximum date range.

REV00211 **History reports must be purged from the expanded list**
Explanation An attempt was made to purge a history report from the LH screen. This is not a valid LH function. The list must be expanded using the EX command before history reports can be purged.
Action Enter EX in the SEL column next to the report to be purged. An expanded list will appear from which the Purge History Report (PH) function can be executed.

REV00212 **Enter date range**
Explanation This prompts you to enter a date range before viewing a history report. The maximum date range (all dates) is the default.
Action Enter a date range in the form of *yyyy-mm-dd*, or press ENTER to default to the maximum date range.

REV00214 **Display program regeneration complete**
Explanation The request to regenerate display programs has completed successfully.
Action This message is for information only.

REV00217 **Review system file not available**
Explanation Adabas Review attempted to read information from its system file but received an Adabas response code of 148 (ADARSP148).
Action Bring up the database that has the Adabas Review repository and make sure that the FILE parameter has been specified correctly.

REV00218 **Default system must be 'DB', 'DC', 'MM', or 'NM'**
Explanation An invalid value was entered for default system. The valid system codes are:

DB	Database (Adabas Review)
DC	Data Communication
MM	Main Menu
NM	Natural Monitor

Action Enter a valid system code.

REV00219	Input not numeric
Explanation	A value was entered into a field that is intended to accept numeric data only.
Action	Enter a valid numeric value.
REV00220	Auto regenerate started
Explanation	The subtask to generate auto-report definitions was successfully started.
Action	This message is for information only.
REV00221	Auto regenerate already active
Explanation	The subtask to generate auto-report definitions is still active from a previous execution.
Action	Wait a few seconds and try the command again.
REV00222	Auto regenerate failed
Explanation	The subtask to regenerate auto-report definitions was not attached and did not run.
Action	Check your Adabas STEPLIB and make certain that the module RAOSAUTO is present.
REV00223	UEX4 version error
Explanation	The Adabas UEX4 module RAOSEXIT is not the correct version.
Action	Verify that Adabas Review has been correctly installed.
REV00224	MSG function not available from this screen
Explanation	The Adabas Review message help subsystem is not available from this screen.
Action	Perform the MSG function from another screen.
REV00225	DBID must be between 1 and 65535
Explanation	The target database ID must be in the range between 1 and 65535.
Action	Enter a database ID in the specified range.
REV00226	SVC is zero
Explanation	The SVC specified cannot be zero (0).
Action	Enter a correct SVC number.

REV00227	Target type must be 'ADA', 'NET', 'NPR', or 'TPF'
Explanation	The target type must be one of the specified values.
Action	Enter the correct target type.
REV00228	DBID for Adabas target type must be less than 255
Explanation	If the target type is <i>ADA</i> , then the target database ID must be in the range of 1 to 255.
Action	Enter a database ID in the specified range.
REV00229	Field value must be 'Y' or 'N'
Explanation	An invalid value was entered for the field.
Action	Enter a valid field value: either yes ("Y") or no ("N").
REV00230	No target definition found for target {target-id}
Explanation	The target definition did not exist for the requested target.
Action	Define the target.
REV00231	Target definition for DBID {dbid} saved
Explanation	The target definition was successfully saved.
Action	This message is for information only.
REV00234	Default definition cannot be purged
Explanation	The default definition for target 00000 cannot be purged.
Action	This message is for information only.
REV00235	Target definition(s) purged successfully
Explanation	The target definitions marked for purge were successfully deleted.
Action	This message is for information only.
REV00236	No target definition exists for DBID dbid and default is not present
Explanation	The target definition for the database specified did not exist, and there was also no default definition.
Action	Add the target definition for the specified target.

REV00237	Generate started
Explanation	The subtask to generate report definitions was successfully started.
Action	This message is for information only.
REV00238	Generate already active
Explanation	The subtask to generate report definitions is still active from a previous execution.
Action	Wait a few seconds and try the command again.
REV00239	Generate failed
Explanation	The subtask to generate report definitions was not attached and did not run.
Action	Check your Adabas STEPLIB and make certain that the module RAOSAUTO is present.
REV00240	Function canceled
Explanation	The requested function was terminated by user request and was not performed.
Action	This message is for information only.
REV00241	Review file set successfully
Explanation	The Adabas Review data file's database ID and file number were set successfully.
Action	This message is for information only.
REV00242	Unable to open command log file for output
Explanation	A report was started with the logging option set to "Y" (yes), but the file specified for output cannot be opened. The report is started without logging.
Action	If this is an online report, make sure the DSN field of the Report Options screen is set to a valid command log output file. If this is a batch report, make sure the DSN= parameter of the LOG statement is set to a valid command log output file.
REV00243	Adabas Online Services is not installed
Explanation	The request to invoke Adabas Online System (AOS) from Adabas Review has failed because AOS is not installed in the current Natural system file.
Action	This message is for information only.

REV00244	Components not installed properly
Explanation	The installation process did not complete successfully.
Action	Make sure that all INPL and IUPD media are properly installed.
REV00245	PF{nn} not defined
Explanation	The PF key that was pressed is not defined to perform a function.
Action	Press a valid PF key.
REV00246	Press 'PF3' to exit or 'PF5' to save the profile
Explanation	To exit without saving the changes made to a user profile, press PF3. To save the changes made to a user profile, press PF5.
Action	See explanation.
REV00247	Userid must be specified
Explanation	A user ID must be specified.
Action	Enter a user ID.
REV00248	Natural error {error-number} has occurred on line {line-number} of program {program-name}
Explanation	A Natural error has occurred in one of Adabas Review's programs.
Action	Record the information given in the message and contact your Software AG technical support representative.
REV00249	Command log data set already in use
Explanation	A report was started with the logging option set to "Y" (yes), but the specified output data set is already in use by another report. The report is started without logging.
Action	Either use another data set, or purge the report that is using the command log data set.
REV00250	Logging is not valid for summary reports
Explanation	LOGGING was specified on the Report Options screen for a summary report. Only detail reports can perform the LOGGING function.
Action	Either set LOGGING to "N" or set SUM/DETAIL to "D".

REV00252	At least one field is required
Explanation	An attempt was made to save a report definition with no fields to be displayed. At least one field is required to save a report.
Action	Correct the report definition and press PF5to save the report definition.
REV00253	There are no report definitions on file
Explanation	A request to list report definitions cannot be satisfied because there are no definitions to list.
Action	This message is for information only.
REV00254	At least one order field is required
Explanation	An attempt to save a summary report failed because there are no ORDER fields. At least one ORDER field is required for summary reports.
Action	Make at least one field an ORDER field and save the report.
REV00255	Report definition conversion complete
Explanation	The process of converting Adabas Review report definitions has completed.
Action	This message is for information only.
REV00256	History file conversion complete
Explanation	The process of converting Adabas Review history reports completed.
Action	This message is for information only.
REV00257	User profile conversion complete
Explanation	The process of converting Adabas Review user profiles has completed.
Action	This message is for information only.
REV00258	Report definition conversion was canceled
Explanation	The process of converting Adabas Review report definitions was canceled at the request of the user. Any reply other than "yes" or "change" on the LFILE confirmation screen will cause this message.
Action	This message is for information only.

REV00259	History file conversion was canceled
Explanation	The process of converting Adabas Review history reports was canceled at the request of the user. Any reply other than "yes" or "change" on the LFILE confirmation screen will cause this message.
Action	This message is for information only.
REV00260	User profile conversion was canceled
Explanation	The process of converting Adabas Review user profiles was canceled at the request of the user. Any reply other than "yes" or "change" on the LFILE confirmation screen will cause this message.
Action	This message is for information only.
REV00261	There are no report definitions to convert
Explanation	An attempt was made to convert report definitions, but there are none to convert. Adabas Review only converts report definitions that do not already exist in the target Adabas Review repository.
Action	This message is for information only.
REV00262	There are no history reports to convert
Explanation	An attempt was made to convert Adabas Review history reports, but there are none to convert.
Action	This message is for information only.
REV00263	There are no user profiles to convert
Explanation	An attempt was made to convert Adabas Review user profiles, but there are none to convert. Adabas Review only converts user profiles that do not already exist in the target Adabas Review repository.
Action	This message is for information only.
REV00264	Error {error-number} while trying to convert report definitions
Explanation	Either an Adabas or a Natural error has occurred while trying to convert report definitions.
Action	Follow the Adabas or Natural procedures for error correction.

REV00265	Error {error-number} while trying to convert history reports
Explanation	Either an Adabas or a Natural error has occurred while trying to convert history reports.
Action	Follow the Adabas or Natural procedures for error correction.
REV00266	Error {error-number} while trying to convert user profiles
Explanation	Either an Adabas or a Natural error occurred while trying to convert user profiles.
Action	Follow the Adabas or Natural procedures for error correction.
REV00267	Do not try to convert to and from the same file
Explanation	An attempt was made to run an Adabas Review conversion program with identical TO and FROM files.
Action	Correct the LFILE for the TO or FROM file.
REV00268	Invalid file number
Explanation	The user attempted to change the database ID and file number of the Adabas Review repository. The file number specified was not an Adabas Review file.
Action	Specify a correct Adabas Review DBID/file number.
REV00269	No active targets found on SVC {svc}
Explanation	No active database targets were found on the SVC number specified in the message.
Action	Verify that the target definitions are defined to the correct SVC number.
REV00270	Database {dbid} is a Natural Process target
Explanation	The target selected is an Entire System Server (formerly Natural Process) target type.
Action	This message is for information only.
REV00271	Database {dbid} is not active
Explanation	The database selected is not active.
Action	This message is for information only.

REV00272	Database {dbid} is a non-Adabas target
Explanation	The database selected is a non-Adabas type target.
Action	This message is for information only.
REV00273	Report is already suspended
Explanation	An attempt was made to suspend a report that was is already suspended.
Action	This message is for information only.
REV00274	Invalid OP summary option
Explanation	An invalid option was entered on the Edit Report screen for the OP summary parameter.
Action	Enter a valid option.
REV00275	New report definition
Explanation	A new report definition is being created.
Action	Enter the parameters for the new report definition or exit.
REV00276	Report is already active
Explanation	An attempt was made to reactivate a report that was already active.
Action	This message is for information only.
REV00277	History data has been purged
Explanation	Historical data was purged.
Action	This message is for information only.
REV00278	History data was not purged
Explanation	Historical data was not purged.
Action	This message is for information only.
REV00279	History data not found
Explanation	Historical data was not found.
Action	This message is for information only.

REV00280	Available storage in thread insufficient
Explanation	The available storage in the thread is insufficient.
Action	Contact your Software AG technical support representative.
REV00281	An invalid request or an invalid FQE was found
Explanation	An invalid request or an invalid free queue element (FQE) was found.
Action	Contact your Software AG technical support representative.
REV00282	No response time report definition was specified
Explanation	No response time report definition was specified.
Action	Contact your Software AG technical support representative.
REV00283	Report definition has been purged
Explanation	Report definition has been purged.
Action	This message is for information only.
REV00284	Report definition was not purged
Explanation	Report definition was not purged.
Action	This message is for information only.
REV00285	Invalid device type for download
Explanation	An attempt was made to download a report but the Natural session is not in PC mode.
Action	If the device is a PC using Entire Connection, set your Natural session to PC mode by entering %+ on the command line, and reenter the DL command.
REV00286	Duplicate order numbers
Explanation	More than one field has the same order number on the Edit Report screen.
Action	Make each order number unique.
REV00288	Report is not active
Explanation	An attempt was made to perform a function on a started report, but no started report with the specified report name was found.
Action	This message is for information only.

REV00289	LOG command not allowed while viewing data
Explanation	An attempt was made to issue the LOG command while viewing a report.
Action	Stop viewing the report and reissue the LOG command.
REV00290	Adabas Review logging status changed
Explanation	The Adabas Review dynamic logging options have been updated.
Action	This message is for information only.
REV00291	Error returned during LOG request - {nnnn}
Explanation	The LOG command was issued and an error occurred during processing. nnnn = the response code associated with the error.
Action	Follow the Adabas or Natural procedures for error correction.
REV00292	Review not installed on database
Explanation	While attempting to view the buffer pool display, Adabas determined that Adabas Review was not installed on that database and issued a response code.
Action	This message is for information only.
REV00293	Function restarted due to Adabas rsp code 9
Explanation	An Adabas Review function was restarted from the beginning because an Adabas response code 9 (ADARSP009) was received.
Action	This message is for information only.
REV00294	NM component not installed
Explanation	An attempt was made to enter Adabas Review NM, but the NM component was not on the installation media.
Action	Determine whether the NM component was actually purchased. If it was purchased, then you may have inadvertently received the wrong Adabas Review installation media. Contact your Software AG representative.
REV00295	Select a history report
Explanation	An attempt was made to view a list of dates and times of history records for a response time report without specifying the name of the report.
Action	Specify the response time name.

REV00296	TID must be between 1 and 65,535
Explanation	The terminal ID (TID) must be between 1 and 65,535.
Action	Enter a valid TID number.
REV00297	Invalid TID specified
Explanation	An invalid terminal ID (TID) was specified.
Action	Enter a valid TID number.
REV00299	Function has been discontinued
Explanation	The current version of Adabas Review no longer supports the requested function.
Action	Refer to the <i>Adabas Review User</i> documentation for a list of available features and functions.
REV00300	Report not on file
Explanation	The requested report definition could not be found in the Adabas Review data file.
Action	This message is for information only.
REV00301	No OP summary information available
Explanation	No OP summary information was available for the report specified.
Action	This message is for information only.
REV00306	First field cannot be a buffer segment
Explanation	A DB report was defined with the first field as a buffer segment (FBSEG01, RBSEG01 ETC). The first field cannot be a buffer segment.
Action	Make another field the first field.
REV00307	No resident PGMLIB defined
Explanation	A request was made to view a list of programs in the resident program library buffer, but none were defined to Com-plete.
Action	This message is for information only.

REV00308	No resident programs defined
Explanation	A request was made to view a list of programs in the resident programs, but none where defined to Com-plete.
Action	This message is for information only.
REV00309	Unable to locate Adabas IDTH
Explanation	Adabas Review was unable to locate the Adabas IDT header.
Action	Contact your Software AG technical support representative.
REV00310	Unable to load ADALDI
Explanation	Adabas Review was unable to load the ADALDI text module from the Adabas TXTLIB.
Action	Verify that the Adabas TXTLIB is accessible from your z/VM machine.
REV00311	Database {dbid} has been ignored
Explanation	The specified database has been ignored because an entry for the DBID was found in the IGNORE table in program N-IGNORE. No STATUS information is returned for this database.
Action	If STATUS information for the database should be returned, edit and STOW the program N-IGNORE.
REV00312	Insufficient storage to reset stopwatch
Explanation	An attempt to reset the stopwatch was unsuccessful due to insufficient storage.
Action	Try again later.
REV00313	Only 'ON' and 'OFF' are valid values
Explanation	A value other than ON or OFF was entered.
Action	Enter ON or OFF.
REV00314	Command log data set switched
Explanation	The command log data set was switched successfully.
Action	This message is for information only.

REV00315	Command logging is not active for report
Explanation	Adabas Review command logging is not active for the specified report.
Action	Choose a report that has command logging.
REV00316	Invalid subpool ID
Explanation	The subpool ID specified was invalid.
Action	Select a valid subpool.
REV00317	There are no transaction summary records
Explanation	A Response Time Report was requested but no transaction summary records exist for the selected report.
Action	This message is for information only.
REV00318	There are no OP summary records
Explanation	A Response Time Report was requested but no OP summary records exist for the selected report.
Action	This message is for information only.
REV00319	Too many "AND" fields in selection criteria
Explanation	The AND fields in the selection criteria have resulted in a data string that is too long for Adabas Review to process.
Action	Reduce the number of AND statements and resave the report.
REV00320	Too many "OR" fields in selection criteria
Explanation	The OR fields in the selection criteria have resulted in a data string that is too long for Adabas Review to process.
Action	Reduce the number of OR statements and resave the report.
REV00321	Target SVC cannot be greater than 255
Explanation	A value larger than allowed was entered in the SVC field of the target definition. The maximum value for this field is 255.
Action	Enter the correct SVC number.

REV00322	User has already been canceled
Explanation	The user specified in the cancel function has already been canceled.
Action	This message is for information only.
REV00323	TID {terminal-id} canceled
Explanation	The specified terminal ID has been canceled.
Action	This message is for information only.
REV00325	TERMINAL {terminal-name} canceled
Explanation	The specified terminal has been canceled.
Action	This message is for information only.
REV00326	TID {terminal-id} not found
Explanation	The terminal ID specified in the cancel, pick, or force function could not be found.
Action	This message is for information only.
REV00327	User {user-id} not found
Explanation	The user specified in the cancel, pick, or force function could not be found.
Action	This message is for information only.
REV00328	Terminal {terminal-name} not found
Explanation	The terminal name specified in the cancel, pick, or force function could not be found.
Action	This message is for information only.
REV00329	Invalid TID specified
Explanation	The terminal ID number specified in the cancel, pick, or force function was not a valid numeric value.
Action	This message is for information only.
REV00330	Response time report - {report-name} STARTED
Explanation	The specified Adabas Review response time report was successfully autostarted.
Action	This message is for information only.

REV00331	No autostarted reports found to start
Explanation	No Adabas Review Response Time reports were found to autostart.
Action	This message is for information only.
REV00332	One report has been autostarted
Explanation	Adabas Review has started one autostarted response time report.
Action	This message is for information only.
REV00333	{count} reports have been autostarted
Explanation	Adabas Review started the specified number of autostarted response time reports.
Action	This message is for information only.
REV00334	History task recovery from Adabas time-out
Explanation	The Adabas Review history interval task successfully recovered from an Adabas timeout (response code 9, ADARSP009).
Action	This message is for information only.
REV00335	RNMH history task initializing in Natural
Explanation	The Adabas Review history interval task successfully invoked Natural and is initializing.
Action	This message is for information only.
REV00336	History task terminating. Unable to locate RNMTAB
Explanation	The Adabas Review history interval task terminated because it was unable to locate RNMTAB.
Action	Check that RNMTAB has been defined to CICS as a resident PPT entry, and that RNMTAB is available to CICS.
REV00337	History task terminating. Unable to load {module-id}
Explanation	The Adabas Review history interval task terminated because it was unable to locate the RNMCIICS.
Action	Check that RNMCIICS has been defined to CICS as a PPT entry and that RNMCIICS is available to CICS.

REV00338	History task terminating. Natural error {error-number} detected during initialization
Explanation	The Adabas Review history interval task terminated because it encountered a Natural error during initialization.
Action	Investigate the Natural error indicated, correct the problem, and restart the history subsystem.
REV00339	History task terminating. NM data file has not been initialized
Explanation	The Adabas Review history interval task terminated because it detected that the Adabas Review Natural Monitor data file was not initialized.
Action	Verify that the INSTALL program has been executed to initialize the Adabas Review Natural Monitor data file.
REV00340	History task terminating. Non-recoverable Natural error detected
Explanation	The Adabas Review history interval task terminated because it encountered an error in Natural from which it could not recover.
Action	Investigate the Natural error indicated, correct the problem, and restart the history subsystem.
REV00341	History task terminating normally
Explanation	The Adabas Review history interval task terminated normally.
Action	This message is for information only.
REV00342	History task terminating. Maximum reinitialization counter exceeded
Explanation	The Adabas Review history interval task terminated because the counter for maximum reinitializations was exceeded.
Action	Check messages sent to Adabas Review prior to this message to determine why the history task has reinitialized so many times.
REV00343	History task terminating
Explanation	The Adabas Review history interval task terminated.
Action	Check other Adabas Review messages issued prior to this message to determine if an error condition was encountered.

REV00344	TID {terminal-id} canceled by {user-id} at terminal {terminal-name}
Explanation	The user with the specified terminal ID was canceled by another user at another terminal.
Action	This message is for information only.
REV00345	User {user-id} canceled by {user-id} at terminal {terminal-name}
Explanation	The user with the specified user ID was canceled by another user at another terminal.
Action	This message is for information only.
REV00346	Terminal {terminal-name} canceled by {user-id} at terminal {terminal-name}
Explanation	The terminal with the specified name was canceled by another user at another terminal.
Action	This message is for information only.
REV00347	TID {terminal-id} forced
Explanation	The user with the specified terminal ID was forced.
Action	This message is for information only.
REV00348	User {user-id} forced
Explanation	The user with the specified user ID was forced.
Action	This message is for information only.
REV00349	Terminal {terminal-name} forced
Explanation	The terminal with the specified name was forced.
Action	This message is for information only.
REV00350	TID {terminal-id} forced by {user-id} at terminal {terminal-name}
Explanation	The user with the specified terminal ID was forced by another user at another terminal.
Action	This message is for information only.
REV00351	User {user-id} forced by {user-id} at terminal {terminal-name}
Explanation	The user with the specified user ID was forced by another user at another terminal.
Action	This message is for information only.

REV00352	Terminal {terminal-name} forced by {user-id} at terminal {terminal-name}
Explanation	The terminal with the specified name was forced by another user at another terminal.
Action	This message is for information only.
REV00353	User must be canceled before force
Explanation	A CANCEL command must be issued for a user before a FORCE command can be issued.
Action	This message is for information only.
REV00354	Invalid autostart option
Explanation	An invalid response time report autostart option was specified. The value must be "Y" or "N".
Action	Specify valid value.
REV00355	Invalid history refresh option
Explanation	An invalid response time report history refresh option was specified. The value must be "Y" or "N".
Action	Specify a valid value.
REV00356	Value must be in range {range-start} through {range-end}
Explanation	The value specified is invalid for the field. Valid values are denoted by <range-start> through <range-end> in the message.
Action	Specify a valid value in the range specified.
REV00357	History task terminating. Review NM incorrectly installed
Explanation	The Adabas Review history interval task terminated because it was unable to verify that the Adabas Review Natural Monitor code was correctly linked with the Natural nucleus.
Action	Verify that the Adabas Review NM code is correctly linked with the Natural nucleus.
REV00359	Report definition has been copied
Explanation	The request to copy a report definition was successful.
Action	This message is for information only.

REV00360	Review repository not available
Explanation	An Adabas response code 148 (ADARSP148) was received while trying to store information in an Adabas Review repository.
Action	Insure that the database ID and file number are correct and that the database is available.
REV00361	Database {dbid} inactive or invalid. Type 'TECH' for reason
Explanation	The user attempted to perform an Adabas Review function against a database that was inactive, did not have Adabas Review installed, or was not running a compatible version of Adabas Review.
Action	From the Database System menu, type TECH to determine why the current Adabas Review database is invalid and correct the error.
REV00362	Review is not installed in database {dbid}
Explanation	Using the DBID= command, the user attempted to change the Adabas Review database being accessed. The database selected did not have Adabas Review installed.
Action	Verify that the database specified in the DBID= command is a valid Adabas Review database.
REV00363	Database {dbid} is not active
Explanation	Using the DBID= command, the user attempted to change the Adabas Review database being accessed. The database selected was not active (Adabas response code 148, ADARSP148).
Action	Verify that the database specified in the DBID= command is a valid Adabas Review database and that it is active.
REV00364	Database {dbid} is below Review V3.4
Explanation	Using the DBID= command, the user attempted to change the Adabas Review database being accessed. The database selected has an invalid version of Adabas Review installed.
Action	Verify that the database specified in the DBID= command is a valid Adabas Review database.
REV00365	Response code {rsp} received accessing DBID {dbid}
Explanation	Using the DBID= command, the user attempted to change the Adabas Review database being accessed. The user received the indicated response code.
Action	Verify that the database specified in the DBID= command is a valid Adabas Review database.

REV00366	TECH command only available from the DB system main menu
Explanation	The user attempted to executed the TECH command from an Adabas Review panel other than the Database System menu. The Adabas Review TECH command is only executable from the Database System menu.
Action	Execute the TECH command from the Database System menu.
REV00367	Display program does not match report
Explanation	A VIEW or VW command terminated because the display program invoked was generated for a different report.
Action	Regenerate the display program for the report that failed using the RG function of the List Reports screen.
REV00368	Parentheses are required for a list or range
Explanation	A list or range of values was entered without parentheses into a processing rule.
Action	Include the values within parentheses.
REV00369	Unpaired parentheses
Explanation	The number of opening and closing parentheses are unequal.
Action	Include a closing parentheses for each opening parentheses.
REV00370	Invalid HELP command
Explanation	An invalid command was entered into the command line of a help screen.
Action	Enter a valid command or press a valid PF key.
REV00371	GENAUTO is not available in CMS
Explanation	A GENAUTO (or GA) command was entered but is not implemented in z/VM.
Action	This message is for information only.
REV00372	Download is invalid from this screen
Explanation	DOWNLOAD (or DL) was entered from a screen where the DOWNLOAD command is invalid.
Action	Enter DL into the SEL column of the List Started Reports screen.

REV00373	MAX K must be at least {n} K
Explanation	The MAX K value specified in the report options must be at least 4K for z/OS and z/VSE and at least 8K for BS2000.
Action	Specify a value for MAX K that is at least the minimum.
REV00374	WRAPPING=Y only allowed on sequence reports
Explanation	The WRAPPING value can only be set to "Y" for a SUMMARY report with SEQUENCE as the first display field.
Action	Only specify WRAPPING=Y for SUMMARY reports with SEQUENCE as the first field.
REV00375	Invalid page size - must be 1-255
Explanation	The page size entered on the Report Options screen is invalid. The value must be between 1 and 255.
Action	Enter a valid page size.
REV00385	Value must be greater than 0.
Explanation	The value must be greater than 0.
Action	This message is for information only.
REV00386	FNR must be between 1 and 254
Explanation	An attempt was made to change the FNR number to less than 1 or greater than 254.
Action	Enter a FNR number in the range of 1 to 254.
REV00388	Invalid line size - must be 72-255
Explanation	The line size entered on the Report Options screen is invalid. The value must be between 72 and 255.
Action	Enter a valid line size.
REV00390	List not sorted due to excessive report data
Explanation	The expanded list of history report occurrences could not be sorted because the resulting ISN list was too large. The list is displayed unsorted.
Action	Increase the value in the LS ADARUN parameter.

REV00391	History report compression complete
Explanation	The request to compress a history report completed successfully.
Action	This message is for information only.
REV00392	File is in use by another compression process
Explanation	An attempt was made to compress a history report but another report was being compressed at the time. This message can also occur if a CH function did not complete successfully.
Action	If another report is being compressed, wait until it completes and try again. If a CH function failed, you must run the RESET function. To run the RESET function: <ol style="list-style-type: none">1. Enter RESET HISTORY FILE on the command line of the DB System menu.2. Follow the instructions on the screen.
REV00393	Compression will not be performed
Explanation	A reply of "N" was given in response to the confirmation prompt prior to compressing a history report.
Action	This message is for information only.
REV00394	History file does not need resetting
Explanation	A request to reset the history file was made but the file does not need resetting.
Action	This message is for information only.
REV00395	History file has been reset
Explanation	This confirms that the history file has been reset. This essentially unlocks the lock that was placed on the file during a CH function.
Action	None if the message says HISTORY FILE HAS BEEN RESET. If the message also says DATA WAS LOST, restore the history file to a state prior to when the failing CH function was performed.
REV00396	Duplicate field in "AND" expression
Explanation	A logical "AND" expression contains a duplicate field name in a processing rule. When using "AND" to connect fields, each field name can be used only once per expression.
Action	Remove the duplicate field name from the expression.

REV00397	Target DBID has been changed
Explanation	The target DBID has been successfully changed for the report definition.
Action	This message is for information only.
REV00398	Bufferpool reports cannot be printed or downloaded
Explanation	The graphical bufferpool reports cannot be downloaded or printed: they may only be viewed.
Action	Use the VW command to view the report.
REV00399	AA is not available in VM/CMS
Explanation	The AA function is not available in z/VM.
Action	This message is for information only.
REV00400	Non zero response from target ={ nnn}
Explanation	A non-zero response code was returned from the specified target.
Action	Determine why the non-zero response code occurred.
REV00401	Report defaults were saved
Explanation	The report defaults were saved successfully.
Action	No action is required for this informational message.
REV00402	No matching reports to generate
Explanation	GENAUTO was started in local mode, but there are no autostarted reports with DBID-TO-MONITOR set to the local DBID. No autostarted reports will be generated.
Action	No action is required for this informational message.
REV00403	Update completed
Explanation	The report options were updated successfully.
Action	No action is required for this informational message.
REV00404	No changes to update
Explanation	A request to update reports was unnecessary because no changes were made.
Action	No action is required for this informational message.

REV00405	Cannot start a rpt that monitors a hub
Explanation	A request to start a report was unsuccessful because the DBID-TO-MONITOR was set to the Adabas Review hub ID. Adabas Review reports can only monitor Adabas targets.
Action	Correct the report and retry.
REV00406	Only one buffer segment allowed per report
Explanation	More than one buffer segment was defined in a report. Only one buffer segment per report is allowed.
Action	Correct the report and retry.
REV00407	There are no history records to convert
Explanation	An attempt was made to convert history records, but there are no history records to convert.
Action	No action is required for this informational message.
REV00408	Only 1 order field allowed with sum exit
Explanation	A summary exit was specified, but more than one order field was chosen for the report. Summary exit reports are limited to one (1) order field.
Action	Reduce the number of order fields to 1.
REV00409	Pulse report cannot be purged
Explanation	A request was made to purge the Pulse report. The Pulse report cannot be purged.
Action	No action is required for this informational message.
REV00410	Report defaults not saved
Explanation	A user canceled a prompt to confirm the saving of report defaults.
Action	No action is required for this informational message.
REV00411	{xxxxxxx} cannot be edited
Explanation	The EP command was used to edit a display program, but the display program is for a fixed format report. Since these programs are specific, not dynamic, no source code is available to the user.
Action	No action is required for this informational message.

REV00412	NUCID {nnnnn} is not available
Explanation	An attempt was made to change the nucleus ID with which Adabas Review communicates, but the requested nucleus ID was not available.
Action	Enter the NUC LIST command to obtain a list of available nucleus IDs and try again.
REV00413	NUCID only valid for cluster databases
Explanation	A user executed the NUCID or NUC LIST command for a non-cluster database.
Action	No action is required for this informational message.
REV00414	Duplicate field names not allowed
Explanation	Two or more fields with the same name were entered on the ER screen. This is not allowed.
Action	Remove the duplicate fields.
REV00415	Detail printer not available
Explanation	A request to start a detail report failed because there was no detail printer available.
Action	Delete another detail report first or provide more printers in the startup JCL. Then try again.
REV00416	Invalid data in rules value
Explanation	An invalid character was entered into a processing rules value.
Action	Remove the invalid character from the rules value and try again.
REV00417	Pulse interval must not be greater than 1440
Explanation	The pulse interval was incorrectly specified for a Pulse report.
Action	Specify a value between 1 and 1440 and try again.
REV00418	BUFFPOOL is not delivered in source form
Explanation	An attempt to edit the display program BUFFPOOL failed because it is not delivered as source.
Action	No action is required for this informational message.

REV00419	List size exceeded
Explanation	The maximum list size of 10 has been exceeded in a processing rule.
Action	Limit the list size to 10 and try again.
REV00420	Unable to obtain SVC list
Explanation	An AA command was issued, but the list of SVCs cannot be accessed.
Action	Make certain that ADATMZ exists and is accessible from the current Adabas Review hub or database. Then try again.
REV00421	There are no targets for this SVC
Explanation	After an AA command, an SVC was selected, but there are not targets available for that SVC.
Action	No action is required for this informational message.
REV00422	Only order fields are allowed for detailed reports
Explanation	SUM, MIN, MAX, AVG, or ROUND were selected on the Edit Reports screen, but the report is a detailed report. ORDER is the only valid entry for a detailed report.
Action	Remove the invalid entries and try again.
REV00423	Report type changed -- defaults were reset
Explanation	While editing a report, the detail/summary report type was changed. Each report type requires its own set of default report options. The default report options for the new report type have now been loaded.
Action	No action is required for this informational message. Press PF2 to make any necessary changes to the report options.
REV00424	Unable to retrieve data from target {nnnnn}
Explanation	For reasons unknown to Adabas Review, the requested target was unable to supply AA information.
Action	No action is required for this informational message.
REV00425	Parameter input is missing or invalid
Explanation	The expected parameter input was either missing or has invalid data.
Action	Correct the input data and try again.

REV00426	Value for {keyword} is missing or invalid.
Explanation	The parameter input for a keyword was either missing or has invalid data.
Action	Correct the keyword input and try again.
REV00427	{TARGET DBID FILE} is not available
Explanation	The parameter input for a SET command keyword refers to an unavailable destination.
Action	Correct the keyword data or make sure the destination is available.
REV00428	{TARGET ID DBID FILE} has been set to {nnnnn}
Explanation	A SET command changed the target ID, database ID, or file successfully.
Action	No action is required for this informational message.
REV00429	SET program has terminated with errors
Explanation	The SET program encountered errors. The error will have been more clearly identified in a previous message.
Action	Correct the error and try again.
REV00430	More than 256 target definitions on file
Explanation	The maximum number of target definitions has been exceeded.
Action	Limit the number of targets to 256.
REV00431	Cannot save report due to error
Explanation	An attempt to save a report was unsuccessful because there was an error in the report definition.
Action	Correct the report definition and try again.
REV00432	There are no REVIEW hubs running on SVC {nnn}
Explanation	The AH (Available Review Hubs) command was entered but there are no hubs running in the current SVC to display.
Action	No action is required for this informational message.

REV00433 ADATMZ cannot be loaded

Explanation Upon initialization, SYSREVDDB calls a program named ADATMZ. This program was not available.

Action Make certain ADATMZ is installed and available to SYSREVDDB. If you are running Adabas Review in a CICS environment, verify that ACITMZ is installed. For more information, read the Adabas Review installation documentation.

If the problem persists, contact your Software AG technical support representative.

REV00434 ADATMZ: {message-text}

Explanation Upon initialization, SYSREVDDB calls a program named ADATMZ. One of the following messages (*message-text*) is included in the message and describes the error that has occurred with ADATMZ.

Message Text	Explanation	Action
No Adabas SVCs found	An internal error has occurred.	Contact your Software AG technical support representative for assistance.
No active targets for an SVC		
IDTHE appears to be invalid		
Invalid or unknown function		
Caller has answer area no answer count		
GETMAIN for SVC table failed		
GETMAIN for target table failed		
Load of link routine failed	ADATMZ dynamically loads ADALNKR. If ADALNKR cannot be loaded, subsequent calls to ADATMZ can cause this problem.	Be sure that the ADATMZ and ADALNKR modules, which are available in the Adabas or WAL load libraries, are all available for the TP monitor.
Load of CCSTCK routine failed	ADATMZ dynamically loads CCSTCK. If CCSTCK cannot be loaded, subsequent calls to ADATMZ can cause this problem.	Be sure that the ADATMZ and CCSTCK modules, which are available in the Adabas or WAL load libraries, are all available for the TP monitor.
Initialization call to DEPRTR failed	An internal error has occurred.	Contact your Software AG technical support representative for assistance.
No SVC table address provided by caller		
SVC table address inconsistent with PAL		

Message Text	Explanation	Action
No SVC count provided by caller		
Invalid SVC number too low	The version of ADATMZ that was loaded is too low.	Install the current version of ADATMZ. Contact your Software AG technical support representative for assistance.
Invalid SVC number too high	The version of ADATMZ that was loaded is too high.	Install the current version of ADATMZ. Contact your Software AG technical support representative for assistance.
No SVC <i>tbladdr</i> on get target call	An internal error has occurred.	Contact your Software AG technical support representative for assistance.
No target <i>tbladdr</i> on get target call		
No target table length		

- REV00435** **Buffer Pool reports cannot have DBID=ALL**
Explanation A value of "ALL" was specified as the DBID to monitor while attempting to start a report. Buffer Pool reports must only collect data from a single database, specifying "ALL" for them is not allowed. The report will not be started.
Action Specify a numeric DBID for the Buffer Pool report.
- REV00436** **Invalid field for client report**
Explanation A reporting field was referenced in a client report that was not valid for client reports. Client reports have a restricted set of available fields. A complete list of these fields is provided in ????.
Action Specify a valid field name.
- REV00437** **The maximum number of fields has been selected**
Explanation While selecting fields for a report using the online field selection screens, the maximum allowable number of fields you can select has been reached. All fields selected beyond the maximum are ignored.
Action Specify fewer fields, ensuring that only the most important fields are selected.

- REV00438** **Invalid field for a database report**
Explanation A client reporting field was referenced in a database report. This field is only permitted in a client report.
Action Specify a valid field name.
- REV00439** **Warning: A client report has been started.
If client monitoring is not turned on,
no client monitoring will be collected.
Press ENTER to exit**
Explanation This message appears in a pop-up box whenever a client report is started. It warns you that if client reporting has not been started, no client reporting data will be collected.
Action No action is required for this informational message. Press the ENTER key to remove the pop-up box containing the message.
- REV00440** **Redisplay buffer full - Redisplay unavailable**
Explanation The Redisplay function is unavailable because more than 5000 lines were displayed.
Action As a workaround, the report data can be printed using the HC command and other tools might be used to scroll through that output.
- REV00441** **Report name cannot be 'ALL'**
Explanation The name "ALL" was used as a report name in the report definition editor. The word "ALL" is reserved in Adabas Review and cannot be used as a report name.
Action Specify a different name.
- REV00442** **The display program has not been generated yet**
Explanation An attempt was made to edit the display program for a report but the display program has not yet been generated. This is most likely due to having copied a report where the display program name shows as "NEED RG".
Action Enter RG on the command line to generate the display program.
- REV00443** **Userid is required**
Explanation User profiles require a unique user or group ID in the **User ID / Group ID** field. You cannot create a user profile without one.
Action Specify a valid user or group ID for the user profile. Valid user or group IDs are eight alphanumeric characters long and begin with either a letter or a national (\$, @, or #) character.

REV00444	Group must be "Y" or "N"
Explanation	The setting for the Group access rule in the user profile definition is not "Y" (yes) or "N" (no). These are the only valid values for the field.
Action	Specify either "Y" or "N" for the Group access rule.
REV00445	Description is required
Explanation	User profiles require a description in the Description field.
Action	Specify up to 20 alphanumeric characters for the description.
REV00446	At least one report type must be "Y" for "EDIT REPORTS=Y"
Explanation	When the Edit Reports? access rule in a profile is set to "Y", at least one of the other edit report access rules must also be set to "Y". The other edit report access rules are Edit Bufferpool Reports? , Edit Client Reports? , Edit Cluster Reports? , Edit Database Reports? , and Edit Pulse Reports? .
Action	Either set the Edit Reports? access rule to "N" or specify "Y" for one of the other edit report access rules.
REV00447	All report types must be "N" for "EDIT REPORTS=N"
Explanation	When the Edit Reports? access rule in a profile is set to "N", none of the other edit report access rules may be set to "Y". The other edit report access rules are Edit Bufferpool Reports? , Edit Client Reports? , Edit Cluster Reports? , Edit Database Reports? , and Edit Pulse Reports? .
Action	Either set the Edit Reports? access rule to "Y" or specify "N" for all of the other edit report access rules.
REV00448	Cannot save - This is the only Administrator profile
Explanation	An attempt has been made to alter and save the only administrator profile so that it is no longer an administrator profile. Adabas Review will not allow you to turn the default profile or any administrator profile into a non-administrator profile if another administrator profile is not available.
Action	If you intend to change the only administrator profile to a non-administrator profile, first create another administrator profile. You can then alter and save the original administrator profile as you wish.

- REV00449** **Cannot purge - This is the only administrator profile**
- Explanation** An attempt has been made to delete the only administrator profile so that there is no longer an administrator profile. Adabas Review will not allow you to delete an administrator profile if another administrator profile is not available.
- Action** If you intend to delete this administrator profile, first create another administrator profile. You can then delete the original administrator profile.
-
- REV00450** **Monitor DBID {dbid} prohibited by profile**
- Explanation** An attempt has been made to create, start or alter a report for a DBID that is not included in the DBID list of your user profile.
- Action** Contact your system administrator to change your user profile or change the DBID you are trying to monitor in the report.
-
- REV00451** **User profiling is already installed**
- Explanation** An attempt was made to install the user profiling system when it is already installed.
- Action** No action is necessary for this informational message.
-
- REV00453** **You must enter at least one DBID**
- Explanation** When editing an Adabas Review user profile, the option **Monitor All Targets?** was set to "N", however, a DBID was not specified. At least one DBID must be specified if this option is set to "N".
- Action** Specify at least one DBID or set **Monitor All Targets?** to "Y".
-
- REV0454** **Profile reset to default values**
- Explanation** All values for the user profile you are viewing have been reset to the factory values.
- Action** No action is required for this informational message.
-
- REV00455** **Group must be 'Y' or 'N'**
- Explanation** An invalid or blank value was entered in the **Group Profile?** option of the user profile. This option must be set to either "Y" or "N".
- Action** Specify a valid value for the **Group Profile?** option.

REV00456	Info: Both "ALL TARGETS" and specific DBIDs are defined
Explanation	The user profile option Monitor All Targets? was set to Y but there are DBIDs listed. This is perfectly valid; in this case, the listed DBIDs have no effect on processing. However, if you later set the option to "N", the listed DBIDs will become the only valid DBIDs for the user.
Action	No action is necessary for this informational message.
REV00457	Invalid user ID
Explanation	The user ID entered on the user profile screen is invalid. User IDs must begin with a letter followed by any combination of alphanumeric or national (@#\$) characters.
Action	Specify a valid user ID.
REV00458	Review Client engine status has been turned {ON OFF}
Explanation	The Review Client status was toggled either on or off, as shown in the message.
Action	No action is required for this informational message.
REV00459	Review exit 2 is not installed
Explanation	While using the CM function, a call to communicate with client monitoring has determined that REVEXIT2 is not properly installed.
Action	Verify that the installation of REVEXIT2 has been performed correctly. For more information, refer to your Adabas Review (Phase 2) installation documentation.
REV00460	Review exit 2 is not active
Explanation	While using the CM function, a call to communicate with client monitoring has determined that REVEXIT2 is not active. It is possible to have REVEXIT2 linked into the link routine but not have it set to active in the LNKGBLS tables.
Action	Verify that the installation of REVEXIT2 has been performed correctly. For more information, refer to your Adabas Review (Phase 2) installation documentation.
REV00461	Response {nnn} received from REVEXIT2
Explanation	While using the CM function, a non-zero response code was returned from REVEXIT2. This is rare.
Action	Verify that the installation of REVEXIT2 has been performed correctly. For more information, refer to your Adabas Review (Phase 2) installation documentation. If you need additional assistance, contact your Software AG support representative.

- REV00462** **Ending apostrophe missing**
Explanation While editing the report processing rules for a report, an argument was specified with unpaired apostrophes.
Action Correct the argument syntax and try again.
- REV00463** **Ending apostrophe incorrectly placed**
Explanation While editing the report processing rules for a report, an apostrophe was incorrectly used.
Action Correct the syntax and try again.
- REV00464** **The maximum number of fields has been selected**
Explanation The maximum field limit has been reached. You cannot select any more fields.
Action Evaluate the fields you have selected, removing ones you don't really need and adding ones you do, but be sure to stay within the maximum field limit.
- REV00465** **Unable to obtain SVC list**
Explanation While trying to use the AA function, the Adabas Review nucleus was unable to obtain the list of available SVCs on the current LPAR.
Action Verify your Adabas Review installation is correct. If the problem persists, contact your Software AG support representative for assistance.
- REV00466** **Report option defaults converted successfully**
Explanation While editing a preexisting report after upgrading Adabas Review from version 4.4, the report defaults were converted to the current standard.
Action No action is required for this informational message.
- REV00467** **Invalid character in field name**
Explanation While editing a report, an invalid character was used in one of the field names.
Action Correct the field name syntax and try again.
- REV00468** **Cannot EC a non-client report**
Explanation An attempt was made to edit a non-client report using the EC command. The EC command only edits client reports.
Action Use the ER command to edit a non-client report.

REV00469	Command line entries are not valid here
Explanation	When entering Adabas Review for the first time after upgrading from a previous version, a user profile conversion takes place. The only actions allowed are on the screen. Command line entries are not allowed for this special one-time event.
Action	Do not enter data on the command line while this conversion is taking place.
REV00470	NUCID only valid in local mode
Explanation	The NUCID command was used but SYSREVDDB is currently communicating with an Adabas Review hub. The NUCID command is only valid when SYSREVDDB is communicating with a local mode target.
Action	Do not use the NUCID command in hub mode.
REV00471	No NUCID was selected
Explanation	PF5 was pressed on a NUCID list screen but no NUCID was selected.
Action	Select a NUCID or use PF3 to exit the NUCID screen.
REV00472	NUCID has been changed
Explanation	Upon request, the NUCID was successfully changed.
Action	No action is required for this informational message.
REV00473	CM function only available in hub mode
Explanation	An attempt to turn on the client report engine using the CM command was made in local mode. The CM command is available only in hub mode.
Action	Operate Adabas Review in hub mode before attempting to start the client reporting engine.
REV00474	Parameter missing or invalid
Explanation	The required NAME parameter was omitted or invalid when using the batch Natural Review program COPYREP.
Action	Add or correct the parameter and rerun the job.
REV00475	Parameter is missing or invalid
Explanation	The required NEWNAME parameter was omitted or invalid when using the batch Natural Review program COPYREP.
Action	Add or correct the parameter and rerun the job.

REV00476	Invalid parameter specified
Explanation	When using a batch Natural Review program, an unknown or invalid parameter keyword was specified.
Action	Correct the error and rerun the job.
REV00477	STACKPARAM= is incorrectly specified
Explanation	The optional STACKPARAM parameter was incorrectly specified when using the batch Natural Review program COPYREP.
Action	Correct the error and rerun the job.
REV00478	NAME= and NEWNAME= parameters are required
Explanation	While using the batch Natural Review program COPYREP, both of the required parameters NAME= AND NEWNAME= were missing.
Action	Supply the correct parameters and rerun the job.
REV00479	Undefined keyword in input
Explanation	When using the batch Natural Review program COPYREP, an unknown parameter keyword was specified. Valid keywords are NAME, NEWNAME, STACKPARAM and GO=YES.
Action	Supply only valid parameters and rerun the job.
REV00480	Words in report names must be separated by periods
Explanation	While using a batch Natural Review program that requires a report name as input, the report name did not have periods between each word. This is required to allow Natural to pass the parameters to the Adabas Review program correctly.
Action	Always place periods between words in report names. Correct the specification and rerun the job.
REV00481	Report already exists
Explanation	The new report name specified in the batch Natural Review program COPYREP already exists. COPYREP will not overwrite an existing report; instead it terminates with response code 12.
Action	Specify a unique name for the new report name or delete the report definition that already exists.

REV00482	Report definition has been purged
Explanation	This message confirms that the request to purge a report definition was successful.
Action	No action is necessary for this informational message.
REV00483	GO= parameter is incorrectly specified
Explanation	The GO= parameter specified in the batch Natural Review program COPYREP is specified incorrectly. The only valid syntax for this parameter is GO=YES.
Action	Correct the error and rerun the job.
REV00484	INVALID COST OPERATOR
Explanation	An invalid cost operator was entered on the Edit Report screen. Valid cost operators are: <ul style="list-style-type: none">■ "+": Plus -- add the cost factor to the field value.■ "-": Minus -- subtract the cost factor from the field value.■ "*": Multiply -- multiply the field value by the cost factor.■ "@": Fixed -- apply a fixed cost to each command select by the report.
Action	Enter a valid cost operator if you want to use the cost feature.
REV00485	COST FACTOR REQUIRED IF OPERATOR IS PROVIDED
Explanation	A cost operator was entered on the Edit Report screen but no cost factor was provided. Both an operator and a cost factor must be specified to use the cost feature.
Action	Specify a cost factor for the field in addition to the operator or remove the cost operator from the field specification on the Edit Report screen.
REV00486	COST OPERATOR REQUIRED IF FACTOR IS PROVIDED
Explanation	A cost factor was entered on the Edit Report screen but no cost operator was provided. Both an operator and a cost factor must be specified to use the cost feature.
Action	Specify a cost operator for the field in addition to the cost factor or remove the cost factor from the field specification on the Edit Report screen.
REV00487	COST FACTOR MUST BE A POSITIVE VALUE
Explanation	A cost factor was provided on the Edit Report screen but the value is zero or negative. The values must be a positive or negative integer. Negative values can only be specified if the cost operator is "*" or "@".
Action	Specify a valid cost factor and try again.

- REV00488** **COST FACTOR IS NOT NUMERIC**
Explanation A cost factor was entered on the Edit Report screen that was not numeric. Only numeric values are valid.
Action Specify a numeric value for the cost factor.
- REV00489** **ERROR WHILE TRYING TO RECATALOG USER EXIT**
Explanation During the first invocation of Adabas Review after a new installation or upgrade, an error occurred compiling and cataloging a user exit. The reason for the error cannot be determined.
Action If the problem persists, examine and correct any user written exits. If no user exit has been written or modified, contact your Software AG technical support representative.
- REV00490** **COST FACTOR can only have 7 numeric digits**
Explanation A COST factor was entered on the Edit Report screen with eight numeric numbers and no decimal points. The maximum number of numeric digits is seven.
Action Enter a value with no more than seven numeric digits. You may place a decimal point anywhere in the field if desired.
- REV00491** **COST OPERATOR '@' CAN ONLY BE USED FOR THE 'COMMANDS' FIELD**
Explanation A COST factor was entered on the Edit Report screen for the field COMMANDS but the operator was not the "@" operator. The only operator allowed for the field COMMANDS is "@", indicating a FIXED cost. No other reporting field may use the "@" operator.
Action Either change the field name to something other than COMMANDS or change the Cost operator to "@" and try again.
- REV00492** **COST IS ONLY VALID FOR SUM FIELDS**
Explanation A COST factor was entered into the ER screen for a field that is not a summary field. If the field does not have the SUM slot checked then COST is not possible.
Action Correct the ER screen and try again.
- REV00493** **THIS FIELD IS NOT ALLOWED FOR DETAIL REPORTS**
Explanation A field was entered on the ER screen for a detail report that can only be used in a summary report.
Action Remove the offending field.

REV00494	TARGET NAME MUST NOT BE BLANK
Explanation	The Target Name field must contain an alpha-numeric value. The field must not be all blanks.
Action	Enter a valid Target Name.
REV00495	REVIEW COMMANDS MUST BE 'Y' OR 'N'
Explanation	The Review Commands fields must contain a "Y" or an "N". All other values, including blank are invalid.
Action	Enter "Y" or "N".
REV00496	INVALID SYNTAX IN START PARAMETERS
Explanation	The Review command START or ST was entered into the command line to start an online report. The parameter data following the START command contained invalid syntax.
Action	Correct the error and re-submit.
REV00497	DBID VALUE IS NOT VALID
Explanation	The Review command START or ST was entered along with a DBID parameter. The DBID parameter data contains invalid syntax.
Action	Correct the error and re-submit.
REV00498	DBID KEYWORD MUST BE FOLLOWED BY "="
Explanation	The Review command START or ST was entered along with a DBID keyword. The DBID keyword must be followed by an equal sign (=). The equal sign was either missing or was an incorrect character.
Action	Correct the error and re-submit.
REV00499	DBID KEYWORD MUST BE PRECEDED BY ","
Explanation	The Review command START or ST was entered along with a DBID keyword. The DBID keyword must be preceded by a comma. The comma was either missing or was an incorrect character.
Action	Correct the error and re-submit.

REV00500	INVALID NUCID
Explanation	In LOCAL mode within a cluster environment, an attempt was made to alter the current nucleus ID, but the value entered was not valid. Valid values are 1 through 65535. Only numeric characters are allowed.
Action	Re-enter the nucleus ID using a valid value.
REV00501	CHANGE DBID PARAMETER ERROR(S)
Explanation	During a CHANGE DBID FROM operation, one or more parameter values were incorrect.
Action	Re-enter the CHANGE DBID command using valid values.
REV00502	INVALID INPUT PARAMETER(S)
Explanation	During a CHANGE DBID FROM operation, one or more parameter values were incorrect.
Action	Re-enter the CHANGE DBID command using valid values.
REV00503	FROM DBID IS INVALID
Explanation	During a CHANGE DBID FROM operation, the FROM DBID value was not valid. Valid values are 1-65535, ALL or NONE.
Action	Re-enter the CHANGE DBID command using valid values.
REV00504	INVALID DBID VALUE
Explanation	During a CHANGE DBID FROM operation, one or more of the DBID values were not valid. Valid values are 1-65535, ALL or NONE.
Action	Re-enter the CHANGE DBID command using valid values.
REV00505	FROM AND TO DBID CANNOT BE THE SAME
Explanation	During a CHANGE DBID FROM operation, both DBID values were identical. The values must be different.
Action	Re-enter the CHANGE DBID command using valid values.
REV00506	NO DBID(S) WERE CHANGED
Explanation	During a CHANGE DBID FROM operation, no DBIDs were found that match the FROM value.
Action	No action is required for this informational message.

REV00507 1 DBID HAS BEEN UPDATED

Explanation During a CHANGE DBID FROM operation, one DBID was found that matched the FROM value and was updated with the TO value.

Action No action is required for this informational message.

REV00508 {nnn} DBIDS HAVE BEEN UPDATED

Explanation During a CHANGE DBID FROM operation, multiple DBIDs were found that matched the FROM value and were updated with the TO value.

nnn will show the number of reports updated.

Action No action is required for this informational message.

11 Adabas Review 20xxx Messages

REV20001 Error in parameters as follows

Explanation

An error was detected during the parameter processing phase of Adabas Review. All parameters are processed for further error diagnosis. However, no data is handled by the Adabas Review processor. This message is followed by one of the PRM nnn error messages shown below.

Message ID	Message Text	Explanation
PRM001	Invalid statement name format	The format of the statement name (the first item of the parameter statement) is not correct.
PRM002	Statement name must be followed by a blank	The basic syntax of the parameter statement requires a blank. The parameter processor cannot correctly identify the statement.
PRM003	Unidentified statement name	The parameter processor has located a statement name that is not valid.
PRM004	Invalid separator	A character other than a comma or an equal sign was used as a delimiter.
PRM007	Insufficient positional parameters defined	More positional parameters were entered than were allowed.
PRM008	Null value invalid for required parameter	Values must be provided for all required parameters.
PRM009	Unidentified keyword	An invalid keyword has been identified.
PRM010	List-format value not allowed	Only a single value may be specified for the parameter.
PRM011	Invalid hex digit	Hexadecimal digits must be 0-9 or A-F.
PRM012	Length exceeded	The parameter supplied is longer than allowed.

Message ID	Message Text	Explanation
PRM013	Unexpected end-of-file	The parameter statements terminated prematurely. The parameter processor was expecting more input.
PRM014	Premature end of hex value	A trailing quote was not supplied to terminate a hexadecimal value.
PRM015	Invalid continuation statement	A statement has not been continued properly.
PRM016	Premature end of statement	The current statement ended abnormally; a comma, parenthesis, or quote may be missing.
PRM017	Invalid character in numeric parameter value	Only the characters 0-9 are allowed in numeric fields.
PRM018	Excessive numeric value length	The numeric value is too large for the parameter.
PRM019	Invalid parameter value	The value specified is not allowed for this parameter.
PRM020	Numeric value too large for processing	The numeric value is too large for the parameter to be processed.
PRM021	Parameter value truncated	Some parameter values were lost due to truncation.
PRM022	List size exceeded	Too many entries have been specified in a list of values.
PRM023	Required parameter missing	A required parameter is missing; it must be provided before execution can proceed.
PRM024	Parameter mutually exclusive to one of the other parameters	A specified parameter is mutually exclusive with one of the other specified parameters; only one of the mutually-exclusive parameters may be specified.

Action Correct the error and resubmit the job.

REV20002 Invalid file-type

Explanation An invalid INPUT statement file-type parameter has been detected. Processing is discontinued.

Action Correct the error and resubmit the job.

REV20003	Invalid file-type
Explanation	An invalid INPUT statement file-type parameter has been detected. Processing is discontinued.
Action	Correct the error and resubmit the job.
REV20004	Prior REPORT statement missing
Explanation	A valid REPORT statement must precede all other parameter statements except the INPUT statement. Processing is discontinued.
Action	Define a valid REPORT statement and resubmit the job.
REV20005	Invalid printer line size
Explanation	The printer line size must be at least 72 positions and cannot exceed 255 positions. Processing is continued with the default size of 133.
Action	To avoid the usage of the default and this message, define a valid LINE SIZE statement and resubmit the job.
REV20007	Detail report exceeds line size
Explanation	The number of printable characters for the report exceeds the report line size.
Action	Increase the report line size if possible, or reduce the report data to be displayed.
REV20008	INVALID FIELD NAME IN DISPLAY STATEMENT <i>fieldname</i>
Explanation	The field <i>fieldname</i> is not allowed in a DISPLAY statement.
Action	The report will be started without this field. The field name is either spelled incorrectly, or the field is not allowed for this TYPE of CLASS of report.
REV20010	Invalid field name in SUM statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20011	Invalid field name in MINIMUM statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.

REV20012	Invalid field name in MAXIMUM statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20013	Invalid field name in AVERAGE statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20014	Invalid field name in PERCENT statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20015	Invalid field name in COST statement
Explanation	The name must match one of the field names or alias names defined for the Adabas command log record.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20016	Invalid field usage for MINIMUM statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20017	Invalid field usage for MAXIMUM statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.

REV20018	Invalid field usage for SUM statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20019	Invalid field usage for AVERAGE statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20020	Invalid field usage for COST statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20021	Invalid field usage for PERCENT statement
Explanation	The field name specified is not a numeric field.
Action	The invalid field name is ignored. Processing is continued for the valid field names specified as positional parameters in this statement.
REV20022	ACCOUNT statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports.
Action	The statement is ignored and processing continues. Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20023	SUM statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports.
Action	The statement is ignored and processing continues. Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20024	MINIMUM statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports.
Action	The statement is ignored and processing continues. Specify this statement following a valid REPORT statement with TYPE=SUMMARY.

REV20025	MAXIMUM statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports. The statement is ignored and processing continues.
Action	Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20026	AVERAGE statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports. The statement is ignored and processing continues.
Action	Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20027	PERCENT statement invalid for a detail report
Explanation	The statement specified can only be used for summary reports. The statement is ignored and processing continues.
Action	Specify this statement following a valid REPORT statement with TYPE=SUMMARY.
REV20028	Applymod {nn} has been turned {ON OFF} by {user-id}
Explanation	The applymod <i>nn</i> has been turned ON/OFF by the user <i>user-id</i> .
Action	This message is for information only.
REV20029	Invalid COST value
Explanation	COST may be specified as field/operator/value, where valid operators are * (TIMES), + (PLUS), and - (MINUS). Fixed costs may be specified using the reserved word FIXED with an operator of @ (AT). Positive and negative values are allowed with or without a single imbedded decimal point.
Action	A value of 0 is assumed. Correct the value and resubmit the job.
REV20030	Invalid COPY file-type
Explanation	An invalid COPY statement file-type parameter was detected.
Action	The COPY statement is ignored and processing is continued. Correct the statement and resubmit the job if necessary.
REV20031	Termination task attached successfully
Explanation	Termination task attached successfully.
Action	This message is for information only.

REV20032	Termination task not found in the program library
Explanation	Termination task not found in the program library.
Action	Contact your Software AG technical support representative.
REV20033	I/O error occurred while loading termination task
Explanation	I/O error occurred while loading termination task.
Action	Contact your Software AG technical support representative.
REV20034	Sever parameter error(s)
Explanation	A parameter error of some significance was reported. All parameters are processed for further error diagnosis. However, the run is discontinued before any input data is processed.
Action	Correct the error and resubmit the job.
REV20035	Severe parameter error(s)
Explanation	A parameter error of some great significance has occurred. Parameter validation is terminated.
Action	Correct the error and resubmit the job.
REV20036	Report discontinued due to LIMIT parameter
Explanation	The report has been discontinued due to the LIMIT parameter. The LIMIT parameter on the report statement has been exceeded.
Action	This message is for information only.
REV20037	Summary report exceeds line size
Explanation	The number of printable characters for the report exceed the report line size.
Action	Increase the report line size if possible or reduce the report data to be displayed.
REV20038	Termination task initiated
Explanation	Termination task initiated.
Action	This message is for information only.

REV20039	Open operation failure on printer
Explanation	An error occurred attempting to open the above file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20040	Open operation failure on copy
Explanation	An error occurred attempting to open the copy file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20041	Open operation failure on log input
Explanation	An error occurred attempting to open the log input file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20042	Output error on printer
Explanation	An error occurred attempting to output to the printer file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20043	Output error on copy
Explanation	An error occurred attempting to output to the copy file. When this occurs, processing is discontinued.
Action	Correct the error and resubmit the job.
REV20044	Close operation failure on {file-name}
Explanation	An error occurred while Adabas Review attempted to close the specified file.
Action	This message is for information only.
REV20045	{YYYY-MM-DD hh:mm:ss} ADABAS RESPONSE CODE {rrr/sssss}
Explanation	A non-zero Adabas response code with subcode <i>sssss</i> has occurred during writing of the Adabas Review history file. In Review batch this was the result of the interaction with Adabas because of the COPY statement with FILETYPE=ADABAS.
Action	In the case of response 148, the history records will be stored on RVUALT file if this is specified in the Hub JCL. In the case of response 9, the Review Hub will do an OP command and re-execute the command.

In the case of any other response code, the data will not be written to the Review history file, but the processing of the report will continue. As long as the reason for the error is not repaired, the following write to the Review history file might end in the same error.

REV20046	Interval statistics task terminating
Explanation	Adabas Review detected that an EOJ command was issued to the Complete nucleus. Adabas Review terminates the interval task and starts the termination task.
Action	This message is for information only.
REV20047	Interval statistics task started
Explanation	The Adabas Review Interval Statistics task has been started.
Action	This message is for information only.
REV20048	No interval statistics record found
Explanation	Adabas Review unsuccessfully attempted to load the interval statistics record from its system file.
Action	Contact your Adabas Review administrator.
REV20049	{xxxxxxxxxxxx} will be saved every {nnn} mins
Explanation	The Adabas Review interval statistics task will save the data from the function or subsystem xxxxxxxxxxxx every nnn minutes.
Action	This message is for information only.
REV20050	{nnnnnnnn} Task attached successfully
Explanation	The Adabas Review task nnnnnnnn was attached successfully.
Action	This message is for information only.
REV20051	No dummy TID available for use by {nnnnnnnn} task
Explanation	Adabas Review was unable to attach the nnnnnnnn task because no dummy TID was available for use by the attached program.
Action	If this problem happens frequently, the system programmer responsible for Complete maintenance should be requested to increase the value of the NOTIBS keyword argument in the TIBTAB definition.

REV20052	{nnnnnnnn} Task not found in the program library
Explanation	Adabas Review was unable to attach the <i>nnnnnnnn</i> task because the program to be attached was not found in the Com-plete program library data set.
Action	Request that the system programmer responsible for Com-plete catalog the program.
REV20053	CLASS=CLIENT only in hub mode allowed
Explanation	The CLASS parameter was invalidly set to "CLIENT" in Adabas Review local mode for automatically started reports. You can only set the CLASS parameter to "CLIENT" in hub mode.
	Adabas Review processing continues, but the report is treated as a non-client report.
Action	Remove the CLASS=CLIENT specification from the parameters in Adabas Review local mode.
REV20054	TARGET=0 not allowed
Explanation	This message is produced in the RVUPRT00 member as an error message when the target database ID is zero, blank, or unassigned in the REVUAUT1 or RVUAUT2 file. Blank or unassigned targets default to a value of zero. Targets of zero are not allowed in autostarted reports.
Action	Update the TARGET parameter setting with a valid database ID.
REV20055	Unknown return code from attach
Explanation	The Adabas Review master interval statistics task was unable to attach the interval task because it received an unknown return code.
Action	Contact your Software AG technical support representative.
REV20056	{xxxxxxxxxxxxxxx} Task incorrectly linked
Explanation	The Adabas Review task has detected that <ul style="list-style-type: none"> ■ the module U2DENQ was not linked in; or ■ the incorrect version of U2DENQ was linked in.
Action	Rerun the link job provided in the Adabas Review source library, ensuring that the JCL is correct.

REV20061	Master interval task already active
Explanation	An attempt was made to start the master interval statistics task but the task was already active.
Action	Do not attempt to start the master interval task.
REV20062	Termination task terminated
Explanation	The termination task has ended.
Action	This message is for information only.
REV20063	{error-type} Error {error-number} occurred on line {line-number} of program {program-name}
Explanation	An error has occurred while executing the specified program: error-type = Command Processing Logon Processing Object Time Non-correctable Syntax
Action	Record message and contact your Software AG technical support representative.
REV20101	History file population started
Explanation	The Adabas Review history file task has been started.
Action	This message is for information only.
REV20102	History file population completed
Explanation	The Adabas Review history file task has completed execution.
Action	This message is for information only.
REV20103	Adabas RSP = {rrr} SUB {sssss} received
Explanation	The Adabas Review history file task received a non-zero Adabas response code <i>rrr</i> with subcode <i>sssss</i> .
Action	Evaluate the severity of the response code and perform the required steps to resolve the problem.

REV20104	History task posted for work
Explanation	The Adabas Review history file task has posted for work. This means that a detailed report with a COPY statement with FILETYPE=ADABAS is active and has selected data to write out to the Adabas Review history file.
Action	This message is for information only.
REV20105	History task waiting for work
Explanation	The Adabas Review history file task is waiting for work.
Action	This message is for information only.
REV20106	History task error during FREEMAIN
Explanation	The Adabas Review history file task received a nonzero return code attempting to free storage.
Action	Contact your Software AG technical support representative.
REV20107	History task unable to open RVUALT
Explanation	An error has occurred while attempting to open the RVUALT file.
Action	Verify that the JCL is correct and that the RVUALT file is available.
REV20108	{dbid} Review suspended, buffer unavailable
Explanation	REVIEW local mode is experiencing a temporary buffer shortage. CLOG records cannot be sent to the sub task REVIEWB. They are skipped until message REV20109 indicates that buffers are again available.
Action	Try to find the reason of buffer shortage.
REV20109	{dbid} Review resumed, {nn} CLOG records skipped
Explanation	Buffers have become available after the shortage noted by message REV20108. The number of CLOG records skipped during the shortage is given in the message (<i>nn</i>).
Action	Try to find the reason of buffer shortage.
REV20110	Corrupted length arrived from Natural. Length truncated to 65535
Explanation	A corrupted length value arrived in the format buffer of a search buffer from Natural. The corrupted length value is truncated to 65535.
Action	Contact your Software AG technical support representative for assistance in resolving the problem.

REV20111	SVC number {nnn} is invalid
Explanation	An invalid SVC number was used (for example, in the history file definition). The Adabas call will not be executed.
Action	Specify a valid SVC number for the Adabas call.
REV20112	RAOSSORT internal error
Explanation	An internal error occurred in the Adabas Review sort routine RAOSSORT. The sum of offset and length for sorted data is too big. The sort request is not performed.
Action	Contact your Software AG technical support representative to obtain a fix for this error.
REV20113	Sort option SUMFIELD not permitted.
Explanation	The sort option, SUMFIELD, was specified for a report, but there are no summary fields in the report.
Action	Remove the SUMFIELD sort option from the report or specify summary fields for the report. Then try again.
REV20114	Sort option SUMFIELD not permitted Report name: {rptname}
Explanation	The sort option, SUMFIELD, was specified for a report, but there are no summary fields in the report.
Action	Remove the SUMFIELD sort option from the report or specify summary fields for the report. Then try again.
REV20115	Field {fn} does not fit into report {rrrr}
Explanation	The field listed in the message (fn) is a valid field name, but it does not fit into the printed report or history file, because the record length is not big enough. As a result, the field is empty in the report or history file.
	<i>rrrr</i> is the report name truncated to 29 characters.
Action	Omit this field or increase the record size.
REV20118	RVUAUT1 selected. RVUAUT2 selected.
Explanation	The user has to specify two data definition job control statements
	<pre>//RVUAUT1 DD ...</pre>
	or
	<pre>//RVUAUT2 DD ...</pre>

- Action** This message tells the user which statement is selected by Adabas Review.
 This message is for your information only.
- REV20119** **Catastrophic error, no registers available, check dump.**
Explanation An abend occurred, the REVIEW Estae got control, but the data were corrupted so completely that the ESTAE cannot continue its work.
Action This message is for your information only. Check the dump to find the error. Contact your Software AG technical support representative.
- REV20120** **Review {v.r.s} running with Adabas {n.n}**
Explanation Adabas Review has been given control for the first time where *v . r . s* is the Adabas Review version and *n . n* is the Adabas version.
Action This message is for information only.
- REV20121** **Attach for Review subtask failed**
Explanation Adabas Review attempted to attach an operating system subtask but received a nonzero return code from this action.
Action Examine the messages displayed by the operating system and correct the problem. The possibility exists that the address space, region, or partition was not large enough to attach the task, or the attached module RAOSRE VW was not in the library concatenations so it could not be found to be loaded.
- REV20122** **REV20122 - Adabas Review ESTAE exit driven.**
REV20122 - ADABAS REVIEW now disabled.
REV20122 - ABEND 000xx000 PSW xxxxxxxx xxxxxxxx
REV20122 - R0 xxxxxxxx - R1 xxxxxxxx - R2 xxxxxxxx - R3 xxxxxxxx
REV20122 - R4 xxxxxxxx - R5 xxxxxxxx - R6 xxxxxxxx - R7 xxxxxxxx
REV20122 - R8 xxxxxxxx - R9 xxxxxxxx - R10 xxxxxxxx - R11 xxxxxxxx
REV20122 - R12 xxxxxxxx - R13 xxxxxxxx - R14 xxxxxxxx - R15 xxxxxxxx
REV20122 - Dump has been taken.
Explanation The main task of Adabas Review had an abend. The REVIEW ESTAE got control and issued these messages and was forced to write a dump. The Adabas nucleus will continue working, but Review will be disabled.
Action This message is for your information only. Check the dump to find the error. Contact your Software AG technical support representative.

REV20123	ESTAE driven recursively.
Explanation	The REVIEW ESTAE is called a second time, although REVIEW should run disabled.
Action	This message is for your information only. Check the dump to find the error. Contact your Software AG technical support representative.
REV20124	Allocation for Review buffer pool failed
Explanation	Adabas Review unsuccessfully acquired storage for the Adabas Review buffer. The size of the buffer is determined by the BUFFER-SEGMENTS parameter on the Adabas Review INPUT statement.
Action	Increase the size of the address space, region, partition, or virtual machine that Adabas Review is executing or decrease the size of the Adabas Review buffer.
REV20125	Review subtask successfully attached
Explanation	Adabas Review successfully attached an operating system subtask.
Action	This message is for information only.
REV20126	Review subtask detached
Explanation	Adabas Review successfully detached an operating system subtask during its termination logic.
Action	This message is for information only.
REV20127	REV20127 - ADABAS REVIEW forced abnormal termination. REV20127 - R0 - nnnnnnnnn R1 - nnnnnnnnn R2 - nnnnnnnnn R3 - nnnnnnnnn REV20127 - R4 - nnnnnnnnn R5 - nnnnnnnnn R6 - nnnnnnnnn R7 - nnnnnnnnn REV20127 - R8 - nnnnnnnnn R9 - nnnnnnnnn RA - nnnnnnnnn RB - nnnnnnnnn REV20127 - RC - nnnnnnnnn RD - nnnnnnnnn RE - nnnnnnnnn RF - nnnnnnnnn
Explanation	The Review subtask REVIEWB or the Review batch module REVIEWB found an internal serious error. REVIEWB is disabled.
Action	This message is for your information only. Check the dump to find the error. Contact your Software AG technical support representative.
REV20128	Attach for history subtask failed
Explanation	Adabas Review attempted to attach an operating system subtask but received a nonzero return code from this action.
Action	Examine the messages also displayed by the operating system and correct the problem. The possibility exists that the address space, region, or partition was not large enough to attach the task, or the attached module was not in the library concatenations so it could not be found to be loaded.

REV20129	History subtask detached
Explanation	Adabas Review successfully detached an operating system subtask during its termination logic.
Action	This message is for information only.
REV20130	History subtask successfully attached
Explanation	Adabas Review successfully attached an operating system subtask.
Action	This message is for information only.
REV20141	GETMAIN for spare area failed
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.
REV20142	RCSBINIT - Review initialization started
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.
REV20144	Trans-Port activity Records queued {qnn} Records skipped {snn}
Explanation	This message displays the number of records from clients that have been queued (<i>qnn</i>) and skipped (<i>snn</i>) via Trans-Port to the Adabas Review hub. Records are skipped when no storage is available to send them to the hub
Action	To resolve the storage problem, you might choose to increase the number of attached buffers (NAB ADARUN parameter) used during the Adabas Review session.
REV20145	Free main error, length is zero
Explanation	An internal error occurred freeing storage; a length of zero is requested.
Action	Contact your Software AG technical support representative for assistance.
REV20146	RCSBSUM - summary processing
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.

REV20147	RCSBFINI - called for termination
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.
REV20148	RCSBREIN - reinitialization
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.
REV20149	Review is operative
Explanation	This message indicates a specific phase of Adabas Review execution.
Action	This message is for information only.
REV20150	File RVUALT can not be opened
Explanation	This is an internal error that rarely occurs.
Action	Contact your Software AG technical support representative.
REV20151	Now switching logs from {clog-dataset1} to {clog-dataset2}
Explanation	A LOG switch is in progress. The FROM data set can now be copied. The TO data set will receive command log output.
Action	This message is for information only.
REV20152	Now it's too late to copy {output-data set}
Explanation	The specified output data set is open for output. The data in this data set can no longer be copied.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4rs003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of your Adabas Review installation.
REV20153	RAOSAUTO subtask detached
Explanation	The RAOSAUTO subtask has been detached successfully.
Action	This message is for information only.

REV20154	Auto regenerate started
Explanation	The RAOSAUTO automatic regeneration subtask started successfully.
Action	This message is for information only.
REV20155	Auto regenerate completed
Explanation	The RAOSAUTO automatic regeneration subtask has completed successfully.
Action	This message is for information only.
REV20156	Response code {rsp} for {cmd} command to DBID= {dbid} ,FNR= {fnr}
Explanation	The RAOSAUTO automatic regeneration subtask issued an Adabas call and received the response indicated in the message.
Action	Verify that the LFILE/NTFILE statement for Adabas Review points to the correct DBID and FNR for the Adabas Review data file.
REV20157	GETMAIN failed
Explanation	A request for a GETMAIN failed in RAOSSYDR. The Adabas task (in hub mode) or the Adabas Review task (in local mode) will be shut down immediately.
Action	Increase the region size for the Adabas task.
REV20158	Doing open call because of Resp 9
Explanation	The Adabas Review history task had to perform an OP (open) call during history data population because an Adabas response code 9 (ADARSP009) was encountered.
Action	This message is for information only.
REV20159	Freemain failed
Explanation	A request for a FREEMAIN to RAOSSYDR failed.
Action	Contact your Software AG technical support representative.
REV20160	History file population failed
Explanation	An error was encountered during Adabas Review history file population and the history subtask was unable to continue.
Action	Check additional warning messages issued by subtask.

REV20161	{nnnnn} ET commands were issued
Explanation	The number of ET commands issued by the Adabas Review history task was <i>nnnnn</i> . The ET commands were issued to synchronize history file population.
Action	This message is for information only.
REV20162	Load failed for {module-name}
Explanation	A request for a LOAD to RAOSSYDR failed. The requested module was not found in the STEPLIB.
Action	Check the STEPLIB to be sure that the module is present.
REV20163	Immediate recovery for RVUALT required
Explanation	The Adabas Review history task encountered an error during history file population and could not continue processing.
Action	Copy the RVUALT data file to another sequential data file and reinitialize Adabas Review.
REV20164	Open failed for {xxxxxxx}
Explanation	A request for an OPEN for DD or file name <i>xxxxxxx</i> to RAOSSYDR failed.
Action	Check that the required DD card or FILEDEF is present in the task job stream.
REV20165	The value of field {fieldname} is {value} It is too big, {trunc-value} stored instead.
Explanation	When storing data into the history file it was detected that the value (<i>value</i>) of the field listed in the message (<i>fieldname</i>) is bigger than the maximum field length allowed in the history file. Storing such a data can result in later Adabas response code 55 (ADARSP055). The value is therefore truncated (<i>trunc-value</i>) and stored instead.
Action	Contact your Software AG support representative about this message to avoid this in the future.
REV20166	Record to {xxxxxxx} skipped, because > 32K
Explanation	While writing a CLOG record, Adabas Review determined that the record was larger than 32767 bytes. Records larger than 32767 bytes are not written to the data set. The DD name or link name of the data set is given in the message (<i>xxxxxxx</i>). This message is issued only one time.
Action	Contact your Software AG technical support representative.

- REV20167** **Big amount of storage requested.**
Explanation More than 2 GB of storage was erroneously requested.
Action Determine why such a large amount of storage was erroneously requested. If the problem persists, contact your Software AG technical support representative for assistance.
- REV20180** **Requested buffer too big.**
Explanation An amount of requested storage is too large.
Action Determine why such a large amount of storage was erroneously requested and who requested it. If the problem persists, contact your Software AG technical support representative for assistance.
- REV20184** **Command log records selected: {nnnnnnnnnn}**
Explanation This message is issued at shut down of REVIEW. It displays the number of command log records arriving the sub task REVIEWB.
Action No action is required for this informational message.
- REV20185** **Unable to load user exit {module-name} - RC {xx} ({xx})**
Explanation The Adabas Review command log processor was unable to load the specified user exit module to copy Adabas Review command logs.
Action Ensure that the module exists in one of the libraries accessible by Adabas Review.
- REV20186** **ADAIOR {function} request failed**
Explanation Internal error occurred.
Action Contact your Software AG technical support representative.
- REV20187** **Function {function} no longer supported by interface**
Explanation Internal error occurred.
Action Contact your Software AG technical support representative.
- REV20189** **{nnnnnnnnnn} Command log record(s) skipped.**
Explanation The number of records which were not sent to subtask REVIEWB because they were sent from the history feature is given in the message (*nnnnnnnnnn*).
Action If this database contains a history file, no action is required for this informational message.

 If this database does not contain a history file, determine why history records are being sent to this database.

REV20190	User parm error - {text}
Explanation	A syntax error was recognized when file RVUFLD was read (custom reporting fields). Possible texts include the following:
	<pre> CANNOT LOCATE USERFLD INVALID NAME PARAMETER INVALID INTYPE PARAMETER INVALID OUTTYPE PARAMETER INVALID HEADER PARAMETER INVALID ADANAME PARAMETER INVALID CALC PARAMETER PREVIOUS PARM LEN TOO LONG PREVIOUS PARM NOT NUMERIC DELIMITER <=> NOT FOUND KEYWORD MISSING OR NOT RECOGNIZED </pre>
Action	Correct the syntax error and restart Adabas Review.
REV20191	Adabas {vrs} not supported
Explanation	In local mode when Adabas Review is called by Adabas, the Adabas Review nucleus verifies that the Adabas version is for a compatible version. If it is incompatible, this message appears. This message identifies the incompatible version of Adabas (<i>vrs</i>). The connection between the two products will not work, and Adabas Review will not collect any data.
Action	Call compatible versions of Adabas Review from the Adabas nucleus. For information about version compatibility, read <i>Adabas and Adabas Review Version Compatibility</i> , in the <i>Adabas Review Release Notes</i> .
REV20192	Only CLOGLAYOUT=8 supported
Explanation	Adabas Review received erroneous CLOG records with CLOGLAYOUT not set to "8". Only CLOGLAYOUT=8 is supported.
Action	In this version of Adabas, only CLOGLAYOUT 8 should be produced. Check the version of Adabas that is being used.
REV20199	Old CLEX from prior ADA V {vr} arrived and will be converted
Explanation	Adabas Review received a call from an Adabas version <i>v.r</i> (or earlier) database. The internal structure of the CLEX is converted to the new format of the CLEX.
Action	No action is required for this informational message.

REV20229 **Corrupted record skipped**

Explanation When analyzing command log records with batch program REVIEWB, corrupted command log records may occur. Instead of abending the batch job, the record is skipped and the message REV20229 is issued. The number of these messages is limited to 20 messages.

Action Find out why there are corrupted command log records. This may involve editing the CLOG and manually looking for inconsistencies. For REVIEW this message is for information only.

REV20230 **Number of corrupted record skipped: {nnnnnn}**

Explanation This message is issued after the sequence of skipped records with message REV20229 is finished.

Action This message is for information only. See also action for REV20229.

REV20231 **Report interval reached {report-name }**

Explanation The report named in the message (*report-name*) was suspended because the time interval specified in the Review Option screen or in the RVUAUT1/2 data set was reached.

Action No action is required for this informational message. It can be switched on or off by applying the optional zap RY4rs003, where *r* is the release number and *s* is the system maintenance level of Adabas Review you have installed.

REV20232 **Report {report-name }{status-message}**

Explanation One of the following status messages applied to the specified report:

`DEACTIVATED DUE TO MAXSTORE LIMIT EXCEEDED`

The specified active report stopped collecting data because all storage space allocated by the MAXSTORE parameter has been used.

`DEACTIVATED DUE TO STORAGE ALLOCATION FAILURE`
`↵`

The specified active report stopped collecting data because no more storage is available in the address space/partition.

`ENCOUNTERED STORAGE ALLOCATION FAILURE ,`
`REINITIALIZATION SCHEDULED`

The specified active report stopped collecting data because no more storage is available in the address space/partition. All reports will be reinitialized.

DEACTIVATED DUE TO HASH TABLE MANAGER
INITIALIZATION ERROR

The specified active report could not collect data because of an error in the hash table manager.

DEACTIVATED DUE TO HASH TABLE MANAGER FIND ERROR

The specified active report could not collect data because of an error in the hash table manager.

DEACTIVATED DUE TO TERMINATION PROCESSING
STORAGE ALLOCATION FAILURE

The specified active report could not perform termination processing because no more storage is available in the address space/partition.

HISTORICAL DATA COLLECTION DEACTIVATED DUE TO
STORAGE ALLOCATION FAILURE

The specified report could not perform historical data collection because no more storage is available in the address space/partition.

Action Investigate the cause of the specific error. In the event of a failure in the hash table manager, contact your Software AG technical support representative.

REV20233

Parameter error(s) encountered processing RVUEXI parameter file

Explanation

Parameter error(s) were encountered when Adabas Review was processing the RVUEXI parameter file specified in the Adabas startup procedure.

Action

Refer to the RVUEXP output file to determine the parameters that were in error and correct the specified parameters.

REV20234

Report suspended {reportname}

Explanation

The report named in the message (*reportname*) was suspended for one of the following reasons:

- The CL, PS, SU, or RF command was issued from within SYSREVDB.
- The time specified in the INTERVAL option for the report was exceeded.

Action

No action is required for this informational message. It can be switched on or off by applying the optional zap RY4*rs*003, where *r* is the release number and *s* is the system maintenance level of Adabas Review you have installed.

REV20235	Report restarted {reportname}
Explanation	The report named in the message (<i>reportname</i>) was restarted automatically after a suspension because the report RESTART option is set to "Y". If a report is suspended with the SU command within SYSREVDDB, it is restarted no matter how the RESTART option is set.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4rs003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.
REV20236	Report {reportname} started by {userid}
Explanation	The report named in the message (<i>reportname</i>) was started as an autostarted report during Adabas Review startup, manually, or after the RF command was issued within SYSREVDDB. The user ID (Natural *INIT-USER value, if this is zero the value UNKNOWN will be displayed) shown in the message is either "AUTOSTRT" if the report is autostarted or the name of the user who started or refreshed the report.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4rs003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.
REV20237	Report resuspended {reportname}
Explanation	The report named in the message (<i>reportname</i>) was suspended for one of the following reasons: <ul style="list-style-type: none"> ■ The CL, PS, SU, or RF command was issued from within SYSREVDDB; ■ The time specified in the INTERVAL option for the report or the MAXK limit was exceeded; or ■ There are internal storage limitations or errors.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4rs003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.
REV20238	Report MAXK suspended {reportname}
Explanation	The report named in the message (<i>reportname</i>) was suspended because the storage maximum specified in the MAXK report option was exceeded. If the report RESTART option is set to "N", message REV20232 is also printed.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4rs003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.

- REV20239** **Field {fldname} is not a client report field**
- Explanation** The field name given in the message (*fldname*) was requested for a client report, but is not valid for client reports.
- Adabas Review processing continues normally, but the values for the field are empty.
- Action** Remove the field from the client report.
-
- REV20241** **A buffer will not fit into LORECR**
- Explanation** During conversion of log records to the Adabas Review internal command log record (LORECR) format, a buffer would not fit into LORECR due to LORECR size limitations. The information of this buffer is cut and you may not be able to find the desired buffer information in the report output.
- Action** If the data in the affected buffer is not used in a report definition, this error can be ignored as it causes no consequences. However, if this error causes data to be missing, contact your Software AG technical support representative for assistance.
-
- REV20253** **This version of ADATMZ does not support all features
ADATMZ version is {v.r.s}**
- Explanation** The module ADATMZ was loaded from either the WAL or the ADA library. The ADATMZ version loaded does not support all of the features needed for the current Adabas Review version. The current version of ADATMZ is given in the message (*v.r.s*).
- Action** Check the Adabas Review version to find out more about the new features and, if necessary, specify a newer WAL or ADA library to obtain the newer version of the ADATMZ module.
-
- REV20255** **{parameter} set too low or missing**
- Explanation** The parameter of the INPUT statement named in the message (*parameter*) is set too low or is not coded. Possible parameters that may appear in this message are the BUFFER-SEGMENTS parameter, the BUFFERS-4K parameter, or the BUFFERS-32K parameter. The following table describes these parameters further:

Parameter	Description	Minimum Value
BUFFERS-4K	The number of buffer pool entries that have a length of 4096 or less. This parameter is usually specified along with the BUFFERS-32K parameter.	124
BUFFERS-32K	The number of buffer pool entries that have a length of 4097 or greater. This parameter is usually specified along with the BUFFERS-4K parameter.	15
BUFFER-SEGMENTS	The number of 512-byte segments to be obtained for the Adabas Review buffer pool	2000 (which results in about

Parameter	Description	Minimum Value
	when running the Adabas Review interactive processor. When a value for BUFFER-SEGMENTS is specified, the total storage indicated by the specification is split in half between 4K buffers and 32K buffers.	124 4K and 15 32K buffers)

Adabas Review runs with the minimum value setting of these parameters. However, if this setting is too small for a hub environment running Trans-*port*, command log records might be lost.

For more information about the INPUT statement, read *INPUT Statement*, in the *Adabas Review User Guide*.

Action Increase the value setting of the buffer parameters, as described above.

REV20257 Rpt '{rptname}' was stopped by {userid}

Explanation The report named in the message (*rptname*) was stopped using the PS command on the Started Reports screen by the user with the user ID (Natural *INIT-USER value, if this is zero the value UNKNOWN will be displayed) listed in the message (*userid*).

Action No action is required for this informational message.

REV20258 For {dsname} no valid data set found.

Explanation For the logging file with dataset name *dsname* there is no internal AMT found. Either the *dsname* is incorrect or this dataset is not defined for the Adabas Review system.

Action Check either the Adabas nucleus JCL (in local mode) or the Adabas Review HUB JCL (in Hub mode) against the report definitions and correct one of them.

REV20259 REVIEW field {fieldname} cannot be stored into history file.

Explanation While building the record buffer for writing the report data to the history file, Adabas Review detected an invalid length definition for the field *fieldname* in its internal tables.

Action Contact your Software AG technical support representative.

REV20260 CLEX conversion caused buffer truncation

Explanation While converting the CLEX from version 82 to 83 format, the command log record had to be cut to 32764 bytes. The message is issued only once upon the first occurrence of this event. It is for informational purpose only.

Action No action is required for this informational message.

REV20261	Rpt {rptname} put on {queue} for sec={nnnn}
Explanation	The report named in the message (<i>rptname</i>) was placed into the queue <i>queue</i> for <i>nnnn</i> seconds. The <i>queue</i> could be either ACTI or SCHD.
Action	No action is required for this informational message. It can be switched on or off by applying the optional zap RY4rs003, where <i>r</i> is the release number and <i>s</i> is the system maintenance level of Adabas Review you have installed.
REV20262	Rpt {rptname} {variable message text}.
Explanation	The auto started scheduled report named in the message (<i>rptname</i>) has invalid schedule data as indicated in the <i>variable message text</i> . The variable message text content can be one of the following: <ul style="list-style-type: none"> ■ schedule start not before schedule end The point in time specified by SCHED-STRTDATE and SCHED-STRTTIME is not before the point in time specified by SCHED-ENDDATE and SCHED-ENDTIME. ■ schedule duration larger than interval SCHED-DURATION and SCHED-INTERVAL have been specified and SCHED-DURATION is larger than SCHED-INTERVAL. If specified, SCHED-INTERVAL has to be larger than SCHED-DURATION. ■ invalid schedule start/end date/time One of the parameters SCHED-STRTDATE, SCHED-STRTTIME, SCHED-ENDDATE, SCHED-ENDTIME contains an invalid date or time value.
Action	Correct the scheduling data of your report definition accordingly.
REV20263	Set timer failed rpt {rptname} RC={nnn} secs={nnnnnnnnnnnn}
Explanation	While processing the scheduled report <i>rptname</i> Adabas Review failed to set a timer for either the active or waiting processing phase of the report with the specified return code (RC= <i>nnn</i>) for the specified amount of seconds (secs= <i>nnnnnnnnnnnn</i>).
Action	Contact your Software AG technical support representative.

12

RE VH* - Adabas Review Hub Messages

RE VH03	{hub-id} CLIENT {dbid} [- {nuc-id}] HAS REGISTERED IN
Explanation	When a client nucleus initializes, the nucleus sends a call to the hub specified on the ADARUN parameter REVIEW to determine whether an Adabas Review hub is active. When it receives the call, the Adabas Review hub displays this message identifying the DBID of the client nucleus. If the client nucleus is a member of an Adabas Parallel Services or Adabas Cluster Services cluster, then the corresponding nucleus ID is also displayed.
Action	No action is required for this informational message.
RE VH04	{hub-id} CLIENT MONITORING {jobname} HAS REGISTERED IN
Explanation	When client reporting initializes, the nucleus sends a call to the hub specified on the ADARUN parameter REVIEW to determine whether an Adabas Review hub is active. When it receives the call, the Adabas Review hub displays this message identifying the job name of the client nucleus.
Action	No action is required for this informational message.
RE VH06	{hub-id} CLIENT {{dbid} {nucid}} HAS CHECKED OUT
Explanation	When a client nucleus is closing, the nucleus calls the hub identified on the ADARUN REVIEW parameter. When it receives the call, the hub displays this message identifying the DBID of the client nucleus. If the client nucleus is a member of an Adabas Parallel Services or Adabas Cluster Services cluster, then the corresponding nucleus ID also displayed.
Action	No action is required for this informational message.

REVH07	{hub-id} CLIENT {dbid} WAS DELETED
Explanation	The specified client nucleus was deleted from the hub's registered client list.
Action	None required. This is for your information only.
REVH10	{hub-id} CLIENT {dbid} WAS SENT A MESSAGE
Explanation	When there is a change in the monitoring or reporting status of a client nucleus by Adabas Review, the hub sends a notification to the client nucleus. This message is displayed when the notification is sent to the client nucleus.
Action	No action is required for this informational message.
REVH11	{hub-id} { NO {count} } REVIEW REPORT(S) STARTED. {hub-id} { NO {count} } REPORT(S) REQUIRING BUFFERS.
Explanation	These messages are displayed in conjunction with the REVH10 message and indicate the status of information transmitted to the client nucleus by the hub. <i>count</i> indicates the number of started reports and/or the number of reports requiring buffers.
Action	None required. This message is for your information only.
REVH12	{hub-id} OUTBOUND MESSAGE TO CLIENT {{dbid} {nucid}} RECEIVED RSP {rsp/subcode}
Explanation	This message is displayed at the completion of a notification call to a client nucleus identified by the database ID (<i>dbid</i>) or nucleus ID (<i>nucid</i>) given in the message. In cluster environments, a nucleus ID is listed; in all other environments, a database ID is listed. A response code of zero indicates that the message was successfully received.
Action	No action is required for this informational message.
REVH13	{hubid} Dbid Nucid Last-act Rpts Buffers Log-records {hubid dbid nucid last-act-time globrpts/dbrpts buffers log-recs} {hubid} CL {jobname last-act-time clientrpts/dbrpts} ----- {log-recs}
Explanation	This message is displayed in response to the DCLIENT operator command. A title that reads " <i>hubid</i> Dbid Nucid Last-act Rpts Buffers Log-records" appears as the first REVH13 message. Thereafter, the following information is supplied under the corresponding column titles for each client nucleus registered with the hub:

<i>buffers</i>	<p>The buffers requested for this client are displayed in the following format <i>frsvtom</i>, where:</p> <ul style="list-style-type: none"> ■ <i>f</i>: An "F" appears here if a format buffer was requested. ■ <i>r</i>: An "R" appears here if a record buffer was requested. ■ <i>s</i>: An "S" appears here if a search buffer was requested. ■ <i>v</i>: A "V" appears here if a value buffer was requested. ■ <i>i</i>: An "I" appears here if an ISN buffer was requested. ■ <i>o</i>: An "O" appears here if an I/O list buffer was requested. ■ <i>m</i>: An "M" appears here if a multifetch buffer was requested <p>If a buffer type was not requested, a dash ("-") appears in the appropriate location above.</p> <p>Note: In the case of the client report line in this message (the line starting with CL), there are no buffers, so dashes will appear in this section.</p>
<i>clientrpts</i>	The number of client reports running.
<i>dbid</i>	The database ID of the client nucleus.
<i>dbrpts</i>	The number of database-specific reports running for this client.
<i>globrpts</i>	The number of DBID=ALL reports running for this client.
<i>hubid</i>	The Adabas Review hub ID.
<i>jobname</i>	The job name of the client reporting client.
<i>last-act-time</i>	The time of last activity or the time when the last command log record was received from the client nucleus, in <i>hh:mm:ss</i> format.
<i>log-recs</i>	The number of command log records received from the client nucleus. For client report entries, this is the number of all command log records received from the client address space identified by the job name given in the message (<i>jobname</i>).
<i>nucid</i>	If the client nucleus represents an Adabas Parallel Services or Adabas Cluster Services database, the number of the nucleus within the cluster is also displayed.

The last line of the message lists the number of client reports running in the hub.

Action

No action is required for this informational message.

REVH14	{hub-id} CLIENT {dbid} IS NOT REGISTERED
Explanation	This message is displayed in response to an operator command that requested a service for a nonexistent client nucleus. The requested client nucleus could not be found in the hub's registered client list.
Action	Ensure that the correct client nucleus ID is properly specified and reenter the operator command.
REVH15	{hub-id} NO CLIENTS REGISTERED
Explanation	An operator command requested a service or status and there are no client nuclei presently listed in the hub's registration list.
Action	None required. This is for your information only.
REVH16	{hub-id} THE REVIEW HUB IS NOT RUNNING APF AUTHORIZED
Explanation	To use the Trans-port feature of the Adabas Review hub under z/OS, the load library needs to be APF-authorized.
Action	APF-authorize the load library if you want to use the Trans-port feature.
REVH17	{hub-id} TRANS-PORT IS DISABLED
Explanation	The reason is provided in the previous message.
Action	The Trans-port feature is not available in z/VSE environments. To use the Trans-port feature in other supported operating environments, refer to the previous message.
REVH21	{hub-id} A CLIENT ATTEMPTED TO REGISTER WITHOUT A DBID
Explanation	The hub received a call from an unknown client. The hub ignores the request.
Action	None required. This is for your information only.
REVH22	{hub-id} CLIENT {dbid} UNABLE TO ALLOCATE LIST SPACE
Explanation	The hub was unable to insert a new client into its registration list. The client is given a non-zero response to prevent further communication. The hub continues processing and the registration of the new client is ignored.
Action	Enter a <code>DCLIENT=ALL</code> operator command and review the list of clients. If there is a possibility of deleting a non-active client, then enter the <code>STOPCLIENT=dbid</code> operator command to stop the client from sending data, followed by a <code>DELCLIENT=dbid</code> to release the space in the registration list. To initiate the registration of the previously rejected client, start an Adabas Review report for that client.

REVH24	{hub-id} REVIEW NUCLEUS TERMINATED, REVIEW HUB ABORTING
Explanation	The Adabas Review nucleus terminated abnormally. The hub can no longer process Adabas Review data and will terminate.
Action	Check all messages from Adabas Review to determine the cause of the abnormal termination of the Adabas Review nucleus. Correct the problem and restart Adabas Review.
REVH25	{hub-id} REVIEW BUFFER SHORTAGE, INCREASE VALUE FOR BUFFER-SEGMENTS
Explanation	The hub incurred a shortage of REVIEW buffers. The value for the available storage can be determined by the BUFFER-SEGMENTS parameter of the INPUT statement
Action	See the <i>Adabas Review User</i> documentation.
REVH26	{hubid} HANDSHAKE COMMAND FOR DATA BASE {{dbid} {nucid}} ISSUED UBRSP={ubrsp}
Explanation	For diagnostic purposes, a handshake trace from the Adabas Review hub to the databases is activated. The Adabas Review hub issues a handshake command to a database because a report for this database is started, changed, or stopped. When the Adabas Review hub is brought down via ADAEND, the handshake command for the databases is also issued. UBRSP=8 indicates that the command is immediately complete and a 16-call is not required. UBRSP=4 indicates that the call is not complete and a 16-call is required.
	Either a database ID (<i>dbid</i>) or nucleus ID (<i>nucid</i>) is given in the message. In cluster environments, a nucleus ID is listed; in all other environments, a database ID is listed.
Action	No action is required for this informational message.
REVH27	{hubid} HANDSHAKE COMMAND FOR DATA BASE {{dbid} {nucid}} HAS COMPLETED {hubid} RSP={acbrsp/acbsubcode}, ACBRSP={acbrsp}
Explanation	For diagnostic purposes, a handshake trace from the Adabas Review hub to the databases is activated. An Adabas X'1C' call with UB was sent to a database by the Adabas Review hub and message REVH26 was issued. A 16-call was issued (if required) and the command completed with the indicated response code and subcode.
	Note: ACBRSP=148 most likely means the database was not active.
	Either a database ID (<i>dbid</i>) or nucleus ID (<i>nucid</i>) is given in the message. In cluster environments, a nucleus ID is listed; in all other environments, a database ID is listed.
Action	No action is required for this informational message.

REVH29	{hubid} NO UB AVAILABLE FOR COMMAND TO CLIENT {dbid}
Explanation	There are not sufficient user blocks to add or communicate with a new client. The Adabas Review hub abends.
Action	This may be a transient condition if the hub is servicing many clients in a very busy system. Issue the STARTCLIENT operator command to reinitiate handshaking. If this does not resolve the error, try decreasing the number of clients or increasing the number of user blocks. The number of user blocks can be increased by an optional zap which increases the value HUBMXCL is increased. For more information, or if this does not resolved the error, contact your Software AG technical support representative.
REVH30	{hubid} LOGIC ERROR COMPLETING COMMAND TO CLIENT {dbid}
Explanation	A command sent from the hub to a client was thought to be complete, but the 16-call did not mark it as complete. This is normally a logic error, but it might also occur during hub termination if the client was unresponsive..
Action	Contact your Software AG technical support representative if this does not relate to an unresponsive client during hub termination.
REVH31	{hubid} INVALID STORAGE KEY {x}
Explanation	The Adabas Review hub can only run in storage key 0 or 8.
Action	Start the Adabas Review hub again under storage key 0 or storage key 8.

13

RTP* - Adabas Review Trans-port Messages

RTP001	Review Abend in RTPSSPC Abend S{syscode} U{usrcode} Reason {rsncode} Hub ID {hubid} PASN {pasn} SASN {sasn} PSW {psw} {extended-information} {general-registers} {access-registers}
Explanation	<p>A program check or system abend was intercepted by the Adabas Review Trans-port ARR routine. This message appears in the Trans-port caller's listings and the system console.</p> <p>The caller does not abend, but the data being sent to the Adabas Review hub may be discarded. A system dump is attempted.</p>
Action	Contact your Software AG technical support representative for assistance.
RTP002	Review Abend in RTPSSPC Abend S{syscode} U{usrcode} SDWA Not Available
Explanation	<p>A program check or system abend was intercepted by the Adabas Review Trans-port ARR routine. This message appears in the Trans-port caller's listings and the system console.</p> <p>z/OS did not provide a System Diagnostic Work Area (SDWA), which reduces the amount of information available.</p> <p>The caller does not abend, but the data being sent to the Adabas Review hub may be discarded. A system dump is attempted.</p>
Action	Contact your Software AG technical support representative for assistance.

RTP003 System Dump Accepted

Explanation The error described in preceding messages RTP001 or RTP002 is recorded in a system dump. Additional dump details are in the system log and the hub's listing.

Action Contact your Software AG technical support representative for assistance.

RTP004 SDUMPX failed Reason {rsncode}

Explanation A system dump was attempted after the error described in the preceding messages RTP001 or RTP002. z/OS was unable to schedule the dump.

Action Check the IBM documentation for the SDUMPX service to determine the meaning of the reason code given in the message. Contact your Software AG technical support representative for assistance.

14

RVCALL* - Adabas Review RVCALL API Messages

RVCALL00 **Function completed successfully**
Explanation The RVCALL function completed successfully.
Action No action is required for this informational message.

RVCALL04 **Invalid RVC-FUNCTION specified**
Explanation An invalid value was specified for the RVCALL parameter RVC-FUNCTION. Valid values are START, DELETE, CLOSE, SUSPEND, REACT, LIST, GETHUBID, GETDBID, EZSTART, VIEWON, or VIEWOFF.
Action Specify a valid value and try again.

RVCALL05 {<msg-text>}
Explanation The message text for this message varies. The following message texts may appear:

Message Text	Explanation
RVC-DBID must be specified	A value for the RVC-DBID parameter is required, but no value was specified.
RVC-DBID must not be greater than 65535	An invalid value was specified for RVC-DBID.
RVC-REVIEW-TARGET must be specified	A value for RVC-REVIEW-TARGET is required, but no value was specified.
RVC-REVIEW-TARGET must not be greater than 65535	An invalid value was specified for RVC-REVIEW-TARGET.

Action Correct the value of the RVC-DBID or RVC-REVIEW-TARGET parameter and try again.

RVCALL06	RVC-REPORT-NAME must be specified
Explanation	A value for the RVC-REPORT-NAME parameter is required, but no value was specified.
Action	Specify an valid value for RVC-REPORT-NAME and try again.
RVCALL07	RVC-ACCOUNT-FIELDS required for summary reports
Explanation	A value for the RVC-ACCOUNT-FIELDS parameter is required, but no value was specified.
Action	Specify the order in which fields should appear for summary reports in the RVC-ACCOUNT-FIELDS parameter. Then try again.
RVCALL08	RVC-WRAP = "Y" valid for sequence reports only
Explanation	RVC-WRAP is specified, but the SEQUENCE field is not specified in the RVC-ACCOUNT-FIELDS parameter.
Action	Examine the problem. Correct either the RVC-WRAP parameter setting or add SEQUENCE to the RVC-ACCOUNT-FIELDS parameter setting. Then try again.
RVCALL09	RVC-HISTORY-DBID must be specified for history reports
Explanation	History data was requested, but no value was specified for the RVC-HISTORY-DBID parameter.
Action	In the RVC-HISTORY-DBID parameter, specify the valid database ID (DBID) of the Adabas Review repository used to store history data. Then try again.
RVCALL10	RVC-HISTORY-FNR must be specified for history reports
Explanation	History data was requested, but no value was specified for the RVC-HISTORY-FNR parameter.
Action	In the RVC-HISTORY-FNR parameter, specify the valid file number of the Adabas Review repository used to store history data. Then try again.
RVCALL11	RVC-HISTORY-SVC must be specified for history reports
Explanation	History data was requested, but no value was specified for the RVC-HISTORY-SVC parameter.
Action	In the RVC-HISTORY-SVC parameter, specify the valid Adabas SVC number used to communicate with the Adabas Review repository to which history data should be written. Then try again.

RVCALL12	RVC-REPORT-NAME already active
Explanation	The report specified in the RVC-REPORT-NAME parameter using the EZSTART function is already active.
Action	Specify a different report in the RVC-REPORT-NAME parameter and try again. Alternatively, you could stop the running report and start it again using RVCALL, but if the report was started online using SYSREVDDB, it will need to be stopped online (not using RVCALL).
RVCALL13	UCMD area storage allocation failed
Explanation	The storage available for Adabas Review reports is inadequate. This was determined during an attempt to run the EZSTART function.
Action	Increase the storage available for Adabas Review reports and try again. If the problem persists, contact your Software AG technical support representative.
RVCALL14	Not enough storage to start report
Explanation	There is not enough storage to start a report using the EZSTART function.
Action	Increase the storage available for Adabas Review reports and try again. If the problem persists, contact your Software AG technical support representative.
RVCALL15	Invalid field definition in report
Explanation	An invalid field definition was found in an Adabas Review report while running the RVCALL EZSTART function.
Action	Using SYSREVDDB, correct the field definition online. Then try the RVCALL EZSTART function again.
RVCALL16	Invalid summary field specified in report
Explanation	An invalid summary field was specified for an Adabas Review report while running the RVCALL EZSTART function.
Action	Using SYSREVDDB, correct the summary field value online. Then try the RVCALL EZSTART function again.
RVCALL17	Field length error in report
Explanation	An invalid field length was specified for an Adabas Review report while running the RVCALL EZSTART function.
Action	Using SYSREVDDB, correct the field length value online. Then try the RVCALL EZSTART function again.

RVCALL18	Field format error in report
Explanation	An invalid field format was specified for an Adabas Review report while running the RVCALL EZSTART function.
Action	Using SYSREVDDB, correct the field format value online. Then try the RVCALL EZSTART function again.
RVCALL19	Error in report processing, resp = {rsp}
Explanation	An unknown error occurred in the RVCALL EZSTART processing of an online report. The response code is given in the message (<i>rsp</i>).
Action	Review the response code and use SYSREVDDB to examine the report definition online. Make appropriate corrections and retry. If the problem persists, contact your Software AG technical support representative.
RVCALL20	RVC-REPORT-NAME is not active
Explanation	The report name specified in the RVC-REPORT-NAME parameter is not active, but must be active for the RVCALL function identified in the RVC-FUNCTION parameter.
Action	Either specify an active report name in the RVC-REPORT-NAME parameter or change the RVCALL function specified in the RVC-FUNCTION parameter.
RVCALL22	No active reports to be listed
Explanation	During RVCALL LIST function processing (RVC-FUNCTION='LIST'), RVCALL found no active reports to list.
Action	Determine whether this is really a problem. No action is required if there are no active reports. However, if there are active reports, verify that the other LIST function input parameters are specified correctly. Then try again.
RVCALL23	Error accessing DBID for L-FILE
Explanation	An error occurred while processing an RVCALL GETDBID function.
Action	Contact your Software AG technical support representative for assistance.
RVCALL24	Found zero HUBIDs on selected SVC
Explanation	No hub IDs were found during RVCALL GETHUBID function processing for the SVC specified in the RVC-SVC parameter.
Action	Verify that the SVC specified in the RVC-SVC parameter is valid and try again. If the problem persists, contact your Software AG technical support representative.

RVCALL25 RVC-SVC is invalid

Explanation The SVC specified in the RVC-SVC parameter for RVCALL GETHUBID function processing was invalid.

Action Specify a valid SVC in the RVC-SVC parameter for the run and try again.

RVCALL27 {<msg-text>}

Explanation One of the following errors occurred using ADATMZ during RVCALL processing.

Message Text	Explanation
ADATMZ: No Adabas SVCs found	No Adabas SVCs were found by ADATMZ.
ADATMZ: No Active targets for an SVC	No active targets were found for the SVC by ADATMZ.

Action Examine the message and take appropriate action. If the problem persists, contact your Software AG technical support representative for assistance.

RVCALL35 BUFFER POOL reports cannot have DBID=ALL

Explanation During RVCALL EZSTART processing, you specified "BUFFER POOL DISPLAY" for the report name and set the RVC-ALL parameter to "ALL". This is not allowed. You cannot produce the buffer pool display for all DBIDs.

Action Specify a single database ID in the RVC-DBID parameter for the RVCALL EZSTART run and remove the RVC-ALL='ALL' specification. Then try again.

RVCALL98 Adabas error, resp = {rsp}

Explanation An error occurred while the RVCALL API was calling Adabas. The response code from the call is given in the message (*rsp*).

Action Review the response code explanation in the Adabas Response Code documentation and try to resolve the problem. If the problem persists, contact your Software AG technical support representative.

RVCALL99 Adabas error, resp = {rsp}

Explanation An error occurred while the RVCALL API was calling Adabas. The response code from the call is given in the message (*rsp*).

Action Review the response code explanation in the Adabas Response Code documentation and try to resolve the problem. If the problem persists, contact your Software AG technical support representative.

RVCALL420	Unable to open command log file for output
Explanation	The report requested during an RVCALL EZSTART run required a command log file that was not available.
Action	Make the command log file available and try again.
RVCALL421	Command log dataset already in use
Explanation	The report requested during an RVCALL EZSTART run required a command log data set that was not available.
Action	Make the command log data set available and try again.
RVCALL499	Detail printer not available
Explanation	The report requested during an RVCALL EZSTART run required a printer, but no printer was available.
Action	Make the printer available and try again.

15 RVCL* - Adabas Review Batch Client Reporting (REVCLRP)

Messages

RVCL001	Review Client Reporting has been {started stopped}
Explanation	Adabas Review client reporting has been started or stopped. (REVEXIT2 has successfully been changed to the requested state: ON or OFF.)
Action	No action is required for this informational message.
RVCL002	Review Client Reporting is currently {on off unavailable}
Explanation	The current status of Adabas Review client reporting is listed in the message.
Action	No action is required for this informational message.
RVCL003	Unexpected error while resetting state
Explanation	While performing the STATUS function, an error occurred resetting the original state after processing. This is due to a very small window of opportunity where an externally controlled process was altered. An example would be if the Adabas Review hub was terminated during the time when the STATUS call has started but not completed.
Action	Retry the operation.
RVCL004	Invalid function code
Explanation	An invalid function code was specified in RVCLFUNC. Valid function codes are "ON", "OFF" or "STATUS".
Action	Specify a valid function code in RVCLFUNC and try again.

RVCL005	Non-zero response from link routine
Explanation	An error condition exists. Output fields RVCLRSP and RVCLRESN will contain the response and reason codes returned by the Adabas link routine, ADALNK. Note: These fields were set by ADALNK, not REVCLRP.
Action	Examine the response code and reason codes to understand the problem and fix it. If you need assistance, contact your Software AG technical support representative.
RVCL006	Review Client Reporting was already {on off}
Explanation	A request was made to change the state of client reporting, but client reporting was already in that state.
Action	Determine whether the request to change the state was requested correctly. If not, correct the request and try again.
RVCL007	REVEXIT2 is not installed
Explanation	An attempt to call REVCLRP was made from an application, but the REVEXIT2 link routine is not currently installed. REVEXIT2 is required for client reporting.
Action	Contact your Software AG technical support representative for assistance.
RVCL008	Insufficient storage for REVEXIT2
Explanation	There is not enough memory available for REVEXIT2 to operate.
Action	Provide more storage and try to run the job that calls REVCLRP again.
RVCL009	The hand shake with the Review hub failed
Explanation	The Trans-Port service was not able to communicate properly with the Adabas Review hub because the PC number was zero.
Action	Contact your Software AG technical support representative; be prepared to provide a dump and protocol information.
RVCL010	The internal Trans-Port mechanism failed
Explanation	Attempts to communicate with the Adabas Review hub failed. Output fields REVCLRSP and RVCLRESN will be set with the response and reason codes from REVCLRP. If the response and reason codes are 148/50, then the hub was terminated after client reporting (REVEXIT2) was activated.
Action	If the response and reason codes are 148 and 50 (respectively), restart the hub and try again. If the response and reason codes are not 148 and 50, contact your Software AG technical support representative for assistance.

RVCL011	Adabas response 148 was received contacting the hub
Explanation	The Adabas Review hub is not available.
Action	Start the Adabas Review hub and try again.

16 Adabas Response Codes

After each Adabas command is processed, a response code is returned in bytes 11 and 12 of the ACB or in the ACBX. Some response codes also return a subcode in the rightmost two bytes of the ACB's Additions 2 field (offset 45-48) or in the ACBX's Error Subcode (ACBXERRC) field (offset 115-116). This section describes those response codes and subcodes.



Note: Proprietary functions of Adabas may also return response codes and subcodes, some of which are not described here. Refer to the documentation for those functions for more information.

Response code 0 indicates that the Adabas command was processed successfully; any other response code is returned as a result of an error during command processing.

All Adabas commands resulting in a response code other than 0 (ADARSP000), 1 (ADARSP001), and 145 (ADARSP145) restore all Adabas control block fields except the response code field (see the Adabas Command Reference documentation) to the contents the fields held at the beginning of command execution.

For internal errors, contact your Adabas technical support representative.

Response 0

Origin	Mainframe and open systems
Explanation	The command was executed successfully.

Response 1

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
1	An online SAVE operation cannot be executed without the nucleus' PLOG.
2	The selected record is not allowed.
3	S2 command did not have enough space.
4	S2/S9 internal program error.
5	System was not in save status at the end of an online ADASAV.

Note: When one of the subcodes 2-4 is present, the cause could be an Sx command using security-by-value that found at least one ISN.

Open Systems

An ISN list could not be sorted as a result of an excessive number of resulting ISNs, or because during a non-descriptor search a value larger than the corresponding field length in the FDT was found, or because the ISN quantity returned does not correspond with the actual number of records found.

For an S9 command, this response indicates that there is no space available for additional temporary working space. For an S2 command, this response is only a warning and the S2 becomes an S1.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Increase the ADARUN LS parameter value.

Open Systems

Provide sufficient disk space for temporary working space or adapt the FDT to the real field length.

Response 2**Origin**

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

This response code can only occur with a BT, ET or RI command. The BT, ET or RI command executes successfully. One of the following has occurred, depending on the subcode:

Subcode	Meaning
1	Adabas attempted to hold an ISN already being held by another user.
2	The number of ISNs as specified in the ISN buffer was too large compared to the ISN buffer length (ET or BT command with the M option).
4	ISN is not on hold during multifetch ET/BT. ET/BT has successfully executed the ISNs so far released. The remaining ISNs are still on hold.
5	An RI command with ISN=0 could not release from hold status all records held by the user, as requested, because one or more records had been updated earlier in the same transaction. Updated records cannot be released from hold status prior to transaction end. All records that had not been updated have been released from hold status.

Open Systems

The required function has not been executed completely. For an OP command with command option 2 = E or for an RE command, the specified record buffer length was shorter than the length of the ET data read. The record buffer has been truncated.

For an A1//N1/N2 command, a descriptor value with the TR option is larger than 1144 bytes. In this case, only the first 1144 bytes are stored in the index. Search operations for truncated values may be inexact since only the first 1144 bytes are evaluated. The first 2 bytes of the Additions 2 field contain the number of descriptor values truncated, the third and fourth bytes contain the field name of the descriptor value that is truncated.

For an S1/S2/S4/S9 command, the resulting ISN list may not represent the exact result: this is because the search values and the values in the database were truncated after 1144 bytes during the search operation of an S1/S2/S4 command and during the sort operation of an S2/S9 command.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Open Systems

For an OP or RE command, increase the record buffer length or ignore the warning.

For an S1/S2/S4/S9 command, either perform a post-selection using the complete field values, perform your own sort operation using the complete field values, or ignore the warning.

Response 3

Origin

Mainframe and open systems

Explanation

One of the following has occurred:

- An end-of-file or end-of-list condition was detected.
- A program tried to read or change a multicient file's record using either a blank or incorrect-length owner ID, or an owner ID that is not allowed for the record.

The following are some possible subcodes:

Subcode	Meaning
1	An end-of-file or end-of-list condition was detected (L3/L6 on a non-expanded file).
4	End of LOB value reached. An attempt was made to read a LOB value segment that begins after the end of the value. This response code/subcode is given to an L1/L4 command with Command Option 2 set to L if the ISN Lower Limit value is greater than or equal to the length of the LOB value being read.
66	A program tried to read or change a multicient file's record using either a blank or incorrect-length owner ID, or an owner ID that is not allowed for the record.
249	Adabas Vista has determined that no data is available to satisfy this command due to one of the following reasons: <ul style="list-style-type: none"> ■ A partitioned file end-of-file or end-of-list condition was detected. ■ None of the partitions were available/online and all of them have the file parameter <code>Critical</code> set to NO. <p><i>Action:</i> No action is required.</p>

Response 4

Origin

Mainframe systems

Explanation

The internal Adabas TRS storage directory is full.

Action

Free some of the active queries.

Response 7

Origin Mainframe systems only
Explanation A complex search command was rejected because it was estimated that it would exceed the maximum search time TLSCMD.

Response 8

Origin Mainframe systems only
Explanation The current user's command was interrupted to prevent a Work overflow because of a pending backout operation.
Action The value specified for the LP parameter might have to be increased.

Response 9

Origin Mainframe and open systems
Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

A subcode indicating the specific cause and action for this response code appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field. The following are the subcodes and their meanings:

Subcode	Meaning
1	The user was backed out because the hold queue was full <i>Action:</i> Set the number of hold queue elements (ADARUN NH parameter) higher, or tune the application to issue more frequent ET commands.
2	The transaction time limit (TT) has been exceeded, and the transaction was backed out. <i>Action:</i> Correct the cause of the timeout, then restart the transaction.
3	One of the following is the case: <ul style="list-style-type: none"> ■ The transaction non-activity time limit (TNAE, TNAX, or TNAA) has been exceeded. ■ The user was stopped by the STOPF or STOPI operator, or an Adabas Online System command. ■ A security violation response code has been returned for an ET-logic user. Information about response codes for security violations is provided in the Adabas Security documentation. ■ When a new user issues an OP cmd with the same user ID (in ADD1) as an earlier user did and the earlier user was inactive for more than 60 seconds, the new user can, by issuing a second OP cmd again (the first

Subcode	Meaning
	<p>OP cmd will get response code 9, subcode 64), take over the user ID of the earlier user. When the earlier user becomes active again, this subcode can be received.</p> <p><i>Action:</i> Correct the cause of the timeout, then restart the transaction.</p>
15	<p>The user was backed out because a pending Work area overflow occurred during this operation.</p> <p><i>Action:</i> Either reduce the transaction length to lessen the data protection area requirement, or increase the protection area on Work.</p>
17	<p>At the end of an online recovery process that was initiated after the failure of a peer nucleus in an Adabas cluster, the nucleus was unable to reacquire the ETID specified by the user in the Additions 1 field of the OP command.</p> <p><i>Action:</i> (In the application program:) Redo the OP command with the ETID specified in the Additions 1 field to reacquire the user ID. Contact your Software AG technical support representative.</p>
18	<p>The user's active transaction was interrupted and backed out because a peer nucleus in an Adabas cluster terminated abnormally.</p> <p><i>Action:</i> (In the application program:) Rerun the transaction.</p>
19	<p>The user's active command was interrupted and stopped because a peer nucleus in an Adabas cluster terminated abnormally. If the interrupted command was using a command ID (CID), the command ID is deleted.</p> <p><i>Action:</i> (In the application program:) Clean up and reacquire the current context pertaining to Adabas command IDs; rerun the transaction.</p>
20	<p>The Adabas cluster nucleus assigned to the user terminated while the user had an open transaction. The transaction has been or will be backed out.</p> <p><i>Action:</i> (In the application program:) If the user was defined with a user ID (ETID) in the Additions 1 field of the OP command, redo the OP command to reacquire the ETID; clean up and reacquire the current context pertaining to Adabas command IDs; rerun the transaction.</p>
21	<p>The user's active command was waiting for an ISN in hold status when the user was backed out and closed due to a timeout or a STOP command.</p>
22	<p>The user's active command was waiting for free space in the work pool when the user was backed out and closed due to a timeout or a STOP command.</p>
23	<p>The user's command was routed to a different cluster nucleus than the one used by previous commands. The user's open transaction has been backed out. It is also possible that the user had already been timed out earlier.</p> <p><i>Action:</i> Restart the transaction and any open read sequences.</p>
24	<p>The user's command was routed to a different cluster nucleus than the one used by previous commands. The user had owned EXU or EXF control over</p>

Subcode	Meaning
	<p>one or more files or had started the Adabas session with an OP command with R-option. As a consequence of creating a new session for the user with the new nucleus, the EXU/EXF control or file list specified in the OP command are no longer in effect.</p> <p><i>Action:</i> Restart the Adabas session with a new OP command.</p>
25	<p>The user's command was routed to a different cluster nucleus than the one used by previous commands. The user had started the Adabas session with an OP command with ETID. As a consequence of creating a new session for the user with the new nucleus, the user is no longer associated with that ETID.</p> <p><i>Action:</i> Restart the Adabas session with a new OP command.</p>
26	<p>The user's command was routed to a different cluster nucleus than the one used by previous commands. Some cluster nucleus terminated abnormally while the new nucleus was creating a new session for the user.</p> <p><i>Action:</i> Restart the Adabas session with a new OP command.</p>
62	<p>An OP (open) command was issued without a user/ET ID, which is required for this type of application or environment.</p> <p><i>Action:</i> Correct the program to specify a user/ET ID, and rerun the program.</p>
63	<p>An OP command was given for an ET user not in ET status. The user is backed out with an Adabas-generated BT command, and the operation is closed.</p> <p><i>Action:</i> Repeat the OP call.</p>
64	<p>An OP command was issued with an 8-byte ET ID that already exists.</p>
66	<p>An Adabas session with OPENRQ=YES was active and the user issued an Adabas command without having issued an OP command.</p> <p><i>Action:</i> Ensure that all users issue an OP command as the first Adabas command.</p>
67	<p>Insufficient Work part 1 space for open command with ETID definition when trying to read the user profile.</p>
68	<p>The user queue element has been deleted. Most likely the command was thrown back due to ISN contention or space shortage. The space shortage is normally workpool space; if this is the case, the LWP parameter setting should be increased.</p>
73	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session had an externally-controlled transaction, the outcome of which was "in doubt". ATM forcibly resolved the "in doubt" transaction. There is a possibility that ATM's resolution of the transaction might be inconsistent with the intended outcome.</p>

Subcode	Meaning
	<p>Check that the outcome of the session's Adabas changes, in its previous transaction, was consistent with its changes to non-Adabas resources.</p> <p>Check the external transaction coordinator for reasons why the original transaction might have been left in the "in doubt" state. If the external coordinator indicates that the transaction was completed, and if the relevant system logs give no indication of the cause of the problem, contact your Software AG support representative.</p>
74	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client's database session has lost its ETID. If a transaction was in progress, ATM attempted to back it out from all affected databases and release all held records.</p> <p>Issue a new OP command to the database.</p>
75	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>Either a commit operation involving an external transaction coordinator failed, or resynchronization with an external transaction coordinator caused the transaction to be backed out. In the first case, ATM attempted to back out the transaction.</p> <p>For the first case, check the external transaction coordinator for the reason. Check for error messages from ATM transaction managers or the ATM client proxy of the failing job.</p>
76	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred while an ATM transaction manager was attempting to rebuild the transaction hierarchy of a client session that has migrated from another ATM transaction manager's domain as a result of dynamic transaction routing. ATM attempted to back out the transaction.</p> <p>Check the status of the transaction using Online Services. Check for error messages from ATM transaction manager or the ATM client proxy of the failing user.</p>
77	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>This message indicates that the client session had an open transaction and has been migrated from one node to another within a cluster (Sysplex), but ATM could not handle the transaction safely because no Migrated Transaction Record (MTR) file had been defined. The transaction was therefore backed out.</p> <p>Define and create an MTR file, and restart the ATM transaction managers and clustered application environments in the COR group.</p>

Subcode	Meaning
78	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>It was not possible to commit the client session's transaction because of a pending ET syncpoint on a target database. This could be because of a concurrent online save operation, database termination, or a SYNCC operator command. Backout of the incomplete transaction was attempted.</p> <p>Restart the transaction when the pending ET syncpoint has been completed.</p>
79	<p>Used by Adabas System Coordinator to signal the (optional) terminal timeout. Refer to the description of Generate RSP009/79 in the Adabas System Coordinator Parameters documentation for more information.</p>
80	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session was not at ET status in the target database. Backout of the incomplete transaction was attempted.</p> <p>Restart the transaction.</p>
81	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>A memory shortage in the ATM transaction manager's address space caused the current global transaction to be backed out.</p> <p>Increase the amount of memory available to the ATM transaction manager, restart it, then restart the transaction.</p>
82	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>A memory shortage occurred in the ATM transaction manager's address space, and ATM attempted to back out the current global transaction.</p> <p>Increase the amount of memory available to the ATM transaction manager, restart it, then restart the transaction.</p>
83	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred during a commit or backout operation for a global transaction. ATM attempted to back the transaction out.</p> <p>If the cause of the error is not apparent from console messages, contact your Software AG technical support representative.</p>
84	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>ATM reported conflicting use of an ETID. For an RE command, this subcode can be returned if the client is known to ATM but has no ETID.</p> <p>The client should issue a CL command to each open database; then re-open.</p>
85	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The global transaction time limit (TMGTT) has been exceeded, and an attempt has been made to back out the global transaction.</p>

Subcode	Meaning
	Correct the cause of the timeout, then restart the transaction.
86	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The global transaction time limit (TMGTT) has been exceeded, and the global transaction has been backed out.</p> <p>Correct the cause of the timeout, then restart the transaction.</p>
90	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The ATM client proxy detected either an inconsistency between its view of the client session's status and the ATM transaction manager's view, or that the transaction manager had restarted. It attempted to back out on all target databases.</p> <p>Close the client's sessions and start them again.</p>
91	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>Transactions on a target database were being quiesced, or an administrator issued a "stop" request for the session's transaction via ATM Online Services or operator command, or there was a pending ET syncpoint on the database. Backout of the incomplete transaction was attempted.</p> <p>Restart the transaction when all required target databases are available.</p>
92	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>Transactions on a target database were being quiesced, or an administrator issued a stop request for the user via ATM Online Services or operator command, or there was a pending ET syncpoint on the database. The incomplete transaction was backed out.</p> <p>Restart the transaction when all required target databases are available.</p>
93	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred while ATM was attempting either to start a new global transaction or to bring a new database into a transaction. The client proxy backed out changes from all databases.</p> <p>The next command issued returns details of the error that caused the backout. Check the meaning of the response code and act accordingly.</p>
94	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred while ATM was attempting either to start a new global transaction or to bring a new database into a transaction. The client proxy attempted to back out changes from all databases.</p> <p>The next command issued returns details of the error that caused the backout. Check the meaning of the response code and act accordingly.</p>

Subcode	Meaning
95	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session's transaction was controlled by an external transaction coordinator, which reported that the transaction has been backed out.</p> <p>Restart the transaction.</p>
96	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session's transaction was controlled by an external transaction coordinator, which reported "backed out, outcome pending" for the transaction. This means that backout has begun for the transaction, and will be completed when all the resource managers involved in it are able to comply with the backout request.</p> <p>Restart the transaction.</p>
97	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The CICS Resource Manager Interface is in use, and the ATM client proxy detected that the client session's Task Interface Element (TIE) was being used by another session.</p> <p>This can occur if all of the following are true:</p> <ul style="list-style-type: none"> ■ Natural is being used, in such a way that two Adabas sessions are maintained for each client; ■ The client control <code>Transaction Model</code> is set to <code>MESSAGE</code>; ■ Natural parameters are set such that Natural might not generate <code>OP</code> commands for all database sessions. <p>You can make sure that Natural generates <code>OP</code> commands by using a non-blank <code>ETID</code>, or by means of Natural's <code>DBOPEN</code> parameter.</p> <p>The condition can also occur if all of the following are true:</p> <ul style="list-style-type: none"> ■ Natural is being used, in such a way that two Adabas sessions are maintained for each client; ■ The Adabas System Coordinator has timed out Natural's "system" session. <p>In this case, a new Natural <code>LOGON</code> might clear the condition. Otherwise terminate the session and start a new session.</p> <p>If the error persists, contact your Software AG support representative.</p>
98	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session was executing in serial mode, and requested that changes be committed. Some of the changes were committed, and some were backed out.</p>

Subcode	Meaning
	Examine the results of the transaction. If necessary, correct the result by manual intervention.
99	This subcode is issued by Adabas Transaction Manager. The client session incurred a security response code; ATM backed out the user's changes. If security permissions are not adequate, correct them and rerun the transaction.
249	In Adabas Vista, all transaction activity by the client has been backed out for one of the following reasons: <ul style="list-style-type: none"> ■ The client is using multiple (different) ETIDs which have collided against a particular database. <p><i>Action:</i> Review the client's use of ETIDs with respect to the current translation rules and/or partitioned files.</p>

Open Systems

This response is caused by one of the following:

- The last user transaction has been backed out by Adabas (ET logic users only) or an exclusive control user (non-ET user) or an access-only user exceeded the Non-Activity Time Limit;
- The user session was abnormally terminated by the operator and the user issued a command;
- The protection log area (= WORK container) was too small and an internal BT was executed.

The ADDITIONS 2 field in the control block contains additional information:

First two bytes	Third and fourth bytes	Explanation
0	TT	Transaction timeout
1	TN	Non-activity timeout
2	ST	STOP user
3	LP	WORK overflow
5	SE	Security
6	DL	Deadlock
8	OP	Open transaction
9	OR	Open required
10	RR	Replication recording failed

First two bytes	Third and fourth bytes	Explanation
		One of the internal Adabas commands issued for replication recording got an unexpected response code, for example 77. This response code is included in the control block in the field ACBXSUBR (only if you use the ACBX interface) and displayed in an RPLIRSP message in the nucleus log.

	First two bytes	Third+ fourth bytes
	-----	-----
Transaction timeout :	0	TT
Non-activity timeout:	1	TN
STOP user :	2	ST
WORK overflow :	3	LP
Security :	5	SE
Deadlock :	6	DL
Open transaction :	8	OP
Open required :	9	OR

The information in the first two bytes is represented as an integer, and the third and fourth bytes are alphanumeric.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

User actions are described in the subcode list in the explanation.

Open Systems

Check the appropriate reason. If the Adabas nucleus was started without the option OPEN_REQUIRED, and the reason for response 9 was a non-activity timeout or a STOP user, users who started their sessions with an OP command must re-issue their OP command under the following circumstances:

- if they set a User ID
- if they specified restricted file lists
- if they had user-specific timeout values
- if they were not ET users.

If too many transactions are backed out because of a Work overflow, the size of the Work container should be increased.

Response 10

Origin Mainframe systems only
Explanation Too many occurrences for a periodic group.

Response 16

Origin Open systems only
Explanation An error occurred in an MC call during subcommand processing. The error code and additional information can be found in the control block of the subcommand. The first 2 bytes of the Additions 2 field contain the number of the subcommand in binary format. The third and fourth bytes of the Additions 2 field contain the offset of the subcommand's control block in the MC call's record buffer in binary format. All subcommands before the one that failed were executed.
Action Correct the failed subcommand if necessary and re-issue the subcommands beginning with the one that had failed.

Response 17

Origin Mainframe and open systems
Explanation A subcode indicating the specific cause and action for this response code appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACB's Error Subcode (ACBXERRC) field. The following are the subcodes and their meanings:

Subcode	Meaning
1	The program tried to access system file 1 or 2, and no OP command was issued. <i>Action:</i> Restructure the program to begin with an OP command.
2	The program tried to access system file 1 or 2, and the user is not authorized. <i>Action:</i> Change the program to avoid the access.
4	One of the following occurred: <ul style="list-style-type: none"> ■ The specified file number is invalid. The file number might be equal to "0" or greater than the maximum allowed. ■ When running with ADARUN DTP=RM or DTP=TM, an attempt was made by a non-Adabas Transaction Manager user to access/update an Adabas Transaction Manager system file.
5	The file is either not loaded, or has been locked by another user for privileged use. On mainframe systems, for ADAORD and ADAINV utility operations, the write phase has started and use of the file is now blocked for the type of operation you requested.

Subcode	Meaning
6	<p>On mainframe systems, an E1 (delete record) command was given without specifying a valid file number.</p> <p>On open systems, the file to be created already exists.</p>
7	The program tried to perform an LF command on system file 1 or 2.
8	<p>On mainframe systems, the program tried to access a file that was not listed in the file list of an open (OP) executed with the R option.</p> <p>On open systems, an ET user with a restricted file list and ACC = file number attempted to issue a UPD command, or a user with a restricted file list attempted to touch a file that is not in the file list</p>
9	<p>The file that the program attempted to access is completely locked. This is usually because the maximum number of logical file extents that can fit into the FCB have been used.</p> <p><i>Action:</i> Reorder, then unlock the file. Continue operation.</p>
10	The program attempted to access a file which is locked with exclusive EXU status.
11	An LF command (read FDT) was run on a file that is not loaded; neither the FCB nor the FDT exists.
12	File has been locked with LOCKF.
13	A file is password-protected and the password was specified, but the corresponding security file is missing (not loaded).
14	A command was issued against a LOB file. Commands involving LB fields should be directed against the associated base file, not the LOB file.
15	A file is being loaded so its information is temporarily unavailable.
16	<p>On mainframe systems, an attempt was made to perform an update (e.g. A1, E1, N1/2) against a file loaded with the attribute RPLUPDATEONLY=YES or READONLY=YES.</p> <p>On open systems, the file was locked by ADAOPR.</p>
17	An attempt was made to perform an update (e.g. A1, E1, N1/2) against a file loaded with the attribute READONLY=YES.
18	File has been locked with ALOCKF.
21	<p>On mainframe systems, there was not enough space for encoding elements (ECSE).</p> <p>On open systems, a two-byte file number was used against a lower version database that does not support large file numbers.</p>
22	<p>On mainframe systems, the required ECS objects needed for conversion between user and system data representation could not be loaded.</p> <p>On open systems, the file control block (FCB) is invalid (corrupted).</p>

Subcode	Meaning
23	<p>ECS object could not be located. The following objects must be available in the encoding objects library: File Alpha, File Wide EDD, User Alpha, User Wide EDD, and the PTOs for the combinations between file/user alpha/wide encodings.</p> <p><i>Action:</i> Check that the required EDD and PTO objects are available.</p>
24	<p>ECS function <code>get_attribute()</code> failed.</p> <p><i>Action:</i> The function's return code is logged with the nucleus message ADAN7A.</p>
25	<p>One of the following occurred: - A required encoding attribute was missing in an ECS object (encoding type, class, and flags) - The default space character length was > 4 - Default space table allocation failed - If DBCS-only plane exists, wide space character was undefined, or the length > 4, or wide space table allocation failed</p>
29	<p>An Adabas Review communication error has occurred. Contact your Software AG support representative.</p>
52	<p>A non-Adabas target was called.</p>
99	<p>The file's FTD is corrupted.</p> <p><i>Action:</i> To resolve the problem, repair the file by running a restore/regenerate from a consistent state.</p>
249 (0x00F9)	<p>While attempting to satisfy a partitioned file command, Adabas Vista detected the unavailability of an FDT – this is invalid for one of the following reasons:</p> <ul style="list-style-type: none"> ■ None of the partitions were available/online and at least one of them has the file parameter <code>Critical</code> set to YES. ■ None of the partitions were available/online and all of them have the file parameter <code>Critical</code> set to NO and the command can not be satisfied with a “no data” response such as RSP003. <p>An error occurred when Adabas Vista (open systems) tried to access a file that was not listed in the file list of an <code>OP</code> command executed with the <code>R</code> option.</p> <p><i>Action:</i> Ensure at least one of the file partitions is available/online or review the program logic.</p>

Response 18

Origin Mainframe and open systems.
Explanation Invalid file number usage. The file number was modified between successive L2/L5 calls or between successive Lx and Sx calls.
Action Correct the file number.

Response 19

Origin Mainframe and open systems.
Explanation An attempt was made to update a file which is either already open for read access or can only be opened for read access. The leftmost two bytes of ACB's Additions 2 field or the ACBX's File Number (ACBXFNR) field may contain the file number.
Action Do not attempt to update a file with read-only access.

Response 20

Origin Mainframe and open systems.
Explanation One of the following invalid values was used for a command ID value:

- Binary zeros
- Blanks
- The high-order byte contains the hexadecimal value "FF", but there is no automatic command ID generation
- The three high-order bytes contain the ASCII string "SYN".

Action Correct the command ID and avoid using any of these invalid command ID values.

Response 21

Origin Mainframe and open systems
Explanation An invalid command ID value was detected. One of the following explanations or subcodes is provided:

Subcode	Meaning
1	The command ID value was not found in the sequential command table. This is not an initial call and there was no previous initial call, or the command ID was deleted or lost in a timeout or recovery action.
3	The command ID value specified for the L3/L6 command was assigned to another Lx command.
5	The command ID value specified for the L9 command was assigned to another Lx command.
6	Unexpected last file in chain.
7	The command ID value specified was assigned to a different file.

Subcode	Meaning
8	The command ID value specified for the Sx command is for a sorted ISN list; the ISN list was not in ISN sequence.
9	An application running with PREFETCH=YES or PREFETCH=OLD attempted to dynamically reverse the read direction of an L3/L6/L9 command. This is not allowed.
10	The master file number is not the same as it was in the initial call for this command ID.
12	ACB(X)Add1 altered after initial call.
13	S9 ISN list already sorted
14	Not a chained file as expected.
15	Not an L2 sequence as expected.
16	Chained file transformed ISNs not permitted.
17	CID does not exist for chained file.
18	File was not master file as expected.
19	Special L3 started on a valid file number and subsequent L3 issued with the API option.
20	Chained file ISNs not transformed.
21	Special L3 system area not as expected. System area changed.
22	The command ID value specified was assigned to a different file and FBL is not equal to zero.
23	Incorrect CID for sort function.
249 (0x00F9)	<p>An invalid command ID value was detected by Adabas Vista (open systems):</p> <ul style="list-style-type: none"> ■ The command ID value specified with the N option of an L1/L4 command was not found. ■ The command ID value specified with the N option of an L1/L4 command does not correspond to an ISN list. ■ One or both of the ISN lists referred to in the ADDITIONS 1 field of an S8 command do not exist. <p><i>Action:</i> Review the program logic.</p>

Action

Correct the command ID.

Response 22**Origin**

Mainframe and open systems

Explanation

The command or command option is invalid. A subcode indicating the specific cause and action for this response code appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field.

When using the LNCSTUB module on mainframe systems, this response code may indicate problems with the initial call (IC) to the Adabas CICS command-level link component. If the Adabas control block shows a command code of "IC", the link routine being used may not be at the proper release level or may not be the command-level version.

The following are the subcodes and their meanings:

Subcode	Meaning
1	The nucleus detected an invalid command code.
2	This command cannot be issued by an ACC (access only) user; and update command cannot be issued by an access-only user.
3	This command cannot be performed on a read-only nucleus; an update command cannot be issued for a read-only database session.
4	This privileged command was issued without a previous OP (open) command.
5	The command is not valid for a nonprivileged user.
6	The command was rejected by user exit 11.
7	Incorrect command options were specified for a privileged command.
8	The command is invalid for an ET user in preliminary ET status. First complete the transaction using Adabas Transaction Manager.
9	The current user is not authorized to issue an ET/BT command.
10	The C2 command is no longer permitted.
11	The C3 command can only be issued by EXU users.
12	The L1/4 command with the option "F" is not valid for expanded files.
13	The call issued is not permitted when the database is in a suspend state.
14	Invalid privileged command.
15	An L1/L4 command specified the multifetch option ("M" or "O") was not combined with either the "I" or "N" option.
16	The user does not have "privileged" command authorization.
17	A refresh file (E1 command with ISN zero) is not permitted during online save database or file.
18	Applications using the ADALNK X'48' call logic receive this response when the logic has been suppressed.

Subcode	Meaning
19	<p>On mainframe systems, a special utility command was issued for an obsolete subfunction.</p> <p>On open systems, an ET or BT with command option "S" was issued without subtransactions being enabled for the current Adabas user session by specifying command option "S" in the OP command.</p>
21	<p>One of the following occurred:</p> <ul style="list-style-type: none"> ■ A BT command was issued by a non-ET logic user. ■ An ET command was issued for a distributed transaction managed by Adabas Transaction Manager; ET commands are invalid for a distributed transaction managed by Adabas Transaction Manager.
22	<p>The current transaction has already been heuristically terminated or the command is not allowed within an MC sequence.</p>
23	<p>One of the following occurred:</p> <ul style="list-style-type: none"> ■ The last MC subcommand is not ET. ■ A BT command was issued for a distributed transaction managed by Adabas Transaction Manager; BT commands are invalid for a distributed transaction managed by Adabas Transaction Manager.
24	<p>One of the following occurred:</p> <ul style="list-style-type: none"> ■ An ET or CL command with user data is not allowed for read-only access to a database. ■ CL is invalid because the user has a transaction in progress that is managed by Adabas Transaction Manager.
25	<p>A command was sent from an Event Replicator Server to an Adabas nucleus, but the Adabas nucleus is not running with ADARUN REPLICATION=YES.</p>
26	<p>An attempt was made by an Adabas nucleus to connect to an Event Replicator Server when the target of the message is actually another Adabas nucleus, not an Event Replicator Server.</p>
28	<p>A replicated utility may not be executed for a replicated file when the Adabas nucleus is running in single-user mode.</p>
29	<p>An error occurred during a connection attempt by an Event Replicator Server database. Ensure that you are trying to connect to another Adabas nucleus and not an Event Replicator Server and try again.</p>
31	<p>API file delete not permitted: not API loaded.</p>
32	<p>An attempt was made to update a replicated file in single-user-mode. Replicated files can be updated only in multi-mode; replication is not supported in single-mode. However, a nucleus with replication support can be started in single-mode for maintenance purposes.</p>

Subcode	Meaning
33	A shared hold status request (with command option 3 set to "C", "Q", or "S") is not allowed for a command with prefetch (command option 1 set to "P"). On open systems, the command option "S" is not allowed for an S9 command with a non-blank Additions 4 field.
34	On open systems, the command was rejected by user exit 11.
35	The command cannot be executed with the nucleus parameter NT=1.
36	The descending option "D" is not allowed for the command.
37	On mainframe systems, a shared hold status request (command option 3 is set to "C", "Q", or "S") is not allowed for a non-ET user. On open systems, a shared hold status request (command option 3 is set to 'C', 'Q', or 'S') is not allowed for a non-ET user.
38	A shared hold status request for a sequential read command (command option 3 is set to "Q") is not allowed for an L4 command without the N-option, nor is it allowed for an S4 command without a command ID (CID) or with an ISN buffer length other than 4 bytes.
39	A shared hold status request for a sequential read command (command option 3 is set to "Q") is not allowed for a command with a multifetch (command option 1 is set to "M" or "O"). Also, a shared hold status request (with command option 3 set to "C", "Q", or "S") is not allowed for a read command with prefetch (command option 1 is set to "P").
40	A keep-in-shared-hold-status request (with command option 3 set to "H") is not allowed for an ET or BT command with multifetch or prefetch (command option 1 is set to "M" or "P").
41	A request to read the next portion of a LOB value (command option 2 is set to "L") is not allowed for an L1/L4 command with multifetch (command option 1 is set to "M" or "O") or prefetch (command option 1 is set to "P").
42	On open systems, for an A1 command with command option 2 = "T", the current time is still the same as the value of the field with SY=TIME in the database.
50	The Router (LCC) detected an invalid command code. This may also arise when a new ACBX-type call is presented to a back-level router.
51	A client call with the ADARUN parameter PREFETCH=OLD has multiple APLX buffers or the contents of APLX+4(chained APLX) is non-zero. To resolve this, use the ADARUN parameter setting PREFETCH=YES.
52	A non-Adabas target was called.
53	Invalid file specified for an Adabas Online System function.
54	The user was stopped with STOPUR or STOPSUR.
55	The command is returned because the command queue timeout time specified by the DELCQ operator command or the AUTOCQTIME ADARUN parameter was reached or exceeded for the command.
1005	The command code is invalid.

Subcode	Meaning
1006	The ACBX is invalid (not first buffer).
1007	The ABD is invalid.
1008	The ABD type is invalid.
1009	More than one search buffer specified.
1010	More than one value buffer specified.
1011	More than one ISN buffer specified.
1012	The number of search and value buffers do not match.
1013	The number of format and record buffers do not match.
1015	A streaming logic error occurred.

Action Correct the command code or command option or the previous OP command, and rerun the program.

Response 23

Origin Mainframe and open systems

Explanation An invalid starting ISN was specified for an L2/L5 command sequence:

- The ISN was not assigned to a record in the file; or
- The ISN was greater than the MAXISN in effect for the file.

Open Systems

On open systems the following subcodes may occur:

Subcode	Meaning
249 (0x00F9)	An invalid ISN was detected by Adabas Vista (open systems). The starting ISN specified for an L2/L5 command sequence is not consistent with the definitions for the partitioned file. <i>Action:</i> Review the program logic.

Action Correct the ISN.

Response 24

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

For an S9 command:

- The ISN list in the ISN buffer was already sorted; or
- The ISN list in the ISN buffer contained an invalid ISN; or
- The "D" option was specified when trying to sort an ISN list by ISN.

Open Systems

An ISN is equal to "0" or is greater than or equal to the first free ISN found in the ISN buffer. The Additions 2 field contains the value of the invalid ISN in 4 byte binary format.

Action Correct the ISN buffer.

Response 25

Origin Mainframe and open systems

Explanation The ISN specified in ISN lower limit field for an S1/S4 or S2/S9 command was not found.

Open Systems

On open systems the following subcodes may occur:

Subcode	Meaning
249 (0x00F9)	An invalid ISN was detected by Adabas Vista (open systems). The ISN specified in the ISN Lower Limit field for an S2 command when retrieving a group of ISNs from a saved ISN list was not found. <i>Action:</i> Review the program logic.

Action Correct the ISN lower limit.

Response 26

Origin Mainframe and open systems

Explanation An invalid ISN buffer length for an S9 command was detected. The number of ISNs to be sorted as provided in ISN quantity is equal to "0".

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
2	An S9 command with an ISN buffer contains ISNs that are higher than the TOP-ISN of the file.

Action Correct the ISN buffer length.

Response 27

Origin Mainframe systems only

Explanation Sufficient work space was not available to accommodate the combined sizes of the search and value buffers as indicated in the search buffer length and value buffer length fields.

Subcode	Meaning
1	Sufficient work space was not available to generate the format translation.

Response 28

Origin Mainframe and open systems

Explanation The first two bytes of the Additions 1 field contained an invalid descriptor for an L3/L6 or S2/S9 command.

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
1	The field was not a descriptor.
2	The use of the descriptor is not supported (for example, phonetic descriptors or the descriptor is contained within a periodic group).
3	The descriptor was changed between successive calls.
4	There is a mismatch of the descriptor names in the Additions 1 field and the search buffer.
5	An initial L3 or L6 call contains no trailing blanks in the Additions 1 field.
7	ADAINV is inverting the file and using the descriptor.
8	The descriptor is missing in the file index.
9	An internal error occurred during SB interpretation.

Action Correct the Additions 1 field.

Response 29

Origin Mainframe and open systems

Explanation In an L3 or L6 command, a value repositioning was attempted (bytes 3-8 of the Additions 1 field contain spaces) and the Command Option 2 field did not contain the value "A", "D", or "V". The command ID is released.

Action Correct the Additions 1 or Command Option 2 field.

Response 34**Origin** Mainframe systems only**Explanation** An invalid command option has been detected.

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
1	An invalid command option has been specified in one of the command option fields.
2	The R option has been specified for the C5 command, but replication is not active.
9	A record buffer must be specified for this command but is missing (not specified of length zero).

Action Either remove the invalid command option or replace it with a valid option.**Response 35****Origin** Mainframe systems only**Explanation** The user/DBA attempted to perform a function for a noncluster Adabas nucleus that is available only for an Adabas cluster database.**Action** Either perform the function against a cluster database or change the function.**Response 39****Origin** Mainframe systems only**Explanation** A logically deleted descriptor was used as a search criterion or was specified in the first two bytes of the Additions 1 field for an L3, L6, L9, S2, or S9 command.**Action** Remove the use of the logically deleted descriptor and inform your database administrator about the problem.**Response 40****Origin** Mainframe and open systems**Explanation** A syntax error was detected in the format buffer.**Mainframe Systems**

On mainframe systems, one of the following subcodes may be used:

Subcode	Meaning
1	Syntax error in format buffer; possible premature end of buffer segment.
2	Syntax error in the format buffer -- bad first or second character of field name or missing "/".
3	Text literal has no ending quote or is too long (more than 255 characters).
4	Text literal is empty.
5	Expected delimiter missing.
6	Conditional format criterion has no closing parentheses ")".
7	The conditional format criterion is empty.
8	Invalid field name, format, or search operator.
9	One of the following occurred: <ul style="list-style-type: none"> ■ An invalid edit mask number (greater than 15) was specified. ■ A syntax error in the conditional format criterion was found. ■ Multiple format buffer segments are specified with conditional format criterion.
10	Invalid character following field name specification.
11	Invalid index specification for MU field in PE group.
12	Expected number missing or too large ($\geq 2^{31}$).
13	Syntax error in LOB segment specification.
14	Syntax error in L element specification.
15	Syntax error in D element specification (daylight savings time indicator).
16	Invalid Date-Time edit mask specification.
17	MU/PE index range specification invalid for LOB segment notation.

On mainframe systems, the following information is returned in the Additions 2 field of the control block:

- The leftmost two bytes contain the two characters being inspected when the error was detected.
- The rightmost two bytes contain the subcode.

Open Systems

One of the following format buffer errors occurred.

- The terminating period was missing;
- The first position contains a period, this only applies to N1 or N2 commands;
- Length and/or format specified with a range definition;
- An invalid element was detected;

- A field segment notation was not correct: it must be specified either as (*byte-number*, *length*) or as (*byte-number*, *length*, *length-2*), where *byte-number* must be either "*" or a decimal number, and *length* and *length-2* are decimal numbers. These numbers must be less than 2,147,483,648;
- A field segment notation was specified for a range of MU fields or for a range of fields within a periodic group.

On open systems, the following information is returned in the Additions 2 field of the control block:

- The leftmost two bytes contain the number of the byte (in binary format) relative to the beginning of the format buffer where the error was detected.
- The rightmost two bytes contain the name of the field being processed when the error was detected.

Action Correct the format buffer.

Response 41

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One or more specification errors exist in the format buffer. When possible, the short name of the field for which the error occurred is stored at offset 2 of the ACB's Additions 2 field or in the ACBX's Error Character Field (ACBXERRB).

The following specification errors may have been made:

Note: A collation descriptor (COLDE) can only be specified in the format buffer of the L9 command and only when the decode option has been specified in the user exit. The value returned is not the index value but the original field value.

Subcode	Meaning
1	Spacing element <i>nX</i> with <i>n=0</i> or <i>n>255</i> not allowed.
2	An invalid sequence of format buffer elements was specified.
3	Miscellaneous types of specification errors were found in the format buffer.
4	A field name was undefined or not elementary.
5	Format without fields.
6	A group field cannot be specified if the group contains a LOB (LB) field.
7	A field name is undefined.
8	Invalid use of <i>f1dD</i> , <i>f1dL</i> , <i>f1d</i> , * or E(<i>date-time-mask</i>) notation.

Subcode	Meaning
9	Elementary field in PE group: 1-N notation not permitted with LOB (LB) fields or <i>fldD</i> notations.
10	A LOB (LB) field, <i>fldL</i> (length indicator notation) or <i>fld,*</i> (asterisk notation) are not permitted with an L9 command.
11	A length indicator (<i>fldL</i>) or asterisk notation (<i>fld,*</i>) are only permitted for LA and LOB (LB) fields.
12	LA or LOB (LB) fields are not permitted with 1-N notation, <i>flda-fldb</i> (field series) notation or old MU syntax.
13	LA or LOB (LB) fields are not permitted with <i>fldC,*</i> (count indicator) or <i>flda-fldb,*</i> (field series notation).
14	Asterisk notation and length indicator notation combinations (<i>fldL,*</i>) are not permitted.
15	SQL significance indicator and asterisk notation combinations (<i>fldS,*</i>) are not permitted.
16	Length indicator (<i>fldL</i>), asterisk notation (<i>fld,*</i>) or daylight savings time indicator notation (<i>fldD</i>) are not permitted for a group field.
17	Daylight savings time indicator notation (<i>fldD</i>) cannot be combined with asterisk notation (<i>fld,*</i>) or a length indicator notation (<i>fldL</i>).
18	Daylight savings time indicator notation (<i>fldD</i>) is only permitted for fields defined with the TZ option.
20	Daylight savings time indicator notation (<i>fldD</i>) is not permitted with count indicator (<i>fldC</i>) or field series notation (<i>flda-fldb</i>).
21	Old MU syntax is not permitted with daylight savings time indicator notation (<i>fldD</i>).
22	An invalid length or format has been specified with daylight savings time indicator notation (<i>fldD</i>); if specified it must be 2,F.
23	An invalid length or format has been specified with length indicator notation (<i>fldL</i>); if specified it must have length 4 and format B.
24	A phonetic, collation, or hyperdescriptor was specified.
25	Date-time edit mask notation (<i>E(date-time-mask)</i>) is not permitted with daylight saving time indicator notation (<i>fldD</i>), asterisk notation (<i>fld,*</i>), or length indicator notation (<i>fldL</i>).
26	Date-time edit mask (<i>E(date-time-mask)</i>) notation requires format P, U, F, or B.
27	Date-time edit mask (<i>E(date-time-mask)</i>) notation and edit mask notation (E0-E15) are not permitted together.
28	Date-time edit mask (<i>E(date-time-mask)</i>) notation and count indicator notation(<i>fldC</i>) are not permitted together.
30	Date-time edit mask (<i>E(date-time-mask)</i>) notation is only permitted for a field defined with a date-time edit mask.

Subcode	Meaning
31	Daylight savings time indicator notation (<i>f1dD</i>), length indicator notation (<i>f1dL</i>), and asterisk notation (<i>f1d,*</i>) are not permitted together with LOB segment notation.
32	LOB segment notation is permitted only for LOB (LB) fields.
33	More than one LOB segment with *-position not permitted.
34	Length/format override not permitted for LOB segment notation.
35	Invalid byte number and length parameters in LOB segment notation.
36	Invalid length-2 parameter in LOB segment notation; must be equal to length parameter.
37	Invalid syntax with daylight saving time indicator in format buffer.

Open Systems

An error was detected in the format buffer:

- The field name specified is reserved for edit mask usage;
- An index was equal to 0;
- A length specified or taken from the FDT standard length is greater than the maximum length of the required format;
- *nnnX* was specified with *nnn* greater than 253;
- A literal with more than 253 characters was specified;
- A subdescriptor, superdescriptor, phonetic descriptor, hyperdescriptor or a collation descriptor was specified;
- A field specified was not present in the file;
- A periodic group name appears without an index;
- A length and/or format was used with a group notation;
- A field in a periodic group was specified without an index;
- A range notation with a group name or a multiple-value field as the first or last element was specified;
- A reference was made to the count of a multiple-value field contained in a periodic group, and no index was included to indicate the periodic group occurrence for which the count was to be returned;
- A collation descriptor with the option HE was specified for an L9 command.
- A count specification was made for a field which was neither a multiple-value field nor was contained within a periodic group;
- A count for a non-multiple value field within a periodic group was specified;
- A length and/or format specification was used with a periodic group notation;
- A (regular or periodic) group containing a multiple-value field was specified;
- Invalid index usage;

- A descending index range was specified;
- A double index was used for a non-periodic field;
- A multiple-value field with an index specification and a multiple-value field without an index specification were used;
- A value cannot be converted to the required format (READ command) or converted to the FDT standard format (UPDATE command);
- The S element was applied to a field that does not have the NC option;
- A field with the NC option was used more than once together with its S element;
- The add option is not compatible with the format/length;
- The specification of a character set was invalid;
- A field was specified with an edit mask not allowed for the field;
- A field segment notation '(byte-number,length)' or '(byte-number,length,length-2)' was not correct: byte-number + length must be less than or equal to the maximum value length + 1, and length-2 must be equal to length. The maximum value for LB fields is 2,147,483,643, for LA fields 16381, and for other values 253 bytes;
- Segment notation is only allowed for values with the format 'A'.

The following information is returned in the Additions 2 field of the control block:

- The leftmost two bytes contain the number of the byte (in binary format) relative to the beginning of the format buffer where the error was detected.
- The rightmost two bytes contain the name of the field being processed when the error was detected.

Action Correct the specification error and reissue the command or job. For more information about syntax rules for multiple field and periodic group indexing, refer to the Adabas Command Reference documentation.

Response 42

Origin Mainframe systems only

Explanation A space problem occurred. The following are the subcodes and their meanings:

Subcode	Meaning
1	The Work pool was too small to store a user format. <i>Action:</i> Increase the LWP specification and retry .
2	The internal format buffer was too small to store a user format (translated into internal structure). <i>Action:</i> Increase LFP specification and retry.

Action See the actions described in the subcodes.

Response 43

Origin	Mainframe and open systems
Explanation	In an L9 command, the descriptor specified in the format buffer did not agree with the descriptor specified in the search buffer.
Action	Correct the format buffer or the search buffer.

Response 44

Origin	Mainframe and open systems
Explanation	The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following format buffer errors occurred (subcodes are shown in the leftmost column):

Subcode	Meaning
1	The specified format is not allowed for an update operation. A possible reason for this is the presence of a conditional format buffer with an update operation.
2	The L9 command's format buffer format is not allowed for other commands.
3	The specified format is not allowed for an update operation. A possible reason for this is the presence of a conditional format buffer with an update operation.
4	The L9 command's format buffer format is not allowed for other commands.
5	Format used for L9 can only contain field and an optional daylight savings time indicator (<i>f1dD</i>).
6	Fixed point format must have length 2, 4, or 8.
7	Conditional format and more than one format buffer was specified.
8	The current Adabas call provides a different number of format buffers than the format reference by CID.
9	Number of format buffer segments (ABDs) is zero.
10	AAS, AA, AA is invalid.
12	L option specified but the format has no LOB segment with *-position.

Open Systems

One of the following situations occurred:

Subcode	Meaning
1	<ul style="list-style-type: none"> ■ The format buffer is invalid for use with an UPDATE command (A1), ADD command (N1/N2): <ul style="list-style-type: none"> ■ Format buffer contains overlapping fields, e.g., GL1-3, GL2-4.; ■ Format buffer contains an 1-N element, e.g., GL1-N.; ■ There is not a 1:1 relation between an L element and the subsequent corresponding element with '*' length; ■ A READ command uses a format buffer from the format pool, which was previously used by update or add command, and which contains an invalid conversion.
12	L option is specified but the format has no LOB section with *-position.
13	The format buffer for an A1 commands with command option 2='T' did not contain a last-update-timestamp system generated field.

Note: Subcodes associated with response 44 are stored in the first two bytes of the Additions 2 field (ACB) and in the error subcode field (ACBX).

Action Correct the format buffer or use a different read or update command.

Response 45

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The internal format buffer space has been exceeded. Either the LWP parameter setting is too small or the internal format buffer requires more than 2 G.

Open Systems

Multiple field or periodic group overflowed when using the N suffix in the format buffer for update.

The following information is returned in the Additions 2 field of the control block:

- The first two bytes will contain the number of the byte (in binary format) relative to the beginning of the record where the error was detected;
- The third and fourth bytes will contain the name of the field being processed when the error was detected.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Increase the size of the LWP parameter and try again. If the problem persists, contact your Software AG technical support representative for assistance.

Open Systems

Because the multiple field or periodic group reached its absolute limit, the application must be redesigned.

Response 46**Origin**

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The maximum value for the NQCID parameter was exceeded (the number of TBI and/or TBQ elements is greater than NQCID).

Open Systems

Mismatch of format buffer usage for the supplied command ID.

- A command ID of global ID format buffer has been found in the format pool and has a different file number to the file supplied by the caller;
- The file number was changed in subsequent Adabas calls with the same normal or global command ID.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Adjust the size of the NQCID parameter and try again.

Open Systems

Check the command IDs used in the call and try again.

Response 47**Origin**

Mainframe and open systems

Explanation

The maximum value for the NISNHQ parameter was exceeded. The following subcodes appearing in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field provide more detailed information.

Subcode	Meaning
1	<p>An attempt was made to put too many ISNs in hold. The maximum number of ISNs that can be put in hold is specified by the NISNHQ parameter and can be overridden via the Additions-4 field (bytes 3-4) of the user's OP command and via the user profile.</p> <p><i>Action:</i> Increase the value of the NISNHQ parameter or the maximum number of ISNs that the user can put in hold specified in the Additions-4 field (bytes 3-4) of the OP command or in the user profile. Alternatively, modify the application program to store fewer ISNs in hold at the same time.</p>
2	<p>The hold queue was full. If another user has put the maximum number of ISNs in hold, that other user is backed out and will next receive response code 9, subcode 1. The user who is given the response code 47 is not backed out; this user should issue an ET or BT command to release the ISNs from hold.</p> <p><i>Action:</i> Increase the value of the NH parameter. Alternatively, modify the application program to store fewer ISNs in hold at the same time.</p>

Action Increase the value of the NISNHQ parameter by modifying its ADARUN parameter value in the nucleus startup file, or (on open systems) using ADAOPR.

Response 48

Origin Mainframe and open systems

Explanation An error occurred during the processing of a command such as OP or N1. Refer to the hexadecimal subcode that appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field.

Subcode	Meaning
	File(s) not available at open time. This is the default message displayed with this response code if another subcode is not provided.
1	A specified file is locked against the requested use.
2	A specified file is currently in conflicting use.
3	A utility cannot start because an online save operation is in progress.
4	A specified file is already locked or being used by an EXU/EXF or utility user. Use operator command DLOCKF to display file locks, DNFV to display a summary of the current file usage.
5	A utility requiring exclusive database control cannot start because an online save operation is in progress.
6	A utility that requires exclusive database control cannot start because the user queue is not empty.

Subcode	Meaning
7	The requested file lock cannot be granted because the file is being used. Use operator command DNFV to display a summary of the current file usage, DFILES to display current users of the file.
8	The user ID specified in the open (OP) command is already in use by another user.
9	An EXU/EXF/UTI lock was requested in the open command, but the file is currently in the file list of a user in UPD/EXU/EXF/UTI status.
10	An EXF/UTI lock was requested in the open command, but the file is currently in the file list of a user in ACC status.
11	A nonprivileged user issued an open (OP) command to a nucleus in UTIONLY (utilities only) status.
13	Online file save attempting to run on an advance-locked file.
14	UPD/ACC open attempted against advance-locked file.
15	A file requested for an online utility (Adabas Online System or ADADBS) or an E1 program refresh is currently being used.
16	ACODE or WCODE was specified in the record buffer on the command but the nucleus was not activated with UES support.
17	A specified file is locked against the requested use and is advance-locked. The data in the file is not accessible. This can happen if a utility aborts or an autorestart fails.
18	On mainframe systems, this means that a second command was issued by a user who is participating in a two-phase commit (preliminary ET completed; final ET outstanding) or whose transaction has been heuristically terminated. On open systems, this means that the index of the specified file is not accessible. This can happen if a utility aborts or if the index has been disabled by ADAREC REGENERATE or an autorestart.
19	The file number is zero or is greater than the maximum number of files allowed for the database (based on the MAXFILES parameter setting when the database was defined using the ADADEF utility).
20	A regenerate/backout with exclusive database control is rejected because there are in-doubt transactions or heuristically terminated transactions on Work part 4.
21	File is locked for utility usage.
22	An attempt was made to release an advance-lock, but the lock was not set.
23	An advance-lock operation was attempted for a file that has not been loaded.
24	An advance-lock operation was attempted for a file that is already advance-locked.

Subcode	Meaning
25	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session has an open global transaction that could not be backed out because it is under the control of an external transaction coordinator and its status is "in doubt".</p> <p>Depending on the transaction coordinator, you may have a choice of actions:</p> <ul style="list-style-type: none"> ■ Wait for the external transaction coordinator to complete or back out the existing transaction. ■ Use the coordinator's facilities to force completion or removal of the transaction. ■ Restart the transaction coordinator to cause resynchronization of in-doubt transactions. ■ Use ATM Online Services to force backout of the local, Adabas-related part of the global transaction. <p>Caution: Using ATM Online Services to force backout of the local, Adabas-related part of the global transaction could result in loss of transaction integrity.</p>
26 - 30	<p>Reserved for Adabas Transaction Manager. These subcodes are given only when Adabas Transaction Manager is in use. Please read the Adabas Transaction Manager documentation for more information.</p>
31	<p>File locked for normal usage</p>
32	<p>A file is in use by an exclusive update (EXU) user. An update request from another user is not permitted.</p>
33	<p>A file is locked for exclusive file control (EXF) or utility update (UTI) usage. The request from a user with a different type is not permitted.</p>
34	<p>An advance-lock operation was performed on a read-only nucleus.</p>
35	<p>An advance-lock operation was performed during an online save.</p>
36	<p>Nucleus in REGENERATE/NOAUTOBACKOUT state.</p>
257 - 260	<p>Reserved for use by Event Replicator for Adabas on open systems.</p>

On open systems, the corresponding file number is returned in the first two bytes of the Additions 2 field in binary format except for value 8 in the third and fourth byte. The value 0 means the whole database.

Action

The following user actions are possible:

- Wait for the other user or utility to finish, then retry the command.
- Make the file available for all users (on open systems, if value 16 occurred in bytes 3 and 4).
- Restore or unlock the file (on open systems, if value 17 occurred in bytes 3 and 4).

- Rebuild the file's index (on open systems, if value 18 occurred in bytes 3 and 4).
- On open systems, if the value in bytes 3 and 4 of the Additions 2 field is 8, and the nucleus was started with the OPEN_REQUIRED option, you can reissue the OP command immediately. This will cause the other user with the same user ID to be stopped, unless that user is currently active.
- On open systems, if a utility receives a response 48 because non-utility users are still active, you can lock the file with ADAOPR LOCK. This ADAOPR command stops all non-utility users from accessing the file and allows only utility users to access the file until it is unlocked again.

On mainframe systems, if a utility receives a response 48 because non-utility users are still active, you can lock the file with ADADBS MODFCB FILEREADONLY. The FILEREADONLY command stops all non-utility users from accessing the file and allows only utility users to access the file until it is unlocked again.

Response 49

Origin

Mainframe and open systems

Explanation

The compressed record was too long. It exceeds the maximum permitted compressed record length for the file.

On open systems, the first two bytes of the Additions 2 field contain the length of the compressed record in binary format.

On mainframe systems, the following subcodes may be indicated:

Note: This response code always means that the compressed record is too long and there are duplicate meanings for subcodes but the subcode can help your Software AG technical support representative analyze where in the code we are giving the response. This can be useful for debugging purposes. Please always provide the subcode when communicating about this response code with your Software AG technical support representative.

Subcode	Meaning
	File(s) not available at open time. This is the default message displayed with this response code if another subcode is not provided.
1	Multiple-value (MU) field.
2	Periodic (PE) group field.
3	MU field.
4	PE group.
5	PE group level.
6	Remaining fields.
7	Record too long for protection logging (internal error).

Subcode	Meaning
8	A compressed record exceeds the permitted length. The error was detected when updating a multiple field.
9	Exceeded segment length maximum.
10	Long alpha or wide field.
11	New compressed record too long
12	Old version MU update.
13	The MU field was defined with an index
14	An MU update caused the compressed record to become too long.
15	An MU update caused the compressed record to become too long.
16	An MU update caused the compressed record to become too long.
17	MU update, MU count > 1
18	An update to an LA field caused the compressed record to become too long.
19	LOB value too long. An attempt was made to update a LOB value segment that ends after the maximum allowed length of LOB value. This response code/subcode combination is produced as a result of an L1/L4 command with Command Option 2 set to "L" but with the ISN Lower Limit value greater than or equal to the length of the LOB value being read.
20	Compressed Data Storage record too long. A LOB update attempted to make a long LOB value (greater than 253 bytes) short (less than or equal to 253 bytes), but the base record was too long to embed the short LOB value. This condition was detected when the LOB value was being read from the LOB file.
21	Compressed Data Storage record too long. A LOB update attempted to make a long LOB value (greater than 253 bytes) short (less than or equal to 253 bytes), but the base record was too long to embed the short LOB value. This condition was detected when an attempt was made to insert the short LOB value into the base record.
90	Segment too long
96	Compressed record too long
99	Exceeded segment length maximum

Action

On open systems, add a new DATA extent with sufficient block size (block size >= compressed record size + 8). Alternatively you can start the nucleus with `OPTIONS=AUTO_EXPAND`; then the Adabas nucleus automatically creates a new DATA extent with sufficient block size.

Response 50**Origin** Mainframe and open systems**Explanation** A syntax error in the record buffer was detected during processing of an OP command, an invalid character set was specified, an invalid time zone was specified, or an invalid file number (zero or greater than maxfiles) was specified.

On open systems, the first two bytes of the Additions 2 field contain the number of bytes (in binary format) relative to the beginning of the record buffer where the error was detected. If a time zone problem occurs, the two right-most bytes of the Additions 2 field in the ACB will contain a subcode; in an ACBX, the Error Subcode field will contain the subcode.

Subcode	Meaning
31	Time zone not found in ADAZON directory. The specified time zone was not found in the ADAZON directory. Verify the time zone was specified correctly. If it was, contact your Software AG technical support representative for assistance.
32	Time zone pool full. No more time zone information could be loaded. Increase the size of the ADARUN LTZ parameter and restart the nucleus.
33	Open error on DD:TZINFO(MEMBER). Contact your Software AG technical support representative for assistance.
34	I/O error on DD:TZINFO(MEMBER). Contact your Software AG technical support representative for assistance.
35	Invalid data in TZ file. Contact your Software AG technical support representative for assistance.
36	Invalid transition time in TZ file. Contact your Software AG technical support representative for assistance.

Action Correct the record buffer and try again.**Response 51****Origin** Mainframe and open systems**Explanation** An error in the record buffer was detected during processing of an OP command.

One of the keywords EXU, UPD, ACC or WCHARSET is duplicated.

On open systems, the following information is returned in the Additions 2 field of the control block:

- the first two bytes contain the number of bytes (in binary format) relative to the beginning of the record buffer where the error was detected;
- the third and fourth bytes contain the open mode that failed (ACC = 1, UPD = 2, EXU = 4, WCHARSET = 128)

Action Correct the record buffer and try again.

Response 52

Origin

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following errors occurred while processing the record, value, or search buffer. In an ACB, the rightmost two bytes of the Additions 2 field contain the subcode; for subcodes 1-5, the leftmost two bytes contain the Adabas name of the field where the error occurred. In an ACBX, the subcode is stored in the Error Subcode (ACBXERRC) field; for subcodes 1-5, the Adabas field name where the error occurred is stored in the Error Character Field (ACBXERRB).

Subcode	Meaning
1	Invalid packed or unpacked decimal value in record buffer.
2	Invalid length for variable-length field specified in record buffer.
3	Invalid null value or no value at all provided for field with NN option.
4	Invalid value for S element in record buffer.
5	Invalid value for S element in value buffer.
6	Encoding a collation descriptor value failed: the collation descriptor exit issued a return code.
7	Decoding a collation descriptor value failed: the collation descriptor exit issued a return code.
99	An invalid field length was specified.

Open Systems

- The value of a G format field was not in floating point format;
- The value of a P format field was not in packed decimal format;
- The value of a U format field was not in unpacked decimal format;
- A variable-length field was specified without a length parameter;
- The SQL null value indicator (S element) has a value of less than -1;
- A field with the NN option is forced to take the SQL null value;
- The resulting value exceeds 4 bytes (longword) if the format is F, or exceeds the maximum (format dependant) length;
- No record with the specified ADAM key was found.

The following information is returned in the Additions 2 field of the control block:

- The first two bytes contain the number of the byte (in binary format) relative to the beginning of the record/value buffer where the error was detected. This value is -1 if a field with the NN option is forced to take the SQL null value.;

- The third and fourth bytes contain the name of the field being processed when the error was detected.

Action Correct the format, record, value, or search buffer and try again.

Response 53

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following errors occurred:

Subcode	Meaning
0	<p>The record buffer is too small.</p> <p><i>Action:</i> If the record buffer size:</p> <ul style="list-style-type: none"> ■ conflicts with the lengths specified in the format buffer, change either the record buffer size or the format buffer specifications to resolve the conflict. ■ conflicts with the established global format ID (GFID), either release the GFID or change the record buffer size to match the GFID. ■ default is too small to hold the records in the file including the DVT when running the ADAULD utility, increase the size of the record buffer by setting the ADAULD LRECL parameter. See the Adabas Utilities documentation for more information.
1	<p>The record buffer is too small. When locating a variable field in the input record, the required buffer length exceeded the given length.</p> <p><i>Action:</i> Verify that the record buffer content matches the given format and that sufficient space for variable fields is provided in the record buffer.</p>
2	<p>The ISN buffer is too small.</p> <p><i>Action:</i> Increase the size of the buffer.</p>
3	<p>The record buffer is too small. When locating a variable field within a group in the input record, the required record buffer length exceeded the given length.</p> <p><i>Action:</i> Verify that the record buffer content matches the given format and that sufficient space for variable fields is provided in the record buffer.</p>
4	<p>The record buffer is too small. When locating a field with A,* notation in the input record, the required record buffer length exceeded the given length.</p> <p><i>Action:</i> Verify that the record buffer content matches the given format and that sufficient space for variable fields is provided in the record buffer.</p>

Subcode	Meaning
7	At least one of the record buffers was too small for the data defined in the corresponding format buffer.
8	The referenced existing format buffer requires more space than that given in one of the record buffers. If this subcode occurs using ADACMP DECOMPRESS, the LRECL of the output record is too small.
249	In Adabas Vista, the record buffer provided for an L9 command with 'I' option against a partitioned file is not large enough to hold the full list of ISNs. <i>Action:</i> Increase the size of the record buffer.

Open Systems

The record buffer was too small, or the ISN buffer was too small for a requested multifetch command. The following information is returned in the Additions 2 field of the control block:

- The first two bytes contain the expected buffer size in binary format. This value is -1 if the command would have exceeded the maximum record size.
- The third and fourth bytes contain the name of the buffer that was too small. ("RB" or "IB"). If the error occurred while using a hyperdescriptor exit, the name of the hyperdescriptor exit is stored here.

Action Increase the record buffer or ISN buffer size, as appropriate.

Response 54

Origin Mainframe and open systems

Explanation The record buffer for a C3, C5, or ET command is too long. The maximum allowed size is 2048 bytes. The following subcodes provide more information:

Subcode	Meaning
1	The record buffer for the C3 command is too long.
2	The record buffer for the C5 command is too long.
3	The record buffer for the ET command is too long.

Action Correct the record buffer specification, then reissue the C3, C5, or ET command.

Response 55**Origin**

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following occurred:

- During a read-type operation, a field defined with the SQL null (NC) option contained a null value, but the format buffer held no "S" (significant null) indicator for the field.

In an ACB, the Additions 2 may contain the field name in the leftmost two bytes; the rightmost two bytes may contain the offset into the record buffer. In an ACBX, the Error Character Field (ACBXERRB) may contain the field name; the Error Offset in Buffer (ACBXERRA or ACBXERRG) fields may contain the offset into the record buffer.

- Attempted format conversion was not possible due to incompatible data formats or other compatibility problems.

In an ACB, the Additions 2 will contain the field name in the leftmost two bytes; the rightmost two bytes will contain the offset into the record buffer. In an ACBX, the Error Character Field (ACBXERRB) will contain the field name; the Error Subcode (ACBXERRC) field will contain the subcode.

Subcode	Meaning
0	Conversion error on record decompression.
1	Invalid conversion between formats.
2	Invalid length for fixed encoding. For example, user encoding Unicode with code-point size of 2 bytes and no even length specified.
4	Conversion error of a floating-point field (underflow) when converting to/from a non-IBM floating-point format.
5	One of the following conditions exists: <ul style="list-style-type: none"> ■ Format conversion of a field with the NV option is not allowed. ■ In a read command (Lx, Sx), the format buffer of a field containing a null value is defined with the NC option, but without the NN option, and is missing the SQL significance indicator (S). For read-type commands, the S indicator is required when the NC fields are defined without the NN option. If the S indicator is not present when a read command detects an NC-specified field and the field actually contains a null value, this response code and subcode are returned.
6	An invalid length was specified (for example, a wide character field in Unicode encoding must have an even length).
7	Invalid conversion between formats (different case than subcode 1).

Subcode	Meaning
8	Conversion error of a floating-point field (overflow) when converting to/from a non-IBM floating-point format.
9	A one-byte field was provided in the record buffer for the occurrence count of an MU field or PE group in a file with extended MU/PE limits. A two-byte occurrence count value is expected.
10	A field using the NC field option has a null value and no S indicator was specified in the format buffer.
20	Unsupported date-time conversion -- internal error.
21	Date-time value outside valid range. The valid range depends on the date-time edit masks being used in the format or search buffer and the FDT.
22	Invalid local time -- (non-existing local time in the gap that occurs when switching from standard to daylight saving time or when the time zone advances GMT offset)
23	Year outside range of 1-9999.
24	Month outside range of 1-12.
25	Day outside range of 1-n.
26	Hours outside range of 0-24.
27	Minutes outside range of 0-59.
28	Seconds outside range of 0-59.
30	Accessing a field defined with option TZ but no time zone was specified in the user session. Issue the OP command with TZ='timezone' parameter in the record buffer to set the time zone for the user session.
31	Invalid daylight saving offset given (<i>f1dD</i>) for date-time and time zone.
n	Data between user and system data representation could not be converted without error and 2-byte error code from ECS.
254	Numeric field length in format shorter than the field length in the FDT.
255	Field length exceeded maximum for variable fields.

Entire Conversion Service (ECS) error codes are described in *Entire Conversion Service (ECS) Errors*, elsewhere in the Adabas Messages documentation.

Open Systems

A format, length conversion, or truncation error occurred while processing field values in the record buffer or value buffer.

- The value for an FI field is too long;
- The resulting value exceeds the border of the FI field;
- Truncation error of numeric field;

- Truncation of alphanumeric fields or truncation of numeric fields which are converted to alphanumeric, except when OPTIONS=TRUNCATION is enabled in ADANUC;
- A value defined without LA or L4 option with variable length is larger than 253 bytes. This may happen for Unicode fields after conversion to another encoding.
- The length specified for a Unicode field for a character set with fixed character length is not a multiple of the character length: in particular, the length for UTF-16 based character sets must be a multiple of 2, and the length for UTF-32 based character sets must be a multiple of 4;
- The specified value is not a valid date/time value;
- The field does not contain a valid date/time value. This can happen if the value was stored without a date/time edit mask;
- A date/time field with option TZ was specified in the format or search buffer, but there was no time zone specified in an OP command for the current Adabas user session;
- The attempted format conversion was not possible due to incompatible data formats or other compatibility problems.

The following information is returned in the first two bytes of the Additions 2 field, and in the case of an ACBX, also in the field ACBXERRC:

Subcode	Meaning
0	Conversion error.
1	Truncation error.
2	Internal structure error.
5	Internal error.
20	Unsupported DATETIME conversion.
21	Date/time value outside valid range. The valid range depends on the date-time edit masks being used in the format or search buffer and the FDT.
22	Date/time value specified in gap when switching from standard time to daylight saving time.
24	Month not between 1 and 12.
25	Day not between 1 and n, where n is the number of days of the month specified.
26	Hours not between 0 and 24.
27	Minutes not between 0 and 59.
28	Seconds not between 0 and 59.
30	Internal error: missing time zone element for conversion with time zone.
31	Invalid daylight saving offset given (fldD) for date/time and time zone.

The field name is returned in the third and fourth byte of the Additions 2 field, and in the case of an ACBX in the field ACBXERRB.

In addition, the following information is returned in the case of an ACBX call:

- The offset in the record or value buffer in ACBXERRA;
- The type of buffer in ACBXERRD ('R' for error in record buffer, 'V' for error in value buffer).

Action

Depending on the reason:

- Correct the appropriate buffer and try again;
- If the time zone specification in the OP command is missing, execute an appropriate OP command;
- On open systems, if a record structure error is indicated, run ADAVFY FIELD against the corresponding file. If this produces errors, then the file must be unloaded, decompressed, recompressed and reloaded;
- On open systems, subcodes 2 and 5 should never occur; you should, therefore, contact your nearest support center if you receive one of these subcodes. A copy of the command log and an export copy or backup of the files accessed will help us to analyze the problem.

Response 56

Origin

Mainframe and open systems

Explanation

One of the following occurred:

Subcode	Meaning
.	The descriptor value was too large. Descriptor values are limited to 1144 bytes.
<i>n</i>	The collation value exceeded the maximum 253 bytes. The subcode <i>n</i> is the collation descriptor exit number.

Action

Store a shorter descriptor value or collation value.

On open systems, you also can specify the TR option for the descriptor, which truncates larger descriptor values before they are stored in the index. Note that with the TR option, search results may be inaccurate: this is because values that are identical in the first 1144 bytes are considered to be equal to each other.

Response 57

Origin	Mainframe and open systems
Explanation	In an L9 command, the descriptor specified in the format or search buffer or in the Additions 1 field was invalid or the descriptor was not specified: <ul style="list-style-type: none"> ■ The field name specified may not be the name of a descriptor. ■ The descriptor specified may be a phonetic descriptor or a hyperdescriptor, which are not allowed in an L9 command. ■ On open systems, the descriptor specified may be a collation descriptor with the option HE.
Action	Correct the descriptor in the format buffer, search buffer, or Additions 1 field and try again.

Response 58

Origin	Mainframe systems only
Explanation	The format could not be found (as defined within format selection criteria).
Action	Adjust the format specification and try again.

Response 59

Origin	Mainframe systems only
Explanation	Format conversion of a subfield is not possible. The source field has fixed point (F) or floating point (G) format.
Action	Correct the field for which you are attempting format conversion and try again.

Response 60

Origin	Mainframe and open systems
Explanation	The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

A syntax error was detected in the format or search buffer. Generally in an ACB, the first two bytes of the Additions 2 field contain the two characters under inspection when the error was detected and the rightmost two bytes of the Additions 2 field in the ACB contain one of the following subcodes. In an ACBX, the Error Character Field (ACBXERRB) contains the two characters under inspection when the error was detected and the Error Subcode (ACBXERRC) field contains one of the following subcodes.

Subcode	Meaning
1	Premature end of search buffer.
2	Syntax error in search buffer; possibly a bad field name.
3	Text literal has no ending quote or is too long (more than 255 characters).
4	Text literal is empty.
5	Expected delimiter missing.
6	Soft coupling criterion has not closing parenthesis (")").
7	Soft coupling criterion is empty.
8	Invalid field name, format, or search operator.
9	Invalid edit mask number (greater than 15).
10	Invalid character following field name specification.
11	Invalid specification of MU field in PE group.
12	Expected number missing or too large (greater than 2 ³¹).
13	Syntax error in LOB segment specification.
14	Syntax error in length indicator notation (L) specification.
15	Syntax error in daylight savings time notation (D) specification.
16	Invalid date-time edit mask specification.
17	MU/PE index range specification is invalid for LOB segment notation.

Open Systems

A syntax error was detected in the search buffer.

The following information will be returned in the Additions 2 field of the control block:

- The first two bytes will contain the number of the byte (in binary format) relative to the beginning of the search buffer where the error was detected;
- The third and fourth bytes will contain the name of the field being processed when the error was detected.

Action Correct the format or search buffer and try again.

Response 61

Origin Mainframe and open systems

Explanation An error was detected in the search buffer, value buffer, or during an S8 command.

Mainframe Systems

On mainframe systems, one of the following subcodes may also be included with this response code:

Subcode	Meaning
2	An invalid value operator was detected in the search buffer.
3	An invalid logical operator was specified for an S8 command - Command Option 2.
7	<p>This subcode indicates that one of the following errors occurred:</p> <ul style="list-style-type: none"> ■ The length of a descriptor value was greater than 253. ■ Invalid file number specification. ■ Invalid selection criteria for an Event Replicator for Adabas initial-state definition. ■ Invalid usage of the "S" or "N" operator. ■ The element order was invalid. ■ The specified field was not a descriptor. ■ The specified field has the "LA" option active. ■ A descriptor contained in a periodic group was specified without an index. ■ Invalid connection of partial criteria or different indices were used for a descriptor contained within a periodic group. ■ Invalid periodic group index. ■ Invalid or disallowed use of a phonetic descriptor. ■ A descriptor derived from or contained in a periodic group is not allowed. ■ The FROM-TO operator was specified with a phonetic descriptor. ■ Invalid FROM-TO range specification, or the FROM value was greater than the TO value. ■ The BUT-NOT value was outside the range of the preceding FROM-TO range. ■ An invalid command option was specified for ISN LIST processing (S8 command). ■ The search buffer "S" significant null indicator was specified with a value operator other than "EQ" (equals), which is not allowed.
8	An invalid FROM-TO range was specified. The BUT-NOT value was outside the range of the preceding FROM-TO value.
9	An invalid search criteria was specified.

Open Systems

On open systems, an error was detected in the search or value buffer, or during an S8 command:

- Invalid command option 2 specified for ISN LIST processing (S8 command);
- Invalid element or element order;

- The specified field was neither a descriptor, subdescriptor, superdescriptor nor a phonetic descriptor;
- Invalid connection of partial criteria and/or different indices used for a descriptor contained within a periodic group;
- Invalid use of a phonetic descriptor;
- Invalid periodic group index;
- Invalid index usage;
- The length of a descriptor value was greater than 253 or greater than the permitted length for the required format;
- Invalid format type;
- Invalid file number specification;
- Invalid usage of the S operator - FROM value greater than TO value;
- Invalid usage of the N operator - BUT NOT value was outside the range of the preceding FROM-TO range;
- Invalid comparator;
- The value in the value buffer cannot be converted into the field's FDT format;
- The specified file name is not an ADAM key while using the V option with an A1 or E1 command;
- Invalid value given in the value buffer while using the V option with the A1 or E1 command;
- Invalid usage of the C option - only allowed for collation descriptors;
- A field was specified with an edit mask that is not allowed for the field.

The following information is returned in the Additions 2 field of the control block (not for the S8 command):

- The first two bytes will contain the number of the byte (in binary format) relative to the beginning of the search buffer where the error was detected;
- If the third byte is zero, the fourth byte contains more information about the error:
 - Fourth byte 1: invalid length.

Otherwise the third and fourth bytes will contain the name of the field being processed when the error was detected.

Action

Correct the search or value buffer or S8 command and try again.

Response 62**Origin** Mainframe and open systems**Explanation** One of the following has occurred:

- The length of the search or value buffers as specified in the search and value buffer length fields, respectively, was not sufficient to accommodate the search criteria specified.
- The first character in the search buffer was a period (.).
- The search buffer does not contain a period (.).

Action Correct the search or value buffer and try again.**Response 63****Origin** Mainframe and open systems**Explanation** The command ID value specified in the search buffer was invalid.

On open systems, the value in the first two bytes of the Additions 2 field indicates the reason (2 byte binary format):

Subcode	Meaning
1	The command ID value specified in the search buffer was not found.
2	The associated ISN list is not sorted in ISN sequence (it has been generated by an S2/S9 command).
3	The command ID was not used in the previous FIND in which the SAVE ISN LIST option was used.

Action Correct the command ID in the search buffer and try again.**Response 64****Origin** Mainframe systems only**Explanation** This response code is used for communication with Adabas utilities and Adabas Online System (AOS), and was returned because the requested function could not be performed on the Adabas system (including checkpoint and security) files or because an error occurred in an AOS or utility function.

The following table shows some of the subcodes that may be returned:

Subcode	Meaning
61	No or duplicate field(s) (see 'xx'); where xx is the first duplicate field encountered. If no field definitions were specified an FC is returned.

Action Refer to the ADAREP output report for a list of the system files, or to the subcodes in the job output for more information. For AOS, a subcode is displayed in the error message, following the AOS module number. For utility functions, the subcodes may be described within the message text.

If you do not understand the action to take for a response code 64 or subcode, note the subcode and the function that caused the response code, and call your Software AG technical support representative for assistance.

Response 65

Origin Mainframe systems only

Explanation An internal error occurred. The nucleus detected a space calculation error.

Action Contact your Software AG technical support representative for assistance.

Response 66

Origin Mainframe systems only

Explanation An incompatible owner ID was detected during an update operation on a multicient file. The owner ID may be blank, or too long.

Action Contact your Software AG technical support representative for assistance.

Response 67

Origin Mainframe systems only

Explanation One of the following errors occurred:

Subcode	Meaning
.	An internal error occurred while executing an Sx command.
2	An error occurred during superfield generation.

Action Retain all related information, and contact your Software AG technical support representative for assistance.

Response 68

Origin	Mainframe systems only
Explanation	A nondescriptor field was used as a search criterion, and the non-descriptor search facility has been set OFF (the default for this facility is ON).
Action	The ADARUN parameter NONDES has been set to reject non-descriptor searches; either reset the NONDES parameter to its default value, or remove non-descriptor searches from your application. Natural provides a trace facility which locates such Natural application characteristics. Contact Software AG for details.

Response 70

Origin	Mainframe systems only
Explanation	An overflow occurred in the table of sequential commands.
Action	The DBA may increase the value used for the LQ parameter or RC commands may be used.

Response 71

Origin	Mainframe systems only
Explanation	An overflow occurred in the table of resulting ISN lists.
Action	The DBA may increase the value used for the LI parameter or RC commands may be used.

Response 72

Origin	Mainframe and open systems
Explanation	One of the following errors occurred:

Subcode	Meaning
6	The NU parameter is too small for the execution of a session autorestart. It is smaller than it was in the previous Adabas nucleus session that failed. In a cluster nucleus, the NU parameter is smaller than in the nucleus that had established the global lock structure.
7	An overflow occurred in the user queue.
8,9	An overflow occurred in the user queue file list pool.

Action	The DBA may increase the value used for the NU parameter.
---------------	---

Response 73**Origin** Mainframe and open systems**Explanation** An overflow occurred in the section of the Work data set (mainframe systems) or the temporary working space (open systems) in which resulting ISN lists are stored.

On open systems, please note that for read-only databases, temporary working space is only created if a location for it is explicitly specified (environment variable `TEMPLOCn` or entries for `TEMPORARY_LOCATION` in the file `DBnnn.INI`); otherwise only some of the space in the Adabas buffer pool is used for storing the ISN lists.

Action On mainframe systems, the DBA may increase the size of the Work data set and/or the number of saved ISN lists during an Adabas session may be decreased.

On open systems, provide enough temporary working space. For read-only databases, specify the location for the temporary working space explicitly or increase the size of the Adabas buffer pool (ADANUC parameter LBP).

Note: The processing of ISN lists was changed for Adabas Version 5.1. If you get this error with an Adabas Version 3 database, please refer to the Adabas Version 3 documentation.

Response 74**Origin** Mainframe and open systems**Explanation** No space was available on the Work data set for complex find commands.**Action** On open systems, increase the size of the Work data set.

On mainframe systems, increasing the size of the Work data set alone will not solve this problem. Instead, set the value of LWKP2 (WORK-PART-2) to a higher value than the calculated one (whatever that might be). Then increase the size of the Work data set to ensure there is sufficient space for WORK-PART-3.

Response 75**Origin** Mainframe and open systems**Explanation** Attempts to allocate additional Associator or Data Storage extents for a file were issued, but the maximum number of extents that can be handled by the FCB have already been allocated.

On mainframe systems, BT (backout) or autorestart processing could cause the file to be locked because of inadequate extent space (see response code 48, ADARSP048).

On open systems, the last extent is allocated only for a command which is being backed out and for AUTORESTART and ADAREC REGENERATE. The first two bytes of the Additions 2 field contain the highest possible extent number (in binary format). The third and fourth bytes indicate where the overflow occurred. Possible values are: "DS" (Data Storage), "AC" (Address Converter), "NI" (Normal Index) and "UI" (Upper Index).

Action On mainframe systems, ask your DBA for assistance; Associator or Data Storage extents may have to be reallocated.

On open systems, unload the file and reload it with appropriate initial allocations.

Response 76

Origin Mainframe and open systems

Explanation An overflow occurred in an inverted list index (the maximum is 15 levels).

Action Unload and reload the file with an appropriate padding factor for the Associator.

Response 77

Origin Mainframe and open systems

Explanation Sufficient space was not available for a required Associator or Data Storage extent.

On mainframe systems, the following subcodes further define the error:

Subcode	Meaning
1	FST empty.
2	AC START RABN not available.
3	AC END RABN not available.
4	FST will not fit into five ASSO blocks.
5	FST exhausted trying to allocate AC extent.
6	ASSO space allocation RABN not on device.
7	ASSO space on required device not available.
8	FROM RABN available, but contiguous space is not sufficient.
9	Data Storage space of the requested size is not available.
10	Data Storage space on the same device as the previous extent is not available.
11	FST is empty, or data storage for the current MAXRECL value is not available.
12	FST empty.

On open systems, the third and fourth bytes of the Additions 2 field contain either "AS" (Associator) or "DS" (Data Storage). You can also get the response 77 if you specified an explicit RABN for an Associator or Data Storage extent and the requested space is not available at the requested RABN. Please note that Adabas distinguishes between small (< 16KB) and large (>= 16KB) index blocks. This means that a response 77 can be returned even though there are enough free Associator blocks, but the free Associator blocks have the wrong size.

Action On mainframe systems, ask your DBA for assistance; Associator or Data Storage extents may have to be reallocated.

On open systems, add a new Associator or Data Storage extent to the database using the ADADBM utility or specify a RABN where the requested space is available.

Note: Response 77 can sometimes be prevented by enabling database autoexpand to execute in the online mode (specify the open systems nucleus parameter OPTIONS=AUTO_EXPAND).

Response 78

Origin

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The cause of this response is indicated by one of the following subcodes:

Subcode	Meaning
1	The AC file cannot be increased; only one file extent is permitted.
2	The file contains more than either 4 billion or 16 MB of ISNs, depending on the ISN length, or if ISNREUSE is in effect, the file has reached TOPISN and is very fragmented and too much effort would be needed to search for a free ISN.

Open Systems

An overflow occurred in the free space table (FST) as a result of Associator or Data Storage fragmentation, or the maximum number of DSST extents has already been allocated.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

If the file has reached the 16-MB limit, you might convert it to a file with the 4-byte ISN option or to an expanded file. If ISNREUSE is in effect, ADABAS ISNREUSE=ON, RESET can be used to reset the rotating ISN pointer or the file can be reloaded to eliminate the fragmentation.

If the file has NOACEXTENSION specified, look for alternatives to increase the file size such as adding an additional file to the expanded file chain. If the file is not part of an expanded file chain, you may want to reload the file to remove the restriction.

Open Systems

If it is an FST problem, reorder the database. If it is a DSST problem, which can only occur in the context of a utility, refer to the message DSSTALL for further information.

Response 79**Origin**

Mainframe and open systems

Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

A collation descriptor exit or hyperdescriptor exit error occurred. The following table describes the possible subcodes for this response code and their meanings:

Subcode	Meaning
1	Either a collation descriptor exit (subcode CDX n where n is the one-byte binary collation descriptor exit number) or a hyperdescriptor exit ("hyperdescriptor exit") was not specified ADARUN.
5	The hyperdescriptor exit stub was called for an extended MU/PE file.
6	Improper use of the parameter list was detected by the Hyperdescriptor Exit Stub. The most likely reason is that a hyperdescriptor exit using the Adabas 8 parameter structures is linked to the Hyperdescriptor Exit Stub.
7	The Hyperdescriptor Exit Stub could not resolve the HEXOLD external reference.
8	Improper use of the parameter list was detected. The second word of the parameter list was modified.
9	A hyperdescriptor exit did not return an output parameter area address.
10	A hyperdescriptor exit rejected the call by setting a nonzero return code in the output parameter header.

Open Systems

A hyperdescriptor exit is not available to the nucleus. The following information is returned in the Additions 2 field of the control block:

- The first two bytes contain the number of the hyperdescriptor exit;
- The third and fourth bytes contain the name of the hyperdescriptor.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The following table describes the actions you should take for each possible subcode for this response code:

Subcode	User Action
1	Reissue ADARUN with the CDX nn or HEX nn parameter. For more information about ADARUN parameters, read <i>Adabas Initialization (ADARUN Statement)</i> , in <i>Adabas Operations Manual</i> ; for more information about user exits and hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
5	The Hyperdescriptor Exit Stub may not be used with extended MU/PE files. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
6,7	Investigate the Hyperdescriptor Exit Stub link job. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
8	A likely cause of the error is that a pre-Adabas 8 hyperdescriptor exit was called without a linked Hyperdescriptor Exit Stub. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
9	Hyperdescriptor exits must return an output parameter area address upon return. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
10	Investigate the hyperdescriptor exit to determine why the call was rejected.

Open Systems

Define the hyperdescriptor exit and restart the nucleus.

Response 81

Origin

Mainframe systems only

Explanation

An MU or PE field error occurred, as described by the subcode:

Subcode	Meaning
1	The PE index is greater than 191 (if the maximum number of PE field occurrences is 191).
2	The PE index is greater than 65534 (if the maximum number of PE field occurrences is 65534).
3	The MU index is greater than 65534 (if the maximum number of MU field occurrences is 65534).
4	The MU index is greater than 191 (if the maximum number of MU field occurrences is 191).

Action

Correct the MU or PE field problem and try again. If the problem persists, contact your Software AG technical support representative for assistance.

Response 82

Origin	Mainframe systems only
Explanation	A hyperdescriptor exit routine returned an invalid ISN.
Action	Correct the hyperdescriptor exit routine logic and restart the nucleus.

Response 83

Origin	Mainframe and open systems
Explanation	The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

A hypertable overflow occurred.

Open Systems

A hyperdescriptor exit routine returned an invalid ISN.

The following information will be returned in the Additions 2 field of the control block:

- The first two bytes contain the offset the invalid ISN in the specified ISN buffer in binary format;
- The third and fourth bytes contain the name of the hyperdescriptor.

Action	The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.
---------------	---

Mainframe Systems**Open Systems**

Correct the hyperdescriptor exit routine and restart the nucleus.

Response 84

Origin	Mainframe systems only
Explanation	Too many values were present for a subdescriptor or a superdescriptor.
Action	Reduce the number of subdescriptor or superdescriptor values and try again.

Response 85

Origin Mainframe and open systems

Explanation The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Too many descriptor values were present for an update or add record command.

Open Systems

The descriptor value table space cannot be allocated from the buffer pool.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Open Systems

Increase the size of the LBP parameter.

Response 86

Origin Mainframe and open systems

Explanation A hyperdescriptor exit return error occurred for one of the following reasons:

- An incorrect sign for a packed descriptor value was created.
- A value with an incorrect length byte was returned.
- The ISN was changed by an update command.

On open systems, the following information is returned in the Additions 2 field of the control block:

- The first two bytes contain a value. This value can be:
 - 1 the hyperdescriptor pool exceeds the nucleus buffer pool
 - 2 the hyperdescriptor exit has returned an invalid pointer, length or count value
 - 3 an element in the user-defined format buffer is not a parent field of the hyperdescriptor
 - 4 - 255 Adabas response code
 - >255 user-defined error return for hyperdescriptor exit routine
- The third and fourth bytes contain the name of the hyperdescriptor or the name of the parent field.

Response 87

Origin Mainframe systems only

Explanation The Adabas buffer pool is locked; it is too small to accommodate all blocks needed for (parallel) command execution.

Action Check the length of the buffer pool (LBP) as follows:

Subcode	User Action
1	Check the LBP value with DPARM.
2	Increase the ADARUN LBP parameter value.
3	Retry the operation. If the error recurs, call your Software AG support representative for assistance.

Response 88

Origin Mainframe and open systems

Explanation This response code generally occurs when there is a workpool (LWP) shortage. Sufficient work pool space is not available or the sort work space is too small (even if only one user is active).

On mainframes systems, when this response code occurs, refer to the hexadecimal subcode that appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field. This subcode describes what kind of operation encountered the error.

The following table describes the mainframe subcodes and provides recommended actions.

Subcode	Operation Encountering the Workpool Shortage	Action
1	Only active command is waiting for workpool space.	Increase the ADARUN LWP setting and try again.
	During session autorestart, insufficient workpool or user queue space was encountered.	
2	Only active command is waiting for workpool space.	Increase the ADARUN LWP setting and try again.
3	A command waiting for workpool space was interrupted for transaction backout.	
4	A1 command	
5	E1 command	
7	Superfield value generation	
8	N1 command	

Subcode	Operation Encountering the Workpool Shortage	Action
9	OP command	
10	Descriptor value generation	
11	Hyperdescriptor value generation	
12		
13	Subdescriptor value generation	
15	DTP=RM: A getmain error during Work-Part-4 initialization.	
16	Hard-coupled file update processing encountered a workpool shortage.	
17	A session autorestart encountered a workpool shortage.	
22	Online reorder by descriptor	
23	Online invert	
24	Open one of the Work data sets in a cluster	
25	Session autorestart in a cluster	
79	Work pool shortage during release of advanced lock function.	
80	Work pool shortage during insert (N1/N2-command) of spanned record	
96	Internal command queue full	
98	Cluster with DTP=RM: Recovery of distributed transactions encountered a workpool shortage.	
99	ET command with P-option	
	Descriptor value generation for multi-client file	
	Single-user mode: Command initialization	
	Replication: Setup of initial-state process	
	DTP=RM: Insufficient user queue space during Work-part-4 initialization	

Action

For mainframe systems, review the actions described in the table above.

For open systems, verify the parameter values for the database that relate to the working storage allocation. Ask your DBA to increase the size of the LWP or LS parameter, as necessary.

Response 89**Origin** Mainframe systems only**Explanation** The UQE was already in use, and an attempt was made to execute two commands at the same time for the same user.**Response 94****Origin** Mainframe systems only**Explanation** An I/O error occurred on DDWORKR4.**Response 95****Origin** Mainframe systems only**Explanation** An I/O error occurred on the Work LP area.**Response 96****Origin** Mainframe systems only**Explanation** An error occurred during ADARES REPAIR utility execution.

Subcode	Meaning
2	An I/O error occurred during nucleus termination; Additions 2 may contain RABN.

Response 97**Origin** Mainframe systems only**Explanation** An I/O error occurred during buffer flush. Additions 2 may contain RABN.**Response 98****Origin** Open systems only**Explanation** A uniqueness violation of a unique descriptor was detected during a store or update processing if subtransactions are not activated, or otherwise at end of a subtransaction. The third and fourth bytes of the Additions 2 field contain the name of the descriptor which caused the uniqueness conflict.**Action** Check the descriptor values.

Response 99

Origin Mainframe and open systems

Explanation An I/O error occurred.

On open systems, the first 2 bytes of the Additions 2 field (in binary format) contain the extent number. The third and fourth bytes contain the container type ("AS" for ASSO, or "DS" for DATA or "WO" for WORK).

Action On open systems, check whether any disk devices have gone offline or check the error log for hardware errors.

Response 101

Origin Mainframe and open systems

Explanation An error has occurred using one of the client-based Adabas add-on products such as Adabas System Coordinator or Adabas Fastpath.

Mainframe Systems

On mainframe systems, one of the following subcodes may also be included with this response code:

- Subcodes of 20 or less are produced by Adabas Fastpath when an error occurs during the processing of an Adabas command..
- Subcodes of 21 or greater are produced by Adabas System Coordinator.

Refer to the hexadecimal subcode that appears in the command's Adabas control block, Additions 2 field, low-order (rightmost) two bytes. The subcodes are described in the table below:

Subcode	Meaning
2	L3/L9 direct optimization internal error. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "2".
6	L3 direction change error. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "6".
7	Direction change integrity check error.This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "7".
8	Default response to internal service commands in the database. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "8".
9	Optional response for Read Ahead Update warning messages. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "9".
10	Error following a PLEX move. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "A".

Subcode	Meaning
21	Session cleanup error. This is an internal error in Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative.
23	Session create error. This is probably due to insufficient memory. <i>Action:</i> Increase the job region size. If the problem persists, contact your Software AG technical support representative.
25	CAB: Allocation failed. Insufficient memory was available for CAB. This is an Adabas System Coordinator error. <i>Action:</i> Increase the job region size. Note: This subcode is not subject to COR Debug.
26	Incorrect use of asynchronous Adabas calls. <i>Action:</i> Contact your Software AG technical support representative. Note: This subcode is not subject to COR Debug.
28	Internal thread concurrency error. <i>Action:</i> Contact your Software AG technical support representative. Note: This subcode is not subject to COR Debug.
29	Internal command error: Value buffer is not present. <i>Action:</i> Contact your Software AG technical support representative.
30	Internal command error: Illegal function. <i>Action:</i> Contact your Software AG technical support representative.
31	Error allocating the internal job-structure. <i>Action:</i> Increase the job region size. If the problem persists, contact your Software AG technical support representative.
32	Internal command error: Insufficient record buffer. <i>Action:</i> Contact your Software AG technical support representative.
33	Internal command error: Record buffer is not present. <i>Action:</i> Contact your Software AG technical support representative.
34	Internal command error: Incorrect value buffer format. <i>Action:</i> Contact your Software AG technical support representative.
35	Memory allocation failure. Insufficient memory was available for an internal area needed for NIM support. This is an Adabas System Coordinator error. <i>Action:</i> Increase the job region size.

Subcode	Meaning
	Note: This subcode is not subject to COR Debug.
38	Internal command error: Unsupported memory function <i>Action:</i> Contact your Software AG technical support representative.
43	Initialization Error. An error occurred during job initialization in Adabas System Coordinator. <i>Action:</i> Ensure that correct runtime controls were defined for the job. If problem persists, contact Software AG Support.
46	CAS: No group header record. This error appears if Adabas System Coordinator fails to find a header record for the required System Coordinator group. <i>Action:</i> First check that you have a valid CORCFG module pointing to the correct database and file number for your configuration file. Ensure that the load library containing CORCFG is included in the load library concatenation of the job. If CORCFG is present and correct, logon to SYSCOR and verify that you have valid Daemon Group parameters for the job you are running. If all parameters are correct, contact your Software AG technical support representative for assistance.
49	Internal eventing error: Illegal request. <i>Action:</i> Contact your Software AG technical support representative.
50	Internal error processing add-on products. <i>Action:</i> Contact your Software AG technical support representative.
53	This job is not defined to use the daemon. <i>Action:</i> Review and correct the installation for this job.
54	Internal services error. <i>Action:</i> Contact your Software AG technical support representative.
55	Latency processing error. This is an internal error in Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative. Note: This subcode is not subject to COR Debug.
56	Latency processing error. This is an internal error in Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative. Note: This subcode is not subject to COR Debug.

Subcode	Meaning
59	<p>CORSnn: Critical products. One or more products have been defined as "Critical" in the Corrdinator configuration file, and one of the following errors was detected:</p> <ul style="list-style-type: none"> ■ The Adabas System Coordinator Kernel module (CORKRN) was not found. ■ Adabas System Coordinator initialization has failed. There will be a Coordinator message indicating the cause of the initialization failure. <p><i>Action:</i> Determine the cause of the concurrent command and modify the application to remove it.</p> <p>Note: This subcode is not subject to COR Debug.</p>
60	<p>CORKRN: Critical Products. One or more products have been defined as "Critical" in the Adabas System Coordinator configuration file, and the product has indicated a critical error during initialization.</p> <p><i>Action:</i> Determine the cause of the concurrent command and modify the application to remove it.</p>
62	<p>CORS02/CORS12: Subsystem storage protect facility not activated. Com-plete has been customised to operate with mixed thread keys, but the IBM subsystem Storage Protection override facility is not enabled. Adabas System Coordinator requires this facility to support mixed thread keys in Com-plete.</p> <p><i>Action:</i> Either activate the Subsystem Storage Protection override facility in this system OR change the Com-plete thread groups to operate in Com-plete's key only (see the description of the THREAD-GROUP parameter in the Com-plete documentation).</p> <p>Note: This subcode is not subject to COR Debug.</p>
64	<p>Net-Work Clustering: Node not member of Group. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
65	<p>Net-Work Clustering: Message segment protocol error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
66	<p>Net-Work Clustering: Message sequence error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
67	<p>z/OS only: Invalid SVC is being used for the execution of an Adabas call.</p> <p><i>Action:</i> Review and correct the installation. If the problem persists, contact your Software AG technical support representative.</p>

Subcode	Meaning
69	<p>Insufficient memory to initialize runtime controls. There is insufficient memory for COR to initialize. This is an Adabas System Coordinator error.</p> <p><i>Action:</i> Increase the memory available to the job.</p>
81	<p>Internal UB Getmain error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
82	<p>Invalid session pointer. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
83	<p>Internal session UB not found. This is an internal error.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
84	<p>Internal error in Adabas buffer analysis. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
85	<p>Internal thread getmain error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Increase the job region size and rerun the job. If the problem persists, contact your Software AG technical support representative.</p>
86	<p>Invalid command block pointer. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
87	<p>Client versioning has not been installed correctly.</p> <p><i>Action:</i> Check the job for any console messages and ensure that client versioning is installed correctly.</p>
88	<p>Adabas CICS link module and TRUE have not been installed correctly.</p> <p><i>Action:</i> Ensure that the Adabas CICS link module and TRUE are installed correctly. This must be done to enable Adabas System Coordinator to operate in a CICS job.</p> <p>Note: This subcode is not subject to COR Debug.</p>
89	<p>The NIM subtask is in the process of being detached.</p> <p><i>Action:</i> None, this subcode simply indicates that a NIM subtask was still issuing Adabas commands when it was terminated by the main NIM task.</p> <p>Note: This subcode is not subject to COR Debug.</p>
90	<p>Internal handshake token validation error.</p>

Subcode	Meaning
91	<p>Latency processing error (no facility). This is an internal error in Adabas System Coordinator. Action: Contact your Software AG technical support representative.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
92	<p>Asynchronous call with no CAB. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
93	<p>Latency processing error (memory). This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Increase the job region size. If the problem persists, contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
94	<p>Latency processing lock error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
95	<p>Daemon latency processing error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Ensure that the System Coordinator daemon is available. If the problem persists, contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
96	<p>Latency processing error (facility deleted). This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
97	<p>Latency processing lock error when using daemon latency.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>
102	<p>Latency processing unlock error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p>Note: This subcode is not subject to COR Debug.</p>

Open Systems

On open systems, one of the following Adabas System Coordinator subcodes may also be included with this response code:

Subcode	Meaning
1 (0x0001)	The standard Adabas or Entire Net-Work ADALNKX library could not be loaded. <i>Action:</i> Check that the ADALNKX parameter in the Initialisation File (cor.cfg) is set correctly and that the library exists.
2 (0x0002)	The standard Adabas or Entire Net-Work ADALNKX library could not be loaded. <i>Action:</i> Contact your Software AG technical support representative.
3 (0x0003)	The standard Adabas or Entire Net-Work ADALNKX library does not export all expected functions. <i>Action:</i> Check that the ADALNKX parameter in the Initialisation File refers to an ADALNKX library and not an ADALNK or ADALNK32 library.
4 (0x0004)	Adabas did not return the database architecture information in the ISN lower limit field when an OP command was issued to the Configuration File. <i>Action:</i> Contact your Software AG technical support representative.
5 (0x0005)	The path to the Initialisation File (cor.cfg) could not be determined. <i>Action:</i> Check the HKLM\SOFTWARE\Software AG\Adabas System Coordinator registry key and ensure the Path value is set correctly (Windows). Check that the \$CORDIR and \$CORVERS environment variables are set correctly (Unix).
6 (0x0006)	The ADALNKX parameter could not be read from the Initialization File (cor.cfg). <i>Action:</i> Check that the Initialization File exists and that the ADALNKX parameter is set correctly.
7 (0x0007)	The LFILE parameter could not be read from the Initialization File. <i>Action:</i> Check that the Initialization File (cor.cfg) exists and that the LFILE parameter is set correctly.

Subcode	Meaning
8 (0x0008)	An incompatible version of an Adabas add-on product is installed. <i>Action:</i> Contact your Software AG technical support representative.
9 (0x0009)	An incompatible version of an Adabas add-on product is installed. <i>Action:</i> Contact your Software AG technical support representative.
10 (0x000A)	The library for an Adabas add-on product could not be loaded. <i>Action:</i> Check that the Adabas add-on product is installed correctly.
11 (0x000B)	The library for an Adabas add-on product could not be unloaded. <i>Action:</i> Contact your Software AG technical support representative.
12 (0x000C)	The address or length of the format, record, search, value or ISN buffer appears to be invalid. <i>Action:</i> Check the buffer addresses passed to the adabas() function and the lengths specified for the buffers in the Adabas control block.
13 (0x000D)	The CORADC load module could not be fetched (Mainframe). <i>Action:</i> Check that \$STEPLIB environment variable is correct and that the CORADC load module exists in the specified data set.
14 (0x000E)	Port range exhausted (there are not enough allocated to this computer). <i>Action:</i> Configure a larger port range for the Adabas System Coordinator Computer using System Management Hub.
15 (0x000F)	Port conflict (the allocated port is in use by another application). <i>Action:</i> Assign a different port to the Adabas System Coordinator daemon or change the port range for the Adabas System Coordinator computer using System Management Hub.
16 (0x0010)	Computer name could not be generated. <i>Action:</i> The Adabas System Coordinator Launch Control could not generate a unique computer name for the machine. Create an Adabas System Coordinator computer for this machine manually using System Management Hub.

Subcode	Meaning
17 (0x0011)	<p>The FDT of the Configuration File is not compatible with Adabas System Coordinator.</p> <p><i>Action:</i> Check that the database and file numbers are correct.</p>
18 (0x0012)	<p>The version of Adabas is not compatible with Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
19 (0x0013)	<p>The SAGABS library could not be loaded.</p> <p><i>Action:</i> Check that the SAGABS library is installed.</p>
20 (0x0014)	<p>The SAGABS library could not be unloaded.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
21 (0x0015)	<p>The SAGABS library is not compatible with Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
22 (0x0016)	<p>Port conflict (the allocated port is in use by another Adabas System Coordinator Group).</p> <p><i>Action:</i> Assign a different Group Services port to the Adabas System Coordinator Computer using System Management Hub.</p>
23 (0x0017)	<p>Unable to spawn process (the command line parameters specified for the process are invalid).</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
24 (0x0018)	<p>Length of compressed record buffer length exceeds limit.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
25 (0x0019)	<p>Length of compressed record buffer could not be determined.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
26 (0x001A)	<p>Product not installed or not configured correctly.</p> <p><i>Action:</i> Check that the Adabas add-on product is installed correctly.</p>

Subcode	Meaning
27 (0x001B)	Configuration file version does not match the running version. <i>Action:</i> Contact your Software AG technical support representative.
28 (0x001C)	Configuration file layout is not as expected for a configuration file. <i>Action:</i> Contact your Software AG technical support representative.
29 (0x001D)	The installed Adabas version does not correctly process LF 'S' commands (Adabas 6.1.9 or earlier). <i>Action:</i> Contact your Software AG technical support representative.
30 (0x001E)	The installed Adabas version does not support LF 'I' commands (unzapped Adabas 8.2.2 or earlier). <i>Action:</i> Contact your Software AG technical support representative.
31 (0x001F)	Migration of the Configuration File was unsuccessful. <i>Action:</i> Check the output of the migration process for errors. If the reason for an unsuccessful migration cannot be determined, contact your Software AG technical support representative.
52 (0x0034)	Exception reading/writing pointer. <i>Action:</i> Contact your Software AG technical support representative.
0000A001-FFFFA001	A TCP/IP error occurred. <i>Action:</i> The left-hand side of the subcode contains the operating system error code.
0000A002-FFFFA002	A DNS error occurred. <i>Action:</i> The left-hand side of the subcode contains the operating system error code.

Response 102

Origin Mainframe systems only
Explanation Space calculation error.
Action Retry the open operation.

Response 106

Origin Mainframe systems only
Explanation The prefetch table record buffer specified in the UDB is too small.

Response 107

Origin Mainframe systems only
Explanation Either a GETMAIN error occurred or there was insufficient space when performing prefetch. Prefetch is switched off.

Response 109

Origin Mainframe systems only
Explanation The specified command ID is already active on another database for this user.

Response 110

Origin Mainframe systems only
Explanation The command ID pool is full.
Action Increase the size of either or both the ADARUN NQCID or NU parameters.

Response 113

Origin Mainframe and open systems
Explanation The specified ISN was invalid for one of the following reasons:

- An HI command was issued with ISN less than MINISN or with an ISN equal to zero (0).
- An N2 command was issued with ISN equal to 0 or larger than the MAXISN in effect for the file.
- An N2 command was issued and the specified ISN was assigned to another record in the file.
- An A1, L1/L4, or S1/S2/S4 (with FB) command was issued for a nonexistent ISN, or an E1 command for a nonexistent ISN other than zero.
- An L3/L6 command found an ISN in the index which did not exist in the address converter.

- An N1/N2 command tried to access a file protected by security-by-value, but the command user is not authorized to access the file.
- A read or update command tried to access a multicient file's record using either a blank or incorrect-length owner ID, or an owner ID that does not apply to the record.
- An RI command was issued for a record that has been updated earlier in the same transaction. The record cannot be released from hold status prior to transaction end. On mainframe systems, subcode 5 is issued for this reason.
- Subcode 19 is given when a base file record is not found in the address converter (AC). At the end of a LOB update in the LOBfile, the associated base file record no longer existed.
- Subcode 249 is given only when Adabas Vista is in use. Refer to the Adabas Vista documentation for more information.

Open Systems

On open systems, the following subcodes may occur:

Subcode	Meaning
249 (0x00F9)	An invalid ISN was detected by Adabas Vista (open systems). The ISN specified for an E1, HI or L1 command is not consistent with the definitions for the partitioned file. <i>Action:</i> Review the program logic

Action Correct the ISN problem and try again.

Response 114

Origin Mainframe and open systems

Explanation A refresh file function using the E1 command was issued (E1 with ISN=0), and one of the following situations has occurred.

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

One of the following subcodes may be present:

Subcode	Description
1	A file refresh is not permitted for the file because either <ul style="list-style-type: none"> ■ the file parameter setting is PGMREFRESH=NO (can be checked with ADAREP or via Adabas Online Services (AOS) Display File) ■ or the command ID field (ACBCID or ACBXCID) is not all blanks.

Subcode	Description
2	The user has not completed transactions to the file. Updates have been performed or records are still in hold, but the user has not issued an ET or BT command to commit or back out the updates.
3	Other users are accessing or updating the file. This is determined by the user access or update counts available internally to Adabas.
4	The file is a multiclient file and the user is not a superuser.

Open Systems

One of the following situations has occurred:

- PGM_REFRESH is not specified for the file.
- The user session is not at ET status.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

If you forgot to specify the ISN for the E1 command, the CID setting is incorrect, the command was not issued at ET status or the user is no superuser: correct your program accordingly.

If other users are accessing or updating the file STOP these users.

If PGMREFRESH=YES was not specified for the file in question, specify PGMREFRESH=YES for the file with ADADBS or Adabas Online Services (AOS) or load the file with the appropriate ADALOD parameter.

Open Systems

If you forgot to specify the ISN for the E1 command, or the command was not issued at ET status, correct your program. If PGM_REFRESH was not specified for the file in question, specify PGM_REFRESH for the file with ADADBM.

Response 123

Origin

Mainframe systems only

Explanation

An error was reported by the Adabas cluster messaging service on the sender's side. The message was not sent. One of the following subcodes may be present:

Subcode	Meaning
4	No valid destination(s)
8	Too many destinations
12	Invalid message type
16	Invalid environment
20	Send buffer length exceeded
24	Receive buffer length exceeded
28	No replies or acknowledgment(s) before the message timed out. For more information about the timeout value, refer to descriptions of the ADARUN MXMSG parameter.
32	Unable to allocate AXMCB
36	Timed out on originating system
40	Timed out on destination system
44	Canceled on destination system
48	Receive error on destination system
52	Unable to allocate buffer
80	Messaging is inactive
96	Terminate member unsuccessful
128	Other Trans- port service error

Action If you are unable to resolve the problem, contact your Software AG technical support representative.

Response 124

Origin Mainframe systems only

Explanation An error was reported by the Adabas cluster messaging service on the receiver's side. The message was sent. One of the subcodes described for response code 123 (ADARSP123) may be present.

Action If you are unable to resolve the problem, contact your Software AG technical support representative.

Response 125

Origin Mainframe systems only

Explanation An internal error occurred when one cluster nucleus attempted to issue an internucleus command to one or more of the other cluster nuclei. This condition usually leads to abnormal termination.

Action Contact your Software AG technical support representative.

Response 126

Origin Mainframe systems only

Explanation A messaging error occurred during internucleus communication:

- The nucleus did not respond within the allotted time (see the ADARUN MXMSG parameter); or
- One or more problems occurred in what could be a broadcast; that is, a communication with multiple targets. In this case, each individual ACB contains either response code 0 (ADARSP000) or 123 (ADARSP123) or 124 (ADARSP124).

Action If you are unable to resolve the problem, contact your Software AG technical support representative.

Response 129

Origin Mainframe systems only

Explanation In an Adabas cluster environment, the user attempted to perform an Adabas function that is not yet supported by Adabas cluster nuclei.

Response 130

Origin Mainframe systems only

Explanation An error identified by one of the following subcodes occurred in an Adabas cluster environment:

Subcode	Description
1	A user table entry (UTE/PLXUSER) was not found in the MPM 8 call. This may indicate that a command was directed to an Adabas Cluster Services or Adabas Parallel Services nucleus ID (NUCID), not the DBID.
2	A user table entry (UTE/PLXUSER) was not found in the MPM 12 call.
9	The associated PLXUSER(UTE) was unsuitable at command initiation. One possibility is that the UQE of the user was deleted between the time the user's command was routed to one nucleus in the cluster and the time that nucleus selected the command for processing. Another possibility is that the PLXUSER and UQE UID string did not match because the PLXUSER may have been released and possibly reassigned to another user.
10	The associated PLXUSER(UTE) was unsuitable at command completion. The PLXUSER and UQE UID string did not match because the PLXUSER may have been released and possibly reassigned to another user.
11	No Work data set entry in active PPT block (bad PPT block).
12	Invalid internal NUCID (internal error).
13	Invalid external NUCID (bad PPT block, internal error).
14	Work data set already open for same internal NUCID, other external NUCID.
15	Work data set already open for same external NUCID, other internal NUCID.

Subcode	Description
16	Different Work data set already open for same peer nucleus.
17	Work data set of peer nucleus could not be opened.
18	I/O error when trying to read Work data set of peer nucleus.
19	Unexpected (invalid) data in Work data set of peer nucleus.
20	Mismatching DBID in Work data set.
21	Mismatching Adabas version indicator in Work data set.
22	Work data set written by non-cluster nucleus.
23	Partially written block in Work data set protection data extension area.

Action For subcode 1, correct the application program attempting to issue commands using the NUCID. If that is not the case, or for other subcodes, contact your Software AG technical support representative for assistance.

Response 131

Origin

Mainframe systems only

Explanation

In most cases this response code will be given to the user in the URBRRSP field of the URBR block with the subcode in the URBRSUB field. The subcode appears either in the low-order (rightmost) two bytes of the additions 2 field or in the URBRSUB field. It indicates the specific cause and action for this response code. The following are the subcodes and their meanings:

Subcode	Meaning
1	The combination of URBD plus payload data does not fit in the output buffer. <i>Action:</i> Change the subscription definition to make the record shorter.
2	The subscription user exit set a value in URBREERRC. <i>Action:</i> Check the URBREERRC field and correct the error if appropriate.
3	There is insufficient space in the nucleus replication pool. In other words, the value specified by LRPL has been exceeded. <i>Action:</i> Increase the LRPL size of the nucleus and try again.
4	There is insufficient space in the Event Replicator Server replication pool. In other words, the value specified by LRPL has been exceeded. <i>Action:</i> Increase the size of the LRPL parameter and try again.
5	The subscription user exit modified data length (URBDLEND) to an invalid value. <i>Action:</i> Check the subscription user exit.

Subcode	Meaning
6	<p>The response destination (URBIRNAM) specified in a client request is undefined or not usable for sending the response.</p> <p><i>Action:</i> Correct the status request to specify the name of an existing destination definition.</p>
7	<p>Both the subscription (URBISNAM) and the destination (URBIDNAM) to be specified in a status request are missing. At least one of them must be specified.</p> <p><i>Action:</i> Correct the status request.</p>
8	<p>The subscription (URBISNAM) specified in a status request is undefined.</p> <p><i>Action:</i> Correct the status request.</p>
9	<p>The initial state name specified was not found.</p> <p><i>Action:</i> Correct the initial-state request.</p>
10	<p>The destination for response in URBI following URBI 1 is not equal to those of URBI 1.</p> <p><i>Action:</i> Correct the initial-state request.</p>
11	<p>The initial state name in URBI following URBI 1 is not equal to that of URBI 1.</p> <p><i>Action:</i> Correct the initial-state request.</p>
12	<p>The combination of DBID and file specified in the initial-state request is not found in the initial-state definition.</p> <p><i>Action:</i> Correct the initial-state request.</p>
14	<p>Not all combinations of DBID and file are specified in the initial-state request. A URBI must be sent for each DBID/file specified in the initial-state definition.</p> <p><i>Action:</i> Correct the initial-state request.</p>
15	<p>Field URBILEND is invalid.</p> <p><i>Action:</i> Correct the initial-state request.</p>
16	<p>The specified ISNLIST is invalid.</p> <p><i>Action:</i> Correct the initial-state request.</p>
17	<p>The initial-state process has been stopped by an operator request.</p> <p><i>Action:</i> No action is required.</p>
18	<p>Different request tokens have been specified in different URBI elements in the same message.</p> <p><i>Action:</i> Correct the initial-state request.</p>

Subcode	Meaning
19	<p>Selection data is not allowed for an initial-state definition for all records or for destination open/close client requests.</p> <p><i>Action:</i> Correct the initial-state or destination open/close client request.</p>
20	<p>Invalid input data for decompression was found during the subscription phase.</p> <p><i>Action:</i> Check the index of the replicated file.</p>
22	<p>The file/DBID supplied for the initial-state process is deactivated for replication.</p> <p><i>Action:</i> Check the cause of deactivation and repeat the request after reactivation.</p>
23	<p>Invalid UES parameter in URBI . URBIARC, URBIACOD, and URBIWCOD must contain invalid values and must not be all blanks.</p> <p><i>Action:</i> Verify that the URBIARC, URBIACOD, and URBIWCOD elements are not all blanks.</p>
24	<p>Invalid UES parameter in URBI.</p> <p>URBIARC, URBIACOD and URBIWCOD must be zero for input requests where encoding and architecture is not evaluated -- that is, for status requests, destination open/close requests, "initial state all records" or "initial state ISN list" requests.</p> <p><i>Action:</i> The URBIARC, URBIACOD, and URBIWCOD elements must be zeros for "initial state all records" requests, "initial state ISN list" requests, status requests, or destination open/close requests. Verify that this is the case.</p>
25	<p>The unused URBIRES1 and URBIRES2 fields must contain binary zeros for all requests.</p> <p><i>Action:</i> Verify that these fields contain binary zeros.</p>
26	<p>The destination (URBIDNAM) specified in a client request is either undefined or not usable for sending the response.</p> <p><i>Action:</i> Correct the client request.</p>
27	<p>No active destinations for status request.</p> <p><i>Action:</i> No action is required.</p>
28	<p>An initial-state request was issued to an Event Replicator Server address space that was terminating as a result of an ADAEND or HALT command. An initial-state request may only be issued when the Event Replicator Server is active.</p> <p><i>Action:</i> Reissue the initial-state request when the Event Replicator Server has been restarted.</p>

Subcode	Meaning
30	<p>Unknown response destination name in URBIRNAM for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
31	<p>Unknown destination name in URBIDNAM for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
32	<p>Unknown or omitted subscription name in URBISNAM for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
33	<p>Destination in URBIDNAM is not related to subscription in URBISNAM for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
34	<p>Subscription in URBISNAM has no resend buffer defined for a prior-transaction request.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
35	<p>Transaction in URBITSNR for subscription in URBISNAM was not found in the resend buffer. The transaction may have been overwritten in the circular resend buffer.</p> <p><i>Action:</i> Check the source of the transaction number.</p>
36	<p>The subscription in URBISNAM is not active.</p> <p><i>Action:</i> No action is required.</p>
37	<p>An invalid transaction was found in the resend buffer. This is an internal error.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>
38	<p>There are no active destinations for a prior-transaction request.</p> <p><i>Action:</i> No action is required.</p>
39	<p>URBILEND must be zero for prior-transaction requests.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
40	<p>URBIDBID and URBIFNR may not be specified for this type of client request.</p> <p><i>Action:</i> Correct the client request.</p>
41	<p>URBIINAM may not be specified for prior-transaction requests.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>

Subcode	Meaning
42	UES parameters URBIARC, URBIACOD and URBIWCOD may not be specified for prior-transaction requests. <i>Action:</i> Correct the prior-transaction request.
43	Reserved fields URBIRES1 and URBIRES2 must be zero for prior-transaction requests. <i>Action:</i> Correct the prior-transaction request.
44	Number of active concurrent initial-state requests exceeded IMAXREQ. <i>Action:</i> Increase the IMAXREQ setting or reduce the number of active concurrent initial-state requests.
45	Input request URBH eyecatcher is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
46	Input request URBHLEN is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
47	Input request URBHBORD is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
48	Input request URBHVERS is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
49	Input request message truncated. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
50	Input request URBHLENT is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
51	Input request URBILENH is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .

Subcode	Meaning
52	<p>Input request URBILEND is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
53	<p>Input request URBILEN is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
54	<p>Input request reserved area is not zero.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
55	<p>Input request more than one status received.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
56	<p>Input request invalid URBI request received.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
57	<p>Input request different interleaved requests received.</p> <p><i>Action:</i> Verify that you are submitting only one kind of request to the Event Replicator Server. Only one type can be submitted at a time (for example, you cannot request initial-state processing and transaction status information requests in the same message).</p> <p>Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
58	<p>Invalid destination for response.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
59	<p>A replay request was issued for a database not defined to the Event Replicator Server.</p> <p><i>Action:</i> Correct the DBID in the replay request or define the database to the Event Replicator Server.</p>

Subcode	Meaning
60	Invalid replay token. The replay token is not defined or is outdated. <i>Action:</i> Specify a valid replay token.
61	Invalid request sent to Event Replicator Server. RBL is insufficient, no FB provided on Init handshake or other such errors. <i>Action:</i> Notify your Software AG technical support representative.
62	After an Adabas failure and session autorestart, replication data was recovered for which a matching FDT was no longer available. The FDT had been changed or deleted by a utility operation. Adabas suppressed the record images of the replicated records, because without a matching FDT, the Event Replicator Server could not process them. <i>Action:</i> Use application-specific means to bring the replicated data in sync again, if necessary.
63	The file specified in a C5 command with R-option is not replicated. <i>Action:</i> Specify the file number of a replicated file.
64	The filter defines a comparison between two field types for which a comparison is invalid. <i>Action:</i> Correct the filter definition.
65	The filter refers to a field that is not defined in the internal format buffer. <i>Action:</i> Correct the filter definition or define the field in the database.
66	The filter defines a comparison against a field that is not selectable as it has no type (for example, a superdescriptor). <i>Action:</i> Correct the filter definition.
67	The filter uses values in an FLIST specification that are invalid or out of range. <i>Action:</i> Correct the filter definition.
69	Replay for same DBID/FNR already running.
71	Date/time format or value incorrect for replay. <i>Action:</i> Check the syntax of the specified date and time values. Do not specify future date and time values.
72	Incorrect replay parameters. <i>Action:</i> Check and correct the specified replay parameters.
73	A subscription involved in the replay was inactive at the beginning of replay processing or was deactivated while the replay was running. <i>Action:</i> Reactivate the deactivated subscription and rerun the replay process for the subscription.

Subcode	Meaning
74	<p>A destination involved in the replay was inactive at the beginning of replay processing or was deactivated while the replay was running.</p> <p><i>Action:</i> Reactivate the deactivated destination and rerun the replay process for the destination.</p>
75	<p>A replay destination that was defined without SLOG was closed at the beginning of replay processing or while the replay was running.</p> <p><i>Action:</i> Reopen the closed destination and rerun the replay process for the destination.</p>
76	<p>ADARPL terminated abnormally.</p> <p><i>Action:</i> Investigate the cause of the error, correct it, and run a new replay job.</p>
77	<p>Invalid replay status transition. Events that change the status of a replay process occurred in an unexpected order.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>
78	<p>New transactions from Adabas could not be kept on hold during a replay in synchronized mode.</p> <p><i>Action:</i> Run a new replay process involving the same subscriptions and destinations as the previous replay process to recover the replication data that Adabas produced while the first replay was running.</p>
79	<p>A replay process was canceled by a user (RPLCLEANUP operator command).</p> <p><i>Action:</i> If appropriate, run another replay job with corrected parameters.</p>
80	<p>A timeout occurred while the Event Replicator Server was waiting for the end of a synchronization process after reactivating replication for a file in Adabas. The synchronization process ends when all transactions have finished that had updated the file before it was reactivated.</p> <p><i>Action:</i> Wait until the Event Replicator Server reports the activation of the file (ADAF2L message). Then run a new replay job.</p>
81	<p>A utility other than ADARPL specified a replay token when connecting to the Event Replicator Server.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>
82	<p>The Event Replicator Server is not connected to Adabas at the start of a replay process with the TOKEN parameter.</p> <p><i>Action:</i> Start Adabas and let it connect to the Event Replicator Server. When running a replay with the TOKEN parameter, Adabas must be active.</p>
83	<p>Neither a subscription nor a destination was specified in a replay request.</p> <p><i>Action:</i> Specify at least one subscription or destination.</p>

Subcode	Meaning
84	<p>A replay in replay-only mode was requested, but replication data from Adabas would flow through an active subscription-destination pair involved in the replay. For a replay in replay-only mode, some subscriptions and destinations must be inactive such that no data from Adabas can flow through the same subscription-destination pairs as the replay data from ADARPL.</p> <p><i>Action:</i> Change the replay parameters or the activation status of the subscriptions or destinations involved in the replay.</p>
85	<p>A file involved in the replay was inactive at the beginning of the replay or deactivated while the replay was running.</p> <p><i>Action:</i> Reactivate the deactivated file and rerun the replay process for the subscriptions involved in the replay that get data from the file.</p>
86	<p>Invalid format buffer was specified for destination-type Adabas update commands.</p> <p><i>Action:</i> Correct the format buffer.</p>
87	<p>An unexpected message sequence number was encountered.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
88	<p>An unrecognized eye-catcher was encountered in control block following the URBH.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
89	<p>The same subscription name was specified more than once for an Adabas automated replay (defined using the Adabas Event Replicator Subsystem).</p> <p><i>Action:</i> Verify that a subscription is specified only once in an automated replay, and try again.</p>
90	<p>The same destination name was specified more than once for an Adabas automated replay (defined using the Adabas Event Replicator Subsystem).</p> <p><i>Action:</i> Verify that a destination is specified only once in an automated replay, and try again.</p>
91	<p>The replay start date and time were not supplied for an automated replay (defined using the Adabas Event Replicator Subsystem) or for multiple destination open/close client requests.</p> <p><i>Action:</i> Verify that a destination is specified only once in an automated replay or in multiple destination open/close client requests and try again.</p>
92	<p>The timeout parameter specified for an automated replay was too high.</p> <p><i>Action:</i> Reduce the timeout parameter value and try again.</p>

Subcode	Meaning
93	<p>PLOG information was not recorded in the Event Replicator Server system file.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
94	<p>The AI/BI format buffer was used also for the key. An attempt was made to decompress a key value, but the related format buffer is for data storage and not for a key.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
95	<p>An attempt to set user/Event Replicator Server encoding 01-RPEQU * failed. This might occur if you are using enhanced filtering logic and UES SACODE/SWCODE/SARC values are set for a subscription.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
96	<p>The Adabas nucleus that was the target of an initial-state request returned response code 148 (ADARSP148), indicating it is not available.</p> <p><i>Action:</i> Start the targeted Adabas nucleus and retry the initial-state request.</p>
99	<p>The subscription name (URBISNAM) specified in the destination open/close client request contains a value other than spaces.</p> <p><i>Action:</i> Correct the destination open/close client request by setting this field to spaces.</p>
100	<p>The transaction sequence number (URBITSNR) specified in a destination open/close client request contains a value other than binary zeroes.</p> <p><i>Action:</i> Correct the destination open/close client request by setting this field to binary zeroes.</p>
101	<p>The destination open/close request failed on some tasks.</p> <p><i>Action:</i> Investigate the cause of the error.</p>
102	<p>The destination open/close request failed.</p> <p><i>Action:</i> Investigate the cause of the error.</p>
103	<p>The destination open/close request was not performed because the destination's status was already in the state being requested. In other words, the destination was already opened or closed.</p> <p><i>Action:</i> No action is required.</p>
104	<p>Begin byte in field filter is longer than the field length.</p> <p><i>Action:</i> Adjust the specifications for the beginning byte or length and try again.</p>

Subcode	Meaning
105	Begin byte plus the portion length in the field filter is longer than the field length. <i>Action:</i> Adjust the specifications for the beginning byte or the portion length and try again.
106	Begin byte or length not supported for field with format U, P, F, G, or W. <i>Action:</i> Specifying a beginning byte or length is only supported for alphanumeric and binary fields. Change the field on which you are working or abandon this attempt.
107	Length value invalid for field. <i>Action:</i> Adjust the length specification and try again.
108	Input request URBI eyecatcher is invalid. <i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .
109	An Adabas security (ADASCR) function has been invalidly replicated to a subscription file defined with SFSECURITYFILE=NO. <i>Action:</i> Ensure the subscription file definition used for the security file is defined with SFSECURITYFILE=YES.
110	An invalid Adabas security (ADASCR) pseudo transaction has been replicated to the Event Replicator Server. <i>Action:</i> Contact your Software AG technical support representative for assistance.
111	A replicated record (e.g., delete, insert, refresh, or update) has been invalidly replicated to a subscription file defined with SFSECURITYFILE=YES. <i>Action:</i> Ensure that the subscription file definitions for a file, other than a security file, is defined with SFSECURITYFILE=NO.

Action Perform the action provided for the appropriate subcode in the subcode table.

Response 132

Origin Mainframe and open system

Explanation The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

This response code indicates that an error occurred while Adabas was reading or updating a *LOB file*. The subcode indicates the kind of error.

If the subcode is less than 256, it is the same as the original response code that occurred during LOB file processing. The most likely subcodes are listed in the table below. For subcodes not listed, see the description of the Adabas response code with the same value.

If the subcode is greater than 256, it signals an error condition unique to the processing of LOB files. These subcodes are listed in the table below.

Subcode	Description
8	A LOB file operation was aborted due to a pending backout of the user's command or transaction. One reason for this backout may be that the user's transaction occupied too much space on the protection area on the Work data set (see response code 9 (ADARSP009), subcode 15).
17	The LOB file is not loaded.
48	The LOB file is locked for exclusive read or update by another user.
65	An internal error in the work pool space calculation occurred for LOB file processing.
113	A LOB file segment record was not found in the Address Converter element referred to by the LOB file index. Either the LOB file is physically inconsistent or an illegal concurrent LOB file update occurred during the LOB file read operation.
145	An attempt failed to put a LOB file segment record on hold for a user, because it was already held by another user. This subcode indicates illegal update contention for the same large object field value. The base file-LOB file pair is possibly inconsistent.
165	The LOB file descriptor is not found in the index; The LOB file index is bad.
172	An ISN in the LOB file index is bad. The LOB file may be physically inconsistent.
175	The descriptor value in a LOB file segment record differs from the descriptor value in the LOB file index. Either the LOB file is physically inconsistent or an illegal concurrent LOB file update occurred during the LOB file read operation.
177	A LOB file segment record was not found in the Data Storage block referred to by the Address Converter. Either the LOB file is physically inconsistent or an illegal concurrent LOB file update occurred during the LOB read operation.
257	An error in the base file-LOB file linkage exists; a file with LB fields is not really the <i>base file</i> of the <i>LOB group</i> .
258	An error in the base file-LOB file linkage exists; the file linked to the base file of a LOB group is not really a LOB file.
259	An error in the base file-LOB file linkage exists; the LOB file linked to a base file of a LOB group refers back to a different base file (or none at all).
260	An error in the base file-LOB file linkage exists; either no LOB file was linked to a base file or the LOB file number is invalid.

Subcode	Description
261	The LOB file has been left in an inconsistent state by an aborted utility execution.
262	An LB field length element specification error occurred in the format buffer ('xxL,4,B' was expected).
263	An invalid LOB file segment descriptor was encountered. The set of LOB file segment records associated with one LB field value is inconsistent. Either the LOB file is bad or an illegal concurrent LOB file update occurred during the LOB file read operation.
264	An invalid LOB file segment record was encountered. The contents of a LOB file record are inconsistent. The LOB file is bad.
265	The length of an LB field value in the LOB file differs from the length stored in the associated base file record. Either the base file and the LOB file are out-of-sync or an illegal concurrent LOB file update occurred during the LOB file read operation.
266	A bad LB field value reference was encountered in a base file record. The base file is bad.
267	An LB field value referred to in a base file record is not present in the LOB file. Probably, the base file and the LOB file are out-of-sync.
268	Internal LOB update error. At the end of a LOB update in the LOB file, the LOB value reference or placeholder was not found in the associated base file record where it was expected. Possibly, the base file record was changed in parallel.
270	Internal LOB update error. At the end of a LOB update in the LOB file, the base record was not in exclusive hold status anymore.
297	A planned feature for large object (LB) fields (for example, character code conversion of LB field values) is not yet supported.
298	Too many (more than 32,767) LB field occurrences were specified in the format buffer.
299	An internal error occurred due to LOB file processing.

Open Systems

LOB data processing may fail because of concurrent updates. If a new attempt to process the LOB data also fails, this response code is returned. The subcode (field ACBXERRC in the ACBX) provides more information:

Subcode	Description
297	A planned feature for large object (LB) fields (for example, character code conversion of LB field values) is not yet supported.
300	The referential integrity and uniqueness checks done by subtransactions are currently not compatible with commands that modify LOB values.

Action The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Resolve the problem described in the subcode list in the explanation.

Open Systems

If one of the subcodes above occurs, you must change the program that is making the Adabas calls.

If the subcode (field ACBXERRC in the ACBX) is not one of the subcodes mentioned above, and if the response code 132 is reproducible even though the accessed LOB fields are not being updated, contact your Software AG technical support representative.

Response 133

Origin Mainframe systems only

Explanation An error was detected when an attempt was made to replicate a compressed record. The subcode identifies the kind of error.

Subcode	Description
1	The function is not permitted for this type of file. The file is a LOB-file.
2	The compressed input record length is invalid .
11	The record structure is invalid.
12	An invalid elementary empty field was encountered. The structure does not agree with the FDT definition.
13	An invalid multiple-field count was encountered.
14	An invalid periodic group count was encountered.
15	An invalid structure of an elementary field was encountered.
65	A space calculation error occurred.

Response 134

Origin Mainframe systems only

Explanation An error was detected when creating system fields. The subcode identifies the kind of error.

Subcode	Description
1	An invalid update parameter was encountered (logic error).
2	The field is not a system field.
4	The file does not support a setting of MUPEX=2 (number of MU occurrences greater than 191).

Response 144

Origin Mainframe and open systems

Explanation One of the following occurred:

- The ISN specified with an update (A1) command was not in hold status for the user and command option H was not specified.
- An ET or BT command specifying the M (multifetch) option specified an ISN in the ISN buffer that is not in hold status for the user. All currently held ISNs are released from hold status.

In this case on open systems, the first 2 bytes of the Additions 2 field (in binary format) contain the offset of that ISN in the ISN buffer.

Action Put the ISN in hold status before using the A1 command or the multifetch ET or BT commands.

If Adabas Transaction Manager is in use, verify that the setting for the Transaction Model parameter is appropriate for the program that was executing and is also appropriate for the runtime environment in use.

Response 145

Origin Mainframe and open system

Explanation The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

On mainframe systems, one of the following situations occurred:

- An N1/N2 command was issued, but no hold queue entry was available.
- A command was issued with the return option specified that attempted to hold an ISN already in the hold queue for another user. The command is not placed in wait status.

Use the subcode associated with this response code to further clarify why this response occurred.

Subcode	Meaning
0	N2 command for an existing ISN was issued.
1	Hold queue space problem detected. The user is the only active user and is running with the -R option.
2	The ISN was held by someone else. The read request is running with the -R option.
8	The hold status of a record could not be upgraded from shared to exclusive because another user was already waiting to do the same. The two users became deadlocked.
9	Two or more users became deadlocked while holding ISNs and attempting to put more ISNs in hold status.

Open Systems

On open systems, one of the following situations occurred:

- An attempt was made to insert a record using an N2 command with an ISN that is in hold status.
- An attempt was made to hold an ISN which was in hold status for another user and the R option is specified. In this case, the Additions 2 field contains the binary value 0;
- Hold queue overflow. In this case, the Additions 2 field contains a value not equal to 0.

Note: This hold queue overflow error can only occur with Adabas versions < 5.1.

Response 146

Origin

Mainframe and open systems

Explanation

The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

An invalid buffer length was detected by the Adabas interface routine. If the command uses a classic ACB, the buffer is larger than 32,767. If the command uses an ACBX, the buffer is greater than 2,147,483,647, or the send length in the ABD is greater than the buffer length. The subcode identifies the buffer type:

Subcode	Buffer Type
1	Format buffer
2	Record buffer
3	Search buffer
4	Value buffer
5	ISN buffer
6	User information buffer
7	Performance buffer
8	Multifetch buffer

Open Systems

An invalid buffer length was detected by the Adabas interface routine, in an MC call, or one of the following errors occurred for a multifetch command:

- the buffer header was invalid (both offsets are set)
- at least one ISN buffer offset was not divisible by 4
- the start offset was outside the multical call buffer range
- the record buffer was not large enough to contain all subcommand control blocks.

The value in the Additions 2 field identifies the buffer: the first 2 bytes contain the buffer number in binary format, the last two bytes contain the buffer name, as shown in the following table:

Bytes 1-2	Bytes 3-4
1	FB (format buffer)
2	RB (record buffer)
3	SB (search buffer)
4	VB (value buffer)
5	IB (ISN buffer)

Action Correct the buffer length and try again.

Response 147

Origin Mainframe and open systems

Explanation The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The ISN was invalid. The ISN transformation resulted in a negative ISN or an ISN greater than the maximum ISN permitted for the file.

Open Systems

A user buffer is not accessible by the Adabas interface routine.

Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Open Systems

Check whether the control block, format buffer, value buffer, record buffer and ISN buffer have valid addresses and lengths. Check whether the control block, ISN buffer and record buffer are write-protected.

Response 148

Origin

Mainframe and open systems

Explanation

The Adabas nucleus was either not active or not accessible (a call could not be sent to the Adabas nucleus when the command was issued). In an ACB, refer to the hexadecimal subcode that appears in the low-order (rightmost) two bytes of the Additions 2 field; in an ACBX, refer to the binary subcode that appears in the Error Subcode (ACBXERRC) field.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

The following are the decimal equivalents of the subcodes and their meanings:

Subcode	Occurrence Location	Description	Action
0	open systems	No active database server was found, either local or remote.	Start the nucleus and reissue the command.
1	mainframe systems	Exclusive database control requirement conflicts with read-only nucleus status.	Remove the READONLY=YES parameter setting for the nucleus and restart it.
2	mainframe systems	A nonprivileged call was made to the nucleus while it was in utility-only (UTI) mode.	Remove the UTIONLY=YES parameter setting for the nucleus and restart it.
3	mainframe and open systems	The nucleus is performing shutdown processing (an ADAEND operation) and will not accept new users or new transactions. Either a new user is attempting to begin operation	Wait for the nucleus to shut down, restart it, and reissue the command.

Subcode	Occurrence Location	Description	Action
		or an existing user in ET status is trying to continue operation.	
4	mainframe systems	A utility with exclusive database control is running.	Either stop the utility or wait for its processing to complete (this is preferred) and try again.
5	mainframe systems	A single-user nucleus could not start operation due to an error that could not be corrected.	Verify that single-user mode has been set up correctly and restart the nucleus.
8	mainframe systems	A user is performing a logical ADALNK call. The IDT for the call has not been allocated.	On BS2000 systems, check the setting of the parameter accessed by the link name DDLNKPAR or DDCARD, or in the macro B2CONFIG of the module SSFB2C. Also check the IDTNAME parameter of the database to be accessed.
21	open systems	Entire Net-Work access communication has failed. The first two bytes of the Additions 2 field contain an error number.	Refer to your Entire Net-Work documentation for further information.
22	open systems	There is a problem with the Adabas IPC driver. The first two bytes of the Additions 2 field contain an error number.	Shut down the nucleus, if it is still active, and restart it. If the error still occurs, try issuing the command <code>showipc -kd <dbid></code> , then restart the nucleus and reissue the command.
23	Adabas open systems version 3.1 only	There is a problem attaching the Adabas IPC driver's shared memory	Shut down the nucleus, if it is still active, and restart it. If the error still occurs, try issuing the command <code>showipc -kd <dbid></code> , then restart the nucleus and reissue the command.
24	open systems	The ADALNK shared library cannot be loaded correctly.	Check the locations and permissions of the ADALNK shared library.
26	open systems	An IPC problem occurred during open processing, e.g. the shared memory could not be attached.	One reason for these messages may be that someone has deleted an IPC resource. If this is the case, shut down the nucleus, if it

Subcode	Occurrence Location	Description	Action
27	open systems	An IPC problem occurred during a read in the message queue.	is still active, and restart it. If the error still occurs, try issuing the command <code>showipc -kd <dbid></code> , then restart the nucleus and reissue the command.
28	open systems	An IPC problem occurred during a write in the message queue.	Another reason these messages may occur may be that the IPC resources are not sufficient. In this case, increase the IPC resources, or decrease the values of some nucleus parameters on which the required amount of IPC resources depends., or stop some other process that also consumes IPC resources. For more information about IPC resources, refer to the section <i>Increasing System V IPC Resources</i> in the Adabas open systems installation documentation.
29	UNIX platforms only	IPC resources exist, but the database server was not active.	Issue the command <code>showipc -kd <dbid></code> , restart the nucleus, and reissue the command.
50	mainframe systems	At command completion RSP148 was set but without a subcode. This subcode is set to indicate the command was processed by the target. This often occurs in a Cluster or Parallel Services environment when one of the targets is no longer active.	Contact your Software AG support representative for assistance.
51	mainframe systems	The command router found no suitable target. The target was determined not to be an Adabas Cluster Services or Adabas Parallel Services database.	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
52	mainframe systems	The command router found no suitable target. The target was determined to be an Adabas Cluster Services or Adabas Parallel Services database.	Contact your Software AG support representative for assistance.
53	mainframe systems	The command router found a suitable target but the target became inactive while queuing the command.	Contact your Software AG support representative for assistance.
54	mainframe systems	When the caller attempted to retrieve the results of a completed command the target was no longer active.	Contact your Software AG support representative for assistance.
55	mainframe systems	The target became inactive while the caller was attempting to retrieve the results of a completed command.	Contact your Software AG support representative for assistance.
58	mainframe systems	An error occurred while POSTing the Adabas nucleus ECB after queuing a command.	This may be seen if the nucleus is terminating. Otherwise contact your Software AG support representative for assistance.
61	mainframe systems	A command sent from a nucleus to another nucleus caused an ABEND while the caller was attempting to initiate the command. The target may have become inactive. The ABEND was intercepted and recovered.	This may be seen if the target nucleus is terminating. Otherwise contact your Software AG support representative for assistance.
64	mainframe systems	A command sent from a nucleus to another nucleus caused an ABEND while the caller was attempting to retrieve the results of a completed command. The target may have become inactive. The ABEND was recovered by ADAMPM.	This may be seen if the target nucleus is terminating. Otherwise contact your Software AG support representative for assistance.
101/201	mainframe systems	Set in SVCCLU when a specifically designated local nucleus is not available for a physical call. The 201 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
102/202	mainframe systems	Set in SVCCLU when a specifically designated remote nucleus is not available for a physical call. The 202 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
103/203	mainframe systems	Target ID disagreement between IDTE and PLXNUC. The 203 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
104/204	mainframe systems	Unable to find PLXMAP matching an existing PLXUSER. The 204 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
105/205	mainframe systems	Entire Net-Work unavailable, can't route existing user to remote nucleus. The 205 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
106/206	mainframe systems	Entire Net-Work unavailable, can't route new user to remote nucleus. The 206 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
107/207	mainframe systems	No nucleus available for remote user. The 207 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
108/208	mainframe systems	Incorrect PLXMAP update received by LOCAL=YES nucleus. The 208 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
109/209	mainframe systems	An internal command used to synchronize across multiple nodes was received for an Adabas Parallel Services database. Such databases may execute on only one node. Depending on intersystem communications timing this may occur as a database is changed from Adabas Cluster	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
		Services to Adabas Parallel Services. Otherwise this is a logic error.	
110/210	mainframe systems	Unable to assign specified nucleus to remote user. The physical command arrived via Entire Net-Work for a specific nucleus, but the specified nucleus is on another system. Only one Entire Net-Work transmission is allowed. The 210 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
1019	open systems	No active database found.	Contact your Software AG support representative for assistance.
1020	open systems	The Entire Net-Work relay failed.	Contact your Software AG support representative for assistance.
1021	open systems	EC: Not XTS directory information available.	Contact your Software AG support representative for assistance.
1022	open systems	No context found.	Contact your Software AG support representative for assistance.
1023	open systems	No local database found.	Contact your Software AG support representative for assistance.
1024	open systems	Invalid context found.	Contact your Software AG support representative for assistance.
1025	open systems	General logic error; no XTS found.	Contact your Software AG support representative for assistance.
1026	open systems	A server shutdown occurred.	Contact your Software AG support representative for assistance.
1027	open systems	A server overload occurred.	Contact your Software AG support representative for assistance.
1028	open systems	The server rejected a call.	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
1029	open systems	No such DBID.	Contact your Software AG support representative for assistance.
1030	open systems	The database is inactive.	Contact your Software AG support representative for assistance.
1031	open systems	No response.	Contact your Software AG support representative for assistance.
1032	open systems	An invalid protocol was found.	Contact your Software AG support representative for assistance.
1033	open systems	An unknown response occurred.	Contact your Software AG support representative for assistance.
1034	open systems	Remote communication is not allowed.	Contact your Software AG support representative for assistance.

Action Review the user actions provided in the explanation above.

Response 149

Origin Open systems only

Explanation A communication error was detected. The Additions 2 field contains the system service completion code which caused the error response.

Subcode	Description
1035	Context allocation failed.
1036	Inconsistent architecture encountered.
1037	XTS error 149/224 occurred.

Action Contact your Software AG technical support representative for assistance.

Response 150

Origin	Open systems only
Explanation	Too many database nuclei have been used in parallel. The Additions 2 field contains the maximum number of nuclei allowed in parallel.
Action	Do not use more database IDs in a single program than the value given in the Additions 2 field.

Response 151

Origin	Mainframe and open systems
Explanation	A command queue overflow occurred. Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.
Action	The DBA may increase the value of the NC parameter or the command may be issued when there is a lower level of command activity. If you are running Entire System Server and receive this response code, your database administrator should increase the size of the NCQE parameter. For more information, refer to the startup parameter documentation included in your Entire System Server administration documentation.

Response 152

Origin	Mainframe and open systems
Explanation	The internal user buffer was not large enough to contain the user buffer areas.
Action	On mainframe systems, the DBA should increase the value of the LU parameter used by the Entire Net-Work nucleus. If you are running Entire System Server and receive this response code, your database administrator should increase the size of the IUBL parameter. For more information, refer to the startup parameter documentation included in your Entire System Server administration documentation. On open systems, contact your Software AG technical support representative.

Response 153

Origin	Mainframe and open systems
Explanation	A second Adabas call was issued while the first one was still being processed.

Subcode	Description
1050	A thread is pending.
1051	A user ID is pending.

Action Issue only one call at a time.

Response 154

Origin Mainframe and open systems

Explanation One of the following occurred:

- The Adabas call was canceled by the user (open systems).
- The command was rejected because it resulted in a trigger being fired, but the queue is full at this time. (mainframe)

Action On open systems, no action is required for this informational message. On mainframe systems, retry the command.

Response 155

Origin Mainframe systems only

Explanation A command resulted in a pre-command trigger being fired. The triggered procedure returned a nonzero command, so the command was not executed.

Action Check the Additions 4 field for the error returned from the procedure.

Response 156

Origin Mainframe systems only

Explanation A command resulted in a post-command trigger being fired. The triggered procedure returned a nonzero command, indicating an unsuccessful execution of the procedure.

Action Check the Additions 4 field for the error returned from the procedure.

Response 157

Origin Mainframe systems only

Explanation A command resulted in either a pre- or post-command trigger being fired; however, Adabas Triggers has been shut down with the option to reject all commands that result in a trigger being fired.

Action Determine the cause of the shut-down and resolve the problem. If rejection of commands is not the required action in such a situation, then set the error action field in the Adabas Triggers profile to halt or ignore.

Response 159**Origin** Mainframe systems only**Explanation** The Adabas link module is missing or invalid. One of the following occurred:

- No Adabas link module is linked to the Natural nucleus and the Adabas link module specified in the Natural profile parameter ADANAME could not be loaded.
- (CICS only) The loaded Adabas link module is macro-level in a command-level only environment.

Action Check the setting of the Natural profile parameter ADANAME and/or provide the correct version of the Adabas link module in one of the current STEPLIBs.**Response 160****Origin** Mainframe systems only**Explanation** Too many Associator and Data Storage blocks were marked as active in the buffer pool for a single command.**Response 161****Origin** Mainframe systems only**Explanation** The RABN chain in the header list of the Adabas buffer pool is invalid.**Response 162****Origin** Mainframe and open systems**Explanation** No additional space is available for the Adabas buffer pool.**Action** Increase the value of the ADARUN LBP parameter.

On open systems, because the buffer pool overflow is normally caused by too many blocks in the buffer pool waiting to be written to disk, specifying a low value for the WRITE_LIMIT parameter is recommended.

Response 163**Origin** Mainframe systems only**Explanation** The RABN to be linked into the RABN header chain is already in the chain.

The following table shows some of the subcodes that may be returned:

Subcode	Description
1	The RABN to be linked into the RABN header chain is already in the chain.
2	A file extent overlap exists such that the same data storage RABN has been assigned to two different files.
3	A supposedly unused data storage RABN is already in use.
4	A file extent overlap exists such that the same Associator RABN has been assigned to two different files.
5	A supposedly unused Associator RABN is already in use.

Action Contact your Software AG technical support representative for assistance.

Response 164

Origin Mainframe systems only

Explanation Too many work areas were allocated for the command.

Response 165

Origin Mainframe and open systems

Explanation A descriptor name was either invalid or did not exist in the descriptor value table (DVT). For expanded files: the descriptor does not exist on all component files.

On open systems, this error may occur during ADAREC generate if one of the following occurs:

- A file was loaded with an incorrect FDT.
- ADAINV was not reexecuted following a stop at a SYNPN checkpoint.

In an ACB, the leftmost two bytes of Additions 2 may contain the descriptor name; in an ACBX, the Error Character Field (ACBXERRB) may contain the descriptor name. If this occurred for an expanded file, check to see if there is an FDT mismatch between the components of the file.

On open systems, bytes 3 and 4 of the Additions 2 field contains the name of the descriptor that caused the error.

Action On open systems, if the error is not a handling error, run the INDEX option of ADAVFY and contact your Software AG technical support representative.

Response 166

Origin	Mainframe and open systems
Explanation	<p>An error was detected in an inverted list index; a descriptor value was not found during a delete operation. The cause may be damage in the Associator.</p> <p>On open systems, bytes 3 and 4 of the Additions 2 field contains the name of the descriptor that caused the error.</p>
Action	<p>On open systems perform the following steps:</p> <ol style="list-style-type: none"> 1. Locate the descriptor that caused the error in the Additions 2 field of the user control block; 2. Run the VERIFY option of ADAINV for this descriptor and save the output; 3. Reinvert the descriptor; 4. If necessary, restart the database (if this is possible); 5. Send the following information to your Software AG technical support representative: <ul style="list-style-type: none"> ■ The output of the VERIFY option of ADAINV; ■ All available PLOGs; ■ The FDT of the file containing the error; ■ If the nucleus crashed, the crash directory.

Response 167

Origin	Mainframe and open systems
Explanation	<p>The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.</p> <p>Mainframe Systems</p> <p>The field in a coupled file does not exist or the coupled list is invalid.</p> <p>Open Systems</p> <p>An error was detected in an inverted list index; a descriptor value was already present during an insert operation.</p> <p>Bytes 3 and 4 of the Additions 2 field contains the name of the descriptor that caused the error.</p>
Action	<p>The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.</p> <p>Mainframe Systems</p> <p>Open Systems</p> <p>Complete the following steps:</p>

1. Locate the descriptor that caused the error in the Additions 2 field of the user control block;
2. Run the VERIFY option of ADAINV for this descriptor and save the output;
3. Reinvert the descriptor;
4. If necessary, restart the database (if this is possible);
5. Send the following information to your nearest support center:
 - The output of the VERIFY option of ADAINV;
 - All available PLOGs;
 - The FDT of the file containing the error;
 - If the nucleus crashed, the crash directory.

Response 168

Origin Mainframe systems only

Explanation An internal command ID required during coupling processing was not found.

Response 170

Origin Mainframe and open systems

Explanation The Adabas RABN required for the command could not be located for one of the following reasons:

- The buffer segment was called with a RABN of zero.
- The specified RABN does not belong to this database and is invalid.

On open systems, the Additions 2 field contains the invalid RABN in 4 byte binary format.

Action On open systems, run the LOST, INDEX and DATA options of ADAVFY for the file in question and contact your Software AG technical support representative.

Response 171

Origin Mainframe systems only

Explanation The constant set used by Adabas could not be located.

Response 172

Origin Mainframe and open systems

Explanation On mainframe systems, an ISN was less than the MINISN or greater than the MAXISN setting in effect for the file.

On open systems, the maximum possible ISN of the file was reached and no more can be allocated.

Action On open systems, if the file contains significantly less than 2^{32} records, you should unload the file with ADAULD and reload it with ADAMUP without USERISN. However, you must be aware that problems may arise if the ISNs have semantics for you - if, for example, you use the ISNs to reference records in this file, additional reorganization of these references will be necessary. The alternative to unloading and reloading the data is to split up your data into more than one file, and to adapt your application accordingly.

Response 173

Origin Mainframe and open systems

Explanation An invalid Data Storage RABN was detected.

On open systems, the Additions 2 field contains the invalid RABN in 4 byte binary format.

Action On open systems, run the DATA option of ADAVFY for the file in question and contact your Software AG technical support representative.

Response 174

Origin Mainframe systems only

Explanation For an L2/L5 command with start ISN, the Data Storage RABN stored in the address converter for the file is invalid.

Response 175

Origin Mainframe systems only

Explanation An inconsistency was detected between the index and Data Storage.

This response code can be expected when reading a descriptor value for a ciphered file if an incorrect cipher code was used.

Subcode	Meaning
99	On logical reads and simple searches without hold, the index value is compared with the value from the data record to ensure consistency. When the values do not match, the read or search is repeated in order to avoid the effects of a possible parallel update. If the values still do not match, response 175 is given.

Action Run the ADACHK utility against the file, and contact your Software AG technical support representative.

Response 176

Origin Mainframe and open systems

Explanation Either an inconsistency was detected in an inverted list or an internal error occurred during inverted list processing.

On open systems, the Additions 2 field contains the inconsistent RABN in 4-byte binary format.

On mainframe systems, the following possible subcodes are associated with this response code:

Subcode	Meaning
2	Bad index
3	Invalid search request
4	Invalid format indicator or field not found in FDT/SDT
11	Invalid search request
12	Bad index block
13	Bad UI block
14	Mismatch block length
15	Bad MI block
16	Mismatching block length
17	Bad NI block
18	Bad ISN count
21	Bad index block
22	Mismatching block length
23	Invalid ISN count
29	Inactive index block
31	Bad index block
32	Mismatching block length
33	Invalid ISN count

Subcode	Meaning
39	Inactive index block
41	Bad index block
42	Mismatching block length
43	Bad MI block
44	Bad NI block
81	Invalid level indicator
82	Bad element position in block
83	Position in block did not match element lengths
84	Bad MI block
85	Bad NI block
86	Bad NI block
87	Invalid ISN count
88	Position in block did not match element lengths
89	Index block not active
91	Wrong level
92	Mismatching block length

Action On mainframe systems, run an appropriate ADACHK utility function to determine whether an inconsistency exists in an inverted list. If not, contact your local Software AG technical support representative. Make sure to report the subcode to your Software AG technical support representative.

On open systems, check if an autorestart or an ADAREC REGENERATE have disabled the index. If not, run the INDEX option of ADAVFY for the file in question. If the INDEX option signaled errors, you should recreate the entire inverted list with ADAINV REINVERT ALL or contact your Software AG technical support representative.

Response 177

Origin Mainframe and open systems

Explanation A record could not be found in the Data Storage block in which it should have been contained as indicated by the address converter. On mainframe systems, if this response code is returned to the ADAULD UNLOAD utility function with the parameter SORTSEQ, the file might be inconsistent and data lost.

Subcode 19 is issued because the base file record was not found in Data Storage. At the end of a LOB update in the LOB file, the associated base file record was no longer present in the data storage block.

Action On mainframe systems, check the file with the ADACHK ACCHECK utility function and contact your Software AG technical support representative.

On open systems, run the AC option of ADAVFY for the file in question and contact your Software AG technical support representative.

Response 178

Origin Mainframe systems only

Explanation An internal error occurred when updating a multiple-value field:

Subcode	Meaning
1	Inconsistency in descriptor value table (DVT).
2	An inconsistency was detected between the field definition table (FDT) and the internal format buffer.
3	Inconsistency when updating a phonetic descriptor.

Response 179

Origin Mainframe systems only

Explanation Internal error; identifier could not be found in Work part 3.

Response 181

Origin Mainframe systems only

Explanation Autobackout was executed and the start of a transaction could not be located.

Response 182

Origin Mainframe and open systems

Explanation Necessary ET data was not found in the appropriate Work block.

Action On open systems, save WORK1 and send it to your nearest Software AG technical support representative together with a description of what caused the pending autorestart and, if possible, the dump directory and the PLOG. Then restore and regenerate the database.

Response 183

Origin Mainframe systems only

Explanation An internally assigned number for a database I/O operation was detected as invalid.

Response 184

Origin Mainframe systems only
Explanation A phonetic field name could not be found.

Response 185

Origin Mainframe systems only
Explanation The ADAM field could not be found in the compressed record.

Response 186

Origin Mainframe systems only
Explanation A wrong cipher code has been specified or a compressed data record is bad (does not conform to the Field Description Table).

The leftmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field contain the field or descriptor name where the error was detected. The rightmost two bytes of the same ACB or ACBX field contain an internal code identifying the routine that detected the error.

Action If the file that was accessed when this response code occurred is ciphered, check whether the correct cipher code has been specified. Correct the cipher code, if necessary.

If the error is not due to an incorrect cipher code, run the ADACMP DECOMPRESS INFILE utility function to unload and decompress all records of the file. ADACMP will write records where it detects errors to its error dataset (DD/FEHL). Contact your Software AG technical support representative for assistance.

Response 187

Origin Mainframe systems only
Explanation The response indicates that an invalid Data Storage block was detected while locating a record by ISN. One of the following error conditions occurred:

- An invalid block length (negative) was encountered.
- An invalid record length (not positive) was encountered.
- The sum of the record lengths is not equal to the block length plus 4.

The Additions 2 field contains the Data Storage block number where the error was detected.

Action Contact your Software AG technical support representative for assistance.

Response 196

Origin Open systems only

Explanation Referential integrity has been violated. Bytes 3 and 4 of the Additions 2 field contain the name of the violated constraint. Bytes 1 and 2 of the Additions 2 field contain the reason as a two-byte binary number:

Subcode	Meaning
1	Required ISN in hold by another user
3	Maximum number of ISNs held by one user is reached
5	Check integrity mismatch, required value not found during check
7	Double update to a record within a cascade detected
8	Limit of stacked commands reached

Action Handle the referential integrity violation, for example, write an error message.

Response 197

Origin Mainframe systems only

Explanation The DEUQ pool is too small.

Action Increase the ADARUN LDEUQP parameter.

Response 198

Origin Mainframe systems only

Explanation An attempt was made to duplicate a descriptor value for a unique descriptor. In an ACB, the leftmost two bytes of the Additions 2 field may contain the descriptor name; in an ACBX, the Error Character Field (ACBXERRB) may contain the descriptor name. The following subcodes may accompany this response code:

Subcode	Meaning
1	Unique descriptor insert failed; value already exists in the index.
2	Unique descriptor insert failed; value in use by another user on this nucleus.
3	Unique descriptor insert failed; value in use by another user on another cluster nucleus.
4	Unique descriptor insert failed; the value we are attempting to insert in the NI block is already there.

Response 199**Origin** Mainframe systems only**Explanation** An inconsistency in the inverted list index was found during an update operation. In an ACB, the leftmost two bytes of Additions 2 may contain the descriptor name; in an ACBX, the Error Character Field (ACBXERRB) may contain the descriptor name. This response code can also occur if UTYPE=EXU was specified for an ADARES BACKOUT operation that uses the sequential (SIBA) log.**Response 200****Origin** Mainframe and open systems**Explanation** Either an invalid cipher code or an Adabas SAF Security or Adabas security violation was detected.

The command could not satisfy the necessary security checks. This response code may be accompanied by one of the following subcodes:

Subcode	Meaning
0	A standard user check failed.
1	There is no free user file cache entry for a workstation user.
2	A cross-level security check failed.
3	No security information is available for the command.
4	A timeout occurred during a workstation logon.
5	An internal SAF Kernel error occurred.
6	A failure occurred during a newcopy/restart operation. The nucleus terminates.
7	A request to make an ABS security check was not of the correct format.
8	A security violation occurred while a file was being loaded into an existing expanded file chain.
11	User is not permitted to do a SEARCH command.
12	User is not permitted to do a SEARCH command.
13	User is not permitted to do a SEARCH command.
14	An invalid cipher code was encountered during update.
15	User is not permitted to read FDT (LF command).
16	Remote workstation user has supplied a new password or passphrase but there is a mismatch with the old: <ul style="list-style-type: none"> ■ old password with new passphrase ■ old passphrase with new password Passwords and passphrases should not be mixed.

Subcode	Meaning
17	Remote workstation user has supplied a password phrase but the detected version of SAFPSEC does not support password phrases. Either: ■ SAFPSEC is an old version that does not support password phrases or ■ SAFPSEC is capable of supporting passphrases but has been assembled with an incorrect REL= parameter (see the installation documentation for more details)
21	User's SAF ID is unknown.
22	User's SAF ID has changed.
24	Remote workstation logon failure; user-id is not defined.
25	Remote workstation logon failure; invalid password / password phrase.
26	Remote workstation logon failure; invalid new password / new password phrase.
27	Remote workstation logon failure; user-id revoked.
28	Remote workstation logon failure; logon not allowed at this time/date.
1060	Open systems ADASAF phase 1 failed.
1061	Open systems ADASAF phase 1 failed with response.
1062	Open systems ADASAF phase 2 failed.

For more information about Adabas SAF Security, read the Adabas SAF Security documentation.

Action Resolve the security error, perhaps by simply supplying the correct password.

Response 201

Origin Mainframe and open systems

Explanation The specified password was not found.

Action Supply the correct password.

Response 202

Origin Mainframe and open systems

Explanation An attempt was made to use a file for which the user is not authorized, or the file password is being changed, or, if Adabas Security is being used, the file has attached Security By Value on this field.

Action Either correct the authorization, or retry the operation with the new password, or, if Adabas Security is being used, remove the Security By Value on the field before the operation on the file can be retried.

Response 203**Origin** Mainframe systems only**Explanation** An attempt was made to delete a record in a file for which the user is not authorized.**Response 204****Origin** Mainframe and open systems**Explanation** On mainframe systems, a password pool overflow occurred.

On open systems, the password supplied is already in use.

Action On open systems, change the password to one that is not already existing.

On mainframe systems, check and possibly increase the value specified for ADARUN LCP parameter in the Adabas nucleus.

Response 207**Origin** Mainframe systems only**Explanation** Adabas SAF Security completed phase 1 of logon and requested phase 2. This is an internal Adabas SAF Security and ADALNK two-phase response code for a remote workstation logon. This code is normally not displayed or presented.

For more information, read your Adabas SAF Security documentation.

Action Send a phase 2 logon request to Adabas SAF Security.**Response 208****Origin** Mainframe and open systems**Explanation** As an Adabas SAF Security remote user, you should execute a phase 1 logon. The logon ID and your password are sent to Adabas SAF Security. This response indicates that two-phase logon can continue.

For more information, read your Adabas SAF Security documentation.

Subcode	Meaning
1066	Open systems ADASAF phase 1 error exit.
1067	Open systems ADASAF phase 2 error exit.

Action If the user application receives this response, it is on a workstation platform that does not have the proper Adabas link routine installed. This response code is intercepted by the workstation Adabas link routine and phase 1 logon is performed.

Response 209

Origin Mainframe systems only

Explanation Adabas SAF Security detected an expired password on the server. The workstation user's password has expired. This code is normally not returned to the application. Instead the workstation user is prompted to enter a new password.

Action Create a valid password on the server for ACF2, RACF, or Top Secret. Entire Net-Work users may use the Adabas SAF Security feature.

Response 210

Origin Mainframe and open systems

Explanation On mainframe systems, a logical ID was greater than 255 (internal error).

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, a receive buffer was lost in NETRDI.

Action On open systems, the DBA may increase the value of the NAB or NC parameters in the NETRDI in the target node.

Response 211

Origin Mainframe and open systems

Explanation On mainframe systems, an invalid ID table index in the UB (internal error) occurred.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, a remote utility cannot be executed because OPTIONS = LOCAL_UTILITIES is set for the database.

Action On open systems, contact the DBA of the remote database.

Response 212

Origin Mainframe and open systems

Explanation On mainframe systems, an invalid input/output buffer was encountered for an internal command.

On open systems, a requested function is not implemented in the target architecture.

Action On open systems, execute the utility on the target node.

Response 213

Origin Mainframe systems only
Explanation ID table not found (SVC not properly installed).

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

The following table describes the possible subcodes that might occur if an Adabas DBID/SVC routing table error occurs:

Subcode	Meaning
16	The specified SVC number does not correspond to a currently installed SVC on the z/OS or z/VSE system. Check to be sure that the specified SVC number is correct and, if it is, ensure that an Adabas SVC is installed using that SVC number.
20	The specified SVC number corresponds to an installed SVC on the z/OS or z/VSE system, but the SVC is not an Adabas SVC. Ensure that the provided SVC number is correct and, if it is, determine why the SVC installed for that number is not an Adabas SVC for z/OS or z/VSE.

Action Inform the DBA. The Adabas installation procedure was not properly executed.

Response 214

Origin Mainframe systems only
Explanation Internal command issued from Adabas version 4 ADALNK.

Response 215

Origin Open systems only
Explanation The Adabas interface (adalnkx, adalnk, adalnknc) used by the application program, or the Entire Net-Work version used is not supported by the Adabas nucleus. For example, the Adabas nucleus Version 6.1 does not support the Adabas interface of Version 5.1. If a 32-bit version and a 64-bit version of Adabas exists for an operating system, the 64-bit nucleus does not support the Adabas interface of the 32-bit version - 32-bit applications must use the 32-bit mode Adabas interface of the 64-bit version.

Note: The compatible Entire Net-Work versions supported by an Adabas open systems version are documented in the Adabas open systems Release Notes.

Action If you are using an incompatible version of Entire Net-Work, upgrade it to a compatible version. Check the definition of the environment variable PATH (Windows) or LD_LIBRARY_PATH (UNIX). If the application has been linked with the s-bit on UNIX, it is necessary that the correct Adabas interface has been installed with \$SAG = /opt/softwareag.

Response 216

Origin Mainframe and open systems
Explanation Command rejected by user exit.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
1070	UEX_ACBX_0 command rejected.

Response 217

Origin Mainframe systems only
Explanation Command rejected by user exit.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Response 218

Origin Mainframe systems only
Explanation The following table describes the subcodes that appear with this response code, clarifying why the response was received.

Subcode	Meaning
00 or 01 or 02	The UB (TP monitor user block) pool is too small. There must be at least one user block for each concurrent user. This is controlled by the TP monitor link routines. The GETMAIN for the UB failed.
13 or 15 or 17	An error has occurred during the freeing of the UB and Work areas for a TL call. This may indicate an internal product error or a TP monitor storage overlay. Contact Software AG technical support for assistance.
72	An IPC message call parameter error occurred. This may indicate an internal product error or a TP-monitor storage overlay. Contact Software AG technical support for assistance.
73	The IPC message caller did not provide a pointer to the extended user ID block. This is probably an internal product error. Contact Software AG technical support.
74	An IPC message internal work area is corrupted. This may indicate an internal product error or a TP monitor storage overlay. Contact Software AG technical support for assistance.

Subcode	Meaning
75	An IPC message call parameter error occurred. This is probably an internal product problem. Contact Software AG technical support for assistance.
76	The extended user ID data provided to the IPC Message Call is either binary zeroes or blank. This is probably an internal product error. Contact Software AG technical support.
77	A getmain failed for the work area used in an IPC Message Call. Determine why the TP monitor is running short of storage. The storage will be acquired in the AMODE of the calling program, usually 31-bit for Natural transactions.
78	An invalid IPC work area has been provided by the caller for a TS call. This is probably an internal product error. Contact Software AG technical support.
79	An error occurred during freemain done for a TS call. This may indicate an internal product error or a TP monitor storage overlay. Contact Software AG technical support for assistance.

Action

In the case of subcode zero, 01 or 02 increase the UB pool by respecifying the NUBS parameter in the link routines. See the LGBLSET macro information in the Adabas Installation documentation.

In all other cases, either the program executing the IPC message has provided invalid parameters, or there are internal product problems such as storage overlay conditions. Contact Software AG technical support for assistance.

Response 219**Origin**

Mainframe systems only

Explanation

This response code should only occur when Adabas Transaction Manager is being used.

Subcode	Meaning
2	The global transaction is not in the status that allows the call.
3	Two transaction ID (XID) entries exist.
4	The "R" and "J" options are not supported; or this is not a global transaction. The transaction ID (XID) does not exist or cannot be found (or example, when the given XID does not belong to the UQE).
5	The record or value buffer definition may be invalid; for example, the length size may be invalid (less than or equal to 144 bytes); or the value buffer content may be invalid; for example, it may not contain a valid transaction ID (XID).

Subcode	Meaning
6	The user is not an update or ET user or is already involved in a global transaction or the user is already on PET (preliminary end-of-transaction) status.
7	A protocol error occurred: The user has been copied to Work 4 or the transaction was backed out.
8	A protocol error occurred: The transaction was terminated or the user has no transaction ID (XID) or the recover call for an active user is not permitted.
9	The system is currently locked due to a pending Work area 4 or DDWORKR4 overflow.
10	The call is not permitted; either ADAEND or an ET-sync point is in process for the nucleus. Force the ATM nucleus to backout (BT) the transaction.
11	The user has not made any updates. A preliminary ET command, therefore, is not permitted.
12	A logic error occurred.
20	The transaction ID (XID) is unknown. This error occurs only in a cluster environment.

Response 220

Origin

Mainframe systems only

Explanation

The request was rejected by Entire Net-Work due to a shortage of short term buffers.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Action

For BS2000 systems running Sockets 2.2 or later, check the address space limit using the SHOW-USER-ATTRIBUTES command in the field ADDRESS-SPACE-LIMIT (the value is in megabytes). If necessary, increase it using the MODIFY-USER-ATTRIBUTES command from a privileged user ID.

For BS2000 systems running Sockets 2.1 or earlier, increase the CMSIZE parameter to enlarge the common memory pool, as long as there is enough room in the address space. Then restart Entire Net-Work.

For z/OS and z/VSE, increase the region size.

Response 221

Origin	Mainframe systems only
Explanation	The LU size of the remote partner is smaller than the size required for the Adabas request.
Action	Either increase the size specified for the LU= parameter on the remote system, or modify the application to reduce its buffer sizes.

Response 222 - 223 (reserved)**Response 224**

Origin	Mainframe and open systems
Explanation	An Adabas command has been timed out by Entire Net-Work. The request waited for a reply for a longer time period than specified by the REPLYTIM parameter in either the Entire Net-Work NODE statement or the SET operator command. The reply may be delayed or lost due to a target malfunction, or because of a connecting link failure. If you are using Natural, and all connections are verified, check the ADAMODE setting. The ADAMODE=0 setting is the only option Entire Net-Work supports.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the ACB Additions 2 field (ACBADD2) or the ACBX Error Subcode field (ACBXERRC) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
1	If the message was compressed using zEDC compression services and the attempt to decompress the message failed, subcode 1 is placed in the rightmost two bytes of the ACB Additions 2 field (ACBADD2) or the ACBX Subcomponent Response Code field (ACBXSUBR).
1076	An XTS timeout error occurred.

Action	Check the node and remote database or contact your database administrator for assistance.
---------------	---

Response 225

Origin	Mainframe and open systems
Explanation	A command was issued from a server, such as an Adabas nucleus, to another server, such as Entire Net-Work. The command did not complete within a prescribed time period. The issuer proceeds and no longer expects a response to the command. Note that the command may still execute in the target. There will be no notification to the issuer if it does. The target may display message ADAM92, User Gone, if the target attempts to notify the issuer of command completion. The subcode identifies the environment from which the command was issued.

Subcode	Issuer
1	ADAMPM
2	Adabas nucleus, thread-synchronous command
3	Adabas nucleus, not thread-synchronous. Under z/OS, the command was TCB-synchronous.

Action Contact your Software AG technical support representative for assistance if the reason for the command's failure to complete cannot be identified.

Response 226 - 227 (reserved)

Response 228

Origin Mainframe systems only

Explanation This response is issued by an Adabas link routine. It indicates that an ASCII-formatted user request has been issued against an EBCDIC-formatted database that is not properly configured to handle the translation:

1	The SVC is not a valid Adabas version 7 SVC.
2	The database is not UES-enabled.

Action Ensure that your Adabas installation is for a supported version and that the database is UES-enabled. Refer to the UES information.

Response 229

Origin Mainframe systems only

Explanation The Entire Net-Work 5 convertor detected an inconsistency or error in the application format buffer or search buffer and is unable to correctly translate the user's data.

Response 230

Origin Open systems only

Explanation The protocol defined by the X/Open XA specification is violated. This happens, for example, if a user tries to issue an ET call for an XA transaction.

Action Follow the XA specification.

Response 231-239

Explanation These response codes are assigned in some Adabas user exits, and have meanings as defined by the user. One example is the response code in the ADALOG log data field issued by user exit 4.

Action Refer to the description of user exits in the Adabas user, hyperdescriptor, and collation descriptor exits documentation for more information.

Response 240

Origin Mainframe systems only

Explanation Adabas Transaction Manager encountered an error. The error code can be found in the Adabas control block Additions 2 field, in the low-order (rightmost) two bytes. A response code may occur in the first two bytes of the Additions 2 field.

Action Check the meaning of the Adabas Transaction Manager error code. If the cause of the problem is not apparent, contact your Software AG technical support representative.

Response 241

Origin Mainframe and open systems

Explanation The explanation for this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

Adabas Transaction Manager (ATM) received an unexpected Adabas response code. The subcode and response code can be found, in that order, in the Adabas control block Additions 2 field. If a positive response code value appears in the Additions 2 field, the response code was detected by the ATM transaction manager. If a negative response code value appears in the Additions 2 field, take its complement: this is the response code received by the client proxy's attempt to communicate with the ATM transaction manager.

Open Systems

The system cannot load the specified user exit shared library or dynamic load library, or the specified function does not exist in this shared library or dynamic load library. If the function does not exist in the shared library or dynamic load library, bytes 1 and 2 of the Additions 2 field contain the system's error number in binary format, otherwise these two bytes contain 0. Bytes 3 and 4 of the Additions 2 field contains the number of the ADALNK user exit which failed in binary format.

Subcode	Meaning
1080	UEX_ACBX_0 load failed.
1081	UEX_ACBX_1 load failed.

Action

Mainframe Systems

Check the meaning of the Adabas response code and subcode. If the cause of the problem is not apparent, contact your Software AG technical support representative.

Open Systems

Make sure that you use the correct environment variable for the user exit.

Response 242

Origin

Mainframe and open systems

Explanation

The explanation for this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The Adabase Transaction Manager (ATM) or ATM client proxy was unable to determine the status of the caller's transaction. There might be an ATM error code in the Adabas control block Additions 2 field, in the low-order (rightmost) two bytes.

Open Systems

A double allocation has been detected between two or more files or a file and the free space table.

Action

Mainframe Systems

Check the meaning of the Adabas Transaction Manager error code, if one is present. Otherwise, determine the status of the global transaction using Online Services. If the required action is not apparent, contact your Software AG technical support representative.

Open Systems

Run ADAVFY without any options to find out which parts of which files are affected. Contact your nearest support center with the output from ADAVFY.

Response 243

Origin Mainframe and open systems

Explanation The explanation for this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

Mainframe Systems

The Adabas Transaction Manager (ATM) or client proxy received an unsolicited syncpoint request. The action taken or the status of the global transaction that was open is indicated by a subcode in the Adabas control block Additions 2 field, in the low-order (rightmost) two bytes.

Subcode	Explanation and Recommended Action
1	The unsolicited syncpoint request was accepted. The status of the current global transaction is not known. Use Online Services to determine the status of the global transaction.
2	The unsolicited syncpoint request was accepted. The client session's global transaction has been committed.
3	The unsolicited syncpoint request was accepted. The client session's global transaction has been backed out.
4	The unsolicited syncpoint request was accepted. The client session's global transaction had mixed completion (partially backed out, partially committed).
5	The unsolicited syncpoint request was accepted. The client session's global transaction is in backout.
6	The unsolicited syncpoint request was accepted. The client session's global transaction is in commit.
7	The unsolicited syncpoint request was accepted. The client session had no global transaction open.
12	The unsolicited syncpoint was attempted, but ATM returned response code 148 (ADARSP148) so the outcome is not known.
16	The unsolicited syncpoint request was rejected.

Open Systems

An invalid FCB extent has been detected for a file.

Action**Mainframe Systems**

Review the Adabas Transaction Manager's TMSYNCMGR parameter and the TransactionControl, Client-sideTransactionManager, and HostSystemTransactionManager client runtime controls for the failing job.

Open Systems

Contact your nearest support center.

Response 245

Origin Mainframe and open systems

Explanation On mainframe systems, this response code is issued for communication problems between add-on products that use the system coordinator (COR) interface to Adabas; that is, Adabas Fastpath, Adabas Vista, Adabas SAF Security, and Adabas Transaction Manager.

Subcode	Meaning
1	Internal error.
2	A required module could not be loaded. This is probably an installation error.

On open systems, pending utility entries exist in the UCB.

Action On mainframe systems, for subcode 1, contact your Software AG technical support representative. For subcode 2, consult the installation instructions for the add-on product.

On open systems, delete the entries with RESET = UCB before executing RECOVER, but ensure that the utilities which own the UCB entries are no longer running.

Response 246

Origin Open systems only

Explanation Utility communication block (UCB) overflow.

Action Execute the RESET function of ADADBM to remove unused entries from the utility communication block if the utilities that own them are no longer running.

Response 247

Origin Open systems only

Explanation Correct ID not found in the utility communication block.

Action The utility cannot be restarted. Delete the utility communication block entry and rerun the utility.

Response 248

Origin Mainframe and open systems

Explanation This response code is returned by Data Archiving for Adabas processing. Subcodes are returned in big-endian byte order in the Additions-2 field of the Adabas control block and conform to the format 0xhhhhChhh where C is the subcode category. The subcodes below are listed in Category order.

Category 0 subcodes:

Subcode	Meaning
1 (0x00000001)	No architecture/version information returned by Adabas in the response to the OP command. <i>Action:</i> Contact your Software AG technical support representative.
2 (0x00000002)	Cannot recall archived data because the architecture of the target database is not compatible with the architecture to the original database. <i>Action:</i> Choose a different mixture.
3 (0x00000003)	Either the Extractor/Accumulator versions are not compatible or the Adabas version of the database being archived from or recalled to is not supported. <i>Action:</i> Contact your Software AG technical support representative.
4 (0x00000004)	The FDT of the file into which data is being recalled or archived is not compatible with the FDT of the original file. <i>Action:</i> Check that FDTs of the files are compatible.
5 (0x00000005)	Cannot coerce a value specified for the extraction criteria to the specified type. <i>Action:</i> Check that the values and types defined for the extraction criteria are correct.
6 (0x00000006)	Date specified for the extraction criteria is prior to the earliest supported data. <i>Action:</i> Contact your Software AG technical support representative.
7 (0x00000007)	Unsupported date/time pattern in extraction criteria. <i>Action:</i> Set a correct pattern in the extraction criteria. Contact Software AG Support.
8 (0x00000008)	Database from which data is being archived or recalled into is not on the local machine. <i>Action:</i> Check the action is correctly configured. The source database must be local to the Extractor and target database local to the Accumulator.
9 (0x00000009)	Cannot load the Adabas System Coordinator library. <i>Action:</i> Check that Adabas System Coordinator is installed correctly.
10 (0x0000000A)	An incompatible version of Adabas System Coordinator is installed.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
11 (0x0000000B)	An incompatible version of Adbas System Coordinator is installed. <i>Action:</i> Contact your Software AG technical support representative.
12 (0x0000000C)	Cannot parse FDT. <i>Action:</i> Contact your Software AG technical support representative.
13 (0x0000000D)	Cannot generate FDU from FDT. <i>Action:</i> Contact your Software AG technical support representative.
14 (0x0000000E)	Cannot create format buffer for the whole FDT. <i>Action:</i> Contact your Software AG technical support representative.
15 (0x0000000F)	PE or MU field(s) not defined correctly. <i>Action:</i> Check that the PE/MU fields in the Extractor/Accumulator filtering and Archive search fields are defined correctly.
16 (0x00000010)	Field does not exist in the FDT. <i>Action:</i> Check that the fields in the Extractor/Accumulator filtering and Archive search fields are defined correctly.
17 (0x00000011)	Recall of a filtered archive using the 'Replace duplicate unique descriptors' option failed because the format/record buffer could not be parsed. <i>Action:</i> Contact your Software AG technical support representative.
18 (0x00000012)	Recall of a filtered archive using the 'Replace duplicate unique descriptors' option failed because the conflicting descriptor does not appear in the format/record buffer. <i>Action:</i> Choose different recall options for handling duplicate unique descriptors or ensure that all UQ fields are included in a filtered archive.
19 (0x00000013)	Internal record buffer overflow. <i>Action:</i> Contact your Software AG technical support representative.
20 (0x00000014)	Internal format buffer overflow.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
21 (0x00000015)	Internal search buffer overflow. <i>Action:</i> Contact your Software AG technical support representative.
22 (0x00000016)	Internal value buffer overflow. <i>Action:</i> Contact your Software AG technical support representative.
23 (0x00000017)	No extraction criteria were specified and there are no DE fields in the FDT. <i>Action:</i> Contact your Software AG technical support representative.
24 (0x00000018)	No Computer record for the current Adabas System Coordinator Group Leader. <i>Action:</i> Check that the correct Repository is being used and that the Adabas System Coordinator Computer is still defined.
25 (0x00000019)	No archive service definition for the Extractor/Accumulator computer. <i>Action:</i> Check that the correct Repository is being used and that the Data Archiving Service is still defined for Adabas System Coordinator Daemon.
26 (0x0000001A)	No Computer or Daemon record for the Extractor/Accumulator computer. <i>Action:</i> Check that the correct Repository is being used and that the Adabas System Coordinator Computer and Daemon is still defined.
27 (0x0000001B)	No Action record found for the current archive/recall/search operation. <i>Action:</i> Check that the correct Repository is being used and that the Action record is still defined.
28 (0x0000001C)	No Vault Validation record found. <i>Action:</i> Check that the validation is correctly configured for this vault.
29 (0x0000001D)	No Vault PATH information for this computer. <i>Action:</i> Check that a Vault Path is defined for the Extractor, Accumulator and ADR Service computers.

Subcode	Meaning
30 (0x0000001E)	<p>Attempt to recall an archive using Extractor/Accumulator computers that not sharing the same Repository.</p> <p><i>Action:</i> Extractor/Accumulator computers for a recall must share the same Repository.</p>
31 (0x0000001F)	<p>No Plan record found for the current archive/recall/search operation.</p> <p><i>Action:</i> Check that the correct Repository is being used and that the Plan record is still defined.</p>
32 (0x00000020)	<p>Archive failed due to invalid/unsupported Extractor settings.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
33 (0x00000021)	<p>Archive failed due to invalid/unsupported Transfer settings.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
34 (0x00000022)	<p>Archive failed due to invalid/unsupported Accumulator settings.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
35 (0x00000023)	<p>Recall failed due to invalid or unsupported Extractor settings.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
36 (0x00000024)	<p>Recall failed due to invalid or unsupported Transfer settings.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
37 (0x00000025)	<p>Recall failed due to invalid or unsupported Accumulator settings.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
38 (0x00000026)	<p>Extractor terminated because the Accumulator is not active.</p> <p><i>Action:</i> Check the response and subcode for the Accumulator in Current or Completed Activities.</p>
39 (0x00000027)	<p>Accumulator timed-out waiting for the Extractor.</p> <p><i>Action:</i> Check the response and subcode for the Extractor in Current or Completed Activities.</p>
40 (0x00000028)	<p>Message protocol error/incompatibility.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>

Subcode	Meaning
41 (0x00000029)	Message protocol error/incompatibility. <i>Action:</i> Contact your Software AG technical support representative.
42 (0x0000002A)	Message protocol error/incompatibility. <i>Action:</i> Contact your Software AG technical support representative.
43 (0x0000002B)	Message protocol error/incompatibility. <i>Action:</i> Contact your Software AG technical support representative.
44 (0x0000002C)	Message protocol error/incompatibility. <i>Action:</i> Contact your Software AG technical support representative.
45 (0x0000002D)	Timeout waiting for lock on archive in Vault. <i>Action:</i> Retry the operation and/or check for competing operations.
46 (0x0000002E)	Version mismatch between Data Archiving for Adabas runtime and Vault contents. <i>Action:</i> Contact your Software AG technical support representative.
47 (0x0000002F)	Invalid/corrupt archive in Vault. <i>Action:</i> Contact your Software AG technical support representative.
48 (0x00000030)	Archive in Vault contains data not supported by this version of the Data Archiving for Adabas runtime. <i>Action:</i> Contact your Software AG technical support representative.
49 (0x00000031)	Archive size would exceed limit. <i>Action:</i> Contact your Software AG technical support representative.
50 (0x00000032)	Invalid/unsupported Vault operation. <i>Action:</i> Contact your Software AG technical support representative.
51 (0x00000033)	Archive does not exist in Vault. <i>Action:</i> Contact your Software AG technical support representative.
52 (0x00000034)	Vault path does not exist.

Subcode	Meaning
	<i>Action:</i> Check that the Vault Path defined for the Extractor, Accumulator and ADR Service computers is correct.
53 (0x00000035)	Access denied to Vault Path. <i>Action:</i> Check that the Extractor, Accumulator and ADR Service computers have the correct filesystem permissions for the Vault Path.
54 (0x00000036)	Logical error manipulating Vault contents. <i>Action:</i> Contact your Software AG technical support representative.
55 (0x00000037)	Extractor/Accumulator failed to load. <i>Action:</i> Check the response and subcode for the Extractor/Accumulator in Pending, Current and Completed Activities.
56 (0x00000038)	Extractor/Accumulator failed to load. <i>Action:</i> Contact your Software AG technical support representative.
57 (0x00000039)	Length of compressed record exceeds limit. <i>Action:</i> Contact your Software AG technical support representative.
58 (0x0000003A)	Length of decompressed record exceeds limit. <i>Action:</i> Contact your Software AG technical support representative.
59 (0x0000003B)	Cannot determine the default codepage for the system. <i>Action:</i> Contact your Software AG technical support representative.
60 (0x0000003C)	Invalid/unsupported codepage specified for archive or recall. <i>Action:</i> Check that the codepage specified for in the Extractor/Accumulator settings in the Action or recall request.
61 (0x0000003D)	'Use default' codepage specified for archive or recall and there is no default UES AMODE= setting for the database. <i>Action:</i> Specify the codepage explicitly or configure the default AMODE= setting for the database.
62 (0x0000003E)	No Search record found. <i>Action:</i> Check that the correct Repository is being used and that the Search Record is still defined for the Action.

Subcode	Meaning
63 (0x0000003F)	Cannot search archive because the data was not archived in compressed format. <i>Action:</i> Contact your Software AG technical support representative.
64 (0x00000040)	Invalid search (search buffer). <i>Action:</i> Contact your Software AG technical support representative.
65 (0x00000041)	Invalid search (value buffer). <i>Action:</i> Contact your Software AG technical support representative.
66 (0x00000042)	Value buffer for search could not be converted from the UI codepage to the codepage of the archived data. <i>Action:</i> Contact your Software AG technical support representative.
67 (0x00000043)	'Use default' codepage specified for archive or recall and there is no default UES WMODE=setting for the database. <i>Action:</i> Specify the codepage explicitly or configure the default WMODE= setting for the database.
68 (0x00000044)	Task already locked. <i>Action:</i> Contact your Software AG technical support representative.
69 (0x00000045)	License file is missing. <i>Action:</i> Contact your Software AG technical support representative.
70 (0x00000046)	License key is invalid. <i>Action:</i> Contact your Software AG technical support representative.
71 (0x00000047)	License has expired. <i>Action:</i> Contact your Software AG technical support representative.
72 (0x00000048)	License is for a different operating system. <i>Action:</i> Contact your Software AG technical support representative.
73 (0x00000049)	License is for a different product. <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
74 (0x0000004A)	License is for a different version. <i>Action:</i> Contact your Software AG technical support representative.
75 (0x0000004B)	Functionality restricted, Community edition. <i>Action:</i> License file required for full functionality.
76 (0x0000004C)	No license file found. <i>Action:</i> Contact your Software AG technical support representative.
77 (0x0000004D)	Duplicate archive identifier detected in the Vault. <i>Action:</i> Contact your Software AG technical support representative.
78 (0x0000004E)	Filename conflict detected in the Vault. <i>Action:</i> Contact your Software AG technical support representative.
79 (0x0000004F)	Some or all of the data for an archive is missing from the Vault. <i>Action:</i> Contact your Software AG technical support representative.
80 (0x00000050)	Vault or archive damaged. <i>Action:</i> Contact your Software AG technical support representative.
81 (0x00000051)	ADR plug-in library could not be loaded. <i>Action:</i> Contact your Software AG technical support representative.
82 (0x00000052)	Incompatible ADR plug-in library. <i>Action:</i> Contact your Software AG technical support representative.
83 (0x00000053)	Occurrence 'N' cannot be specified for a PE/MU LOB field in an Extractor Filter (Open Systems only). <i>Action:</i> Correct the format buffer in the Extractor Filter Settings.
84 (0x00000054)	An Extractor Filter must contain at least one non-LOB field. <i>Action:</i> Correct the format buffer in the Extractor Filter Settings.
85 (0x00000055)	The data being archived or recalled contains LOB fields but no LOB file number has been specified.

Subcode	Meaning
	<i>Action:</i> Specify a LOB file number, for recalls set in the recall settings and for archive set in the Accumulator settings in the Action.
86 (0x00000056)	License file does not provide the Price Units required by the system. <i>Action:</i> Contact your Software AG technical support representative.
87 (0x00000057)	License file does not provide the Price Quantity required by the system. <i>Action:</i> Contact your Software AG technical support representative.
88 (0x00000058)	License file does not provide Extended Rights. <i>Action:</i> Contact your Software AG technical support representative.
89 (0x00000059)	The file size of the archive file checked by the validation process is incorrect. <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
90 (0x0000005A)	The number of records in the archive file checked by the validation process is incorrect. <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
91 (0x0000005B)	The check sum for the archive file checked by the validation process is incorrect. <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
92 (0x0000005C)	The lengths of the records in the archive file checked by the validation process are incorrect. <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
93 (0x0000005D)	License file does not provide Archive to Vault required by the system. <i>Action:</i> Contact your Software AG technical support representative.
94 (0x0000005E)	License file does not provide Transfer to Adabas required by the system.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
95 (0x0000005F)	License file does not provide Delete from Adabas required by the system. <i>Action:</i> Contact your Software AG technical support representative.
96 (0x00000060)	Inconsistency in join data for archive. <i>Action:</i> Contact your Software AG technical support representative.
97 (0x00000061)	Inconsistent object/archive identifiers for archive. <i>Action:</i> Contact your Software AG technical support representative.
98 (0x00000062)	File list for action does not match the archive data. <i>Action:</i> Contact your Software AG technical support representative.
99 (0x00000063)	Archive identifier does not match API data. <i>Action:</i> Contact your Software AG technical support representative.
100 (0x00000064)	Group, plan or name of action does not match API data. <i>Action:</i> Contact your Software AG technical support representative.
101 (0x00000065)	File list for action does not match API data. <i>Action:</i> Contact your Software AG technical support representative.
102 (0x00000066)	Duplicate activity encountered. <i>Action:</i> Delete activity from Activities List and rerun.
103 (0x00000067)	Related file record is missing. <i>Action:</i> Contact your Software AG technical support representative.
104 (0x00000068)	Recall target record is missing. <i>Action:</i> Contact your Software AG technical support representative.
105 (x00000069)	Recall target information is not valid. <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
106 (x0000006A)	Maximum number of related files exceeded. <i>Action:</i> Contact your Software AG technical support representative.
107 (x0000006B)	Maximum number of transfer destinations exceeded. <i>Action:</i> Contact your Software AG technical support representative.
108 (x0000006C)	Transfer destination not defined. <i>Action:</i> Contact your Software AG technical support representative.
109 (x0000006D)	Maximum number of related files or transfer destinations exceeded. <i>Action:</i> Contact your Software AG technical support representative.
110 (x0000006E)	Invalid related file. <i>Action:</i> Contact your Software AG technical support representative.
111 (x0000006F)	Invalid transfer destination. <i>Action:</i> Contact your Software AG technical support representative.
112 (0x00000070)	Archive, recall or search failed. <i>Action:</i> Check the response and subcode for the Extractor/Accumulator in Completed Activities.
113 (0x00000071)	Archive, recall or search incomplete. <i>Action:</i> Records have been skipped due to contention or errors.
114 (0x00000072)	Invalid settings specified for file in action. <i>Action:</i> Contact your Software AG technical support representative.
115 (0x00000073)	Recall configuration records inconsistent. <i>Action:</i> Contact your Software AG technical support representative.
116 (0x00000074)	Recall configuration records inconsistent. <i>Action:</i> Contact your Software AG technical support representative.
117 (0x00000075)	API library is not installed.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
118 (0x00000076)	API library could not be loaded. <i>Action:</i> Contact your Software AG technical support representative.
119 (0x00000077)	Entry-point symbol missing from API library. <i>Action:</i> Contact your Software AG technical support representative.
120 (0x00000078)	Wrong version of API library. <i>Action:</i> Contact your Software AG technical support representative.
121 (0x00000079)	Fault detected in API library. <i>Action:</i> Contact your Software AG technical support representative.
122 (0x0000007A)	API library is missing. <i>Action:</i> Contact your Software AG technical support representative.
123 (0x0000007B)	No data returned by API. <i>Action:</i> Contact your Software AG technical support representative.
124 (0x0000007C)	Incorrect API parameters specified by user. <i>Action:</i> Contact your Software AG technical support representative.
125 (0x0000007D)	Memory allocation failed in API. <i>Action:</i> Contact your Software AG technical support representative.
126 (0x0000007E)	Internal API error. <i>Action:</i> Contact your Software AG technical support representative.
128 (0x00000080)	Incorrect parameter passed to API. <i>Action:</i> Contact your Software AG technical support representative.
129 (0x00000081)	API notification failed (state inconsistent). <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
130 (0x00000082)	API library name is too long. <i>Action:</i> Reduce the length of the API library name.
131 (0xhhhh0083)	Error occurred while processing the Extraction Syntax. An extended error code (identified by hhhh) may also be reported for subcode 131. <i>Action:</i> Check the Extraction Syntax and if the error persists contact your Software AG technical support representative providing the full subcode value and the Extraction Syntax being used.
132 (0x00000084)	No dynamic extraction object code exists <i>Action:</i> Ensure that you have successfully saved and compiled your dynamic extraction syntax.
133 (0x00000085)	Duplicate Related file record with differing scopes. <i>Action:</i> Contact your Software AG technical support representative.
134 (0x00000086)	API To-Do list locked, it is already in use by another process. <i>Action:</i> Ensure that only one application/process accesses a To-Do list at any one time.
135 (0x00000087)	Extractor data targets do not match those in the Repository. <i>Action:</i> Contact your Software AG technical support representative.
136 (0x00000088)	Extractor/Accumulator was terminated unexpectedly or cancelled by the user. <i>Action:</i> Check the response and subcode for the Extractor/Accumulator in Pending, Current and Completed Activities.
137 (0x00000089)	Accumulator terminated because the Extractor is not active. <i>Action:</i> Check the response and subcode for the Extractor in Current Activities or Recently Completed.
138 (0x0000008A)	An archive activity could not be resumed/restarted because the FDT of one of the Source Files has been changed since the activity was paused/failed. <i>Action:</i> Contact your Software AG technical support representative.
139 (0x0000008B)	An archive activity could not be resumed/restarted because the Codepage setting for a Source File or the AMODE/WMODE

Subcode	Meaning
	<p>settings for the associated database have been changed since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
140 (0x0000008C)	<p>An archive activity could not be resumed/restarted because the Computer defined for the Extractor or Accumulator has been changed since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
141 (0x0000008D)	<p>An archive activity could not be resumed/restarted because the Source or Target File definitions for the Action have been changed since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
142 (0x0000008E)	<p>The Extractor was unable to read the FCB of one of the Source Files.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
143 (0x0000008F)	<p>The FCB of the Source Files is in a format not recognised by the Extractor.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
144 (0x00000090)	<p>An archive activity could not be resumed/restarted because one of the Source Files has been reloaded since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
145 (0x00000091)	<p>An archive activity could not be restarted because the archive could not be validated, the repair was unsuccessful.</p> <p><i>Action:</i> Review the meaning of any log messages written at the time of the failure and, if necessary, contact your Software AG technical support representative.</p>
146 (0x00000092)	<p>An archive activity could not be validated/restarted because one of the archive file segments is missing.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
147 (0x00000093)	<p>Invalid archive identifier.</p>

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
148 (0x00000094)	Length mismatch detected whilst updating archive file record. <i>Action:</i> Contact your Software AG technical support representative.
149 (0x00000095)	No Vault record found. <i>Action:</i> Check that the Vault defined for the Plan or Action exists.
150 (0x00000096)	The ADR Service does not support the granularity setting configured for the Vault. <i>Action:</i> Contact your Software AG technical support representative.
151 (0x00000097)	Vault path does not exist. <i>Action:</i> Check that the Vault Path defined for the Extractor, Accumulator and ADR Service computers are correct.
152 (0x00000098)	An archive activity could not be validated/restarted because too many archive file segments exist. <i>Action:</i> Contact your Software AG technical support representative.
153 (0x00000099)	Timed-out whilst caching Vault content on local Computer. <i>Action:</i> Contact your Software AG technical support representative.
154 (0x0000009A)	Vault path does not exist. <i>Action:</i> Check that the Vault Path defined for the Extractor, Accumulator and ADR Service computers are correct.

Category 7 subcodes:

Subcode	Meaning
0xhhhh7004	An error has occurred whilst accessing a Vault where hhhh is the operating system error code. Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes). If the cause of the error is not apparent, contact your Software AG technical support representative.
0xhhhh700B	An error has occurred whilst writing to a Vault where hhhh is the operating system error code.

Subcode	Meaning
	<p>Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).</p> <p>If the cause of the error is not apparent, contact your Software AG technical support representative.</p>

Category A subcodes:

Subcode	Meaning
0xhhhhA001	<p>A TCP/IP error has occurred where hhhh is the operating system error code.</p> <p>Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).</p> <p>If the cause of the error is not apparent, contact your Software AG technical support representative.</p>
0xhhhhA002	<p>A DNS error has occurred where hhhh is the operating system error code.</p> <p>Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).</p> <p>If the cause of the error is not apparent, contact your Software AG technical support representative.</p>

Response 249

Origin

Mainframe and open systems

Explanation

Mainframe Systems

Adabas Vista uses a default Adabas response code 249 for all processing errors. This response code can be changed by using the Job Parameter function of Adabas Vista Online Services.

The following table describes each of the subcodes possible for response code 249. Adabas Vista issues these subcodes as well to provide additional information.

Subcode	Meaning
1	<p>The partitioned file concurrency limit has been reached.</p> <p><i>Action:</i> Increase the partitioned file concurrency limit using the File Partitioning function of Adabas Vista Online Services.</p>
6	<p>The job parameter <code>Enable Multiple Updates</code> is set to NO. After updating one database, the user attempted to update a second database in the same transaction.</p> <p><i>Action:</i> Review the job parameter <code>Enable Multiple Updates</code> in the Job Parameter function of Adabas Vista Online Services.</p>
8	<p>This partitioned file has been defined with an unsupported Partitioning Field. The Partitioning Field may not be:</p> <ul style="list-style-type: none"> ■ A multiple value field ■ An item in a periodic group ■ A field with format F, G, or W ■ A variable length field ■ A field with the long alphanumeric (LA) attribute ■ A SUPDE or SUPFN of format Alphanumeric with at least one parent of format W <p><i>Action:</i> Review the partitioning criteria.</p>
9	<p>One of the following errors was detected while processing a partitioned file:</p> <ul style="list-style-type: none"> ■ A distributed access can not be successfully processed due to the client encoding being incompatible with Vista's record collating process. ■ A command can not be successfully processed due to the client encoding being incompatible with the defined partition criteria. <p><i>Action:</i> Review the use of client encodings.</p>
10	<p>One of the following errors was detected in the Adabas search buffer while processing a partitioned file:</p> <ul style="list-style-type: none"> ■ the specified field is not in the Adabas FDT. ■ an S or N operator is used incorrectly. ■ a superdescriptor with a variable-length parent field is not allowed. ■ coupled file syntax is not allowed. ■ the value1 operator (EQ, GE, GT, etc.) is unknown. ■ a connecting operator (D, O, R, etc.) is unknown. ■ a command ID enclosed in parentheses is not allowed ■ a memory request failed. ■ collation descriptors are not supported.

Subcode	Meaning
	<i>Action:</i> Review and correct the application program.
12	<p>Runtime controls have been changed dynamically without the client previously resetting all Adabas context to null. In this situation Vista is forced to discard all Adabas context and alert the application with this response.</p> <p><i>Action:</i> Avoid this response by ensuring the client has no Adabas context prior to the runtime controls being changed.</p>
14	<p>One of the following errors was detected in the Adabas format or record buffer while processing a update/store for a partitioned file:</p> <ul style="list-style-type: none"> ■ The partitioning field specified in the format buffer could not be located in the Adabas FDT (N1 and N2). ■ An Adabas field specified in the format buffer could not be located in the Adabas FDT (N1, N2 and A1). ■ The partitioning field value specified in the record buffer is inconsistent with the defined partitioning criteria for the file (N1 and N2). ■ The partitioning field value specified in the record buffer is inconsistent with the partition criteria defined to the partition identified by the ISN in the Adabas control block (N2 only). ■ The partitioning field value specified in the record buffer is null and the Store Control Option is set to 2 (N1 only). ■ The partitioning field/value has not been specified and no target partition has been identified (N1 and N2). <p><i>Action:</i> Review application program and partitioning criteria.</p>
15	<p>The partitioning field value specified in the record buffer of the A1 command is inconsistent with the partition criteria defined to the partition identified by the ISN in the Adabas control block.</p> <p>Such an update requires the relocation of the ISN to another partition, which is not allowed.</p> <p><i>Action:</i> Review the application program. Use a delete and store as an alternative.</p>
16	<p>An ISN has been detected that is invalid for one of the following reasons:</p> <ul style="list-style-type: none"> ■ The partition identifier extracted from the Adabas Vista ISN is not consistent with any partition defined to the partitioned file. ■ The Adabas ISN read from a partition is greater than the TOPISN value defined for the partition. ■ An attempt to store a record has resulted in an Adabas ISN greater than the TOPISN value defined for the partition.

Subcode	Meaning
	<ul style="list-style-type: none"> ■ (Extreme partitioned files only) The number of partitions is greater than the limit of 255. ■ (Extreme partitioned files only) The application-supplied ISN is no longer associated with this partitioned file. <p><i>Action:</i> For Standard partitioned files, review the application program, the partition definitions, and check TOPISN setting. For Extreme partitioned files, review the application's use of the supplied ISN.</p>
21	<p>One of the following errors occurred while processing Distributed Lock Mode (DLM) against a partitioned file:</p> <ul style="list-style-type: none"> ■ Prefetch/multifetch options on a distributed access L6 command are not allowed for DLM options 2 and 3. ■ DLM option 4 is specified and a distributed access S4 or L6 command was issued. ■ DLM option 3 is specified and the distributed access data integrity check failed. <p><i>Action:</i> Review the application and use of the DLM option.</p>
22	<p>The client runtime control for CL convergence is set to reject when your Vista rules used during runtime result in activity for multiple source databases converging into a single target database. With this setting the CL command cannot be processed by Vista because it would result in the loss of cursor/transaction activity in the target database for source database(s) beyond the one indicated in this CL command which would result in unpredictable results and errors if those other source databases are used further.</p> <p><i>Action:</i> Review the application program and the convergent translation/partitioning rules or alter the CL convergence runtime control setting.</p>
25	<p>One of the following unsupported commands has been issued:</p> <ul style="list-style-type: none"> ■ an S5 command (partitioned files only) ■ a C5 command ■ a BT command with Command Option 2 set to F (any transaction will have been backed out) ■ an L1 command with Command Option 1 or 2 set to F <p><i>Action:</i> Review application program.</p>
28	<p>An update command has been issued to a partitioned file; however, the target partition does not have the option ACCESS=FULL.</p> <p><i>Action:</i> Review application program and partition ACCESS options.</p>

Subcode	Meaning
31	<p>An existing Command ID has been reused after the client's translation context has been modified but this now references a different file, which is an illegal situation and is therefore rejected.</p> <p><i>Action:</i> Review programming practices for changing client contexts.</p>
32	<p>Partitioned files can not be subjected to a change in client context</p> <p><i>Action:</i> Review programming practices for changing client contexts.</p>
36	<p>A session-related memory allocation failed during an inter-system dynamic transaction routing operation, the client session is unable to continue. This sub-code may not indicate an error on this current Adabas command, but it indicates that an internal error has prevented the Vista session continuing successfully.</p> <p><i>Action:</i> Increase the shared memory available.</p>
37	<p>A file-related memory allocation failed during an inter-system dynamic transaction routing operation, the client session is unable to continue using the file. This sub-code may not indicate an error on this current Adabas command, but it indicates that an internal error has prevented the Vista session continuing successfully with one of the files currently being used so Vista is alerting you immediately.</p> <p><i>Action:</i> Increase the shared memory available.</p>
39	<p>An L1 (get next) command was issued but the supplied command ID is not currently active.</p> <p><i>Action:</i> Review application program.</p>
45	<p>An error has occurred during the processing of a distributed L3/L9 command against a partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
50	<p>An A1 command was issued without the H option and the DLM option is set to 1. However, the ISN to be updated has not been previously read by a hold command.</p> <p><i>Action:</i> Review application program and use of DLM option.</p>
51	<p>The number of segmented buffers used by this ACBX call against a Partitioned File is greater than the maximum allowed.</p> <p><i>Action:</i> Reduce the number of segmented buffers.</p>
52	<p>The file parameter Enable ISN Positioning is set to NO and one of the following commands was issued:</p> <ul style="list-style-type: none"> ■ L1 with Command Option 2 set to I

Subcode	Meaning
	<ul style="list-style-type: none"> ■ L2/5 with starting ISN ■ L3/6 with starting ISN ■ Sx with the ISN Lower Limit field specified <p><i>Action:</i> Review application program and the file parameter Enable ISN Positioning.</p>
60	<p>A memory request failed.</p> <p><i>Action:</i> Review the memory availability of the</p> <ul style="list-style-type: none"> ■ host TP system; ■ host operating system; and ■ global common memory pool (BS2000 only; specified in the Adabas System Coordinator group definition).
65	<p>One of the following invalid values was used for a command ID value:</p> <ul style="list-style-type: none"> ■ X'00000000' ■ X'40404040' <p><i>Action:</i> Do not use the above command ID values.</p>
70	<p>Support for the use of this API has been withdrawn.</p> <p><i>Action:</i> Please refer to the currently supported APIs or, alternatively, contact your Software AG technical support representative to discuss your requirements.</p>
72	<p>An ET Data related command has been issued, but the runtime control (see <i>Database Number for ET Data</i>, in the <i>Adabas Vista Parameters</i> manual) is not set to a specific database number and Vista has been unable to establish a target database to satisfy the command.</p> <p><i>Action:</i> Review the runtime control <i>Database Number for ET Data</i>, in the <i>Adabas Vista Parameters</i> manual, to specifically identify the database number to be used.</p>
74	<p>A sequence direction change has been detected during an L3 or L9 command against a Partitioned File whose Command ID sequence has been previously subjected to multifetch.</p> <p><i>Action:</i> Review the program logic.</p>
81	<p>An error has occurred during the processing of an L1 'get next' command against a partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>

Subcode	Meaning
86	<p>The Adabas Vista database process is not installed. It must be installed on all Adabas databases which contain Adabas Vista partitions. This subcode indicates that a database</p> <ul style="list-style-type: none"> ■ is not running with ADARUN VISTA=YES; or ■ is not running Adabas version 7 or above. <p><i>Action:</i> Refer to the Adabas Vista installation procedures.</p>
96	<p>An error has occurred during the parsing of the Format Buffer during the processing of an Ax or Nx command against a partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
106	<p>The configuration for the first-level null definition policy for this target category (mode) is set to reject "null" as the outcome of translation processing.</p> <p><i>Action:</i> Review the null definition policy for the target category (mode) used if you do not wish to receive this error.</p>
107	<p>Translation processing has been configured to disallow redirection to a different target category (mode).</p> <p><i>Action:</i> Remove the redirection rule(s) or review the category adjustment policy for the target category (mode) in use.</p>
108	<p>The configuration for the first-level null definition policy redirects to another target category (mode) which in turn has resulted in a "null" outcome. The second-level null definition policy is set to reject such an outcome.</p> <p><i>Action:</i> Review the translation rules in use to avoid a null result or alter the null definition policies.</p>
109	<p>Translation processing has detected a recursive redirection.</p> <p><i>Action:</i> Review the translation rules in use.</p>
112	<p>An error has occurred during the processing of the current command.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
116	<p>A command has been issued against a partitioned file which has the Shared Partition option set to YES for one or more of its partitions. However, the partitioning field defined does not exist in the Adabas FDT.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>

Subcode	Meaning
117	<p>One of the following errors occurred while processing the record, value, or search buffer:</p> <ul style="list-style-type: none"> ■ A P format field value was not in packed decimal format. ■ A U format field value was not in unpacked decimal format. ■ The attempted format conversion was not possible because of incompatible data formats or other compatibility problems. ■ The field length was zero or not consistent with the field format. <p><i>Action:</i> Check field values for correct formats and lengths.</p>
119	<p>One of the following has occurred:</p> <ul style="list-style-type: none"> ■ Runtime configuration on behalf of this client was unsuccessful and Adabas Vista has been defined as “critical” using the Critical Product Support feature of the Adabas System Coordinator. ■ The Adabas Vista configuration file was not available during an attempt to satisfy an Adabas Vista API request. <p><i>Action:</i> Check the availability of the configuration file.</p> <p>If the client runtime control Error Reporting WTO option is set to YES, this error may be accompanied by an AVI-0017-10 console message.</p>
120	<p>The client previously issued a command to a source file for which Vista was unable to determine the existence of any translation rules due to the configuration file not being available at the time. Subsequently, Vista has detected the availability of the configuration file and has determined the existence of a translation rule for this source file. This subcode is returned the next time the client attempts to access the source file.</p> <p><i>Action:</i> Review the availability of the configuration file.</p>
122	<p>An invalid partitioned file definition has been found in the Adabas Vista configuration file.</p> <p><i>Action:</i> Check the file definition using Adabas Vista Online Services.</p>
123	<p>An invalid translation rule has been found in the Adabas Vista configuration file.</p> <p><i>Action:</i> Check the rule using Adabas Vista Online Services.</p>
124	<p>An error in the record buffer was detected during processing of an OP command.</p>
126	<p>One of the following errors occurred while processing an S8 command:</p> <ul style="list-style-type: none"> ■ An invalid command ID was specified in the Additions 1 field. ■ Different file numbers were detected for ISN lists. ■ An error occurred while processing a subsequent S8 call.

Subcode	Meaning
	<i>Action:</i> Review the application program.
127	<p>One of the following errors occurred while processing an S2 command:</p> <ul style="list-style-type: none"> ■ An invalid sort sequence was specified. ■ An invalid ISN was detected during processing. ■ An error was detected during ISN processing. <p><i>Action:</i> Review the application program.</p>
128	<p>One of the following errors occurred while processing an S9 command:</p> <ul style="list-style-type: none"> ■ The command ID value specified was assigned to another command. ■ An invalid sort sequence was specified. ■ An invalid ISN buffer length was detected. ■ The number of ISNs to be sorted as provided in ISN quantity is equal to 0. ■ The command ID value specified in Additions 4 was not found. ■ An invalid ISN was detected during processing. ■ An error was detected during ISN processing. <p><i>Action:</i> Review the application program.</p>
129	<p>The command limit defined for this source file has been exceeded.</p> <p><i>Action:</i> Review the command limit.</p>
131	<p>A requested file refresh of a partitioned file has failed due to an unexpected Adabas response code. The partitioned file is in a partially refreshed state.</p> <p><i>Action:</i> Review the Adabas response code.</p>
133	<p>One of the following errors occurred whilst processing a direction change during an L9 command sequence:</p> <ul style="list-style-type: none"> ■ A second direction change for this sequence was attempted. ■ A format override cannot be processed. ■ A length override greater than specified in the FDT cannot be processed. ■ A length override has been specified with complex search criteria. <p><i>Action:</i> Review the use of the L9 command and the Adabas Vista restrictions.</p>
134	<p>An S2 command to continue a sequence has been received. The sequence was not started by an S2 command.</p> <p><i>Action:</i> Amend the command sequence to process either all S1 commands, or all S2 commands, as appropriate.</p>
200	ISN quantity is too high on this Sx command.

Subcode	Meaning
	<i>Action:</i> Perform a more specific Sx .
201	<p>One of the following errors occurred while initializing AVIKRN:</p> <ul style="list-style-type: none"> ■ The dynamic load failed. ■ The version is not compatible. <p><i>Action:</i> Check the Adabas Vista installation procedures.</p>
250	<p>ISN error when issuing ACBX style RI shared-hold calls with ACBXCOP3 set to "S" .</p> <p><i>Action:</i> Check ISN usage on shared-hold commands.</p>
305	<p>An error has occurred while attempting to access an Extreme partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
496	<p>The session is not compliant with correct distributed transaction processing. Read <i>Transaction Directives</i>, in <i>Adabas Vista Programming Guidelines</i> for a more detailed explanation of this subcode.</p> <p><i>Action:</i> Adhere to correct distributed transaction processing.</p>
532	<p>This session has not complied with the correct transactional processing behavior when using the discrete file setting.</p> <p><i>Action:</i> Review the discrete file setting and ensure correct transactional processing.</p>
588	<p>For ACBX calls, a conflict with shared hold status option "H" has been detected. The client session is using this option in a conflicting manner during an ET or BT sequence after a commit/backout process has been performed. The transaction outcome is unaffected but records may no longer be in shared hold status.</p> <p><i>Action:</i> Review usage of this option.</p>

Open Systems

In Adabas Vista (open systems) an error occurred during command execution. One of the following subcodes may occur:

Subcode	Meaning
1 (0x0001)	<p>An inconsistency in an internal data structure was detected. This may indicate a code fault within Adabas Vista.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
2 (0x0002)	<p>An inconsistency in an internal data structure was detected. This may indicate a logic error within Adabas Vista.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
3 (0x0003)	<p>The S9 command is not supported on partitioned files.</p> <p><i>Action:</i> Review the program logic.</p>
4 (0x0004)	<p>The F option for an L1 command is not supported on partitioned files</p> <p><i>Action:</i> Review the program logic.</p>
5 (0x0005)	<p>The F option for a BT command is not supported.</p> <p><i>Action:</i> Review the program logic.</p>
6 (0x0006)	<p>The ISN buffer for a BT or ET command with the M option is not consistent with ISN Buffer Length in the Adabas control block.</p> <p><i>Action:</i> Review the program logic.</p>
7 (0x0007)	<p>The maximum number of active command ID values has been reached.</p> <p><i>Action:</i> Review the program logic.</p>
8 (0x0008)	<p>The command ID value specified for TBLES/TBQ (sequential) or TBI (ISN list) command is already in use by a different TBLES/TBQ or TBI command.</p> <p><i>Action:</i> Review the program logic.</p>
9 (0x0009)	<p>Adabas Vista is not compatible with the installed version of Natural, Adabas or Entire Net-Work.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
10 (0x000A)	<p>The definitions for partitioned file do not exist.</p> <p><i>Action:</i> Review the partition definitions in SYSAVI.</p>
11 (0x000B)	<p>The partitioning field does not exist in the FDT.</p> <p><i>Action:</i> Review the partition definitions in SYSAVI.</p>
12 (0x000C)	<p>The field type in the partition definition does not match the field type in the FDT.</p> <p><i>Action:</i> Review the partition definitions in SYSAVI.</p>
13 (0x000D)	<p>The type for the partitioning field is not suitable.</p> <p><i>Action:</i> Review the partition definitions in SYSAVI.</p>

Subcode	Meaning
14 (0x000E)	The format buffer specified for an N1 or N2 command does not contain the partitioning field. <i>Action:</i> Review the program logic.
15 (0x000F)	The value of the partitioning field in the record buffer specified for an N1 or N2 command could not be converted to the standard field length and format. <i>Action:</i> Review the program logic.
16 (0x0010)	The value of the partitioning field in the record buffer specified for an A1 , N1 or N2 command does not correspond to any partition defined for the file. <i>Action:</i> Review the partition definitions in SYSAVI.
17 (0x00011)	The value of the partitioning field in the record buffer specified for an A1 command would require the ISN to be relocated to a different partition. <i>Action:</i> Review the program logic.
18 (0x00012)	The ISN and the value of the partitioning field in the record buffer specified for an N2 command do not correspond to the same partition. <i>Action:</i> Review the program logic.
19 (0x00013)	The license is not valid for this operating system. <i>Action:</i> Contact your Software AG technical support representative.
20 (0x00014)	The license has expired. <i>Action:</i> Contact your Software AG technical support representative.
21 (0x00015)	The license file could not be found. <i>Action:</i> Contact your Software AG technical support representative.
22 (0x00016)	The license key is invalid. <i>Action:</i> Contact your Software AG technical support representative.
23 (0x00017)	The license is for a different version of the product. <i>Action:</i> Contact your Software AG technical support representative.
24 (0x00018)	The license is not for this product. <i>Action:</i> Contact your Software AG technical support representative.
25 (0x00019)	The ISN of a record read from a partition or the ISN of a record stored using an N1 command is too large. <i>Action:</i> Check the settings for the Adabas file to ensure that the ISN values cannot exceed the highest value defined for the partition in SYSAVI.

Response 250

Origin Mainframe and open systems

Explanation On mainframe systems, the ACBX (ACBX) failed validation. The following subcodes are possible:

Subcode	Meaning
1	Unsupported ACBX version
2	ADACBX provided without UBE.
3	ACBX file number > 65,535.
4	Reserved field not zero.
5	ACBX length incorrect

On open systems, a requested function is not yet implemented.

Action On mainframe systems, if subcode 3 occurs, notify your Software AG technical support representative. If any of the other subcodes occur, correct the ACBX specification and rerun.

On open systems, wait for a later version of Adabas.

Response 251

Origin Mainframe and open systems

Explanation On mainframe systems, an error occurred in Adabas cluster processing. Under certain conditions, the Adabas cluster SVC (SVCCLU) component of the ADASVC returns response code 251 in the ACB's response code field, along with a hexadecimal subcode (listed below in decimal) in the low-order (rightmost) two bytes of the Additions 2 field. In the case of an ACBX, the ADASVC returns response code 251 in the ACBX's Response Code (ACBXRSP) field and the subcode in the Error Subcode (ACBXERRC) field.

- If the local SVCCLU detects the condition, the subcode will range from 2 through 30.
- If a remote SVCCLU detects the condition, it will range from 102 through 130.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
2	The remote cluster nucleus to which the user is assigned cannot be accessed.
4	There are no user table entries (UTES) available for use.
5	Internal error. The nucleus specified by an internal command was not found.
7	Internal error. The user was assigned to a remote nucleus by the local system but the remote system found that the nucleus was not active.
9	Internal error. The 28-byte user ID is all zeros.
17	Entire Net-Work is not active.
19	Internal error. Invalid internal command code.
20	Remote nuclei are active; command must be assigned remotely but the remote nuclei are not accepting commands.
21	The remote image to which the user is assigned has no usable nuclei.
22	An attempt was made to assign a user remotely but Entire Net-Work is not active.
25	No system image target
26	System image target changed
27	Internal error.
28	Version mismatch between the PLXCB and the SVCCLU part of the ADASVC.
29	Probably, you used a NUCID value from a restricted range. Otherwise, this is an internal error. <i>Action:</i> Ensure that the NUCID assignments are valid.
30	More than 32 NUCIDs were detected for the same SVC/DBID combination. <i>Action:</i> Reduce the number of NUCIDs on the SVC/DBID to 32.
41	An invalid PLXCB dataspace ALET was detected during command initiation. The PLXCB is unusable. The ALET has been removed from the IDTH prefix.
45	An invalid PLXCB dataspace ALET was detected during command completion. The PLXCB is unusable. The ALET has been removed from the IDTH prefix.
43	An invalid PLXCB dataspace header was detected. The PLXCB is unusable. The ALET has been removed from the IDTH prefix.
44	A program check occurred while using the PLXCB dataspace ALET. The PLXCB is unusable. The ALET has been removed from the IDTH prefix. Under z/OS a software LOGREC (EREP) record was created.

On open systems, an invalid utility call - versions conflict occurred.

Action

For internal errors on mainframe systems, contact your Software AG technical support representative. For all other mainframe errors except as noted, contact your systems administrator.

On open systems, check whether the utilities and database nuclei are of the same version. Contact your Software AG technical support representative for assistance.

Response 252

Origin

Mainframe and open systems

Explanation

On mainframe systems, an error occurred during Adabas SVC processing (post error).

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, an invalid subroutine call - coding error occurred. This response may also be returned on setting the Entire Net-Work timeout via Adaset Timeout if Entire Net-Work is not correctly installed.

Action

For open systems, contact your Software AG technical support representative.

Response 253

Origin

Mainframe and open systems

Explanation

On mainframe systems, an error occurred processing a buffer.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

The following subcodes are possible:

Subcode	Meaning
0	Buffer length 0 (ACB user only)
1	Format buffer address zero
2	Record buffer address zero
3	Search buffer address zero
4	Value buffer address zero
5	ISN buffer address zero
6	User information buffer address zero
7	Performance buffer address zero
8	Multifetch buffer address zero
9	Unsupported ABD buffer type
10	Attached buffer overrun
11	Unsupported ABD version
12	ACBX not accepted by target
13	Unable to convert ACBX to ACB

Subcode	Meaning
14	ALET value not permitted
15	Unable to process 64-bit buffer address
16	Invalid buffer location indicator
17	Logic error locating ABD
18	More than 65,535 ABDs of any single type.
19	Reserved field not zero
20	ADABDX length incorrect
1xx	An error occurred attempting to allocate a Pause Element. The subcode is 100 (decimal) added to the return code from the z/OS IEAVAPE service. <i>Action:</i> Refer to IBM z/OS documentation for IEAVAPE for an explanation of its return code. Contact your Software AG support representative for assistance.
2xx	An error occurred attempting to pause using a Pause Element. The subcode is 200 (decimal) added to the return code from the z/OS IEAVPSE service. <i>Action:</i> Refer to IBM z/OS documentation for IEAVPSE for an explanation of its return code. Contact your Software AG support representative for assistance.

On open systems, the system file is not loaded or inconsistent.

Action

For mainframe systems, subcodes 10 and 17 are internal logic errors; notify your Software AG support representative. For all other subcodes, correct the buffer specification error and rerun.

On open systems, check the system files by running ADAVFY.

Response 254

Origin

Mainframe systems only

Explanation

A validation error occurred during command completion processing while attempting to return results to the caller.

One of the following has occurred:

- An internal error occurred during processing of an attached buffer (buffer overflow)
- The CT parameter limit was exceeded. Message ADAM93 (or a similar message) is printed or displayed on the console.

If the CT parameter limit was exceeded, the nucleus terminated the user, generated the equivalent of a BT command internally, released the CQE and attached buffer space, and issued ADAM93 (or a similar message).

If the user was not terminated, the subcode in the right-most two bytes of the ACB's Additions 2 field or the subcode in the ACBX's Error Subcode (ACBXERRC) field describes the failed validity check.

- If you are running with Entire System Server, the TIME parameter limit was exceeded. Message ADAM93 (or a similar message) displays on the console.

Note: If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
1	UBCQEX is less than or equal to zero
2	UBCQEX is greater than CQHNCQES
3	CQEFLAG is not equal to CQEFAB plus CQEFW16
4	CQEAUB is not equal to A'UB
5	CQEAUPL is not equal to A'APL
6	The low-order 6 bytes of CQECKSUM does not equal UBCKSUM
7	CQE was timed out
8	An inconsistency in the CQE such as the following: <ul style="list-style-type: none"> ■ The CQE was unexpectedly taken by another call . ■ The user buffer (UB) is not receiving expected user information. ■ The target move data length is inconsistent.
9	Record buffer overflow
10	ISN buffer overflow
11	Inconsistent format buffer length
12	Inconsistent search buffer length
13	Inconsistent value buffer length
14	Inconsistent user buffer length
15	Invalid attached buffer ABD index (internal logic error)
16	Buffer overflow; see ACBXERRD and ACBXERRE

Action

Ensure that the caller's control structures and parameters are not altered while the command is being processed. If you are unable to resolve the error, notify your Software AG support representative.

Response 255**Origin**

Mainframe and open systems

Explanation

On mainframe systems, all attached buffers were allocated at the time the command was processed. Buffer allocation "high water marks" may not reflect this condition when no buffer allocation occurs.

Note: A Response 255 may also be issued by Entire Net-Work and in these circumstances the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, the Adabas command could not be processed because not enough Adabas nucleus or operating system resources are available. The value in the first two bytes of the Additions 2 field indicates the reason (2-byte binary format).

Action

On open systems, perform the following actions, based on the subcode:

Subcode	Action
1	No space is available for the attached buffers. Increase the LAB (length of attached buffers) parameter.
2	No space is available in the client ID table. Increase the NCL (number of client threads) parameter.
3	Message queue generation failed. Increase the corresponding operating system parameters (please refer to the Adabas open systems installation documentation for further information).
4-6	An internal error occurred; an unexpected response code was received from a system function. Contact your Software AG technical support representative.
7 (only with ADALNKX)	The ADAMPLNK executable could not be loaded. Make this module available.
8	No space is available for extended attached buffers. Increase the value of the LABX (length of extended attached buffers) parameter.

