

# **Entire Net-Work Client Installation and Administration Guide**

## **Messages and Codes**

Version 1.8.1

October 2021

This document applies to Entire Net-Work Client Version 1.8.1 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2004-2021 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG.

**Document ID: WCL-OWCPOSMESSAGES-181-20210428**

## Table of Contents

Messages and Codes Reference .....	v
1 About this Documentation .....	1
Document Conventions .....	2
Online Information and Support .....	2
Data Protection .....	3
2 Adabas Response Codes .....	5
3 Entire Net-Work LUW Messages .....	169
4 XTS* - Software AG Internal Transport Subsystem Messages .....	231
Warnings .....	232
Errors .....	234
Generic TCP/IP Messages .....	248



---

# Messages and Codes Reference

---

This document explains the Entire Net-Work messages and the Entire Net-Work and Adabas response codes you might receive during Entire Net-Work processing. It is intended for all users of Entire Net-Work.

This document is organized as follows:

<i>Response Codes</i>	Explains the possible response codes you might receive during Adabas and Entire Net-Work processing.
<i>Entire Net-Work Open System Messages</i>	Explains the possible Entire Net-Work LUW messages you might receive during its processing.
<i>Software AG Internal Transport Subsystem Messages</i>	Explains the possible internal transport subsystem messages you might receive during its processing.

For information about Adabas response codes, refer to your Adabas documentation. Adabas documentation can be found on the Adabas documentation CD.

---

# 1 About this Documentation

---

▪ Document Conventions .....	2
▪ Online Information and Support .....	2
▪ Data Protection .....	3

## Document Conventions

---

Convention	Description
<b>Bold</b>	Identifies elements on a screen.
Monospace font	Identifies service names and locations in the format <i>folder.subfolder.service</i> , APIs, Java classes, methods, properties.
<i>Italic</i>	Identifies:  Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources.
Monospace font	Identifies:  Text you must type in. Messages displayed by the system. Program code.
{ }	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.
	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the   symbol.
[ ]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [ ] symbols.
...	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...).

## Online Information and Support

---

### Software AG Documentation Website

You can find documentation on the Software AG Documentation website at <https://documentation.softwareag.com>.

### Software AG Empower Product Support Website

If you do not yet have an account for Empower, send an email to [empower@softwareag.com](mailto:empower@softwareag.com) with your name, company, and company email address and request an account.

Once you have an account, you can open Support Incidents online via the eService section of Empower at <https://empower.softwareag.com/>.

You can find product information on the Software AG Empower Product Support website at <https://empower.softwareag.com>.

To submit feature/enhancement requests, get information about product availability, and download products, go to [Products](#).

To get information about fixes and to read early warnings, technical papers, and knowledge base articles, go to the [Knowledge Center](#).

If you have any questions, you can find a local or toll-free number for your country in our Global Support Contact Directory at [https://empower.softwareag.com/public\\_directory.aspx](https://empower.softwareag.com/public_directory.aspx) and give us a call.

### **Software AG TECHcommunity**

You can find documentation and other technical information on the Software AG TECHcommunity website at <http://techcommunity.softwareag.com>. You can:

- Access product documentation, if you have TECHcommunity credentials. If you do not, you will need to register and specify "Documentation" as an area of interest.
- Access articles, code samples, demos, and tutorials.
- Use the online discussion forums, moderated by Software AG professionals, to ask questions, discuss best practices, and learn how other customers are using Software AG technology.
- Link to external websites that discuss open standards and web technology.

## **Data Protection**

---

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

---

## 2 Adabas Response Codes

---

After each Adabas command is processed, a response code is returned in bytes 11 and 12 of the ACB or in the ACBX. Some response codes also return a subcode in the rightmost two bytes of the ACB's Additions 2 field (offset 45-48) or in the ACBX's Error Subcode (ACBXERRC) field (offset 115-116). This section describes those response codes and subcodes.



**Note:** Proprietary functions of Adabas may also return response codes and subcodes, some of which are not described here. Refer to the documentation for those functions for more information.

Response code 0 indicates that the Adabas command was processed successfully; any other response code is returned as a result of an error during command processing.

All Adabas commands resulting in a response code other than 0 (ADARSP000), 1 (ADARSP001), and 145 (ADARSP145) restore all Adabas control block fields except the response code field (see the Adabas Command Reference documentation) to the contents the fields held at the beginning of command execution.

For internal errors, contact your Adabas technical support representative.

### Response 0

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	The command was executed successfully.

**Response 1**

**Origin** Mainframe and open systems

**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
1	An online SAVE operation cannot be executed without the nucleus' PLOG.
2	The selected record is not allowed.
3	S2 command did not have enough space.
4	S2/S9 internal program error.
5	System was not in save status at the end of an online ADASAV.

**Note:** When one of the subcodes 2-4 is present, the cause could be an Sx command using security-by-value that found at least one ISN.

**Open Systems**

An ISN list could not be sorted as a result of an excessive number of resulting ISNs, or because during a non-descriptor search a value larger than the corresponding field length in the FDT was found, or because the ISN quantity returned does not correspond with the actual number of records found.

For an S9 command, this response indicates that there is no space available for additional temporary working space. For an S2 command, this response is only a warning and the S2 becomes an S1.

**Action** The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

Increase the ADARUN LS parameter value.

**Open Systems**

Provide sufficient disk space for temporary working space or adapt the FDT to the real field length.

**Response 2****Origin**

Mainframe and open systems

**Explanation**

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

This response code can only occur with a BT, ET or RI command. The BT, ET or RI command executes successfully. One of the following has occurred, depending on the subcode:

Subcode	Meaning
1	Adabas attempted to hold an ISN already being held by another user.
2	The number of ISNs as specified in the ISN buffer was too large compared to the ISN buffer length (ET or BT command with the M option).
4	ISN is not on hold during multifetch ET/BT. ET/BT has successfully executed the ISNs so far released. The remaining ISNs are still on hold.
5	An RI command with ISN=0 could not release from hold status all records held by the user, as requested, because one or more records had been updated earlier in the same transaction. Updated records cannot be released from hold status prior to transaction end. All records that had not been updated have been released from hold status.

**Open Systems**

The required function has not been executed completely. For an OP command with command option 2 = E or for an RE command, the specified record buffer length was shorter than the length of the ET data read. The record buffer has been truncated.

For an A1//N1/N2 command, a descriptor value with the TR option is larger than 1144 bytes. In this case, only the first 1144 bytes are stored in the index. Search operations for truncated values may be inexact since only the first 1144 bytes are evaluated. The first 2 bytes of the Additions 2 field contain the number of descriptor values truncated, the third and fourth bytes contain the field name of the descriptor value that is truncated.

For an S1/S2/S4/S9 command, the resulting ISN list may not represent the exact result: this is because the search values and the values in the database were truncated after 1144 bytes during the search operation of an S1/S2/S4 command and during the sort operation of an S2/S9 command.

**Action**

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Open Systems**

For an OP or RE command, increase the record buffer length or ignore the warning.

For an S1/S2/S4/S9 command, either perform a post-selection using the complete field values, perform your own sort operation using the complete field values, or ignore the warning.

**Response 3**

**Origin**

Mainframe and open systems

**Explanation**

One of the following has occurred:

- An end-of-file or end-of-list condition was detected.
- A program tried to read or change a multicient file's record using either a blank or incorrect-length owner ID, or an owner ID that is not allowed for the record.

The following are some possible subcodes:

Subcode	Meaning
1	An end-of-file or end-of-list condition was detected (L3/L6 on a non-expanded file).
4	End of LOB value reached. An attempt was made to read a LOB value segment that begins after the end of the value. This response code/subcode is given to an L1/L4 command with Command Option 2 set to L if the ISN Lower Limit value is greater than or equal to the length of the LOB value being read.
66	A program tried to read or change a multicient file's record using either a blank or incorrect-length owner ID, or an owner ID that is not allowed for the record.
249	Adabas Vista has determined that no data is available to satisfy this command due to one of the following reasons: <ul style="list-style-type: none"> <li>■ A partitioned file end-of-file or end-of-list condition was detected.</li> <li>■ None of the partitions were available/online and all of them have the file parameter <code>Critical</code> set to NO.</li> </ul> <p><i>Action:</i> No action is required.</p>

**Response 4**

**Origin**

Mainframe systems

**Explanation**

The internal Adabas TRS storage directory is full.

**Action**

Free some of the active queries.

**Response 7**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	A complex search command was rejected because it was estimated that it would exceed the maximum search time TLSCMD.

**Response 8**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	The current user's command was interrupted to prevent a Work overflow because of a pending backout operation.
<b>Action</b>	The value specified for the LP parameter might have to be increased.

**Response 9**

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

A subcode indicating the specific cause and action for this response code appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field. The following are the subcodes and their meanings:

Subcode	Meaning
1	The user was backed out because the hold queue was full  <i>Action:</i> Set the number of hold queue elements (ADARUN NH parameter) higher, or tune the application to issue more frequent ET commands.
2	The transaction time limit (TT) has been exceeded, and the transaction was backed out.  <i>Action:</i> Correct the cause of the timeout, then restart the transaction.
3	One of the following is the case: <ul style="list-style-type: none"> <li>■ The transaction non-activity time limit (TNAE, TNAX, or TNAA) has been exceeded.</li> <li>■ The user was stopped by the STOPF or STOPI operator, or an Adabas Online System command.</li> <li>■ A security violation response code has been returned for an ET-logic user. Information about response codes for security violations is provided in the Adabas Security documentation.</li> <li>■ When a new user issues an OP cmd with the same user ID (in ADD1) as an earlier user did and the earlier user was inactive for more than 60 seconds, the new user can, by issuing a second OP cmd again (the first</li> </ul>

Subcode	Meaning
	<p>OP cmd will get response code 9, subcode 64), take over the user ID of the earlier user. When the earlier user becomes active again, this subcode can be received.</p> <p><i>Action:</i> Correct the cause of the timeout, then restart the transaction.</p>
15	<p>The user was backed out because a pending Work area overflow occurred during the user's transaction. Adabas decides to back out a transaction when its start on Work is approximately 1/4th of ADARUN parameter LP away from the current position on Work.</p> <p><i>Action:</i> Either reduce the transaction length (number of updates) or duration (time between transaction start and end) to lessen the data protection area requirement, or increase the data protection area on Work (ADARUN parameter LP).</p>
17	<p>At the end of an online recovery process that was initiated after the failure of a peer nucleus in an Adabas cluster, the nucleus was unable to reacquire the ETID specified by the user in the Additions 1 field of the OP command.</p> <p><i>Action:</i> (In the application program:) Redo the OP command with the ETID specified in the Additions 1 field to reacquire the user ID. Contact your Software AG technical support representative.</p>
18	<p>The user's active transaction was interrupted and backed out because a peer nucleus in an Adabas cluster terminated abnormally.</p> <p><i>Action:</i> (In the application program:) Rerun the transaction.</p>
19	<p>The user's active command was interrupted and stopped because a peer nucleus in an Adabas cluster terminated abnormally. If the interrupted command was using a command ID (CID), the command ID is deleted.</p> <p><i>Action:</i> (In the application program:) Clean up and reacquire the current context pertaining to Adabas command IDs; rerun the transaction.</p>
20	<p>The Adabas cluster nucleus assigned to the user terminated while the user had an open transaction. The transaction has been or will be backed out.</p> <p><i>Action:</i> (In the application program:) If the user was defined with a user ID (ETID) in the Additions 1 field of the OP command, redo the OP command to reacquire the ETID; clean up and reacquire the current context pertaining to Adabas command IDs; rerun the transaction.</p>
21	<p>The user's active command was waiting for an ISN in hold status when the user was backed out and closed due to a timeout or a STOP command.</p>
22	<p>The user's active command was waiting for free space in the work pool when the user was backed out and closed due to a timeout or a STOP command.</p>

Subcode	Meaning
23	<p>The user's command was routed to a different cluster nucleus than the one used by previous commands. The user's open transaction has been backed out. It is also possible that the user had already been timed out earlier.</p> <p><i>Action:</i> Restart the transaction and any open read sequences.</p>
24	<p>The user's command was routed to a different cluster nucleus than the one used by previous commands. The user had owned EXU or EXF control over one or more files or had started the Adabas session with an OP command with R-option. As a consequence of creating a new session for the user with the new nucleus, the EXU/EXF control or file list specified in the OP command are no longer in effect.</p> <p><i>Action:</i> Restart the Adabas session with a new OP command.</p>
25	<p>The user's command was routed to a different cluster nucleus than the one used by previous commands. The user had started the Adabas session with an OP command with ETID. As a consequence of creating a new session for the user with the new nucleus, the user is no longer associated with that ETID.</p> <p><i>Action:</i> Restart the Adabas session with a new OP command.</p>
26	<p>The user's command was routed to a different cluster nucleus than the one used by previous commands. Some cluster nucleus terminated abnormally while the new nucleus was creating a new session for the user.</p> <p><i>Action:</i> Restart the Adabas session with a new OP command.</p>
62	<p>An OP (open) command was issued without a user/ET ID, which is required for this type of application or environment.</p> <p><i>Action:</i> Correct the program to specify a user/ET ID, and rerun the program.</p>
63	<p>An OP command was given for an ET user not in ET status. The user is backed out with an Adabas-generated BT command, and the operation is closed.</p> <p><i>Action:</i> Repeat the OP call.</p>
64	<p>An OP command was issued with an 8-byte ET ID that already exists.</p>
66	<p>An Adabas session with OPENRQ=YES was active and the user issued an Adabas command without having issued an OP command.</p> <p><i>Action:</i> Ensure that all users issue an OP command as the first Adabas command.</p>
67	<p>Insufficient Work part 1 space for open command with ETID definition when trying to read the user profile.</p>
68	<p>The user queue element has been deleted. Most likely the command was thrown back due to ISN contention or space shortage. The space shortage is normally workpool space; if this is the case, the LWP parameter setting should be increased.</p>

Subcode	Meaning
73	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session had an externally-controlled transaction, the outcome of which was “in doubt”. ATM forcibly resolved the “in doubt” transaction. There is a possibility that ATM’s resolution of the transaction might be inconsistent with the intended outcome.</p> <p>Check that the outcome of the session’s Adabas changes, in its previous transaction, was consistent with its changes to non-Adabas resources.</p> <p>Check the external transaction coordinator for reasons why the original transaction might have been left in the “in doubt” state. If the external coordinator indicates that the transaction was completed, and if the relevant system logs give no indication of the cause of the problem, contact your Software AG support representative.</p>
74	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client’s database session has lost its ETID. If a transaction was in progress, ATM attempted to back it out from all affected databases and release all held records.</p> <p>Issue a new OP command to the database.</p>
75	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>Either a commit operation involving an external transaction coordinator failed, or resynchronization with an external transaction coordinator caused the transaction to be backed out. In the first case, ATM attempted to back out the transaction.</p> <p>For the first case, check the external transaction coordinator for the reason. Check for error messages from ATM transaction managers or the ATM client proxy of the failing job.</p>
76	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred while an ATM transaction manager was attempting to rebuild the transaction hierarchy of a client session that has migrated from another ATM transaction manager’s domain as a result of dynamic transaction routing. ATM attempted to back out the transaction.</p> <p>Check the status of the transaction using Online Services. Check for error messages from ATM transaction manager or the ATM client proxy of the failing user.</p>
77	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>This message indicates that the client session had an open transaction and has been migrated from one node to another within a cluster (Sysplex), but ATM could not handle the transaction safely because no Migrated</p>

Subcode	Meaning
	<p>Transaction Record (MTR) file had been defined. The transaction was therefore backed out.</p> <p>Define and create an MTR file, and restart the ATM transaction managers and clustered application environments in the COR group.</p>
78	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>It was not possible to commit the client session's transaction because of a pending ET syncpoint on a target database. This could be because of a concurrent online save operation, database termination, or a SYNCC operator command. Backout of the incomplete transaction was attempted.</p> <p>Restart the transaction when the pending ET syncpoint has been completed.</p>
79	<p>Used by Adabas System Coordinator to signal the (optional) terminal timeout. Refer to the description of Generate RSP009/79 in the Adabas System Coordinator Parameters documentation for more information.</p>
80	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session was not at ET status in the target database. Backout of the incomplete transaction was attempted.</p> <p>Restart the transaction.</p>
81	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>A memory shortage in the ATM transaction manager's address space caused the current global transaction to be backed out.</p> <p>Increase the amount of memory available to the ATM transaction manager, restart it, then restart the transaction.</p>
82	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>A memory shortage occurred in the ATM transaction manager's address space, and ATM attempted to back out the current global transaction.</p> <p>Increase the amount of memory available to the ATM transaction manager, restart it, then restart the transaction.</p>
83	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred during a commit or backout operation for a global transaction. ATM attempted to back the transaction out.</p> <p>If the cause of the error is not apparent from console messages, contact your Software AG technical support representative.</p>
84	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>ATM reported conflicting use of an ETID. For an RE command, this subcode can be returned if the client is known to ATM but has no ETID.</p>

Subcode	Meaning
	The client should issue a CL command to each open database; then re-open.
85	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The global transaction time limit (TMGTT) has been exceeded, and an attempt has been made to back out the global transaction.</p> <p>Correct the cause of the timeout, then restart the transaction.</p>
86	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The global transaction time limit (TMGTT) has been exceeded, and the global transaction has been backed out.</p> <p>Correct the cause of the timeout, then restart the transaction.</p>
90	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The ATM client proxy detected either an inconsistency between its view of the client session's status and the ATM transaction manager's view, or that the transaction manager had restarted. It attempted to back out on all target databases.</p> <p>Close the client's sessions and start them again.</p>
91	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>Transactions on a target database were being quiesced, or an administrator issued a "stop" request for the session's transaction via ATM Online Services or operator command, or there was a pending ET syncpoint on the database. Backout of the incomplete transaction was attempted.</p> <p>Restart the transaction when all required target databases are available.</p>
92	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>Transactions on a target database were being quiesced, or an administrator issued a stop request for the user via ATM Online Services or operator command, or there was a pending ET syncpoint on the database. The incomplete transaction was backed out.</p> <p>Restart the transaction when all required target databases are available.</p>
93	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred while ATM was attempting either to start a new global transaction or to bring a new database into a transaction. The client proxy backed out changes from all databases.</p> <p>The next command issued returns details of the error that caused the backout. Check the meaning of the response code and act accordingly.</p>

Subcode	Meaning
94	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>An error occurred while ATM was attempting either to start a new global transaction or to bring a new database into a transaction. The client proxy attempted to back out changes from all databases.</p> <p>The next command issued returns details of the error that caused the backout. Check the meaning of the response code and act accordingly.</p>
95	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session's transaction was controlled by an external transaction coordinator, which reported that the transaction has been backed out.</p> <p>Restart the transaction.</p>
96	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session's transaction was controlled by an external transaction coordinator, which reported "backed out, outcome pending" for the transaction. This means that backout has begun for the transaction, and will be completed when all the resource managers involved in it are able to comply with the backout request.</p> <p>Restart the transaction.</p>
97	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The CICS Resource Manager Interface is in use, and the ATM client proxy detected that the client session's Task Interface Element (TIE) was being used by another session.</p> <p>This can occur if all of the following are true:</p> <ul style="list-style-type: none"> <li>■ Natural is being used, in such a way that two Adabas sessions are maintained for each client;</li> <li>■ The client control <code>Transaction Model</code> is set to <code>MESSAGE</code>;</li> <li>■ Natural parameters are set such that Natural might not generate <code>OP</code> commands for all database sessions.</li> </ul> <p>You can make sure that Natural generates <code>OP</code> commands by using a non-blank <code>ETID</code>, or by means of Natural's <code>DBOPEN</code> parameter.</p> <p>The condition can also occur if all of the following are true:</p> <ul style="list-style-type: none"> <li>■ Natural is being used, in such a way that two Adabas sessions are maintained for each client;</li> <li>■ The Adabas System Coordinator has timed out Natural's "system" session.</li> </ul> <p>In this case, a new Natural <code>LOGON</code> might clear the condition. Otherwise terminate the session and start a new session.</p>

Subcode	Meaning
	If the error persists, contact your Software AG support representative.
98	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session was executing in serial mode, and requested that changes be committed. Some of the changes were committed, and some were backed out.</p> <p>Examine the results of the transaction. If necessary, correct the result by manual intervention.</p>
99	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session incurred a security response code; ATM backed out the user's changes.</p> <p>If security permissions are not adequate, correct them and rerun the transaction.</p>
249	<p>In Adabas Vista, all transaction activity by the client has been backed out for one of the following reasons:</p> <ul style="list-style-type: none"> <li>■ The client is using multiple (different) ETIDs which have collided against a particular database.</li> </ul> <p><i>Action:</i> Review the client's use of ETIDs with respect to the current translation rules and/or partitioned files.</p>

**Open Systems**

This response is caused by one of the following:

- The last user transaction has been backed out by Adabas (ET logic users only) or an exclusive control user (non-ET user) or an access-only user exceeded the Non-Activity Time Limit;
- The user session was abnormally terminated by the operator and the user issued a command;
- The protection log area (= WORK container) was too small and an internal BT was executed.

The ADDITIONS 2 field in the control block contains additional information:

First two bytes	Third and fourth bytes	Explanation
0	TT	Transaction timeout
1	TN	Non-activity timeout
2	ST	STOP user
3	LP	WORK overflow
5	SE	Security

First two bytes	Third and fourth bytes	Explanation
6	DL	Deadlock
8	OP	Open transaction
9	OR	Open required
10	RR	Replication recording failed  One of the internal Adabas commands issued for replication recording got an unexpected response code, for example 77. This response code is included in the control block in the field ACBXSUBR (only if you use the ACBX interface) and displayed in an RPLIRSP message in the nucleus log.

	First two bytes	Third+ fourth bytes
	-----	-----
Transaction timeout :	0	TT
Non-activity timeout:	1	TN
STOP user :	2	ST
WORK overflow :	3	LP
Security :	5	SE
Deadlock :	6	DL
Open transaction :	8	OP
Open required :	9	OR

The information in the first two bytes is represented as an integer, and the third and fourth bytes are alphanumeric.

### Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

#### Mainframe Systems

User actions are described in the subcode list in the explanation.

#### Open Systems

Check the appropriate reason. If the Adabas nucleus was started without the option OPEN\_REQUIRED, and the reason for response 9 was a non-activity timeout or a STOP user, users who started their sessions with an OP command must re-issue their OP command under the following circumstances:

- if they set a User ID
- if they specified restricted file lists
- if they had user-specific timeout values
- if they were not ET users.

If too many transactions are backed out because of a Work overflow, the size of the Work container should be increased.

**Response 10**

**Origin** Mainframe systems only  
**Explanation** Too many occurrences for a periodic group.

**Response 16**

**Origin** Open systems only  
**Explanation** An error occurred in an MC call during subcommand processing. The error code and additional information can be found in the control block of the subcommand. The first 2 bytes of the Additions 2 field contain the number of the subcommand in binary format. The third and fourth bytes of the Additions 2 field contain the offset of the subcommand's control block in the MC call's record buffer in binary format. All subcommands before the one that failed were executed.  
**Action** Correct the failed subcommand if necessary and re-issue the subcommands beginning with the one that had failed.

**Response 17**

**Origin** Mainframe and open systems  
**Explanation** A subcode indicating the specific cause and action for this response code appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field. The following are the subcodes and their meanings:

Subcode	Meaning
1	The program tried to access system file 1 or 2, and no OP command was issued.  <i>Action:</i> Restructure the program to begin with an OP command.
2	The program tried to access system file 1 or 2, and the user is not authorized.  <i>Action:</i> Change the program to avoid the access.
4	One of the following occurred: <ul style="list-style-type: none"> <li>■ The specified file number is invalid. The file number might be equal to "0" or greater than the maximum allowed.</li> <li>■ When running with ADARUN DTP=RM or DTP=TM, an attempt was made by a non-Adabas Transaction Manager user to access/update an Adabas Transaction Manager system file.</li> </ul>

Subcode	Meaning
5	<p>The file is either not loaded, or has been locked by another user for privileged use.</p> <p>On mainframe systems, for ADAORD and ADAINV utility operations, the write phase has started and use of the file is now blocked for the type of operation you requested.</p>
6	<p>On mainframe systems, an E1 (delete record) command was given without specifying a valid file number.</p> <p>On open systems, the file to be created already exists.</p>
7	The program tried to perform an LF command on system file 1 or 2.
8	<p>On mainframe systems, the program tried to access a file that was not listed in the file list of an open (OP) executed with the R option.</p> <p>On open systems, an ET user with a restricted file list and ACC = file number attempted to issue a UPD command, or a user with a restricted file list attempted to touch a file that is not in the file list</p>
9	<p>The file that the program attempted to access is completely locked. This is usually because the maximum number of logical file extents that can fit into the FCB have been used.</p> <p><i>Action:</i> Reorder, then unlock the file. Continue operation.</p>
10	The program attempted to access a file which is locked with exclusive EXU status.
11	An LF command (read FDT) was run on a file that is not loaded; neither the FCB nor the FDT exists.
12	File has been locked with LOCKF.
13	A file is password-protected and the password was specified, but the corresponding security file is missing (not loaded).
14	A command was issued against a LOB file. Commands involving LB fields should be directed against the associated base file, not the LOB file.
15	A file is being loaded so its information is temporarily unavailable.
16	<p>On mainframe systems, an attempt was made to perform an update (e.g. A1, E1, N1/2) against a file loaded with the attribute RPLUPDATEONLY=YES or READONLY=YES.</p> <p>On open systems, the file was locked by ADAOPR.</p>
17	An attempt was made to perform an update (e.g. A1, E1, N1/2) against a file loaded with the attribute READONLY=YES.
18	File has been locked with ALOCKF.

Subcode	Meaning
21	<p>On mainframe systems, there was not enough space for encoding elements (ECSE).</p> <p>On open systems, a two-byte file number was used against a lower version database that does not support large file numbers.</p>
22	<p>On mainframe systems, the required ECS objects needed for conversion between user and system data representation could not be loaded.</p> <p>On open systems, the file control block (FCB) is invalid (corrupted).</p>
23	<p>ECS object could not be located. The following objects must be available in the encoding objects library: File Alpha, File Wide EDD, User Alpha, User Wide EDD, and the PTOs for the combinations between file/user alpha/wide encodings.</p> <p><i>Action:</i> Check that the required EDD and PTO objects are available.</p>
24	<p>ECS function <code>get_attribute()</code> failed.</p> <p><i>Action:</i> The function's return code is logged with the nucleus message ADAN7A.</p>
25	<p>One of the following occurred: - A required encoding attribute was missing in an ECS object (encoding type, class, and flags) - The default space character length was &gt;4 - Default space table allocation failed - If DBCS-only plane exists, wide space character was undefined, or the length &gt;4, or wide space table allocation failed</p>
29	<p>An Adabas Review communication error has occurred. Contact your Software AG support representative.</p>
52	<p>A non-Adabas target was called.</p>
99	<p>The file's FTD is corrupted.</p> <p><i>Action:</i> To resolve the problem, repair the file by running a restore/regenerate from a consistent state.</p>
249 (0x00F9)	<p>While attempting to satisfy a partitioned file command, Adabas Vista detected the unavailability of an FDT – this is invalid for one of the following reasons:</p> <ul style="list-style-type: none"> <li>■ None of the partitions were available/online and at least one of them has the file parameter <code>Critical</code> set to YES.</li> <li>■ None of the partitions were available/online and all of them have the file parameter <code>Critical</code> set to NO and the command can not be satisfied with a “no data” response such as RSP003.</li> </ul> <p>An error occurred when Adabas Vista (open systems) tried to access a file that was not listed in the file list of an <code>OP</code> command executed with the <code>R</code> option.</p>

Subcode	Meaning
	<i>Action:</i> Ensure at least one of the file partitions is available/online or review the program logic.

**Response 18**

<b>Origin</b>	Mainframe and open systems.
<b>Explanation</b>	Invalid file number usage. The file number was modified between successive L2/L5 calls or between successive L $\times$ and S $\times$ calls.
<b>Action</b>	Correct the file number.

**Response 19**

<b>Origin</b>	Mainframe and open systems.
<b>Explanation</b>	An attempt was made to update a file which is either already open for read access or can only be opened for read access. The leftmost two bytes of ACB's Additions 2 field or the ACBX's File Number (ACBXFNR) field may contain the file number.
<b>Action</b>	Do not attempt to update a file with read-only access.

**Response 20**

<b>Origin</b>	Mainframe and open systems.
<b>Explanation</b>	One of the following invalid values was used for a command ID value: <ul style="list-style-type: none"> <li data-bbox="492 1144 667 1180">■ Binary zeros</li> <li data-bbox="492 1186 597 1222">■ Blanks</li> <li data-bbox="492 1228 1479 1304">■ The high-order byte contains the hexadecimal value "FF", but there is no automatic command ID generation</li> <li data-bbox="492 1310 1208 1354">■ The three high-order bytes contain the ASCII string "SYN".</li> </ul>
<b>Action</b>	Correct the command ID and avoid using any of these invalid command ID values.

**Response 21**

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	An invalid command ID value was detected. One of the following explanations or subcodes is provided:

Subcode	Meaning
1	The command ID value was not found in the sequential command table. This is not an initial call and there was no previous initial call, or the command ID was deleted or lost in a timeout or recovery action.
3	The command ID value specified for the L3/L6 command was assigned to another Lx command.
5	The command ID value specified for the L9 command was assigned to another Lx command.
6	Unexpected last file in chain.
7	The command ID value specified was assigned to a different file.
8	The command ID value specified for the Sx command is for a sorted ISN list; the ISN list was not in ISN sequence.
9	An application running with PREFETCH=YES or PREFETCH=OLD attempted to dynamically reverse the read direction of an L3/L6/L9 command. This is not allowed.
10	The master file number is not the same as it was in the initial call for this command ID.
12	ACB(X)Add1 altered after initial call.
13	S9 ISN list already sorted
14	Not a chained file as expected.
15	Not an L2 sequence as expected.
16	Chained file transformed ISNs not permitted.
17	CID does not exist for chained file.
18	File was not master file as expected.
19	Special L3 started on a valid file number and subsequent L3 issued with the API option.
20	Chained file ISNs not transformed.
21	Special L3 system area not as expected. System area changed.
22	The command ID value specified was assigned to a different file and FBL is not equal to zero.
23	Incorrect CID for sort function.
249 (0x00F9)	<p>An invalid command ID value was detected by Adabas Vista (open systems):</p> <ul style="list-style-type: none"> <li>■ The command ID value specified with the N option of an L1/L4 command was not found.</li> <li>■ The command ID value specified with the N option of an L1/L4 command does not correspond to an ISN list.</li> <li>■ One or both of the ISN lists referred to in the ADDITIONS 1 field of an S8 command do not exist.</li> </ul> <p><i>Action:</i> Review the program logic.</p>

**Action** Correct the command ID.

## Response 22

**Origin** Mainframe and open systems

**Explanation** The command or command option is invalid. A subcode indicating the specific cause and action for this response code appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field.

When using the LNCSTUB module on mainframe systems, this response code may indicate problems with the initial call (IC) to the Adabas CICS command-level link component. If the Adabas control block shows a command code of "IC", the link routine being used may not be at the proper release level or may not be the command-level version.

The following are the subcodes and their meanings:

Subcode	Meaning
1	The nucleus detected an invalid command code.
2	This command cannot be issued by an ACC (access only) user; and update command cannot be issued by an access-only user.
3	This command cannot be performed on a read-only nucleus; an update command cannot be issued for a read-only database session.
4	This privileged command was issued without a previous OP (open) command.
5	The command is not valid for a nonprivileged user.
6	The command was rejected by user exit 11.
7	Incorrect command options were specified for a privileged command.
8	The command is invalid for an ET user in preliminary ET status. First complete the transaction using Adabas Transaction Manager.
9	The current user is not authorized to issue an ET/BT command.
10	The C2 command is no longer permitted.
11	The C3 command can only be issued by EXU users.
12	The L1/4 command with the option "F" is not valid for expanded files.
13	The call issued is not permitted when the database is in a suspend state.
14	Invalid privileged command.
15	An L1/L4 command specified the multifetch option ("M" or "O") was not combined with either the "I" or "N" option.
16	The user does not have "privileged" command authorization.
17	A refresh file (E1 command with ISN zero) is not permitted during online save database or file.

Subcode	Meaning
18	Applications using the ADALNK X'48' call logic receive this response when the logic has been suppressed.
19	<p>On mainframe systems, a special utility command was issued for an obsolete subfunction.</p> <p>On open systems, an ET or BT with command option "S" was issued without subtransactions being enabled for the current Adabas user session by specifying command option "S" in the OP command.</p>
21	<p>One of the following occurred:</p> <ul style="list-style-type: none"> <li>■ A BT command was issued by a non-ET logic user.</li> <li>■ An ET command was issued for a distributed transaction managed by Adabas Transaction Manager; ET commands are invalid for a distributed transaction managed by Adabas Transaction Manager.</li> </ul>
22	The current transaction has already been heuristically terminated or the command is not allowed within an MC sequence.
23	<p>One of the following occurred:</p> <ul style="list-style-type: none"> <li>■ The last MC subcommand is not ET.</li> <li>■ A BT command was issued for a distributed transaction managed by Adabas Transaction Manager; BT commands are invalid for a distributed transaction managed by Adabas Transaction Manager.</li> </ul>
24	<p>One of the following occurred:</p> <ul style="list-style-type: none"> <li>■ An ET or CL command with user data is not allowed for read-only access to a database.</li> <li>■ CL is invalid because the user has a transaction in progress that is managed by Adabas Transaction Manager.</li> </ul>
25	A command was sent from an Event Replicator Server to an Adabas nucleus, but the Adabas nucleus is not running with ADARUN REPLICATION=YES.
26	An attempt was made by an Adabas nucleus to connect to an Event Replicator Server when the target of the message is actually another Adabas nucleus, not an Event Replicator Server.
28	A replicated utility may not be executed for a replicated file when the Adabas nucleus is running in single-user mode.
29	An error occurred during a connection attempt by an Event Replicator Server database. Ensure that you are trying to connect to another Adabas nucleus and not an Event Replicator Server and try again.
31	API file delete not permitted: not API loaded.
32	An attempt was made to update a replicated file in single-user-mode. Replicated files can be updated only in multi-mode; replication is not

Subcode	Meaning
	supported in single-mode. However, a nucleus with replication support can be started in single-mode for maintenance purposes.
33	A shared hold status request (with command option 3 set to "C", "Q", or "S") is not allowed for a command with prefetch (command option 1 set to "P").  On open systems, the command option "S" is not allowed for an S9 command with a non-blank Additions 4 field.
34	On open systems, the command was rejected by user exit 11.
35	The command cannot be executed with the nucleus parameter NT=1.
36	The descending option "D" is not allowed for the command.
37	On mainframe systems, a shared hold status request (command option 3 is set to "C", "Q", or "S") is not allowed for a non-ET user.  On open systems, a shared hold status request (command option 3 is set to 'C', 'Q', or 'S') is not allowed for a non-ET user.
38	A shared hold status request for a sequential read command (command option 3 is set to "Q") is not allowed for an L4 command without the N-option, nor is it allowed for an S4 command without a command ID (CID) or with an ISN buffer length other than 4 bytes.
39	A shared hold status request for a sequential read command (command option 3 is set to "Q") is not allowed for a command with a multifetch (command option 1 is set to "M" or "O"). Also, a shared hold status request (with command option 3 set to "C", "Q", or "S") is not allowed for a read command with prefetch (command option 1 is set to "P").
40	A keep-in-shared-hold-status request (with command option 3 set to "H") is not allowed for an ET or BT command with multifetch or prefetch (command option 1 is set to "M" or "P").
41	A request to read the next portion of a LOB value (command option 2 is set to "L") is not allowed for an L1/L4 command with multifetch (command option 1 is set to "M" or "O") or prefetch (command option 1 is set to "P").
42	On open systems, for an A1 command with command option 2 = "T", the current time is still the same as the value of the field with SY=TIME in the database.
48	An obsolete internal request to shut down Adabas, supposedly coming from Entire Net-Work, has been issued and rejected.
50	The Router (LCC) detected an invalid command code. This may also arise when a new ACBX-type call is presented to a back-level router.
51	A client call with the ADARUN parameter PREFETCH=OLD has multiple APLX buffers or the contents of APLX+4(chained APLX) is non-zero. To resolve this, use the ADARUN parameter setting PREFETCH=YES.
52	A non-Adabas target was called.
53	Invalid file specified for an Adabas Online System function.
54	The user was stopped with STOPUR or STOPSUR.

Subcode	Meaning
55	The command is returned because the command queue timeout time specified by the DELCQ operator command or the AUTOCQTIME ADARUN parameter was reached or exceeded for the command.
1005	The command code is invalid.
1006	The ACBX is invalid (not first buffer).
1007	The ABD is invalid.
1008	The ABD type is invalid.
1009	More than one search buffer specified.
1010	More than one value buffer specified.
1011	More than one ISN buffer specified.
1012	The number of search and value buffers do not match.
1013	The number of format and record buffers do not match.
1015	A streaming logic error occurred.

**Action** Correct the command code or command option or the previous OP command, and rerun the program.

**Response 23**

**Origin** Mainframe and open systems

**Explanation** An invalid starting ISN was specified for an L2/L5 command sequence:

- The ISN was not assigned to a record in the file; or
- The ISN was greater than the MAXISN in effect for the file.

**Open Systems**

On open systems the following subcodes may occur:

Subcode	Meaning
249 (0x00F9)	An invalid ISN was detected by Adabas Vista (open systems). The starting ISN specified for an L2/L5 command sequence is not consistent with the definitions for the partitioned file.  <i>Action:</i> Review the program logic.

**Action** Correct the ISN.

**Response 24**

**Origin** Mainframe and open systems

**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

For an S9 command:

- The ISN list in the ISN buffer was already sorted; or
- The ISN list in the ISN buffer contained an invalid ISN; or
- The "D" option was specified when trying to sort an ISN list by ISN.

**Open Systems**

An ISN is equal to "0" or is greater than or equal to the first free ISN found in the ISN buffer. The Additions 2 field contains the value of the invalid ISN in 4 byte binary format.

**Action** Correct the ISN buffer.

**Response 25**

**Origin** Mainframe and open systems

**Explanation** The ISN specified in ISN lower limit field for an S1/S4 or S2/S9 command was not found.

**Open Systems**

On open systems the following subcodes may occur:

Subcode	Meaning
249 (0x00F9)	An invalid ISN was detected by Adabas Vista (open systems). The ISN specified in the ISN Lower Limit field for an S2 command when retrieving a group of ISNs from a saved ISN list was not found.  <i>Action:</i> Review the program logic.

**Action** Correct the ISN lower limit.

**Response 26**

**Origin** Mainframe and open systems

**Explanation** An invalid ISN buffer length for an S9 command was detected. The number of ISNs to be sorted as provided in ISN quantity is equal to "0".

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
2	An S9 command with an ISN buffer contains ISNs that are higher than the TOP-ISN of the file.

**Action** Correct the ISN buffer length.

**Response 27**

**Origin** Mainframe systems only

**Explanation** Sufficient work space was not available to accommodate the combined sizes of the search and value buffers as indicated in the search buffer length and value buffer length fields.

Subcode	Meaning
1	Sufficient work space was not available to generate the format translation.

**Response 28**

**Origin** Mainframe and open systems

**Explanation** The first two bytes of the Additions 1 field contained an invalid descriptor for an L3/L6 or S2/S9 command.

Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
1	The field was not a descriptor.
2	The use of the descriptor is not supported (for example, phonetic descriptors or the descriptor is contained within a periodic group).
3	The descriptor was changed between successive calls.
4	There is a mismatch of the descriptor names in the Additions 1 field and the search buffer.
5	An initial L3 or L6 call contains no trailing blanks in the Additions 1 field.
7	ADAINV is inverting the file and using the descriptor.
8	The descriptor is missing in the file index.
9	An internal error occurred during SB interpretation.

**Action** Correct the Additions 1 field.

**Response 29**

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	In an L3 or L6 command, a value repositioning was attempted (bytes 3-8 of the Additions 1 field contain spaces) and the Command Option 2 field did not contain the value "A", "D", or "V". The command ID is released.
<b>Action</b>	Correct the Additions 1 or Command Option 2 field.

**Response 34**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	An invalid command option has been detected.  Depending on the subcode in the rightmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field, one of the following has occurred:

Subcode	Meaning
1	An invalid command option has been specified in one of the command option fields.
2	The R option has been specified for the C5 command, but replication is not active.
9	A record buffer must be specified for this command but is missing (not specified of length zero).

<b>Action</b>	Either remove the invalid command option or replace it with a valid option.
---------------	---

**Response 35**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	The user/DBA attempted to perform a function for a noncluster Adabas nucleus that is available only for an Adabas cluster database.
<b>Action</b>	Either perform the function against a cluster database or change the function.

**Response 39**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	A logically deleted descriptor was used as a search criterion or was specified in the first two bytes of the Additions 1 field for an L3, L6, L9, S2, or S9 command.
<b>Action</b>	Remove the use of the logically deleted descriptor and inform your database administrator about the problem.

**Response 40**

**Origin**

Mainframe and open systems

**Explanation**

A syntax error was detected in the format buffer.

**Mainframe Systems**

On mainframe systems, one of the following subcodes may be used:

Subcode	Meaning
1	Syntax error in format buffer; possible premature end of buffer segment.
2	Syntax error in the format buffer -- bad first or second character of field name or missing "/".
3	Text literal has no ending quote or is too long (more than 255 characters).
4	Text literal is empty.
5	Expected delimiter missing.
6	Conditional format criterion has no closing parentheses ")".
7	The conditional format criterion is empty.
8	Invalid field name, format, or search operator.
9	One of the following occurred: <ul style="list-style-type: none"> <li>■ An invalid edit mask number (greater than 15) was specified.</li> <li>■ A syntax error in the conditional format criterion was found.</li> <li>■ Multiple format buffer segments are specified with conditional format criterion.</li> </ul>
10	Invalid character following field name specification.
11	Invalid index specification for MU field in PE group.
12	Expected number missing or too large ( $\geq 2^{31}$ ).
13	Syntax error in LOB segment specification.
14	Syntax error in L element specification.
15	Syntax error in D element specification (daylight savings time indicator).
16	Invalid Date-Time edit mask specification.
17	MU/PE index range specification invalid for LOB segment notation.

On mainframe systems, the following information is returned in the Additions 2 field of the control block:

- The leftmost two bytes contain the two characters being inspected when the error was detected.
- The rightmost two bytes contain the subcode.

### Open Systems

One of the following format buffer errors occurred.

- The terminating period was missing;
- The first position contains a period, this only applies to N1 or N2 commands;
- Length and/or format specified with a range definition;
- An invalid element was detected;
- A field segment notation was not correct: it must be specified either as *(byte-number, length)* or as *(byte-number, length, length-2)*, where *byte-number* must be either "\*" or a decimal number, and *length* and *length-2* are decimal numbers. These numbers must be less than 2,147,483,648;
- A field segment notation was specified for a range of MU fields or for a range of fields within a periodic group.

On open systems, the following information is returned in the Additions 2 field of the control block:

- The leftmost two bytes contain the number of the byte (in binary format) relative to the beginning of the format buffer where the error was detected.
- The rightmost two bytes contain the name of the field being processed when the error was detected.

**Action** Correct the format buffer.

### Response 41

**Origin** Mainframe and open systems

**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

### Mainframe Systems

One or more specification errors exist in the format buffer. When possible, the short name of the field for which the error occurred is stored at offset 2 of the ACB's Additions 2 field or in the ACBX's Error Character Field (ACBXERRB).

The following specification errors may have been made:

**Note:** A collation descriptor (COLDE) can only be specified in the format buffer of the L9 command and only when the decode option has been specified in the user exit. The value returned is not the index value but the original field value.

Subcode	Meaning
1	Spacing element <i>nX</i> with <i>n=0</i> or <i>n&gt;255</i> not allowed.
2	An invalid sequence of format buffer elements was specified.
3	Miscellaneous types of specification errors were found in the format buffer.
4	A field name was undefined or not elementary.
5	Format without fields.
6	A group field cannot be specified if the group contains a LOB (LB) field.
7	A field name is undefined.
8	Invalid use of <i>f1dD</i> , <i>f1dL</i> , <i>f1d,*</i> or <i>E(date-time-mask)</i> notation.
9	Elementary field in PE group: 1-N notation not permitted with LOB (LB) fields or <i>f1dD</i> notations.
10	A LOB (LB) field, <i>f1dL</i> (length indicator notation) or <i>f1d,*</i> (asterisk notation) are not permitted with an L9 command.
11	A length indicator ( <i>f1dL</i> ) or asterisk notation ( <i>f1d,*</i> ) are only permitted for LA and LOB (LB) fields.
12	LA or LOB (LB) fields are not permitted with 1-N notation, <i>f1da-f1db</i> (field series) notation or old MU syntax.
13	LA or LOB (LB) fields are not permitted with <i>f1dC,*</i> (count indicator) or <i>f1da-f1db,*</i> (field series notation).
14	Asterisk notation and length indicator notation combinations ( <i>f1dL,*</i> ) are not permitted.
15	SQL significance indicator and asterisk notation combinations ( <i>f1dS,*</i> ) are not permitted.
16	Length indicator ( <i>f1dL</i> ), asterisk notation ( <i>f1d,*</i> ) or daylight savings time indicator notation ( <i>f1dD</i> ) are not permitted for a group field.
17	Daylight savings time indicator notation ( <i>f1dD</i> ) cannot be combined with asterisk notation ( <i>f1d,*</i> ) or a length indicator notation ( <i>f1dL</i> ).
18	Daylight savings time indicator notation ( <i>f1dD</i> ) is only permitted for fields defined with the TZ option.
20	Daylight savings time indicator notation ( <i>f1dD</i> ) is not permitted with count indicator ( <i>f1dC</i> ) or field series notation ( <i>f1da-f1db</i> ).
21	Old MU syntax is not permitted with daylight savings time indicator notation ( <i>f1dD</i> ).
22	An invalid length or format has been specified with daylight savings time indicator notation ( <i>f1dD</i> ); if specified it must be 2,F.
23	An invalid length or format has been specified with length indicator notation ( <i>f1dL</i> ); if specified it must have length 4 and format B.
24	A phonetic, collation, or hyperdescriptor was specified.
25	Date-time edit mask notation ( <i>E(date-time-mask)</i> ) is not permitted with daylight saving time indicator notation ( <i>f1dD</i> ), asterisk notation ( <i>f1d,*</i> ), or length indicator notation ( <i>f1dL</i> ).

Subcode	Meaning
26	Date-time edit mask ( <i>E(date-time-mask)</i> ) notation requires format P, U, F, or B.
27	Date-time edit mask ( <i>E(date-time-mask)</i> ) notation and edit mask notation (E0-E15) are not permitted together.
28	Date-time edit mask ( <i>E(date-time-mask)</i> ) notation and count indicator notation ( <i>fldC</i> ) are not permitted together.
30	Date-time edit mask ( <i>E(date-time-mask)</i> ) notation is only permitted for a field defined with a date-time edit mask.
31	Daylight savings time indicator notation ( <i>fldD</i> ), length indicator notation ( <i>fldL</i> ), and asterisk notation ( <i>fld,*</i> ) are not permitted together with LOB segment notation.
32	LOB segment notation is permitted only for LOB (LB) fields.
33	More than one LOB segment with *-position not permitted.
34	Length/format override not permitted for LOB segment notation.
35	Invalid byte number and length parameters in LOB segment notation.
36	Invalid length-2 parameter in LOB segment notation; must be equal to length parameter.
37	Invalid syntax with daylight saving time indicator in format buffer.

### Open Systems

An error was detected in the format buffer:

- The field name specified is reserved for edit mask usage;
- An index was equal to 0;
- A length specified or taken from the FDT standard length is greater than the maximum length of the required format;
- *nnnX* was specified with *nnn* greater than 253;
- A literal with more than 253 characters was specified;
- A subdescriptor, superdescriptor, phonetic descriptor, hyperdescriptor or a collation descriptor was specified;
- A field specified was not present in the file;
- A periodic group name appears without an index;
- A length and/or format was used with a group notation;
- A field in a periodic group was specified without an index;
- A range notation with a group name or a multiple-value field as the first or last element was specified;
- A reference was made to the count of a multiple-value field contained in a periodic group, and no index was included to indicate the periodic group occurrence for which the count was to be returned;

- A collation descriptor with the option HE was specified for an L9 command.
- A count specification was made for a field which was neither a multiple-value field nor was contained within a periodic group;
- A count for a non-multiple value field within a periodic group was specified;
- A length and/or format specification was used with a periodic group notation;
- A (regular or periodic) group containing a multiple-value field was specified;
- Invalid index usage;
- A descending index range was specified;
- A double index was used for a non-periodic field;
- A multiple-value field with an index specification and a multiple-value field without an index specification were used;
- A value cannot be converted to the required format (READ command) or converted to the FDT standard format (UPDATE command);
- The S element was applied to a field that does not have the NC option;
- A field with the NC option was used more than once together with its S element;
- The add option is not compatible with the format/length;
- The specification of a character set was invalid;
- A field was specified with an edit mask not allowed for the field;
- A field segment notation '(byte-number,length)' or '(byte-number,length,length-2)' was not correct: byte-number + length must be less than or equal to the maximum value length + 1, and length-2 must be equal to length. The maximum value for LB fields is 2,147,483,643, for LA fields 16381, and for other values 253 bytes;
- Segment notation is only allowed for values with the format 'A'.

The following information is returned in the Additions 2 field of the control block:

- The leftmost two bytes contain the number of the byte (in binary format) relative to the beginning of the format buffer where the error was detected.
- The rightmost two bytes contain the name of the field being processed when the error was detected.

**Action**

Correct the specification error and reissue the command or job. For more information about syntax rules for multiple field and periodic group indexing, refer to the Adabas Command Reference documentation.

**Response 42****Origin** Mainframe systems only**Explanation** A space problem occurred. The following are the subcodes and their meanings:

Subcode	Meaning
1	The Work pool was too small to store a user format. <i>Action:</i> Increase the LWP specification and retry .
2	The internal format buffer was too small to store a user format (translated into internal structure). <i>Action:</i> Increase LFP specification and retry.

**Action** See the actions described in the subcodes.**Response 43****Origin** Mainframe and open systems**Explanation** In an L9 command, the descriptor specified in the format buffer did not agree with the descriptor specified in the search buffer.**Action** Correct the format buffer or the search buffer.**Response 44****Origin** Mainframe and open systems**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.**Mainframe Systems**

One of the following format buffer errors occurred (subcodes are shown in the leftmost column):

Subcode	Meaning
1	The specified format is not allowed for an update operation. A possible reason for this is the presence of a conditional format buffer with an update operation.
2	The L9 command's format buffer format is not allowed for other commands.
3	The specified format is not allowed for an update operation. A possible reason for this is the presence of a conditional format buffer with an update operation.
4	The L9 command's format buffer format is not allowed for other commands.
5	Format used for L9 can only contain field and an optional daylight savings time indicator ( <i>f1dD</i> ).

Subcode	Meaning
6	Fixed point format must have length 2, 4, or 8.
7	Conditional format and more than one format buffer was specified.
8	The current Adabas call provides a different number of format buffers than the format reference by CID.
9	Number of format buffer segments (ABDs) is zero.
10	AAS, AA, AA is invalid.
12	L option specified but the format has no LOB segment with *-position.

**Open Systems**

One of the following situations occurred:

Subcode	Meaning
1	<ul style="list-style-type: none"> <li>■ The format buffer is invalid for use with an UPDATE command (A1), ADD command (N1/N2):                             <ul style="list-style-type: none"> <li>■ Format buffer contains overlapping fields, e.g., GL1-3, GL2-4.;</li> <li>■ Format buffer contains an 1-N element, e.g., GL1-N.;</li> <li>■ There is not a 1:1 relation between an L element and the subsequent corresponding element with '*' length;</li> </ul> </li> <li>■ A READ command uses a format buffer from the format pool, which was previously used by update or add command, and which contains an invalid conversion.</li> </ul>
12	L option is specified but the format has no LOB section with *-position.
13	The format buffer for an A1 commands with command option 2='T' did not contain a last-update-timestamp system generated field.

**Note:** Subcodes associated with response 44 are stored in the first two bytes of the Additions 2 field (ACB) and in the error subcode field (ACBX).

**Action**

Correct the format buffer or use a different read or update command.

**Response 45**

**Origin**

Mainframe and open systems

**Explanation**

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

The internal format buffer space has been exceeded. Either the LWP parameter setting is too small or the internal format buffer requires more than 2 G.

**Open Systems**

Multiple field or periodic group overflowed when using the N suffix in the format buffer for update.

The following information is returned in the Additions 2 field of the control block:

- The first two bytes will contain the number of the byte (in binary format) relative to the beginning of the record where the error was detected;
- The third and fourth bytes will contain the name of the field being processed when the error was detected.

**Action**

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

Increase the size of the LWP parameter and try again. If the problem persists, contact your Software AG technical support representative for assistance.

**Open Systems**

Because the multiple field or periodic group reached its absolute limit, the application must be redesigned.

**Response 46****Origin**

Mainframe and open systems

**Explanation**

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

Subcode	Meaning
1	Too many TBLES elements for this user.
2	The maximum value for the NQCID parameter was exceeded (the number of TBI and/or TBQ elements is greater than NQCID).

**Open Systems**

Mismatch of format buffer usage for the supplied command ID.

- A command ID of global ID format buffer has been found in the format pool and has a different file number to the file supplied by the caller;
- The file number was changed in subsequent Adabas calls with the same normal or global command ID.

**Action**

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

Adjust the size of the NQCID parameter and try again.

**Open Systems**

Check the command IDs used in the call and try again.

**Response 47**

**Origin**

Mainframe and open systems

**Explanation**

The maximum value for the NISNHQ parameter was exceeded. The following subcodes appearing in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field provide more detailed information.

Subcode	Meaning
1	<p>An attempt was made to put too many ISNs in hold. The maximum number of ISNs that can be put in hold is specified by the NISNHQ parameter and can be overridden via the Additions-4 field (bytes 3-4) of the user's OP command and via the user profile.</p> <p><i>Action:</i> Increase the value of the NISNHQ parameter or the maximum number of ISNs that the user can put in hold specified in the Additions-4 field (bytes 3-4) of the OP command or in the user profile. Alternatively, modify the application program to store fewer ISNs in hold at the same time.</p>
2	<p>The hold queue was full. If another user has put the maximum number of ISNs in hold, that other user is backed out and will next receive response code 9, subcode 1. The user who is given the response code 47 is not backed out; this user should issue an ET or BT command to release the ISNs from hold.</p> <p><i>Action:</i> Increase the value of the NH parameter. Alternatively, modify the application program to store fewer ISNs in hold at the same time.</p>

**Action**

Increase the value of the NISNHQ parameter by modifying its ADARUN parameter value in the nucleus startup file, or (on open systems) using ADAOPR.

**Response 48**

**Origin**

Mainframe and open systems

**Explanation**

An error occurred during the processing of a command such as OP or N1. Refer to the hexadecimal subcode that appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field.

Subcode	Meaning
	File(s) not available at open time. This is the default message displayed with this response code if another subcode is not provided.
1	A specified file is locked against the requested use.
2	A specified file is currently in conflicting use.
3	A utility cannot start because an online save operation is in progress.
4	A specified file is already locked or being used by an EXU/EXF or utility user. Use operator command DLOCKF to display file locks, DNFV to display a summary of the current file usage.
5	A utility requiring exclusive database control cannot start because an online save operation is in progress.
6	A utility that requires exclusive database control cannot start because the user queue is not empty.
7	The requested file lock cannot be granted because the file is being used. Use operator command DNFV to display a summary of the current file usage, DFILES to display current users of the file.
8	The user ID specified in the open (OP) command is already in use by another user.
9	An EXU/EXF/UTI lock was requested in the open command, but the file is currently in the file list of a user in UPD/EXU/EXF/UTI status.
10	An EXF/UTI lock was requested in the open command, but the file is currently in the file list of a user in ACC status.
11	A nonprivileged user issued an open (OP) command to a nucleus in UTIONLY (utilities only) status.
13	Online file save attempting to run on an advance-locked file.
14	UPD/ACC open attempted against advance-locked file.
15	A file requested for an online utility (Adabas Online System or ADADBS) or an E1 program refresh is currently being used.
16	ACODE or WCODE was specified in the record buffer on the command but the nucleus was not activated with UES support.
17	A specified file is locked against the requested use and is advance-locked. The data in the file is not accessible. This can happen if a utility aborts or an autorestart fails.
18	On mainframe systems, this means that a second command was issued by a user who is participating in a two-phase commit (preliminary ET completed; final ET outstanding) or whose transaction has been heuristically terminated.  On open systems, this means that the index of the specified file is not accessible. This can happen if a utility aborts or if the index has been disabled by ADAREC REGENERATE or an autorestart.

Subcode	Meaning
19	The file number is zero or is greater than the maximum number of files allowed for the database (based on the MAXFILES parameter setting when the database was defined using the ADADEF utility).
20	A regenerate/backout with exclusive database control is rejected because there are in-doubt transactions or heuristically terminated transactions on Work part 4.
21	File is locked for utility usage.
22	An attempt was made to release an advance-lock, but the lock was not set.
23	An advance-lock operation was attempted for a file that has not been loaded.
24	An advance-lock operation was attempted for a file that is already advance-locked.
25	<p>This subcode is issued by Adabas Transaction Manager.</p> <p>The client session has an open global transaction that could not be backed out because it is under the control of an external transaction coordinator and its status is "in doubt".</p> <p>Depending on the transaction coordinator, you may have a choice of actions:</p> <ul style="list-style-type: none"> <li>■ Wait for the external transaction coordinator to complete or back out the existing transaction.</li> <li>■ Use the coordinator's facilities to force completion or removal of the transaction.</li> <li>■ Restart the transaction coordinator to cause resynchronization of in-doubt transactions.</li> <li>■ Use ATM Online Services to force backout of the local, Adabas-related part of the global transaction.</li> </ul> <p><b>Caution:</b> Using ATM Online Services to force backout of the local, Adabas-related part of the global transaction could result in loss of transaction integrity.</p>
26 - 30	Reserved for Adabas Transaction Manager. These subcodes are given only when Adabas Transaction Manager is in use. Please read the Adabas Transaction Manager documentation for more information.
31	File locked for normal usage
32	A file is in use by an exclusive update (EXU) user. An update request from another user is not permitted.
33	A file is locked for exclusive file control (EXF) or utility update (UTI) usage. The request from a user with a different type is not permitted.
34	An advance-lock operation was performed on a read-only nucleus.
35	An advance-lock operation was performed during an online save.
36	Nucleus in REGENERATE/NOAUTOBACKOUT state.

Subcode	Meaning
257 - 260	Reserved for use by Event Replicator for Adabas on open systems.

On open systems, the corresponding file number is returned in the first two bytes of the Additions 2 field in binary format except for value 8 in the third and fourth byte. The value 0 means the whole database.

**Action**

The following user actions are possible:

- Wait for the other user or utility to finish, then retry the command.
- Make the file available for all users (on open systems, if value 16 occurred in bytes 3 and 4).
- Restore or unlock the file (on open systems, if value 17 occurred in bytes 3 and 4).
- Rebuild the file's index (on open systems, if value 18 occurred in bytes 3 and 4).
- On open systems, if the value in bytes 3 and 4 of the Additions 2 field is 8, and the nucleus was started with the OPEN\_REQUIRED option, you can reissue the OP command immediately. This will cause the other user with the same user ID to be stopped, unless that user is currently active.
- On open systems, if a utility receives a response 48 because non-utility users are still active, you can lock the file with ADAOPR LOCK. This ADAOPR command stops all non-utility users from accessing the file and allows only utility users to access the file until it is unlocked again.

On mainframe systems, if a utility receives a response 48 because non-utility users are still active, you can lock the file with ADADBS MODFCB FILEREADONLY. The FILEREADONLY command stops all non-utility users from accessing the file and allows only utility users to access the file until it is unlocked again.

**Response 49****Origin**

Mainframe and open systems

**Explanation**

The compressed record was too long. It exceeds the maximum permitted compressed record length for the file.

On open systems, the first two bytes of the Additions 2 field contain the length of the compressed record in binary format.

On mainframe systems, the following subcodes may be indicated:

**Note:** This response code always means that the compressed record is too long and there are duplicate meanings for subcodes but the subcode can help your Software AG technical support representative analyze where in the code we are giving the response. This can be useful for debugging purposes. Please always provide the subcode when communicating about this response code with your Software AG technical support representative.

Subcode	Meaning
	File(s) not available at open time. This is the default message displayed with this response code if another subcode is not provided.
1	Multiple-value (MU) field.
2	Periodic (PE) group field.
3	MU field.
4	PE group.
5	PE group level.
6	Remaining fields.
7	Record too long for protection logging (internal error).
8	A compressed record exceeds the permitted length. The error was detected when updating a multiple field.
9	Exceeded segment length maximum.
10	Long alpha or wide field.
11	New compressed record too long
12	Old version MU update.
13	The MU field was defined with an index
14	An MU update caused the compressed record to become too long.
15	An MU update caused the compressed record to become too long.
16	An MU update caused the compressed record to become too long.
17	MU update, MU count > 1
18	An update to an LA field caused the compressed record to become too long.
19	LOB value too long. An attempt was made to update a LOB value segment that ends after the maximum allowed length of LOB value. This response code/subcode combination is produced as a result of an L1/L4 command with Command Option 2 set to "L" but with the ISN Lower Limit value greater than or equal to the length of the LOB value being read.
20	Compressed Data Storage record too long. A LOB update attempted to make a long LOB value (greater than 253 bytes) short (less than or equal to 253 bytes), but the base record was too long to embed the short LOB value. This condition was detected when the LOB value was being read from the LOB file.
21	Compressed Data Storage record too long. A LOB update attempted to make a long LOB value (greater than 253 bytes) short (less than or equal to 253 bytes), but the base record was too long to embed the short LOB value. This condition was detected when an attempt was made to insert the short LOB value into the base record.
90	Segment too long
96	Compressed record too long
99	Exceeded segment length maximum

**Action** On open systems, add a new DATA extent with sufficient block size (block size  $\geq$  compressed record size + 8). Alternatively you can start the nucleus with `OPTIONS=AUTO_EXPAND`; then the Adabas nucleus automatically creates a new DATA extent with sufficient block size.

**Response 50**

**Origin** Mainframe and open systems

**Explanation** A syntax error in the record buffer was detected during processing of an OP command, an invalid character set was specified, an invalid time zone was specified, or an invalid file number (zero or greater than maxfiles) was specified.

On open systems, the first two bytes of the Additions 2 field contain the number of bytes (in binary format) relative to the beginning of the record buffer where the error was detected. If a time zone problem occurs, the two right-most bytes of the Additions 2 field in the ACB will contain a subcode; in an ACBX, the Error Subcode field will contain the subcode.

Subcode	Meaning
31	Time zone not found in ADAZON directory. The specified time zone was not found in the ADAZON directory. Verify the time zone was specified correctly. If it was, contact your Software AG technical support representative for assistance.
32	Time zone pool full. No more time zone information could be loaded. Increase the size of the ADARUN LTZ parameter and restart the nucleus.
33	Open error on DD:TZINFO(MEMBER). Contact your Software AG technical support representative for assistance.
34	I/O error on DD:TZINFO(MEMBER). Contact your Software AG technical support representative for assistance.
35	Invalid data in TZ file. Contact your Software AG technical support representative for assistance.
36	Invalid transition time in TZ file. Contact your Software AG technical support representative for assistance.

**Action** Correct the record buffer and try again.

**Response 51**

**Origin** Mainframe and open systems

**Explanation** An error in the record buffer was detected during processing of an OP command.

One of the keywords EXU, UPD, ACC or WCHARSET is duplicated.

On open systems, the following information is returned in the Additions 2 field of the control block:

- the first two bytes contain the number of bytes (in binary format) relative to the beginning of the record buffer where the error was detected;
- the third and fourth bytes contain the open mode that failed (ACC = 1, UPD = 2, EXU = 4, WCHARSET = 128)

**Action** Correct the record buffer and try again.

**Response 52**

**Origin** Mainframe and open systems

**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

One of the following errors occurred while processing the record, value, or search buffer. In an ACB, the rightmost two bytes of the Additions 2 field contain the subcode; for subcodes 1-5, the leftmost two bytes contain the Adabas name of the field where the error occurred. In an ACBX, the subcode is stored in the Error Subcode (ACBXERRC) field; for subcodes 1-5, the Adabas field name where the error occurred is stored in the Error Character Field (ACBXERRB).

Subcode	Meaning
1	Invalid packed or unpacked decimal value in record buffer.
2	Invalid length for variable-length field specified in record buffer.
3	Invalid null value or no value at all provided for field with NN option.
4	Invalid value for S element in record buffer.
5	Invalid value for S element in value buffer.
6	Encoding a collation descriptor value failed: the collation descriptor exit issued a return code.
7	Decoding a collation descriptor value failed: the collation descriptor exit issued a return code.
99	An invalid field length was specified.

**Open Systems**

- The value of a G format field was not in floating point format;
- The value of a P format field was not in packed decimal format;
- The value of a U format field was not in unpacked decimal format;
- A variable-length field was specified without a length parameter;
- The SQL null value indicator (S element) has a value of less than -1;
- A field with the NN option is forced to take the SQL null value;

- The resulting value exceeds 4 bytes (longword) if the format is F, or exceeds the maximum (format dependant) length;
- No record with the specified ADAM key was found.

The following information is returned in the Additions 2 field of the control block:

- The first two bytes contain the number of the byte (in binary format) relative to the beginning of the record/value buffer where the error was detected. This value is -1 if a field with the NN option is forced to take the SQL null value.;
- The third and fourth bytes contain the name of the field being processed when the error was detected.

**Action** Correct the format, record, value, or search buffer and try again.

### Response 53

**Origin** Mainframe and open systems

**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

#### Mainframe Systems

One of the following errors occurred:

Subcode	Meaning
0	<p>The record buffer is too small.</p> <p><i>Action:</i> If the record buffer size:</p> <ul style="list-style-type: none"> <li>■ conflicts with the lengths specified in the format buffer, change either the record buffer size or the format buffer specifications to resolve the conflict.</li> <li>■ conflicts with the established global format ID (GFID), either release the GFID or change the record buffer size to match the GFID.</li> <li>■ default is too small to hold the records in the file including the DVT when running the ADAULD utility, increase the size of the record buffer by setting the ADAULD LRECL parameter. See the Adabas Utilities documentation for more information.</li> </ul>
1	<p>The record buffer is too small. When locating a variable field in the input record, the required buffer length exceeded the given length.</p> <p><i>Action:</i> Verify that the record buffer content matches the given format and that sufficient space for variable fields is provided in the record buffer.</p>
2	<p>The ISN buffer is too small.</p> <p><i>Action:</i> Increase the size of the buffer.</p>

Subcode	Meaning
3	The record buffer is too small. When locating a variable field within a group in the input record, the required record buffer length exceeded the given length.  <i>Action:</i> Verify that the record buffer content matches the given format and that sufficient space for variable fields is provided in the record buffer.
4	The record buffer is too small. When locating a field with A,* notation in the input record, the required record buffer length exceeded the given length.  <i>Action:</i> Verify that the record buffer content matches the given format and that sufficient space for variable fields is provided in the record buffer.
7	At least one of the record buffers was too small for the data defined in the corresponding format buffer.
8	The referenced existing format buffer requires more space than that given in one of the record buffers.  If this subcode occurs using ADACMP DECOMPRESS, the LRECL of the output record is too small.
249	In Adabas Vista, the record buffer provided for an L9 command with 'I' option against a partitioned file is not large enough to hold the full list of ISNs.  <i>Action:</i> Increase the size of the record buffer.

**Open Systems**

The record buffer was too small, or the ISN buffer was too small for a requested multifetch command. The following information is returned in the Additions 2 field of the control block:

- The first two bytes contain the expected buffer size in binary format. This value is -1 if the command would have exceeded the maximum record size.
- The third and fourth bytes contain the name of the buffer that was too small. ("RB" or "IB"). If the error occurred while using a hyperdescriptor exit, the name of the hyperdescriptor exit is stored here.

**Action** Increase the record buffer or ISN buffer size, as appropriate.

**Response 54**

**Origin** Mainframe and open systems

**Explanation** The record buffer for a C3, C5, or ET command is too long. The maximum allowed size is 2048 bytes. The following subcodes provide more information:

Subcode	Meaning
1	The record buffer for the C3 command is too long.
2	The record buffer for the C5 command is too long.
3	The record buffer for the ET command is too long.

**Action** Correct the record buffer specification, then reissue the C3, C5, or ET command.

## Response 55

### Origin

Mainframe and open systems

### Explanation

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

#### Mainframe Systems

One of the following occurred:

- During a read-type operation, a field defined with the SQL null (NC) option contained a null value, but the format buffer held no "S" (significant null) indicator for the field.

In an ACB, the Additions 2 may contain the field name in the leftmost two bytes; the rightmost two bytes may contain the offset into the record buffer. In an ACBX, the Error Character Field (ACBXERRB) may contain the field name; the Error Offset in Buffer (ACBXERRA or ACBXERRG) fields may contain the offset into the record buffer.

- Attempted format conversion was not possible due to incompatible data formats or other compatibility problems.

In an ACB, the Additions 2 will contain the field name in the leftmost two bytes; the rightmost two bytes will contain the offset into the record buffer. In an ACBX, the Error Character Field (ACBXERRB) will contain the field name; the Error Subcode (ACBXERRC) field will contain the subcode.

Subcode	Meaning
0	Conversion error on record decompression.
1	Invalid conversion between formats.
2	Invalid length for fixed encoding. For example, user encoding Unicode with code-point size of 2 bytes and no even length specified.
4	Conversion error of a floating-point field (underflow) when converting to/from a non-IBM floating-point format.
5	One of the following conditions exists: <ul style="list-style-type: none"> <li>■ Format conversion of a field with the NV option is not allowed.</li> <li>■ In a read command (Lx, Sx), the format buffer of a field containing a null value is defined with the NC option, but without the NN option,</li> </ul>

Subcode	Meaning
	and is missing the SQL significance indicator (S). For read-type commands, the S indicator is required when the NC fields are defined without the NN option. If the S indicator is not present when a read command detects an NC-specified field and the field actually contains a null value, this response code and subcode are returned.
6	An invalid length was specified ( for example, a wide character field in Unicode encoding must have an even length).
7	Invalid conversion between formats (different case than subcode 1).
8	Conversion error of a floating-point field (overflow) when converting to/from a non-IBM floating-point format.
9	A one-byte field was provided in the record buffer for the occurrence count of an MU field or PE group in a file with extended MU/PE limits. A two-byte occurrence count value is expected.
10	A field using the NC field option has a null value and no S indicator was specified in the format buffer.
20	Unsupported date-time conversion -- internal error.
21	Date-time value outside valid range. The valid range depends on the date-time edit masks being used in the format or search buffer and the FDT.
22	Invalid local time – (non-existing local time in the gap that occurs when switching from standard to daylight saving time or when the time zone advances GMT offset)
23	Year outside range of 1-9999.
24	Month outside range of 1-12.
25	Day outside range of 1-n.
26	Hours outside range of 0-24.
27	Minutes outside range of 0-59.
28	Seconds outside range of 0-59.
30	Accessing a field defined with option TZ but no time zone was specified in the user session. Issue the OP command with TZ='timezone' parameter in the record buffer to set the time zone for the user session.
31	Invalid daylight saving offset given ( <i>fldD</i> ) for date-time and time zone.
n	Data between user and system data representation could not be converted without error and 2-byte error code from ECS.
254	Numeric field length in format shorter than the field length in the FDT.
255	Field length exceeded maximum for variable fields.

Entire Conversion Service (ECS) error codes are described in *Entire Conversion Service (ECS) Errors*, elsewhere in the Adabas Messages documentation.

## Open Systems

A format, length conversion, or truncation error occurred while processing field values in the record buffer or value buffer.

- The value for an FI field is too long;
- The resulting value exceeds the border of the FI field;
- Truncation error of numeric field;
- Truncation of alphanumeric fields or truncation of numeric fields which are converted to alphanumeric, except when OPTIONS=TRUNCATION is enabled in ADANUC;
- A value defined without LA or L4 option with variable length is larger than 253 bytes. This may happen for Unicode fields after conversion to another encoding.
- The length specified for a Unicode field for a character set with fixed character length is not a multiple of the character length: in particular, the length for UTF-16 based character sets must be a multiple of 2, and the length for UTF-32 based character sets must be a multiple of 4;
- The specified value is not a valid date/time value;
- The field does not contain a valid date/time value. This can happen if the value was stored without a date/time edit mask;
- A date/time field with option TZ was specified in the format or search buffer, but there was no time zone specified in an OP command for the current Adabas user session;
- The attempted format conversion was not possible due to incompatible data formats or other compatibility problems.

The following information is returned in the first two bytes of the Additions 2 field, and in the case of an ACBX, also in the field ACBXERRC:

Subcode	Meaning
0	Conversion error.
1	Truncation error.
2	Internal structure error.
5	Internal error.
20	Unsupported DATETIME conversion.
21	Date/time value outside valid range. The valid range depends on the date-time edit masks being used in the format or search buffer and the FDT.
22	Date/time value specified in gap when switching from standard time to daylight saving time.
24	Month not between 1 and 12.
25	Day not between 1 and n, where n is the number of days of the month specified.

Subcode	Meaning
26	Hours not between 0 and 24.
27	Minutes not between 0 and 59.
28	Seconds not between 0 and 59.
30	Internal error: missing time zone element for conversion with time zone.
31	Invalid daylight saving offset given (fldD) for date/time and time zone.

The field name is returned in the third and fourth byte of the Additions 2 field, and in the case of an ACBX in the field ACBXERRB.

In addition, the following information is returned in the case of an ACBX call:

- The offset in the record or value buffer in ACBXERRA;
- The type of buffer in ACBXERRD ('R' for error in record buffer, 'V' for error in value buffer).

**Action**

Depending on the reason:

- Correct the appropriate buffer and try again;
- If the time zone specification in the OP command is missing, execute an appropriate OP command;
- On open systems, if a record structure error is indicated, run ADAVFY FIELD against the corresponding file. If this produces errors, then the file must be unloaded, decompressed, recompressed and reloaded;
- On open systems, subcodes 2 and 5 should never occur; you should, therefore, contact your nearest support center if you receive one of these subcodes. A copy of the command log and an export copy or backup of the files accessed will help us to analyze the problem.

**Response 56**

**Origin**

Mainframe and open systems

**Explanation**

One of the following occurred:

Subcode	Meaning
.	The descriptor value was too large. Descriptor values are limited to 1144 bytes.
<i>n</i>	The collation value exceeded the maximum 253 bytes. The subcode <i>n</i> is the collation descriptor exit number.

**Action**

Store a shorter descriptor value or collation value.

On open systems, you also can specify the TR option for the descriptor, which truncates larger descriptor values before they are stored in the index. Note that with the TR

option, search results may be inaccurate: this is because values that are identical in the first 1144 bytes are considered to be equal to each other.

**Response 57****Origin**

Mainframe and open systems

**Explanation**

In an L9 command, the descriptor specified in the format or search buffer or in the Additions 1 field was invalid or the descriptor was not specified:

- The field name specified may not be the name of a descriptor.
- The descriptor specified may be a phonetic descriptor or a hyperdescriptor, which are not allowed in an L9 command.
- On open systems, the descriptor specified may be a collation descriptor with the option HE.

**Action**

Correct the descriptor in the format buffer, search buffer, or Additions 1 field and try again.

**Response 58****Origin**

Mainframe systems only

**Explanation**

The format could not be found (as defined within format selection criteria).

**Action**

Adjust the format specification and try again.

**Response 59****Origin**

Mainframe systems only

**Explanation**

Format conversion of a subfield is not possible. The source field has fixed point (F) or floating point (G) format.

**Action**

Correct the field for which you are attempting format conversion and try again.

**Response 60****Origin**

Mainframe and open systems

**Explanation**

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

A syntax error was detected in the format or search buffer. Generally in an ACB, the first two bytes of the Additions 2 field contain the two characters under inspection when the error was detected and the rightmost two bytes of the Additions 2 field in the ACB contain one of the following subcodes. In an ACBX, the Error Character Field (ACBXERRB) contains the two characters under inspection when the error was detected and the Error Subcode (ACBXERRC) field contains one of the following subcodes.

Subcode	Meaning
1	Premature end of search buffer.
2	Syntax error in search buffer; possibly a bad field name.
3	Text literal has no ending quote or is too long (more than 255 characters).
4	Text literal is empty.
5	Expected delimiter missing.
6	Soft coupling criterion has not closing parenthesis (").
7	Soft coupling criterion is empty.
8	Invalid field name, format, or search operator.
9	Invalid edit mask number (greater than 15).
10	Invalid character following field name specification.
11	Invalid specification of MU field in PE group.
12	Expected number missing or too large (greater than 2 <sup>31</sup> ).
13	Syntax error in LOB segment specification.
14	Syntax error in length indicator notation (L) specification.
15	Syntax error in daylight savings time notation (D) specification.
16	Invalid date-time edit mask specification.
17	MU/PE index range specification is invalid for LOB segment notation.

**Open Systems**

A syntax error was detected in the search buffer.

The following information will be returned in the Additions 2 field of the control block:

- The first two bytes will contain the number of the byte (in binary format) relative to the beginning of the search buffer where the error was detected;
- The third and fourth bytes will contain the name of the field being processed when the error was detected.

**Action** Correct the format or search buffer and try again.

**Response 61**

**Origin** Mainframe and open systems

**Explanation** An error was detected in the search buffer, value buffer, or during an S8 command.

**Mainframe Systems**

On mainframe systems, one of the following subcodes may also be included with this response code:

Subcode	Meaning
2	An invalid value operator was detected in the search buffer.
3	An invalid logical operator was specified for an S8 command - Command Option 2.
7	<p>This subcode indicates that one of the following errors occurred:</p> <ul style="list-style-type: none"> <li>■ The length of a descriptor value was greater than 253.</li> <li>■ Invalid file number specification.</li> <li>■ Invalid selection criteria for an Event Replicator for Adabas initial-state definition.</li> <li>■ Invalid usage of the "S" or "N" operator.</li> <li>■ The element order was invalid.</li> <li>■ The specified field was not a descriptor.</li> <li>■ The specified field has the "LA" option active.</li> <li>■ A descriptor contained in a periodic group was specified without an index.</li> <li>■ Invalid connection of partial criteria or different indices were used for a descriptor contained within a periodic group.</li> <li>■ Invalid periodic group index.</li> <li>■ Invalid or disallowed use of a phonetic descriptor.</li> <li>■ A descriptor derived from or contained in a periodic group is not allowed.</li> <li>■ The FROM-TO operator was specified with a phonetic descriptor.</li> <li>■ Invalid FROM-TO range specification, or the FROM value was greater than the TO value.</li> <li>■ The BUT-NOT value was outside the range of the preceding FROM-TO range.</li> <li>■ An invalid command option was specified for ISN LIST processing (S8 command).</li> <li>■ The search buffer "S" significant null indicator was specified with a value operator other than "EQ" (equals), which is not allowed.</li> </ul>
8	An invalid FROM-TO range was specified. The BUT-NOT value was outside the range of the preceding FROM-TO value.
9	An invalid search criteria was specified.

### Open Systems

On open systems, an error was detected in the search or value buffer, or during an S8 command:

- Invalid command option 2 specified for ISN LIST processing (S8 command);
- Invalid element or element order;

- The specified field was neither a descriptor, subdescriptor, superdescriptor nor a phonetic descriptor;
- Invalid connection of partial criteria and/or different indices used for a descriptor contained within a periodic group;
- Invalid use of a phonetic descriptor;
- Invalid periodic group index;
- Invalid index usage;
- The length of a descriptor value was greater than 253 or greater than the permitted length for the required format;
- Invalid format type;
- Invalid file number specification;
- Invalid usage of the S operator - FROM value greater than TO value;
- Invalid usage of the N operator - BUT NOT value was outside the range of the preceding FROM-TO range;
- Invalid comparator;
- The value in the value buffer cannot be converted into the field's FDT format;
- The specified file name is not an ADAM key while using the V option with an A1 or E1 command;
- Invalid value given in the value buffer while using the V option with the A1 or E1 command;
- Invalid usage of the C option - only allowed for collation descriptors;
- A field was specified with an edit mask that is not allowed for the field.

The following information is returned in the Additions 2 field of the control block (not for the S8 command):

- The first two bytes will contain the number of the byte (in binary format) relative to the beginning of the search buffer where the error was detected;
- If the third byte is zero, the fourth byte contains more information about the error:
  - Fourth byte 1: invalid length.

Otherwise the third and fourth bytes will contain the name of the field being processed when the error was detected.

**Action**

Correct the search or value buffer or S8 command and try again.

**Response 62****Origin** Mainframe and open systems**Explanation** One of the following has occurred:

- The length of the search or value buffers as specified in the search and value buffer length fields, respectively, was not sufficient to accommodate the search criteria specified.
- The first character in the search buffer was a period (.).
- The search buffer does not contain a period (.)

**Action** Correct the search or value buffer and try again.**Response 63****Origin** Mainframe and open systems**Explanation** The command ID value specified in the search buffer was invalid.

On open systems, the value in the first two bytes of the Additions 2 field indicates the reason (2 byte binary format):

Subcode	Meaning
1	The command ID value specified in the search buffer was not found.
2	The associated ISN list is not sorted in ISN sequence (it has been generated by an S2/S9 command).
3	The command ID was not used in the previous FIND in which the SAVE ISN LIST option was used.

**Action** Correct the command ID in the search buffer and try again.**Response 64****Origin** Mainframe systems only

**Explanation** This response code is used for communication with Adabas utilities and Adabas Online System (AOS), and was returned because the requested function could not be performed on the Adabas system (including checkpoint and security) files or because an error occurred in an AOS or utility function.

The following table shows some of the subcodes that may be returned:

Subcode	Meaning
61	No or duplicate field(s) (see 'xx'); where xx is the first duplicate field encountered. If no field definitions were specified an FC is returned.

**Action** Refer to the ADAREP output report for a list of the system files, or to the subcodes in the job output for more information. For AOS, a subcode is displayed in the error message, following the AOS module number. For utility functions, the subcodes may be described within the message text.

If you do not understand the action to take for a response code 64 or subcode, note the subcode and the function that caused the response code, and call your Software AG technical support representative for assistance.

**Response 65**

**Origin** Mainframe systems only

**Explanation** An internal error occurred. The nucleus detected a space calculation error.

**Action** Contact your Software AG technical support representative for assistance.

**Response 66**

**Origin** Mainframe systems only

**Explanation** An incompatible owner ID was detected during an update operation on a multicient file. The owner ID may be blank, or too long.

**Action** Contact your Software AG technical support representative for assistance.

**Response 67**

**Origin** Mainframe systems only

**Explanation** One of the following errors occurred:

Subcode	Meaning
.	An internal error occurred while executing an Sx command.
2	An error occurred during superfield generation.

**Action** Retain all related information, and contact your Software AG technical support representative for assistance.

**Response 68**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	A nondescriptor field was used as a search criterion, and the non-descriptor search facility has been set OFF (the default for this facility is ON).
<b>Action</b>	The ADARUN parameter NONDES has been set to reject non-descriptor searches; either reset the NONDES parameter to its default value, or remove non-descriptor searches from your application. Natural provides a trace facility which locates such Natural application characteristics. Contact Software AG for details.

**Response 70**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	An overflow occurred in the table of sequential commands.
<b>Action</b>	The DBA may increase the value used for the LQ parameter or RC commands may be used.

**Response 71**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	An overflow occurred in the table of resulting ISN lists.
<b>Action</b>	The DBA may increase the value used for the LI parameter or RC commands may be used.

**Response 72**

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	One of the following errors occurred:

Subcode	Meaning
6	The NU parameter is too small for the execution of a session autorestart. It is smaller than it was in the previous Adabas nucleus session that failed. In a cluster nucleus, the NU parameter is smaller than in the nucleus that had established the global lock structure.
7	An overflow occurred in the user queue.
8,9	An overflow occurred in the user queue file list pool.

<b>Action</b>	The DBA may increase the value used for the NU parameter.
---------------	---

**Response 73**

**Origin** Mainframe and open systems

**Explanation** An overflow occurred in the section of the Work data set (mainframe systems) or the temporary working space (open systems) in which resulting ISN lists are stored.

On open systems, please note that for read-only databases, temporary working space is only created if a location for it is explicitly specified (environment variable `TEMPLOCn` or entries for `TEMPORARY_LOCATION` in the file `DBnnn.INI`); otherwise only some of the space in the Adabas buffer pool is used for storing the ISN lists.

**Action** On mainframe systems, the DBA may increase the size of the Work data set and/or the number of saved ISN lists during an Adabas session may be decreased.

On open systems, provide enough temporary working space. For read-only databases, specify the location for the temporary working space explicitly or increase the size of the Adabas buffer pool (ADANUC parameter LBP).

**Note:** The processing of ISN lists was changed for Adabas Version 5.1. If you get this error with an Adabas Version 3 database, please refer to the Adabas Version 3 documentation.

**Response 74**

**Origin** Mainframe and open systems

**Explanation** No space was available on the Work data set for complex find commands.

**Action** On open systems, increase the size of the Work data set.

On mainframe systems, increasing the size of the Work data set alone will not solve this problem. Instead, set the value of LWKP2 (WORK-PART-2) to a higher value than the calculated one (whatever that might be). Then increase the size of the Work data set to ensure there is sufficient space for WORK-PART-3.

**Response 75**

**Origin** Mainframe and open systems

**Explanation** Attempts to allocate additional Associator or Data Storage extents for a file were issued, but the maximum number of extents that can be handled by the FCB have already been allocated.

On mainframe systems, BT (backout) or autorestart processing could cause the file to be locked because of inadequate extent space (see response code 48, ADARSP048).

On open systems, the last extent is allocated only for a command which is being backed out and for AUTORESTART and ADAREC REGENERATE. The first two bytes of the Additions 2 field contain the highest possible extent number (in binary format). The third and fourth bytes indicate where the overflow occurred. Possible values are: "DS" (Data Storage), "AC" (Address Converter), "NI" (Normal Index) and "UI" (Upper Index).

**Action** On mainframe systems, ask your DBA for assistance; Associator or Data Storage extents may have to be reallocated.

On open systems, unload the file and reload it with appropriate initial allocations.

### Response 76

**Origin** Mainframe and open systems

**Explanation** An overflow occurred in an inverted list index (the maximum is 15 levels).

**Action** Unload and reload the file with an appropriate padding factor for the Associator.

### Response 77

**Origin** Mainframe and open systems

**Explanation** Sufficient space was not available for a required Associator or Data Storage extent.

On mainframe systems, the following subcodes further define the error:

Subcode	Meaning
1	FST empty.
2	AC START RABN not available.
3	AC END RABN not available.
4	FST will not fit into five ASSO blocks.
5	FST exhausted trying to allocate AC extent.
6	ASSO space allocation RABN not on device.
7	ASSO space on required device not available.
8	FROM RABN available, but contiguous space is not sufficient.
9	Data Storage space of the requested size is not available.
10	Data Storage space on the same device as the previous extent is not available.
11	FST is empty, or data storage for the current MAXRECL value is not available.
12	FST empty.

On open systems, the third and fourth bytes of the Additions 2 field contain either "AS" (Associator) or "DS" (Data Storage). You can also get the response 77 if you specified an explicit RABN for an Associator or Data Storage extent and the requested space is not available at the requested RABN. Please note that Adabas distinguishes between small (< 16KB) and large (>= 16KB) index blocks. This means that a response 77 can be returned even though there are enough free Associator blocks, but the free Associator blocks have the wrong size.

**Action** On mainframe systems, ask your DBA for assistance; Associator or Data Storage extents may have to be reallocated.

On open systems, add a new Associator or Data Storage extent to the database using the ADADBM utility or specify a RABN where the requested space is available.

**Note:** Response 77 can sometimes be prevented by enabling database autoexpand to execute in the online mode (specify the open systems nucleus parameter OPTIONS=AUTO\_EXPAND).

**Response 78**

**Origin**

Mainframe and open systems

**Explanation**

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

The cause of this response is indicated by one of the following subcodes:

Subcode	Meaning
1	The AC file cannot be increased; only one file extent is permitted.
2	The file contains more than either 4 billion or 16 MB of ISNs, depending on the ISN length, or if ISNREUSE is in effect, the file has reached TOPISN and is very fragmented and too much effort would be needed to search for a free ISN.

**Open Systems**

An overflow occurred in the free space table (FST) as a result of Associator or Data Storage fragmentation, or the maximum number of DSST extents has already been allocated.

**Action**

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

If the file has reached the 16-MB limit, you might convert it to a file with the 4-byte ISN option or to an expanded file. If ISNREUSE is in effect, ADABAS ISNREUSE=ON, RESET can be used to reset the rotating ISN pointer or the file can be reloaded to eliminate the fragmentation.

If the file has NOACEXTENSION specified, look for alternatives to increase the file size such as adding an additional file to the expanded file chain. If the file is not part of an expanded file chain, you may want to reload the file to remove the restriction.

**Open Systems**

If it is an FST problem, reorder the database. If it is a DSST problem, which can only occur in the context of a utility, refer to the message DSSTALL for further information.

**Response 79****Origin**

Mainframe and open systems

**Explanation**

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

A collation descriptor exit or hyperdescriptor exit error occurred. The following table describes the possible subcodes for this response code and their meanings:

Subcode	Meaning
1	Either a collation descriptor exit (subcode CDX $n$ where $n$ is the one-byte binary collation descriptor exit number) or a hyperdescriptor exit ("hyperdescriptor exit") was not specified ADARUN.
5	The hyperdescriptor exit stub was called for an extended MU/PE file.
6	Improper use of the parameter list was detected by the Hyperdescriptor Exit Stub. The most likely reason is that a hyperdescriptor exit using the Adabas 8 parameter structures is linked to the Hyperdescriptor Exit Stub.
7	The Hyperdescriptor Exit Stub could not resolve the HEXOLD external reference.
8	Improper use of the parameter list was detected. The second word of the parameter list was modified.
9	A hyperdescriptor exit did not return an output parameter area address.
10	A hyperdescriptor exit rejected the call by setting a nonzero return code in the output parameter header.

**Open Systems**

A hyperdescriptor exit is not available to the nucleus. The following information is returned in the Additions 2 field of the control block:

- The first two bytes contain the number of the hyperdescriptor exit;
- The third and fourth bytes contain the name of the hyperdescriptor.

**Action**

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

The following table describes the actions you should take for each possible subcode for this response code:

Subcode	User Action
1	Reissue ADARUN with the CDX $nn$ or HEX $nn$ parameter. For more information about ADARUN parameters, read <i>Adabas Initialization (ADARUN Statement)</i> , in <i>Adabas Operations Manual</i> ; for more information about user exits and hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
5	The Hyperdescriptor Exit Stub may not be used with extended MU/PE files. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
6,7	Investigate the Hyperdescriptor Exit Stub link job. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
8	A likely cause of the error is that a pre-Adabas 8 hyperdescriptor exit was called without a linked Hyperdescriptor Exit Stub. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
9	Hyperdescriptor exits must return an output parameter area address upon return. For more information about hyperdescriptor exits, read <i>User Exits and Hyperdescriptor Exits</i> , in <i>Adabas User, Hyperdescriptor, and Collation Descriptor Exits Manual</i> .
10	Investigate the hyperdescriptor exit to determine why the call was rejected.

**Open Systems**

Define the hyperdescriptor exit and restart the nucleus.

**Response 81**

**Origin**

Mainframe systems only

**Explanation**

An MU or PE field error occurred, as described by the subcode:

Subcode	Meaning
1	The PE index is greater than 191 (if the maximum number of PE field occurrences is 191).
2	The PE index is greater than 65534 (if the maximum number of PE field occurrences is 65534).
3	The MU index is greater than 65534 (if the maximum number of MU field occurrences is 65534).
4	The MU index is greater than 191 (if the maximum number of MU field occurrences is 191).

**Action**

Correct the MU or PE field problem and try again. If the problem persists, contact your Software AG technical support representative for assistance.

**Response 82**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	A hyperdescriptor exit routine returned an invalid ISN.
<b>Action</b>	Correct the hyperdescriptor exit routine logic and restart the nucleus.

**Response 83**

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

A hypertable overflow occurred.

**Open Systems**

A hyperdescriptor exit routine returned an invalid ISN.

The following information will be returned in the Additions 2 field of the control block:

- The first two bytes contain the offset the invalid ISN in the specified ISN buffer in binary format;
- The third and fourth bytes contain the name of the hyperdescriptor.

<b>Action</b>	The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.
---------------	---

**Mainframe Systems****Open Systems**

Correct the hyperdescriptor exit routine and restart the nucleus.

**Response 84**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	Too many values were present for a subdescriptor or a superdescriptor.
<b>Action</b>	Reduce the number of subdescriptor or superdescriptor values and try again.

**Response 85**

**Origin** Mainframe and open systems

**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

Too many descriptor values were present for an update or add record command.

**Open Systems**

The descriptor value table space cannot be allocated from the buffer pool.

**Action** The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

**Open Systems**

Increase the size of the LBP parameter.

**Response 86**

**Origin** Mainframe and open systems

**Explanation** A hyperdescriptor exit return error occurred for one of the following reasons:

- An incorrect sign for a packed descriptor value was created.
- A value with an incorrect length byte was returned.
- The ISN was changed by an update command.

On open systems, the following information is returned in the Additions 2 field of the control block:

- The first two bytes contain a value. This value can be:
  - 1 the hyperdescriptor pool exceeds the nucleus buffer pool
  - 2 the hyperdescriptor exit has returned an invalid pointer, length or count value
  - 3 an element in the user-defined format buffer is not a parent field of the hyperdescriptor
  - 4 - 255 Adabas response code
  - >255 user-defined error return for hyperdescriptor exit routine
- The third and fourth bytes contain the name of the hyperdescriptor or the name of the parent field.

**Response 87**

**Origin** Mainframe systems only

**Explanation** The Adabas buffer pool is locked; it is too small to accommodate all blocks needed for (parallel) command execution.

**Action** Check the length of the buffer pool (LBP) as follows:

Subcode	User Action
1	Check the LBP value with DPARM.
2	Increase the ADARUN LBP parameter value.
3	Retry the operation. If the error recurs, call your Software AG support representative for assistance.

**Response 88**

**Origin** Mainframe and open systems

**Explanation** This response code generally occurs when there is a workpool (LWP) shortage. Sufficient work pool space is not available or the sort work space is too small (even if only one user is active).

On mainframes systems, when this response code occurs, refer to the hexadecimal subcode that appears in the low-order (rightmost) two bytes of the ACB's Additions 2 field or in the ACBX's Error Subcode (ACBXERRC) field. This subcode describes what kind of operation encountered the error.

The following table describes the mainframe subcodes and provides recommended actions.

Subcode	Operation Encountering the Workpool Shortage	Action
1	Only active command is waiting for workpool space.	Increase the ADARUN LWP setting and try again.
	During session autorestart, insufficient workpool or user queue space was encountered.	
2	Only active command is waiting for workpool space.	Increase the ADARUN LWP setting and try again.
3	A command waiting for workpool space was interrupted for transaction backout.	
4	A1 command	
5	E1 command	
7	Superfield value generation	
8	N1 command	

Subcode	Operation Encountering the Workpool Shortage	Action
9	OP command	
10	Descriptor value generation	
11	Hyperdescriptor value generation	
12		
13	Subdescriptor value generation	
15	DTP=RM: A getmain error during Work-Part-4 initialization.	
16	Hard-coupled file update processing encountered a workpool shortage.	
17	A session autorestart encountered a workpool shortage.	
22	Online reorder by descriptor	
23	Online invert	
24	Open one of the Work data sets in a cluster	
25	Session autorestart in a cluster	
79	Work pool shortage during release of advanced lock function.	
80	Work pool shortage during insert (N1/N2-command) of spanned record	
96	Internal command queue full	
98	Cluster with DTP=RM: Recovery of distributed transactions encountered a workpool shortage.	
99	ET command with P-option	
	Descriptor value generation for multi-client file	
	Single-user mode: Command initialization	
	Replication: Setup of initial-state process	
	DTP=RM: Insufficient user queue space during Work-part-4 initialization	

**Action**

For mainframe systems, review the actions described in the table above.

For open systems, verify the parameter values for the database that relate to the working storage allocation. Ask your DBA to increase the size of the LWP or LS parameter, as necessary.

**Response 89****Origin** Mainframe systems only**Explanation** The UQE was already in use, and an attempt was made to execute two commands at the same time for the same user.**Response 94****Origin** Mainframe systems only**Explanation** An I/O error occurred on DDWORKR4.**Response 95****Origin** Mainframe systems only**Explanation** An I/O error occurred on the Work LP area.**Response 96****Origin** Mainframe systems only**Explanation** An error occurred during ADARES REPAIR utility execution.

Subcode	Meaning
2	An I/O error occurred during nucleus termination; Additions 2 may contain RABN.

**Response 97****Origin** Mainframe systems only**Explanation** An I/O error occurred during buffer flush. Additions 2 may contain RABN.**Response 98****Origin** Open systems only**Explanation** A uniqueness violation of a unique descriptor was detected during a store or update processing if subtransactions are not activated, or otherwise at end of a subtransaction. The third and fourth bytes of the Additions 2 field contain the name of the descriptor which caused the uniqueness conflict.**Action** Check the descriptor values.

**Response 99**

**Origin** Mainframe and open systems

**Explanation** An I/O error occurred.

On open systems, the first 2 bytes of the Additions 2 field ( in binary format) contain the extent number. The third and fourth bytes contain the container type ("AS" for ASSO, or "DS" for DATA or "WO" for WORK).

**Action** On open systems, check whether any disk devices have gone offline or check the error log for hardware errors.

**Response 101**

**Origin** Mainframe and open systems

**Explanation** An error has occurred using one of the client-based Adabas add-on products such as Adabas System Coordinator or Adabas Fastpath.

**Mainframe Systems**

On mainframe systems, one of the following subcodes may also be included with this response code:

- Subcodes of 20 or less are produced by Adabas Fastpath when an error occurs during the processing of an Adabas command..
- Subcodes of 21 or greater are produced by Adabas System Coordinator.

Refer to the hexadecimal subcode that appears in the command's Adabas control block, Additions 2 field, low-order (rightmost) two bytes. The subcodes are described in the table below:

Subcode	Meaning
2	L3/L9 direct optimization internal error. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "2".
6	L3 direction change error. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "6".
7	Direction change integrity check error.This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "7".
8	Default response to internal service commands in the database. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "8".
9	Optional response for Read Ahead Update warning messages. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "9".
10	Error following a PLEX move. This is an Adabas Fastpath error. The hexadecimal representation for this subcode is "A".

Subcode	Meaning
21	Session cleanup error. This is an internal error in Adabas System Coordinator.  <i>Action:</i> Contact your Software AG technical support representative.
22	You are using the CORS09 client component in a zIIP enabler for Natural environment and Natural zap NA97065 is not applied.  <i>Action:</i> Apply Natural zap NA97065.
23	Session create error. This is probably due to insufficient memory.  <i>Action:</i> Increase the job region size. If the problem persists, contact your Software AG technical support representative.
25	CAB: Allocation failed. Insufficient memory was available for CAB. This is an Adabas System Coordinator error.  <i>Action:</i> Increase the job region size.  <b>Note:</b> This subcode is not subject to COR Debug.
26	Incorrect use of asynchronous Adabas calls.  <i>Action:</i> Contact your Software AG technical support representative.  <b>Note:</b> This subcode is not subject to COR Debug.
28	Internal thread concurrency error.  <i>Action:</i> Contact your Software AG technical support representative.  <b>Note:</b> This subcode is not subject to COR Debug.
29	Internal command error: Value buffer is not present.  <i>Action:</i> Contact your Software AG technical support representative.
30	Internal command error: Illegal function.  <i>Action:</i> Contact your Software AG technical support representative.
31	Error allocating the internal job-structure.  <i>Action:</i> Increase the job region size. If the problem persists, contact your Software AG technical support representative.
32	Internal command error: Insufficient record buffer.  <i>Action:</i> Contact your Software AG technical support representative.
33	Internal command error: Record buffer is not present.  <i>Action:</i> Contact your Software AG technical support representative.
34	Internal command error: Incorrect value buffer format.  <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
35	<p>Memory allocation failure. Insufficient memory was available for an internal area needed for NIM support. This is an Adabas System Coordinator error.</p> <p><i>Action:</i> Increase the job region size.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
38	<p>Internal command error: Unsupported memory function</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
43	<p>Initialization Error. An error occurred during job initialization in Adabas System Coordinator.</p> <p><i>Action:</i> Ensure that correct runtime controls were defined for the job. If problem persists, contact Software AG Support.</p>
46	<p>CAS: No group header record. This error appears if Adabas System Coordinator fails to find a header record for the required System Coordinator group.</p> <p><i>Action:</i> First check that you have a valid CORCFG module pointing to the correct database and file number for your configuration file. Ensure that the load library containing CORCFG is included in the load library concatenation of the job. If CORCFG is present and correct, logon to SYSCOR and verify that you have valid Daemon Group parameters for the job you are running. If all parameters are correct, contact your Software AG technical support representative for assistance.</p>
49	<p>Internal eventing error: Illegal request.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
50	<p>Internal error processing add-on products.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
53	<p>This job is not defined to use the daemon.</p> <p><i>Action:</i> Review and correct the installation for this job.</p>
54	<p>Internal services error.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
55	<p>Latency processing error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
56	<p>Latency processing error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>

Subcode	Meaning
	<b>Note:</b> This subcode is not subject to COR Debug.
59	<p>CORSnn: Critical products. One or more products have been defined as "Critical" in the Corrdinator configuration file, and one of the following errors was detected:</p> <ul style="list-style-type: none"> <li>■ The Adabas System Coordinator Kernel module (CORKRN) was not found.</li> <li>■ Adabas System Coordinator initialization has failed. There will be a Coordinator message indicating the cause of the initialization failure.</li> </ul> <p><i>Action:</i> Determine the cause of the concurrent command and modify the application to remove it.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
60	<p>CORKRN: Critical Products. One or more products have been defined as "Critical" in the Adabas System Coordinator configuration file, and the product has indicated a critical error during initialization.</p> <p><i>Action:</i> Determine the cause of the concurrent command and modify the application to remove it.</p>
62	<p>CORS02/CORS12: Subsystem storage protect facility not activated. Com-plete has been customised to operate with mixed thread keys, but the IBM subsystem Storage Protection override facility is not enabled. Adabas System Coordinator requires this facility to support mixed thread keys in Com-plete.</p> <p><i>Action:</i> Either activate the Subsystem Storage Protection override facility in this system OR change the Com-plete thread groups to operate in Com-plete's key only (see the description of the THREAD-GROUP parameter in the Com-plete documentation).</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
64	<p>Net-Work Clustering: Node not member of Group. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
65	<p>Net-Work Clustering: Message segment protocol error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
66	<p>Net-Work Clustering: Message sequence error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>

Subcode	Meaning
67	<p>z/OS only: Invalid SVC is being used for the execution of an Adabas call.</p> <p><i>Action:</i> Review and correct the installation. If the problem persists, contact your Software AG technical support representative.</p>
68	<p>z/OS only: The batch Adabas System Coordinator client component (CORS01) is being incorrectly used for a Multi-TCB job.</p> <p><i>Action:</i> Refer to installation step “Add the System Coordinator to the Adabas Client” in the Installation Procedure section of the Adabas System Coordinator Installation documentation for information regarding the available CORS0<i>n</i> client components and their applicability to different job types.</p> <p>If the problem persists, contact your Software AG technical support representative.</p>
69	<p>Insufficient memory to initialize runtime controls. There is insufficient memory for COR to initialize. This is an Adabas System Coordinator error.</p> <p><i>Action:</i> Increase the memory available to the job.</p>
81	<p>Internal UB Getmain error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
82	<p>Invalid session pointer. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
83	<p>Internal session UB not found. This is an internal error.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
84	<p>Internal error in Adabas buffer analysis. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
85	<p>Internal thread getmain error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Increase the job region size and rerun the job. If the problem persists, contact your Software AG technical support representative.</p>
86	<p>Invalid command block pointer. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
87	<p>Client versioning has not been installed correctly.</p> <p><i>Action:</i> Check the job for any console messages and ensure that client versioning is installed correctly.</p>

Subcode	Meaning
88	<p>Adabas CICS link module and TRUE have not been installed correctly.</p> <p><i>Action:</i> Ensure that the Adabas CICS link module and TRUE are installed correctly. This must be done to enable Adabas System Coordinator to operate in a CICS job.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
89	<p>The NIM subtask is in the process of being detached.</p> <p><i>Action:</i> None, this subcode simply indicates that a NIM subtask was still issuing Adabas commands when it was terminated by the main NIM task.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
90	Internal handshake token validation error.
91	<p>Latency processing error (no facility). This is an internal error in Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
92	<p>Asynchronous call with no CAB. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
93	<p>Latency processing error (memory). This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Increase the job region size. If the problem persists, contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
94	<p>Latency processing lock error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
95	<p>Daemon latency processing error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Ensure that the System Coordinator daemon is available.</p> <p>If the client that receives this error is using the COLAT daemon latency disk file to manage their session-related information, then this subcode may be indicative that the disk file is full. If so, check the daemon job log for any accompanying error messages.</p>

Subcode	Meaning
	<p>If the problem persists, contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
96	<p>Latency processing error (facility deleted). This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
97	<p>Latency processing lock error when using daemon latency.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
102	<p>Latency processing unlock error. This is an internal error in Adabas System Coordinator.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
103	<p>Latency processing error for IMS.</p> <p><i>Action:</i> Increase the size of the Daemon latency /pulse services shared memory area size in the COR daemon parameters.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
200	<p>When running Multi-system dynamic transaction routing (z/OS only), there was an error writing to the Coupling Facility Cache structure.</p> <p><i>Action:</i> Refer to the accompanying COR010S message in the daemon.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
201	<p>When running Multi-system dynamic transaction routing (z/OS only), there was an error reading from the Coupling Facility Cache structure.</p> <p><i>Action:</i> Refer to the accompanying COR009S message in the daemon.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
202	<p>When running Multi-system dynamic transaction routing (z/OS only), an incorrect record was read from the Coupling Facility Cache structure.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>

Subcode	Meaning
203	<p>When running Multi-system dynamic transaction routing (z/OS only), there was a memory shortage in the local daemon when attempting communications with a peer daemon.</p> <p><i>Action:</i> Increase the region size for the daemon. If the problem persists, contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
204	<p>When running Multi-system dynamic transaction routing (z/OS only), there was a protocol error in the local daemon when attempting communications with a peer daemon.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
205	<p>When running Multi-system dynamic transaction routing (z/OS only), a peer daemon returned an error when contacted by the local daemon.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
206	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was an internal problem identifying the correct facility.</p> <p><i>Action:</i> Contact your Software AG technical support representative. <b>Note:</b> This subcode is not subject to COR Debug.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
207	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was a memory shortage in the local daemon.</p> <p><i>Action:</i> Increase the region size for the daemon. If the problem persists, contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
208	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was a protocol error in the local daemon when attempting communications with a peer daemon.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>

Subcode	Meaning
209	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, a peer daemon returned an error.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
210	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was an internal error with the facility size.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
211	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, the facility could not be moved into daemon managed shared memory in the local daemon due to a lack of space.</p> <p><i>Action:</i> Refer to the daemon group member parameter Daemon latency/pulse services and increase the size of the dataspace. If the problem persists, contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
212	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was an internal error writing to daemon managed shared memory.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
213	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, there was a protocol error in the local daemon when attempting to remove the facility from a peer daemon.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>
214	<p>When running Multi-system dynamic transaction routing (z/OS only) and attempting to move a facility across the Sysplex, a peer daemon returned an error when instructed to remove a facility.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p> <p><b>Note:</b> This subcode is not subject to COR Debug.</p>

## Open Systems

On open systems, one of the following Adabas System Coordinator subcodes may also be included with this response code:

Subcode	Meaning
1 (0x0001)	The standard Adabas or Entire Net-Work ADALNKX library could not be loaded.  <i>Action:</i> Check that the ADALNKX parameter in the Initialisation File (cor.cfg) is set correctly and that the library exists.
2 (0x0002)	The standard Adabas or Entire Net-Work ADALNKX library could not be loaded.  <i>Action:</i> Contact your Software AG technical support representative.
3 (0x0003)	The standard Adabas or Entire Net-Work ADALNKX library does not export all expected functions.  <i>Action:</i> Check that the ADALNKX parameter in the Initialisation File refers to an ADALNKX library and not an ADALNK or ADALNK32 library.
4 (0x0004)	Adabas did not return the database architecture information in the ISN lower limit field when an OP command was issued to the Configuration File.  <i>Action:</i> Contact your Software AG technical support representative.
5 (0x0005)	The path to the Initialisation File (cor.cfg) could not be determined.  <i>Action:</i> Check the HKLM\SOFTWARE\Software AG\Adabas System Coordinator registry key and ensure the Path value is set correctly (Windows).  Check that the \$CORDIR and \$CORVERS environment variables are set correctly (Unix).
6 (0x0006)	The ADALNKX parameter could not be read from the Initialization File (cor.cfg).  <i>Action:</i> Check that the Initialization File exists and that the ADALNKX parameter is set correctly.
7 (0x0007)	The LFILE parameter could not be read from the Initialization File.  <i>Action:</i> Check that the Initialization File (cor.cfg) exists and that the LFILE parameter is set correctly.

Subcode	Meaning
8 (0x0008)	<p>An incompatible version of an Adabas add-on product is installed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
9 (0x0009)	<p>An incompatible version of an Adabas add-on product is installed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
10 (0x000A)	<p>The library for an Adabas add-on product could not be loaded.</p> <p><i>Action:</i> Check that the Adabas add-on product is installed correctly.</p>
11 (0x000B)	<p>The library for an Adabas add-on product could not be unloaded.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
12 (0x000C)	<p>The address or length of the format, record, search, value or ISN buffer appears to be invalid.</p> <p><i>Action:</i> Check the buffer addresses passed to the adabas() function and the lengths specified for the buffers in the Adabas control block.</p>
13 (0x000D)	<p>The CORADC load module could not be fetched (Mainframe).</p> <p><i>Action:</i> Check that \$STEPLIB environment variable is correct and that the CORADC load module exists in the specified data set.</p>
14 (0x000E)	<p>Port range exhausted (there are not enough allocated to this computer).</p> <p><i>Action:</i> Configure a larger port range for the Adabas System Coordinator Computer using System Management Hub.</p>
15 (0x000F)	<p>Port conflict (the allocated port is in use by another application).</p> <p><i>Action:</i> Assign a different port to the Adabas System Coordinator daemon or change the port range for the Adabas System Coordinator computer using System Management Hub.</p>
16 (0x0010)	<p>Computer name could not be generated.</p> <p><i>Action:</i> The Adabas System Coordinator Launch Control could not generate a unique computer name for the machine. Create an Adabas System Coordinator computer for this machine manually using System Management Hub.</p>

Subcode	Meaning
17 (0x0011)	The FDT of the Configuration File is not compatible with Adabas System Coordinator. <i>Action:</i> Check that the database and file numbers are correct.
18 (0x0012)	The version of Adabas is not compatible with Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative.
19 (0x0013)	The SAGABS library could not be loaded. <i>Action:</i> Check that the SAGABS library is installed.
20 (0x0014)	The SAGABS library could not be unloaded. <i>Action:</i> Contact your Software AG technical support representative.
21 (0x0015)	The SAGABS library is not compatible with Adabas System Coordinator. <i>Action:</i> Contact your Software AG technical support representative.
22 (0x0016)	Port conflict (the allocated port is in use by another Adabas System Coordinator Group). <i>Action:</i> Assign a different Group Services port to the Adabas System Coordinator Computer using System Management Hub.
23 (0x0017)	Unable to spawn process (the command line parameters specified for the process are invalid). <i>Action:</i> Contact your Software AG technical support representative.
24 (0x0018)	Length of compressed record buffer length exceeds limit. <i>Action:</i> Contact your Software AG technical support representative.
25 (0x0019)	Length of compressed record buffer could not be determined. <i>Action:</i> Contact your Software AG technical support representative.
26 (0x001A)	Product not installed or not configured correctly. <i>Action:</i> Check that the Adabas add-on product is installed correctly.

Subcode	Meaning
27 (0x001B)	<p>Configuration file version does not match the running version.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
28 (0x001C)	<p>Configuration file layout is not as expected for a configuration file.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
29 (0x001D)	<p>The installed Adabas version does not correctly process LF 'S' commands (Adabas 6.1.9 or earlier).</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
30 (0x001E)	<p>The installed Adabas version does not support LF 'I' commands (unzapped Adabas 8.2.2 or earlier).</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
31 (0x001F)	<p>Migration of the Configuration File was unsuccessful.</p> <p><i>Action:</i> Check the output of the migration process for errors. If the reason for an unsuccessful migration cannot be determined, contact your Software AG technical support representative.</p>
52 (0x0034)	<p>Exception reading/writing pointer.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
0000A001-FFFFA001	<p>A TCP/IP error occurred.</p> <p><i>Action:</i> The left-hand side of the subcode contains the operating system error code.</p>
0000A002-FFFFA002	<p>A DNS error occurred.</p> <p><i>Action:</i> The left-hand side of the subcode contains the operating system error code.</p>

**Response 102**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	Space calculation error.
<b>Action</b>	Retry the open operation.

**Response 105**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	An ADAECS error occurred. Please check for an accompanying ADAN7A message with further information.

**Response 106**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	The prefetch table record buffer specified in the UDB is too small.

**Response 107**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	Either a GETMAIN error occurred or there was insufficient space when performing prefetch. Prefetch is switched off.

**Response 109**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	The specified command ID is already active on another database for this user.

**Response 110**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	The command ID pool is full.
<b>Action</b>	Increase the size of either or both the ADARUN NQCID or NU parameters.

**Response 113**

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	The specified ISN was invalid for one of the following reasons: <ul style="list-style-type: none"><li>■ An HI command was issued with ISN less than MINISN or with an ISN equal to zero (0).</li><li>■ An N2 command was issued with ISN equal to 0 or larger than the MAXISN in effect for the file.</li><li>■ An N2 command was issued and the specified ISN was assigned to another record in the file.</li></ul>

- An A1, L1/L4, or S1/S2/S4 (with FB) command was issued for a nonexistent ISN, or an E1 command for a nonexistent ISN other than zero.
- An L3/L6 command found an ISN in the index which did not exist in the address converter.
- An N1/N2 command tried to access a file protected by security-by-value, but the command user is not authorized to access the file.
- A read or update command tried to access a multicient file's record using either a blank or incorrect-length owner ID, or an owner ID that does not apply to the record.
- An RI command was issued for a record that has been updated earlier in the same transaction. The record cannot be released from hold status prior to transaction end. On mainframe systems, subcode 5 is issued for this reason.
- Subcode 19 is given when a base file record is not found in the address converter (AC). At the end of a LOB update in the LOBfile, the associated base file record no longer existed.
- Subcode 249 is given only when Adabas Vista is in use. Refer to the Adabas Vista documentation for more information.

**Open Systems**

On open systems, the following subcodes may occur:

Subcode	Meaning
249 (0x00F9)	<p>An invalid ISN was detected by Adabas Vista (open systems). The ISN specified for an E1, HI or L1 command is not consistent with the definitions for the partitioned file.</p> <p><i>Action:</i> Review the program logic</p>

**Action**                      Correct the ISN problem and try again.

**Response 114**

**Origin**                        Mainframe and open systems

**Explanation**                A refresh file function using the E1 command was issued (E1 with ISN=0), and one of the following situations has occurred.

The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

One of the following subcodes may be present:

Subcode	Description
1	A file refresh is not permitted for the file because either <ul style="list-style-type: none"> <li>■ the file parameter setting is PGMREFRESH=NO (can be checked with ADAREP or via Adabas Online Services (AOS) Display File )</li> <li>■ or the command ID field (ACBCID or ACBXCID) is not all blanks.</li> </ul>
2	The user has not completed transactions to the file. Updates have been performed or records are still in hold, but the user has not issued an ET or BT command to commit or back out the updates.
3	Other users are accessing or updating the file. This is determined by the user access or update counts available internally to Adabas.
4	The file is a multiclient file and the user is not a superuser.

### Open Systems

One of the following situations has occurred:

- PGM\_REFRESH is not specified for the file.
- The user session is not at ET status.

### Action

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

#### Mainframe Systems

If you forgot to specify the ISN for the E1 command, the CID setting is incorrect, the command was not issued at ET status or the user is no superuser: correct your program accordingly.

If other users are accessing or updating the file STOP these users.

If PGMREFRESH=YES was not specified for the file in question, specify PGMREFRESH=YES for the file with ADADBS or Adabas Online Services (AOS) or load the file with the appropriate ADALOD parameter.

#### Open Systems

If you forgot to specify the ISN for the E1 command, or the command was not issued at ET status, correct your program. If PGM\_REFRESH was not specified for the file in question, specify PGM\_REFRESH for the file with ADADBM.

**Response 123**

**Origin** Mainframe systems only

**Explanation** An error was reported by the Adabas cluster messaging service on the sender's side. The message was not sent. One of the following subcodes may be present:

Subcode	Meaning
4	No valid destination(s)
8	Too many destinations
12	Invalid message type
16	Invalid environment
20	Send buffer length exceeded
24	Receive buffer length exceeded
28	No replies or acknowledgment(s) before the message timed out. For more information about the timeout value, refer to descriptions of the ADARUN MXMSG parameter.
32	Unable to allocate AXMCB
36	Timed out on originating system
40	Timed out on destination system
44	Canceled on destination system
48	Receive error on destination system
52	Unable to allocate buffer
56	Too many buffer elements
80	Messaging is inactive
96	Terminate member unsuccessful
128	Other Trans- port service error

**Action** If you are unable to resolve the problem, contact your Software AG technical support representative.

**Response 124**

**Origin** Mainframe systems only

**Explanation** An error was reported by the Adabas cluster messaging service on the receiver's side. The message was sent. One of the subcodes described for response code 123 (ADARSP123) may be present.

**Action** If you are unable to resolve the problem, contact your Software AG technical support representative.

**Response 125**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	An internal error occurred when one cluster nucleus attempted to issue an internucleus command to one or more of the other cluster nuclei. This condition usually leads to abnormal termination.
<b>Action</b>	Contact your Software AG technical support representative.

**Response 126**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	A messaging error occurred during internucleus communication: <ul style="list-style-type: none"> <li>■ The nucleus did not respond within the allotted time (see the ADARUN MXMSG parameter); or</li> <li>■ One or more problems occurred in what could be a broadcast; that is, a communication with multiple targets. In this case, each individual ACB contains either response code 0 (ADARSP000) or 123 (ADARSP123) or 124 (ADARSP124).</li> </ul>
<b>Action</b>	If you are unable to resolve the problem, contact your Software AG technical support representative.

**Response 129**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	In an Adabas cluster environment, the user attempted to perform an Adabas function that is not yet supported by Adabas cluster nuclei.

**Response 130**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	An error identified by one of the following subcodes occurred in an Adabas cluster environment:

Subcode	Description
1	A user table entry (UTE/PLXUSER) was not found in the MPM 8 call. This may indicate that a command was directed to an Adabas Cluster Services or Adabas Parallel Services nucleus ID (NUCID), not the DBID.
2	A user table entry (UTE/PLXUSER) was not found in the MPM 12 call.
9	The associated PLXUSER(UTE) was unsuitable at command initiation. One possibility is that the UQE of the user was deleted between the time the user's command was routed to one nucleus in the cluster and the time that nucleus selected the command for processing. Another possibility is that the PLXUSER and UQE UID string did not match because the PLXUSER may have been released and possibly reassigned to another user.

Subcode	Description
10	The associated PLXUSER(UTE) was unsuitable at command completion. The PLXUSER and UQE UID string did not match because the PLXUSER may have been released and possibly reassigned to another user.
11	No Work data set entry in active PPT block (bad PPT block).
12	Invalid internal NUCID (internal error).
13	Invalid external NUCID (bad PPT block, internal error).
14	Work data set already open for same internal NUCID, other external NUCID.
15	Work data set already open for same external NUCID, other internal NUCID.
16	Different Work data set already open for same peer nucleus.
17	Work data set of peer nucleus could not be opened.
18	I/O error when trying to read Work data set of peer nucleus.
19	Unexpected (invalid) data in Work data set of peer nucleus.
20	Mismatching DBID in Work data set.
21	Mismatching Adabas version indicator in Work data set.
22	Work data set written by non-cluster nucleus.
23	Partially written block in Work data set protection data extension area.

**Action** For subcode 1, correct the application program attempting to issue commands using the NUCID. If that is not the case, or for other subcodes, contact your Software AG technical support representative for assistance.

**Response 131**

**Origin** Mainframe systems only

**Explanation** In most cases this response code will be given to the user in the URBRRSP field of the URBR block with the subcode in the URBRSUB field. The subcode appears either in the low-order (rightmost) two bytes of the additions 2 field or in the URBRSUB field. It indicates the specific cause and action for this response code. The following are the subcodes and their meanings:

Subcode	Meaning
1	The combination of URBD plus payload data does not fit in the output buffer.  <i>Action:</i> Change the subscription definition to make the record shorter.
2	The subscription user exit set a value in URBERRRC.  <i>Action:</i> Check the URBERRRC field and correct the error if appropriate.
3	There is insufficient space in the nucleus replication pool. In other words, the value specified by LRPL has been exceeded.  <i>Action:</i> Increase the LRPL size of the nucleus and try again.

Subcode	Meaning
4	There is insufficient space in the Event Replicator Server replication pool. In other words, the value specified by LRPL has been exceeded.  <i>Action:</i> Increase the size of the LRPL parameter and try again.
5	The subscription user exit modified data length (URBDLEND) to an invalid value.  <i>Action:</i> Check the subscription user exit.
6	The response destination (URBIRNAM) specified in a client request is undefined or not usable for sending the response.  <i>Action:</i> Correct the status request to specify the name of an existing destination definition.
7	Both the subscription (URBISNAM) and the destination (URBIDNAM) to be specified in a status request are missing. At least one of them must be specified.  <i>Action:</i> Correct the status request.
8	The subscription (URBISNAM) specified in a status request is undefined.  <i>Action:</i> Correct the status request.
9	The initial state name specified was not found.  <i>Action:</i> Correct the initial-state request.
10	The destination for response in URBI following URBI 1 is not equal to those of URBI 1.  <i>Action:</i> Correct the initial-state request.
11	The initial state name in URBI following URBI 1 is not equal to that of URBI 1.  <i>Action:</i> Correct the initial-state request.
12	The combination of DBID and file specified in the initial-state request is not found in the initial-state definition.  <i>Action:</i> Correct the initial-state request.
14	Not all combinations of DBID and file are specified in the initial-state request. A URBI must be sent for each DBID/file specified in the initial-state definition.  <i>Action:</i> Correct the initial-state request.
15	Field URBILEND is invalid.  <i>Action:</i> Correct the initial-state request.
16	The specified ISNLIST is invalid.  <i>Action:</i> Correct the initial-state request.

Subcode	Meaning
17	<p>The initial-state process has been stopped by an operator request.</p> <p><i>Action:</i> No action is required.</p>
18	<p>Different request tokens have been specified in different URBI elements in the same message.</p> <p><i>Action:</i> Correct the initial-state request.</p>
19	<p>Selection data is not allowed for an initial-state definition for all records or for destination open/close client requests.</p> <p><i>Action:</i> Correct the initial-state or destination open/close client request.</p>
20	<p>Invalid input data for decompression was found during the subscription phase.</p> <p><i>Action:</i> Check the index of the replicated file.</p>
22	<p>The file/DBID supplied for the initial-state process is deactivated for replication.</p> <p><i>Action:</i> Check the cause of deactivation and repeat the request after reactivation.</p>
23	<p>Invalid UES parameter in URBI . URBIARC, URBIACOD, and URBIWCOD must contain invalid values and must not be all blanks.</p> <p><i>Action:</i> Verify that the URBIARC, URBIACOD, and URBIWCOD elements are not all blanks.</p>
24	<p>Invalid UES parameter in URBI.</p> <p>URBIARC, URBIACOD and URBIWCOD must be zero for input requests where encoding and architecture is not evaluated -- that is, for status requests, destination open/close requests, "initial state all records" or "initial state ISN list" requests.</p> <p><i>Action:</i> The URBIARC, URBIACOD, and URBIWCOD elements must be zeros for "initial state all records" requests, "initial state ISN list" requests, status requests, or destination open/close requests. Verify that this is the case.</p>
25	<p>The unused URBIRES1 and URBIRES2 fields must contain binary zeros for all requests.</p> <p><i>Action:</i> Verify that these fields contain binary zeros.</p>
26	<p>The destination (URBIDNAM) specified in a client request is either undefined or not usable for sending the response.</p> <p><i>Action:</i> Correct the client request.</p>
27	<p>No active destinations for status request.</p> <p><i>Action:</i> No action is required.</p>

Subcode	Meaning
28	An initial-state request was issued to an Event Replicator Server address space that was terminating as a result of an ADAEND or HALT command. An initial-state request may only be issued when the Event Replicator Server is active.  <i>Action:</i> Reissue the initial-state request when the Event Replicator Server has been restarted.
30	Unknown response destination name in URBIRNAM for a prior-transaction request.  <i>Action:</i> Correct the prior-transaction request.
31	Unknown destination name in URBIDNAM for a prior-transaction request.  <i>Action:</i> Correct the prior-transaction request.
32	Unknown or omitted subscription name in URBISNAM for a prior-transaction request.  <i>Action:</i> Correct the prior-transaction request.
33	Destination in URBIDNAM is not related to subscription in URBISNAM for a prior-transaction request.  <i>Action:</i> Correct the prior-transaction request.
34	Subscription in URBISNAM has no resend buffer defined for a prior-transaction request.  <i>Action:</i> Correct the prior-transaction request.
35	Transaction in URBITSNR for subscription in URBISNAM was not found in the resend buffer. The transaction may have been overwritten in the circular resend buffer.  <i>Action:</i> Check the source of the transaction number.
36	The subscription in URBISNAM is not active.  <i>Action:</i> No action is required.
37	An invalid transaction was found in the resend buffer. This is an internal error.  <i>Action:</i> Notify your Software AG technical support representative.
38	There are no active destinations for a prior-transaction request.  <i>Action:</i> No action is required.
39	URBILEND must be zero for prior-transaction requests.  <i>Action:</i> Correct the prior-transaction request.
40	URBIDBID and URBIFNR may not be specified for this type of client request.  <i>Action:</i> Correct the client request.

Subcode	Meaning
41	<p>URBIINAM may not be specified for prior-transaction requests.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
42	<p>UES parameters URBIARC, URBIACOD and URBIWCOD may not be specified for prior-transaction requests.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
43	<p>Reserved fields URBIRES1 and URBIRES2 must be zero for prior-transaction requests.</p> <p><i>Action:</i> Correct the prior-transaction request.</p>
44	<p>Number of active concurrent initial-state requests exceeded IMAXREQ.</p> <p><i>Action:</i> Increase the IMAXREQ setting or reduce the number of active concurrent initial-state requests.</p>
45	<p>Input request URBH eyecatcher is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
46	<p>Input request URBHLEN is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
47	<p>Input request URBHBORD is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
48	<p>Input request URBHVERS is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
49	<p>Input request message truncated.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
50	<p>Input request URBHLENT is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>

Subcode	Meaning
51	<p>Input request URBILENH is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
52	<p>Input request URBILEND is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
53	<p>Input request URBILEN is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
54	<p>Input request reserved area is not zero.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
55	<p>Input request more than one status received.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
56	<p>Input request invalid URBI request received.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
57	<p>Input request different interleaved requests received.</p> <p><i>Action:</i> Verify that you are submitting only one kind of request to the Event Replicator Server. Only one type can be submitted at a time (for example, you cannot request initial-state processing and transaction status information requests in the same message).</p> <p>Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>
58	<p>Invalid destination for response.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i> .</p>

Subcode	Meaning
59	<p>A replay request was issued for a database not defined to the Event Replicator Server.</p> <p><i>Action:</i> Correct the DBID in the replay request or define the database to the Event Replicator Server.</p>
60	<p>Invalid replay token. The replay token is not defined or is outdated.</p> <p><i>Action:</i> Specify a valid replay token.</p>
61	<p>Invalid request sent to Event Replicator Server. RBL is insufficient, no FB provided on Init handshake or other such errors.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>
62	<p>After an Adabas failure and session autorestart, replication data was recovered for which a matching FDT was no longer available. The FDT had been changed or deleted by a utility operation. Adabas suppressed the record images of the replicated records, because without a matching FDT, the Event Replicator Server could not process them.</p> <p><i>Action:</i> Use application-specific means to bring the replicated data in sync again, if necessary.</p>
63	<p>The file specified in a C5 command with R-option is not replicated.</p> <p><i>Action:</i> Specify the file number of a replicated file.</p>
64	<p>The filter defines a comparison between two field types for which a comparison is invalid.</p> <p><i>Action:</i> Correct the filter definition.</p>
65	<p>The filter refers to a field that is not defined in the internal format buffer.</p> <p><i>Action:</i> Correct the filter definition or define the field in the database.</p>
66	<p>The filter defines a comparison against a field that is not selectable as it has no type (for example, a superdescriptor).</p> <p><i>Action:</i> Correct the filter definition.</p>
67	<p>The filter uses values in an FLIST specification that are invalid or out of range.</p> <p><i>Action:</i> Correct the filter definition.</p>
69	<p>Replay for same DBID/FNR already running.</p>
71	<p>Date/time format or value incorrect for replay.</p> <p><i>Action:</i> Check the syntax of the specified date and time values. Do not specify future date and time values.</p>
72	<p>Incorrect replay parameters.</p> <p><i>Action:</i> Check and correct the specified replay parameters.</p>

Subcode	Meaning
73	<p>A subscription involved in the replay was inactive at the beginning of replay processing or was deactivated while the replay was running.</p> <p><i>Action:</i> Reactivate the deactivated subscription and rerun the replay process for the subscription.</p>
74	<p>A destination involved in the replay was inactive at the beginning of replay processing or was deactivated while the replay was running.</p> <p><i>Action:</i> Reactivate the deactivated destination and rerun the replay process for the destination.</p>
75	<p>A replay destination that was defined without SLOG was closed at the beginning of replay processing or while the replay was running.</p> <p><i>Action:</i> Reopen the closed destination and rerun the replay process for the destination.</p>
76	<p>ADARPL terminated abnormally.</p> <p><i>Action:</i> Investigate the cause of the error, correct it, and run a new replay job.</p>
77	<p>Invalid replay status transition. Events that change the status of a replay process occurred in an unexpected order.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>
78	<p>New transactions from Adabas could not be kept on hold during a replay in synchronized mode.</p> <p><i>Action:</i> Run a new replay process involving the same subscriptions and destinations as the previous replay process to recover the replication data that Adabas produced while the first replay was running.</p>
79	<p>A replay process was canceled by a user (RPLCLEANUP operator command).</p> <p><i>Action:</i> If appropriate, run another replay job with corrected parameters.</p>
80	<p>A timeout occurred while the Event Replicator Server was waiting for the end of a synchronization process after reactivating replication for a file in Adabas. The synchronization process ends when all transactions have finished that had updated the file before it was reactivated.</p> <p><i>Action:</i> Wait until the Event Replicator Server reports the activation of the file (ADAF2L message). Then run a new replay job.</p>
81	<p>A utility other than ADARPL specified a replay token when connecting to the Event Replicator Server.</p> <p><i>Action:</i> Notify your Software AG technical support representative.</p>

Subcode	Meaning
82	<p>The Event Replicator Server is not connected to Adabas at the start of a replay process with the TOKEN parameter.</p> <p><i>Action:</i> Start Adabas and let it connect to the Event Replicator Server. When running a replay with the TOKEN parameter, Adabas must be active.</p>
83	<p>Neither a subscription nor a destination was specified in a replay request.</p> <p><i>Action:</i> Specify at least one subscription or destination.</p>
84	<p>A replay in replay-only mode was requested, but replication data from Adabas would flow through an active subscription-destination pair involved in the replay. For a replay in replay-only mode, some subscriptions and destinations must be inactive such that no data from Adabas can flow through the same subscription-destination pairs as the replay data from ADARPL.</p> <p><i>Action:</i> Change the replay parameters or the activation status of the subscriptions or destinations involved in the replay.</p>
85	<p>A file involved in the replay was inactive at the beginning of the replay or deactivated while the replay was running.</p> <p><i>Action:</i> Reactivate the deactivated file and rerun the replay process for the subscriptions involved in the replay that get data from the file.</p>
86	<p>Invalid format buffer was specified for destination-type Adabas update commands.</p> <p><i>Action:</i> Correct the format buffer.</p>
87	<p>An unexpected message sequence number was encountered.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
88	<p>An unrecognized eye-catcher was encountered in control block following the URBH.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
89	<p>The same subscription name was specified more than once for an Adabas automated replay (defined using the Adabas Event Replicator Subsystem).</p> <p><i>Action:</i> Verify that a subscription is specified only once in an automated replay, and try again.</p>
90	<p>The same destination name was specified more than once for an Adabas automated replay (defined using the Adabas Event Replicator Subsystem).</p> <p><i>Action:</i> Verify that a destination is specified only once in an automated replay, and try again.</p>

Subcode	Meaning
91	<p>The replay start date and time were not supplied for an automated replay (defined using the Adabas Event Replicator Subsystem) or for multiple destination open/close client requests.</p> <p><i>Action:</i> Verify that a destination is specified only once in an automated replay or in multiple destination open/close client requests and try again.</p>
92	<p>The timeout parameter specified for an automated replay was too high.</p> <p><i>Action:</i> Reduce the timeout parameter value and try again.</p>
93	<p>PLOG information was not recorded in the Event Replicator Server system file.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
94	<p>The AI/BI format buffer was used also for the key. An attempt was made to decompress a key value, but the related format buffer is for data storage and not for a key.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
95	<p>An attempt to set user/Event Replicator Server encoding 01-RPEQU * failed. This might occur if you are using enhanced filtering logic and UES SACODE/SWCODE/SARC values are set for a subscription.</p> <p><i>Action:</i> Contact your Software AG support representative.</p>
96	<p>The Adabas nucleus that was the target of an initial-state request returned response code 148 (ADARSP148), indicating it is not available.</p> <p><i>Action:</i> Start the targeted Adabas nucleus and retry the initial-state request.</p>
97	<p>A format buffer was specified which contains a LOB field, which is not supported.</p> <p><i>Action:</i> Correct the format buffer.</p>
99	<p>The subscription name (URBISNAM) specified in the destination open/close client request contains a value other than spaces.</p> <p><i>Action:</i> Correct the destination open/close client request by setting this field to spaces.</p>
100	<p>The transaction sequence number (URBITSNR) specified in a destination open/close client request contains a value other than binary zeroes.</p> <p><i>Action:</i> Correct the destination open/close client request by setting this field to binary zeroes.</p>
101	<p>The destination open/close request failed on some tasks.</p> <p><i>Action:</i> Investigate the cause of the error.</p>
102	<p>The destination open/close request failed.</p> <p><i>Action:</i> Investigate the cause of the error.</p>

Subcode	Meaning
103	<p>The destination open/close request was not performed because the destination's status was already in the state being requested. In other words, the destination was already opened or closed.</p> <p><i>Action:</i> No action is required.</p>
104	<p>Begin byte in field filter is longer than the field length.</p> <p><i>Action:</i> Adjust the specifications for the beginning byte or length and try again.</p>
105	<p>Begin byte plus the portion length in the field filter is longer than the field length.</p> <p><i>Action:</i> Adjust the specifications for the beginning byte or the portion length and try again.</p>
106	<p>Begin byte or length not supported for field with format U, P, F, G, or W.</p> <p><i>Action:</i> Specifying a beginning byte or length is only supported for alphanumeric and binary fields. Change the field on which you are working or abandon this attempt.</p>
107	<p>Length value invalid for field.</p> <p><i>Action:</i> Adjust the length specification and try again.</p>
108	<p>Input request URBI eyecatcher is invalid.</p> <p><i>Action:</i> Correct the input information and try again. For more information, read <i>Event Replicator Client Requests</i> in the <i>Event Replicator for Adabas Application Programmer's Reference</i>.</p>
109	<p>An Adabas security (ADASCR) function has been invalidly replicated to a subscription file defined with SFSECURITYFILE=NO.</p> <p><i>Action:</i> Ensure the subscription file definition used for the security file is defined with SFSECURITYFILE=YES.</p>
110	<p>An invalid Adabas security (ADASCR) pseudo transaction has been replicated to the Event Replicator Server.</p> <p><i>Action:</i> Contact your Software AG technical support representative for assistance.</p>
111	<p>A replicated record (e.g., delete, insert, refresh, or update) has been invalidly replicated to a subscription file defined with SFSECURITYFILE=YES.</p> <p><i>Action:</i> Ensure that the subscription file definitions for a file, other than a security file, is defined with SFSECURITYFILE=NO.</p>
118	<p>Replay-Only Replay is not allowed if one or more destinations involved are closed.</p> <p><i>Action:</i> Ensure that the destination(s) selected for replay-only mode replay processing are not closed.</p>

**Action** Perform the action provided for the appropriate subcode in the subcode table.

## Response 132

**Origin** Mainframe and open system

**Explanation** The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

### Mainframe Systems

This response code indicates that an error occurred while Adabas was reading or updating a *LOB file*. The subcode indicates the kind of error.

If the subcode is less than 256, it is the same as the original response code that occurred during LOB file processing. The most likely subcodes are listed in the table below. For subcodes not listed, see the description of the Adabas response code with the same value.

If the subcode is greater than 256, it signals an error condition unique to the processing of LOB files. These subcodes are listed in the table below.

Subcode	Description
8	A LOB file operation was aborted due to a pending backout of the user's command or transaction. One reason for this backout may be that the user's transaction occupied too much space on the protection area on the Work data set (see response code 9 (ADARSP009), subcode 15).
17	The LOB file is not loaded.
48	The LOB file is locked for exclusive read or update by another user.
65	An internal error in the work pool space calculation occurred for LOB file processing.
113	A LOB file segment record was not found in the Address Converter element referred to by the LOB file index. Either the LOB file is physically inconsistent or an illegal concurrent LOB file update occurred during the LOB file read operation.
145	An attempt failed to put a LOB file segment record on hold for a user, because it was already held by another user. This subcode indicates illegal update contention for the same large object field value. The base file-LOB file pair is possibly inconsistent.
165	The LOB file descriptor is not found in the index; The LOB file index is bad.
172	An ISN in the LOB file index is bad. The LOB file may be physically inconsistent.
175	The descriptor value in a LOB file segment record differs from the descriptor value in the LOB file index. Either the LOB file is physically inconsistent or an illegal concurrent LOB file update occurred during the LOB file read operation.

Subcode	Description
177	A LOB file segment record was not found in the Data Storage block referred to by the Address Converter. Either the LOB file is physically inconsistent or an illegal concurrent LOB file update occurred during the LOB read operation.
257	An error in the base file-LOB file linkage exists; a file with LB fields is not really the <i>base file</i> of the <i>LOB group</i> .
258	An error in the base file-LOB file linkage exists; the file linked to the base file of a LOB group is not really a LOB file.
259	An error in the base file-LOB file linkage exists; the LOB file linked to a base file of a LOB group refers back to a different base file (or none at all).
260	An error in the base file-LOB file linkage exists; either no LOB file was linked to a base file or the LOB file number is invalid.
261	The LOB file has been left in an inconsistent state by an aborted utility execution.
262	An LB field length element specification error occurred in the format buffer ('xxL,4,B' was expected).
263	An invalid LOB file segment descriptor was encountered. The set of LOB file segment records associated with one LB field value is inconsistent. Either the LOB file is bad or an illegal concurrent LOB file update occurred during the LOB file read operation.
264	An invalid LOB file segment record was encountered. The contents of a LOB file record are inconsistent. The LOB file is bad.
265	The length of an LB field value in the LOB file differs from the length stored in the associated base file record. Either the base file and the LOB file are out-of-sync or an illegal concurrent LOB file update occurred during the LOB file read operation.
266	A bad LB field value reference was encountered in a base file record. The base file is bad.
267	An LB field value referred to in a base file record is not present in the LOB file. Probably, the base file and the LOB file are out-of-sync.
268	Internal LOB update error. At the end of a LOB update in the LOB file, the LOB value reference or placeholder was not found in the associated base file record where it was expected. Possibly, the base file record was changed in parallel.
270	Internal LOB update error. At the end of a LOB update in the LOB file, the base record was not in exclusive hold status anymore.
297	A planned feature for large object (LB) fields (for example, character code conversion of LB field values) is not yet supported.
298	Too many (more than 32,767) LB field occurrences were specified in the format buffer.
299	An internal error occurred due to LOB file processing.

### Open Systems

LOB data processing may fail because of concurrent updates. If a new attempt to process the LOB data also fails, this response code is returned. The subcode (field ACBXERRC in the ACBX) provides more information:

Subcode	Description
297	A planned feature for large object (LB) fields (for example, character code conversion of LB field values) is not yet supported.
300	The referential integrity and uniqueness checks done by subtransactions are currently not compatible with commands that modify LOB values.

**Action** The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

### Mainframe Systems

Resolve the problem described in the subcode list in the explanation.

### Open Systems

If one of the subcodes above occurs, you must change the program that is making the Adabas calls.

If the subcode (field ACBXERRC in the ACBX) is not one of the subcodes mentioned above, and if the response code 132 is reproducible even though the accessed LOB fields are not being updated, contact your Software AG technical support representative.

## Response 133

**Origin** Mainframe systems only

**Explanation** An error was detected when an attempt was made to replicate a compressed record. The subcode identifies the kind of error.

Subcode	Description
1	The function is not permitted for this type of file. The file is a LOB-file.
2	The compressed input record length is invalid .
11	The record structure is invalid.
12	An invalid elementary empty field was encountered. The structure does not agree with the FDT definition.
13	An invalid multiple-field count was encountered.
14	An invalid periodic group count was encountered.
15	An invalid structure of an elementary field was encountered.
65	A space calculation error occurred.

**Response 134**

**Origin** Mainframe systems only

**Explanation** An error was detected when creating system fields. The subcode identifies the kind of error.

Subcode	Description
1	An invalid update parameter was encountered (logic error).
2	The field is not a system field.
4	The file does not support a setting of MUPEX=2 (number of MU occurrences greater than 191).

**Response 144**

**Origin** Mainframe and open systems

**Explanation** One of the following occurred:

- The ISN specified with an update (A1) command was not in hold status for the user and command option H was not specified.
- An ET or BT command specifying the M (multifetch) option specified an ISN in the ISN buffer that is not in hold status for the user. All currently held ISNs are released from hold status.

In this case on open systems, the first 2 bytes of the Additions 2 field (in binary format) contain the offset of that ISN in the ISN buffer.

**Action** Put the ISN in hold status before using the A1 command or the multifetch ET or BT commands.

If Adabas Transaction Manager is in use, verify that the setting for the Transaction Model parameter is appropriate for the program that was executing and is also appropriate for the runtime environment in use.

**Response 145**

**Origin** Mainframe and open system

**Explanation** The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

On mainframe systems, one of the following situations occurred:

- An N1/N2 command was issued, but no hold queue entry was available.

- A command was issued with the return option specified that attempted to hold an ISN already in the hold queue for another user. The command is not placed in wait status.

Use the subcode associated with this response code to further clarify why this response occurred.

Subcode	Meaning
0	N2 command for an existing ISN was issued.
1	Hold queue space problem detected. The user is the only active user and is running with the -R option.
2	The ISN was held by someone else. The read request is running with the -R option.
8	The hold status of a record could not be upgraded from shared to exclusive because another user was already waiting to do the same. The two users became deadlocked.
9	Two or more users became deadlocked while holding ISNs and attempting to put more ISNs in hold status.

### Open Systems

On open systems, one of the following situations occurred:

- An attempt was made to insert a record using an N2 command with an ISN that is in hold status.
- An attempt was made to hold an ISN which was in hold status for another user and the R option is specified. In this case, the Additions 2 field contains the binary value 0;
- Hold queue overflow. In this case, the Additions 2 field contains a value not equal to 0.

**Note:** This hold queue overflow error can only occur with Adabas versions < 5.1.

### Response 146

#### Origin

Mainframe and open systems

#### Explanation

The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

### Mainframe Systems

An invalid buffer length was detected by the Adabas interface routine. If the command uses a classic ACB, the buffer is larger than 32,767. If the command uses an ACBX, the buffer is greater than 2,147,483,647, or the send length in the ABD is greater than the buffer length. The subcode identifies the buffer type:

Subcode	Buffer Type
1	Format buffer
2	Record buffer
3	Search buffer
4	Value buffer
5	ISN buffer
6	User information buffer
7	Performance buffer
8	Multifetch buffer

**Open Systems**

An invalid buffer length was detected by the Adabas interface routine, in an MC call, or one of the following errors occurred for a multifetch command:

- the buffer header was invalid (both offsets are set)
- at least one ISN buffer offset was not divisible by 4
- the start offset was outside the multical call buffer range
- the record buffer was not large enough to contain all subcommand control blocks.

The value in the Additions 2 field identifies the buffer: the first 2 bytes contain the buffer number in binary format, the last two bytes contain the buffer name, as shown in the following table:

Bytes 1-2	Bytes 3-4
1	FB (format buffer)
2	RB (record buffer)
3	SB (search buffer)
4	VB (value buffer)
5	IB (ISN buffer)

**Action**                      Correct the buffer length and try again.

**Response 147**

**Origin**                        Mainframe and open systems

**Explanation**                The exact meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

The ISN was invalid. The ISN transformation resulted in a negative ISN or an ISN greater than the maximum ISN permitted for the file.

**Open Systems**

A user buffer is not accessible by the Adabas interface routine.

**Action**

The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems****Open Systems**

Check whether the control block, format buffer, value buffer, record buffer and ISN buffer have valid addresses and lengths. Check whether the control block, ISN buffer and record buffer are write-protected.

**Response 148****Origin**

Mainframe and open systems

**Explanation**

The Adabas nucleus was either not active or not accessible (a call could not be sent to the Adabas nucleus when the command was issued). In an ACB, refer to the hexadecimal subcode that appears in the low-order (rightmost) two bytes of the Additions 2 field; in an ACBX, refer to the binary subcode that appears in the Error Subcode (ACBXERRC) field.

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

The following are the decimal equivalents of the subcodes and their meanings:

Subcode	Occurrence Location	Description	Action
0	open systems	No active database server was found, either local or remote.	Start the nucleus and reissue the command.
1	mainframe systems	Exclusive database control requirement conflicts with read-only nucleus status.	Remove the READONLY=YES parameter setting for the nucleus and restart it.
2	mainframe systems	A nonprivileged call was made to the nucleus while it was in utility-only (UTI) mode.	Remove the UTIONLY=YES parameter setting for the nucleus and restart it.
3	mainframe and open systems	The nucleus is performing shutdown processing (an ADAEND operation) and will not accept new users or new transactions. Either a new user is attempting to begin operation	Wait for the nucleus to shut down, restart it, and reissue the command.

Subcode	Occurrence Location	Description	Action
		or an existing user in ET status is trying to continue operation.	
4	mainframe systems	A utility with exclusive database control is running.	Either stop the utility or wait for its processing to complete (this is preferred) and try again.
5	mainframe systems	A single-user nucleus could not start operation due to an error that could not be corrected.	Verify that single-user mode has been set up correctly and restart the nucleus.
8	mainframe systems	A user is performing a logical ADALNK call. The IDT for the call has not been allocated.	On BS2000 systems, check the setting of the parameter accessed by the link name DDLNKPAR or DDCARD, or in the macro B2CONFIG of the module SSFB2C. Also check the IDTNAME parameter of the database to be accessed.
21	open systems	Entire Net-Work access communication has failed. The first two bytes of the Additions 2 field contain an error number.	Refer to your Entire Net-Work documentation for further information.
22	open systems	There is a problem with the Adabas IPC (Interprocess communication) driver. The first two bytes of the Additions 2 field contain an error number.	Shut down the nucleus, if it is still active, and restart it. If the error still occurs, try issuing the command <code>showipc -kd &lt;dbid&gt;</code> , then restart the nucleus and reissue the command.
23	Adabas open systems version 3.1 only	There is a problem attaching the Adabas IPC (Interprocess communication) driver's shared memory	Shut down the nucleus, if it is still active, and restart it. If the error still occurs, try issuing the command <code>showipc -kd &lt;dbid&gt;</code> , then restart the nucleus and reissue the command.
24	open systems	The ADALNK shared library cannot be loaded correctly.	Check the locations and permissions of the ADALNK shared library.
26	open systems	An IPC (Interprocess communication) problem occurred during open processing, e.g. the shared memory could not be attached.	One reason for these messages may be that someone has deleted an IPC resource. If this is the case, shut down the nucleus, if it

Subcode	Occurrence Location	Description	Action
27	open systems	An IPC (Interprocess communication) problem occurred during a read in the message queue.	is still active, and restart it. If the error still occurs, try issuing the command <code>showipc -kd &lt;dbid&gt;</code> , then restart the nucleus and reissue the command.
28	open systems	An IPC (Interprocess communication) problem occurred during a write in the message queue.	Another reason these messages may occur may be that the IPC resources are not sufficient. In this case, increase the IPC resources, or decrease the values of some nucleus parameters on which the required amount of IPC resources depends, or stop some other process that also consumes IPC resources. For more information about IPC resources, refer to the section <i>Increasing System V IPC Resources</i> in the Adabas open systems installation documentation.
29	UNIX platforms only	IPC (Interprocess communication) resources exist, but the database server was not active.	Issue the command <code>showipc -kd &lt;dbid&gt;</code> , restart the nucleus, and reissue the command.
50	mainframe systems	At command completion RSP148 was set but without a subcode. This subcode is set to indicate the command was processed by the target. This often occurs in a Cluster or Parallel Services environment when one of the targets is no longer active.	Contact your Software AG support representative for assistance.
51	mainframe systems	The command router found no suitable target. The target was determined not to be an Adabas Cluster Services or Adabas Parallel Services database.	Contact your Software AG support representative for assistance.
52	mainframe systems	The command router found no suitable target. The target was determined to be an Adabas	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
		Cluster Services or Adabas Parallel Services database.	
53	mainframe systems	The command router found a suitable target but the target became inactive while queuing the command.	Contact your Software AG support representative for assistance.
54	mainframe systems	When the caller attempted to retrieve the results of a completed command the target was no longer active.	Contact your Software AG support representative for assistance.
55	mainframe systems	The target became inactive while the caller was attempting to retrieve the results of a completed command.	Contact your Software AG support representative for assistance.
58	mainframe systems	An error occurred while POSTing the Adabas nucleus ECB after queuing a command.	This may be seen if the nucleus is terminating. Otherwise contact your Software AG support representative for assistance.
59	mainframe systems	This subcode is set as a default in the first stage of command routing.	Contact your Software AG support representative for assistance.
61	mainframe systems	A command sent from a nucleus to another nucleus caused an ABEND while the caller was attempting to initiate the command. The target may have become inactive. The ABEND was intercepted and recovered.	This may be seen if the target nucleus is terminating. Otherwise contact your Software AG support representative for assistance.
64	mainframe systems	A command sent from a nucleus to another nucleus caused an ABEND while the caller was attempting to retrieve the results of a completed command. The target may have become inactive. The ABEND was recovered by ADAMPM.	This may be seen if the target nucleus is terminating. Otherwise contact your Software AG support representative for assistance.
101/201	mainframe systems	Set in SVCCLU when a specifically designated local nucleus is not available for a physical call. The 201 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
102/202	mainframe systems	Set in SVCCLU when a specifically designated remote nucleus is not available for a physical call. The 202 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
103/203	mainframe systems	Target ID disagreement between IDTE and PLXNUC. The 203 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
104/204	mainframe systems	Unable to find PLXMAP matching an existing PLXUSER. The 204 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
105/205	mainframe systems	Entire Net-Work unavailable, cannot route existing user to remote nucleus. The 205 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
106/206	mainframe systems	Entire Net-Work unavailable, cannot route new user to remote nucleus. The 206 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
107/207	mainframe systems	No nucleus available for remote user. The 207 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
108/208	mainframe systems	Incorrect PLXMAP update received by LOCAL=YES nucleus. The 208 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
109/209	mainframe systems	An internal command used to synchronize across multiple nodes was received for an Adabas Parallel Services database. Such databases may execute on only one node. Depending on intersystem communications timing this may occur as a database is changed from Adabas Cluster Services to	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
		Adabas Parallel Services. Otherwise this is a logic error.	
110/210	mainframe systems	Unable to assign specified nucleus to remote user. The physical command arrived via Entire Net-Work for a specific nucleus, but the specified nucleus is on another system. Only one Entire Net-Work transmission is allowed. The 210 subcode appears when this subcode is set on a remote node.	Contact your Software AG support representative for assistance.
1019	open systems	No active database found.	Contact your Software AG support representative for assistance.
1020	open systems	The Entire Net-Work relay failed.	Contact your Software AG support representative for assistance.
1021	open systems	EC: Not XTS directory information available.	Contact your Software AG support representative for assistance.
1022	open systems	No context found.	Contact your Software AG support representative for assistance.
1023	open systems	No local database found.	Contact your Software AG support representative for assistance.
1024	open systems	Invalid context found.	Contact your Software AG support representative for assistance.
1025	open systems	General logic error; no XTS found.	Contact your Software AG support representative for assistance.
1026	open systems	A server shutdown occurred.	Contact your Software AG support representative for assistance.
1027	open systems	A server overload occurred.	Contact your Software AG support representative for assistance.
1028	open systems	The server rejected a call.	Contact your Software AG support representative for assistance.

Subcode	Occurrence Location	Description	Action
1029	open systems	No such DBID.	Contact your Software AG support representative for assistance.
1030	open systems	The database is inactive.	Contact your Software AG support representative for assistance.
1031	open systems	No response.	Contact your Software AG support representative for assistance.
1032	open systems	An invalid protocol was found.	Contact your Software AG support representative for assistance.
1033	open systems	An unknown response occurred.	Contact your Software AG support representative for assistance.
1034	open systems	Remote communication is not allowed.	Contact your Software AG support representative for assistance.

**Action** Review the user actions provided in the explanation above.

### Response 149

**Origin** Open systems only

**Explanation** A communication error was detected. The Additions 2 field contains the system service completion code which caused the error response.

Subcode	Description
1035	Context allocation failed.
1036	Inconsistent architecture encountered.
1037	XTS error 149/224 occurred.

**Action** Contact your Software AG technical support representative for assistance.

### Response 150

<b>Origin</b>	Open systems only
<b>Explanation</b>	Too many database nuclei have been used in parallel. The Additions 2 field contains the maximum number of nuclei allowed in parallel.
<b>Action</b>	Do not use more database IDs in a single program than the value given in the Additions 2 field.

### Response 151

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	A command queue overflow occurred.  <b>Note:</b> If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.
<b>Action</b>	The DBA may increase the value of the NC parameter or the command may be issued when there is a lower level of command activity.  If you are running Entire System Server and receive this response code, your database administrator should increase the size of the NCQE parameter. For more information, refer to the startup parameter documentation included in your Entire System Server administration documentation.

### Response 152

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	The internal user buffer was not large enough to contain the user buffer areas.
<b>Action</b>	On mainframe systems, the DBA should increase the value of the LU parameter used by the Entire Net-Work nucleus.  If you are running Entire System Server and receive this response code, your database administrator should increase the size of the IUBL parameter. For more information, refer to the startup parameter documentation included in your Entire System Server administration documentation.  On open systems, contact your Software AG technical support representative.

### Response 153

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	A second Adabas call was issued while the first one was still being processed.

Subcode	Description
1050	A thread is pending.
1051	A user ID is pending.

**Action** Issue only one call at a time.

#### Response 154

**Origin** Mainframe and open systems

**Explanation** One of the following occurred:

- The Adabas call was canceled by the user (open systems).
- The command was rejected because it resulted in a trigger being fired, but the queue is full at this time. (mainframe)

**Action** On open systems, no action is required for this informational message. On mainframe systems, retry the command.

#### Response 155

**Origin** Mainframe systems only

**Explanation** A command resulted in a pre-command trigger being fired. The triggered procedure returned a nonzero command, so the command was not executed.

**Action** Check the Additions 4 field for the error returned from the procedure.

#### Response 156

**Origin** Mainframe systems only

**Explanation** A command resulted in a post-command trigger being fired. The triggered procedure returned a nonzero command, indicating an unsuccessful execution of the procedure.

**Action** Check the Additions 4 field for the error returned from the procedure.

#### Response 157

**Origin** Mainframe systems only

**Explanation** A command resulted in either a pre- or post-command trigger being fired; however, Adabas Triggers has been shut down with the option to reject all commands that result in a trigger being fired.

**Action** Determine the cause of the shut-down and resolve the problem. If rejection of commands is not the required action in such a situation, then set the error action field in the Adabas Triggers profile to halt or ignore.

**Response 159**

**Origin** Mainframe systems only

**Explanation** The Adabas link module is missing or invalid. One of the following occurred:

- No Adabas link module is linked to the Natural nucleus and the Adabas link module specified in the Natural profile parameter ADANAME could not be loaded.
- (CICS only) The loaded Adabas link module is macro-level in a command-level only environment.

**Action** Check the setting of the Natural profile parameter ADANAME and/or provide the correct version of the Adabas link module in one of the current STEPLIBs.

**Response 160**

**Origin** Mainframe systems only

**Explanation** Too many Associator and Data Storage blocks were marked as active in the buffer pool for a single command.

**Response 161**

**Origin** Mainframe systems only

**Explanation** The RABN chain in the header list of the Adabas buffer pool is invalid.

**Response 162**

**Origin** Mainframe and open systems

**Explanation** No additional space is available for the Adabas buffer pool.

**Action** Increase the value of the ADARUN LBP parameter.

On open systems, because the buffer pool overflow is normally caused by too many blocks in the buffer pool waiting to be written to disk, specifying a low value for the WRITE\_LIMIT parameter is recommended.

**Response 163**

**Origin** Mainframe systems only

**Explanation** The RABN to be linked into the RABN header chain is already in the chain.

The following table shows some of the subcodes that may be returned:

Subcode	Description
1	The RABN to be linked into the RABN header chain is already in the chain.
2	A file extent overlap exists such that the same data storage RABN has been assigned to two different files.
3	A supposedly unused data storage RABN is already in use.
4	A file extent overlap exists such that the same Associator RABN has been assigned to two different files.
5	A supposedly unused Associator RABN is already in use.

**Action** Contact your Software AG technical support representative for assistance.

#### Response 164

**Origin** Mainframe systems only

**Explanation** Too many work areas were allocated for the command.

#### Response 165

**Origin** Mainframe and open systems

**Explanation** A descriptor name was either invalid or did not exist in the descriptor value table (DVT). For expanded files: the descriptor does not exist on all component files.

On open systems, this error may occur during ADAREC generate if one of the following occurs:

- A file was loaded with an incorrect FDT.
- ADAINV was not reexecuted following a stop at a SYNCP checkpoint.

In an ACB, the leftmost two bytes of Additions 2 may contain the descriptor name; in an ACBX, the Error Character Field (ACBXERRB) may contain the descriptor name. If this occurred for an expanded file, check to see if there is an FDT mismatch between the components of the file.

On open systems, bytes 3 and 4 of the Additions 2 field contains the name of the descriptor that caused the error.

**Action** On open systems, if the error is not a handling error, run the INDEX option of ADAVFY and contact your Software AG technical support representative.

**Response 166**

**Origin** Mainframe and open systems

**Explanation** An error was detected in an inverted list index; a descriptor value was not found during a delete operation. The cause may be damage in the Associator.

On open systems, bytes 3 and 4 of the Additions 2 field contains the name of the descriptor that caused the error.

**Action** On open systems perform the following steps:

1. Locate the descriptor that caused the error in the Additions 2 field of the user control block;
2. Run the VERIFY option of ADAINV for this descriptor and save the output;
3. Reinvert the descriptor;
4. If necessary, restart the database (if this is possible);
5. Send the following information to your Software AG technical support representative:
  - The output of the VERIFY option of ADAINV;
  - All available PLOGs;
  - The FDT of the file containing the error;
  - If the nucleus crashed, the crash directory.

**Response 167**

**Origin** Mainframe and open systems

**Explanation** The meaning of this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

The field in a coupled file does not exist or the coupled list is invalid.

**Open Systems**

An error was detected in an inverted list index; a descriptor value was already present during an insert operation.

Bytes 3 and 4 of the Additions 2 field contains the name of the descriptor that caused the error.

**Action** The method of resolving the error varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

**Open Systems**

Complete the following steps:

1. Locate the descriptor that caused the error in the Additions 2 field of the user control block;
2. Run the VERIFY option of ADAINV for this descriptor and save the output;
3. Reinvert the descriptor;
4. If necessary, restart the database (if this is possible);
5. Send the following information to your nearest support center:
  - The output of the VERIFY option of ADAINV;
  - All available PLOGs;
  - The FDT of the file containing the error;
  - If the nucleus crashed, the crash directory.

**Response 168****Origin**

Mainframe systems only

**Explanation**

An internal command ID required during coupling processing was not found.

**Response 170****Origin**

Mainframe and open systems

**Explanation**

The Adabas RABN required for the command could not be located for one of the following reasons:

- The buffer segment was called with a RABN of zero.
- The specified RABN does not belong to this database and is invalid.

On open systems, the Additions 2 field contains the invalid RABN in 4 byte binary format.

**Action**

On open systems, run the LOST, INDEX and DATA options of ADAVFY for the file in question and contact your Software AG technical support representative.

**Response 171****Origin**

Mainframe systems only

**Explanation**

The constant set used by Adabas could not be located.

**Response 172**

**Origin** Mainframe and open systems

**Explanation** On mainframe systems, an ISN was less than the MINISN or greater than the MAXISN setting in effect for the file.

On open systems, the maximum possible ISN of the file was reached and no more can be allocated.

**Action** On open systems, if the file contains significantly less than  $2^{32}$  records, you should unload the file with ADAULD and reload it with ADAMUP without USERISN. However, you must be aware that problems may arise if the ISNs have semantics for you - if, for example, you use the ISNs to reference records in this file, additional reorganization of these references will be necessary. The alternative to unloading and reloading the data is to split up your data into more than one file, and to adapt your application accordingly.

**Response 173**

**Origin** Mainframe and open systems

**Explanation** An invalid Data Storage RABN was detected.

On open systems, the Additions 2 field contains the invalid RABN in 4 byte binary format.

**Action** On open systems, run the DATA option of ADAVFY for the file in question and contact your Software AG technical support representative.

**Response 174**

**Origin** Mainframe systems only

**Explanation** For an L2/L5 command with start ISN, the Data Storage RABN stored in the address converter for the file is invalid.

**Response 175**

**Origin** Mainframe systems only

**Explanation** An inconsistency was detected between the index and Data Storage.

This response code can be expected when reading a descriptor value for a ciphered file if an incorrect cipher code was used.

Subcode	Meaning
99	On logical reads and simple searches without hold, the index value is compared with the value from the data record to ensure consistency. When the values do not match, the read or search is repeated in order to avoid the effects of a possible parallel update. If the values still do not match, response 175 is given.

**Action** Run the ADACHK utility against the file, and contact your Software AG technical support representative.

### Response 176

**Origin** Mainframe and open systems

**Explanation** Either an inconsistency was detected in an inverted list or an internal error occurred during inverted list processing.

On open systems, the Additions 2 field contains the inconsistent RABN in 4-byte binary format.

On mainframe systems, the following possible subcodes are associated with this response code:

Subcode	Meaning
2	Bad index
3	Invalid search request
4	Invalid format indicator or field not found in FDT/SDT
11	Invalid search request
12	Bad index block
13	Bad UI block
14	Mismatch block length
15	Bad MI block
16	Mismatching block length
17	Bad NI block
18	Bad ISN count
21	Bad index block
22	Mismatching block length
23	Invalid ISN count
29	Inactive index block
31	Bad index block
32	Mismatching block length
33	Invalid ISN count

Subcode	Meaning
39	Inactive index block
41	Bad index block
42	Mismatching block length
43	Bad MI block
44	Bad NI block
81	Invalid level indicator
82	Bad element position in block
83	Position in block did not match element lengths
84	Bad MI block
85	Bad NI block
86	Bad NI block
87	Invalid ISN count
88	Position in block did not match element lengths
89	Index block not active
91	Wrong level
92	Mismatching block length

**Action** On mainframe systems, run an appropriate ADACHK utility function to determine whether an inconsistency exists in an inverted list. If not, contact your local Software AG technical support representative. Make sure to report the subcode to your Software AG technical support representative.

On open systems, check if an autorestart or an ADAREC REGENERATE have disabled the index. If not, run the INDEX option of ADAVFY for the file in question. If the INDEX option signaled errors, you should recreate the entire inverted list with ADAINV REINVERT ALL or contact your Software AG technical support representative.

**Response 177**

**Origin** Mainframe and open systems

**Explanation** A record could not be found in the Data Storage block in which it should have been contained as indicated by the address converter. On mainframe systems, if this response code is returned to the ADAULD UNLOAD utility function with the parameter SORTSEQ, the file might be inconsistent and data lost.

Subcode 19 is issued because the base file record was not found in Data Storage. At the end of a LOB update in the LOB file, the associated base file record was no longer present in the data storage block.

**Action** On mainframe systems, check the file with the ADACHK ACCHECK utility function and contact your Software AG technical support representative.

On open systems, run the AC option of ADAVFY for the file in question and contact your Software AG technical support representative.

**Response 178**

**Origin** Mainframe systems only

**Explanation** An internal error occurred when updating a multiple-value field:

Subcode	Meaning
1	Inconsistency in descriptor value table (DVT).
2	An inconsistency was detected between the field definition table (FDT) and the internal format buffer.
3	Inconsistency when updating a phonetic descriptor.

**Response 179**

**Origin** Mainframe systems only

**Explanation** Internal error; identifier could not be found in Work part 3.

**Response 181**

**Origin** Mainframe systems only

**Explanation** Autobackout was executed and the start of a transaction could not be located.

**Response 182**

**Origin** Mainframe and open systems

**Explanation** Necessary ET data was not found in the appropriate Work block.

**Action** On open systems, save WORK1 and send it to your nearest Software AG technical support representative together with a description of what caused the pending autorestart and, if possible, the dump directory and the PLOG. Then restore and regenerate the database.

**Response 183**

**Origin** Mainframe systems only

**Explanation** An internally assigned number for a database I/O operation was detected as invalid.

**Response 184**

**Origin** Mainframe systems only  
**Explanation** A phonetic field name could not be found.

**Response 185**

**Origin** Mainframe systems only  
**Explanation** The ADAM field could not be found in the compressed record.

**Response 186**

**Origin** Mainframe systems only  
**Explanation** A wrong cipher code has been specified or a compressed data record is bad (does not conform to the Field Description Table).

The leftmost two bytes of the ACB's Additions 2 field or the ACBX's Error Subcode (ACBXERRC) field contain the field or descriptor name where the error was detected. The rightmost two bytes of the same ACB or ACBX field contain an internal code identifying the routine that detected the error.

**Action** If the file that was accessed when this response code occurred is ciphered, check whether the correct cipher code has been specified. Correct the cipher code, if necessary.

If the error is not due to an incorrect cipher code, run the ADACMP DECOMPRESS INFIL utility function to unload and decompress all records of the file. ADACMP will write records where it detects errors to its error dataset (DD/FEHL). Contact your Software AG technical support representative for assistance.

**Response 187**

**Origin** Mainframe systems only  
**Explanation** The response indicates that an invalid Data Storage block was detected while locating a record by ISN. One of the following error conditions occurred:

- An invalid block length (negative) was encountered.
- An invalid record length (not positive) was encountered.
- The sum of the record lengths is not equal to the block length plus 4.

The Additions 2 field contains the Data Storage block number where the error was detected.

**Action** Contact your Software AG technical support representative for assistance.

**Response 196****Origin** Open systems only**Explanation** Referential integrity has been violated. Bytes 3 and 4 of the Additions 2 field contain the name of the violated constraint. Bytes 1 and 2 of the Additions 2 field contain the reason as a two-byte binary number:

Subcode	Meaning
1	Required ISN in hold by another user
3	Maximum number of ISNs held by one user is reached
5	Check integrity mismatch, required value not found during check
7	Double update to a record within a cascade detected
8	Limit of stacked commands reached

**Action** Handle the referential integrity violation, for example, write an error message.**Response 197****Origin** Mainframe systems only**Explanation** The DEUQ pool is too small.**Action** Increase the ADARUN LDEUQP parameter.**Response 198****Origin** Mainframe systems only**Explanation** An attempt was made to duplicate a descriptor value for a unique descriptor. In an ACB, the leftmost two bytes of the Additions 2 field may contain the descriptor name; in an ACBX, the Error Character Field (ACBXERRB) may contain the descriptor name. The following subcodes may accompany this response code:

Subcode	Meaning
1	Unique descriptor insert failed; value already exists in the index.
2	Unique descriptor insert failed; value in use by another user on this nucleus.
3	Unique descriptor insert failed; value in use by another user on another cluster nucleus.
4	Unique descriptor insert failed; the value we are attempting to insert in the NI block is already there.

**Response 199**

**Origin** Mainframe systems only

**Explanation** An inconsistency in the inverted list index was found during an update operation. In an ACB, the leftmost two bytes of Additions 2 may contain the descriptor name; in an ACBX, the Error Character Field (ACBXERRB) may contain the descriptor name. This response code can also occur if UTYPE=EXU was specified for an ADARES BACKOUT operation that uses the sequential (SIBA) log.

**Response 200**

**Origin** Mainframe and open systems

**Explanation** Either an invalid cipher code or an Adabas SAF Security or Adabas security violation was detected.

The command could not satisfy the necessary security checks. This response code may be accompanied by one of the following subcodes:

Subcode	Meaning
0	A standard user check failed.
1	There is no free user file cache entry for a workstation user.
2	A cross-level security check failed.
3	No security information is available for the command.
4	A timeout occurred during a workstation logon.
5	An internal SAF Kernel error occurred.
6	A failure occurred during a newcopy/restart operation. The nucleus terminates.
7	A request to make an ABS security check was not of the correct format.
8	A security violation occurred while a file was being loaded into an existing expanded file chain.
11	User is not permitted to do a SEARCH command.
12	User is not permitted to do a SEARCH command.
13	User is not permitted to do a SEARCH command.
14	An invalid cipher code was encountered during update.
15	User is not permitted to read FDT (LF command).
16	Remote workstation user has supplied a new password or passphrase but there is a mismatch with the old: <ul style="list-style-type: none"> <li>■ old password with new passphrase</li> <li>■ old passphrase with new password</li> </ul> Passwords and passphrases should not be mixed.

Subcode	Meaning
17	Remote workstation user has supplied a password phrase but the detected version of SAFPSEC does not support password phrases.  Either:  ■ SAFPSEC is an old version that does not support password phrases  or  ■ SAFPSEC is capable of supporting passphrases but has been assembled with an incorrect REL= parameter (see the installation documentation for more details)
21	User's SAF ID is unknown.
22	User's SAF ID has changed.
24	Remote workstation logon failure; user-id is not defined.
25	Remote workstation logon failure; invalid password / password phrase.
26	Remote workstation logon failure; invalid new password / new password phrase.
27	Remote workstation logon failure; user-id revoked.
28	Remote workstation logon failure; logon not allowed at this time/date.
30	A utility function-level authorization check failed. The user is not permitted to perform this utility function.
1060	Open systems ADASAF phase 1 failed.
1061	Open systems ADASAF phase 1 failed with response.
1062	Open systems ADASAF phase 2 failed.

For more information about Adabas SAF Security, read the Adabas SAF Security documentation.

**Action** Resolve the security error, perhaps by simply supplying the correct password.

#### Response 201

**Origin** Mainframe and open systems

**Explanation** The specified password was not found.

**Action** Supply the correct password.

**Response 202**

**Origin** Mainframe and open systems

**Explanation** An attempt was made to use a file for which the user is not authorized, or the file password is being changed, or, if Adabas Security is being used, the file has attached Security By Value on this field.

**Action** Either correct the authorization, or retry the operation with the new password, or, if Adabas Security is being used, remove the Security By Value on the field before the operation on the file can be retried.

**Response 203**

**Origin** Mainframe systems only

**Explanation** An attempt was made to delete a record in a file for which the user is not authorized.

**Response 204**

**Origin** Mainframe and open systems

**Explanation** On mainframe systems, a password pool overflow occurred.

On open systems, the password supplied is already in use.

**Action** On open systems, change the password to one that is not already existing.

On mainframe systems, check and possibly increase the value specified for ADARUN LCP parameter in the Adabas nucleus.

**Response 207**

**Origin** Mainframe systems only

**Explanation** Adabas SAF Security completed phase 1 of logon and requested phase 2. This is an internal Adabas SAF Security and ADALNK two-phase response code for a remote workstation logon. This code is normally not displayed or presented.

For more information, read your Adabas SAF Security documentation.

**Action** Send a phase 2 logon request to Adabas SAF Security.

**Response 208**

**Origin** Mainframe and open systems

**Explanation** As an Adabas SAF Security remote user, you should execute a phase 1 logon. The logon ID and your password are sent to Adabas SAF Security. This response indicates that two-phase logon can continue.

For more information, read your Adabas SAF Security documentation.

Subcode	Meaning
1066	Open systems ADASAF phase 1 error exit.
1067	Open systems ADASAF phase 2 error exit.

**Action** If the user application receives this response, it is on a workstation platform that does not have the proper Adabas link routine installed. This response code is intercepted by the workstation Adabas link routine and phase 1 logon is performed.

#### Response 209

**Origin** Mainframe systems only

**Explanation** Adabas SAF Security detected an expired password on the server. The workstation user's password has expired. This code is normally not returned to the application. Instead the workstation user is prompted to enter a new password.

**Action** Create a valid password on the server for ACF2, RACF, or Top Secret. Entire Net-Work users may use the Adabas SAF Security feature.

#### Response 210

**Origin** Mainframe and open systems

**Explanation** On mainframe systems, a logical ID was greater than 255 (internal error).

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, a receive buffer was lost in NETRDI.

**Action** On open systems, the DBA may increase the value of the NAB or NC parameters in the NETRDI in the target node.

#### Response 211

**Origin** Mainframe and open systems

**Explanation** On mainframe systems, an invalid ID table index in the UB (internal error) occurred.

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, a remote utility cannot be executed because OPTIONS = LOCAL\_UTILITIES is set for the database.

**Action** On open systems, contact the DBA of the remote database.

**Response 212**

**Origin** Mainframe and open systems

**Explanation** On mainframe systems, an invalid input/output buffer was encountered for an internal command.

On open systems, a requested function is not implemented in the target architecture.

**Action** On open systems, execute the utility on the target node.

**Response 213**

**Origin** Mainframe systems only

**Explanation** ID table not found (SVC not properly installed).

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

The following table describes the possible subcodes that might occur if an Adabas DBID/SVC routing table error occurs:

Subcode	Meaning
16	The specified SVC number does not correspond to a currently installed SVC on the z/OS or z/VSE system. Check to be sure that the specified SVC number is correct and, if it is, ensure that an Adabas SVC is installed using that SVC number.
20	The specified SVC number corresponds to an installed SVC on the z/OS or z/VSE system, but the SVC is not an Adabas SVC. Ensure that the provided SVC number is correct and, if it is, determine why the SVC installed for that number is not an Adabas SVC for z/OS or z/VSE.

**Action** Inform the DBA. The Adabas installation procedure was not properly executed.

**Response 214**

**Origin** Mainframe systems only

**Explanation** Internal command issued from Adabas version 4 ADALNK.

**Response 215**

**Origin** Open systems only

**Explanation** The Adabas interface (adalnkx, adalnkc, adalnkcnc) used by the application program, or the Entire Net-Work version used is not supported by the Adabas nucleus. For example, the Adabas nucleus Version 6.1 does not support the Adabas interface of Version 5.1. If a 32-bit version and a 64-bit version of Adabas exists for an operating system, the 64-bit nucleus does not support the Adabas interface of the 32-bit version - 32-bit applications must use the 32-bit mode Adabas interface of the 64-bit version.

**Note:** The compatible Entire Net-Work versions supported by an Adabas open systems version are documented in the Adabas open systems Release Notes.

**Action**

If you are using an incompatible version of Entire Net-Work, upgrade it to a compatible version. Check the definition of the environment variable PATH (Windows) or LD\_LIBRARY\_PATH (UNIX). If the application has been linked with the s-bit on UNIX, it is necessary that the correct Adabas interface has been installed with \$SAG = /opt/softwareag.

**Response 216****Origin**

Mainframe and open systems

**Explanation**

Command rejected by user exit.

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
1070	UEX_ACBX_0 command rejected.

**Response 217****Origin**

Mainframe systems only

**Explanation**

Command rejected by user exit.

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

**Response 218****Origin**

Mainframe systems only

**Explanation**

The following table describes the subcodes that appear with this response code, clarifying why the response was received.

Subcode	Meaning
00 or 01 or 02	The UB (TP monitor user block) pool is too small. There must be at least one user block for each concurrent user. This is controlled by the TP monitor link routines. The GETMAIN for the UB failed.
13 or 15 or 17	An error has occurred during the freeing of the UB and Work areas for a TL call. This may indicate an internal product error or a TP monitor storage overlay. Contact Software AG technical support for assistance.

Subcode	Meaning
72	An IPC (Interprocess communication) message call parameter error occurred. This may indicate an internal product error or a TP-monitor storage overlay. Contact Software AG technical support for assistance.
73	The IPC message caller did not provide a pointer to the extended user ID block. This is probably an internal product error. Contact Software AG technical support.
74	An IPC message internal work area is corrupted. This may indicate an internal product error or a TP monitor storage overlay. Contact Software AG technical support for assistance.
75	An IPC message call parameter error occurred. This is probably an internal product problem. Contact Software AG technical support for assistance.
76	The extended user ID data provided to the IPC Message Call is either binary zeroes or blank. This is probably an internal product error. Contact Software AG technical support.
77	A getmain failed for the work area used in an IPC Message Call. Determine why the TP monitor is running short of storage. The storage will be acquired in the AMODE of the calling program, usually 31-bit for Natural transactions.
78	An invalid IPC work area has been provided by the caller for a TS call. This is probably an internal product error. Contact Software AG technical support.
79	An error occurred during freemain done for a TS call. This may indicate an internal product error or a TP monitor storage overlay. Contact Software AG technical support for assistance.
100	Unable to communicate with the Adabas Directory Server. Check the LTCPSET parameters ADIHOST and ADIPOINT.
101	An error occurred when closing a socket. Contact Software AG technical support for assistance.
102	A socket could not be allocated. Contact Software AG technical support for assistance.
103	The TCP/IP socket could not connect to the database. Check that the database is active.
104	Unable to establish a context on the database. Contact Software AG technical support for assistance.
110	Internal error processing a parameter list. Contact Software AG technical support for assistance.
111	An error occurred when sending data on a socket. Contact Software AG technical support for assistance.
120	Unable to receive results due to no database context. Contact Software AG technical support for assistance.

Subcode	Meaning
121	An attempt has been made to receive results from a database which has not previously been contacted. Contact Software AG technical support for assistance.
122	Unable to receive results due to no client context on the database. Contact Software AG technical support for assistance.
123	An error occurred when receiving data on a socket. Contact Software AG technical support for assistance.
130	The RCVTIME has been exceeded whilst waiting to receive data on a socket.

**Action**

In the case of subcode zero, 01 or 02 increase the UB pool by respecifying the NUBS parameter in the link routines. See the LGBLSET macro information in the Adabas Installation documentation.

In all other cases, either the program executing the IPC (Interprocess communication) message has provided invalid parameters, or there are internal product problems such as storage overlay conditions. Contact Software AG technical support for assistance.

**Response 219****Origin**

Mainframe systems only

**Explanation**

This response code should only occur when Adabas Transaction Manager is being used.

Subcode	Meaning
2	The global transaction is not in the status that allows the call.
3	Two transaction ID (XID) entries exist.
4	The "R" and "J" options are not supported; or this is not a global transaction. The transaction ID (XID) does not exist or cannot be found (or example, when the given XID does not belong to the UQE).
5	The record or value buffer definition may be invalid; for example, the length size may be invalid (less than or equal to 144 bytes); or the value buffer content may be invalid; for example, it may not contain a valid transaction ID (XID).
6	The user is not an update or ET user or is already involved in a global transaction or the user is already on PET (preliminary end-of-transaction) status.
7	A protocol error occurred: The user has been copied to Work 4 or the transaction was backed out.
8	A protocol error occurred: The transaction was terminated or the user has no transaction ID (XID) or the recover call for an active user is not permitted.

Subcode	Meaning
9	The system is currently locked due to a pending Work area 4 or DDWORKR4 overflow.
10	The call is not permitted; either ADAEND or an ET-sync point is in process for the nucleus. Force the ATM nucleus to backout (BT) the transaction.
11	The user has not made any updates. A preliminary ET command, therefore, is not permitted.
12	A logic error occurred.
20	The transaction ID (XID) is unknown. This error occurs only in a cluster environment.

### Response 220

**Origin** Mainframe systems only

**Explanation** The request was rejected by Entire Net-Work due to a shortage of short term buffers.

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

**Action** For BS2000 systems running Sockets 2.2 or later, check the address space limit using the SHOW-USER-ATTRIBUTES command in the field ADDRESS-SPACE-LIMIT (the value is in megabytes). If necessary, increase it using the MODIFY-USER-ATTRIBUTES command from a privileged user ID.

For BS2000 systems running Sockets 2.1 or earlier, increase the CMSIZE parameter to enlarge the common memory pool, as long as there is enough room in the address space. Then restart Entire Net-Work.

For z/OS and z/VSE, increase the region size.

### Response 221

**Origin** Mainframe systems only

**Explanation** The LU size of the remote partner is smaller than the size required for the Adabas request.

**Action** Either increase the size specified for the LU= parameter on the remote system, or modify the application to reduce its buffer sizes.

**Response 222 - 223 (reserved)****Response 224****Origin** Mainframe and open systems**Explanation** An Adabas command has been timed out by Entire Net-Work. The request waited for a reply for a longer time period than specified by the REPLYTIM parameter in either the Entire Net-Work NODE statement or the SET operator command. The reply may be delayed or lost due to a target malfunction, or because of a connecting link failure. If you are using Natural, and all connections are verified, check the ADAMODE setting. The ADAMODE=0 setting is the only option Entire Net-Work supports.**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the ACB Additions 2 field (ACBADD2) or the ACBX Error Subcode field (ACBXERRC) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
1	If the message was compressed using zEDC compression services and the attempt to decompress the message failed, subcode 1 is placed in the rightmost two bytes of the ACB Additions 2 field (ACBADD2) or the ACBX Subcomponent Response Code field (ACBXSUBR).
1076	An XTS timeout error occurred.

**Action** Check the node and remote database or contact your database administrator for assistance.**Response 225****Origin** Mainframe and open systems**Explanation** A command was issued from a server, such as an Adabas nucleus, to another server, such as Entire Net-Work. The command did not complete within a prescribed time period. The issuer proceeds and no longer expects a response to the command.

Note that the command may still execute in the target. There will be no notification to the issuer if it does. The target may display message ADAM92, User Gone, if the target attempts to notify the issuer of command completion.

The subcode identifies the environment from which the command was issued.

Subcode	Issuer
1	ADAMPM
2	Adabas nucleus, thread-synchronous command
3	Adabas nucleus, not thread-synchronous. Under z/OS, the command was TCB-synchronous.

**Action** Contact your Software AG technical support representative for assistance if the reason for the command's failure to complete cannot be identified.

**Response 226 - 227 (reserved)**

**Response 228**

**Origin** Mainframe systems only

**Explanation** This response is issued by an Adabas link routine. It indicates that an ASCII-formatted user request has been issued against an EBCDIC-formatted database that is not properly configured to handle the translation:

1	The SVC is not a valid Adabas version 7 SVC.
2	The database is not UES-enabled.

**Action** Ensure that your Adabas installation is for a supported version and that the database is UES-enabled. Refer to the UES information.

**Response 229**

**Origin** Mainframe systems only

**Explanation** The Entire Net-Work 5 convertor detected an inconsistency or error in the application format buffer or search buffer and is unable to correctly translate the user's data.

**Response 230**

**Origin** Open systems only

**Explanation** The protocol defined by the X/Open XA specification is violated. This happens, for example, if a user tries to issue an ET call for an XA transaction.

**Action** Follow the XA specification.

**Response 231-239**

**Explanation** These response codes are assigned in some Adabas user exits, and have meanings as defined by the user. One example is the response code in the ADALOG log data field issued by user exit 4.

**Action** Refer to the description of user exits in the Adabas user, hyperdescriptor, and collation descriptor exits documentation for more information.

**Response 240**

<b>Origin</b>	Mainframe systems only
<b>Explanation</b>	Adabas Transaction Manager encountered an error. The error code can be found in the Adabas control block Additions 2 field, in the low-order (rightmost) two bytes. A response code may occur in the first two bytes of the Additions 2 field.
<b>Action</b>	Check the meaning of the Adabas Transaction Manager error code. If the cause of the problem is not apparent, contact your Software AG technical support representative.

**Response 241**

<b>Origin</b>	Mainframe and open systems
<b>Explanation</b>	The explanation for this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

Adabas Transaction Manager (ATM) received an unexpected Adabas response code. The subcode and response code can be found, in that order, in the Adabas control block Additions 2 field. If a positive response code value appears in the Additions 2 field, the response code was detected by the ATM transaction manager. If a negative response code value appears in the Additions 2 field, take its complement: this is the response code received by the client proxy's attempt to communicate with the ATM transaction manager.

**Open Systems**

The system cannot load the specified user exit shared library or dynamic load library, or the specified function does not exist in this shared library or dynamic load library. If the function does not exist in the shared library or dynamic load library, bytes 1 and 2 of the Additions 2 field contain the system's error number in binary format, otherwise these two bytes contain 0. Bytes 3 and 4 of the Additions 2 field contains the number of the ADALNK user exit which failed in binary format.

Subcode	Meaning
1080	UEX_ACBX_0 load failed.
1081	UEX_ACBX_1 load failed.

<b>Action</b>	<b>Mainframe Systems</b>
	Check the meaning of the Adabas response code and subcode. If the cause of the problem is not apparent, contact your Software AG technical support representative.

**Open Systems**

Make sure that you use the correct environment variable for the user exit.

**Response 242**

**Origin** Mainframe and open systems

**Explanation** The explanation for this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

The Adabase Transaction Manager (ATM) or ATM client proxy was unable to determine the status of the caller’s transaction. There might be an ATM error code in the Adabas control block Additions 2 field, in the low-order (rightmost) two bytes.

**Open Systems**

A double allocation has been detected between two or more files or a file and the free space table.

**Action** **Mainframe Systems**

Check the meaning of the Adabas Transaction Manager error code, if one is present. Otherwise, determine the status of the global transaction using Online Services. If the required action is not apparent, contact your Software AG technical support representative.

**Open Systems**

Run ADAVFY without any options to find out which parts of which files are affected. Contact your nearest support center with the output from ADAVFY.

**Response 243**

**Origin** Mainframe and open systems

**Explanation** The explanation for this response code varies, depending on whether you are using Adabas on mainframe systems or Adabas on open systems.

**Mainframe Systems**

The Adabas Transaction Manager (ATM) or client proxy received an unsolicited syncpoint request. The action taken or the status of the global transaction that was open is indicated by a subcode in the Adabas control block Additions 2 field, in the low-order (rightmost) two bytes.

Subcode	Explanation and Recommended Action
1	The unsolicited syncpoint request was accepted. The status of the current global transaction is not known.  Use Online Services to determine the status of the global transaction.
2	The unsolicited syncpoint request was accepted. The client session’s global transaction has been committed.

Subcode	Explanation and Recommended Action
3	The unsolicited syncpoint request was accepted. The client session's global transaction has been backed out.
4	The unsolicited syncpoint request was accepted. The client session's global transaction had mixed completion (partially backed out, partially committed).
5	The unsolicited syncpoint request was accepted. The client session's global transaction is in backout.
6	The unsolicited syncpoint request was accepted. The client session's global transaction is in commit.
7	The unsolicited syncpoint request was accepted. The client session had no global transaction open.
12	The unsolicited syncpoint was attempted, but ATM returned response code 148 (ADARSP148) so the outcome is not known.
16	The unsolicited syncpoint request was rejected.

### Open Systems

An invalid FCB extent has been detected for a file.

### Action

### Mainframe Systems

Review the Adabas Transaction Manager's TMSYNCMGR parameter and the TransactionControl, Client-sideTransactionManager, and HostSystemTransactionManager client runtime controls for the failing job.

### Open Systems

Contact your nearest support center.

## Response 245

### Origin

Mainframe and open systems

### Explanation

On mainframe systems, this response code is issued for communication problems between add-on products that use the system coordinator (COR) interface to Adabas; that is, Adabas Fastpath, Adabas Vista, Adabas SAF Security, and Adabas Transaction Manager.

Subcode	Meaning
1	Internal error.
2	A required module could not be loaded. This is probably an installation error.

On open systems, pending utility entries exist in the UCB.

**Action** On mainframe systems, for subcode 1, contact your Software AG technical support representative. For subcode 2, consult the installation instructions for the add-on product.

On open systems, delete the entries with RESET = UCB before executing RECOVER, but ensure that the utilities which own the UCB entries are no longer running.

**Response 246**

**Origin** Open systems only

**Explanation** Utility communication block (UCB) overflow.

**Action** Execute the RESET function of ADADBM to remove unused entries from the utility communication block if the utilities that own them are no longer running.

**Response 247**

**Origin** Open systems only

**Explanation** Correct ID not found in the utility communication block.

**Action** The utility cannot be restarted. Delete the utility communication block entry and rerun the utility.

**Response 248**

**Origin** Mainframe and open systems

**Explanation** This response code is returned by Data Archiving for Adabas processing. Subcodes are returned in big-endian byte order in the Additions-2 field of the Adabas control block and conform to the format 0xhhhhChhh where C is the subcode category. The subcodes below are listed in Category order.

Category 0 subcodes:

Subcode	Meaning
1 (0x00000001)	No architecture/version information returned by Adabas in the response to the OP command.  <i>Action:</i> Contact your Software AG technical support representative.
2 (0x00000002)	Cannot recall archived data because the architecture of the target database is not compatible with the architecture to the original database.  <i>Action:</i> Choose a different mixture.
3 (0x00000003)	Either the Extractor/Accumulator versions are not compatible or the Adabas version of the database being archived from or recalled to is not supported.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
4 (0x00000004)	The FDT of the file into which data is being recalled or archived is not compatible with the FDT of the original file.  <i>Action:</i> Check that FDTs of the files are compatible.
5 (0x00000005)	Cannot coerce a value specified for the extraction criteria to the specified type.  <i>Action:</i> Check that the values and types defined for the extraction criteria are correct.
6 (0x00000006)	Date specified for the extraction criteria is prior to the earliest supported data.  <i>Action:</i> Contact your Software AG technical support representative.
7 (0x00000007)	Unsupported date/time pattern in extraction criteria.  <i>Action:</i> Set a correct pattern in the extraction criteria. Contact Software AG Support.
8 (0x00000008)	Database from which data is being archived or recalled into is not on the local machine.  <i>Action:</i> Check the action is correctly configured. The source database must be local to the Extractor and target database local to the Accumulator.
9 (0x00000009)	Cannot load the Adabas System Coordinator library.  <i>Action:</i> Check that Adabas System Coordinator is installed correctly.
10 (0x0000000A)	An incompatible version of Adabas System Coordinator is installed.  <i>Action:</i> Contact your Software AG technical support representative.
11 (0x0000000B)	An incompatible version of Adabas System Coordinator is installed.  <i>Action:</i> Contact your Software AG technical support representative.
12 (0x0000000C)	Cannot parse FDT.  <i>Action:</i> Contact your Software AG technical support representative.
13 (0x0000000D)	Cannot generate FDU from FDT.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
14 (0x0000000E)	Cannot create format buffer for the whole FDT.  <i>Action:</i> Contact your Software AG technical support representative.
15 (0x0000000F)	PE or MU field(s) not defined correctly.  <i>Action:</i> Check that the PE/MU fields in the Extractor/Accumulator filtering and Archive search fields are defined correctly.
16 (0x00000010)	Field does not exist in the FDT.  <i>Action:</i> Check that the fields in the Extractor/Accumulator filtering and Archive search fields are defined correctly.
17 (0x00000011)	Recall of a filtered archive using the 'Replace duplicate unique descriptors' option failed because the format/record buffer could not be parsed.  <i>Action:</i> Contact your Software AG technical support representative.
18 (0x00000012)	Recall of a filtered archive using the 'Replace duplicate unique descriptors' option failed because the conflicting descriptor does not appear in the format/record buffer.  <i>Action:</i> Choose different recall options for handling duplicate unique descriptors or ensure that all UQ fields are included in a filtered archive.
19 (0x00000013)	Internal record buffer overflow.  <i>Action:</i> Contact your Software AG technical support representative.
20 (0x00000014)	Internal format buffer overflow.  <i>Action:</i> Contact your Software AG technical support representative.
21 (0x00000015)	Internal search buffer overflow.  <i>Action:</i> Contact your Software AG technical support representative.
22 (0x00000016)	Internal value buffer overflow.  <i>Action:</i> Contact your Software AG technical support representative.
23 (0x00000017)	No extraction criteria were specified and there are no DE fields in the FDT.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
24 (0x00000018)	No Computer record for the current Adabas System Coordinator Group Leader.  <i>Action:</i> Check that the correct Repository is being used and that the Adabas System Coordinator Computer is still defined.
25 (0x00000019)	No archive service definition for the Extractor/Accumulator computer.  <i>Action:</i> Check that the correct Repository is being used and that the Data Archiving Service is still defined for Adabas System Coordinator Daemon.
26 (0x0000001A)	No Computer or Daemon record for the Extractor/Accumulator computer.  <i>Action:</i> Check that the correct Repository is being used and that the Adabas System Coordinator Computer and Daemon is still defined.
27 (0x0000001B)	No Action record found for the current archive/recall/search operation.  <i>Action:</i> Check that the correct Repository is being used and that the Action record is still defined.
28 (0x0000001C)	No Vault Validation record found.  <i>Action:</i> Check that the validation is correctly configured for this vault.
29 (0x0000001D)	No Vault PATH information for this computer.  <i>Action:</i> Check that a Vault Path is defined for the Extractor, Accumulator and ADR Service computers.
30 (0x0000001E)	Attempt to recall an archive using Extractor/Accumulator computers that not sharing the same Repository.  <i>Action:</i> Extractor/Accumulator computers for a recall must share the same Repository.
31 (0x0000001F)	No Plan record found for the current archive/recall/search operation.  <i>Action:</i> Check that the correct Repository is being used and that the Plan record is still defined.
32 (0x00000020)	Archive failed due to invalid/unsupported Extractor settings.  <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
33 (0x00000021)	Archive failed due to invalid/unsupported Transfer settings. <i>Action:</i> Contact your Software AG technical support representative.
34 (0x00000022)	Archive failed due to invalid/unsupported Accumulator settings. <i>Action:</i> Contact your Software AG technical support representative.
35 (0x00000023)	Recall failed due to invalid or unsupported Extractor settings. <i>Action:</i> Contact your Software AG technical support representative.
36 (0x00000024)	Recall failed due to invalid or unsupported Transfer settings. <i>Action:</i> Contact your Software AG technical support representative.
37 (0x00000025)	Recall failed due to invalid or unsupported Accumulator settings. <i>Action:</i> Contact your Software AG technical support representative.
38 (0x00000026)	Extractor terminated because the Accumulator is not active. <i>Action:</i> Check the response and subcode for the Accumulator in Current or Completed Activities.
39 (0x00000027)	Accumulator timed-out waiting for the Extractor. <i>Action:</i> Check the response and subcode for the Extractor in Current or Completed Activities.
40 (0x00000028)	Message protocol error/incompatibility. <i>Action:</i> Contact your Software AG technical support representative.
41 (0x00000029)	Message protocol error/incompatibility. <i>Action:</i> Contact your Software AG technical support representative.
42 (0x0000002A)	Message protocol error/incompatibility. <i>Action:</i> Contact your Software AG technical support representative.
43 (0x0000002B)	Message protocol error/incompatibility. <i>Action:</i> Contact your Software AG technical support representative.
44 (0x0000002C)	Message protocol error/incompatibility.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
45 (0x0000002D)	Timeout waiting for lock on archive in Vault. <i>Action:</i> Retry the operation and/or check for competing operations.
46 (0x0000002E)	Version mismatch between Data Archiving for Adabas runtime and Vault contents. <i>Action:</i> Contact your Software AG technical support representative.
47 (0x0000002F)	Invalid/corrupt archive in Vault. <i>Action:</i> Contact your Software AG technical support representative.
48 (0x00000030)	Archive in Vault contains data not supported by this version of the Data Archiving for Adabas runtime. <i>Action:</i> Contact your Software AG technical support representative.
49 (0x00000031)	Archive size would exceed limit. <i>Action:</i> Contact your Software AG technical support representative.
50 (0x00000032)	Invalid/unsupported Vault operation. <i>Action:</i> Contact your Software AG technical support representative.
51 (0x00000033)	Archive does not exist in Vault. <i>Action:</i> Contact your Software AG technical support representative.
52 (0x00000034)	Vault path does not exist. <i>Action:</i> Check that the Vault Path defined for the Extractor, Accumulator and ADR Service computers is correct.
53 (0x00000035)	Access denied to Vault Path. <i>Action:</i> Check that the Extractor, Accumulator and ADR Service computers have the correct filesystem permissions for the Vault Path.
54 (0x00000036)	Logical error manipulating Vault contents. <i>Action:</i> Contact your Software AG technical support representative.
55 (0x00000037)	Extractor/Accumulator failed to load.

Subcode	Meaning
	<i>Action:</i> Check the response and subcode for the Extractor/Accumulator in Pending, Current and Completed Activities.
56 (0x00000038)	Extractor/Accumulator failed to load.  <i>Action:</i> Contact your Software AG technical support representative.
57 (0x00000039)	Length of compressed record exceeds limit.  <i>Action:</i> Contact your Software AG technical support representative.
58 (0x0000003A)	Length of decompressed record exceeds limit.  <i>Action:</i> Contact your Software AG technical support representative.
59 (0x0000003B)	Cannot determine the default codepage for the system.  <i>Action:</i> Contact your Software AG technical support representative.
60 (0x0000003C)	Invalid/unsupported codepage specified for archive or recall.  <i>Action:</i> Check that the codepage specified for in the Extractor/Accumulator settings in the Action or recall request.
61 (0x0000003D)	'Use default' codepage specified for archive or recall and there is no default UES AMODE= setting for the database.  <i>Action:</i> Specify the codepage explicitly or configure the default AMODE= setting for the database.
62 (0x0000003E)	No Search record found.  <i>Action:</i> Check that the correct Repository is being used and that the Search Record is still defined for the Action.
63 (0x0000003F)	Cannot search archive because the data was not archived in compressed format.  <i>Action:</i> Contact your Software AG technical support representative.
64 (0x00000040)	Invalid search (search buffer).  <i>Action:</i> Contact your Software AG technical support representative.
65 (0x00000041)	Invalid search (value buffer).  <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
66 (0x00000042)	Value buffer for search could not be converted from the UI codepage to the codepage of the archived data.  <i>Action:</i> Contact your Software AG technical support representative.
67 (0x00000043)	'Use default' codepage specified for archive or recall and there is no default UES WMODE=setting for the database.  <i>Action:</i> Specify the codepage explicitly or configure the default WMODE= setting for the database.
68 (0x00000044)	Task already locked.  <i>Action:</i> Contact your Software AG technical support representative.
69 (0x00000045)	License file is missing.  <i>Action:</i> Contact your Software AG technical support representative.
70 (0x00000046)	License key is invalid.  <i>Action:</i> Contact your Software AG technical support representative.
71 (0x00000047)	License has expired.  <i>Action:</i> Contact your Software AG technical support representative.
72 (0x00000048)	License is for a different operating system.  <i>Action:</i> Contact your Software AG technical support representative.
73 (0x00000049)	License is for a different product.  <i>Action:</i> Contact your Software AG technical support representative.
74 (0x0000004A)	License is for a different version.  <i>Action:</i> Contact your Software AG technical support representative.
75 (0x0000004B)	Functionality restricted, Community edition.  <i>Action:</i> License file required for full functionality.
76 (0x0000004C)	No license file found.  <i>Action:</i> Contact your Software AG technical support representative.
77 (0x0000004D)	Duplicate archive identifier detected in the Vault.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
78 (0x0000004E)	Filename conflict detected in the Vault.  <i>Action:</i> Contact your Software AG technical support representative.
79 (0x0000004F)	Some or all of the data for an archive is missing from the Vault.  <i>Action:</i> Contact your Software AG technical support representative.
80 (0x00000050)	Vault or archive damaged.  <i>Action:</i> Contact your Software AG technical support representative.
81 (0x00000051)	ADR plug-in library could not be loaded.  <i>Action:</i> Contact your Software AG technical support representative.
82 (0x00000052)	Incompatible ADR plug-in library.  <i>Action:</i> Contact your Software AG technical support representative.
83 (0x00000053)	Occurrence 'N' cannot be specified for a PE/MU LOB field in an Extractor Filter (Open Systems only).  <i>Action:</i> Correct the format buffer in the Extractor Filter Settings.
84 (0x00000054)	An Extractor Filter must contain at least one non-LOB field.  <i>Action:</i> Correct the format buffer in the Extractor Filter Settings.
85 (0x00000055)	The data being archived or recalled contains LOB fields but no LOB file number has been specified.  <i>Action:</i> Specify a LOB file number, for recalls set in the recall settings and for archive set in the Accumulator settings in the Action.
86 (0x00000056)	License file does not provide the Price Units required by the system.  <i>Action:</i> Contact your Software AG technical support representative.
87 (0x00000057)	License file does not provide the Price Quantity required by the system.  <i>Action:</i> Contact your Software AG technical support representative.
88 (0x00000058)	License file does not provide Extended Rights.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
89 (0x00000059)	The file size of the archive file checked by the validation process is incorrect.  <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
90 (0x0000005A)	The number of records in the archive file checked by the validation process is incorrect.  <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
91 (0x0000005B)	The check sum for the archive file checked by the validation process is incorrect.  <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
92 (0x0000005C)	The lengths of the records in the archive file checked by the validation process are incorrect.  <i>Action:</i> Restore the archive file from a backup and rerun the validation to check the integrity of the data.
93 (0x0000005D)	License file does not provide Archive to Vault required by the system.  <i>Action:</i> Contact your Software AG technical support representative.
94 (0x0000005E)	License file does not provide Transfer to Adabas required by the system.  <i>Action:</i> Contact your Software AG technical support representative.
95 (0x0000005F)	License file does not provide Delete from Adabas required by the system.  <i>Action:</i> Contact your Software AG technical support representative.
96 (0x00000060)	Inconsistency in join data for archive.  <i>Action:</i> Contact your Software AG technical support representative.
97 (0x00000061)	Inconsistent object/archive identifiers for archive.  <i>Action:</i> Contact your Software AG technical support representative.
98 (0x00000062)	File list for action does not match the archive data.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
99 (0x00000063)	Archive identifier does not match API data.  <i>Action:</i> Contact your Software AG technical support representative.
100 (0x00000064)	Group, plan or name of action does not match API data.  <i>Action:</i> Contact your Software AG technical support representative.
101 (0x00000065)	File list for action does not match API data.  <i>Action:</i> Contact your Software AG technical support representative.
102 (0x00000066)	Duplicate activity encountered.  <i>Action:</i> Delete activity from Activities List and rerun.
103 (0x00000067)	Related file record is missing.  <i>Action:</i> Contact your Software AG technical support representative.
104 (0x00000068)	Recall target record is missing.  <i>Action:</i> Contact your Software AG technical support representative.
105 (x00000069)	Recall target information is not valid.  <i>Action:</i> Contact your Software AG technical support representative.
106 (x0000006A)	Maximum number of related files exceeded.  <i>Action:</i> Contact your Software AG technical support representative.
107 (x0000006B)	Maximum number of transfer destinations exceeded.  <i>Action:</i> Contact your Software AG technical support representative.
108 (x0000006C)	Transfer destination not defined.  <i>Action:</i> Contact your Software AG technical support representative.
109 (x0000006D)	Maximum number of related files or transfer destinations exceeded.  <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
110 (x0000006E)	Invalid related file. <i>Action:</i> Contact your Software AG technical support representative.
111 (x0000006F)	Invalid transger destination. <i>Action:</i> Contact your Software AG technical support representative.
112 (0x00000070)	Archive, recall or search failed. <i>Action:</i> Check the response and subcode for the Extractor/Accumulator in Completed Activities.
113 (0x00000071)	Archive, recall or search incomplete. <i>Action:</i> Records have been skipped due to contention or errors.
114 (0x00000072)	Invalid settings specified for file in action. <i>Action:</i> Contact your Software AG technical support representative.
115 (0x00000073)	Recall configuration records inconsistent. <i>Action:</i> Contact your Software AG technical support representative.
116 (0x00000074)	Recall configuration records inconsistent. <i>Action:</i> Contact your Software AG technical support representative.
117 (0x00000075)	API library is not installed. <i>Action:</i> Contact your Software AG technical support representative.
118 (0x00000076)	API library could not be loaded. <i>Action:</i> Contact your Software AG technical support representative.
119 (0x00000077)	Entry-point symbol missing from API library. <i>Action:</i> Contact your Software AG technical support representative.
120 (0x00000078)	Wrong version of API library. <i>Action:</i> Contact your Software AG technical support representative.
121 (0x00000079)	Fault detected in API library. <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
122 (0x0000007A)	API library is missing.  <i>Action:</i> Contact your Software AG technical support representative.
123 (0x0000007B)	No data returned by API.  <i>Action:</i> Contact your Software AG technical support representative.
124 (0x0000007C)	Incorrect API parameters specified by user.  <i>Action:</i> Contact your Software AG technical support representative.
125 (0x0000007D)	Memory allocation failed in API.  <i>Action:</i> Contact your Software AG technical support representative.
126 (0x0000007E)	Internal API error.  <i>Action:</i> Contact your Software AG technical support representative.
128 (0x00000080)	Incorrect parameter passed to API.  <i>Action:</i> Contact your Software AG technical support representative.
129 (0x00000081)	API notification failed (state inconsistent).  <i>Action:</i> Contact your Software AG technical support representative.
130 (0x00000082)	API library name is too long.  <i>Action:</i> Reduce the length of the API library name.
131 (0xhhhh0083)	Error occurred while processing the Extraction Syntax. An extended error code (identified by hhhh) may also be reported for subcode 131.  <i>Action:</i> Check the Extraction Syntax and if the error persists contact your Software AG technical support representative providing the full subcode value and the Extraction Syntax being used.
132 (0x00000084)	No dynamic extraction object code exists  <i>Action:</i> Ensure that you have successfully saved and compiled your dynamic extraction syntax.
133 (0x00000085)	Duplicate Related file record with differing scopes.  <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
134 (0x00000086)	API To-Do list locked, it is already in use by another process.  <i>Action:</i> Ensure that only one application/process accesses a To-Do list at any one time.
135 (0x00000087)	Extractor data targets do not match those in the Repository.  <i>Action:</i> Contact your Software AG technical support representative.
136 (0x00000088)	Extractor/Accumulator was terminated unexpectedly or cancelled by the user.  <i>Action:</i> Check the response and subcode for the Extractor/Accumulator in Pending, Current and Completed Activities.
137 (0x00000089)	Accumulator terminated because the Extractor is not active.  <i>Action:</i> Check the response and subcode for the Extractor in Current Activities or Recently Completed.
138 (0x0000008A)	An archive activity could not be resumed/restarted because the FDT of one of the Source Files has been changed since the activity was paused/failed.  <i>Action:</i> Contact your Software AG technical support representative.
139 (0x0000008B)	An archive activity could not be resumed/restarted because the Codepage setting for a Source File or the AMODE/WMODE settings for the associated database have been changed since the activity was paused/failed.  <i>Action:</i> Contact your Software AG technical support representative.
140 (0x0000008C)	An archive activity could not be resumed/restarted because the Computer defined for the Extractor or Accumulator has been changed since the activity was paused/failed.  <i>Action:</i> Contact your Software AG technical support representative.
141 (0x0000008D)	An archive activity could not be resumed/restarted because the Source or Target File definitions for the Action have been changed since the activity was paused/failed.  <i>Action:</i> Contact your Software AG technical support representative.
142 (0x0000008E)	The Extractor was unable to read the FCB of one of the Source Files.

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
143 (0x0000008F)	<p>The FCB of the Source Files is in a format not recognised by the Extractor.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
144 (0x00000090)	<p>An archive activity could not be resumed/restarted because one of the Source Files has been reloaded since the activity was paused/failed.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
145 (0x00000091)	<p>An archive activity could not be restarted because the archive could not be validated, the repair was unsuccessful.</p> <p><i>Action:</i> Review the meaning of any log messages written at the time of the failure and, if necessary, contact your Software AG technical support representative.</p>
146 (0x00000092)	<p>An archive activity could not be validated/restarted because one of the archive file segments is missing.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
147 (0x00000093)	<p>Invalid archive identifier.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
148 (0x00000094)	<p>Length mismatch detected whilst updating archive file record.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
149 (0x00000095)	<p>No Vault record found.</p> <p><i>Action:</i> Check that the Vault defined for the Plan or Action exists.</p>
150 (0x00000096)	<p>The ADR Service does not support the granularity setting configured for the Vault.</p> <p><i>Action:</i> Contact your Software AG technical support representative.</p>
151 (0x00000097)	<p>Vault path does not exist.</p> <p><i>Action:</i> Check that the Vault Path defined for the Extractor, Accumulator and ADR Service computers are correct.</p>
152 (0x00000098)	<p>An archive activity could not be validated/restarted because too many archive file segments exist.</p>

Subcode	Meaning
	<i>Action:</i> Contact your Software AG technical support representative.
153 (0x00000099)	Timed-out whilst caching Vault content on local Computer.  <i>Action:</i> Contact your Software AG technical support representative.
154 (0x0000009A)	Vault path does not exist.  <i>Action:</i> Check that the Vault Path defined for the Extractor, Accumulator and ADR Service computers are correct.

Category 7 subcodes:

Subcode	Meaning
0xhhhh7004	An error has occurred whilst accessing a Vault where hhhh is the operating system error code.  Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).  If the cause of the error is not apparent, contact your Software AG technical support representative.
0xhhhh700B	An error has occurred whilst writing to a Vault where hhhh is the operating system error code.  Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).  If the cause of the error is not apparent, contact your Software AG technical support representative.

Category A subcodes:

Subcode	Meaning
0xhhhhA001	A TCP/IP error has occurred where hhhh is the operating system error code.  Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).  If the cause of the error is not apparent, contact your Software AG technical support representative.
0xhhhhA002	A DNS error has occurred where hhhh is the operating system error code.

Subcode	Meaning
	<p>Refer to your operating system documentation for an explanation of hhhh (z/OS customers should refer to z/OS UNIX System Services Messages and Codes).</p> <p>If the cause of the error is not apparent, contact your Software AG technical support representative.</p>

**Response 249**

**Origin**

Mainframe and open systems

**Explanation**

**Mainframe Systems**

Adabas Vista uses a default Adabas response code 249 for all processing errors. This response code can be changed by using the Job Parameter function of Adabas Vista Online Services.

The following table describes each of the subcodes possible for response code 249. Adabas Vista issues these subcodes as well to provide additional information.

Subcode	Meaning
1	<p>The partitioned file concurrency limit has been reached.</p> <p><i>Action:</i> Increase the partitioned file concurrency limit using the File Partitioning function of Adabas Vista Online Services.</p>
6	<p>The job parameter <code>Enable Multiple Updates</code> is set to NO. After updating one database, the user attempted to update a second database in the same transaction.</p> <p><i>Action:</i> Review the job parameter <code>Enable Multiple Updates</code> in the Job Parameter function of Adabas Vista Online Services.</p>
8	<p>This partitioned file has been defined with an unsupported Partitioning Field. The Partitioning Field may not be:</p> <ul style="list-style-type: none"> <li>■ A multiple value field</li> <li>■ An item in a periodic group</li> <li>■ A field with format F, G, or W</li> <li>■ A variable length field</li> <li>■ A field with the long alphanumeric (LA) attribute</li> <li>■ A SUPDE or SUPFN of format Alphanumeric with at least one parent of format W</li> </ul> <p><i>Action:</i> Review the partitioning criteria.</p>
9	<p>One of the following errors was detected while processing a partitioned file:</p>

Subcode	Meaning
	<ul style="list-style-type: none"> <li>■ A distributed access can not be successfully processed due to the client encoding being incompatible with Vista's record collating process.</li> <li>■ A command can not be successfully processed due to the client encoding being incompatible with the defined partition criteria.</li> </ul> <p><i>Action:</i> Review the use of client encodings.</p>
10	<p>One of the following errors was detected in the Adabas search buffer while processing a partitioned file:</p> <ul style="list-style-type: none"> <li>■ the specified field is not in the Adabas FDT.</li> <li>■ an S or N operator is used incorrectly.</li> <li>■ a superdescriptor with a variable-length parent field is not allowed.</li> <li>■ coupled file syntax is not allowed.</li> <li>■ the value1 operator (EQ, GE, GT, etc.) is unknown.</li> <li>■ a connecting operator (D, O, R, etc.) is unknown.</li> <li>■ a command ID enclosed in parentheses is not allowed</li> <li>■ a memory request failed.</li> <li>■ collation descriptors are not supported.</li> </ul> <p><i>Action:</i> Review and correct the application program.</p>
12	<p>Runtime controls have been changed dynamically without the client previously resetting all Adabas context to null. In this situation Vista is forced to discard all Adabas context and alert the application with this response.</p> <p><i>Action:</i> Avoid this response by ensuring the client has no Adabas context prior to the runtime controls being changed.</p>
14	<p>One of the following errors was detected in the Adabas format or record buffer while processing a update/store for a partitioned file:</p> <ul style="list-style-type: none"> <li>■ The partitioning field specified in the format buffer could not be located in the Adabas FDT (N1 and N2).</li> <li>■ An Adabas field specified in the format buffer could not be located in the Adabas FDT (N1, N2 and A1).</li> <li>■ The partitioning field value specified in the record buffer is inconsistent with the defined partitioning criteria for the file (N1 and N2).</li> <li>■ The partitioning field value specified in the record buffer is inconsistent with the partition criteria defined to the partition identified by the ISN in the Adabas control block (N2 only).</li> <li>■ The partitioning field value specified in the record buffer is null and the Store Control Option is set to 2 (N1 only).</li> </ul>

Subcode	Meaning
	<ul style="list-style-type: none"> <li>■ The partitioning field/value has not been specified and no target partition has been identified (N1 and N2).</li> </ul> <p><i>Action:</i> Review application program and partitioning criteria.</p>
15	<p>The partitioning field value specified in the record buffer of the A1 command is inconsistent with the partition criteria defined to the partition identified by the ISN in the Adabas control block.</p> <p>Such an update requires the relocation of the ISN to another partition, which is not allowed.</p> <p><i>Action:</i> Review the application program. Use a delete and store as an alternative.</p>
16	<p>An ISN has been detected that is invalid for one of the following reasons:</p> <ul style="list-style-type: none"> <li>■ The partition identifier extracted from the Adabas Vista ISN is not consistent with any partition defined to the partitioned file.</li> <li>■ The Adabas ISN read from a partition is greater than the TOPISN value defined for the partition.</li> <li>■ An attempt to store a record has resulted in an Adabas ISN greater than the TOPISN value defined for the partition.</li> <li>■ (Extreme partitioned files only) The number of partitions is greater than the limit of 255.</li> <li>■ (Extreme partitioned files only) The application-supplied ISN is no longer associated with this partitioned file.</li> </ul> <p><i>Action:</i> For Standard partitioned files, review the application program, the partition definitions, and check TOPISN setting. For Extreme partitioned files, review the application's use of the supplied ISN.</p>
21	<p>One of the following errors occurred while processing Distributed Lock Mode (DLM) against a partitioned file:</p> <ul style="list-style-type: none"> <li>■ Prefetch/multifetch options on a distributed access L6command are not allowed for DLM options 2 and 3.</li> <li>■ DLM option 4 is specified and a distributed access S4 or L6 command was issued.</li> <li>■ DLM option 3 is specified and the distributed access data integrity check failed.</li> </ul> <p><i>Action:</i> Review the application and use of the DLM option.</p>
22	<p>The client runtime control for CL convergence is set to reject when your Vista rules used during runtime result in activity for multiple source databases converging into a single target database. With this setting the CL command cannot be processed by Vista because it would result in the loss of cursor/transaction activity in the target database for source database(s)</p>

Subcode	Meaning
	<p>beyond the one indicated in this CL command which would result in unpredictable results and errors if those other source databases are used further.</p> <p><i>Action:</i> Review the application program and the convergent translation/partitioning rules or alter the CL convergence runtime control setting.</p>
25	<p>One of the following unsupported commands has been issued:</p> <ul style="list-style-type: none"> <li>■ an S5 command (partitioned files only)</li> <li>■ a C5 command</li> <li>■ a BT command with Command Option 2 set to F (any transaction will have been backed out)</li> <li>■ an L1 command with Command Option 1 or 2 set to F</li> </ul> <p><i>Action:</i> Review application program.</p>
28	<p>An update command has been issued to a partitioned file; however, the target partition does not have the option ACCESS=FULL.</p> <p><i>Action:</i> Review application program and partition ACCESS options.</p>
31	<p>An existing Command ID has been reused after the client's translation context has been modified but this now references a different file, which is an illegal situation and is therefore rejected.</p> <p><i>Action:</i> Review programming practices for changing client contexts.</p>
32	<p>Partitioned files can not be subjected to a change in client context</p> <p><i>Action:</i> Review programming practices for changing client contexts.</p>
36	<p>A session-related memory allocation failed during an inter-system dynamic transaction routing operation, the client session is unable to continue. This sub-code may not indicate an error on this current Adabas command, but it indicates that an internal error has prevented the Vista session continuing successfully.</p> <p><i>Action:</i> Increase the shared memory available.</p>
37	<p>A file-related memory allocation failed during an inter-system dynamic transaction routing operation, the client session is unable to continue using the file. This sub-code may not indicate an error on this current Adabas command, but it indicates that an internal error has prevented the Vista session continuing successfully with one of the files currently being used so Vista is alerting you immediately.</p> <p><i>Action:</i> Increase the shared memory available.</p>
39	<p>An L1 (get next) command was issued but the supplied command ID is not currently active.</p>

Subcode	Meaning
	<i>Action:</i> Review application program.
45	<p>An error has occurred during the processing of a distributed L3/L9 command against a partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
50	<p>An A1 command was issued without the H option and the DLM option is set to 1. However, the ISN to be updated has not been previously read by a hold command.</p> <p><i>Action:</i> Review application program and use of DLM option.</p>
51	<p>The number of segmented buffers used by this ACBX call against a Partitioned File is greater than the maximum allowed.</p> <p><i>Action:</i> Reduce the number of segmented buffers.</p>
52	<p>The file parameter Enable ISN Positioning is set to NO and one of the following commands was issued:</p> <ul style="list-style-type: none"> <li>■ L1 with Command Option 2 set to I</li> <li>■ L2/5 with starting ISN</li> <li>■ L3/6 with starting ISN</li> <li>■ Sx with the ISN Lower Limit field specified</li> </ul> <p><i>Action:</i> Review application program and the file parameter Enable ISN Positioning.</p>
60	<p>A memory request failed.</p> <p><i>Action:</i> Review the memory availability of the</p> <ul style="list-style-type: none"> <li>■ host TP system;</li> <li>■ host operating system; and</li> <li>■ global common memory pool (BS2000 only; specified in the Adabas System Coordinator group definition).</li> </ul>
65	<p>One of the following invalid values was used for a command ID value:</p> <ul style="list-style-type: none"> <li>■ X'00000000'</li> <li>■ X'40404040'</li> </ul> <p><i>Action:</i> Do not use the above command ID values.</p>
70	Support for the use of this API has been withdrawn.

Subcode	Meaning
	<i>Action:</i> Please refer to the currently supported APIs or, alternatively, contact your Software AG technical support representative to discuss your requirements.
72	An ET Data related command has been issued, but the runtime control ( see <i>Database Number for ET Data</i> , in the <i>Adabas Vista Parameters</i> manual) is not set to a specific database number and Vista has been unable to establish a target database to satisfy the command.  <i>Action:</i> Review the runtime control <i>Database Number for ET Data</i> , in the <i>Adabas Vista Parameters</i> manual, to specifically identify the database number to be used.
74	A sequence direction change has been detected during an L3 or L9 command against a Partitioned File whose Command ID sequence has been previously subjected to multifetch.  <i>Action:</i> Review the program logic.
81	An error has occurred during the processing of an L1 'get next' command against a partitioned file.  <i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.
86	The Adabas Vista database process is not installed. It must be installed on all Adabas databases which contain Adabas Vista partitions. This subcode indicates that a database  <ul style="list-style-type: none"> <li>■ is not running with ADARUN VISTA=YES; or</li> <li>■ is not running Adabas version 7 or above.</li> </ul> <i>Action:</i> Refer to the Adabas Vista installation procedures.
96	An error has occurred during the parsing of the Format Buffer during the processing of an Ax or Nx command against a partitioned file.  <i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.
106	The configuration for the first-level null definition policy for this target category (mode) is set to reject "null" as the outcome of translation processing.  <i>Action:</i> Review the null definition policy for the target category (mode) used if you do not wish to receive this error.
107	Translation processing has been configured to disallow redirection to a different target category (mode).  <i>Action:</i> Remove the redirection rule(s) or review the category adjustment policy for the target category (mode) in use.

Subcode	Meaning
108	<p>The configuration for the first-level null definition policy redirects to another target category (mode) which in turn has resulted in a “null” outcome. The second-level null definition policy is set to reject such an outcome.</p> <p><i>Action:</i> Review the translation rules in use to avoid a null result or alter the null definition policies.</p>
109	<p>Translation processing has detected a recursive redirection.</p> <p><i>Action:</i> Review the translation rules in use.</p>
112	<p>An error has occurred during the processing of the current command.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
116	<p>A command has been issued against a partitioned file which has the <code>Shared Partition</code> option set to YES for one or more of its partitions. However, the partitioning field defined does not exist in the Adabas FDT.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
117	<p>One of the following errors occurred while processing the record, value, or search buffer:</p> <ul style="list-style-type: none"> <li>■ A P format field value was not in packed decimal format.</li> <li>■ A U format field value was not in unpacked decimal format.</li> <li>■ The attempted format conversion was not possible because of incompatible data formats or other compatibility problems.</li> <li>■ The field length was zero or not consistent with the field format.</li> </ul> <p><i>Action:</i> Check field values for correct formats and lengths.</p>
119	<p>One of the following has occurred:</p> <ul style="list-style-type: none"> <li>■ Runtime configuration on behalf of this client was unsuccessful and Adabas Vista has been defined as “critical” using the Critical Product Support feature of the Adabas System Coordinator.</li> <li>■ The Adabas Vista configuration file was not available during an attempt to satisfy an Adabas Vista API request.</li> </ul> <p><i>Action:</i> Check the availability of the configuration file.</p> <p>If the client runtime control Error Reporting WTO option is set to YES, this error may be accompanied by an AVI-0017-10 console message.</p>
120	<p>The client previously issued a command to a source file for which Vista was unable to determine the existence of any translation rules due to the configuration file not being available at the time. Subsequently, Vista has</p>

Subcode	Meaning
	<p>detected the availability of the configuration file and has determined the existence of a transaction rule for this source file. This subcode is returned the next time the client attempts to access the source file.</p> <p><i>Action:</i> Review the availability of the configuration file.</p>
122	<p>An invalid partitioned file definition has been found in the Adabas Vista configuration file.</p> <p><i>Action:</i> Check the file definition using Adabas Vista Online Services.</p>
123	<p>An invalid translation rule has been found in the Adabas Vista configuration file.</p> <p><i>Action:</i> Check the rule using Adabas Vista Online Services.</p>
124	<p>An error in the record buffer was detected during processing of an OP command.</p>
126	<p>One of the following errors occurred while processing an S8 command:</p> <ul style="list-style-type: none"> <li>■ An invalid command ID was specified in the Additions 1 field.</li> <li>■ Different file numbers were detected for ISN lists.</li> <li>■ An error occurred while processing a subsequent S8 call.</li> </ul> <p><i>Action:</i> Review the application program.</p>
127	<p>One of the following errors occurred while processing an S2 command:</p> <ul style="list-style-type: none"> <li>■ An invalid sort sequence was specified.</li> <li>■ An invalid ISN was detected during processing.</li> <li>■ An error was detected during ISN processing.</li> </ul> <p><i>Action:</i> Review the application program.</p>
128	<p>One of the following errors occurred while processing an S9 command:</p> <ul style="list-style-type: none"> <li>■ The command ID value specified was assigned to another command.</li> <li>■ An invalid sort sequence was specified.</li> <li>■ An invalid ISN buffer length was detected.</li> <li>■ The number of ISNs to be sorted as provided in ISN quantity is equal to 0.</li> <li>■ The command ID value specified in Additions 4 was not found.</li> <li>■ An invalid ISN was detected during processing.</li> <li>■ An error was detected during ISN processing.</li> </ul> <p><i>Action:</i> Review the application program.</p>
129	<p>The command limit defined for this source file has been exceeded.</p> <p><i>Action:</i> Review the command limit.</p>

Subcode	Meaning
131	<p>A requested file refresh of a partitioned file has failed due to an unexpected Adabas response code. The partitioned file is in a partially refreshed state.</p> <p><i>Action:</i> Review the Adabas response code.</p>
133	<p>One of the following errors occurred whilst processing a direction change during an L9 command sequence:</p> <ul style="list-style-type: none"> <li>■ A second direction change for this sequence was attempted.</li> <li>■ A format override cannot be processed.</li> <li>■ A length override greater than specified in the FDT cannot be processed.</li> <li>■ A length override has been specified with complex search criteria.</li> </ul> <p><i>Action:</i> Review the use of the L9 command and the Adabas Vista restrictions.</p>
134	<p>An S2 command to continue a sequence has been received. The sequence was not started by an S2 command.</p> <p><i>Action:</i> Amend the command sequence to process either all S1 commands, or all S2 commands, as appropriate.</p>
200	<p>ISN quantity is too high on this Sx command.</p> <p><i>Action:</i> Perform a more specific Sx .</p>
201	<p>One of the following errors occurred while initializing AVIKRN:</p> <ul style="list-style-type: none"> <li>■ The dynamic load failed.</li> <li>■ The version is not compatible.</li> </ul> <p><i>Action:</i> Check the Adabas Vista installation procedures.</p>
250	<p>ISN error when issuing ACBX style RI shared-hold calls with ACBXCOP3 set to "S".</p> <p><i>Action:</i> Check ISN usage on shared-hold commands.</p>
305	<p>An error has occurred while attempting to access an Extreme partitioned file.</p> <p><i>Action:</i> Contact your Software AG technical support representative and use the COR Debug Event Monitor controls specifying Response 249 and this subcode to provide diagnostic information.</p>
496	<p>The session is not compliant with correct distributed transaction processing. Read <i>Transaction Directives</i>, in <i>Adabas Vista Programming Guidelines</i> for a more detailed explanation of this subcode.</p> <p><i>Action:</i> Adhere to correct distributed transaction processing.</p>
532	<p>This session has not complied with the correct transactional processing behavior when using the discrete file setting.</p>

Subcode	Meaning
	<i>Action:</i> Review the discrete file setting and ensure correct transactional processing.
588	For ACBX calls, a conflict with shared hold status option "H" has been detected. The client session is using this option in a conflicting manner during an ET or BT sequence after a commit/backout process has been performed. The transaction outcome is unaffected but records may no longer be in shared hold status.  <i>Action:</i> Review usage of this option.

### Open Systems

In Adabas Vista (open systems) an error occurred during command execution. One of the following subcodes may occur:

Subcode	Meaning
1 (0x0001)	An inconsistency in an internal data structure was detected. This may indicate a code fault within Adabas Vista.  <i>Action:</i> Contact your Software AG technical support representative.
2 (0x0002)	An inconsistency in an internal data structure was detected. This may indicate a logic error within Adabas Vista.  <i>Action:</i> Contact your Software AG technical support representative.
3 (0x0003)	The S9 command is not supported on partitioned files.  <i>Action:</i> Review the program logic.
4 (0x0004)	The F option for an L1 command is not supported on partitioned files  <i>Action:</i> Review the program logic.
5 (0x0005)	The F option for a BT command is not supported.  <i>Action:</i> Review the program logic.
6 (0x0006)	The ISN buffer for a BT or ET command with the M option is not consistent with ISN Buffer Length in the Adabas control block.  <i>Action:</i> Review the program logic.
7 (0x0007)	The maximum number of active command ID values has been reached.  <i>Action:</i> Review the program logic.
8 (0x0008)	The command ID value specified for TBLES/TBQ (sequential) or TBI (ISN list) command is already in use by a different TBLES/TBQ or TBI command.  <i>Action:</i> Review the program logic.

Subcode	Meaning
9 (0x0009)	Adabas Vista is not compatible with the installed version of Natural, Adabas or Entire Net-Work.  <i>Action:</i> Contact your Software AG technical support representative.
10 (0x000A)	The definitions for partitioned file do not exist.  <i>Action:</i> Review the partition definitions in SYSAVI.
11 (0x000B)	The partitioning field does not exist in the FDT.  <i>Action:</i> Review the partition definitions in SYSAVI.
12 (0x000C)	The field type in the partition definition does not match the field type in the FDT.  <i>Action:</i> Review the partition definitions in SYSAVI.
13 (0x000D)	The type for the partitioning field is not suitable.  <i>Action:</i> Review the partition definitions in SYSAVI.
14 (0x000E)	The format buffer specified for an N1 or N2 command does not contain the partitioning field.  <i>Action:</i> Review the program logic.
15 (0x000F)	The value of the partitioning field in the record buffer specified for an N1 or N2 command could not be converted to the standard field length and format.  <i>Action:</i> Review the program logic.
16 (0x0010)	The value of the partitioning field in the record buffer specified for an A1 , N1 or N2 command does not correspond to any partition defined for the file.  <i>Action:</i> Review the partition definitions in SYSAVI.
17 (0x00011)	The value of the partitioning field in the record buffer specified for an A1 command would require the ISN to be relocated to a different partition.  <i>Action:</i> Review the program logic.
18 (0x00012)	The ISN and the value of the partitioning field in the record buffer specified for an N2 command do not correspond to the same partition.  <i>Action:</i> Review the program logic.
19 (0x00013)	The license is not valid for this operating system.  <i>Action:</i> Contact your Software AG technical support representative.
20 (0x00014)	The license has expired.  <i>Action:</i> Contact your Software AG technical support representative.

Subcode	Meaning
21 (0x00015)	The license file could not be found. <i>Action:</i> Contact your Software AG technical support representative.
22 (0x00016)	The license key is invalid. <i>Action:</i> Contact your Software AG technical support representative.
23 (0x00017)	The license is for a different version of the product. <i>Action:</i> Contact your Software AG technical support representative.
24 (0x00018)	The license is not for this product. <i>Action:</i> Contact your Software AG technical support representative.
25 (0x00019)	The ISN of a record read from a partition or the ISN of a record stored using an N1 command is too large. <i>Action:</i> Check the settings for the Adabas file to ensure that the ISN values cannot exceed the highest value defined for the partition in SYSAVI.

**Response 250****Origin**

Mainframe and open systems

**Explanation**

On mainframe systems, the ACBX (ACBX) failed validation. The following subcodes are possible:

Subcode	Meaning
1	Unsupported ACBX version
2	ADACBX provided without UBE.
3	ACBX file number > 65,535.
4	Reserved field not zero.
5	ACBX length incorrect

On open systems, a requested function is not yet implemented.

**Action**

On mainframe systems, if subcode 3 occurs, notify your Software AG technical support representative. If any of the other subcodes occur, correct the ACBX specification and rerun.

On open systems, wait for a later version of Adabas.

**Response 251**

**Origin**

Mainframe and open systems

**Explanation**

On mainframe systems, an error occurred in Adabas cluster processing. Under certain conditions, the Adabas cluster SVC (SVCCLU) component of the ADASVC returns response code 251 in the ACB's response code field, along with a hexadecimal subcode (listed below in decimal) in the low-order (rightmost) two bytes of the Additions 2 field. In the case of an ACBX, the ADASVC returns response code 251 in the ACBX's Response Code (ACBXRSP) field and the subcode in the Error Subcode (ACBXERRC) field.

- If the local SVCCLU detects the condition, the subcode will range from 2 through 30.
- If a remote SVCCLU detects the condition, it will range from 102 through 130.

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
2	The remote cluster nucleus to which the user is assigned cannot be accessed.
4	There are no user table entries (UTES) available for use.
5	Internal error. The nucleus specified by an internal command was not found.
7	Internal error. The user was assigned to a remote nucleus by the local system but the remote system found that the nucleus was not active.
9	Internal error. The 28-byte user ID is all zeros.
17	Entire Net-Work is not active.
19	Internal error. Invalid internal command code.
20	Remote nuclei are active; command must be assigned remotely but the remote nuclei are not accepting commands.
21	The remote image to which the user is assigned has no usable nuclei.
22	An attempt was made to assign a user remotely but Entire Net-Work is not active.
25	No system image target
26	System image target changed
27	Internal error.
28	Version mismatch between the PLXCB and the SVCCLU part of the ADASVC.
29	Probably, you used a NUCID value from a restricted range. Otherwise, this is an internal error.  <i>Action:</i> Ensure that the NUCID assignments are valid.

Subcode	Meaning
30	More than 32 NUCIDs were detected for the same SVC/DBID combination. <i>Action:</i> Reduce the number of NUCIDs on the SVC/DBID to 32.
41	An invalid PLXCB dataspace ALET was detected during command initiation. The PLXCB is unusable. The ALET has been removed from the IDTH prefix.
45	An invalid PLXCB dataspace ALET was detected during command completion. The PLXCB is unusable. The ALET has been removed from the IDTH prefix.
43	An invalid PLXCB dataspace header was detected. The PLXCB is unusable. The ALET has been removed from the IDTH prefix.
44	A program check occurred while using the PLXCB dataspace ALET. The PLXCB is unusable. The ALET has been removed from the IDTH prefix. Under z/OS a software LOGREC (EREP) record was created.

On open systems, an invalid utility call - versions conflict occurred.

**Action**

For internal errors on mainframe systems, contact your Software AG technical support representative. For all other mainframe errors except as noted, contact your systems administrator.

On open systems, check whether the utilities and database nuclei are of the same version. Contact your Software AG technical support representative for assistance.

**Response 252****Origin**

Mainframe and open systems

**Explanation**

On mainframe systems, an error occurred during Adabas SVC processing (post error).

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, an invalid subroutine call - coding error occurred. This response may also be returned on setting the Entire Net-Work timeout via Adaset Timeout if Entire Net-Work is not correctly installed.

**Action**

For open systems, contact your Software AG technical support representative.

**Response 253****Origin**

Mainframe and open systems

**Explanation**

On mainframe systems, an error occurred processing a buffer.

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

The following subcodes are possible:

Subcode	Meaning
0	Buffer length 0 (ACB user only)
1	Format buffer address zero
2	Record buffer address zero
3	Search buffer address zero
4	Value buffer address zero
5	ISN buffer address zero
6	User information buffer address zero
7	Performance buffer address zero
8	Multifetch buffer address zero
9	Unsupported ABD buffer type
10	Attached buffer overrun
11	Unsupported ABD version
12	ACBX not accepted by target
13	Unable to convert ACBX to ACB
14	ALET value not permitted
15	Unable to process 64-bit buffer address
16	Invalid buffer location indicator
17	Logic error locating ABD
18	More than 65,535 ABDs of any single type.
19	Reserved field not zero
20	ADABDX length incorrect
1xx	An error occurred attempting to allocate a Pause Element. The subcode is 100 (decimal) added to the return code from the z/OS IEAVAPE service.  <i>Action:</i> Refer to IBM z/OS documentation for IEAVAPE for an explanation of its return code. Contact your Software AG support representative for assistance.
2xx	An error occurred attempting to pause using a Pause Element. The subcode is 200 (decimal) added to the return code from the z/OS IEAVPSE service.  <i>Action:</i> Refer to IBM z/OS documentation for IEAVPSE for an explanation of its return code. Contact your Software AG support representative for assistance.

On open systems, the system file is not loaded or inconsistent.

**Action**

For mainframe systems, subcodes 10 and 17 are internal logic errors; notify your Software AG support representative. For all other subcodes, correct the buffer specification error and rerun.

On open systems, check the system files by running ADAVFY.

**Response 254**

**Origin**

Mainframe systems only

**Explanation**

A validation error occurred during command completion processing while attempting to return results to the caller.

One of the following has occurred:

- An internal error occurred during processing of an attached buffer (buffer overflow)
- The CT parameter limit was exceeded. Message ADAM93 (or a similar message) is printed or displayed on the console.

If the CT parameter limit was exceeded, the nucleus terminated the user, generated the equivalent of a BT command internally, released the CQE and attached buffer space, and issued ADAM93 (or a similar message).

If the user was not terminated, the subcode in the right-most two bytes of the ACB's Additions 2 field or the subcode in the ACBX's Error Subcode (ACBXERRC) field describes the failed validity check.

- If you are running with Entire System Server, the TIME parameter limit was exceeded. Message ADAM93 (or a similar message) displays on the console.

**Note:** If you are running with Entire Net-Work, the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

Subcode	Meaning
1	UBCQEX is less than or equal to zero
2	UBCQEX is greater than CQHNCQES
3	CQEFLAG is not equal to CQEFAB plus CQEFW16
4	CQEAUB is not equal to A'UB
5	CQEAUPL is not equal to A'APL
6	The low-order 6 bytes of CQECKSUM does not equal UBCKSUM
7	CQE was timed out
8	An inconsistency in the CQE such as the following: <ul style="list-style-type: none"> <li>■ The CQE was unexpectedly taken by another call .</li> <li>■ The user buffer (UB) is not receiving expected user information.</li> <li>■ The target move data length is inconsistent.</li> </ul>
9	Record buffer overflow
10	ISN buffer overflow

Subcode	Meaning
11	Inconsistent format buffer length
12	Inconsistent search buffer length
13	Inconsistent value buffer length
14	Inconsistent user buffer length
15	Invalid attached buffer ABD index (internal logic error)
16	Buffer overflow; see ACBXERRD and ACBXERRE

**Action** Ensure that the caller's control structures and parameters are not altered while the command is being processed. If you are unable to resolve the error, notify your Software AG support representative.

**Response 255**

**Origin** Mainframe and open systems

**Explanation** On mainframe systems, all attached buffers were allocated at the time the command was processed. Buffer allocation "high water marks" may not reflect this condition when no buffer allocation occurs.

**Note:** A Response 255 may also be issued by Entire Net-Work and in these circumstances the leftmost two bytes of the Additions 2 field (in the ACB) or the ACBXERRC field (in the ACBX) may contain the ID of the Entire Net-Work node that issued this response code.

On open systems, the Adabas command could not be processed because not enough Adabas nucleus or operating system resources are available. The value in the first two bytes of the Additions 2 field indicates the reason (2-byte binary format).

**Action** On open systems, perform the following actions, based on the subcode:

Subcode	Action
1	No space is available for the attached buffers. Increase the LAB (length of attached buffers) parameter.
2	No space is available in the client ID table. Increase the NCL (number of client threads) parameter.
3	Message queue generation failed. Increase the corresponding operating system parameters (please refer to the Adabas open systems installation documentation for further information).
4-6	An internal error occurred; an unexpected response code was received from a system function. Contact your Software AG technical support representative.
7 (only with ADALNKX)	The ADAMPLNK executable could not be loaded. Make this module available.
8	No space is available for extended attached buffers. Increase the value of the LABX (length of extended attached buffers) parameter.

# 3

## Entire Net-Work LUW Messages

---

All Entire Net-Work messages appear in the *net-work.log* file located wherever Entire Net-Work log files are stored.

<b>WCP000I</b>	<b>Software AG Internal tracing</b>
<b>Explanation</b>	Used for Software AG internal tracing.
<b>Action</b>	No action is required for this informational message.
<b>WCP0001I</b>	<b>Incoming connection from Entire Net-Work Server={nodename}</b>
<b>Explanation</b>	An incoming connection from the named Entire Net-Work server node has been received. The reference number ( <i>ref-num</i> ) given in the message is for internal Software AG use only.
<b>Action</b>	No action is required for this informational message.
<b>WCP0002I</b>	<b>DBID={dbid} is now active on remote Entire Net-Work Server={nodename}</b>
<b>Explanation</b>	The identified database is active on the named Entire Net-Work remote server node and can therefore be accessed from the local node.
<b>Action</b>	No action is required for this informational message.
<b>WCP0003I</b>	<b>DBID={dbid} has been deactivated on remote Entire Net-Work Server={nodename}</b>
<b>Explanation</b>	The identified database has been deactivated on the named Entire Net-Work server node and is therefore no longer available to the local node.
<b>Action</b>	No action is required for this informational message.

<b>WCP0004I</b>	<b>Outbound connection to Entire Net-Work Classic node={nodename}</b>
<b>Explanation</b>	An outbound connection has been made to the named Entire Net-Work classic node.
<b>Action</b>	No action is required for this informational message.
<b>WCP0005I</b>	<b>Node identifier is {nodeid}, maximum message size is {size}</b>
<b>Explanation</b>	This message indicates the node identifier and the maximum possible message size acceptable to the remote node specified by the previous log entry.
<b>Action</b>	No action is required for this informational message.
<b>WCP0006I</b>	<b>Entire Net-Work for {platform} is initializing on {hostname}</b>
<b>Explanation</b>	Entire Net-Work for the named platform is initializing on the named host computer.
<b>Action</b>	No action is required for this informational message.
<b>WCP0007I</b>	<b>Product Information: Version={version} Patch Level={level}</b>
<b>Explanation</b>	This message provides the version and patch level for the Entire Net-Work product.
<b>Action</b>	No action is required for this informational message.
<b>WCP0008I</b>	<b>{string1}</b> <b>{string2}</b>
<b>Explanation</b>	This message displays two informational messages strings.
<b>Action</b>	No action is required for this informational message.
<b>WCP0009I</b>	<b>Total Kernel Requests {count}</b>
<b>Explanation</b>	This message provides the total number of Kernel requests made to the Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0010I</b>	<b>Process Resources: FSIZE ({d}/{d}) NOFILE ({d}/{d})</b>
<b>Explanation</b>	This message provides information to Software AG technical support.
<b>Action</b>	No action is required for this informational message.
<b>WCP0011I</b>	<b>Total Direct Clients {count}</b>
<b>Explanation</b>	This message provides the total number of direct clients connected to the Kernel.
<b>Action</b>	No action is required for this informational message.

---

<b>WCP0012I</b>	<b>Total Relayed Clients {count}</b>
<b>Explanation</b>	This message provides the total number of relayed clients connected to the Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0013I</b>	<b>Period time {n}h.{n}m.{n}s</b>
<b>Explanation</b>	This message provides the length of time the Kernel has been running.
<b>Action</b>	No action is required for this informational message.
<b>WCP0014I</b>	<b>e-Business Administration Messages {count}</b>
<b>Explanation</b>	This message provides the total number of e-business administration messages made to the Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0015I</b>	<b>e-Business Communication Errors {count}</b>
<b>Explanation</b>	This message provides the total number of e-business communication errors that occurred with the Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0016I</b>	<b>Total Kernel Replies {count}</b>
<b>Explanation</b>	This message provides the total number of replies made by the Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0017I</b>	<b>Total Kernel Input Bytes {count}</b>
<b>Explanation</b>	This message provides the total number of bytes input to the Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0018I</b>	<b>Entire Net-Work initialization complete</b>
<b>Explanation</b>	Entire Net-Work has completed the initialization process.
<b>Action</b>	No action is required for this informational message.
<b>WCP0019I</b>	<b>Total Kernel Output Bytes {count}</b>
<b>Explanation</b>	This message provides the total number of bytes output by the Kernel.
<b>Action</b>	No action is required for this informational message.

<b>WCP0020I</b>	<b>License parameter {name}</b>
<b>Explanation</b>	This message shows license parameter values.
<b>Action</b>	No action is required for this informational message.
<b>WCP0021I</b>	<b>License 90-day Trial License</b>
<b>Explanation</b>	This message indicates that you are running with a 90-day trial license.
<b>Action</b>	No action is required for this informational message.
<b>WCP0022I</b>	<b>Disconnection requested by remote Entire Net-Work Server={nodename}</b>
<b>Explanation</b>	The remote Entire Net-Work node listed in the message has requested a disconnection. The reference number ( <i>ref-num</i> ) given in the message is for internal Software AG use only.
<b>Action</b>	No action is required for this informational message.
<b>WCP0023I</b>	<b>Disconnection notified by remote Entire Net-Work Server={nodename}</b>
<b>Explanation</b>	The remote Entire Net-Work node listed in the message has successfully disconnected. The reference number ( <i>ref-num</i> ) given in the message is for internal Software AG use only.
<b>Action</b>	No action is required for this informational message.
<b>WCP0024I</b>	<b>This Entire Net-Work log file is being closed by {user-name}</b>
<b>Explanation</b>	The log file is being closed by a user of the System Management Hub or the NETSTOP utilities. A new <i>net-work.log</i> file is being created.
<b>Action</b>	No action is required for this informational message.
<b>WCP0025I</b>	<b>DBID={dbid} is now e-business registered on the local kernel</b>
<b>Explanation</b>	An Adabas database with the identified database number is now available via the Entire Net-Work e-business Listen port (default port number 9010).
<b>Action</b>	No action is required for this informational message.
<b>WCP0026I</b>	<b>DBID={dbid} no longer e-business registered on the local kernel</b>
<b>Explanation</b>	The Adabas database with the identified database ID is no longer available via the Entire Net-Work e-business Listen port (default port number 9010).
<b>Action</b>	No action is required for this informational message.

---

<b>WCP0027I</b>	<b>Immediate disconnect indication from Entire Net-Work Classic node={nodename}</b>
<b>Explanation</b>	The identified classic Entire Net-Work node has indicated an immediate disconnection.
<b>Action</b>	No action is required for this informational message.
<b>WCP0028I</b>	<b>Immediate disconnection of DBID={dbid}</b>
<b>Explanation</b>	The identified e-business database has indicated an immediate disconnection.
<b>Action</b>	No action is required for this informational message.
<b>WCP0029I</b>	<b>DBID={dbid} is now connected to the local kernel</b>
<b>Explanation</b>	The identified e-business Adabas database is now active on the local Entire Net-Work node.
<b>Action</b>	No action is required for this informational message.
<b>WCP0030I</b>	<b>Information from Internal Transport Subsystem:</b>
<b>Explanation</b>	This message provides an internal transport subsystem message as the result of a previously logged error.
<b>Action</b>	No action is required for this informational message.
<b>WCP0031I</b>	<b>Remote Kernel is of type {system-type}</b>
<b>Explanation</b>	This message provides the operating system or hardware type of the remote Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0032I</b>	<b>Total CPU Time since started {n}h.{n}m.{n}s</b>
<b>Explanation</b>	This message provides the total CPU time that occurred since the Kernel started.
<b>Action</b>	No action is required for this informational message.
<b>WCP0033I</b>	<b>Entire Net-Work for {platform} timestamp on {year-month-day}</b>
<b>Explanation</b>	This message identifies the operating system or hardware platform of the Entire Net-Work node as well as the current date and time. The message is provided at intervals in a log file to assist in identifying the Entire Net-Work configuration.
<b>Action</b>	No action is required for this informational message.

<b>WCP0035I</b>	<b>Entire Net-Work Server &lt;Service={service}&gt;</b>
<b>Explanation</b>	This message identifies the Entire Net-Work Server.
<b>Action</b>	No action is required for this informational message.
<b>WCP0036I</b>	<b>Entire Net-Work Client &lt;Service={service}&gt;</b>
<b>Explanation</b>	This message identifies the Entire Net-Work Client.
<b>Action</b>	No action is required for this informational message.
<b>WCP0037I</b>	<b>Entire Net-Work &lt;Kernel={id}&gt;</b>
<b>Explanation</b>	This message identifies the Entire Net-Work Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0038I</b>	<b>e-Business Nodes {count}</b>
<b>Explanation</b>	This message provides the number of e-business nodes that Entire Net-Work knows about.
<b>Action</b>	No action is required for this informational message.
<b>WCP0039I</b>	<b>Connected e-Business Nodes Count {count}</b>
<b>Explanation</b>	This message provides the number of e-business nodes to which Entire Net-Work is connected.
<b>Action</b>	No action is required for this informational message.
<b>WCP0040I</b>	<b>*****Periodic statistical data report*****</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0041I</b>	<b>Current Direct Clients {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of current direct clients connected to this node.
<b>Action</b>	No action is required for this informational message.

---

<b>WCP0042I</b>	<b>Current Relayed Clients {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of current relayed clients connected to this node.
<b>Action</b>	No action is required for this informational message.
<b>WCP0043I</b>	<b>Total Memory Allocations {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0044I</b>	<b>Total Memory Frees {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0045I</b>	<b>Known Databases {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0046I</b>	<b>Active Databases {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0047I</b>	<b>Local Adabas Calls {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0048I</b>	<b>Host Counter {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of hosts connected to this node.
<b>Action</b>	No action is required for this informational message.

<b>WCP0049I</b>	<b>Number of Work Units Processed {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0050I</b>	<b>Classic Node Count {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0051I</b>	<b>Connected Classic Nodes {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0052I</b>	<b>Classic Messages Processed {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0053I</b>	<b>Classic Messages in Progress {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0054I</b>	<b>Classic Administration Messages {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0055I</b>	<b>Classic Communication Errors {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.

---

<b>WCP0056I</b>	<b>e-Business Messages Processed {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0057I</b>	<b>Ping Counter {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of pings to this node.
<b>Action</b>	No action is required for this informational message.
<b>WCP0058I</b>	<b>e-Business Contexts Processed {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of e-business contexts processed by the node.
<b>Action</b>	No action is required for this informational message.
<b>WCP0059I</b>	<b>e-Business Contexts Active {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of active e-business contexts.
<b>Action</b>	No action is required for this informational message.
<b>WCP0060I</b>	<b>Kernel Inbound Requests/Sec {rate}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the rate (requests per second) at which inbound requests have been processed by the Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0061I</b>	<b>Kernel Outbound Requests/Sec {rate}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the rate (requests per second) at which outbound requests have been processed by the Kernel.
<b>Action</b>	No action is required for this informational message.

<b>WCP0062I</b>	<b>Kernel Inbound Data Rate (Bytes/Sec) {rate}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the rate (bytes per second) at which inbound data has been processed by the Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0063I</b>	<b>Kernel Outbound Data Rate (Bytes/Sec) {rate}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the rate (bytes per second) at which outbound data has been processed by the Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0064I</b>	<b>Database Requests/Second {rate}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0065I</b>	<b>Database Replies/Second {rate}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0066I</b>	<b>Database Request Data Rate (Bytes/Sec) {rate}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0067I</b>	<b>Database Reply Data Rate (Bytes/Sec) {rate}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.

---

<b>WCP0068I</b>	<b>Percentage of CPU Usage {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0069I</b>	<b>Time since started {hh:mm:ss}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0070I</b>	<b>e-Business Relay Calls {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report. It displays the number of e-business relay calls to this node.
<b>Action</b>	No action is required for this informational message.
<b>WCP0071I</b>	<b>Thread {thread-number} Work Units Completed {count}</b>
<b>Explanation</b>	This message is one of many messages that comprise the Periodic Statistical Data Report.
<b>Action</b>	No action is required for this informational message.
<b>WCP0072I</b>	<b>Disconnection indication from DBID={dbid}</b>
<b>Explanation</b>	The identified e-business database has indicated an immediate disconnection.
<b>Action</b>	No action is required for this informational message.
<b>WCP0073I</b>	<b>Current CPU usage {value}</b>
<b>Explanation</b>	The current CPU usage is shown in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0074I</b>	<b>Disconnection from Entire Net-Work Server={server-name}</b>
<b>Explanation</b>	An attempt to disconnect from a remote Entire Net-Work Server occurred.
<b>Action</b>	No action is required for this informational message.

<b>WCP0075I</b>	<b>Outbound connection to Entire Net-Work Server={server-name}"</b>
<b>Explanation</b>	An outbound connection exists for the Entire Net-Work Server listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0076E</b>	<b>Outbound connection to Entire Net-Work Server={server-name} failed rc={rsp}</b>
<b>Explanation</b>	The outbound connection for the Entire Net-Work Server listed in the message failed. The response code from the attempt is also given in the message.
<b>Action</b>	Make sure the node of the outbound connection is up and that its parameters are configured correctly. Then refresh the Entire Net-Work Server connections, restarting it if necessary to do so.
<b>WCP0077I</b>	<b>e-Business server listening on TCPIP port={portnum}</b>
<b>Explanation</b>	An e-business server is listening on the TCP/IP port listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0078I</b>	<b>e-Business server listening on SSL port={portnum}</b>
<b>Explanation</b>	An e-business server is listening on the SSL port listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0079I</b>	<b>SMH server listening on TCPIP port={portnum}</b>
<b>Explanation</b>	The SMH server is listening on the TCP/IP port listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0080I</b>	<b>DBID={dbid} has now started on the local kernel</b>
<b>Explanation</b>	The identified database is now active on the local Kernel and can therefore be accessed by both classic and e-business clients.
<b>Action</b>	No action is required for this informational message.
<b>WCP0081I</b>	<b>Local DBID={dbid} is no longer available</b>
<b>Explanation</b>	The identified database has been deactivated on the local node and is therefore no longer available to any clients.
<b>Action</b>	No action is required for this informational message.

<b>WCP0082I</b>	<b>Shutdown request received for {node-name}</b>
<b>Explanation</b>	A shutdown request has been received for the node name listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0083I</b>	<b>Shutdown request received from {node-name}</b>
<b>Explanation</b>	The identified remote System Management Hub operator has requested a shutdown of Entire Net-Work. This instance will complete its shutdown once various administration tasks have completed.
<b>Action</b>	No action is required for this informational message.
<b>WCP0084I</b>	<b>Signal value={value}</b>
<b>Explanation</b>	The message identifies the signal that interrupted the process before it crashed. These values provide system information useful to Software AG technical support.
<b>Action</b>	No action is required for this informational message.
<b>WCP0085E</b>	<b>e-Business server failed with error={number}</b>
<b>Explanation</b>	The message indicates that the e-business server failed. An error number is provided in the message.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0086I</b>	<b>Periodic ping of classic node={node-name} took {nnnn} milliseconds</b>
<b>Explanation</b>	As the result of a periodic heartbeat operations, this classic node was sent a ping message to check its connection path. The classic node replied within the time indicated.
<b>Action</b>	No action is required for this informational message.
<b>WCP0087I</b>	<b>Periodic ping of DBID={dbid} took {nnnn} milliseconds</b>
<b>Explanation</b>	As the result of a periodic "heartbeat" operation, this database was sent a "PING" message to check its availability. The database replied within the time indicated.
<b>Action</b>	No action is required for this informational message.
<b>WCP0088I</b>	<b>Continuation of previous log file, renamed to {netxxxx.log}</b>
<b>Explanation</b>	The log file is renamed to <i>netxxxx.log</i> , where <i>xxxxxx</i> is a number. This message appears as the first line on a continuation log file.
<b>Action</b>	No action is required for this informational message.

<b>WCP0089I</b>	<b>e-Business server incoming connection</b>
<b>Explanation</b>	An e-business server incoming connection is described in the message. The reference number ( <i>ref-num</i> ) listed in the message is for internal Software AG use only.
<b>Action</b>	No action is required for this informational message.
<b>WCP0090I</b>	<b>e-Business server is now connected to {nodename}</b>
<b>Explanation</b>	The identified server is now connected to the local node. The reference number ( <i>ref-num</i> ) listed in the message is for internal Software AG use only.
<b>Action</b>	No action is required for this informational message.
<b>WCP0091I</b>	<b>Entire Net-Work Servers {nnnnnnnnn}</b>
<b>Explanation</b>	This message is part of the periodic statistical data report.
<b>Action</b>	None. This message is informational only.
<b>WCP0092I</b>	<b>Entire Net-Work Server={server-name} is now registered</b>
<b>Explanation</b>	The identified Entire Net-Work Server is now accessible from the local node.
<b>Action</b>	None. This message is informational only.
<b>WCP0093I</b>	<b>Immediate disconnection from Entire Net-Work Server={server-name}</b>
<b>Explanation</b>	An immediate disconnection for the named Entire Net-Work Server occurred. The reference number ( <i>ref-num</i> ) given in the message is for internal Software AG use only.
<b>Action</b>	No action is required for this informational message.
<b>WCP0094I</b>	<b>Command Parameter={name}: {value}</b>
<b>Explanation</b>	This message lists the value of the parameter used to start the running Kernel.
<b>Action</b>	No action is required for this informational message
<b>WCP0095I</b>	<b>Setting Partition={partition-name}"</b>
<b>Explanation</b>	This message indicates that a partition has been defined and gives the name of the partition.
<b>Action</b>	No action is required for this informational message

<b>WCP0097I</b>	<b>e-Business for clients listening on TCPIP port={portnum}</b>
<b>Explanation</b>	This message identifies the TCP/IP port number on which e-business clients are listening.
<b>Action</b>	No action is required for this informational message
<b>WCP0098I</b>	<b>e-Business for clients listening on SSL port={portnum}</b>
<b>Explanation</b>	This message identifies the SSL port number on which e-business clients are listening.
<b>Action</b>	No action is required for this informational message
<b>WCP0099I</b>	<b>Shutdown complete. Entire Net-Work is terminating.</b>
<b>Explanation</b>	Entire Net-Work is shutting down. Entire Net-Work
<b>Action</b>	No action is required for this informational message.
<b>WCP0100I</b>	<b>Classic server listening on TCPIP port=%d</b>
<b>Explanation</b>	This message identifies the TCP/IP port on which a classic server is listening.
<b>Action</b>	No action is required for this informational message.
<b>WCP0101W</b>	<b>Duplicate database number {dbid} detected on Kernel {kernel-name}</b>
<b>Explanation</b>	A Kernel has indicated that the identified database is active. However, the local node is already aware of this database due to a previous connection. The duplication is ignored and the original path to the database is maintained.
<b>Action</b>	This error may be caused by a genuine duplication of a database number, which should be corrected by the DBA or by excessively complex connections among classic Entire Net-Work nodes. You should examine your configuration to determine if the connections causing this message can be eliminated.
<b>WCP0102W</b>	<b>No outbound connections defined for this configuration</b>
<b>Explanation</b>	Entire Net-Work cannot make outbound connections unless connections to other classic Entire Net-Work nodes are defined.
<b>Action</b>	If outbound connections are desired, they must be defined. For more information, see the section <i>Entire Net-Work Client Administration</i> in the <i>Entire Net-Work Client Installation and Administration Guide</i> .

<b>WCP0103W</b>	<b>Adabas Context={context} DBID={dbid} Client={client-id} Timeout deletion</b>
<b>Explanation</b>	The Adabas context listed in the message has been deleted for the database listed in the message.
<b>Action</b>	No action is required for this warning message.
<b>WCP0104W</b>	<b>Remote administration of this kernel has been disabled</b>
<b>Explanation</b>	The local Entire Net-Work Kernel cannot be administered remotely by a System Management Hub. This is normally the result of a specific configuration action to inhibit remote management.
<b>Action</b>	If remote management is desired, the Entire Net-Work Kernel must be restarted with configuration changes.
<b>WCP0105W</b>	<b>e-Business incoming connection from Entire Net-Work Server={servername}</b>
<b>Explanation</b>	A connection between two Entire Net-Work nodes was detected. This is not recommended and is usually an indication of a configuration error.
<b>WCP0106W</b>	<b>Remote kernel rejected connection request. rc={code}</b>
<b>Explanation</b>	The remote kernel has rejected a connection from Entire Net-Work for open systems. Typical reasons include: <ul style="list-style-type: none"><li>■ incorrect configuration at the remote node</li><li>■ unsolicited mode not enabled at the remote node</li><li>■ errors in DNS or DHCP operation</li></ul>
<b>Action</b>	No action is required for this informational message.
<b>WCP0107W</b>	<b>Remote kernel rejected connection. Local kernel is unknown</b>
<b>Explanation</b>	A connection attempt from the local kernel was rejected by a classic remote node because the local kernel was not defined.
<b>Action</b>	Add the name of the local kernel to the definitions at the remote node or enable unsolicited connections at the remote node.
<b>WCP0108W</b>	<b>Adabas Context={context} DBID={dbid} Client={client-id} Set for timeout deletion</b>
<b>Explanation</b>	The Adabas context listed in the message for the database and owners listed in the message is scheduled for deletion.
<b>Action</b>	No action is required for this warning message.

---

<b>WCP0109W</b>	<b>Local DBID={dbid} starting, but previous location was remote</b>
<b>Explanation</b>	A database has started on the local node; however, this database ID was previously used by another database on a remote node.
<b>Action</b>	This indicates a configuration error that needs to be corrected.
<b>WCP0110W</b>	<b>Classic node disconnect. Pending request TID={terminal ID} gets rc=149</b>
<b>Explanation</b>	The named classic Entire Net-Work node is disconnecting while there are active database calls being processed. The application with the indicated Terminal ID will receive an Adabas response code 149 (ADARSP149 - communications error) as the database is no longer reachable.
<b>Action</b>	Restart the application.
<b>WCP0111I</b>	<b>Trace level set to {newlevel} by the user</b>
<b>Explanation</b>	A user has changed the tracing level to the new numeric level shown in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0112I</b>	<b>Ping request received from the user; Target {target ID}, Length {length}, Count {number}</b>
<b>Explanation</b>	A user has requested a PING operation to the target ID identified in the message. PINGs are used to test the integrity of a remote classic connection to the path to a database.
<b>Action</b>	No action is required for this informational message.
<b>WCP0113I</b>	<b>Start new log file requested by the user</b>
<b>Explanation</b>	A user has requested that the current logging file be closed and a new log file started.
<b>Action</b>	No action is required for this informational message.
<b>WCP0114W</b>	<b>No directory information for Entire Net-Work Server={server-ID}</b>
<b>Explanation</b>	An internal error occurred for an Entire Net-Work Server. It was not possible to create the definitions for a classic database to allow it to be accessed by e-business clients.
<b>Action</b>	Restart Entire Net-Work.

<b>WCP0115W</b>	<b>Unidentified database ping reply received</b>
<b>Explanation</b>	A PING message was received for which there was no PING request. This indicates that a logical messages sequencing failure occurred at a remote database.
<b>Action</b>	If the error persists, restart the remote database.
<b>WCP0116W</b>	<b>Calling DBID={dbid} failed; response code={rc-code}</b>
<b>Explanation</b>	Following a connection by an e-business database (message WCP0029I), the Entire Net-Work Kernel tried to send a simple Adabas command to the database to test the integrity of the communications path. This test failed. The database is not e-business registered at the local node nor is it broadcast to classic nodes. This error normally results from a failure to provide an XTSaccess URL for the e-business database in the Directory Server. The Adabas response code from the connection attempt is given in the message. For complete information on Adabas response codes, refer to the <i>Adabas Messages and Codes Manual</i> .
<b>Action</b>	Verify that you have provided an XTSaccess URL for the e-business database in the Directory Server and try again.
<b>WCP0117W</b>	<b>DBID={dbid} is now connected as e-business</b>
<b>Explanation</b>	An Adabas database has connected previously as a classic or local database, disconnected, and is now being connected as an e-business database. This may be intentional or it may be a configuration error.
<b>Action</b>	No action is required for this informational message.
<b>WCP0118W</b>	<b>DBID={dbid} issued an e-business disconnection</b>
<b>Explanation</b>	A database was originally connected as a classic or local database, but an e-business disconnection was received.  The database is not disconnected.
<b>Action</b>	If the error persists, contact your Software AG technical support representative.
<b>WCP0119W</b>	<b>Duplicate URL={url} for target={target} in the Directory Server</b>
<b>Explanation</b>	During the Kernel startup process, a duplicate URL was discovered in the Directory Server. The duplicate URL is ignored. This error can be caused by incorrect administration of the Directory Server entries.
<b>Action</b>	No action is necessary unless the duplicate URL is in error. In this case, correct the URL as described in your Adabas Directory Server documentation. Read <i>Directory Server Target Entries</i> in the <i>Software AG Directory Server Installation and Administration Guide</i> .

---

<b>WCP0120W</b>	<b>This entry URL={url} for target={target} in the Directory Server has a syntax error</b>
<b>Explanation</b>	During the Kernel startup process, a URL was read in the Directory Server with a syntax error. The incorrect URL is ignored. This error can be caused by incorrect administration of the Directory Server entries.
<b>Action</b>	Correct the URL as described in your Adabas Directory Server documentation. Read <i>Directory Server Target Entries in the Software AG Directory Server Installation and Administration Guide</i> .
<b>WCP0121I</b>	<b>Client ID={client-id} Host={host-id} Port={portnum} accepted; Current clients={count}</b>
<b>Explanation</b>	This message indicates that an incoming client connection was made and identifies the client ID, the host ID, the port number, and the number of current active client connections.
<b>Action</b>	No action is required for this informational message.
<b>WCP0122I</b>	<b>Client ID={client-id} disconnected; Current clients={count}</b>
<b>Explanation</b>	This message indicates that a client connection was dropped and identifies the client ID and the number of current client connections.
<b>Action</b>	No action is required for this informational message.
<b>WCP0123W</b>	<b>e-Business Server not defined</b>
<b>Explanation</b>	An e-business Entire Net-Work Server access definition has not been defined in this Entire Net-Work implementation.
<b>Action</b>	No action is required for this informational message.
<b>WCP0124W</b>	<b>Classic Server not defined</b>
<b>Explanation</b>	A classic Entire Net-Work Server access definition has not been defined in this Entire Net-Work implementation.
<b>Action</b>	No action is required for this informational message.
<b>WCP0125W</b>	<b>e-Business Client Access not defined</b>
<b>Explanation</b>	An Entire Net-Work Client access definition has not been defined in this Entire Net-Work implementation.
<b>Action</b>	No action is required for this informational message.

<b>WCP0126I</b>	<b>License File={name}</b>
<b>Explanation</b>	The name of the license file used for this installation of Entire Net-Work is given in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0127I</b>	<b>Relayed Client ID={client-id} DBID={dbid} Host={host} Port={port} connected; Relayed Clients={count}</b>
<b>Explanation</b>	The relay client ID, database ID, host name, port number and number of relayed clients are given in the message..
<b>Action</b>	No action is required for this informational message.
<b>WCP0128I</b>	<b>Relayed Client ID={client-id} DBID={dbid} disconnected; Relayed Clients={count}</b>
<b>Explanation</b>	The relay client ID, database ID, and number of relayed clients that have been disconnected are given in the message..
<b>Action</b>	No action is required for this informational message.
<b>WCP0131I</b>	<b>Client ID={client-id} Relaying to DBID={dbid}</b>
<b>Explanation</b>	The client named in the message is relaying data to the Adabas database identified in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0132I</b>	<b>Client ID={client-id} Local Calls to DBID={dbid}</b>
<b>Explanation</b>	The client named in the message is making local calls to the Adabas database identified in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0134I</b>	<b>Client ID={client-id} Name={name}</b>
<b>Explanation</b>	The client is identified in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0135W</b>	<b>Context inactive life={nnnn} seconds (zero is infinite)</b>
<b>Explanation</b>	The inactive life span of the context is given in the message.
<b>Action</b>	No action is required for this warning message.

<b>WCP0136W</b>	<b>Warning: the license does not allow SSL, however the kernel has SSL settings</b>
<b>Explanation</b>	Your Entire Net-Work license file does not support SSL use with Entire Net-Work, but SSL settings have been supplied for the kernel.
<b>Action</b>	Verify that the kernel settings are correct and adjust them if necessary. If they are correct, contact your Software AG technical support representative to obtain an updated license file.
<b>WCP0150I</b>	<b>e-Business server {server-name} connected via remote Entire Net-Work Server {server-name}</b>
<b>Explanation</b>	An Entire Net-Work-to-Entire Net-Work connection has occurred and the remote Entire Net-Work has a Kernel connected to it.  If a Kernel was started as a Windows service and subsequently shut down by means of the Services Control Panel, this informational message is added to the log.
<b>Action</b>	No action is required for this informational message.
<b>WCP0151I</b>	<b>e-Business DBID={dbid} connected via remote Entire Net-Work Server {server-name }</b>
<b>Explanation</b>	An Entire Net-Work-to-Entire Net-Work connection has occurred and databases known to the remote Entire Net-Work are now known to both.
<b>Action</b>	No action is required for this informational message.
<b>WCP0152I</b>	<b>Kernel {kernel-id} migrated from WCP73</b>
<b>Explanation</b>	The Kernel listed in the message was successfully migrated from the 7.3 version of Entire Net-Work.
<b>Action</b>	No action is required for this informational message.
<b>WCP0153I</b>	<b>Client {client-id} migrated from WCL13</b>
<b>Explanation</b>	The client listed in the message was successfully migrated from the 1.3 version of Entire Net-Work Client.
<b>Action</b>	No action is required for this informational message.
<b>WCP0154I</b>	<b>Kernel {kernel-id} has been migrated from WCP74</b>
<b>Explanation</b>	The kernel listed in the message was successfully migrated from the 7.4 version of Entire Net-Work.
<b>Action</b>	No action is required for this informational message.

<b>WCP0155I</b>	<b>Client {client-id} migrated from WCL14</b>
<b>Explanation</b>	The client listed in the message was successfully migrated from the 1.4 version of Entire Net-Work Client.
<b>Action</b>	No action is required for this informational message.
<b>WCP0156I</b>	<b>e-Business DBID={dbid} rejected for traffic relay</b>
<b>Explanation</b>	An e-business database was rejected for traffic relay, as defined by the Entire Net-Work filter settings. Entire Net-Work will not process requests for the database with the database ID given in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0157I</b>	<b>Classic DBID={dbid} rejected for traffic relay</b>
<b>Explanation</b>	A classic database was rejected for traffic relay, as defined by the Entire Net-Work filter settings. Entire Net-Work will not process requests for the database with the database ID given in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0158I</b>	<b>Adabas DBID={dbid} verified and active</b>
<b>Explanation</b>	During the periodic check of its known connections, Entire Net-Work has verified that its connection to the e-business database listed in the message is valid and active.
<b>Action</b>	No action is required for this informational message.
<b>WCP0159I</b>	<b>e-Business DBID={dbid} rejected by filter</b>
<b>Explanation</b>	An e-business database was rejected by a filter, as defined by the Entire Net-Work filter settings. Entire Net-Work will not process requests for the database with the database ID given in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0160I</b>	<b>Incoming Classic connection</b>
<b>Explanation</b>	This message indicates that an incoming classic connection was made.
<b>Action</b>	No action is required for this informational message.

---

<b>WCP0161I</b>	<b>Outgoing Classic connection to {node}</b>
<b>Explanation</b>	This message indicates that an outgoing classic connection was made.
<b>Action</b>	No action is required for this informational message.
<b>WCP0162I</b>	<b>Connection already exists; new connection rejected</b>
<b>Explanation</b>	An attempt to connect to an already active connection occurred. The connection attempt was rejected.
<b>Action</b>	No action is required for this informational message.
<b>WCP0203E</b>	<b>Connection from Kernel={kernel-id} rejected by filters; node in the rejected list</b>
<b>Explanation</b>	An attempt to connect by the Kernel referenced in the message was rejected by filters. The Kernel node is included in the rejected filter list.
<b>Action</b>	No action is necessary unless you want a connection by the kernel to be accepted. If you do, adjust the parameters on the Kernel Filters panel in SMH.
<b>WCP0204E</b>	<b>Illegal message from classic server</b>
<b>Explanation</b>	Entire Net-Work received an illegal message from a classic server that it could not recognize. The message is ignored.
<b>Action</b>	If the problem persists, contact your Software AG support representative.
<b>WCP0205E</b>	<b>Adabas reply received from Kernel={kernel-id} for an unknown Adabas request</b>
<b>Explanation</b>	An Adabas reply has been received from the identified Kernel for a request that cannot be identified.
<b>Action</b>	If the error persists, restart Entire Net-Work.
<b>WCP0206E</b>	<b>Failure sending data to Kernel={kernel-id}.</b>
<b>Explanation</b>	The identified Kernel has been disconnected due to an I/O error detected during the send process.
<b>Action</b>	Check the connection status and try again.
<b>WCP0207E</b>	<b>Classic callback routine failure={code}</b>
<b>Explanation</b>	A connection failure has been detected by the internal transport subsystem. An internal transport subsystem failure code is provided in the message.
<b>Action</b>	Verify the connections are valid. If the error persists, contact you network administrator or your Software AG support representative for assistance.

<b>WCP0208E</b>	<b>Unexpected error in registering database={dbid} rc={rc}</b>
<b>Explanation</b>	An unexpected error has occurred while registering the identified classic database; the return code is provided.
<b>Action</b>	Take corrective action as indicated by the following internal transport subsystem message.
<b>WCP0209E</b>	<b>Connection from Kernel={kernel-id} rejected by filters; node not in the accepted list</b>
<b>Explanation</b>	An attempt to connect by the Kernel referenced in the message was rejected by filters. The Kernel node is <i>not</i> included in the accepted filter list.
<b>Action</b>	No action is necessary unless you want a connection by the kernel to be accepted. If you do, adjust the parameters on the Kernel Filters panel in SMH.
<b>WCP0210E</b>	<b>Client ID={client-id} Host={host} Port={port} rejected; Host not accepted by filter</b>
<b>Explanation</b>	The client on the host machine and port listed in the message has been rejected because the host machine is not accepted by the filter settings.
<b>Action</b>	No action is necessary unless you want a connection to be accepted. If you do, adjust the parameters on the Kernel Filters panel in SMH.
<b>WCP0211E</b>	<b>e-Business database connecting with an invalid DBID={dbid}</b>
<b>Explanation</b>	An e-business database has connected to Entire Net-Work but has indicated a database number that is not in the valid range of 0 - 65535.
<b>Action</b>	Change the database ID to the valid range.
<b>WCP0212E</b>	<b>Unsolicited connection attempt from Kernel={kernel-id} being rejected</b>
<b>Explanation</b>	A classic Entire Net-Work node with an unknown node name attempted to connect to Entire Net-Work while the SECURE parameter was set to ON.
<b>Action</b>	Define the node to Entire Net-Work for open systems.
<b>WCP0213E</b>	<b>Host={hostname} not accepted by filter</b>
<b>Explanation</b>	The host machine listed in the message is not accepted by the filter settings.
<b>Action</b>	No action is necessary unless you want a connection to the host machine to be accepted. If you do, adjust the parameters on the Kernel Filters panel in SMH.

---

<b>WCP0214E</b>	<b>Incoming classic connection from Entire Net-work node={nodename}</b>
<b>Explanation</b>	Connecting two Entire Net-Work nodes using the RDA protocol is not allowed.
<b>Action</b>	Remove or redefine the connection attempt.
<b>WCP0215E</b>	<b>SMH callback routine rc={code}</b>
<b>Explanation</b>	An error has occurred in a System Management Hub callback routine. The response code is given in the message.
<b>Action</b>	If the problem persists, contact your Software AG support representative.
<b>WCP0216E</b>	<b>SMH send data failure rc={code}</b>
<b>Explanation</b>	An error has occurred in a System Management Hub send routine. The return code for the failure is given in the message.
<b>Action</b>	If the problem persists, contact your Software AG support representative.
<b>WCP0217E</b>	<b>Broadcast callback routine failure completion rc={code}</b>
<b>Explanation</b>	An error occurred during a broadcast routine. The return code for the failure is given in the message.
<b>Action</b>	Verify that all the nodes are up and correctly configured. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0218E</b>	<b>Relay callback routine for Client ID={client-id} completion rc={code}</b>
<b>Explanation</b>	An error occurred during a relay routine. The return code for the failure is given in the message.
<b>Action</b>	Verify that all the nodes are up and correctly configured. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0219E</b>	<b>Relay callback routine for Client ID={client-id} DBID={dbid} zero length message</b>
<b>Explanation</b>	A zero length message was received during a relay routine.
<b>Action</b>	If the problem persists, contact your Software AG support representative.
<b>WCP0220E</b>	<b>Local database started with an invalid identifier={dbid}</b>
<b>Explanation</b>	A local database has started with an ID of less than 1 or greater than 65535. The startup is being ignored and the database is inaccessible from this Entire Net-Work node.
<b>Action</b>	Check the database configuration files.

<b>WCP0221E</b>	<b>Local database is starting with a conflicting DBID={dbid}</b>
<b>Explanation</b>	A local database has started with an ID that is already in use by another database (local, classic, or e-business remote) known to this Entire Net-Work node. The duplicate will be ignored.
<b>Action</b>	This indicated a configuration error that needs to be corrected.
<b>WCP0222E</b>	<b>Adabas reply received from Kernel {kernel-id} for an incorrect Adabas request</b>
<b>Explanation</b>	An Adabas reply was received from a Kernel. The reply could not be matched to a pending Adabas request and will be ignored.
<b>Action</b>	If the error persists, restart Entire Net-Work.
<b>WCP0223E</b>	<b>Unexpected error in registering Entire Net-Work Server={servername} rc={rc}</b>
<b>Explanation</b>	An internal error occurred registering Entire Net-Work Server. The response code is given in the message.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0224E</b>	<b>Client Id={client-id} not recognized by this server</b>
<b>Explanation</b>	The client identified in the message is not recognized by the Entire Net-Work server.
<b>Action</b>	If the problem persists, contact your Software AG support representative.
<b>WCP0228E</b>	<b>Adabas call to e-Business DBID={dbid} failed rc={code}</b>
<b>Explanation</b>	An internal failure occurred during an Adabas call to an e-business database. The database referenced in the Adabas call and the return code from the call are given in the message.
<b>Action</b>	Verify that the Adabas call is valid for the e-business database. If the problem persists, contact your Software AG support representative.
<b>WCP0229E</b>	<b>Adabas ACBX call to e-Business DBID={dbid} failed rc={code} acbxrc={acbxrc}</b>
<b>Explanation</b>	An internal failure occurred during an Adabas ACBX call to an e-business database. The database referenced in the Adabas call, the return code from the call, and the extended Adabas control block (ACBX) return code are given in the message.
<b>Action</b>	Verify that the Adabas call is valid for the e-business database. If the problem persists, contact your Software AG support representative.

<b>WCP0230E</b>	<b>Periodic ping of DBID={dbid} failed.</b>
<b>Explanation</b>	During the periodic check of database status, the database became unavailable.
<b>Action</b>	No user action is required.
<b>WCP0231E</b>	<b>Periodic ping of remote Kernel {kernel-id} failed, kernel disconnected</b>
<b>Explanation</b>	During the periodic check of a remote Kernel, the kernel became unavailable. The Kernel connection is disconnected.
<b>Action</b>	No user action is required.
<b>WCP0232E</b>	<b>Invalid e-Business DBID={dbid}; disconnecting...</b>
<b>Explanation</b>	An invalid Adabas DBID was encountered. Connections to the database are disconnected.
<b>Action</b>	If the error persists, contact your Software AG technical support representative.
<b>WCP0233E</b>	<b>Unknown e-Business DBID={dbid}; disconnected...</b>
<b>Explanation</b>	An unknown Adabas DBID was encountered and is disconnected.
<b>Action</b>	If the error persists, contact your Software AG technical support representative.
<b>WCP0235E</b>	<b>Unknown e-business Kernel={kernel-id}</b>
<b>Explanation</b>	An unknown Kernel (identified in the message) was encountered.
<b>Action</b>	If the error persists, contact your Software AG technical support representative.
<b>WCPO236E</b>	<b>Bad RDA packet header received.</b>
<b>Explanation</b>	A message was received on a classic connection that was not in the correct format. This can be caused by a port number configuration problem or it may be a denial of service attempt by Entire Net-Work 7.  The system marks the node as unusable and will not accept data from it.
<b>Action</b>	Review your use of RDA port numbers and correct them if necessary. Otherwise, you can ignore this message.
<b>WCP0237E</b>	<b>Unable to spawn Kernel={kernel-id}</b>
<b>Explanation</b>	For some reason, Entire Net-Work cannot start the Kernel identified in the message.
<b>Action</b>	Contact your Software AG technical support representative for assistance.

<b>WCP0238E</b>	<b>Syntax error in URL={url} for target={target-id}</b>
<b>Explanation</b>	A syntax error occurred during Entire Net-Work processing. The URL in error and the target ID for the URL are given in the message. This error can occur if manual updates to URL connection information are attempted.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0239E</b>	<b>EBZProxy callback routine for Client ID={client-id} DBID={dbid} completion rc={rcode}</b>
<b>Explanation</b>	A proxy error occurred. The client ID, database ID, and the return code from the attempt are given in the message.
<b>Action</b>	Make sure the proxy nodes are all up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0240E</b>	<b>EBZServer callback routine for Client ID={client-id} DBID={dbid} completion rc={rcode}</b>
<b>Explanation</b>	An Entire Net-Work Server error occurred. The client ID, database ID and the return code from the attempt are given in the message.
<b>Action</b>	Make sure the Entire Net-Work Server nodes are all up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0241E</b>	<b>EBZClient callback routine for Client ID={client-id} DBID={dbid} completion rc={rcode}</b>
<b>Explanation</b>	An Entire Net-Work Client error occurred. The client ID, database ID and the return code from the attempt are given in the message.
<b>Action</b>	Make sure the Entire Net-Work Client nodes are all up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0242E</b>	<b>Failed to relay request to Client ID={client-id} DBID={dbid} rc={rcode}</b>
<b>Explanation</b>	An attempt to relay a request to a database failed. The database ID and the return code from the attempt are given in the message.
<b>Action</b>	Make sure the Entire Net-Work nodes and the database in question are all up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.

---

<b>WCP0243E</b>	<b>ACBX request for Classic DBID={dbid} is not supported</b>
<b>Explanation</b>	An attempt to make an Adabas ACBX call to a classic (pre-Version 6 on open systems or pre-Version 8 on mainframe systems) Adabas database was made. ACBX calls are only allowed against Adabas 8 (or later) databases.
<b>Action</b>	Resolve the error (either run the ACBX call against a valid database or change the call to an ACB call) and try again.
<b>WCP0245E</b>	<b>DBID={dbid} is invalid, request rejected</b>
<b>Explanation</b>	A request was made to an invalid database.
<b>Action</b>	Correct the database specification and try again.
<b>WCP0246E</b>	<b>DBID={dbid} is inactive, request rejected</b>
<b>Explanation</b>	A request was made to an inactive Adabas database.
<b>Action</b>	Start the Adabas database and try again.
<b>WCP0247E</b>	<b>Context with Verifier={nnnn} LocalContext={context-id} DBID={dbid} ClientId={client-id} does not exist; request rejected</b>
<b>Explanation</b>	A communication error occurred. The request is rejected. The database ID of the database to which the request was directed is given in the message.
<b>Action</b>	Verify that all connections and the database in question are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0248E</b>	<b>Outbound connection failure; unknown target</b>
<b>Explanation</b>	An outbound connection was attempted but failed because the target could not be identified..
<b>Action</b>	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0249E</b>	<b>Invalid DBID={dbid}, no corresponding Kernel defined</b>
<b>Explanation</b>	A communication error occurred. The request is rejected. The database ID of the database to which the request was directed is given in the message.
<b>Action</b>	Verify that all connections and the database in question are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.

<b>WCP0250E</b>	<b>Failure to send data Kernel={kernel-id} rc={rcode}</b>
<b>Explanation</b>	A communication error occurred. The request is rejected. The return code from the request is given in the message.
<b>Action</b>	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0251E</b>	<b>Unknown request Client ID={client-id} DBID={dbid}, disconnecting...</b>
<b>Explanation</b>	An unknown client request was encountered. The client ID and Adabas database ID are given in the message.
<b>Action</b>	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0252E</b>	<b>Client ID={client-id} Host={hostname} Port={port} rejected; the number of client connections cannot exceed={count}</b>
<b>Explanation</b>	A client request was not processed because the number client connections has been exceeded. The client ID, host name, port number, and maximum number of client connections are given in the message.
<b>Action</b>	Verify that the maximum number of client connections is set correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0253E</b>	<b>Replying to Client ID={client-id} DBID={dbid} failed rc={rcode}</b>
<b>Explanation</b>	An attempt to reply to a client failed. The client ID, Adabas database ID, and return code from the attempt are given in the message.
<b>Action</b>	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0254E</b>	<b>Client ID={client-id} Host={hostname} Port={port} rejected; The CPU Threshold={percentage} exceeds maximum allowed={value}</b>
<b>Explanation</b>	The client on the host machine and port listed in the message was rejected because the CPU threshold was exceeded.
<b>Action</b>	Increase the CPU threshold setting. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0255E</b>	<b>ClientId={client-id} DBID={dbid} Replying error code={error} to client</b>
<b>Explanation</b>	An attempt to reply to a client failed. The client ID, Adabas database ID, and error from the attempt are given in the message.
<b>Action</b>	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.

---

<b>WCP0256E</b>	<b>DBID={dbid} is a non-accessible mainframe database; client traffic is not allowed.</b>
<b>Explanation</b>	An attempt to connect to a mainframe database failed. The Adabas database ID is given in the message.
<b>Action</b>	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0257E</b>	<b>Disconnecting Kernel={kernel-id} ...</b>
<b>Explanation</b>	An error occurred. The Kernel listed in the message is disconnected.
<b>Action</b>	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0258E</b>	<b>Context={context} DBID={dbid} set for deletion; request rejected.</b>
<b>Explanation</b>	An attempt to delete the Adabas context listed in the message for the database listed in the message failed.
<b>Action</b>	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0258E</b>	<b>Context deleted for DBID={dbid}; request rejected</b>
<b>Explanation</b>	An attempt to connect to the Adabas database listed in the message could not occur because the context for the database is deleted.
<b>Action</b>	Verify that all connections are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0259E</b>	<b>Unexpected destroy context received for Context={context} ClientId={client-id} from ClientId={client-id}; request rejected</b>
<b>Explanation</b>	An unexpected request to destroy a context was received for a client. The request is rejected.
<b>Action</b>	If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0301S</b>	<b>Unable to set the Directory Server</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Contact your Software AG technical support representative for assistance.

<b>WCP0302S</b>	<b>Unable to initialize Directory Server</b>
<b>Explanation</b>	An internal error has occurred in the internal transport subsystem, preventing the use of Directory Services.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0303S</b>	<b>Unable to start Directory Server</b>
<b>Explanation</b>	An internal error has occurred in the internal transport subsystem, preventing the use of Directory Services.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0304S</b>	<b>Unable to add a Directory Server entry</b>
<b>Explanation</b>	An internal error has occurred in the internal transport subsystem, preventing the use of Directory Services.
<b>Action</b>	Contact Software AG support with the information from accompanying message WCP0030I.
<b>WCP0308S</b>	<b>Unable to start the System Management Hub</b>
<b>Explanation</b>	This error is usually caused by an error in the internal transport subsystem.
<b>Action</b>	See the internal transport subsystem message following this message for more information.
<b>WCP0310S</b>	<b>Work Semaphore failed in thread {thread-number} error={error-number}</b>
<b>Explanation</b>	The Entire Net-Work threading mechanism failed.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.
<b>WCP0311S</b>	<b>Threading yield: failed in thread {thread-number} error={error-number}</b>
<b>Explanation</b>	The Entire Net-Work threading mechanism failed.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.
<b>WCP0312S</b>	<b>Invalid System Management Hub eyecatcher received</b>
<b>Explanation</b>	An invalid message was received from a System Management Hub. This error can be caused by incorrect Directory Service entries. The message is ignored.
<b>Action</b>	Check the version of the System Management Hub being used for compatibility with Entire Net-Work.

---

<b>WCP0313S</b>	<b>Invalid System Management Hub protocol version received</b>
<b>Explanation</b>	An invalid message was received from a System Management Hub. This error can be caused by incorrect Directory Service entries. The message is ignored.
<b>Action</b>	Check the version of the System Management Hub being used for compatibility with Entire Net-Work.
<b>WCP0314S</b>	<b>Invalid System Management Hub segment received</b>
<b>Explanation</b>	An invalid message was received from a System Management Hub. This error can be caused by incorrect Directory Service entries. The message is ignored.
<b>Action</b>	Check the version of the System Management Hub being used for compatibility with Entire Net-Work.
<b>WCP0315S</b>	<b>Request failed to wake work semaphore rc={rcode}</b>
<b>Explanation</b>	The Entire Net-Work semaphoring mechanism failed. The return code from the call is given in the message.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0316S</b>	<b>Thread wakeup call failed rc={rcode}</b>
<b>Explanation</b>	The Entire Net-Work threading mechanism failed. The return code from the call is given in the message.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.
<b>WCP0317S</b>	<b>Unable to remove Directory Service entry</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0318S</b>	<b>Local database resources problem. Increase NU parameter.</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0319S</b>	<b>Request failed to wake timer semaphore rc={rcode}</b>
<b>Explanation</b>	The Entire Net-Work semaphoring mechanism failed. The return code from the call is given in the message.
<b>Action</b>	Contact your Software AG technical support representative for assistance.

<b>WCP0402F</b>	<b>Unable to continue due to a severe error at startup</b>
<b>Explanation</b>	A previously logged error is preventing the startup of Entire Net-Work.
<b>Action</b>	Correct the previously reported error and restart Entire Net-Work.
<b>WCP0406F</b>	<b>Semaphore for TimerThread failed rc={rcode}</b>
<b>Explanation</b>	The Entire Net-Work timer threading mechanism failed. The return code is given in the message.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.
<b>WCP0407F</b>	<b>Thread create for TimerThread failed rc={rcode}</b>
<b>Explanation</b>	The Entire Net-Work threading mechanism failed. The return code is given in the message.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.
<b>WCP0408F</b>	<b>Semaphore for WorkSemaphore failed rc={rcode}</b>
<b>Explanation</b>	The Entire Net-Work threading mechanism failed. The return code is given in the message.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.
<b>WCP0409F</b>	<b>Thread create for thread {thread-number} failed rc={rcode}</b>
<b>Explanation</b>	The Entire Net-Work threading mechanism failed. The return code is given in the message.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.
<b>WCP0410F</b>	<b>Threading mechanism failed to start rc={rcode}</b>
<b>Explanation</b>	The Entire Net-Work threading mechanism failed. The return code is given in the message.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.

---

<b>WCP0411F</b>	<b>Semaphore for killer thread failed rc={rccode}</b>
<b>Explanation</b>	The Entire Net-Work killer threading mechanism failed. The return code is given in the message.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.
<b>WCP0412F</b>	<b>Thread create for killer thread failed rc={rccode}</b>
<b>Explanation</b>	The Entire Net-Work killer threading mechanism failed. The return code is given in the message.
<b>Action</b>	Repeated occurrences of this message may require a restart of the Entire Net-Work Kernel.
<b>WCP0413F</b>	<b>Killer thread has timed out shutdown. Task exiting</b>
<b>Explanation</b>	The Entire Net-Work killer thread ran to completion. The killer thread runs when normal shutdown has problems.
<b>Action</b>	No user action is required.
<b>WCP0414F</b>	<b>Remote Directory Server cannot be accessed</b>
<b>Explanation</b>	An attempt was made to use a remoteDirectory Server. The attempt failed.
<b>Action</b>	Determine why the remote Directory Server cannot be accessed, fix the problem, and try again.
<b>WCP0415F</b>	<b>CFG Directory Server cannot be accessed</b>
<b>Explanation</b>	A Directory Server problem occurred.
<b>Action</b>	Make sure no Directory Server or Entire Net-Work installation files were deleted and that your user ID has security access to use all files in the installation directories. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0416F</b>	<b>INI Directory Server cannot be accessed</b>
<b>Explanation</b>	A Directory Server problem occurred.
<b>Action</b>	Make sure no Directory Server or Entire Net-Work installation files were deleted and that your user ID has security access to use all files in the installation directories. If the problem persists, contact your Software AG support representative for assistance.

<b>WCP0501F</b>	<b>Licensing file for Entire Net-Work not found</b>
<b>Explanation</b>	The license file for Entire Net-Work was not found.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0502F</b>	<b>No Product Key found in Entire Net-Work Licensing file</b>
<b>Explanation</b>	The product key is missing from the license file.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0503F</b>	<b>License Key is invalid or has been tampered with</b>
<b>Explanation</b>	The license key in the license file is invalid.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0504F</b>	<b>Required parameter not found in licensing file</b>
<b>Explanation</b>	A required parameter is missing from the license file.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0505F</b>	<b>Required component not found in licensing file</b>
<b>Explanation</b>	A required component is missing from the license file.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0506F</b>	<b>All license parameters need to be set</b>
<b>Explanation</b>	All parameters of the license key require a value. The license key is not valid.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0507F</b>	<b>Tried to use the external version to create a license</b>
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0508F</b>	<b>Memory failure when checking the license</b>
<b>Explanation</b>	A memory failure occurred during product license processing.
<b>Action</b>	Contact your Software AG technical support representative for assistance.

---

<b>WCP0509F</b>	<b>License expired</b>
<b>Explanation</b>	The license key in the license file has expired.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0510F</b>	<b>License does not contain the correct OS</b>
<b>Explanation</b>	The operating system for which the license applies does not match the operating system of the machine on which you have attempted to deploy Entire Net-Work.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0511F</b>	<b>File read license error (fread)</b>
<b>Explanation</b>	The license file cannot be read.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0512F</b>	<b>Trial License Key file must not be write-protected</b>
<b>Explanation</b>	The trial license is write-protected.
<b>Action</b>	Remove the write protection from the trial license file.
<b>WCP0513F</b>	<b>ASCII-to-EBCDIC (or vice-versa) conversion error occurred</b>
<b>Explanation</b>	An internal ASCII-to-EBCDIC conversion error occurred while trying to process the license file.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0514F</b>	<b>UTF License Conversion Source Exhausted</b>
<b>Explanation</b>	An internal UTF conversion error occurred while trying to process the license file.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0515F</b>	<b>UTF License Conversion Target Exhausted</b>
<b>Explanation</b>	An internal UTF conversion error occurred while trying to process the license file.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0516F</b>	<b>File License write error (fwrite)</b>
<b>Explanation</b>	A write error occurred while trying to process the license file.
<b>Action</b>	Contact your Software AG technical support representative for assistance.

<b>WCP0517F</b>	<b>GetVersion() failed</b>
<b>Explanation</b>	An internal error occurred during license file processing.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0518F</b>	<b>File License read error (fseek)</b>
<b>Explanation</b>	An attempt to read the license file failed.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0519F</b>	<b># of physical CPUs present exceeded</b>
<b>Explanation</b>	The number of CPUs you are using exceeds the number allowed by the Entire Net-Work license.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0520F</b>	<b>determination of # of CPU failed</b>
<b>Explanation</b>	An attempt to identify the number CPUs during license processing failed.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0521F</b>	<b>iwmqvs() failed</b>
<b>Explanation</b>	An internal error occurred during license processing.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0522F</b>	<b>Tag CPU-ID not found</b>
<b>Explanation</b>	The CPU ID setting cannot be found in the license file.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0523F</b>	<b>Tag LPARName not found</b>
<b>Explanation</b>	The logical partition name cannot be found while processing the license file.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0524F</b>	<b>LPARName not allowed for MSU</b>
<b>Explanation</b>	An internal error occurred during license processing.
<b>Action</b>	Contact your Software AG technical support representative for assistance.

<b>WCP0525F</b>	<b>MSU value insufficient</b>
<b>Explanation</b>	The MSU value in the license file is insufficient.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0526F</b>	<b>Check MSU (warning)</b>
<b>Explanation</b>	The MSU value in the license needs to be checked.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0551F</b>	<b>Unable to retrieve current version registry value</b>
<b>Explanation</b>	An internal error occurred during license processing.
<b>Action</b>	If the error persists, reinstall Entire Net-Work correctly.
<b>WCP0552F</b>	<b>Unable to retrieve common files registry value</b>
<b>Explanation</b>	An internal error occurred during license processing.
<b>Action</b>	If the error persists, reinstall Entire Net-Work correctly.
<b>WCP0553F</b>	<b>Error in cleaning up registry access</b>
<b>Explanation</b>	An internal error occurred during license processing.
<b>Action</b>	If the error persists, reinstall Entire Net-Work correctly.
<b>WCP0554F</b>	<b>Unable to resolve the \$\$SAG environment value</b>
<b>Explanation</b>	UNIX systems only. The \$\$SAG environment variable must point to a standard Software AG product directory structure.
<b>Action</b>	Ensure \$\$SAG is set to the correct value.
<b>WCP0555F</b>	<b>This Kernel is not correctly licensed to run Entire Net-Work Server</b>
<b>Explanation</b>	The local Entire Net-Work configuration is not licensed to operate in this system. This error can be caused by illegally copying license files.
<b>Action</b>	Obtain a valid license file for Entire Net-Work and install it in the appropriate /Lkey directory.

<b>WCP0556E</b>	<b>The license does not provide the maximum number of clients allowed</b>
<b>Explanation</b>	The license is not valid; it does not provide the maximum number of clients allowed.
<b>Action</b>	Obtain a valid license file for Entire Net-Work and install it in the appropriate /Lkey directory.
<b>WCP0557E</b>	<b>The license does not specify if SSL is allowed</b>
<b>Explanation</b>	The license is not valid; it does not provide the maximum number of clients allowed.
<b>Action</b>	Obtain a valid license file for Entire Net-Work and install it in the appropriate /Lkey directory.
<b>WCP0558I</b>	<b>The system has virtualization present</b>
<b>Explanation</b>	The virtualization parameter PPAR is present for the system.
<b>Action</b>	No action is required for this informational message.
<b>WCP0559I</b>	<b>License set for Packages={pkg} PhysCPU={physcpuid} LogicalCPU={logcpuid}</b>
<b>Explanation</b>	The license has been established for the software package with the physical and logical CPU IDs listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0560F</b>	<b>The CPU count verification failed</b>
<b>Explanation</b>	The number of CPUs used does not match the number of CPUs allowed by the license.
<b>Action</b>	Resolve the difference in these counts. Entire Net-Work cannot be used until these numbers are resolved. For assistance, contact your Software AG technical support representative.
<b>WCP0561I</b>	<b>The license bucket value is {bucketval}</b>
<b>Explanation</b>	The core performance class value for this license (the license bucket value) is given in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0562I</b>	<b>The license bucket check failed</b>
<b>Explanation</b>	The core performance class value (the license bucket value) for this license is invalid.
<b>Action</b>	Determine why the core performance class of the license failed. For assistance, contact your Software AG technical support representative.

---

<b>WCP0563I</b>	<b>The CPU model is {modelnum}</b>
<b>Explanation</b>	The model number of the CPU is given in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0564W</b>	<b>The virtualization parameter PPAR not present</b>
<b>Explanation</b>	The virtualization parameter PPAR is not present for the system. An attempt to apply the license to a virtual machine failed.
<b>Action</b>	Verify that the license should support virtual machines. For assistance, contact your Software AG technical support representative.
<b>WCP0565F</b>	<b>The license CPU count check failed</b>
<b>Explanation</b>	The number of CPUs allowed by the license does not match the number of CPUs used.
<b>Action</b>	Resolve the difference in these counts. Entire Net-Work cannot be used until these numbers are resolved. For assistance, contact your Software AG technical support representative.
<b>WCP0601E</b>	<b>Internal error{errorcode}</b>
<b>Explanation</b>	An internal error occurred. The error code is given in the message.
<b>Action</b>	Analyze the error description to try to identify and resolve the problem. If the problem persists, contact your Software AG technical support representative for assistance.
<b>WCP0602E</b>	<b>Node is unreachable. It may not be active or there may be a configuration problem. Detailed error response was: {response}</b>
<b>Explanation</b>	An Entire Net-Work 7.2 node cannot be reached. The response from the connection attempt is given in the message.
<b>Action</b>	Verify that the node is started. If it is, analyze the installation of the Entire Net-Work 7.2 node to identify and resolve any configuration problem that may exist. If the problem persists, contact your Software AG technical support representative for assistance.
<b>WCP0603E</b>	<b>Kernel {kernel-id} already exists in the Directory Server</b>
<b>Explanation</b>	An attempt to add a Kernel to the System Management Hub (SMH) was made, but the Kernel already is added.
<b>Action</b>	No action is required for this informational message.

<b>WCP0604I</b>	<b>{definition} successfully added to SMH management; refreshing the tree...</b>
<b>Explanation</b>	The definition listed in the message was successfully added to SMH.
<b>Action</b>	No action is required for this informational message.
<b>WCP0605E</b>	<b>Kernel {kernel-id} not found in the Directory Server</b>
<b>Explanation</b>	The Kernel listed in the message was not found in the Adabas Directory Server.
<b>Action</b>	If you cannot identify and resolve the problem, contact your Software AG technical support representative for assistance.
<b>WCP0606I</b>	<b>{definition} successfully deleted from SMH management; refreshing the tree...</b>
<b>Explanation</b>	The definition listed in the message was successfully deleted from SMH.
<b>Action</b>	No action is required for this informational message.
<b>WCP0607E</b>	<b>No client entries found</b>
<b>Explanation</b>	No client configuration definitions were found to manage in the System Management Hub (SMH).
<b>Action</b>	Verify that the service for Entire Net-Work Client is started. Client configuration definitions cannot be reviewed in the System Management Hub (SMH) unless the client service is started. For more information, read <i>Starting and Stopping Entire Net-Work Client</i> , in the <i>Entire Net-Work Client Installation and Administration Guide</i> . If the problem persists, contact your Software AG technical support representative for assistance.
<b>WCP0608E</b>	<b>No server definitions found in the Directory Server</b>
<b>Explanation</b>	No Entire Net-Work Server definitions were found in the Adabas Directory Server, so no server machines can be listed in the System Management Hub (SMH).
<b>Action</b>	Verify that Entire Net-Work Server has been installed and that its service has been started. For more information on starting Entire Net-Work Server, read <i>Starting and Stopping Entire Net-Work Server</i> in your Entire Net-Work Server documentation.
<b>WCP0609E</b>	<b>Incompatible version of Net-Work</b>
<b>Explanation</b>	The version of Entire Net-Work you are trying to use is incompatible with the Entire Net-Work SMH agent.
<b>Action</b>	Contact your Software AG technical support representative for assistance.

---

<b>WCP0610I</b>	<b>Ping request returned in {number} milliseconds</b>
<b>Explanation</b>	The ping request was returned in the number of milliseconds listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0611I</b>	<b>No databases found on Kernel {kernel-id}</b>
<b>Explanation</b>	No databases were found on the Kernel listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0612E</b>	<b>Kernel is unreachable rc={rcode}</b>
<b>Explanation</b>	An error occurred during an attempt to communicate with a node. The return code is given in the message.
<b>Action</b>	Use the return code to determine what the problem is and resolve it. Then try again. If the problem persists, contact your Software AG technical support representative.
<b>WCP0613I</b>	<b>No adjacent Kernels found on Kernel={kernel-id}</b>
<b>Explanation</b>	No connection were made. Either the Kernel is down or there is a configuration error.
<b>Action</b>	No action is required for this informational message.
<b>WCP0614I</b>	<b>No clients found on Kernel={kernel-id}</b>
<b>Explanation</b>	No clients were found on the Kernel listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0615I</b>	<b>No hosts connected to Kernel={kernel-id} found</b>
<b>Explanation</b>	No hosts were found connected to the Kernel listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0616I</b>	<b>Shutdown initiated</b>
<b>Explanation</b>	Shutdown processing has been started.
<b>Action</b>	No action is required for this informational message.
<b>WCP0618E</b>	<b>Return code {rc} received</b>
<b>Explanation</b>	The return code listed in the message was received during Entire Net-Work processing.
<b>Action</b>	Analyze the return code to see if you can diagnose and resolve the problem. If the problem persists, contact your Software AG technical support representative.

<b>WCP0619E</b>	<b>Invalid context</b>
<b>Explanation</b>	An invalid context was encountered.
<b>Action</b>	Verify that all connections and the database in question are up and configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0620E</b>	<b>Invalid Client</b>
<b>Explanation</b>	An invalid client was encountered.
<b>Action</b>	Verify that all clients are configured correctly. If the problem persists, contact your Software AG support representative for assistance.
<b>WCP0621I</b>	<b>New log file started</b>
<b>Explanation</b>	A new log file has been started.
<b>Action</b>	No action is required for this informational message.
<b>WCP0622I</b>	<b>Trace level set</b>
<b>Explanation</b>	A new trace level has been set.
<b>Action</b>	No action is required for this informational message.
<b>WCP0623I</b>	<b>Stats level set</b>
<b>Explanation</b>	A new statistics level has been set.
<b>Action</b>	No action is required for this informational message.
<b>WCP0624I</b>	<b>Dump configuration initiated</b>
<b>Explanation</b>	A dump configuration has been initiated.
<b>Action</b>	No action is required for this informational message.
<b>WCP0625E</b>	<b>Invalid DBID</b>
<b>Explanation</b>	An invalid Adabas database ID has been specified.
<b>Action</b>	Specify a correct database ID.

<b>WCP0626E</b>	<b>Invalid Host</b>
<b>Explanation</b>	An invalid host was specified.
<b>Action</b>	Specify a valid host name.
<b>WCP0627E</b>	<b>Directory Server is unreachable. It may not be active or there may be a configuration problem. Detailed error response was: {error}</b>
<b>Explanation</b>	A problem occurred during an attempt to communicate with the Adabas Directory Server.
<b>Action</b>	Verify that the Adabas Directory Server is stated and try again. If the problem persists, contact your Software AG technical support representative.
<b>WCP0628I</b>	<b>Connect procedure has been initiated</b>
<b>Explanation</b>	A connection attempt was started.
<b>Action</b>	No action is required for this informational message.
<b>WCP0629I</b>	<b>Disconnect procedure has been initiated</b>
<b>Explanation</b>	A disconnection attempt was started.
<b>Action</b>	No action is required for this informational message.
<b>WCP0630I</b>	<b>Delete procedure successful</b>
<b>Explanation</b>	The deletion attempt was successful.
<b>Action</b>	No action is required for this informational message.
<b>WCP0631E</b>	<b>Invalid node</b>
<b>Explanation</b>	An attempt was made connect to an invalid node.
<b>Action</b>	Refresh your SMH screens. The node was probably deleted since you started your SMH session.
<b>WCP0632E</b>	<b>Kernel already connected</b>
<b>Explanation</b>	An attempt occurred to connect to a Kernel that is already connected.
<b>Action</b>	If you are having problems communicating with the Kernel and you are getting this error, contact your Software AG technical support representative for assistance.

<b>WCP0633E</b>	<b>Kernel already disconnected</b>
<b>Explanation</b>	An attempt was made to disconnect a Kernel that is already disconnected.
<b>Action</b>	No action is required.
<b>WCP0634E</b>	<b>Unknown return code {rcode} received</b>
<b>Explanation</b>	An unknown return code was received. The return code is given in the message.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0635E</b>	<b>XTS library cannot be loaded</b>
<b>Explanation</b>	The Software AG Transport Subsystem library could not be loaded.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0636E</b>	<b>Kernel already allocated</b>
<b>Explanation</b>	An attempt was made to allocate a Kernel that was already allocated.
<b>Action</b>	Try specifying a different Kernel name for the Kernel you are allocating. If the problem persists, contact your Software AG technical support representative.
<b>WCP0637E</b>	<b>Invalid request</b>
<b>Explanation</b>	An invalid request was attempted.
<b>Action</b>	If you cannot identify and resolve the problem, contact your Software AG technical support representative for assistance.
<b>WCP0638E</b>	<b>Failure to create file</b>
<b>Explanation</b>	An attempt to create a file was unsuccessful.
<b>Action</b>	If you cannot identify and resolve the problem, contact your Software AG technical support representative for assistance.
<b>WCP0639E</b>	<b>Unknown command code {cmd-code} received</b>
<b>Explanation</b>	An unknown command request was received. The command code is given in the message.
<b>Action</b>	If you cannot identify and resolve the problem, contact your Software AG technical support representative for assistance.

---

<b>WCP0640I</b>	<b>Kernel {name} configuration successful</b>
<b>Explanation</b>	The Kernel definition configuration attempt was successful. The Kernel definition name is given in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0641I</b>	<b>Client {name} configuration successful</b>
<b>Explanation</b>	The client configuration attempt was successful. The client configuration name is given in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0642I</b>	<b>Migrating {kernel-id} Kernel successful</b>
<b>Explanation</b>	An attempt to migrate a Kernel definition from an older version of Entire Net-Work to a newer version was successful. The name of the Kernel is given in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCPO643I</b>	<b>Kernel {kernel-id} migrated from WCP73</b>
<b>Explanation</b>	The Kernel listed in the message has been migrated from a previous version of Entire Net-Work.
<b>Action</b>	No action is required for this informational message.
<b>WCP0644E</b>	<b>Invalid entry</b>
<b>Explanation</b>	An invalid entry was specified.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0645I</b>	<b>Modification procedure successful</b>
<b>Explanation</b>	The modification was successful.
<b>Action</b>	No action is required for this informational message.
<b>WCP0646E</b>	<b>Invalid data</b>
<b>Explanation</b>	Invalid data was specified.
<b>Action</b>	Correct the data and try again. If the problem persists, contact your Software AG technical support representative.

<b>WCP0647I</b>	<b>Client {name} deletion successful</b>
<b>Explanation</b>	The attempt to delete the client configuration was successful.
<b>Action</b>	No action is required for this informational message.
<b>WCP0648I</b>	<b>Kernel {name} deletion successful</b>
<b>Explanation</b>	The attempt to delete the Kernel definition was successful.
<b>Action</b>	No action is required for this informational message.
<b>WCP0649I</b>	<b>Kernel {name} is active, deletion failed</b>
<b>Explanation</b>	An attempt to delete a Kernel definition was made, but the Kernel is running.
<b>Action</b>	Stop the Kernel before attempting to delete it.
<b>WCP0650I</b>	<b>Kernel {name} is active, starting not initiated</b>
<b>Explanation</b>	An attempt to start a Kernel was made, but the Kernel is already running.
<b>Action</b>	No action is required for this informational message.
<b>WCP0651I</b>	<b>Startup initiated for Kernel {name}</b>
<b>Explanation</b>	The Kernel is starting.
<b>Action</b>	No action is required for this informational message.
<b>WCP0652I</b>	<b>Unable to start this Kernel</b>
<b>Explanation</b>	The Kernel cannot be started for some reason.
<b>Action</b>	Examine the Kernel log file for reasons for the failure, make appropriate corrections, and try again. If the error persists, contact your Software AG technical support representative for assistance.
<b>WCP0653I</b>	<b>Set parameters successful</b>
<b>Explanation</b>	The parameter changes were successfully processed.
<b>Action</b>	No action is required for this informational message.
<b>WCP0654I</b>	<b>No Kernels available</b>
<b>Explanation</b>	No Kernel definitions have been defined, so none are available.
<b>Action</b>	Define some Kernel definitions.

---

<b>WCPO655I</b>	<b>Client {client-id} migrated from WCL13</b>
<b>Explanation</b>	The client listed in the message has been migrated from a previous version of Entire Net-Work.
<b>Action</b>	No action is required for this informational message.
<b>WCP0656E</b>	<b>Kernel={name} cannot have more than 8 characters</b>
<b>Explanation</b>	The name of a Kernel definition cannot exceed eight characters. An attempt was made to specify a name longer than eight characters and the name specified is given in the message.
<b>Action</b>	Reduce the length of the name of the Kernel definition.
<b>WCP0657E</b>	<b>XTS function cannot be loaded.</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0658E</b>	<b>A valid (non-zero) port has to be specified</b>
<b>Explanation</b>	The port number was not specified or is invalid.
<b>Action</b>	Specify a valid port number. For more information, read <i>Port Number Reference</i> , in the <i>Entire Net-Work Client Installation and Administration Guide</i> .
<b>WCP0659E</b>	<b>A valid (non-zero) host has to be specified</b>
<b>Explanation</b>	A host name was not specified or is invalid.
<b>Action</b>	Specify a valid host name.
<b>WCP0660E</b>	<b>Data segment unknown={data}</b>
<b>Explanation</b>	Data received by the SMH agents is not recognized.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0661E</b>	<b>SSL Connection not allowed</b>
<b>Explanation</b>	An SSL connection was attempted but is not allowed.
<b>Action</b>	If the problem persists, contact your Software AG support representative for assistance.

<b>WCP0670E</b>	<b>No URL available yet in the Directory Server for the target server</b>
<b>Explanation</b>	An internal error occurred in a Directory Server definition.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0671E</b>	<b>Entire Net-Work Kernel={kernel-id} has to be unique across the network</b>
<b>Explanation</b>	The name of an Entire Net-Work Kernel must be unique across the network. A name that has already been used was specified.
<b>Action</b>	Change the Kernel name so it is unique.
<b>WCP0672E</b>	<b>Default client cannot be deleted</b>
<b>Explanation</b>	You cannot delete the default client configuration that is distributed with Entire Net-Work Client.
<b>Action</b>	No action is required.
<b>WCP0673E</b>	<b>DBID syntax error; follow this rule : n1 or n1,n2 or n1-n2, or n1,n2,n2,n4-n5</b>
<b>Explanation</b>	The list of databases was not specified correctly. The syntax for a list of databases is given in the message.
<b>Action</b>	Correct the list of databases.
<b>WCP0674E</b>	<b>Trace syntax error; follow this rule : nnnnn or 0xn</b>
<b>Explanation</b>	The trace information was not specified correctly. The correct syntax for trace information is given in the message.
<b>Action</b>	Correct the trace information.
<b>WCP0675E</b>	<b>UNSOLICITED values are YES or NO</b>
<b>Explanation</b>	An invalid value for the UNSOLICITED parameter was specified. Valid values are "YES" or "NO".
<b>Action</b>	Specify a valid value for the parameter.
<b>WCP0676E</b>	<b>Adabas timeout cannot be less than 5 seconds</b>
<b>Explanation</b>	An invalid value was specified for the ADABAS_TIMEOUT parameter. The value cannot be less than 5 seconds.
<b>Action</b>	Specify a valid value for the parameter.

---

<b>WCP0677I</b>	<b>Command sent to Kernel {kernel-id}</b>
<b>Explanation</b>	The command was sent to the Kernel listed in the message.
<b>Action</b>	No action is required for this informational message.
<b>WCP0678E</b>	<b>The timer timeout has to be between 1 and 3600 seconds</b>
<b>Explanation</b>	An invalid value was specified for the TIMER_TIMEOUT parameter. The value must be between 1 and 3600 seconds.
<b>Action</b>	Specify a valid value for the parameter.
<b>WCP0679E</b>	<b>The statistics logging period has to be between 1 and 1440 minutes</b>
<b>Explanation</b>	An invalid value was specified for the STATISTICS_INTERVAL parameter. The value must be between 1 and 1440 minutes.
<b>Action</b>	Specify a valid value for the parameter.
<b>WCP0680E</b>	<b>The log size value has to be between 1MB and 500MB</b>
<b>Explanation</b>	An invalid value was specified for the LOGSIZE parameter. The value must be between 1 and 500 megabytes.
<b>Action</b>	Specify a valid value for the parameter.
<b>WCP0681E</b>	<b>The remote check period has to be between 1 and 1440 minutes</b>
<b>Explanation</b>	An invalid value was specified for the PING_DB_INTERVAL parameter. The value must be between 1 and 1440 minutes.
<b>Action</b>	Specify a valid value for the parameter.
<b>WCP0682E</b>	<b>The local check period has to be between 5 and 600 seconds</b>
<b>Explanation</b>	An invalid value was specified for the CHECK_DBS_INTERVAL parameter. The value must be between 5 and 600 seconds.
<b>Action</b>	Specify a valid value for the parameter.
<b>WCP0683E</b>	<b>Port={port} value has to be between 0 and 65535</b>
<b>Explanation</b>	An invalid port number was specified.
<b>Action</b>	Specify a valid port number. For more information, read <i>Port Number Reference</i> , in the <i>Entire Net-Work Client Installation and Administration Guide</i> .

- WCP0684E**            **Kernel ID value has to be between 1 and 65535**  
**Explanation**        An invalid value was specified for the Kernel ID. The value must be between 1 and 65535.  
**Action**                Specify a valid Kernel ID.
- WCP0685E**            **Client name={name} cannot have more than 16 characters**  
**Explanation**        An invalid client configuration name was specified. The client configuration name cannot exceed 16 characters.  
**Action**                Specify a valid client configuration name.
- WCP0686E**            **Relay values are YES or NO**  
**Explanation**        An invalid value was specified for the RELAY\_VALUES parameter. Valid values are "YES" or "NO".  
**Action**                Specify a valid value for the parameter.
- WCP0687E**            **Port={port} value has to be between 1 and 65535**  
**Explanation**        An invalid port number was specified. Valid values must lie between "1" and "65535".  
**Action**                Correct the port number and try again.
- WCP0689E**            **Port={port} string is not numerical**  
**Explanation**        An invalid port number was specified.  
**Action**                Specify a valid port number. For more information, read *Port Number Reference*, in the *Entire Net-Work Client Installation and Administration Guide*.
- WCP0690E**            **Numerical values required for parameter={parameter-name}**  
**Explanation**        A non-numeric value was specified for a parameter when a numeric value is expected. The parameter name is given in the message.  
**Action**                Specify a valid value for the parameter.
- WCP0691E**            **AUTOSTART/AUTOSTOP values are YES or NO**  
**Explanation**        An invalid value was specified for the AUTOSTART or AUTOSTOP parameters. Valid values are "YES" or "NO".  
**Action**                Specify a valid value for the parameter.

---

<b>WCP0692E</b>	<b>No Kernel definition found in Directory Server</b>
<b>Explanation</b>	No Kernel definitions were found to manage in the Adabas Directory Server and, consequently, in the System Management Hub (SMH).
<b>Action</b>	Verify that the service for Entire Net-Work Server is started. Kernel definitions cannot be reviewed in the System Management Hub (SMH) unless the server service is started. For more information, read <i>Starting and Stopping Entire Net-Work Server</i> in your Entire Net-Work Server documentation. If the problem persists, contact your Software AG technical support representative for assistance.
<b>WCP0693E</b>	<b>No Net-Work 7.X.X found in Directory Server</b>
<b>Explanation</b>	No Entire Net-Work 7.2 node definitions were found to manage in the Adabas Directory Server and, consequently, in the System Management Hub (SMH).
<b>Action</b>	If you have any Entire Net-Work 7.2 nodes to be managed, you must first add them in SMH.
<b>WCP0694E</b>	<b>The DBID has to be between 1 and 65535</b>
<b>Explanation</b>	An invalid Adabas database ID was specified. Valid database IDs are between 1 and 65535.
<b>Action</b>	Specify a valid database ID.
<b>WCP0695E</b>	<b>Kernel={name} should not include the # . [ ] = \ * characters</b>
<b>Explanation</b>	The name of a Kernel definition was specified with one of the special characters listed in the message. These characters cannot be used in a Kernel definition name.
<b>Action</b>	Specify a valid Kernel definition name.
<b>WCP0696E</b>	<b>Client name should not include the # . [ ] = \ * characters</b>
<b>Explanation</b>	The name of a client configuration was specified with one of the special characters listed in the message. These characters cannot be used in a client configuration name.
<b>Action</b>	Specify a valid client configuration name.
<b>WCP0697E</b>	<b>The WCP72 Kernel does not appear to be local</b>
<b>Explanation</b>	The Entire Net-Work 7.2 node cannot be found and does not appear to be installed on the local machine.
<b>Action</b>	Correct the Entire Net-Work 7.2 node definition in SMH to point to the correct host machine.

<b>WCP0698E</b>	<b>Duplication</b>
<b>Explanation</b>	An attempt to add a definition that has already been added. The definition you tried to add is not added.
<b>Action</b>	No action is required for this informational message.
<b>WCP0699E</b>	<b>Kernel file does not exist (it could be deleted)</b>
<b>Explanation</b>	An attempt occurred to delete a Kernel failed; it is possible that it was already deleted.
<b>Action</b>	No action is required for this informational message.
<b>WCP0700E</b>	<b>No Kernel entries found</b>
<b>Explanation</b>	No Kernel definitions were found to manage in the System Management Hub (SMH).
<b>Action</b>	Verify that the service for Entire Net-Work Server is started. Kernel definitions cannot be reviewed in the System Management Hub (SMH) unless the server service is started. For more information, read <i>Starting and Stopping Entire Net-Work Server</i> in your Entire Net-Work Server documentation. If the problem persists, contact your Software AG technical support representative for assistance.
<b>WCP0701E</b>	<b>No Server entries found</b>
<b>Explanation</b>	No Entire Net-Work Server entries were found to manage in the System Management Hub (SMH).
<b>Action</b>	Verify that the service for Entire Net-Work Server is started. Server definitions cannot be reviewed in the System Management Hub (SMH) unless the server service is started. For more information, read <i>Starting and Stopping Entire Net-Work Server</i> in your Entire Net-Work Server documentation. If the problem persists, contact your Software AG technical support representative for assistance.
<b>WCP0702E</b>	<b>Kernel={kernel-id} name cannot be numeric only</b>
<b>Explanation</b>	The Kernel name cannot contain only numeric values.
<b>Action</b>	Specify a valid Kernel name.
<b>WCP0703E</b>	<b>Client name={client-id} cannot be numeric only</b>
<b>Explanation</b>	The client name cannot contain only numeric values.
<b>Action</b>	Specify a valid client name.

---

<b>WCP0704E</b>	<b>No such entry in the Directory Server, please refresh!</b>
<b>Explanation</b>	An attempt to reference an entry in the Directory Server failed.
<b>Action</b>	Refresh your SMH display to obtain the latest Directory Server entries.
<b>WCP0705E</b>	<b>Port value has to be between 1 and 65535</b>
<b>Explanation</b>	An invalid port number was specified.
<b>Action</b>	Specify a valid port number. For more information, read <i>Port Number Reference</i> , in the <i>Entire Net-Work Client Installation and Administration Guide</i> .
<b>WCP0706E</b>	<b>Retry string not numerical</b>
<b>Explanation</b>	The retry count specification was not numeric.
<b>Action</b>	Specify a numeric retry count.
<b>WCP0707E</b>	<b>Retry interval string not numerical</b>
<b>Explanation</b>	The retry interval specification was not numeric.
<b>Action</b>	Specify a numeric retry interval.
<b>WCP0708E</b>	<b>Host name={name} should not include the # [ ] = \ * characters</b>
<b>Explanation</b>	The host name was specified with one of the special characters listed in the message. These characters cannot be used in a host name.
<b>Action</b>	Specify a valid host name.
<b>WCP0709I</b>	<b>No additional parameters supplied</b>
<b>Explanation</b>	No additional parameters were supplied for the Entire Net-Work Client configuration.
<b>Action</b>	No action is required for this informational message.
<b>WCP0710E</b>	<b>Port={port} value has to be between 1 and 65535</b>
<b>Explanation</b>	An invalid port number was specified.
<b>Action</b>	Specify a valid port number. For more information, read <i>Port Number Reference</i> , in the <i>Entire Net-Work Client Installation and Administration Guide</i> .

<b>WCP0711E</b>	<b>Port2={port2} has to be greater than Port1={port1}</b>
<b>Explanation</b>	When specifying a range of port numbers, the second port number should be larger than the first port number in the range. The port numbers specified are given in the message.
<b>Action</b>	Specify a valid range of port numbers.
<b>WCP0713E</b>	<b>DBID={dbid} string is not numerical</b>
<b>Explanation</b>	The Adabas database ID specified was not numeric.
<b>Action</b>	Specify a numeric database ID.
<b>WCP0714E</b>	<b>DBID2={dbid2} has to be greater than DBID1={dbid1}</b>
<b>Explanation</b>	When specifying a range of Adabas database IDs, the second database ID should be larger than the first database ID in the range. The database IDs specified are given in the message.
<b>Action</b>	Specify a valid range of database IDs.
<b>WCP0715E</b>	<b>Empty string</b>
<b>Explanation</b>	A blank string was specified for a parameter.
<b>Action</b>	Specify a valid value for the parameter.
<b>WCP0716E</b>	<b>At least one access definition has to be selected</b>
<b>Explanation</b>	An attempt to add an access definition was made but no access type was selected (for example, Classic, e-business Client, e-business SSL Client, etc.).
<b>Action</b>	Select an access type when adding an access definition.
<b>WCP0717I</b>	<b>No listens found on Kernel ={kernel-id}</b>
<b>Explanation</b>	No active access entries were found for the active Kernel.
<b>Action</b>	No action is required for this informational message.
<b>WCP0718I</b>	<b>No connections found on Kernel={kernel-id}</b>
<b>Explanation</b>	No active connection entries were found for the active Kernel.
<b>Action</b>	No action is required for this informational message.

---

<b>WCP0719E</b>	<b>REMEMBER_DBID values are YES or NO</b>
<b>Explanation</b>	An invalid value was specified for the REMEMBER_DBID parameter. Valid values are "YES" or "NO".
<b>Action</b>	Specify a valid value for the parameter.
<b>WCP0720E</b>	<b>The number active clients value has to be between 5 and 65535</b>
<b>Explanation</b>	An invalid value was specified for the MAX_CLIENTS parameter. Valid values must be between 5 and 65535.
<b>Action</b>	Specify a valid value for the parameter.
<b>WCP0721E</b>	<b>Timeout error; check if the Server or Kernel is down</b>
<b>Explanation</b>	A system timeout error occurred.
<b>Action</b>	Verify that the Entire Net-Work Server or Kernel is not down. If it is, restart it. If the problem persists, contact your Software AG technical support representative.
<b>WCP0722E</b>	<b>DBID={dbid} not defined</b>
<b>Explanation</b>	An Adabas database ID was not specified or an invalid one was specified.
<b>Action</b>	Specify a valid database ID.
<b>WCP0723E</b>	<b>DBID={dbid} not active</b>
<b>Explanation</b>	The Adabas database is not active.
<b>Action</b>	Start the database.
<b>WCP0724E</b>	<b>Kernel={kernel-id} not defined</b>
<b>Explanation</b>	An attempt was made to ping a Kernel, but the Kernel does not exist.
<b>Action</b>	Refresh your System Management Hub displays. The node may have been deleted since you started this SMH session.
<b>WCP0725E</b>	<b>Kernel={kernel-id} not active</b>
<b>Explanation</b>	An attempt was made to ping a Kernel, but the Kernel was not active.
<b>Action</b>	Start the node if you wish.

<b>WCP0726E</b>	<b>No entry available</b>
<b>Explanation</b>	An attempt was made to review an entry that is no longer available.
<b>Action</b>	Refresh your System Management Hub displays. The entry may have been deleted since you started this SMH session.
<b>WCP0727E</b>	<b>Empty Kernel name</b>
<b>Explanation</b>	No Kernel definition name was specified.
<b>Action</b>	Specify a valid Kernel definition name.
<b>WCP0728E</b>	<b>Empty client name</b>
<b>Explanation</b>	No client configuration name was specified.
<b>Action</b>	Specify a valid client configuration name.
<b>WCP0729E</b>	<b>Empty host name</b>
<b>Explanation</b>	No host name was specified.
<b>Action</b>	Specify a valid host name.
<b>WCP0730E</b>	<b>Empty DBID string</b>
<b>Explanation</b>	No Adabas database ID was specified.
<b>Action</b>	Specify at least one database ID.
<b>WCP0731E</b>	<b>Empty port string</b>
<b>Explanation</b>	No port number was specified.
<b>Action</b>	Specify a valid port number. For more information, read <i>Port Number Reference</i> , in the <i>Entire Net-Work Client Installation and Administration Guide</i> .
<b>WCP0732E</b>	<b>No client definitions found in the Directory Server</b>
<b>Explanation</b>	No client configuration definitions were found in the Adabas Directory Server.
<b>Action</b>	Verify that the service for Entire Net-Work Client is started. Client configuration definitions cannot be reviewed in the System Management Hub (SMH) unless the client service is started. For more information, read <i>Starting and Stopping Entire Net-Work Client</i> , in the <i>Entire Net-Work Client Installation and Administration Guide</i> . If the problem persists, contact your Software AG technical support representative for assistance.

<b>WCP0733E</b>	<b>Connection URL syntax error</b>
<b>Explanation</b>	A syntax error exists in a connection URL. Entire Net-Work cannot make the connection.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0734E</b>	<b>Connection with the same NODENAME already defined</b>
<b>Explanation</b>	An attempt was made to define a connection to the same node twice. Only one connection definition is needed.
<b>Action</b>	Make sure that there is only one connection definition for the node.
<b>WCP0735E</b>	<b>Host Name={hostname} not defined in DNS</b>
<b>Explanation</b>	The host identified in the message is not defined in the DNS.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0736E</b>	<b>Host Name={hostname} not defined in DNS</b>
<b>Explanation</b>	The host identified in the message is not defined in the DNS.
<b>Action</b>	Contact your Software AG technical support representative for assistance.
<b>WCP0738E</b>	<b>Target is down or not defined in the Directory Server</b>
<b>Explanation</b>	A connection attempt was made to a target that is not correctly defined to Entire Net-Work.
<b>Action</b>	Verify that the target definition is correct and complete (no required parameters are undefined) and try again. If the error persists, contact you Software AG technical support representative for assistance.
<b>WCP0739E</b>	<b>Incoming Kernel already connected</b>
<b>Explanation</b>	An attempt was made to define two connections for the same incoming Kernel. Only one connection definition is needed.
<b>Action</b>	Make sure that only one connection definition exists for the incoming Kernel. If the problem persists, contact your Software AG technical support representative for assistance.

<b>WCP0740E</b>	<b>Connection failure; reason={rsncode}</b>
<b>Explanation</b>	An attempt to make a defined connection failed. The reason code is given in the message.
<b>Action</b>	Analyze the reason code and try to resolve the problem. If the problem persists, contact your Software AG technical support representative for assistance.
<b>WCP0741E</b>	<b>The GATEWAY_THREADS value has to be between 5 and 1024</b>
<b>Explanation</b>	The value of the GATEWAY_THREADS Kernel parameter is not correct. It must be a numeric value between 5 and 1024.
<b>Action</b>	Correct the value and try again.
<b>WCP0742E</b>	<b>No data available</b>
<b>Explanation</b>	The Kernel log file cannot be found.
<b>Action</b>	Contact your Software AG technical support representative.
<b>WCP0743E</b>	<b>MULTIPLEX values are YES or NO</b>
<b>Explanation</b>	An invalid value was specified for the MULTIPLEX parameter. Valid values are "YES" or "NO".
<b>Action</b>	Correct the value and try again.
<b>WCP0744E</b>	<b>NOLOCAL values are YES or NO</b>
<b>Explanation</b>	An invalid value was specified for the NOLOCAL parameter. Valid values are "YES" or "NO".
<b>Action</b>	Correct the value and try again.
<b>WCP0745E</b>	<b>NOREMOTE values are YES or NO</b>
<b>Explanation</b>	An invalid value was specified for the NOREMOTE parameter. Valid values are "YES" or "NO".
<b>Action</b>	Correct the value and try again.
<b>WCP0746E</b>	<b>LOAD_BALANCIING values are YES or NO</b>
<b>Explanation</b>	An invalid value was specified for the LOAD_BALANCING parameter. Valid values are "YES" or "NO".
<b>Action</b>	Correct the value and try again.

---

<b>WCP0747E</b>	<b>The maximum CPU threshold has to be between 10 and 99</b>
<b>Explanation</b>	An invalid value has been specified for the MAX_CPU_THRESHOLD parameter.
<b>Action</b>	Correct the value and try again.
<b>WCP0749E</b>	<b>STATISTICS_DETAILS values are YES or NO</b>
<b>Explanation</b>	An invalid value was specified for the STATISTICS_DETAILS parameter. Valid values are "YES" or "NO".
<b>Action</b>	Correct the value and try again.
<b>WCP0750E</b>	<b>USE_LOCAL_ADABASES values are YES or NO</b>
<b>Explanation</b>	An invalid value was specified for the USE_LOCAL_ADABASES parameter. Valid values are "YES" or "NO".
<b>Action</b>	Correct the value and try again.
<b>WCP0751E</b>	<b>Kernel={kernel-id} is not set to process local databases</b>
<b>Explanation</b>	The Kernel listed in the message is not defined to process local databases.
<b>Action</b>	Correct the USE_LOCAL_ADABASES parameter value in the Kernel definition and try again.
<b>WCP0752E</b>	<b>DATE_STAMP values are YES or NO</b>
<b>Explanation</b>	An invalid value was specified for the DATE_STAMP parameter. Valid values are "YES" or "NO".
<b>Action</b>	Correct the value and try again.
<b>WCP0753E</b>	<b>The CHECK_CXT_INTERVAL value has to be 0 or between 60 and 24*60*60 seconds</b>
<b>Explanation</b>	An invalid value was specified for the CHECK_CXT_INTERVAL parameter. Valid values are zero (0) seconds or lie between 60 seconds and 86,400 seconds (24 * 60 * 60).
<b>Action</b>	Correct the value and try again.
<b>WCP0754I</b>	<b>Kernel is migrated from WCP74</b>
<b>Explanation</b>	The kernel listed in the message was successfully migrated from the 7.4 version of Entire Net-Work.
<b>Action</b>	No action is required for this informational message.

<b>WCP0755I</b>	<b>Client is migrated from WCL14</b>
<b>Explanation</b>	The client listed in the message was successfully migrated from the 1.4 version of Entire Net-Work Client.
<b>Action</b>	No action is required for this informational message.
<b>WCP0756E</b>	<b>DBID={dbid} not accessible</b>
<b>Explanation</b>	The database listed in the message could not be accessed.
<b>Action</b>	No action is required for this informational message.

# 4 XTS\* - Software AG Internal Transport Subsystem Messages

---

- Warnings ..... 232
- Errors ..... 234
- Generic TCP/IP Messages ..... 248

The Software AG internal transport subsystem Messages and Codes documentation provides information for each warning and error message that you can encounter using the internal transport subsystem of Software AG products.

This documentation is organized as follows:

<i>Warnings</i>	Provides the message ID, message text, and a brief explanation for each warning message.
<i>Errors</i>	Provides the message ID, message text, and a brief explanation for each error message.
<i>Generic TCP/IP Messages</i>	Lists the message ID and message text for each generic TCP/IP error. For complete information on the TCP/IP error conditions, refer to your TCP/IP documentation.



**Note:** The internal component API returns warnings as positive values and errors as negative values.

## Warnings

---

<b>XTS0000W</b>	<b>XTS Success</b>
<b>Explanation</b>	The transport subsystem processing completed successfully.
<b>XTS0001W</b>	<b>XTS No LISTEN has been issued</b>
<b>Explanation</b>	A server has only XTSconnect entries and no XTSlisten. It is possible for a server to connect only to a proxy, and the warning helps applications determine if XTSlisten is missing.
<b>XTS0003W</b>	<b>XTS Load message file failed</b>
<b>Explanation</b>	The transport subsystem failed to load the <i>XTS.MSG</i> file. This file contains text for the error messages; there is an internal table also, so <i>XTS.MSG</i> is not mandatory.
<b>XTS0004W</b>	<b>XTS Client already registered</b>
<b>Explanation</b>	Multiple <code>XtsBindClient</code> calls occurred for the same client. Only the first call is considered.

<b>XTS0005W</b>	<b>XTS More data</b>
<b>Explanation</b>	The receive buffer defined by a transport subsystem send and wait call is not big enough to get all data received by the transport subsystem. A subsequent call has to be made to receive all data.
<b>XTS0006W</b>	<b>XTS No SSL random file warning</b>
<b>Explanation</b>	There is no random file defined for a transport subsystem/Secure Sockets Layer (SSL) application; a random file usage by SSL is highly recommended.
<b>XTS0007W</b>	<b>XTS Notify connect</b>
<b>Explanation</b>	This is a receive callback notification for an incoming connection.
<b>XTS0008W</b>	<b>XTS Notify disconnect</b>
<b>Explanation</b>	This is a receive callback notification for a disconnection.
<b>XTS0009W</b>	<b>XTS Notify broadcast</b>
<b>Explanation</b>	This is a receive callback notification for a broadcast attempt.
<b>XTS0010W</b>	<b>XTS Notify unsupported</b>
<b>Explanation</b>	This is a receive callback notification when protocols set by XTSlisten are not supported.
<b>XTS0011W</b>	<b>XTS Notify message reference dead</b>
<b>Explanation</b>	This is a receive callback notification indicating the active message references are deleted when a client disconnects.
<b>XTS0012W</b>	<b>XTS Notify outbound connect</b>
<b>Explanation</b>	This is a receive callback notification for an outbound connection.
<b>XTS0013W</b>	<b>XTS Notify listen failure</b>
<b>Explanation</b>	This is a notification to the callback routine submitted by XtsRegisterByTargetName or XtsRegisterByTargetId indicating a failure of an XTSlisten URL.

**XTS0014W**            **XTS Notify connect failure**  
**Explanation**        This is a notification to the callback routine submitted by `XtsRegisterByTargetName` or `XtsRegisterByTargetId` indicating a failure of an XTSconnect URL.

**XTS0015W**            **XTS Notify end broadcast**  
**Explanation**        This is a notification to the callback routine submitted by `XtsRegisterByTargetName` or `XtsRegisterByTargetId` indicating an end broadcast message was received from another node.

## Errors

---

**XTS0050E**            **XTS Semaphore Error**  
**Explanation**        A failure to create a semaphore occurred. Contact Software AG customer support.

**XTS0051E**            **XTS Memory Allocation Error**  
**Explanation**        A failure to allocate memory occurred. Contact Software AG customer support.

**XTS0052E**            **XTS Server already registered**  
**Explanation**        The transport subsystem server is already registered.

**XTS0053E**            **XTS Incorrect URL**  
**Explanation**        A URL with a syntax error was encountered. Check the Directory Server repositories.

**XTS0054E**            **XTS Failure Loading Protocol Handler**  
**Explanation**        A failure to load protocol handlers (for example, `Xtstcp.lib`) occurred. It was probably caused by a configuration problem. Contact Software AG customer support.

**XTS0055E**            **XTS Protocol Init failed**  
**Explanation**        A protocol initialization failure occurred. Contact Software AG customer support.

<b>XTS0056E</b>	<b>XTS Invalid protocol type</b>
<b>Explanation</b>	The specified protocol is not supported by the transport subsystem. This is possibly and error in URL syntax.
<b>XTS0057E</b>	<b>XTS Listen Failed</b>
<b>Explanation</b>	A listen failed. Check the log file for protocol-specific errors. This is caused mostly by trying to listen on a port taken by another server.
<b>XTS0058E</b>	<b>XTS Accept Failed</b>
<b>Explanation</b>	The accept failed. Check the log file for protocol-specific errors.
<b>XTS0059E</b>	<b>XTS Connect Failed</b>
<b>Explanation</b>	The connect failed. Check the log file for protocol-specific errors.
<b>XTS0060E</b>	<b>XTS No directory information</b>
<b>Explanation</b>	No XTSaccess information is provided for the server to which the application wants to connect. Please add a target definition through the Directory Server.
<b>XTS0061E</b>	<b>XTS Failure to create a thread</b>
<b>Explanation</b>	A failure to create a thread occurred. Contact Software AG customer support
<b>XTS0062E</b>	<b>XTS Timeout error</b>
<b>Explanation</b>	A failure to connect or send data in the time set by the user occurred. To complete the connect or send, repeat the call or increase the timeout value.
<b>XTS0063E</b>	<b>XTS Send Failed</b>
<b>Explanation</b>	A completion code is returned to the send callback routine when send fails. Check the log file for the protocol-specific error code.
<b>XTS0064E</b>	<b>XTS Invalid reference</b>
<b>Explanation</b>	An invalid message reference was passed by the user.

<b>XTS0065E</b>	<b>XTS Send incomplete</b>
<b>Explanation</b>	A send was interrupted by a client disconnection.
<b>XTS0066E</b>	<b>XTS No such server</b>
<b>Explanation</b>	A nonexistent server name was passed by the user. It applies to the transport subsystem statistics and dumps calls.
<b>XTS0069E</b>	<b>XTS Resolve Target failed</b>
<b>Explanation</b>	The client failed to send a handshake message to the server; Error caused by the server going down or a protocol send error.
<b>XTS0070E</b>	<b>XTS Resolve Target Reply failed</b>
<b>Explanation</b>	The server failed to reply to the client during handshaking. This error is caused by the client going down or by a protocol send error.
<b>XTS0071E</b>	<b>XTS Target cannot be resolved</b>
<b>Explanation</b>	The client failed to resolve the target name. This error is caused by different names used by the server and the client but with the same address.
<b>XTS0072E</b>	<b>XTS Not initialized</b>
<b>Explanation</b>	The transport subsystem call was submitted before the transport subsystem was initialized. Errors were returned by XtsShutdown, XtsSendMessageByRT, and the transport subsystem statistics call.
<b>XTS0073E</b>	<b>XTS Bind Client failed</b>
<b>Explanation</b>	The client bind failed because of a protocol send error or because the server went down.
<b>XTS0074E</b>	<b>XTS Too many user threads</b>
<b>Explanation</b>	The number of user threads in existence reached the maximum (64). Stop creating new user threads or reduce their time to live (timeout).

<b>XTS0075E</b>	<b>XTS Created thread failed</b>
<b>Explanation</b>	The transport subsystem failed to create a new user thread. This is an SMP error, possibly because of the limitations of the number of threads that a system can support. Contact Software AG customer support.
<b>XTS0077E</b>	<b>XTS Conversion failed</b>
<b>Explanation</b>	The conversion between wide character and MBNS failed. Contact Software AG customer support.
<b>XTS0078E</b>	<b>XTS No Target Name</b>
<b>Explanation</b>	The target name is a zero pointer. Pass a valid string.
<b>XTS0079E</b>	<b>XTS No Client Name</b>
<b>Explanation</b>	The client name is a zero pointer. Pass a valid string.
<b>XTS0082E</b>	<b>XTS Zero Length not accepted</b>
<b>Explanation</b>	The length of the data to be sent is zero, Make the length a positive number.
<b>XTS0083E</b>	<b>XTS Target ID Out of Range</b>
<b>Explanation</b>	The target ID value is bigger than "2113929215".
<b>XTS0084E</b>	<b>XTS Channel Inactive</b>
<b>Explanation</b>	The server-client connection was no longer active when XtsSendByRt or XtsBindClient were called. This error is generated by a client going down during the call.
<b>XTS0085E</b>	<b>XTS Disconnect message</b>
<b>Explanation</b>	A client or server disconnection was detected during a transport subsystem call.
<b>XTS0086E</b>	<b>XTS Hash table error</b>
<b>Explanation</b>	An internal transport subsystem hash table error occurred. Contact Software AG customer support.

<b>XTS0087E</b>	<b>XTS Thread key error</b>
<b>Explanation</b>	An allocate/delete thread memory failure occurred. Contact Software AG customer support.
<b>XTS0088E</b>	<b>XTS No CONNECT or LISTEN has been issued</b>
<b>Explanation</b>	A server registration failed to submit at least one listen or connect. Check the XTSlisten or XTSconnect URL parameters.
<b>XTS0089E</b>	<b>XTS Protocol not supported</b>
<b>Explanation</b>	An attempt was made to use XtsBindClient over the RAW or XTSDS protocol. This feature is not supported.
<b>XTS0090E</b>	<b>XTS Single Thread not supported</b>
<b>Explanation</b>	This error code is returned when the transport subsystem call does not support the single thread feature. Examples include XtsRegisterServerByName(ID) and XtsGiveThread.
<b>XTS0094E</b>	<b>XTS Zero pointer</b>
<b>Explanation</b>	A zero pointer was passed by the user. This is an invalid value.
<b>XTS0095E</b>	<b>XTS Hash table full</b>
<b>Explanation</b>	An internal transport subsystem hash table error occurred. Contact Software AG customer support.
<b>XTS0096E</b>	<b>XTS Send User Exit failed</b>
<b>Explanation</b>	The user exit send routine failed. Check the user exit code.
<b>XTS0097E</b>	<b>XTS Recv User Exit failed</b>
<b>Explanation</b>	The user exit receive routine failed. Check the user exit code.
<b>XTS0098E</b>	<b>XTS Load User Exit failed</b>
<b>Explanation</b>	The transport subsystem failed to load the user exit library. Check the environment or the user exit routine names.

<b>XTS0100E</b>	<b>XTS Shutdown in process</b>
<b>Explanation</b>	This error code is returned when the transport subsystem is in shutdown mode (because XtsShutdown was called by another thread).
<b>XTS0101E</b>	<b>XTS Route Timeout</b>
<b>Explanation</b>	The proxy cannot deliver the message because the route timeout was insufficient. Change the route timeout.
<b>XTS0102E</b>	<b>XTS Route Table overflow</b>
<b>Explanation</b>	The proxy cannot deliver the message because of a route table overflow. Repeat the transport subsystem call.
<b>XTS0103E</b>	<b>XTS Route TTL expired</b>
<b>Explanation</b>	The proxy cannot deliver the message because the route time to live was insufficient. Change the time to live time.
<b>XTS0104E</b>	<b>XTS Route failed</b>
<b>Explanation</b>	The proxy cannot deliver the message because of a route failure. Repeat the transport subsystem call.
<b>XTS0105E</b>	<b>XTS Null parameter</b>
<b>Explanation</b>	A null parameter is encountered when a notify callback routine registration is called.
<b>XTS0106E</b>	<b>XTS Connection Rejected</b>
<b>Explanation</b>	The connection was rejected by the notify callback routine.
<b>XTS0107E</b>	<b>XTS Replica redirected</b>
<b>Explanation</b>	The connection was redirected by the callback routine.
<b>XTS0108E</b>	<b>XTS timeout - connect in progress</b>
<b>Explanation</b>	A timeout error occurred, but connection is in progress. Submit the call again or increase the timeout value.

<b>XTS0109E</b>	<b>XTS invalid session</b>
<b>Explanation</b>	An invalid session handle was used by the transport subsystem session calls.
<b>XTS0110E</b>	<b>XTS invalid key</b>
<b>Explanation</b>	An invalid session handle was used by the transport subsystem session calls.
<b>XTS0111E</b>	<b>XTS Count converters failed</b>
<b>Explanation</b>	The count of available converter names failed.
<b>XTS0112E</b>	<b>XTS Convert enum failed</b>
<b>Explanation</b>	The enumeration of text converter names failed.
<b>XTS0113E</b>	<b>XTS Buffer too small</b>
<b>Explanation</b>	The text conversion buffer is not big enough..
<b>XTS0114E</b>	<b>XTS No more ports available</b>
<b>Explanation</b>	No replicated server ports are available .
<b>XTS0115E</b>	<b>XTS Text converter library load failed</b>
<b>Explanation</b>	The load of the transport subsystem converter ending failed.
<b>XTS0116E</b>	<b>XTS Text converter resolve failed</b>
<b>Explanation</b>	The text converter interface function could not be resolved.
<b>XTS0117E</b>	<b>XTS Name to EDDkey map failed</b>
<b>Explanation</b>	The ICU converter name to Software AG ECS EDD key conversion failed..
<b>XTS0118E</b>	<b>XTS XDS library loading failed</b>
<b>Explanation</b>	The XDS library used by ADVDIR could not be loaded.

<b>XTS0119E</b>	<b>XTS DS access time out error</b>
<b>Explanation</b>	A timeout occurred accessing the Directory Server (the default timeout is one minute).
<b>XTS0120E</b>	<b>XTS Failed to set ECS environment</b>
<b>Explanation</b>	A failure occurred when setting the ECS environment.
<b>XTS0121E</b>	<b>XTS Set UDP Port failed</b>
<b>Explanation</b>	The UDP port selected by user cannot be used (because it is used by another application).
<b>XTS0122E</b>	<b>XTS Sync and async send in raw mode not allowed</b>
<b>Explanation</b>	Using synchronous and asynchronous calls on the same channel is not allowed.
<b>XTS0123E</b>	<b>XTS Unknown received buffer</b>
<b>Explanation</b>	The transport subsystem received an unknown buffer from an application.
<b>XTS0124E</b>	<b>XTS Function retired</b>
<b>Explanation</b>	The transport subsystem function is not supported any longer.
<b>XTS0126E</b>	<b>XTS invalid duplicate server</b>
<b>Explanation</b>	This error is generated when the same server is registered again with a different protocol than the one used when it was first registered.
<b>XTS0127E</b>	<b>XTS Fatal error</b>
<b>Explanation</b>	An internal error occurred, indicating a severe transport subsystem code problem. Contact Software AG customer support.
<b>XTS0128E</b>	<b>XTS Load library failed</b>
<b>Explanation</b>	The transport subsystem failed to load a library (the log file indicates which one).

<b>XTS0129E</b>	<b>XTS Key not found</b>
<b>Explanation</b>	The key used to retrieve transport subsystem parameters does not exist.
<b>XTS0130E</b>	<b>XTS Xts.Config Key not found</b>
<b>Explanation</b>	The key used by the user to retrieve transport subsystem parameters from <i>xts.config</i> file does not exist.
<b>XTS0131E</b>	<b>XTS No directory information for XTS profile</b>
<b>Explanation</b>	The profile is not defined in the Directory Server.
<b>XTS0132E</b>	<b>XTS Load function failed</b>
<b>Explanation</b>	A failure occurred loading a function (the name of the function and the name of the library are in the log file).
<b>XTS0150E</b>	<b>XTS SSL init failed</b>
<b>Explanation</b>	The transport subsystem failed to initialize the Secure Sockets Layer (SSL) library. Check the log file for the SSL error messages.
<b>XTS0151E</b>	<b>XTS SSL Verify CA locations failed</b>
<b>Explanation</b>	The Secure Sockets Layer (SSL) failed to load the CA certificates. Probable causes include an invalid path specification or nonexistent CA certificates.
<b>XTS0152E</b>	<b>XTS SSL Certificate file not specified</b>
<b>Explanation</b>	No Secure Sockets Layer (SSL) certificate was specified.
<b>XTS0153E</b>	<b>XTS SSL Invalid Certificate</b>
<b>Explanation</b>	The URL-specified Secure Sockets Layer (SSL) certificate has an invalid format.
<b>XTS0154E</b>	<b>XTS SSL Invalid Key File</b>
<b>Explanation</b>	The URL-specified Secure Sockets Layer (SSL) key file has an invalid format.

<b>XTS0155E</b>	<b>XTS SSL Invalid Key</b>
<b>Explanation</b>	The Secure Sockets Layer (SSL) key specified by the user is invalid.
<b>XTS0156E</b>	<b>XTS SSL Connect failed</b>
<b>Explanation</b>	A Secure Sockets Layer (SSL) connect failed (caused by an SSL handshaking error). Check the log file for the Secure Sockets Layer (SSL) error messages.
<b>XTS0157E</b>	<b>XTS SSL Accept failed</b>
<b>Explanation</b>	A Secure Sockets Layer (SSL) accept failed (caused by an SSL handshaking error). Check the log file for the SSL error messages.
<b>XTS0158E</b>	<b>XTS SSL Read failed</b>
<b>Explanation</b>	A Secure Sockets Layer (SSL) read failed. Check the log file for the SSL error messages.
<b>XTS0159E</b>	<b>XTS SSL Write failed</b>
<b>Explanation</b>	A Secure Sockets Layer (SSL) write failed. Check the log file for the SSL error messages.
<b>XTS0163E</b>	<b>XTS SSL Failed loading library</b>
<b>Explanation</b>	A failure to load the Secure Sockets Layer (SSL) library occurred. Check the environment.
<b>XTS0167E</b>	<b>XTS SSL Illegal host name</b>
<b>Explanation</b>	The peer certificate subject name and host name are different, indicating an illegal connection.
<b>XTS0168E</b>	<b>XTS SSL No local certificate</b>
<b>Explanation</b>	There is no local Secure Sockets Layer (SSL) certificate.
<b>XTS0169E</b>	<b>XTS SSL No remote certificate</b>
<b>Explanation</b>	There is no local Secure Sockets Layer (SSL) certificate.

<b>XTS0170E</b>	<b>XTS SSL insufficient user memory</b>
<b>Explanation</b>	There is insufficient user memory for returning the requested data.
<b>XTS0171E</b>	<b>XTS SSL certificate rejected</b>
<b>Explanation</b>	The certificate was rejected during verification.
<b>XTS0172E</b>	<b>XTS SSL zero length message return</b>
<b>Explanation</b>	The Secure Sockets Layer (SSL) write or read routines returned an invalid zero value. Contact Software AG customer support.
<b>XTS0173E</b>	<b>XTS SSL want read error</b>
<b>Explanation</b>	The Secure Sockets Layer (SSL) write routine returned want read error code. Contact Software AG customer support. This is a transport subsystem internal sequence error.
<b>XTS0174E</b>	<b>XTS SSL want write error</b>
<b>Explanation</b>	The Secure Sockets Layer (SSL) read routine returned want write error code. Contact Software AG customer support. This is a transport subsystem internal sequence error.
<b>XTS0200E</b>	<b>DS Open File failed</b>
<b>Explanation</b>	A failure to open a file occurred. Check if the file exists and that the path is correct.
<b>XTS0201E</b>	<b>DS Incomplete Entry</b>
<b>Explanation</b>	A URL syntax error occurred. Check the log file for detailed information.
<b>XTS0203E</b>	<b>DS Service not provided</b>
<b>Explanation</b>	An invalid Directory Service selection was made.
<b>XTS0204E</b>	<b>DS Null parameter</b>
<b>Explanation</b>	A Directory Service call was encountered with a null parameter.

<b>XTS0205E</b>	<b>DS Incomplete Entry</b>
<b>Explanation</b>	An attempt to add an incomplete URL record was made.
<b>XTS0206E</b>	<b>DS Topic Not Defined</b>
<b>Explanation</b>	The user tried to use a qualifier unknown to the Directory Server.
<b>XTS0207E</b>	<b>DS Unknown request</b>
<b>Explanation</b>	An unknown XTSDS request was encountered. Check the syntax of the Directory Server call.
<b>XTS0208E</b>	<b>DS No Entries</b>
<b>Explanation</b>	The Directory Server or configuration file contains no entries for the specified target.
<b>XTS0209E</b>	<b>DS Delete Failed</b>
<b>Explanation</b>	A Directory Service delete call failed. Check the log file for detailed information.
<b>XTS0210E</b>	<b>DS Connection Failed</b>
<b>Explanation</b>	Connection to the Directory Server failed.
<b>XTS0211E</b>	<b>DS Bind Failed</b>
<b>Explanation</b>	Deprecated message.
<b>XTS0212E</b>	<b>DS Search Failed</b>
<b>Explanation</b>	Retrieve URL command failed.
<b>XTS0213E</b>	<b>DS Add Failed</b>
<b>Explanation</b>	Addition of a new URL failed.
<b>XTS0214E</b>	<b>DS Already Exists</b>
<b>Explanation</b>	An attempt was made to add a record that already exists.

<b>XTS0215E</b>	<b>DS Failure Loading Service Handler</b>
<b>Explanation</b>	A failure occurred loading a directory service. Check the environment. Contact Software AG customer support.
<b>XTS0216E</b>	<b>DS Wrong directory parameter</b>
<b>Explanation</b>	Unknown directory parameter.
<b>XTS0217E</b>	<b>DS not Initialized</b>
<b>Explanation</b>	Directory Server was not initialized before usage.
<b>XTS0218E</b>	<b>DS Invalid target Name</b>
<b>Explanation</b>	The target name contains one of the following characters: "#", ".", "[", "]", "=", "\", "\", or "*". The target name is invalid.
<b>XTS0219E</b>	<b>DS Incomplete request</b>
<b>Explanation</b>	An incomplete XTSDS request was caused by a zero value of the target, qualifier, or user data.
<b>XTS0220E</b>	<b>DS No URL entries</b>
<b>Explanation</b>	The XTSDS server does not have any URL to return for the retrieve call.
<b>XTS0221E</b>	<b>DS XDS error</b>
<b>Explanation</b>	An XDS processing error occurred..
<b>XTS0222E</b>	<b>DS Rollback is not implemented</b>
<b>Explanation</b>	No Directory Service rollback was performed..
<b>XTS0223E</b>	<b>DS OVO error</b>
<b>Explanation</b>	An OVO error occurred during Directory Service processing.

<b>XTS0224E</b>	<b>DS One time set violation</b>
<b>Explanation</b>	A one-time setting function was called multiple times. A programs encoding mode cannot change once it is set.
<b>XTS0225E</b>	<b>DS Encoding conflict</b>
<b>Explanation</b>	The INIDIR file encoding conflicts with programs encoding.
<b>XTS0226E</b>	<b>DS Create file failed</b>
<b>Explanation</b>	The file creation failed during Directory Service processing..
<b>XTS0227E</b>	<b>DS IO file failed</b>
<b>Explanation</b>	A file I/O error occurred during Directory Service processing.
<b>XTS0228E</b>	<b>DS Wrong file format`</b>
<b>Explanation</b>	The INIDIR file format was not recognized.
<b>XTS0229E</b>	<b>DS Send buffer bigger than maximum allowed</b>
<b>Explanation</b>	An internal transport subsystem error occurred, generated when a URL is added or deleted from the Directory Server and its size exceeds 65520 bytes.
<b>XTS0230E</b>	<b>DS Invalid Service</b>
<b>Explanation</b>	Invalid type of service used.
<b>XTS0231E</b>	<b>DS Invalid Header</b>
<b>Explanation</b>	Invalid Directory Service header used for communication.
<b>XTS1000E</b>	<b>XTS Unknown error = {code}</b>
<b>Explanation</b>	This message is returned by XtsGetMessage when it cannot find text for a given error code.

## Generic TCP/IP Messages

---

<b>XTS1001E</b>	<b>TCP/IP Operation not permitted</b>
<b>XTS1002E</b>	<b>TCP/IP No such file or directory</b>
<b>XTS1003E</b>	<b>TCP/IP No such process</b>
<b>XTS1004E</b>	<b>TCP/IP Interrupted function call</b>
<b>XTS1005E</b>	<b>TCP/IP I/O error</b>
<b>XTS1006E</b>	<b>TCP/IP No such device or address</b>
<b>XTS1007E</b>	<b>TCP/IP Arg list too long</b>
<b>XTS1008E</b>	<b>TCP/IP Exec format error</b>
<b>XTS1009E</b>	<b>TCP/IP Bad file number</b>
<b>XTS1010E</b>	<b>TCP/IP No children</b>
<b>XTS1011E</b>	<b>TCP/IP Operation would cause deadlock</b>
<b>XTS1012E</b>	<b>TCP/IP Not enough core</b>
<b>XTS1013E</b>	<b>TCP/IP Permission denied</b>

XTS1014E	TCP/IP Bad address
XTS1015E	TCP/IP Block device required
XTS1016E	TCP/IP Mount device busy
XTS1017E	TCP/IP File exists
XTS1018E	TCP/IP Cross-device link
XTS1019E	TCP/IP No such device
XTS1020E	TCP/IP Not a directory
XTS1021E	TCP/IP Is a directory
XTS1022E	TCP/IP Invalid argument
XTS1023E	TCP/IP File table overflow
XTS1024E	TCP/IP Too many open sockets
XTS1025E	TCP/IP Inappropriate ioctl for device
XTS1026E	TCP/IP Text file busy
XTS1027E	TCP/IP File too large

XTS1028E	TCP/IP No space left on device
XTS1029E	TCP/IP Illegal seek
XTS1030E	TCP/IP Read-only file system
XTS1031E	TCP/IP Too many links
XTS1032E	TCP/IP Broken pipe
XTS1033E	TCP/IP Argument too large
XTS1034E	TCP/IP Result too large
XTS1035E	TCP/IP Resource temporarily unavailable
XTS1036E	TCP/IP Operation now in progress
XTS1037E	TCP/IP Operation already in progress
XTS1038E	TCP/IP Socket operation on non-socket
XTS1039E	TCP/IP Destination address required
XTS1040E	TCP/IP Message too long
XTS1041E	TCP/IP Protocol wrong type for socket

XTS1042E	TCP/IP Bad protocol option
XTS1043E	TCP/IP Protocol not supported
XTS1044E	TCP/IP Socket type not supported
XTS1045E	TCP/IP Operation not supported
XTS1046E	TCP/IP Protocol Family not supported
XTS1047E	TCP/IP Address family not supported by protocol family
XTS1048E	TCP/IP Address already in use
XTS1049E	TCP/IP Cannot assign requested address
XTS1050E	TCP/IP Network is down
XTS1051E	TCP/IP Network is unreachable
XTS1052E	TCP/IP Network dropped connection on reset
XTS1053E	TCP/IP Software caused connection abort
XTS1054E	TCP/IP Connection reset by peer
XTS1055E	TCP/IP No buffer space available

XTS1056E	TCP/IP Socket is already connected
XTS1057E	TCP/IP Socket is not connected
XTS1058E	TCP/IP Cannot send after socket shutdown
XTS1059E	TCP/IP Too many references
XTS1060E	TCP/IP Connection timed out
XTS1061E	TCP/IP Connection refused
XTS1062E	TCP/IP Too many levels of symbolic links
XTS1063E	TCP/IP File name too long
XTS1064E	TCP/IP Host is down
XTS1065E	TCP/IP No route to host
XTS1066E	TCP/IP Directory not empty
XTS1067E	TCP/IP Too many processes
XTS1068E	TCP/IP Too many users
XTS1069E	TCP/IP Disc quota exceeded

XTS1070E	TCP/IP Stale NFS file handle
XTS1071E	TCP/IP Too many levels of remote in path
XTS1072E	TCP/IP Device not ready
XTS1073E	TCP/IP Write-protected media
XTS1074E	TCP/IP Unformatted media
XTS1075E	TCP/IP No connection
XTS1076E	TCP/IP Old, currently unused AIX errno
XTS1077E	TCP/IP Restart the system call
XTS1078E	TCP/IP Invalid file system control data
XTS1079E	TCP/IP Media surface error
XTS1080E	TCP/IP I/O completed, but needs relocation
XTS1081E	TCP/IP No attribute found
XTS1082E	TCP/IP Out of STREAM resources
XTS1083E	TCP/IP System call timed out

XTS1084E	TCP/IP Next message has wrong type
XTS1085E	TCP/IP Protocol error
XTS1086E	TCP/IP No message on stream read queue
XTS1087E	TCP/IP fd not associated with a stream
XTS1088E	TCP/IP Security authentication denied
XTS1089E	TCP/IP Not a trusted program
XTS1090E	TCP/IP Illegal byte sequence
XTS1091E	TCP/IP Network subsystem is unavailable
XTS1092E	TCP/IP WINSOCK.DLL version out of range
XTS1093E	TCP/IP Successful WSAStartup not yet performed
XTS1094E	TCP/IP Cross mount point (not really error)
XTS1095E	TCP/IP cannot start operation
XTS1096E	TCP/IP Cannot access a needed shared library
XTS1097E	TCP/IP operation (now) in progress

XTS1098E	TCP/IP Lib section in a.out corrupted
XTS1099E	TCP/IP Attempting to link in too many shared libraries
XTS1100E	TCP/IP Cannot exec a shared library directly
XTS1101E	TCP/IP Graceful shutdown in progress
XTS1102E	TCP/IP Streams pipe error
XTS1103E	TCP/IP Structure needs cleaning
XTS1104E	TCP/IP Not a XENIX named tip file
XTS1105E	TCP/IP No XENIX semaphores available
XTS1106E	TCP/IP Is a named type file
XTS1107E	TCP/IP Remote I/O error
XTS1108E	TCP/IP No medium found
XTS1109E	TCP/IP Wrong medium type
XTS1111E	TCP/IP Host not found
XTS1112E	TCP/IP Non-authoritative host not found

XTS1113E	TCP/IP This is a non-recoverable error
XTS1114E	TCP/IP Valid name, no data record of requested type
XTS1115E	TCP/IP Resource unavailable
XTS1116E	TCP/IP Operation canceled
XTS1118E	TCP/IP Disc quota exceeded
XTS1119E	TCP/IP Identifier removed
XTS1120E	TCP/IP Too many open files
XTS1122E	TCP/IP Multihop attempted
XTS1123E	TCP/IP No locks available
XTS1124E	TCP/IP The link has been severed
XTS1125E	TCP/IP No message of the desired type
XTS1126E	TCP/IP Function not supported
XTS1127E	TCP/IP Directory not empty
XTS1128E	TCP/IP Operation not supported

XTS1129E	TCP/IP Value too large to be stored in data
XTS1130E	TCP/IP Stale NFS file handle
XTS1131E	TCP/IP There is no more data available
XTS1132E	TCP/IP The call has been canceled
XTS1133E	TCP/IP Invalid procedure table from service provider
XTS1134E	TCP/IP Invalid service provider version number
XTS1135E	TCP/IP Unable to initialize a service provider
XTS1136E	TCP/IP System call failure
XTS1137E	TCP/IP Service not found
XTS1138E	TCP/IP Type not found
XTS1139E	TCP/IP There is no more data available
XTS1140E	TCP/IP The call has been canceled
XTS1141E	TCP/IP Refused
XTS1142E	TCP/IP Cbannel number out of range

XTS1143E	TCP/IP Level 2 not synchronized
XTS1144E	TCP/IP Level 3 halted
XTS1145E	TCP/IP Level 3 reset
XTS1146E	TCP/IP Link number out of range
XTS1147E	TCP/IP Protocol driver not attached
XTS1148E	TCP/IP No 43 CSI structure available
XTS1149E	TCP/IP Level 2 halted
XTS1150E	TCP/IP Invalid exchange
XTS1151E	TCP/IP Invalid request descriptor
XTS1152E	TCP/IP Exchange full
XTS1153E	TCP/IP No anode
XTS1154E	TCP/IP Invalid request code
XTS1155E	TCP/IP Invalid slot
XTS1156E	TCP/IP File locking deadlock error

XTS1157E	TCP/IP Bad fon file fmt
XTS1158E	TCP/IP Process died with the lock
XTS1159E	TCP/IP Lock is not recoverable
XTS1160E	TCP/IP Machine is not on the network
XTS1161E	TCP/IP Package not installed
XTS1162E	TCP/IP The object is remote
XTS1163E	TCP/IP Advertise error
XTS1164E	TCP/IP Mount error
XTS1165E	TCP/IP Communication error on send
XTS1166E	TCP/IP Locked lock was unmapped
XTS1167E	TCP/IP Name not unique on network
XTS1168E	TCP/IP FD invalid for this operation
XTS1169E	TCP/IP Remote address changed

