



ARIS

USER MANAGEMENT COMMAND-LINE TOOL

Version 10.0 - Service Release 4

April 2018

This document applies to ARIS Version 10.0 and to all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2010 - 2018 [Software AG](#), Darmstadt, Germany and/or [Software AG](#) USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name [Software AG](#) and all Software AG product names are either trademarks or registered trademarks of [Software AG](#) and/or [Software AG](#) USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products".

These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Contents

1	Legal notices.....	1
2	Text conventions	2
3	Command line tools for the ARIS Administration.....	3
3.1	Password encryption	4
3.2	Tenant Management	6
3.3	Parameters for y-tenantmgmt.bat/y-tenantmgmt.sh	7
3.4	LDAP synchronization	15
3.5	Data migration	18
4	Contacting support	20
5	Disclaimer	21

1 Legal notices

This manual describes the settings and features as they were at the time of print. Since manual and software are subject to different production cycles, the description of settings and features may differ from actual settings and features. Information about discrepancies is provided in the Readme file that accompanies the product. Please read this file and take the information into account when installing, setting up, and using the product.

If you want to install all technical and/or business system functions without the services of Software AG, you require extensive knowledge of the system to be installed, its intended purpose, the target systems, and their various dependencies. Due to the number of platforms and interdependent hardware and software configurations, we can only describe specific installations. It is not possible to document all settings and dependencies.

When you combine various technologies, please observe the manufacturers' instructions, particularly announcements concerning releases on their Internet pages. We cannot guarantee proper functioning and installation of approved third-party systems and do not support them. Always follow the instructions provided in the installation manuals of the relevant manufacturers. If you experience difficulties, please contact the relevant manufacturer.

If you need help installing third-party systems, contact your local Software AG sales organization. Please note that this type of manufacturer-specific or customer-specific customizing is not subject to the standard Software AG software maintenance agreement and can be performed only on special request and agreement.

If a description refers to a specific ARIS product, the product is named. If this is not the case, names for ARIS products are used as follows:

Name	Includes
ARIS products	Refers to all products to which the license regulations of Software AG standard software apply.
ARIS Clients	Refers to all programs, for example, ARIS Architect or ARIS Designer that access shared databases via ARIS Server.
ARIS Download clients	Refers to ARIS clients that can be started from a browser.

2 Text conventions

Menu items, file names, etc. are indicated in texts as follows:

- Menu items, key combinations, dialogs, file names, entries, etc. are displayed in **bold**.
- User-defined entries are shown **<in bold and in angle brackets>**.
- Single-line example texts (for example, a long directory path that covers several lines due to a lack of space) are separated by ↵ at the end of the line.
- File extracts are shown in this font format:
This paragraph contains a file extract.
- Warnings have a colored background:

Warning

This paragraph contains a warning.

3 Command line tools for the ARIS Administration

ARIS provides a set of command-line tools that can be used to perform administrative operations.

There are always at least two tenants, the tenant **default** and the tenant **master**. Most command-line operations require user authentication. The provided user must have sufficient permissions to perform the requested operation, for example, a tenant create, read, update or delete can only be performed by administrators of tenant **master**.

- ARIS must be running.
- The command-line tools must be executed in the following path:
ARIS installation path > /server/bin/work/word_umcadmin_< your installation size, for example, s,m, or l > **/tools/bin** for Windows® operating systems
and
/home/ARIS/cloudagent/bin/work/word_umcadmin_< your installation size, for example, s,m, or l > **/tools/bin** for Linux operating systems.

The following command line tools are provided:

- y-datadump.bat
- y-elasticsearch.bat
- y-ldapsync.bat
- y-password.bat
- y-tenantmgmt.bat

For more information about parameters and commands please type the tool name without parameters or commands.

For Unix operating systems please use the following:

- y-datadump.sh
- y-elasticsearch.sh
- y-ldapsync.sh
- y-password.sh
- y-tenantmgmt.sh

3.1 Password encryption

There are many places where you might want to use and store a password. The **y-password.bat** can be used to encrypt these passwords. Run it without argument to see the usage instructions.

Procedure

Open a command prompt on the above folder (**Start > Run > cmd**).

1. Enter **y-password.bat <option> <password>**
2. Mark and copy the encrypted password and paste it to your configuration file or use it directly from command line.

The following is output:

```
[CLI] Setting verbosity level... [VALUE: 0=OFF]
[CLI] Plain:      <password>
[CLI] Encrypted:  f4a28327ad2f0c87336dd74fe0a70c39
```

General usage

Options	Description
-?, -h, --help	Show help Default: false

Commands	Description
encrypt	encrypts the password

Example

Input

```
y-password.bat encrypt aris
```

Output

```
[CLI] Setting verbosity level... [VALUE: 0=OFF]
```

```
[CLI] Plain:      aris
```

```
[CLI] Encrypted:  f4a28327ad2f0c87336dd74fe0a70c39
```

Usage of an encrypted password from command line

This example shows how to use the encrypted password while executing the LDAP synchronization from the command line.

Input

```
y-ldapsync.bat syncUser -au <user_name> -u system -p  
{crypte}f4a28327ad2f0c87336dd74fe0a70c39
```

Output

```
Connected to User Management at end point 'http://servername:1080/umc' for tenant 'default'.  
Synchronizing user 'system' with LDAP...  
Synchronization of user with LDAP is complete.
```


3.2 Tenant Management

The batch file **y-tenantmgmt.bat** can be used to manage tenants. Run it without argument to see the usage instructions.

You do not need to stop the Process Governance runnable to back up or restore Process Governance data. To avoid inconsistencies, you cannot back up or restore Process Governance data while a process is still running. During a backup or restore, Process Governance is not accessible to avoid inconsistencies.

Using some advanced ACC commands, you can create a tenant, import a license and restore a database in one step. If you do not use the standard database system, please make sure to create additional schemes in your Oracle or Microsoft SQL database management system and you have assigned the tenants to these schemes.

You have to redirect the ports in case of a Linux operating system.

Prerequisites

- ARIS Server installation
Users need the function privileges **License administrator, User administrator, Technical configuration administrator**.
- ARIS Design Server Installation
Users need to login as **superuser** or they need either an **ARIS Architect** license or an **ARIS UML Designer** license. For LOCAL systems they need to login as system user **system**.

Procedure

1. Open a command prompt (**Start > Run > cmd**).
2. Enter **y-tenantmgmt.bat** without parameters to display the help.
Enter **y-tenantmgmt.bat -t <tenant name> <command> -u <user name> -p <password>** to enter a command (page 7). Parameters may differ.

After creating a tenant, you must import the relevant license and create the users. You can do so from the command line or using the graphical user interface ARIS Administration.

You are recommended to change the password of the default user **system** immediately after the installation.

3.3 Parameters for y-tenantmgmt.bat/y-tenantmgmt.sh

General usage

Options	Description
-?, -h, --help	Show help, default: false
-s, --server	URL of the server, for example, http://my_host_url: <port number other than default port 80 or 1080>

Commands	Description	Parameters
anonymize	Anonymizes the audit log files.	<p>Please note that you must wait at least 30 minutes after the deletion of the user from User Management before you can start the anonymizing process.</p> <p>* -n, --name Name of the user or user group</p> <p>-p, --password Password of editor, default: superuser</p> <p>* -type, --type UUID type is user or user group</p> <p>-u, --user User name of editor, default: superuser</p>
assignLicense	Assigns a license to user.	<p>-ag, --affectedGroup Name of affected user group, default: []</p> <p>-au, --affectedUser User name of affected user, default: []</p> <p>* -l, --license Product code, default: []</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>

Commands	Description	Parameters
assignPrivilege	Assigns privileges	<p>-ag, --affectedGroup Name of affected user group, default: []</p> <p>-au, --affectedUser User name of affected user, default: []</p> <p>-p, --password Password of editor, default: superuser</p> <p>* -pr, --privilege Privilege, default: []</p> <p>-u, --user User name of editor, default: superuser</p>
assignUser	Associates a user to a user group.	<p>* -ag, --affectedGroup Name of affected user group</p> <p>* -au, --affectedUser User name of affected user</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>
changePassword	Changes a password.	<p>* -ap, --affectedPassword Password of affected user</p> <p>* -au, --affectedUser User name of affected user</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>
checkLicense	Checks tenant license.	<p>* -l, --license Product code, default: []</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>

Commands	Description	Parameters
createGroup	Creates a user group.	<p>-ad, --affectedDescription Description of affected user group</p> <p>* -ag, --affectedGroup Name of affected user group</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>
createTenant	Creates a new tenant.	<p>-u, --user User name of editor, default: superuser</p> <p>-p, --password Password of editor, default: superuser</p> <p>-t, --tenant <TENANTNAME> (mandatory) For tenant names please only use up to 25 lowercase ASCII characters and numbers. The name must begin with a character. Special characters and characters, for example, in Chinese, Cyrillic or Arabic cannot be used.</p> <p>--arisservicePassword (-arisservicep) <PASSWORD> --superuserPassword (-superuserp) <PASSWORD> --systemPassword (-systemp) <PASSWORD></p>
createUser	Creates a new user.	<p>-ad, --affectedDescription Description of affected user</p> <p>-ae, --affectedEmail E-mail address of affected user</p> <p>-af, --affectedFirstName First name of affected user</p> <p>-al, --affectedLastName Last name of affected user</p> <p>-ap, --affectedPassword Password of affected user</p> <p>* -au, --affectedUser User name of affected user</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>

Commands	Description	Parameters
deleteGroup	Deletes a user group.	<p>* -ag, --affectedGroup Name of affected user group</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>
deleteLicense	Deletes the licenses for a product.	<p>* -l, --license Product code</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>
deleteTenant	Deletes an existing tenant.	<p>* -au, --affectedUser User name of affected user</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>
deleteUser	Deletes an existing user.	<p>--user (-u) <USERNAME> (mandatory)</p> <p>--password (-p) <PASSWORD> (mandatory)</p> <p>--tenant (-t) <TENANTNAME> (mandatory)</p> <p>--affectedUser (-au) <USERLOGIN> (mandatory)</p>
exportConfig	Exports configuration of tenant.	<p>-f, --file Configuration file, default: umc.properties</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>
getTenant	Prints information about a tenant.	<p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>

Commands	Description	Parameters
getUser	Prints information about a user.	* -au, --affectedUser User name of affected user -p, --password Password of editor, default: superuser -u, --user User name of editor, default: superuser
importConfig	Updates configuration of tenant.	-f, --file Configuration file, default: umc.properties -p, --password Password of editor, default: superuser -u, --user User name of editor, default: superuser
importConfigFile	Updates the tenant configuration file.	-f, --file Configuration file -o, --option Configuration option -p, --password Password of editor, default: superuser -u, --user User name of editor, default: superuser
importLicense	Imports license files for a tenant	-f, --file License file, default: license.zip -p, --password Password of editor, default: superuser -u, --user User name of editor, default: superuser
listPrivileges	Lists the privileges of the user mentioned in the command	-au, --affectedUser User name of affected user -p, --password Password of editor, default: superuser -u, --user User name of editor, default: superuser

Commands	Description	Parameters
listTenants	Lists all existing tenants.	-p, --password Password of editor, default: superuser -u, --user User name of editor, default: superuser
purgeAuditLogByUser	Deletes all audit logs of a deleted user.	* -ed, --endDate End date in format (yyyy-MM-dd HH:mm:ss) -p, --password Password of editor, default: superuser -sd, --startDate Start date in format (yyyy-MM-dd HH:mm:ss) u, --user User name of editor, default: superuser
unassignLicense	Removes a license from user.	-ag, --affectedGroup Name of affected user group -au, --affectedUser User name of affected user * -l, --license Product code -p, --password Password of editor, default: superuser -u, --user User name of editor, default: superuser
unassignPrivilege	Removes the privilege assignment.	-ag, --affectedGroup Name of affected user group -au, --affectedUser User name of affected user -p, --password Password of editor, default: superuser * -pr, --privilege Privilege -u, --user User name of editor, default: superuser

Commands	Description	Parameters
unassignUser	Remove a user from a user group.	<p>* -ag, --affectedGroup Name of affected user group</p> <p>* -au, --affectedUser User name of affected user</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>
updateLicense	Replaces the license file for a tenant.	<p>-f, --file License file, default: license.zip</p> <p>* -l, --license Product code, default: []</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>
updateUser	Updates an existing user.	<p>-ad, --affectedDescription Description of affected user</p> <p>-ae, --affectedEmail E-mail address of affected user</p> <p>-af, --affectedFirstName First name of affected user</p> <p>-al, --affectedLastName Last name of affected user</p> <p>* -au, --affectedUser User name of affected user</p> <p>-p, --password Password of editor, default: superuser</p> <p>-u, --user User name of editor, default: superuser</p>

Examples

The following line creates a tenant with name **test**. Please pay attention to the order of parameters.

```
y-tenantmgmt.bat -s http://my_aris_host.com -t test createTenant -u system -p manager
```

The following line creates a new tenant with name **test01**, port used 81, and initial system user password **abc**. Please pay attention to the order of parameters.

```
y-tenantmgmt.bat -s http://my_aris_host.com:81 -t test01 createTenant -u system -p manager -systemp abc
```

The following line gets information of the default tenant.

```
y-tenantmgmt.bat -s http://my_aris_host.com -t default getTenant -u system -p manager
```

The following line updates the configuration of default tenant.

```
y-tenantmgmt.bat -s http://my_aris_host.com -t default importConfig -f sldapconfig.properties -u superuser -p superuser
```

The following line assigns a license configuration to the user **my_user**.

```
y-tenantmgmt.bat -s http://my_aris_host.com -t default -assignLicense au my_user -l YCZUS -u system -p manager
```

3.4 LDAP synchronization

The batch file **y-ldapsync.bat** can be used to synchronize the ARIS Administration with LDAP. Run it without argument to see the usage instructions.

You have to redirect the ports in case of a Linux operating system.

Procedure

1. Open a command prompt (**Start > Run > cmd**).
2. Enter **y-ldapsync.bat -s <http://host_url:<port number other than default port 80 or 1080>> -t <tenant name> <command> -u <user name> -p <password>**

Users are synchronized or imported from an LDAP system.

General usage

Options	Description
-?, -h, --help	Show help
-u	User name of the relevant user.
-p	Password of the relevant user.
-f	LDAP search filter
-s, --server	URL of the server, for example, http://my_host_url: <port number other than default port 80 or 1080>
-t, --tenant	Tenant name Default: default

Commands	Description
importUsers	<p>Imports users from an LDAP system, the spelling is case sensitive.</p> <p>* -f, --filter</p> <p>Search filter for LDAP as defined in RFC 2254, for example, '(cn=*)'. The filter will be combined with the configured import filters.</p> <p>-p, --password</p> <p>Password of the editor</p> <p>Default: superuser</p> <p>-u, --user</p> <p>User name of the editor</p> <p>Default: superuser</p>
importGroups	<p>Imports a hierarchy from an LDAP system, the spelling is case sensitive.</p> <p>* -f, --filter</p> <p>Search filter for LDAP as defined in RFC 2254, for example, '(cn=*)'. The filter will be combined with the configured import filters.</p> <p>-p, --password</p> <p>Password of the editor</p> <p>Default: superuser</p> <p>-u, --user</p> <p>User name of the editor</p> <p>Default: superuser</p>
syncUser	<p>Synchronizes a specific existing user with an LDAP system, the spelling is case sensitive.</p>
syncUsers	<p>Synchronizes existing users with an LDAP system, the spelling is case sensitive.</p> <p>* -au, --affectedUser</p> <p>User name of affected user</p> <p>-p, --password</p> <p>Password of the editor</p> <p>Default: superuser</p> <p>-u, --user</p> <p>User name of the editor</p> <p>Default: superuser</p>

Commands	Description
syncGroup	<p>Synchronizes a specific existing group with an LDAP system, the spelling is case sensitive.</p> <p>* -ag, --affectedGroup Name of the affected user group</p> <p>-p, --password Password of the editor Default: superuser</p> <p>-u, --user User name of the editor Default: superuser</p>
syncGroups	<p>Synchronizes existing groups with an LDAP system, the spelling is case sensitive.</p> <p>-p, --password Password of the editor Default: superuser</p> <p>-u, --user User name of the editor Default: superuser</p>

Example 1

y-ldapsync.bat -s http://my_aris_host.com -t default importUsers -u system -p manager -f (cn=userID)

[CLI] Setting verbosity level... [VALUE: 0=OFF]

[CLI] Importing users... [TENANT: 30ff3081-aa9e-33e7-a7d7-5f9d00ae89ee, FILTER: (cn=userID)]

[CLI] Users successfully imported. [TENANT: 30ff3081-aa9e-33e7-a7d7-5f9d00ae89ee, COUNT: 1]

[CLI] CN=myuser,OU=Users,DC=mydomain

Example 2

Import all users from an LDAP system.

y-ldapsync.bat -s http://my_aris_host.com:81 -t default importUsers -u system -p manager -f (cn=*)

3.5 Data migration

Run it without arguments to see usage instructions. In case of a data import, the target database has to be empty. Run it without argument to see the usage instructions.

You have to redirect the ports in case of a Linux operating system.

Procedure

1. Open a command prompt (**Start > Run > cmd**).
2. Enter **y-datadump.bat -s <http://host_url:<port number other than default port 80 or 1080>> -t <tenant name > <command> -u <user name> -p >password> -f <dump file>**

In this case, a dump file written containing the database content. The following is output:

```
[CLI] Setting verbosity level... [VALUE: 0=OFF]
```

```
[CLI] Exporting data... [TENANT: 30ff3081-aa9e-33e7-a7d7-5f9d00ae89ee, FILE: C:\out.zip]
```

```
[CLI] Data successfully exported. [TENANT: 30ff3081-aa9e-33e7-a7d7-5f9d00ae89ee]
```

General usage

Options	Description
-?, -h, --help	Show help
-f	File name of the dump file.
-s, --server	URL of the server, URL of the server, for example, http://my_host_url: <port number other than default port 80 or 1080>
-t, --tenant	Tenant name Default: default

Commands	Description
export	<p>Exports all data of the specified tenant to a data dump file. Currently, a dump contains the following information:</p> <ul style="list-style-type: none">▪ tenant▪ users▪ groups▪ user-group assignments▪ profile pictures (optional)▪ permissions, dependent on the privileges of the user who enters the command▪ licenses, dependent on the privileges of the user who enters the command▪ configuration, dependent on the privileges of the user who enters the command <p>The data is stored in JSON format and packed into an encrypted ZIP file. The ZIP file can be restored using the same command line tool.</p>
import	Imports a data base dump from a file.

Example

In this example, data is exported into a dump file.

```
y-datadump.bat -s <http://host_url> -t default export -u system -p manager -f  
"C:\backup\backup.zip"
```

4 Contacting support

ONLINE

A valid support contract allows you to access the solution database.

Click <https://empower.softwareag.com/> (<https://empower.softwareag.com/>).

If you have any questions on specific installations that you cannot perform yourself, contact your local Software AG sales organization

(https://empower.softwareag.com/public_directory.asp).

BY TELEPHONE

If you have a valid support contract, you can contact Global Support ARIS at:

+800 ARISHELP

"+" stands for the prefix required in a given country to dial an international connection.

Example for dialing within Germany with a direct extension line: 00 800 2747 4357

5 Disclaimer

ARIS products are intended and developed for use by persons. Automated processes, such as the generation of content and the import of objects/artifacts via interfaces, can lead to an outsized amount of data, and their execution may exceed processing capacities and physical limits. For example, processing capacities are exceeded if models and diagrams transcend the size of the modeling area or an extremely high number of processing operations is started simultaneously. Physical limits may be exceeded if the memory available is not sufficient for the execution of operations or the storage of data.

Proper operation of ARIS products requires the availability of a reliable and fast network connection. Networks with insufficient response time will reduce system performance and may cause timeouts.

If ARIS products are used in a virtual environment, sufficient resources must be available there in order to avoid the risk of overbooking.

The system was tested using scenarios that included 100,000 groups (folders), 100,000 users, and 1,000,000 modeling artifacts. It supports a modeling area of 25 square meters.

If projects or repositories are larger than the maximum size allowed, a powerful functionality is available to break them down into smaller, more manageable parts.

Some restrictions may apply when working with process administration, ARIS Administration, ARIS document storage, and ARIS Process Board, and when generating executable processes. Process Governance has been tested and approved for 1000 parallel process instances. However, the number may vary depending on process complexity, for example, if custom reports are integrated.

ARIS document storage was tested with 40.000 documents. We recommend monitoring the number and overall size of stored documents and archiving some documents if needed.