



ARIS

SERVER INSTALLATION GUIDE - LINUX

Version 10.0

April 2017

This document applies to ARIS Version 10.0 and to all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2010 - 2017 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products".

These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Contents

| | | |
|---------|--|----|
| 1 | Installation..... | 1 |
| 1.1 | Setup scenarios..... | 4 |
| 1.1.1 | Linux operating system..... | 7 |
| 1.1.1.1 | Installing ARIS Connect on a Linux operating system using the standard database | 8 |
| 1.1.1.2 | Installing ARIS Connect on a Linux operating system using a Microsoft SQL Server® | 12 |
| 1.1.1.3 | Installing ARIS Connect on a Linux operating system using an Oracle® database | 19 |
| 1.1.1.4 | Installing ARIS Publisher Server on a Linux operating system using a Microsoft SQL Server® | 26 |
| 1.1.1.5 | Installing ARIS Publisher Server on a Linux operating system using an Oracle® database | 31 |

1 Installation

This chapter describes the single node installation of ARIS Connect or ARIS Publisher Server using the setup program. The ARIS Connect installation makes ARIS Download Client available.

The ARIS Risk & Compliance Manager installation procedure is described in the **ARIS Risk & Compliance Manager Installation Guide** (see installation media). Documents can also be downloaded from Empower (<https://empower.softwareag.com/>), where a login is required, or from the ARIS Download Center (aris.softwareag.com).

Each setup program will install one specific product. If you need different products, they must be installed on a dedicated machine each. For advanced installations Software AG strongly recommends that you request an installation service by Global Consulting Services. You can order that service from your Software AG sales representative. This is of particular importance when you intend to install ARIS across several computers/VMs (distributed installation). Such a specific scenario requires profound knowledge of the technical ARIS infrastructure and environment. This cannot be provided in the product documentation. The required know-how can be acquired only by attending the training course **ARIS Server Installation**, available via Global Education Services (<http://softwareag.com/training>).

SETUPS

Make sure to have at least 15 GB free disk space to run the setup.

Each setup will install ARIS on one machine. If you are going to use ARIS Connect along with ARIS Publisher Server or ARIS Risk & Compliance Manager, the products must be installed on different machines. You can only install one product on one machine.

Setup activities are logged in the files **%temp%\ARIS_install_log** and **%temp%\aris_install_full.log**.

REMOTE INSTALLATION

To perform remote installations on Linux, first provide ARIS Agent (page 7) on the remote computers. Then you can install remotely from your Windows machine.

UPDATE

When you update or uninstall ARIS by an ARIS setup, the current installation will automatically be backed up. This process takes additional time and requires additional disk space while the setup is running. Make sure that the size of the free disk space is at least 15 GB larger than the folder size of the working directories <ARIS installation path>\server\bin\work (Windows®) or /home/ARIS/cloudagent/work (Linux). The update will fail if there is insufficient free disk space. If the update process fails, all ARIS components will be rolled back automatically.

To update customized installations e.g. multi-node systems, when an ARIS installations spans across several computers, please contact your local Software AG sales organization.

APPLICABLE DOCUMENTS

To avoid redundancies this document does not re-iterate information available in other documents. All documents are available on the installation media. If you have installed ARIS some documents can be opened using the Windows start menu. All documents can be downloaded from Empower (<https://empower.softwareag.com/>), where a login is required, or from the ARIS Download Center (aris.softwareag.com).

For more details please review relevant documents. The **Readme** file provides last-minute information that couldn't be included in the documents anymore. The **ARIS Guidelines for the Usage of Technical Documents** guide explains where to find relevant information, e. g.:

- **ARIS System Requirements**

Provides information about hardware and software requirements.

- **ARIS - Process-driven Management for SAP**

Provides information an how to configure Process-Driven Management for SAP® Solutions.

- **SAP Requirements**

Provides information about SAP software requirements (needed for Process-Driven Management for SAP® Solutions).

- **Technical Whitepaper**

Gives an overview on the product and software architecture of ARIS and non-functional and provisioning aspects of typical ARIS installations.

- **ARIS Update Cookbook**

This document is meant for ARIS administrators who are experienced in manually installing ARIS only. Knowing just how to install ARIS by using the provided ARIS standard setups is insufficient.

- **ARIS Client Installation Guide**

Describes how to install a local ARIS Client and ARIS Administrator Tools locally.

- **Functional Product Matrix**

Gives an overview on features and functionalities.

- **Technical Product Matrix**

For an overview on supported interfaces, methods, languages, and compatibilities.

- **Release notes**

Provides detailed information on new or changed features in this ARIS version.

1.1 Setup scenarios

This chapter describes the installation processes of ARIS products using different database management systems. Microsoft Windows operating systems and Linux operating systems (page 7) are supported. Each setup will install ARIS on one machine. If you are going to use ARIS Connect along with ARIS Publisher Server or ARIS Risk & Compliance Manager, the products must be installed on different machines. You can only install one product on one machine.

The ARIS Risk & Compliance Manager server installation procedure is described in the ARIS Risk & Compliance Manager Installation Guide (see installation media). Documents can be downloaded from Empower (<https://empower.softwareag.com/>), where a login is required, or from the ARIS Download Center (aris.softwareag.com).

You find all setup programs within the **ARIS_Server** folder or the **ARIS_Publisher_Server** folder on the installation media. If you do not use the installation media to setup ARIS, copy the whole content to a directory of your choice. This will make available all documents needed to setup ARIS as well as the database scripts. These scripts are needed to setup your external database management system for the use of ARIS.

If you only copy a single ARIS setup, make sure to copy the content of the folder containing the **setup.exe** file as well as the **Setup_Data** folder.

DVD FOLDERS

| Folder | Content |
|-----------------------|--|
| Add-ons | Required files needed to connect third-party tools, e. g. Microsoft SQL server, Oracle databases or SAP tools. |
| Content | ARIS databases, method filters and templates, the system database and queries, report scripts and macros that can be imported. |
| Documents | All required documents, guides (pdf) and ARIS Interactive Guides in different languages. All documents can be downloaded from Empower (https://empower.softwareag.com/) (login required) or from the ARIS Download Center (aris.softwareag.com). |
| Setups | All required setup files. |
| Linux <system> | Required files to install ARIS Agent and ARIS Cloud Controller on different Linux systems. Please refer to the Linux installation procedures (page 7). |
| ARIS_Agent | Provides ARIS Agent. After ARIS Agent is provided, you can install an ARIS server remotely (page 7) from a Windows machine. |
| ARIS_Cloud_Controller | Provides ARIS Cloud Controller on a Linux system. |
| Windows | All setup programs to be run on Windows machines. |
| ARIS_Agent | <p>Installs ARIS Agent. ARIS Agent will be installed on all Windows machines that will have an ARIS Server. It provides basic components, e.g. ARIS Cloud Controller (ACC) and handles internal communication processes.</p> <p>If you are about to install an ARIS Server remotely, please make sure to first install ARIS Agent locally on that machine.</p> |
| ARIS_Client | Installs an ARIS Client. |

| Folder | Content |
|-----------------------|--|
| ARIS_Server | <p>Installs ARIS Connect.</p> <p>This setup will install ARIS Agent, ARIS Server comprises of 100% of ARIS Design Server, standard database system (optional), ARIS Connect Viewer, ARIS Connect Designer and ARIS download clients. It provides the default tenant for all user data. The functionalities ARIS Connect workflows, Share model, Change request and Approve model are available using an ARIS Server license. For full ARIS Process Governance functionality you need to purchase and import an ARIS Process Governance license.</p> <p>ARIS Aware can be installed optionally. It provides dashboards in ARIS Connect.</p> <p>This setup can be run on Windows operating systems using the standard database system, your Microsoft SQL Server or your Oracle database. You can also install it on a Linux operating system.</p> |
| ARIS_Publisher_Server | <p>Installs ARIS Publisher Server or ARIS Publisher Report Server.</p> <p>This setup will install ARIS Agent and ARIS Publisher Server.</p> <p>Installation procedures are available for Windows operating system and Linux operating systems (page 7).</p> |
| Setup_Data | <p>Folder content needed for all setups.</p> <p>If you only copy one ARIS server setup, please make sure to copy the content of the folder containing the setup.exe file as well as the Setup_Data folder.</p> |

1.1.1 Linux operating system

In this chapter you find the ARIS server installation processes for a Linux operating system:

ARIS CONNECT

- Installing ARIS Connect on a Linux operating system using the standard database (page 8)
- Installing ARIS Connect on a Linux operating system using a Microsoft SQL Server® (page 12)
- Installing ARIS Connect on a Linux operating system using an Oracle® database (page 19)

ARIS PUBLISHER SERVER

- Installing ARIS Publisher Server on a Linux operating system using a Microsoft SQL Server® (page 26)
- Installing ARIS Publisher Server on a Linux operating system using an Oracle® database (page 31)
- The demo system, using Derby as database system, is not available on Linux systems.

1.1.1.1 Installing ARIS Connect on a Linux operating system using the standard database

Before installing an ARIS server on a Linux operating system you must provide ARIS Agent to your Linux Red Hat, SUSE or CentOS system. To allow customizing activities additionally provide **ARIS Cloud Controller (ACC)**. Use the ***.rpm** files for Red Hat, SUSE or CentOS systems. After you have copied and installed the files start the remote installation from a Windows system.

In **RedHat**, **SUSE**, and **CentOS** systems ***.rpm** files will perform these actions automatically:

- **/etc/sysctl.conf**

```
kernel.shmmax:  
if "kernel.shmmax < 629145600" then "kernel.shmmax = 629145600"  
max_file_max:  
if "max_file_max < 200000" then "fs.file-max = 200000"
```

- **/etc/security/limits.d/40-aris.conf**

```
$max_file_max = "ulimit -n"  
If "$max_file_max > 2^20" then max_file_max = 2^20  
aris soft nofile $max_file_max  
aris hard nofile $max_file_max  
aris soft nproc unlimited  
aris hard nproc unlimited
```

- **/etc/pam.d/su**

```
session required pam_limits.so
```

Prerequisites

- If you would like to import the ARIS license file during the setup procedure, please make sure to have the zip file saved on this computer. Otherwise licenses must be imported after the installation.
- You need access to the ***.rpm** files (DVD folder **Setups\Linux <system>\ARIS_Agent** or **ARIS_Cloud_Controller**).

Procedure

1. Copy the file **aris-acc_<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.
This file provides ARIS Cloud Controller (ACC).
2. Copy the file **aris-cloud-agent-<number>-1.x86_64.rpm** or **aris-cloud-agent-SLES-<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.
This file provides ARIS Agent. ARIS Agent is needed to perform a remote server installation.

3. Depending on the files you have copied and the type of the Linux system enter the relevant command to install the files.

It is important to first install ARIS Cloud Controller, then ARIS Agent.

rpm –i aris-acc-<number>-1.x86_64.rpm

This command installs ARIS Cloud Controller (/bin/acc.sh) to your Red Hat and SUSE system.

rpm –i aris-cloud-agent-<number>-1.x86_64.rpm

This command installs ARIS Agent to your Red Hat system.

rpm –i aris-cloud-agent-SLES-<number>-1.x86_64.rpm

This command installs ARIS Agent to your SUSE system.

These installations will create an unprivileged and locked user **ARIS** which uses **/home/ARIS** to install ARIS itself.

4. Perform the ARIS Server installation from a machine running a Microsoft Windows operating system (DVD folder **Setups\Windows\ARIS_Server**).
5. Start the **setup.exe** file as an administrator.
6. Select the **Perform installation on a remote server** option and enter the name of your Linux system.
7. Select the installation directory.
8. Only if you need to specify an external IP address for incoming requests please enter the server name or server IP.
9. Change the ARIS Agent user's credentials to prevent unauthorized access to your ARIS system.
If you change the credentials, you will be further on prompted to enter that password you've chosen whenever you start/stop the ARIS Server or access your ARIS installation using ARIS Cloud Controller.
10. If the ports **1080** or **1443** are already in use, specify the port numbers to be used. If you change the default port numbers users must add :<**this port number**> to the URL (see below).
11. To force secure connections uncheck **ARIS Server port**. If you do so, please make sure to make a valid SSL server certificate available.
12. Select the suitable system settings option. You need to take the RAM required and the number of users who will be accessing the ARIS Server into account. For a productive system it is recommended to select the **Medium** or **Large** option.
The Demo scenario option is recommended for demonstration purposes (laptop) only.
13. To import the ARIS license file, click **Change** to navigate to the license zip file. Otherwise licenses must be imported after the installation.
14. Select the **Standard** database system.

15. Enter the SMTP mail processing parameters of an existing account.

If you don't, ARIS will not send any notifications, due to the missing mailing functionality.

But you can configure SMTP mail processing at any later point of time. Some parameters can also be managed using the ARIS Administration of this server. Please refer to the online help of ARIS Administration.

16. Activate **Use TLS/SSL encryption** to prevent password sniffing.

17. Only if your mail server requires SMTP authentication, select the option **SMTP authentication** and enter the user's credentials.

If you enter these parameters but your mail server does not require SMTP authentication, the connection will be rejected.

18. If you are about to use a proxy server, please enter all proxy processing parameters. You can also enter them later, using the ARIS Administration of this server. Please refer to the online help of ARIS Administration.

19. Configure the start option:

Select **Start automatically** if you want to have the server started up with every restart of your operating system.

Select **Start manually** if you want to start/stop the server on the active computer manually.

20. Start the installation process.

21. Configure the system, once after the installation process is completed. Settings entered during the setup process can be adjusted. Use the **reconfigure ACC** command to change settings.

22. Start **ARIS Cloud Controller** (acc.sh).

As the internal ARIS user running all runnables has no root privileges all privileged ports (<1024) cannot be used. To run ARIS under a privileged port you need to redirect the ports.

23. Enter **startall**. This process will take a while.

24. Enter **list** to check the status of all runnables.

25. After the ARIS Server is running open your browser and enter **localhost** or **http://<IP address or fully-qualified host name>:<load balancer port>/#<tenant name>/adminSettings**. You must enter the port number only if you have changed or redirected the standard port. The login dialog opens.

26. Enter the user name **superuser** and the password **superuser**. This user only has access to the server's ARIS Administration.

27. The ARIS Administration's **Configuration > User management** tab opens.

28. Click  **Licenses** and check whether the licenses were properly imported during setup.
29. Create users and user groups and assign privileges and licenses for the **default** tenant. If you have created additional tenants, users and licenses must be managed for each additional tenant.

30. Create additional system users and superusers holding all required privileges. This will allow access to the ARIS system in case of password loss.

To prevent unauthorized access to the ARIS system, after data migration, change the passwords of the **arisservice** user, the **guest** user, the **system** user and the **superuser** user on all operational tenants, as well as on the infrastructure tenant (master). If you did not change the **ARIS Agent** user's credentials during the setup process, please at least change the **ARIS Agent** user's password manually.

31. Click **Logout**.
32. Send the URL **http://<IP address or fully-qualified host name>:<load balancer port>/#<tenant name>/home** to all users.

ARIS Server is installed, customized and running.

You can stop the server by entering **stopall** in the **ARIS Cloud Controller**. For some functionalities and extension packs, e.g. ARIS Publisher/IT Inventory or Process-Driven Management for SAP® Solutions you must customize ARIS depending on the functionality to be provided. Dashboards must be made available as well. Examples can be provided using the **United Motor Group** database (see ARIS Aware - Configuration Guide; ARIS Architect and ARIS Connect online help: ARIS Aware). You can also change settings entered during the setup process using the administration tools.

To obtain information on additional settings required please refer to the related documents in the **Administration** folder on DVD. Documents can also be downloaded from Empower (<https://empower.softwareag.com/>), where a login is required, or from the ARIS Download Center (aris.softwareag.com).

To uninstall ARIS from a Red Hat, SUSE or a CentOS system enter **rpm –e aris-cloud-agent** and **rpm –e aris-acc**.

1.1.1.2 Installing ARIS Connect on a Linux operating system using a Microsoft SQL Server®

Before installing an ARIS server on a Linux operating system you must provide ARIS Agent to your Linux Red Hat, SUSE or CentOS system. To allow customizing activities additionally provide **ARIS Cloud Controller** (ACC). Use the *.rpm files for Red Hat, SUSE or CentOS systems. After you have copied and installed the files start the remote installation from a Windows system.

In **RedHat**, **SUSE**, and **CentOS** systems *.rpm files will perform these actions automatically:

- **/etc/sysctl.conf**

```
kernel.shmmax:  
if "kernel.shmmax < 629145600" then "kernel.shmmax = 629145600"  
max_file_max:  
if "max_file_max < 200000" then "fs.file-max = 200000"
```

- **/etc/security/limits.d/40-aris.conf**

```
$max_file_max = "ulimit -n"  
If "$max_file_max > 2^20" then max_file_max = 2^20  
aris soft nofile $max_file_max  
aris hard nofile $max_file_max  
aris soft nproc unlimited  
aris hard nproc unlimited
```

- **/etc/pam.d/su**

```
session required pam_limits.so
```

Prerequisites

- An operating Microsoft SQL Server database. If you have not yet installed the Microsoft SQL Server, please follow the instructions in the Microsoft installation program, as well as the documentation provided by the manufacturer.
- The **SQL Server and Windows authentication mode** (mixed mode) option should be selected (Microsoft SQL Console > **Security** tab).
- You need to know the port number, the database name of the new database instance and also the credentials, i.e., the user name and the password of the application user.
- The Microsoft JDBC driver **sqljdbc4.jar**. You can download this driver from the Microsoft Web Site to a directory of your choice.
- SQL scripts and all additional files. All scripts and files are located on the installation medium (Add-ons\DatabaseScripts\ARIS Server\mssql) or they can be downloaded from the ARIS Download Center (aris.softwareag.com).
- If you would like to import the ARIS license file during the setup procedure, make sure to have the license file saved on this computer. Otherwise licenses must be imported after the installation.
- You need access to the *.rpm files (DVD folder **Setups\Linux <system>\ARIS_Agent** or **ARIS_Cloud_Controller**).

Procedure

1. Copy the file **aris-acc_<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.

This file provides ARIS Cloud Controller (ACC).

2. Copy the file **aris-cloud-agent-<number>-1.x86_64.rpm** or **aris-cloud-agent-SLES-<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.

This file provides ARIS Agent. ARIS Agent is needed to perform a remote server installation.

3. Depending on the files you have copied and the type of the Linux system enter the relevant command to install the files.

It is important to first install ARIS Cloud Controller, then ARIS Agent.

rpm -i aris-acc-<number>-1.x86_64.rpm

This command installs ARIS Cloud Controller (/bin/acc.sh) to your Red Hat and SUSE system.

rpm -i aris-cloud-agent-<number>-1.x86_64.rpm

This command installs ARIS Agent to your Red Hat system.

rpm -i aris-cloud-agent-SLES-<number>-1.x86_64.rpm

This command installs ARIS Agent to your SUSE system.

These installations will create an unprivileged and locked user **ARIS** which uses **/home/ARIS** to install ARIS itself.

4. Adjust the settings used by all configuration scripts.

Edit the **envset.bat** file to specify the connection data of the Microsoft SQL server instance. It's a good idea to write down the credentials. They must be entered later during the ARIS setup process.

To specify the connection data of the Microsoft SQL instance, modify the highlighted parameters:

```
@ECHO OFF
REM
REM You may edit this section for customizing purposes.
REM

REM If you use named instances then append a "\ " and the name of your instance
SET MSSQL_SAG_MSSQL_SERVER_NAME=localhost

REM The login name that is used to execute this script
SET MSSQL_SAG_MSSQL_LOGIN_NAME=localhost\username

REM name of database that will be created by the script.
SET MSSQL_SAG_DATABASE_NAME=ARIS10DB

REM folder in which the database files should be stored.
SET MSSQL_SAG_FILEGROUP_FILE_DIR=F:\msqldata\ARIS10DB

REM credentials of the login that is used by the application.
SET MSSQL_SAG_APP_USER=ARIS10
SET MSSQL_SAG_APP_PWD=*ARIS!1dm9n#

REM schema names for the default and master tenants
SET MSSQL_SAG_TENANT_DEFAULT=aris_default
SET MSSQL_SAG_TENANT_MASTER=aris_master
...
```

5. Execute the **inst.bat** file. This will create the database including the two mandatory tenants and the application user. The application user (APP_USER) is the Microsoft SQL user connecting ARIS and the Microsoft SQL database. The default user name is **ARIS10**. But you may have changed that name in the **envset.bat** earlier. Two schemes are mandatory. One for the **master** tenant and one for the **default** tenant. The values must be entered later during the ARIS Server setup process.
6. If you need additional tenants you must create additional schemes for each additional tenant. If you are going to create additional tenants for ARIS10.0 in order to migrate data from ARIS 9.8.7 or later, make sure to use identical names in both ARIS versions.

Run the script **create_schema_for_tenant.bat** and pass the schema name as parameter, e.g.:

create_schema_for_tenant.bat <schema name for additional tenant>

If the schema already exists it will be dropped and recreated automatically.

7. After you have set up the schemas you need to assign the tenants to additionally created schemes only:

Discover the database service ID (<dbServiceID>):

list external services

assign tenant <tenant name> to service <dbServiceID> com.aris.cip.db.schema
=<schema name>

For tenant names please only use up to 30 lowercase ASCII characters and numbers. The name must begin with a character. Special characters and characters e. g. in Chinese, Cyrillic or Arabic cannot be used.

8. Create the new tenant:

create tenant <tenant name>

9. If you do not use the scripts you can also setup the database and create an empty schema for each tenant manually.

10. Perform the ARIS Server installation from a machine running a Microsoft Windows operating system (DVD folder **Setups\Windows\ARIS_Server**).

11. Start the **setup.exe** file as an administrator.

12. Select the **Perform installation on a remote server** option and enter the name of your Linux system.

13. Select the installation directory.

14. Only if you need to specify an external IP address for incoming requests please enter the server name or server IP.

15. Change the ARIS agent user's credentials to prevent unauthorized access to your ARIS system.

If you change the credentials, you will be further on prompted to enter that password you've chosen whenever you start/stop the ARIS Server or access your ARIS installation using ARIS Cloud Controller.

16. If the ports **1080** or **1443** are already in use, specify the port numbers to be used. If you change the default port numbers users must add :<this port number> to the URL (see below).

17. Select the suitable system settings option. You need to take the RAM required and the number of users who will be accessing the ARIS Server into account. For a productive system it is recommended to select the **Medium** or **Large** option.

The Demo scenario option is recommended for demonstration purposes (laptop) only.

18. To import the ARIS license file, click **Change** to navigate to the license zip file. Otherwise licenses must be imported after the installation.

19. Select **MSSQL**.

20. Select the required JDBC driver for the Microsoft SQL database management system.

21. Enter the connection parameters used in the **envset.bat** file and exactly the values used by the **Microsoft SQL server**.

The values shown are the default values used in the **envset.bat** file and the default parameters used when setting up the Microsoft SQL server.

Server

Fully qualified name or IP address of the Microsoft SQL server. The default parameter used in the **envset.bat** file is **localhost**. The default name works only if you run that script from the machine where the Microsoft SQL server is installed.

Port

Port addressing the SQL server instance running over TCP. The default port number used in the **envset.bat** file is **1433**.

Instance name

When setting up a Microsoft SQL server, the default instance name is **MSSQLSERVER**. If you use named instances, enter the used named instance name instead.

Database name

Name of the database that was created by the **envset.bat** script. The default value is **ARIS9DB**.

Application user

Login user name that is used by the application. The default value used in the from **envset.bat** file is **ARIS9**.

Password

The application user's password. The default value used in the from **envset.bat** file is ***ARIS!1dm9n#**.

Default schema

Schema name for the **default** tenant and user name for that schema's owner. The default value used in the from **envset.bat** file is **ARIS_DEFAULT**.

Master schema

Schema name for the **master** tenant and user name for that schema's owner. The default value used in the from **envset.bat** file is **ARIS_MASTER**.

22. Enter the SMTP mail processing parameters of an existing account.

If you don't, ARIS will not send any notifications, due to the missing mailing functionality

But you can configure SMTP mail processing at any later point of time. Some parameters can also be managed using the ARIS Administration of this server. Please refer to the online help of ARIS Administration.

23. Activate **Use TLS/SSL encryption** to prevent password sniffing.

24. Only if your mail server requires SMTP authentication, select the option **SMTP authentication** and enter the user's credentials.

If you enter these parameters but your mail server does not require SMTP authentication, the connection will be rejected.

25. If you are about to use a proxy server, please enter all proxy processing parameters. You can also enter them later, using the ARIS Administration of this server. Please refer to the online help of ARIS Administration.
26. Configure the start option:
Select **Start automatically** if you want to have the server started up with every restart of your operating system.
Select **Start manually** if you want to start/stop the server on the active computer manually.
27. Start the installation process.
If you have changed the ARIS Agent's default user credentials during this procedure, you will be prompted for that password you have chosen.
28. Configure the system, once after the installation process is completed. Settings entered during the setup process can be adjusted. Use the **reconfigure** ACC command to change settings.
29. Start **ARIS Cloud Controller** (acc.sh).
As the internal ARIS user running all runnables has no root privileges all privileged ports (<1024) cannot be used. To run ARIS under a privileged port you need to redirect the ports.
30. Enter **startall**. This process will take a while.
31. Enter **list** to check the status of all runnables.
32. After the ARIS Server is running open your browser and enter **localhost** or **http://<IP address or fully-qualified host name>:<load balancer port>/#<tenant name>/adminSettings**. You must enter the port number only if you have changed or redirected the standard port. The login dialog opens.
33. Enter the user name **superuser** and the password **superuser**. This user only has access to the server's ARIS Administration.
34. The ARIS Administration's **Configuration > User management** tab opens.
35. Click  **Licenses** and check whether the licenses were properly imported during setup.
36. Create users and user groups and assign privileges and licenses for the **default** tenant. If you have created additional tenants, users and licenses must be managed for each additional tenant.
37. Create additional system users and superusers holding all required privileges. This will allow access to the ARIS system in case of password loss.

To prevent unauthorized access to the ARIS system, after data migration, change the passwords of the **arisservice** user, the **guest** user, the **system** user and the **superuser** user on all operational tenants, as well as on the infrastructure tenant (master). If you did not change the **ARIS Agent** user's credentials during the setup process, please at least change the **ARIS Agent** user's password manually.
38. Click **Logout**.

39. Send the URL **http://<IP address or fully-qualified host name>:<load balancer port>/#<tenant name>/home** to all users.

ARIS Server is installed, customized and running.

You can stop the server by entering **stopall** in the **ARIS Cloud Controller**. For some functionalities and extension packs, e.g. ARIS Publisher/IT Inventory or Process-Driven Management for SAP® Solutions you must customize ARIS depending on the functionality to be provided. Dashboards must be made available as well. Examples can be provided using the **United Motor Group** database (see ARIS Aware - Configuration Guide; ARIS Architect and ARIS Connect online help: ARIS Aware). You can also change settings entered during the setup process using the administration tools.

To obtain information on additional settings required please refer to the related documents in the **Administration** folder on DVD. Documents can also be downloaded from Empower (<https://empower.softwareag.com/>), where a login is required, or from the ARIS Download Center (aris.softwareag.com).

To uninstall ARIS from a Red Hat, SUSE or a CentOS system enter **rpm –e aris-cloud-agent** and **rpm –e aris-acc**.

1.1.1.3 Installing ARIS Connect on a Linux operating system using an Oracle® database

Before installing an ARIS server on a Linux operating system you must provide ARIS Agent to your Linux Red Hat, SUSE or CentOS system. To allow customizing activities additionally provide **ARIS Cloud Controller (ACC)**. Use the *.rpm files for Red Hat, SUSE or CentOS systems. After you have copied and installed the files start the remote installation from a Windows system.

In **RedHat**, **SUSE**, and **CentOS** systems *.rpm files will perform these actions automatically:

- **/etc/sysctl.conf**

```
kernel.shmmax:  
if "kernel.shmmax < 629145600" then "kernel.shmmax = 629145600"  
max_file_max:  
if "max_file_max < 200000" then "fs.file-max = 200000"
```

- **/etc/security/limits.d/40-aris.conf**

```
$max_file_max = "ulimit -n"  
If "$max_file_max > 2^20" then max_file_max = 2^20  
aris soft nofile $max_file_max  
aris hard nofile $max_file_max  
aris soft nproc unlimited  
aris hard nproc unlimited
```

- **/etc/pam.d/su**

```
session required pam_limits.so
```

Prerequisites

- An operating Oracle database management system. The Oracle database management system is not included in the package. If you have not yet installed the Oracle database management system, please follow the instructions in the Oracle installation program, as well as the documentation provided by the manufacturer.
- Ensure that SQL*PLUS is available.
Therefore an ORACLE client or an ORACL server must be installed on the machine where the scripts are run.
- You need to know the port number, the database/service name of the new database instance and also the credentials, i.e., the user name and the password of the application user.
- The **ojdbc6.jar** or **ojdbc7.jar** driver. You can download the most current file from the Oracle Web Site to a directory of your choice.
- SQL scripts and all additional files. All scripts and files are located on the installation medium (Add-ons\DatabaseScripts\ARIS Server\oracle) or they can be downloaded from the ARIS Download Center (aris.softwareag.com).
- If you would like to import the ARIS license file during the setup procedure, please make sure to have the zip file saved on this computer. Otherwise licenses must be imported after the installation.
- You need access to the *.rpm files (DVD folder **Setups\Linux <system>\ARIS_Agent** or **ARIS_Cloud_Controller**).

Procedure

1. Copy the file **aris-acc_<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.
This file provides ARIS Cloud Controller (ACC).
2. Copy the file **aris-cloud-agent-<number>-1.x86_64.rpm** or **aris-cloud-agent-SLES-<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.
This file provides ARIS Agent. ARIS Agent is needed to perform a remote server installation.

3. Depending on the files you have copied and the type of the Linux system enter the relevant command to install the files.

It is important to first install ARIS Cloud Controller, then ARIS Agent.

rpm -i aris-acc-<number>-1.x86_64.rpm

This command installs ARIS Cloud Controller (/bin/acc.sh) to your Red Hat and SUSE system.

rpm -i aris-cloud-agent-<number>-1.x86_64.rpm

This command installs ARIS Agent to your Red Hat system.

rpm -i aris-cloud-agent-SLES-<number>-1.x86_64.rpm

This command installs ARIS Agent to your SUSE system.

These installations will create an unprivileged and locked user **ARIS** which uses **/home/ARIS** to install ARIS itself.

4. Adjust the settings used by all configuration scripts.

Edit the file **envset.bat** to specify the connection data of the Oracle instance. It's a good idea to write down values and credentials. They must be entered later during the ARIS Server setup process.

5. Edit the **envset.bat** file and adjust the following lines replacing the **highlighted** parameters with the settings appropriate for your environment:

REM The path to where sqlplus.exe can be found.

SET CIP_ORA_BIN_PATH=<enter the path>

REM hostname, port and service name

SET TARGET_HOST=localhost

SET TARGET_PORT=1521

SET TARGET_SERVICE_NAME=ARIS

6. Edit the following lines to change the **highlighted** credentials of the application user:

REM credentials of the user that is used by the application.

SET CIP_APP_USER=ARIS10

SET CIP_APP_PWD=*ARIS!1dm9n#

REM password of the tenant schemas.

SET CIP_TENANT_SCHEMA_PWD=*ARIS!1dm9n#yy

7. With the next two lines you specify the DBA user you intend to use to create the application user and this DBA user's password:

REM credentials of the Oracle user that will be used to create the application schema.

REM Note that this user must be endowed with DBA privileges such as user SYSTEM.

SET CIP_INSTALL_USER=system

SET CIP_INSTALL_PWD=manager

8. If your data table space name is different from **ARISDATA** respectively **TEMP** for temp table space, you will also need to modify these highlighted parameters accordingly:
REM tablespace name of the tablespace in which the data of the application schema should be stored.

SET CIP_TS_DATA=**ARISDATA**

REM name of the temporary tablespace.

SET CIP_TS_TEMP=**TEMP**

9. Save the **envset.bat** file. So you can use it for future update setups again.

10. Run the script **cip_create_app_user.bat**.

This will create the application user. The application user (CIP_APP_USER) is the Oracle user connecting ARIS and the Oracle database. The default user name is **ARIS10**. But you may have changed that name in the **envset.bat** earlier.

11. Create an empty schema for each tenant. Two schemes are mandatory. One for the **master** tenant and one for the **default** tenant. The names, e.g. **aris_master** and **aris_default** can be modified. These names must be entered later during the ARIS Server setup process. If you need additional tenants you must create additional schemes.

To create the schema objects, run these commands for each schema name **aris_master**, **aris_default** and additional tenants.

Run the script **cip_create_schema_for_tenant.bat** and pass the schema name as parameter, e.g.:

cip_create_schema_for_tenant.bat aris_master (mandatory)

cip_create_schema_for_tenant.bat aris_default (mandatory)

cip_create_schema_for_tenant.bat <oracle schema name for additional tenant>
(optional)

If you are going to create additional tenants for ARIS10.0 in order to migrate data from ARIS 9.8.7 or later, make sure to use identical names in both ARIS versions. If the schema already exists it will be dropped and recreated.

12. After you have set up the schemas you need to assign the tenants to additionally created schemes.

13. Perform the ARIS Server installation from a machine running a Microsoft Windows operating system (DVD folder **Setups\Windows\ARIS_Server**).

14. Start the **setup.exe** file as an administrator.

15. Select the **Perform installation on a remote server** option and enter the name of your Linux system.

16. Select the installation directory.

17. Only if you need to specify an external IP address for incoming requests please enter the server name or server IP.

18. Change the ARIS agent user's credentials to prevent unauthorized access to your ARIS system.

If you change the credentials, you will be further on prompted to enter that password you've chosen whenever you start/stop the ARIS Server or access your ARIS installation using ARIS Cloud Controller.

19. If the ports **1080** or **1443** are already in use, specify the port numbers to be used. If you change the default port numbers users must add :<**this port number**> to the URL (see below).

20. Select the suitable system settings option. You need to take the RAM required and the number of users who will be accessing the ARIS Server into account. For a productive system it is recommended to select the **Medium** or **Large** option.

The Demo scenario option is recommended for demonstration purposes (laptop) only.

21. To import the ARIS license file, click **Change** to navigate to the license zip file. Otherwise licenses must be imported after the installation.

22. Select **Oracle**.

23. Select the required JDBC driver for the Oracle database management system.

24. Enter the connection parameters used in the **envset.bat** file and exactly the values used by the Oracle server.

The values shown are the default values used in the **envset.bat** file and the default parameters used when setting up the Oracle server.

Enter exactly the values used by the Oracle server, e. g. **database name**. Use the **default** schema's name and the **master** schema's name that have been created earlier.

Server

Fully qualified name or IP address of the Oracle server. The default parameter used in the **envset.bat** file is **localhost**. The default name works only if you run that script from the machine where the Oracle server is installed.

Port

Port addressing the Oracle server instance running over TCP. The default port number used in the **envset.bat** file is **1521**.

Database/Service name

Oracle SID or Oracle service name. The default value used in the from **envset.bat** file is **ARIS**.

Application user

Login user name that is used by the application. The default value used in the from **envset.bat** file is **ARIS9**.

Password

The application user's password. The default value used in the from **envset.bat** file is ***ARIS!1dm9n#**.

Default schema

Schema name for the **default** tenant and user name for that schema's owner. Enter exactly the name used when you have created the schema (see step 6), e. g. **aris_default**.

Master schema

Schema name for the **master** tenant and user name for that schema's owner. Enter exactly the name used when you have created the schema (see step 6), e. g. **aris_master**.

If you are about to use an Oracle cluster you must change the format string in the next dialog:

syntax:

jdbc:oracle:thin:@<ORACLE_SERVER>:<ORACLE_PORT>:<ORACLE_SID>. After the setup process is completed you need to update the external service.

25. Enter the SMTP mail processing parameters of an existing account.

If you don't, ARIS will not send any notifications, due to the missing mailing functionality

But you can configure SMTP mail processing at any later point of time. Some parameters can also be managed using the ARIS Administration of this server. Please refer to the online help of ARIS Administration.

26. Activate **Use TLS/SSL encryption** to prevent password sniffing.

27. Only if your mail server requires SMTP authentication, select the option **SMTP authentication** and enter the user's credentials.

If you enter these parameters but your mail server does not require SMTP authentication, the connection will be rejected.

28. If you are about to use a proxy server, please enter all proxy processing parameters. You can also enter them later, using the ARIS Administration of this server. Please refer to the online help of ARIS Administration.

29. Configure the start option:

Select **Start automatically** if you want to have the server started up with every restart of your operating system.

Select **Start manually** if you want to start/stop the server on the active computer manually.

30. Start the installation process.

If you have changed the ARIS Agent's default user credentials during this procedure, you will be prompted for that password you have chosen.

31. Configure the system, once after the installation process is completed. Settings entered during the setup process can be adjusted. Use the **reconfigure ACC** command to change settings.

32. Start **ARIS Cloud Controller** (acc.sh).

As the internal ARIS user running all runnables has no root privileges all privileged ports (<1024) cannot be used. To run ARIS under a privileged port you need to redirect the ports.

33. Enter **startall**. This process will take a while.

34. Enter **list** to check the status of all runnables.

35. After the ARIS Server is running open your browser and enter **localhost** or **http://<IP address or fully-qualified host name>:<load balancer port>/#<tenant name>/adminSettings**. You must enter the port number only if you have changed or redirected the standard port. The login dialog opens.

36. Enter the user name **superuser** and the password **superuser**. This user only has access to the server's ARIS Administration.

37. The ARIS Administration's **Configuration > User management** tab opens.

38. Click  **Licenses** and check whether the licenses were properly imported during setup.

39. Create users and user groups and assign privileges and licenses for the **default** tenant. If you have created additional tenants, users and licenses must be managed for each additional tenant.

40. Create additional system users and superusers holding all required privileges. This will allow access to the ARIS system in case of password loss.

To prevent unauthorized access to the ARIS system, after data migration, change the passwords of the **arisservice** user, the **guest** user, the **system** user and the **superuser** user on all operational tenants, as well as on the infrastructure tenant (master). If you did not change the **ARIS Agent** user's credentials during the setup process, please at least change the **ARIS Agent** user's password manually.

41. Click **Logout**.

42. Send the URL **http://<IP address or fully-qualified host name>:<load balancer port>/#<tenant name>/home** to all users.

ARIS Server is installed, customized and running.

You can stop the server by entering **stopall** in the **ARIS Cloud Controller**. For some functionalities and extension packs, e.g. ARIS Publisher/IT Inventory or Process-Driven Management for SAP® Solutions you must customize ARIS depending on the functionality to be provided. Dashboards must be made available as well. Examples can be provided using the **United Motor Group** database (see ARIS Aware - Configuration Guide; ARIS Architect and ARIS Connect online help: ARIS Aware). You can also change settings entered during the setup process using the administration tools.

To obtain information on additional settings required please refer to the related documents in the **Administration** folder on DVD. Documents can also be downloaded from Empower (<https://empower.softwareag.com/>), where a login is required, or from the ARIS Download Center (aris.softwareag.com).

To uninstall ARIS from a Red Hat, SUSE or a CentOS system enter **rpm -e aris-cloud-agent** and **rpm -e aris-acc**.

Update installations are available. Components will be stopped. After the system has been updated all components will be started automatically.

1.1.1.4 Installing ARIS Publisher Server on a Linux operating system using a Microsoft SQL Server®

Before installing an ARIS server on a Linux operating system you must provide ARIS Agent to your Linux Red Hat, SUSE or CentOS system. To allow customizing activities additionally provide **ARIS Cloud Controller** (ACC). Use the *.rpm files for Red Hat, SUSE or CentOS systems. After you have copied and installed the files start the remote installation from a Windows system.

In **RedHat**, **SUSE**, and **CentOS** systems *.rpm files will perform these actions automatically:

- **/etc/sysctl.conf**

```
kernel.shmmax:  
if "kernel.shmmax < 629145600" then "kernel.shmmax = 629145600"  
max_file_max:  
if "max_file_max < 200000" then "fs.file-max = 200000"
```

- **/etc/security/limits.d/40-aris.conf**

```
$max_file_max = "ulimit -n"  
If "$max_file_max > 2^20" then max_file_max = 2^20  
aris soft nofile $max_file_max  
aris hard nofile $max_file_max  
aris soft nproc unlimited  
aris hard nproc unlimited
```

- **/etc/pam.d/su**

```
session required pam_limits.so
```

This setup will install **ARIS Agent** and **ARIS Publisher Server**. The standard setup installs ARIS Publisher Server including **Tomcat** Web Application Server. As the used **Tomcat** version cannot be the most recent version a denial of service (DoS) vulnerability can occur. This vulnerability is not critical for intranet use. For Internet use please make sure to use the most recent web application server version that matches your security requirements.

For a productive ARIS Publisher system you must select the **small** or **large** installation option. For these installation options an external database system is required. The external database system is not included in the package. Depending on the ARIS Publisher Server license purchased, the system enables all users to simultaneously work on exports.

Prerequisites

- You need access to the *.rpm files (DVD folder **Setups\Linux <system>\ARIS_Agent** or **ARIS_Cloud_Controller**).
- The file **create_db.sql** (<installation media\Add-ons\DatabaseScripts\PublisherServer\mssql) is copied to a directory of your choice. This script can be modified according to your security guide lines.
- You have installed Microsoft SQL Server under **Microsoft Windows**. Microsoft SQL Server is not included in the package. If you install or configure a database yourself, always follow the instructions provided by the respective manufacturer, or contact your local Software AG sales organization.
- You have downloaded the SQL Server JDBC driver (**jTDS.jar** or **sqljdbc4.jar**) from the Microsoft Download Center to a directory of your choice.
- To encrypt passwords use the ARIS Server Administrator command **encrypt**.
- If you would like to import the ARIS license file during the setup procedure, please make sure to have the zip file saved on this computer. Otherwise licenses must be imported after the installation.

Procedure

1. Copy the file **aris-acc-<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.
This file provides ARIS Cloud Controller (ACC).
2. Copy the file **aris-cloud-agent-<number>-1.x86_64.rpm** or **aris-cloud-agent-SLES-<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.
This file provides ARIS Agent. ARIS Agent is needed to perform a remote server installation.
3. Depending on the files you have copied and the type of the Linux system enter the relevant command to install the files.
It is important to first install ARIS Cloud Controller, then ARIS Agent.
rpm -i aris-acc-<number>-1.x86_64.rpm
This command installs ARIS Cloud Controller (/bin/acc.sh) to your Red Hat and SUSE system.
rpm -i aris-cloud-agent-<number>-1.x86_64.rpm
This command installs ARIS Agent to your Red Hat system.
rpm -i aris-cloud-agent-SLES-<number>-1.x86_64.rpm
This command installs ARIS Agent to your SUSE system.
These installations will create an unprivileged and locked user **ARIS** which uses **/home/ARIS** to install ARIS itself.

4. Adjust the system as required to manage ARIS Publisher Server in combination with a Microsoft SQL Server database. For additional information about Microsoft SQL Server, visit <http://support.microsoft.com/kb/914277/en-us>.
5. Open the Microsoft SQL Console.
6. Open the **Server properties** dialog.
7. On the **Security** tab, select the **SQL Server and Windows authentication mode** option (mixed mode).
8. Create a database using the **create_db.sql** script.
9. Note the database name, user name, and password. You must enter these values later during the setup process.
10. Ensure that **Latin1_General_CI_AI** sorting is selected for the **COLLATE** statement.

The script creates the specified data groups. Note these values. You must enter the values later during the setup process.

ARISBPDATA: contains all database objects

ARISBPIINDEX: contains all index data

11. Close the Microsoft SQL Console.
12. Start the ARIS Publisher Server installation as an administrator (DVD folder **Setups\Windows\ARIS_Publisher_Server**).
13. Start the ARIS Publisher Server installation from a machine running a Microsoft Windows operating system (DVD folder **Setups\Windows\ARIS_Publisher_Server**).
14. Start the **setup.exe** file as an administrator.
15. Select the **Perform installation on a remote server** option and enter the name of your Linux system.
16. Select the installation directory.
17. To import the ARIS license file right now, click **Select file...** to navigate to the license file. Otherwise licenses must be imported after the installation.
18. Select the ARIS Publisher Server to be installed. A Report Server can only be installed on another machine. This is to optimize system performance when running reports.
19. If you retain the settings of the installation program, the context path and the default port **19990** to the web server are entered automatically. Either make sure that the default port is not used by other programs, or enter another free port number.
20. If you use Process Governance please specify the IP address or fully-qualified ARIS Server name. Enter the port number only if it is another than the standard port.

The **Process Governance** module and the **Start governance process** pop-up menu are only available in the Publisher exports if a Process Governance license is available for the connected ARIS Server and all Process Governance integration parameters have been entered during the ARIS Publisher Server setup process.

21. To use the user and license management of another ARIS server, select **Use the ARIS Administration of an existing ARIS server**.

Enter the URL to that ARIS Server ARIS Administration:

http://<IP address or fully-qualified host name>:<load balancer port>/umc

You must enter the port number only if you have changed or redirected the standard port.

Enter the ARIS Administration user's name **superuser** and the corresponding password.

22. If you are about to manage documents using ARIS document storage of another ARIS Server, enter the required parameters. Only in this case ARIS document storage will be available if customized.

23. Select the **Medium** or **Large** installation option. You need to take the memory requirement into account to ensure optimum load distribution and better protection against failure.

24. Select the **Microsoft SQL Server** as database system.

25. Select the required JDBC driver for the Microsoft SQL database management system.

26. Enter the connection parameters used in the **create_db.sql** file and exactly the values used by the **Microsoft SQL server**.

The values shown are the default values used in the **create_db.sql** file and the default parameters used when setting up the Microsoft SQL server.

Server

Fully qualified name or IP address of the Microsoft SQL server.

Port

Port addressing the SQL server instance running over TCP. The default port number is **1433**.

Instance name

When setting up a Microsoft SQL server, the default instance name is **MSSQLSERVER**. If you use named instances, append a backslash and enter the used instance name instead.

Database name

Name of the database that was created by the **create_db.sql** script. The default value is **ARISBP9**.

Application user

Login user name that is used by the application. The default value used in the from **create_db.sql** file is **ARISBP9**.

Password

The application user's password. The default value used in the **create_db.sql** file is ***ARISBP!1dm95n#**.

Data file group

Name of the table space for table data that had been created earlier. The default value used in the **create_db.sql** file is **ARISBPDATA**.

Index file group

Name of the table space for index data that had been created earlier. The default value used in the **create_db.sql** file is **ARISBPINDEX**.

27. Start the installation process.
28. Configure the system, once after the installation process is completed. Settings entered during the setup process can be adjusted. Use the **reconfigure ACC** command to change settings.
29. Start **ARIS Cloud Controller** (acc.sh).
As the internal ARIS user running all runnables has no root privileges all privileged ports (<1024) cannot be used. To run ARIS under a privileged port you need to redirect the ports.
30. Enter **startall**. This process will take a while.
31. Enter **list** to check the status of all runnables.
32. After ARIS Publisher Server is running open your browser and enter:

`http://<IP address or fully-qualified host name>:<port number>/businesspublisher,`
`e.g. http://arispublishersrv:19990/businesspublisher`

33. Start the ARIS Administration of the ARIS Server and import the ARIS Publisher Server license file.

ARIS Publisher Server is installed, customized and running.

You can stop the server by entering **stopall** in the **ARIS Cloud Controller**. For some functionalities and extension packs, e.g. ARIS Publisher/IT Inventory or Process-Driven Management for SAP® Solutions you must customize ARIS depending on the functionality to be provided. Dashboards must be made available as well. Examples can be provided using the **United Motor Group** database (see ARIS Aware - Configuration Guide; ARIS Architect and ARIS Connect online help: ARIS Aware). You can also change settings entered during the setup process using the administration tools.

To obtain information on additional settings required please refer to the related documents in the **Administration** folder on DVD. Documents can also be downloaded from Empower (<https://empower.softwareag.com/>), where a login is required, or from the ARIS Download Center (aris.softwareag.com).

After the installation, reports are run by ARIS Publisher Server. You can additionally install a Report Server to optimize system performance when running reports. To install ARIS Publisher Report Server, start this setup again and select the ARIS Publisher Report Server to be installed. After you have installed ARIS Publisher Report Server, exports are managed by ARIS Publisher Server and reports are run by ARIS Publisher Report Server.

To uninstall ARIS from a Red Hat, SUSE or a CentOS system enter **rpm –e aris-cloud-agent** and **rpm –e aris-acc**.

Update installations are available. Components will be stopped. After the system has been updated all components will be started automatically.

1.1.1.5 Installing ARIS Publisher Server on a Linux operating system using an Oracle® database

Before installing an ARIS server on a Linux operating system you must provide ARIS Agent to your Linux Red Hat, SUSE or CentOS system. To allow customizing activities additionally provide **ARIS Cloud Controller** (ACC). Use the *.rpm files for Red Hat, SUSE or CentOS systems. After you have copied and installed the files start the remote installation from a Windows system.

In **RedHat**, **SUSE**, and **CentOS** systems *.rpm files will perform these actions automatically:

- **/etc/sysctl.conf**

```
kernel.shmmax:  
if "kernel.shmmax < 629145600" then "kernel.shmmax = 629145600"  
max_file_max:  
if "max_file_max < 200000" then "fs.file-max = 200000"
```

- **/etc/security/limits.d/40-aris.conf**

```
$max_file_max = "ulimit -n"  
If "$max_file_max > 2^20" then max_file_max = 2^20  
aris soft nofile $max_file_max  
aris hard nofile $max_file_max  
aris soft nproc unlimited  
aris hard nproc unlimited
```

- **/etc/pam.d/su**

```
session required pam_limits.so
```

This setup will install **ARIS Agent** and **ARIS Publisher Server**. The standard setup installs ARIS Publisher Server including **Tomcat 7.x** Web Application Server. As the used **Tomcat** version cannot be the most recent version a denial of service (DoS) vulnerability can occur. This vulnerability is not critical for intranet use. For Internet use please make sure to use the most recent web application server version that matches your security requirements.

For a productive ARIS Publisher system you must select the **small** or **large** installation option. For these installation options an external database system is required. The external database system is not included in the package. If you have not yet installed the Oracle database management system, please follow the instructions in the Oracle installation program, as well as the documentation provided by the manufacturer.

Depending on the ARIS Publisher Server license purchased, the system enables all users to simultaneously work on exports.

Prerequisites

- You have access to the *.rpm files (DVD folder **Setups\Linux <system>\ARIS_Agent** or **ARIS_Cloud_Controller**).
- We recommend two separate Oracle database instances for ARIS Server and ARIS Publisher. This keeps the two systems from competing for resources, and you achieve better performance and higher availability.
- While creating the database instance used by ARIS Publisher, write down all defined connection parameters, e.g. the database name, the tablespace names, the user name, and password. You must enter these values later during the setup process.
- Use of the database character set **AL32UTF8** is mandatory.
- We recommend a block size of **8K**.
- **query_rewrite_enabled=true**
- **query_rewrite_integrity=trusted**
- Two tablespaces, e. g. **ARISBPDATA** (for table data) and **ARISBPIINDEX** (for index data) have been created.

We recommend setting the tablespaces for automatic, unlimited growth. Otherwise, you run the risk of completely exhausting the memory in the tablespaces, which may cause important functions of ARIS Server and ARIS Publisher to fail. If the option for automatic growth is not set, regular monitoring (e.g. weekly) of the Oracle instance is required to ensure that the tablespaces are manually increased on time.

- We recommend turning off the Oracle recycle bin because large quantities of tables accumulate there when exports are deleted.
- An Oracle user has been created using the **Create_user.bat** and **bpadduser.sql** scripts (<installation media\Add-ons\DatabaseScripts\PublisherServer\oracle). The **ORACLE_SID** and the **Oracle system user's password** must have been adapted in the **Create_user.bat** file. Prompted during script execution, the name of the Oracle user as well as the password is arbitrary.
- If you would like to import the license file right now please make sure to have the ARIS Publisher Server license zip file saved on this computer. Otherwise licenses must be imported after the installation.

Procedure

1. Copy the file **aris-acc-<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.

This file provides ARIS Cloud Controller (ACC).

2. Copy the file **aris-cloud-agent-<number>-1.x86_64.rpm** or **aris-cloud-agent-SLES-<number>-1.x86_64.rpm** from the installation media to the hard drive of your Linux system.

This file provides ARIS Agent. ARIS Agent is needed to perform a remote server installation.

3. Depending on the files you have copied and the type of the Linux system enter the relevant command to install the files.

It is important to first install ARIS Cloud Controller, then ARIS Agent.

rpm -i aris-acc-<number>-1.x86_64.rpm

This command installs ARIS Cloud Controller (/bin/acc.sh) to your Red Hat and SUSE system.

rpm -i aris-cloud-agent-<number>-1.x86_64.rpm

This command installs ARIS Agent to your Red Hat system.

rpm -i aris-cloud-agent-SLES-<number>-1.x86_64.rpm

This command installs ARIS Agent to your SUSE system.

These installations will create an unprivileged and locked user **ARIS** which uses **/home/ARIS** to install ARIS itself.

4. Start the ARIS Publisher Server installation from a machine running a Microsoft Windows operating system (DVD folder **Setups\Windows\ARIS_Publisher_Server**).
5. Start the **setup.exe** file as an administrator.
6. Select the **Perform installation on a remote server** option and enter the name of your Linux system.
7. Select the installation directory.
8. To import the ARIS license file right now, click **Select file...** to navigate to the license zip file. Otherwise licenses must be imported after the installation.
9. Select the ARIS Publisher Server to be installed. A Report Server can only be installed on another machine. This is to optimize system performance when running reports.
10. If you retain the settings of the installation program, the context path and the default port **19990** to the web server are entered automatically. Either make sure that the default port is not used by other programs, or enter another free port number.
11. If you use Process Governance please specify the IP address or fully-qualified ARIS Server name. Enter the port number only if it is another than the standard port.

The **Process Governance** module and the **Start governance process** pop-up menu are only available in the Publisher exports if a Process Governance license is available for the connected ARIS Server and all Process Governance integration parameters have been entered during the ARIS Publisher Server setup process.

12. To use the user and license management of another ARIS Server, select **Use the ARIS Administration of an existing ARIS Server**.

Enter the URL to that ARIS Server ARIS Administration:

http://<IP address or fully-qualified host name>:<load balancer port>/umc

You must enter the port number only if you have changed or redirected the standard port.

Enter the ARIS Administration user name **superuser** and the corresponding password.

13. If you are about to manage documents using ARIS document storage of another ARIS Server, enter the required parameters. Only in this case ARIS document storage will be available if customized.

14. Select the **Medium** or **Large** installation option. You need to take the memory requirement into account to ensure optimum load distribution and better protection against failure.

15. Select **Oracle** as database system.

16. Select the required JDBC driver for the Oracle database management system.

17. Enter the connection parameters you have defined while creating the Oracle database.

Server

Fully qualified name or IP address of the Oracle system.

Port

Port addressing the Oracle server instance running over TCP. The default port number is **1521**.

Database instance name

Oracle SID or Oracle service name.

Application user

Login user name that is used by the application. This is the name of the Oracle user created by the **Create_user.bat** and **bpadduser.sql** scripts.

Password

The application user password.

Data tablespace name

Name of the table space for table data that had been created earlier. The default value is **ARISBPDATA**.

Index tablespace name

Name of the table space for index data that had been created earlier. The default value is **ARISBPIINDEX**.

18. Start the installation process.

19. Configure the system, once after the installation process is completed. You may change the standard database connection parameters. You can adjust all parameters that have been entered during the setup process.

20. Start **ARIS Cloud Controller** (acc.sh).

As the internal ARIS user running all runnables has no root privileges all privileged ports (<1024) cannot be used. To run ARIS under a privileged port you need to redirect the ports.

21. Enter **startall**. This process will take a while.

22. Enter **list** to check the status of all runnables.

23. After ARIS Publisher Server is running open your browser and enter:

http://<IP address or fully-qualified host name>:<port number>/businesspublisher, e.g.:
http://arispublishersrv:19990/businesspublisher

24. Start the ARIS Administration of the ARIS Server and import the ARIS Publisher Server license file.

ARIS Publisher Server is installed, customized and running.

You can stop the server by entering **stopall** in the **ARIS Cloud Controller**. For some functionalities and extension packs, e.g. ARIS Publisher/IT Inventory or Process-Driven Management for SAP® Solutions you must customize ARIS depending on the functionality to be provided. Dashboards must be made available as well. Examples can be provided using the **United Motor Group** database (see ARIS Aware - Configuration Guide; ARIS Architect and ARIS Connect online help: ARIS Aware). You can also change settings entered during the setup process using the administration tools.

To obtain information on additional settings required please refer to the related documents in the **Administration** folder on DVD. Documents can also be downloaded from Empower (<https://empower.softwareag.com/>), where a login is required, or from the ARIS Download Center (aris.softwareag.com).

After the installation, reports are run by ARIS Publisher Server. You can additionally install a Report Server to optimize system performance when running reports. To install ARIS Publisher Report Server, start this setup again and select the ARIS Publisher Report Server to be installed. After you have installed ARIS Publisher Report Server, exports are managed by ARIS Publisher Server and reports are run by ARIS Publisher Report Server.

To uninstall ARIS from a Red Hat, SUSE or a CentOS system enter **rpm –e aris-cloud-agent** and **rpm –e aris-acc**.

Update installations are available. Components will be stopped. After the system has been updated all components will be started automatically.