

Adabas System Coordinator

Adabas System Coordinator Parameters

Version 8.6.2

September 2026

This document applies to Adabas System Coordinator Version 8.6.2 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2026 Software GmbH, Darmstadt, Germany and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software GmbH product names are either trademarks or registered trademarks of Software GmbH and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software GmbH and/or its subsidiaries is located at <https://softwareag.com/licenses>.

Use of this software is subject to adherence to Software GmbH's licensing conditions and terms. These terms are part of the product documentation, located at <https://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software GmbH Products / Copyright and Trademark Notices of Software GmbH Products". These documents are part of the product documentation, located at <https://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software GmbH.

Document ID: COR-PARAMETERS-862-20260922

Table of Contents

Preface	v
1 About this Documentation	1
Document Conventions	2
Online Information and Support	2
Data Protection	3
2 Client Runtime Controls	5
Client Runtime Control Descriptions	6
3 Daemon Parameters	15
Daemon Group Parameters	16
Daemon Group Member Parameters	19

Preface

Adabas System Coordinator operation is controlled by the following types of parameters:

- **Client Runtime Controls**
- **Daemon Parameters**

Adabas System Coordinator parameters can be maintained using Adabas System Coordinator Online Services, function Maintenance.

1

About this Documentation

■ Document Conventions	2
■ Online Information and Support	2
■ Data Protection	3

Document Conventions

Convention	Description
Bold	Identifies elements on a screen.
Monospace font	Identifies service names and locations in the format <i>folder.subfolder.service</i> , APIs, Java classes, methods, properties.
<i>Italic</i>	Identifies: Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources.
Monospace font	Identifies: Text you must type in. Messages displayed by the system. Program code.
{ }	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.
	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the symbol.
[]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [] symbols.
...	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...).

Online Information and Support

Product Documentation

You can find the product documentation on our documentation website at <https://documentation.softwareag.com>.

Product Training

You can find helpful product training material on our Learning Portal at <https://learn.software-ag.com>.

Tech Community

You can collaborate with Software GmbH experts on our Tech Community website at <https://tech-community.softwareag.com>. From here you can, for example:

- Browse through our vast knowledge base.
- Ask questions and find answers in our discussion forums.
- Get the latest Software GmbH news and announcements.
- Explore our communities.
- Go to our public GitHub and Docker repositories at <https://github.com/softwareag> and <https://hub.docker.com/publishers/softwareag> and discover additional Software GmbH resources.

Product Support

Support for Software GmbH products is provided to licensed customers via our Empower Portal at <https://empower.softwareag.com>. Many services on this portal require that you have an account. If you do not yet have one, you can request it at <https://empower.softwareag.com/register>. Once you have an account, you can, for example:

- Download products, updates and fixes.
- Search the Knowledge Center for technical information and tips.
- Subscribe to early warnings and critical alerts.
- Open and update support incidents.
- Add product feature requests.

Data Protection

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

2

Client Runtime Controls

■ Client Runtime Control Descriptions	6
---	---

Runtime controls are used to control the operation of the jobs managed by Adabas System Coordinator

Client Runtime Controls	Overridable
Control Name	-
Service Member Name	-
Operation Mode	-
Activity pulse	-
Daemon connection messages	-
API Runtime Overrides	-
Threadsafe operation	-
Use Additional Exits	-
Maximum Idle Time	-
Non-terminal Idle Time	-
Generate RSP009/79	-
Latency Controls	-
Enable CICSplex DTR	-
Site Information Menu Function	-
Transaction, Stepname or Login Override (Override function)	-
Cleanup at Start, Cleanup at End	Y
Message Controls	-
Command retry	-
Debug settings	-
Unified trace settings	Y
Site-dependent controls	Y
Review	Y
Client Monitor	Y

Client Runtime Control Descriptions

This section provides a description of each Adabas System Coordinator parameter:

Control Name

Parameter Type	Use	Minimum	Maximum	Default
Client Runtime Control	Within a particular Job Type (eg. Batch, COM-LETE, CICS, etc.), this is the name of a specific job and the controls defined will apply solely to this job. If the value '*' is specified, the controls defined will apply to all jobs, within the corresponding Job Type, that do not have explicit Control Names defined for them. For a multi-job TP monitor service (eg. Job Type=CICS(DTR)), this is a unique name for the multi-job service. The controls defined will apply to each of the individual jobs defined as a <i>Service Member Name</i> within the multi-job service.	1 character	8 characters	see text

Service Member Name

Parameter Type	Use	Minimum	Maximum	Default
Client Runtime Control	The name of a job that runs as part of a multi-job TP monitor service. These job names are maintained by selecting the appropriate <i>Control Name</i> with 'J' for Jobs.	1 character	8 characters	see text

Operation Mode

Parameter Type	Use	Possible Values	Default
Client Runtime Control	Indicate operation mode for COR	Normal autodetect COR detects other products and switches itself off if none are found Enable without products COR remains active, even if no other products are detected Disable all COR switches itself off and disables any other active products	Normal autodetect

Activity pulse

Parameter Type	Use
Client Runtime Control	You can use a System Coordinator daemon to enable “single-seat” display of session activities in any client job. To enable a client job for this feature, specify: ■ The group in which the daemon runs. When you choose to make these statistics available externally a daemon is required. During periods when the daemon is unavailable (planned or unplanned outage) statistics are unavailable. ■ The frequency at which statistics are pulsed to the daemon: ■ Every <i>nnnnnnnn</i> Adabas calls and/or ■ Every <i>nnnnnn</i> seconds Set both to zeroes to disable the refresh. The statistics are held in shared memory, so you must configure your daemon to use shared memory (refer to <i>Considerations and Configuration for using a Daemon in the Adabas System Coordinator Operations and Programming Guide</i> for information on configuring the daemon to use shared memory). Note: For dynamic transaction routing (DTR) systems (CICS/MRO, CICS/PLEX, IMS/TM) you must always specify a group, even if you do not want to make use of “single-seat” activity displays. This is because the System Coordinator daemon is also responsible for managing DTR client sessions while they are at rest.

Daemon connection messages

Parameter Type	Use	Possible Values	Default
Client Runtime Control	Indicates whether or not the client job should issue daemon-related connection information messages; COR060I, COR061I, COR075I, COR076I.	Y N	N

API Runtime Overrides

Parameter Type	Use	Possible Values	Default
Client Runtime Control	Indicates whether controls can be dynamically overridden at runtime via a customised API call to COR. Note: This feature is not currently supported.	Y N	N

Threadsafe operation

Parameter Type	Use
Client Runtime Control	This parameter is only applicable to runtime controls of type CICS and CICS/DTR and specifies whether or not the System Coordinator client environment runs in CICS threadsafe mode. When running in threadsafe mode the installation recommendations to make COR modules available in DFHRPL will be enforced. (Refer to the <i>Installation Procedures</i>). Note: The Debug Event Monitor and local DDMSG files are disabled when running in threadsafe mode. If you wish to use either of these facilities, set the “Threadsafe operation” runtime control to N and then set it back after you have finished.

Use Additional Exits

Parameter Type	Use	Default
Client Runtime Control	Enables calling of additional installation exits (IEXIT1, IEXIT2) before and after the Adabas command. Refer to <i>Before You Install</i> in the Installation section for information about installing additional exits.	N

Maximum Idle Time

Parameter Type	Use	Possible Values	Default
Client Runtime Control	Indicates a time limit after which terminal sessions are eligible for timeout termination if no activity has occurred.	0 - nnnnnnnnn seconds A value of “0” means no time limit.	For job types where there are Terminal Sessions the default value is 3600. For all other job types the default value is 0.

Non-Terminal Idle Time

Parameter Type	Use	Possible Values	Default
Client Runtime Control	Indicates a time limit after which non-terminal sessions are eligible for timeout termination if no activity has occurred. Note: This parameter is now redundant. Resources used by non-terminal tasks are automatically released at task end.	0 - nnnnnnnnn seconds A value of “0” means no time limit.	none

Generate RSP009/79

Parameter Type	Use	Possible Values	Default
Client Runtime Control	Indicates a time limit for sessions that are timed out to receive response code 9, subcode 79 if they are re-activated. Specifies a number of seconds after which response code 9, subcode 79 will no longer be returned to re-activated sessions that were previously timed out. 0 means that response code 9, subcode 79 is always returned to sessions that were previously timed out, no matter how much time has passed since they were timed out.	Y N (enable or disable RSP009/79 setting) 0-nnnnnnnnnnn (time limit for setting RSP009/79)	Y 0

Latency Controls

Parameter Type	Use
Client Runtime Control	Specify where session-related information is stored when sessions are at rest. Latency – Local (Y/N) For standard job types, this is set to Y by default so that session-related information resides in the job's private memory. TSQ prefix For CICS, temporary storage queues are required and you can specify an optional prefix for the queue name. The default prefix is "COR" followed by a hexadecimal "FF". On z/OS systems the queue name includes the CICS job-name to ensure that it is unique in a multi-job CICS system. However, the CSD TSMODEL definition for these temporary storage queues should not specify a POOLNAME or REMOTESYSTEM, as they cannot be shared.
	Latency – Daemon (Y/N) Daemon managed latency is required by dynamic transaction routing (DTR) systems (eg. CICS/MRO, CICS/PLEX or IMS). For these jobs, Daemon managed latency is enforced (Y) as is Group name. For any other job type the default value is N and you should only change this if advised by support. When this parameter is set to Y, by default, the session-related information is maintained in the local daemon's private memory. For performance you are strongly recommended to use daemon shared memory (see daemon group member parameter Daemon latency/pulse services). To Disk (Y/N) The default value for this parameter is N. This parameter is only applicable when "Latency - Daemon" (see above) is set to Y indicating at rest session-related information is to be managed by the daemon. Setting this parameter to Y

Parameter Type	Use
	notifies the Daemon that this session-related information is to be maintained in the COLAT daemon latency disk file. In order to use this option the daemon group parameter <i>Full Crash Recovery Disk File</i> must be set to Y.

Enable CICSplex DTR

Parameter Type	Use	Possible Values	Default
Client Runtime Control	This option is offered for CICS (DTR) services only. A value of 'Y' should be set if the CICS (DTR) service is eligible for dynamic transaction routing across multiple systems (i.e., CICSplex). When using this option, the Adabas System Coordinator daemon must also be configured appropriately. For more information, refer to the section <i>Multi-system dynamic transaction routing</i>.	Y N	N

Site Information Menu Function

Parameter Type	Use
Client Runtime Control – Information Menu option	Used to define up to 256 bytes of alphanumeric data, which is stored with the runtime control definition and may be retrieved at runtime using the site information API. Refer to <i>API To Retrieve Runtime Control Site Information</i> for more information.

Transaction, Stepname or Login Override (Override function)

Parameter Type	Use	Possible Values
Client Runtime Control – Override Menu option	Used to define runtime overrides of the basic control for the job. After definition the override can be modified with the Modify menu option.	Depending on Job Type, Stepname, Login or Transaction overrides can be defined. Note: The override name must start with one or more alphanumeric characters but it may also optionally end with a wildcard (*). For example, if an override should apply to all transactions that start with the character "A" then the override name should be defined as "A*".

Cleanup at Start, Cleanup at End

Parameter Type	Use	Possible Values	Default
Client Runtime Control Override	Indicate whether session cleanup is required when a session override is activated (Cleanup at Start) or deactivated (cleanup at End).	Y N	N

Message Controls

Parameter Type	Use	Possible Values	Default
Client Runtime Control	Indicates where messages are written. If you elect to use a DDMSG file, you must select “Forward to the Daemon DDMSG file” for TP systems because sequential files are not suited to TP. If you select “Local DDMSG file” for batch type systems, you must add the Adabas load library to the job’s loading environment. The DDMSG file should be defined as fixed records of length 133, with an appropriate blocksize. It is possible that operating system factors (such as blocking, caching) may cause messages not to be seen until the job terminates.	Console message job log Local DDMSG file Forward to the Daemon DDMSG file	Console

Command Retry

Parameter Type	Use	Default
Client Runtime Control	Allows automatic retry of Adabas commands that receive the specified response codes. You can also ■ restrict retry to particular sub-codes ■ restrict it to certain database ids and file numbers ■ specify the number and frequency of retry attempts ■ specify whether or not command retry should cause a console message to be issued ■ specify whether or not retried commands should be shown to user exits	None

Debug Settings

Parameter Type	Use	Default
Client Runtime Control	Define client debug events. For more information, refer to the section <i>Using the Client Event Debug Monitor</i> in the <i>Adabas System Coordinator Operations and Programming Guide</i> .	None

Unified Trace Settings

Parameter Type	Use	Default
Client Runtime Control	Define unified trace settings. For more information, refer to the section <i>Using the Unified Trace</i> in the <i>Adabas System Coordinator Operations and Programming Guide</i> .	None

Site-dependent controls

Parameter Type	Use	Possible Values	Default
Client Runtime Control	You can define two eight-character runtime controls for your own use. By default the controls are called "Area" and "System". They can be specified for jobs, overrides and dynamically and are shown in the Adabas Client Activities displays.	Anything	None

Review

Parameter Type	Use	Possible Values	Default
Client Runtime Control	Controls whether or not the REVEXIT1 link module component of the Adabas Review performance monitor is to be called. This control is only available for Com-plete, CICS and Batch/TSO systems and is only honored if the link module globals table was assembled with the option REVIEW=COR. This control can be overridden and can also be changed dynamically via the SYSCOR Current Activities "Controls" task or by use of Natural or 3GL APIs (refer to <i>API to Modify Runtime Controls</i>).	Y N	N

Client Monitor

Parameter Type	Use	Possible Values	Default
Client Runtime Control	Controls whether or not the Adabas Review client monitoring component REVEXIT2 is to be called. This control is only available for CICS and Batch/TSO systems and is only honored if the link module globals table was assembled with the options REVIEW=YES or COR and RVCLNT=COR. If REVIEW=COR, this control is only honored if the Review client runtime control is also set to Y. This control can be overridden and can also be changed dynamically via the SYSCOR Current Activities “Controls” task or by use of Natural or 3GL APIs (refer to <i>API to Modify Runtime Controls</i>).	Y N	N

3

Daemon Parameters

■ Daemon Group Parameters	16
■ Daemon Group Member Parameters	19

Daemon parameters are used to define the environment and operational requirements for Adabas System Coordinator daemons. *Daemon Group Parameters* apply to all daemons in that group. *Daemon Group Member Parameters* and *Daemon Runtime Parameters* apply to individual daemons and may differ from one daemon to another in the group.

- *Daemon Group Parameters*
- *Daemon Group Member Parameters*
- *Daemon Runtime Parameters*

Daemon Group Parameters

Daemon group parameters are used to define the Adabas System Coordinator daemon environment.

Daemon Group Parameters
Daemon Group Name
Daemon SVC
System Type
Full crash recovery disk file
Messages - database
Messages - daemon
Sysplex Cache Structure Name

Daemon Parameters Descriptions

This section describes the daemon parameters.

Daemon Group Name (Daemon Group Parameter)

Parameter Type	Use	Default
Daemon Group	The daemon group name is used to control communication between Adabas System Coordinator daemon peers in an operating system cluster. For example, the peer daemons communicate using an XCF group with this name in an IBM parallel sysplex.	none

Daemon SVC

Parameter Type	Use	Default
Daemon Group	The router (SVC) number that is used for communicating with the group. This same number must be used by all daemon group members.	none

System Type

Parameter Type	Use	Possible Values	Default
Daemon Group	Type of coordination to be performed by the daemon group Possible values are: ■ Standard single-system: A single system is to be coordinated. This system type includes support for: ■ Adabas Fastpath ■ Adabas Transaction Manager ■ <i>Single-seat current activity displays</i> ■ <i>Single-system dynamic transaction routing</i> ■ Standard multi-system using XCF: Multiple systems are to be coordinated using XCF for cross-system communications. This system type includes support for: ■ Standard single-system (see above) ■ Adabas Fastpath in a distributed system environment ■ Adabas Transaction Manager in a distributed system environment ■ <i>Multi-system dynamic transaction routing</i> ■ Standard multi-system using Net-Work: This option is only applicable if multiple systems cannot be connected using XCF.	Single Multi-XCF Multi-Net-Work	none

Full Crash Recovery Disk File

Parameter Type	Use	Possible Values	Default
Daemon Group	Indicates whether session-related information for client jobs managed by this daemon group can be optionally maintained in the COLAT daemon latency disk file This feature enables appropriately defined client sessions, at rest at the time of a daemon failure, to resume processing after the daemon has restarted. Refer to the client runtime control <i>Latency Controls</i> for information on how to enable a client job to use this option.	Y N	N

Messages – database

Parameter Type	Use	Possible Values	Default
Daemon Group	Indicates the destination for database messages written by the Adabas System Coordinator component in the database (including messages written by products which use its services). Database messages, by default, are written to the console. Additionally, or instead of, these messages may be directed to a disk file by selecting the DDSMG file option. The DDMSG file must be specified in the database execution control script and should be defined as fixed records of length 133, with an appropriate blocksize. It is possible that operating system factors (such as blocking, caching) may cause all messages not to be seen until the database terminates.	Console message job log Local DDMSG file in the database job	Console

Messages – daemon

Parameter Type	Use	Possible Values	Default
Daemon Group	Indicates the destination for messages written by the Adabas System Coordinator daemon (including messages written by products which use its services). Daemon messages, by default, are written to the console. Additionally, or instead of, these messages may be directed to a disk file by selecting the DDSMG file option. The DDMSG file must be specified in the daemon execution control script and should be defined as fixed records of length	Console message job log Local DDMSG file in the daemon job	Console

Parameter Type	Use	Possible Values	Default
	133, with an appropriate blocksize. It is possible that operating system factors (such as blocking, caching) may cause all messages not to be seen until the daemon terminates.		

Sysplex Cache Structure Name

Parameter Type	Use	Default
Daemon Group	Indicates whether session-related information for client jobs of type CICS (DTR) - managed by this daemon group - should be maintained in the Sysplex cache structure of the specified name. This facility enables such client sessions to operate within a CICSplex environment. Refer to the client runtime control Enable CICSplex DTR for information on how to enable a client job of type CICS (DTR) to use this facility. For additional information, refer also to the section <i>Multi-system dynamic transaction routing</i>. The specified cache structure name should be sized according to the following formula: Cache Structure size (k) = $n/4$ where n is the maximum number of client sessions eligible for CICSplex DTR across all client jobs of type CICS (DTR) managed by this daemon group.	none

Daemon Group Member Parameters

Daemon Group Member Parameters
Daemon job name
Node id
Recovery
Daemon latency/pulse services
Unified trace settings
Debug settings

Daemon Job Name

Parameter Type	Use	Default
Daemon Group Member	The job name under which this daemon executes. This is the name of the job or started task as known to the operating system.	none

Node id

Parameter Type	Use	Default
Daemon Group Member	Daemons sign on as targets to the Adabas router. Specify the node id to be used by the daemon. This node id must be unique across all your systems.	none

Recovery

Parameter Type	Use	Possible Values	Default
Daemon Group Member	Setting Continuous Operation to “Y” causes the daemon to intercept failures, react by automatically terminating and restarting the appropriate component(s) and then continuing. Setting Continuous Operation to “N” causes the daemon to react to a failure by terminating. You are recommended always to set Continuous Operation to “Y”.	Y N	N

Daemon latency/pulse services

Parameter Type	Use	Possible Values	Default
Daemon Group Member	Defines the shared memory limits for holding at-rest session-related information and also activity information for jobs defined to use activity pulsing. Shared memory is mandatory if you want to use activity pulsing (see Client Runtime control Activity pulse) and is recommended for dynamic transaction routing (DTR) systems (eg. CICS/MRO, CICS/PLEX or IMS) that require daemon latency for performance and resilience (see Client Runtime control Latency controls). The required shared memory area size depends on the number of sessions, the installed product mix and configuration, and the nature of the	0 – 2097151 Valid dataspace name.	none

Parameter Type	Use	Possible Values	Default
	application workload and also on how extensively you use activity pulsing. If the shared memory area is not large enough, the daemon will transparently use its own local memory for DTR systems latency. You should monitor the shared memory area usage with the DRES daemon operator command which shows the maximum, current and highwater-mark allocations for Shared Memory. This shared memory will be allocated as a dataspace of the specified name. For more information on shared memory requirements, refer to <i>Considerations and Configuration for using a Daemon in the Adabas System Coordinator Operations and Programming Guide</i>.		

Unified trace settings

Parameter Type	Use	Possible Values	Default
Daemon	Define unified trace settings. For more information, refer to the section <i>Using the Unified Trace in the Adabas System Coordinator Operations and Programming Guide</i> .	Refer to <i>The Daemon Unified Trace in the Adabas System Coordinator Operations and Programming Guide</i> .	None

Debug settings

Parameter Type	Use	Possible Values	Default
Daemon	CORDUMP for transient situations...Some internal communications (for example) may suffer intermittent, transient failure. System Coordinator automatically tolerates and recovers from these issues without problem. However, sometimes support may ask that diagnostics are taken when investigating a problem by requiring this setting to be Y.	N Y	N
	Number of outputs...when diagnostics are being taken it is possible (and wise) to limit the number of times diagnostics are taken using this number.	0-65535	0

