

# Using Special Functions

This document describes certain ETP maintenance functions that are not performed often, if at all; some of these are operations that should only be performed after careful consideration.

This chapter covers the following topics:

- Special Functions Screen
- Display Transactions
- Delete Transactions
- Modify Confirmation File
- Modify System Profile
- Modify User Profile
- Check Definitions for Performance Problems
- Change Administration File

## Special Functions Screen

By either entering the SPecial direct command or selecting the S option on the ETP main menu, the Special Functions screen appears.

### The Special Functions Screen

```

23:59:59          ***** ENTIRE TRANSACTION PROPAGATOR *****          2000-12-24
                    Special Functions

                DI Display transactions
                DE Delete transactions
                MC Modify confirmation file time stamp
                MS Modify system profile
                MU Modify user profile
                CD Check definitions for performance problems
                CA Change to another administration file

Command ==>
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10---PF11---PF12---
                Help  Menu  Exit  Last          Flip          Tech          Canc

```

## Display Transactions

By either entering the Display TRansactions direct command or selecting the DI option on the Special Functions selection menu, the Display Transactions screen appears.

### The Display Transactions Screen

```

23:59:59          ***** ENTIRE TRANSACTION PROPAGATOR *****          2000-12-24
                    Display transactions

Log file .....* _____          _____

Time stamp or time start value for display
Time stamp ..* 0000000000000000>          (hexadecimal value)
Time .....* 1900-01-01 00:00:00.0> (yyyy-mm-dd hh:mm:ss.t)

Mark to display additional data for selected ETs
Control block (CB) ..... _
Format buffer (FB) ..... _
Record buffer (RB) ..... _
CB, FB, RB as selected for all DB operations .. _

Printer name .. _____ (' ' = terminal)

Command ==>
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10---PF11---PF12---
      Help  Menu  Exit  Last          Flip          Tech          Canc

```

By default, a window appears that displays only the ET timestamps of previously logged transactions. If you want the CB (Control Block), RB (Record Buffer), or FB (Format Buffer) to be displayed for the entry, mark the appropriate fields in the screen. To display the marked data for all DB operations, mark the CB, FB, RB... screen entry.

### Screen Field Description

Log file DBID/FNR	Enter the database ID and file number of the log file for which you want transactions displayed. If you use wild card notation for the log file, a window appears which allows you to select a single log file for which the transactions are to be displayed.
Time Stamp	Enter either the hexadecimal ET time stamp to display a specific log file entry, or enter a wild card to display a list of all log file entries having time stamp values that meet the selection criterion. If you enter a value here, do not enter a time value in the next field.
Time	Enter a valid ET date/time to limit the displayed log file entry, or enter a wild card to display a list of all log file entries having time values that meet the selection criterion. If you enter a value here, do not enter a time stamp value in the field above.  <b>Note:</b> Entries in the Time field are first converted to the time stamp value and then back to normal notation. This conversion can result in a value slightly different from the entered value.
Control Block	Mark this field with any non-blank character to display the Adabas Control Block.
Format Buffer	Mark this field with any non-blank character to display the Adabas Format Buffer.
Record Buffer	Mark this field with any non-blank character to display the Adabas Record Buffer.
CB, FB, RB ... for all DB Operations	Mark this selection with any non-blank character if you also want to display the data selected in the above fields for all STORE, UPDATE and DELETE operations.
Printer Name	To print out the log file entries, enter a valid printer ID here. Leaving this field blank causes the information to be displayed on your terminal.

## Delete Transactions

By either entering the DElete TRansactions direct command or selecting the DE option on the Special Functions selection menu, the Delete Transactions screen appears.

### The Delete Transactions Screen

```

23:59:59          ***** ENTIRE TRANSACTION PROPAGATOR *****          2000-12-24
                        Delete transactions

                                DBID          FNR
Log file .....* _____ _____

Time stamp or time start value for display
Time stamp ..* 0000000000000000>          (hexadecimal value)
Time .....* 1900-01-01 00:00:00.0> (yyyy-mm-dd hh:mm:ss.t)

Command ==>
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10---PF11---PF12---
      Help  Menu  Exit  Last          Flip          Tech          Canc
    
```



**Warning:**

**The "Delete Transactions" function allows you to remove log file entries that *have not been completed* as well as those that have. Removing uncompleted transactions can cause loss of master/replicate file integrity. To remove only completed transactions, use the Clean Up Log File function.**

Selection of transactions is restricted to the entries for a single log file. If you use wild card notation for the log file, a window appears which allows you to select a single log file for which the transactions are to be displayed.

**Screen Field Description**

Delete Entries for Log	Enter the database ID and file number of the log file for which File DBID/FNR transactions are to be deleted. If you use wild card notation for the log file, a window appears which allows you to select a single master file for which the transactions can be deleted.
------------------------	---

The following Time Stamp and Time fields allow you to select transactions to be deleted, either individually or after a specific time:



```

23:59:59          ***** ENTIRE TRANSACTION PROPAGATOR *****          2000-12-24
                    Modify confirmation file time stamp

Replicate file ..*  _____  _____
                    DBID          FNR

Time stamp or time value of confirmation file

Time stamp .. _____ (hexadecimal value)
Time ..... _____ (yyyy-mm-dd hh:mm:ss.t)

Command ==> _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10---PF11---PF12---
      Help  Menu  Exit  Last          Flip          Tech          Canc

```

When the screen is first displayed, all fields except the replicate file DBID/file number are protected against updating. After you enter a valid DBID/file number, those fields are then protected against updating, but all other fields can be changed. To change your original DBID/file number selection, you must exit and then reselect the screen.

### Screen Field Description

Replicate file DBID/FNR	Enter the database ID and file number of the replicate file whose confirmation file time stamp you want to modify. If you enter a wild card in either the database ID or file number field, a window appears from which you can select a single replicate file definition whose time stamp you want to modify.
Time stamp	Enter a valid time stamp for the confirmation file. If you enter a time stamp value here, do not enter a date/time value in the next field. The initial value of this field is the current time stamp of the confirmation file.
Time	Enter a valid date/time value for the confirmation file. If you enter a date/time value here, do not enter a date/time value in the previous field. ETP converts any time value you enter to a hexadecimal time stamp value, which ETP uses for all comparisons.  <b>Note:</b> Entries in the Time field are first converted to the time stamp value and then back to normal notation. This conversion can result in a value slightly different from the entered value.

# Modify System Profile

The ETP operating profile, defined when the administration file is first installed, permits you to set parameters that apply to all definitions contained in the administration file.

## The Modify System Profile Screen

```

23:59:59          ***** ENTIRE TRANSACTION PROPAGATOR *****          2000-12-24
                          Modify system profile

Parameters for program start after master file ET

Name of program to be started ..... HUGO____
Terminal ID (used for CICS only) ..... NOWHERE_

Verify transaction consistency during logging .. N (N/Y)

Command ==>
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help  Menu  Exit  Last      Flip              Tech              Canc
    
```

By either entering the Modify Sysprof direct command or selecting the MS task on the Special Functions menu, the Modify System Profile screen. The screen fields and their possible settings are:

### Screen Field Description:

Parameters for program start after master file ET:

Name of Program	Specify the name of the user program you want ETP to run after to be Started each ET command performed on a master file. The master file's definition (see Add Master File Definition screen or Modify Master File Definition screen) must enable the user program call. Only one user program can be defined. For more information, see ET-Time User Program.
Terminal ID	(CICS only) Specify the terminal ID when the user program defined above runs under CICS.
Verify transaction consistency	If, during logging, you want ETP to verify that all master files during logging updated in the same transaction have the same log file assigned, specify "Y". If multiple master files with different log files are updated by a single transaction, the consistency of the transaction during replication cannot be preserved. If you specify "N" (no, the default), transaction consistency is not checked.

## Modify User Profile

Certain ETP maintenance utility tasks display confirmation windows before executing. These Are you sure? . . . windows are always displayed for those functions unless you disable them for the individual user's profiles. This "Modify User Profile" function lets you control the various confirmation windows.

By either entering the Modify Userprof direct command or selecting the MU task on the Special Functions menu, the Modify User Profilescreen appears. The screen fields and their possible settings are:

### The Modify User Profile Screen

```

23:59:59          ***** ENTIRE TRANSACTION PROPAGATOR *****          2000-12-24
                          Modify user profile

Profile for user HAL

Display a window before EXIT, CANCEL, MENU .. Y (Y/N)
Display a window before DELETE, RESET..... Y (Y/N)
Display a window before SAVE, EXECUTE ..... Y (Y/N)

Command ==>
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help  Menu  Exit  Last          Flip          Tech          Canc

```

#### Note:

The default values shown in the figure above are the original values effective at installation for all users, and are displayed when you first select the screen. The field descriptions below describe how to display the current settings for a specific user.

### Screen Field Description



Display a window before EXIT, CANCEL, MENU	Enables the confirmation window before the current EXIT screen, CANCEL, and MENU (return to the main menu) functions. An example of a confirmation window that appears, if enabled (Y), is shown under the heading <i>Dialogue Functions</i> .
Display a window before DELETE, RESET	Enables the confirmation window before one of the following objects is actually deleted; - master file definition - replicate file definition - logged transactions in the log file - the in-use or error indication is reset for a replicate file
Display a window before SAVE, EXECUTE	Enables the confirmation window before either the SAVE (current data) or EXECUTE (specified program).

The following applies:

- When the EXIT or MENU dialogue functions are executed and the confirmation window is disabled, any selected functions are performed directly before the dialogue functions are performed.
- When the CANCEL dialogue function is executed and the confirmation window is disabled, any selected functions are **not** performed before the CANCEL dialogue function is performed.
- When the confirmation window for deleting or resetting objects is disabled, the objects are deleted or the flags are reset directly before any dialogue function or direct command is performed.
- When the SAVE or EXECUTE confirmation window is disabled, the dialogue functions are performed.
- Direct commands imply execution of the EXIT dialogue function.

## Check Definitions for Performance Problems

To check your master and replicate file definitions for potential performance problems, use the Check Definitions... function. "Potential" problems are problems that are reported by the function but that may not actually occur due to, say, a low update frequency of the log file. However, the hints given by the Check definitions... function should be checked carefully.

### The Change Administration File Screen

```

23:59:59          ***** ENTIRE TRANSACTION PROPAGATOR *****          2000-12-24
                    Check definitions for performance problems

Display definition xref .. N (Y/N)
Printer name .....

( ' ' = terminal)

Command ==>
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help  Menu  Exit  Last          Flip                Tech                Canc

```

By either entering the CHEck Definitions direct command or selecting the CD task on the Special Functions menu, the Change Administration File screen appears.

### Screen Field Description

Display definition xref	If Y (yes) is specified, all master and replicate file definitions are summarized to show their relationships and to give an overview.
Printer Name	To print out the check results, enter a valid printer ID here. Leaving this field blank causes the information to be displayed on your terminal.

## Change Administration File

Use the "Change Administration File" function to specify a new administration file for the ETP environment. You can use this function to switch back and forth among different administration files from within the same application at a single node.

By either entering the CHAnge Administration direct command or selecting the CA task on the Special Functions menu, the "Change Administration File" screen appears.

### The Change Administration File Screen

```

23:59:59          ***** ENTIRE TRANSACTION PROPAGATOR *****          2000-12-24
                          Change administration file

Current administration file ...      DBID      FNR
                                   10         152
New      administration file .. _____

Command ==>
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help Menu Exit Last          Flip          Tech          Canc

```

### Screen Field Description

Current administration file DBID/FNR	These fields show the database ID and file number of the administration file that is currently active.
New administration file DBID/FNR	Enter the database ID and file number of the file you want to become the new administration file.