

Object List - LIST Workplan

An object list is a Workplan of the type LIST, which specifies object selection criteria for the objects to be processed in the UNLOAD, LOAD or FIND command. An object list can be used as an alternative to the *select-clause* and the SELECTION Workplan.

The following syntax applies to an object list:

```
TYPE LIST
{ object-type-and-location (object-name-description ...) } ...
```

The syntactical options are explained in the following section. The keywords and variable values contained in the syntax diagrams shown in this section represent parameters that are used to specify object selection criteria. If indicated, a variable value must be supplied with a keyword. Each syntax element (except for the ones enclosed in parentheses) must start on a new line and end on the same line.

For explanations of the keywords contained in the syntax diagrams, refer to the section *select-clause*.

- Syntax of object-type-and-location
- Syntax of object-name-description
- Example of an Object List

Syntax of *object-type-and-location*

The syntax diagrams that apply to *object-type-and-location* are shown in the following section.

- Natural Objects and DDMs
- Natural System Error Messages
- Natural Command Processor Sources
- Natural-Related Debug Environments
- Natural-Related Profiles
- Natural-Related DL/I Subfiles
- FDTs

Natural Objects and DDMs

```

LIBRARY library-name
[
  DBID dbid FNR fnr [NAME vsam-name] [CIPHER cipher] [
    {
      PASSWORD
      PSW
    } password
  ]
]
[ OBJTYPE group-type ]

```

Notes:

1. No ranges are allowed for *library-name*.
2. For DDMs, OBJTYPE must be set to D.

Natural System Error Messages

```

ERROR NATERROR
[
  DBID dbid FNR fnr [NAME vsam-name] [CIPHER cipher] [
    {
      PASSWORD
      PSW
    } password
  ]
]

```

Natural Command Processor Sources

```

PROCESSOR npc-library-name
[
  DBID dbid FNR fnr [NAME vsam-name] [CIPHER cipher] [
    {
      PASSWORD
      PSW
    } password
  ]
]

```

Note:

No ranges are allowed for *npc-library-name*.

Natural-Related Debug Environments

```

NATPATH DEBUG
LIBRARY library-name
[
  [
    DBID dbid [FNR fnr]
  ] [NAME vsam-name] [CIPHER cipher] [
    {
      PASSWORD
      PSW
    } password
  ]
]

```

Natural-Related Profiles

```

NATPATH PROFILE
[ [ DBID dbid [FNR fnr] ] [NAME vsam-name] [CIPHER cipher] [ { PASSWORD } password ] ] ]

```

Natural-Related DL/I Subfiles

```

NATPATH SUBFILE
[ [ DBID dbid [FNR fnr] ] [NAME vsam-name] [CIPHER cipher] [ { PASSWORD } password ] ] ]

```

FDTs

```

FDT

```

Syntax of *object-name-description*

The syntax diagrams that apply to *object-name-description* are shown in the following section:

- Natural Objects
- DDMs
- Natural System Error Messages
- Natural Command Processor Sources
- Natural-Related Debug Environments
- Natural-Related Profiles
- Natural-Related DL/I Subfiles
- FDTs

Natural Objects

```

{ object-name [SCKIND object-kind]
  error-number [ SLKIND message-type] [ LANGUAGE languages]
  FMNUM error-number-from TONUM error-number-to [SLKIND message-type] [LANGUAGE languages] }

```

DDMs

object-name

Natural System Error Messages

$$\left\{ \begin{array}{l} \text{error-number} [\underline{\text{SLKIND}} \text{ message-type}] [\underline{\text{LANGUAGE}} \text{ languages}] \\ \text{FMNUM error-number-from TONUM error-number-to} [\underline{\text{SLKIND}} \text{ message-type}] [\underline{\text{LANGUAGE}} \text{ languages}] \end{array} \right\}$$

Natural Command Processor Sources

object-name

Natural-Related Debug Environments

object-name

Natural-Related Profiles

object-name [OBJTYPE *profile-type*]

Natural-Related DL/I Subfiles

object-name [OBJTYPE *subfile-type*]

FDTs

$$\text{DBID } dbid \text{ FNR } fnr [\text{CIPHER } cipher] \left[\left\{ \begin{array}{l} \text{PASSWORD} \\ \text{PSW} \end{array} \right\} password \right]$$

Example of an Object List

The following is an example of a Workplan of the type LIST:

```
TYPE LIST
  LIBRARY LIB-1 OBJTYPE N      /* process Natural objects from library 'LIB-1'
    ( A* SCKIND S              /* all sources objects whose names start with 'A'
      B1                        /* source and/or cataloged object of 'B1'
      CDE> SCKIND C )          /* all cataloged objects with names greater than/equal to 'CDE'
    /*                          /* comment line
  LIBRARY LIB-2                /* process Natural objects from library 'LIB-2'
    /*                          /* including error messages and shared resources
    ( *                          /* all source and/or cataloged objects
    /*                          /* including shared resources
  FMNUM 1 TONUM 100           /* error messages from 1 to 100
  )
```