

PROGRAM - Non-Natural Program Receiving Control after Termination

This Natural profile parameter specifies a non-Natural back-end program which is to receive control after the termination of the Natural session.

Possible settings	1-8 characters	Non-Natural back-end program.
	numeric value	Setting a numeric value, for example PROGRAM=0, indicates "no back-end processing". This is particularly relevant when Natural is invoked by a front-end program, because a default may be taken if PROGRAM is blank or not specified; see <i>Front-End Invoked via XCTL</i> in the <i>TP Monitor Interfaces</i> documentation.
Default setting	none	
Dynamic specification	yes	It can also be set dynamically from within a Natural program by calling the Natural subprogram CMPGMSET which is provided in the library SYSEXTP.
Specification within session	yes	
Application Programming Interface	USR4001N (available on mainframes)	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.
	USR6204N (available on all platforms)	

Data for the program specified with the PROGRAM parameter can be supplied with the TERMINATE statement.

For the conventions of calling non-Natural back-end programs, see *Back-End Program Calling Conventions* in the *Operations* documentation.

CICS-Specific Information:

In addition to back-end programs, the Natural CICS interface also supports back-end transactions which may be specified via RET=XXXX or RTI=XXXX or STR=XXXX instead of a program name, with XXXX being a valid CICS transaction ID.

- RET=XXXX or RTI=XXXX indicates that control has to be passed to CICS together with a return transaction ID by a CICS RETURN TRANSID ('XXXX') command.
- RTI=XXXX indicates that control has to be passed to CICS with a return transaction ID by a CICS RETURN TRANSID ('XXXX' IMMEDIATE) command.

- STR=XXXX indicates that a new transaction has to be started by a CICS START TRANSID ('XXXX') TERMID (*INIT-ID), before relinquishing control via a CICS RETURN command.