

# Examples of DEFINE DATA Statement Usage

The following topics are covered:

- Example 1 - DEFINE DATA LOCAL (Direct Data Definition)
  - Example 2 - DEFINE DATA LOCAL (Array Definition/Initialization)
  - Example 3 - DEFINE DATA (View Definition, Array Redefinition)
  - Example 4 - DEFINE DATA (Global, Parameter and Local Data Areas)
  - Example 5 - DEFINE DATA (Initialization)
  - Example 6 - DEFINE DATA (Variable Array)
- 

## Example 1 - DEFINE DATA LOCAL (Direct Data Definition)

```

** Example 'DDAEX1': DEFINE DATA
*****
DEFINE DATA LOCAL
1 #VAR1      (A15)
1 #VAR2
  2 #VAR2A   (N4.1) INIT <1111>
  2 #VAR2B   (N6.2) INIT <222222>
1 REDEFINE #VAR2
  2 #VAR2C   (A2)
  2 #VAR2D   (A2)
  2 #VAR2E   (A6)
END-DEFINE
*
WRITE NOTITLE '=' #VAR2A / '=' #VAR2B /
              '=' #VAR2C / '=' #VAR2D / '=' #VAR2E
*
END

```

### Output of Program DDAEX1:

```

#VAR2A:  1111.0
#VAR2B:  222222.00
#VAR2C:  11
#VAR2D:  11
#VAR2E:  022222

```

## Example 2 - DEFINE DATA LOCAL (Array Definition/Initialization)

```

** Example 'DDAEX2': DEFINE DATA (array definition/initialization)
*****
DEFINE DATA LOCAL
1 #VAR1 (A1/1:2,1:2) INIT (1,V) <'A','B'>
1 #VAR2 (N5/1:2,1:3) INIT (1,2) <200>
1 #VAR3 (A1/1:4,1:3) INIT (V,2:3) <'W','X','Y','Z'>
END-DEFINE
*
WRITE NOTITLE '=' #VAR1 (1,1) '=' #VAR1 (1,2)
           / '=' #VAR1 (2,1) '=' #VAR1 (2,2)
*
WRITE      /// '=' #VAR2 (1,1) '=' #VAR2 (1,2)
           / '=' #VAR2 (2,1) '=' #VAR2 (2,2)
*
WRITE      /// '=' #VAR3 (1,1) '=' #VAR3 (1,2) '=' #VAR3 (1,3)
WRITE      / '=' #VAR3 (2,1) '=' #VAR3 (2,2) '=' #VAR3 (2,3)
WRITE      / '=' #VAR3 (3,1) '=' #VAR3 (3,2) '=' #VAR3 (3,3)
WRITE      / '=' #VAR3 (4,1) '=' #VAR3 (4,2) '=' #VAR3 (4,3)
*
END

```

### Output of Program DDAEX2:

```

#VAR1: A #VAR1: B
#VAR1:  #VAR1:

```

```

#VAR2:      0 #VAR2:      200
#VAR2:      0 #VAR2:      0

```

```

#VAR3:      #VAR3: W #VAR3: W

```

```

#VAR3:      #VAR3: X #VAR3: X

```

```

#VAR3:      #VAR3: Y #VAR3: Y

```

```

#VAR3:      #VAR3: Z #VAR3: Z

```

## Example 3 - DEFINE DATA (View Definition, Array Redefinition)

```

** Example 'DDAEX3': DEFINE DATA (view definition, array redefinition)
*****
DEFINE DATA LOCAL
1 EMPLOY-VIEW VIEW OF EMPLOYEES
  2 NAME
  2 ADDRESS-LINE (A20/2)
  2 PHONE
*
1 #ARRAY      (A75/1:4)
1 REDEFINE #ARRAY
  2 #ALINE    (A25/1:4,1:3)
1 #X          (N2) INIT <1>
1 #Y          (N2) INIT <1>
END-DEFINE
*
FORMAT PS=20

```

```

LIMIT 5
FIND EMPLOY-VIEW WITH NAME = 'SMITH'
  MOVE NAME          TO #ALINE (#X,#Y)
  MOVE ADDRESS-LINE(1) TO #ALINE (#X+1,#Y)
  MOVE ADDRESS-LINE(2) TO #ALINE (#X+2,#Y)
  MOVE PHONE         TO #ALINE (#X+3,#Y)
  IF #Y = 3
    RESET INITIAL #Y
    PERFORM PRINT
  ELSE
    ADD 1 TO #Y
  END-IF
AT END OF DATA
  PERFORM PRINT
END-ENDDATA
END-FIND
*
DEFINE SUBROUTINE PRINT
  WRITE NOTITLE (AD=OI) #ARRAY(*)
  RESET #ARRAY(*)
  SKIP 1
END-SUBROUTINE
*
END

```

### Output of Program DDAEX3:

SMITH	SMITH	SMITH
ENGLANDSVEJ 222	3152 SHETLAND ROAD	14100 ESWORTHY RD.
554349	MILWAUKEE	MONTERREY
	877-4563	994-2260
SMITH	SMITH	
5 HAWTHORN	13002 NEW ARDEN COUR	
OAK BROOK	SILVER SPRING	
150-9351	639-8963	

## Example 4 - DEFINE DATA (Global, Parameter and Local Data Areas)

```

** Example 'DDAEX4': DEFINE DATA (global and local data area definition)
*****
DEFINE DATA
GLOBAL
  USING DDAEX4G
LOCAL
  1 #FIELD1 (A10)
  1 #FIELD2 (N5)
END-DEFINE
*
MOVE 'HELLO' TO #FIELD1
MOVE 123     TO #FIELD2
*
CALLNAT 'DDAEX4N' #FIELD1 #FIELD2
*
END

```

**Global data area DDAEX4G used by Program DDAEX4:**

```
1 GLOBAL-FIELD                A   10
```

**Subprogram DDAEX4N called by Program DDAEX4:**

```
** Example 'DDAEX4N': DEFINE DATA PARAMETER (called by DDAEX4)
*****
DEFINE DATA
PARAMETER
1 #FIELDA (A10)
1 #FIELDB (N5)
END-DEFINE
*
WRITE '=' #FIELDA '=' #FIELDB
END
```

**Output of Program DDAEX4:**

```
Page          1                                05-01-12  08:55:53

#FIELDA: HELLO          #FIELDB:      123
```

**Example 5 - DEFINE DATA (Initialization)**

```
** Example 'DDAEX5': DEFINE DATA (initialization)
*****
DEFINE DATA LOCAL
1 #START-DATE (D)   INIT <*DATX>
1 #UNDERLINE   (A50) INIT FULL LENGTH <'_'>
1 #SCALE      (A65) INIT LENGTH 65 <'....+..../'>
END-DEFINE
*
WRITE NOTITLE #START-DATE (DF=L)
              / #UNDERLINE
              / #SCALE
END
```

**Output of Program DDAEX5:**

```
2005-01-12
-----
....+..../....+..../....+..../....+..../....+..../....+..../....+
```

**Example 6 - DEFINE DATA (Variable Array)**

```
** Example 'DDAEX6': DEFINE DATA (variable array with (1:V))
*****
DEFINE DATA LOCAL
1 #ARRAY   (A1/1:10)
1 #MAX-ARR (P3)
END-DEFINE
*
#ARRAY (1) := 'R'
#ARRAY (2) := 'E'
#ARRAY (3) := 'D'
#MAX-ARR := 4
*
WRITE #ARRAY(*)
```

```

*
CALLNAT 'DDAEX6N' #ARRAY(1:4) #MAX-ARR
*
WRITE #ARRAY(*)
*
*
#MAX-ARR := 5
*
CALLNAT 'DDAEX6N' #ARRAY(1:5) #MAX-ARR
*
WRITE #ARRAY(*)
*
END

```

### Subprogram DDAEX6N called by Program DDAEX6:

```

** Example 'DDAEX6N': DEFINE DATA (variable array with (1:V))
*****
DEFINE DATA
PARAMETER
1 #STRING (A1/1:V)
1 #MAX (P3)
END-DEFINE
*
IF #MAX = 4
  MOVE 'B' TO #STRING (1)
  MOVE 'L' TO #STRING (2)
  MOVE 'U' TO #STRING (3)
  MOVE 'E' TO #STRING (4)
END-IF
*
IF #MAX = 5
  MOVE 'W' TO #STRING (1)
  MOVE 'H' TO #STRING (2)
  MOVE 'I' TO #STRING (3)
  MOVE 'T' TO #STRING (4)
  MOVE 'E' TO #STRING (5)
END-IF
END

```

### Output of Program DDAEX4:

Page 1

05-01-12 09:06:43

R E D  
B L U E  
W H I T E