

Context Menu

This chapter covers the following topics:

- Description
 - Attributes for Context Menu
 - Events
-

Description

The context menu allows you to define menus which appear when the user clicks a dialog or dialog element with the right mouse button. You can retrieve the position of the click via the INQ-CLICKPOSITION action, should this be necessary.

Context menus are defined separately from the dialog elements and associated with the relevant dialog element(s) via the CONTEXT-MENU attribute. The context menu can be modified before it is displayed via the Before-Open Event.

The context menu is constructed and handled almost identically to the submenu control. Like the submenu control, a context menu can contain menu items which open up submenus when selected. Each submenu in such a multi-level context menu receives its own Before-Open Event each time the submenu is displayed.

Attributes for Context Menu

Attribute Name	Query	Set/Modify	In Attr. Window
CLIENT-DATA	X	X/X	
CLIENT-HANDLE	X	X/X	
CLIENT-KEY	X	X/X	
CLIENT-VALUE	X	X/X	
CONTROL	X	-/-	
ENABLED	X	X/X	X
FIRST-CHILD	X	-/-	
HELP-ID	X	X/X	
LAST-CHILD	X	-/-	
PARENT	X	X/-	
PREDECESSOR	X	-/-	
STYLE	X	X/-	X
SUCCESSOR	X	-/-	
SUPPRESS-BEFORE-OPEN-EVENT	X	X/X	
TYPE	X	X/-	

Events

Before-Open Event (may be suppressed).