

# SUPPRESS-DRAG-DROP-EVENT

Determines whether or not the Drag-Drop Event will be suppressed for the dialog or dialog element. If it is suppressed, the dialog or dialog element will not get control when a drop occurs over the dialog or dialog element during a drag-drop operation.

For OLE drag-drop operations, the status of this attribute also determines whether a drop is currently possible when the dialog or dialog element is defined as a drop target (see the DROP-MODE attribute) and the drag cursor enters or traverses the area occupied by the dialog or dialog element during a drag-drop operation. If it is suppressed, a "no drop" drag cursor is displayed and no drop is allowed, even if the DROP-MODE attribute value would otherwise allow it. Therefore, by dynamically updating the status of this attribute during a drag-enter and/or drag-leave event, you can temporarily inhibit or allow a drop depending on the current context (e.g., position within the dialog or dialog element).

<b>Applies to</b>	ActiveX control, bitmap control, control box control, dialog (all types), edit area control, list box control, list view control, tree view control.
<b>Data Type</b>	I4
<b>Default Value</b>	1 (SUPPRESSED)
<b>Possible Values</b>	0 (NOT-SUPPRESSED) / 1 (SUPPRESSED)

**Note:**

You can use the symbols SUPPRESSED and NOT-SUPPRESSED defined in the local data area NGULKEY1. NGULKEY1 is automatically included in your application.