BREADCRUMB BREADCRUMB

BREADCRUMB

The BREADCRUMB control represents a horizontal list of links. The number of links and the name of each link is dynamically controlled by the application.

The control always occupies 100% of the given width.

The following topics are covered below:

- Example
- Adapter Interface
- Built-in Events
- Properties

Example

```
Bread Crumbs... 

Books ▶ Computers ▶ Ajax
```

The XML layout definition is:

Adapter Interface

```
DEFINE DATA PARAMETER

1 ITEMS (1:*)

2 STYLE (U) DYNAMIC

2 TEXT (U) DYNAMIC

2 TOOLTIP (U) DYNAMIC

1 ITEMSINFO

2 SELECTEDITEM (I4)

END-DEFINE
```

Built-in Events

value-of-breadcrumbprop.onSelect

Properties

BREADCRUMB Properties

Basic			
breadcrumbprop	Name of the adapter parameter that represents the control in the adapter.	Obligatory	
breadcrumbstyle	control. With the style you can individually influence the rendering of the control. You can specify any style sheet expressions. Examples are: border: 1px solid #FF0000 background-color: #808080 You can combine expressions by appending and separating them with a semicolon. Sometimes it is useful to have a look into the generated HTML code in order to know where direct style definitions are applied. Press right mouse-button in your browser and select the "View	Optional	background-color: #FF0000 color: #0000FF font-weight: bold
pixeldistance	source" or "View frame's source" function. Pixel distance between the links that are rendered.	Optional	1
practuistance	1 IACI distance between the mas that are rendered.	Optional	3
			int-value
comment	Comment without any effect on rendering and behaviour. The comment is shown in the layout editor's tree view.	Optional	