TQMARK - Translate Quotation Marks

This Natural profile parameter controls the translation of a quotation mark (`"`) within a Natural text constant. It takes effect at compilation time only.

Possible settings	ON	Each quotation mark within a text constant is output as a single apostrophe.
	OFF	Quotation marks within text constants are not translated, they are output as quotation marks.
Default setting	ON	
Dynamic specification	yes	
Specification within session	yes	Applicable Statements: `OPTIONS`
		Applicable Command: `TQMARK option of COMPOPT`

Anmerkung:

Do not confuse quotation mark (`"`) with double apostrophes (`''`). Double apostrophes within a text constant are always output as a single apostrophe (`'`), regardless of the setting of the `TQMARK` parameter.

Example 1 (TQMARK=ON):

```
WRITE 'THERE"S A QUOTATION MARK'
```

is displayed as: `THERE'S A QUOTATION MARK`

Example 2 (TQMARK=OFF):

```
WRITE 'THERE"S A QUOTATION MARK'
```

is displayed as: `THERE"S A QUOTATION MARK`

Example 3 (TQMARK=ON or OFF):

```
WRITE 'DOUBLE APOSTROPHES'' OUTPUT IS A SINGLE APOSTROPHE'
```

is displayed as: `DOUBLE APOSTROPHES' OUTPUT IS A SINGLE APOSTROPHE`