INatAutoNatsvar INatAutoNatsvar

INatAutoNatsvar

This chapter covers the following topics:

- Purpose
- Properties

Purpose

Gives access to some of the system variables of a Natural development environment.

Properties

The following properties are available:

- Parent
- Studio
- Language
- SystemVariables

Parent

Used to navigate to the parent interface of this interface.

Natural Data Format	Variant Type	Remark
HANDLE OF OBJECT	VT_DISPATCH (INatAutoEnvironment)	Get only

Studio

Used to navigate to the root interface.

Natural Data Format	Variant Type	Remark
HANDLE OF OBJECT	VT_DISPATCH (INatAutoStudio)	Get only

Language

The system variable *LANGUAGE.

Natural Data Format	Variant Type	Remark
12	VT_I2	Get only

INatAutoNatsvar SystemVariables

SystemVariables

A string containing an XML document that contains the current values of a defined subset of the Natural system variables. For the meaning of the individual system variables, refer to the *System Variables* documentation. In the case of a remote environment, the system variables cannot be delivered and the property contains an empty string.

For the local environment, the XML document is structured according to the DTD provided in the section DTD for INatAutoNatsvar - Local Environment.

Natural Data Format	Variant Type	Remark
A	VT_BSTR	Get only