

Load Style Sheet from the Resource Directory and Apply XSLT Processing on Return Document

Subroutine Name	Executable Example	Viewable Example	Used Resource
W3APPLY-XSLT-XML-TO-DYNAMIC	E3XSLT3	E3XSLT3	E3XSLT3.HTML E3XSLT3.XSL E3XSLT3.XML

Description

Call an XSLT processor and transform the output page with a stylesheet loaded from the resource directory of the given Natural library. If no library is specified, use the current library.

Parameters

```

1 W3XSLT      (A)  DYNAMIC BY VALUE /* i /m : xslt
1 W3XML       (A)  DYNAMIC BY VALUE /* i /m : xml
1 W3RESULT    (A)  DYNAMIC          /* o/m : result
1 W3RESPONSE (I4) OPTIONAL          /* o/o : result

```

If the W3RESPONSE parameter is not specified, the Web Interface error processing is triggered if an error occurs. If the W3RESPONSE parameter is specified, the parameter contains the Natural message number if an error occurred, or zero on success.

How To Invoke

```

PERFORM W3APPLY-XSLT-XML-TO-DYNAMIC W3XSLT W3XML W3RESULT
PERFORM W3APPLY-XSLT-XML-TO-DYNAMIC W3XSLT W3XML W3RESULT W3RESPONSE

```

Restriction

Load Style Sheet and Apply XSLT Processing is available only on Natural for Windows and UNIX supporting non-natural files/resources and that contain the User Exit USR 6001P. Internally uses workfile 12.