

# Info About Internal Values

Subroutine Name	Executable Example	Viewable Example
W3INFO	E3INFO	E3INFO

## Description

This program enables you to set and read some internal values of the Web Interface.

### Read (Action 'R')

The values for ERROR-NR, VERSION, LOG-TIME, FORM, LIST(\*) and LIST\_MAX will be returned.

### Set List (Action 'L')

For H3-OPEN-LIST, H3-CLOSE-LIST and H3-LIST-ITEM, an internal array is used to save the style of the generated list. This style will be used to generate the correct close tag.

### Set Form (Action 'F')

For all programs, you can generate tags that can only be used inside a FORM tag. A flag can be called to check if a FORM is open or not. The flag will be changed by H3-OPEN-FORM and H3-CLOSE-FORM.

## Changes from previous version

The LDA W3PINFO has been changed, and the variables LOG-TIME, VERSION and WEBAPI have been changed to (A) dynamic.

## Parameters

LOCAL USING W3PINFO

## PDA W3PINFO

```

1 ##W3INFO
2 ACTION (A1) /* i /m : Action to be called
2 LOG-TIME (A) DYNAMIC /* o/m : Log time set by the Natural Web Interface
2 VERSION (A) DYNAMIC /* o/m : Version set by the HTTP Server Extension
2 WEBAPI (A) DYNAMIC /* o/m : Version set by the Natural Web Interface
2 ERROR-NR (I4) /* o/m : Error number set by the Natural Web Interface
2 FORM (L) /* io/m : Indicates whether a FORM is open
2 LIST (A1/1:10) /* io/m : Saves the type of LIST
2 LIST_MAX (N2) /* io/m : Current number of nested LISTS

```

## How To Invoke

PERFORM W3INFO ##W3INFO