

# Evaluate Mime-Type and Transfer/Data-Type

Subroutine Name	Executable Example	Viewable Example
W3MIME-DATA MIMEDATA	NAT-RES?source=e3xslt2.xml&lib=sysweb3 NAT-RES?source=composing_natural_logo.jpg&lib=sysweb3	NAT-RES

## Description

Each Program needs to initialize and end the web interface by special programs. The initialisation is done by W3INIT. The W3PARAM PDA must be passed to initialize passed parameters for further use. W3END ends the document and prepares the return to the HTTPserver. The W3PARAM PDA defined at the initial program has to be passed to W3END. If W3\* calls are performed after W3END, the written output will not be transferred to the HTTP server.

## Parameters

### 1. W3INIT

```
USING W3PARAM /* io/m : Parameter of Subprogram
```

### 2. W3END

```
USING W3PARAM /* io/m : Parameter of Subprogram
```

### 3. W3PARAM

```
1 ##RPC
2 VERSION          (A010)      /* i /m : Interface version
2 LOG-TIME         (A030)      /* i /m : Timestamp
2 RETURN_PAGE     (A250/1:V) /* io/m : Transfer area
2 RETURN_PAGE_COUNT (I004)     /* io/m : Bytes sent
2 ERROR-NR        (I004)     /* o/m : Error number
```

## How To Invoke

```
PERFORM W3INIT ##RPC
PERFORM W3END ##RPC
```