

## **Natural for UNIX**

### **Parameter Reference**

Version 6.3.8 for UNIX

February 2010

This document applies to Natural Version 6.3.8 for UNIX.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 1992-2010 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, United States of America, and/or their licensors.

The name Software AG, webMethods and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices and license terms, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". This document is part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

## Table of Contents

1 Parameter Reference .....	1
2 Introduction to Profile Parameters .....	3
Profile Parameter Usage .....	4
Common Profile and Session Parameter Descriptions .....	4
3 Introduction to Session Parameters .....	5
Session Parameter Usage .....	6
How to Set Session Parameters .....	6
Session Parameter Evaluation .....	8
4 ACIVERS - Define ACI Version for Use with EntireX Broker ACI .....	9
5 AD - Attribute Definition .....	11
AD Parameter Syntax .....	12
Field Representation .....	13
Field Alignment .....	14
Field Input/Output Characteristics .....	14
Interpretation of Alphanumeric Fields .....	16
Mandatory Input .....	16
Length of Input Value .....	16
Field Upper/Lower Case Characteristics .....	17
Filler Character .....	17
6 AL - Alphanumeric Length for Output .....	19
7 AUTO - Automatic Logon .....	21
8 AUTORPC - Automatic Natural RPC Execution .....	23
9 BATCH - Batch Mode Simulation .....	25
10 BATCHMODE - Batch Mode .....	27
11 BMBLANK - Display Trailing Blanks .....	29
12 BMCONTROL - Display Control Characters .....	31
13 BMFRAME - Window Frame Characters .....	33
14 BMSIM - Similar Batch Mode Output .....	35
15 BMTIME - Display Process Time .....	37
16 BMTITLE - Display Window Title .....	39
17 BMVERSION - Display Natural Version .....	41
18 BPID - Specify Buffer Pool ID .....	43
19 BPID2 - Specify Secondary Buffer Pool .....	45
20 BPNAME - Name of Natural Global Buffer Pool .....	47
21 BPSFI - Object Search First in Buffer Pool .....	49
22 CC - Error Processing in Batch Mode .....	51
23 CD - Color Definition .....	53
24 CDYNAM - Dynamic Loading of Non-Natural Programs .....	55
25 CF - Character for Terminal Commands .....	57
26 CLEAR - Processing of CLEAR Key in NEXT Mode .....	59
27 CM - Command Mode .....	61
28 CMOBJIN - Batch Input File for Natural INPUT Data .....	63
29 CMPRINT - Batch Output File .....	65

30	CMPRTnn - Additional Report .....	67
31	CMSYNIN - Batch Input File for Natural Commands and INPUT Data .....	69
32	CMWRKnn - Natural Work Files .....	71
33	CO - Compiler Output .....	73
34	COMPR - Set RPC Buffer Compression .....	75
35	CP - Default Code Page Name .....	77
36	CPCVERR - Code Page Conversion Error .....	79
37	CPOBJIN - Code Page of Batch Input File .....	81
38	CPPRINT - Code Page of Batch Output File .....	83
39	CPRPC - Define Code Page Name .....	85
40	CPSYNIN - Code Page of Batch Input File for Commands .....	87
41	CV - Attribute Control Variable .....	89
42	CVMIN - Control Variable Modified at Input .....	91
43	DBSHORT - Interpretation of Database Field Short Names .....	93
44	DBUPD - Database Updating .....	97
45	DC - Character for Decimal Point Notation .....	99
46	DD - Day Differential .....	101
47	DF - Date Format .....	103
48	DFOUT - Date Format for Output .....	105
49	DFS - Specify RPC Client's Default Server Address .....	107
50	DFSTACK - Date Format for Stack .....	109
51	DFTITLE - Output Format of Date in Standard Report Title .....	111
52	DL - Display Length for Output .....	113
53	DO - Display Order of Output Data .....	115
54	DTFORM - Date Format .....	117
55	DU - Dump Generation .....	119
56	DY - Dynamic Attributes .....	121
	DY Parameter Syntax .....	122
	Examples .....	124
57	DYNPARM - Control Use of Dynamic Parameters .....	127
58	ECHO - Control Printing of Batch Input Data .....	129
59	ECPMOD - Entire Connection Protocol Mode .....	131
60	EDITOR - Other Program Editor .....	133
61	EDTBPSIZE - Software AG Editor Buffer Pool Size .....	135
62	EDTLFILES - Number of Software AG Editor Logical Files .....	137
63	EDTRB - Program Editor Ring Buffer .....	139
64	EJ - Page Eject .....	141
65	EM - Edit Mask .....	143
	Syntax .....	144
	Blanks in Edit Masks .....	145
	Default Edit Masks .....	145
	Edit Masks for Numeric Fields .....	146
	Edit Masks for Alphanumeric Fields .....	149
	Edit Masks for Binary Fields - Format B .....	151
	Hexadecimal Edit Masks .....	151

---

Edit Masks for Date and Time Fields - Formats D and T .....	153
Edit Masks for Logical Fields - Format L .....	157
66 EMFM - Edit Mask Free Mode .....	159
67 EMU - Unicode Edit Mask .....	161
68 ENDIAN - Endian Mode for Compiled Objects .....	163
69 ENDMMSG - Display Session-End Message .....	165
70 ES - Empty Line Suppression .....	167
71 ESCAPE - Ignore Terminal Commands %% and % .....	169
72 ESXDB - Database ID Used for Entire System Server DDMs .....	171
73 ET - Execution of END/BACKOUT TRANSACTION Statements .....	173
74 ETA - Error Transaction Program .....	175
75 ETDB - Database for Transaction Data .....	177
76 ETEOP - Issue END TRANSACTION at End of Program .....	179
77 ETID - Adabas User Identification .....	181
78 ETPDB - Databases Containing Entire Transaction Propagator Master Files .....	183
79 ETPSIZE - Size of Entire Transaction Propagator Buffer .....	185
80 FC - Filler Character for INPUT Statement .....	187
81 FC - Filler Character for DISPLAY Statement .....	189
82 FCDP - Filler Character for Dynamically Protected Input Fields .....	191
83 FDDM - Natural System File for DDMs .....	193
84 FDIC - Predict System File .....	195
85 FL - Floating Point Mantissa Length .....	197
86 FNAT - Natural System File for System Programs .....	199
87 FREEGDA - Release GDA in Utility Mode .....	201
88 FS - Default Format/Length Setting for User-Defined Variables .....	203
89 FSEC - Natural Security System File .....	205
90 FUSER - Natural System File for User Programs .....	207
91 GC - Filler Character for Group Headers .....	209
92 GFID - Global Format IDs .....	211
93 HC - Header Centering .....	213
94 HD - Header Definition .....	215
95 HE - Helproutine .....	217
HE Parameter Syntax .....	218
Execution of Helproutines .....	220
Examples .....	220
96 HI - Help Character .....	223
97 HW - Heading Width .....	225
98 IA - Input Assign Character .....	227
99 IC - Insertion Character .....	231
100 ICU - Unicode Insertion Character .....	233
101 ID - Input Delimiter Character .....	235
102 IKEY - Processing of PA and PF Keys .....	237
103 IM - Input Mode .....	239
104 INIT-LIB - Library for Automatic Logon .....	241
105 IP - INPUT Prompting Text .....	243

106 IS - Identical Suppress .....	245
107 KC - Check for Statement Keywords .....	247
108 KCHECK - Check for Statement Keywords .....	249
109 KD - Key Definition .....	251
110 KEY - Setting Assignments to PA, PF and CLEAR Keys .....	253
111 LC - Lower to Upper Case Translation .....	255
112 LC - Leading Characters .....	257
113 LCU - Unicode Leading Characters .....	259
114 LE - Reaction when Limit for Processing Loop Exceeded .....	261
115 LFILE - Logical System File Definition .....	263
LFILE Parameter Syntax .....	265
Example of LFILE Parameter .....	265
116 LOGONRQ - Logon for RPC Server Request Required .....	267
117 LS - Line Size .....	269
Profile Parameter LS .....	270
Session Parameter LS .....	270
Specification with Statements .....	271
118 LT - Limit for Processing Loops .....	273
119 MADIO - Maximum DBMS Calls between Screen I/O Operations .....	275
120 MAINPR - Override Default Output Report Number .....	277
121 MASKCME - MASK Compatible with MOVE EDITED .....	279
122 MAXBUFF - Maximum Buffer Size .....	281
123 MAXCL - Maximum Number of Program Calls .....	283
124 MAXYEAR - Maximum Year for Date/Time Values .....	285
125 MC - Multiple-Value Field Count .....	287
126 MFSET - Multi-Fetch Setting .....	289
127 ML - Position of Message Line .....	291
128 MP - Maximum Number of Pages of a Report .....	293
129 MS - Manual Skip .....	295
130 MSGSF - Display System Error Messages in Short/Full Format .....	297
131 NATLOG - Natural Log File .....	299
Examples .....	300
132 NATVERS - Switching between Natural Environments .....	303
133 NC - Use of Natural System Commands .....	305
134 NCFVERS - NCF File Protocol Version .....	307
135 NENTRY - Left/Right Alignment of Numeric Field Entries .....	309
136 NL - Numeric Length for Output .....	311
137 NOAPPLERR - Suppress Message Number Prefix NAT .....	313
138 NOPROX - Specify Local Domains for Direct Addressing .....	315
139 NOSSLPRX - Specify Local Domains for Direct Addressing SSL .....	317
140 OPF - Overwriting of Protected Fields by Helproutines .....	319
141 OPRB - Database Open/Close Processing .....	321
OPRB String Syntax .....	323
142 PARM - Alternative Parameter File .....	325
143 PC - Control of Personal-Computer Access Method .....	327

144 PC - Periodic Group Count .....	329
145 PCHECK - Parameter Checking for Object Calling Statements .....	331
146 PD - Size of Page Dataset .....	333
147 PM - Print Mode .....	335
Profile Parameter PM .....	336
Session Parameter PM .....	336
148 PRGPAR - Data to be Passed to Program Receiving Control at Termination .....	339
149 PROGRAM - Non-Natural Program Receiving Control after Termination .....	341
150 PROX - Specify URL of Proxy Server .....	343
151 PROXPORT - Specify Port Number of Proxy .....	345
152 PS - Page Size for Natural Reports .....	347
153 PSIGNF - Internal Representation of Positive Sign of Packed Numbers .....	349
154 RCFIND - Handling of Response Code 113 for FIND Statement .....	351
155 RCGET - Handling of Response Code 113 for GET Statement .....	353
156 RDACTIVE - Activate Remote Debugger .....	355
157 RDNODE - Remote Debugger Node Name .....	357
158 RDPORT - Remote Debugger Port .....	359
159 RDS - Define Remote Directory Server .....	361
160 RECAT - Dynamic Recataloging .....	363
161 REINP - Issue Internal REINPUT Statement for Invalid Data .....	365
162 ROSY - Read-Only Access to System Files .....	367
163 RPCSDIR - Library for Service Directory .....	369
164 RTINT - Allow Runtime Interrupt .....	371
165 SA - Sound Terminal Alarm .....	373
166 SB - Selection Box .....	375
Syntactical Considerations .....	376
Runtime Considerations .....	377
167 SD - Time Delay between Two Screens .....	379
168 SERVER - Start Natural Session as an RPC Server Session .....	381
169 SF - Spacing Factor .....	383
170 SG - Sign Position .....	385
171 SHELL - Grant Shell Access to Natural User .....	387
172 SSLPRX - Specify URL of SSL Proxy Server .....	389
173 SSLPRXPT - Specify Port Number of SSL Proxy .....	391
174 SM - Programming in Structured Mode .....	393
175 SNAT - Sound a Bell at Syntax Error .....	395
176 SORTSZE - Size of Sort Buffer .....	397
177 SRETAIN - Retain Source Format .....	399
178 SRVCMIT - Server Commit Time .....	401
179 SRVNAME - Name of RPC Server .....	403
180 SRVNODE - Name of Node .....	405
181 SRVTERM - Server Termination Event .....	407
182 SRVUSER - User ID for RPC Server Registry .....	409
183 SRVWAIT - Wait Time of RPC Server .....	411
184 SSIZE - Size of Source Area Allocated by the Editors .....	413




185 STACK - Place Data/Commands on the Stack .....	415
186 STARTUP - Program Name for System Variable *STARTUP .....	417
187 STEPLIB - Initial Setting for *STEPLIB System Variable .....	419
188 SUBCHAR - Substitution Character for Default Code Page .....	421
189 SUTF8 - UTF-8 Format for Sources .....	423
190 SYMGEN - Generate Symbol Table .....	425
191 SYNERR - Control of Syntax Errors .....	427
192 TC - Trailing Characters .....	429
193 TCU - Unicode Trailing Characters .....	431
194 TD - Time Differential .....	433
195 TF - Translation of Database ID/File Number .....	435
196 THSEP - Dynamic Thousands Separator .....	437
197 THSEPCH - Thousands Separator Character .....	439
198 TIMEOUT - Wait Time for RPC Server Response .....	441
199 TMPSORTUNIQU - Alternate Algorithm for Generating Sort Work File Names .....	443
200 TQ - Translate Quotation Marks .....	445
201 TQMARK - Translate Quotation Marks .....	447
202 TRACE - Define Trace Level for Natural RPC Servers .....	449
203 TRANSP - Server Transport Protocol .....	451
204 TRYALT - Try Alternative Server Address .....	453
205 UC - Underlining Character .....	455
206 UDB - User Database ID .....	457
207 ULANG - User Language .....	459
208 USEDIC - Common Logical Name for Dictionary Servers .....	461
209 USER - User ID .....	463
210 USEREP - Repository Usage .....	465
211 USIZE - Size of User Buffer .....	467
212 WEBIO - Use Natural Web I/O Interface .....	469
213 WFOPFA - Opening of Work Files .....	471
214 WH - Wait for Record in Hold Status .....	473
215 WORK - Work-File Assignments .....	475
216 XADB - Database for Coordination of Transaction Processing .....	477
217 XREF - Creation of XRef Data for Natural .....	479
Extended XRef Data Generation (For Internal Use Only) .....	481
218 YSLW - Year Sliding or Fixed Window .....	483
219 ZD - Zero-Division Check .....	485
220 ZP - Zero Printing .....	487



# 1 Parameter Reference

---

This documentation contains detailed information on the Natural profile and session parameters. It is organized under the following headings:

 <b>Introduction to Profile Parameters</b>	Contains general information on profile parameter usage, including a list of references to related documents.
 <b>Introduction to Session Parameters</b>	Contains general information on session parameter usage and evaluation.
 Parameters in Alphabetical Order	Descriptions of all profile parameters and session parameters in alphabetical order.

General information on using parameters can be found in the *Operations* documentation, see *Profile Parameter Usage*.

---

# 2 Introduction to Profile Parameters

---

- Profile Parameter Usage ..... 4
- Common Profile and Session Parameter Descriptions ..... 4

## Profile Parameter Usage

---

As the use of the Natural profile parameters is different on the platforms supported by Natural, general information about parameter usage is included in the corresponding platform-specific documentation.

See the following documents:

- Profile Parameter Usage in the *Operations* documentation
- Creating a New Parameter File in the *Configuration Utility* documentation
- Overview of Profile Parameters in the *Configuration Utility* documentation

## Common Profile and Session Parameter Descriptions

---

If a Natural session parameter with the same name and functionality as a Natural profile parameter exists, the descriptions of both parameters are combined in a single document.

# 3 Introduction to Session Parameters

---

- Session Parameter Usage ..... 6
- How to Set Session Parameters ..... 6
- Session Parameter Evaluation ..... 8

## Session Parameter Usage

---

In Natural, session parameters are used:

- to specify certain characters,
- to set processing time limits,
- to set a particular response for a given condition,
- to set various size limits,
- to determine various aspects of output reports.

At the installation of Natural, the Natural administrator sets these parameters to default values which are then valid for all users of Natural.

To see which parameter values apply to your session, you enter the system command `GLOBALS` (described in the *System Commands* documentation).

## How to Set Session Parameters

---

Natural session parameters can be set in several ways:

- via the default parameter file `NATPARM`, which is set when Natural is installed;
- via dynamic parameters specified when invoking Natural (as described in your *Natural Operations* documentation);
- via the system command `GLOBALS`;
- via a `SET GLOBALS` statement (in reporting mode only);
- via a `FORMAT` statement;
- via parameter specification within statements where parameters also are evaluated, for example, `INPUT, DISPLAY, WRITE`;
- via terminal commands.

Instead of the parameter values `ON` and `OFF`, you can also specify `T` (true) or `F` (false) respectively.

## Changing Session Parameters at Session Level Using the GLOBALS Command

For your Natural session you can change some of the parameter values set by the Natural administrator.

Within your Natural session, you can change these parameters by issuing the following system command:

### GLOBALS

When you issue the GLOBALS command, a screen is displayed showing the parameter values that are currently in effect for your session. On this screen, you can change the values that do not suit your requirements.

A parameter value set with a GLOBALS command remains in effect until the end of the Natural session (and applies to every object you store during the session), unless you change it again with another GLOBALS command.

## Changing Session Parameters at Program Level Using the FORMAT Statement

You can change certain parameters for the duration of a single program (report). This is done by using a FORMAT statement in the program, which will override the session-wide settings for these parameters.

### Example of a FORMAT Statement:

```
FORMAT AL=10 HC=R
```

Parameters set with a FORMAT statement apply until the end of the executed program, unless they are changed with another FORMAT statement in the program.

Not all session parameters can be changed at program level, while several parameters that can be specified at program level cannot be specified at session level; most of the latter are parameters which affect the format of an output report.

## Changing Session Parameters at Statement Level

Most of the parameters you can change with a FORMAT statement you can also change for an individual statement; for example, for a particular DISPLAY, WRITE, INPUT or REINPUT statement.

This is done by specifying the parameter (in parentheses) after the statement name.

**Example:**

```
DISPLAY (SF=4) NAME JOB-TITLE CURR-CODE SALARY
```

A parameter set at statement level applies only to the statement in which it is specified. The setting at statement level overrides, for that statement only, all other settings of that parameter at other levels.

**Changing Session Parameters at Field Level**

Within a DISPLAY, WRITE, INPUT or REINPUT statement, you can also change some parameters for an individual field or output element.

This is done by specifying the parameter (in parentheses) after the field name.

**Example:**

```
DISPLAY NAME (AL=10) JOB-TITLE CURR-CODE SALARY
```

The parameter value then applies only to that field. The setting at field level overrides, for that field only, all other settings of that parameter at other levels. However, only some of the parameters that can be set at statement level can also be set at field level.

## Session Parameter Evaluation

---

Parameters specified with the statements DISPLAY, FORMAT, PRINT, INPUT, REINPUT, WRITE, WRITE TITLE and WRITE TRAILER are processed during program compilation and are therefore included in the corresponding object module for the program.

The following hierarchy is used for evaluation:

1. Parameters set at element/field (highest priority)
2. Parameters set at statement level
3. Parameters set with a FORMAT statement
4. The default parameter settings (lowest priority)

Parameters set with a SET GLOBALS statement cause the execution time environment to be modified. These modifications remain in effect until overridden by another SET GLOBALS statement (or GLOBALS system command).



# 4 ACIVERS - Define ACI Version for Use with EntireX Broker

## ACI

---

This Natural profile parameter specifies the API version to be used with the EntireX Broker ACI. The broker stub in use as well as the called EntireX Broker must support the ACI version defined here. Please, refer to the EntireX documentation for the supported API versions. The setting of ACIVERS enables special features of the EntireX Broker, depending on the API version you are using. For details, see *Setting Up an EntireX Broker Access* in the *Natural Remote Procedure Call* documentation.

ACIVERS can be specified on both the client and the server side.

<b>Possible settings</b>	1 - 9	Single-digit number. The higher the version, the more features are available.
<b>Default setting</b>	2	API Version 2 is used.
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For additional information on Natural RPC, see the *Natural Remote Procedure Call (RPC)* documentation.



# 5 AD - Attribute Definition

---

▪ AD Parameter Syntax .....	12
▪ Field Representation .....	13
▪ Field Alignment .....	14
▪ Field Input/Output Characteristics .....	14
▪ Interpretation of Alphanumeric Fields .....	16
▪ Mandatory Input .....	16
▪ Length of Input Value .....	16
▪ Field Upper/Lower Case Characteristics .....	17
▪ Filler Character .....	17

With this session parameter, you specify field attributes at field/element or statement level.

Related session parameter: [CD - Color Definition](#)

<b>Possible settings</b>	see below	You can specify multiple attributes in any sequence.
<b>Default setting</b>	see below	
<b>Applicable statements:</b>	FORMAT	
	DISPLAY INPUT NEWPAGE WITH TITLE PRINT REINPUT WRITE WRITE TITLE WRITE TRAILER	Parameter may be specified at statement level and/or at element level.
	ASSIGN CALLNAT CALLDBPROC COMPUTE MOVE PERFORM SEND METHOD	Parameter may be specified at element level, however, only the attributes specified in the relevant statement description can be used.
<b>Applicable command:</b>	none	




**Note:** The AD parameter may be also specified in function calls, however, only the attributes specified in the section *Function Call* can be used.

The following topics are covered below:

## AD Parameter Syntax

```
AD=[field-representation] [field-alignment] [field-i/o-characteristics]
[interpretation-of-alphanumeric-fields] [mandatory-input] [input-value-length]
[field-upper/lower-case] [filler-character]
```

You can specify multiple attributes in any sequence. Possible values are:



The meaning of the attributes and the possible values are explained below.

### Examples:

```
DISPLAY #FIELD A (AD=R)
INPUT #FIELD B (AD=M)
INPUT (AD=IM) #FIELD A #FIELD B
```

## Field Representation

Value	Meaning	Statements	Explanation
B	blinking (*)	ASSIGN	The value of the field is displayed blinking.
C	cursive/italic (*)	COMPUTE MOVE	The value of the field is displayed cursive/italic.
D	default intensity	DISPLAY FORMAT	The value of the field is displayed with normal intensity, that is, not highlighted in any way. This is the default value.
I	intensified	INPUT	The value of the field is displayed intensified.
N	non-display	PRINT REINPUT	A value entered in the field will not be displayed.
U	underlined	WRITE	The value of the field is displayed underlined.
V	reverse video (*)		The value of the field is displayed reverse video.
Y	dynamic attributes	INPUT DISPLAY PRINT WRITE	Attributes are to be controlled via an attribute control variable (Format C).

\* The field representation attributes marked with an asterisk (\*) require corresponding hardware features, and will be ignored at runtime if these features are not available.

## Field Alignment

Value	Meaning	Statements	Explanation
L	left-justified	DISPLAY FORMAT	The value of the field is displayed left-justified. This is the default value for alphanumeric fields.
R	right-justified	INPUT PRINT REINPUT	The value of the field is displayed right-justified. This is the default value for numeric fields.
Z	leading zeros	WRITE	Numeric values are displayed with leading zeros, right-justified.

## Field Input/Output Characteristics

Value	Meaning	Statements	Explanation
A	input field, non-protected	INPUT FORMAT	The value of the field is to be entered in response to the INPUT statement. This is the default value.
	input only	CALLNAT CALLDBPROC PERFORM SEND METHOD Function Call	<p>If you mark a parameter with AD=A, its value will not be passed to the called object (subprogram, stored procedure, subroutine, dialog, method), but it will receive a value from the called object.</p> <p>For a field defined with BY VALUE in the called object's parameter data area, the calling object cannot receive a value. In this case, AD=A only causes the field to be reset to the low value of the respective format (blanks for alphanumeric, binary zeroes for binary and zeroes for numeric fields) before the object is called.</p> <p>For CALLNAT, AD=A may be useful for remote subprograms executed via Natural RPC in a client/server environment to reduce the load of data sent. If a subprogram is executed locally, AD=A fields will be reset to the low value of the respective format before the object is called.</p> <p>If for SEND METHOD, a method is not implemented in Natural, the behavior depends on the method implementation. The parameter is then passed as an initialized variant. Whether the external component is able to return a value is described in the documentation of the external component. It can also be viewed in the Natural Component Browser.</p>
M	output field, modifiable	INPUT FORMAT	The value of the field is to be displayed during INPUT statement execution, and a different value may be entered by the user. The field is an output field and may be modified.
	modifiable	CALLNAT CALLDBPROC	By default, the passed value of a parameter can be changed in the called object (subprogram, stored procedure, subroutine, dialog,

Value	Meaning	Statements	Explanation
		PERFORM SEND METHOD Function Call	<p>method) and the changed value passed back to the calling object, where it overwrites the original value.</p> <p>For a field defined with <code>BY VALUE</code> in the called object's parameter data area, no value is passed back.</p> <p>If, for <code>SEND METHOD</code>, a method is <i>not</i> implemented in Natural, the behavior depends on the method implementation. The parameter is then passed <code>BY REFERENCE</code>. Whether the external component accepts a by reference or by value parameter is described in the documentation of the external component. It can also be viewed in the Natural Component Browser.</p>
0	output field, write-protected	INPUT FORMAT	The value of the field is to be displayed during <code>INPUT</code> execution. The field is an output field and may not be modified.
	non-modifiable	CALLNAT CALLDBPROC PERFORM SEND METHOD Function Call	<p>If you mark a parameter with <code>AD=0</code>, the passed value can be changed in the called object (subprogram, stored procedure, subroutine, dialog, method), but the changed value cannot be passed back to the calling object; that is, the field in the calling object retains its original value.</p> <p>Internally, <code>AD=0</code> is processed in the same way as a call-by-value (see <code>BY VALUE</code> in the section Parameter Data Definition in the description of the <code>DEFINE DATA</code> statement).</p> <p>If for <code>SEND METHOD</code>, a method is implemented in Natural, the parameter is treated like it was defined <code>BY VALUE</code> in the method's parameter data area (see the <i>PARAMETER clause</i> of the <code>INTERFACE</code> statement).</p> <p>If for <code>SEND METHOD</code>, a method is <i>not</i> implemented in Natural, the behavior depends on the method implementation. The parameter is then passed <code>BY VALUE</code>. Whether the external component accepts a call by reference or by value parameter is described in the documentation of the external component. It can also be viewed in the Natural Component Browser.</p>
P	temporarily protected	INPUT REINPUT	Used in conjunction with an attribute control variable (Format C), the <code>DY</code> parameter (dynamic attributes), and the <code>REINPUT</code> statement.



**Note:** The Field Input/Output Characteristics A, M and 0 of the AD parameter may be also specified in Function Calls.

## Interpretation of Alphanumeric Fields

Value	Meaning	Statements	Explanation
Q	display alphanumeric field as if it were a numeric field	ASSIGN COMPUTE MOVE DISPLAY FORMAT INPUT PRINT REINPUT WRITE	<p>This attribute is available on mainframe computers only. A corresponding hardware feature is required.</p> <p>An alphanumeric field is interpreted as if it were a numeric field. If the field is displayed under the scope of profile or session parameter <code>PM=I</code>, the value of the field is interpreted from left to right instead of right to left.</p>

## Mandatory Input

Value	Meaning	Statements	Explanation
E	value mandatory	INPUT FORMAT	A value must be entered in the field in response to an INPUT statement; otherwise an error message will be issued. This is only relevant for input-only fields (AD=A).
F	value optional	INPUT FORMAT	A value can, but need not, be entered in the field in response to an INPUT statement. This is the default value.

## Length of Input Value

Value	Meaning	Statements	Explanation
G	value size	INPUT FORMAT	The value entered in the field in response to an INPUT statement must be of the same length as the field. This is only relevant for input-only fields (AD=A).
H	value size	INPUT FORMAT	The value entered in the field in response to an INPUT statement may be shorter than the field. This is the default value.



## Field Upper/Lower Case Characteristics

Value	Meaning	Statements	Explanation
T	translate lower to upper case	INPUT FORMAT	The value entered is to be translated to upper case.
W	accept lower case	INPUT FORMAT	Lower case values are to be accepted. To make AD=W effective, you have to specify the value ON for the Natural profile parameter LC. This is the default value.

## Filler Character


Value	Meaning	Statements	Explanation
' c '	filler character	INPUT FORMAT	The empty field is to be filled with the specified character c (for display only) if AD=A (input field, non-protected) or AD=M (output field, modifiable) is specified.

Before the value is displayed for a modifiable field (AD=M), field positions that are not occupied by the value are filled with the specified filler character as follows:

- Leading or trailing positions (depending on the field alignment) are filled for format I, N and P fields.
- Trailing positions are filled for format A fields.

If the user enters a value in response to the INPUT statement, before the value has been assigned to the field,

- both leading and trailing filler characters are removed for format I, N and P fields,
- trailing filler characters are removed for format A fields.

 **Caution:** Filler characters that may occur as part of the value in either leading or trailing position should be avoided to prevent undesired results. For example, if the filler character "0" (zero) is defined for a field of format N5 and the value 00100 is entered as input data, leading and trailing zeroes are removed so that only the value 1 remains, and will be assigned to the field. For the same reason, the minus sign "-" should be avoided as a filler character for numeric fields if negative values are to be entered.



# 6 AL - Alphanumeric Length for Output

---

With this session parameter, you specify the default output length for an alphanumeric field; that is, when it is specified shorter than the field length, the field will be right-truncated.

<b>Possible settings</b>	1 to $n$	$n$ = value of <b>LS</b> (line size) parameter minus 1
<b>Default setting</b>	none	
<b>Applicable statements:</b>	FORMAT	
	DISPLAY	Parameter may be specified at statement level and/or at element level.
	INPUT	
	PRINT	
WRITE		
<b>Applicable command:</b>	none	



## Notes:

1. It is not recommended to use the AL session parameter for input fields (**attribute definition** AD=A or AD=M) in an INPUT statement.
2. Any edit mask specified for a field (see session parameter EM) will override the AL session parameter for this field.

## Example:

```
FORMAT AL=20
```

See also *Parameters to Influence the Output of Fields* in the *Programming Guide*.



# 7 AUTO - Automatic Logon

---

This Natural profile parameter causes an automatic logon to a specific library at the start of the Natural session.

<b>Possible settings</b>	ON	An automatic logon is executed at the start of the Natural session.
	OFF	No automatic logon is performed.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

The setting of the profile parameter `INIT-LIB` is used as library ID for the logon.



**Note:** If used with Natural Security, `AUTO=ON` disables logons with another user ID, and the `INIT-LIB` parameter is not evaluated (see the *Natural Security* documentation for further information).



# 8

## AUTORPC - Automatic Natural RPC Execution

---

This Natural profile parameter determines whether or not Natural RPC will automatically try to execute a subprogram remotely (on the server side) which was not found locally (on the client side). For details see *Stubs and Automatic RPC* in the *Natural Remote Procedure Call (RPC)* documentation.

AUTORPC is specified on the client side only.

<b>Possible settings</b>	ON	Natural RPC will automatically try to execute it remotely.
	OFF	Natural RPC will not automatically try to execute it remotely. If AUTORPC=OFF, you can execute CALLNATs remotely using stubs.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	yes	At runtime, this value can be overwritten using the Parameter Maintenance function of the SYSRPC utility.

For additional information on Natural RPC, see the *Natural Remote Procedure Call (RPC)* documentation.





# 9

## BATCH - Batch Mode Simulation

---

This Natural profile parameter sets the system variable \*DEVICE to BATCH when Natural is started.

<b>Possible settings</b>	ON	When Natural is started with profile parameter BATCH set, error messages are not displayed, but written to a log file. The log file is named <i>natbatch.log</i> and is located in the Natural binary directory.
	OFF	Error messages are displayed but not written to a log file.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	This parameter can only be specified dynamically.
<b>Specification within session</b>	no	

To run Natural in batch mode, use the parameter `BATCHMODE` instead of `BATCH`.



# 10 BATCHMODE - Batch Mode

---

This Natural profile parameter applies to batch mode only. It enables batch mode and sets the system variable \*DEVICE to BATCH when Natural is started.

<b>Possible settings</b>	ON	Natural will run in batch mode.
<b>Default setting</b>	OFF	Natural will run in interactive mode, or in batch mode simulation.
<b>Dynamic specification</b>	yes	The parameter can only be specified dynamically.
<b>Specification within session</b>	no	



# 11 BMBLANK - Display Trailing Blanks

---

This Natural profile parameter applies to batch mode only.

It is used to control the display of trailing blanks in the batch output file **CMPRINT**.

This parameter applies only if the parameter **BMSIM** is set to MF. Trailing blanks are generated automatically if **BMSIM** is set to MF. **BMBLANK** has no effect if **BMSIM** is set to OS or VM.

<b>Possible settings</b>	ON	Trailing blanks are written to <b>CMPRINT</b> .
	OFF	No trailing blanks are written to <b>CMPRINT</b> .
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 12

## BMCONTROL - Display Control Characters

---

This Natural profile parameter applies to batch mode only.

It controls the output of control characters (such as form feed and line feed) in the batch output file `CMPRINT`.

<b>Possible settings</b>	ON	Control characters will be written to CMPRINT.
	OFF	No control characters will be written to CMPRINT.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	





# 13 BMFRAME - Window Frame Characters

---

This Natural profile parameter applies to batch mode only.

With this parameter you can define window frame characters that will be written to the batch output file [CMPRINT](#).

Specify a sequence of 6 characters.

<b>Possible settings</b>	6 characters	Character Position:	Displays:
		1	Horizontal bar
		2	Vertical bar
		3	Upper-left corner
		4	Upper-right corner
		5	Lower-left corner
		6	Lower-right corner
<b>Default setting</b>	- !++++		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	no		

**Example:**

To define the following frame you have to specify `BMFRAME=123456`.

```
3111111111114
2           2
2           2
5111111111116
```

# 14 BMSIM - Similar Batch Mode Output

This Natural profile parameter applies to batch mode only.

It is used for the general appearance description of the batch mode output file [CMPRINT](#).

<b>Possible settings</b>	MF	Forces output similar to Natural for Mainframe Version 2.3. Each line in <a href="#">CMPRINT</a> is filled with trailing blanks.												
		A control character appears at the beginning of each line of <a href="#">CMPRINT</a> . The control character codes are similar to the IBM control character option ASA.												
		The following control character codes are used:												
		<table border="1"> <thead> <tr> <th>Control Code</th> <th>Interpretation</th> </tr> </thead> <tbody> <tr> <td>blank</td> <td>Normal output line without control characters</td> </tr> <tr> <td>0</td> <td>Insert one empty line</td> </tr> <tr> <td>-</td> <td>Insert two empty lines</td> </tr> <tr> <td>+</td> <td>Print this line twice (bold printing)</td> </tr> <tr> <td>1</td> <td>Form feed before printing this line</td> </tr> </tbody> </table>	Control Code	Interpretation	blank	Normal output line without control characters	0	Insert one empty line	-	Insert two empty lines	+	Print this line twice (bold printing)	1	Form feed before printing this line
		Control Code	Interpretation											
		blank	Normal output line without control characters											
		0	Insert one empty line											
	-	Insert two empty lines												
	+	Print this line twice (bold printing)												
	1	Form feed before printing this line												
VM	Forces output similar to Natural for OpenVMS Version 2.1.													
	The following control character codes are used:													
<table border="1"> <thead> <tr> <th>Control Code</th> <th>Interpretation</th> </tr> </thead> <tbody> <tr> <td>\n</td> <td>Line feed before printing this line</td> </tr> <tr> <td>\f</td> <td>Form feed before printing this line</td> </tr> </tbody> </table>	Control Code	Interpretation	\n	Line feed before printing this line	\f	Form feed before printing this line								
Control Code	Interpretation													
\n	Line feed before printing this line													
\f	Form feed before printing this line													
	The FIN command will be generated if it is not specified in the batch command file <a href="#">CMSYNIN</a> .													
OS	Forces output similar to Natural for UNIX or OpenVMS.													
	The following control character codes are used:													

		<b>Control Code</b>	<b>Interpretation</b>
		\n	Line feed before printing this line
		\f	Form feed before printing this line
<b>Default setting</b>	0S		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	no		

# 15 BMTIME - Display Process Time

---

This Natural profile parameter applies to batch mode only.

It is used to display the elapsed and used CPU time consumed by the Natural process. This output will be written to the end of the batch output file [CMPRINT](#).

<b>Possible settings</b>	ON	The elapsed and used CPU time is written to the end of the batch output file.
	OFF	The output is not written to the batch output file.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

The time format is as follows:

*DDDxHH:II:SS.UU*

where:

- *DDD* is the number of days (at maximum 999)
- *x* is blank if *DDD* is less or equal to 999,  
or + (plus sign) if *DDD* is greater than 999
- *HH* is the number of hours
- *II* is the number of minutes
- *SS* is the number of seconds
- *UU* is the number of hundredths of seconds

Example:

```
Used CPU time:  0 00:00:00.56  
Elapsed time:  0 00:00:16.20
```

# 16

## BMTITLE - Display Window Title

---

This Natural profile parameter applies to batch mode only.

It is used to control the displaying of window titles in the batch output file [CMPRINT](#).

<b>Possible settings</b>	ON	A window title will be displayed in CMPrint.
	OFF	No window title will be displayed in CMPrint.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	





# 17

## BMVERSION - Display Natural Version

---

This Natural profile parameter is used to control the display of the Natural version including the startup and termination time.

<b>Possible settings</b>	ON	The Natural version and startup time are written to the very first line of the batch output file <code>CMPRINT</code> , the termination time is written at the end of <code>CMPRINT</code> .
	OFF	The Natural version and startup time are not written to <code>CMPRINT</code> .
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 18

## BPID - Specify Buffer Pool ID

---

This Natural profile parameter specifies the name (ID) of the Natural buffer pool.

<b>Possible settings</b>	1 - 8 characters	Name of the Natural buffer pool.
<b>Default setting</b>	NATBP	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



**Note:** Do not delete the default buffer pool “NATBP”, as it is possible that Natural may not function properly anymore.



# 19

## BPID2 - Specify Secondary Buffer Pool

---

This Natural profile parameter specifies the name (ID) of a secondary buffer pool.

When Natural runs with a read-only buffer pool as the primary buffer pool, objects missing in the read-only buffer pool cannot be loaded. To avoid this, Natural can attach during execution to a secondary standard buffer pool (which allows read/write access) and activate the missing objects there. For further information, see *Secondary Read/Write Buffer Pool* in the *Operations* documentation.

<b>Possible settings</b>	1 - 8 characters	Name of the secondary buffer pool.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 20

## BPNAME - Name of Natural Global Buffer Pool

---

This Natural profile parameter specifies the name of the Natural global buffer pool.

<b>Possible settings</b>	1 - 8 characters, or blank	Name of the Natural global buffer pool.  If BPNAME= ' ' (blank) is set, a <i>local</i> Natural buffer pool is used.
<b>Default setting</b>	blank	
<b>Dynamic specification</b>	yes	This parameter can only be specified dynamically.
<b>Specification within session</b>	no	





# 21 BPSFI - Object Search First in Buffer Pool

This Natural profile parameter determines the sequence in which a requested object that is to be executed is searched for in the buffer pool and in the system file(s).

You can choose between two search sequences:

<b>Possible settings</b>	ON	<p>Search Sequence 1 is used (search buffer pool first for all libraries, then the system file(s)).</p> <p>Natural looks for the object in the following sequence until it is found:</p> <ol style="list-style-type: none"> <li>1. in the buffer pool, first in the current library, then in one steplib after another, then in the two SYSTEM libraries;</li> <li>2. in the system file(s), first in the current library, then in one steplib after another, then in the two SYSTEM libraries.</li> </ol> <p>For performance reasons, it is recommended that you set BPSFI=ON in production environments.</p> <p><b>Caution:</b> If you set BPSFI=ON, make sure that object names are unique across all libraries that are involved in the search. If objects with the same name exist in different libraries being searched, unpredictable results may occur.</p>
	OFF	<p>Search Sequence 2 is used (alternating search in buffer pool and system file(s) for each library).</p> <p>Natural looks for the object in the following sequence until it is found:</p> <ol style="list-style-type: none"> <li>1. in the current library, first in the buffer pool, then in the system file(s);</li> <li>2. in one steplib after another, first in the buffer pool, then in the system file(s) for each steplib;</li> <li>3. in the two SYSTEM libraries, first in the buffer pool, then in the system file(s) for each library.</li> </ol>

		BPSFI=OFF is recommended in development environments to always get the most current object from your own current library.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For further information, see *Steplibs* and *Search Sequence for Object Execution* in the *Using Natural* documentation.

# 22

## CC - Error Processing in Batch Mode

This Natural profile and session parameter specifies the action to be taken if an error is detected during the compilation/execution of a Natural program in batch mode. It only applies in batch mode.

It does not apply if user-written error-handling routines are used.

Within a Natural session, the profile parameter `CC` can be overridden by the session parameter `CC`.

<b>Possible settings</b>	ON	Natural flushes the input data stream for the batch input files <code>CMSYNIN</code> and <code>CMOBJIN</code> until a line containing <code>%%</code> in the first two positions is encountered or until an end-of-file condition is detected. If more data are available in the input stream, Natural resumes reading after the line containing <code>%%</code> .	
	OFF	Natural attempts to process the next program (or command) in the input stream.  If all input is processed, Natural terminates with Return Code 61 and writes the Natural error 9987 (Error occurred during execution/compilation.) to the batch output file (if the profile parameter <code>ENDMSG</code> is set to ON).	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>			
<b>Specification within session</b>	yes	Applicable Statements:	
		Applicable Command:	
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	



# 23 CD - Color Definition

---

With this session parameter, you specify the color attributes for fields. If no color screen is used, this parameter will be ignored at runtime.

Related session parameter: [AD](#) - Attribute Definition

<b>Possible settings</b>	BL	blue
	GR	green
	NE	neutral
	PI	pink
	RE	red
	TU	turquoise
	YE	yellow
<b>Default setting</b>	NE	
<b>Applicable statements:</b>	FORMAT	
	DISPLAY INPUT PRINT WRITE	Parameter may be specified at statement level and/or at element level.
	ASSIGN MOVE REINPUT	Parameter may be specified at statement level.
<b>Applicable command:</b>	none	

**Example:**

```
INPUT (CD=RE) #A #B
```

# 24

## CDYNAM - Dynamic Loading of Non-Natural Programs

---

This Natural profile parameter determines whether or not non-Natural programs are to be loaded dynamically by Natural.

<b>Possible settings</b>	ON	Any number of non-Natural programs can be loaded dynamically during the execution of a Natural program.
	OFF	Dynamic loading of non-Natural programs is not performed by Natural.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	





# 25

## CF - Character for Terminal Commands

This Natural profile and session parameter specifies the control character for Natural terminal commands; that is, the character which is to be used as the first character of any terminal command.

Within a Natural session, the profile parameter `CF` can be overridden by the session parameter `CF`.

<b>Possible settings</b>	any special character	A terminal command must begin with the character specified. The character specified with the <code>CF</code> parameter <ul style="list-style-type: none"> <li>■ must not be the same as the one specified with the <code>HI</code> parameter (help character) or <code>IA</code> parameter (input assign character).</li> <li>■ should not be the same as the one specified with the <code>DC</code> parameter (decimal character) or <code>ID</code> parameter (input delimiter character).</li> <li>■ In the map editor, the control character for terminal commands is always “%” (so as to avoid conflicts with delimiter characters used in maps), no matter which character is defined with the <code>CF</code> parameter.</li> </ul>	
	OFF	No control character for terminal commands is available. Terminal commands issued with <code>SET CONTROL</code> statements, however, are still accepted.	
<b>Default setting</b>	%	A terminal command must begin with the character “%”.	
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

**Under Natural Security:** The setting of this parameter can be overridden by the *Session Parameters* option of the Library Profile.



# 26

## CLEAR - Processing of CLEAR Key in NEXT Mode

---

This Natural profile parameter causes Natural to execute a specific Natural terminal command whenever CLEAR is pressed during program execution in NEXT mode.

<b>Possible settings</b>	any character	The default action can be overridden by supplying a character which, when appended to the terminal-command control character (as specified with the <code>CF</code> parameter), forms a valid Natural terminal command.  Example:  <pre>CF=% CLEAR=R</pre> Natural executes the terminal command <code>%R</code> when the CLEAR key is pressed in NEXT mode.
<b>Default setting</b>	%	By default, when the CLEAR key is pressed, Natural responds as if the user had entered the terminal command <code>%%</code> .
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

**Under Natural Security:** The setting of this parameter can be overridden by the Session Parameters option of the Library Profile.



# 27

## CM - Command Mode

---

This Natural profile parameter can be used to suppress Natural command mode (NEXT and MORE).

<b>Possible settings</b>	ON	NEXT and MORE are available for command input.
	OFF	The Natural session will be terminated whenever NEXT is encountered; the MORE line will be write-protected (no input possible).
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 28

## CMOBJIN - Batch Input File for Natural INPUT Data

---

This Natural profile parameter applies to batch mode only.

It is used for data intended to be read by Natural INPUT statements. These types of data can alternatively be placed in the CMSYNIN file immediately following the relevant RUN or EXECUTE command. The number of characters actually processed is restricted to 512 characters per line.



**Note:** If the file name or path assigned to this parameter contains special characters (e.g. backslash) or spaces, the entire string must be enclosed in double quotes, see example below.

<b>Possible settings</b>	any string	CMOBJIN="\$HOME/tmp/batch.inp"
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

If the setting for the profile parameter CMSYNIN is equal to the setting of CMOBJIN, Natural reads input from CMSYNIN.

If an error occurs, Natural reacts in accordance with the setting of the profile/session parameter CC.





# 29

## CMPRINT - Batch Output File

---

This Natural profile parameter applies to batch mode only.

It is used to specify the batch output file for the output report resulting from `DISPLAY`, `PRINT` and `WRITE` statement in a Natural program. In addition, Natural commands from `CMSYNIN` and `INPUT` data from `CMOBJIN` are written to `CMPRINT`.



**Note:** If the file name or path assigned to this parameter contains special characters (for example, backslash) or spaces, the entire string must be enclosed in double quotes, see example below.

<b>Possible settings</b>	any string	<code>CMPRINT="\$HOME/tmp/batch.out"</code>
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 30 CMPRTnn - Additional Report

---

This Natural profile parameter applies to batch mode only.

It is used for additional reports referenced by any Natural program executed during the session. *nn* is a two digit decimal number in the range from 01 to 31 corresponding to the LPT device used by a report in a DISPLAY, PRINT and WRITE statement.

<b>Possible settings</b>	any string	If the file name or path assigned to this parameter contains special characters, e.g. backslash (\) or spaces, the entire string must be enclosed in double quotes.  <b>Example:</b>  CMPRT07="\$HOME/tmp/report7.txt"
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

In order to allow the user to specify variable print file names, alpha-format system variables and numeric counter markers may be embedded in the file name specification for CMPRT*nn*.

The supported alpha-format system variables are:

- \*APPLIC-ID
- \*APPLIC-NAME
- \*DEVICE
- \*ETID
- \*INIT-USER
- \*LIBRARY-ID
- \*NET-USER
- \*PID
- \*PROGRAM

\*USER  
\*USER-NAME

If any of these strings (in upper case only) is encountered within the print file specification, it will be replaced at run-time with the contents of the appropriate system variable. Additionally, a counter marker (#) may be used. This will be replaced by a 2-digit counter which will automatically be incremented for each print file.

**Example:**

The specification `CMPRT01=abc_*PID_*ETID_*PROGRAM_#.dat` in a Natural session with process ID 1234, ETID XYZ running a program with the name PRINT which produces print file output to File 01 would produce print files with the following names (assuming the program runs 3 times):

```
abc_1234_XYZ_PRINT_01.dat  
abc_1234_XYZ_PRINT_02.dat  
abc_1234_XYZ_PRINT_03.dat
```

See also *Using Natural in Batch Mode* in the *Operations* documentation.

# 31 CMSYNIN - Batch Input File for Natural Commands and INPUT Data

---

This Natural profile parameter applies to batch mode only.

CMSYNIN is used for the batch input file. It contains Natural commands and data to be read by INPUT statements during execution of Natural programs (optionally). The number of characters actually processed is restricted to 512 characters per line.



**Note:** If the file name or path assigned to this parameter contains special characters, e.g. backslash (\) or spaces, the entire string must be enclosed in double quotes, see example below.

<b>Possible settings</b>	any string	CMSYNIN="\$HOME/tmp/batch.cmd"
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

See also *Using Natural in Batch Mode* in the *Operations* documentation.



# 32 CMWRKnn - Natural Work Files

---

This Natural profile parameter applies to batch mode only.

CMWRKnn is used for Natural work files referenced by any Natural program executed during the session.

nn is a two digit decimal number in the range from 01 to 32 corresponding to the number used in a READ WORK FILE or WRITE WORK FILE statement.



**Note:** If the file name or path assigned to this parameter contains special characters, e.g. backslash (\) or spaces, the entire string must be enclosed in double quotes, see example below.

<b>Possible settings</b>	any string	CMWRK05="\$HOME/tmp/workfile5.sag"
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

See also *Using Natural in Batch Mode* in the *Operations* documentation.





# 33

## CO - Compiler Output

---

This Natural profile and session parameter can be used to deactivate or reactivate the compiler operation-in-progress window wherein, by default, the code is displayed as it is processed by the compiler.

<b>Possible settings</b>	ON	A compiler listing is displayed in a special operation-in-progress window on the screen. This setting is useful in the event of a crash because the code display will stop at the position affected.  <b>Note:</b> This setting should be used only if actually needed, because it results in a significantly longer compilation time. Especially a CATALL command will take a rather long time to compile all objects.  CO=ON is not supported in batch mode.	
	OFF	Compiler operation-in-progress window off.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	<b>Applicable statements:</b>	SET GLOBALS
		<b>Applicable command:</b>	GLOBALS



# 34 COMPR - Set RPC Buffer Compression

---

This Natural profile parameter can be used to set the RPC buffer compression. It is effective only, if the automatic Natural RPC execution is used (`AUTORPC=ON`) and the `CALLNAT` is executed without a stub. If a stub is used, the compression has already been set during stub generation. For details, see *Using Compression* in the *Natural Remote Procedure Call* documentation.

COMPR is specified on the client side only.

<b>Possible settings</b>	0	No compression will be performed.
	1	The send buffer contains modifiable fields and output fields and the format buffer. The reply buffer contains modifiable fields and input fields.
	2	Same as <code>COMPR=1</code> , additionally the reply buffer also contains the format buffer.
<b>Default setting</b>	1	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	yes	At runtime, this value can be overwritten using the Parameter Maintenance function of the <code>SYSRPC</code> utility.

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.



# 35

## CP - Default Code Page Name

---

This Natural profile parameter defines the default code page for Natural data and Natural sources.

If no code page is specified for a code page sensitive operation such as data conversions to and from Unicode (for example, by means of a statement specific `ENCODED` option or by another profile parameter), the default code page applies.

For the current Natural session, it is assumed that all code page data, for example, Natural sources, contents of A-format fields, etc., are stored in this code page format.

See also *Profile Parameters* in the *Unicode and Code Page Support* documentation.

<b>Possible settings</b>	1 - 64 characters	The name of the desired code page.
	' ' (blank)	Reset to system code page.
<b>Default setting</b>	' ' (blank)	System code page.
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 36

## CPCVERR - Code Page Conversion Error

---

This Natural profile and session parameter specifies whether a conversion error that occurs when converting

- from Unicode to code page or
- from code page to Unicode or
- from one code page to another code page

results in a Natural error or not. Anyway, after the conversion, the target operand will contain the conversion result where all characters which can not be converted will be replaced by a substitution character which is defined by ICU for the affected code page. This parameter is not regarded for the conversion of Natural sources when loading them into the source area or during catalog.

On mainframe platforms, it is not regarded whether a Unicode field is converted into the code page before an I/O on a terminal emulation. In this case, the substitution character is replaced by the place holder character which is defined in NATCONFIG.

See also:

- *Profile Parameters in the Unicode and Code Page Support documentation.*
- *Using an Error Transaction Program in the Programming Guide*



**Note:**

<b>Possible settings</b>	ON	A Natural error NAT3413 is issued, if at least one code point could not be translated correctly during ICU conversion.
	OFF	No error is generated if one or more code points could not be translated correctly during ICU conversion.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	

<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS



# 37

## CPOBJIN - Code Page of Batch Input File

---

This Natural profile parameter specifies the code page of the batch input file which is defined by the Natural profile parameter [CMOBJIN](#).

See also *Profile Parameters in the Unicode and Code Page Support* documentation.

<b>Possible settings</b>	1 -64 characters	ICU code page name (IANA name recommended).
	' ' (blank)	The code page resulting from the evaluation of the profile parameter <a href="#">CP</a> is used.
<b>Default setting</b>	' ' (blank)	The code page resulting from the evaluation of the profile parameter <a href="#">CP</a> is used.
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 38

## CPPRINT - Code Page of Batch Output File

---

This Natural profile parameter specifies the code page of the batch output file which is defined by the Natural profile parameter [CPPRINT](#).

See also *Profile Parameters in the Unicode and Code Page Support* documentation.

<b>Possible settings</b>	1 - 64 characters	ICU code page name (IANA name recommended).
	' ' (blank)	The code page resulting from the evaluation of the profile parameter <a href="#">CP</a> is used.
<b>Default setting</b>	' ' (blank)	The code page resulting from the evaluation of the profile parameter <a href="#">CP</a> is used.
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 39

## CPRPC - Define Code Page Name

---

This Natural profile parameter specifies the name of the code page used by the EntireX Broker. Currently, it applies only to the Natural RPC facility when the transport protocol ACI (that is EntireX Broker) is used.

For more information about EntireX Broker refer to the section about Software AG's Internationalization in the EntireX Broker documentation.

See also *Unicode and Code Page Support, Configuration and Administration of the Unicode/Code Page Environment, Profile Parameters*.

CPRPC can be specified on both the client and the server side.

<b>Possible settings</b>	1 to 40 characters	Valid code page name of EntireX Broker.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 40

## CPSYNIN - Code Page of Batch Input File for Commands

---

This Natural profile parameter specifies the code page of the batch input file for commands which is defined by the Natural profile parameter [CMSYNIN](#).

See also *Profile Parameters in the Unicode and Code Page Support* documentation.

<b>Possible settings</b>	1 - 64 characters	ICU code page name (IANA name recommended).
	' ' (blank)	The code page resulting from the evaluation of the profile parameter <a href="#">CP</a> is used.
<b>Default setting</b>	' ' (blank)	The code page resulting from the evaluation of the profile parameter <a href="#">CP</a> is used.
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	





# 41 CV - Attribute Control Variable

---

This session parameter is used to reference an attribute control variable. An attribute control variable is defined with Format C (see *Special Formats* in the *Programming Guide*) and is used to

- assign field attributes dynamically and/or
- check the “modified” status of a field in conjunction with an INPUT or PROCESS PAGE statement; see also *Logical Condition Criteria, MODIFIED Option - Check whether Field Content has been Modified* in the *Programming Guide*.

<b>Possible settings</b>	B, C, D, I, N, U, V	Field representation attributes (see session parameter <a href="#">AD</a> ).
	P	Field protection (see session parameter <a href="#">AD</a> ).
	BL, GR, NE, PI, RE, TU, YE	Color (for an explanation of the color codes, see the session parameter <a href="#">CD</a> ).
<b>Default setting</b>	none	
<b>Applicable statements:</b>	DISPLAY INPUT PRINT PROCESS PAGE WRITE	Parameter may be specified at statement level and/or at element level.
<b>Applicable command:</b>	none	

**Example:**

```
DEFINE DATA LOCAL
1 #ATTR(C)
1 #A (N5)
END-DEFINE
...
MOVE (AD=I CD=RE) TO #ATTR
INPUT #A (CV=#ATTR)
...
```

By specifying the `MODIFIED` option of the `IF` statement, the attribute control variable can be used to check whether the contents of a field has been modified during the execution of an `INPUT` or `PROCESS PAGE` statement:

```
IF #ATTR MODIFIED ...
```

A single attribute control variable can be applied to several input fields by specifying it once at statement level or multiple times at element level, in which case the “modified” status indication is set if any of the fields referencing the control variable has been modified. If the `CV` parameter is specified both at statement level and at field level and the attribute control variable for the individual field is empty, the attribute control variable for the statement will be used for the field.

The attribute control variable can be expanded up to three dimensions, for example, `CONTR(*)`, `CONTR(*,*)`, `CONTR(*,*,*)`, depending on the rank of the corresponding array.

# 42

## CVMIN - Control Variable Modified at Input

---

This Natural profile parameter determines whether or not an attribute control variable is assigned the status `MODIFIED` when the setting of the field to which the attribute control variable is attached is overwritten by an *identical* setting. If an attribute control variable has been assigned the status `MODIFIED`, the `MODIFIED` option evaluates this as `TRUE`. This applies regardless of whether the input was entered manually, read from the stack or supplied in batch mode.

<b>Possible settings</b>	ON	If a field setting is overwritten by the same setting, the corresponding control variable will be assigned the status <code>MODIFIED</code> .
	OFF	If a field setting is overwritten by the same setting, the corresponding control variable will not be assigned the status <code>MODIFIED</code> .
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 43

## DBSHORT - Interpretation of Database Field Short Names

---

This Natural profile and session parameter can be used to determine the interpretation of database field short names. It corresponds to the option `DBSHORT` of the Natural system command `COMPOPT`.

A database field defined in a DDM is described by two names:

- the short name with a length of 2 characters, used by Natural to communicate with the database (especially with Adabas);
- the long name with a length of 3-32 characters (1-32 characters, if the underlying database type accessed is DB2/SQL), which is supposed to be used to reference the field in the Natural programming code.

Under special conditions, you may reference a database field in a Natural program with its short name instead of the long name. This applies if running in Reporting Mode without Natural Security and if the database access statement contains a reference to a DDM instead of a view.

The decision if a field name is regarded as a short-name reference depends on the name length. When the field identifier consists of two characters, a short-name reference is assumed; a field name with another length is considered as a long-name reference. This standard interpretation rule for database fields can additionally be influenced and controlled by setting the compiler option `DBSHORT` to `ON` or `OFF`:

<b>Possible settings</b>	ON	The usage of a short name is allowed for referencing a database field.  However, a data base short name is <i>not permitted</i> in general (even if <code>DBSHORT=ON</code> ) <ul style="list-style-type: none"><li>■ for the definition of a field when a view is created;</li><li>■ when a view field is used in the programming code;</li><li>■ when a <code>DEFINE DATA LOCAL</code> statement was previously used to defines variables;</li><li>■ when running under Natural Security.</li></ul>
--------------------------	----	---

	OFF	<p>A database field may only be referenced via its long name. Every database field identifier is considered as a long-name reference, regardless of its length.</p> <p>If a two character name is supplied which can only be found as a short name but not as a long name, syntax error NAT0981 is raised at compile time.</p> <p>This makes it possible to use long names defined in a DDM with 2-byte identifier length. This option is essential if the underlying database you access with this DDM is SQL (DB2) and table columns with a two character name exist. For all other database types (for example, Adabas), however, any attempt to define a long field with a 2-byte name length will be rejected at DDM generation.</p> <p>Moreover, if no short-name references are used (what can be enforced via DBSHORT=OFF), the program becomes independent of being compiled without Natural Security.</p>	
<b>Default setting</b>	ON		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	OPTIONS
		Applicable Command:	DBSHORT option of COMPOPT

**Examples:**

Assume the following data base field definition in the DDM EMPLOYEES:

Short Name	Long Name
AA	PERSONNEL-ID

**Example 1:**

```

OPTIONS DBSHORT=ON
READ EMPLOYEES
  DISPLAY AA      /* data base short name AA is allowed
END
    
```

**Example 2:**

```
OPTIONS DBSHORT=OFF
READ EMPLOYEES
  DISPLAY AA      /* syntax error NAT0981, because DBSHORT=OFF
END
```

**Example 3:**

```
OPTIONS DBSHORT=ON
DEFINE DATA LOCAL
1 V1 VIEW OF EMPLOYEES
  2 PERSONNEL-ID
END-DEFINE
READ V1 BY PERSONNEL-ID
  DISPLAY AA      /* syntax error NAT0981, because PERSONNEL-ID is defined in view;
                  /* (even if DBSHORT=ON)
END-READ
END
```





# 44 DBUPD - Database Updating

---

This Natural profile parameter indicates whether database updating is to be permitted during the Natural session.

<b>Possible settings</b>	ON	Database update is permitted.
	OFF	Database update is not permitted. A Natural statement which would cause a database update (STORE, UPDATE, DELETE) is not executed and an error message is generated.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.
	USR1042N *	* Recommended.

The DBUPD setting has no effect on the execution of Natural system commands.



# 45

## DC - Character for Decimal Point Notation

This Natural profile and session parameter determines the character to be used as decimal separator, that is, a point or a comma.

Within a Natural session, the profile parameter `DC` can be overridden by the session parameter `DC`.

<b>Possible settings</b>	any special character	<p>The character assigned to <code>DC</code> will be in effect for all notations where a decimal separator is possible; that is, variables, constants and edit masks. The character specified with the <code>DC</code> parameter</p> <ul style="list-style-type: none"> <li>■ must not be the same as the one specified with the <code>IA</code> profile/session parameter (input assign character) or <code>ID</code> profile/session parameter (input delimiter character),</li> <li>■ should not be the same as the one specified with the <code>CF</code> profile/session parameter (control character for terminal commands) or <code>HI</code> profile parameter (help character).</li> </ul>		
<b>Default setting</b>	. (period)			
<b>Dynamic specification</b>	yes			
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS	Parameter is evaluated at runtime.
		Applicable Command:	GLOBALS	Parameter may be specified dynamically with the GLOBALS system command.
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.		



**Note:** If you change `DC` in your parameter file, you must resave the DDM you are using in your Natural program which stores a new `.NSD` file on disk.

**Under Natural Security:** The setting of this parameter can be overridden by the Session Parameters option of the *Library Profile*.

# 46 DD - Day Differential

---

This Natural profile parameter is used to adjust the current machine date (as read by using the internal machine time) by adding/subtracting any number of days to/from it. This makes it possible to re-run an application that was to be run at a certain date but for some reason could not be run at that date.

The DD profile parameter is specified as follows:

DD=+nn

or

DD=-nn

where *nn* is the number of days.

<b>Possible settings</b>	-10953 to +10953	Machine date is adjusted. Specification of "+" is optional.
	0	No adjustment is made.
<b>Default setting</b>	0	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR1005N	See SYSEXT - <i>Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

See also the profile parameter [TD](#).



# 47 DF - Date Format

With the DF session parameter, you determine the length of a date when converted to alphanumeric representation without an edit mask being specified. The DF parameter is evaluated at compilation time.

The sequence of the day, month and year components and the delimiter characters used are determined by the profile parameter [DTFORM](#).

<b>Possible settings</b>	S	8-byte representation with 2-digit year component and delimiters ( <i>yy-mm-dd</i> ).  With DF=S, only 2 digits are provided for the year information; this means that if the date value contained the century, this information would be lost during the conversion.
	I	8-byte representation with 4-digit year component and no delimiters ( <i>yyyymmdd</i> ). * See Note.
	L	10-byte representation with 4-digit year component and delimiters ( <i>yyyy-mm-dd</i> ). * See Note.
<b>Default setting</b>	S	
<b>Applicable statements:</b>	FORMAT	
	INPUT DISPLAY WRITE PRINT	Parameter may be specified at statement level and/or at element level.
	MOVE COMPRESS STACK RUN FETCH	Parameter may be specified at element level.
<b>Applicable command:</b>	none	

When the value of a date field is converted to alphanumeric format (for example, in a `MOVE`, `DISPLAY`, `WRITE` or `INPUT` statement) and no edit mask is specified for the conversion, the default date format as determined by the profile parameter `DTFORM` is used as edit mask. The same is true for the input validation of a date variable used in an `INPUT` statement: If no edit mask is specified, the input is validated according to the date format determined by the `DTFORM` parameter.



**Note:** By using `DF=I` or `DF=L`, you can gradually change your applications to use 4-digit year representations and at the same time continue to make use of the flexibility provided by the profile parameter `DTFORM`.

See also Processing of Date Information, *Date Format for Alphanumeric Representation - DF Parameter* in the *Programming Guide*.



# 48 DFOUT - Date Format for Output

This Natural profile and session parameter determines the format in which the settings of date variables are displayed by `INPUT`, `DISPLAY`, `PRINT` and `WRITE` statements.

Within a Natural session, the profile parameter `DFOUT` can be overridden by the session parameter `DFOUT`.

<b>Possible settings</b>	S	Date variables are displayed with a 2-digit year component, and delimiters as determined by the profile parameter <code>DTFORM</code> . For example: <i>yy-mm-dd</i> .	
	I	Date variables are displayed with a full 4-digit year component and no delimiters. For example: <i>yyyymmdd</i> .	
<b>Default setting</b>	S		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	



## Notes:

1. The *profile parameter* `DFOUT` is evaluated at runtime. It applies to date fields in `INPUT`, `DISPLAY`, `PRINT` and `WRITE` statements for which no explicit edit mask is specified and for which the *session parameter* `DF` is not set.
2. The sequence of the day, month and year components in the date settings is determined by the `DTFORM` profile parameter.

See also *Processing of Date Information* in the *Programming Guide*.



# 49

## DFS - Specify RPC Client's Default Server Address

This Natural profile parameter can be used to define an RPC default server address. It determines the server name, the server node, the logon indicator and the transport protocol. The default server address will be used only if no appropriate server is found in the service directory. For further information, see *Specifying RPC Server Addresses* in the *Natural Remote Procedure Call (RPC)* documentation.

To define a default server address, you specify up to 4 subparameters.

DFS is specified on the client side only.

<b>Possible settings</b>	<i>server-name</i>	(1 - 192 characters). There is no default, the value must be specified.		
	<i>server-node</i>	(1 - 192 characters). There is no default, the value must be specified.		
	<i>logon-indicator</i>	L	The client initiates a Natural logon to the server with the library name of the current library on the client.	
		(blank)	No server logon will be executed.	
			If nothing is specified, blank is the default.	
			<b>Note for Windows platforms:</b> Instead of specifying L, check the selection box.	
<i>transport-protocol-name</i>	The transport protocol to be used. ACI is the only possible value and the default.			
<i>service-directory-indicator</i>	SERVDIR	A service directory must be present before the DFS profile parameter is evaluated.		

		NOSERVDIR	No service directory is used before the DFS profile parameter is evaluated; that is, a service directory needs not be available on the client side.
			If nothing is specified, SERVDIR is the default.
<b>Default setting</b>	none		Subparameter defaults, see above.
<b>Dynamic specification</b>	yes		See below.
<b>Specification within session</b>	yes		At runtime, this value can be overwritten using the Natural application programming interface USR2007N.
<b>Application Programming Interface</b>	USR2007N		See <i>Application Programming Interfaces for Use with Natural RPC</i> in the <i>Natural Remote Procedure Call (RPC)</i> documentation and <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

For dynamic specification, the syntax is as follows:

```
DFS=(server-name,server-node,logon-indicator,transport-protocol-name,service-directory-indicator)
```

For the possible values of *server-name* and *server-node*, refer to [SRVNAME](#) and [SRVNODE](#).

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.

# 50

## DFSTACK - Date Format for Stack

This Natural profile and session parameter determines the format in which the settings of date variables are placed on the stack via a `STACK`, `RUN` or `FETCH` statement.

Within a Natural session, the profile parameter `DFSTACK` can be overridden by the session parameter `DFSTACK`.

<b>Possible settings</b>	S	Date variables are placed on the stack with a 2-digit year component, and delimiters as determined by the profile parameter <code>DTFORM</code> . For example: <i>yy-mm-dd</i> .	
	C	Same as <code>DFSTACK=S</code> . In addition, if the century used when the setting is read from the stack is not the same as that of the original date setting, Natural will issue a runtime error.	
	I	Date variables are placed on the stack with a full 4-digit year component and no delimiters. For example: <i>yyyymmdd</i> .	
<b>Default setting</b>	S		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

The profile parameter `DFSTACK` does not apply to `STACK`, `RUN` or `FETCH` statements for which the session parameter `DF` is set.

See also *Processing of Date Information* in the *Programming Guide*.



# 51 DFTITLE - Output Format of Date in Standard Report Title

This Natural profile and session parameter determines the output format of the date in the default title line of a report page (as output with a `DISPLAY`, `WRITE` or `PRINT` statement).

Within a Natural session, the profile parameter `DFTITLE` can be overridden by the session parameter `DFTITLE`.

<b>Possible settings</b>	S	The date is output with a 2-digit year component and delimiters. For example: <i>yy-mm-dd</i> .	
	L	The date is output with a 4-digit year component and delimiters. For example: <i>yyyy-mm-dd</i> .	
	I	The date is output with a 4-digit year component and no delimiters. For example: <i>yyyymmdd</i> .	
<b>Default setting</b>	S		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	



## Notes:

1. `DFTITLE` is evaluated at runtime and determines whether the date is displayed with a 2-digit or 4-digit year component with or without delimiters. It has no effect on a user-defined page title (as specified with a `WRITE TITLE` statement).
2. The sequence of the day, month and year components and the delimiter characters used are determined by the profile parameter `DTFORM`.

See also *Processing of Date Information* and *Date Format for Default Page Title - DFTITLE Parameter* in the *Programming Guide*.





# 52 DL - Display Length for Output

---

With this session parameter, you specify the display length for a field of format A or U. The default display length is the length of the field.

<b>Possible settings</b>	1 to $n$	$n$ = value of LS (line size) parameter minus 1
<b>Default setting</b>	none	
<b>Applicable statements:</b>	FORMAT	
	DISPLAY INPUT PRINT WRITE	Parameter may be specified at statement level and/or at element level.
<b>Applicable command:</b>	none	

## Example:

```
FORMAT DL=20
```

For further information and an example of the DL session parameter usage, see the following topics in the *Programming Guide*:

- *Parameters to Influence the Output of Fields*
- *Output Length - AL and NL Parameters*
- *Display Length for Output - DL Parameter*



# 53

## DO - Display Order of Output Data

---

This Natural profile and session parameter specifies how fields are to be interpreted for display on terminals that support bidirectional data.

The I/O device must be able to create the correct display order depending on the character properties. This is for instance the case if an application runs in a browser under Natural Web I/O Interface. For other terminal types, this parameter does not have any effect.

<b>Possible settings</b>	L	Specifies that the data from the application is in logical display order.  The field characters are displayed according to their character property (left-to-right or right-to-left).	
	V	Specifies that the data from the application is in visual order.  All fields are inverted by Natural before they are sent to the terminal. This option is required for old applications written for terminals which support inverse (right-to-left) print mode using profile parameter <code>PM=I</code> or terminal command <code>%VON</code> .	
<b>Default setting</b>	L		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statement:	SET GLOBALS
		Applicable Command:	GLOBALS

For detailed information on how to use the setting `PM=I`, see *Bidirectional Language Support* in the *Unicode and Code Page Support* documentation.



# 54 DTFORM - Date Format

---

This Natural profile parameter indicates the default format in which dates are to be provided automatically by Natural as part of the default title on Natural reports, as date constants and date input.

Possible settings	Value	Area	Date Format
	E	Europe	DD/MM/YYYY
	G	Germany	DD.MM.YYYY
	I	International	YYYY-MM-DD
	U	USA	MM/DD/YYYY
Default setting	I		
Dynamic specification	yes		
Specification within session	no		
Application Programming Interface	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

The first day of a week is assumed to be Monday - unless DTFORM=U is specified, in which case Sunday is used.

For date constants, the year component (YYYY) consists of all four digits. Only the last two digits of the year component are used for reports, date input, the Natural system function VAL, and when the date is moved to an alphanumeric field.

The output format of the date in a default report page title is also specified by the profile parameter [DFTITLE](#).

See also *Processing of Date Information* and *Default Edit Mask for Date - DTFORM Parameter* in the *Programming Guide*.



# 55

## DU - Dump Generation

This Natural profile and session parameter determines whether a disassembled object code dump is to be generated.

Within a Natural session, the profile parameter `DU` can be overridden by the session parameter `DU`.

<b>Possible settings</b>	ON	When one of the system commands <code>CHECK</code> , <code>STOW</code> , <code>CATALOG</code> , <code>RUN</code> or <code>CATALL</code> is executed, a disassembled object code file is produced.  This dump file is written into the directory which is defined in the Natural TMP directory option in the Natural Configuration Utility; see <i>Local Configuration File, Installation Assignments</i> .  The name of this dump file consists of the source file name and the extension <code>.DIA</code> . If the source file has not been saved, the name of the dump file is <code>GEN.DIA</code> . If the program contains database access statements, dump files with the extension <code>.ADA</code> (for Adabas) or <code>.SQL</code> (for SQL databases) are also created. If <code>XREF</code> data are generated, a dump file <code>.XRF</code> is created.  <b>Note:</b> <code>DU=ON</code> may create a large dump file (depending on the size of the source file), which can cause significant degradation in system performance.	
	OFF	No dump file is generated.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS

**Under Natural Security:** The setting of this parameter can be overridden by the *Session Parameters* option of the Library Profile.





# 56

## DY - Dynamic Attributes

---

- DY Parameter Syntax ..... 122
- Examples ..... 124

This session parameter is used to assign attributes for dynamic attribute field display.

<b>Possible settings</b>		See below.
<b>Default setting</b>	none	
<b>Applicable statements:</b>	DISPLAY INPUT PRINT WRITE	Parameter may be specified at statement level and/or at element level.
<b>Applicable command:</b>	none	

Special identification characters (escape characters) are used to indicate the beginning and end of attribute definitions.

An alphanumeric field which is processed with an INPUT, DISPLAY, WRITE or PRINT statement, and which contains escape characters, is split into subfields at the escape character position. The corresponding attribute is then assigned to the subfield. A blank is substituted for the escape character.



**Note:** For a part of a field for which a DY specification applies, the current field presentation and color attributes remain in effect, unless new settings are defined in the DY entry. This means, the field color is only changed by a DY attribute if the DY parameter itself defines a new color. The same applies to the **field representation attributes**, such as (AD=B,C,D,I,N,U,V).

## DY Parameter Syntax

```
DY={{escape-character1} [color-attribute] [i/o-characteristics]
[field-representation-attribute]} ... {escape-character2}
```

The possible settings are explained below.

*escape-character1*

An escape character which denotes the beginning of the attribute definition. Any special character or a hexadecimal number preceded by an apostrophe ('xx) may be used.

*color-attribute*

The color attribute to be assigned. See also session parameter [CD](#) (color definition).

BL	blue
GR	green
NE	neutral
PI	pink
RE	red
TU	turquoise
YE	yellow

*i/o-characteristics*

Value	Meaning
P	Subfield is to be write-protected.

A **P** may be specified to make the subfield write-protected. See also session parameter [AD](#) (attribute definition).

*field-representation-attribute*

Additional attributes to be assigned. See also session parameter [AD](#) (attribute definition).

Value	Meaning
B	blinking (*)
C	cursive/italic (*)
D	default intensity
I	intensified
N	non-display
U	underlined
V	reverse video (*)

\* The field representation attributes marked with an asterisk (\*) require corresponding hardware features, and will be ignored at runtime if these features are not available.

*escape-character2*

An escape character which denotes the end of the attribute definition. Any special character (*c*) or a hexadecimal number preceded by an apostrophe (*'xx*) may be used.

You may specify up to eight escape sequences (escape characters and attributes) before the character indicating the end of the attribute definitions.

## Examples

---

### Example 1:

```
DY=<U>
```

The text string:

```
THIS <i s> UNDERLINED
```

is printed as:

```
THIS i s UNDERLINED
```

### Example 2:

```
DY=<BL|RE/GR>
```

Assigns:

Blue to <

Red to |

Green to /

> switches back to the initial field color.

### Example 3:

```
DY=<P>;
```

The text string:

```
Do not overwrite <this>
```

is printed as:

```
Do not overwrite this
```

(where this is protected)

---

# 57

## DYNPARM - Control Use of Dynamic Parameters

---

This Natural profile parameter enables/disables the use of Natural dynamic parameters.

<b>Possible settings</b>	ON	Dynamic parameters supplied during Natural startup are processed.
	OFF	Dynamic parameters supplied during Natural startup are not processed.  <b>Note:</b> If DYNPARM is set to OFF in the Natural default parameter file NATPARM, no alternative user-defined parameter files can be used when starting Natural.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	

See *Dynamic Assignment of Parameter Values* for additional information on the use of dynamic parameters.





# 58

## ECHO - Control Printing of Batch Input Data

---

This Natural profile parameter only applies in batch mode.

It is used to enable or disable the printing of input data provided to Natural during batch mode processing.

<b>Possible settings</b>	ON	Natural prints the input data provided during batch mode processing to the batch output file CMPRINT.
	OFF	Natural does <i>not</i> print input data provided during batch processing.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

It is also possible to suppress printing of a *single input line* by preceding it with a line containing the terminal command for record suppression %\*.

Input read from CMSYNIN in command (NEXT) mode is echoed to the batch output file CMPRINT always.



# 59

## ECPMOD - Entire Connection Protocol Mode

---

This Natural profile parameter determines the protocol that is used when downloading workfiles.

<b>Possible settings</b>	ON	The TCP/IP protocol is used.
	OFF	The ZMODEM protocol is used.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 60

## EDITOR - Other Program Editor

---

This Natural profile parameter can be used to invoke a program editor other than the standard editor provided by Software AG.

<b>Possible settings</b>	any character string	Name of the editor you want to use. Specification, see below.
<b>Default setting</b>	NATEDIT	Standard editor provided by Software AG.
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



**Note:** If an external editor is being used, the 4-digit line numbers at the beginning of each Natural source line have to be added manually, if an existing source is edited.

To use an external editor, specify the path and editor name:

```
path-name editor-name command-to-specify-line %l command-to-specify-file %f
```

The string before %l is replaced by the ASCII representation of the line number. The string before %f is replaced by the file name as known by Natural.

The use of an external editor is not recommended as code page conflicts may arise. These conflicts can - but not necessarily must - deteriorate your source code.

**Example:**

```
vi +%l %f
```

To use “vi” as a program editor, edit your parameter files as specified. If the existing parameter files are not updated, the specified editor (that is, “vi”) cannot find the error line.

# 61 EDTBPSIZE - Software AG Editor Buffer Pool Size

---

This Natural profile parameter is used to set the size of the Software AG Editor buffer pool.

<b>Possible settings</b>	0 - 4000	Size of the editor buffer pool in KB.
<b>Default setting</b>	400	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	





# 62

## EDTLFILES - Number of Software AG Editor Logical Files

---

This Natural profile parameter is used to set the maximum number of the Software AG Editor sessions a user can open at a time.

<b>Possible settings</b>	10-999	Maximum number of Software AG Editor sessions.
<b>Default setting</b>	100	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 63 EDTRB - Program Editor Ring Buffer

---

This Natural profile parameter can be used to determine whether the ring buffer of the program editor is to be used or not.

For further information, see *Multiple Editor Sessions*.

<b>Possible settings</b>	ON	Ring buffer is used.
	OFF	Ring buffer is not used.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 64 EJ - Page Eject

---

This Natural profile and session parameter is used to specify whether a page eject is to be performed as a result of a logical page break, a break between program input and output, and the “normal end” message.

Within a Natural session, the profile parameter EJ can be overridden by the session parameter EJ. The EJ setting can in turn be overridden by an EJECT statement.

<b>Possible settings</b>	ON	A page eject is performed.		
	OFF	No page eject is performed. This setting may be used to save paper during test runs where page ejections are not needed.		
<b>Default setting</b>	ON			
<b>Dynamic specification</b>	yes			
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS	Parameter is evaluated at runtime.
		Applicable Command:	GLOBALS	Parameter may be specified dynamically with the GLOBALS system command.
<b>Application Programming Interface</b>	USR1005N	See SYSEXT - <i>Natural Application Programming Interfaces</i> in the Utilities documentation.		

This parameter only applies to the first report (Report 0). For additional reports, the statement EJECT with report specification (*rep*) has to be used.

Under Natural Security, the setting of this parameter can be overridden by the Session Parameters option of the Library Profile.



# 65

## EM - Edit Mask

---

▪ Syntax .....	144
▪ Blanks in Edit Masks .....	145
▪ Default Edit Masks .....	145
▪ Edit Masks for Numeric Fields .....	146
▪ Edit Masks for Alphanumeric Fields .....	149
▪ Edit Masks for Binary Fields - Format B .....	151
▪ Hexadecimal Edit Masks .....	151
▪ Edit Masks for Date and Time Fields - Formats D and T .....	153
▪ Edit Masks for Logical Fields - Format L .....	157

With this session parameter, you can specify an edit mask for an input and/or output field that is used in a `DEFINE DATA`, `DISPLAY`, `INPUT`, `MOVE EDITED`, `PRINT`, `PROCESS PAGE/PROCESS PAGE UPDATE` or `WRITE` statement.

For information on Unicode edit masks, see session parameter [EMU](#).

The parameter `EM` can also be used with `U` format fields. For information on Unicode format, see *Unicode and Code Page Support in the Natural Programming Language, Session Parameters*, [EMU](#), [ICU](#), [LCU](#), [TCU](#) versus `EM`, `IC`, `LC`, `TC`.

<b>Possible settings</b>		See below.
<b>Default setting</b>	none	
<b>Applicable statements:</b>	FORMAT	
	DEFINE DATA DISPLAY INPUT PRINT PROCESS PAGE/PROCESS PAGE UPDATE WRITE	Parameter may be specified at statement level and/or at element level.
	MOVE EDITED	Parameter may be specified at element level.
<b>Applicable command:</b>	none	

The following topics are covered below:

See also *Edit Masks - EM Parameter* in the *Programming Guide*.

## Syntax

For input fields, values must be entered exactly matching the edit mask. If you would like to display the edit mask for an input field, the field should be defined as modifiable (`AD=M`).

For a database field, a default edit mask may have been defined in the DDM. If you specify with the `EM` parameter an edit mask for a database field, this edit mask specified will be used instead of any default edit mask which may be defined for the field in the DDM.

If you specify `EM=OFF` for a field, no edit mask will be used for the field, not even one that may be defined in the DDM.

At statement level of a `DISPLAY`, `FORMAT`, `INPUT` or `WRITE` statement, no detail field edit mask may be specified, except `EM=OFF`.

An edit mask overrides any settings for the session parameters [AL](#), [NL](#) and [SG](#).



The characters 9, H, X and Z represent significant print positions in numeric (9, Z), hexadecimal (H), and alphanumeric (X) edit masks. For the difference between 9 and Z, see [Edit Masks for Numeric Fields](#), below.

### Examples:

```
DISPLAY AA(EM=OFF) AB(EM=XX.XX)
WRITE SALARY (EM=ZZZ,ZZ9)
```

An abbreviated notation can be used for long edit masks. The following examples demonstrate the abbreviated notation which may be used for numeric, hexadecimal, and alphanumeric edit masks:

```
EM=9(4)-9(5) is equivalent to: EM=9999-99999
EM=H(10) is equivalent to: EM=HHHHHHHHHH
EM=X(6)..X(3) is equivalent to: EM=XXXXXX..XXX
```

## Blanks in Edit Masks

Blanks within an edit mask are represented by the character on your keyboard that in hexadecimal code corresponds to H'20' (ASCII) or H'5F' (EBCDIC), that is, the character ^ (or ¬).

## Default Edit Masks

If no edit mask is specified for a field, a default edit mask is assigned to the field depending on the field format:

Field Format	Default Edit Mask
A	X
B	H
N, P, I	Z9
F	scientific representation
D	depends on default date format (as set with the profile parameter <a href="#">DTFORM</a> )
T	HH:II:SS
L	blank / X

## Edit Masks for Numeric Fields

An edit mask specified for a field of format N, P, I, or F must contain at least one 9 or Z.

If more 9s or Zs exist than the number of positions contained in the field value, the number of print positions in the edit mask will be adjusted to the number of digits defined for the field value.

If fewer 9s or Zs exist, the high-order digits before the decimal separator and/or low-order digits after the decimal separator will be truncated.

The following topics are covered below:

- [Characters for the Definition of Numeric Edit Masks](#)
- [Sign Characters](#)
- [Literal Leading Characters](#)
- [Literal Insertion and Trailing Characters](#)
- [Trailing Sign Characters](#)
- [Examples of Numeric Edit Masks](#)

### Characters for the Definition of Numeric Edit Masks

Character	Function
9	Position to be displayed (one digit of the field value).
. (period)	The first period inserted is used as a decimal separator. Subsequent periods are treated as literal characters.  <b>Note:</b> At this point, the period represents the sign currently defined as decimal separator character. If another character is chosen (for example, a comma) with the session or profile parameter <a href="#">DC</a> , this character is to be used instead.
Z	Zero suppression for leading zeros. This is the default for numeric fields. The letter Z may be repeatedly specified to represent floating zero suppression. Z must not be specified to the right of the decimal separator character. A zero value may be displayed as blanks using all Zs in the edit mask (see also session parameter <a href="#">ZP</a> ).

The 9s or Zs can be preceded by one or more other characters.

## Sign Characters

If the first character before the 9s or Zs is +, -, S or N, a sign may be displayed:

Character	Function
+	A floating sign is to be displayed preceding (leading sign character) or following (trailing sign character) the number. The sign may be generated as a plus or minus depending on the value of the field.
-	A floating minus is to be displayed preceding (leading sign character) or following (trailing sign character) the number if the value of the field is negative.
S	A sign is to be displayed to the left of the column. A plus sign is displayed for a positive value and a minus sign is displayed for a negative value.
N	A minus sign is to be displayed to the left of the column if the value of the field is negative.

## Literal Leading Characters

Any number of literal leading characters can appear before the first displayable position (as indicated by Z or 9). These must follow any sign character. If there is no sign character and the first literal leading character is +, -, S or N, it must be enclosed in apostrophes. If a literal leading character is H, X, Z or 9, it must be enclosed in apostrophes.

The first literal leading character specified will appear in the output only if the value contains leading zeros and the edit mask is defined with Z (leading zero suppression). This character will then be used as a filler character displayed instead of a blank for leading zeros. Subsequent literal leading characters will be displayed as they are input.

## Literal Insertion and Trailing Characters

Literal insertion and trailing characters can also be used. The symbol (^) can be used to represent a leading, inserted, or trailing blank. By enclosing significant characters (9, H, Z, X) in apostrophes, it is possible to use any characters as leading, insertion, or trailing characters. Insignificant edit mask characters need not be enclosed in apostrophes. Within the same edit mask notation, it is possible to have groups of leading, insertion, and/or trailing character strings, some of which are bounded by apostrophes and some of which are not.

## Trailing Sign Characters

A trailing sign character can be specified for numeric edit masks by using the + or - character as the last character in the edit mask. A + will produce a trailing + or - sign depending on the value of the field. A - will produce a trailing space or - sign depending on the value of the field. If a leading and trailing sign are specified in the edit mask, both will be produced.

## Examples of Numeric Edit Masks

The table below lists the results obtained from the original values shown at the top of each column as they are output without editing mask. All values used as column headings represent format N fields. The lines below the top column represent the formats obtained using the different editing masks:

Value	0000.03 (N4.2)	-0054 (N4)	+0087 (N4)	0962 (N4)	1830 (N4)
<b>Edit Mask</b>					
EM=9.9	0.0	4.	7.	2.	0.
EM=99	00	54	87	62	30
EM=S99	+00	-54	+87	+62	+30
EM=+Z9	+0	-54	+87	+62	+30
EM=-9.99	0.03	-4.	7.	2.	0.
EM=N9	0	-4	7	2	0
EM=*9.99	0.03	4.	7.	2.	0.
EM=Z99	00	54	87	962	830
EM=*EURZZ9.9	EUR**0.0	EUR*54.	EUR*87.	EUR962.	EUR830.
EM=999+	000+	054-	087+	962+	830+
EM=999-	000	054-	087	962	830
IC=\$ EM=ZZZ.99	\$.03	\$54.	\$87.	\$962.	\$830.
<b>EM=H(6)</b>					
- ASCII:	303030303033	30303574	30303837	30393632	31383330
- EBCDIC:	F0F0F0F0F0F3	F0F0F5D4	F0F0F8F7	F0F9F6F2	F1F8F3F0

By combining edit masks with the parameters IC and TC, negative numbers can be displayed in varying formats using a DISPLAY statement.

## Edit Masks for Alphanumeric Fields

An alphanumeric edit mask which is only to be used with A format fields must contain at least one X which represents a character to be displayed. An H as the first character designates a **hexadecimal edit mask**. A blank is represented by a (^) symbol. All other characters except parentheses are permissible including leading, trailing, and insertion characters. It is also possible to specify leading, insertion, or trailing characters enclosed within apostrophes. If the character X, a closing parenthesis, or a quotation mark is specified as an insertion character, it must be enclosed within apostrophes.

If leading characters are used before the first displayable position X of an alphanumeric edit mask, the first of these leading characters will not be displayed, but is used as filler character and replaces all leading blanks in the alphanumeric output field.

### Example:

```
DEFINE DATA LOCAL
1 #X (A4) INIT <' 34'>
END-DEFINE
WRITE #X (EM=*A:X:)
      6X #X (EM=*A:XX:)
      6X #X (EM=*A:XXX:)
      6X #X (EM=*A:XXXX:)
      6X #X (EM=1234XXXX5678)
END
```

### Output Produced:

```
A:*:      A:**:      A:**3:      A:**34:      23411345678
```

Trailing characters which immediately follow the last permissible print position will be displayed.

If the number of positions specified with the mask is smaller than the field length, the overhanging field content is not displayed.

If the number of positions specified with the mask is higher than the field length, the mask is truncated on the first overhanging position.

**Example:**

```

DEFINE DATA LOCAL
  1 #TEXT (A4) INIT <'BLUE'>
END-DEFINE
WRITE #TEXT (EM=X-X-X)      displays as 'B-L-U'      .. only three bytes of field
WRITE #TEXT (EM=X-X-X-X)   displayed
                           displays as 'B-L-U-E-' .. mask definition was
                           truncated to (EM=X-X-X-X-)

```

**Example of Alphanumeric Edit Masks**

The following program lists the alphanumeric edit masks for a field that is defined with format/length A4 and contains the value BLUE.

```

** Example 'EMMASK1': Edit mask
*****
DEFINE DATA LOCAL
  1 #TEXT (A4)
END-DEFINE
*
ASSIGN #TEXT = 'BLUE'
WRITE NOTITLE 'MASK 1:' 5X #TEXT (EM=X.X.X.X)
/             'MASK 2:' 5X #TEXT (EM=X^X^X^X)
/             'MASK 3:' 5X #TEXT (EM=X--X--X)
/             'MASK 4:' 5X #TEXT (EM=X-X-X-X-X-X)
/             'MASK 5:' 5X #TEXT (EM=X' 'X' 'X' 'X)
/             'MASK 6:' 5X #TEXT (EM=XX....XXX)
/             'MASK 7:' 5X #TEXT (EM=1234XXXX)
END

```

**Output of Program EMMASK1:**

```

MASK 1:    B.L.U.E
MASK 2:    B L U E
MASK 3:    B--L--U
MASK 4:    B-L-U-E-
MASK 5:    B L U E
MASK 6:    BL....UE
MASK 7:    234BLUE

```

## Edit Masks for Binary Fields - Format B

---

Edit masks for binary fields may be set using X or H notation. For binary fields, the X notation is supported as if H had been specified instead of X.

## Hexadecimal Edit Masks

---

If the character H is specified as the first character in an edit mask, the content of an alphanumeric or numeric field will be displayed in hexadecimal format. Each H represents two print positions that will occur for each byte in the source field. Characters other than H serve as insertion or trailing characters in the mask. The number of positions to be displayed will be adjusted to the length of the edit mask if the mask is shorter than the field. The length of the edit mask will be adjusted to the length of the field if the field length is shorter than the edit mask.

Insertion or trailing characters may be optionally specified bounded by apostrophes.

All fields displayed with a hexadecimal edit mask are treated as alphanumeric. Therefore, if the edit mask is shorter than the field to be edited, numeric or alphanumeric positions will be displayed from left to right disregarding any decimal separator positions.

If a hexadecimal edit mask is used as an input edit mask, every 0-9, a-f, A-F, blank and hex zero are accepted as a hex digit.



**Note:** Blank and hex zero are regarded as 0 and a lower-case letter (a-f) is regarded as an upper-case letter.

### Edit Mask Examples for Hexadecimal Fields:

The tables below list the hexadecimal edit masks with results obtained from the original fields and values shown above each column. All numeric values (-10, +10, 01) to which edit masks have been applied originated in fields defined with N2 format. The alphanumeric value AB originated from a field defined with format/length A2.

**ASCII:**

Value =>	AB	-10	+10	01
EM=HH	4142	3170	3130	3031
EM=H^H	41 42	31 70	31 30	30 31
EM=HH^H	4142	3170	3130	3031
EM=H-H	41-42	31-70	31-30	30-31
EM=H	41	31	31	30

**EBCDIC:**

Value =>	AB	-10	+10	01
EM=HH	C1C2	F1D0	F1F0	F0F1
EM=H:H	C1 C2	F1 D0	F1 F0	F0 F1
EM=HH:H	C1C2	F1D0	F1F0	F0F1
EM=H-H	C1-C2	F1-D0	F1-F0	F0-F1
EM=H	C1	F1	F1	F0

**Example Program Using Hexadecimal Edit Masks:**

```

** Example 'EMMASK2': Edit mask
*****
DEFINE DATA LOCAL
1 #TEXT1 (A2)
1 #TEXT2 (N2)
END-DEFINE
*
ASSIGN #TEXT1 = 'AB'
    
```



```

ASSIGN #TEXT2 = 10
*
WRITE NOTITLE
    'MASK (EM=HH)  :' 18T #TEXT1 (EM=HH)    30T #TEXT2 (EM=HH)
  / 'MASK (EM=H^H) :' 18T #TEXT1 (EM=H^H)  30T #TEXT2 (EM=H^H)
  / 'MASK (EM=HH^H):' 18T #TEXT1 (EM=HH^H)  30T #TEXT2 (EM=HH^H)
  / 'MASK (EM=H-H) :' 18T #TEXT1 (EM=H-H)   30T #TEXT2 (EM=H-H)
  / 'MASK (EM=H)   :' 18T #TEXT1 (EM=H)     30T #TEXT2 (EM=H)
END

```

### Output of Program EMMASK2 (ASCII):

```

MASK (EM=HH)  : 4142      3130
MASK (EM=H^H) : 41 42    31 30
MASK (EM=HH^H): 4142      3130
MASK (EM=H-H) : 41-42    31-30
MASK (EM=H)   : 41       31

```

### Output of Program EMMASK2 (EBCDIC):

```

MASK (EM=HH)  : C1C2      F1F0
MASK (EM=H^H) : C1 C2    F1 F0
MASK (EM=HH^H): C1C2      F1F0
MASK (EM=H-H) : C1-C2    F1-F0
MASK (EM=H)   : C1       F1

```

## Edit Masks for Date and Time Fields - Formats D and T

In edit masks for fields which are defined with format D (date) or T (time), the characters described in the following sections can be specified.

- [Date - Format D, and Time - Format T](#)
- [Syntactical Restrictions for Date Characters](#)
- [Hints for Input Edit Mask](#)
- [Hints for Week Display \(WW or ZW\) in Output Edit Mask](#)
- [Time - Format T - only](#)

- Examples of Date and Time Edit Masks

### Date - Format D, and Time - Format T

Character	Usage
DD	Day.
ZD	Day, with zero suppression.
MM	Month.
ZM	Month, with zero suppression.
YYYY	Year, 4 digits (see the section <a href="#">Hints for Input Edit Mask</a> ).
YY	Year, 2 digits (see the section <a href="#">Hints for Input Edit Mask</a> ).
Y	Year, 1 digit. Must not be used for input fields.
WW	Number of week (see the sections <a href="#">Hints for Input Edit Mask</a> and <a href="#">Hints for Week Display in Output Edit Mask</a> ).
ZW	Number of week, with zero suppression (see the sections <a href="#">Hints for Input Edit Mask</a> and <a href="#">Hints for Week Display in Output Edit Mask</a> ).
JJJ	Julian day.
ZZJ	Julian day with zero suppression.
NN . . . or N( <i>n</i> )	Name of day (language-dependent). The maximum length is determined by the number of Ns or by <i>n</i> . If the name is longer than the maximum length, it will be truncated; if it is shorter, the actual length of the name will be used.
0	Number of week day. The profile parameter <code>DTFORM</code> determines whether Monday or Sunday is considered the first day of the week. With <code>DTFORM=U</code> : (Sunday = 1, Monday = 2, etc.). With <code>DTFORM=other</code> : (Monday = 1, Tuesday = 2, etc.).
LL . . . or L( <i>n</i> )	Name of month (language-dependent). The maximum length is determined by the number of L characters or by <i>n</i> . If the name is longer than the maximum length, it will be truncated; if it is shorter, the actual length of the name will be used.
R	Year in Roman numerals (maximum 13 digits). Must not be used for input fields.

### Syntactical Restrictions for Date Characters

For *Input* and *Output* edit masks, you *may not* use the following:

text			characters		
month	with	month name	MM or ZM	with	LL or L( <i>n</i> )
day name	with	week day number	NN or N( <i>n</i> )	with	0

For *Input* edit masks, you *may not* use the following:

text			characters		
1-digit year	nor	a year in Roman numerals	Y	nor	R
Day	without	month or month name	DD or ZD	without	MM or ZM or LL or L( <i>n</i> )
Week	without	year	WW or ZW	without	YYYY or YY
Month	without	year	MM or ZM	without	YYYY or YY
Julian day	without	year	JJJ or ZZJ	without	YYYY or YY
Day name	without	week	NN or N( <i>n</i> )	without	WW or ZW
Week day number	without	week	0	without	WW or ZW
Julian day	with	month	JJJ or ZZJ	with	MM or ZM
Julian day	with	week	JJJ or ZZJ	with	WW or ZW
Month	with	week	MM or ZM	with	WW or ZW

### Hints for Input Edit Mask

The range of valid year values (YYYY) is 1582 - 2699.

If only year (YY or YYYY) but no month or day is specified within an input edit mask, the values for month and day will both be set to 01. If only year (YY or YYYY) and month (MM) but no day is specified within an input edit mask, the value for day will be set to 01.

If a 2-digits year (YY) is used, the century used to fill up the year representation is the current century by default. However, this does not apply when a Sliding or Fixed Window is set. For more details, please refer to profile parameter [YSLW](#) in the Natural Parameter Reference documentation.

If a week number (WW or ZW) but no number of week day (0) or name of day (NN . . .) is specified, the first day of the week is assumed.

### Hints for Week Display (WW or ZW) in Output Edit Mask

When `DTFORM=U` (USA format) is set, the week starts on Sunday; whereas for all other `DTFORM` settings the first weekday is Monday. Whether a week is week 52/53 of the old year or week 01 of the new year depends on which year contains more days of the week. In other words, if Thursday (Wednesday for `DTFORM=U`) of that week is in the previous year, the week belongs to the previous year; if it is in the next year, the week belongs to the next year.

If the number of week (WW or ZW) and a year representation (YYYY or YY or Y) is in the same edit mask, the display for year always corresponds to the week number, regardless of the year in the underlying date field.

**Example:**

```
DEFINE DATA LOCAL
1 D (D)
END-DEFINE
MOVE EDITED '31-12-2003' TO D(EM=DD-MM-YYYY)
DISPLAY D(EM=DD-MM-YYYY_N(10)) D(EM=DD-MM-YYYY/WW)
```

Although the underlying date is the 31 Dec. 2003, when the week number WW is contained in the edit mask, it displays as:

```
-----D-----D-----
31-12-2003_Wednesday 31-12-2004/01
```

**Time - Format T - only**

Character	Usage
T	Tenths of a second.
SS	Seconds.
ZS	Seconds, with zero suppression.
II	Minutes.
ZI	Minutes, with zero suppression.
HH	Hours.
ZH	Hours, with zero suppression.
AP	AM/PM element.

**Examples of Date and Time Edit Masks**

```
** Example 'EMDATI': Edit mask for date and time variables
*****
*
WRITE NOTITLE
' DATE INTERNAL : ' *DATX (DF=L) /
'           : ' *DATX (EM=N(9)' 'ZW.'WEEK 'YYYY) /
'           : ' *DATX (EM=ZZJ'.DAY 'YYYY) /
'   ROMAN      : ' *DATX (EM=R) /
'   AMERICAN   : ' *DATX (EM=MM/DD/YYYY)      12X 'OR ' *DAT4U /
'   JULIAN     : ' *DATX (EM=YYYYJJJ)        15X 'OR ' *DAT4J /
'   GREGORIAN : ' *DATX (EM=ZD.' 'L(10)' 'YYYY) 5X 'OR ' *DATG ///
```

```

*
' TIME INTERNAL : ' *TIMX                14X 'OR ' *TIME /
'              : ' *TIMX (EM=HH.II.SS.T) /
'              : ' *TIMX (EM=HH.II.SS' 'AP) /
'              : ' *TIMX (EM=HH)
END

```

### Output of Program EMDATI:

```

DATE INTERNAL : 2005-01-12
               : Wednesday 2.WEEK 2005
               : 12.DAY 2005
  ROMAN       : MMV
  AMERICAN    : 01/12/2005           OR 01/12/2005
  JULIAN      : 2005012              OR 2005012
  GREGORIAN   : 12.January2005      OR 12January 2005

TIME INTERNAL : 16:04:14             OR 16:04:14.8
               : 16.04.14.8
               : 04.04.14 PM
               : 16

```

## Edit Masks for Logical Fields - Format L

For fields of format L (logical fields), edit masks can be defined as follows:

```
(EM=[false-string][true-string])
```

The *false-string* must not be longer than 31 characters.

### Example of Edit Masks for Logical Field

```

** Example 'EMLOGV': Edit mask for logical variables
*****
DEFINE DATA LOCAL
1 #SWITCH (L) INIT <true>
1 #INDEX (I1)
END-DEFINE
*
FOR #INDEX 1 5
  WRITE NOTITLE #SWITCH (EM=FALSE/TRUE) 5X 'INDEX =' #INDEX
  WRITE NOTITLE #SWITCH (EM=OFF/ON)      7X 'INDEX =' #INDEX
  IF #SWITCH
    MOVE FALSE TO #SWITCH

```

```
ELSE
  MOVE TRUE TO #SWITCH
END-IF
/*
SKIP 1
END-FOR
END
```

**Output of Program** EMLOGV:

```
TRUE      INDEX = 1
ON        INDEX = 1

FALSE     INDEX = 2
OFF       INDEX = 2

TRUE      INDEX = 3
ON        INDEX = 3

FALSE     INDEX = 4
OFF       INDEX = 4

TRUE      INDEX = 5
ON        INDEX = 5
```

# 66

## EMFM - Edit Mask Free Mode

---

This Natural profile parameter is used to activate/deactivate the Edit Mask Free mode at session startup. This mode allows you to omit literals during input into a field with a numeric edit mask.

<b>Possible settings</b>	ON	Edit Mask Free Mode is activated.
	OFF	Edit Mask Free Mode is deactivated.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	Within a running Natural session, you may override this setting with the terminal control command %FM+ or %FM-.

For additional information, see *Numeric Edit Mask Free Mode* in the INPUT statement description in the *Statements* documentation.





# 67

## EMU - Unicode Edit Mask

---

With this session parameter, you can specify a Unicode edit mask for an input and/or output field that is used in a `DEFINE DATA`, `DISPLAY`, `INPUT`, `MOVE EDITED`, `PRINT`, `PROCESS PAGE` or `WRITE` statement.

<b>Possible settings</b>		See below.
<b>Default setting</b>	none	
<b>Applicable statements</b>		
	DEFINE DATA DISPLAY INPUT PRINT WRITE	Parameter may be specified at element level.
	MOVE EDITED	Parameter may be specified at element level.
<b>Applicable command</b>	none	

The syntax of the session parameter `EMU` is identical to that of the session parameter `EM` (see [EM syntax](#)).

See also *Unicode Edit Masks - EMU Parameter* in the *Programming Guide*.

Edit masks which are defined with `EMU` are kept in Unicode format so that the content is independent of the installed system code page.

For further information and an example, see also *Unicode and Code Page Support in the Natural Programming Language, Session Parameters*, section *EMU, ICU, LCU, TCU versus EM, IC, LC, TC*.



# 68

## ENDIAN - Endian Mode for Compiled Objects

---

This Natural profile and session parameter specifies the architecture for which the compiler should generate GP. See also *Portable Natural Generated Programs* in the *Programming Guide*.

Within a Natural session, the profile parameter settings can be overwritten by the session parameter ENDIAN.

<b>Possible settings</b>	DEFAULT	Endian mode is derived from the architecture currently used.	
	LITTLE	The compiler generates GP for Little Endian mode.	
	BIG	The compiler generates GP for Big Endian mode.	
<b>Default setting</b>	DEFAULT		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	none
		Applicable Command:	GLOBALS



# 69

## ENDMSG - Display Session-End Message

---

This Natural profile parameter is used to suppress the display the default message NAT9995 that is displayed at the end of the Natural session to indicate that the Natural session has been ended normally.

<b>Possible settings</b>	ON	Message NAT9995, NAT9978 or NAT9987 is written to the batch output file <b>CMPRINT</b> at the end of the session.
	OFF	Message NAT9995, NAT9978 or NAT9987 does not appear in <b>CMPRINT</b> .
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

- If Natural terminates with a startup error, then Natural message NAT9987 will be used instead of NAT9995.
- If Natural terminates with a runtime error, then Natural message NAT9978 will be used instead of NAT9995.



# 70

## ES - Empty Line Suppression

---

With this session parameter, you can suppress the printing of empty lines generated by a `DISPLAY` or `WRITE` statement.

<b>Possible settings</b>	ON	A line resulting from a <code>DISPLAY</code> or <code>WRITE</code> statement which contains all blank values will not be printed.  This setting is particularly useful when displaying arrays (for example, multiple-value fields or fields contained within a periodic group) to avoid printing a large number of empty lines.
	OFF	Empty line suppression is disabled.
<b>Default setting</b>	OFF	
<b>Specification within session</b>	yes	
<b>Applicable statements:</b>	<code>DISPLAY</code> <code>FORMAT</code> <code>WRITE</code>	
<b>Applicable command:</b>	none	

To achieve empty suppression for numeric values, the field must be specified with `ZP=OFF` and `ES=ON` in order to have null values printed as blanks. See also the session parameters [IS](#) and [ZP](#).

### Example:

```
DISPLAY (ES=ON) NAME CITY
```

See also *Parameters to Influence the Output of Fields* in the *Programming Guide*.





# 71 ESCAPE - Ignore Terminal Commands %% and %.

---

This Natural profile parameter can be used to disable the terminal commands %% and %..

<b>Possible settings</b>	ON	Enables the use of terminal commands %% and %..
	OFF	The terminal commands %% and %.. will be ignored; that is, it will not be possible to leave the currently active Natural program or the Natural session respectively by entering %% or %..
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 72

## ESXDB - Database ID Used for Entire System Server DDMs

---

This Natural profile parameter applies to the Entire System Server Interface.

It specifies the database ID used for Entire System Server's DDMs.

<b>Possible settings</b>	1 - 254	Database ID. To activate this parameter, a database ID in the range of 1 to 254 must be specified.  <b>Note:</b> Entire System Server's DDMs are cataloged with DBID=148. If you are using an Adabas database with this DBID, specify a different number for ESXDB. For information on how to do this, please refer to <i>Setting up the Entire System Server Interface</i> in the <i>Operations</i> documentation.
	0	With ESXDB=0, the Entire System Server Interface is not active.
<b>Default setting</b>	0	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 73

## ET - Execution of END/BACKOUT TRANSACTION

### Statements

---

This Natural profile parameter specifies for which databases END TRANSACTION and BACKOUT TRANSACTION statements are to be executed.

<b>Possible settings</b>	ON	END TRANSACTION and BACKOUT TRANSACTION statements are executed for all databases which have been referenced since the beginning of the Natural session or since the last execution of an END TRANSACTION and BACKOUT TRANSACTION statement.
	OFF	END TRANSACTION and BACKOUT TRANSACTION statements are executed only for the databases affected by the transaction (and - if applicable - for the database to which transaction data are written).
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



**Note:** Any updates to a database which are not executed under the control of Natural (that is, by native invocation of the database link routines) do not affect the Natural transaction logic.



# 74

## ETA - Error Transaction Program

---

This Natural profile parameter provides the name of the program which receives control if an error condition is detected during Natural program execution.

<b>Possible settings</b>	1 to 8 characters	Program name for error transaction.
	blank	With ETA=' ' (blank), no error transaction program is called.
<b>Default setting</b>	blank	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	yes	
<b>Application Programming Interface</b>	USR1041N	USR1041N is a sample error transaction program delivered in source form. See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

The setting of this parameter can be modified by a user program by way of assignment to the system variable \*ERROR-TA or, if Natural Security is installed, within the Natural Security library profile; see *Components of a Library Profile* in the *Natural Security* documentation.

For further information, see *Using an Error Transaction Program* in the *Programming Guide*.





# 75

## ETDB - Database for Transaction Data

---

This Natural profile parameter specifies the database in which transaction data, as supplied with an `END TRANSACTION` statement is to be stored.

<b>Possible settings</b>	1 - 65535, except 255	Database ID.  Database ID 255 is reserved for logical system files for Software AG products, see profile parameter <a href="#">LFILE</a> .
	0	The transaction data is written to the database specified with the profile parameter <a href="#">UDB</a> .
<b>Default setting</b>	0	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

Other transaction processing related parameters: [ET](#) | [ETEOP](#)

---

# 76

## ETEOP - Issue END TRANSACTION at End of Program

---

This Natural profile parameter determines whether or not an implicit END TRANSACTION statement is to be issued at the end of a Natural program (that is, before NEXT mode is reached).

<b>Possible settings</b>	ON	Natural will issue an implicit END TRANSACTION statement at the end of a Natural program.
	OFF	Natural will not issue any implicit END TRANSACTION statement at the end of a Natural program.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

---

# 77

## ETID - Adabas User Identification

---

This Natural profile parameter is used as an identifier for Adabas-related information; for example, for identification of data stored as a result of an `END TRANSACTION` statement.

<b>Possible settings</b>	1 to 8 characters	The setting is used as the user ID setting in an Adabas open call.  The Adabas user ID has its own syntax. Please consult your Adabas Command Reference Documentation if you want to use special characters for the setting of ETID.
	OFF	The ETID is set to ' ' (blanks), but Natural Security is allowed to set the ETID.
	' ' (blank)	The ETID is set to ' ' (blanks). This value is passed to Adabas on an open call without being modified by Natural Security.
	\$\$	The ETID is replaced by the process ID.
<b>Default setting</b>	' ' (blank)	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

If the ETID is not specified neither in NATPARM nor dynamically, Natural uses the setting of \*INIT-USER to fill the ETID.

The UNIX shell will replace \$\$ by the process ID of your shell process before executing Natural, however, if the ETID is specified in NATPARM, \$\$ will be evaluated during the start-up of Natural.

The ETID might also be used by Natural for work-file name generation. This might cause problems when running multiple instances on one machine or again, if special characters are used for the setting of ETID. Please refer to the Natural parameter [TMPSORTUNIQU](#) for a solution.



# 78 ETPDB - Databases Containing Entire Transaction

## Propagator Master Files

---

This Natural profile parameter only applies if Software AG's Entire Transaction Propagator is installed.

ETPDB specifies the databases that contain Entire Transaction Propagator master files.

<b>Possible settings</b>	1 - 255	Database IDs; for details, see the Entire Transaction Propagator documentation.  Mark all databases in the parameter's database list that contain master files.
	0	Entire Transaction Propagator is not to be used.
	' ' (blank)	
<b>Default setting</b>	' ' (blank)	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	





# 79

## ETPSIZE - Size of Entire Transaction Propagator Buffer

---

This Natural profile parameter only applies if Entire Transaction Propagator is installed. It determines the size of the Entire Transaction Propagator buffer.

<b>Possible settings</b>	10 - 63	Size of the Entire Transaction Propagator buffer in KB.  If Entire Transaction Propagator is to be used, an appropriate value has to be specified for this parameter; see the Entire Transaction Propagator documentation.  If the requested space is not available, the Entire Transaction Propagator cannot be used.
	0	Entire Transaction Propagator is not to be used.
<b>Default setting</b>	0	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 80

## FC - Filler Character for INPUT Statement

---

This Natural profile parameter is used to specify the default filler character to be used for fields displayed by an INPUT statement.

<b>Possible settings</b>	any character	Default filler character.  It is used to pre-fill fields non-protected input fields (field attribute specification <code>AD=A</code> ) when fields are written to a terminal by an INPUT statement.  For modifiable input fields (field attribute specification <code>AD=M</code> ), it is used to fill the rest of the field.
<b>Default setting</b>	blank	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

---

# 81 FC - Filler Character for DISPLAY Statement

---

With this session parameter, you specify the filler character which will appear on either side of a heading produced by a `DISPLAY` statement across the full column width.

Unlike the `GC` parameter, which applies to headings across a group of columns, the `FC` parameter applies to individual columns.

<b>Possible settings</b>	any character	Filler character for individual headings.  FC only applies if the column width is determined by the field length and not by the header (see also session parameter <code>HW</code> ); otherwise the <code>FC</code> setting will be ignored.	
<b>Default setting</b>	blank		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT
		Applicable Command:	none

## Example:

```
DISPLAY (FC=*)
```

---

# 82

## FCDP - Filler Character for Dynamically Protected Input

### Fields

---

This Natural profile and session parameter can be used to suppress the display of filler characters for input fields that have been made write-protected dynamically (that is, to which the attribute `AD=P` has been assigned via an attribute control variable).

Depending on the setting of the `FCDP` parameter, dynamically protected input fields are displayed filled either with blanks or with the defined filler characters.

Within a Natural session, the profile parameter `FCDP` can be overridden by the session parameter `FCDP`.

<b>Possible settings</b>	ON	Dynamically protected input fields are displayed filled with filler characters. This may suggest to the users that they could enter something in the fields.	
	OFF	Dynamically protected input fields are displayed filled with blanks.	
<b>Default setting</b>	ON		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces in the Utilities</i> documentation.	

**Example:**

```

DEFINE DATA LOCAL
1 #FIELD1 (A5)
1 #FIELD2 (A5)
1 #CVAR1 (C) INIT <(AD=P)>
1 #CVAR2 (C)
END-DEFINE
*
INPUT #FIELD1 (AD=Y'_' CV=#CVAR1) /* field is protected
      #FIELD2 (AD=Y'_' CV=#CVAR2) /* field is not protected
...
END

```

Execution of the above program will display the following:

FCDP=ON:

#FIELD1 \_\_\_\_\_ #FIELD2 \_\_\_\_\_

FCDP=OFF:

#FIELD1            #FIELD2 \_\_\_\_\_



# 83

## FDDM - Natural System File for DDMs

This Natural profile parameter is used to specify five subparameters for the Natural system file for DDMs.

If this system file is defined, all DDMs are stored on the specified path. DDMs stored in libraries will no longer be accessible from Natural. This is similar to Natural on mainframes, where all DDMs are stored in the system file `FDIC`.

If the FDDM system file is undefined (*database-ID* and *file-number* = 0), the DDMs are stored in the libraries as supplied before. The system file FDDM is displayed as an inactive environment.

For information on system files, refer to: System Files in the Natural Operations documentation.

<b>Possible settings</b>	<i>database-ID</i>	1 - 254	Database ID 255 is reserved for logical system files for Software AG products, see Natural profile parameter <a href="#">LFILE</a> .
	<i>file-number</i>	1 - 255	File number.
	<i>password</i>	1 - 8 characters	The password is only required if the Natural user-program system file has been password-protected using the Adabas security feature.  The password is reserved for future use; currently, it is ignored.
	<i>cipher key</i>	1 - 8 numeric digits	The cipher key is only required if the Natural user-program system file has been ciphered using the Adabas security feature.  The cipher key is reserved for future use; currently, it is ignored.
	RO		Indicates that the Natural user-program system file is "read-only" and is only specified if modifications on the file are to be disabled.

<b>Default setting</b>	none
<b>Dynamic specification</b>	yes
<b>Specification within session</b>	no

The syntax of this parameter is:

```
FDDM=(database-ID,file-number,password,cipher-key,RO)
```

**Examples:**

```
FDDM=(22,5)
FDDM=(22,5,,12345)
FDDM=(22,5,,,RO)
```

# 84 FDIC - Predict System File

This Natural profile parameter defines four subparameters for the Predict system file which Predict uses to retrieve and/or store data.



**Note:** In a remote development environment, a Development Server File is used instead, see the *SPoD - Natural's Single Point of Development* and the *Natural Development Server* documentation.

For specific information on system files, refer to:

*System Files* in the *Operations* documentation.

<b>Possible settings</b>	<i>database-ID</i>	1 - 65535, except 255	Database ID 255 is reserved for logical system files for Software AG products, see profile parameter <a href="#">LFILE</a> . If no FDIC is available, do not enter anything in the DBID field.
	<i>file-number</i>	:1 - 5000	File number. If no FDIC is available, do not enter anything in the file number field.
	<i>password</i>	1 to 8 characters	The password is only required if the Predict system file has been password-protected using the Adabas security feature.
	<i>cipher-key</i>	1 to 8 numeric digits	Cipher key for the Predict system file. It is only required if the Predict system file has been ciphered using the Adabas security feature.
		RO	Read only option - not supported on this platform.
<b>Default setting</b>	none		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	no		

The syntax for this parameter is:

```
FDIC=(database-ID,file-number,password,cipher-key,RO)
```

**Examples:**

```
FDIC=(10,5,PASSW1,12345678)
FDIC=(1,200,,12345678)
FDIC=(1,5)
FDIC=(,5)
```

# 85

## FL - Floating Point Mantissa Length

---

With this session parameter, you specify the mantissa length of a floating point variable during input or output.

<b>Possible settings</b>	1 - 16	Mantissa length. The total length is FL + 6 for sign, exponent, and decimal character.	
<b>Default setting</b>	none		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT INPUT PRINT WRITE
		Applicable Command:	none

### Example:

```
DISPLAY FL=5    ->    +1.2345E+03
```

---

# 86

## FNAT - Natural System File for System Programs

This Natural profile parameter is used to specify the database ID, file number, password and cipher key and read-only flag for the Natural system file for Natural system programs.

The Natural system file is the file from which all Natural system programs are retrieved and upon which all system commands operate. Error texts and Natural help information related to the Natural system libraries are also contained in this system file.

For specific information on system files, refer to *System Files* in the *Operations* documentation.

<b>Possible settings</b>	<i>database-ID</i>	1-254	Database ID 255 is reserved for logical system files for Software AG products, see profile parameter <a href="#">LFILE</a> .
	<i>file-number</i>	1-255	File number.
	<i>password</i>	1 to 8 characters	The password is only required if the Natural system file has been password-protected using the Adabas security feature.  The password is reserved for future use; currently, it is ignored.
	<i>cipher key</i>	1 to 8 numeric digits	The cipher key is only required if the Natural system file has been ciphered using the Adabas security feature.  The cipher key is reserved for future use; currently, it is ignored.
	R0		Read-only option. R0 indicates that the Natural system file is "read-only" and is only specified if modifications on the file are to be disabled.
<b>Default setting</b>	none		
<b>Dynamic specification</b>	yes		

<b>Specification within session</b>	no
-------------------------------------	----

The syntax of this parameter is:

```
FNAT=(database-ID,file-number,password,cipher-key,RO)
```

**Examples:**

```
FNAT=( ,102)  
FNAT=(99,102, , ,RO)  
FNAT=(99,102,PASSW2)
```



# 87

## FREEGDA - Release GDA in Utility Mode

---

This Natural profile parameter controls whether current user global data area (GDA) and application-independent variables (AIV) are to be reset or not when a utility is invoked in utility mode (see *Utility Activation* in the *Utilities* documentation), that is, by using the direct command that corresponds to the utility's name.

<b>Possible settings</b>	ON	The current user GDA and AIV variables are reset before a utility is started. This behavior corresponds to the previous situation when the utility was invoked using the system command <code>LOGON &lt;library&gt;</code> .
	OFF	The current user GDA and AIV variables are preserved when a utility is started. Note that this will increase the data size correspondingly and may lead to thread problems under certain operating systems.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 88

## FS - Default Format/Length Setting for User-Defined

### Variables

---

This Natural profile and session parameter only applies to reporting mode; it has no effect in structured mode.

This parameter determines whether a default format/length setting is to be in effect for the definition of user-defined variables in reporting mode; see also *Format and Length of User-Defined Variables* in the *Programming Guide*.

Within a Natural session, the profile parameter FS can be overridden by the session parameter FS.

<b>Possible settings</b>	ON	No default format/length is assigned by Natural for a newly introduced variable in reporting mode. The format/length of all user-defined variables must be explicitly specified.	
	OFF	A user-defined variable in a Natural program for which no format/length is specified is assigned the default format/length N7.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See SYSEXT - <i>Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

**Under Natural Security:** The setting of this parameter can be overridden by the Session Parameters option of the Library Profile.



# 89

## FSEC - Natural Security System File

This Natural profile parameter only applies if Natural Security is used.

This parameter defines four subparameters for the Natural Security system file which is used by Natural Security to retrieve/store its security information.

For information on system files, refer to *System Files* in the *Operations* documentation.

Possible settings	<i>database-ID</i>	1-65535, except 255	Database ID 255 is reserved for logical system files for Software AG products, see profile parameter <a href="#">LFILE</a> .
		0	DBID=0 sets FSEC inactive. This is mandatory for a non-security environment.  If no FSEC system file is available, do not enter anything in the file number field.
	<i>file-number</i>	1-5000	File number for the Natural Security system file.
		0	FNR=0 sets FSEC inactive. This is mandatory for a non-security environment.  If no FSEC system file is available, do not enter anything in the file number field.
	<i>password</i>	1 to 8 characters	The password is only required if the Natural Security system file has been password-protected using the Adabas security feature.  The password is reserved for future use; currently, it is ignored.
	<i>cipher-key</i>	1 to 8 numeric digits	The cipher key is only required if the Natural Security system file has been ciphered using the Adabas security feature.  The cipher key is reserved for future use; currently, it is ignored.

	RO	Read only option - not supported on this platform.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

The syntax of this parameter is:

```
FSEC=(database-ID,file-number,password,cipher-key,RO)
```

**Examples:**

```
FSEC=(10,8)
FSEC=10,5,PASSW1,12345678
FSEC=1,200,,12345678
```

# 90

## FUSER - Natural System File for User Programs

This Natural profile parameter defines five subparameters for the Natural user-program system file. This system file is the database file from which all user-written Natural programs are retrieved.

For information on system files, refer to: *System Files* in the *Operations* documentation.

<b>Possible settings</b>	<i>database-ID</i>	1-254	Database ID 255 is reserved for logical system files for Software AG products, see profile parameter <a href="#">LFILE</a> .
	<i>file-number</i>	1-255	File number.
	<i>password</i>	1 to 8 characters	The password is only required if the Natural user-program system file has been password-protected using the Adabas security feature.  The password is reserved for future use; currently, it is ignored.
	<i>cipher-key</i>	1 to 8 numeric digits	The cipher key is only required if the Natural user-program system file has been ciphered using the Adabas security feature.  The cipher key is reserved for future use; currently, it is ignored.
	RO		Read-only option. RO indicates that the Natural user-program system file is "read-only" and is only specified if modifications on the file are to be disabled.
<b>Default setting</b>	none		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	no		

The syntax of this parameter is:

```
FUSER=(database-ID,file-number,password,cipher-key,RO)
```

**Examples:**

```
FUSER=( 22 , 5 )  
FUSER=( 22 , 5 , , , RO )  
FUSER=( 22 , 5 , PASSW2 )
```



# 91 GC - Filler Character for Group Headers

---

With this session parameter, you specify the filler character which will appear on either side of a group heading produced by a `DISPLAY` statement across all field columns that belong to that group.

Unlike the `FC` parameter, which applies to individual columns, the `GC` parameter applies to headings across a group of columns.

<b>Possible settings</b>	any character	Filler character for group headers.	
<b>Default setting</b>	blank		
<b>Specification within session</b>	yes	Applicable Statements:	<code>DISPLAY</code> <code>FORMAT</code>
		Applicable Command:	None

## Example:

```
DISPLAY (GC=*)
```



# 92 GFID - Global Format IDs

---

This Natural profile and session parameter is used to control Natural's internal generation of global format IDs so as to influence Adabas's performance concerning the re-usability of format buffer translations.

<b>Possible settings</b>	ON	Global format IDs are generated for all views.	
	OFF	Global format IDs are not generated.	
	VID	Global format IDs are generated only for views in local/global data areas, but not for views defined within programs.	
<b>Default setting</b>	ON		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	OPTIONS
		Applicable Commands:	GFID option of COMPOPT.

For details on global format IDs, see the Adabas documentation.



# 93

## HC - Header Centering

---

This session parameter determines the placement of column headers.

<b>Possible settings</b>	C	Headers will be centered.	
	L	Headers will be left-justified.	
	R	Headers will be right-justified.	
<b>Default setting</b>	C		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT
		Applicable Command:	none

### Example:

```
DISPLAY (HC=L)
```

---



# 94

## HD - Header Definition

---

With this session parameter, you define which default text is to be used when

- the field is output with a `DISPLAY` statement;
- an equal sign (=) is placed immediately before the field in a `WRITE` or `INPUT` statement.

<b>Possible settings</b>	<code>'text'</code>	120 alphanumeric or Unicode characters at maximum.
<b>Default setting</b>	none	
<b>Applicable Statement:</b>	<code>DEFINE DATA</code>	Parameter may be specified at field/element level.
<b>Applicable Command:</b>	none	





# 95 HE - Helproutine

---

▪ HE Parameter Syntax .....	218
▪ Execution of Helproutines .....	220
▪ Examples .....	220

With this session parameter, you assign a helproutine or a help map to a field.

<b>Possible settings</b>		See <i>HE Parameter Syntax</i> below.	
<b>Default setting</b>	none		
<b>Specification within session</b>	yes	Applicable Statements:	INPUT
		Applicable Command:	none

Helproutines can be created with the Natural program editor, help maps with the Natural map editor.

The helproutine or help map may then be invoked during processing of an INPUT statement or a map by choosing either of the following methods:

- In the field for which to invoke the help request, enter the help character (question mark (?) by default) and press ENTER.
- Place the cursor in the field for which to invoke the help request and press the PF key defined as help function key with the SET KEY statement.

The following topics are covered below:

## HE Parameter Syntax

---

The syntax of this parameter is:

$$HE=operand1 \left[ , \left\{ \begin{array}{l} operand2 \\ = \\ nX \end{array} \right\} \right] \dots 20$$

Operand Definition Table:

Operand	Possible Structure	Possible Formats	Referencing Permitted	Dynamic Definition
<i>operand1</i>	C S	A	no	no
<i>operand2</i>	C S A	A U N P I F B D T L C O	no	no

## Syntax Description:

<i>operand1</i>	<i>operand1</i> is the name of the helproutine or help map to be invoked. The name may be a 1 to 8 character alphanumeric constant or user-defined variable. If a variable is used, it must have been previously defined. The name may contain an ampersand (&); at execution time, this character will be replaced by the one-character code corresponding to the current value of the Natural system variable *LANGUAGE. This feature allows the use of multi-lingual helproutines or help maps.
<i>operand2</i>	You may specify 1 to 20 parameters ( <i>operand2</i> ) which are passed to the helproutine or help map. They may be specified as constants or as user-defined variables which contain the values of the parameters.
=	<p>The equals sign (=) is used to pass an object or a field name to a helproutine or help map:</p> <ul style="list-style-type: none"> <li>■ If the equals sign is entered in the HE= specification at statement level, the name of the object (as contained in the system variable *PROGRAM) being executed is passed to the helproutine or help map. In <a href="#">Example 3</a>, the object name passed is PROGRAM1.</li> <li>■ If the equals sign is entered in the HE= specification at field level, the name of the field is passed to the helproutine or help map. In <a href="#">Example 3</a>, the field name passed is #PARAM1.</li> </ul> <p>If the equals sign is used as a parameter, the corresponding parameter in the helproutine or help map must be specified with format/length A65.</p>
<i>nX</i>	The notation <i>nX</i> can be used to specify parameters to be omitted, that is, for which no values are to be passed. The corresponding receiving parameters in the called helproutine's DEFINE DATA PARAMETER statement must be defined as OPTIONAL.

**Notes:**

1. The operands must be separated either by the input delimiter character (as specified with the session parameter **ID**) or by a comma. However, a comma must not be used for this purpose if the comma is defined as decimal character (with the session parameter **DC**).
2. If parameters are specified, the helproutine must begin with a DEFINE DATA PARAMETER statement which defines fields that correspond with the parameters in format and length.
3. The value of the field for which a helproutine is specified may be referenced within the helproutine. This is done by specifying a field in the DEFINE DATA PARAMETER statement which corresponds in format and length with the original field. In the block of fields defined within the DEFINE DATA PARAMETER statement, this field must always be defined behind the parameters, if present.
4. If the field for which a helproutine is specified is an array element, its indices may be referenced by the helproutine. To do so, you specify index parameters with format I (integer), N (numeric unpacked), or P (packed numeric) at the end of the DEFINE DATA PARAMETER statement. You may specify up to three index parameters according to array dimensions.

## Execution of Helproutines

---

If a helproutine or help map is requested - by entering a question mark (?) in the field, or by pressing the help key (as defined with a `SET KEY` statement), or via a `REINPUT USING HELP` statement - all other data that may have been entered into fields are not assigned to the program variables until all help requests have been processed.



**Note:** Only one help request per `INPUT` statement is possible; that is, if help is requested for more than one field (for example, by entering question marks in multiple fields), only the first help request will be executed.

## Examples

---

### Example 1:

```
/* MAIN PROGRAM
DEFINE DATA
1 #A(A20/1:3)
END-DEFINE
...
SET KEY PF1=HELP
...
INPUT #A (2) (HE='HELPA',=)
...
END
```

### Example 2:

```
/* HELP-ROUTINE 'HELPA'
DEFINE DATA PARAMETER
1 #VARNAME (A65)
1 #PARM1 (A20)
1 #VARINDEX (I2)
END-DEFINE
...
```

**Example 3:**

```
* Program 'PROGRAM1'
*
DEFINE DATA LOCAL
1 #PARM1 (A65) INIT <'valueparm1'>
END-DEFINE
SET KEY PF1 = HELP
FORMAT KD=ON
*
INPUT (AD=M HE='HELP1',=)
  'Enter ? for name of executed object:'
  / #PARM1
*
INPUT (AD=M)
  'Enter ? for field name:'
  / #PARM1 (HE='HELP1',=)
*
END
```

**Parameter Data Area in Example Helproutine HELP1:**

```
* Helproutine 'HELP1'
*
DEFINE DATA PARAMETER
1 #FLD1 (A65)
END-DEFINE
...
```



# 96

## HI - Help Character

This Natural profile parameter defines the character which is to be used to invoke a field-specific helproutine or a map helproutine (if defined for a given map).

<b>Possible settings</b>	any special character	The character which is to be used to invoke a field-specific helproutine or a map helproutine.  The character specified with the profile parameter HI must not be the same as the one specified with the profile/session parameter CF (control character for mainframe terminal commands); it should not be the same as the one specified with the profile/session parameter DC (decimal character), profile/session parameter IA (input assign character) or profile/session parameter ID (input delimiter character).
	blank	When HI=' ' is set, a help key must be defined in the Natural application, using the SETKEY statement correspondingly; otherwise it is not possible to invoke a helproutine for any field.
<b>Default setting</b>	?	Question mark.
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR0350N	See SYSEXT - <i>Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.





# 97 HW - Heading Width

---

With this session parameter you determine the width of a column output with a `DISPLAY` statement.

<b>Possible settings</b>	ON	The width of a <code>DISPLAY</code> column is determined by either the length of the heading text or the length of the field, whichever is longer. This is true even if no heading text is output, either because the <code>DISPLAY</code> statement contains the keyword <code>NOHDR</code> or the <code>DISPLAY</code> statement is a subsequent <code>DISPLAY</code> (see also the <code>DISPLAY</code> statement).	
	OFF	The width of a <code>DISPLAY</code> column is determined by the length of the field. <code>HW=OFF</code> only applies to <code>DISPLAY</code> statements which do not create headers (that is, either a first <code>DISPLAY</code> statement with <code>NOHDR</code> option or a subsequent <code>DISPLAY</code> statement).	
<b>Default setting</b>	ON		
<b>Specification within session</b>	yes	Applicable Statements:	<code>DISPLAY</code> <code>FORMAT</code>
		Applicable Command:	none

## Example:

```
DISPLAY (HW=OFF)
```



# 98

## IA - Input Assign Character

This Natural profile and session parameter defines the character to be used as the assignment character for the input parameter processing in `INPUT` statements, either in keyword/delimiter mode or when processing data from the Natural stack.

Within a Natural session, the profile parameter `IA` can be overridden by the session parameter `IA`.

<b>Possible settings</b>	any special character	Assignment character for the input parameter processing in <code>INPUT</code> statements. The character specified with the <code>IA</code> parameter <ul style="list-style-type: none"> <li>■ must not be the same as the character specified with the profile/session parameters <code>CF</code> (control character for mainframe terminal commands), <code>DC</code> (decimal character) or <code>ID</code> (input delimiter character);</li> <li>■ should not be the same as the one specified with the profile parameter <code>HI</code> (help character).</li> </ul>	
<b>Default setting</b>	=	Equals sign.	
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

**Example:**

In the following example, it is assumed that, for the beginning, the default input assign character (=) applies.

```
** Example 'IACHAR': Input Assign character
*****
DEFINE DATA LOCAL
1 #A (A1)
1 #B (A1)
END-DEFINE
*
INPUT #A #B
*
WRITE 'Field #A:' #A / 'Field #B:' #B
*
END
```

**1. Enter the command**

```
IACHAR #A=Y,#B=X
```

The program produces the following output:

```
Page      1                                05-01-19  11:05:51
Field #A: Y
Field #B: X
```

**2. Enter the command**

```
GLOBALS IA=:
```

This sets the input assign character to colon (:).

**3. Then enter the command**

```
IACHAR #B:X,#A:Y
```

The program produces the following output:

Page 1

06-11-13 12:12:24

Field #A: Y


Field #B: X

**Under Natural Security:** The setting of this parameter can be overridden by the *Session Parameters* option of the Library Profile.



# 99 IC - Insertion Character

With this session parameter, you specify the character string to be inserted in the column immediately preceding the value of a field output with a `DISPLAY` statement. The width of the output column is enlarged accordingly.

 **Note:** The difference between the session parameters `LC`, `LCU` and `IC`, `ICU` will be evident, if the corresponding field is output right justified (`AD=R`). The insertion character is inserted between leading spaces and the field value whereas the leading character is output in front of the leading space.

For numeric values, the insertion characters will be placed before the first significant digit printed.

The `IC` and `LC` parameters are mutually exclusive.

The parameter `IC` can also be used with `U` format fields. For information on Unicode format, see also *Unicode and Code Page Support in the Natural Programming Language, Session Parameters, EMU, ICU, LCU, TCU versus EM, IC, LC, TC* in the *Unicode and Code Page Support* documentation.

<b>Possible settings</b>	any character	Character string to be inserted. You can specify a string of one to ten characters. Insertion characters may optionally be specified within apostrophes, in which case any characters can be specified. Any character string specified which contains a closing parenthesis or a quotation mark must be enclosed within apostrophes. A blank in a character string not enclosed within apostrophes is represented by a circumflex (^).	
<b>Default setting</b>	none		
<b>Specification within session</b>	yes	Applicable Statements:	<code>DISPLAY</code> <code>FORMAT</code>
		Applicable Command:	none

**Examples:**

```
DISPLAY AA(IC=*)  
DISPLAY SALARY(IC='$')
```

See also *Parameters to Influence the Output of Fields in the Programming Guide*.



# 100

## ICU - Unicode Insertion Character

---

The session parameter `ICU` is identical to the session parameter `IC`. The difference is that the insertion characters are always stored in Unicode format. This allows you to specify insertion characters with mixed characters from different code pages, and assures that always the correct character is displayed independent of the installed system code page.

With this session parameter, you specify the character string to be inserted in the column immediately preceding the value of a field output with a `DISPLAY` statement. The width of the output column is enlarged accordingly.

For numeric values, the insertion characters will be placed before the first significant digit printed.

The parameters `ICU` and `LCU` are mutually exclusive.

<b>Possible settings</b>	any character	Character string to be inserted. You can specify a string of one to ten characters.  Insertion characters may optionally be specified within apostrophes, in which case any characters can be specified. Any character string specified which contains a closing parenthesis or a quotation mark must be enclosed within apostrophes. A blank in a character string not enclosed within apostrophes is represented by a circumflex (^).	
<b>Default setting</b>	none		
<b>Specification within session</b>	yes	Applicable Statements:	<code>DISPLAY</code> <code>FORMAT</code>
		Applicable Command:	none

See also:

- *Parameters to Influence the Output of Fields in the Programming Guide*
- *Unicode and Code Page Support in the Natural Programming Language, Session Parameters, EMU, ICU, LCU, TCU versus EM, IC, LC, TC in the Unicode and Code Page Support documentation.*



# 101 ID - Input Delimiter Character

---

This Natural profile and session parameter defines the character to be used as a delimiter character for INPUT statements in keyword/delimiter mode.

Within a Natural session, the profile parameter ID can be overridden by the session parameter ID.

<b>Possible settings</b>	any special character	Input delimiter character. The character specified with this parameter <ul style="list-style-type: none"><li>■ must not be the same as the one specified with the profile/session parameter <b>DC</b> (decimal character) or <b>IA</b> (input assign character);</li><li>■ should not be the same as the one specified with the <b>CF</b> parameter (control character for mainframe terminal commands) or <b>HI</b> parameter (help character).</li></ul> The period (.) should not be used as input delimiter, because this might lead to situations in which a program termination period would be misinterpreted as input delimiter. An asterisk (*) should not be used either.
--------------------------	-----------------------	---

**Under Natural Security:** The setting of this parameter can be overridden by the Session Parameters option of the Library Profile.



# 102

## IKEY - Processing of PA and PF Keys

---

This Natural profile parameter specifies the action to be taken when a video-terminal program-attention key (PA key) or program-function key (PF key) is used to enter data, and the key has not been defined to the Natural program with the `SET KEY` statement.

<b>Possible settings</b>	ON	Natural reacts as if ENTER had been pressed.
	OFF	A REINPUT message is generated, prompting the user to press a valid key.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 103

## IM - Input Mode

---

This Natural profile and session parameter determines the default mode for video-terminal input.

Within a Natural session, the setting of the profile parameter IM can be overridden by the session parameter IM.

<b>Possible settings</b>	F	Forms mode.	
	D	Delimiter mode.	
<b>Default setting</b>	F		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

For information on delimiter mode and forms mode, see the `INPUT` statement.

**Under Natural Security:** The setting of this parameter can be overridden by the Session Parameters option of the Library Profile.





# 104

## INIT-LIB - Library for Automatic Logon

---

This Natural profile parameter specifies the name of the library to be used for an automatic logon (see the profile parameter [AUTO](#)) when Natural is started.

<b>Possible settings</b>	1-8 characters	Valid library name.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	

If Natural Security is installed, `INIT-LIB` is not evaluated; the library to be used for automatic logon is read from the FSEC system file (see the *Natural Security* documentation for further information).



# 105

## IP - INPUT Prompting Text

---

This session parameter is used to control prompting text in INPUT statements.

<b>Possible settings</b>	ON	Even if no text is specified preceding the input/output in an INPUT statement, the name of the field will be generated by default as a text element preceding the field as prompting text.	
	OFF	No automatic prompting text will be generated for input/output fields in an INPUT statement. Only fields explicitly preceded with a text element will receive the text as prompting text.	
<b>Default setting</b>	ON		
<b>Specification within session</b>	yes	Applicable Statements:	FORMAT INPUT
		Applicable Command:	none

### Example:

```
FORMAT IP=OFF
```

---



# 106 IS - Identical Suppress

With this session parameter, you can suppress the printing of identical information in successive lines created by a `WRITE` or `DISPLAY` statement.

The `IS` parameter setting can be suspended for one record by issuing the `SUSPEND IDENTICAL SUPPRESS` statement.

The `IS` parameter may be used in combination with the parameters `ES` and `ZP` to cause empty line suppression.

<b>Possible settings</b>	ON	A value which is identical to the previous value for the field will not be displayed.  If a <code>DISPLAY</code> or <code>WRITE</code> statement is used to create multiple output lines using the <code>VERT</code> or slash (/) notation, <code>IS=ON</code> applies only to the first line.	
	OFF	No automatic suppression will be used.	
<b>Default setting</b>	OFF		
<b>Specification within session</b>	yes	Applicable Statements:	<code>DISPLAY</code> <code>FORMAT</code> <code>WRITE</code>
		Applicable Command:	none

## Example:

```
FORMAT IS=ON
```

See also *Parameters to Influence the Output of Fields in the Programming Guide*.



# 107

## KC - Check for Statement Keywords

---

This parameter corresponds to the Natural profile parameter [KCHECK](#).





# 108

## KCHECK - Check for Statement Keywords

---

This profile parameter checks field declarations in a programming object against a set of critical Natural keywords. If a variable name defined matches one of these keywords, a syntax error is reported when the programming object is checked or cataloged.

<b>Possible settings</b>	ON	The check for keywords is performed.	
	OFF	No check for keywords is performed.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	OPTIONS
		Applicable Command:	KCHECK option of COMPOPT

The section *Performing a Check for Natural Reserved Keywords* contains a list of the keywords that are checked by the KCHECK parameter.

The document *Natural Reserved Keywords* in the *Programming Guide* contains an overview of all Natural keywords and reserved words.



# 109

## KD - Key Definition

---

This session parameter is used to display the names assigned to the PF keys (see the SET KEY statement).

This information will always be displayed automatically in the two bottom lines of the physical screen with any output created by the INPUT, WRITE, DISPLAY, and PRINT statement.

As this display requires two lines, the logical page size (see the session parameter PS) must be reduced by two.

<b>Possible settings</b>	ON	The names assigned to the PF keys are displayed.	
	OFF	The names assigned to the PF keys are not displayed.	
<b>Default setting</b>	OFF		
<b>Specification within session</b>	yes	Applicable Statements:	FORMAT
		Applicable Command:	none

### Example:

```
FORMAT KD=ON
```



# 110

## KEY - Setting Assignments to PA, PF and CLEAR Keys

---

This Natural profile parameter is used to assign settings to the CLEAR key, program attention keys (PA keys) and program function keys (PF keys) on video terminals.

<b>Possible settings</b>	any character string	Settings can be assigned to the keys PA1 to PA3, PF1 to PF24 and to the CLEAR key.  The setting assigned to each key can be any character string. The character string must represent a Natural system command or a user command (user program). If the setting contains embedded blanks, it must be enclosed in apostrophes.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	yes	
<b>Application Programming Interface</b>	USR4005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

Assignments made with the profile parameter `KEY` are only valid from within the Natural Direct Command window.

The entire string specified with the profile parameter `KEY` must be enclosed in parentheses (except `KEY=OFF`). `KEY=OFF` un-assigns all keys.

**Examples:**

```
KEY PF4=OFF  
KEY PF3="EDIT MAP"  
KEY CLR=LOGOFF  
KEY OFF
```

# 111 LC - Lower to Upper Case Translation

---

This Natural profile parameter controls lower-case to upper-case translation of input characters.



**Note:** This parameter does not apply to Natural stack data which was placed on the Natural stack by the `STACK` statement.

<b>Possible settings</b>	ON	No translation of lower-case characters to upper case is performed.
	OFF	All lower-case characters, except input from the Natural stack which was place there by the <code>STACK</code> statement, is translated to upper case by Natural.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	To disable or enable lower-case to upper-case translation dynamically within the active Natural session, you should use the terminal commands <code>%L</code> or <code>%U</code>
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.





# 112 LC - Leading Characters

---

With this session parameter, you can specify leading characters that are displayed immediately before a field output by a `DISPLAY` statement. The width of the output column is enlarged accordingly.

The session parameters `LC` and `IC` are mutually exclusive.

The parameter `LC` can also be used with `U` format fields. For information on Unicode format, see also *Unicode and Code Page Support in the Natural Programming Language, Session Parameters, EMU, ICU, LCU, TCU versus EM, IC, LC, TC*.

<b>Possible settings</b>	any character	Up to 10 characters may be specified.  Leading characters may optionally be specified enclosed within apostrophes, in which case, any characters can be specified. Any character string specified which contains a closing parenthesis or a quotation mark must be enclosed within apostrophes. A circumflex (^) is used to represent a blank in a character string not enclosed within apostrophes.	
<b>Default setting</b>	none		
<b>Specification within session</b>	yes	Applicable Statements:	<code>DISPLAY</code> <code>FORMAT</code>
		Applicable Command:	<code>none</code>

**Example:**

```
DISPLAY {LC=*}
```

See also *Parameters to Influence the Output of Fields in the Programming Guide*.

# 113 LCU - Unicode Leading Characters

---

The session parameter `LCU` is identical to the session parameter `LC`. The difference is that the leading characters are always stored in Unicode format. This allows you to specify leading characters with mixed characters from different code pages, and assures that always the correct character is displayed independent of the installed system code page.

With this session parameter, you can specify leading characters that are displayed immediately before a field output by a `DISPLAY` statement. The width of the output column is enlarged accordingly.

The session parameters `LCU` and `ICU` are mutually exclusive.

<b>Possible settings</b>	any character	Up to 10 characters may be specified.  Leading characters may optionally be specified enclosed within apostrophes, in which case, any characters can be specified. Any character string specified which contains a closing parenthesis or a quotation mark must be enclosed within apostrophes. A circumflex (^) is used to represent a blank in a character string not enclosed within apostrophes.	
<b>Default setting</b>	none		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT
		Applicable Command:	none

See also:

- *Parameters to Influence the Output of Fields in the Programming Guide*
- *Unicode and Code Page Support in the Natural Programming Language, Session Parameters, EMU, ICU, LCU, TCU versus EM, IC, LC, TC in the Unicode and Code Page Support documentation.*



# 114

## LE - Reaction when Limit for Processing Loop Exceeded

This Natural profile and session parameter controls the action to be taken if the limit of retrieved records was exceeded in a `READ`, `FIND` or `HISTOGRAM` processing loop. The limit may be specified either globally for a Natural object by using the `LIMIT` statement or by specifying an explicit limit value supplied in the database processing loop.

Within a Natural session, the profile parameter `LE` can be overridden by using the session parameter `LE`.

<b>Possible settings</b>	ON	The database loop will be terminated when the limit is reached. The program flow will continue normally with the statement following the terminated database loop. When the execution of the Natural object is complete, error NAT0957 (Database loop limit reached with 'LE=ON'.) is raised.  LE=ON applies only to programs which are loaded from a library located in the system file <code>FUSER</code> , that is, library <code>SYSTEM</code> , or with a (library) name that does not start with the prefix <code>SYS</code> .	
	OFF	The database loop will be terminated when the limit is reached. The program flow will continue normally with the statement following the terminated database loop. When the execution of the Natural object is complete, no error message appears.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

The `LE` parameter applies to `READ`, `FIND` and `HISTOGRAM` statements with a limit specified.

### Example:

```
DEFINE DATA LOCAL
1 EMPL-VIEW VIEW OF EMPLOYEES
  2 NAME
END-DEFINE
READ (10) EMPL-VIEW BY NAME
  WRITE NAME
END-READ
END
```

LE=OFF: after 10 records the loop ends without a message.

LE=ON: after 10 records the loop ends with an error message NAT0957 (Database loop limit reached with 'LE=ON').

# 115

## LFILE - Logical System File Definition

---

- LFILE Parameter Syntax ..... 265
- Example of LFILE Parameter ..... 265

This Natural profile parameter specifies information concerning the physical database file to be associated with a logical system file for Software AG products.

It can be used for Software AG products which have their own system files (for example, Connect and Natural Elite) to specify where such a system file is to be located. Such products use Database ID 255 and a logical file number (FNR) in their data definition modules (DDMs). With the LFILe parameter, you specify which physical database ID (DBID) and file number (and, if applicable, password and cipher key) are associated with that logical file number.

Natural records the physical file information and uses it for any database calls to Database ID=255 and File number=*logical-ID*.

<b>Possible settings</b>	<i>logical-FNR</i>	1 - 251	Logical file number (LFL). This parameter is mandatory.
	<i>physical-DBID</i>	0 - 65535, except 255	Physical database ID (DBID). Database ID 255 is reserved for logical system files for Software AG products.
	<i>physical-FNR</i>	1 - 5000	Physical file number (FNR).
	<i>password</i>		Must be a setting of 1 to 8 characters. *
	<i>cipher-key</i>		Must be a setting of 1 - 8 numeric digits. *
	<i>options</i>	RO	For read-only access. The RO flag is not supported on this platform.
<b>Default setting</b>	none		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	no		
<b>Application Programming Interface</b>	USR0011N	See SYSEXT - <i>Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation. * Recommended.	
	USR2004N *		

\* Password and cipher key are only required if the database file has been password-protected and/or ciphered using the Adabas security feature. With FDDM, FNAT and FUSER, the password and the cipher key are reserved for future use; currently they are ignored.

To define different logical files, the LFILe parameter must be specified several times.

The following topics are covered below:



## LFILE Parameter Syntax

---

The LFILE parameter is specified as follows:

```
LFILE=(logical-FNR,physical-DBID,physical-FNR,password,cipher-key,RO)
```

## Example of LFILE Parameter

---

```
LFILE=(180,73,10),LFILE=(251,40,9,TEST99)
```



# 116

## LOGONRQ - Logon for RPC Server Request Required

---

This Natural profile parameter determines whether or not logon data are required for an RPC server request.

LOGONRQ is specified on the server side only.

<b>Possible settings</b>	ON	A logon is required; that is, the server only accepts requests from clients which include logon data in the RPC server request. For conversational requests, the logon data is only necessary when the conversation is opened.
	OFF	A logon is <i>not required</i> . Logon data is nevertheless processed.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For Natural clients the logon data can either be requested:

- by setting the LOGON option of the SYSRPC Service Directory Maintenance;
- using the logon indicator of the profile parameter [DFS](#).

You are strongly recommended to set LOGONRQ=ON if the Natural RPC server runs under Natural Security. For further information, see *Using Natural RPC with Natural Security* in the *Natural Remote Procedure Call (RPC)* documentation.

For additional information on Natural RPC, see the *Natural Remote Procedure Call (RPC)* documentation.



# 117

## LS - Line Size

---

- Profile Parameter LS ..... 270
- Session Parameter LS ..... 270
- Specification with Statements ..... 271

This Natural profile and session parameter specifies the maximum number of characters permitted per line for DISPLAY, INPUT and WRITE statements.

The following topics are covered below:

## Profile Parameter LS

---

When used as a profile parameter, LS is honored in batch mode only and defines the physical line size. In online mode, the line size is always set to the physical screen width.

<b>Possible settings</b>	35 - 250	Maximum number of characters permitted per line.
	0	Use physical line size (mostly 132).
<b>Default setting</b>	0	
<b>Dynamic specification</b>	yes	

## Session Parameter LS

---

<b>Possible settings</b>	2 - 250	Maximum number of characters permitted per line.
<b>Default setting</b>	0	Physical line size.
<b>Applicable command:</b>	GLOBALS	
<b>Applicable statements:</b>	FORMAT SET GLOBALS	
<b>Application Programming Interface</b>	USR1005N	See SYSEXT - <i>Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.



**Note:** At logon to a library, LS is reset to the physical line size.

**Under Natural Security:** The setting of this parameter can be overridden by the Session Parameters option of the Library Profile.

---

## Specification with Statements

---

When specified with a statement, the LS parameter is evaluated at compilation time.

<b>Applicable Statements:</b>	DISPLAY INPUT WRITE	Parameter may be specified at statement level.
-------------------------------	---------------------------	--





This Natural profile and session parameter is used to limit the number of database records which can be retrieved within Natural applications. This limit applies to all statements retrieving records from the database, that is:

- statements that initiate processing loops, such as `READ`, `FIND`, `HISTOGRAM` or `SELECT` and
- statements that retrieve only a single record, such as `FIND UNIQUE`, `FIND NUMBER`, `FIND FIRST`, `GET (SAME)` and `SELECT SINGLE`.

All retrieved records are counted and the result of the count is compared with the `LT` limit. The count also includes those records which were rejected by a `WHERE` clause of a `FIND`, `READ` or `HISTOGRAM` statement. The `LT` limit does not affect the statements `STORE`, `UPDATE`, `DELETE`, `END TRANSACTION` and `BACKOUT TRANSACTION`.

Within a Natural session, the profile parameter `LT` can be overridden by using the session parameter `LT`.

When a record is retrieved from the database, the count of retrieved records is incremented before it is compared with the current value of the `LT` parameter. If the incremented count exceeds the current `LT` value, Natural error NAT1003 (“Global limit for database calls reached”) is raised. The count of retrieved records is reset to zero whenever a Natural program is started on Level 1. The count is not reset if the program on Level 1 invokes another Natural object (for further information, see *Multiple Levels of Invoked Objects* in the *Programming Guide*). Therefore the `LT` parameter limits the number of records retrieved from the database by a Level 1 program and objects invoked by that program on a level other than 1.

If the value of the LT parameter is dynamically changed within a program by using a SET GLOBALS LT=*n* statement, the new limit value becomes effective for the next statement that retrieves a record from the database.

<b>Possible settings</b>	0 - 2147483647 Within a session: 0 to <i>n</i> ( <i>n</i> = value of profile parameter LT at session start)	Maximum number of records that can be retrieved. All retrieved records (including records rejected by means of a WHERE clause) are counted and compared with this limit.  LT=0 defines that no limit is in effect for the number of retrieved records.	
<b>Default setting</b>	99999999		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS, see Note.
		Applicable Command:	GLOBALS, see Note.
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	



**Note:** When the LT parameter is used in conjunction with the statement SET GLOBALS or the system command GLOBALS, the limit value that can be set may not exceed the LT value defined in the Natural parameter file NATPARM.

# 119

## MADIO - Maximum DBMS Calls between Screen I/O

### Operations

---

This Natural profile parameter is used to specify the maximum number of DBMS calls permitted between two screen I/O operations (also in batch mode).

<b>Possible settings</b>	30 - 32767	Maximum number of DBMS calls.
	0	MADIO=0 indicates that no limit is to be in effect.
<b>Default setting</b>	512	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.  * Recommended.
	USR1068N *	

If the specified limit is exceeded, the Natural program is interrupted and the user is notified with an appropriate Natural error message.



# 120

## MAINPR - Override Default Output Report Number

---

This Natural profile parameter is used to override the default output report number for all Natural reports. It must be set to a valid printer number (0 - 31).

<b>Possible settings</b>	0 - 31	Valid printer number.
<b>Default setting</b>	0	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR6002N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

Specifying a MAINPR setting is the same as changing all of the DISPLAY, PRINT, WRITE or INPUT statements' printer references from the default setting (0) to the desired printer number.

A physical printer corresponding to the report number specified must be defined to Natural as described in the *Configuration Utility* documentation, section *Device/Report Assignments*.



# 121

## MASKCME - MASK Compatible with MOVE EDITED

---

This Natural profile parameter is used to control Natural's compiler.

<b>Possible settings</b>	ON	The range of valid year values that match the YYYY mask characters is 1582 - 2699 to make the MASK option compatible to MOVE EDITED.	
	OFF	The range of valid year values that match the YYYY mask characters is 0000 - 2699.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	OPTIONS
		Applicable Command:	MASKCME option of COMPOPT





# 122

## MAXBUFF - Maximum Buffer Size

---

This Natural profile parameter can be specified on both the client and the server side.

On the server side, it determines the size of the buffer provided by the server to receive the client request including data and to send back the result. The buffer must be large enough to hold the largest of the following two data areas for all client requests:

- the request received by the client,
- the result send back to the client.

If the size of the buffer is too small for a request, a temporary buffer with the required size is allocated and used for this request.

On the client side, it determines the size of the buffer provided for the automatic execution of Natural RPC calls. This buffer is used to build the client request including data and to receive the result from the server. The buffer must be large enough to hold the largest of the following two data areas for all requests sent by the client:

- the request send to the server,
- the result received from the server.

If the size of the buffer is too small for a request, a temporary buffer with the required size is allocated and used for this request.

For further information, see *Stubs and Automatic RPC Execution* in the *Natural Remote Procedure Call (RPC)* documentation.

The size of the data exchanged between the client and server is provided by the stub generation function of the `SYSRPC` utility. To calculate the size for automatic RPC execution, you may use the `SYSRPC CSMASS` command; see *Calculating Size Requirements* in the *SYSRPC Utility* documentation.

<b>Possible settings</b>	1 - 2097147	Maximum buffer size in KB.
	0	No buffer is allocated.
<b>Default setting</b>	0	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

**Dependency on ACIVERS Settings**

In case of an EntireX Broker node, special considerations apply if you are using Entire Net-Work as a transport layer. With Entire Net-Work, the receive buffer length passed to the EntireX Broker stub is restricted by the startup parameter `IUBL` and must not exceed 32 KB. Depending on the setting of the Natural profile parameter `ACIVERS`, the receive buffer length is set as follows:

- `ACIVERS=1`: 32000
- `ACIVERS=2`: 30K
- `ACIVERS>2`: the value specified with `MAXBUFF`

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.

# 123

## MAXCL - Maximum Number of Program Calls

---

This Natural profile parameter is used to specify the maximum number of program calls permitted between two screen I/O operations.

If the specified limit is exceeded, the Natural program is interrupted and the user is notified with an appropriate Natural error message.

<b>Possible settings</b>	10 - 32767	Maximum number of program calls.
	0	MAXCL=0 indicates that no limit is to be in effect.
<b>Default setting</b>	50	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.  * Recommended.
	USR1068N *	



# 124

## MAXYEAR - Maximum Year for Date/Time Values

This Natural profile parameter sets the maximum value for the year part of date and time values that can be entered as constants or as terminal input.

<b>Possible settings</b>	2699	The maximum year that can be entered is 2699; that is, the maximum date value that can be entered is 2699-12-31.
	9999	The maximum year that can be entered is 9999; that is, the maximum date value that can be entered is 9999-12-31.
<b>Default setting</b>	2699	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

MAXYEAR=9999 changes the maximum date value that can be entered from 2699-12-31 to 9999-12-31.



**Note:** Before setting the value for MAXYEAR to 9999, you should carefully check your application for arithmetic operations or assignments of date or time values to fields that have data formats other than date or time, and perform the necessary changes. Otherwise, unexpected overflows leading to Natural errors at execution time may occur. For example, you should check for

- redefinitions of date/time fields with P6/P12 fields
- assignments of date/time values to non-date/time fields such as `P6 := D`
- arithmetic operations with date/time values where the result is assigned to a non-date/time field, for example: `P6 := D + 7`

- input of date/time fields that is used in arithmetic operations with non-date/time fields later on, for example:

```
INPUT D(D)
P6 := D + 1
```

The use of the Natural Engineer is recommended to check your application.

The setting of MAXYEAR affects

- checking of date/time constants by the compiler, for example: P6 := D'2699-12-31'
- INPUT statements with input or modifiable date/time fields
- MOVE EDITED statements with source or target date/time fields
- IS (D) option in logical condition criteria
- MASK option in logical condition criteria with four-digit year check (YYYY)
- VAL system function with date field as target operand

You should ensure that the MAXYEAR settings are the same for

- cataloging and executing a Natural application
- Natural RPC servers and Natural RPC clients

See also:

- *Formats D - Date, and T - Time in the Programming Guide*
- *Date and Time Constants in the Programming Guide*
- Session parameter [EM](#) in the *Parameter Reference* documentation

# 125

## MC - Multiple-Value Field Count

---



**Note:** This parameter may be used in reporting mode only.

With this session parameter, you determine the number of values of a multiple-value field to be output by default when the field is specified without an index in a `DISPLAY` or `WRITE` statement.

<b>Possible settings</b>	1 - 191	Number of values.	
<b>Default setting</b>	1		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT INPUT PRINT WRITE
		Applicable Command:	None

### Example:

```
FORMAT MC=5
```

---





# 126

## MFSET - Multi-Fetch Setting

---

This Natural profile parameter specifies whether multi-fetch is used to retrieve records from Adabas databases.

<b>Possible settings</b>	NEVER	Always use single-fetch.
	OFF	Use single-fetch as default. This can be overwritten on statement level.
	ON	Use multi-fetch as default. This can be overwritten on statement level.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 127

## ML - Position of Message Line

---

This profile and session parameter specifies the line to be used for the display of applications which do not set the message line position explicitly by using the `SET CONTROL 'M'` statement. For information on the operand 'M', see also Natural terminal command %M (Control of Message Line).



**Note:** The profile parameter does not exist in the Configuration Utility. Use session parameter ML instead.

Within a Natural session, the profile parameter ML can be overridden by the session parameter ML.

<b>Possible settings</b>	B	Natural messages are displayed at the bottom of the screen.	
	T	Natural messages are displayed at the top of the screen.	
<b>Default setting</b>	B		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET CONTROL 'M'
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	



# 128

## MP - Maximum Number of Pages of a Report

---

This Natural profile and session parameter specifies the maximum number of pages to be produced for a report.

Within a Natural session, the setting of profile parameter MP can be reduced, but not increased by the `FORMAT` statement. The value specified with the session parameter MP applies only to the specified report.

<b>Possible settings</b>	1 - 99999	The value specified is the number of physical pages and has no effect on the starting page number used. The program will be terminated with an error message if the MP value is exceeded.	
	0	No page limit is defined.	
<b>Default setting</b>	0		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	no	Applicable Statements:	DISPLAY FORMAT PRINT WRITE
		Applicable Command:	



# 129

## MS - Manual Skip

---

With this session parameter, you control the cursor positioning during the processing of an INPUT statement.

<b>Possible settings</b>	ON	See example below. <b>Note:</b> The setting MS=ON is not supported under BS2000/OSD.	
	OFF	The cursor will be positioned to the next input field as soon as the value for the current field is entered with all positions.	
<b>Default setting</b>	OFF		
<b>Specification within session</b>	yes	Applicable Statements:	FORMAT INPUT
		Applicable Command:	none

### Example:

```
INPUT (MS=ON) #A #B
```





# 130

## MSGSF - Display System Error Messages in Short/Full

### Format

---

This Natural profile parameter can be used to avoid truncation of Natural system error messages.

<b>Possible settings</b>	ON	System error messages will be displayed in full; that is, program name, line number and actual message text.
	OFF	System error messages will be displayed in short form; that is, only the actual message text will be displayed (but not the program name and line number).
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	yes	

By default, a Natural system error message consists of the following:

- the name of the program,
- the number of the line that caused the error,
- the actual text of the message.

Depending on the size of the window in which the message is displayed, the text may be truncated. With this parameter, you can avoid such truncation.



# 131

## NATLOG - Natural Log File

---

- Examples ..... 300

This Natural profile parameter is used to log messages that will not (or could not) be written to the standard output in interactive mode or to the output file `CMPRINT` in batch mode.

<b>Possible settings</b>	OFF	Disables the log mechanism.
	ERR	Logs error messages.
	INF	Logs information and success messages.
	WRN	Logs warning messages.
	ALL	Logs all types of messages.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

The location of the NATLOG file is the `TEMP` directory of Natural (specified in the local configuration file `NATURAL.INI`). If this path is unknown, Natural creates the file in the current directory.

Natural tries to create the following file name, if the `user-ID/et-ID` information could be retrieved:

`NATURAL_<user-ID>_<et-ID>.LOG`

If `user-ID` and `et-ID` could not be retrieved, then the following file name is used: `NATURAL.LOG`.

**Example File Names:**

A Natural batch process is running with `user-ID=SYSTEM` and `et-ID=14`, then the resulting file name is `NATURAL_SYSTEM_14.LOG`.

If the `user-ID` could not be retrieved (which is the case if an error occurs during the initialization phase of Natural), then the resulting file name is `NATURAL.LOG`.

## Examples

---

The following example shows the contents of a Natural log file. At top of the file, there is a header with some environment information, for example the Natural Version, the parameter file currently in use and so on. Two entries follow. The first one an entry which displays the I/O channels needed for batch mode. The second entry shows an error message. Both messages are counted in the statistics summary.

## Example NATLOG Output Contents for UNIX:

```

# #####
#           N a t u r a l   L o g   F i l e
# #####
#
# Logging started at : 06-Mar-2007 08:08:38.023
#
# Natural Version      : V v . r . s SAG 2003
# Server Type         : (none)
# Device              : BATCH (real)
# Parameter File      : NATPARM
#
# User ID             : NATURAL
# ET ID              : TEST
# Network User ID     : NATURAL
#
# Host Name          : hpn2
# Machine Class      : UNIX
# Operating System    : HP_HPUX B.10.20A
#
# Process ID         : 17921
#
# NATLOG Option      : ALL
#
# #####
#
# -----
# 08:08:38.025 NATURAL      INFORMATIONAL  STATISTICS:  INF=1  WRN=0  ERR=0
# -----
# setting of parameter CMSYNIN (command file)
# $HOME/tmp/batch.cmd
# setting of parameter CMOBJIN (input file)
#
# setting of parameter CMPRINT (output file)
# $HOME/tmp/batch.out
# -----
# 08:08:38.028 NATURAL      ERROR          STATISTICS:  INF=1  WRN=0  ERR=1
# -----
#           NATURAL Startup Error:  42
#           Batch mode driver error.
#           Parameter CMOBJIN not set.

```



# 132

## NATVERS - Switching between Natural Environments

---

This Natural profile parameter enables you to access various Natural environments, that is, various *err*, *txt*, *bin*, *etc*, *samples* and *tmp* subdirectories.

<b>Possible settings</b>	any character string	Determines the Natural version.
<b>Default setting</b>	<i>v.r.s</i>	<b>Note:</b> A DEFAULT-VERSION entry in <i>SAG.INI</i> is no longer necessary.
<b>Dynamic specification</b>	yes	This parameter can only be specified dynamically.
<b>Specification within session</b>	no	

Where *v.r.s* is the current version of Natural. In the following sample programs, the characters *v.r.s* stand for the *version, release, system maintenance level*.

The NATVERS value you enter is used by Natural to determine the *SAG.INI* section you want to use with your Natural session. By default, the Natural installation creates a section in the *SAG.INI* file that points to the installed Natural environment.

The Natural installation automatically identifies the Natural version and creates the section [NATURAL=*v.r.s*] in your *SAG.INI* file that points to the installed Natural environment. This might look as in the following example:

```
[NATURAL-v.r.s]  
PROD_API=C:\Program Files\Software AG\v.r.s\Bin\natprd32.dll  
NATGUI_BMP=C:\Program Files\Software AG\Natapps\Pic  
NATDIR=C:\Program Files\Software AG  
NATINI=C:\Program Files\Software AG\v.r.s\Etc  
[NATURAL-v.r.s-END]
```

If you want to access environments other than the one that was installed automatically, create a new section for each environment as shown in the following example:

```
[NATURAL-Server v.r.s]
NATVERS=v.r.s
PROD_API=\\Server\Program Files\Software AG\v.r.s\Bin\natprd32.dll
NATGUI_BMP=\\Server\Program Files\Software AG\Natapps\Pic
NATDIR=\\Server\Program Files\Software AG
NATINI=\\Server\Program Files\Software AG\v.r.s\Etc
[NATURAL-Server v.r.s-END]
```

Replaced settings are still contained in the *SAG.INI* file and can be used by specifying them with NATVERS to switch to the corresponding Natural environments.



# 133

## NC - Use of Natural System Commands

This Natural profile parameter controls whether Natural system commands can be used during the Natural session or not.

Within a Natural session, the profile parameter `NC` can be overridden by the session parameter `NC`.

<b>Possible settings</b>	ON	System commands cannot be used - except FIN, LAST, LOGOFF, LOGON, RENUMBER, RETURN, SETUP and TECH.  If you have Natural Security installed, any system command restrictions you set with Natural Security are valid, regardless of the setting of the NC profile parameter.  In a Natural Development Server environment on mainframe computers, the value OFF will be assumed for the Natural Development Server, even if NC=ON has been specified.  If NC=ON has been specified on the client side, subsequent system commands issued on the client side will be rejected as described above.	
	OFF	All system commands can be used.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	
		Applicable Command:	
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces in the Utilities</i> documentation.	



**Note:** Natural terminal commands and user-created commands (object module names) are not affected by the `NC` parameter.



# 134

## NCFVERS - NCF File Protocol Version

---

This Natural profile parameter enables downward compatibility with Natural Versions lower than Version 6.1. It specifies the protocol version of the Entire Connection format file (.NCF) to be used. This Entire Connection format is generated when work files of type `ENTIRE CONNECTION` or `DEFAULT` work files with the file extension `.NCD` are written.

<b>Possible settings</b>	0	A format file of Entire Connection Protocol Version 0 is written. The format files created are compatible with those of Natural Versions lower than Version 6.1.
	2	A format file of Entire Connection Protocol Version 2 is written, which is created by Natural Version 6.1 or 6.2.
	3	A format file of Entire Connection Protocol Version 3 is written, which is created by Natural Version 6.3.
<b>Default setting</b>	3	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	

For information on the work file types `ENTIRE CONNECTION` and the Entire Connection format, refer to *Work File Formats* in the *Operations* documentation.



# 135

## NENTRY - Left/Right Alignment of Numeric Field Entries

---

This Natural profile parameter defines the alignment of input entered in numeric INPUT fields (that is, fields of format I, N, P or F).

<b>Possible settings</b>	LEFT	The characters entered in a numeric INPUT field are left justified.
	RIGHT	The characters entered in a numeric INPUT field are right justified.
<b>Default setting</b>	LEFT	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 136

## NL - Numeric Length for Output

This session parameter determines the default input/output length for a numeric field used in a DISPLAY, INPUT, PRINT or WRITE statement.

The NL parameter must not be specified for groups.

Any edit mask specified for a field will override the NL parameter for this field.

<b>Possible settings</b>	<i>nn.m</i>	<p>The length is specified as <i>nn.m</i>, where <i>nn</i> represents the number of positions before the decimal separator and <i>m</i> represents the number of positions after the decimal separator.</p> <p>The <i>m</i> notation is optional. The value of <i>m</i> must not exceed 7. The total of <i>n+m</i> must not exceed 29.</p> <p><b>Note:</b></p> <ol style="list-style-type: none"> <li>1. If NL is set less than the field length, values are truncated. No error is produced when relevant digits are truncated.</li> <li>2. If NL is set greater than the field length, values are expanded with blanks. No error is produced when an input field is truncated.</li> </ol>	
<b>Default setting</b>	none		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT INPUT PRINT WRITE
		Applicable Command:	none

**Example:**

```
DISPLAY #AA(NL=20) #AB(NL=3.2)
```

See also *Parameters to Influence the Output of Fields in the Programming Guide*.



# 137

## NOAPPLERR - Suppress Message Number Prefix NAT

---

This Natural profile parameter is used to suppress the message number prefix "NAT" with user-supplied error messages.

<b>Possible settings</b>	ON	The prefix "NAT" is not displayed in error messages.
	OFF	The prefix "NAT" is displayed in error messages.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 138

## NOPROX - Specify Local Domains for Direct Addressing

---

This Natural profile parameter specifies the domain(s) which shall be addressed directly, that is, not via the proxy.

<b>Possible settings</b>		See example below.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	

### Example:

```
"*.software-ag.de; sagus.software-ag.com"
```

---

# 139 NOSSLPRX - Specify Local Domains for Direct

## Addressing SSL

---

This Natural profile parameter specifies the domain(s) which shall be addressed directly, that is, not via the SSL proxy.

<b>Possible settings</b>		See example below.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	

### Example:

```
"*.software-ag.de; sagus.software-ag.com"
```



# 140

## OPF - Overwriting of Protected Fields by Help routines

This Natural profile and session parameter specifies whether the content of a write-protected field (attribute definition AD=P) can be overwritten by a help routine assigned to the field.

Within a Natural session, the profile parameter OPF can be overridden by the session parameter OPF.

<b>Possible settings</b>	ON	A help routine assigned to a field can overwrite the field's content, even if the field is write-protected.	
	OFF	Help routines cannot overwrite the contents of write-protected fields.	
<b>Default setting</b>	ON		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See SYSEXT - <i>Natural Application Programming Interfaces in the Utilities</i> documentation.	



### Notes:

1. The OPF profile parameter only applies to the field for which a help routine is invoked; it does not affect parameters explicitly passed to the help routine. This means that the OPF profile parameter takes no effect if the field for which help is invoked is also explicitly specified as a parameter to be passed to the help routine.
2. In addition, in reporting mode you can change the OPF setting using the statement SET GLOBALS.





# 141

## OPRB - Database Open/Close Processing

---

- OPRB String Syntax ..... 323

This Natural profile parameter controls the use of the Adabas C `Open/Close` commands during a Natural session.

<b>Possible settings</b>	OFF	If the OPRB parameter is set to OFF, a Natural session starts with an Adabas OP command requesting UPD (access/update) to the Natural system file. Natural also issues RELEASE CID (Adabas RC) commands to release all ISN lists (ISN lists specified in a RETAIN clause of a Natural FIND statement are not released).
	OPRB=( <i>string</i> )	You can specify an Open request in accordance with the syntax described below. See also the examples listed.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	

It is required if any of the following conditions are true:

- An explicit list of Adabas files to be accessed/updated is to be provided. This is necessary, for example, if Adabas cluster updating or exclusive file control is to be requested.
- The Adabas record buffer to be used with the initial Adabas OP command can be explicitly provided. To access databases you have to specify the DBIDs and file numbers with their corresponding access rights at the OPRB string.
- The character set for Adabas format W is to be provided. To access databases you have to specify the DBIDs and the required encoding name.

Entries may not contain blanks, must be enclosed in parenthesis and must follow the rules defined in the relevant Adabas documentation.

In addition to the Adabas syntax, internal file numbers can be specified by using the *x-y* notation (that is, all numbers between *x* and *y*).

## OPRB String Syntax

DBID=(*x*) specifies the database for the following access right entries:

ACC=( <i>file-list</i> )	Specifies access permission (read) for the files in the file list.
UPD=( <i>file-list</i> )	Specifies update permission (read/write) for the files in the file list.
EXU=( <i>file-list</i> )	Specifies exclusive update permission (exclusive read/write) for the files in the file list.
WCODE= <i>encoding</i>	Specifies the encoding for W fields in the Adabas user session (Adabas for Mainframes).  Required encoding code for Adabas on Mainframes is 4095.
WCHARSET= <i>charset</i>	Specifies the default character set used for W fields in record and value buffers in the Adabas user session (Adabas for UNIX, OpenVMS and Windows).  Required encoding names for Adabas on UNIX, OpenVMS and Windows are UTF-16LE or UTF-16BE.

The trailing record buffer dot (.) can be omitted in the OPRB string because it is appended automatically.

DBID=0 specifies the default record buffer entry and can be omitted if it is the first DBID listed in the OPRB string. This default record buffer is taken if there is no specific entry for the requested database.

Combinations of the keywords ACC, UPD, EXU and WCODE or WCHARSET must follow the rules as defined in the relevant Adabas documentation. Natural issues an OP command at the start of a Natural session and a CL command at the end of the session. At the end of a Natural program, only the required RC commands are issued to release held ISN lists.

### Example 1:

```
(ACC=2,3,4,DBID=15,UPD=3,4,ACC=5)
```

The following entries were defined:

```
'UPD=3,4,ACC=5.' for DB 15  
'ACC=2,3,4.' for other databases (DB 0)
```

**Example 2:**

```
(DBID=15,ACC=2-7)
```

The following entry was defined:

```
'ACC=2,3,4,5,6,7.' for DB 15; access to other databases is not permitted.
```

**Example 3:**

```
(DBID=0,ACC=2,3,4,5.)
```

The following entry was defined:

```
'ACC=2,3,4,5.' for all databases (DB 0).
```



**Note:** If you have Natural Security installed, open/close processing works the same way as without Natural Security; the OPRB parameter in the security profile is provided for future use only.

**Example 4:**

```
(DBID=0,ACC=2,3,4,5,DBID=12,WCHARSET='UTF-16LE',UPD=3-10)
```

The following entry was defined:

```
'ACC=2,3,4,5.' for all databases (DB 0).
```

```
WCHARSET='UTF-16LE',UPD=3,4,5,6,7,8,9,10. for DB 12.
```

# 142

## PARM - Alternative Parameter File

---

This Natural profile parameter can be used for Natural startup (Studio/Runtime/Server) in order to specify an alternative parameter file Natural is to run with. If no PARM parameter is specified, Natural will start using the default NATPARM parameter file containing all default settings for each single parameter. Use the Natural Configuration Utility in order to create your own new parameter file. See *Creating a New Parameter File* in the *Configuration Utility* documentation.

<b>Possible settings</b>	1-8 characters	Any valid file name.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	This parameter can only be specified dynamically.
<b>Specification within session</b>	no	



# 143

## PC - Control of Personal-Computer Access Method

---

This Natural profile parameter only applies if Natural Connection is installed.

It determines whether support of the personal-computer access method is to be provided using Natural Connection.

<b>Possible settings</b>	ON	Personal-computer support is enabled. The Natural statements READ PC FILE or WRITE PC FILE can be used (for uploading or downloading); see UPLOAD PC FILE and DOWNLOAD PC FILE.  With PC=ON, the system variable *DEVICE will always contain the value PC.
	OFF	No personal-computer support is to be provided.
	NAM	Field names are sent when data are uploaded/downloaded. This value is for mainframe environments only.
	NONAM	No field names are sent when data are uploaded/downloaded. This value is for mainframe environments only.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	yes	

The files used for the PC access method have to be defined with the profile parameter [WORK](#).





# 144

## PC - Periodic Group Count

---

This session parameter may be used in reporting mode only. It determines the number of periodic group occurrences to be output by default if a periodic group (or a field contained within a periodic group) is specified without an index in a `DISPLAY` or `WRITE` statement.

<b>Possible settings</b>	1 - 191	Number of values.
<b>Default setting</b>	1	
<b>Applicable statements:</b>	FORMAT	
	INPUT DISPLAY WRITE PRINT	Parameter may be specified at statement level and/or at element level.
<b>Applicable command:</b>	none	

### Example:

```
FORMAT PC=5
```



# 145

## PCHECK - Parameter Checking for Object Calling

### Statements

---

This Natural profile parameter is used to control Natural's compiler.

<b>Possible settings</b>	<p>ON</p> <p>The compiler checks the number, format, length and array index bounds of the parameters that are specified in an object calling statement, such as <code>CALLNAT</code>, <code>PERFORM</code>, <code>INPUT USING MAP</code>, <code>PROCESS PAGE USING</code>, helproutine calls. Also, the <code>OPTIONAL</code> feature of the <code>DEFINE DATA PARAMETER</code> statement is considered in the parameter check.</p> <p>The parameter check is based on a comparison of the parameters of the calling statement with the <code>DEFINE DATA PARAMETER</code> definitions for the object to be called.</p> <p>It requires that</p> <ul style="list-style-type: none"><li>■ the name of the subprogram to be invoked is defined as an alphanumeric constant (not as an alphanumeric variable),</li><li>■ the subprogram to be invoked is available as a cataloged object.</li></ul> <p>Otherwise, <code>PCHECK=ON</code> will have no effect.</p> <p><b>Problems in Using the <code>CATALL</code> Command with <code>PCHECK=ON</code></b></p> <p>When a <code>CATALL</code> command is used in conjunction with <code>PCHECK=ON</code>, you should consider the following:</p> <p>If a <code>CATALL</code> process is invoked, the order in which the programming objects are compiled depends primarily on the type of the object and secondarily on the alphabetical name of the object. The object type sequence used is: <code>DDMs</code>, <code>GDA</code>s, <code>LDA</code>s, <code>PDA</code>s, classes, maps, external subroutines, subprograms, functions, adapters, helproutines, programs. Within objects of the same type, the alphabetical order of the name determines the sequence in which they are cataloged.</p> <p>As mentioned above, the parameters of the object calling statement are checked against the compiled form of the called object. If the calling object (the one which is being compiled</p>
--------------------------	---

		<p>and includes the object calling statement) is cataloged before the invoked object, the PCHECK result may be wrong if the parameters in the object calling statement and in the called object were changed. In this case, the new object image of the called object has not yet been produced by the CATALL command.</p> <p>This causes the <i>new</i> parameter layout in the object calling statement to be compared with the <i>old</i> parameter layout of the DEFINE DATA PARAMETER statement of the called subprogram.</p> <p>Solution:</p> <ul style="list-style-type: none"> <li>■ Set compiler option PCHECK to OFF.</li> <li>■ Perform a general compile with CATALL on the complete library, or if just one or a few objects were changed, perform a separate compile on these objects.</li> <li>■ Set compiler option PCHECK=ON.</li> <li>■ On the complete library, perform a general compile with the function CHECK of system command CATALL enabled.</li> </ul>	
	OFF	No parameter check is performed.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	OPTIONS
		Applicable Command:	PCHECK option of COMPOPT

# 146 PD - Size of Page Dataset

---

This Natural profile and session parameter specifies the maximum number of pages (screens) which can be stored at the same time in the Natural system file (FUSER) with the screen-paging utility.

Within a Natural session, the profile parameter PD can be overridden by the session parameter PD.

<b>Possible settings</b>	0 - 255	Maximum number of pages (screens).
<b>Default setting</b>	50	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	yes	Applicable Statements: SET GLOBALS
		Applicable Command: GLOBALS



## Notes:

1. If the number of stored screens exceeds the setting of PD, wrap-around technique is used for the system file, which means that the oldest page is overwritten.
2. For further information on the screen page utility, see the terminal commands %E, %I, %O, %P and %S.



# 147

## PM - Print Mode

---

- Profile Parameter PM ..... 336
- Session Parameter PM ..... 336

The following topics are covered below:

## Profile Parameter PM

---

The Natural profile parameter specifies how fields are to be printed or displayed.

PM=I affects any system controlled output screen items, that is, system variables and PF key lines. Moreover, all non-alphanumeric fields, for example, numeric and date are affected. In addition, for Natural Web I/O Interface terminals the field sequence is changed from left to right into right to left. The field inversion routine is supplied as assembler module NATPM in the Natural source library and can be modified in case of need.

For detailed information on how to use the setting PM=I, see *Bidirectional Language Support* in the *Unicode and Code Page Support* documentation.

<b>Possible settings</b>	I	The default screen direction when running programs is right-to-left.
	R	The default screen direction when running programs is left-to-right.
<b>Default setting</b>	R	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	yes	
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

## Session Parameter PM

---

This session parameter is used to indicate how fields are to be displayed.

<b>Possible settings</b>	PM=I	The field direction is reversed.
	PM=N	The field is ignored (that is, not printed) for hardcopy output.
<b>Default setting</b>	none	The default field direction is used and it is regarded for hardcopy output.
<b>Applicable Statements</b>	COMPRESS DEFINE DATA DISPLAY FORMAT INPUT MOVE PRINT WRITE	



For detailed information on how to use the setting `PM=I`, see *Bidirectional Language Support* in the *Unicode and Code Page Support* documentation.



# 148 PRGPAR - Data to be Passed to Program Receiving

## Control at Termination

---

This Natural profile parameter specifies data to be passed to the program that receives control when Natural terminates (see also profile parameter [PROGRAM](#)).

<b>Possible settings</b>	any valid character string	Data to be passed.
<b>Default setting</b>	blank	No data is passed.
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 149 PROGRAM - Non-Natural Program Receiving Control after Termination

---

This Natural profile parameter specifies the non-Natural program which is to receive control after the termination of the Natural session.

<b>Possible settings</b>	1-12 characters	Non-Natural program
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR6204N (for all platforms)	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

Data for the program specified with the profile parameter PROGRAM can be supplied with the TERMINATE statement.



# 150

## PROX - Specify URL of Proxy Server

---

This Natural profile parameter specifies the Uniform Resource Locator (URL) of the (Intranet) proxy server through which all requests have to be routed (optional).

<b>Possible settings</b>	URL of proxy server
<b>Default setting</b>	none
<b>Dynamic specification</b>	no
<b>Specification within session</b>	no





# 151 PROXPORT - Specify Port Number of Proxy

---

This Natural profile parameter specifies the port number of the proxy, if any is set.

<b>Possible settings</b>	4 characters at maximum	Port number of proxy.
<b>Default setting</b>	80	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 152

## PS - Page Size for Natural Reports

This Natural profile and session parameter specifies the maximum number of lines per page to be used for Natural reports created with the `DISPLAY` or `WRITE` statement. When used as a profile parameter, the `PS` parameter is honored in batch mode only and defines the physical page size. In online mode, the physical page size is always set to the physical screen height.

<b>Possible settings</b>	1 - 250	Maximum number of lines per page.	
	0	<p>The physical page size is to be used.</p> <p>If <code>PS=0</code> is specified for the first report to be output (Report 0), the physical-device page-size minus 1 will be used.</p> <p>If <code>PS=0</code> is specified for Reports 1 - 31, this will cause automatic new-page processing to be inhibited, that is, no automatic page-break processing will be performed.</p>	
<b>Default setting</b>	0		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT INPUT SET GLOBALS WRITE
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

See also *Page Size - PS Parameter* in the *Programming Guide*.

**Under Natural Security:** The setting of this parameter can be overridden by the Session Parameters option of the Library Profile.



# 153 PSIGNF - Internal Representation of Positive Sign of Packed Numbers

---

This Natural profile parameter can be used to define the internal representation of the positive sign of packed numbers.

<b>Possible settings</b>	ON	The positive sign of a packed number is represented internally as H ' F ' .	
	OFF	The positive sign of a packed number is represented internally as H ' C ' .	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	OPTIONS
		Applicable Command:	PSIGNF option of COMPOPT



# 154 RCFIND - Handling of Response Code 113 for FIND

## Statement

---

This Natural profile parameter specifies the action to be taken if Adabas Response Code 113 (requested ISN not found) is returned during the execution of a `FIND` statement processing loop.

<b>Possible settings</b>	ON	Response Code 113 causes the program to be terminated.
	OFF	Response Code 113 will be ignored, and processing of the <code>FIND</code> loop will continue by reading the next record.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	





# 155

## RCGET - Handling of Response Code 113 for GET

### Statement

---

This Natural profile parameter specifies the action to be taken if Adabas Response Code 113 (requested ISN not found) is returned during the execution of a GET statement.

<b>Possible settings</b>	ON	Response Code 113 causes the program to be terminated.
	OFF	Response Code 113 will be ignored, the system variable *ISN will be set to 0, and processing will continue.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 156

## RDACTIVE - Activate Remote Debugger

---

This Natural profile parameter specifies whether a remote debugger on a Windows computer is to be used or not. `RDACTIVE` is only relevant if the system command `DEBUG` has been used. It is used in combination with the profile parameters `RDNODE` (where the relevant node name is specified) and `RDPORT` (where the port number is specified).

<b>Possible settings</b>	ON	Remote debugging is enabled.  For DCOM (Windows only) or RPC servers, the remote debugging session is opened automatically.
	OFF	No debugging is possible.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 157

## RDNODE - Remote Debugger Node Name

---

This Natural profile parameter specifies the node name of the Windows computer on which a remote debugger is to be called.

<b>Possible settings</b>	Character string	Node name.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 158

## RDPORT - Remote Debugger Port

---

This Natural profile parameter specifies the port number on which a remote debugger on a Windows computer has been installed.

<b>Possible settings</b>	0 - 9999	Port number.  By default, the debugger service is installed on the Windows computer's Port 2600. You can therefore leave the UNIX computer's RDPORT setting at the default. If, however, Port 2600 on Windows has been reserved for another service, and a different port number has been specified, you must change RDPORT accordingly.
<b>Default setting</b>	2600	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	





# 159

## RDS - Define Remote Directory Server

This Natural profile parameter allows you to define up to 10 remote directory servers. For each remote directory server, you specify up to 5 subparameters.

RDS is specified on the client side only.

<b>Possible settings</b>	<i>server-name</i>	The server name (1 - 8 characters). There is no default, the value must be specified.	
	<i>server-node</i>	The server node (1 - 8 characters). There is no default, the value must be specified.	
	<i>subprogram</i>	The name of the subprogram titled CALLNAT, (1 - 8 characters) to be used as interface (default is RDSSCDIR).	
	<i>logon-indicator</i>	A logon indicator. If nothing is specified, blank is the default.	
		L	The client initiates a Natural logon to the server with the library name of the current library on the client.
		blank	No server logon will be executed.
	Note for Windows platforms: instead of L, check the selection box.		
<i>transport-protocol-name</i>	The transport protocol to be used. ACI is the only possible value and the default.		
<b>Default setting</b>	none	Subparameter defaults, see above.	
<b>Dynamic specification</b>	yes	See below.	
<b>Specification within session</b>	no		

For dynamic specification the syntax is as follows.

**Using 1 server:**

```
RDS=(server-name,server-node-name,subprogram,logon-indicator,transport-protocol-name)
```

**Using 2-10 servers:**

```
RDS=((server-name,server-node  
name,subprogram,logon-indicator,transport-protocol-name)(server-name,server-node  
name,subprogram,logon-indicator,transport-protocol-name)...(server-name,server-node  
name,subprogram,logon-indicator,transport-protocol-name))
```

For additional information on Natural RPC, see the *Natural Remote Procedure Call (RPC)* documentation.

# 160

## RECAT - Dynamic Recataloging

This Natural profile parameter specifies the action to be taken if Natural detects an inconsistency in the global data area definition as defined in the program currently being executed; that is, the global data area in the program does not correspond to the definition of the global data area currently in use.

<b>Possible settings</b>	ON	<p><b>Important:</b> This profile parameter only applies to Natural objects of Version 2.3 and above.</p> <p>Natural issues an error message and disables the <b>system commands</b> CATALOG, PURGE and SAVE.</p> <p>If the RECAT parameter has been set to ON, and an object exists in both source and cataloged form, then the source and the cataloged object cannot be processed independently. In order to ensure consistency between the source and the cataloged object, Natural disables the system command CATALOG (also when invoked via CATALL). In addition, the system commands PURGE and SAVE are disabled for a source for which a corresponding cataloged object exists.</p> <p><b>Note:</b> Only objects satisfying the criteria for a particular command (such as PURGE) will be displayed in the corresponding selection box.</p>
	OFF	Natural issues an error message.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR1005N	See SYSEXT - <i>Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.



# 161

## REINP - Issue Internal REINPUT Statement for Invalid

### Data

---

This Natural profile and session parameter can be used to prevent an internal REINPUT for invalid data.

By default, Natural automatically issues an internal REINPUT statement if invalid data have been entered in response to an INPUT statement. With this parameter, you can switch this mechanism off. This will allow you to handle such input errors yourself in your application.

Within a Natural session, the profile parameter REINP can be overridden by the session parameter REINP.

<b>Possible settings</b>	ON	An internal REINPUT statement is issued when invalid data have been entered.	
	OFF	An internal REINPUT statement is not issued when invalid data have been entered.	
<b>Default setting</b>	ON		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N		



# 162

## ROSY - Read-Only Access to System Files

---

This Natural profile parameter disables modifications on the Natural system files [FDDM](#), [FNAT](#), [FUSER](#), [FDIC\\*](#) and [FSEC\\*](#).

\* Not supported on this platform.

<b>Possible settings</b>	ON	No data can be written to, modified on or deleted from the system files. Natural issues an error message instead of performing any action that would modify any of these system files.
	OFF	Data can be written to, modified on and deleted from the system files.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	





# 163

## RPCSDIR - Library for Service Directory

---

This Natural profile parameter specifies the name of the Natural library (or one of its steplibs) used by the client at runtime. This parameter is evaluated by the `SYSRPC` utility functions Service Directory Maintenance and Server Command Execution.

`RPCSDIR` is specified on the client side only.

<b>Possible settings</b>	1 - 8 characters	Valid Natural library name.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For further information on Natural RPC, see the *Natural Remote Procedure Call (RPC)* documentation.



# 164

## RTINT - Allow Runtime Interrupt

---

This Natural profile parameter determines whether it should be allowed to interrupt a running Natural application that does not respond anymore by using the interrupt key combination of the operating system (typically CTRL+C).

<b>Possible settings</b>	ON	Interrupts are allowed.
	OFF	Interrupts are not allowed.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For further information, see *Interrupting a Running Natural Application* in the *Programming Guide*.



# 165

## SA - Sound Terminal Alarm

---

This Natural profile and session parameter specifies whether the terminal alarm feature is to be used.

Within a Natural session, the profile parameter SA can be overridden by the session parameter SA.

<b>Possible settings</b>	ON	The terminal alarm is sounded each time the user is prompted for input by Natural.	
	OFF	No terminal alarm is used for input prompting, however, the alarm may still be activated with the SOUND ALARM option of the REINPUT statement.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See SYSEXT - <i>Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	



# 166

## SB - Selection Box

---

▪ Syntactical Considerations .....	376
▪ Runtime Considerations .....	377

Selection boxes in an `INPUT` statement are available on mainframe computers only. For other platforms, selection boxes may be defined in the map editor only.

Selection boxes can be attached to input fields. They are a comfortable alternative to help routines attached to fields, since you can code a selection box direct in your program. You do not need an extra program as with help routines.

You may define a selection box clause for every `INPUT` variable of type alpha, regardless if this field is an input or output field, or both.

The syntax is:

```
SB=operand1 [,operand1]...
```

where *operand1* represents a value operand which is used to fill up the selection box with items.

Operand	Possible Structure	Possible Formats	Referencing Permitted	Dynamic Definition
<i>operand1</i>	C S A	A	yes	no

With SB, you specify the values to be displayed within the selection box.

**To assign a selection box to a field:**

Specify the attribute SB for an alpha `INPUT` field in your Natural program using the following example syntax:

```
INPUT #FLD (SB='value1', #ITEM1, #ITEM2(1:3), #ITEM3(*))
```

The following topics are covered below:

## Syntactical Considerations

---

It is possible to assign both a selection box and a help routine to a field.



Selection boxes can be defined for every variable field in an `INPUT` statement. Exceptions are the following:

<b>System Variables</b>	For example: *PROGRAM, *COM
<b>Named Constants (mainframe only)</b>	defined with a <code>CONST</code> clause of <code>DEFINE DATA</code> statement.

In addition to the `SB` attribute, other attributes can be defined as well, for example: `AD` or `CD`.

The selection box field does not have to be modifiable, as is the case with `AD=A` or `AD=M`. In other words, it is possible to provide a selection box (and select values) even for a write-protected output field, such as `AD=0`. If you use `AD=0`, the user is forced to choose from a set of predefined values, which themselves appear in a selection box.

## Runtime Considerations

---

### Selection Box Position

When a program containing a selection box is executed, the selection box is positioned on the screen according to the same positioning algorithm used for help windows; that is, the size and position of the selection box are determined automatically, “near” the field.

### Selection Box Attributes

The color and intensified attributes assigned to the field are also applied to the values displayed in the corresponding selection box.

### Edit Masks in Selection Boxes

If an edit mask has been defined for the field, the edit mask is applied to all selection box values.

#### To define an edit mask for a field:

Using the `INPUT` statement, you can define an edit mask for a field. This is demonstrated in following code example.

```
DEFINE DATA
LOCAL
1 A(A4)
END-DEFINE
MOVE 'ABCD' TO A
*
SET KEY PF1 = HELP
FORMAT KD=ON
```

```
*  
INPUT A (AD=M EM=X.X.X.X SB='1234','WXYZ')  
WRITE A  
END
```

### **Selection Box Line Sizes**

The line size of the selection box matches the field length to which the box corresponds.

If a value intended for the selection box exceeds the line size of the selection box, the value is truncated.

### **Sequence of Selection Box Values**

Selection box values are displayed in the order they appear in the SB attribute.

# 167

## SD - Time Delay between Two Screens

---

This Natural profile parameter can be used to delay the time related to screen output display. This is the time delay between two screens during a non-conversational write operation (see the Natural terminal command %N).

<b>Possible settings</b>	0 - 100	The unit for the specified setting is a tenth of a second, which means that SD=10 leads to a delay of one second.
<b>Default setting</b>	0	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 168

## SERVER - Start Natural Session as an RPC Server

### Session

---

This Natural profile parameter specifies whether or not the Natural session will be started as an RPC server session.

SERVER can be specified on both the client and the server side.

<b>Possible settings</b>	ON	The Natural session will be started as an RPC server session.
	OFF	The Natural session will not be started as an RPC server session.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.



# 169 SF - Spacing Factor

---

This Natural profile and session parameter specifies the default number of spaces to be inserted between field settings of columns on Natural reports created using a `DISPLAY` statement.

Within a Natural session, the profile parameter `SF` can be overridden by the session parameter `SF`.

<b>Possible settings</b>	1 - 30	Number of spaces.  The <code>SF</code> parameter cannot be set to 0; that is, at least one blank character must be placed between report columns.	
<b>Default setting</b>	1		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

**Under Natural Security:** The setting of this parameter can be overridden by the *Session Parameters* option of the Library Profile.

See also *Column Spacing - SF Parameter and nX Notation* in the *Programming Guide*.





# 170

## SG - Sign Position

---

This session parameter determines whether or not a sign position is to be allocated for a numeric field.

If the **EM** (edit mode) parameter is specified, it overrides the **SG** parameter.

<b>Possible settings</b>	ON	A sign position will be allocated.	
	OFF	No sign position will be allocated.  SG=OFF causes numeric fields with negative values to be output without a minus (-) sign.  SG=OFF does not prevent you from entering negative values in input fields.	
<b>Default setting</b>	ON		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT INPUT PRINT WRITE
		Applicable Command:	none

### Example:

```
FORMAT SG=OFF
```

See also *Parameters to Influence the Output of Fields in the Programming Guide*.



# 171

## SHELL - Grant Shell Access to Natural User

---

This Natural profile parameter can only be set by Natural administrators. This parameter allows or disallows the shell exit from the Natural Main Menu for specific users.



**Caution:** Be careful when granting shell access to a Natural user. This might introduce security problems, because the user would then be able to use the underlying features of the operating system.

<b>Possible settings</b>	YES	Shell exit is allowed. If the shell exit is allowed for a user, the name of the shell that will be started for this user can be specified by the administrator.  This shell name must be the full path name of an executable UNIX program, for example: <i>/bin/csh</i> .
	NO	Shell exit is not allowed.
<b>Default setting</b>	NO	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 172

## SSLPRX - Specify URL of SSL Proxy Server

---

This Natural profile parameter specifies the Uniform Resource Locator (URL) of the (intranet) SSL proxy server through which all requests have to be routed (optional).

<b>Possible settings</b>	<i>url</i>	URL of SSL proxy server
<b>Default setting</b>	none	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 173

## SSLPRXPT - Specify Port Number of SSL Proxy

---

This Natural profile parameter specifies the port number of the proxy, if any is set.

<b>Possible settings</b>	<i>nnnn</i>	Port number of proxy, 4 characters at maximum.
<b>Default setting</b>	443	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	





# 174

## SM - Programming in Structured Mode

This Natural profile and session parameter specifies whether or not structured mode must be used.

Within a Natural session, the profile parameter setting `SM=OFF` can be overridden by the session parameter `SM=ON`.

<b>Possible settings</b>	ON	Forces the use of structured mode syntax.  <b>Note:</b> If structured mode ( <code>SM=ON</code> ) is specified by profile parameter <code>SM</code> , an attempt to change this setting with system command <code>GLOBALS</code> and session parameter <code>SM</code> will be rejected (Reporting mode not permitted).	
	OFF	Programming can be done in either structured mode or reporting mode.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	none
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

### If Natural Security is installed:

- the setting of the mode option in the library's security profile determines whether the `SM` profile parameter can be used; see also *Programming mode* in the *Natural Security* documentation.
- this parameter may be disabled by Natural Security to the effect that structured mode is invariably in effect for a given library.



# 175

## SNAT - Sound a Bell at Syntax Error

---

This Natural profile parameter is used to sound a bell when the compiler detects a syntax error in a Natural program.

<b>Possible settings</b>	ON	A bell will sound when a syntax error is encountered.
	OFF	No bell will sound in the case of syntax errors.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 176

## SORTSIZE - Size of Sort Buffer

---

This Natural profile parameter specifies the amount of storage to be reserved for use by the SORT program. This sort buffer is only allocated when executing a Natural program which contains a SORT statement.

<b>Possible settings</b>	500 - 2048	Buffer size in KB. Increasing the setting leads to faster SORT processing, in particular when all data to be sorted fit into the sort buffer.
<b>Default setting</b>	500	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 177

## SRETAIN - Retain Source Format

---

This Natural profile parameter specifies that all existing sources have to be saved in their original encoding format.

This parameter only takes effect if sources are edited in a Natural Single Point of Development environment, because otherwise sources which have an encoding that is different from the current code page cannot be opened anyway.

When new sources are created, they will be saved either in the current code page format or in UTF-8 format, depending on the setting of profile parameter `SUTF8`. This is independent of the setting of `SRETAIN`.

If a source can not be saved in the target code page format, because this code page does not define all characters contained in the source, a message is displayed which allows the user to choose whether he/she wants to remove the problematic characters or cancel the save process.

See also *Profile Parameters in the Unicode and Code Page Support* documentation.

<b>Possible settings</b>	ON	The original code page of an existing Natural source is retained.  If the profile parameter <code>SUTF8</code> is defined as well, new sources will be saved in UTF-8 format.
	OFF	For existing Natural sources with format UTF-8 the encoding will not be changed. Existing sources with other encodings will be saved using the current code page.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	





# 178

## SRVCMIT - Server Commit Time

---

This Natural profile parameter specifies the time at which a Natural RPC server automatically commits an RPC conversation or a non-conversational RPC request. This parameter is only evaluated if the profile parameter [ETEOP](#) is set to ON.

SRVCMIT is specified on the server side only.

<b>Possible settings</b>	B	The Natural RPC server automatically commits a database transaction before the reply is sent to the client. If the reply fails, the database transaction is already committed.
	A	The Natural RPC server automatically commits a database transaction after the reply has been successfully sent to the client. If the reply fails, the database transaction is rolled back.
<b>Default setting</b>	B	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.



# 179

## SRVNAME - Name of RPC Server

---

This Natural profile parameter specifies the name of the RPC server, with which it registers on the node specified with the profile parameter [SRVNODE](#).

SRVNAME is specified on the server side only.

<b>Possible settings</b>	1 - 192 characters	Valid server name.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

You may either specify a physical server name of up to 32 characters or a logical service name of up to 192 characters. In case of a logical service name, an asterisk (\*) must be specified with the [SRVNODE](#) parameter(intentionally left empty).

In case of an EntireX Broker node, the value of SRVNAME corresponds to the value of the SERVER attribute of a service entry in the broker attribute file, as below:

```
CLASS=RPC, SERVICE=CALLNAT, SERVER=srvname
```

### Example:

```
SRVNAME='PRODUCTION_SERVER'           /* physical server name */  
SRVNAME='MY_LOGICAL_SERVICE,MY_SET'    /* logical server name */
```

For more details about Location Transparency and logical service names, refer to the EntireX documentation.

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.



# 180

## SRVNODE - Name of Node

---

This Natural profile parameter specifies the name of the node upon which an RPC server registers.

SRVNODE is specified on the server side only.

<b>Possible settings</b>	1 - 192 characters	Node name.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

You may either specify a physical node name of up to 32 characters, a logical node name of up to 192 characters or an asterisk (\*) (intentionally left empty) to indicate that `SRVNAME` contains a logical service name.

In case of an EntireX Broker node, a physical node name may refer to an Entire Net-Work node or to an TCP/IP address. Note that the broker stub in use must support the naming notation. For details about the structure of node names and their support by the broker stubs, refer to the EntireX documentation.

The examples below are based on the EntireX notation.

```
SRVNODE=ETB001 /* Entire Net-Work node */
SRVNODE=PCBROKER /* host name for a TCP/IP address */
SRVNODE='157.189.160.95:1958:TCP' /* TCP/IP address with port number */
SRVNODE='tcpip://host.com:1958' /* host name for a TCP/IP address
with port number */
SRVNODE='LOGBROKER=MY_LOGICAL_NODE,MY_SET' /* logical node name */
SRVNODE='*' /* logical service name in SRVNAME */
```

If a host name is used for the TCP/IP address, the name must either be known to your DNS server or it must be defined in the hosts file of your TCP/IP configuration.

If the port number is omitted, either a default port number is used by the EntireX broker stub or a host name must be used, and the host name must be known to your DNS server or must be defined in the services file of your TCP/IP configuration.

For more details about Location Transparency and logical node names, refer to the EntireX documentation.

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.

# 181

## SRVTERM - Server Termination Event

---

This Natural profile parameter specifies the event at which a Natural RPC server is automatically terminated.

SRVTERM is specified on the server side only.

<b>Possible settings</b>	NEVER	A Natural RPC server is never automatically terminated. To terminate a Natural RPC server refer to <i>Terminating a Natural RPC Server</i> and <i>Terminating an EntireX Broker Service</i> in the <i>Natural Remote Procedure Call (RPC)</i> documentation.
	TIMEOUT	A Natural RPC server is automatically terminated if the wait time for the next client request outside of an RPC conversation is exceeded. TIMEOUT should only be set if you use an Attach Manager to dynamically start Natural RPC servers on request.
<b>Default setting</b>	NEVER	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.





# 182

## SRVUSER - User ID for RPC Server Registry

This Natural profile parameter specifies the user ID needed to register an RPC server on the node specified with the profile parameter [SVRNODE](#).

In case of an EntireX Broker node, `SRVUSER` is also used to logon to the EntireX Broker. A password is either taken from Natural Security (see `*NSC` below) or specified via the application programming interface `USR2072N`.

`SRVUSER` is specified on the server side only.

<b>Possible settings</b>	<i>user-ID</i>	Valid user ID, *USER or *NSC. 1 to16 characters.
	*USER	If <code>SRVUSER</code> is set to *USER, the Natural server uses the current Natural user ID (see system variable *USER) to logon to the node.
	*NSC	If <code>SRVUSER</code> is set to *NSC and Natural Security is installed, the Natural server uses the current Natural user ID (see system variable *USER) and the password defined for this user ID in Natural Security to logon to the node.
<b>Default setting</b>	<i>timestamp</i>	If the user ID is omitted, the timestamp will be used.
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.



# 183

## SRVWAIT - Wait Time of RPC Server

---

This Natural profile parameter specifies the number of seconds the server is to wait for an RPC client request. If this time is exceeded, the RPC server is informed by the transport layer. The RPC server writes a corresponding message to the Natural RPC server trace file and continues to wait for an RPC client request.

SRVWAIT is specified on the server side only.

<b>Possible settings</b>	0 - 32767	Wait time in seconds.
<b>Default setting</b>	0	Unlimited wait time.
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.



# 184

## SSIZE - Size of Source Area Allocated by the Editors

---

This Natural profile parameter determines the maximum size of the Natural source area, which will be dynamically allocated by the Natural editors.

<b>Possible settings</b>	1 - 100	Maximum size of the Natural source area in MB.
<b>Default setting</b>	1	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



**Note:** The maximum size for one Natural source member is 1 MB (independent of SSIZE).



# 185

## STACK - Place Data/Commands on the Stack

---

This Natural profile parameter is used to place data/commands on the Natural stack.



**Note:** If STACK is used, a colon (:) must be specified with the profile (or session) parameters DC, HI, IA and ID .

<b>Possible settings</b>	any character string
<b>Default setting</b>	none
<b>Dynamic specification</b>	yes
<b>Specification within session</b>	no

The profile parameter STACK is used to place data/commands on the Natural command stack. The amount of data to be passed with this parameter is limited to 512 bytes. If this limit is exceeded, a corresponding error message is returned.

The stack can contain a sequence of Natural commands and/or user-specified commands, together with their data, for execution at the beginning of the Natural session. The command stack is processed before the user is prompted for input on the screen.

If an INPUT statement is encountered during stack processing, the corresponding input screen is generated only if the required input data were not supplied with the command when the stack was created. Any reports generated during stack processing are displayed as usual.

Each system or user-defined command can be optionally followed by data which are used to satisfy requests for information required during the processing of the command. If the command is a user command (that is the name of a user program), any data provided resolve the data requirements of INPUT statements within the user program.

Multiple settings for one `INPUT` statement are separated by a comma. Data for multiple `INPUT` statements are separated by a colon (:). A semicolon (;) is used to delimit multiple commands, for example:

```
LOGON:USER1;UCMD1 A,B;UCMD2 C,D:E;FIN
```

Logs on to the library `USER1`, executes the commands `UCMD1` and `UCMD2` providing the corresponding input data, and ends the Natural session.

```
CMD DATA:DATA;CMD
```

Places commands and data on stack. Since some commands (for example, `GLOBALS`) do not read parameters by `INPUT`, a blank character should be used rather than a colon to delimit a command from the first parameter data element.

If specified dynamically, the character string provided as data for the `STACK` parameter must be enclosed in apostrophes; if the character string contains multiple commands, it must also be enclosed in parentheses, for example:

```
STACK="(LOGON SYSTEM;UCMND)"
```

Logs on to the library `SYSTEM` and executes the command `UCMND`.



# 186

## STARTUP - Program Name for System Variable

### \*STARTUP

---

This Natural profile parameter specifies a program name for the Natural system variable \*STARTUP. The program whose name is contained in \*STARTUP is executed each time the Natural command line is invoked. In a Natural program, you can assign another program name to \*STARTUP.

<b>Possible settings</b>	1 - 8 characters	Valid program name.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



**Note:** If you have Natural Security installed, STARTUP is not evaluated; the startup program to be used is read from the library profile defined in Natural Security.



# 187

## STEPLIB - Initial Setting for \*STEPLIB System Variable

---

This Natural profile parameter specifies the initial setting for the system variable \*STEPLIB.

<b>Possible settings</b>	1-8 characters	Any valid library name.
<b>Default setting</b>	SYSTEM	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

The contents of the system variable \*STEPLIB influences the order in which objects are searched in the system file.

Using the Configuration Utility, you can define additional steplib's that can be searched for objects which cannot be found in the current library. See *Steplibs* in the *Configuration Utility* documentation.

See also *Steplibs* and *Search Sequence for Object Execution* in the *Using Natural* documentation.



# 188

## SUBCHAR - Substitution Character for Default Code

### Page

---

This Natural profile parameter allows you to specify the substitution character for the default code page. The substitution character is automatically inserted whenever the conversion of a Unicode character into the current default code page (see profile parameter [CP](#)) fails and the profile parameter [CPCVERR](#) is set to `OFF`.

<b>Possible settings</b>	<i>n</i>	Substitution character.
	<code>OFF</code>	If <code>OFF</code> is specified, the ICU default substitution character is used; for further information, see also <i>Profile Parameters</i> in the <i>Unicode and Code Page Support</i> documentation.
<b>Default setting</b>	<code>OFF</code>	
<b>Dynamic specification</b>	<code>no</code>	
<b>Specification within session</b>	<code>no</code>	



# 189

## SUTF8 - UTF-8 Format for Sources

---

This Natural profile parameter specifies the default format to be used when Natural sources are saved.

It is valid only for Natural Development Server sessions; it will be ignored in a native Natural for UNIX session.

See also *Profile Parameters in the Unicode and Code Page Support* documentation.

<b>Possible settings</b>	ON	The default format for saving Natural sources is UTF-8.  All sources will be saved in UTF-8 format, which assures that the source content does not depend on the installed system code page.  If the profile parameter <b>SRETAIN</b> is also set to ON, only newly created sources will be saved in UTF-8 format. Existing sources will then be saved in the original encoding, if possible.
	OFF	The default format for saving Natural sources is "code page".
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	





# 190

## SYMGEN - Generate Symbol Table

---

This Natural profile and session parameter specifies whether a symbol table is to be generated or not.

The symbol table contains all symbols used within a Natural program (for example, variable names). It is part of the generated program and is required, for example, for the Natural Debugger and the dialog editor.

Within a session, the profile parameter SYMGEN can be overridden by the session parameter SYMGEN.

<b>Possible settings</b>	ON	A symbol table will be generated.	
	OFF	No symbol table will be generated.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	none
		Applicable Command:	GLOBALS



# 191

## SYNERR - Control of Syntax Errors

---

This Natural profile parameter specifies whether or not syntax errors will be passed to the error transaction program.

<b>Possible settings</b>	ON	Syntax errors are passed to the error transaction program.
	OFF	Syntax errors are not passed to the error transaction program.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR4007N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

The error transaction program is defined either with the profile parameter [ETA](#) or by a user program by way of assignment to the system variable \*ERROR-TA or, if Natural Security is installed, within the Natural Security library profile; see *Components of a Library Profile* in the *Natural Security* documentation.

For further information, see *Using an Error Transaction Program* in the *Programming Guide*.



# 192 TC - Trailing Characters

With this session parameter, you can specify trailing characters that are to be displayed immediately to the right of a field output with a `DISPLAY` statement. The width of the output column is enlarged accordingly.

The parameter `TC` can also be used with `U` format fields. For information on Unicode format, see also *Unicode and Code Page Support in the Natural Programming Language, Session Parameters, EMU, ICU, LCU, TCU versus EM, IC, LC, TC*.

<b>Possible settings</b>	any character	Up to 10 characters may be specified.  Trailing characters may optionally be specified enclosed within apostrophes, in which case any characters can be specified. Any character string specified which contains a closing parenthesis or a quotation mark must be enclosed within apostrophes.	
<b>Default setting</b>	none		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT
		Applicable Command:	none

## Examples:

```
FORMAT TC=*
DISPLAY (TC='*B*')
```

See also *Parameters to Influence the Output of Fields in the Programming Guide*.



# 193

## TCU - Unicode Trailing Characters

---

The session parameter `TCU` is identical to the session parameter `TC`. The difference is that the trailing characters are always stored in Unicode format. This allows you to specify trailing characters with mixed characters from different code pages, and assures that always the correct character is displayed independent of the installed system code page.

With this session parameter, you can specify trailing characters that are to be displayed immediately to the right of a field output with a `DISPLAY` statement. The width of the output column is enlarged accordingly.

<b>Possible settings</b>	any character	Up to 10 characters may be specified.  Trailing characters may optionally be specified enclosed within apostrophes, in which case any characters can be specified. Any character string specified which contains a closing parenthesis or a quotation mark must be enclosed within apostrophes.	
<b>Default setting</b>	none		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT
		Applicable Command:	none

See also:

- *Parameters to Influence the Output of Fields in the Programming Guide*
- *Unicode and Code Page Support in the Natural Programming Language, Session Parameters, EMU, ICU, LCU, TCU versus EM, IC, LC, TC*





# 194 TD - Time Differential

---

This Natural profile parameter specifies a time differential to be applied to the Natural time/date setting to ensure that the current local time/date is used, rather than the computer center time/date. This parameter is applicable in an environment in which remote nodes are being used in a computer network.

<b>Possible settings</b>	- 23 , 59 to 23 , 59	The notation <i>hours , minutes</i> is used to add/subtract the specified time to/from the physical machine time to set the time/date to be used by Natural; <i>minutes</i> (if specified) must be 00-59.
<b>Default setting</b>	0 , 0	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

## Examples:

```
TD=6           (6 hours ahead)
TD=-11         (11 hours behind)
TD=(5,30)      (5 hours and 30 minutes ahead)
TD=(-6,30)     (6 hours and 30 minutes behind)
```



# 195

## TF - Translation of Database ID/File Number

 **Caution:** This parameter applies to user files only. It does not apply to system files.

This Natural profile parameter is used to translate the database ID/file number of a production database into the database ID/file number of a test database.

The translation of file number is relevant when developing an application in a production environment; it enables you to develop an application in a test database and then transfer the finished application to the production database without having to change or re-compile the application.

The transfer is done by a translation of the application's database identification (DBID) and file number (FNR): with the `TF` parameter, you specify the production DBID/FNR and the test DBID/FNR. The Natural objects are then cataloged with the production DBID/FNR, but whenever a database access is executed, the production DBID/FNR is translated into the test DBID/FNR; that is, the test database is used. This means that testing can take place in the actual production environment, but not with production data.

<b>Possible settings</b>	<i>production-DBID</i>	0-65535, except 255 or can be an asterisk (*) which stands for all DBIDs. DBID 255 is reserved for logical system files for Software AG products, see profile parameter <a href="#">LFILE</a> .
	<i>production-FNR</i>	1-5000, or an asterisk (*) which stands for all FNRs.
	<i>test-DBID</i>	0-65535, except 255.
	<i>test-FNR</i>	1-5000
<b>Default setting</b>	none	
<b>Dynamic specification</b>	yes	This parameter can be specified dynamically and in the Natural parameter file NATPARM.
<b>Specification within session</b>	no	

The asterisk (\*) notation for *production-DBID* and *production-FNR* is mutually exclusive.

The parameter is specified as follows:

```
TF=(production-DBID,production-FNR,test-DBID,test-FNR)
```

The TF parameter can be specified several times. Existing specifications are displayed in a corresponding list box.



**Notes:**

1. Production and test databases must be of the same type (Adabas/Adabas, for example).
2. If the database type is not specified in NATPARM, the Adabas is used as default type; that is, SQL and XML databases must be specified explicitly.
3. For SQL and XML databases, the file number must always be set to 1. The DBID must be in the range of 0-254.
4. The profile parameter UDB (User Database ID) is evaluated before the TF parameter is evaluated.

This Natural profile parameter is used to enable or disable the use of dynamic thousands separators in edit masks at compilation time. At runtime the dynamic thousands separators are replaced by the value (thousands separator character) of the profile and session parameter [THSEPCH](#).

<b>Possible settings</b>	ON	Dynamic thousands separators are used. Every dynamic thousands separator that is not part of a string literal is replaced at runtime with the thousands separator character defined with <a href="#">THSEPCH</a> .	
	OFF	Dynamic thousands separators are not used, that is, thousands separators in the edit mask are treated as literal and displayed unchanged at runtime. This is the compatibility setting.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	OPTIONS
		Applicable Command:	THSEP option of COMPOPT



#### Notes:

1. In the Natural source, the dynamic thousands separator is either a comma (,) or a period (.), depending on the current setting of the profile and session parameter [DC](#) (decimal character). If a comma is specified, then the dynamic thousands separator is a period, otherwise it is a comma.
2. Fields in Unicode format should not be redefined as alphanumeric (A) or numeric (N) fields.

See also:

- Profile parameter [THSEPCH](#) in the *Parameter Reference*.
- *Customizing Separator Character Displays* in the *Programming Guide*.



# 197

## THSEPCH - Thousands Separator Character

This Natural profile and session parameter is used to specify the character to be used as thousands separator at runtime. Then the thousands separator character replaces the dynamic thousands separators in edit masks.



**Note:** In the Natural source, the dynamic thousands separator is always represented by a comma (,) or a period (.).

<b>Possible settings</b>	any character	At runtime, the dynamic thousands separator is replaced with this character.  If the thousands separator character is to be a comma, it must be enclosed in quotes, that is, THSEPCH=' , ' when using the dynamic parameter facility, because a comma is used to separate individual parameters.  If the thousands separator character is to be a quote, it must be specified as two quotes enclosed in quotes, that is, THSEPCH=' ' ' ' .	
<b>Default setting</b>	, (comma)	By default, a comma is used as thousands separator.	
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	none
		Applicable Command:	GLOBALS

See also:

- Profile parameter [THSEP](#) in the *Parameter Reference* documentation.
- Option THSEP of system command COMPOPT in the *System Commands* documentation.
- *Customizing Separator Character Displays* in the *Programming Guide*.





# 198

## TIMEOUT - Wait Time for RPC Server Response

---

This Natural profile parameter specifies the number of seconds the client is to wait for an RPC server response. If this time is exceeded, the remote procedure call will be terminated with a corresponding error message.

TIMEOUT is specified on the client side only.

<b>Possible settings</b>	0-32767	Seconds.
<b>Default setting</b>	55	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	yes	At runtime, this value can be overwritten using the Parameter Maintenance function of the SYSRPC utility.

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.



# 199

## TMPSORTUNIQ - Alternate Algorithm for Generating

### Sort Work File Names

---

If this profile parameter is specified on the Natural startup command, Natural will use a different algorithm from normal when generating work file names for sort operations. It forces Natural to generate a unique file name for any required work files without embedding the values of the `ETID` parameter and user ID into the file name.

The normal, default algorithm creates work file names with the values of the `ETID` setting and the user ID embedded. Whereas this algorithm usually results in file names which are unique to a particular Natural session, this may cause problems in environments where the `ETID` contains characters which are invalid within a file name, or where multiple Natural sessions are running which use the same user ID and no `ETID` specification (thus possibly resulting in work file names for sort operations being created which are not unique).

<b>Possible settings</b>	specified or not specified	If specified, Natural will use a different algorithm from normal when generating work file names for sort operations.
<b>Default setting</b>	not specified	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



## 200 TQ - Translate Quotation Marks

---

This parameter corresponds to the Natural profile parameter [TQMARK](#).



# 201

## TQMARK - Translate Quotation Marks

---

This Natural profile parameter controls the translation of a quotation mark (") within a Natural text constant. It takes effect at compilation time only.

<b>Possible settings</b>	ON	Each quotation mark within a text constant is output as a single apostrophe.	
	OFF	Quotation marks within text constants are not translated, they are output as quotation marks.	
<b>Default setting</b>	ON		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	OPTIONS
		Applicable Command:	TQMARK option of COMPOPT



**Note:** Do not confuse quotation mark (") with double apostrophes ( ' '). Double apostrophes within a text constant are always output as a single apostrophe ( ' ), regardless of the setting of the TQMARK parameter.

### Example 1 (TQMARK=ON):

```
WRITE 'THERE"S A QUOTATION MARK'
```

is displayed as: THERE'S A QUOTATION MARK

**Example 2 (TQMARK=OFF):**

```
WRITE 'THERE"S A QUOTATION MARK'
```

is displayed as: THERE"S A QUOTATION MARK

**Example 3 (TQMARK=ON or OFF):**

```
WRITE 'DOUBLE APOSTROPHES'' OUTPUT IS A SINGLE APOSTROPHE'
```

is displayed as: DOUBLE APOSTROPHES' OUTPUT IS A SINGLE APOSTROPHE



# 202

## TRACE - Define Trace Level for Natural RPC Servers

---

This Natural profile parameter activates the RPC trace facility and determines the trace level *n* to be used. For further information, see *Using the Server Trace Facility* p.p. in the *Natural Remote Procedure Call (RPC)* documentation.

TRACE is specified on the server side only.

<b>Possible settings</b>	0	Nothing is traced.
	1	Only messages (inclusive Natural errors) are traced.
	(1, E)	Messages are traced in the event of an error only.
	2	All messages and data from/to client are traced.
	(2, E)	Messages and data from/to client are traced in the event of an error only.
<b>Default setting</b>	0	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

The values 3 - 9 are also accepted. These values are for future use and behave like TRACE=2.

For further information see the *Natural Remote Procedure Call (RPC)* documentation.



# 203

## TRANSP - Server Transport Protocol

---

This Natural profile parameter determines which server transport protocol is used. If ACI is used, you can additionally specify the transport method.

TRANSP is specified on the server side only.

<b>Possible settings</b>	ACI	ACI is used. The transport method is defined by the EntireX Broker.
	(ACI , TCP)	ACI is used with TCP/IP.
	(ACI , NET)	ACI is used with Entire Net-work, i.e. using the Adabas protocol.
	(ACI , TCP - NET)	Trying to use ACI with TCP. If not available, ACI is used with NET.
	(ACI , NET - TCP)	Trying to use ACI with NET. If not available, ACI is used with TCP.
<b>Default setting</b>	ACI	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

The use of TRANSP is no longer required as you may now specify the full node name with [SRVNODE](#). It is still supported for compatibility reasons.

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.



# 204

## TRYALT - Try Alternative Server Address

---

This Natural profile parameter determines whether an RPC client should try to execute an RPC request on an alternative server (ON) or not (OFF). For further information, see *Specifying RPC Server Adresses* in the *Natural Remote Procedure Call (RPC)* documentation.

TRYALT is specified on the client side only.

<b>Possible settings</b>	ON	If a request could not be executed on the node you specified, the RPC client tries to find an alternative server address to send that request to.
	OFF	No such attempt will be made.
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	yes	At runtime, this value can be overwritten using the Parameter Maintenance function of the SYSRPC utility.

For further information, see the *Natural Remote Procedure Call (RPC)* documentation.



# 205

## UC - Underlining Character

---

This session parameter determines the character that is used as underlining character for the following:

- column headings generated by `DISPLAY` statements;
- page titles/trailers produced by `WRITE TITLE`/`WRITE TRAILER` statements with `UNDERLINED` option.

<b>Possible settings</b>	any character	See also Note below.	
	OFF		
<b>Default setting</b>	- (hyphen)		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT WRITE TITLE WRITE TRAILER
		Applicable Command:	none



**Note:** If you do not wish column headers to be underlined, you have the following options:

- `UC=` - A blank line will be output instead of underlining.
- `UC=OFF` - The field values will be output immediately below the heading line, without any blank line in between.

You can specify `UC=OFF` only at the statement level of a `DISPLAY` statement; in this case, you cannot make any other `UC` specifications for individual fields in that statement.

**Examples:**

```
FORMAT UC=*  
DISPLAY (UC= ) NAME AGE (UC=+)
```

See also *Underlining Character for Titles and Headers - UC Parameter* in the *Programming Guide*.



# 206

## UDB - User Database ID

This Natural profile parameter specifies the DBID to be used for a database access at runtime. This database ID specified with the `UDB` parameter replaces DBID 0 when Natural objects are executed.

<b>Possible settings</b>	0 - 65535, except 255	Valid database ID. Database ID 255 is reserved for logical system files for Software AG products, see profile parameter <a href="#">LFILE</a> .
<b>Default setting</b>	1	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.  * Recommended.
	USR1040N *	



### Notes:

1. The database type of DBID 0, which is specified in the DBMS assignments table of the Configuration Utility, and the database types of the DBID specified with the `UDB` parameter must be the same: ADA/ADA, ADA2/ADA2, SQL/SQL or XML/XML. As an exception, the combination ADA/ADA2 is possible. The first type is the database type of DBID 0 and the second type is the database type of the DBID specified with the `UDB` parameter.
2. If the DBID in the DDM used is 0, then the database type is taken from the DBMS assignments table entry `DBID=0` at compilation time, whereas the database type of the DBID specified with the `UDB` parameter is used only at runtime.
3. If no DBID 0 is specified in the DBMS assignments table, then the default database type is set to ADA.
4. If no DBID is specified in the DDM used, the DBID specified with the `UDB` profile parameter determines which database is accessed. If so, the `UDB` profile parameter must be set to a valid DB number.

5. UDB is also used to specify the DBID for storing transaction data if the profile parameter [ETDB](#) is not specified.

# 207 ULANG - User Language

---

This Natural profile parameter specifies the language to be used for date edit masks, system messages, user messages, helptexts, help routines, and multi-lingual maps. The setting is used to set the Natural system variable \*LANGUAGE.

<b>Possible settings</b>	1 - 60	Language code.  For example, 1 is assigned to English, 2 is assigned to German, 3 is assigned to French.  For a detailed list of language codes, see the table in the documentation of the *LANGUAGE variable.
<b>Default setting</b>	1	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	
<b>Application Programming Interface</b>	USR1005N	See SYSEXT - <i>Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.

Within the session, the language code can be specified using the terminal command %L=.

See also:

- *Screen Design, Skill-Sensitive User Interfaces* in the *Programming Guide*.



# 208

## USEDIC - Common Logical Name for Dictionary Servers

---

This Natural profile parameter is used to specify a common logical name for dictionary servers defined with Natural RPC to enable remote dictionary access on a mainframe or UNIX host.

See also *Dictionary Server Assignments* in the *Configuration Utility* documentation.

<b>Possible settings</b>	any valid server name	Remote dictionary access will be possible.
<b>Default setting</b>	blank	Remote dictionary access will not be possible.
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 209

## USER - User ID

---

This Natural profile parameter is used to enter a user ID. If the default setting is used, the login user ID from the operating system applies.

<b>Possible settings</b>	any valid user ID
<b>Default setting</b>	blank
<b>Dynamic specification</b>	no
<b>Specification within session</b>	no



**Note:** Under Natural Security, this profile parameter is ignored.





# 210

## USEREP - Repository Usage

---

This Natural profile parameter enables you to use the repository.

<b>Possible settings</b>	ON	Repository usage enabled.
	OFF	Repository usage disabled.
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 211

## USIZE - Size of User Buffer

---

This Natural profile parameter specifies the size of the user buffer in virtual memory. The user buffer contains all data dynamically allocated by Natural.

<b>Possible settings</b>	10 - 1024	Buffer size in MB.
	0	With USIZE=0, the memory capacity will be unrestricted.
<b>Default setting</b>	20	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 212

## WEBIO - Use Natural Web I/O Interface

---

This Natural profile parameter defines whether the Natural input and output (I/O) remains unchanged (i.e. terminal emulation in case of SPoD, and emulation from where Natural is started when calling Natural directly on UNIX) or whether the Natural Web I/O Interface is used.

The Natural Web I/O Interface displays the input and output data in a web browser. On platforms other than Windows, it is only possible with the Natural Web I/O Interface to display and enter U format fields with characters which are not contained in the current code page.

The parameter `WEBIO` can only be used when Natural is running as a server, not in an interactive Natural session.

See also *Profile Parameters in the Unicode and Code Page Support* documentation.

<b>Possible settings</b>	ON	I/O via Natural Web I/O Interface.
	OFF	I/O remains unchanged (terminal emulation).
<b>Default setting</b>	OFF	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	



# 213

## WFOPFA - Opening of Work Files

---

This Natural profile parameter specifies when work files are to be opened by Natural.

<b>Possible settings</b>	ON	A work file is opened at the time when it is first accessed by a given READ WORK FILE or WRITE WORK FILE statement. This means that only those work files which are actually accessed are opened, while the contents of unopened work files are not deleted.
	OFF	All work files referenced in a Natural object are opened when the execution of this object starts. (This may delete the content of a work file when closing if the work file was referenced by a WRITE WORK FILE statement that was never executed.)
<b>Default setting</b>	ON	
<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

WFOPFA=OFF only affects main programs; for routines, WFOPFA=ON always applies.





# 214

## WH - Wait for Record in Hold Status

This Natural profile and session parameter applies to Adabas databases only.

It specifies the action to be taken if a required record is not available for processing, because it has been placed in hold status by another user.

Within a Natural session, the profile parameter `WH` can be overridden by the session parameter `WH`.

<b>Possible settings</b>	ON	The user is placed in wait status until either the requested record becomes available, or an error message is issued due to Adabas exceeding a time limit or other limit while attempting to place the record in hold status.	
	OFF	An error message is returned if any of these records cannot be placed in hold status.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	



**Note:** When a Natural statement is executed which results in Adabas records being read and an update/delete operation could follow, Natural requests that Adabas places these records in hold status. See the Adabas *Command Reference* documentation for further information on hold processing.

**Under Natural Security:** The setting of this parameter can be overridden by the Session Parameters option of the *Library Profile*.



# 215

## WORK - Work-File Assignments

---

This Natural profile parameter defines the number of work files to be used during the session.

<b>Possible settings</b>	0 - 32	Number of work files.
<b>Default setting</b>	32	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	

WORK=*nn*

If WORK is set to *nn* (in the range 1 - 32), this setting defines the highest work file number which is available for the Natural session.

See also *Work Files* in the *Operations* documentation.



# 216 XADB - Database for Coordination of Transaction

## Processing

---

This Natural profile parameter is reserved for future use.

It specifies the databases, where transaction processing is to be coordinated by a TP-monitor system. Mark all such databases in the parameter's database list box.

<b>Possible settings</b>	ON / OFF	Use the check boxes to specify the relevant databases.
<b>Default setting</b>	none	
<b>Dynamic specification</b>	no	
<b>Specification within session</b>	no	



# 217

## XREF - Creation of XRef Data for Natural

---

- Extended XRef Data Generation (For Internal Use Only) ..... 481

This Natural profile parameter is used to enable/disable the creation of XRef data for Natural. These are generated in two cases:

- The Natural compiler writes XRef data for Natural programs and data areas when these are cataloged (provided that the XREF parameter has been set to either ON or FORCE, see below).
- Natural Security writes XRef data for programs that are used as Startup, Restart or Error-Transaction in an application or as a special link if the XREF parameter is set to ON or FORCE in the application's Natural Security definition and a user system file is defined for the application.

This parameter controls the compilation in two aspects:

- generation of XRef data in the cases described above and
- to fulfil premise to document implementation objects. The adherence to this premise can be ensured by allowing the completion of the catalog operation only for objects that are documented in the Predict FDIC system file or in the development server file used in Natural Single Point of Development (SPoD).

This parameter also determines how XRef data are treated when Natural members are processed with the Natural utilities SYSMAIN or INPL or with the Object Handler.

<b>Possible settings</b>	ON	XRef data are generated in the cases described above. Documentation premise is not checked.	
	OFF	XRef data are not generated. Documentation premise is not checked.	
	FORCE	A Natural object can only be cataloged if a documentation object already exists for this implementation object. XRef data are generated in the cases described above.	
	DOC	A Natural object can only be cataloged if a documentation object already exists for this object. XRef data are not generated.	
<b>Default setting</b>	OFF		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	none
		Applicable Commands:	XREF

There are different ways to set the Natural XREF parameter:

- In the Natural parameter file.
- As a dynamic parameter when starting a Natural session.
- In Natural Security. If Natural Security has been used to set the XREF parameter, the XREF command may only be used to enforce this setting (by changing from ON to FORCE, from OFF to ON or FORCE).



- With the Natural XREF command. If Natural Security is not installed, the XREF parameter is usually set with the Natural XREF command. The Natural command XREF ? displays the current setting of the XREF parameter.

## Extended XRef Data Generation (For Internal Use Only)

---



**Important:** The extended XREF parameter is reserved for internal use by Natural.

The extended XREF parameter has the following syntax:

```
XREF=(normal-xref-setting,extended-xref-setting)
```



# 218

## YSLW - Year Sliding or Fixed Window

This Natural profile parameter specifies the range of years covered by the “year sliding window” or “year fixed window”.

The sliding-window or “year fixed window” mechanism assumes a date with a 2-digit year to be within a “window” of 100 years. Within these 100 years, every 2-digit year setting is uniquely related to a specific century, so that there is no confusion about which century is meant.

<b>Possible settings</b>	Normal Setting	0	When you set the parameter to 0, the current century is assumed. No sliding or fixed-window mechanism is used.
	Sliding Window	1 - 99	By setting the parameter to a value between 1 - 99, you determine when the 100-year range begins in the past. The YSLW setting is subtracted from the current year to determine the first year of the window range.  <b>Example:</b>  If the current year is 2002 and you specify YSLW=40, the sliding window will cover the years 1962 to 2061. A 2-digit year setting <i>nn</i> from 62 to 99 is then interpreted accordingly as 19 <i>nn</i> , while a 2-digit year setting <i>nn</i> from 00 to 61 is interpreted as 20 <i>nn</i> .
	Fixed Window	1582 - 2600	By setting the parameter to a value between 1582 - 2600, you determine the first year of a 100-year range. The upper boundary of the 100-year range is evaluated by adding 99 to the value specified.  <b>Example:</b>  If you specify YSLW=1985, the fixed window will cover the years 1985 to 2084. A 2-digit year setting <i>nn</i> from 85 to 99 is then interpreted accordingly as 19 <i>nn</i> , while a 2-digit year setting <i>nn</i> from 00 to 84 is interpreted as 20 <i>nn</i> .
<b>Default setting</b>	0		No sliding or fixed-window mechanism is used.

<b>Dynamic specification</b>	yes	
<b>Specification within session</b>	no	

The YSLW parameter is evaluated at runtime when an alphanumeric date setting with a 2-digit year component is moved into a date variable. This applies to data settings which are:

- used with the mathematical function VAL;
- used with the IS(D) option in a logical condition;
- read from the stack as input data;
- or entered in a map as input data.

See also the section *Processing of Date Information* in the *Programming Guide*.

# 219

## ZD - Zero-Division Check

---

This Natural profile and session parameter specifies the action to be taken when an attempt is made to perform a division operation in which the divisor is 0.

Within a Natural session, the profile parameter ZD can be overridden by the session parameter ZD.

<b>Possible settings</b>	ON	Natural issues an error message if a division by 0 is attempted.	
	OFF	Natural returns a result of 0 for any division operation in which the divisor is 0.	
<b>Default setting</b>	ON		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	SET GLOBALS
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

**Under Natural Security:** The setting of this parameter can be overridden by the *Session Parameters* option of the Library Profile.



# 220 ZP - Zero Printing

This Natural profile and session parameter specifies how a field which contains a setting of all zeros is to be output; that is, it is used to suppress the display of a numeric field (format N, I, P or F) or time field (format T) which contains a value of all zeros.

Within a Natural session, the profile parameter ZP can be overridden by the session parameter ZP.

<b>Possible settings</b>	ON	Each field value which consists of all zeros is output as one zero, right justified (for numeric fields) or all zeros (for time fields).	
	OFF	Each field value which consists of all zeros is suppressed.	
<b>Default setting</b>	ON		
<b>Dynamic specification</b>	yes		
<b>Specification within session</b>	yes	Applicable Statements:	DISPLAY FORMAT INPUT PRINT REINPUT SET GLOBALS WRITE
		Applicable Command:	GLOBALS
<b>Application Programming Interface</b>	USR1005N	See <i>SYSEXT - Natural Application Programming Interfaces</i> in the <i>Utilities</i> documentation.	

See also *Parameters to Influence the Output of Fields* in the *Programming Guide*.

