

Write Resource

Subroutine Name	Executable Example	Viewable Example	Resources
W3WRITE-RESOURCE	E3RESOUR	E3RESOUR	E3SAVE.HTML

Description

Write a resource file to the given library and fill with a given dynamic variable. If no library is specified, use the current library.

Parameters

```

1 W3LIBRARY      (A8) BY VALUE OPTIONAL /* i /o : Natural Library ID
1 W3FILE         (A) DYNAMIC BY VALUE  /* i /m : File Name
1 W3DYN          (A) DYNAMIC BY VALUE  /* i /m : Read Resource
1 W3RESPONSE    (I4)OPTIONAL           /* o/o : Response

```

If the W3RESPONSE parameter is not specified, the Web Interface error processing is triggered if an error occurs. If the W3RESPONSE parameter is specified, the parameter contains the Natural message number if an error occurred, or zero on success.

How To Invoke

```

PERFORM W3WRITE-RESOURCE W3LIBRARY W3FILE W3DYN
PERFORM W3WRITE-RESOURCE W3LIBRARY "Test.txt" W3DYN
PERFORM W3WRITE-RESOURCE W3LIBRARY W3FILE W3DYN W3RESPONSE

```

Restriction

Load Resource is only available on Natural for Windows, OpenVMS and UNIX supporting non-natural files/resources. Internally it uses workfile 12.