

Font Control

This chapter covers the following topics:

- Description
 - Attributes for Font Control
 - Events
-

Description

A font control is used to display the `STRING` attribute value of a dialog element in a certain font face, size and style. It is generated automatically if you select a font in the attributes window of a dialog element. You should, however, not rely on the automatic generation of specific font control names. You can also create a font control dynamically by using the `NGU-FONT-SELECT` dialog from library `SYSTEM`. When you assign the handle value of this font control to the `FONT-HANDLE` attribute of another dialog element, the `STRING` of the other dialog element is displayed accordingly.

Example:

```
#TC-1.FONT-HANDLE := #FNT-1
/* The STRING of the text constant control /* #TC-1 will be displayed in the face,
/* style and size of #FNT-1.
```

Attributes for Font Control

Attribute Name	Query	Set/Modify	In Attr. Window
CLIENT-HANDLE	X	X/X	
CLIENT-KEY	X	X/X	
CLIENT-VALUE	X	X/X	
FIRST-CHILD	X	-/-	
LAST-CHILD	X	-/-	
PARENT	X	X/-	
PREDECESSOR	X	-/-	
STRING	X	X/-	X
SUCCESSOR	X	-/-	
TYPE	X	X/-	

Events

This dialog element does not create events.