

Push Button Control

This chapter covers the following topics:

- Description
 - Attributes for Push Button Control
 - Events
-

Description

A push button control is a representation of a button. The end user can click on it to trigger a certain action (specified in the click-event handler code). You can use a push button control's handle value in the DEFAULT-BUTTON attribute of a dialog; your push button control then serves as the dialog's default button.

Note:

Under Windows, a push button control's background and foreground colors will be displayed as the system default at runtime, regardless of the specified value.

Attributes for Push Button Control

Attribute Name	Query	Set/Modify	In Attr. Window
ACCELERATOR	X	X/X	X
BACKGROUND-COLOUR-NAME	X	X/X	X
BACKGROUND-COLOUR-VALUE	X	X/X	X
CLIENT-DATA	X	X/X	
CLIENT-HANDLE	X	X/X	
CLIENT-KEY	X	X/X	
CLIENT-VALUE	X	X/X	
CONTEXT-MENU	X	X/X	X
DIL-TEXT	X	X/X	X
ENABLED	X	X/X	X
FIRST-CHILD	X	-/-	
FOLLOWS	X	X/X	
FONT-HANDLE	X	X/X	X
FOREGROUND-COLOUR-NAME	X	X/X	X
FOREGROUND-COLOUR-VALUE	X	X/X	X
HELP-ID	X	X/X	X

Attribute Name	Query	Set/Modify	In Attr. Window
LAST-CHILD	X	-/-	
OWNER	X	X/-	
PARENT	X	X/-	
PREDECESSOR	X	-/-	
RECTANGLE-H	X	X/X	X
RECTANGLE-W	X	X/X	X
RECTANGLE-X	X	X/X	X
RECTANGLE-Y	X	X/X	X
STRING	X	X/X	X
STYLE	X	X/-	X
SUCCESSOR	X	-/-	
TOOLTIP	X	X/X	
TYPE	X	X/-	
VISIBLE	X	X/X	X

Events

Click Event.