

# List Box Control Attributes Window

## ▶ Accessible Using

1. Double-click on the list box control; or
  2. if selected: "Control > Attributes" or by selecting 'Attributes...' from the control's context menu or
  3. if selected: ENTER.
- 

## Entries

### Note:

For context-sensitive help on attribute entries, select the entry so it has the focus, and press F1.

Entry in Attributes Window	Represents
<b>Name</b>	Handle name of the list box control (may be overwritten with another name).
<b>Items</b>	Input field where you can specify the number of list box items in the list box control. When you enter a number here, the dialog editor generates the corresponding list box items and the "Source" dialog box becomes enabled.
...	Dialog box for determining sources of the list box items' STRING attribute values.
<b>Font</b>	Output field where the font currently selected is displayed.
...	Dialog box for selecting fonts.
<b>DIL text</b>	DIL-TEXT attribute value (string).
...	Dialog box for determining sources of DIL-TEXT attribute values.
<b>Accelerator</b>	ACCELERATOR attribute value.
...	Dialog box for determining sources of ACCELERATOR attribute values.
<b>Context Menu</b>	CONTEXT-MENU attribute value. Specifies the context menu (if any) associated with the control.
<b>Help ID</b>	HELP-ID attribute value. You must use the help topic's .h file to map the numerical ID that you enter here to the corresponding help topic ID (created by a markup in the .hlp file).
<b>Drag Mode</b>	DRAG-MODE attribute value. Indicates whether the control can act as the source in a drag-drop operation and, if so, which types of drag-drop operation it supports.
<b>Drop Mode</b>	DROP-MODE attribute value. Indicates whether the control can act as the target in a drag-drop operation and, if so, which types of drag-drop operation it supports.
<b>State:</b>	
<b>Visible</b>	VISIBLE attribute value.
<b>Enabled</b>	ENABLED attribute value.

<b>Entry in Attributes Window</b>	<b>Represents</b>
<b>Multiple selection</b>	MULTI-SELECTION attribute value. If you check this entry, the end user may select several list box items at a time.
<b>Sorted</b>	SORTED attribute value. If you check this entry, the items are sorted and you cannot modify them.
<b>Autoselect</b>	AUTOSELECT attribute value. If you check this entry, Natural automatically updates the selection in response to a right mouse button click before displaying a context menu.
<b>Style:</b>	
<b>3-D Border</b>	STYLE attribute value: list box has sunken appearance.
<b>Integral height</b>	STYLE attribute value: partial rows are not displayed.
<b>Insertion Mark</b>	STYLE attribute value: insertion mark will be displayed if the control is a target in a drag-drop operation and a drop is allowed.
<b>Rectangle:</b>	The following four attributes decide the list box control's x and y axis position, its height and its width on the screen.  <b>X</b> - RECTANGLE-X attribute value. <b>Y</b> - RECTANGLE-Y attribute value. <b>W</b> - RECTANGLE-W attribute value. <b>H</b> - RECTANGLE-H attribute value.
<b>Foreground color:</b>	
<b>Selection box</b>	FOREGROUND-COLOUR-NAME attribute value.
<b>...</b>	"Custom" dialog box for editing FOREGROUND-COLOUR-VALUE attribute value.
<b>Background color:</b>	
<b>Selection box</b>	BACKGROUND-COLOUR-NAME attribute value.
<b>...</b>	"Custom" dialog box for editing BACKGROUND-COLOUR-VALUE attribute value.
<b>OK</b>	Save settings and exit the window.
<b>Cancel</b>	Exit the window without saving the settings.
<b>Help</b>	Provides online help on the attributes window.