

INatAutoLinkedApplications

This chapter covers the following topics:

- Purpose
 - Properties
 - Methods
-

Purpose

Collection of applications that are linked to a compound application.

Properties

The following properties are available:

- Parent
- Studio
- Count

Parent

Used to navigate to the parent interface of this interface.

Natural Data Format	Variant Type	Remark
HANDLE OF OBJECT	VT_DISPATCH (INatAutoApplication)	Get only

Studio

Used to navigate to the root interface.

Natural Data Format	Variant Type	Remark
HANDLE OF OBJECT	VT_DISPATCH (INatAutoStudio)	Get only

Count

The number of applications in the collection.

Natural Data Format	Variant Type	Remark
I4	VT_I4	Get only

Methods

The following methods are available:

- Item
- Add
- Remove

Item

Returns a specific application from the collection.

Parameters

Name	Natural Data Format	Variant Type	Remark
Return value	HANDLE OF OBJECT	VT_DISPATCH (INatAutoApplication)	
Index	I4 A	VT_I4 VT_BSTR	

Return value

The application identified by the value specified in Index.

Index

Identifies a specific application in the collection. This can be either the index of the application in the collection (a value between 1 and Count) or the name of the application.

Add

Adds the given application to the collection (effectively links it to the parent application).

Parameters

Name	Natural Data Format	Variant Type	Remark
Return value	HANDLE OF OBJECT	VT_DISPATCH (INatAutoApplication)	
Application	A	VT_BSTR	

Return value

The newly linked application.

Application

Name of the application to be linked.

Remove

Removes the application from the collection (effectively unlinks it from the parent application).

Parameters

Name	Natural Data Format	Variant Type	Remark
Index	I4 A	VT_I4 VT_BSTR	

Index

Identifies a specific application in the collection. This can be either the index of the application in the collection (a value between 1 and Count) or the name of the application.