

# INatAutoObjectList

This chapter covers the following topics:

- Purpose
  - Properties
  - Methods
  - Notifications
- 

## Purpose

An open list view document window.

## Properties

The following properties are available:

- Parent
- Studio
- PlugInID

## Parent

Used to navigate to the parent interface of this interface.

Natural Data Format	Variant Type	Remark
HANDLE OF OBJECT	VT_DISPATCH (INatAutoObjectLists)	Get only

## Studio

Used to navigate to the root interface.

Natural Data Format	Variant Type	Remark
HANDLE OF OBJECT	VT_DISPATCH (INatAutoStudio)	Get only

## PlugInID

The ID of the plug-in that created the list view document window. A plug-in can use this property to iterate only across its own document windows.

Natural Data Format	Variant Type	Remark
A	VT_BSTR	Get only

## Methods

The following method is available:

- Close

### Close

Closes the list view document window. This method is executed asynchronously. In particular, this means that if it is called from within the method `OnCommand` of a plug-in, the window will only really be closed after the method `OnCommand` has terminated.

## Notifications

A plug-in that has created a list view document window can expect to receive the following notifications through its method `OnNotify`.

- `PLUGIN-NOTIFY-ACTIVATE`
- `PLUGIN-NOTIFY-CLOSE`
- `PLUGIN-NOTIFY-REFRESH`
- `PLUGIN-NOTIFY-HELP`