

INatAutoPlugIns

This chapter covers the following topics:

- Purpose
 - Properties
 - Methods
-

Purpose

Collection of the currently installed plug-ins.

Properties

The following properties are available:

- Parent
- Studio
- Count

Parent

Used to navigate to the parent interface of this interface.

Natural Data Format	Variant Type	Remark
HANDLE OF OBJECT	VT_DISPATCH (INatAutoStudio)	Get only

Studio

Used to navigate to the root interface.

Natural Data Format	Variant Type	Remark
HANDLE OF OBJECT	VT_DISPATCH (INatAutoStudio)	Get only

Count

The number of installed plug-ins.

Natural Data Format	Variant Type	Remark
I4	VT_I4	Get only

Methods

The following method is available:

- Item

Item

Returns a specific plug-in from the collection.

Parameters

Name	Natural Data Format	Variant Type	Remark
Return value	HANDLE OF OBJECT	VT_DISPATCH (INatAutoPlugIn)	
Index	I4 A	VT_I4 VT_BSTR	

Return value

The plug-in identified by the value specified in Index.

Index

Identifies a specific plug-in in the collection. This can be either the index of the plug-in in the collection (a value between 1 and Count) or the Plug-in ID (the value of the ID property of the corresponding INatAutoPlugIn object).