

Radio Button Group

Subprogram Name	Source Name	Executable Example	Viewable Example
H3-RADIO-GROUP	H3RBGROU	E3RBGROU	E3RBGROU

Description

Creates a radio button group. The group can be formatted inside a table.

Appearance

```
<INPUT TYPE=RADIO NAME=string>
```

Supported Attributes

```
VALUE=string, CHECKED
```

Parameters

```
1 H3ARRAYCOUNT (I4)          /* i /m : Number of group elements
1 H3NAME          (A) dynamic  /* i /m : Name of the group variable
1 H3ARRAYVALUE   (A/1:V) dynamic /* i /M : Default value of the default group
*                               /*      variable
1 H3ARRAYLABEL   (A/1:V)      /* i /mH: Label of the group element
1 H3ISCHECKED    (I4)         /* i /M : Number of default selected
*                               /*      button
1 H3LINEBREAK    (L)         /* i /M : Set line breaks between
*                               /*      buttons
1 H3ROW          (N4)         /* i /m : Set number of rows for tables
1 H3COLUMN       (N4)         /* i /m : Set number of columns for
*                               /*      tables
```

How To Invoke

```
PERFORM H3-RADIO-GROUP H3ARRAYCOUNT H3NAME
        H3ARRAYVALUE(*) H3ARRAYLABEL(*)
        H3ISCHECKED H3LINEBREAK H3ROW H3COLUMN
```