

# Read Resource

Subroutine Name	Executable Example	Viewable Example	Resources
W3READ-RESOURCE	E3RESOUR	E3RESOUR	E3SAVE.HTML

## Description

Read a resource file from the given library into a dynamic variable. If no library is specified, use the current library.

Use together with **W3APPLY-XSLT** for template processing.

## Parameters

```

1 W3LIBRARY      (A8) BY VALUE OPTIONAL /* i /o : Natural Library ID
1 W3FILE         (A) DYNAMIC BY VALUE  /* i /m : File Name
1 W3DYN          (A) DYNAMIC           /* o/m : Read Resource
1 W3RESPONSE    (I4) OPTIONAL          /* o/o : Response

```

If the W3RESPONSE parameter is not specified, the Web Interface error processing is triggered if an error occurs. If the W3RESPONSE parameter is specified, the parameter contains the Natural message number if an error occurred, or zero on success.

## How To Invoke

```
PERFORM W3READ-RESOURCE W3LIBRARY W3FILE W3DYN
```

```
PERFORM W3READ-RESOURCE W3LIBRARY W3FILE W3DYN W3RESPONSE
```

## Restriction

Load Resource is only available on Natural for Windows and UNIX supporting non-natural files/resources. Internally it uses workfile 12.