

Natural for UNIX

Natural Web I/O Interface

バージョン 8.4.1

2017 年 10 月

このマニュアルは Natural バージョン 8.4.1 およびそれ以降のすべてのリリースに適用されます。

このマニュアルに記載される仕様は変更される可能性があります。変更は以降のリリースノートまたは新しいマニュアルに記述されます。

Copyright © 1992-2017 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, United States of America, and/or their licensors.

The name Software AG, webMethods and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Software AG およびその子会社が所有する登録商標および特許の詳細については、<http://documentation.softwareag.com/legal/> を確認してください。

本ソフトウェアの一部にはサードパーティ製製品が含まれています。サードパーティの著作権表示およびライセンス規約については『License Texts, Copyright Notices and Disclaimers of Third-Party Products』を参照してください。このドキュメントは製品ドキュメントセットの一部であり、<http://documentation.softwareag.com/legal/> 上、またはライセンス製品のルートインストールディレクトリ内にあります。

本ソフトウェアの利用は、Software AG のライセンス規約に則って行われるものとします。ライセンス規約は製品ドキュメントセット内、<http://documentation.softwareag.com/legal/> 上、またはライセンス製品のルートインストールディレクトリ内にあります。

ドキュメント IDは: NATUX-NNATWEBIO-841-20200614

Table of Contents

Preface	vii
1 About this Documentation	1
表記規則	2
オンライン情報	2
データ保護	3
I Introduction	5
2 Introduction	7
What is the Natural Web I/O Interface?	8
Components of the Natural Web I/O Interface	8
Executing a Natural Application in a Web Browser	9
Client-Server Compatibility	10
Terminology	10
Differences in a SPoD Development Environment	11
Restrictions When Using the Natural Web I/O Interface with Natural Applications	11
Differences between the Natural Web I/O Interface Client and Terminal Emulation	13
II Installing and Configuring the Natural Web I/O Interface Server	15
3 Installing and Configuring the Natural Web I/O Interface Server	17
Installing the Natural Web I/O Interface Daemon	18
Setting Up the Natural Web I/O Interface Components	18
Directories	20
Configuring the Natural Web I/O Interface Daemon on UNIX	21
Logging Information	28
SSL Support	29
Working with the UNIX Components of the Natural Web I/O Interface	31
III Installing the Natural Web I/O Interface Client	35
4 Prerequisites	37
Servlet Container	38
Natural for Mainframes	38
Natural for UNIX	38
Natural for OpenVMS	39
Natural for Windows	39
Browser Prerequisites	39
5 Installing the Natural Web I/O Interface Client on Apache Tomcat	41
Installation Steps	42
Installation Verification	44
6 Migrating the Natural Web I/O Interface Client from IIS to Apache Tomcat	45
Before You Install the Natural Web I/O Interface Client	46
Installing the Natural Web I/O Interface Client on Apache Tomcat	47
Configuring the Natural Web I/O Interface Client on Apache Tomcat	47
IV Configuring the Client	51
7 About the Logon Page	53

Starting a Natural Application from the Logon Page	54
Examples of Logon Pages	54
Dynamically Changing the CICS Transaction Name when Starting a Session	55
Specifying a Password in the Logon Page	56
Changing the Password in the Logon Page	56
Browser Restrictions	57
8 Natural Client Session Configuration	59
General Information	60
Name and Location of the Configuration File	60
9 Natural Client Configuration Tool	61
Invoking the Configuration Tool	62
Session Configuration	63
Logging Configuration	71
Logon Page	71
Logout	72
10 Natural Web I/O Style Sheets	73
Name and Location of the Style Sheets	74
Editing the Style Sheets	74
Modifying the Position of the Main Output and of the PF Keys	74
Modifying the Font Size	76
Modifying the Font Type	77
Defining Underlined and Blinking Text	77
Defining Italic Text	78
Defining Bold Text	78
Defining Different Styles for Output Fields	79
Modifying the Natural Windows	79
Modifying the Message Line	80
Modifying the Background Color	80
Modifying the Color Attributes	81
Modifying the Style of the PF Key Buttons	82
XSLT Files	82
11 Starting a Natural Application with a URL	85
12 Configuring Container-Managed Security	87
General Information	88
Name and Location of the Configuration File	88
Activating Security	88
Defining Security Constraints	89
Defining Roles	89
Selecting the Authentication Method	90
Configuring the UserDatabaseRealm	90
13 Configuring SSL	91
General Information	92
Creating Your Own Trust File	92
Defining SSL Usage in the Configuration File	93

14 Logging 95

 General Information 96

 Name and Location of the Configuration File 96

 Invoking the Logging Configuration Page 96

 Overview of Options for the Output File 98

Preface

This documentation is organized under the following headings:

Introduction	What is the Natural Web I/O Interface?
Installing and Configuring the Natural Web I/O Interface Server	How to install and configure the Natural Web I/O Interface server in a UNIX environment.
Installing the Natural Web I/O Interface Client	How to install the Natural Web I/O Interface client on an application server or in a servlet container so that it can be used with the Natural Web I/O Interface server.
Configuring the Client	How to define the information that is to appear in the logon page.



Note: This documentation only explains how to install the Natural Web I/O Interface server in a UNIX environment. For information on how to install it in a mainframe, OpenVMS or Windows environment, see the Natural documentation for the appropriate platform.

1 About this Documentation

■ 表記規則	2
■ オンライン情報	2
■ データ保護	3

表記規則

規則	説明
太字	画面上の要素を表します。
モノスペースフォント	<code>folder.subfolder:service</code> という規則を使用して webMethods Integration Server 上のサービスの保存場所を表します。
大文字	キーボードのキーを表します。同時に押す必要があるキーは、プラス記号 (+) で結んで表記されます。
斜体	独自の状況または環境に固有の値を指定する必要がある変数を表します。本文で最初に出現する新しい用語を表します。
モノスペースフォント	入力する必要があるテキストまたはシステムから表示されるメッセージを表します。Program code.
{ }	選択肢のセットを表します。ここから1つ選択する必要があります。中カッコの内側にある情報のみを入力します。{} 記号は入力しません。
	構文行で相互排他的な2つの選択肢を区切ります。いずれかの選択肢を入力します。 記号は入力しません。
[]	1つ以上のオプションを表します。大カッコの内側にある情報のみを入力します。[] 記号は入力しません。
...	同じ種類の情報を複数回入力できることを示します。情報だけを入力してください。実際のコードに繰り返し記号 (...) を入力しないでください。

オンライン情報

Software AG マニュアルの Web サイト

マニュアルは、Software AG マニュアルの Web サイト (<http://documentation.softwareag.com>) で入手できます。このサイトでは Empower クレデンシャルが必要です。Empower クレデンシャルがない場合は、TECHcommunity Web サイトを使用する必要があります。

Software AG Empower 製品のサポート Web サイト

もしまだ Empower のアカウントをお持ちでないのなら、こちらへ empower@softwareag.com 電子メールにてあなたのお名前、会社名、会社の電子メールアドレスをお書きの上、アカウントを請求してください。

いったんアカウントをお持ちになれば、Empower <https://empower.softwareag.com/> の eService セクションにてサポートインシデントをオンラインで開くことができます。

製品情報は、Software AG Empower 製品のサポート Web サイト (<https://empower.software-ag.com>) で入手できます。

機能および拡張機能に関するリクエストの送信、製品の可用性に関する情報の取得、**製品**のダウンロードを実行するには、Products に移動します。

修正に関する情報を取得し、早期警告、技術論文、Knowledge Base の記事を読むには、**Knowledge Center** に移動します。

もしご質問があれば、こちらのhttps://empower.softwareag.com/public_directory.asp グローバルサポート連絡一覧の、あなたの国の電話番号を選んで、わたくし共へご連絡ください。

Software AG TECHcommunity

マニュアルおよびその他の技術情報は、Software AG TECHcommunity Web サイト (<http://techcommunity.softwareag.com>) で入手できます。以下の操作を実行できます。

- TECHcommunity クレデンシアルを持っている場合は、製品マニュアルにアクセスできます。TECHcommunity クレデンシアルがない場合は、登録し、関心事の領域として [マニュアル] を指定する必要があります。
- 記事、コードサンプル、デモ、チュートリアルにアクセスする。
- Software AG の専門家によって承認されたオンライン掲示板フォーラムを使用して、質問したり、ベストプラクティスを話し合ったり、他の顧客が Software AG のテクノロジーをどのように使用しているかを学んだりすることが可能です。
- オープンスタンダードや Web テクノロジーを取り扱う外部 Web サイトにリンクできます。

データ保護

Software AG製品は、EU一般データ保護規則(GDPR)を尊重した個人データの処理機能を提供します。該当する場合、適切な手順がそれぞれの管理ドキュメントに記載されています。

I Introduction

2 Introduction

■ What is the Natural Web I/O Interface?	8
■ Components of the Natural Web I/O Interface	8
■ Executing a Natural Application in a Web Browser	9
■ Client-Server Compatibility	10
■ Terminology	10
■ Differences in a SPoD Development Environment	11
■ Restrictions When Using the Natural Web I/O Interface with Natural Applications	11
■ Differences between the Natural Web I/O Interface Client and Terminal Emulation	13

This chapter describes the purpose and the functions of the Natural Web I/O Interface.



Note: This introduction mainly describes how the Natural Web I/O Interface works in a runtime (production) environment. The section [Differences in a SPoD Development Environment](#) briefly explains the special version that is used in a SPoD development environment.

What is the Natural Web I/O Interface?

The Natural Web I/O Interface is used to execute Natural applications in a web browser. It fully supports the following:

- The display and input of Unicode characters. See *Unicode Input/Output Handling in Natural Applications* in the *Unicode and Code Page Support* documentation.
- Rich internet applications developed with Natural for Ajax.

Components of the Natural Web I/O Interface

The Natural Web I/O Interface consists of a server and a client.

Server

The Natural Web I/O Interface server enables you to use a browser as the I/O device for Natural applications. The server does the user authentication, creates the Natural session and handles the I/O between Natural and the client. The Natural Web I/O Interface server is installed on the same machine as the Natural application.

Client

The client handles the communication between the user's web browser and the Natural Web I/O Interface server. It converts the output from the Natural application to web pages, and returns the user input to Natural.


Two types of client are supported:

- Natural Web I/O Interface client for displaying character-based applications in the web browser. Maps with GUI controls are not supported in this case.
- Natural for Ajax for displaying rich internet applications in the web browser. For further information on this type of client, see the Natural for Ajax documentation.

The client is installed on a web/application server. This can be done on any machine in the network.

Executing a Natural Application in a Web Browser

The Natural Web I/O Interface receives data from a Natural application and delivers web pages to the user's web browser. This is illustrated in the following graphic:



The communication steps for executing a Natural application in the web browser are:

1. The user enters the address (URL) of a logon page in the web browser. The client then displays the logon page in the web browser.



Note: For information on how to invoke and configure the logon page, see [Configuring the Client](#).

2. The user enters all required information for starting a Natural application into the logon page. This information is sent to the client.
3. The client asks the Natural Web I/O Interface server to start the requested Natural application for this user.
4. The Natural Web I/O Interface server checks the supplied user ID and password, creates a Natural session for the user and starts the Natural application.

5. The Natural application returns the first application screen which is then transferred via the Natural Web I/O Interface server to the client and finally as a web page to the web browser.

Different web browsers are supported. Note that cookies and JavaScript must be enabled in the web browser. For a list of the currently supported web browsers, see the browser prerequisites for the type of client that you are using.

Client-Server Compatibility

The following rules apply:

- The Natural Web I/O Interface server can work with any client that has the same or a higher protocol version.

If the server detects that the client is using a version that is lower than the server version, the server replies that the client is too old and the connection is closed.

- The client can work with any server that has the same or a lower protocol version.

If the client detects that the server is using a version that is lower than the client version, the client switches to the server version. However, new client functionality is not supported in this case.

- The Natural Web I/O Interface server must have the same protocol version as the Natural process that is started by the server. If Natural detects that the server is using a different protocol version, an error message is sent to the user and the connection is closed.

Terminology

On the different Natural platforms for which the Natural Web I/O Interface is supported, different techniques are used for implementing the server part of the Natural Web I/O Interface. On Natural for UNIX and Natural for OpenVMS, it is implemented as a daemon. On Natural for Windows, it is implemented as a service. On the mainframe, it is implemented as a server. In this documentation, the general term “server” is therefore used for all different kinds of implementation.

Differences in a SPoD Development Environment

The previous sections of this introduction have described how the Natural Web I/O Interface works in a runtime (production) environment. This section briefly explains the differences in a SPoD development environment.

A special version of the Natural Web I/O Interface is used when working in a remote development environment with Natural for Windows (SPoD). In this case, the Natural Web I/O Interface is an integrated component which does not require a separate installation. The server is part of the Natural Development Server (NDV), and the client is part of Natural Studio. Other than in the runtime environment, the screen is not displayed in a browser but in a normal window. Rich GUI pages created by Natural for Ajax are not supported in the development environment.

It is important that I/O via the Natural Web I/O Interface has been enabled on the Natural host. Otherwise, the Natural Web I/O Interface cannot be invoked. See also *Unicode Input/Output Handling in Natural Applications* in the *Unicode and Code Page Support* documentation.

Restrictions When Using the Natural Web I/O Interface with Natural Applications

There are several restrictions when using the Natural Web I/O Interface with Natural applications on UNIX, OpenVMS, mainframe or Windows hosts.



Note: The term “application” refers to application software. It does not refer to system software or software for development.

The following restrictions apply:

- **GUI controls**

GUI controls are not supported: dialogs, buttons, radio buttons, list boxes, list views, check boxes etc. The Natural Web I/O Interface only supports Natural applications developed without GUI controls.

- **File transfer**

File transfer (for example, with the `DOWNLOAD` statement) is not supported by the Natural Web I/O Interface.

- **Runtime errors**

This restriction applies to older Natural versions on UNIX and Windows. As of version 6.3.3, this restriction no longer applies.

Runtime errors in Natural applications are not handled by the Natural Web I/O Interface. This leads to a loss of the session. Bypass: use the Natural system variable *ERROR-TA to handle the error. Sample Natural error transaction:

```
DEFINE DATA
LOCAL
1 ERR_INFO
  2 ERR_NR(N5)
  2 ERR_LINE(N4)
  2 ERR_STAT(A1)
  2 ERR_PNAM(A8)
  2 ERR_LEVEL(N2)
END-DEFINE
INPUT ERR_INFO
DISPLAY ERR_INFO
TERMINATE
END
```

■ Terminal commands

Terminal commands are not supported. They do not work when entered in the Natural Web I/O Interface client.

■ Natural system variable *INIT-ID

When using the Natural Web I/O Interface client with Natural applications on UNIX, OpenVMS, mainframe or Windows hosts, the Natural system variable *INIT-ID will not be filled with a value for the terminal type. On UNIX, OpenVMS and Windows, it will contain the value "notty". On mainframes, it will contain a session ID that is unique on that server.

The following restrictions apply to Natural on UNIX, OpenVMS and Windows hosts (the mainframe does not have these restrictions):

■ Return to the Natural main screen

You must not use Natural applications that return to the Natural main screen as this leads to wrong screen display and a loss of the session.

■ Natural editors and utilities

You must not use Natural utilities such as SYSMAIN or SYSDDM and editors such as the program editor as this leads to wrong screen display and a loss of the session.

■ Natural system commands

You must not use any Natural system command such as CATALL, FIND, GLOBALS, HELP, KEY, LIST, RETURN, SCAN, SETUP or XREF as this leads to wrong screen display and a loss of the session.

Differences between the Natural Web I/O Interface Client and Terminal Emulation

The Natural Web I/O Interface client runs as an HTML terminal emulator inside a browser control. The look and feel of the Natural Web I/O Interface client display is quite similar to that of the regular terminal (emulation), but there are some differences due to browser functionality:

- A double-click with the mouse pointer on any field simulates the ENTER key.
- It is not possible to position the cursor outside the range of input and output fields.
- The cursor can be moved with the left and right arrow keys within one input field. It is also possible to jump from one input field to another using the left, right, up and down arrow keys.
- The insert mode can be switched on and off using the INSERT key.
- For Unicode character sets (type U; for example, Chinese), one character may require more space than an ordinary alphanumeric character, because the Unicode character representation is proportional. The application design must take this into account, because Natural is based on characters with fixed width. For input fields it is possible to scroll within the field, but for output fields there may not be sufficient space to display the Unicode characters. The display length for a field can be controlled by the session parameter DL.
- Type-ahead mode is not supported.
- Paste in overwrite mode is not supported.
- Key schemes are fixed; keys such as the right CTRL key and the ENTER key on the numeric pad are no longer definable.
- Screen update is slower since the complete screen is sent rather than updates.
- The blink attribute is not supported in Internet Explorer.
- The keys PF1 through PF12 are simulated by the key combinations F1 through F12.
- The keys PF13 through PF24 are simulated by the key combinations SHIFT+F1 through SHIFT+F12.
- The keys PF25 through PF36 are simulated by the key combinations CTRL+F1 through CTRL+F12.
- The keys PF37 through PF48 are simulated by the key combinations ALT+F1 through ALT+F12.
- The program attention keys (PA1, PA2 and PA3) are simulated by the key combinations CTRL+SHIFT+F1, CTRL+SHIFT+F2, CTRL+SHIFT+F3.
- The clear key is simulated by CTRL+SHIFT+F4.

IBM Mainframes Only

- The terminal screen size is controlled by the Natural profile parameter TMODEL. The default setting TMODEL=0 means 24 lines and 80 columns.
- There is no ATTN (attention interrupt) key, no RESET key and no EEOF (erase end of file) key.

VT Only

- The I/O occurs in block mode. Therefore, the Natural program will only react when a function key is pressed.

II Installing and Configuring the Natural Web I/O Interface Server

3 Installing and Configuring the Natural Web I/O Interface

Server

■ Installing the Natural Web I/O Interface Daemon	18
■ Setting Up the Natural Web I/O Interface Components	18
■ Directories	20
■ Configuring the Natural Web I/O Interface Daemon on UNIX	21
■ Logging Information	28
■ SSL Support	29
■ Working with the UNIX Components of the Natural Web I/O Interface	31

On UNIX, the server part of the Natural Web I/O Interface runs in the background as a so-called daemon.

Installing the Natural Web I/O Interface Daemon

The Natural Web I/O Interface daemon is installed with Natural for UNIX if the corresponding option is set during the installation. See the *Installation* documentation for further information.

Setting Up the Natural Web I/O Interface Components

Setting up the Natural Web I/O Interface on UNIX consists of the following steps:

- [Step 1: Stop the Natural Web I/O Interface Daemons](#)
- [Step 2: Establish the Environment](#)
- [Step 3: Install Natural and the Natural Web I/O Interface](#)
- [Step 4: Check the Environment Variables for the Natural Web I/O Interface](#)
- [Step 5: Read the READ_NWO Files](#)

Step 1: Stop the Natural Web I/O Interface Daemons

This step is only required for an upgrade installation. It is not required when you install the Natural Web I/O Interface for the first time.

1. Stop the *nwosrzd* process using the following command:

```
nwosrzd.sh portnumber stop
```

Or use the script `$NAT_HOME/INSTALL/nwosrzd.bsh` which will be generated during the Natural Web I/O Interface installation for a specified port.

```
nwosrzd.bsh stop
```

2. Repeat the above command (with an adapted port in script *nwosrzd.bsh*, if applicable) for each Natural Web I/O Interface service that is needed.

Step 2: Establish the Environment

- Besides the settings for the Natural environment, additional settings for the Natural Web I/O Interface environment must be set. Ensure that the environment settings for Natural are set by the *natenv* environment script. The *nwoenv* environment script is called by the *natenv* environment script. Therefore, the Natural Web I/O Interface environment will be set with the Natural environment if it is set after the Natural Web I/O Interface installation.

If the Natural Web I/O Interface environment is to be separate from the Natural environment, use the shell script *nwoenv* or *nwoenv.csh* by entering one of the following commands:

```
source nwoenv
```

```
source nwoenv.csh
```

These scripts can be found after the installation in *\$NAT_HOME/INSTALL*.

Step 3: Install Natural and the Natural Web I/O Interface

- The Natural Web I/O Interface can be selected in the **Choose Packages** screen during the Natural installation.

Optionally, you may install a runlevel script to start/stop a Natural Web I/O Interface daemon when the machine starts/stops.

After the Natural installation has finished, the Natural Web I/O Interface must be activated by starting Natural through a Natural Web I/O Interface client on Windows.

When a runlevel script is used, the Natural Web I/O Interface daemon can only be administered by the user "root".

When you install Natural with the Natural Web I/O Interface, the directory *\$NAT_HOME/nwo/\$NWONODE* is created. The template files located in *\$NAT_HOME/nwo/node-name* are then copied to this new directory.

Step 4: Check the Environment Variables for the Natural Web I/O Interface

- The Natural Web I/O Interface-specific settings are shown below:

Environment Variable	Description
NWODIR	The home directory for the product located at <i>\$NAT_HOME/nwo</i> .
NWONODE	The name of the node (machine) on which the Natural Web I/O Interface is installed.
NWO_SVRDCONF	The configuration file <i>\$NAT_HOME/nwo/\$NWONODE/nwosrvd.conf</i> for the Natural Web I/O Interface daemon.

Environment Variable	Description
NWO_TIMEOUT	The maximum time, in seconds, that the Natural Web I/O Interface daemon will wait for a response. "0" means no timeout. The Natural Web I/O Interface daemon will terminate when it receives the timeout.

Step 5: Read the READ_NWO Files

1. Access the directory `$NAT_HOME/nwo` and check the files `READ_NWO.TXT` and `READ_NWO.FIX` for any version-specific installation considerations concerning the particular platform.
2. Add the services as described in the file `READ_NWO.TXT`.

Directories

The following directories are created when Natural is installed together with the Natural Web I/O Interface on a UNIX system:

Directory	Description
<code>\$NAT_HOME</code>	Top-level Natural directory.
<code>\$NATDIR</code>	Only used for compatibility with previous versions. Top-level Natural directory.
<code>\$NATDIR/\$NATVERS</code>	Only used for compatibility with previous versions. The version subdirectory has been removed. Since <code>\$NATVERS</code> is set to ".", it equals <code>\$NAT_HOME</code> and <code>\$NATDIR</code> .
<code>\$NWODIR</code>	Directory with the Natural Web I/O Interface components for the current version.
<code>\$NWONODE</code>	Contains the name of the machine (<code>uname -n</code>).
<code>\$NAT_HOME/INSTALL</code>	Shell scripts and environment files for the Natural Web I/O Interface (<code>nwoenv</code> , <code>nwoenv.csh</code>).
<code>\$NWODIR/bin</code>	Natural Web I/O Interface executable files (<code>nwosrvd</code> , <code>nwosrvd.tr</code>).
<code>\$NWODIR/node-name</code>	Contains the template files (<code>nwosrvd.sh</code> , <code>nwo.sh</code> , <code>nwosrvd.conf</code>).
<code>\$NWODIR/nwoexuex/userexit1</code>	Contains the files for building the <code>libnwouserexit1</code> .
<code>\$NWODIR/nwoexuex/userexit2</code>	Contains the files for building the <code>libnwouserexit2</code> .
<code>\$NAT_HOME/nwo/\$NWONODE</code>	Work directory, contains the configuration files (<code>nwosrvd.sh</code> , <code>nwo.sh</code> , <code>nwosrvd.conf</code>).



Note: The above table lists the most important directories and files.

Configuring the Natural Web I/O Interface Daemon on UNIX

When the Natural installation has finished, the directory `$NAT_HOME/nwo/$NWONODE` contains the files `nwosrvd.conf`, `nwosrvd.sh` and `nwo.sh`.

The configuration of the Natural Web I/O Interface daemon can be done using the Natural Web I/O Interface daemon commands or by editing the configuration file `nwosrvd.conf`.

The following topics are covered below:

- [Natural Web I/O Interface Daemon Commands](#)
- [nwosrvd.conf - Configuration File for the Natural Web I/O Interface Daemon](#)
- [nwosrvd.sh - Shell Script for Starting and Stopping the Natural Web I/O Interface Daemon](#)
- [nwo.sh - Shell Script for Starting Natural](#)
- [Environment Variables](#)

Natural Web I/O Interface Daemon Commands

The following commands can be specified at the UNIX command prompt:

Command	Description
<code>nwosrvd -help</code>	Shows all available Natural Web I/O Interface daemon commands and subcommands.
<code>nwosrvd -v</code>	Shows the version of the Natural Web I/O Interface daemon.
<code>nwosrvd nnnn</code>	Defines the listening port number.
<code>nwosrvd -show</code>	Shows the configuration of the Natural Web I/O Interface daemon.
<code>nwosrvd -config keys</code>	<p>Changes the configuration of the Natural Web I/O Interface daemon. The following keys can be specified:</p> <ul style="list-style-type: none"> <code>-host=hostname</code> The host name used. <code>-userexit1=pathname</code> The message defined with this key is saved in the <code>UserExit1</code> key of the configuration file <code>nwosrvd.conf</code>, section <code>[UserExits]</code>. <code>-userexit2=pathname</code> The message defined with this key is saved in the <code>UserExit2</code> key of the configuration file <code>nwosrvd.conf</code>, section <code>[UserExits]</code>. <code>-passparam=parameters</code> The message defined with this key is saved in the <code>Parameters</code> key of the configuration file <code>nwosrvd.conf</code>, section <code>[PasswdArguments]</code>. <code>-passold=message</code> The message defined with this key is saved in the <code>EnterOldPassword</code> key of the configuration file <code>nwosrvd.conf</code>, section <code>[PasswdMessages]</code>.

Command	Description
	<p>-passnew=<i>message</i> The message defined with this key is saved in the NewPassword key of the configuration file <i>nwosrvd.conf</i>, section [PasswdMessages].</p> <p>-passreenter=<i>message</i> The message defined with this key is saved in the ReEnterNewPassword key of the configuration file <i>nwosrvd.conf</i>, section [PasswdMessages].</p> <p>-passsuccess=<i>message</i> The message defined with this key is saved in the PasswordSuccessful key of the configuration file <i>nwosrvd.conf</i>, section [PasswdMessages].</p> <p>-logging=<i>option</i> The option defined with this key is saved in the Logging key of the configuration file <i>nwosrvd.conf</i>, section [Miscellaneous].</p> <p>-ssl=[yes no] The option defined with this key is saved in the ssl key of the configuration file <i>nwosrvd.conf</i>, section [SSL].</p> <p>-pam=[yes no] The option defined with this key is saved in the pam key of the configuration file <i>nwosrvd.conf</i>, section [PAM]. PAM itself also has a configuration file or section (depends on the PAM implementation); the PAM configuration name must be <i>nwosrvd</i>.</p> <p>To remove any user exits from the configuration, enter the following command:</p> <pre>nwosrvd -config -userexit1=</pre> <p>Once the configuration was changed, the Natural Web I/O Interface daemon must be restarted.</p>

nwosrvd.conf - Configuration File for the Natural Web I/O Interface Daemon

The configuration file *nwosrvd.conf* contains information that the user exits need for the Natural Web I/O Interface daemon. It has the following content:

```
[Miscellaneous]
Logging=I

[UserExits]
; UserExit1=/FS/sag/nat/nwoexuex/userexit1/libnwouserexit1.so
; UserExit2=/FS/sag/nat/nwoexuex/userexit2/libnwouserexit2.so

[PasswdArguments]
Parameters=

[PasswdMessages]
EnterOldPassword=Enter existing login password:
NewPassword=New Password:
```

```
ReEnterNewPassword=Re-enter new Password:
PasswordSuccessful=passwd: password successfully changed for*
```

```
[SSL]
ssl=no
```

```
[PAM]
pam=no
```

```
[Host]
host=pctest
```

Section in Configuration File	Description
[Miscellaneous]	<p>The key <code>Logging</code> is used to define the amount of logging information that is to be reported. One of the following options can be specified:</p> <p>E for errors. W for warnings. I for information.</p> <p>See also Logging Information.</p>
[Host]	The hostname used. (optional)
[UserExits]	<p>Two user exits can be defined:</p> <p><code>UserExit1</code></p> <p>The library that is defined by <code>UserExit1</code> contains the following function:</p> <pre>int nwo_CheckUsernameAndPassword(const char *pUsername, const char *pPassword, const char *pNewPassword, char *pErrorMessage)</pre> <p>If the key <code>UserExit1</code> is defined in the configuration file, the function <code>nwo_CheckUsernameAndPassword</code> is responsible for checking the user name and password. If a new password is received, user exit 1 is also responsible for changing the password.</p> <p>In the case of an error, the return code of the function must be "0"; in this case, the <code>pErrorMessage</code> is returned to the client.</p> <p>When user name and password are correct, the return code must be a value other than "0". "1" indicates that the Natural session runs under the user who started the daemon (authentication). "2" indicates that the Natural session runs under the login user (authentication and impersonation).</p> <p><code>UserExit2</code></p> <p>The library that is defined by <code>UserExit2</code> contains the following functions:</p> <pre>int nwo_Messages(int *iNumberOfMessages, char *pMessage[])</pre>

Section in Configuration File	Description
	<p><code>iNumberOfMessages</code>: Number of messages returned in the array.</p> <p><code>pMessage</code>: Array of messages.</p> <p>If the key <code>UserExit2</code> is defined in the configuration file, the function <code>nwo_Messages</code> is called when a new connection (client) is accepted and the messages returned by this function are sent to the client. User exit 2 may be used, for example, to send a message such as the following: "For maintenance reasons, the Natural application XXXXX will be down next monday, from 18:00 until 19:00".</p> <p>In the case of an error, the return code of the function must be "0".</p> <p>After the function <code>nwo_Messages</code> has been called, the function <code>nwo_FreeMessages</code> is called.</p> <pre>■ int nwo_FreeMessages(int iNumberOfMessages, char *pMessage[])</pre> <p><code>iNumberOfMessages</code>: Number of messages.</p> <p><code>pMessage</code>: Array of messages.</p> <p>If the key <code>UserExit2</code> is defined, the function <code>nwo_FreeMessages</code> is called to free any resources (normally memory) allocated in the function <code>nwo_Messages</code>.</p> <p>In the case of an error, the return code of the function must be "0".</p>
[PasswdArguments]	The key <code>Parameters</code> is used to define any additional parameter(s) that have to be passed to the <code>passwd</code> command.
[PasswdMessages]	<p>The keys in this section define the messages that are to be returned by the system (<code>passwd</code> command) when a user changes the password. If any of these messages is not identified by the daemon, an error will be returned to the client.</p> <p>Password Mechanism</p> <p>The password and new password are encrypted on the client side and decrypted on the UNIX side. A maximum of 8 characters is allowed.</p> <p>If user exit 1 is active, user name, password and new password are passed to the user exit.</p> <p>If user exit 1 is not active, the daemon checks whether user name and password are correct for the system. If a new password is sent, the daemon changes the password by calling the UNIX command <code>passwd</code>.</p>
[SSL]	<p>The key <code>ssl</code> is used to define whether the SSL protocol is to be used. One of the following values can be specified: "yes" or "no".</p> <p>See also SSL Support.</p>
[PAM]	The key <code>pam</code> is used to define whether the PAM (Pluggable Authentication Modules) mechanism is to be used. One of the following values can be specified: "yes" or "no".

Section in Configuration File	Description
	<p>PAM itself also has a configuration file or section (depends on the PAM implementation); the PAM configuration name must be <code>nwosrzd</code>.</p> <p>Note: On Red Hat Enterprise Linux, only PAM authentication is possible.</p>

nwosrzd.sh - Shell Script for Starting and Stopping the Natural Web I/O Interface Daemon

The shell script `nwosrzd.sh` is used to start and stop the Natural Web I/O Interface daemon. For further information, see [Starting and Stopping the Natural Web I/O Interface Daemon](#).

nwo.sh - Shell Script for Starting Natural

In order to start a Natural session, the Natural Web I/O Interface service executes a shell script. The shell script prepares the environment for the Natural session and eventually starts Natural. It must therefore contain all environment settings needed to run the Natural session.

The shell script receives certain parameters from the Natural Web I/O Interface client. The parameters can either be evaluated by the shell script itself or passed on to Natural. A client who wants to start a Natural session can specify the shell script to be used.

The shell script `nwo.sh` is called from the Natural Web I/O Interface daemon in order to start a Natural session. It has the following content:

```
#!/bin/sh

echo "Number of arguments $# " > nwo.log

IPAddress=""
ClientId=""
CodePage=""
CustomParameters=""
NaturalParameters=""

if [ "$1" != "null" ]
then
    IPAddress="$1"
fi

if [ "$2" != "null" ]
then
    ClientId="$2"
fi

if [ "$3" != "null" ]
then
    CodePage="$3"
```

```
fi

if [ "$4" != "null" ]
then
    CustomParameters="$4"
fi

if [ "$5" != "null" ]
then
    NaturalParameters="$5"
fi

#echo "IP Address=$IPAddress >> nwo.log
#echo "Client Id=$ClientId >> nwo.log
#echo "Code Page=$CodePage >> nwo.log
#echo "Custom Parameters=$CustomParameters >> nwo.log
#echo "Natural Parameters=$NaturalParameters >> nwo.log
#echo "NWO_BROWSER_IO=$NWO_BROWSER_IO >> nwo.log

$NAT_HOME/bin/natural $NaturalParameters etid=$$ > /dev/null 2>&1
```

You have to create such a shell script for each Natural application. It can have any name and it must be located in a directory which is defined in the environment variable `PATH`.

The name of the shell script is taken from the configuration file for the session. It is taken from the configuration file section that is defined for the session that the user has selected in the logon page. For further information, see [Configuring the Client](#).

Arguments

The shell script will receive the following arguments:

Order	Argument	Description
1	IPAddress	The client IP address from where the session is opened. Note: If there is a proxy, this will not be the IP address of the client workstation. Instead, it will be the IP address of the proxy.
2	ClientId	The user name from the logon page is passed as the client ID.
3	CodePage	The encoding that is defined in the configuration file for the session. This value can be used to set the Natural system variable <code>*CODEPAGE</code> .
4	CustomParameters	From the logon page, it is possible to pass any values to the script in order to execute any desired action. Example: you pass a small text to the script which describes an error. When the script receives this error text, it sends it as an e-mail to the administrator.
5	NaturalParameters	These can be any Natural parameters. The parameters are either defined in the configuration file for the session, or they are entered in the logon page.

Order	Argument	Description
		<p>The following is an example of the corresponding entry in the configuration file:</p> <pre><natural_parameter>parm=nwoparm\ stack=(logon\ mylib;start-program;fin)<natural_parameter></pre> <p>The language that is selected in the logon page is added as the first element to the Natural parameters in the form "ulang=x".</p>

Arguments 1 to 4 can be used to audit the client, to allow to run an application from a specific PC (identifying the IP address), to build statistics, to do special actions, etc.

Environment Variables

In the shell script, several environment variables can be set for the Natural session that is started by the daemon:

NWO_ENABLE_ACK=["YES"|"NO"]

This environment variable is used for asynchronous screens (SET CONTROL N).

YES When asynchronous screens are sent to the client, Natural will wait to receive an ACK package before the next screen can be sent.

NO No waiting between asynchronous screens. Default value.

NWO_PF_MSG_LINES_NATIVE_FORMAT=["YES"|"NO"]

This environment variable defines how the PF keys and the message line are to be shown.

YES The PF key prompting lines and the message line are shown as output text, as in the native UNIX environment.

NO The PF keys are rendered as buttons and the message line is rendered as a special message line element. Default value.

NWO_TIMEOUT=[*number-of-seconds*]

The maximum time, in seconds, that Natural waits to receive any input from the client before it closes the session. If the number of seconds is "0", Natural waits infinitely (no timeout). The default value is "0".

Error NAT5466 is returned at timeout. In Natural, the application can handle this error and decide how to continue or terminate.

Logging Information

The logging information system reports errors, warnings and/or session information, depending on the option that has been defined with the following **Natural Web I/O Interface daemon command**:

```
nwosrzd -config -logging=option
```

option can be one of the following:

Option	Description
E	Error. When this option is specified, the Natural Web I/O Interface daemon reports only errors. In the case of an error, the daemon usually exits immediately.
W	Warning. When this option is specified, the Natural Web I/O Interface daemon reports errors and warnings for uncritical errors. In the case of a warning, the daemon continues to run.
I	Information. When this option is specified, the Natural Web I/O Interface daemon reports errors, warnings and information. The information messages allow to check the session parameters, IP address, etc.

Help information, for example, on how to run, configure and install the Natural Web I/O Interface daemon is always provided. The messages which inform you when the daemon has been started or stopped are also part of the help information.

To find out which logging option is currently active, enter the following Natural Web I/O Interface daemon command:

```
nwosrzd -show
```

The logging messages are shown directly for the standard output. The format of the messages is as in the following example:

```
%NWOSRVD-E: 18.01.2008 14:55:20 NWO_SRVDCONF is not established.
```

The following information is provided:

- %NWOSRVD is the internal name of the Natural Web I/O Interface daemon.
- The message type is shown directly after %NWOSRVD. It can be one of the following: -E (error), -W (warning), -I (information), or -H (help).
- Date and time when the message was reported.
- Any text or message which pertains to the error, warning, information or help.

If you want to save these messages, you have to redirect the standard output to a file.

Example for csh:

```
nwosrwd 5454 >& nwosrwd_5454.log
```

Example for sh, ksh and bsh:

```
nwosrwd 5454 >& nwosrwd_5454.log 2>&1
```

SSL Support

SSL is used for a secure connection between the Natural Web I/O Interface server and the Natural Web I/O Interface client or Natural for Ajax. Server authentication cannot be switched off. A certificate and a private key is always required on the server.

To establish an SSL connection, you have to proceed as described in the following topics:

- [Creating an SSL Certificate and a Private Key](#)
- [Configuring the Daemon](#)
- [Configuring the Client](#)

Creating an SSL Certificate and a Private Key

To create and use an SSL certificate and a private key on the server, proceed as described below.

1. Adapt the example configuration file *openssl.cnf* to your needs.



Note: *openssl.cnf* and *openssl* are delivered in *<install-dir>/bin*.

2. Set the environment variable so that it points to the file *openssl.cnf*:

```
set OPENSSL_CONF=<install-dir>\bin\openssl.cnf
export OPENSSL_CONF;
```

3. Generate a certificate signing request:

```
openssl req -new > server.cert.csr
```

4. Generate a private RSA key:

```
openssl rsa -in privkey.pem -out server.cert.key
```

5. Generate a self-signed certificate:

```
openssl x509 -in server.cert.csr -out server.cert.crt -req -signkey ↵  
server.cert.key -days 365
```

It is important that the name of the generated certificate is *server.cert.crt* and that the name of the generated private key is *server.cert.key*.



Note: The certificate can be self-signed or it can be signed by a CA (Certificate Authority) such as VeriSign.

6. Put the generated files into the same directory as the scripts which start the Natural Web I/O Interface server.

Configuring the Daemon

After you have created an SSL certificate and a private key as described above, proceed as follows:

1. Change the configuration of the Natural Web I/O Interface daemon using the following command:

```
nwosrzd -config -ssl yes
```

2. Restart the Natural Web I/O Interface daemon.

See also [Configuring the Natural Web I/O Interface Daemon on UNIX](#).

Configuring the Client

After you have configured the daemon as described above, you have to import the generated *server.cert.crt* file to a truststore on the client. For information on how to do this for the Natural Web I/O Interface client, see [Configuring SSL](#). If you are using Natural for Ajax as the client, see [Configuring SSL](#) in the Natural for Ajax documentation.

Working with the UNIX Components of the Natural Web I/O Interface

The UNIX components of the Natural Web I/O Interface are used to start the Natural applications linked with the Natural Web I/O Interface library.

The following topics are covered below:

- [Starting and Stopping the Natural Web I/O Interface Daemon](#)
- [Starting a Natural Application](#)

Starting and Stopping the Natural Web I/O Interface Daemon

The Natural Web I/O Interface daemons are responsible for accepting new sessions.

Since the daemon checks the user name and password, the following permissions must be set as follows (for setting the permissions, you must be super-user):

```
chmod 6755 nwsrwd.sh
```

```
chown root nwsrwd.sh
```

The Natural installation attempts to set permissions and owner. However, you have to verify this before you start the Natural Web I/O Interface daemon.

The daemon can be started and stopped using the following command:

```
cd $NAT_HOME/nwo/$NWO_NODE  
nwsrwd.sh portnumber [start|stop]
```

Alternatively:

```
cd $NAT_HOME/INSTALL  
nwsrwd.bsh [start|stop]
```



Note: The daemon must be started on a port which is not yet used.

The shell script you have created must be in the same directory as the *nwsrwd.sh* script. It will be used by the Natural Web I/O Interface (configuration file for the session; see [Configuring the Client](#)). The following is an example of the corresponding entry in the configuration file:

```
<natural_program>your-shell-script.sh</natural_program>
```

Starting a Natural Application

Almost any Natural application can be used with the Natural Web I/O Interface. See also [Differences between the Natural Web I/O Interface Client and Terminal Emulation](#).

To start a new Natural application with the Natural Web I/O Interface, proceed as follows:

1. Create a new parameter file from NWOPARM using the Configuration Utility.
2. In this new parameter file, modify the STACK command as follows:

```
logon library; startprogram; fin
```



Note: Only “real” Natural applications can be used. The Natural **Main Menu** cannot be used as a Natural application.

Add the new service as follows:

1. Look for a port number which is not yet used.
2. Create a new shell script (similar to *nwo.sh*) for starting the Natural application:

```
cd $NAT_HOME/nwo/$NWONODE
copy nwo.sh your-shell-script.sh
vi your-shell-script.sh
```

You have to decide which (last) line you will use in the script. Use one of the following:

```
$NAT_HOME/bin/natural parm=parameter-file etid=$$ >output-file 2>&1
```

```
$NAT_HOME/bin/natural $5 etid=$$ >output-file 2>&1
```

When using the line with *parm=parameter-file*, the above step in which you modify the STACK command is mandatory.

When using *\$5*, the Natural parameter (*parameter-file* and STACK command) is taken from the configuration file for the session (see [Configuring the Client](#)). The following is an example of the corresponding entry in the configuration file:

```
<natural_parameter>parm=mysparm stack=(logon mylib;menu;fin)<natural_parameter>
```

3. If you want to define special settings for the Natural session, you can set the environment variables in your shell script. See [above](#).
4. Set the permissions for the shell script which starts the service as follows:

```
chmod 775 script-name
```


The service is now available for use with a PC.

III

Installing the Natural Web I/O Interface Client

This part explains how to install the Natural Web I/O Interface client on Tomcat so that it can be used with the server part of the Natural Web I/O Interface that is running in a Natural for Mainframes, Natural for UNIX, Natural for OpenVMS or Natural for Windows runtime environment.

The following topics are covered:

[Prerequisites](#)

[Installing the Natural Web I/O Interface Client on Apache Tomcat](#)

[Migrating the Natural Web I/O Interface Client from IIS to Apache Tomcat](#)

4

Prerequisites

■ Servlet Container	38
■ Natural for Mainframes	38
■ Natural for UNIX	38
■ Natural for OpenVMS	39
■ Natural for Windows	39
■ Browser Prerequisites	39

Servlet Container

The following servlet container is supported. The servlet container is not delivered with the Natural Web I/O Interface. It can be obtained from the location indicated below, according to its license terms.

- **Apache Tomcat 7 and 8**

See <http://tomcat.apache.org/>.

Natural for Mainframes

If you want to use the Natural Web I/O Interface client with Natural for Mainframes, the following must be installed:

- Natural for Mainframes Version 8.2.5 or above, and
- the Natural Web I/O Interface server.

For detailed information, see:

- the *Installation* documentation for the different operating systems which is provided for Natural for Mainframes;
- the section *Installing and Configuring the Natural Web I/O Interface Server* in the version of this *Natural Web I/O Interface* documentation which is provided for Natural for Mainframes.

Natural for UNIX

If you want to use the Natural Web I/O Interface client with Natural for UNIX, the following must be installed:

- Natural for UNIX Version 8.3 or above, and
- the Natural Web I/O Interface server (which is implemented as a daemon).

For detailed information, see:

- the *Installation* documentation which is provided for Natural for UNIX;
- the section *Installing and Configuring the Natural Web I/O Interface Server* in the version of this *Natural Web I/O Interface* documentation which is provided for Natural for UNIX.

Natural for OpenVMS

If you want to use the Natural Web I/O Interface client with Natural for OpenVMS, the following must be installed:

- Natural for OpenVMS Version 6.3.4 or above, and
- the Natural Web I/O Interface server (which is implemented as a daemon).

For detailed information, see:

- the *Installation* documentation which is provided for Natural for OpenVMS;
- the section *Installing and Configuring the Natural Web I/O Interface Server* in the version of this *Natural Web I/O Interface* documentation which is provided for Natural for OpenVMS.

Natural for Windows

If you want to use the Natural Web I/O Interface client with Natural for Windows, the following must be installed:

- Natural for Windows Version 8.3 or above, and
- the Natural Web I/O Interface server (which is implemented as a service).

For detailed information, see:

- the *Installation* documentation which is provided for Natural for Windows;
- the section *Installing and Configuring the Natural Web I/O Interface Server* in the version of this *Natural Web I/O Interface* documentation which is provided for Natural for Windows.

Browser Prerequisites

Supported browsers in this version are:

Internet Explorer 11 ⁽¹⁾

Microsoft Edge

Mozilla Firefox Extended Support Release 38 and 45 ⁽²⁾

Google Chrome ⁽³⁾

Notes:

⁽¹⁾ The Natural Web I/O Interface client Version 1.3.15 is the last version that supports Internet Explorer 8.

⁽²⁾ Only the Extended Support Releases of Mozilla Firefox are explicitly supported. Due to frequent upgrades of the Mozilla Firefox consumer release, the compatibility of the Natural Web I/O Interface client with future versions of Mozilla Firefox cannot be fully guaranteed. Possible incompatibilities will be removed during the regular maintenance process of the Natural Web I/O Interface client.

⁽³⁾ The Google Chrome support is based on Google Chrome Version 31. Due to frequent version upgrades of Google Chrome, compatibility of the Natural Web I/O Interface client with future versions of Google Chrome cannot be fully guaranteed. Possible incompatibilities will be removed during the regular maintenance process of the Natural Web I/O Interface client.



Important: Cookies and JavaScript must be enabled in the browser.

5 Installing the Natural Web I/O Interface Client on Apache

Tomcat

■ Installation Steps	42
■ Installation Verification	44

If you want to use the Natural Web I/O Interface client with Apache Tomcat, you must proceed as described in this chapter.

Installation Steps

The Natural Web I/O Interface client is installed using the Tomcat Manager.

The following is assumed:

- `<install-dir>` is the path to Software AG's main installation directory. By default, this is `C:\SoftwareAG` on Windows and `/opt/softwareag` on UNIX.
- `<host>` is the name of the machine on which Apache Tomcat is installed.
- `<port>` is the name of the port where Apache Tomcat is installed. In a default installation, this is port 8080.
- `<tomcat>` is the path to the directory in which Apache Tomcat is installed.

The following topics are covered below:

- [First-time Installation](#)
- [Update Installation](#)

First-time Installation

➤ To install the Natural Web I/O Interface client

- 1 Natural for Windows and UNIX: Copy the complete contents of the `<install-dir>/natural/INSTALL/nwoclient/j2ee/v<nnnn>/tomcat` directory to a directory of your choice on your hard disk.

Or:

Download the Natural Web I/O Interface client for Apache Tomcat from Empower (<https://empower.softwareag.com/>) and unzip the contents to a directory of your choice on your hard disk.

- 2 On UNIX platforms: Dearchive the TAR file using the following command:

```
tar -xvf nwonnnn.tar
```

- 3 Make sure that Apache Tomcat is running.
- 4 Open your web browser and enter the following URL:

```
http://<host>:<port>/manager/html
```

This opens the Tomcat Manager.

- 5 Deploy the web application file *natuniweb.war*:
 - Under **Select WAR file to upload** select the path to the file *natuniweb.war*.
 - Choose **Deploy**.
- 6 In the Tomcat Manager, look for the application **Natural Web I/O Interface Client** and choose **Reload**.

Update Installation

➤ To update the Natural Web I/O Interface client

- 1 Natural for Windows and UNIX: Copy the complete contents of the `<install-dir>/natural/INSTALL/nwoclient/j2ee/v<nnnn>/tomcat` directory to a directory of your choice on your hard disk.

Or:

Download the Natural Web I/O Interface client for Apache Tomcat from Empower (<https://empower.softwareag.com/>) and unzip the contents to a directory of your choice on your hard disk.

- 2 On UNIX platforms: Dearchive the TAR file using the following command:

```
tar -xvf nwonnnn.tar
```

- 3 Shut down Apache Tomcat.
- 4 Create a backup copy of your *sessions.xml* file, which is located in `<tomcat>/webapps/natuniweb/WEB-INF`.
- 5 Start Apache Tomcat.
- 6 Open your web browser and enter the following URL:

```
http://<host>:<port>/manager/html
```

This opens the Tomcat Manager.

- 7 Select *natuniweb.war* in the list of installed applications.
- 8 Choose **Undeploy**.
- 9 Deploy the new version of the Natural Web I/O Interface client as in a first-time installation.
- 10 Restore the *sessions.xml* file that you have backed up previously.

Installation Verification

It is assumed that `http://<host>:<port>` is the URL of your application server.

➤ To verify the installation

- Enter the following URL in your web browser:

```
http://<host>:<port>/natuniweb/natural.jsp
```

For example:

```
http://myhost:8080/natuniweb/natural.jsp
```

The Natural Web I/O Interface client is now started in your browser. The entries which appear in the resulting logon page depend on the settings in your configuration file. For further information, see [Configuring the Client](#).

6

Migrating the Natural Web I/O Interface Client from IIS to Apache Tomcat

■ Before You Install the Natural Web I/O Interface Client	46
■ Installing the Natural Web I/O Interface Client on Apache Tomcat	47
■ Configuring the Natural Web I/O Interface Client on Apache Tomcat	47

Microsoft Internet Information Services (IIS) is no longer supported. If you are currently using the Natural Web I/O Interface client on IIS, you have to move to Apache Tomcat.



Note: JBoss Application Server and Oracle GlassFish Server are also no longer supported. If you are currently using one of these application servers, you also have to move to Apache Tomcat. In this case, however, you can reuse your previous settings (that is, the URL for logon page and the configuration file *sessions.xml*).

The most simple solution is to migrate the Natural Web I/O Interface client from IIS to Apache Tomcat. Therefore, this chapter gives IIS administrators a quick introduction to a Tomcat installation and describes the migration steps.

Before You Install the Natural Web I/O Interface Client

If Apache Tomcat is not yet installed, proceed as described in the topics below:

- [Installing Tomcat](#)
- [Installing Java](#)
- [Starting the Tomcat Server](#)

Installing Tomcat

Go to <http://tomcat.apache.org/download-60.cgi> and download Tomcat 6 as a zip file.

For Microsoft Windows users: download either the 32-bit or the 64-bit Windows zip file.

Unzip the downloaded zip file to a directory of your choice.

Installing Java

Tomcat is based on Java. Therefore, you have to make sure that a Java Runtime Environment (JRE) or a Java Development Kit (JDK) is installed. The version of the Java runtime should be at least Java 6 update 24. This is the minimum version that is required for the Natural Web I/O Interface client on Tomcat.

You can download the Java JRE or JDK from the Oracle website at <http://www.oracle.com/technetwork/java/javase/downloads/index.html>.

If Java is installed on your system, make sure that the environment variable `JAVA_HOME` is set to the Java home directory.

Starting the Tomcat Server

When Tomcat and the appropriate Java version have been installed, you can start Tomcat.

To start Tomcat, execute the *startup.bat* file from the *bin* directory of your Tomcat installation. To check whether Tomcat is running, enter the following URL:

```
http://localhost:8080
```

This should display Tomcat's default home page.

Installing the Natural Web I/O Interface Client on Apache Tomcat

When Apache Tomcat has been installed, install the Natural Web I/O Interface client as described in [Installing the Natural Web I/O Interface Client on Apache Tomcat](#).

Configuring the Natural Web I/O Interface Client on Apache Tomcat

When the Natural Web I/O Interface client has been installed, proceed as described in the topics below:

- [Invoking the Logon Page](#)
- [Changing the Tomcat HTTP Port](#)
- [Using the Settings from Your IIS Configuration File](#)
- [Using the Configuration Tool](#)
- [Protecting the Configuration Tool Against Unauthorized Access](#)
- [Displaying the Logon Page by Default](#)

Invoking the Logon Page

Enter the following URL to invoke the logon page (this is different from the URL that was used with IIS):

```
http://localhost:8080/natuniweb/natural.jsp
```

Changing the Tomcat HTTP Port

IIS usually runs on the default port 80. If you want Tomcat to work with the same port, edit the file *server.xml* which is located in Tomcat's *conf* subdirectory and then search for the following text:

```
<Connector port="8080" protocol="HTTP/1.1"
```

Change the port number so that it looks as follows:

```
<Connector port="80" protocol="HTTP/1.1"
```

Using the Settings from Your IIS Configuration File

With Tomcat, you can reuse the *settings.xml* configuration file of IIS, but you have to rename the file to *sessions.xml*. Proceed as follows:

1. Copy the *settings.xml* file from your IIS installation to the following directory of your Tomcat installation:
webapps/natuniweb/WEB-INF
2. Either rename the *sessions.xml* file which comes with the Natural Web I/O Interface client installation on Tomcat (for example, to *sessions-original.xml*) or delete it.
3. Rename the *settings.xml* file to *sessions.xml*.

Using the Configuration Tool

When the Natural Web I/O Interface client runs on Tomcat, it is no longer necessary to edit the configuration file manually. Instead, you can use the configuration tool. Using this tool has the advantage that it is not possible for you to create invalid XML code and thus damage the XML file. See [Using the Configuration Tool](#) for further information.

The IIS-specific entries in the renamed configuration file will be ignored. These are:

```
natural_parameter visible  
theme  
screen top  
screen left  
screen size  
screen pfkeypos
```

You can still edit the configuration file manually. However, this is no longer recommended.

Protecting the Configuration Tool Against Unauthorized Access

It is possible to protect the configuration tool against unauthorized access. See [Configuring Container-Managed Security](#) for detailed information.

For detailed information on the necessary realm configuration for Tomcat, see <http://tomcat.apache.org/tomcat-6.0-doc/realm-howto.html>.

Displaying the Logon Page by Default

When you enter the URL `http://localhost:8080/natuniweb`, Tomcat shows the default page of the Natural Web I/O Interface client which allows you to access either the **logon page** or the **configuration tool** of the Natural Web I/O Interface client.



Note: If you have defined a different port (for example, 80), make sure to use that port number in the URL.

This behavior is different from IIS which displays the logon page by default. If you also want Tomcat to display the logon page by default, edit the file `web.xml` which is located in Tomcat's `webapps\natuniweb\WEB-INF` directory and search for the following entry:

```
<welcome-file-list>
  <welcome-file>
    index.html
  </welcome-file>
</welcome-file-list>
```

Change the name of the welcome file to `natural.jsp` as shown in the following example:

```
<welcome-file-list>
  <welcome-file>
    natural.jsp
  </welcome-file>
</welcome-file-list>
```


IV

Configuring the Client

This part explains how to configure the Natural Web I/O Interface client so that it can be used in a Natural runtime environment. The following topics are covered:

[About the Logon Page](#)

[Natural Client Session Configuration](#)

[Natural Client Configuration Tool](#)

[Natural Web I/O Style Sheets](#)

[Starting a Natural Application with a URL](#)

[Configuring Container-Managed Security](#)

[Configuring SSL](#)

[Logging](#)

7

About the Logon Page

■ Starting a Natural Application from the Logon Page	54
■ Examples of Logon Pages	54
■ Dynamically Changing the CICS Transaction Name when Starting a Session	55
■ Specifying a Password in the Logon Page	56
■ Changing the Password in the Logon Page	56
■ Browser Restrictions	57

Starting a Natural Application from the Logon Page

When you start the Natural Web I/O Interface client in the browser, a logon page appears. The entries in this logon page depend on the settings in your configuration file (see [Natural Client Session Configuration](#)).

In order to start a Natural application from the logon page, you enter the following URL inside your browser:


```
http://<host>:<port>/natuniweb/natural.jsp
```

where *<host>* and *<port>* are the host name and port number of your application server.

Examples of Logon Pages

For each session definition that has been configured in the configuration file, an entry appears on the logon page. If the user selects the corresponding entry, only those parameters that were not preconfigured in the configuration file need to be specified in the logon page in order to start the application. Usually, you will preconfigure all connection parameters except user name and password.

The following example shows part of a logon page which results from a configuration file in which no special entries are defined for a session:



Enter connection details:

Session ID:	<input type="text" value="Connect to Natural"/>	<input type="button" value="Connect"/>	<input type="button" value="Change password"/>
Host name:	<input type="text"/>		
Port number:	<input type="text"/>		
User name:	<input type="text"/>		
Password:	<input type="password"/>		
Application:	<input type="text"/>		
Natural parameters:	<input type="text"/>		

The following example shows part of a logon page which results from a configuration file in which many settings are already predefined (including user ID and password):

Enter connection details:

Session ID: Demo Application (localhost:2900) Connect

To log on to a session, you have to specify all required information in the logon page (for example, you select a session from the corresponding drop-down list box). When you choose the **Connect** button, the screen for the selected session appears.

Dynamically Changing the CICS Transaction Name when Starting a Session

The following description applies if you want to switch to a different CICS transaction on a mainframe.

You specify the CICS transaction name in the same text box in which you also specify the dynamic parameters for the Natural environment. So that the CICS transaction name can be evaluated, it is important that you specify it before any Natural parameters, using the following syntax:

```
<TA_NAME=name>
```

where *name* can be 1 to 4 characters long. This must be the name of an existing CICS transaction which applies to a CICS Adapter. It will override the transaction name which is currently defined in the configuration file for the CICS Adapter on the Natural Web I/O Interface server (NWO). Ask your administrator for further information.

Make sure to put the entire definition in angle brackets. When this definition is followed by a Natural parameter, insert a blank before the Natural parameter. Example:

```
<TA_NAME=NA82> STACK=(LOGON SYSCP)
```

If the specified CICS transaction name cannot be found, an error message occurs and the session cannot be started.



Note: The above definition for the CICS transaction name can also be specified in the [configuration tool](#), in the same place where you also specify the Natural parameters, and together with the [URL parameter](#) natparam.

Specifying a Password in the Logon Page

The following information applies when the field for entering a password appears on the logon page. This field does not appear when a password has already been defined in the configuration file.

Under Windows, UNIX and OpenVMS, you always have to enter the operating system password, even if Natural Security is active.

On the mainframe, this is different: When Natural Security is not active, you have to enter the operating system password. When Natural Security is active, you have to enter the Natural Security password.

Changing the Password in the Logon Page

Currently, this functionality is only available for Natural for UNIX, Natural for OpenVMS and Natural for Windows.

The following information applies when the fields for entering a user ID and a password appear on the logon page. These fields do not appear when user ID and password have already been defined in the configuration file; in this case, it is not possible to change the password in the logon page.

When your password has expired, you are automatically asked for a new password. When you try to log on with your current password, an error message appears and input fields for changing the password are shown.

➤ To change the password

- 1 Choose the **Change password** button in the logon page.

The name of this button changes to **Don't change password** and the following two input fields are shown in the logon page:

- **New password**
- **Repeat new password**

- 2 Enter your user ID and your current password as usual.
- 3 Enter the new password in the two input fields.
- 4 Choose the **Connect** button to change the password.

Or:

If you do not want to change your password, choose the **Don't change password** button. The two input fields will then disappear.

Browser Restrictions

The browser's "Back" and "Forward" buttons do not work with the Natural Web I/O Interface client and should therefore not be used.

If you want to run two Natural sessions in parallel, you have to start a new instance of the browser (for example, by choosing the corresponding icon in the Quick Launch toolbar of Windows). You must not use the browser's "New Window" function. This would result in one session running in two browsers, which is not allowed.

8

Natural Client Session Configuration

■ General Information	60
■ Name and Location of the Configuration File	60

General Information

The configuration file is an XML file which is required to define the sessions that can be invoked from the logon page.

To edit the configuration file, you use the configuration tool. Using this tool has the advantage that it is not possible for you to create invalid XML code and thus damage the XML file. See [Natural Client Configuration Tool](#) for further information.

Name and Location of the Configuration File

The name of the configuration file is *sessions.xml*. It can be found in the *WEB-INF* directory.

`<tomcat-install-dir>/webapps/natuniweb/WEB-INF`

9

Natural Client Configuration Tool

■ Invoking the Configuration Tool	62
■ Session Configuration	63
■ Logging Configuration	71
■ Logon Page	71
■ Logout	72

Invoking the Configuration Tool

The Natural Web I/O Interface client offers a configuration tool. The configuration tool is used to create the session configurations which are then available in the logon page. It can also be used for logging purposes in case of problems; however, this should only be done when requested by Software AG support.

The configuration tool is automatically installed when you install the Natural Web I/O Interface client.

➤ To invoke the configuration tool

- Enter the following URL in your browser:


```
http://<host>:<port>/natuniweb/conf_index.jsp
```

where *<host>* and *<port>* are the host name and port number of your application server.



Note: You might wish to protect the configuration tool against unauthorized access. See [Configuring Container-Managed Security](#) for information on how to restrict the access to sensitive areas of the application server environment. If you have restricted access to the configuration tool, an authentication dialog appears. The appearance of this dialog depends on the authentication model you have chosen.

The configuration tool appears.



The configuration tool has two frames.

The home page of the configuration tool is initially shown in the right frame. It provides brief descriptions for the links provided in the left frame. It also provides links to several Software AG pages on the web.

When you have invoked a function (for example, when you are currently viewing the session configuration), you can always choose the **Home** link in the left frame to return to the home page of the configuration tool.

The functions that are invoked by the other links in the left frame are described below.

Session Configuration

This section explains how to manage the content of the configuration file for the sessions. It covers the following topics:

- [Invoking the Session Configuration Page](#)
- [Global Settings](#)
- [Adding a New Session](#)
- [Editing a Session](#)
- [Overview of Session Options](#)
- [Duplicating a Session](#)
- [Deleting a Session](#)
- [Adding a New User](#)
- [Saving the Configuration](#)

Invoking the Session Configuration Page

The content of the configuration file for the sessions is managed using the **Session Configuration** page.

➤ To invoke the Session Configuration page

- In the frame on the left, choose the **Session Configuration** link.

The **Session Configuration** page appears in the right frame. It shows the global settings and lists all sessions and users that are currently defined. For a session, some of the configuration file information is shown. Example:

Session Configuration

Save Configuration

Global Settings

Last activity timeout (n seconds):

Trace directory:

SSL trust file path:

SSL trust file password:

Sessions

Session ID	Host Name	Port Number	Application	Natural Parameters	Edit	Duplicate	Delete
Connect to Natural					Edit	Duplicate	Delete
localtestserver	localhost	6640			Edit	Duplicate	Delete

Add New Session

Users

User ID	Edit	Duplicate	Delete
user1	Edit	Duplicate	Delete

Add New User

Global Settings

The global settings apply for all defined sessions. You can define the following global settings in the configuration file:

Option	Description
Last activity timeout (n seconds)	The number of seconds that the client waits for the next user activity. When the defined number of seconds has been reached without user activity, the session is closed. The default is 3600 seconds.
Trace directory	<p>Optional. Location of a different trace directory.</p> <p>When a different trace directory is not defined, the trace files are written to the default trace directory. By default, the trace files are written to the directory which has been set by the Java property <code>java.io.tmpdir</code>. On Windows, this is normally the environment variable <code>TMP</code> for the user who started the application server. On UNIX, this is normally <code>/tmp</code> or <code>/var/tmp</code>.</p> <p>You can also set this property in the start script for the application server.</p>

Option	Description
	Tracing can be enabled individually for each session (see Overview of Session Options below). However, it should only be enabled when requested by Software AG support.
SSL trust file path	Optional. The path to your trust file. See Configuring SSL for further information.
SSL trust file password	<p>If your trust file is password-protected, you have to specify the appropriate password.</p> <p>When you do not specify the password for a password-protected trust file, the trust file cannot be opened and it is thus not possible to open an SSL session.</p> <p>When your trust file is not password-protected, you should not specify a password.</p>

Adding a New Session

You can add a new session to the configuration file.

➤ To add a new session

- 1 Choose the **Add New Session** button.

The **Edit Session** page appears.

- 2 Specify all required information as described below in the section [Overview of Session Options](#).
- 3 Choose the **OK** button to return to the **Session Configuration** page.

The new session is not yet available in the configuration file.

- 4 Choose the **Save Configuration** button to write the new session to the configuration file.

Editing a Session

You can edit any existing session in the configuration file.

➤ To edit a session

- 1 Choose the **Edit** link that is shown next to the session that you want to edit.

The **Edit Session** page appears.

- 2 Specify all required information as described below in the section [Overview of Session Options](#).
- 3 Choose the **OK** button to return to the **Session Configuration** page.

The modifications are not yet available in the configuration file.

- 4 Choose the **Save Configuration** button to write the modifications to the configuration file.

Overview of Session Options

The **Edit Session** page appears when you

- **add** a new session, or
- **edit** an existing session.

Example:

Edit Session

Session ID:	<input type="text"/>
Type:	Undefined ▼
Host name:	<input type="text"/>
Port number:	<input type="text"/>
Use SSL	<input type="radio"/> Yes <input checked="" type="radio"/> No
User name:	<input type="text"/>
User name in upper case:	<input type="radio"/> Yes <input checked="" type="radio"/> No
Password:	<input type="password"/>
Application:	<input type="text"/>
Natural parameters:	<input type="text"/>
Double-click behavior:	Enter ▼
Screen rows:	<input type="text" value="24"/>
Screen columns:	<input type="text" value="80"/>
Show function key numbers:	<input type="radio"/> Yes <input checked="" type="radio"/> No
Check for numeric input:	<input checked="" type="radio"/> Yes <input type="radio"/> No
Trace:	<input type="radio"/> Yes <input checked="" type="radio"/> No
Timeout (in seconds):	<input type="text" value="60"/>
Filler character:	<input type="text"/>
<div><input type="button" value="OK"/> <input type="button" value="Cancel"/></div>	

The **Edit Session** page provides the following options:

Option	Description
Session ID	Mandatory. A session name of your choice. On the logon page, the session name is provided in a drop-down list box.
Type	<p>The platform on which user ID and password are authenticated. You can select the required setting from the drop-down list box.</p> <ul style="list-style-type: none"> ■ Undefined Default. User ID and password can have a maximum of 32 characters. See also the description for Natural for Windows, UNIX or OpenVMS below. ■ Natural for Mainframes User ID and password can have a maximum of 8 characters. ■ Natural for Mainframes with Natural Security User ID and password can have a maximum of 8 characters. The user ID must comply with the Natural naming conventions for library names. ■ Natural for Windows, UNIX or OpenVMS User ID and password can have a maximum of 32 characters. When a domain is required, you have to specify it together with the user ID (in the form <i>"domain\user-ID"</i>).
Host name	The name or TCP/IP address of the server on which Natural and the Natural Web I/O Interface server are running. When this is specified, the corresponding field does not appear on the logon page.
Port number	The TCP/IP port number on which the Natural Web I/O Interface server is listening. When this is specified, the corresponding field does not appear on the logon page.
Use SSL	<p>If set to Yes, a secure connection is established between the Natural Web I/O Interface client on the application server and the Natural Web I/O Interface server.</p> <p>Important: If you want to use SSL with Natural for Mainframes, one of the corresponding mainframe types must be selected; the type must not be Undefined or Natural for Windows, UNIX or OpenVMS. The other way around, if you want to use SSL with Natural for Windows, UNIX or OpenVMS, you must not select one of the mainframe types; the type may also be Undefined in this case.</p>
User name	Optional. A valid user ID for the current machine. When this is specified, the corresponding field does not appear on the logon page.
User name in upper case	If selected, the input field for the user ID is in upper-case mode.
Password	<p>Optional. A valid password for the above user ID.</p> <p>Under Windows, UNIX and OpenVMS, this is always the operating system password of the user, even if Natural Security is active.</p> <p>On the mainframe, this is different: When Natural Security is not active, this is the operating system password of the user. When Natural Security is active, this is the Natural Security password.</p>

Option	Description
	When a password is specified, the corresponding field does not appear on the logon page. The configuration tool saves the password in encrypted form.
Application	<p>■ Natural for Mainframes The name of the Natural program or a command sequence that starts your application as you would enter it on the NEXT prompt. Example:</p> <pre>TEST01 data1,data2</pre> <p>■ Natural for UNIX The name of the UNIX shell script for starting the Natural application (a file similar to <i>nwo.sh</i>).</p> <p>■ Natural for OpenVMS The name of the Natural image file (for example, <i>natural<version></i> or <i>natural<version>.exe</i>).</p> <p>■ Natural for Windows The name of the Windows command file (<i>.bat</i>) for starting the Natural application.</p> <p>When this is specified, the corresponding field does not appear on the logon page.</p>
Natural parameters	<p>Optional. Parameters for starting the Natural application. This can be stack parameters, a parameter file/module or other Natural-specific information.</p> <p>■ Natural for Mainframes Used to pass dynamic Natural profile parameters to the session, for example:</p> <pre>SYSPARM=(MYPARMS) STACK=(LOGON MYAPPL)</pre> <p>Note: It is recommended to specify the Natural program that starts the application with the option Application instead of passing it with the profile parameter <i>STACK</i>.</p> <p>■ Natural for UNIX and Natural for Windows Used when the above shell script (UNIX) or command file (Windows) uses the parameter \$5 after "natural", for example:</p> <pre>PARM=MYPARM STACK=(LOGON MYLIB;MENU)</pre> <p>■ Natural for OpenVMS Used for starting a Natural application, for example:</p> <pre>BP=BPnode-name NLDCHK WEBIO=ON "STACK=(LOGON SYSEXT;MENU)"</pre>
Double-click behavior	<p>The key that is to be simulated when double-clicking an output field. By default, this is the ENTER key.</p> <p>It is possible to disable the double-click behavior, or to define a function key (PF1 through PF12).</p> <p>You can select the required setting from the drop-down list box.</p>

Option	Description
	Tip: When context-sensitive help has been defined for the output fields, it may be useful to define PF1. The help function will then be invoked when the user double-clicks an output field.
Screen rows	The number of rows in the output window. Possible values: minimum 24, no upper limit. Default: 24. Not used by Natural for Mainframes which uses the profile parameter <code>TMODEL</code> instead.
Screen columns	The number of columns in the output window. Possible values: minimum 80, no upper limit. Default: 80. Not used by Natural for Mainframes which uses the profile parameter <code>TMODEL</code> instead.
Show function key numbers	If set to Yes , the PF key numbers are shown next to the PF keys.
Trace	Should only be set to Yes when requested by Software AG support.
Check for numeric input	If set to Yes (default), numeric input fields are validated. In this case, only the following characters are allowed in numeric input fields (in addition to the numbers "0" through "9"): <i>blank</i> + (plus) - (minus) _ (underscore) , (comma) . (period) ? (question mark) If set to No , numeric input fields are not validated.
Timeout (in seconds)	The number of seconds that the client waits for a response after an updated page was sent to the Natural session. When the defined number of seconds has been reached without response, the session is closed. The default is 60 seconds. Normally, you need not change this value.
Filler character	Optional. The filler character that is to be removed from the input fields. An application can define, for example, an underscore (<code>_</code>) as the filler character. Trailing filler characters will be removed from the input fields, and leading filler characters will be replaced with blanks.

Duplicating a Session

You can add a copy of any existing session to the configuration file.

➤ To duplicate a session

- 1 Choose the **Duplicate** link that is shown next to the session that you want to duplicate.

A new entry is shown at the bottom of the list of sessions. Its name is "Copy of *session-ID*". The duplicated session is not yet available in the configuration file.
- 2 **Edit** and save the duplicated session as described above.

Deleting a Session

You can delete any existing session from the configuration file.

➤ To delete a session

- 1 Choose the **Delete** link that is shown next to the session that you want to delete.

The session is deleted from the list of sessions. It is not yet deleted in the configuration file.
- 2 Choose the **Save Configuration** button to delete the session from the configuration file.

Adding a New User

You can predefine Natural users and their passwords in the configuration file.

When a Natural page is opened with a URL that specifies a user in the URL parameter `natuser`, the specified user is matched against the list of users in the configuration file. When the specified user is defined in the configuration file, the corresponding password is used to authenticate the user when the Natural session is started. See also [Starting a Natural Application with a URL](#).

Example - when the following URL is used, the password defined for "user1" is used:

<http://myhost:8080/natuniweb/natural.jsp?natuser=user1...>

➤ To add a new user

- 1 Choose the **Add New User** button.

The **Edit User** page appears.
- 2 Specify a user name and password
- 3 Choose the **OK** button to return to the **Session Configuration** page.

The new user is not yet available in the configuration file.

- 4 Choose the **Save Configuration** button to write the new user to the configuration file.



Note: You edit, duplicate and delete a user in the same way as a session (see the corresponding descriptions above).

Saving the Configuration

When you choose the **Save Configuration** button, all of your changes are written to the configuration file. The server picks up the new settings automatically the next time it reads data from the configuration file.



Caution: If you do not choose the **Save Configuration** button but log out instead or leave the configuration tool by entering another URL, the new settings are not written to the configuration file.

Logging Configuration

The content of the configuration file for logging is managed using the **Logging Configuration** page. See the section [Logging](#) for detailed information.

Logon Page

The configuration tool provides the following link in the left frame:

■ Natural Web I/O Interface Logon

This link opens the logon page in the right frame.

The logon page uses the current settings in the configuration file. When you select a session from the drop-down list box, you can check whether the connection details are shown as desired. If not, you can go back to the session configuration and modify the settings of the corresponding session.

See also [About the Logon Page](#).

Logout

When the configuration tool is protected against unauthorized access and you log out of the configuration tool, you make sure that no other user can change the client configuration when you leave your PC unattended for a while.

> To log out

- In the frame on the left, choose the **Logout** link.

When the configuration tool is protected against unauthorized access, the authentication dialog is shown again.

When it is not protected, the home page is shown again.

10

Natural Web I/O Style Sheets

■ Name and Location of the Style Sheets	74
■ Editing the Style Sheets	74
■ Modifying the Position of the Main Output and of the PF Keys	74
■ Modifying the Font Size	76
■ Modifying the Font Type	77
■ Defining Underlined and Blinking Text	77
■ Defining Italic Text	78
■ Defining Bold Text	78
■ Defining Different Styles for Output Fields	79
■ Modifying the Natural Windows	79
■ Modifying the Message Line	80
■ Modifying the Background Color	80
■ Modifying the Color Attributes	81
■ Modifying the Style of the PF Key Buttons	82
■ XSLT Files	82

Name and Location of the Style Sheets

Several aspects on a page (such as font, font style or color) are controlled by a style sheet (CSS file).

The Natural Web I/O Interface client is delivered with the style sheet `3270.css`, which is located in:

`../natuniapp.ear/natuniweb.war/resources`



Note: For more information on style sheets, see <http://www.w3.org/Style/CSS/>.

Editing the Style Sheets

It is recommended that you have a basic understanding of CSS files.

You can edit the predefined style sheets or create your own style sheets.

It is recommended that you work with backup copies. When a problem occurs with your style sheet, you can thus always revert to the original state.

To see your changes in the browser, you have to

1. delete the browser's cache, and
2. restart the session.

Modifying the Position of the Main Output and of the PF Keys

Applies when only the named PF keys are displayed. This feature cannot be used when all PF keys are displayed, since they are always displayed at the same position. See also [Overview of Session Options](#).

The following elements are available:

Element Name	Description
<code>.mainlayer</code>	Controls the position of the main output in the output window. Used for languages that are written from left-to-right (LTR).
<code>.mainlayer_rtl</code>	Controls the position of the main output in the output window. Used for languages that are written from right-to-left (RTL).
<code>.pfkeydiv</code>	Controls the position of the PF keys in the output window. Used for languages that are written from left-to-right (LTR).

Element Name	Description
.pfkeydiv_rtl	Controls the position of the PF keys in the output window. Used for languages that are written from right-to-left (RTL).

The *_rtl elements are only used if Natural sends the web I/O screen with a right-to-left flag (SET CONTROL 'VON'). In the browser, the screen elements are then shown on the right side (instead of the left side).

For web I/O in applications where only the left-to-right orientation is used, the *_rtl elements are not required.

If the PF keys are to appear at the bottom, define the elements as shown in the following example:

```
/* Defines the main screen position */
.mainlayer {
    top: 5px;
    left: 0px;
    height: 550px;
}

/* Defines the main screen position for right-to-left */
.mainlayer_rtl{
    top: 5px;
    right: 30px;
    height: 550px;
}

/* Defines the PF keys screen position */
.pfkeydiv {
    height: 70px;
    left: 0px;
    top: 580px;
    width: 100%;
}

/* Defines the PF keys screen position for right-to-left */
.pfkeydiv_rtl {
    height: 70px;
    right: 30px;
    top: 580px;
    width: 100%;
}
```

Modifying the Font Size

Depending on the screen resolution, one of the following style sheets for defining the font size is used in addition to the default style sheet:

- *model2.css*
- *model3.css*
- *model4.css*
- *model5.css*

These style sheets are located in the *tmodels* subdirectory of the *resources* directory in which all style sheets are located.

Depending on what comes closest to the standard 3270 screen model, the corresponding style sheet from the *tmodels* subdirectory is automatically used. It is selected according to the following criteria:

Standard 3270 Screen Model	Criteria	Style Sheet
Model 2 (80x24)	30 rows or less.	<i>model2.css</i>
Model 3 (80x32)	Between 31 and 40 rows.	<i>model3.css</i>
Model 4 (80x43)	41 rows or more.	<i>model4.css</i>
Model 5 (132x27)	30 rows or less, and more than 100 columns.	<i>model5.css</i>

The font sizes in the above style sheets can be adjusted. Example for *model4.css*:

```
body {  
    font-size: 10px;  
}
```

The default font sizes for the above 3270 screen models are:

Standard 3270 Screen Model	Default Font Size
Model 2	16px
Model 3	14px
Model 4	10px
Model 5	12px

Modifying the Font Type

As a rule, you should only use monospace fonts such as Courier New or Lucida Console. With these fonts, all characters have the same width. Otherwise, when using variable-width fonts, the output will appear deformed.

If you want to define a different font type, you should define the same font type for the body, the output fields and the input fields as shown in the following example:

```
body {
  background-color: #F3F5F0;
  font-family: Lucida Console;
}

.OutputField {
  white-space:pre;
  border-width:0;
  font-family: Lucida Console;
  font-size: 100%;
}

.InputField {
  background-color: white;
  font-family: Lucida Console;
  border-width: 1px;
  font-size: 100%;
  border-color: #A7A9AB;
}
```

Defining Underlined and Blinking Text

The following elements are available:

Element Name	Description
.natTextDecoUnderline	Defines underlined text.
.natTextDecoBlinking	Defines blinking text.
.natTextDecoNormal	Defines normal text (no underline, no blinking).

Example:

```
/* Text decoration */
.natTextDecoUnderline { text-decoration:underline; }
.natTextDecoBlinking {text-decoration:blink; }
.natTextDecoNormal {text-decoration:normal;}
```

Blinking text is not supported by the Internet Explorer.

Defining Italic Text

The following elements are available:

Element Name	Description
.natFontStyleItalic	Defines italic text.
.natFontStyleNormal	Defines normal text (no italics).

Example:

```
/* font style */
.natFontStyleItalic {font-style:italic;}
.natFontStyleNormal {font-style:normal;}
```

Defining Bold Text

The following elements are available:

Element Name	Description
.natFontWeightBold	Defines bold text.
.natFontWeightNormal	Defines normal text (not bold).

```
/* Font weight */
.natFontWeightBold {font-weight:bolder;}
.natFontWeightNormal {font-weight:normal;}
```

When you define bold text (`{font-weight:bolder;}`) for the default font Courier New, your text always has the same width as with normal text (`{font-weight:normal;}`).

However, when you define bold text for Courier or Lucida Console, the bold text will be wider than the normal text and your output may thus appear deformed. It is therefore recommended that you switch off bold text for Courier and Lucida Console:

```
.natFontWeightBold {font-weight:normal;}
```

Defining Different Styles for Output Fields

The following elements are available:

Element Name	Description
.FieldVariableBased	Defines the style for output fields that are based on a variable.
.FieldLiteralBased	Defines the style for output fields that are based on a literal.

Example:

```
.FieldVariableBased {
    /* font-style:italic; */
}

.FieldLiteralBased {
    /* font-style:normal; */
}
```



Note: In the above example, as well as in the standard CSS files delivered by Software AG, the variable-based output fields are defined as italic, but are commented out.

Modifying the Natural Windows

The following elements are available:

Element Name	Description
.naturalwindow	Controls the rendering of the Natural windows.
.wintitle	Controls the rendering of the titles of the Natural windows.

Example:

```
.naturalwindow {
    border-style: solid;
    border-width: 1px;
    border-color: white;
    background-color: black;
}

.wintitle {
    left: 0px;
```

```
top: 1px;
height: 17px;
width: 100%;
color: black;
font-size: 100%;
font-weight: bold;
background-color: white;
text-align: center;
font-family: Verdana;
border-bottom-style: solid;
border-bottom-width: 2px;
}
```



Note: In a mainframe environment, you have to set the Natural profile parameter `WEBIO` accordingly to enable this feature. See *WEBIO - Web I/O Interface Screen Rendering* in the *Parameter Reference* which is provided with Natural for Mainframes.

Modifying the Message Line

The rendering of the message line is controlled by the `.MessageLine` element.

Example:

```
.MessageLine {
  color: blue;
}
```



Note: In a mainframe environment, you have to set the Natural profile parameter `WEBIO` accordingly to enable this feature. See *WEBIO - Web I/O Interface Screen Rendering* in the *Parameter Reference* which is provided with Natural for Mainframes.

Modifying the Background Color

The background color is defined in the `body` element.

Example:


```
body {  
  background-color: #F3F5F0;  
  font-family: Lucida Console;  
}
```

Modifying the Color Attributes

You can define different colors for all Natural color attributes. These are:

Red
Green
Blue
Yellow
White
Black
Pink
Turquoise
Transparent

You can define these color attributes for input fields and output fields, and for normal output and reverse video.

The following examples show how to define the color attribute “Red”.

Define the color for a normal output field:

```
.natOutputRed {color: darkred;}
```

Define the foreground and background colors for an output field with reverse video:

```
.reverseOutputRed {background-color: darkred; color:#F3F5F0;}
```

Define the color for a normal input field:

```
.natInputRed {color: darkred;}
```

Define the foreground and background colors for an input field with reverse video:

```
.reverseInputRed {background-color: darkred; color:#F3F5F0;}
```

Modifying the Style of the PF Key Buttons

The following elements are available:

Element Name	Description
.PFButton	Controls the style for normal rendering.
.PFButton:hover	Controls the style that is used when the mouse hovers over a PF key button.

Example:

```
.PFButton {
  text-align: center;
  width: 90px;
  border-style: ridge;
  border-width: 3px;
  padding: 2px;
  text-decoration: none;
  font-family: Verdana;
  font-size: 12px;
  height: 22px;
}

.PFButton:hover {
  color: #FFFFF0;
  background-color: #222222;
}
```



Note: In a mainframe environment, you have to set the Natural profile parameter `WEBIO` accordingly to enable this feature. See *WEBIO - Web I/O Interface Screen Rendering* in the *Parameter Reference* which is provided with Natural for Mainframes.

XSLT Files

In addition to the CSS files described above, the Natural Web I/O Interface client uses XSLT files with specific names for the conversion of the Natural Web I/O Interface screens from the internal XML format to HTML. The following elements are affected:

- Input text is placed into the HTML element `<input>`.
- Output text is placed into the HTML element `<input>` (with attribute `readonly="readonly"`).
- A message line is placed into the HTML element ``.

- PF keys are embedded in an XML island and then rendered with JavaScript.
- Window elements are embedded in an XML island and then rendered with JavaScript.



Note: The JavaScript file which is part of the above conversion is *natunicscript.js*. It is located in the *scripts* directory which can be found in the `<install_dir>/natuniweb` directory.

The name of the default XSLT file is:

- *transuni.xsl* for all supported browsers.

The default XSLT file can be found in the following directory:

`<install_dir>/natuniweb/web-INF`

The XSLT file is only read once when the server is started.



Important: It is recommended that you do not change the above XSLT file. Software AG may change or correct the original XSLT transformations in new versions or service packs of the product.

You can copy your own XSLT file into the above directory. In this case, the file must have the following name:

- *usertransuni.xsl* for all supported browsers.

If this user file can be found when the server is started, it is read instead of the default XSLT file.

When you make changes to this file, you have to restart the server so that your changes become effective.

11

Starting a Natural Application with a URL

The connection parameters available in the configuration file for the session and on the logon page can also be specified as URL parameters of the logon page URL. This allows bookmarking the startup URL of a Natural application or starting an application by clicking a hyperlink in a document.

The URL parameters overrule the definitions in the configuration file, with the exception described in the table below.

The following URL parameters are available for the logon page:

URL Parameter	Corresponding Option in the Session Configuration
natsession	Session ID
natserver	Host name
natport	Port number
natuser	User name
natprog	Application
natparam	Natural parameters
natparamext	Natural parameters The URL parameter <code>natparamext</code> extends an existing Natural parameter definition in the configuration file. The extension works in the following way: the Natural parameters defined in the configuration file come first. Then, the Natural parameters defined in the URL parameter <code>natparamext</code> are added, separated by a space character. If you want to overrule the definition in the configuration file, use the URL parameter <code>natparam</code> instead.
nattimeout	Timeout (n seconds)



Important: All parameter values must be URL-encoded.

Example: In order to start the Natural program `dump`, while your application server is running on *myhost:8080* and your Natural Web I/O Interface server is running on *myserver1:4811*, you can use the following URL:

`http://myhost:8080/natuniweb/natural.jsp?natserver=myserver1&natport=4811&natprog=dump&natuser=my-username`

12

Configuring Container-Managed Security

■ General Information	88
■ Name and Location of the Configuration File	88
■ Activating Security	88
■ Defining Security Constraints	89
■ Defining Roles	89
■ Selecting the Authentication Method	90
■ Configuring the UserDatabaseRealm	90

General Information

The Natural Web I/O Interface client comes as a Java EE-based application. For the ease of installation, the access to this application is by default not secured. You might, however, wish to restrict the access to certain parts of the application to certain users. An important example is the [configuration tool](#), which enables you to modify the Natural session definitions and the logging configuration of the Natural Web I/O Interface client. Another example is the Natural logon page.

This section does not cover the concepts of JAAS-based security in full extent. It provides, however, sufficient information to activate the preconfigured security settings of the Natural Web I/O Interface client and to adapt them to your requirements.

Name and Location of the Configuration File

Security is configured in the file *web.xml*. This file is located in the following directory:

```
<tomcat-install-dir>/webapps/natuniweb/WEB-INF
```

Activating Security

Great care must be taken when editing and changing the configuration file *web.xml*. After a change, the application server must be restarted.

Edit the file *web.xml* and look for the section that is commented with "Uncomment the next lines to add security constraints and roles.". Uncomment this section by removing the comment marks shown in boldface below:

```
<!-- Uncomment the next lines to add security constraints and roles. -->
<!--
<security-constraint>
  <web-resource-collection>
    <web-resource-name>Configuration Tool</web-resource-name>
    <url-pattern>/conf_index.jsp</url-pattern>
    <url-pattern>/faces/*</url-pattern>
  </web-resource-collection>
  ...
<security-role>
  <description>Administrator</description>
  <role-name>nwoadmin</role-name>
</security-role>
-->
```


Defining Security Constraints

The security constraints defined by default are just examples. A `<security-constraint>` element contains a number of `<web-resource-collection>` elements combined with an `<auth-constraint>` element. The `<auth-constraint>` element contains a `<role-name>`. The whole `<security-constraint>` element describes which roles have access to the specified resources.

Example - the following definition specifies that only users in the role "nwoadmin" have access to the configuration tool:

```
<security-constraint>
  <web-resource-collection>
    <web-resource-name>Configuration Tool</web-resource-name>
    <url-pattern>/conf_index.jsp</url-pattern>
    <url-pattern>/faces/*</url-pattern>
  </web-resource-collection>
  <auth-constraint>
    <role-name>nwoadmin</role-name>
  </auth-constraint>
</security-constraint>
```

In the following section, you will see where and how the roles are defined.

Defining Roles

A few lines below in the file *web.xml*, there is a section `<security-role>`. Here, the roles that can be used in `<security-constraint>` elements are defined. You can define additional roles as needed. The assignment of users to roles is done outside this file and will often be done in a user management that is already established at your site.

Example:

```
<security-role>
  <description>Administrator</description>
  <role-name>nwoadmin</role-name>
</security-role>
```

Selecting the Authentication Method

In the file *web.xml*, there is a section `<login-config>`. The only element that should possibly be adapted here is `<auth-method>`. You can choose between the authentication methods "FORM" and "BASIC". Form-based authentication displays a specific page on which users who try to access a restricted resource can authenticate themselves. Basic authentication advises the web browser to retrieve the user credentials with its own dialog box.

Example:

```
<login-config>
  <auth-method>FORM</auth-method>
  ...
</login-config>
```

Configuring the UserDatabaseRealm

In the *tomcat-users.xml* file (which is located in the *conf* directory), specify the role "nwoadmin" for any desired user name and password. For example:

```
<user username="pepe" password="pepe123" roles="nwoadmin"/>
```

For detailed information on the necessary realm configuration for Tomcat, see <http://tomcat.apache.org/tomcat-6.0-doc/realm-howto.html#UserDatabaseRealm>.

13

Configuring SSL

■ General Information	92
■ Creating Your Own Trust File	92
■ Defining SSL Usage in the Configuration File	93

General Information

Trust files are used for a secure connection between the Natural Web I/O Interface server and the Natural Web I/O Interface client. Server authentication cannot be switched off. A trust file is always required.

A trust file contains the certificates that you trust. These can be certificates of a CA (Certificate Authority) such as VeriSign, or self-signed certificates.

For information on the steps that are required on the Natural Web I/O Interface server and how to generate a self-signed certificate which needs to be imported to the client, see [SSL Support](#).

To establish a secure connection, you have to proceed as described in the topics below.

Creating Your Own Trust File

To create your own trust file, you can use, for example, Sun's keytool utility which can be found in the *bin* directory of the Java Runtime Environment (JRE). Here are some helpful examples:

- Create an empty, password-protected trust file:

```
keytool -genkey -alias foo -keystore truststore.jks -storepass "your-password"
keytool -delete -alias foo -keystore truststore.jks
```

- Import a certificate:

```
keytool -import -alias "name-for-ca" -keystore truststore.jks -storepass ↵
"your-password" -file server.cert.crt
```

You should use a meaningful name for the alias.

- List the certificates in a trust file:

```
keytool -list -v -keystore truststore.jks
```

- Delete a certificate from a trust file:

```
keytool -delete -alias "name-for-ca" -keystore truststore.jks
```

When you modify the trust file or its password, you have to restart the application server so that your modification takes effect.

Defining SSL Usage in the Configuration File

Invoke the [configuration tool](#) and proceed as follows:

1. In the global settings for all defined sessions, define the **SSL trust file path** and, if required, the **SSL trust file password**. See also [Global Settings](#) in *Natural Client Configuration Tool*.

With the server authentication, the Natural Web I/O Interface client checks whether the certificate of the Natural Web I/O Interface server is known. If it is not known, the connection is rejected.

When a trust file is not defined in the configuration tool, the Natural Web I/O Interface client tries to read the file *calist* from the *lib/security* directory of the Java Runtime Environment (JRE). The default password for this file is "changeit".

2. Define a session and set the session option **Use SSL** to **Yes**. See also [Overview of Session Options](#) in *Natural Client Configuration Tool*.

14

Logging

■ General Information	96
■ Name and Location of the Configuration File	96
■ Invoking the Logging Configuration Page	96
■ Overview of Options for the Output File	98

General Information

The Natural Web I/O Interface client uses the Java Logging API. In case of problems with the Natural Web I/O Interface client, you can enable logging and thus write the logging information to an output file. This should only be done when requested by Software AG support.

You configure logging using the [configuration tool](#).



Note: Some logging information is also written to the console, regardless of the settings in the configuration file. The console shows the information which is normally provided by the logging levels SEVERE, WARNING and INFO.

Name and Location of the Configuration File

The name of the configuration file is *natlogger.xml*, which is located in:.

`<application-server-install-dir>server/default/deploy/naturalunicode.rar/log`

Invoking the Logging Configuration Page

The content of the configuration file *natlogger.xml* is managed using the **Logging Configuration** page of the [configuration tool](#).

➤ **To invoke the Logging Configuration page**

- 1 In the frame on the left, choose the **Logging Configuration** link.

The **Logging Configuration** page appears in the right frame. Example:

Logging Configuration

Specify the output log file characteristics.

- `"/"` : The local pathname separator
- `"%t"`: The system temporary directory
- `"%h"`: The value of the "user.home" system property
- `"%g"`: The generation number to distinguish rotated logs
- `"%u"`: A unique number to resolve conflicts
- `"%%"`: Translates to a single percent sign `"%"`

File pattern name:

File type:

File size (in Kbytes; 0=unlimited):

Number of files:

File enabled: ☒ Yes ☐ No

Append mode: ☐ Yes ☒ No

Specify log levels for individual modules. The available settings are:

- SEVERE: Events that interfere with normal program execution
- WARNING: Warnings, including exceptions
- INFO: Messages related to server configuration or server status, excluding errors
- CONFIG: Messages related to server configuration
- FINE: Minimal verbosity
- FINER: Moderate verbosity
- FINEST: Maximum verbosity

Communication:

Resource adapter:

Session beans:

Message beans:

Configuration file:

Logging:

Utilities:

Natural Web I/O Interface pages:

- 2 Specify the characteristics of the output file as described below in the section [Overview of Options for the Output File](#).
- 3 Specify the log levels for individual modules by selecting the log level from the corresponding drop-down list box.

A brief description for each log level is provided on the **Logging Configuration** page.

- 4 Choose the **Save Configuration** button to write the modifications to the configuration file.



Caution: When you do not choose the **Save Configuration** button but log out instead or leave the configuration tool by entering another URL, your modifications are not written to the configuration file.

Overview of Options for the Output File

The following options are provided for specifying the characteristics of the output file:

Option	Description
File pattern name	<p>The pattern for generating the output file name. Default: "%h/nwolog%g.log".</p> <p>The default value means that an output file with the name <i>nwolog<number>.log</i> will be created in the home directory of the user who has started the application server.</p> <p>For detailed information on how to specify the pattern, see the Java API documentation.</p>
File type	<p>The format of the output file. Select one of the following entries from the drop-down list box:</p> <ul style="list-style-type: none">■ Text format Output in simple text format (default).■ XML format Output in XML format. <p>The corresponding formatter class is then used.</p>
File size	<p>The maximum number of bytes that is to be written to an output file. Zero (0) means that there is no limit. Default: "0".</p>
Number of files	<p>The number of output files to be used. This value must be at least "1". Default: "10".</p>
File enabled	<p>If set to Yes (default), the file handler is enabled. If set to No, the file handler is disabled.</p>
Append mode	<p>If set to Yes, the logging information is appended to the existing output file. If set to No (default), the logging information is written to a new output file.</p>