

# Installation

Refer to the *Natural* documentation for information on how to start the installation; then follow the instructions of the installation program.

- Installation Notes
  - Starting Output Management GUI Client
- 

## Installation Notes

Ensure that your desired broker is accessible. This means that your installation requires:

- additional broker parameters like definition of an RPC server.
- a suitable middleware installation, for example: TCP/IP parameters like entries in files ...*\etc\hosts* and/or ...*\etc\services*
- the correct RPC server (SRVNAME) and broker (SRVNODE) names to be entered in your Natural parameter module (usually NATPARM).

### Notes:

1. Some errors at start time are caused by an incomplete registration of NGC's OCX controls. Ensure that the DLL files located in directory ...*\FUSER\SYSNOM\RES\OCX* are registered. If not, use the command `REGSRV32 filename.DLL` for registration.
2. If application definitions not found is issued towards the end of the installation, start program NOINIT-P in order to load the definitions.
3. You can find the installation log file *NGC111Inst.log* in your installation directory.

### Caution:

Ensure that your RPC server has got the definitions for logical files 206 and 91. LFILE 206 must point to your Entire Output Management system file, LFILE 91 must point to your Entire Output Management active data file. If you did not split the Entire Output Management system file, both, LFILEs 206 and 91 will point to your Entire Output Management system file, because in this case Entire Output Management system file and active data file are one and the same file.

The Output Management GUI Client has been optimized for small fonts and a resolution of 1024 x 768 pixels. We recommend using these parameters.

## Starting Output Management GUI Client

A desktop icon for the Output Management GUI Client (NGC) is generated automatically by the installation procedure.

To start NGC, double-click this icon.